

US009363714B2

(12) **United States Patent**
Rahman et al.

(10) **Patent No.:** **US 9,363,714 B2**
(45) **Date of Patent:** ***Jun. 7, 2016**

(54) **REDIRECTING HANDOVERS IN LTE NETWORKS**

H04W 36/0022; H04W 36/08; H04W 36/0016; H04W 36/0033; H04W 36/00; H04W 36/30; H04W 36/14

(71) Applicant: **AT&T Intellectual Property I, L.P.**, Atlanta, GA (US)

USPC 455/436-445; 370/328-333
See application file for complete search history.

(72) Inventors: **Moshiur Rahman**, Marlboro, NJ (US); **Christopher Opara**, Buford, GA (US)

(56) **References Cited**

(73) Assignee: **AT&T INTELLECTUAL PROPERTY I, L.P.**, Atlanta, GA (US)

U.S. PATENT DOCUMENTS

6,353,902 B1 3/2002 Kulatunge et al.
6,564,227 B2 5/2003 Sakakibara et al.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(Continued)

This patent is subject to a terminal disclaimer.

FOREIGN PATENT DOCUMENTS

WO A12009084864 7/2009
WO A12010017961 2/2010

(21) Appl. No.: **14/658,996**

OTHER PUBLICATIONS

(22) Filed: **Mar. 16, 2015**

Office Action dated Mar. 23, 2012 for U.S. Appl. Serial No. 12/577,899, 25 pages.

(65) **Prior Publication Data**

(Continued)

US 2015/0189554 A1 Jul. 2, 2015

Related U.S. Application Data

(63) Continuation of application No. 14/147,221, filed on Jan. 3, 2014, now Pat. No. 9,008,664, which is a continuation of application No. 12/855,435, filed on Aug. 12, 2010, now Pat. No. 8,644,832.

Primary Examiner — Olumide T Ajibade Akonai
(74) *Attorney, Agent, or Firm* — Amin, Turocy & Watson, LLP

(51) **Int. Cl.**
H04W 36/00 (2009.01)
H04W 24/04 (2009.01)

(Continued)

(57) **ABSTRACT**


An architecture that can redirect communications upon detection of a handover failure in a Long Term Evolution (LTE) network is described. The architecture can obtain information indicative of a handover failure that is available in a first portion of the LTE network (e.g., a serving gateway) that has no control over the communication path. The architecture can utilize the information to instruct a second portion of the LTE network (e.g., a mobility management entity), one that can control the communication path but conventionally has no access to the handover information, to reroute the communication path to avoid unresponsive or failing network entities.

(52) **U.S. Cl.**
CPC **H04W 36/0016** (2013.01); **H04W 24/04** (2013.01); **H04W 36/0022** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC H04W 36/0055; H04W 36/0083;

20 Claims, 11 Drawing Sheets

600



- (51) **Int. Cl.**
H04W 40/20 (2009.01)
H04W 40/36 (2009.01)
H04W 28/04 (2009.01)
- (52) **U.S. Cl.**
 CPC *H04W36/0055* (2013.01); *H04W 36/0083*
 (2013.01); *H04W 40/20* (2013.01); *H04W*
40/36 (2013.01); *H04W 28/04* (2013.01)

- 2010/0142367 A1 6/2010 Zhang et al.
 2010/0208681 A1 8/2010 Elmaleh et al.
 2010/0226267 A1 9/2010 Jang et al.
 2010/0267378 A1 10/2010 Hamabe et al.
 2011/0021154 A1 1/2011 Marinier et al.
 2011/0110225 A1 5/2011 Mihaly et al.
 2011/0188468 A1 8/2011 Vikberg et al.
 2011/0194427 A1 8/2011 Shirota et al.
 2012/0039299 A1 2/2012 Teyeb et al.

OTHER PUBLICATIONS

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 7,080,294 B1 7/2006 Weber et al.
 8,280,381 B2 10/2012 Zhu et al.
 8,483,174 B2 7/2013 Ahmavaara et al.
 8,644,832 B2 * 2/2014 Rahman H04W 36/0055
 370/328
 9,008,664 B2 * 4/2015 Rahman H04W 36/0055
 370/328
- 2002/0123365 A1 9/2002 Thorson et al.
 2003/0207687 A1 11/2003 Svedevall et al.
 2008/0162981 A1 7/2008 Jajoo et al.
 2008/0192697 A1 8/2008 Shaheen et al.
 2008/0227455 A1 9/2008 Kim et al.
 2009/0149180 A1 6/2009 Kitazoe et al.
 2009/0180451 A1 7/2009 Alpert et al.

- Office Action dated Sep. 11, 2012 for U.S. Appl. No. 12/577,899, 27 pages.
 Office Action dated Sep. 21, 2012 for U.S. Appl. No. 12/855,435, 95 pages.
 Notice of Allowance mailed dated Oct. 2, 2013 for U.S. Appl. No. 12/855,435, 22 pages.
 Office Action dated May 20, 2014 for U.S. Appl. No. 14/147,221, 22 Pages.
 Office Action dated Aug. 13, 2014 for U.S. Appl. No. 12/577,899, 39 pages.
 Final Office Action dated Feb. 9, 2015 for U.S. Appl. No. 12/577,899, 46 pages.
 Notice of Allowance dated Dec. 17, 2014 for U.S. Appl. No. 14/147,221, 17 pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

600




FIG. 6





FIG. 7



800

FIG. 8




FIG. 9




FIG. 11

1

REDIRECTING HANDOVERS IN LTE NETWORKS

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of, and claims priority to each of, U.S. patent application Ser. No. 14/147,221 (now U.S. Pat. No. 9,008,664), entitled, "REDIRECTING HANDOVERS IN LTE NETWORKS", filed Jan. 3, 2014, which is a continuation of U.S. Pat. No. 8,644,832, entitled, "REDIRECTING HANDOVERS IN LTE NETWORKS", filed Aug. 12, 2010. The entireties of these applications are hereby incorporated herein by reference.

TECHNICAL FIELD

The present application relates generally to Long-Term Evolution (LTE) communications networks, and more specifically to utilizing a mobility management entity (MME) for redirecting handovers that might otherwise fail.

BACKGROUND

Conventional wireless networks typically provide for handover operations or transactions in which a mobile device switches from a first channel to a second channel. Handover transactions can occur for a variety of reasons, some of the more common of which are to enable the mobile device to maintain a call or data session even when traveling in and out of the effective ranges of cells; to enable interoperability of disparate network technologies; to allow more efficient sharing of network resources; to avoid interference, or to better suit behavior such as high travel speed or to enable required or desired features or services.

Regardless of the purpose or nature of the handover transaction, in some cases, handover transactions end in a failure for one reason or another. In modern Long Term Evolution (LTE) communication networks, evidence of handover failures can be determined by an associated serving gateway, however, in LTE networks, the serving gateway has no control over the communication path that is selected, and therefore cannot take any suitable action to remedy the problem. As a result, a call or other data session can be dropped by the LTE network, leading to customer dissatisfaction. Accordingly, conventional LTE networks do not adequately handle handover failures with respect to maintaining a call in spite of a handover failure. For example, an eNB (or other network entity) can fail to accept a handover due to one or more issues associated with the eNB (or other network entity), even though that eNB has been selected to receive the handover.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of a system that can redirect communications such as mobile handset calls, data sessions, or other transactions, upon detection of a handover failure in a Long Term Evolution (LTE) network.

FIG. 2 provides a block diagram of various examples of alternative radio access technologies (RAT).

FIG. 3 illustrates a graphic depiction that illustrates two example situations in which a handover can fail.

FIG. 4 is a block diagram of a system that can predict handover difficulties in a LTE network and reroute the communication path in response.

FIG. 5 illustrates a block diagram of a system that can perform or aid with various determinations or inferences.

2

FIG. 6 depicts an exemplary flow chart of procedures defining a method for rerouting handover transactions in a LTE network.

FIG. 7 is an exemplary flow chart of procedures that define a method for providing additional features or aspects in connection with selecting an alternative communication path.

FIG. 8 depicts an exemplary flow chart of procedures defining a method for providing additional features or aspects in connection with identifying and/or determining a handover failure.

FIG. 9 illustrates an example wireless communication environment with associated components that can enable operation of an enterprise network in accordance with aspects described herein.

FIG. 10 illustrates a schematic deployment of a macro cell for wireless coverage in accordance with aspects of the subject specification.

FIG. 11 illustrates a block diagram of a computer operable to execute a portion of the disclosed architecture.

DETAILED DESCRIPTION

The subject matter disclosed herein, in one aspect thereof, comprises an architecture that can redirect communications such as calls or data sessions upon detection of a handover failure in a Long Term Evolution (LTE) network prior to dropping or otherwise losing the call or data session. In accordance therewith and to other related ends, the architecture can include a monitor component that can be operatively coupled to a serving gateway of a LTE-access network. Thus, the monitor component can be configured to identify a handover failure (or abnormalities that could lead to a handover failure) associated with a particular LTE handover procedure, given that in LTE networks serving gateways have access to data that can be employed to detect the occurrence of a handover failure. Upon identification of a handover failure, the monitor component can therefore generate a failure notification, including relevant information relating to the handover failure.

In addition, the architecture can include routing component that can be operatively coupled to a mobility management entity (MME) of the LTE-access network. Since the MME in an LTE network can authorize bearers and/or select network entities to carry a particular communication, the routing component can be configured to instruct the MME to select an alternative communication path upon receipt of the failure notification.

The disclosed subject matter is now described with reference to the drawings, wherein like reference numerals are used to refer to like elements throughout. In the following description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the disclosed subject matter. It may be evident, however, that the disclosed subject matter may be practiced without these specific details. In other instances, well-known structures and devices are shown in block diagram form in order to facilitate describing the disclosed subject matter.

As used in this application, the terms "system," "component," "interface," and the like are intended to refer to a computer-related entity or an entity related to an operational machine with one or more specific functionalities. The entities disclosed herein can be either hardware, a combination of hardware and software, software, or software in execution. For example, a component may be, but is not limited to being, a process running on a processor, a processor, an object, an executable, a thread of execution, a program, and/or a computer. By way of illustration, both an application running on

a server and the server can be a component. One or more components may reside within a process and/or thread of execution and a component may be localized on one computer and/or distributed between two or more computers. These components also can execute from various computer readable media having various data structures stored thereon. The components may communicate via local and/or remote processes such as in accordance with a signal having one or more data packets (e.g., data from one component interacting with another component in a local system, distributed system, and/or across a network such as the Internet with other systems via the signal). As another example, a component can be an apparatus with specific functionality provided by mechanical parts operated by electric or electronic circuitry that is operated by software or firmware application(s) executed by a processor, wherein the processor can be internal or external to the apparatus and executes at least a part of the software or firmware application. As yet another example, a component can be an apparatus that provides specific functionality through electronic components without mechanical parts, the electronic components can include a processor therein to execute software or firmware that confers at least in part the functionality of the electronic components. An interface can include input/output (I/O) components as well as associated processor, application, and/or API components.

Furthermore, the disclosed subject matter may be implemented as a method, apparatus, or article of manufacture using standard programming and/or engineering techniques to produce software, firmware, hardware, or any combination thereof to control a computer to implement the disclosed subject matter. The term “article of manufacture” as used herein is intended to encompass a computer program accessible from any computer-readable device, carrier, or media. For example, computer readable media can include but are not limited to magnetic storage devices (e.g., hard disk, floppy disk, magnetic strips . . .), optical disks (e.g., compact disk (CD), digital versatile disk (DVD) . . .), smart cards, and flash memory devices (e.g., card, stick, key drive . . .). Additionally it should be appreciated that a carrier wave can be employed to carry computer-readable electronic data such as those used in transmitting and receiving electronic mail or in accessing a network such as the Internet or a local area network (LAN). Of course, those skilled in the art will recognize many modifications may be made to this configuration without departing from the scope or spirit of the disclosed subject matter.

As used herein, the terms “infer” or “inference” generally refer to the process of reasoning about or inferring states of the system, environment, and/or user from a set of observations as captured via events and/or data. Inference can be employed to identify a specific context or action, or can generate a probability distribution over states, for example. The inference can be probabilistic—that is, the computation of a probability distribution over states of interest based on a consideration of data and events. Inference can also refer to techniques employed for composing higher-level events from a set of events and/or data. Such inference results in the construction of new events or actions from a set of observed events and/or stored event data, whether or not the events are correlated in close temporal proximity, and whether the events and data come from one or several event and data sources.

Further, terms like “user equipment,” “mobile station,” “mobile,” subscriber station,” “access terminal,” “terminal,” “handset,” and similar terminology, generally refer to a wireless device utilized by a subscriber or user of a wireless communication service to receive or convey data, control,

voice, video, sound, gaming, or substantially any data-stream or signaling-stream. The foregoing terms are utilized interchangeably in the subject specification and related drawings. Likewise, the terms “access point,” “base station,” “cell site,” and the like, are utilized interchangeably in the subject application, and refer to a wireless network component or appliance that serves and receives data, control, voice, video, sound, gaming, or substantially any data-stream or signaling-stream from a set of subscriber stations. Data and signaling streams can be packetized or frame-based flows. It is noted that in the subject specification and drawings, context or explicit distinction provides differentiation with respect to access points or base stations that serve and receive data from a mobile device in an outdoor environment, and access points or base stations that operate in a confined, primarily indoor environment overlaid in an outdoor coverage area. Data and signaling streams can be packetized or frame-based flows.

Furthermore, the terms “user,” “subscriber,” “customer,” “consumer,” and the like are employed interchangeably throughout the subject specification, unless context warrants particular distinction(s) among the terms. It should be appreciated that such terms can refer to human entities, associated devices, or automated components supported through artificial intelligence (e.g., a capacity to make inference based on complex mathematical formalisms) which can provide simulated vision, sound recognition and so forth. In addition, the terms “wireless network” and “network” are used interchangeably in the subject application, when context wherein the term is utilized warrants distinction for clarity purposes such distinction is made explicit.

Moreover, the word “exemplary” is used herein to mean serving as an example, instance, or illustration. Any aspect or design described herein as “exemplary” is not necessarily to be construed as preferred or advantageous over other aspects or designs. Rather, use of the word exemplary is intended to present concepts in a concrete fashion. As used in this application, the term “or” is intended to mean an inclusive “or” rather than an exclusive “or”. That is, unless specified otherwise, or clear from context, “X employs A or B” is intended to mean any of the natural inclusive permutations. That is, if X employs A; X employs B; or X employs both A and B, then “X employs A or B” is satisfied under any of the foregoing instances. In addition, the articles “a” and “an” as used in this application and the appended claims should generally be construed to mean “one or more” unless specified otherwise or clear from context to be directed to a singular form.

Referring now to the drawing, with reference initially to FIG. 1, system **100** that can redirect communications (e.g., mobile handset calls, data sessions, or other transactions) upon detection of a handover failure in a Long Term Evolution (LTE) network is depicted. Generally, system **100** can include monitor component **102** that can be operatively or communicatively coupled to serving gateway **104** of a LTE-access network, which is further detailed infra. Monitor component **102** can be configured to identify failure **106** associated with a particular LTE handover procedure **108**. For example, based upon the role serving gateways (e.g., serving gateway **104**) play in LTE networks, these serving gateways are in a position to determine or detect evidence of handover failure occurrences, even though the serving gateways are not able to rectify or alleviate the issue. Thus, monitor component **102** can leverage the ability of serving gateway **104** to detect evidence of handover failure **106**. Accordingly, when such evidence of handover failure **106** is detected by serving gateway **104**, monitor component **102** can identify the failure and provide failure notification **110**.

In addition, system **100** can further include routing component **112**, which can be the recipient of failure notification **110**. As with monitor component **102**, routing component **112** can also be coupled to one or more core components of an LTE access network. Yet, in this case, routing component **112** can be operatively or communicatively coupled to mobility management entity (MME) **114** of the LTE-access network. One role of MMEs (e.g., MME **114**) in conventional LTE networks is to authorize bearers for communication paths and/or select suitable serving gateways or other network entities. However, since MMEs do not manage data packets or the like, MMEs in traditional LTE networks have no way of knowing that a handover procedure has failed. Thus, routing component **112**, upon receipt of failure notification **110**, can be configured to instruct MME **114** to select alternative communication path (ACP) **116**. Hence, in broad terms, monitor component **102** can leverage information (e.g., information relating to handover failure **106**) inherently available to serving gateway **104**, while routing component **112** can leverage inherent capabilities (e.g., to select communication paths) of MME **114** that, when combined, can provide features not available in conventional LTE networks such as, e.g., redirecting a call or data session to alternative communication path **116**.

In more detail, LTE networks include a core network, denoted evolved packet core (EPC) and an associated air interface, denoted evolved UTRAN (Universal Mobile Telecommunications System) Terrestrial Radio Access Network or eUTRAN (e.g., eUTRAN **118**). The air interface or eUTRAN can include a set of evolved Node B (eNB) elements (e.g., eNB **120**) that interface to user equipment (UE) such as mobile handsets or the like. Likewise, the EPC can include a set of serving gateways, a MME, and a set of packet data network (PDN) gateways (e.g., PDN gateway **122**).

Traditionally, the MME operates as the control-plane function for eUTRAN access and/or is the key control-node for the LTE access-network. The MME is responsible for authentication and critical management for mobile devices as well as for tracking and paging procedures for mobile devices in idle mode. Moreover, the MME authorizes bearer activation/deactivation including serving gateway and PDN gateway selection. Likewise, the serving gateway operates as a local mobility anchor for eUTRAN mobility, switching packets between the S5/S8 interface and the General Radio Packet System (GPRS) Tunneling Protocol (GTP)-based S1-U interface for mobile devices in connected mode. For mobile devices in idle mode, the serving gateway is responsible for terminating the down-link data path and when down-link data is received. On the other hand, the PDN gateway can operate as the permanent Internet Protocol (IP) point-of-attachment for access via the eUTRAN. The PDN gateway performs IP policy and charging enforcement on packet flows to and from mobile devices. The same access point name (APN) concepts from a UTRAN packet switching core network apply, allowing a mobile device to have simultaneous connectivity to multiple PDNs.

A characteristic of modern LTE networks is that these networks seek to leverage existing broadband infrastructure, and operate as an all-IP system. Hence, eNBs, serving gateways, and PDN gateways are all coupled via an always-on IP connection, which is illustrated by reference numeral **124**. Therefore, serving gateway **104** can be aware of any abnormalities associated with such network elements (e.g., often eNB **120**) involved in handover procedure **108** as well as actual handover failures **106**. Such information (e.g., failure notification **110**) can be provided to routing component **112**,

which can then instruct MME **114** to select alternate communication path **116**, as detailed supra.

In one or more aspect, routing component **112** can instruct MME **114** to select an alternate radio access technology (RAT) for the alternate communication path **116**. The alternate RAT, also denoted by reference numeral **116** can be substantially any suitable access technology, but will generally differ from LTE-based eUTRAN **118**. Thus, in the event of handover failure **106** in the LTE network, MME **114** can select some (typically non-LTE) other appropriate RAT **116**. For example, the alternate RAT **116** can be associated with at least one of a second generation partnership project (2GPP) communication standard, a third generation partnership project (3GPP) communication standard, or a satellite-based communication standard. Thus, UE with LTE service provision that experience issues that can lead to a dropped connection can be instead rerouted to other access technologies prior to losing the connection and/or service. These alternate RATs **116**, being independent of eUTRAN **118** will typically not be subject to the same network issues, and therefore can be leveraged as a failsafe of sorts.

Examples of alternative RATs **116** are provided with reference to FIG. **2**. In particular, and as noted supra, MME **114** can select 2GPP **202**, 3GPP **204**, satellite **206**, or any other suitable access technology with which an associated UE is equipped to utilize.

While still referring to FIG. **1**, but turning now also to FIG. **3**, graphic depiction **300** illustrates two example situations in which a handover can fail. As depicted, eUTRAN **118** can comprise a plurality of eNBs, including source eNB **302** and target eNB **304**, which respectively serve source UE **306** and target UE **308**. As previously mentioned, routing component **112** can be configured to instruct MME **114** to select an ACP **116** upon receipt of failure notification **110**. Thus, in a first case handover failure **106** is associated with source eNB **302**, in which case alternate source entity **310** of an associated RAT **116** can be selected to avoid the issues being experienced by source eNB **302**. In a second case, handover failure **106** arises with respect to target eNB **304**. Thus, alternate target entity **312** of some suitable RAT **116** can be selected to substitute for failing target eNB **304**. Appreciably, when handover procedures fail due to substantially any reason, serving gateway **104** is capable of detecting evidence of such a failure and/or any other abnormality, which can be identified by monitor component **102**.

In accordance therewith, in one or more aspect of the disclosed subject matter, monitor component **102** can identify handover failure **106** based upon an unavailability condition associated with target eNB **304**. As another example, monitor component **102** can identify handover failure **106** based upon a degraded air interface (e.g., eUTRAN) between UE (e.g., UE **306** and/or **308**) and either source eNB **302** or target eNB **304**. As a third example, monitor component **102** can identify handover failure **106** based upon a buffer overflow condition or a packet loss condition associated with at least one of source eNB **302** or target eNB **304**. In addition, as a fourth example, monitor component **102** can identify handover failure **106** based upon a threshold crossing alarm (TCA) count associated with at least one of source eNB **302** or target eNB **304**, which is further detailed in connection with FIG. **4**, infra. Furthermore, it should be appreciated that handover failure **106** can be associated with substantially any type of LTE handover procedure **108**. For example, LTE handover procedure can be directed to a backward handover initiated by source eNB **402** or to a forward handover initiated by UE.

Continuing the discussion of FIG. **1**, as noted, monitor component **102** can identify handover failure **106** and trans-

mit failure notification **110** to routing component **112**, which in turn can then instruct MME **114** to select ACP **116** in order to, e.g., bypass the failing network entity or entities. In addition, in one or more aspect, routing component **112** can further instruct MME **114** to interact with home subscriber server (HSS) **126**. Typically, HSS **126** operates as a master user database that supports network entities that handle calls or other data sessions. The HSS **126** can include subscription-related information such as subscriber profiles, can perform authentication and authorization of users, and can provide information about a subscriber's location or IP information. The above-mentioned interaction between MME **114** and HSS **126** can be accomplished by way of non-access stratum (NAS) signaling, and the NAS signaling interaction can be for the purposes of determining parameters associated with quality of service (QoS) and/or service level agreement (SLA) in connection with the provisioned service that is experiences difficulties. As a result, MME **114** can choose a most appropriate ACP/RAT **116** when redirecting the failed handoff, which can be accomplished prior to losing a network data connection (e.g., dropping a call).

With reference now to FIG. **4**, system **400** that can predict handover difficulties in a LTE network is provided. Broadly, system **400** intended to represent an alternate embodiment of, and to be substantially similar to, system **100** of FIG. **1**. However, whereas system **100** is directed to early response to handover failure **106**, system **400** is directed to preemptive activity such that handover failure **106** can be predicted in advance as well. Hence, as with system **100**, system **400** can include monitor component **102** that can be operatively coupled to serving gateway **104** of a LTE-access network, wherein monitor component **102** can be configured to identify failing eNB **402** that is potentially unable to accept a LTE-based handover and/or that may not be capable of sustaining a data connection. System **400** can also include routing component **112** as substantially described in connection with FIG. **1**. Specifically, routing component **112** can be operatively coupled to MME **114** of the LTE-access network, wherein routing component **112** can be configured to instruct MME **114** to select an alternative communication path **116** upon receipt of a LTE handover request associated with failing eNB **402**.

In addition, system **400** can further include tracking component **404** that can store information associated with failing eNB **402**, for instance, to a data store or error list **406**. Thus, all the evidentiary data available to serving gateway **104** discussed previously, e.g., unavailability, buffer overflow, packet loss and so on, can be actively tracked and stored in a real-time database, such as error list **406**. Such information can be employed, e.g., to determine whether or not a target eNB is capable of accepting a handover rather than examining such information after failing eNB **402** has generated a handover failure. In particular, monitor component **102** can identify failing eNB **402** based upon a TCA count associated with failing eNB **402**. Such data can be recorded in error list, and be maintained with respect to failing eNB **402** until the issue is corrected and/or no longer exists, in which case the entry in error list **406** relating to failing eNB **402** can be cleared. In the meantime, should MME **114** otherwise attempt to select failing eNB as a recipient of a handover or otherwise involved in a handover transaction, routing component **112** can alert MME **114** of the potential for a fault and instruct MME **114** to select an ACP **116** instead of failing eNB **402**.

Similarly, monitor component **102** can identify failing eNB **402** based upon a degraded air interface between UE and failing eNB **402** or based upon a buffer overflow condition or a packet loss condition associate with failing eNB **402**. In

either case, this information can be stored to error list **406** and referenced should eNB at issue be selected during a handover procedure as detailed supra.

As with other portions of this disclosure, in this case routing component **112** can instruct MME **114** to select alternate RAT **116** for the alternative communication path **116**, wherein alternate RAT **116** differs from an LTE-based eUTRAN. For example, alternate RAT **116** can be associated with at least one of a 2GPP communication standard, a 3GPP communication standard, a satellite-based communication standard, or another suitable access technology communication standard or technique. Regardless, based upon the above, MME **114** can employ alternate RAT **116** to bypass failing eNB **402** in connection with the LTE-based handover.

Now turning to FIG. **5**, system **500** that can perform or aid with various determinations or inferences is illustrated. Generally, system **500** can include monitor component **102**, routing component **112**, tracking component **404**, as well as other components described herein. In addition to what has been described, the above-mentioned components can make intelligent determinations or inferences. For example, Bayesian probabilities or confidence measures can be employed or inferences can be based upon machine learning techniques related to historical analysis, feedback, and/or previous determinations or inferences.

For instance, fault monitor component **102** can intelligently determine or infer indicia of a failing eNB **402**, e.g., based upon TCA counts, or based upon QoS, noise, latency, and so forth. Likewise, routing component **112** can intelligently determine or infer a suitable ACP/RAT **116** based upon subscriber profiles or the like. In addition, tracking component **404** can intelligently determine or infer whether or not to update error list **406** based upon, e.g., time, recovery operations, etc. Regardless of the actual intelligent determination or inference, as noted, such can be based upon historical analysis, probabilistic inferences or machine learning techniques.

In addition, system **500** can also include intelligence component **502** that can provide for or aid in various inferences or determinations. In particular, in accordance with or in addition to what has been described supra with respect to intelligent determinations or inferences provided by various components described herein, e.g., all or portions of monitor component **102**, routing component **112**, or tracking component **404**. Additionally or alternatively, all or portions of intelligence component **502** can be included in one or more components described herein. Thus, intelligence component **502** can reside in whole or in part within system **100** or system **400** or within components described therein.

Moreover, intelligence component **502** will typically have access to all or portions of data sets described herein, such as data store **504**. As used herein, data store **504** is intended to be a repository of all or portions of data, data sets, or information described herein or otherwise suitable for use with the described subject matter (e.g., user profiles, service agreements, history, network traffic data either current or historical, device types/capabilities, etc.). Data store **504** can be centralized, either remotely or locally cached, or distributed, potentially across multiple devices and/or schemas. Furthermore, data store **504** can be embodied as substantially any type of memory, including but not limited to volatile or non-volatile, sequential access, structured access, or random access and so on. It should be understood that all or portions of data store **504** can be included in systems **100** or **400**, or can reside in part or entirely remotely from systems **100** or **400**.

In more detail, in order to provide for or aid in the numerous inferences described herein, intelligence component **502**

can examine the entirety or a subset of the data available and can provide for reasoning about or infer states of the system, environment, and/or user from a set of observations as captured via events and/or data. Inference can be employed to identify a specific context or action, or can generate a probability distribution over states, for example. The inference can be probabilistic—that is, the computation of a probability distribution over states of interest based on a consideration of data and events. Inference can also refer to techniques employed for composing higher-level events from a set of events and/or data.

Such inference can result in the construction of new events or actions from a set of observed events and/or stored event data, whether or not the events are correlated in close temporal proximity, and whether the events and data come from one or several event and data sources. Various classification (explicitly and/or implicitly trained) schemes and/or systems (e.g., support vector machines, neural networks, expert systems, Bayesian belief networks, fuzzy logic, data fusion engines . . .) can be employed in connection with performing automatic and/or inferred action in connection with the disclosed subject matter.

A classifier can be a function that maps an input attribute vector, $x=(x_1, x_2, x_3, x_4, x_n)$, to a confidence that the input belongs to a class, that is, $f(x)=\text{confidence}(\text{class})$. Such classification can employ a probabilistic and/or statistical-based analysis (e.g., factoring into the analysis utilities and costs) to prognose or infer an action that a user desires to be automatically performed. A support vector machine (SVM) is an example of a classifier that can be employed. The SVM operates by finding a hyper-surface in the space of possible inputs, where the hyper-surface attempts to split the triggering criteria from the non-triggering events. Intuitively, this makes the classification correct for testing data that is near, but not identical to training data. Other directed and undirected model classification approaches include, e.g., naive Bayes, Bayesian networks, decision trees, neural networks, fuzzy logic models, and probabilistic classification models providing different patterns of independence can be employed. Classification as used herein also is inclusive of statistical regression that is utilized to develop models of priority.

FIGS. 6-8 illustrate various methodologies in accordance with the disclosed subject matter. While, for purposes of simplicity of explanation, the methodologies are shown and described as a series of acts, it is to be understood and appreciated that the disclosed subject matter is not limited by the order of acts, as some acts may occur in different orders and/or concurrently with other acts from that shown and described herein. For example, those skilled in the art will understand and appreciate that a methodology could alternatively be represented as a series of interrelated states or events, such as in a state diagram. Moreover, not all illustrated acts may be required to implement a methodology in accordance with the disclosed subject matter. Additionally, it should be further appreciated that the methodologies disclosed hereinafter and throughout this specification are capable of being stored on an article of manufacture to facilitate transporting and transferring such methodologies to computers. The term article of manufacture, as used herein, is intended to encompass a computer program accessible from any computer-readable device, carrier, or media.

Turning now to FIG. 6, exemplary method 600 for rerouting handover transactions in a LTE network is depicted. Generally, at reference numeral 602, information received by a serving gateway of a LTE-access network can be monitored, which can include substantially any information relating to

abnormalities that can lead to handover failure or degraded service, examples of which are detailed in connection with FIG. 8, *infra*.

Accordingly, the information received at reference numeral 602 can, at reference numeral 604, be employed for determining a failure associated with a LTE handover procedure. In accordance therewith, at reference numeral 606, a failure notification can be transmitted to a MME upon determining the handover failure. Hence, at reference numeral 608, the MME can be employed for selecting an alternative communication path upon receipt of the failure notification. Additional features, aspects, or examples of the selection process or the alternative communication path are provided with reference to FIG. 7, below.

Turning now to FIG. 7, exemplary method 700 for providing additional features or aspects in connection with selecting an alternative communication path is illustrated. At reference numeral 702, a disparate radio access technology (RAT) is selected for the alternative communication path. Appreciably, the RAT can be substantially any suitable technology a particular UE is equipped to utilize, yet will typically be disparate from the eUTRAN technology employed by the underlying LTE service. Moreover, at reference numeral 704, the disparate RAT can be selected based upon non-access stratum (NAS) signaling associate with a HSS network entity. Thus, upon interacting with the HSS, the MME can obtain useful information in determining the most suitable RAT for the particular case at hand.

By way of example, at reference numeral 706, at least one 2GPP network entity can be selected for the alternative communication path. As a second example, at reference numeral 708, at least one 3GPP network entity can be selected for the alternative communication path. As a third example, at reference numeral 710, at least one satellite network entity can be selected for the alternative communication path. However, regardless of the type or nature of the alternative communication path, at reference numeral 712, all communication otherwise intended for the original (e.g., failing) communication path can be rerouted via the alternate communication path prior to dropping a network data connection.

With reference now FIG. 8, exemplary method 800 for providing additional features or aspects in connection with identifying and/or determining a handover failure is depicted. In general, at reference numeral 802, the handover failure determined in connection with reference numeral 604 of FIG. 6 can be determined based upon a degraded air interface condition between UE and a source eNB or between UE and a target eNB.

Likewise, at reference numeral 804, the handover failure can be determined based upon a buffer overflow condition or a packet loss condition associated with at least one of a source eNB or a target eNB. Similarly, at reference numeral 806, the handover failure can be determined based upon an unavailability condition associated with a target eNB. Moreover, at reference numeral 808, the handover failure can be determined based upon a TCA count associated with at least one of a source eNB or a target eNB. Appreciably, any such handover failure can be determined in connection with a backward handover initiated by a source eNB or with a forward handover initiated by UE, as discussed in connection with reference numeral 810.

To provide further context for various aspects of the subject specification, FIG. 9 illustrates an example wireless communication environment 900, with associated components that can enable operation of a femtocell enterprise network in accordance with aspects described herein. Wireless communication environment 900 includes two wireless network plat-

forms: (i) A macro network platform **910** that serves, or facilitates communication) with user equipment **975** via a macro radio access network (RAN) **970**. It should be appreciated that in cellular wireless technologies (e.g., 4G, 3GPP UMTS, HSPA, 3GPP LTE, 3GPP UMB), macro network platform **910** is embodied in a Core Network. (ii) A femto network platform **980**, which can provide communication with UE **975** through a femto RAN **990**, linked to the femto network platform **980** through a routing platform **92** via backhaul pipe(s) **985**, wherein backhaul pipe(s) are substantially the same as a backhaul link **3853** below. It should be appreciated that femto network platform **980** typically offloads UE **975** from macro network, once UE **975** attaches (e.g., through macro-to-femto handover, or via a scan of channel resources in idle mode) to femto RAN.

It is noted that RAN includes base station(s), or access point(s), and its associated electronic circuitry and deployment site(s), in addition to a wireless radio link operated in accordance with the base station(s). Accordingly, macro RAN **970** can comprise various coverage cells like cell **1205**, while femto RAN **990** can comprise multiple femto access points. As mentioned above, it is to be appreciated that deployment density in femto RAN **990** is substantially higher than in macro RAN **970**.

Generally, both macro and femto network platforms **910** and **980** include components, e.g., nodes, gateways, interfaces, servers, or platforms, that facilitate both packet-switched (PS) (e.g., internet protocol (IP), frame relay, asynchronous transfer mode (ATM)) and circuit-switched (CS) traffic (e.g., voice and data) and control generation for networked wireless communication. In an aspect of the subject innovation, macro network platform **910** includes CS gateway node(s) **912** which can interface CS traffic received from legacy networks like telephony network(s) **940** (e.g., public switched telephone network (PSTN), or public land mobile network (PLMN)) or a SS7 network **960**. Circuit switched gateway **912** can authorize and authenticate traffic (e.g., voice) arising from such networks. Additionally, CS gateway **912** can access mobility, or roaming, data generated through SS7 network **960**; for instance, mobility data stored in a VLR, which can reside in memory **930**. Moreover, CS gateway node(s) **912** interfaces CS-based traffic and signaling and gateway node(s) **918**. As an example, in a 3GPP UMTS network, gateway node(s) **918** can be embodied in gateway GPRS support node(s) (GGSN).

In addition to receiving and processing CS-switched traffic and signaling, gateway node(s) **918** can authorize and authenticate PS-based data sessions with served (e.g., through macro RAN) wireless devices. Data sessions can include traffic exchange with networks external to the macro network platform **910**, like wide area network(s) (WANs) **950**; it should be appreciated that local area network(s) (LANs) can also be interfaced with macro network platform **910** through gateway node(s) **918**. Gateway node(s) **918** generates packet data contexts when a data session is established. To that end, in an aspect, gateway node(s) **918** can include a tunnel interface (e.g., tunnel termination gateway (TTG) in 3GPP UMTS network(s); not shown) which can facilitate packetized communication with disparate wireless network(s), such as Wi-Fi networks. It should be further appreciated that the packetized communication can include multiple flows that can be generated through server(s) **914**. It is to be noted that in 3GPP UMTS network(s), gateway node(s) **918** (e.g., GGSN) and tunnel interface (e.g., TTG) comprise a packet data gateway (PDG).

Macro network platform **910** also includes serving node(s) **916** that convey the various packetized flows of information

or data streams, received through gateway node(s) **918**. As an example, in a 3GPP UMTS network, serving node(s) can be embodied in serving GPRS support node(s) (SGSN).

As indicated above, server(s) **914** in macro network platform **910** can execute numerous applications (e.g., location services, online gaming, wireless banking, wireless device management . . .) that generate multiple disparate packetized data streams or flows, and manage (e.g., schedule, queue, format . . .) such flows. Such application(s), for example can include add-on features to standard services provided by macro network platform **910**. Data streams can be conveyed to gateway node(s) **918** for authorization/authentication and initiation of a data session, and to serving node(s) **916** for communication thereafter. Server(s) **914** can also effect security (e.g., implement one or more firewalls) of macro network platform **910** to ensure network's operation and data integrity in addition to authorization and authentication procedures that CS gateway node(s) **912** and gateway node(s) **918** can enact. Moreover, server(s) **914** can provision services from external network(s), e.g., WAN **950**, or Global Positioning System (GPS) network(s) (not shown). It is to be noted that server(s) **914** can include one or more processor configured to confer at least in part the functionality of macro network platform **910**. To that end, the one or more processor can execute code instructions stored in memory **930**, for example.

In example wireless environment **900**, memory **930** stores information related to operation of macro network platform **910**. Information can include business data associated with subscribers; market plans and strategies, e.g., promotional campaigns, business partnerships; operational data for mobile devices served through macro network platform; service and privacy policies; end-user service logs for law enforcement; and so forth. Memory **930** can also store information from at least one of telephony network(s) **940**, WAN (s) **950**, or SS7 network **960**, enterprise NW(s) **965**, or service NW(s) **967**.

Femto gateway node(s) **984** have substantially the same functionality as PS gateway node(s) **918**. Additionally, femto gateway node(s) **984** can also include substantially all functionality of serving node(s) **916**. In an aspect, femto gateway node(s) **984** facilitates handover resolution, e.g., assessment and execution. Further, control node(s) **920** can receive handover requests and relay them to a handover component (not shown) via gateway node(s) **984**. According to an aspect, control node(s) **920** can support RNC capabilities.

Server(s) **982** have substantially the same functionality as described in connection with server(s) **914**. In an aspect, server(s) **982** can execute multiple application(s) that provide service (e.g., voice and data) to wireless devices served through femto RAN **990**. Server(s) **982** can also provide security features to femto network platform. In addition, server(s) **982** can manage (e.g., schedule, queue, format . . .) substantially all packetized flows (e.g., IP-based, frame relay-based, ATM-based) it generates in addition to data received from macro network platform **910**. It is to be noted that server(s) **982** can include one or more processor configured to confer at least in part the functionality of macro network platform **910**. To that end, the one or more processor can execute code instructions stored in memory **986**, for example.

Memory **986** can include information relevant to operation of the various components of femto network platform **980**. For example operational information that can be stored in memory **986** can comprise, but is not limited to, subscriber information; contracted services; maintenance and service records; femto cell configuration (e.g., devices served

through femto RAN 990; access control lists, or white lists); service policies and specifications; privacy policies; add-on features; and so forth.

It is noted that femto network platform 980 and macro network platform 910 can be functionally connected through one or more reference link(s) or reference interface(s). In addition, femto network platform 980 can be functionally coupled directly (not illustrated) to one or more of external network(s) 940, 950, 960, 965 or 967. Reference link(s) or interface(s) can functionally link at least one of gateway node(s) 984 or server(s) 986 to the one or more external networks 940, 950, 960, 965 or 967.

FIG. 10 illustrates a wireless environment that includes macro cells and femtocells for wireless coverage in accordance with aspects described herein. In wireless environment 1050, two areas 1005 represent "macro" cell coverage; each macro cell is served by a base station 1010. It can be appreciated that macro cell coverage area 1005 and base station 1010 can include functionality, as more fully described herein, for example, with regard to system 1000. Macro coverage is generally intended to serve mobile wireless devices, like UE 1020_A, 1020_B, in outdoors locations. An over-the-air wireless link 105 provides such coverage, the wireless link 1215 comprises a downlink (DL) and an uplink (UL), and utilizes a predetermined band, licensed or unlicensed, of the radio frequency (RF) spectrum. As an example, UE 1020_A, 1020_B can be a 3GPP Universal Mobile Telecommunication System (UMTS) mobile phone. It is noted that a set of base stations, its associated electronics, circuitry or components, base stations control component(s), and wireless links operated in accordance to respective base stations in the set of base stations form a radio access network (RAN). In addition, base station 1010 communicates via backhaul link(s) 1051 with a macro network platform 1060, which in cellular wireless technologies (e.g., 3rd Generation Partnership Project (3GPP) Universal Mobile Telecommunication System (UMTS), Global System for Mobile Communication (GSM)) represents a core network.

In an aspect, macro network platform 1060 controls a set of base stations 1010 that serve either respective cells or a number of sectors within such cells. Base station 1010 comprises radio equipment 1014 for operation in one or more radio technologies, and a set of antennas 1012 (e.g., smart antennas, microwave antennas, satellite dish(es) . . .) that can serve one or more sectors within a macro cell 1005. It is noted that a set of radio network control node(s), which can be a part of macro network platform; a set of base stations (e.g., Node B 1010) that serve a set of macro cells 1005; electronics, circuitry or components associated with the base stations in the set of base stations; a set of respective OTA wireless links (e.g., links 1015 or 1016) operated in accordance to a radio technology through the base stations; and backhaul link(s) 1055 and 1051 form a macro radio access network (RAN). Macro network platform 1060 also communicates with other base stations (not shown) that serve other cells (not shown). Backhaul link(s) 1051 or 1053 can include a wired backbone link (e.g., optical fiber backbone, twisted-pair line, T1/E1 phone line, a digital subscriber line (DSL) either synchronous or asynchronous, an asymmetric ADSL, or a coaxial cable . . .) or a wireless (e.g., line-of-sight (LOS) or non-LOS) backbone link. Backhaul pipe(s) 1055 link disparate base stations 1010. According to an aspect, backhaul link 1053 can connect multiple femto access points 1030 and/or controller components (CC) 1001 to the femto network platform 1002. In one example, multiple femto APs can be connected to a routing platform (RP) 1087, which in turn can be connect to a controller component (CC) 1001. Typically, the information from

UEs 1020_A can be routed by the RP 102, for example, internally, to another UE 1020_A connected to a disparate femto AP connected to the RP 1087, or, externally, to the femto network platform 1002 via the CC 1001, as discussed in detail supra.

In wireless environment 1050, within one or more macro cell(s) 1005, a set of femtocells 1045 served by respective femto access points (APs) 1030 can be deployed. It can be appreciated that, aspects of the subject innovation are geared to femtocell deployments with substantive femto AP density, e.g., 10^4 - 10^7 femto APs 1030 per base station 1010. According to an aspect, a set of femto access points 1030₁-1030_N, with N a natural number, can be functionally connected to a routing platform 1087, which can be functionally coupled to a controller component 1001. The controller component 1001 can be operationally linked to the femto network platform 330 by employing backhaul link(s) 1053. Accordingly, UE 1020_A connected to femto APs 1030₁-1030_N can communicate internally within the femto enterprise via the routing platform (RP) 1087 and/or can also communicate with the femto network platform 1002 via the RP 1087, controller component 1001 and the backhaul link(s) 1053. It can be appreciated that although only one femto enterprise is depicted in FIG. 10, multiple femto enterprise networks can be deployed within a macro cell 1005.

It is noted that while various aspects, features, or advantages described herein have been illustrated through femto access point(s) and associated femto coverage, such aspects and features also can be exploited for home access point(s) (HAPs) that provide wireless coverage through substantially any, or any, disparate telecommunication technologies, such as for example Wi-Fi (wireless fidelity) or picocell telecommunication. Additionally, aspects, features, or advantages of the subject innovation can be exploited in substantially any wireless telecommunication, or radio, technology; for example, Wi-Fi, Worldwide Interoperability for Microwave Access (WiMAX), Enhanced General Packet Radio Service (Enhanced GPRS), 3GPP LTE, 3GPP2 UMB, 3GPP UMTS, HSPA, HSDPA, HSUPA, or LTE Advanced. Moreover, substantially all aspects of the subject innovation can include legacy telecommunication technologies.

Referring now to FIG. 11, there is illustrated a block diagram of an exemplary computer system operable to execute the disclosed architecture. In order to provide additional context for various aspects of the disclosed subject matter, FIG. 11 and the following discussion are intended to provide a brief, general description of a suitable computing environment 1100 in which the various aspects of the disclosed subject matter can be implemented. Additionally, while the disclosed subject matter described above may be suitable for application in the general context of computer-executable instructions that may run on one or more computers, those skilled in the art will recognize that the disclosed subject matter also can be implemented in combination with other program modules and/or as a combination of hardware and software.

Generally, program modules include routines, programs, components, data structures, etc., that perform particular tasks or implement particular abstract data types. Moreover, those skilled in the art will appreciate that the inventive methods can be practiced with other computer system configurations, including single-processor or multiprocessor computer systems, minicomputers, mainframe computers, as well as personal computers, hand-held computing devices, micro-processor-based or programmable consumer electronics, and the like, each of which can be operatively coupled to one or more associated devices.

The illustrated aspects of the disclosed subject matter may also be practiced in distributed computing environments where certain tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing environment, program modules can be located in both local and remote memory storage devices.

A computer typically includes a variety of computer-readable media. Computer-readable media can be any available media that can be accessed by the computer and includes both volatile and nonvolatile media, removable and non-removable media. By way of example, and not limitation, computer-readable media can comprise computer storage media and communication media. Computer storage media can include either volatile or nonvolatile, removable and non-removable media implemented in any method or technology for storage of information such as computer-readable instructions, data structures, program modules or other data. Computer storage media includes, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disk (DVD) or other optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by the computer.

Communication media typically embodies computer-readable instructions, data structures, program modules or other data in a modulated data signal such as a carrier wave or other transport mechanism, and includes any information delivery media. The term "modulated data signal" means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. By way of example, and not limitation, communication media includes wired media such as a wired network or direct-wired connection, and wireless media such as acoustic, RF, infrared and other wireless media. Combinations of the any of the above should also be included within the scope of computer-readable media.

With reference again to FIG. 11, the exemplary environment 1100 for implementing various aspects of the disclosed subject matter includes a computer 1102, the computer 1102 including a processing unit 1104, a system memory 1106 and a system bus 1108. The system bus 1108 couples to system components including, but not limited to, the system memory 1106 to the processing unit 1104. The processing unit 1104 can be any of various commercially available processors. Dual microprocessors and other multi-processor architectures may also be employed as the processing unit 1104.

The system bus 1108 can be any of several types of bus structure that may further interconnect to a memory bus (with or without a memory controller), a peripheral bus, and a local bus using any of a variety of commercially available bus architectures. The system memory 1106 includes read-only memory (ROM) 1110 and random access memory (RAM) 1112. A basic input/output system (BIOS) is stored in a non-volatile memory 1110 such as ROM, EPROM, EEPROM, which BIOS contains the basic routines that help to transfer information between elements within the computer 1102, such as during start-up. The RAM 1112 can also include a high-speed RAM such as static RAM for caching data.

The computer 1102 further includes an internal hard disk drive (HDD) 1114 (e.g., EIDE, SATA), which internal hard disk drive 1114 may also be configured for external use in a suitable chassis (not shown), a magnetic floppy disk drive (FDD) 1116, (e.g., to read from or write to a removable diskette 1118) and an optical disk drive 1120, (e.g., reading a CD-ROM disk 1122 or, to read from or write to other high capacity optical media such as the DVD). The hard disk drive

1114, magnetic disk drive 1116 and optical disk drive 1120 can be connected to the system bus 1108 by a hard disk drive interface 1124, a magnetic disk drive interface 1126 and an optical drive interface 1128, respectively. The interface 1124 for external drive implementations includes at least one or both of Universal Serial Bus (USB) and IEEE1394 interface technologies. Other external drive connection technologies are within contemplation of the subject matter disclosed herein.

The drives and their associated computer-readable media provide nonvolatile storage of data, data structures, computer-executable instructions, and so forth. For the computer 1102, the drives and media accommodate the storage of any data in a suitable digital format. Although the description of computer-readable media above refers to a HDD, a removable magnetic diskette, and a removable optical media such as a CD or DVD, it should be appreciated by those skilled in the art that other types of media which are readable by a computer, such as zip drives, magnetic cassettes, flash memory cards, cartridges, and the like, may also be used in the exemplary operating environment, and further, that any such media may contain computer-executable instructions for performing the methods of the disclosed subject matter.

A number of program modules can be stored in the drives and RAM 1112, including an operating system 1130, one or more application programs 1132, other program modules 1134 and program data 1136. All or portions of the operating system, applications, modules, and/or data can also be cached in the RAM 1112. It is appreciated that the disclosed subject matter can be implemented with various commercially available operating systems or combinations of operating systems.

A user can enter commands and information into the computer 1102 through one or more wired/wireless input devices, e.g., a keyboard 1138 and a pointing device, such as a mouse 1140. Other input devices (not shown) may include a microphone, an IR remote control, a joystick, a game pad, a stylus pen, touch screen, or the like. These and other input devices are often connected to the processing unit 1104 through an input device interface 1142 that is coupled to the system bus 1108, but can be connected by other interfaces, such as a parallel port, an IEEE1394 serial port, a game port, a USB port, an IR interface, etc.

A monitor 1144 or other type of display device is also connected to the system bus 1108 via an interface, such as a video adapter 1146. In addition to the monitor 1144, a computer typically includes other peripheral output devices (not shown), such as speakers, printers, etc.

The computer 1102 may operate in a networked environment using logical connections via wired and/or wireless communications to one or more remote computers, such as a remote computer(s) 1148. The remote computer(s) 1148 can be a workstation, a server computer, a router, a personal computer, a mobile device, portable computer, microprocessor-based entertainment appliance, a peer device or other common network node, and typically includes many or all of the elements described relative to the computer 1102, although, for purposes of brevity, only a memory/storage device 1150 is illustrated. The logical connections depicted include wired/wireless connectivity to a local area network (LAN) 1152 and/or larger networks, e.g., a wide area network (WAN) 1154. Such LAN and WAN networking environments are commonplace in offices and companies, and facilitate enterprise-wide computer networks, such as intranets, all of which may connect to a global communications network, e.g., the Internet.

When used in a LAN networking environment, the computer 1102 is connected to the local network 1152 through a

wired and/or wireless communication network interface or adapter **1156**. The adapter **1156** may facilitate wired or wireless communication to the LAN **1152**, which may also include a wireless access point disposed thereon for communicating with the wireless adapter **1156**.

When used in a WAN networking environment, the computer **1102** can include a modem **1158**, or is connected to a communications server on the WAN **1154**, or has other means for establishing communications over the WAN **1154**, such as by way of the Internet. The modem **1158**, which can be internal or external and a wired or wireless device, is connected to the system bus **1108** via the serial port interface **1142**. In a networked environment, program modules depicted relative to the computer **1102**, or portions thereof, can be stored in the remote memory/storage device **1150**. It will be appreciated that the network connections shown are exemplary and other means of establishing a communications link between the computers can be used.

The computer **1102** is operable to communicate with any wireless devices or entities operatively disposed in wireless communication, e.g., a printer, scanner, desktop and/or portable computer, portable data assistant, communications satellite, any piece of equipment or location associated with a wirelessly detectable tag (e.g., a kiosk, news stand, restroom), and telephone. This includes at least Wi-Fi and Bluetooth™ wireless technologies. Thus, the communication can be a predefined structure as with a conventional network or simply an ad hoc communication between at least two devices.

Wi-Fi, or Wireless Fidelity, allows connection to the Internet from a couch at home, a bed in a hotel room, or a conference room at work, without wires. Wi-Fi is a wireless technology similar to that used in a cell phone that enables such devices, e.g., computers, to send and receive data indoors and out; anywhere within the range of a base station. Wi-Fi networks use radio technologies called IEEE802.11 (a, b, g, n, etc.) to provide secure, reliable, fast wireless connectivity. A Wi-Fi network can be used to connect computers to each other, to the Internet, and to wired networks (which use IEEE802.3 or Ethernet). Wi-Fi networks operate in the unlicensed 2.4 and 5 GHz radio bands, at an 11 Mbps (802.11b) or 54 Mbps (802.11a) data rate, for example, or with products that contain both bands (dual band), so the networks can provide real-world performance similar to the basic “10BaseT” wired Ethernet networks used in many offices.

Various aspects or features described herein can be implemented as a method, apparatus, or article of manufacture using standard programming and/or engineering techniques. In addition, various aspects disclosed in the subject specification can also be implemented through program modules stored in a memory and executed by a processor, or other combination of hardware and software, or hardware and firmware. The term “article of manufacture” as used herein is intended to encompass a computer program accessible from any computer-readable device, carrier, or media. For example, computer readable media can include but are not limited to magnetic storage devices (e.g., hard disk, floppy disk, magnetic strips . . .), optical disks (e.g., compact disc (CD), digital versatile disc (DVD), blu-ray disc (BD) . . .), smart cards, and flash memory devices (e.g., card, stick, key drive . . .). Additionally it should be appreciated that a carrier wave can be employed to carry computer-readable electronic data such as those used in transmitting and receiving electronic mail or in accessing a network such as the internet or a local area network (LAN). Of course, those skilled in the art will recognize many modifications may be made to this configuration without departing from the scope or spirit of the disclosed subject matter.

As it employed in the subject specification, the term “processor” can refer to substantially any computing processing unit or device comprising, but not limited to comprising, single-core processors; single-processors with software multithread execution capability; multi-core processors; multi-core processors with software multithread execution capability; multi-core processors with hardware multithread technology; parallel platforms; and parallel platforms with distributed shared memory. Additionally, a processor can refer to an integrated circuit, an application specific integrated circuit (ASIC), a digital signal processor (DSP), a field programmable gate array (FPGA), a programmable logic controller (PLC), a complex programmable logic device (CPLD), a discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. Processors can exploit nanoscale architectures such as, but not limited to, molecular and quantum-dot based transistors, switches and gates, in order to optimize space usage or enhance performance of user equipment. A processor also can be implemented as a combination of computing processing units.

In the subject specification, terms such as “store,” “data store,” “data storage,” “database,” “repository,” and substantially any other information storage component relevant to operation and functionality of a component, refer to “memory components,” or entities embodied in a “memory” or components comprising the memory. It will be appreciated that the memory components described herein can be either volatile memory or nonvolatile memory, or can include both volatile and nonvolatile memory. In addition, memory components or memory elements can be removable or stationary. Moreover, memory can be internal or external to a device or component, or removable or stationary. Memory can include various types of media that are readable by a computer, such as hard-disc drives, zip drives, magnetic cassettes, flash memory cards or other types of memory cards, cartridges, or the like.

By way of illustration, and not limitation, nonvolatile memory can include read only memory (ROM), programmable ROM (PROM), electrically programmable ROM (EPROM), electrically erasable ROM (EEPROM), or flash memory. Volatile memory can include random access memory (RAM), which acts as external cache memory. By way of illustration and not limitation, RAM is available in many forms such as synchronous RAM (SRAM), dynamic RAM (DRAM), synchronous DRAM (SDRAM), double data rate SDRAM (DDR SDRAM), enhanced SDRAM (ESDRAM), Synchlink DRAM (SLDRAM), and direct Rambus RAM (DRRAM). Additionally, the disclosed memory components of systems or methods herein are intended to comprise, without being limited to comprising, these and any other suitable types of memory.

What has been described above includes examples of the various embodiments. It is, of course, not possible to describe every conceivable combination of components or methodologies for purposes of describing the embodiments, but one of ordinary skill in the art may recognize that many further combinations and permutations are possible. Accordingly, the detailed description is intended to embrace all such alterations, modifications, and variations that fall within the spirit and scope of the appended claims.

In particular and in regard to the various functions performed by the above described components, devices, circuits, systems and the like, the terms (including a reference to a “means”) used to describe such components are intended to correspond, unless otherwise indicated, to any component which performs the specified function of the described component (e.g., a functional equivalent), even though not struc-

turally equivalent to the disclosed structure, which performs the function in the herein illustrated exemplary aspects of the embodiments. In this regard, it will also be recognized that the embodiments includes a system as well as a computer-readable medium having computer-executable instructions for performing the acts and/or events of the various methods.

In addition, while a particular feature may have been disclosed with respect to only one of several implementations, such feature may be combined with one or more other features of the other implementations as may be desired and advantageous for any given or particular application. Furthermore, to the extent that the terms “includes,” and “including” and variants thereof are used in either the detailed description or the claims, these terms are intended to be inclusive in a manner similar to the term “comprising.”

What is claimed is:

1. A non-transitory machine readable storage medium comprising executable instructions that, when executed by a processor, facilitate performance of operations, comprising: receiving, from a gateway device, handoff data representing a handoff event that changes a first communication path for a user equipment device to a second communication path;

in response to determining a handoff issue associated with the handoff event for the user equipment based on the handoff data, generating a notification; and

transmitting the notification to a mobility management entity device, wherein the notification causes the mobility management entity device to select a different communication path for the user equipment and wherein the different communication path differs from the second communication path.

2. The machine readable storage medium of claim 1, wherein the gateway device is a serving gateway device.

3. The machine readable storage medium of claim 1, wherein the determining the handoff issue is based on count data representing a count of a threshold crossing alarm associated with an evolved nodeB device of the second communication path.

4. The machine readable storage medium of claim 1, wherein the determining the handoff issue is based on an unavailability condition associated with an evolved nodeB device of the second communication path.

5. The machine readable storage medium of claim 1, wherein the determining the handoff issue is based on a degraded air interface between the user equipment and an evolved nodeB device of the second communication path.

6. The machine readable storage medium of claim 1, wherein the determining the handoff issue is based on one of a buffer overflow condition or a packet loss condition associated with an evolved nodeB device of the second communication path.

7. The machine readable storage medium of claim 1, wherein the alternative communication path is associated with an alternate radio access technology that differs from a radio access technology associated with the second communication path.

8. The machine readable storage medium of claim 7, wherein the alternate radio access technology is associated with a communications standard that differs from a communications standard associated with a long term evolution network.

9. The machine readable storage medium of claim 1, wherein the transmitting the notification to the mobility management entity device comprises transmitting the notification to the mobility management entity device prior to a handoff failure associated with the user equipment.

10. The machine readable storage medium of claim 1, wherein the handoff event is directed to a first handoff initiated by an evolved nodeB device associated with the first communication path or a second handoff initiated by the user equipment.

11. A non-transitory machine readable storage medium comprising executable instructions that, when executed by a processor, facilitate performance of operations, comprising: receiving handoff data representing a handoff operation that reroutes a first communication path for a user equipment to a second communication path that differs from the first communication path;

in response to identifying, prompted by the handoff data, a handoff issue associated with the handoff operation, generating a notification comprising an instruction for a mobility management entity device of a long term evolution network to select an alternative communication path for the user equipment, wherein the alternative communication path differs from the second communication path; and providing the notification to the mobility management entity device.

12. The machine readable storage medium of claim 11, wherein the identifying the handoff issue is based on count data representing a count of a threshold crossing alarm associated with an evolved nodeB device of the second communication path.

13. The machine readable storage medium of claim 11, wherein the identifying the handoff issue is based on an unavailability condition associated with an evolved nodeB device of the second communication path.

14. The machine readable storage medium of claim 11, wherein the identifying the handoff issue is based on a degraded air interface between the user equipment and an evolved nodeB device of the second communication path.

15. The machine readable storage medium of claim 11, wherein the identifying the handoff issue is based on a buffer overflow condition associated with an evolved nodeB device of the second communication path.

16. A non-transitory machine readable storage medium comprising executable instructions that, when executed by a processor, facilitate performance of operations, comprising: receiving, from a gateway device of a long term evolution communication network, handoff data representing a handoff transaction that switches a first communication path for a mobile device to a second communication path that differs from the first communication path; and

in response to determining a handoff issue associated with the handoff transaction based on the handoff data, determining an alternative communication path for the mobile device, wherein the alternative communication path differs from the second communication path.

17. The machine readable storage medium of claim 16, wherein the receiving the handoff data comprises receiving the handoff data from a serving gateway device.

18. The machine readable storage medium of claim 16, wherein the alternative communication path is associated with an alternate radio access technology that differs from a radio access technology associated with the second communication path.

19. The machine readable storage medium of claim 18, wherein the alternate radio access technology is associated with a communications standard that differs from a communications standard associated with a long term evolution network.

20. The machine readable storage medium of claim 16, wherein the determining the alternative communication path

comprises determining the alternative communication path prior to a handoff failure associated with the second communication path.

* * * * *