

US009364047B2

(12) **United States Patent**
Fackler

(10) **Patent No.:** **US 9,364,047 B2**
(45) **Date of Patent:** **Jun. 14, 2016**

(54) **ICE FLOP STOPPER**

(71) Applicant: **Frank L Fackler**, Chicago, IL (US)

(72) Inventor: **Frank L Fackler**, Chicago, IL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/324,075**

(22) Filed: **Jul. 3, 2014**

(65) **Prior Publication Data**

US 2016/0000186 A1 Jan. 7, 2016

(51) **Int. Cl.**

A43C 15/06 (2006.01)

A63C 13/00 (2006.01)

A43C 15/00 (2006.01)

(52) **U.S. Cl.**

CPC *A43C 15/061* (2013.01); *A43C 15/00* (2013.01); *A63C 13/003* (2013.01); *A63C 13/006* (2013.01)

(58) **Field of Classification Search**

CPC A43B 3/16; A43C 11/1406; A43C 15/061; A43C 15/06; A43C 15/09; A43C 15/006; A43C 15/003

USPC 36/113, 114, 116, 117.2, 117.4, 117.5, 36/122, 123, 129, 7.7, 159, 160, 97, 1, 7.5, 36/7.6, 59 R, 62, 112, 115, 131, 132, 460, 36/305; 482/79

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

800,734 A * 10/1905 Friedheim 36/7.6
1,204,376 A * 11/1916 Newkirk 2/305
1,207,005 A * 12/1916 Fache 36/7.6
1,216,896 A * 2/1917 Webb 36/7.6
1,458,497 A * 6/1923 Perkins 36/7.6

1,539,762 A * 5/1925 Scipio 36/97
1,562,128 A * 11/1925 Stanley 450/29
1,749,522 A * 3/1930 Bertrand 36/7.7
1,776,707 A * 9/1930 Schmeichel 2/305
1,860,727 A * 5/1932 Ansley 2/305
2,617,209 A * 11/1952 Jackson 36/7.3
2,719,302 A * 10/1955 Cooperman 2/73
3,019,533 A * 2/1962 Smith 36/7.6
3,095,657 A * 7/1963 Fradette 36/7.6
3,229,389 A * 1/1966 Adams 36/7.6
3,609,888 A * 10/1971 Richman 36/7.5
4,299,037 A * 11/1981 Carey 36/7.6
4,353,172 A * 10/1982 Bryant A43C 15/068
36/62
4,525,939 A * 7/1985 McNeil et al. 36/7.6
5,125,479 A * 6/1992 Nemes A63C 5/00
182/230

(Continued)

OTHER PUBLICATIONS

[Http://link.springer.com/article/10.1007/s00421-011-1958-4/fulltext.html](http://link.springer.com/article/10.1007/s00421-011-1958-4/fulltext.html) Changes in muscle contractile characteristics and jump height following 24 days of unilateral lower limb suspension, Apr. 20, 2011.*


(Continued)

Primary Examiner — Shaun R Hurley
Assistant Examiner — Bao-Thieu L Nguyen
(74) *Attorney, Agent, or Firm* — Fraline J. Allgaier

(57) **ABSTRACT**

A traction overshoe which enables a user to safely cover the footwear while sitting or standing. The traction overshoe has left side flaps, right side flaps and a tension cord system. The left side flaps and the right side flaps are contiguous with the front and back supports of the traction overshoe and a tension cord system is attached to the right side flaps and the left side flaps. In use, a user grips a bottom grip-bar and moves the left side flaps and the right side flaps into vertical positions. The user then slips the footwear into the device and moves the bottom grip-bar in an upward position to secure the left side flaps and the right side flaps against the footwear.

1 Claim, 4 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,341,582 A * 8/1994 Liautaud 36/7.6
 5,659,978 A * 8/1997 Bell et al. 36/7.6
 5,689,901 A * 11/1997 Bell et al. 36/7.6
 5,950,334 A * 9/1999 Gerhardt 36/59 R
 6,044,578 A * 4/2000 Kelz 36/7.5
 6,154,982 A * 12/2000 Bell et al. 36/7.6
 6,223,456 B1 * 5/2001 Hawkins 36/113
 6,836,977 B2 * 1/2005 Larson et al. 36/59 R
 6,988,328 B2 * 1/2006 Rosen et al. 36/7.1 R
 7,716,855 B2 * 5/2010 Gallay et al. 36/122
 D664,331 S * 7/2012 Weis D2/906
 8,827,873 B2 * 9/2014 Arnstein A61H 1/0266
 482/79
 2002/0095820 A1 * 7/2002 Giovale 36/7.6
 2003/0154626 A1 * 8/2003 Larson et al. 36/7.6
 2004/0016145 A1 * 1/2004 Skrivan et al. 36/7.6
 2004/0045190 A1 * 3/2004 Washburn et al. 36/7.6
 2004/0049943 A1 * 3/2004 Glicksman 36/7.1 R
 2004/0194346 A1 * 10/2004 Petzl et al. 36/59 R

2005/0193588 A1 * 9/2005 Dombowsky 36/7.5
 2007/0056187 A1 * 3/2007 Burgess 36/7.6
 2009/0071034 A1 * 3/2009 Lotterhos et al. 36/7.3
 2011/0047829 A1 * 3/2011 Bell et al. 36/134
 2012/0266491 A1 * 10/2012 May 36/62
 2013/0180130 A1 * 7/2013 Giovale et al. 36/62
 2013/0312281 A1 * 11/2013 Girard 36/62
 2013/0312282 A1 * 11/2013 Girard 36/62
 2014/0215862 A1 * 8/2014 Curl et al. 36/59 R

OTHER PUBLICATIONS

[Http://blog.alpineinstitute.com/2011/03/rappelling-rope-climbing-trick.html](http://blog.alpineinstitute.com/2011/03/rappelling-rope-climbing-trick.html) Rappelling Rope Climbing Trick, Mar. 22, 2011.*
[Http://www.rehab.research.va.gov/jour/04/41/5/Zancan.html](http://www.rehab.research.va.gov/jour/04/41/5/Zancan.html) A new hip-knee-ankle-foot sling: Kinematic comparison with a traditional ankle-foot orthosis, vol. 41 No. 5, Sep./Oct. 2004.*
[Https://web.archive.org/web/20140315150206/http://www.itsalwaysautumn.com/wp-content/uploads/2014/01/fun-for-kids-rainy-day-crafts-activities-best-ideas-10.jpg](https://web.archive.org/web/20140315150206/http://www.itsalwaysautumn.com/wp-content/uploads/2014/01/fun-for-kids-rainy-day-crafts-activities-best-ideas-10.jpg) Walking stilts for kids, Mar. 15, 2014.*

* cited by examiner

FIG. 1

FIG. 2




FIG. 3




FIG. 4





FIG. 5a

FIG. 5b



1

ICE FLOP STOPPER

CLAIM TO DOMESTIC PRIORITY

The present non-provisional application claims priority of 5 U.S. Provisional Application Ser. No. 61/965,242 entitled "The Ice Flop Stopper", filed on Jan. 27, 2014, by Frank Lee Fackler, the entire contents of which is incorporated herein by reference thereto.

FIELD OF THE INVENTION

This application relates generally to footwear and more particularly to footwear covers which are adapted to provide 15 traction and support for the bottom surfaces of various types of footwear.

BACKGROUND OF THE INVENTION

Injuries related to slips and falls are common during the winter months in many areas of the world. These injuries can occur while walking or performing common activities including walking to and from cars, buses or trains. These injuries can occur especially when walking on icy steps or icy side-walks when entering or exiting vehicles. These types of activities would often require a person to pay special attention to avoid slipping and falling.

A variety of footwear has been developed to help individuals maneuver on icy surfaces. Many pedestrians have used 30 boots with grooved bottoms, boots made of non-slip rubber or neoprene, anti-slip studs or ice grippers. However, many of these products still lack sufficient traction to grip the surface and might break during use. Products such as ice grippers can be difficult to stretch over the user's footwear. They can be especially difficult for those individuals who have arthritis or other hand related conditions that cause a limited range of motion, making it very difficult to stretch the grippers over their footwear.

Walking on ice requires footwear that will help prevent slips or falls that cause injuries. The device of the present invention offers superior winter walking assistance on ice or snow. It makes it easy for the user to put the device on from either a standing or sitting position. The device features front and back supports which allows it to stay in place while being worn. The plurality of ice cleats provides extra safety when walking on ice or packed snow. The tension cords are attached to the device and give the user a better sense of security and safety. This helps the user walk with a more natural stride.

The device can be manufactured in variable sizes and it can 40 be worn by professionals, pedestrians, the elderly, and children. It will help to increase outdoor activity during winter months because of the ease of both putting on and removing the device.

SUMMARY OF THE INVENTION

In view of the problems associated with walking on ice or snow, it is an object of the present invention to provide a device that allows a person to safely walk on these surfaces. 60

Another objective of the present invention is to provide a device that affords security without slippage when walking or engaging in outdoor activities during winter months.

Another objective of the present invention is to provide a device that is secured directly to the footwear and the upper 65 torso and allows the user to walk with additional security and confidence.

2

Still another objective of the present invention is to provide a device which is simple and economical in its construction and effective for its intended use.

In accordance with the present invention, a device that covers footwear and provides additional traction while walking on ice is provided. The device comprises a shoe base and cords. The shoe base can be constructed from a durable material that is resistant to oil, heat and weathering. The shoe base features a front support, a back support, cleats and side flaps. 10

The flaps are attached along the sides of the device. They are connected to a tension cord system that is adapted to fit across the top torso of a user's body. The flaps can retract into horizontal and upright positions to enable the user to slide his or her footwear onto the shoe base. Ice cleats are attached to the bottom of the shoe base. The cleats can be constructed from a durable material and are adapted to grip ice or hard snow. The cleats are adapted to hold its position in the ice when the shoe retainer is moved forward.

The device features cords that are adapted to fit across the top torso of a person's body. The cords are constructed of a durable elastic material and are adapted to be connected to the flaps. Additional advantages of the invention will become apparent from the following detailed description taken in conjunction with the accompanying drawings. 25

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

FIG. 1 illustrates a front view of a person using the traction overshoe and the left side flaps and the right side flaps being secured against the traction overshoe.

FIG. 2 illustrates a side view of a person using the traction overshoe and the left side flaps and the right side flaps being secured against the traction overshoe. 35

FIG. 3 illustrates a modified version of the traction overshoe attached to a smaller tension cord system having a plurality of bottom grip-bars.

FIG. 4 is a perspective view of the traction overshoe.

FIG. 5a is a top perspective view of a right traction overshoe being engaged to allow a user to insert his or her footwear.

FIG. 5b is a top perspective view of a left traction overshoe being engaged to allow a user to insert his or her footwear. 45

DETAILED DESCRIPTION OF THE INVENTION

This invention relates to a traction overshoe **10** that can be used by individuals requiring assistance putting on shoes or boots in icy or slick situations. Individuals with a physical handicap or upper body pain can put on the traction overshoe **10** while sitting or standing. The traction overshoe **10** can be made to accommodate various types of footwear **28** including 50 tennis shoes, boots, sandals and dress shoes.

Referring now to the drawings, FIG. 1 and FIG. 2 show the preferred embodiment of the improved traction overshoe **10**. The traction overshoe **10** comprising right side flaps **12**, left side flaps **14** and a tension cord system **16**. The right side flaps **12** and the left side flaps **14** are located between the front portion **18** and the back portion **22** of the traction overshoe **10**. The right side flaps **12** and the left side flaps **14** are sufficiently spaced to allow independent movement and are attached to the base **24** of the traction overshoe **10**. The right side flaps **12** and the left side flaps **14** are adapted to move into horizontal and vertical positions to enable the user **20** to place his footwear **28** into the traction overshoe **10**. The right side flaps **12** 65

and the left side flaps **14** are attached to the tension cord system **16**. The tension cord system **16** has a top grip-bar **32** and a bottom grip-bar **34**.

With the traction overshoe **10** in a horizontal position, the user **20** grips the bottom grip-bar **34**, relaxes the tension cord system **16**, and allow the right side flaps **12** and the left side flaps **14** to move into horizontal positions. This allows the user **20** to slip the footwear **28** into the overshoe **10** and further adjust the right side flaps **12** and the left side flaps **14** against the side of the footwear **28** by pulling upwards on the bottom grip-bar **34**. The top grip-bar **32** can be used to adjust the tension cord system **16** onto the torso **42**. The tension cord system **16** can be draped over the head of the user **20** and slipped down to further engage with the torso **42**.

The right side flaps **12** are contiguous with the adjacent edges of the front portion **36** and the adjacent edges of the back portion **38** of the traction overshoe **10** once the bottom grip-bar **34** is pulled upwards. The left side flaps **14** are contiguous with the adjacent edges of the front portion **36** and the contiguous edges of the back portion **38** once the bottom grip-bar **34** is pulled upwards. The right side flaps **12** and the left side flaps **14** are adapted to support the side of the footwear **28** while the traction overshoe **10** is being used.

The right side flaps **12** and the left side flaps **14** are constructed from a flexible material that enables the right side flaps **12** and the left side flaps **14** to move into horizontal and vertical positions when the tension cord system **16** is being used. Examples of flexible material that can be used are cloth, suede, leather, fabric and plastic.

The tension cord system **16** can have a nominal thickness of at least one inch and can have a variety of tension cord resistance force levels. The tension cord system **16** can be constructed from a durable elastic material and can have various heights to facilitate an easier mounting process.

What is claimed is:

1. An improved traction overshoe comprising: right side flaps, left side flaps and a tension cord system; said right side flaps and said left side flaps being located between the front portion and back portion of said traction overshoe; said right side flaps and said left side flaps being sufficiently spaced to allow independent movement of said right side flaps and said left side flaps; said right side flaps and said left side flaps being attached to said traction overshoe base; said right side flaps and said left side flaps being adapted to move into horizontal and vertical positions to enable the user to place his footwear into said traction overshoe; said right side flaps and said left side flaps being attached to said tension cord system; said tension cord system having a top grip-bar and a bottom grip-bar; said user gripping said bottom grip-bar and moving said right side flaps and said left side flaps into a horizontal position and allowing said user to insert said footwear into said traction overshoe; said bottom grip-bar being pulled up to move said right side flaps and said left side flaps into a vertical position on said traction overshoe; said right side flaps being contiguous with the adjacent edges of said front portion and said back portion of said traction overshoe once said bottom grip-bar is pulled upwards; said left side flaps being contiguous with the adjacent edges of said front portion and said back portion of said traction overshoe once said bottom grip-bar is pulled upwards; said top grip-bar being used to adjust said tension cord system onto said user's torso; said right side flaps and said left side flaps being adapted to support the side of said user's footwear while said traction overshoe is being used; said right side flaps and said left side flaps being constructed from a flexible material that enables said right side flaps and said left side flaps to move into horizontal and vertical positions when said tension cord system is being used.

* * * * *