



US009372994B1

(12) **United States Patent**  
**Yampolskiy et al.**

(10) **Patent No.:** **US 9,372,994 B1**  
(45) **Date of Patent:** **Jun. 21, 2016**

(54) **ENTITY IP MAPPING**

- (71) Applicant: **Security Scorecard**, New York, NY (US)
- (72) Inventors: **Aleksandr Yampolskiy**, Brooklyn, NY (US); **Rob Blackin**, East Brunswick, NJ (US); **Samuel Kassoumeh**, Brooklyn, NY (US); **Nick Matviko**, New York, NY (US)
- (73) Assignee: **Security Scorecard, Inc.**, New York, NY (US)
- (\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
- (21) Appl. No.: **14/702,668**
- (22) Filed: **May 1, 2015**

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,205,489	B1 *	3/2001	Kapoor	709/245
7,178,166	B1	2/2007	Taylor et al.	
7,237,264	B1	6/2007	Graham et al.	
7,574,740	B1	8/2009	Kennis	
7,634,800	B2	12/2009	Ide et al.	
7,913,303	B1	3/2011	Rouland et al.	
7,934,254	B2	4/2011	Graham	
8,131,745	B1 *	3/2012	Hoffman et al.	707/766
8,316,440	B1 *	11/2012	Hsieh	G06F 11/108 713/168
8,856,239	B1 *	10/2014	Oliver et al.	709/206
2005/0060297	A1 *	3/2005	Najork	707/3
2006/0248190	A1 *	11/2006	Gardos et al.	709/225
2008/0043617	A1 *	2/2008	Schekochikhin	H04L 43/0817 370/229
2008/0172738	A1 *	7/2008	Bates	G06F 17/30887 726/22
2008/0250159	A1 *	10/2008	Wang et al.	709/239
2009/0300768	A1 *	12/2009	Krishnamurthy et al.	726/26
2010/0037314	A1 *	2/2010	Perdisci	H04L 63/1416 726/22
2010/0088761	A1 *	4/2010	Podjarny	G06F 21/00 726/22

(Continued)

**Related U.S. Application Data**

- (60) Provisional application No. 62/091,477, filed on Dec. 13, 2014, provisional application No. 62/091,478, filed on Dec. 13, 2014.

- (51) **Int. Cl.**  
**G06F 21/57** (2013.01)  
**H04L 12/26** (2006.01)  
**H04L 29/12** (2006.01)  
**G06F 11/00** (2006.01)

- (52) **U.S. Cl.**  
CPC ..... **G06F 21/57** (2013.01); **H04L 43/065** (2013.01); **H04L 61/25** (2013.01); **G06F 2221/034** (2013.01)

- (58) **Field of Classification Search**  
CPC . G06F 21/57; G06F 2221/034; H04L 43/065; H04L 61/25

See application file for complete search history.


*Primary Examiner* — Darren B Schwartz

(74) *Attorney, Agent, or Firm* — Norton Rose Fulbright US LLP

(57) **ABSTRACT**

Systems and methods for mapping IP addresses to an entity include receiving at least one domain name associated with the entity. Embodiments may further include determining one or more variations of the at least one domain name based on analysis of domain name data collected from a plurality of domain name data sources that mention a variation of the at least one domain name. Some embodiments may also include identifying one or more IP addresses pointed to by the one or more variations of the entity's domain name based on analysis of IP address data collected from a plurality of IP address data sources. Additional embodiments include assigning weights to each of the identified one or more IP addresses and creating a mapping of IP addresses to associate with the entity based on analysis of the weighted one or more IP addresses.

**20 Claims, 5 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

2010/0121981	A1 *	5/2010	Drako .....	709/245	2013/0061321	A1 *	3/2013	Gardner .....	H04L 29/12066 726/22
2010/0257024	A1 *	10/2010	Holmes et al. ....	705/10	2013/0117282	A1 *	5/2013	Mugali et al. ....	707/748
2011/0167474	A1 *	7/2011	Sinha .....	G06F 21/56 726/1	2013/0203023	A1	8/2013	Sadeh-Konieczpol et al.	
2011/0276716	A1 *	11/2011	Coulson et al. ....	709/238	2013/0254179	A1 *	9/2013	Tan .....	707/706
2012/0089745	A1 *	4/2012	Turakhia .....	709/245	2014/0098955	A1	4/2014	Hughes et al.	
2012/0110672	A1 *	5/2012	Judge .....	H04L 51/12 726/25	2014/0189860	A1	7/2014	Hull Roskos	
2012/0180125	A1 *	7/2012	Sun .....	H04L 63/1441 726/22	2014/0199663	A1	7/2014	Sadeh-Konieczpol et al.	
					2014/0199664	A1	7/2014	Sadeh-Konieczpol et al.	
					2014/0280305	A1 *	9/2014	James et al. ....	707/769
					2014/0331318	A1 *	11/2014	Windsor et al. ....	726/22
					2015/0074579	A1	3/2015	Gladstone et al.	
					2015/0207809	A1 *	7/2015	Macaulay .....	726/22

\* cited by examiner




FIG. 1




FIG. 2




FIG. 2B




FIG. 3




FIG. 4

1

**ENTITY IP MAPPING****CROSS-REFERENCE TO RELATED APPLICATIONS**

This application claims priority to U.S. Provisional Patent Application No. 62/091,477 entitled "CORPORATE IP ADDRESS DISCOVERY THROUGH SUBSIDIARY AND INTERNAL SYSTEM MAPPING SYSTEM AND METHOD," filed on Dec. 13, 2014, and also claims priority to U.S. Provisional Patent Application No. 62/091,478 entitled "CORPORATE CYBER SECURITY BENCHMARKING AS A SERVICE SYSTEM AND METHOD," filed on Dec. 13, 2014. The entire contents of both are incorporated herein by reference.

**FIELD OF THE DISCLOSURE**

This disclosure generally relates to corporate cybersecurity technology. More specifically, this disclosure relates to mapping Internet Protocol (IP) addresses to an entity to assist in benchmarking the entity's cybersecurity risk.

**BACKGROUND**

An entity, such as an organization, corporation, or governmental entity, may have a number of IP addresses allocated to it through which computers may be used for internal and external communication. For some entities, employees at different locations may communicate with each other using different network service providers, such as Internet Service Providers (ISPs). Some entities may also be accessed using third-party hosting providers and virtualized cloud services, which often assign part of their own allocated IP addresses to the entity instead of one of the IP addresses already allocated to the entity. As a result, an entity may not know each of the different IP addresses through which employees and computers of the entity communicate.

**SUMMARY**

A scorecard system may create a mapping of IP addresses that are associated with an entity to improve accuracy in the calculation of the entity's cybersecurity risk. For example, according to one embodiment, a method for mapping IP addresses to an entity may include receiving, by a processor, at least one domain name associated with the entity. The method may also include determining, by the processor, one or more variations of the at least one domain name based on analysis of domain name data collected from a plurality of domain name data sources that mention a variation of the at least one domain name. The method may further include identifying, by the processor, one or more IP addresses pointed to by the one or more variations of the entity's domain name based on analysis of IP address data collected from a plurality of IP address data sources. The method may also include assigning, by the processor, a weight to each of the identified one or more IP addresses based on a correlation between each of the identified one or more IP addresses and the one or more variations of the at least one domain name. The method may further include creating, by the processor, a mapping of IP addresses to associate with the entity based on analysis of the weighted one or more IP addresses.

According to another embodiment, a computer program product includes a non-transitory computer-readable medium comprising instructions which, when executed by a processor of a computing system, cause the processor to perform the

2

step of receiving at least one domain name associated with the entity. The medium may also include instructions which cause the processor to perform the step of determining one or more variations of the at least one domain name based on analysis of domain name data collected from a plurality of domain name data sources that mention a variation of the at least one domain name. The medium may further include instructions which cause the processor to perform the step of identifying one or more IP addresses pointed to by the one or more variations of the entity's domain name based on analysis of IP address data collected from a plurality of IP address data sources. The medium may also include instructions which cause the processor to perform the step of assigning a weight to each of the identified one or more IP addresses based on a correlation between each of the identified one or more IP addresses and the one or more variations of the at least one domain name. The medium may further include instructions which cause the processor to perform the step of creating a mapping of IP addresses to associate with the entity based on analysis of the weighted one or more IP addresses.

According to yet another embodiment, an apparatus includes a memory and a processor coupled to the memory. The processor can be configured to execute the step of receiving at least one domain name associated with the entity. The processor may also be configured to execute the step of determining one or more variations of the at least one domain name based on analysis of domain name data collected from a plurality of domain name data sources that mention a variation of the at least one domain name. The processor can be configured to execute the step of identifying one or more IP addresses pointed to by the one or more variations of the entity's domain name based on analysis of IP address data collected from a plurality of IP address data sources. The processor may also be configured to execute the step of assigning a weight to each of the identified one or more IP addresses based on a correlation between each of the identified one or more IP addresses and the one or more variations of the at least one domain name. The processor can be configured to execute the step of creating a mapping of IP addresses to associate with the entity based on analysis of the weighted one or more IP addresses.

The foregoing has outlined rather broadly the features and technical advantages of the present invention in order that the detailed description of the invention that follows can be better understood. Additional features and advantages of the invention will be described hereinafter that form the subject of the claims of the invention. It should be appreciated by those skilled in the art that the concepts and specific embodiments disclosed can be readily utilized as a basis for modifying or designing other structures for carrying out the same purposes of the present invention. It should also be realized by those skilled in the art that such equivalent constructions do not depart from the spirit and scope of the invention as set forth in the appended claims. The novel features that are believed to be characteristic of the invention, both as to its organization and method of operation, together with further objects and advantages will be better understood from the following description when considered in connection with the accompanying figures. It is to be expressly understood, however, that each of the figures is provided for the purpose of illustration and description only and is not intended as a definition of the limits of the present invention.

**BRIEF DESCRIPTION OF THE DRAWINGS**

For a more complete understanding of the disclosure, reference is made to the following FIGURES taken in conjunction with their accompanying descriptions:



## 3

FIG. 1 is a block diagram of a network that includes a scorecard server, data sources, and an entity with a cybersecurity risk according to an embodiment;

FIG. 2 is a block diagram of a system for calculating and benchmarking an entity's cybersecurity risk according to an embodiment;

FIG. 2B is a block diagram of underlying components of a system for mapping IP addresses to an entity according to an embodiment; and

FIG. 3 is a flow chart of a method for mapping IP addresses to an entity according to an embodiment.

FIG. 4 is a flow diagram illustrating IP mapping with respect to one or more entities according to an embodiment.

## DETAILED DESCRIPTION

The IP addresses associated with an entity, including IP addresses associated with subsidiary and/or internal systems of the entity, may be determined based solely from knowledge of a domain name of an entity. Knowledge of the IP addresses associated with an entity may be useful for a variety of applications. For example, as illustrated in FIGS. 1-2, a mapping of the IP addresses associated with an entity may be used to determine a cybersecurity risk for an entity.

An IP address, as used herein, is a numerical label assigned to a device, such as a computer or printer, participating in a computer network that uses the Internet Protocol for communication. An IP address primarily serves two principal functions: (1) identification of a host or network interface, and (2) location addressing. IP addresses are typically binary numbers that are usually stored in text files and displayed in human-readable notations, such as 172.16.254.1 (for IPv4), and 2001:db8:0:1234:0:567:8:1 (for IPv6).

Certain units described in this specification have been labeled as modules in order to more particularly emphasize their implementation independence. A module is "[a] self-contained hardware or software component that interacts with a larger system." Alan Freedman, "The Computer Glossary" 268 (8th ed. 1998). A module comprises a machine- or machines-executable instructions. For example, a module may be implemented as a hardware circuit comprising custom VLSI circuits or gate arrays, off-the-shelf semiconductors such as logic chips, transistors, or other discrete components. A module may also be implemented in programmable hardware devices such as field programmable gate arrays, programmable array logic, programmable logic devices or the like.

Modules may also include software-defined units or instructions, that when executed by a processing machine or device, transform data stored on a data storage device from a first state to a second state. An identified module of executable code may, for instance, comprise one or more physical or logical blocks of computer instructions that may be organized as an object, procedure, or function. Nevertheless, the executables of an identified module need not be physically located together, but may comprise disparate instructions stored in different locations that, when joined logically together, comprise the module, and when executed by the processor, achieve the stated data transformation. A module of executable code may be a single instruction, or many instructions, and may even be distributed over several different code segments, among different programs, and/or across several memory devices. Similarly, operational data may be identified and illustrated herein within modules, and may be embodied in any suitable form and organized within any suitable type of data structure. The operational data may be

## 4

collected as a single data set, or may be distributed over different locations including over different storage devices.

In the following description, numerous specific details are provided, such as examples of programming, software modules, user selections, network transactions, database queries, database structures, hardware modules, hardware circuits, hardware chips, etc., to provide a thorough understanding of the present embodiments. One skilled in the relevant art will recognize, however, that the invention may be practiced without one or more of the specific details, or with other methods, components, materials, and so forth. In other instances, well-known structures, materials, or operations are not shown or described in detail to avoid obscuring aspects of the invention.

FIG. 1 is a block diagram of network **100** that includes a scorecard server **110**, a communication network **120**, an entity server **130**, an entity **140**, data sources **150**, and user station **160**. The scorecard server **110** includes one or more servers that, according to one embodiment, are configured to perform several of the functions described herein. One or more of the servers comprising the scorecard server **110** include memory, storage hardware, software residing thereon, and one or more processors configured to perform functions associated with network **100**. For example, components comprising user station **160**, such as CPU **162**, can be used to interface and/or implement scorecard server **110**. One of skill in the art will readily recognize that different server and computer architectures can be utilized to implement scorecard server **110** and that scorecard server **110** is not limited to a particular architecture so long as the hardware implementing scorecard server **110** supports the functions of the scorecard system disclosed herein.

The communication network **120** facilitates communications of data between the scorecard server **110** and the data sources **150**. The communication network **120** can also facilitate communications of data between the scorecard server **110** and other servers/processors, such as entity server **130**. The communication network **120** includes any type of communications network, such as a direct PC-to-PC connection, a local area network (LAN), a wide area network (WAN), a modem-to-modem connection, the Internet, a combination of the above, or any other communications network now known or later developed within the networking arts which permits two or more computers to communicate.

The entity server **130** includes the servers which the entity **140** uses to support its operations and which the scorecard server **110** accesses to collect further information to calculate and benchmark an entity's cybersecurity risk. The data sources **150** include the sources from which the scorecard server **110** collects information to calculate and benchmark an entity's cybersecurity risk.

The Entity **140** includes any organization, company, corporation, or group of individuals. For example, and not limitation, one entity may be a corporation with thousands of employees and headquarters in New York City, while another entity may be a group of one or more individuals associated with a website and having headquarters in a residential home.

Data Sources **150** includes any source of data accessible over Network **120**. For example, and not limitation, one source of data can include a website associated with a company, while another source of data may be an online database of various information. In general, the data sources **150** may be sources of any kind of data, such as domain name data, social media data, multimedia data, IP address data, and the like. One of skill in the art would readily recognize that data sources **150** are not limited to a particular data source, and that any source from which data may be retrieved may serve as a data source so long as it can be accessed by network **120**.

## 5

With respect to user station **160**, the central processing unit (“CPU”) **161** is coupled to the system bus **162**. The CPU **161** can be a general purpose CPU or microprocessor performing the functions of the scorecard server **110**, a graphics processing unit (“GPU”), and/or microcontroller. Embodiments are not restricted by the architecture of the CPU **161** so long as the CPU **161**, whether directly or indirectly, supports the operations described herein. The CPU **161** is one component may execute the various described logical instructions.

The user station **160** also comprises random access memory (RAM) **163**, which can be synchronous RAM (SRAM), dynamic RAM (DRAM), synchronous dynamic RAM (SDRAM), or the like. The user station **160** may utilize RAM **163** to store the various data structures used by a software application. The user station **160** also comprises read only memory (ROM) **164** which can be PROM, EPROM, EEPROM, optical storage, or the like. The ROM may store configuration information for booting the user station **160**. The RAM **163** and the ROM **164** hold user and system data, and both the RAM **163** and the ROM **164** can be randomly accessed.

The user station **160** also comprises an input/output (I/O) adapter **165**, a communications adapter **166**, a user interface adapter **167**, and a display adapter **168**. The I/O adapter **165** and/or the user interface adapter **167** may, in certain embodiments, enable a user to interact with the user station **160**. In a further embodiment, the display adapter **168** may display a graphical user interface (GUI) associated with a software or web-based application on a display device **169**, such as a monitor or touch screen.

The I/O adapter **165** may couple one or more storage devices **170**, such as one or more of a hard drive, a solid state storage device, a flash drive, a compact disc (CD) drive, a floppy disk drive, and a tape drive, to the user station **160**. Also, the data storage **170** can be a separate server coupled to the user station **160** through a network connection to the I/O adapter **165**. The communications adapter **166** can be adapted to couple the user station **160** to a network, which can be one or more of a LAN, WAN, and/or the Internet. The user interface adapter **167** couples user input devices, such as a keyboard **171**, a pointing device **172**, and/or a touch screen (not shown) to the user station **160**. The display adapter **168** can be driven by the CPU **161** to control the display on the display device **169**. Any of the devices **161-168** can be physical and/or logical.

The concepts described herein are not limited to the architecture of user station **160**. Rather, the user station **160** is provided as an example of one type of computing device that can be adapted to perform the functions of a server and/or the user interface device **165**. For example, any suitable processor-based device can be utilized including, without limitation, personal data assistants (PDAs), tablet computers, smartphones, computer game consoles, and multi-processor servers. Moreover, the systems and methods of the present disclosure can be implemented on application specific integrated circuits (ASIC), very large scale integrated (VLSI) circuits, or other circuitry. In fact, persons of ordinary skill in the art may utilize any number of suitable structures capable of executing logical operations according to the described embodiments.

It should be appreciated that user station **160**, or certain components thereof, may reside at, or be installed in, different locations within network **100**. According to the illustrated embodiment, user station **160** directly interfaces with scorecard server **110**. Such an embodiment is conducive for an individual or user not directly associated with entity **140** to effectuate computation of a cybersecurity risk and/or benchmark of same for that entity. However, in other embodiments,

## 6

one or more users located at entity **140** or locations directly associated with same, may effectuate computation of a cybersecurity risk and/or benchmark of same for that entity. In such an embodiment, user station **160** (or at least certain components thereof) may directly interface with entity servers **130**. Likewise, entity servers **130** may comprise the hardware and/or software found in scorecard server **110** in the illustrated embodiment. Importantly, the features necessary to compute cybersecurity risk scores and benchmarks can be collocated within network **100** or distributed across, e.g., scorecard server **110** and entity servers **130**, and user station(s) **160**.

FIG. **2** is a block diagram of a system for calculating and benchmarking an entity’s cybersecurity risk according to an embodiment. Such a system is described in detail in co-owned, U.S. Patent Application No. 14/702,661, filed May 1, 2015 and entitled “CALCULATING AND BENCHMARKING AN ENTITY’S CYBERSECURITY RISK SCORE,” [the disclosure of which is incorporated herein by reference in its entirety. System **200** can be implemented with one or more computing devices, such as scorecard server **110**, entity servers **130**, and user station(s) **160** illustrated in FIG. **1**. System **200** comprises a security signal collection module **210**, a contextualization and attribution module **220**, and a benchmarking module **230**.

Security signal collection module **210** collects one or more types of data that relate to the cybersecurity risks associated with an entity. Security signal collection module **210** comprises submodules that collect different types of data from a predefined “threat sphere.” The threat sphere may change depending on the entity for which a cybersecurity risk score is calculated, and may further change according to the goals and/or objectives of the entity. In any event, the threat sphere is typically defined to include sources of information that likely comprise, generate, are responsible for, or otherwise correspond to data indicative of an entity’s cybersecurity risk. Accordingly, each module or submodule that collects data corresponds to one more channels or data feeds from sources comprising the threat sphere.

According to the illustrated embodiment, security signal collection module **210** comprises a social engineering collection module **201**, a malware and botnet infection collection module **202**, an application vulnerabilities collection module **203**, a breach history collection module **204**, a network exploits collection module **205**, a DNS Health collection module **206**, a patching cadence collection module **207**, and a leaked credentials collection module **208**.

Security signal collection module **210** can also comprises a hacker forum monitoring module **209** for collecting data from hacker forums can also and an endpoint security analysis module **211** for collecting endpoint data.

Security signal collection module **210** can also comprises modules for specifying when data is collected and how data is associated with an entity. For example, the security signal collection module **210** comprises a continuous Internet scans module **212** for performing continuous scans of Internet data to collect data associated with an entity. The security signal collection module **210** can also comprises a real-time scans collection module **213** for collecting data in real time, such as collecting real-time threat intelligence/data and collecting data in real time from a malicious IP feed, which can include digesting 2000+ bad (IPS) per second. The security signal collection module **210** can also comprises an IP Mapping module **214** to reliably identify IP addresses associated with an entity. By mapping IP addresses to an entity, data collected the Internet over one or more channels comprising the threat sphere (or beyond) can be determined to be associated with, or attributable to, the given entity.

Contextualization and attribution module **220** contextualizes data collected by the security signal collection module **210**. The contextualization and attribution module **220** comprises an extraction module **222** to extract data relevant to cybersecurity of a given entity from the collected data. The contextualization and attribution module **220** can also comprise a normalization module **224** and a weighting module **226** to normalize and/or weight a preliminary security score determined based on a raw scoring of the extracted security data. The normalization and/or weighting of a preliminary score may depend on multiple factors, such as, for example, the size of the entity, the relationship between the extracted information and overall security performance, and the type of data collected.

The contextualization and attribution module **220** can also comprise a machine learning module **228** to identify and update which factors most significantly affect an entity's cybersecurity. This information can be used to further contextualize the collected data. For example, the security scores identified as being the most relevant may then be normalized and/or weighted to account for their relevancy. The contextualization process can also comprise applying temporal adjustments to security data or calculated security scores based on the time span between an event that generated the security data and the current date. In some embodiments, contextualization can also comprise validating threats, such as, for example, by confirming that an event creating data that indicates the presence of a malware event is in fact a malware event. Further aspects of the contextualization submodules are described in detail below.

Benchmarking module **230** calculates an overall cybersecurity risk score for an entity, as well as a benchmark based on cybersecurity performance metrics. The computed benchmark may further comprise a percentile ranking for the entity. For example, the benchmarking module **230** comprises a scoring module **232** to obtain the overall cybersecurity risk score for an entity based on the contextualization of the entity's security data and processing of scores for each of the different types of security data collected for the entity.

The benchmarking module **230** can also comprise a percentiles module **234** to determine a percentile ranking for the entity which provides an indication of how the entity's cybersecurity fares with respect to similar companies in the same industry. Further aspects of the benchmarking submodules are described in detail below. A scorecard server, such as scorecard server **100** from FIG. 1, may utilize one or more of the submodules in the security signal collection **210**, contextualization **220**, and benchmarking **230** modules to score and benchmark an entity's cybersecurity risk.

As is apparent from FIG. 1 and FIG. 2, a mapping of the IP addresses associated with an entity may be useful to improve the accuracy with which a scorecard system calculates a cybersecurity score for an entity. FIG. 2B is a block diagram of underlying components of a system for mapping IP addresses to an entity, and FIG. 3 is a flow chart illustrating a method for mapping IP addresses to an entity using the underlying components of the system for mapping IP addresses to an entity. It is noted that embodiments of method **300** can be implemented with the systems described with respect to FIGS. 1-2, in particular the underlying components illustrated in FIG. 2B. For example, a processor disclosed in method **300** may correspond to a processor within a scorecard server disclosed in this disclosure. Specifically, method **300** includes, at block **302**, receiving at least one domain name associated with the entity. For example, scorecard system **200** can implement reception module **219A** to receive a URL associated with an entity. The URL may include the domain

name for the entity. The URL, and in particular the domain name, may be input by a user accessing scorecard system **200**, for example, a user accessing scorecard system **200** via user station **160** illustrated in FIG. 1.

At block **304**, method **300** includes determining one or more variations of the at least one domain name. For example, scorecard system **200** can implement domain name variations module **219B** to determine one or more variations of a received domain name. In some embodiments, determination of the variations of the domain name may be based on analysis of domain name data collected from a plurality of domain name data sources that mention a variation of the domain name. As noted with respect to FIG. 1, data sources **150** from which domain name data may be gathered include any sources of data which include information about the domain names used or mentioned in the data source. Examples, and not limitations, of data sources include databases, such as Freebase™ and CrunchBase©, online services, such as LinkedIn©, and general informational websites, such as CNN.com. For example, given a domain "gs.com," scorecard system **200** may collect domain name data from multiple data sources across the Internet. The scorecard system **200** may analyze the domain name data collected from the data sources to determine one or more variations of the domain name, such as "gs.com" and "goldmansachs.com." In general, the domain name data may also include general mentions of an entity in a data source. For example, given a domain "gs.com," domain name variations may also include "Goldman Sachs, Inc." and "The Goldman Sachs," each of which may point to IP addresses. The information collected from all the data sources may be correlated to determine the most accurate variations of the domain names associated with an entity. For example, a machine learning algorithm may be developed to correlate the domain name data collected from all the data sources to determine the most accurate variations of the domain names associated with the entity. In some embodiments, the scorecard system **200** may also suffix or append characters to an identified domain name to aid in the determination of the domain name variations.

At block **306**, method **300** includes identifying one or more IP addresses pointed to by the one or more variations of the entity's domain name. For example, scorecard system **200** can implement IP address collection module **219C** to identify IP addresses pointed to by domain name data. In some embodiments, identification of the one or more IP addresses may be based on analysis of IP address data collected from a plurality of IP address data sources. Examples, and not limitations, of data sources from which IP addresses may be collected include IP registries, such as the American Registry for Internet Numbers (ARIN), the European IP Networks (RIPE), the Latin America and Caribbean Network Information Centre (LACNIC), the African Network Information Center (AFRINIC), and the Asia-Pacific Network Information Centre (APNIC). Other data sources include third-party IP address databases. In some embodiments, the scorecard system **200** may also analyze data in Domain Name System (DNS) records, Border Gateway Protocol (BGP) records, Secure Socket Layer (SSL) certificates, security scanners, such as Nmap, content delivery network (CDN) databases, and known security IP addresses, such as honeypots and sinkholes owned by security companies. From analysis of data collected from the data sources, the scorecard system can identify the IP addresses pointed to by the different variations of the entity's domain name.

At block **308**, method **300** includes assigning, by the processor, a weight to each of the identified one or more IP addresses. For example, scorecard system **200** can implement

IP weighting module **219D** to weigh the identified IP addresses. In some embodiments, weighting may be based on a correlation between each of the identified one or more IP addresses and the one or more variations of the at least one domain name. In one embodiment, a good correlation may consist of an IP address that is pointed to by multiple variations of the domain name data. In other words, weighting may include assigning a larger weight to an IP address of the identified one or more IP addresses that maps to multiple of the one or more variations of the at least one domain name than the weight assigned to an IP address of the identified one or more IP addresses that maps to only one of the one or more variations of the at least one domain name. For example, in one embodiment, a mapping  $C_i$  may consist of a single mapping between an IP address and a domain name data variation. For multiple mappings, such as  $C_1, C_2, \dots, C_n$ , the number of times an IP address maps to a different variation of the domain name data may be tracked. Based on the number of times an IP address maps to a different variation of the domain name data for an entity, a weight between 0 and 1 can be assigned to the IP address. A higher weight may be assigned to IP addresses pointed to multiple times than IP addresses pointed to once.

Weighting with weighting module **219D** may also include weighting based on the reliability of the domain name variation determined for an entity. For example, if the scorecard system **200** had to perform truncation or appending to obtain the domain name variation or if the domain name variation is mentioned only once in only a single data source, then the scorecard system **200** may assign a lower weight to the IP address pointed to by the domain name variation. In other words, a good indication that an IP address is associated with an entity is that multiple variations for the entity's domain name point to the same IP address. In contrast, if the domain name pointing to an IP address is mentioned in numerous databases in association with the company or if the domain name variation is one specifically provided by an employee of the company, then the scorecard system **200** may assign a larger weight to the IP address. In another embodiment, weighing with weighting module **219D** may also include weighting based on the specific type of entity network with which the collected IP addresses are associated. For example, an IP address associated with a guest network or WiFi network of the entity may be assigned a lower weight than an IP address associated with an intranet network of the entity.

The scorecard system **200** may also include a machine learning algorithm to perform the weighting disclosed herein. For example, the scorecard system **200** may utilize a machine learning algorithm to, in addition to implement the other weighting routines disclosed above, analyze anonymized fingerprints of browsers when analyzing IP addresses obtained from online advertisements or e-mails. One of skill in the art would readily recognize that the machine learning algorithm is not limited to implementing only the weighting factors disclosed herein, and that many other factors may be incorporated into the machine learning algorithm so long as the machine learning algorithm utilizes the factors to weight the IP addresses association with domain name variations of an entity.

At block **310**, method **300** includes creating a mapping of IP addresses to associate with the entity based on analysis of the weighted one or more IP addresses. For example, scorecard system **200** can implement IP mapping creation module **219E** to create the mapping. In particular, the scorecard system **200** may create the IP mapping by selecting only the IP addresses that are most reliably associated with the entity for inclusion into the IP mapping. For example, in one embodi-

ment, the scorecard system **200** may set a minimum weight threshold for IP addresses to be included in the created IP mapping. IP addresses with weights higher than then minimum threshold, for example IP addresses pointed to by domain name variations mentioned in numerous databases in association with the company or specifically provided by an employee of the company, may be included in the created IP mapping. IP addresses with weights below the minimum threshold, for example IP addresses pointed to by unreliable domain name variations, may be excluded from inclusion in the created IP mapping. In some embodiments, the created mapping of IP addresses may be adjusted or maintained up-to-date by periodically executing the reception **219A**, domain name variations **219B**, IP address collection **219C**, weighting **219D**, and IP mapping creation **219E** modules as disclosed herein.

The IP mapping for an entity, such as the IP mapping created at block **310** using IP mapping creation module **219E**, may be adjusted for a variety of reasons. For example, in one embodiment, a representative of an entity may provide specific IP addresses for inclusion in the IP mapping for the entity or the representative of the entity may specify which IP addresses in the created IP mapping should not be included in the IP mapping. In other words, the scorecard system **200** adjusts the created mapping of IP addresses based on user input. In some embodiments, the representative may input the IP addresses to include or exclude by accessing the scorecard system **200** via user station **160**. The scorecard system may then modify the IP mapping based on the information provided by the entity representative. In some embodiments, the scorecard system **200** may also exclude from the IP mapping IP addresses associated with networks other than the entity network, such as a Wi-Fi, third-party hosting, guest, or security network. The scorecard system **200** may associate IP addresses with the other networks based on user input provided on user station **160**. The scorecard system may also associate IP addresses to the other networks based on the weighting performed by weighting module **219D**. For example, the machine learning algorithm utilized during weighting may have identified networks not associated with the entity and weighted the IP addresses associated with such networks lower than other IP addresses. As another example, the machine learning algorithm may have detected IP addresses not having access to data internal to the entity and assigned lower weights to those IP addresses.

The scorecard system **200** may also determine the IP addresses to be excluded from the IP mapping during creation of an IP mapping without user input. For example, in one embodiment, IP addresses associated with security providers, such as CloudFlare and Akamai, may be excluded from the created IP mapping because they are associated with the security provider and not the entity. To identify IP addresses associated with security providers and IP addresses behind the security provider that are associated with an entity, the scorecard system **200** may utilize IP address collection module **219C** to collect IP address information from unusual data sources. For example, the scorecard system **200** may collect IP address information from alternative domain data sources which may not be configured properly. As another example, the scorecard system **200** may collect and analyze data transmission headers associated with the security providers. In yet another example, the scorecard system **200** may read IP addresses from TCP port **80**. In another embodiment, the scorecard system **200** may collect the IP address information directly from the security provider.

The scorecard system **200** may also determine IP addresses to be excluded from the created IP mapping by determining

11

whether the collected IP addresses are associated with a WiFi or guest network provided by the entity. In some embodiments, the entity may provide the scorecard system **200** with the WiFi or guest networks provided by the entity. In other embodiments, the scorecard system may determine the networks during execution of the IP address collection module **219C** by collecting data for data sources that specify WiFi and guest networks available by the entity. The scorecard system **200** may also perform an Nmap banner grab during IP address collection to identify whether the IP address is associated with a guest network of the entity.

The IP mapping created with IP mapping creation module **219E** may be associated with a subnetwork of an entity's network because some entities, such as network hosting entities, may have multiple networks. In one embodiment, the desired IP addresses to be associated with the entity may be only those IP addresses associated with the entity's network. In another embodiment, the desired IP addresses to be associated with the entity may be the IP addresses that are hosted for other entities. The scorecard system **200** may create the different IP mappings based on a variety of factors. For example, the scorecard system **200** may be provided with information by the entity which specifies which collected IP addresses should be associated with the entity's network and which IP addresses should be associated with the entity's hosting network. In another embodiment, the scorecard system **200** may look at whether a collected IP address is associated with a hosted virtual machine to determine in which IP mapping the IP address should be placed. In other embodiments, the scorecard system **200** may use the machine learning algorithm utilized while executing weighting module **219D** to identify factors that may indicate that an IP address is associated with a hosted IP address as opposed to an IP address of the network. The machine learning algorithm may develop the factors and incorporate them into the algorithm to further weigh the IP addresses.

The schematic flow chart diagram of FIG. **3** is generally set forth as a logical flow chart diagram. As such, the depicted order and labeled steps are indicative of aspects of the disclosed method. Other steps and methods can be conceived that are equivalent in function, logic, or effect to one or more steps, or portions thereof, of the illustrated method. Additionally, the format and symbols employed are provided to explain the logical steps of the method and are understood not to limit the scope of the method. Although various arrow types and line types can be employed in the flow chart diagram, they are understood not to limit the scope of the corresponding method. Indeed, some arrows or other connectors can be used to indicate only the logical flow of the method. For instance, an arrow may indicate a waiting or monitoring period of unspecified duration between enumerated steps of the depicted method. Additionally, the order in which a particular method occurs may or may not strictly adhere to the order of the corresponding steps shown.

FIG. **4** is a flow diagram illustrating IP mapping implemented by scorecard system **200** according to an embodiment of the disclosure. It is noted that embodiments of flow **400** can be implemented with the systems described with respect to FIGS. **1-2**, in particular the underlying components illustrated in FIG. **2B**. For example, a processor disclosed in flow **400** may correspond to a processor within a scorecard server disclosed in this disclosure. Referring to flow **400**, at block **402**, scorecard system **200** receives a new domain associated with an entity. For example, scorecard system **200** can implement reception module **219A** to receive a URL associated with an entity.

12

At blocks **404a-404c**, flow **400** includes queries **404a-404c** of data feeds to determine the different variations of the received domain name and to identify the IP addresses pointed to by the domain name data in the data feeds. Data feeds may correspond to one or more data sources, such as one or more of data sources **150** illustrated in FIG. **1**. In some embodiments, to implement queries **404a-404c**, scorecard system **200** can implement domain name variations module **219B** and/or IP address collection module **219C**. In some embodiments, scorecard system **200** may implement at least one of queries **404a-404c** by collecting data from one or more data sources and then implementing together the functions of domain name variations module **219B** and IP address collection module **219C** described above. In another embodiment, scorecard system **200** may implement at least one of queries **404a-404c** by implementing domain variations module **219B** before implementing IP collection module **219C**. In yet another embodiment, scorecard system **200** may implement at least one of queries **404a-404c** by implementing IP collection module **219C** before implementing domain name variations module **219B**.

After performing queries **404a-404c**, scorecard system **200** may perform further analysis of the identified IP addresses to create an IP mapping for the entity. For example, in one embodiment, scorecard system **200** may implement weighting module **219D** to weigh the identified IP addresses and IP mapping creation module **219E** to create the IP mapping based at least on the weighting of the IP addresses. Based on the further analysis performed by implementing the functions of weighting module **219D** and IP mapping creation module **219E**, scorecard system **200** may create the IP mapping for an entity. For example, in one embodiment, the results of the further analysis may identify which IP addresses can be reliably included in the IP mapping for the entity and which IP addresses require additional analysis to determine whether the IP addresses should be included in the IP mapping for the entity or excluded from the IP mapping for the entity.

As noted with respect to FIG. **3**, the scorecard system **200** may identify which IP addresses are most reliably associated with the entity based on a weight threshold. For example, in one embodiment, the scorecard system **200** may set a minimum weight threshold for IP addresses to be included in the created IP mapping. IP addresses with weights higher than the minimum threshold, for example IP addresses pointed to by domain name variations mentioned in numerous databases in association with the company or specifically provided by an employee of the company, may be indicated as reliably associated with the entity. In addition, IP addresses found in the majority of data feeds/sources may also be identified as reliably associated with the entity. In contrast, IP addresses with weights below the minimum threshold, for example IP addresses pointed to by unreliable domain name variations, may be indicated as not reliably associated with the entity. In addition, IP addresses not found in the majority of data feeds/sources may be indicated as not reliably associated with the entity.

As indicated in flow **400**, IP addresses indicated as reliably associated with the entity may be grouped together, for example in bucket one **406**. IP addresses in bucket one **406** may be automatically included in the entity's initial IP mapping **410**. In contrast, the IP addresses indicated as not initially being associated with the entity may be grouped together in a separate group, for example in bucket two **408**, to undergo further processing, as indicated in further processing block **412** in flow **400**.

In some embodiments, further processing **412** performed on IP addresses grouped into bucket two **408** may include implementation of various aspects of IP address collection module **219C**, weighting module **219D**, and IP mapping creation module **219E**, as described in blocks **306**, **308**, and **310** of method **300**, respectively. For example, further processing **412** may include implementing IP collection module **219C** to collect IP specific information from IP specific data sources, such as ARIN, RIPE, LACNIC, AFRINIC, and APNIC. In addition, further processing may include analyzing data in DNS records, such as performing reverse DNS automation, and analyzing data in BGP records, SSL certificates, security scanners, such as Nmap, CDN databases, and known security IP addresses, such as honeypots and sinkholes owned by security companies.

Scorecard system **200** may identify further IP addresses to include in the initial IP mapping **410** based on the further processing **412** performed on the IP addresses in bucket two **408**. For example, scorecard system **200** may identify IP addresses matching perfectly to an IP address associated with the entity as indicated by the IP addresses collected for the entity during the performance of further processing **412**. As an example, scorecard system **200** may group together the IP addresses matching perfectly into bucket three **414** and include the IP addresses in the initial IP mapping **410**.

In other embodiments, those IP addresses that were not identified during further processing **412** as matching perfectly to an IP address known to be associated with the entity based on the IP addresses collected using IP address collection module **219C** may undergo additional processing, such as at processing block **416**. The processing performed on IP addresses at block **416** may include implementation of various aspects of IP address collection module **219C**, weighting module **219D**, and IP mapping creation module **219E**, as described in blocks **306**, **308**, and **310** of method **300**, respectively. For example, the processing at block **416** may include implementation of machine learning, such as the machine learning processing disclosed in the discussion regarding weighting module **219D** and block **308**.

In some embodiments, the IP addresses placed in the initial mapping **410** may be verified as being associated with the entity through analysis of information provided for the entity on data sources, such as Freebase databases **418** and social media websites, for example LinkedIn **420**. In some embodiments, the initial IP mapping **410**, either before or after the optional aforementioned verification processing, may be identified as the final IP mapping created for an entity, such as the final IP mapping created for an entity at block **310** of FIG. **3**.

If implemented in firmware and/or software, the functions described above can be stored as one or more instructions or code on a computer-readable medium. Examples include non-transitory computer-readable media encoded with a data structure and computer-readable media encoded with a computer program. Computer-readable media includes physical computer storage media. A storage medium can be any available medium that can be accessed by a computer. By way of example, and not limitation, such computer-readable media can comprise RAM, ROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium that can be used to store desired program code in the form of instructions or data structures and that can be accessed by a computer. Disk and disc includes compact discs (CD), laser discs, optical discs, digital versatile discs (DVD), floppy disks and blu-ray discs. Generally, disks reproduce data magnetically, and discs

reproduce data optically. Combinations of the above should also be included within the scope of computer-readable media.

In addition to storage on computer-readable medium, instructions and/or data can be provided as signals on transmission media included in a communication apparatus. For example, a communication apparatus includes a transceiver having signals indicative of instructions and data. The instructions and data can be configured to cause one or more processors to implement the functions outlined in the claims.

Although the present disclosure and its advantages have been described in detail, it should be understood that various changes, substitutions and alterations can be made herein without departing from the spirit and scope of the disclosure as defined by the appended claims. Moreover, the scope of the present application is not intended to be limited to the particular embodiments of the process, machine, manufacture, composition of matter, means, methods and steps described in the specification. As one of ordinary skill in the art will readily appreciate from the present invention, disclosure, machines, manufacture, compositions of matter, means, methods, or steps, presently existing or later to be developed that perform substantially the same function or achieve substantially the same result as the corresponding embodiments described herein can be utilized according to the present disclosure. Accordingly, the appended claims are intended to include within their scope such processes, machines, manufacture, compositions of matter, means, methods, or steps.

What is claimed is:

**1.** A method for mapping Internet Protocol (IP) addresses to an entity, the method comprising:

determining, by a processor operating at a node in a network, one or more variations of at least one domain name based on analysis of domain name data collected from a plurality of domain name data sources over the network that mention a variation of the at least one domain name;

identifying, by the processor, one or more IP addresses pointed to by the one or more variations of the entity's at least one domain name based on analysis of IP address data collected from a plurality of IP address data sources; and

assigning, by the processor, a weight to each of the identified one or more IP addresses based on a correlation between each of the identified one or more IP addresses and the one or more variations of the at least one domain name; wherein assigning a weight comprises:

assigning a first weight to an IP address of the identified one or more IP addresses that maps to multiple of the one or more variations of the at least one domain name and

assigning a second weight to an IP address of the identified one or more IP addresses that maps to only one of the one or more variations of the at least one domain name;

where the first weight is greater than the second weight.

**2.** The method of claim **1**, wherein identifying one or more IP addresses comprises collecting one or more IP addresses that map to the one or more variations of the at least one domain name.

**3.** The method of claim **1**, further comprising: mapping IP addresses to the entity based on analysis of the first weighted one or more IP addresses and the second weighted or more IP addresses.

**4.** The method of claim **3**, further comprising adjusting the created mapping of IP addresses based on user input.

## 15

5. The method of claim 3, further comprising adjusting or maintaining up-to-date the created mapping of IP addresses by periodically performing the foregoing steps of receiving, determining, identifying, assigning, and creating.

6. The method of claim 1, further comprising:

associating IP addresses with one or more networks that do not include the entity based on a detection of IP addresses not having access to data internal to the entity.

7. The method of claim 6, wherein the networks other than the entity comprise at least one of a Wi-Fi, third-party hosting, guest, or security network.

8. A computer program product, comprising:

a non-transitory computer-readable medium comprising instructions which, when executed by a processor of a computing system, cause the processor to perform the steps of:

determining one or more variations of at least one domain name based on analysis of domain name data collected from a plurality of domain name data sources that mention a variation of the at least one domain name;

identifying one or more IP addresses pointed to by the one or more variations of the at least one domain name based on analysis of IP address data collected from a plurality of IP address data sources; and

assigning a weight to each of the identified one or more IP addresses based on a correlation between each of the identified one or more IP addresses and the one or more variations of the at least one domain name, wherein assigning a weight comprises:

assigning a first weight to an IP address of the identified one or more IP addresses that maps to multiple of the one or more variations of the at least one domain name, and

assigning a second weight to an IP address of the identified one or more IP addresses that maps to only one of the one or more variations of the at least one domain name;

where the first weight is greater than the second weight.

9. The computer program product of claim 8, wherein identifying one or more IP addresses comprises collecting one or more IP addresses that map to the one or more variations of the at least one domain name.

10. The computer program product of claim 8, wherein the medium further comprises instructions to cause the processor further perform:

mapping IP addresses to the entity based on analysis of the first weighted one or more IP addresses and the second weighted one or more IP addresses.

11. The computer program product of claim 8, wherein the medium further comprises instructions to cause the processor to perform:

adjusting the created mapping of IP addresses based on user input.

12. The computer program product of claim 8, wherein the medium further comprises instructions to cause the processor to perform:

adjusting or maintaining up-to-date the created mapping of IP addresses by periodically performing the foregoing steps of receiving, determining, identifying, assigning, and creating.

## 16

13. The computer program product of claim 10, wherein the medium further comprises instructions to cause the processor to perform: associating IP addresses with one or more networks that do not include the entity based on a detection of IP addresses not having access to data internal to the entity.

14. The computer program product of claim 8, wherein the networks other than the entity comprise at least one of a Wi-Fi, third-party hosting, guest, or security network.

15. An apparatus, comprising:

a memory; and

a processor coupled to the memory, the processor configured to execute the steps of:

determining one or more variations of the at least one domain name based on analysis of domain name data collected from a plurality of domain name data sources that mention a variation of the at least one domain name;

identifying one or more IP addresses pointed to by the one or more variations of the entity's domain name based on analysis of IP address data collected from a plurality of IP address data sources; and

assigning a weight to each of the identified one or more IP addresses based on a correlation between each of the identified one or more IP addresses and the one or more variations of the at least one domain name, wherein assigning a weight comprises:

assigning a first weight to an IP address of the identified one or more IP addresses that maps to multiple of the one or more variations of the at least one domain name, and

assigning a second weight to an IP address of the identified one or more IP addresses that maps to only one of the one or more variations of the at least one domain name;

where the first weight is greater than the second weight.

16. The apparatus of claim 15, wherein identifying one or more IP addresses comprises collecting one or more IP addresses that map to the one or more variations of the at least one domain name.

17. The apparatus of claim 15, wherein the processor is further configured to:

map IP addresses to the entity based on analysis of the first weighted one or more IP addresses and the second weighted one or more IP addresses.

18. The apparatus of claim 15, wherein the processor is further configured to:

adjust the created mapping of IP addresses based on user input.

19. The apparatus of claim 15, wherein the processor is further configured to:

adjust or maintain the created mapping of IP addresses by periodically performing the foregoing steps of receiving, determining, identifying, assigning, and creating.

20. The apparatus of claim 15, wherein the processor is further configured to:

associate IP addresses with one or more networks that do not include the entity based on a detection of IP addresses not having access to data internal to the entity, wherein the one or more networks comprise at least one of a Wi-Fi, third-party hosting, guest, or security network.

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 9,372,994 B1  
APPLICATION NO. : 14/702668  
DATED : June 21, 2016  
INVENTOR(S) : Aleksandr Yampolskiy et al.

Page 1 of 2

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims:

At column 14, claim number 1, line number 51, add --,-- after “name”.

At column 14, claim number 4, line number 67, delete “created”.

At column 15, claim number 5, line number 2, delete “created”.

At column 15, claim number 5, line number 4, delete “identifying, assigning, and creating.” and replace with --identifying, and assigning.--.

At column 15, claim number 10, line number 46, insert --non-transitory computer-readable-- before “medium”.

At column 15, claim number 10, line number 48, delete “the entity” and replace with --an entity--.

At column 15, claim number 11, line number 52, insert --non-transitory computer-readable-- before “medium”.

At column 15, claim number 11, line number 54, delete “created”.

At column 15, claim number 12, line number 57, insert --non-transitory computer-readable-- before “medium”.

At column 15, claim number 12, line number 59, delete “created”.

At column 15, claim number 12, line number 61, delete “identifying, assigning, and creating.” and replace with --identifying, and assigning.--.

At column 16, claim number 13, line number 2, insert --non-transitory computer-readable-- before “medium”.

At column 16, claim number 15, line number 13, delete “the”.

At column 16, claim number 15, line number 19, delete “entity’s” and replace with --at least one--.

At column 16, claim number 15, line number 13, delete “the”.

At column 16, claim number 15, line number 19, delete “entity’s” and replace with --at least one--.

At column 16, claim number 17, line number 41, delete “the entity” and replace with --an entity--.

Signed and Sealed this  
Twenty-seventh Day of September, 2016



Michelle K. Lee  
Director of the United States Patent and Trademark Office



**CERTIFICATE OF CORRECTION (continued)**

**U.S. Pat. No. 9,372,994 B1**

At column 16, claim number 18, line number 46, delete “created”.

At column 16, claim number 19, line number 50, delete “created”.

At column 16, claim number 19, line number 52, delete “identifying, assigning, and creating.” and replace with --identifying, and assigning.--.