



US009386348B2

(12) **United States Patent**
Robbins et al.

(10) **Patent No.:** **US 9,386,348 B2**
(45) **Date of Patent:** ***Jul. 5, 2016**

(54) **SHARING BEHAVIORAL PATTERNS
BETWEEN DEVICES**

(71) Applicant: **AT&T INTELLECTUAL PROPERTY
I, LP, Atlanta, GA (US)**

(72) Inventors: **William Stanley Robbins, Sun Prairie,
WI (US); R. Tyler Wallis, Greenwood
Village, CO (US); Anup D Karnalkar,
Allen, TX (US); Mark Ryan, Norcross,
GA (US)**

(73) Assignee: **AT&T INTELLECTUAL PROPERTY
I, LP, Atlanta, GA (US)**

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **14/817,712**

(22) Filed: **Aug. 4, 2015**

(65) **Prior Publication Data**

US 2015/0341688 A1 Nov. 26, 2015

Related U.S. Application Data

(63) Continuation of application No. 14/486,196, filed on
Sep. 15, 2014, now Pat. No. 9,137,571, which is a
continuation of application No. 12/339,381, filed on
Dec. 19, 2008, now Pat. No. 8,869,184.

(51) **Int. Cl.**

H04N 21/25 (2011.01)
H04N 21/258 (2011.01)
H04N 21/442 (2011.01)
G06N 5/04 (2006.01)
H04N 21/482 (2011.01)
H04N 7/16 (2011.01)
H04N 21/433 (2011.01)
H04N 21/436 (2011.01)

H04N 21/47 (2011.01)

H04N 21/472 (2011.01)

H04N 21/478 (2011.01)

H04L 29/08 (2006.01)

H04N 21/488 (2011.01)

(52) **U.S. Cl.**

CPC **H04N 21/44222** (2013.01); **G06N 5/047**
(2013.01); **H04L 67/10** (2013.01); **H04N 7/163**
(2013.01); **H04N 21/4334** (2013.01); **H04N**
21/43615 (2013.01); **H04N 21/44204**
(2013.01); **H04N 21/44218** (2013.01); **H04N**
21/47 (2013.01); **H04N 21/478** (2013.01);
H04N 21/47214 (2013.01); **H04N 21/488**
(2013.01); **H04N 21/4826** (2013.01); **H04N**
21/4828 (2013.01)

(58) **Field of Classification Search**

None

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,039,699 B1 5/2006 Narin

7,882,522 B2 2/2011 Neufeld et al.

(Continued)

Primary Examiner — Brian T Pendelton


Assistant Examiner — Jean D Saint Cyr

(74) *Attorney, Agent, or Firm* — Guntin & Gust, PLC; Atanu
Das

(57) **ABSTRACT**

A system that incorporates teachings of the present disclosure
may include, for example, a set-top box having a controller to
present media content at a presentation device as directed by
a user, monitor the media content consumed by the user,
detect a first behavioral pattern based on the media content
consumed by the user, transmit the detected first behavioral
pattern to a communication device of the user, receive from
the communication device a second behavioral pattern, and
identify media content correlating to the second behavioral
pattern. The communication device can be adapted to adjust
communication operations according to the detected first
behavioral pattern. Other embodiments are disclosed.

20 Claims, 7 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2002/0198786 A1 12/2002 Tripp et al.

2005/0028207 A1 * 2/2005 Finseth H04N 7/17318
725/46

2006/0075420 A1 4/2006 Ludvig et al.


2007/0111726 A1 * 5/2007 Lambert H04M 1/72563
455/432.1


2009/0133090 A1 * 5/2009 Busse H04N 7/163
725/132

2009/0276801 A1 11/2009 Reece


* cited by examiner

100
FIG. 1







200
FIG. 2





300
FIG. 3



400
FIG. 4







700
FIG. 7




FIG. 8 800

1

SHARING BEHAVIORAL PATTERNS
BETWEEN DEVICESCROSS-REFERENCE TO RELATED
APPLICATION(S)

This application is a continuation of and claims priority to U.S. patent application Ser. No. 14/486,196 filed Sep. 15, 2014, which is a continuation of and claims priority to U.S. patent application Ser. No. 12/339,381 filed Dec. 19, 2008 (now U.S. Pat. No. 8,869,184), the disclosures of which are hereby incorporated by reference in their entirety.

FIELD OF THE DISCLOSURE

The present disclosure relates generally to behavior detection techniques and more specifically to sharing behavioral patterns between devices.

BACKGROUND

There are many types of media devices today such as for example MP3 players, set-top boxes, DVD players, DVR recorders, CD players, and so on. Similarly, there are many types of communication devices available today such as for example landline phones, mobile phones, computers, and so on. It is common for users to program some or all of these devices with operational preferences to provide the user a desirable experience.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1-2 depict illustrative embodiments of communication systems that provide media services;

FIG. 3 depicts an illustrative embodiment of a portal interacting with the communication systems of FIGS. 1-2;

FIG. 4 depicts an illustrative embodiment of a communication device utilized in the communication systems of FIGS. 1-2;

FIG. 5 depicts an illustrative embodiment of a method according to the present disclosure;

FIGS. 6-7 depict illustrative embodiments of the method of FIG. 5; and

FIG. 8 is a diagrammatic representation of a machine in the form of a computer system within which a set of instructions, when executed, may cause the machine to perform any one or more of the methodologies discussed herein.

DETAILED DESCRIPTION

One embodiment of the present disclosure can entail a set-top box having a controller to present media content at a presentation device as directed by a user, monitor the media content consumed by the user, detect a first behavioral pattern based on the media content consumed by the user, transmit the detected first behavioral pattern to a communication device of the user, receive from the communication device a second behavioral pattern, and identify media content correlating to the second behavioral pattern. The communication device can be adapted to adjust communication operations according to the detected first behavioral pattern.

Another embodiment of the present disclosure can entail a computer-readable storage medium having computer instructions to monitor media content consumed by a user, detect a behavioral pattern based on the media content consumed by

2

the user, and transmit the detected behavioral pattern to a communication device of the user operating independently of the storage medium.

Yet another embodiment of the present disclosure can entail a communication device having a controller to monitor communication activities of a user, detect a behavioral pattern from the monitored communication activities of the user, and transmit the detected behavioral pattern to a media processor. The media processor can be adapted to identify media content correlating to the behavioral pattern.

FIG. 1 depicts an illustrative embodiment of a first communication system **100** for delivering media content. The communication system **100** can represent an Internet Protocol Television (IPTV) broadcast media system. The IPTV media system can include a super head-end office (SHO) **110** with at least one super headend office server (SHS) **111** which receives media content from satellite and/or terrestrial communication systems. In the present context, media content can represent audio content, moving image content such as videos, still image content, or combinations thereof. The SHS server **111** can forward packets associated with the media content to video head-end servers (VHS) **114** via a network of video head-end offices (VHO) **112** according to a common multicast communication protocol.

The VHS **114** can distribute multimedia broadcast programs via an access network **118** to commercial and/or residential buildings **102** housing a gateway **104** (such as a common residential or commercial gateway). The access network **118** can represent a group of digital subscriber line access multiplexers (DSLAMs) located in a central office or a service area interface that provide broadband services over optical links or copper twisted pairs to buildings **102**. The gateway **104** can use common communication technology to distribute broadcast signals to media processors **106** such as Set-Top Boxes (STBs) which in turn present broadcast channels to media devices **108** such as computers or television sets managed in some instances by a media controller **107** (such as an infrared or RF remote control).

The gateway **104**, the media processors **106**, and media devices **108** can utilize tethered interface technologies (such as coaxial or phone line wiring) or can operate over a common wireless access protocol. With these interfaces, unicast communications can be invoked between the media processors **106** and subsystems of the IPTV media system for services such as video-on-demand (VoD), browsing an electronic programming guide (EPG), or other infrastructure services.

Some of the network elements of the IPTV media system can be coupled to one or more computing devices **130** a portion of which can operate as a web server for providing portal services over an Internet Service Provider (ISP) network **132** to wireline media devices **108** or wireless communication devices **116** by way of a wireless access base station **117** operating according to common wireless access protocols such as Wireless Fidelity (WiFi), or cellular communication technologies (such as GSM, CDMA, UMTS, WiMAX, Software Defined Radio or SDR, and so on).

It will be appreciated by an artisan of ordinary skill in the art that a satellite broadcast television system can be used in place of the IPTV media system. In this embodiment, signals transmitted by a satellite **115** supplying media content can be intercepted by a common satellite dish receiver **131** coupled to the building **102**. Modulated signals intercepted by the satellite dish receiver **131** can be submitted to the media processors **106** for generating broadcast channels which can be presented at the media devices **108**. The media processors

3

106 can be equipped with a broadband port to the ISP network **132** to enable infrastructure services such as VoD and EPG described above.

In yet another embodiment, an analog or digital broadcast distribution system such as cable TV system **133** can be used in place of the IPTV media system described above. In this embodiment the cable TV system **133** can provide Internet, telephony, and interactive media services.

It follows from the above illustrations that the present disclosure can apply to any present or future interactive over-the-air or landline media content services.

FIG. 2 depicts an illustrative embodiment of a communication system **200**, employing an IP Multimedia Subsystem (IMS) network architecture to facilitate the combined services of circuit-switched and packet-switched systems. Communication system **200** can be overlaid or operably coupled with communication system **100** as another representative embodiment of communication system **100**.

Communication system **200** can comprise a Home Subscriber Server (HSS) **240**, a tElephone NUmber Mapping (ENUM) server **230**, and other common network elements of an IMS network **250**. The IMS network **250** can establish communications between IMS compliant communication devices (CD) **201**, **202**, Public Switched Telephone Network (PSTN) CDs **203**, **205**, and combinations thereof by way of a Media Gateway Control Function (MGCF) **220** coupled to a PSTN network **260**.

IMS CDs **201**, **202** can register with the IMS network **250** by contacting a Proxy Call Session Control Function (P-CSCF) which communicates with a corresponding Serving CSCF (S-CSCF) to register the CDs with at the HSS **240**. To initiate a communication session between CDs, an originating IMS CD **201** can submit a Session Initiation Protocol (SIP INVITE) message to an originating P-CSCF **204** which communicates with a corresponding originating S-CSCF **206**. The originating S-CSCF **206** can submit queries to the ENUM system **230** to translate an E.164 telephone number in the SIP INVITE to a SIP Uniform Resource Identifier (URI) if the terminating communication device is IMS compliant.

The SIP URI can be used by an Interrogating CSCF (I-CSCF) **207** to submit a query to the HSS **240** to identify a terminating S-CSCF **214** associated with a terminating IMS CD such as reference **202**. Once identified, the I-CSCF **207** can submit the SIP INVITE to the terminating S-CSCF **214**. The terminating S-CSCF **214** can then identify a terminating P-CSCF **216** associated with the terminating CD **202**. The P-CSCF **216** then signals the CD **202** to establish communications.

If the terminating communication device is instead a PSTN CD such as references **203** or **205**, the ENUM system **230** can respond with an unsuccessful address resolution which can cause the originating S-CSCF **206** to forward the call to the MGCF **220** via a Breakout Gateway Control Function (BGCF) **219**. The MGCF **220** can then initiate the call to the terminating PSTN CD by common means over the PSTN network **260**.

The aforementioned communication process is symmetrical. Accordingly, the terms "originating" and "terminating" in FIG. 2 are interchangeable. It is further noted that communication system **200** can be adapted to support video conferencing by way of common protocols such as H.323. In addition, communication system **200** can be adapted to provide the IMS CDs **201**, **203** the multimedia and Internet services of communication system **100**.

FIG. 3 depicts an illustrative embodiment of a portal **302** which can operate from the computing devices **130** described earlier of communication **100** illustrated in FIG. 1. The portal

4

302 can be used for managing services of communication systems **100-200**. The portal **302** can be accessed by a Uniform Resource Locator (URL) with a common Internet browser such as Microsoft's Internet Explorer™ using an Internet-capable communication device such as those described for FIGS. 1-2. The portal **302** can be configured, for example, to access a media processor **106** and services managed thereby such as a Digital Video Recorder (DVR), a VoD catalog, an EPG, a personal catalog (such as personal videos, pictures, audio recordings, etc.) stored in the media processor, provisioning IMS services described earlier, provisioning Internet services, provisioning cellular phone services, and so on.

FIG. 4 depicts an exemplary embodiment of a communication device **400**. Communication **400** can serve in whole or in part as an illustrative embodiment of the communication devices of FIGS. 1-2. The communication device **400** can comprise a wireline and/or wireless transceiver **402** (herein transceiver **402**), a user interface (UI) **404**, a power supply **414**, a location receiver **416**, and a controller **406** for managing operations thereof. The transceiver **402** can support short-range or long-range wireless access technologies such as Bluetooth, WiFi, Digital Enhanced Cordless Telecommunications (DECT), or cellular communication technologies, just to mention a few. Cellular technologies can include, for example, CDMA-1X, UMTS/HSDPA, GSM/GPRS, TDMA/EDGE, EV/DO, WiMAX, SDR, and next generation cellular wireless communication technologies as they arise. The transceiver **402** can also be adapted to support circuit-switched wireline access technologies (such as PSTN), packet-switched wireline access technologies (such as TCP/IP, VoIP, etc.), and combinations thereof.

The UI **404** can include a depressible or touch-sensitive keypad **408** with a navigation mechanism such as a roller ball, joystick, mouse, or navigation disk for manipulating operations of the communication device **400**. The keypad **408** can be an integral part of a housing assembly of the communication device **400** or an independent device operably coupled thereto by a tethered wireline interface (such as a USB cable) or a wireless interface supporting for example Bluetooth. The keypad **408** can represent a numeric dialing keypad commonly used by phones, and/or a Qwerty keypad with alphanumeric keys. The UI **404** can further include a display **410** such as monochrome or color LCD (Liquid Crystal Display), OLED (Organic Light Emitting Diode) or other suitable display technology for conveying images to an end user of the communication device **400**. In an embodiment where the display **410** is touch-sensitive, a portion or all of the keypad **408** can be presented by way of the display.

The UI **404** can also include an audio system **412** that utilizes common audio technology for conveying low volume audio (such as audio heard only in the proximity of a human ear) and high volume audio (such as speakerphone for hands free operation). The audio system **412** can further include a microphone for receiving audible signals of an end user. The audio system **412** can also be used for voice recognition applications. The UI **404** can further include an image sensor **413** such as a charged coupled device (CCD) camera for capturing still or moving images.

The power supply **414** can utilize common power management technologies such as replaceable and rechargeable batteries, supply regulation technologies, and charging system technologies for supplying energy to the components of the communication device **400** to facilitate long-range or short-range portable applications. The location receiver **416** can utilize common location technology such as a global positioning system (GPS) receiver for identifying a location of the

5

communication device **100** based on signals generated by a constellation of GPS satellites, thereby facilitating common location services such as navigation.

The communication device **100** can use the transceiver **402** to also determine a proximity to a cellular, WiFi or Bluetooth access point by common power sensing techniques such as utilizing a received signal strength indicator (RSSI) and/or a signal time of arrival (TOA) or time of flight (TOF). The controller **406** can utilize computing technologies such as a microprocessor, a digital signal processor (DSP), and/or a video processor with associated storage memory such as a Flash, ROM, RAM, SRAM, DRAM or other storage technologies.

The communication device **400** can be adapted to perform the functions of the media processor **106**, the media devices **108**, or the portable communication devices **116** of FIG. 1, as well as the IMS CDs **201-202** and PSTN CDs **203-205** of FIG. 2. It will be appreciated that the communication device **400** can also represent other common devices that can operate in communication systems **100-200** of FIGS. 1-2 such as a gaming console and a media player.

FIG. 5 depicts an illustrative a method **500** operating in portions of the aforementioned communication systems. FIG. 6 shows an illustrative embodiment of communication devices operating according to method **500**. Block diagram **600** comprises a landline communication device **602** in the form of a tablet with a touch-sensitive display (herein referred to as tablet **602**). The tablet **602** can include communication technology to support both DECT and WiFi protocols. The tablet **602** can be communicatively coupled to a base unit **606** by way of DECT and WiFi air interfaces. A plurality of cordless handsets **604** can also be communicatively coupled to the base unit **606** using the DECT protocol.

The base unit **606** can include communication technology for communicatively interfacing to a PSTN, VoIP or IMS network such as those described earlier. The base unit **606** can be coupled to an Internet/router modem **608** for communicatively interfacing to the ISP network **132**. The base unit **606** can provide the cordless handsets voice communication services, and the tablet **602** a combination of voice and data communication services. The tablet **602** and cordless handsets **604** can be equipped with common camera sensors **610** (such as CCD sensors) which can enable these devices to support video communication services and capture still images or pictures. The tablet **602** can also be communicatively coupled to the STB **106** by way of the base unit **606** using a WiFi air interface.

With the configuration of FIG. 6 in mind, method **500** can begin with step **502** in which a media processor such as the STB **106** of FIG. 1 is directed by a user by common means (e.g., controller **107**) to present media content on a media presentation device such as a television. Media content in the present context can represent audio content, still or moving image content or both. In step **504**, the STB **106** can be programmed to monitor the media content consumed by the user. The STB **106** can detect from the monitored consumed media content in step **506** a behavioral pattern of the user. The behavioral pattern can identify among other things media content of interest to the user, broadcast channels of interest to the user, and a temporal profile of the user's consumption of said content. Using common pattern recognition techniques, the STB **106** can also identify media content of interest by genre, actors, producers, directors, and so on.

For illustration purposes only, suppose a detected behavioral pattern of the user indicates that the user has an interest in college football, and typically selects football games on a specific broadcast channel (e.g., ESPN) which the user

6

records on a DVR for viewing in the evening. The behavioral pattern can also indicate that the user likes action movies, specific actors or actresses, or directors. The behavioral pattern can further indicate that the user has an affinity for Jazz music of specific bands and/or performers. The STB **106** can be programmed with common statistical analysis software applications which can detect patterns such as described from the user's consumption of media content.

The STB **106** can be programmed to transmit in step **508** the detected pattern to one or more communication devices of the user. A communication device in the present context can represent a landline phone, a mobile phone, or a computer. Other communication devices are contemplated by the present disclosure. For illustration purposes only, suppose the communication device in the present instance is the tablet **602** of FIG. 6. In step **510**, the tablet **602** can adjust a user interface (UI) presented thereby and/or its communication operations according to the detected behavioral pattern detected in step **506**.

Suppose for instance that the behavioral pattern indicates that the user likes a particular type of sport and team such as the NJ Devils hockey team, and likes to monitor news related to the team coach. In FIG. 7, the tablet **602** can present a UI **702** with a plurality of toolbars for engaging in communication activities that can be selected by the user by way of the touch-sensitive display of the tablet. Based on the behavioral pattern provided in step **508**, the tablet **602** can use this information to search for content related to the NJ Devils from a source such as a portal of the National Hockey League (NHL). Suppose in this illustration that the tablet **602** establishes communications with an NHL portal by way of the base unit **606** over a WiFi air interface. Further suppose that the NHL portal can provide news information about the NJ Devils (NJD) coach, a game schedule for the NJD, NJD team statistics, and NJD statistics by player.

With this information, the tablet **602** can be programmed in step **510** to adapt the UI **702** by adding a new toolbar **704** which it calls NHL with selectable buttons tailored for the user. The new toolbar **704** can have a selectable button with news about the NJD's coach, a button for the NJD game schedule, a button for the NJD team statistics, and a button for the NJD statistics by player. Selecting the toolbar **704** or any of the selectable sub-buttons can direct the tablet **602** to retrieve information from the NHL portal which can be presented to the user.

Steps **502-510** represent an embodiment where the STB **106** shares detected behavioral pattern data with the tablet **602**. Steps **512-528** represent an embodiment where the tablet **602** shares detected behavioral pattern data with the STB **106**. In step **512**, the tablet **602** can be programmed to monitor activities of the user relating to how the user utilizes the tablet. Using common pattern recognition software, the tablet **602** can detect in step **514** a behavioral pattern from the monitored activities of the user. The tablet **602** can for example detect personal preferences or settings entered by the user which can indicate certain behavioral patterns. The tablet **602** can also detect that the user often selects the Sports button in the News & Info toolbar, and searches for statistics about the NJD. The tablet **602** can also detect that the user has created a custom toolbar for accessing the NHL portal with the custom buttons shown. In this illustration, it is the user that creates the NHL toolbar **704**, not by automation as discussed in step **510**.

Behavioral patterns such as these can be transmitted in step **516** to the STB **106**. In step **518**, the STB **106** can use this information to search for media content, advertisements and/or promotions that correlate to the behavioral pattern detected by the tablet **602**. For instance, the STB **106** can search an

electronic programming guide (EPG) for NHL games and specifically for games associated with the NJDs. Suppose that the STB 106 identifies in step 520 that the NJDs are being presented on ESPN. In the same step, the STB 106 can present the user the availability of NJD games on ESPN with an option to record the games by way of an DVR integrated in or operably coupled to the STB.

If the user accepts this option in step 522, the STB 106 can proceed to step 524 where it directs the DVR to record all games relating to the NJD on ESPN (as well as other channels if found). In step 526, the STB 106 can also present the user advertisements and/or promotions identified in the search which for example may be related to the NJDs (e.g., availability of tickets to be purchased at a local hockey stadium where the NJDs will be playing, apparel promoted by the NJDs, sports magazines, and so on). In addition to these steps, the STB 106 can adjust its UI and/or profile of the user to reflected the user's interest in the NJDs. The EPG for example can be customized so that the ESPN channel highlights the NJDs schedule. In another embodiment, the STB 106 can create a customized UI that presents NJD information supplied by for example the NHL portal. In this embodiment, the NHL portal can provide the STB 106 NJD videos, reruns, and so on in HDTV which may not be possible on the tablet 602.

Upon reviewing the aforementioned embodiments, it would be evident to an artisan with ordinary skill in the art that said embodiments can be modified, reduced, or enhanced without departing from the scope and spirit of the claims described below. Method 500 can be adapted so that tablet 602 can be programmed to search for advertisements and promotions according to the behavioral pattern detected by the STB 106. In another embodiment, method 500 can be adapted so that the STB 106 shares user preferences with the tablet 602. In yet another embodiment, the tablet 602 and/or the STB 106 can adapt their operations in a multi-user environment so that the shared behavioral patterns of one user are adapted exclusively for the user and not the others who share the same device. Generally speaking, the present disclosure can be applied to any type of media device and communication device shared by the same user.

Other suitable modifications can be applied to the present disclosure without departing from the scope of the claims below. Accordingly, the reader is directed to the claims section for a fuller understanding of the breadth and scope of the present disclosure.

FIG. 8 depicts an exemplary diagrammatic representation of a machine in the form of a computer system 800 within which a set of instructions, when executed, may cause the machine to perform any one or more of the methodologies discussed above. In some embodiments, the machine operates as a standalone device. In some embodiments, the machine may be connected (e.g., using a network) to other machines. In a networked deployment, the machine may operate in the capacity of a server or a client user machine in server-client user network environment, or as a peer machine in a peer-to-peer (or distributed) network environment.

The machine may comprise a server computer, a client user computer, a personal computer (PC), a tablet PC, a laptop computer, a desktop computer, a control system, a network router, switch or bridge, or any machine capable of executing a set of instructions (sequential or otherwise) that specify actions to be taken by that machine. It will be understood that a device of the present disclosure includes broadly any electronic device that provides voice, video or data communication. Further, while a single machine is illustrated, the term "machine" shall also be taken to include any collection of

machines that individually or jointly execute a set (or multiple sets) of instructions to perform any one or more of the methodologies discussed herein.

The computer system 800 may include a processor 802 (e.g., a central processing unit (CPU), a graphics processing unit (GPU, or both), a main memory 804 and a static memory 806, which communicate with each other via a bus 808. The computer system 800 may further include a video display unit 810 (e.g., a liquid crystal display (LCD), a flat panel, a solid state display, or a cathode ray tube (CRT)). The computer system 800 may include an input device 812 (e.g., a keyboard), a cursor control device 814 (e.g., a mouse), a disk drive unit 816, a signal generation device 818 (e.g., a speaker or remote control) and a network interface device 820.

The disk drive unit 816 may include a machine-readable medium 822 on which is stored one or more sets of instructions (e.g., software 824) embodying any one or more of the methodologies or functions described herein, including those methods illustrated above. The instructions 824 may also reside, completely or at least partially, within the main memory 804, the static memory 806, and/or within the processor 802 during execution thereof by the computer system 800. The main memory 804 and the processor 802 also may constitute machine-readable media.

Dedicated hardware implementations including, but not limited to, application specific integrated circuits, programmable logic arrays and other hardware devices can likewise be constructed to implement the methods described herein. Applications that may include the apparatus and systems of various embodiments broadly include a variety of electronic and computer systems. Some embodiments implement functions in two or more specific interconnected hardware modules or devices with related control and data signals communicated between and through the modules, or as portions of an application-specific integrated circuit. Thus, the example system is applicable to software, firmware, and hardware implementations.

In accordance with various embodiments of the present disclosure, the methods described herein are intended for operation as software programs running on a computer processor. Furthermore, software implementations can include, but not limited to, distributed processing or component/object distributed processing, parallel processing, or virtual machine processing can also be constructed to implement the methods described herein.

The present disclosure contemplates a machine readable medium containing instructions 824, or that which receives and executes instructions 824 from a propagated signal so that a device connected to a network environment 826 can send or receive voice, video or data, and to communicate over the network 826 using the instructions 824. The instructions 824 may further be transmitted or received over a network 826 via the network interface device 820.

While the machine-readable medium 822 is shown in an example embodiment to be a single medium, the term "machine-readable medium" should be taken to include a single medium or multiple media (e.g., a centralized or distributed database, and/or associated caches and servers) that store the one or more sets of instructions. The term "machine-readable medium" shall also be taken to include any medium that is capable of storing, encoding or carrying a set of instructions for execution by the machine and that cause the machine to perform any one or more of the methodologies of the present disclosure.

The term "machine-readable medium" shall accordingly be taken to include, but not be limited to: solid-state memories such as a memory card or other package that houses one or

more read-only (non-volatile) memories, random access memories, or other re-writable (volatile) memories; magneto-optical or optical medium such as a disk or tape; and/or a digital file attachment to e-mail or other self-contained information archive or set of archives is considered a distribution medium equivalent to a tangible storage medium. Accordingly, the disclosure is considered to include any one or more of a machine-readable medium or a distribution medium, as listed herein and including art-recognized equivalents and successor media, in which the software implementations herein are stored.

Although the present specification describes components and functions implemented in the embodiments with reference to particular standards and protocols, the disclosure is not limited to such standards and protocols. Each of the standards for Internet and other packet switched network transmission (e.g., TCP/IP, UDP/IP, HTML, HTTP) represent examples of the state of the art. Such standards are periodically superseded by faster or more efficient equivalents having essentially the same functions. Accordingly, replacement standards and protocols having the same functions are considered equivalents.

The illustrations of embodiments described herein are intended to provide a general understanding of the structure of various embodiments, and they are not intended to serve as a complete description of all the elements and features of apparatus and systems that might make use of the structures described herein. Many other embodiments will be apparent to those of skill in the art upon reviewing the above description. Other embodiments may be utilized and derived therefrom, such that structural and logical substitutions and changes may be made without departing from the scope of this disclosure. Figures are also merely representational and may not be drawn to scale. Certain proportions thereof may be exaggerated, while others may be minimized. Accordingly, the specification and drawings are to be regarded in an illustrative rather than a restrictive sense.

Such embodiments of the inventive subject matter may be referred to herein, individually and/or collectively, by the term "invention" merely for convenience and without intending to voluntarily limit the scope of this application to any single invention or inventive concept if more than one is in fact disclosed. Thus, although specific embodiments have been illustrated and described herein, it should be appreciated that any arrangement calculated to achieve the same purpose may be substituted for the specific embodiments shown. This disclosure is intended to cover any and all adaptations or variations of various embodiments. Combinations of the above embodiments, and other embodiments not specifically described herein, will be apparent to those of skill in the art upon reviewing the above description.

The Abstract of the Disclosure is provided to comply with 37 C.F.R. §1.72(b), requiring an abstract that will allow the reader to quickly ascertain the nature of the technical disclosure. It is submitted with the understanding that it will not be used to interpret or limit the scope or meaning of the claims. In addition, in the foregoing Detailed Description, it can be seen that various features are grouped together in a single embodiment for the purpose of streamlining the disclosure. This method of disclosure is not to be interpreted as reflecting an intention that the claimed embodiments require more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive subject matter lies in less than all features of a single disclosed embodiment. Thus the following claims are hereby incorporated into the Detailed Description, with each claim standing on its own as a separately claimed subject matter.

What is claimed is:

1. A computing device, comprising:
 - a memory that stores executable instructions; and
 - a processor coupled to the memory, wherein, responsive to execution by the processor, the executable instructions facilitate performance of operations comprising:
 - determining a first behavioral pattern of a user based on monitoring of user interaction with first media content;
 - transmitting the first behavioral pattern to a communication device associated with the user for adjusting communication operations according to the first behavioral pattern to generate adjusted communication operations at the communication device, wherein the adjusted communication operations include changing a graphical user interface presented by the communication device;
 - receiving, from the communication device, a second behavioral pattern that is determined based on a monitored user input at the communication device;
 - searching an electronic programming guide according to the second behavioral pattern;
 - identifying second media content that is correlated to the second behavioral pattern based on the searching of the electronic programming guide; and
 - providing access to the second media content.
2. The computing device of claim 1, wherein the changing of the graphical user interface includes a presentation of a toolbar at the communication device that includes a group of buttons, wherein each button of the group of buttons enables initiating a communication session with a different content source to access different content.
3. The computing device of claim 1, wherein the monitored user input at the communication device includes user interaction with a group of buttons presented according to the changing of the graphical user interface.
4. The computing device of claim 1, wherein the second behavioral pattern is determined by the communication device based in part on user preferences inputted by the user, and wherein the adjusted communication operations include adjusting a user profile stored at the communication device to indicate content preferences for the user.
5. The computing device of claim 1, wherein the processor is integrated with a set top box, and wherein the adjusted communication operations include adjusting a user profile for the user to indicate content preferences for the user.
6. The computing device of claim 1, wherein the communication device comprises a mobile phone, and wherein the monitoring of the first media content is utilized for targeting advertisement at the communication device.
7. The computing device of claim 1, wherein the adjusted communication operations are limited for use by the user and not for use by other users that share the communication device, wherein the processor is integrated with a set top box, and wherein the monitoring of the first media content is utilized for providing advertisements targeted to the user according to a subject matter of the first media content.
8. The computing device of claim 1, wherein the transmitting of the first behavioral pattern to the communication device causes a presentation of an advertisement that is correlated to subject matter associated with the first behavioral pattern.
9. A method comprising:
 - receiving, by a communication device, a first behavioral pattern for a user of a computing device, the first behavioral pattern being received from the computing device

11

based on monitoring user interaction with first media content that is presented by the computing device;

adjusting, by the communication device, communication operations of the communication device according to the first behavioral pattern to generate adjusted communication operations, wherein the adjusted communication operations include changing a graphical user interface presented by the communication device to generate a modified graphical user interface;

monitoring, by the communication device, a user interaction with the modified graphical user interface to determine a second behavioral pattern of the user; and

transmitting, by the communication device to the computing device, the second behavioral pattern to enable the computing device to select and present targeted advertising according to the second behavioral pattern.

10. The method of claim 9, further comprising limiting, by the communication device, use of the adjusted communication operations to the user and preventing use of the adjusted communication operations by other users that share the communication device.

11. The method of claim 9, wherein the transmitting of the second behavioral pattern to the computing device enables the computing device to identify second media content that is correlated to the second behavioral pattern and enables the computing device to provide access to the second media content.

12. The method of claim 11, wherein the second media content is identified by the computing device by searching an electronic programming guide according to the second behavioral pattern.

13. The method of claim 11, wherein the modified graphical user interface includes a group of buttons, wherein a first button of the group of buttons enables first access by the communication device to a first content source via a first web portal, wherein the access by the computing device to the second media content is enabled via a second web portal from a second content source.

14. The method of claim 9, wherein the communication device comprises a mobile phone, wherein the computing device comprises a set top box, wherein the modified graphical user interface includes a group of buttons, and wherein each button of the group of buttons enables initiating a communication session with a different content source to access different content.

12

15. The method of claim 9, comprising:

storing, by the communication device, a user profile; and adjusting the user profile according to the second behavioral pattern to indicate content preferences.

16. A computer-readable storage device, comprising executable instructions which, responsive to being executed by a processor, facilitate performance of operations comprising:

detecting a first behavioral pattern of a user based on monitoring of access to first media content;

transmitting the first behavioral pattern to a communication device associated with the user for adjusting communication operations according to the first behavioral pattern to generate adjusted communication operations at the communication device;

receiving, from the communication device, a second behavioral pattern that is determined based on a monitored user interaction of the user with the adjusted communication operations at the communication device;

identifying a targeted advertisement according to the first and second behavioral patterns; and presenting the targeted advertisement.

17. The computer-readable storage device of claim 16, wherein the operations further comprise:

identifying second media content that is correlated to the second behavioral pattern; and

presenting an option to record the second media content by way of a digital media recorder.

18. The computer-readable storage device of claim 16, wherein the communication device is a mobile device, wherein the processor operates in a set-top box, and wherein the operations further comprise:

searching an electronic programming guide according to the second behavioral pattern to identify second media content that is correlated to the second behavioral pattern; and

providing access to the second media content.

19. The computer-readable storage device of claim 16, wherein the first behavioral pattern identifies content of interest to the user based on genre, individuals associated with the content, broadcast channels of interest to the user, a temporal profile of consumption of the content by the user, or any combination thereof.

20. The computer-readable storage device of claim 16, wherein the second behavioral pattern is determined by the communication device based on user preferences established by the user, and wherein the adjusted communication operations include adjusting a user profile stored at the communication device to indicate content preferences.

* * * * *