



US009392377B2

(12) **United States Patent**
Olsen et al.

(10) **Patent No.:** **US 9,392,377 B2**
(45) **Date of Patent:** **Jul. 12, 2016**

(54) **ANATOMICALLY CUSTOMIZED EAR CANAL HEARING APPARATUS**

(71) Applicant: **EarLens Corporation**, Menlo Park, CA (US)

(72) Inventors: **Jake L. Olsen**, Palo Alto, CA (US);
David Chazan, Palo Alto, CA (US);
Jonathan P. Fay, San Mateo, CA (US);
Micha Rosen, Tsur Hadassa (IL); **Sunil Puria**, Sunnyvale, CA (US)

(73) Assignee: **EarLens Corporation**, Menlo Park, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/919,079**

(22) Filed: **Jun. 17, 2013**

(65) **Prior Publication Data**
US 2014/0056453 A1 Feb. 27, 2014

Related U.S. Application Data
(63) Continuation of application No. PCT/US2011/066306, filed on Dec. 20, 2011.
(60) Provisional application No. 61/425,000, filed on Dec. 20, 2010.

(51) **Int. Cl.**
H04R 25/00 (2006.01)
H04R 25/02 (2006.01)
A61F 2/18 (2006.01)

(52) **U.S. Cl.**
CPC **H04R 25/02** (2013.01); **H04R 25/606** (2013.01); **H04R 25/652** (2013.01); **H04R 2225/023** (2013.01)

(58) **Field of Classification Search**
USPC 381/320-328; 181/129; 600/25
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,229,049 A 1/1966 Goldberg
3,440,314 A 4/1969 Eldon

(Continued)

FOREIGN PATENT DOCUMENTS

AU 2004301961 A1 2/2005
DE 2044870 A1 3/1972

(Continued)

OTHER PUBLICATIONS

Ayatollahi, et al. Design and Modeling of Micromachined Condenser MEMS Loudspeaker using Permanent Magnet Neodymium—Iron—Boron (Nd—Fe—B). IEEE International Conference on Semiconductor Electronics, 2006. ICSE '06, Oct. 29, 2006-Dec. 1, 2006; 160-166.

(Continued)


Primary Examiner — Sunita Joshi

(74) *Attorney, Agent, or Firm* — Wilson, Sonsini, Goodrich & Rosati

(57) **ABSTRACT**

Embodiments of the present invention provide improved methods and apparatus suitable for use with hearing devices. A vapor deposition process can be used to make a retention structure having a shape profile corresponding to a tissue surface, such as a retention structure having a shape profile corresponding to one or more of an eardrum, the eardrum annulus, or a skin of the ear canal. The retention structure can be resilient and may comprise an anatomically accurate shape profile corresponding to a portion of the ear, such that the resilient retention structure provides mechanical stability for an output transducer assembly placed in the ear for an extended time. The output transducer may couple to the eardrum with direct mechanical coupling or acoustic coupling when retained in the ear canal with the retention structure.

45 Claims, 27 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

3,549,818 A	12/1970	Turner	5,411,467 A	5/1995	Hortmann et al.
3,585,416 A	6/1971	Mellen	5,425,104 A	6/1995	Shennib
3,594,514 A	7/1971	Wingrove	5,440,082 A	8/1995	Claes
3,710,399 A	1/1973	Hurst	5,440,237 A	8/1995	Brown et al.
3,712,962 A	1/1973	Epley	5,455,994 A	10/1995	Termeer et al.
3,764,748 A	10/1973	Branch et al.	5,456,654 A	10/1995	Ball
3,808,179 A	4/1974	Gaylord	5,531,787 A	7/1996	Lesinski et al.
3,882,285 A	5/1975	Nunley et al.	5,531,954 A	7/1996	Heide et al.
3,965,430 A	6/1976	Brandt	5,535,282 A	7/1996	Luca
3,985,977 A	10/1976	Beaty et al.	5,554,096 A	9/1996	Ball
4,002,897 A	1/1977	Kleinman et al.	5,558,618 A	9/1996	Maniglia
4,061,972 A	12/1977	Burgess	5,606,621 A	2/1997	Reiter et al.
4,075,042 A	2/1978	Das	5,624,376 A	4/1997	Ball et al.
4,098,277 A	7/1978	Mendell	5,692,059 A	11/1997	Kruger
4,109,116 A	8/1978	Victoreen	5,707,338 A	1/1998	Adams et al.
4,120,570 A	10/1978	Gaylord	5,715,321 A	2/1998	Andrea et al.
4,248,899 A	2/1981	Lyon et al.	5,721,783 A	2/1998	Anderson
4,252,440 A	2/1981	Frosch et al.	5,729,077 A	3/1998	Newnham et al.
4,303,772 A	12/1981	Novicky	5,740,258 A	4/1998	Goodwin-Johansson
4,319,359 A	3/1982	Wolf	5,762,583 A	6/1998	Adams et al.
4,334,315 A	6/1982	Ono et al.	5,772,575 A	6/1998	Lesinski et al.
4,334,321 A	6/1982	Edelman	5,774,259 A	6/1998	Saitoh et al.
4,339,954 A	7/1982	Anson et al.	5,782,744 A	7/1998	Money
4,357,497 A	11/1982	Hochmair et al.	5,788,711 A	8/1998	Lehner et al.
4,380,689 A	4/1983	Giannetti	5,795,287 A	8/1998	Ball et al.
4,428,377 A	1/1984	Zollner et al.	5,797,834 A	8/1998	Goode
4,524,294 A	6/1985	Brody	5,800,336 A	9/1998	Ball et al.
4,540,761 A	9/1985	Kawamura et al.	5,804,109 A	9/1998	Perkins
4,556,122 A	12/1985	Goode	5,804,907 A	9/1998	Park et al.
4,592,087 A	5/1986	Killion	5,814,095 A	9/1998	Muller et al.
4,606,329 A	8/1986	Hough	5,825,122 A	10/1998	Givargizov et al.
4,611,598 A	9/1986	Hortmann et al.	5,836,863 A	11/1998	Bushek et al.
4,628,907 A	12/1986	Epley	5,842,967 A	12/1998	Kroll
4,641,377 A	2/1987	Rush et al.	5,857,958 A	1/1999	Ball et al.
4,689,819 A	8/1987	Killion	5,859,916 A	1/1999	Ball et al.
4,696,287 A	9/1987	Hortmann et al.	5,879,283 A	3/1999	Adams et al.
4,729,366 A	3/1988	Schaefer	5,888,187 A	3/1999	Jaeger et al.
4,741,339 A	5/1988	Harrison et al.	5,897,486 A	4/1999	Ball et al.
4,742,499 A	5/1988	Butler	5,899,847 A	5/1999	Adams et al.
4,756,312 A	7/1988	Epley	5,900,274 A	5/1999	Chatterjee et al.
4,766,607 A	8/1988	Feldman	5,906,635 A	5/1999	Maniglia
4,774,933 A	10/1988	Hough et al.	5,913,815 A	6/1999	Ball et al.
4,776,322 A	10/1988	Hough et al.	5,940,519 A	8/1999	Kuo
4,800,884 A	1/1989	Heide et al.	5,949,895 A	9/1999	Ball et al.
4,817,607 A	4/1989	Tatge	5,987,146 A	11/1999	Pluvinage et al.
4,840,178 A	6/1989	Heide et al.	5,987,146 A	11/1999	Pluvinage et al.
4,845,755 A	7/1989	Busch et al.	6,005,955 A	12/1999	Kroll et al.
4,870,688 A	9/1989	Voroba et al.	6,024,717 A	2/2000	Ball et al.
4,932,405 A	6/1990	Peeters et al.	6,045,528 A	4/2000	Arenberg et al.
4,936,305 A	6/1990	Ashtiani et al.	6,050,933 A	4/2000	Bushek et al.
4,944,301 A	7/1990	Widin et al.	6,068,589 A	5/2000	Neukermans
4,948,855 A	8/1990	Novicky	6,068,590 A	5/2000	Brisken
4,957,478 A	9/1990	Maniglia	6,084,975 A	7/2000	Perkins
4,963,963 A	10/1990	Dorman	6,093,144 A	7/2000	Jaeger et al.
4,999,819 A	3/1991	Newnham et al.	6,135,612 A	10/2000	Clore
5,003,608 A	3/1991	Carlson	6,137,889 A	10/2000	Shennib et al.
5,012,520 A	4/1991	Steeger	6,139,488 A	10/2000	Ball
5,015,224 A	5/1991	Maniglia	6,153,966 A	11/2000	Neukermans
5,015,225 A	5/1991	Hough et al.	6,174,278 B1	1/2001	Jaeger et al.
5,031,219 A	7/1991	Ward et al.	6,181,801 B1	1/2001	Puthuff et al.
5,061,282 A	10/1991	Jacobs	6,190,305 B1	2/2001	Ball et al.
5,066,091 A	11/1991	Stoy et al.	6,190,306 B1	2/2001	Kennedy
5,094,108 A	3/1992	Kim et al.	6,208,445 B1	3/2001	Reime
5,117,461 A	5/1992	Moseley	6,217,508 B1	4/2001	Ball et al.
5,142,186 A	8/1992	Cross et al.	6,222,302 B1	4/2001	Imada et al.
5,163,957 A	11/1992	Sade et al.	6,222,927 B1	4/2001	Feng et al.
5,167,235 A	12/1992	Seacord et al.	6,240,192 B1	5/2001	Brennan et al.
5,201,007 A	4/1993	Ward et al.	6,241,767 B1	6/2001	Stennert et al.
5,259,032 A	11/1993	Perkins et al.	6,261,224 B1	7/2001	Adams et al.
5,272,757 A	12/1993	Scofield et al.	6,277,148 B1	8/2001	Dormer
5,276,910 A	1/1994	Buchele	6,312,959 B1	11/2001	Datskos
5,277,694 A	1/1994	Leysieffer et al.	6,339,648 B1	1/2002	McIntosh et al.
5,360,388 A	11/1994	Spindel et al.	6,354,990 B1	3/2002	Juneau et al.
5,378,933 A	1/1995	Pfannenmueller et al.	6,366,863 B1	4/2002	Bye et al.
5,402,496 A	3/1995	Soli et al.	6,385,363 B1	5/2002	Rajic et al.
			6,387,039 B1	5/2002	Moses
			6,393,130 B1	5/2002	Stonikas et al.
			6,422,991 B1	7/2002	Jaeger
			6,432,248 B1	8/2002	Popp et al.
			6,436,028 B1	8/2002	Dormer

(56)

References Cited

U.S. PATENT DOCUMENTS

6,438,244 B1	8/2002	Juneau et al.	8,715,154 B2	5/2014	Perkins et al.
6,445,799 B1	9/2002	Taenzer et al.	8,824,715 B2	9/2014	Fay et al.
6,473,512 B1	10/2002	Juneau et al.	8,858,419 B2	10/2014	Puria et al.
6,475,134 B1	11/2002	Ball et al.	8,885,860 B2	11/2014	Djalilian et al.
6,491,644 B1	12/2002	Vujanic et al.	9,049,528 B2	6/2015	Fay et al.
6,493,454 B1	12/2002	Loi et al.	9,154,891 B2	10/2015	Puria et al.
6,519,376 B2	2/2003	Biagi et al.	9,226,083 B2	12/2015	Puria et al.
6,536,530 B2	3/2003	Schultz et al.	2001/0024507 A1	9/2001	Boesen
6,537,200 B2	3/2003	Leysieffer et al.	2001/0027342 A1	10/2001	Dormer
6,549,633 B1	4/2003	Westermann	2002/0012438 A1	1/2002	Leysieffer et al.
6,549,635 B1	4/2003	Gebert	2002/0030871 A1	3/2002	Anderson et al.
6,554,761 B1	4/2003	Puria et al.	2002/0085728 A1	7/2002	Shennib et al.
6,575,894 B2	6/2003	Leysieffer et al.	2002/0086715 A1	7/2002	Sahagen
6,592,513 B1	7/2003	Kroll et al.	2002/0172350 A1	11/2002	Edwards et al.
6,603,860 B1	8/2003	Taenzer et al.	2002/0183587 A1	12/2002	Dormer
6,620,110 B2	9/2003	Schmid	2003/0021903 A1	1/2003	Shlenker et al.
6,626,822 B1	9/2003	Jaeger et al.	2003/0064746 A1	4/2003	Rader et al.
6,629,922 B1	10/2003	Puria et al.	2003/0081803 A1	5/2003	Petilli et al.
6,668,062 B1	12/2003	Luo et al.	2003/0125602 A1	7/2003	Sokolich et al.
6,676,592 B2	1/2004	Ball et al.	2003/0142841 A1	7/2003	Wiegand
6,695,943 B2	2/2004	Juneau et al.	2003/0208099 A1	11/2003	Ball
6,724,902 B1	4/2004	Shennib et al.	2004/0165742 A1	8/2004	Shennib et al.
6,726,718 B1	4/2004	Carlyle et al.	2004/0202340 A1	10/2004	Armstrong et al.
6,728,024 B2	4/2004	Ribak	2004/0208333 A1	10/2004	Cheung et al.
6,735,318 B2	5/2004	Cho	2004/0234089 A1	11/2004	Rembrand et al.
6,754,358 B1	6/2004	Boesen et al.	2004/0234092 A1	11/2004	Wada et al.
6,801,629 B2	10/2004	Brimhall et al.	2004/0236416 A1*	11/2004	Falotico A61L 31/10 623/1.42
6,829,363 B2	12/2004	Sacha	2004/0240691 A1	12/2004	Grafenberg
6,842,647 B1	1/2005	Griffith et al.	2005/0020873 A1	1/2005	Berrang et al.
6,888,949 B1	5/2005	Vanden et al.	2005/0036639 A1	2/2005	Bachler et al.
6,900,926 B2	5/2005	Ribak	2005/0163333 A1	7/2005	Abel et al.
6,912,289 B2	6/2005	Vonlanthen et al.	2005/0226446 A1	10/2005	Luo et al.
6,920,340 B2	7/2005	Laderman	2006/0023908 A1	2/2006	Perkins et al.
6,931,231 B1	8/2005	Griffin	2006/0062420 A1	3/2006	Araki
6,940,989 B1	9/2005	Shennib et al.	2006/0074159 A1	4/2006	Lu et al.
D512,979 S	12/2005	Corcoran et al.	2006/0075175 A1	4/2006	Jensen et al.
6,975,402 B2	12/2005	Bisson et al.	2006/0107744 A1	5/2006	Li et al.
6,978,159 B2	12/2005	Feng et al.	2006/0177079 A1	8/2006	Baekgaard et al.
7,043,037 B2	5/2006	Lichtblau	2006/0189841 A1	8/2006	Pluvinage et al.
7,050,675 B2	5/2006	Zhou	2006/0233398 A1	10/2006	Husung
7,072,475 B1	7/2006	DeNap et al.	2006/0247735 A1	11/2006	Honert et al.
7,076,076 B2	7/2006	Bauman	2006/0251278 A1	11/2006	Puria et al.
7,095,981 B1	8/2006	Voroba et al.	2007/0083078 A1	4/2007	Easter et al.
7,167,572 B1	1/2007	Harrison et al.	2007/0100197 A1	5/2007	Perkins et al.
7,174,026 B2	2/2007	Niederdrank et al.	2007/0127748 A1	6/2007	Carlile et al.
7,203,331 B2	4/2007	Boesen	2007/0127752 A1	6/2007	Armstrong
7,239,069 B2	7/2007	Cho	2007/0127766 A1	6/2007	Combest
7,245,732 B2	7/2007	Jorgensen et al.	2007/0135870 A1	6/2007	Shanks et al.
7,255,457 B2	8/2007	Ducharme et al.	2007/0191673 A1	8/2007	Ball et al.
7,266,208 B2	9/2007	Charvin et al.	2007/0236704 A1	10/2007	Carr et al.
7,289,639 B2	10/2007	Abel et al.	2007/0250119 A1	10/2007	Tyler et al.
7,322,930 B2	1/2008	Jaeger et al.	2007/0286429 A1	12/2007	Grafenberg et al.
7,354,792 B2	4/2008	Mazur et al.	2008/0021518 A1	1/2008	Hochmair et al.
7,376,563 B2	5/2008	Leysieffer et al.	2008/0051623 A1	2/2008	Schneider et al.
7,390,689 B2	6/2008	Mazur et al.	2008/0054509 A1	3/2008	Berman et al.
7,421,087 B2	9/2008	Perkins et al.	2008/0063228 A1	3/2008	Mejia et al.
7,444,877 B2	11/2008	Li et al.	2008/0089292 A1	4/2008	Kitazoe et al.
7,630,646 B2	12/2009	Anderson et al.	2008/0107292 A1	5/2008	Kornagel
7,668,325 B2	2/2010	Puria et al.	2008/0123866 A1	5/2008	Rule et al.
7,747,295 B2	6/2010	Choi	2009/0092271 A1*	4/2009	Fay H04R 25/604 381/328
7,867,160 B2	1/2011	Pluvinage et al.	2009/0097681 A1	4/2009	Puria et al.
8,090,134 B2	1/2012	Takigawa et al.	2009/0262966 A1	10/2009	Vestergaard et al.
8,233,651 B1	7/2012	Haller	2009/0310805 A1	12/2009	Petroff
8,295,505 B2	10/2012	Weinans et al.	2010/0034409 A1	2/2010	Fay et al.
8,295,523 B2	10/2012	Fay et al.	2010/0048982 A1	2/2010	Puria et al.
8,320,601 B2	11/2012	Takigawa et al.	2010/0202645 A1	8/2010	Puria et al.
8,391,527 B2	3/2013	Feucht et al.	2010/0222639 A1*	9/2010	Purcell H04R 25/606 600/25
8,396,239 B2	3/2013	Fay et al.	2011/0077453 A1	3/2011	Pluvinage et al.
8,401,212 B2	3/2013	Puria et al.	2011/0116666 A1	5/2011	Dittberner et al.
8,545,383 B2	10/2013	Wenzel et al.	2011/0152602 A1	6/2011	Perkins et al.
8,600,089 B2	12/2013	Wenzel et al.	2012/0008807 A1	1/2012	Gran
8,696,054 B2	4/2014	Crum	2012/0039493 A1	2/2012	Rucker et al.
8,696,541 B2	4/2014	Pluvinage et al.	2012/0140967 A1	6/2012	Aubert et al.
8,715,152 B2	5/2014	Puria et al.	2013/0034258 A1*	2/2013	Lin 1/8
8,715,153 B2	5/2014	Puria et al.	2013/0287239 A1	10/2013	Fay et al.
			2013/0308782 A1	11/2013	Dittberner et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0003640 A1 1/2014 Puria et al.
 2014/0169603 A1 6/2014 Sacha et al.
 2014/0286514 A1 9/2014 Pluvinage et al.
 2014/0296620 A1 10/2014 Puria et al.
 2015/0023540 A1 1/2015 Fay et al.
 2015/0271609 A1 9/2015 Puria
 2016/0029132 A1 1/2016 Freed et al.

FOREIGN PATENT DOCUMENTS

DE 3243850 A1 5/1984
 DE 3508830 A1 9/1986
 EP 0092822 A2 11/1983
 EP 0296092 A2 12/1988
 EP 0296092 A3 8/1989
 EP 1845919 A1 10/2007
 FR 2455820 A1 11/1980
 JP S60154800 A 8/1985
 JP 2000504913 A 4/2000
 JP 2004187953 A 7/2004
 WO WO-9621334 A1 7/1996
 WO WO-9745074 A1 12/1997
 WO WO-9903146 A1 1/1999
 WO WO-9915111 A1 4/1999
 WO WO-0150815 A1 7/2001
 WO WO-0158206 A2 8/2001
 WO WO-0176059 A2 10/2001
 WO WO-0158206 A3 2/2002
 WO WO 03/063542 A2 7/2003
 WO WO-03063542 A3 1/2004
 WO WO-2004010733 A1 1/2004
 WO WO-2005015952 A1 2/2005
 WO WO-2005107320 A1 11/2005
 WO WO-2006014915 A2 2/2006
 WO WO-2006037156 A1 4/2006
 WO WO-2006042298 A2 4/2006
 WO WO 2006/075175 A1 7/2006
 WO WO-2006042298 A3 12/2006
 WO WO-2010033933 A1 3/2010
 WO WO-2012149970 A1 11/2012

OTHER PUBLICATIONS

Birch, et al. Microengineered systems for the hearing impaired. IEE Colloquium on Medical Applications of Microengineering, Jan. 31, 1996; pp. 2/1-2/5.

Cheng, et al. A Silicon Microspeaker for Hearing Instruments. *Journal of Micromechanics and Microengineering* 2004; 14(7):859-866. International search report and written opinion dated Jun. 19, 2012 for PCT Application No. US2011/066306.

O'Connor, et al. Middle ear cavity and ear canal pressure-driven stapes velocity responses in human cadaveric temporal bones. *J Acoust Soc Am.* Sep. 2006; 120(3):1517-28.

Puria, et al. Tympanic-membrane and malleus-incus-complex co-adaptations for high-frequency hearing in mammals. *Hear Res.* May 2010; 263(1-2):183-90. doi: 10.1016/j.heares.2009.10.013. Epub Oct. 28, 2009.

Sound Design Technologies,—Voyager TDTM Open Platform DSP System for Ultra Low Power Audio Processing—GA3280 Data Sheet. Oct. 2007; retrieved from the Internet: <<<http://www.sounddes.com/pdf/37601DOC.pdf>>>, 15 page total.

Wang, et al. Preliminary Assessment of Remote Photoelectric Excitation of an Actuator for a Hearing Implant. *Proceeding of the 2005 IEEE, Engineering in Medicine and Biology 27th Annual Conference, Shanghai, China.* Sep. 1-4, 2005; 6233-6234.

Yi, et al. Piezoelectric Microspeaker with Compressive Nitride Diaphragm. *The Fifteenth IEEE International Conference on Micro Electro Mechanical Systems*, 2002; 260-263.

Atasoy [Paper] Opto-acoustic Imaging. For BYM504E Biomedical Imaging Systems class at ITU, downloaded from the Internet www2.itu.edu.tr/~cilesiz/courses/BYM504-2005-OA_504041413.pdf, 14 pages.

Athanassiou, et al. Laser controlled photomechanical actuation of photochromic polymers *Microsystems. Rev. Adv. Mater. Sci.* 2003; 5:245-251.

Baer, et al. Effects of Low Pass Filtering on the Intelligibility of Speech in Noise for People With and Without Dead Regions at High Frequencies. *J. Acoust. Soc. Am* 112 (3), pt. 1, (Sep. 2002), pp. 1133-1144.

Best, et al. The influence of high frequencies on speech localization. Abstract 981 (Feb. 24, 2003) from www.aro.org/abstracts/abstracts.html.

Burkhard, et al. Anthropometric Manikin for Acoustic Research. *J. Acoust. Soc. Am.*, vol. 58, No. 1, (Jul. 1975), pp. 214-222.

Camacho-Lopez, et al. Fast Liquid Crystal Elastomer Swims Into the Dark, *Electronic Liquid Crystal Communications*. Nov. 26, 2003; 9 pages total.

Carlile, et al. Spatialisation of talkers and the segregation of concurrent speech. Abstract 1264 (Feb. 24, 2004) from www.aro.org/abstracts/abstracts.html.

Co-pending U.S. Appl. No. 14/554,606, filed Nov. 26, 2014.

Co-pending U.S. Appl. No. 14/813,301, filed Jul. 30, 2015.

Co-pending U.S. Appl. No. 14/843,030, filed Sep. 2, 2015.

Datskos, et al. Photoinduced and thermal stress in silicon microcantilevers. *Applied Physics Letters*. Oct. 19, 1998; 73(16):2319-2321.

Decraemer, et al. A method for determining three-dimensional vibration in the ear. *Hearing Res.*, 77:19-37 (1994).

Ear. Retrieved from the Internet: <http://www.mgs.bionet.nsc.ru/mgs/gnw/trrd/thesaurus/Se/ear.html>. Accessed Jun. 17, 2008.

Fay, et al. Cat eardrum response mechanics. *Mechanics and Computation Division. Department of Mechanical Engineering. Stanford University.* 2002; 10 pages total.

Fletcher. Effects of Distortion on the Individual Speech Sounds. Chapter 18, *ASA Edition of Speech and Hearing in Communication, Acoust Soc. of Am.* (republished in 1995) pp. 415-423.

Freyman, et al. Spatial Release from Informational Masking in Speech Recognition. *J. Acoust. Soc. Am.*, vol. 109, No. 5, pt. 1, (May 2001); 2112-2122.

Freyman, et al. The Role of Perceived Spatial Separation in the Unmasking of Speech. *J. Acoust. Soc. Am.*, vol. 106, No. 6, (Dec. 1999); 3578-3588.

Gennum, GA3280 Preliminary Data Sheet: Voyager TD Open Platform DSP System for Ultra Low Audio Processing, downloaded from the Internet: <<<http://www.sounddesigntechnologies.com/products/pdf/37601DOC.pdf>>>, Oct. 2006; 17 pages.

Gobin, et al. Comments on the physical basis of the active materials concept. *Proc. SPIE* 2003; 4512:84-92.

Hato, et al. Three-dimensional stapes footplate motion in human temporal bones. *Audiol. Neurootol.*, 8:140-152 (Jan. 30, 2003).

Headphones. Wikipedia Entry, downloaded from the Internet: en.wikipedia.org/wiki/Headphones. 9 pages total.

Hofman, et al. Relearning Sound Localization With New Ears. *Nature Neuroscience*, vol. 1, No. 5, (Sep. 1998); 417-421.

Jin, et al. Speech Localization. *J. Audio Eng. Soc.* convention paper, presented at the AES 112th Convention, Munich, Germany, May 10-13, 2002, 13 pages total.

Killion. Myths About Hearing Noise and Directional Microphones. *The Hearing Review*. Feb. 2004; 11(2):14, 16, 18, 19, 72 & 73.

Killion. SNR loss: I can hear what people say but I can't understand them. *The Hearing Review*, 1997; 4(12):8-14.

Lee, et al. A Novel Opto-Electromagnetic Actuator Coupled to the tympanic Membrane. *J Biomech.* Dec. 5, 2008; 41(16):3515-8. Epub Nov. 7, 2008.

Lee, et al. The optimal magnetic force for a novel actuator coupled to the tympanic membrane: a finite element analysis. *Biomedical engineering: applications, basis and communications.* 2007; 19(3):171-177.

Lezal. Chalcogenide glasses—survey and progress. *Journal of Optoelectronics and Advanced Materials*. Mar. 2003; 5(1):23-34.

Martin, et al. Utility of Monaural Spectral Cues is Enhanced in the Presence of Cues to Sound-Source Lateral Angle. *JARO*. 2004; 5:80-89.

(56)

References Cited

OTHER PUBLICATIONS

- Moore. Loudness perception and intensity resolution. Cochlear Hearing Loss, Chapter 4, pp. 90-115, Whurr Publishers Ltd., London (1998).
- Murugasu, et al. Malleus-to-footplate versus malleus-to-stapes-head ossicular reconstruction prostheses: temporal bone pressure gain measurements and clinical audiological data. *Otol Neurotol.* Jul. 2005; 26(9):572-582.
- Musicant, et al. Direction-Dependent Spectral Properties of Cat External Ear: New Data and Cross-Species Comparisons. *J. Acoustic Soc. Am.*, May 10-13, 2002, vol. 87, No. 2, (Feb. 1990), pp. 757-781.
- National Semiconductor, LM4673 Boomer: Filterless, 2.65W, Mono, Class D Audio Power Amplifier, [Data Sheet] downloaded from the Internet: <<<http://www.national.com/ds/LM/LM4673.pdf>>>; Nov. 1, 2007; 24 pages.
- Poosanaas, et al. Influence of sample thickness on the performance of photostrictive ceramics, *J. App. Phys.* Aug. 1, 1998; 84(3):1508-1512.
- Puria et al. A gear in the middle ear. ARO Denver CO, 2007b.
- Puria, et al. Malleus-to-footplate ossicular reconstruction prosthesis positioning: cochleovestibular pressure optimization. *Otol Nerotol.* May 2005; 26(3):368-379.
- Puria, et al. Measurements and model of the cat middle ear: Evidence of tympanic membrane acoustic delay. *J. Acoust. Soc. Am.*, 104(6):3463-3481 (Dec. 1998).
- Puria, et al. Middle Ear Morphometry From Cadaveric Temporal Bone MicroCT Imaging. Proceedings of the 4th International Symposium, Zurich, Switzerland, Jul. 27-30, 2006, Middle Ear Mechanics in Research and Otology, pp. 259-268.
- Puria, et al. Sound-Pressure Measurements in the Cochlear Vestibule of Human-Cadaver Ears. *Journal of the Acoustical Society of America.* 1997; 101 (5-1): 2754-2770.
- Sekaric, et al. Nanomechanical resonant structures as tunable passive modulators. *App. Phys. Lett.* Nov. 2003; 80(19):3617-3619.
- Shaw. Transformation of Sound Pressure Level From the Free Field to the Eardrum in the Horizontal Plane. *J. Acoust. Soc. Am.*, vol. 56, No. 6, (Dec. 1974), 1848-1861.
- Shih. Shape and displacement control of beams with various boundary conditions via photostrictive optical actuators. *Proc. IMECE.* Nov. 2003; 1-10.
- Stuchlik, et al. Micro-Nano Actuators Driven by Polarized Light. *IEEE Proc. Sci. Meas. Techn.* Mar. 2004; 151(2):131-136.
- Suski, et al. Optically activated ZnO/SiO₂/Si cantilever beams. *Sensors and Actuators A (Physical)*, 0 (nr: 24). 2003; 221-225.
- Takagi, et al. Mechanochemical Synthesis of Piezoelectric PLZT Powder. *KONA.* 2003; 51(21):234-241.
- Thakoor, et al. Optical microactuation in piezoceramics. *Proc. SPIE.* Jul. 1998; 3328:376-391.
- Thompson. Tutorial on microphone technologies for directional hearing aids. *Hearing Journal.* Nov. 2003; 56(11):14-16,18, 20-21.
- Tzou, et al. Smart Materials, Precision Sensors/Actuators, Smart Structures, and Structronic Systems. *Mechanics of Advanced Materials and Structures.* 2004; 11:367-393.
- Uchino, et al. Photostrictive actuators. *Ferroelectrics.* 2001; 258:147-158.
- U.S. Appl. No. 61/073,271, filed Jun. 17, 2008.
- U.S. Appl. No. 61/073,281, filed Jun. 17, 2008.
- Vickers, et al. Effects of Low-Pass Filtering on the Intelligibility of Speech in Quiet for People With and Without Dead Regions at High Frequencies. *J. Acoust. Soc. Am.* Aug. 2001; 110(2):1164-1175.
- Wiener, et al. On the Sound Pressure Transformation by the Head and Auditory Meatus of the Cat. *Acta Otolaryngol.* Mar. 1966; 61(3):255-269.
- Wightman, et al. Monaural Sound Localization Revisited. *J Acoust Soc Am.* Feb. 1997;101(2):1050-1063.
- Yu, et al. Photomechanics: Directed bending of a polymer film by light. *Nature.* Sep. 2003; 425:145.
- Carlile, et al. Frequency bandwidth and multi-talker environments. Audio Engineering Society Convention 120. Audio Engineering Society, May 20-23, 2006. Paris, France. 118: 8 pages.
- Co-pending U.S. Appl. No. 14/949,495, filed on Nov. 23, 2015.
- Co-pending U.S. Appl. No. 14/988,304, filed on Jan. 5, 2016.
- Killion, et al. The case of the missing dots: AI and SNR loss. *The Hearing Journal*, 1998. 51(5), 32-47.
- Moore, et al. Perceived naturalness of spectrally distorted speech and music. *J Acoust Soc Am.* Jul. 2003;114(1):408-19.
- Puria. Measurements of human middle ear forward and reverse acoustics: implications for otoacoustic emissions. *J Acoust Soc Am.* May 2003;113(5):2773-89.
- Fay, et al. Preliminary evaluation of a light-based contact hearing device for the hearing impaired. *Otol Neurotol.* Jul. 2013;34(5):912-21. doi: 10.1097/MAO.0b013e31827de4b1.

* cited by examiner




FIG. 1




FIG. 2A



FIG. 2B




FIG. 3-1




FIG. 3-2




FIG. 3-3




FIG. 3-4




FIG. 3-5




FIG. 3-6




FIG. 3-7




FIG. 3-8




FIG. 3-9




FIG. 3-9A




FIG. 3-9B




FIG. 3-10




FIG. 3-11




FIG. 3-12




FIG. 4




FIG. 5A




FIG. 5A1




FIG. 5A2




FIG. 5A3




FIG. 5A4




FIG. 5A5




FIG. 5B




FIG. 5B1




FIG. 5B2




FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8D




FIG. 8E




FIG. 8F




FIG. 9A




FIG. 9B




FIG. 10A




FIG. 10B




FIG. 10C




FIG. 11




FIG. 12

1

ANATOMICALLY CUSTOMIZED EAR CANAL HEARING APPARATUS

CROSS-REFERENCES TO RELATED APPLICATIONS

This application is a continuation of international application number PCT/US11/66306, filed Dec. 20, 2011, which claims priority to U.S. Pat. App. Ser. No. 61/425,000, filed Dec. 20, 2010, entitled "Anatomically Customized Ear Canal Hearing Apparatus", the entire disclosures of which are incorporated herein by reference.

STATEMENT AS TO RIGHTS TO INVENTIONS MADE UNDER FEDERALLY SPONSORED RESEARCH AND DEVELOPMENT

Not Applicable

REFERENCE TO A "SEQUENCE LISTING," A TABLE, OR A COMPUTER PROGRAM LISTING APPENDIX SUBMITTED ON A COMPACT DISK

Not Applicable

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention is related to systems, devices and methods that couple to tissue such as hearing systems. Although specific reference is made to hearing aid systems, embodiments of the present invention can be used in many applications in which a signal is used to stimulate the ear.

People like to hear. Hearing allows people to listen to and understand others. Natural hearing can include spatial cues that allow a user to hear a speaker, even when background noise is present. People also like to communicate with those who are far away, such as with cellular phones.

Hearing devices can be used with communication systems to help the hearing impaired and to help people communicate with others who are far away. Hearing impaired subjects may need hearing aids to verbally communicate with those around them. Unfortunately, the prior hearing devices can provide less than ideal performance in at least some respects, such that users of prior hearing devices remain less than completely satisfied in at least some instances.

Examples of deficiencies of prior hearing devices include feedback, distorted sound quality, less than desirable sound localization, discomfort and autophony. Feedback can occur when a microphone picks up amplified sound and generates a whistling sound. Autophony includes the unusually loud hearing of a person's own self-generated sounds such as voice, breathing or other internally generated sound. Possible causes of autophony include occlusion of the ear canal, which may be caused by an object blocking the ear canal and reflecting sound vibration back toward the eardrum, such as an unvented hearing aid or a plug of earwax reflecting sound back toward the eardrum.

Although acoustic hearing aids can increase the volume of sound to a user, acoustic hearing aids provide sound quality that can be less than ideal and may not provide adequate speech recognition for the hearing impaired in at least some instances. Acoustic hearing aids can rely on sound pressure to transmit sound from a speaker within the hearing aid to the eardrum of the user. However, the sound quality can be less than ideal and the sound pressure can cause feedback to a microphone placed near the ear canal opening. Although

2

placement of an acoustic hearing aid along the bony portion of the ear canal may decrease autophony and feedback, the fitting of such deep canal acoustic devices can be less than ideal such that many people are not able to use the devices. In at least some instances sound leakage around the device may result in feedback. The ear canal may comprise a complex anatomy and the prior deep canal acoustic devices may be less than ideally suited for the ear canals of at least some patients. Also, the amount of time a hearing device can remain inserted in the bony portion of the ear canal can be less than ideal, and in at least some instances skin of the ear canal may adhere to the hearing device such that removal and comfort may be less than ideal.

Although it has been proposed to couple a transducer to the eardrum to stimulate the eardrum with direct mechanical coupling, the clinical implementation of the prior direct mechanical coupling devices has been less than ideal in at least some instances. Coupling the transducer to the eardrum can provide amplified sound with decreased feedback, such that in at least some instances a microphone can be placed in or near the ear canal to provide hearing with spatial information cues. However, the eardrum is a delicate tissue structure, and in at least some instances the placement and coupling of the direct mechanical coupling devices can be less than ideal. For example, in many patients the deepest portion of the ear canal comprises the anterior sulcus, and a device extending to the anterior sulcus can be difficult for a clinician to view in at least some instances. Further, at least some prior direct coupling devices have inhibited viewing of the eardrum and the portion of the device near the eardrum, which may result in less than ideal placement and coupling of the transducer to the eardrum. Also, direct coupling may result in autophony in at least some instances. The eardrum can move substantially in response to atmospheric pressure changes, for example about one millimeter, and at least some of the prior direct coupling devices may not be well suited to accommodate significant movement of the eardrum in at least some instances. Also, the naturally occurring movement of the user such as chewing and eardrum movement may decouple at least some of the prior hearing devices. Although prior devices have been provided with a support to couple a magnet to the eardrum, the success of such coupling devices can vary among patients and the results can be less than ideal in at least some instances.

Although the above described prior systems can help people hear better, many people continue to have less than ideal hearing with such devices and it would be beneficial to provide improved coupling of the transducer assembly to the eardrum and ear canal. Also, it would be helpful to provide improved coupling in simplified manner such that the assemblies can be manufactured reliably for many users such that many people can enjoy the benefits of better hearing.

For the above reasons, it would be desirable to provide hearing systems and improved manufacturing which at least decrease, or even avoid, at least some of the above mentioned limitations of the prior hearing devices. For example, there is a need to provide improved manufacturing of reliable, comfortable hearing devices which provide hearing with natural sound qualities, for example with spatial information cues, and which decrease autophony, distortion and feedback.

2. Description of the Background Art

Patents and publications that may be relevant to the present application include: U.S. Pat. Nos. 3,585,416; 3,764,748; 3,882,285; 5,142,186; 5,554,096; 5,624,376; 5,795,287; 5,800,336; 5,825,122; 5,857,958; 5,859,916; 5,888,187; 5,897,486; 5,913,815; 5,949,895; 6,005,955; 6,068,590; 6,093,144; 6,139,488; 6,174,278; 6,190,305; 6,208,445; 6,217,508; 6,222,302; 6,241,767; 6,422,991; 6,475,134;

6,519,376; 6,620,110; 6,626,822; 6,676,592; 6,728,024; 6,735,318; 6,900,926; 6,920,340; 7,072,475; 7,095,981; 7,239,069; 7,289,639; D512,979; 2002/0086715; 2003/0142841; 2004/0234092; 2005/0020873; 2006/0107744; 2006/0233398; 2006/075175; 2007/0083078; 2007/0191673; 2008/0021518; 2008/0107292; commonly owned U.S. Pat. No. 5,259,032; U.S. Pat. No. 5,276,910; U.S. Pat. No. 5,425,104; U.S. Pat. No. 5,804,109; U.S. Pat. No. 6,084,975; U.S. Pat. No. 6,554,761; U.S. Pat. No. 6,629,922; U.S. Publication Nos. 2006/0023908; 2006/0189841; 2006/0251278; and 2007/0100197. Non-U.S. patents and publications that may be relevant include EP1845919 PCT Publication Nos. WO 03/063542; WO 2006/075175; U.S. Publication Nos. Journal publications that may be relevant include: Ayatollahi et al., "Design and Modeling of Micro-machines Condenser MEMS Loudspeaker using Permanent Magnet Neodymium-Iron-Boron (Nd—Fe—B)", ISCE, Kuala Lumpur, 2006; Birch et al., "Microengineered Systems for the Hearing Impaired", IEE, London, 1996; Cheng et al., "A silicon microspeaker for hearing instruments", *J. Micro-mech. Microeng.*, 14 (2004) 859-866; Yi et al., "Piezoelectric microspeaker with compressive nitride diaphragm", *IEEE*, 2006, and Zhigang Wang et al., "Preliminary Assessment of Remote Photoelectric Excitation of an Actuator for a Hearing Implant", *IEEE Engineering in Medicine and Biology 27th Annual Conference*, Shanghai, China, Sep. 1-4, 2005. Other publications of interest include: Gennum GA3280 Preliminary Data Sheet, "Voyager TDTM. Open Platform DSP System for Ultra Low Power Audio Processing" and National Semiconductor LM4673 Data Sheet, "LM4673 Filterless, 2.65 W, Mono, Class D audio Power Amplifier"; Puria, S. and Steele, C Tympanic-membrane and malleus-incus-complex co-adaptations for high-frequency hearing in mammals. *Hear Res* 2010 263(1-2):183-90; O'Connor, K. and Puria, S. "Middle ear cavity and ear canal pressure-driven stapes velocity responses in human cadaveric temporal bones" *J. Acoust. Soc. Am.* 120(3) 1517-1528.

BRIEF SUMMARY OF THE INVENTION

The present invention is related to hearing systems, devices and methods. Although specific reference is made to hearing aid systems, embodiments of the present invention can be used in many applications in which a signal is used to transmit sound to a user, for example cellular communication and entertainment systems. The vapor deposition and polymerization as described herein can be used with many devices, such as medical devices comprising a component having a shape profile corresponding to a tissue surface. Although specific reference is made to a transducer assembly for placement in an ear canal of a user, embodiments of the present invention can be used with many devices and tissues, such as dental tissue, teeth, orthopedic tissue, bones, joints, ocular tissue, eyes and combinations thereof. In many embodiments, the vapor deposition and polymerization can be used to manufacture a component of a hearing system used to transmit sound to a user.

Embodiments of the present invention provide improved methods of manufacturing suitable for use with hearing devices so as to overcome at least some of the aforementioned limitations of the prior methods and apparatus. In many embodiments, a vapor deposition process can be used to make a support structure having a shape profile corresponding to a tissue surface, such as a retention structure having a shape profile corresponding to one or more of the eardrum, the eardrum annulus, or a skin of the ear canal. The retention structure can be deflectable to provide comfort, resilient to

provide support, and may comprise a component of an output transducer assembly to couple to the eardrum of the user. The resilient retention structure may comprise an anatomically accurate shape profile corresponding to a portion of the ear, such that the resilient retention structure provides mechanical stability for the output transducer assembly and comfort for the user when worn for an extended time. The output transducer assembly comprising the retention structure having the shape profile can be placed in the ear of the user, and can be comfortably worn for months and in many embodiments worn comfortably and maintain functionality for years.

The output transducer assembly may comprise a support having stiffness greater than a stiffness of the resilient retention structure, and the stiff support may comprise one or more of arms, a rigid frame, or a chassis. The support stiffness greater than the retention structure can maintain alignment of the components coupled to the support, such that appropriate amounts of force can be used to urge a coupling structure against the eardrum so as to couple the transducer to the eardrum with decreased autophony. The stiff support can be coupled to at least one spring so as to provide appropriate amounts of force to the eardrum with the coupling structure and to inhibit deformation of the device when placed in the loaded configuration for the extended time. The deflectable retention structure may provide a narrow profile configuration when advanced into the ear canal and a wide profile configuration when placed in the ear canal, and the stiff support can be used to deflect and advance the retention structure along the ear canal. A photodetector and an output transducer can be coupled to the support, such that the transducer assembly can be mechanically secure and stable when placed within the anatomy of the ear canal of the user. The support can have an elastomeric bumper structure placed thereon so as to protect the eardrum and skin when the support and retention structure are coupled to the eardrum and skin. Alternatively, the stiff support can be placed on the layer of vapor deposited polymer and affixed to the layer, such that the vapor deposited layer contacts the eardrum or skin. A second layer can be deposited on the first layer when the first layer has been placed on the first layer to situate the stiff support structure between the layers. The stiff support may comprise a part comprising arms, an intermediate portion extending between the arms, and at least one spring, such that the stiff support part can be placed an affixed to the retention structure.

The output transducer assembly may comprise a biasing structure coupled to the support to adjust a position of a coupling structure that engages the eardrum. The at least one spring can be coupled to the support and the transducer, so as to support the transducer and the coupling structure in an unloaded configuration. The biasing structure can be configured to adjust the unloaded position of the coupling structure prior to placement. The at least one spring can be coupled to the coupling structure such that the coupling structure can move about one millimeter from the unloaded position in response to the eardrum loading the coupling structure. The spring can be configured to provide an appropriate force to the coupling structure engage the eardrum and to inhibit occlusion when the coupling structure comprises either the unloaded configuration or the configuration with displacement in response to eardrum movement of about one millimeter. Alternatively or in combination, the biasing structure may comprise a dynamic biasing structure having a biasing transducer coupled to the at least one spring to urge the coupling structure into engagement with the eardrum in response to a signal to the output transducer.

A vapor deposition and polymerization process can be used to provide a strong and secure connection extending between

5

the support and the resilient retention structure. The vapor deposition process may comprise a poly(p-xylylene) polymer deposited on the support and the resilient retention structure may comprise a layer of vapor deposited poly(p-xylylene) polymer adhered to the support. The vapor-deposited Poly(p-xylylene) polymer may also adhere to the elastomeric bumper structure material such as a silicone material. The vapor deposition of the layer of material to form the retention structure can provide a uniform accurate shape profile in a semi-automated manner that can increase reproducibility and accuracy with decreased labor so as to improve coupling and hearing for many people.

The vapor deposition process can be used to manufacture the output transducer assembly with a positive mold of the ear canal of the user. The positive mold may comprise an optically transmissive material, and a release agent may coat an inner surface of the positive mold. The release agent may comprise a hydrophilic material such that the coating can be removed from the mold with water. The layer can be formed with vapor deposition within the positive mold. The components can be placed on the layer. The positive mold may comprise a transparent material, such that the placement of the components within the positive mold can be visualized. A second layer can be vapor deposited over the first layer to affix the components to the first layer and the second layer.

The retention structure may comprise a deflection to receive epithelium. The retention structure may comprise a surface to contact a surface of an epithelial tissue. The epithelial tissue may migrate under the retention structure when placed for an extended time. The deflection of the retention structure surface can be located near an edge of the retention structure and extend away from the surface of the tissue so as to inhibit accumulation of epithelial tissue near the edge of the retention structure. The deflected edge can be oriented toward a source of epithelium such as the umbo when the retention structure is placed in the ear canal.

The output transducer assembly may comprise an oleophobic coating to inhibit autophony and accumulation of oil on components of the assembly.

The retention structure can be configured in many ways to permit viewing of the retention structure and the eardrum. The retention structure may comprise a transparent material, which can allow a clinician to evaluate coupling of the retention structure to the tissue of the ear canal. In many embodiments, the ear canal comprises an opening, which allows a clinician to view at least a portion of the eardrum and evaluate placement of the output transducer assembly. In many embodiments, the retention structure is dimensioned and shaped to avoid extending into the anterior sulcus to improve visibility when placed, and the retention structure may extend substantially around an outer portion of the eardrum such as the eardrum annulus so as to define an aperture through which the eardrum can be viewed. Alternatively, the retention structure may extend around no more than a portion of the annulus. In many embodiments, the retention structure extends to a viewable location an opposite side of the ear canal, so as to limit the depth of placement in the ear canal and facilitate the clinician viewing of the retention structure. The visibility of the retention structure can be increased substantially when the retention structure extends around no more than a portion of the annulus and also extends to a portion of the ear canal opposite the eardrum. The wall opposite the eardrum can support the transducer with the portion opposite the annulus so as to improve coupling. The portions of the retention structure extending to the canal wall opposite the eardrum and

6

around no more than a portion of the annulus can be easily viewed and may define a viewing aperture through which the eardrum can be viewed.

In a first aspect, embodiments provide a method of making a support for placement on a tissue of a user. A material of a vapor is deposited on a substrate to form the support. The substrate has a shape profile corresponding to the tissue, and the support is separated from the substrate.

In many embodiments, the material is polymerized on the substrate to form the support having the shape profile.

In many embodiments, a solid layer of the material forms having the shape profile and wherein the support comprises the solid layer when separated from the substrate.

In many embodiments, the release agent is disposed on the substrate between the substrate and the support when the vapor is deposited on the release agent to form the support. The release agent may comprise one or more of one or more of PEG, a hydrophilic coating, a surface treatment such as corona discharge, a surfactant, a wax, hydrophilic wax, or petroleum jelly. The release agent may comprise a solid when the vapor is deposited at an ambient temperature, and the release agent can be heated so as to comprise a liquid when the support is separated from the substrate. The release agent may have a first surface oriented toward the substrate and in contact with the substrate and a second surface oriented away from the substrate so as to contact the support, and the second surface can be smoother than the first surface such that the release agent may also comprise a smoothing agent.

In many embodiments, the release agent comprises a water soluble material such as water soluble polymer or a surfactant.

In many embodiments, the material of the vapor comprises monomer molecules having aromatic rings and wherein the monomer molecules are polymerized to form a polymer on the substrate having the aromatic rings.

In many embodiments, the material of the vapor comprises Poly(p-xylylene) polymer and the slip agent comprises petroleum jelly.

In many embodiments, the material of the vapor comprises polyvinyl alcohol (hereinafter "PVA") or polyvinyl alcohol hydrogel (hereinafter "PVA-H").

In many embodiments, the material of the vapor can be deposited with one or more of thermal deposition, radio frequency deposition, or plasma deposition.

In many embodiments, the shape profile of the substrate corresponds to a shape profile of a tissue surface, and the shape profile comprises a portion having a deflection away from the shape profile of the tissue surface so as to provide a deflection in the support away from a surface of the tissue. The tissue surface may comprise an epithelial surface, and the deflection is configured to extend away from the epithelial surface when the support is placed. The deflection can be oriented on the support so as to receive the advancing epithelium under the deflection.

In many embodiments, the substrate comprises a portion of an optically transmissive positive mold of the tissue, and components of a hearing device are placed in the mold with visualization of the components through the optically transmissive positive mold.

In many embodiments, the tissue comprises at least a portion of an ear canal or a tympanic membrane of a user. A negative mold is made of the at least the portion or the tympanic membrane. The negative mold is coated with an optically transmissive material. The coating is cured. The cured coating is placed in a container comprising an optically transmissive flowable material. The optically transmissive flowable material is cured to form a positive mold, the cured

coating inhibits deformation of the negative mold when the optically transmissive flowable material is cured.

In many embodiments, the support comprises a first layer of the polymerizable material and a second layer of the polymerizable material, and components of a hearing device are situated between the first layer and the second layer.

In many embodiments, components of the hearing device are placed on the first layer and the second layer deposited on the components placed on the first layer and the first layer.

In many embodiments, an oleophobic coating is placed on one or more of the first transducer or the retention structure.

In many embodiments, the support comprises a retention structure shaped for placement in an ear canal of a user, and a part is placed. The part comprises a support component comprising arms, and the arms are affixed to the retention structure.

In many embodiments, the vapor is deposited on the part to affix the part to the retention structure.

In many embodiments, a projection extends from the part to place the retention structure in the ear canal of the user.

In many embodiments, the support comprises a retention structure shaped for placement in an ear canal of a user, and the support is cut along a portion toward an eardrum and a portion toward an opening of the ear canal so as to define an opening to couple a transducer to an eardrum of the user. The portion toward the eardrum may correspond to an anterior sulcus of the ear canal, and the portion toward the opening of the ear canal may correspond to the bony part of the ear canal. The portion toward the eardrum can be cut to limit insertion depth such that a clinician can view the portion toward the eardrum when placed.

In another aspect, embodiments provide an apparatus for placement with a user, the apparatus comprises a transducer and a retention structure. The retention structure comprises a layer of polymer having a shape profile corresponding to a tissue of the user to couple the transducer to the user.

In many embodiments, the retention structure comprises a curved portion having an inner surface toward an eardrum when placed, and the curved portion couples to an ear canal wall oriented toward the eardrum when placed to couple a transducer to the eardrum. The curved portion may couple to the ear canal on a first side of the ear canal opposite the eardrum, and a second portion of the retention structure may couple to a second side of the ear canal opposite the first side to hold the retention structure in the ear canal. The curved portion and the second portion can be connected so as to define an aperture extending therebetween to view at least a portion of the eardrum when the curved portion couples to the first side of the ear canal and the second portion couples to the second side.

In many embodiments, the support comprises a first layer of a polymerizable material and a second layer of a polymerizable material and wherein components of a hearing device are situated between the first layer and the second layer.

In many embodiments, an oleophobic layer is coated on one or more of the first transducer or the retention structure.

In many embodiments, the tissue comprises an eardrum having a first resistance to deflection and a bony portion of the ear canal having a second resistance to deflection greater than the first resistance, and the layer comprises a resistance to deflection greater than the eardrum and less than the bony portion of the ear canal.

In many embodiments, the layer comprises a material having a thickness to resist deflection away from the shape profile and wherein the layer comprises the shape profile in an unloaded configuration.

In many embodiments, the transducer couples to a tissue structure having a resistance to deflection, and the layer comprises a resistance to deflection greater than the tissue structure.

In many embodiments, the layer comprises a thickness within a range from about 1 μm to about 100 μm . The layer may comprise a substantially uniform thickness to provide the resistance to deflection and the shape profile in the unloaded configuration. The thickness of the layer can be uniform to within about ± 25 percent of an average thickness to provide the shape profile.

In many embodiments, the retention structure comprises a resilient retention structure to maintain a location of the transducer when coupled to the user.

In many embodiments, wherein the resilient retention structure is sized to fit within an ear canal of the user and contact one or more of a skin of the ear canal or an eardrum annulus so as to maintain a location of the transducer when placed in the ear canal.

In many embodiments, the retention structure comprises a layer composed of one or more of poly(chloro-p-xylene), poly(p-xylene), poly(dichloro-p-xylene), or fluorinated poly(p-xylene).

In many embodiments, the apparatus comprises a support to couple the transducer to the retention structure. The support may comprise a stiff support having a pair of curved arms extending substantially along outer portions of the retention structure, and the curved arms can be configured to deflect inward with the retention structure when the support is advanced along an ear canal of the user.

In many embodiments, the transducer is supported with at least one spring extending between the support and the transducer. The support may comprise an intermediate portion extending between the arms, and the at least one spring may extend from the intermediate portion to the transducer to support the transducer. The at least one spring comprises a cantilever extending from the intermediate portion to the transducer to support the transducer. The at least one spring, the arms, and the intermediate section may comprise a single part manufactured with a material.

In many embodiments, a projection extends from the single part to place the retention structure in the ear canal of the user. The single part may comprise one or more of a molded part, an injection molded part, or a machined part.

In many embodiments, the at least one spring comprises a pair of springs, a first spring of the pair coupled to a first side of the transducer, a second spring of the pair coupled to a second side of the transducer opposite the first side, so as to support the transducer with springs coupled to the support on opposing sides.

In many embodiments, the apparatus further comprises a coupling structure shaped to engage the eardrum to vibrate the eardrum, and a biasing structure to adjust an offset between the support and the coupling structure.

In many embodiments, the biasing structure is configured to adjust a separation distance extending between a lower surface of the retention structure and a lower surface of the coupling structure in an unloaded configuration, and the coupling structure is coupled to the support with at least one spring such that the separation distance decreases when the coupling structure contacts the eardrum.

In many embodiments, the biasing structure, the support, and the coupling structure are coupled to the at least one spring so as to provide about 8 mm or more of deflection of the coupling structure toward the support when the coupling structure engages the eardrum in a loaded configuration.

In many embodiments, the biasing structure is configured to adjust a position of the transducer in relation so as to the support to position the coupling structure with the offset.

In many embodiments, a photodetector attached to a casing of the transducer. The transducer can be configured to pivot relative to the support, and the photodetector pivots with the transducer.

In many embodiments, the shape profile corresponds to a shape profile of a tissue surface, and the shape profile comprises a portion having a deflection away from the shape profile of the tissue surface. The tissue surface may comprise an epithelial surface, and the deflection extends away from the epithelial surface when the support is placed. The deflection may be oriented on the support so as to receive advancing epithelium under the deflection.

In another aspect, embodiments provide a method of manufacturing an output transducer assembly for placement within a canal of an ear of a user, in which the user has an eardrum. A retention structure is provided that is sized to fit within the ear canal and contact one or more of a skin of the ear canal or an eardrum annulus. A support is coupled to the retention structure, and the support is sized to fit within the ear canal and defines an aperture. A transducer is coupled to the support, and the transducer comprises an elongate vibratory structure. The transducer is coupled to the support such that the elongate vibratory structure extends through the aperture to couple the transducer to the eardrum when the elongate structure is placed within the ear canal.

In many embodiments, the retention structure has a shape profile based on a mold corresponding to an anterior sulcus of the ear canal of the user.

In many embodiments, the retention structure comprises Poly(p-xylylene) polymer.

In many embodiments, the retention structure comprises a substantially annular retention structure and wherein the substantially annular retention structure defines an inner region, and the inner region is aligned with the aperture when the support is coupled to the retention structure such that the vibratory structure extends through the inner region and the aperture.

In many embodiments, the retention structure comprise a resilient retention structure and wherein the resilient retention structure has a first configuration comprising first dimensions so as to contact the eardrum annulus when placed, and the resilient retention structure has a second configuration when compressed. The second configuration comprises second dimensions such that the retention structure is sized to move along the ear canal for placement. Upon removal of compression the retention structure returns from the second configuration substantially to the first configuration.

In many embodiments, the support comprises an elongate dimension and rigidity greater than the retention structure and wherein the retention structure comprises a first portion sized to fit an anterior sulcus of the ear canal, and the elongate dimension is aligned with the first portion such that the retention structure can be compressed when moved along the ear canal.

In many embodiments, the support comprises a rigid sheet material cut so as to define the aperture and an outer perimeter of the support.

In many embodiments, the transducer comprises a housing having a first end and a second end and wherein the vibratory structure extends through a first end of the housing and a pair of coil springs is coupled to the second end of the housing. The pair extends between the second end and the support such that transducer is supported with the springs, and the vibratory structure is urged through the aperture when the retention

structure is placed within the ear canal. Each of the coil springs may have a pivot axis extending through the coil and the pivot axis of said each coil can extend through the other coil such that the transducer pivots about a pivot axis extending through the coils to couple to the eardrum when the vibratory structure extends through the aperture. The aperture can be sized to receive the housing of the transducer assembly such that the transducer assembly can pivot through the aperture to increase the dynamic range of the pivoting of the transducer to couple to the eardrum.

In many embodiments, a photo transducer is coupled to the support and the transducer.

In another aspect, embodiments provide an output transducer assembly for placement in an ear of a user. A retention structure is sized to fit within the ear canal and contact one or more of a skin of the ear canal or an eardrum annulus. A support is coupled to the retention structure, and the support is sized to fit within the ear canal and defines an aperture. A transducer is coupled to the support. The transducer comprises an elongate vibratory structure, and the elongate vibratory structure extends through the aperture to couple the transducer to the eardrum when the elongate structure is placed within the ear canal.

In many embodiments, the aperture is sized to receive a housing of the transducer such that the housing extends at least partially through the aperture when the elongate vibratory structure is coupled to the eardrum.

In another aspect, embodiments provide a method of placing output transducer assembly in an ear of a user. A retention structure is compressed from a first wide profile configuration to a narrow profile configuration. The wide profile configuration is sized to fit within the ear canal and contact one or more of a skin of the ear canal or an eardrum annulus, and the narrow profile configuration sized to advance along the ear canal. A support coupled to the retention structure is advanced along the ear canal when the retention structure comprises the narrow profile configuration. The support is sized to fit within the ear canal and defines an aperture. A transducer is coupled to the support, and the transducer comprising an elongate vibratory structure. The elongate vibratory structure extends through the aperture to couple the transducer to the eardrum when the elongate structure is placed within the ear canal.

In many embodiments, the retention structure comprises a resilient retention structure in which the wide profile configuration has a shape profile corresponding to a portion of the ear canal of the user. The resilient retention structure expands from the narrow profile configuration to the wide profile configuration when advanced along the ear canal. The support comprises a rigid support having a substantially constant profile when the resilient retention structure is compressed and when the resilient retention structure is expanded.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a hearing aid system configured to transmit electromagnetic energy to an output transducer assembly, in accordance with embodiments of the present invention;

FIGS. 2A and 2B show isometric and top views, respectively, of the output transducer assembly in accordance with embodiments of the present invention;

FIG. 3-1 shows an injection step, in accordance with embodiments of the present invention;

FIG. 3-2 shows a removal step, in accordance with embodiments of the present invention;

FIG. 3-3 shows a coating step, in accordance with embodiments of the present invention;

11

FIG. 3-4 shows an embedding step, in accordance with embodiments of the present invention;

FIG. 3-5 shows a machining step, in accordance with embodiments of the present invention;

FIG. 3-6 shows a submersion step, in accordance with embodiments of the present invention;

FIG. 3-7 shows a pretreatment step of coating a support, in accordance with embodiments of the present invention;

FIG. 3-8 shows a step of coupling the coated support to the mold, in accordance with embodiments of the present invention;

FIG. 3-9 shows vapor deposition of monomer to the mold to form a layer Parylene™ polymer film, in accordance with embodiments of the present invention;

FIG. 3-9A shows the structure Parylene™, in accordance with embodiments of the present invention;

FIG. 3-9B shows the structure Parylene™ C, in accordance with embodiments of the present invention;

FIG. 3-10 shows a top view of the mold and cutting of the layer of Parylene™ polymer film to prepare the film for removal from the mold, in accordance with embodiments of the present invention;

FIG. 3-11 shows the layer of Parylene™ polymer film removed from the mold and suitable for supporting with a backing material, in accordance with embodiments of the present invention;

FIG. 3-12 shows cutting the layer with a backing material, in accordance with embodiments of the present invention;

FIG. 4 shows a method of assembling an output transducer assembly, in accordance with embodiments of the present invention;

FIGS. 5A and 5B show top and bottom views, respectively, of a retention structure comprising a stiff support extending along a portion of the retention structure, in accordance with embodiments of the present invention;

FIG. 5A1 shows an integrated component comprising the stiff support and resilient spring, in accordance with embodiments of the present invention;

FIGS. 5A2 and 5A3 show cross-sectional views of the resilient spring and the stiff support, respectively, in accordance with embodiments of the present invention;

FIGS. 5A4 and 5A5 show a top view and a side view, respectively, of a support comprising a graspable projection to place the output transducer assembly in the ear canal, in accordance with embodiments of the present invention;

FIG. 5B1 shows a lower surface support positioned a distance beneath the lower surface of retention structure, in accordance with embodiments of the present invention;

FIG. 5B2 shows a component of the output transducer assembly retained between a first layer and a second layer, in accordance with embodiments of the present invention;

FIGS. 6A and 6B show side and top views, respectively, of a resilient tubular retention structure comprising a stiff support extending along a portion of the resilient tubular retention structure, in accordance with embodiments of the present invention;

FIGS. 7A, 7B and 7C show side, top and front views, respectively, of a resilient retention structure comprising an arcuate portion and a stiff support extending along a portion of resilient retention structure, in accordance with embodiments of the present invention;

FIG. 8A shows components of an output transducer assembly placed in a transparent block of material comprising a positive mold of the ear canal and eardrum of a patient, in accordance with embodiments of the present invention;

12

FIG. 8B shows a transducer configured to receive a vapor deposition coating, in accordance with embodiments of the present invention;

FIG. 8C shows the transducer of FIG. 8B with a deposited layer, in accordance with embodiments of the present invention;

FIG. 8D shows the transducer of FIG. 8B with a blocking material to inhibit formation of the deposited layer on the reed of the transducer, in accordance with embodiments of the present invention;

FIG. 8E shows the transducer of FIG. 8B with a blocking material placed over a bellows to inhibit formation of the deposited layer on the bellows of the transducer, in accordance with embodiments of the present invention;

FIG. 8F shows an oleophobic layer deposited on the output transducer, in accordance with embodiments of the present invention;

FIG. 9A shows a retention structure comprising an curved portion shaped to extend along a surface of the bony portion of the ear canal opposite an eardrum when placed, in which the curved portion is coupled to a transducer with a structure extending from the curved portion to the transducer to couple the transducer with the eardrum, in accordance with embodiments of the present invention;

FIG. 9B shows a dynamic biasing system, in accordance with embodiments of the present invention;

FIG. 10A shows laser sculpting of a negative mold to provide a deflection of the epithelium contacting surface of the retention structure to receive migrating epithelium, in accordance with embodiments of the present invention;

FIG. 10B shows a deflection of the epithelium contacting surface of the retention structure to receive migrating epithelium, in accordance with embodiments of the present invention;

FIG. 10C shows a epithelium migrating under the deflection of FIG. 10B, in accordance with embodiments of the present invention;

FIG. 11 shows a transducer to deflect the output transducer toward the eardrum and couple the output transducer to the eardrum in response to the output signal, in accordance with embodiments of the present invention; and

FIG. 12 shows a retention structure configured for placement in the middle ear supporting an acoustic hearing aid, in accordance with embodiments of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Embodiments of the present invention are well suited to improve communication among people, for example with cellular communication and as a hearing aid with decreased invasiveness that can be readily placed by a health care provider.

As used herein, light encompasses electromagnetic radiation having wavelengths within the visible, infrared and ultraviolet regions of the electromagnetic spectrum.

In many embodiments, the hearing device comprises a photonic hearing device, in which sound is transmitted with photons having energy, such that the signal transmitted to the ear can be encoded with transmitted light.

As used herein, an emitter encompasses a source that radiates electromagnetic radiation and a light emitter encompasses a light source that emits light.

As used herein like references numerals and letters indicate similar elements having similar structure, function and methods of use.

As used herein a surfactant encompasses a wetting agent capable of reducing the surface tension of a liquid.

As used herein, scientific notation may comprises known E notation known to persons of ordinary skill in the art using computer programs such as spreadsheets, for example. The exponential value $A \times 10^{-B}$ can be expressed as Ae-B, or AE-B, for example.

As used herein reference to a chemical structure encompasses the chemical structure and derivatives thereof.

Transducer assemblies that couple the transducer to the eardrum so as to decrease occlusion are described in U.S. Pat. App. Nos. 61,217,801, filed Jun. 3, 2009, entitled “Balanced Armature Device and Methods for Hearing”; and PCT/US2009/057719, filed 21 Sep. 2009, entitled “Balanced Armature Device and Methods for Hearing”, published as WO 2010/033933, the full disclosures of which are incorporated herein by reference and suitable for combination in accordance with embodiments as described herein.

FIG. 1 shows a hearing aid system 10 configured to transmit electromagnetic energy to an output transducer assembly 100 positioned in the ear canal EC of the user. The ear comprises an external ear, a middle ear ME and an inner ear. The external ear comprises a Pinna P and an ear canal EC and is bounded medially by an eardrum TM. Ear canal EC extends medially from pinna P to eardrum TM. Ear canal EC is at least partially defined by a skin SK disposed along the surface of the ear canal. The eardrum TM comprises an annulus TMA that extends circumferentially around a majority of the eardrum to hold the eardrum in place. The middle ear ME is disposed between eardrum TM of the ear and a cochlea CO of the ear. The middle ear ME comprises the ossicles OS to couple the eardrum TM to cochlea CO. The ossicles OS comprise an incus IN, a malleus ML and a stapes ST. The malleus ML is connected to the eardrum TM and the stapes ST is connected to an oval window OW, with the incus IN disposed between the malleus ML and stapes ST. Stapes ST is coupled to the oval window OW so as to conduct sound from the middle ear to the cochlea.

The hearing system 10 includes an input transducer assembly 20 and an output transducer assembly 100 to transmit sound to the user. Hearing system 10 may comprise a behind the ear unit BTE. Behind the ear unit BTE may comprise many components of system 10 such as a speech processor, battery, wireless transmission circuitry and input transducer assembly 10. Behind the ear unit BTE may comprise many component as described in U.S. Pat. Pub. Nos. 2007/0100197, entitled “Output transducers for hearing systems”; and 2006/0251278, entitled “Hearing system having improved high frequency response”, the full disclosures of which are incorporated herein by reference and may be suitable for combination in accordance with some embodiments of the present invention. The input transducer assembly 20 can be located at least partially behind the pinna P, although the input transducer assembly may be located at many sites. For example, the input transducer assembly may be located substantially within the ear canal, as described in U.S. Pub. No. 2006/0251278. The input transducer assembly may comprise a blue tooth connection to couple to a cell phone and may comprise, for example, components of the commercially available Sound ID 300, available from Sound ID of Palo Alto, Calif. The output transducer assembly 100 may comprise components to receive the light energy and vibrate the eardrum in response to light energy. An example of an output transducer assembly having components suitable for combination in accordance with embodiments as described herein is described in U.S. Pat. App. Nos. 61,217,801, filed Jun. 3, 2009, entitled “Balanced Armature Device and Methods for Hearing” and PCT/US2009/057719, filed 21 Sep. 2009, Bal-

anced Armature Device and Methods for Hearing”, the full disclosure of which is incorporated herein by reference.

The input transducer assembly 20 can receive a sound input, for example an audio sound. With hearing aids for hearing impaired individuals, the input can be ambient sound. The input transducer assembly comprises at least one input transducer, for example a microphone 22. Microphone 22 can be positioned in many locations such as behind the ear, as appropriate. Microphone 22 is shown positioned to detect spatial localization cues from the ambient sound, such that the user can determine where a speaker is located based on the transmitted sound. The pinna P of the ear can diffract sound waves toward the ear canal opening such that sound localization cues can be detected with frequencies above at least about 4 kHz. The sound localization cues can be detected when the microphone is positioned within ear canal EC and also when the microphone is positioned outside the ear canal EC and within about 5 mm of the ear canal opening. The at least one input transducer may comprise a second microphone located away from the ear canal and the ear canal opening, for example positioned on the behind the ear unit BTE. The input transducer assembly can include a suitable amplifier or other electronic interface. In some embodiments, the input may comprise an electronic sound signal from a sound producing or receiving device, such as a telephone, a cellular telephone, a Bluetooth connection, a radio, a digital audio unit, and the like.

In many embodiments, at least a first microphone can be positioned in an ear canal or near an opening of the ear canal to measure high frequency sound above at least about one 4 kHz comprising spatial localization cues. A second microphone can be positioned away from the ear canal and the ear canal opening to measure at least low frequency sound below about 4 kHz. This configuration may decrease feedback to the user, as described in U.S. Pat. Pub. No. US 2009/0097681, the full disclosure of which is incorporated herein by reference and may be suitable for combination in accordance with embodiments of the present invention.

Input transducer assembly 20 includes a signal output source 12 which may comprise a light source such as an LED or a laser diode, an electromagnet, an RF source, or the like. The signal output source can produce an output based on the sound input. Output transducer assembly 100 can receive the output from input transducer assembly 20 and can produce mechanical vibrations in response. Output transducer assembly 100 comprises a sound transducer and may comprise at least one of a coil, a magnet, a magnetostrictive element, a photostrictive element, or a piezoelectric element, for example. For example, the output transducer assembly 100 can be coupled input transducer assembly 20 comprising an elongate flexible support having a coil supported thereon for insertion into the ear canal as described in U.S. Pat. Pub. No. 2009/0092271, entitled “Energy Delivery and Microphone Placement Methods for Improved Comfort in an Open Canal Hearing Aid”, the full disclosure of which is incorporated herein by reference and may be suitable for combination in accordance with some embodiments of the present invention. Alternatively or in combination, the input transducer assembly 20 may comprise a light source coupled to a fiber optic, for example as described in U.S. Pat. Pub. No. 2006/0189841 entitled, “Systems and Methods for Photo-Mechanical Hearing Transduction”, the full disclosure of which is incorporated herein by reference and may be suitable for combination in accordance with some embodiments of the present invention. The light source of the input transducer assembly 20 may also be positioned in the ear canal, and the output transducer assembly and the BTE circuitry components may be located

15

within the ear canal so as to fit within the ear canal. When properly coupled to the subject's hearing transduction pathway, the mechanical vibrations caused by output transducer assembly 100 can induce neural impulses in the subject which can be interpreted by the subject as the original sound input.

FIGS. 2A and 2B show isometric and top views, respectively, of the output transducer assembly 100. Output transducer assembly 100 comprises a retention structure 110, a support 120, a transducer 130, at least one spring 140 and a photodetector 150. Retention structure 110 is sized to couple to the eardrum annulus TMA and at least a portion of the anterior sulcus AS of the ear canal EC. Retention structure 110 comprises an aperture 110A. Aperture 110A is sized to receive transducer 130.

The retention structure 110 can be sized to the user and may comprise one or more of an o-ring, a c-ring, a molded structure, or a structure having a shape profile so as to correspond to a mold of the ear of the user. For example retention structure 110 may comprise a polymer layer 115 coated on a positive mold of a user, such as an elastomer or other polymer. Alternatively or in combination, retention structure 110 may comprise a layer 115 of material formed with vapor deposition on a positive mold of the user, as described herein. Retention structure 110 may comprise a resilient retention structure such that the retention structure can be compressed radially inward as indicated by arrows 102 from an expanded wide profile configuration to a narrow profile configuration when passing through the ear canal and subsequently expand to the wide profile configuration when placed on one or more of the eardrum, the eardrum annulus, or the skin of the ear canal.

The retention structure 110 may comprise a shape profile corresponding to anatomical structures that define the ear canal. For example, the retention structure 110 may comprise a first end 112 corresponding to a shape profile of the anterior sulcus AS of the ear canal and the anterior portion of the eardrum annulus TMA. The first end 112 may comprise an end portion having a convex shape profile, for example a nose, so as to fit the anterior sulcus and so as to facilitate advancement of the first end 112 into the anterior sulcus. The retention structure 110 may comprise a second end 114 having a shape profile corresponding to the posterior portion of eardrum annulus TMA.

The support 120 may comprise a frame, or chassis, so as to support the components connected to support 120. Support 120 may comprise a rigid material and can be coupled to the retention structure 110, the transducer 130, the at least one spring 140 and the photodetector 150. The support 120 may comprise a biocompatible metal such as stainless steel so as to support the retention structure 110, the transducer 130, the at least one spring 140 and the photodetector 150. For example, support 120 may comprise cut sheet metal material. Alternatively, support 120 may comprise injection molded biocompatible plastic. The support 120 may comprise an elastomeric bumper structure 122 extending between the support and the retention structure, so as to couple the support to the retention structure with the elastomeric bumper. The elastomeric bumper structure 122 can also extend between the support 120 and the eardrum, such that the elastomeric bumper structure 122 contacts the eardrum TM and protects the eardrum TM from the rigid support 120. The support 120 may define an aperture 120A formed thereon. The aperture 120A can be sized so as to receive the balanced armature transducer 130, for example such that the housing of the balanced armature transducer 130 can extend at least partially through the aperture 120A when the balanced armature transducer is coupled to the eardrum TM. The support 120 may comprise an elongate

16

dimension such that support 120 can be passed through the ear canal EC without substantial deformation when advanced along an axis corresponding to the elongate dimension, such that support 120 may comprise a substantially rigid material and thickness.

The transducer 130 comprises structures to couple to the eardrum when the retention structure 120 contacts one or more of the eardrum, the eardrum annulus, or the skin of the ear canal. The transducer 130 may comprise a balanced armature transducer having a housing and a vibratory reed 132 extending through the housing of the transducer. The vibratory reed 132 is affixed to an extension 134, for example a post, and an inner soft coupling structure 136. The soft coupling structure 136 has a convex surface that contacts the eardrum TM and vibrates the eardrum TM. The soft coupling structure 136 may comprise an elastomer such as silicone elastomer. The soft coupling structure 136 can be anatomically customized to the anatomy of the ear of the user. For example, the soft coupling structure 136 can be customized based a shape profile of the ear of the user, such as from a mold of the ear of the user as described herein.

At least one spring 140 can be connected to the support 120 and the transducer 130, so as to support the transducer 130. The at least one spring 140 may comprise a first spring 122 and a second spring 124, in which each spring is connected to opposing sides of a first end of transducer 130. The springs may comprise coil springs having a first end attached to support 120 and a second end attached to a housing of transducer 130 or a mount affixed to the housing of the transducer 130, such that the coil springs pivot the transducer about axes 140A of the coils of the coil springs and resiliently urge the transducer toward the eardrum when the retention structure contacts one or more of the eardrum, the eardrum annulus, or the skin of the ear canal. The support 120 may comprise a tube sized to receiving an end of the at least one spring 140, so as to couple the at least one spring to support 120.

A photodetector 150 can be coupled to the support 120. A bracket mount 152 can extend substantially around photodetector 150. An arm 154 extend between support 120 and bracket 152 so as to support photodetector 150 with an orientation relative to support 120 when placed in the ear canal EC. The arm 154 may comprise a ball portion so as to couple to support 120 with a ball-joint. The photodetector 150 can be coupled to transducer 130 so as to driven transducer 130 with electrical energy in response to the light energy signal from the output transducer assembly.

Resilient retention structure 110 can be resiliently deformed when inserted into the ear canal EC. The retention structure 110 can be compressed radially inward along the pivot axes 140A of the coil springs such that the retention structure 110 is compressed as indicated by arrows 102 from a wide profile configuration having a first width 110W1 to an elongate narrow profile configuration having a second width 110W2 when advanced along the ear canal EC as indicated by arrow 104 and when removed from the ear canal as indicated by arrow 106. The elongate narrow profile configuration may comprise an elongate dimension extending along an elongate axis corresponding to an elongate dimension of support 120 and aperture 120A. The elongate narrow profile configuration may comprise a shorter dimension corresponding to a width 120W of the support 120 and aperture 120A along a shorter dimension. The retention structure 110 and support 120 can be passed through the ear canal EC for placement. The reed 132 of the balanced armature transducer 130 can be aligned substantially with the ear canal EC when the assembly 100 is advanced along the ear canal EC in the elongate narrow profile configuration having second width 110W2.

The support **120** may comprise a rigidity greater than the resilient retention structure **110**, such that the width **120W** remains substantially fixed when the resilient retention structure is compressed from the first configuration having width **110W1** to the second configuration having width **110W2**. The rigidity of support **120** greater than the resilient retention structure **110** can provide an intended amount of force to the eardrum TM when the inner soft coupling structure **136** couples to the eardrum, as the support **120** can maintain a substantially fixed shape with coupling of the at least one spring **140**. In many embodiments, the outer edges of the resilient retention structure **110** can be rolled upwards toward the side of the photodetector **150** so as to compress the resilient retention structure from the first configuration having width **110W1** to the second configuration having width **110W2**, such that the assembly can be easily advanced along the ear canal EC.

FIGS. **3-1** to **3-12** show a method **300** of making resilient retention structure **110** to hold an output transducer assembly in an ear of the user. The method **300** can be performed with one or more components of an apparatus **200** to make the resilient retention structure.

The process may comprise making an anatomically accurate mold and the vapor deposition polymerization of Parylene™ onto the mold. The mold can be constructed and prepared in such a way as to provide both the dimensional accuracy of the deposited Parylene™ and the removal the Parylene™ without distortion or strain. Additionally or alternatively, the Parylene™ may comprise an integrated structural member of the finished assembly, for example when the Parylene™ is deposited on the support **120**.

Formation of Negative Impression of Ear Canal

FIG. **3-1** shows an injection step **305**. The process for creating an anatomically accurate, uniformly thick, and flexible platform of biocompatible material can include with the creation of a representation of the human ear canal of interest. A physician can perform this procedure in a clinical setting. A biocompatible, two-part silicone **205**, for example polyvinyl siloxane hereinafter “PVS”, can be dispensed into the ear canal with a dispensing tube **207** such as a bent stainless steel tube. The PVS may include mineral oil or other oil, for example.

FIG. **3-2** shows a removal step **310**. The PVS can be allowed to fully cure, and then be removed. The resulting negative impression **210** comprises a dimensionally accurate, customized negative representation of the ear canal (herein “PVS impression”). The PVS impression may exude mineral oil, such that the impression can be easily removed from the ear canal and eardrum, and may form an anatomically accurate impression of the anterior sulcus AS.

Formation of Positive Mold of Ear Canal

The positive mold of the ear canal can be formed based on the negative impression in many ways. The positive mold may have a shape profile corresponding to the ear canal and may comprise a substrate for vapor deposition so as to form the resilient retention structure **110** having the shape profile corresponding to the ear canal, for example with a release agent disposed between the substrate and the vapor deposition layer **115**.

The material used to form the positive mold may comprise one or more of many materials such as an acrylate, an epoxy, a UV curable epoxy, a plaster, or a dental mold.

FIG. **3-3** shows a coating step **315**. The PVS negative impression **210** can be coated to create a thin rigid coating **215**, for example a shell, corresponding to the retention structure **110**. The thin coating may comprise a resin such as an acrylate resin, for example pattern resin comprising acrylate

such as polymethylmethacrylate (hereinafter “PMMA”), or a curable epoxy such as a UV curable epoxy.

FIG. **3-4** shows an embedding step **320**.

In order to provide both protection of the fragile thin shell and to provide a base for future handling, the PVS impression and coating **215** can be embedded in a small cylindrical cup **220** holding the same uncured pattern resin **222**, or a UV curable epoxy or acrylate which is allowed to cure. The two-step molding process can allow the use of a large cross-sectional mold for ease of handling without the dimensional changes that may result from the larger cross section when used to create the internal mold dimensions without the shell. The PVS impression **210** can then be removed from the mold. The finished positive mold **225** is then machined flat to provide a smooth, orthogonal surface for future handling of the Parylene™ part as described herein.

The pattern resin can be replaced with a low-shrinkage acrylate, for example a UV curable acrylate, such that the mold **225** can be created by embedding the PVS impression without forming the coating. The pattern resin may comprise a shrinkage of about 3% when cured, for example, and the low shrinkage acrylate may have a shrinkage less than 1%, such that the low shrinkage acrylate or epoxy can be used to form the mold without forming the shell, for example when the low shrinkage acrylate comprises a UV curable acrylate having a shrinkage of less than 1%.

Many materials can be used to form the mold from the PVS impression, and a person of ordinary skill in the art can determine many materials based on the teachings as described herein.

The cured pattern resin may comprise a positive mold **225** of the user’s ear canal.

FIG. **3-5** shows a machining step **325**. The cured pattern resin can be molded in a cylindrical mold. The negative impression **210** can be removed leaving a channel **229** corresponding to the ear canal, and the cured surface can be machined substantially orthogonal to the axis of the cylinder. The flat machined surface **227** can be used to handle the Parylene™ layer **115** when deposited on the mold **225** comprising the machined surface **227** and the cured coating **215**.

Passivation and Removal Agent Coating of Positive Mold

FIG. **3-6** shows a submersion step **330**, in accordance with embodiments of the method of FIG. **3**;

The pattern resin can be porous and may also contain volatile compounds (water, air, and organic vapors), which are a result of the polymerization reaction of the pattern resin. The volatile compounds can interfere with the deposition of Parylene™. The affect of the porous surface and the volatile compounds of the mold **225** can be decreased substantially with treatment prior to the vapor deposition and polymerization. Gases can be released from the surface of the mold when the Parylene™ layer is deposited in the vacuum chamber. In order to decrease this gas release, the mold material can be passivated prior to placement into the deposition chamber. This passivation process can substantially improve the quality of the Parylene™ finished “film”, as the number of pinholes formed by gas release are decreased, and the mold surface is smoothed with the release agent filling the pores near the deposition surface.

After removal of the PVS impression from the mold, the mold is placed into a bath of heated petroleum jelly such that the heated petroleum jelly comprises a liquid, for example heated to 100 degrees C. The bath of heated petroleum jelly can be provided with a container **234** comprising the heated petroleum jelly. The container **234** and mold can be placed in

a vacuum chamber **232** to provide low pressure and elevated temperature. The petroleum jelly may comprise the release agent **231**.

To remove the volatile compounds, a pre-deposition pump down (low pressure) time period of 2-4 hours can be used, and the mold **225** immersed in the bath can be placed in a vacuum of about 5 to 10 Torr for the 2-4 hour period, so as to inhibit formation of pinholes when the vapor is deposited and polymerized. The mold immersed in the bath can be heated when placed in the vacuum for the 2-4 hour period.

After the de-gas step is complete, the pressure is allowed to return to atmosphere while the mold remains submerged in the heated liquefied petroleum jelly. This allows many evacuated cavities within the mold **225** to be replaced with the liquefied petroleum jelly, such that petroleum jelly substantially fills the cavities and pores. The mold **225** can be removed, placed upside down so as to drain the liquefied petroleum jelly, and allowed to cool, so as to provide a substantially smooth surface to receive the Parylene™ precursor vapor and form the smooth coating and so as to release the formed coating from the smooth surface.

The petroleum jelly can be wiped at room temperature so as to provide the smooth surface for deposition of the Parylene™ precursor monomer and formation of the Parylene™.

The petroleum jelly, can be referred to as petrolatum or soft paraffin, CAS number 8009-03-8, is a semi-solid mixture of hydrocarbons, with a majority carbon numbers mainly higher than 25. The petroleum jelly may comprise a semi-solid mixture of hydrocarbons, having a melting-point usually within a few degrees of 75° C. (167° F.). Petroleum jelly can comprise a non-polar hydrocarbon that is hydrophobic (water-repelling) and insoluble in water.

Support Chassis Placement on Positive Mold

FIG. 3-7 shows a pretreatment step **335** of coating a support chassis.

After the mold **225** is removed from the petroleum jelly bath, the stainless steel support chassis can be placed into the mold. The chassis support **120** may comprise an internal support, or “skeleton”, for the placement and positioning of the transducer on the finished assembly, and the placement and orientation of the chassis can be important to the final performance and positional stability of the final activated assembly.

The positional stability of the chassis within the mold can be accomplished by a two-step bumperization of the support chassis using fluorosilicone. This thin region of fluorosilicone may comprise a cushion between the stainless steel chassis and the sensitive skin of the ear canal.

Prior to placement in the mold **225**, the support can be treated with a coating to protect the skin of the ear canal and the tympanic membrane of the user, and to improve adherence of the support **120** to the resilient retention structure **110**. For example, the support may comprise a metallic sheet material securely connected to the resilient Parylene™ retention structure.

The ends of support **120** can be coated in many ways. For example, each end of the support **120** can be dipped in fluorosilicone to form an elastomeric bumper **122** on each end of support **120**.

FIG. 3-8 shows a step **340** of coupling the coated support to the mold.

When the dip coated fluorosilicone is cured, a second coating of fluorosilicone can be applied to the ends of the support and the support can be placed in the mold. The second application **240** can be applied to each of the cured bumpers **122**. The support **120** can be inserted into the mold and aligned

with positive impression of the ear, for example aligned with the eardrum and anterior sulcus, so as to correspond with an intended alignment of the ear of the user. This second step application **240** of fluorosilicone can provide positional stability of the support in the mold and provide mechanical connection between the support and the Parylene™, for example with an increased surface area so as to improve adhesion. The elastomer comprising fluorosilicone disposed between the support **120** and resilient retention structure **110** can improve coupling, for example when the retention structure **110** is resiliently deformed and the support **120** retains a substantially fixed and rigid configuration when the retention structure and support are advanced along the ear canal. When the fluorosilicone application is complete and fully cured, the support chassis is very stable for the handling of the mold prior to and during the Parylene™ deposition process.

Parylene™ Deposition on Positive Mold and Support Chassis

FIG. 3-9 shows a step **345** of vapor deposition of monomer precursor to the mold to form a layer **115** of Parylene™ polymer film **250**. The vapor deposition may occur in a chamber **245**. The Parylene™ precursor monomer enters the mold through an opening **229** corresponding to a cross section of the ear canal EC. The vapor is deposited on support **120** and bumpers **122**. The bumpers **122** contact the release agent **231** deposited on the cured coating **215**. The vapor deposition and Parylene™ formation process can occur at an ambient room temperature, for example when the release agent comprising petroleum jelly is a solid.

FIG. 3-9A shows the structure of Parylene™, in accordance with embodiments. Parylene™ is the trade name for members of a unique genus of polymers, which includes one or more of Parylene™ N, Parylene™ C, or Parylene™ HT among others. The resilient retention structure **110** as described herein may comprise one or more commercially available Parylene™, such as one or more of Parylene™ N, Parylene™ C, or Parylene™ HT. The thickness of the retention structure **110** can be within a range from about 2 um to about 100 um, for example within a range from about 5 to 50 um, so as to provide the custom resilient retention structure **110** from the custom acrylic mold substrate such that the retention structure can be resiliently folded by the skin tissue of the ear canal when advanced along the ear canal. Work in relation to embodiments suggests that a Parylene™ thickness within a range from about 10 to 25 um can be preferred. The modulus of the deposited layer **115** comprising Parylene™ can be at least about 200,000 PSI, for example at least about 300 PSI. Based on the teachings described herein, a person of ordinary skill in the art can determine the modulus and thickness so as to provide resilient structure **110** with suitable rigidity for advancement along the ear canal and placement against one or more of the eardrum or skin as described herein.

Parylene™ comprises a polymer having aromatic rings connected with carbon-carbon bonds. Parylene™ can be formed with deposition of monomer molecules having the aromatic rings, so as to form the Parylene™ polymer having the aromatic rings.

In accordance with embodiments described herein, Parylene™ can be formed with deposition on a substrate corresponding to a shape profile of a tissue structure of the subject, and the formed Parylene™ can unexpectedly be separated from the substrate so as to provide the resilient support having the shape profile of the subject. Parylenes™ suitable for incorporation in accordance with embodiments as disclosed herein are described on the world wide web, for example on Wikipedia. (wikipedia.org/wiki/Parylene)

Parylene™ is the trademark for a variety of chemical vapor deposited poly(p-xylylene) based polymers and derivatives thereof that can be deposited on the substrate with a release agent to form the support. The Parylene™ may comprise one or more of Parylene™ A, Parylene™ C, Parylene™ D or Parylene™.

Parylene™ C and AF-4, SF, HT can be used for medical devices and may comprise an FDA accepted coating devices permanently implanted into the body.

FIG. 3-9B shows the structure of Parylene™ C. In many embodiments, the Parylene™ comprises Parylene™ C having a hydrogen atom of the benzene ring substituted with substituted chlorine, for example at the C1 location.

Parylene™ N is a polymer manufactured from di-p-xylylene, a dimer synthesized from p-xylylene. Di-p-xylylene, more properly known as [2.2]paracyclophane, can be made from p-xylylene in several steps involving bromination, amination and elimination.

Parylene™ N may comprise an unsubstituted molecule. Heating [2.2]paracyclophane under low pressure (0.01-1 Torr) conditions can give rise to a diradical species which polymerizes when deposited on a surface. The monomer can be in a gaseous phase until surface contact, such that the monomer can access the entire exposed surface.

There are many Parylene™ derivatives, Parylene™ N (hereinafter “N Poly(p-xylylene)”, hydrocarbon), Parylene™ C (hereinafter “poly(chloro-p-xylylene)”, one chlorine group per repeat unit), Parylene™ D (hereinafter “poly(dichloro-p-xylylene)”, two chlorine groups per repeat unit), Parylene™ AF-4 (generic name, aliphatic fluorination 4 atoms), Parylene™ SF (Kisco product), Parylene™ HT (hereinafter “fluorinated poly(p-xylylene)”, AF-4, SCS product), Parylene™ A (one amine per repeat unit, Kisco product), Parylene™ AM (one methylene amine group per repeat unit, Kisco product), Parylene™ VT-4 (generic name, fluorine atoms on the aromatic ring), Parylene™ CF (VT-4, Kisco product), and Parylene™ X (a cross-linkable version, not commercially available).

Parylene™ can have the following advantages: a hydrophobic, hydrophobic, chemically resistant; biostable, biocompatible coating; FDA approved, thin highly conformal, uniform, transparent coating, coating without temperature load of the substrates as coating takes place at ambient temperature in the vacuum, homogeneous surface, low intrinsic thin film stress due to its room temperature deposition, low coefficient of friction (AF-4, HT, SF). The Parylene™ coating can have a uniformity within a range from about +/-25 percent, for example.

Parylene™ Film Removal/Cutting

FIG. 3-10 shows a top view of the mold and step 350 of cutting the layer 115 of Parylene™ polymer film 250 to prepare the film for removal from the mold.

Once the Parylene™ has been deposited onto the mold/support/fluorosilicone assembly, the next step can be to remove the Parylene™ structure (herein “film”) from the mold. Due to the extremely thin cross section of the Parylene™ and its relatively inelastic mechanical properties, the Parylene™ layer 115 of polymer film 250 can be subject to being permanently deformed during removal, which can compromise its dimensional accuracy as it relates to the human anatomy such that the film may no longer fit in the ear. This is where the preparation of the mold can be helpful to the successful removal of the Parylene™ film. The defect-free, smooth surface of the mold and lubricious character of the release agent comprising petroleum jelly can be helpful for a successful outcome at this step.

In order to prepare the mold for the film release, the mold is placed into an oven so as to liquefy the thin layer of petroleum jelly that separates the Parylene™ film from the acrylate mold substrate and so as to release the Parylene™ film. Alternatively or in combination, the release agent may comprise a surfactant, or polyethylene glycol (hereinafter “PEG”) and the Parylene™ film can be separated from the mold with water so as to decouple the then film from the mold when the water contacts the surfactant.

The film 250 is then cut along the circumference of the machined upper surface 227 of the mold so as to provide a flat, substantially circular flange 252, which can be used as a handle with which the film can be removed from the mold.

FIG. 3-11 shows step 355 of removing the layer 115 of Parylene™ polymer film 250 from the mold with the film comprising a 3D self supporting structure and suitable for supporting with a backing material for cutting. The support 120 and the Parylene™ film comprising the resilient retention structure 110 are shown removed from the mold. The thin film can benefit from a stiff backing material in order to be accurately cut with acceptable edge condition. The film can be supported with a backing material such as polyethylene glycol (hereinafter “PEG”) In order to accomplish this, the intact free film is filled with heated liquid polyethylene glycol (PEG) which hardens when it cools to room temperature as described herein. Due to potentially excessive shrinkage, the film can be lightly pressurized to force the outer dimensions of the film to be maintained during the PEG cooling.

FIG. 3-12 shows a step 360 of cutting the layer 115 of polymer film 250 with a backing material, in accordance with embodiments of the method of FIG. 3.

The film can be cut into the intended shape. The film 250 can be fixed by the flat flange 252 to an X, Y, Z alignment device 264. The alignment device 264 may comprise an alignment device having six degrees of freedom, three rotational and three translational, such as a goniometer coupled to an X, Y, Z, translation stage. A planar cutting guide can then correctly oriented to the first desired cut. The outside of the PEG-filled film is then scored with a blade to cut through the film along the plane 262 of the blade guide 260. A second cut is made in the same manner, the result of which may comprise the desired shape of retention structure 110 and support 120. Alternatively to mechanical cutting, the Parylene™ coating can be cut with light such as excimer laser ablation, or other laser ablation, for example. The PEG can be dissolved with water.

The resilient Parylene™ retention structure and support 120 can be suitable combination with additional components of output transducer assembly 100 as described herein.

In some embodiments, the vapor comprises polyvinyl alcohol (PVA), or its hydrogel form (PVA-H).

Alternative to Parylene™ deposition or in combination with Parylene deposition, the deposited material may comprise one or more of a hydrogel material such as polyvinyl alcohol (hereinafter “PVA”), a sugar, cellulose, a carbon based material such as a diamond like coating or silicon based material such as SiO₂. The material can be deposited in many ways such as vapor deposition, thermo deposition, radiofrequency deposition, or plasma deposition. For example, PVA-H can be blended before or after deposition with one or more other materials such as chitosan, gelatin, or starch. PVA-H can be deposited and polymerized by chemical crosslinking photocrosslinking, irradiation, or physical crosslinking, such as a freeze-thaw technique. When PVA-H is crosslinked, the cross-linked PVA-H can have stable volume and material properties. The deposited polymer can be coagulated, for example with quenching a deposited polymer

solution in an aqueous nonsolvent, resulting in solvent-nonsolvent exchange and polymer precipitation.

A biocompatible nano composite material can be formed when PVA is combined with bacterial cellulose (BC) fibers. These can have the desired mechanical properties and manufacturing repeatability to make a resilient retention structure as described herein.

In many embodiments, the monomer molecules are deposited and polymerized using thermal deposition methods and using Radio Frequency deposition methods, such as plasma vapor deposition. Carbon based materials such polyethylene are compatible with such techniques.

The method 300 can be performed in many ways, and one or more of the materials may be substituted or combined with one or more materials to provide one or more of the steps as described herein. The material to provide the coating 215 on the PVS negative impression 210 can be one or more of many materials that can provide a stiff coating that retains the shape of the impression, for example with a stiff shell 215. In many embodiments, the material provides a rigid shell 215 over the PVS negative impression when cured. Suitable materials include adhesive, UV curable adhesive, epoxy, UV curable epoxy, UV curable acrylates, PMMA, and other castable resins such as epoxy, polyester, etc. The material of the coating 215 may comprise a substantially non-porous material, such as epoxy. Work in relation to embodiments indicates that UV curable adhesives such as UV curable epoxy substantially retain the shape of the negative impression 210 when cured, and that epoxies may comprise a porosity substantially less than acrylates such as PMMA. A UV cured epoxy can retain the shape of the negative impression 210, and has a sufficiently low porosity so as to be capable of use with one or more of many release agents.

The use of clear mold materials can enable visualization of components when placed so as to ensure proper alignment with the tissue structures of the ear canal. For example, the photodetector can be placed within the canal of the positive mold and visualized and aligned within the canal so as to ensure alignment, for example. In many embodiments, a plurality of components are visualized within the canal, for example, the placement of one or more of the support 120, the transducer 130, the post 134, the coupling structure 136, the at least one spring 140, or the photodetector 150, and combinations thereof, can be visualized and aligned when placed in the canal of the positive mold.

In order to make the positive mold 225, the coating 215 and PVS impression 210 can be handled in many ways so as to protect of the fragile thin shell and to provide a base for future handling. The PVS impression 210 and coating 215 can be embedded in a small container, for example cylindrical cup 220, holding a flowable material similar to the material of coating 215. The flowable material can harden over the coating 215 so as to protect coating 215. The flowable material that hardens over the coating 215 may comprise one or more of resin, pattern resin, epoxy, epoxy resin, or UV curable epoxy resin, for example. In many embodiments, the flowable material comprises a UV curable resin 222 which is cured in the container, for example cup 220.

The positive mold 225 may comprise a translucent mold to allow visualization of the components placed in the positive mold, and in many embodiments mold 225 is transparent. The coating 215 may comprise a translucent material, for example a transparent material, and the material placed over the coating 215 to form mold 225 may comprise a translucent material, for example a transparent material. The positive mold 225 can be machined in many ways, and the optically trans-

missive material can be machined so as to provide a smooth surface permitting visualization of the components placed in the positive mold 225.

The release agent 231 provided on coating 215 to release the layer 115 of Parylene™ film 250 may comprise one or more of PEG, a hydrophilic coating, a surface treatment such as corona discharge, a surfactant, a wax, hydrophilic wax, or petroleum jelly, for example. The release agent 231 may comprise a material deposited on the surface, such as a surfactant, or a surface resulting from treatment such as corona discharge such that the surface becomes hydrophilic in response to the treatment.

In many embodiments, the coating 215 comprises a UV curable epoxy and the release agent 231 comprises a hydrophilic material, such that the coating 215 can be separated from the layer 215 with application of a solvent such as water.

In many embodiments, the coupling structure 136 comprises layer 115 of Parylene™ film 250. The release agent 231 provided on coating 215 can be configured so as to release the layer 115 of Parylene™ film 250 from positive mold 225 at a location corresponding to coupling structure 136. The layer 115 can be removed from positive mold 225, and the layer 115 can be cut so as to permit coupling structure 136 to vibrate. For example, the layer 115 can be cut so as to separate the coupling structure 136 from the retention structure 110. The coupling structure 136 comprising layer 115 can reduce the mass of the vibratory structures coupled to the umbo, can provide anatomical alignment of the coupling structure 136 to the umbo, and can be readily manufactured based on the teachings described herein, and can ensure that the coupling structure 136 remains attached to post 134.

It should be appreciated that the method 300 of making the resilient retention structure provides non-limiting examples in accordance with embodiments as described herein. A person of ordinary skill in the art will recognize many variations and adaptations based on the teachings described herein. For example, the steps of the method can be performed in any order, and the steps can be deleted, or added, and may comprise multiple steps or sub-steps based on the teachings described herein. Further the method can be modified so as to provide any retention structure or output transducer assembly as described herein and so as to provide one or more of the functions any one or more of the retention structures or assemblies as described herein.

FIG. 4 shows an assembly drawing and a method of assembling output transducer assembly 100, in accordance with embodiments of the present invention. The resilient retention structure 110 as described herein can be coupled to the support 120 as described herein, for example with bumpers 122 extending between the resilient retention structure 110 and the support 120. The resilient retention structure 110 may define an aperture 110A having a width 110AW corresponding to the wide profile configuration. The support 120 may define an aperture 120A having a width 120AW that remains substantially fixed when the resilient retention structure is compressed. The aperture 110A of the resilient retention structure can be aligned with the aperture 120A of the support. The support 120 can be affixed to resilient retention structure 110 in many ways, for example with one or more of Parylene™ vapor deposition as described herein, or with an adhesive, or combinations thereof. The resilient retention structure 110 may comprise the Parylene™ layer 115, a fluorosilicone layer 115, an O-ring sized to the user, or a C-ring sized to the user, or combinations thereof.

The support 120 can be coupled to the photodetector 150 as described herein. The support 120 may comprise mounts 128,

and mount 128 can be coupled to couple arm 128 and bracket 152, such that the support is coupled to the photodetector 150.

The transducer 130 may comprise a housing 139 and a mount 138 attached to the housing, in which the mount 138 is shaped to receive the at least one spring 140. The transducer 130 may comprise a reed 132 extending from the housing, in which the reed 132 is attached to a post 134. The post 134 can be connected to the inner soft coupling structure 136.

The support 120 can be coupled to the transducer 130 with the at least one spring 140 extending between the coil and the transducer such that the inner soft coupling structure 136 is urged against the eardrum TM when the assembly 100 is placed to transmit sound to the user. The support 120 may comprise mounts 126, for example welded tubes, and the mounts 126 can be coupled to a first end of the at least one spring 140, and a second end of the at least one spring 140 can be coupled to the transducer 130 such that the at least one spring 140 extends between the support and the transducer. The spring has a spring constant corresponding approximately to a mass and distance from the pivot axis of the coil spring to the inner soft coupling structure 136 such that the spring urges the inner soft coupling structure toward the eardrum TM within a range of force from about 0.5 mN to about 2.0 mN when the resilient retention structure 110 is placed against one or more of the eardrum, the eardrum annulus or the skin of the ear canal wall, for example skin of an anterior sulcus define with the ear canal wall. The coil spring may comprise a torsion spring, and the torsion spring constant can be within a range from range from $0.1e-5$ to $2.0e-4$ mN*m/rad, for example within a range from about $0.5e-5$ N-m/rad to about $8e-5$ N-m/rad. This range can provide sufficient force to the inner support so as to maintain coupling of the inner support to the eardrum when the head of the user is horizontal, for example supine, and when the head is upright, for example vertical.

The resilient retention structure and the support can be configured in many ways so as a resistance to deflection within a range from about 1 N/m to about 10,000 N/m, for example within a range from about 250 N/m to about 10,000 N/m. The resistance to deflection within this range can provide sufficient stiffness to the retention structure 110 to support the transducer with the retention structure and so as to allow the retention structure to deflect inward when advanced into the ear canal so as to comprise the narrow profile configuration when the retention structure 110 slides along the ear canal, for example. In many embodiments, the resistance to deflection of the retention structure 110 coupled to support 120 is between the resistance to deflection of the ear canal and the resistance to deflection of the eardrum. The resistance to deflection within this range provides sufficient support to displace the eardrum and enough flexibility to permit the retention structure 110 to transform from the wide profile configuration to the narrow profile configuration as described herein when advanced into the ear canal.

FIGS. 5A and 5B show top and bottom views, respectively, of an output transducer assembly 100 having a retention structure 110 comprising a stiff support 120 extending along a portion of the retention structure. The stiff support 120 may comprise a pair of arms comprising a first arm 121, a second arm 123 opposite the first arm, and an intermediate portion 125 extending between the first arm and the second arm. The stiff support 110 may comprise the resilient spring 140 coupled to the intermediate portion 125, for example. In many embodiments, the resilient spring and stiff support 120 comprise an integrated component such as an injection molded

unitary component comprising a modulus of elasticity and dimensions so as to provide the resilient spring 140 and the stiff support 110.

The stiff support 120 and resilient spring 140 can be configured to couple the output transducer 130 to the eardrum TM when the retention structure is placed. The resilient spring 140 can be attached to the stiff support 120, such that the resilient spring 140 directly engages the stiff support 120. The stiff support 120 can be affixed to the resilient spring 140 so as to position the structure 136 below the retention structure 110, such that the structure 136 engages the tympanic membrane TM when the retention structure 110 is placed, for example on the eardrum annulus TMA. The resilient spring 140 can be configured to provide an amount of force to the eardrum when placed.

The stiff support can be configured in many ways so as to comprise the stiffness capable of deflection when placed and resistance to deflection to couple the output transducer 130 to the eardrum TM. The stiff support 120 may comprise one or more of many materials such as polymer, cured epoxy, silicone elastomer having a suitable rigidity, biaxially-oriented polyethylene terephthalate (hereinafter "BoPET", commercially available under the trademark Mylar™), metal, Polyether ether ketone (hereinafter "PEEK"), thermoplastic, shape memory material, nitinol, thermoplastic PEEK, shape memory PEEK, thermoplastic polyimide, acetal, Parylene™, and combinations thereof, for example. These polymer materials can be crosslinked to enhance their resistance to long term creep. The stiff support material may comprise a modulus, tensile strength and dimensions such as a cross-sectional diameter and length so as to provide the stiffness capable of deflection when placed and resistance to deflection to couple the output transducer.

The resilient spring 140 can be configured in many ways so as to comprise the resistance to deflection and force in response to displacement so as to couple the output transducer 130 to the eardrum TM. In many embodiments, the resilient spring 140 comprises a cantilever, in which the cantilever is fixed on a first end to the stiff support 120 and affixed to the output transducer 130 on an opposite end. The spring 140 may comprise one or more of many materials such as polymer, cured epoxy, elastomers, Mylar™, metal, Polyether ether ketone (hereinafter "PEEK"), thermoplastic, shape memory material, nitinol, thermoplastic PEEK, shape memory PEEK, and combinations thereof, for example. The resilient spring material may comprise a modulus, tensile strength and dimensions such as a cross-sectional diameter and length so as to provide the stiffness capable of deflection when placed and resistance to deflection to couple the output transducer.

The stiff support 120 and resilient spring 140 may comprise similar materials, and may comprise substantially the same material in many embodiments, for example.

The coupling structure 136 may comprise one or more of many materials as described herein. For example the coupling structure 136 may comprise a soft material such as an elastomer, for example. Alternatively, the coupling structure 136 may comprise a stiff material, for example a layer of Parylene™ film as described herein. The coupling structure 136 may comprise layer 115 deposited on the positive mold, for example. The Parylene™ layer can be cut as described herein so as to provide the coupling structure 136, for example. Alternatively, the coupling structure may comprise a curable material, for example a UV curable epoxy.

In many embodiments, the assembly 100 comprises a biasing structure 149 coupled to the stiff support 120 and the resilient spring 140 to position the structure 136 for engage-

ment with the eardrum TM. The at least one spring **140** may comprise a resilient cantilever beam, for example a spring having a size and thickness as described herein. The biasing structure can be configured in many ways, and may comprise a shim or spacer, for example. The biasing structure **149** can be placed between the stiff support **120** and resilient spring **140** so as to deflect the spring and position the structure **136** to engage the eardrum TM. For example, the biasing structure **149** can be placed on a lower surface of stiff support **120** and on an upper surface of resilient spring **140** so as to deflect the spring. The biasing structure coupled directly to the stiff support **120** and resilient spring **140** can inhibit creep of the structure **136** relative to retention structure **110** so as to maintain coupling of the structure **136** to the eardrum when placed. In many embodiments, the biasing structure is adjusted to deflect the resilient spring **140** prior to or subsequent to deposition of the layer **115**, such that the layer **115** can lock the biasing structure in place.

The photodetector **150** can be attached to the output transducer **130** with a mount **153**. The photodetector and output transducer can deflect together when the biasing structure **149**, for example a spacer, is adjusted to couple the output transducer **130** and the structure **136** to the tympanic membrane TM.

In many embodiments, the components are assembled in the mold and coated with Parylene™. The photodetector **150** can be placed in the mold and coated with one or more components of output transducer assembly **100**. The layer **115** of film **250** may comprise a translucent material that can be deposited on the light receiving surface of the photodetector **150**. A substantial amount of light can be transmitted through the coating and received with the photodetector to provide the output signal to the user. Parylene™ comprises a light transmissive material such that the coating can be any desirable thickness so as to provide strength to assembly **100**. The resilient spring **140** can be coated with the layer **115**, for example the layer Parylene™ film **250** as described herein. Each of the components of the output transducer assembly **100** can be coated with the layer **115** of Parylene™ film, for example, so as to provide a protective coating and form the resilient retention structure **110**.

FIG. **5A1** shows an integrated component **400** comprising the stiff support **120** and resilient spring **140**. The integrated component **400** can be formed in many ways. The integrated component can be formed by one or more of placing a flowable material in a mold, curing a flowable material, or an injection molding, and combinations thereof. The integrated component **400** may comprise a modulus of elasticity and dimensions so as to provide the resilient spring **140** and the stiff support **110** based on the cross-sectional dimensions and length of the spring **140** and cross-sectional dimensions and length of stiff support **140**.

FIGS. **5A2** and **5A3** show cross-sectional views of the resilient spring **140** and the stiff support **120**, respectively. The resilient spring **140** may comprise a leaf spring having a thickness **140T** and a width **140W**, for example. The stiff support **120** may comprise a cross-sectional dimension **120D**, for example. The thickness **140T** may be less than a cross-sectional dimension of the stiff support **120** and a width greater than the cross-sectional dimension of the stiff support. For example, the leaf spring may have a thickness less than a cross-sectional diameter of the stiff support **120** and a width greater than the cross-sectional diameter of the stiff support. Alternatively, the stiff-support may have non-circular cross-sectional dimensions, such as oval, square, or rectangular, for example.

FIGS. **5A4** and **5A5** show a top view and a side view, respectively, of a stiff support **120** comprising a graspable projection **410** that may be used to place the output transducer assembly in the ear canal. The projection **410** can be affixed to the stiff support **120**. The at least one spring **140** may comprise a resilient spring having a width and thickness as described herein and can be affixed to the stiff support **120**. The at least one spring **140** may comprise a cantilever spring affixed to stiff support **120** on one end and supporting the transducer on the other end, for example. Alternatively or in combination, the projection **410** may be detachable from the stiff support **120**. In many embodiments, the integrated component **400** comprises the resilient spring **140**, the stiff support **120**, and the projection **410**. The integrated component **400** can be made in one or more of many ways as described herein, and may comprise substantially the same material for each of the stiff support **120**, the resilient spring **140** and the projection **410**.

FIG. **5B1** shows a lower surface structure **136** positioned a distance **149D** beneath the lower surface of retention structure **110**. The distance **149D** may comprise a sufficient distance, for example about 1 mm such that structure **136** can engage the eardrum TM with movement of the eardrum, for example movement in response to pressure change. Changes in atmospheric pressure can result in displacements of the umbo of about 1 mm, for example. The amount of displacement for sound can be about 1 μ m, for example. The resilient spring structure **140** can be configured so as to deflect about 1 mm and provide a force to the eardrum TM, for example about 5 mN. The deflection of the coupling structure **136** at the umbo can be about 3 mm during placement of the device, and the at least one spring **140** can be configured to deflect at least about 3 mm, for example.

FIG. **5B2** shows a component of the output transducer assembly **100** retained between a first layer **115A** and a second layer **115B**. The layer **115** may comprise the first layer **115A** and the second layer **115B**, for example. Any one or more of the components of the transducer assembly **100** can be placed on the first layer **115A**, and the second layer **115B** applied so as to affix the one or more components between the first layer **115A** and the second layer **115B**. For example, the one or more components can be sandwiched between the first layer **115A** and the second layer **115B** so as to retain the one or more components between the first layer and the second layer, which each may comprise Parylene™. In many embodiments, the stiff support **110** can be retained between a first layer **115A** and a second layer **115B** of the retention structure **115B**. The first layer **115A** and the second layer **115B** may increase the stiffness of the stiff support **120** when retained between layers, for example.

In many embodiments, the stiff support **120** and resilient retention structure **110** can be resiliently deflected when inserted into the ear canal EC. To place the retention structure **110** on the surface of one or more of the eardrum TM, the eardrum annulus TMA, or the bony portion BP of the ear canal, it can be helpful, and in some instances necessary, for the retention structure to deflect from a wide profile configuration having a first width **110W1** to an elongate narrow profile configuration having a second width **110W2** when advanced along the ear canal EC as described herein. The stiff support **120** can be configured to deflect inward to provide the narrow profile configuration, and configured with sufficient resilience so as to return to the wide profile configuration having the first width when placed. The stiff, deflectable support **120** may also comprise sufficient stiffness so as to couple the output transducer **130** to the retention structure **110** so as to distribute force of the transducer substantially

along the retention structure **110** and transmit force from the resilient spring **140** to locations away from resilient spring **140**. This distribution of force to locations away from the resilient structure **140** sufficient surface area of retention structure **110** can allow the retention structure **110** to the couple the output transducer **130** to the eardrum with a surface tension of a coupling agent such as an oil, for example.

The first layer **115A** may be formed with film **250** as described herein. The components can be placed in the positive mold on the first layer **115A**, which may comprise a translucent layer, for example a transparent layer, so as to allow placement within the positive mold transparent block **400** as described herein. The second layer **115B** can be deposited on positive mold having the components placed on the first layer.

FIGS. **6A** and **6B** show side and top views, respectively, of a resilient retention structure comprising a stiff support extending along a portion of the resilient tubular retention structure. The stiff support **120** may comprise a pair of arms comprising a first arm **121**, a second arm **123** opposite the first arm, and an intermediate portion **125** extending between the first arm and the second arm. The retention structure **110** comprises a curved portion, for example an arcuate portion **111**, so as to engage the ear canal wall opposite the eardrum TM. The curved portion such as arcuate portion **111** can improve stability of the retention structure **110** in the ear canal, and provide improved coupling of the transducer **130** to the eardrum TM so as to decrease reliance on oil, for example. The curved portion such as arcuate portion **111** provides a structure opposite the tympanic membrane TM, and provides a second region on an opposite side of the ear canal to which the retention structure **110** and transducer **130** can couple. The retention structure and arcuate portion **111** comprise the layer **115** of material comprising Parylene™ film **250**, such that the retention structure comprising arcuate portion **111** is shaped to the ear canal EC of the user as described herein.

The resilient retention structure **110** can engage one or more of the bony portion BP of the ear canal wall, the eardrum annulus TMA, the eardrum TM. In many embodiments, the leading end opposite the stiff support **120** can extend into the anterior sulcus when placed. The retention structure **110** may comprise a substantially tubular portion of the film **250** deposited in the ear canal mold. The substantially tubular portion may comprise a medial cut edge **110A1** and a lateral cut edge **110A2**. The cut edge **110A1** and the cut edge **110A2** may define ends of the substantially tubular cut portion of the film **250**. The substantially tubular portion may comprise an axis, and the cut edge **110A1** and the cut edge **110A2** can be cut oblique to the axis. Aperture **110A** can extend through the substantially tubular retention structure **110**.

FIGS. **7A**, **7B** and **7C** show side, top and front views, respectively, of an output transducer assembly **100** having a resilient retention structure **110** comprising curved portion such as an arcuate portion **111** and a stiff support **120** extending along a portion of the resilient retention structure. The retention structure **110** comprises a curved portion such as an arcuate portion **111** to engage the ear canal wall opposite the eardrum TM similar to the arcuate structure of FIGS. **6A** and **6B**. However, the portion extending into the anterior sulcus may be cut away. Work in relation to embodiments indicates that the anterior sulcus AS can be difficult to view, and truncation of the medial end of the film **250** can shape the retention structure **110** such to inhibit placement of the retention structure **110** in the anterior sulcus AS. The curved portion such as arcuate portion **111** can provide substantially coupling of the transducer to the bony portion BP of the ear canal EC wall opposite the eardrum TM. The stiff support **120** may

provide provides sufficient stiffness so as to pivotally couple transducer **130** to the canal wall with the curved portion such as arcuate portion **111**.

The retention structure **110** can be molded as described herein so as to comprise a thin layer **115** of material corresponding tubular portion of the ear canal. An aperture **110A** can extend through the tubular portion. The aperture **110A** can be defined with a first cut profile **110A1** and the second cut profile **110A2** of the tubular section of Parylene™.

The resilient retention structure **110** may comprise enough stiffness so as to couple the arcuate portion to the ear canal wall opposite tympanic membrane TM to the transducer **130**.

The embodiments illustrated in FIGS. **6A** to **7C** show examples of retention structures, and the retention structure **110** may comprise a shape intermediate to FIGS. **6A-6B** and FIGS. **7A-7C**, for example. In many embodiments, the layer **115** comprises a tubular structure, and the shape of retention structure **110** depends upon the first cut profile **110A** and the second cut profile **110B**, for example.

FIG. **8A** shows components of an output transducer assembly **100** placed in a transparent block **800** of material comprising the positive mold **225** of the ear canal and eardrum of the patient. The transparent block **800** may comprise the cured coating **215**, the flat machined surface **227** and the release agent **231**. The components placed in the transparent block **800** comprising the transparent mold **225** of the ear canal and eardrum may comprise one or more of the transducer **130**, the photodetector **150**, the at least one spring **140**, or the support **120**, and combinations thereof. The transparent block **800** permits the components placed in the block **800** to be viewed by an eye **810** of an assembler **810**. The assembler may be a person or a machine such as a robotic arm. The Parylene™ can be deposited before, or after the components have been placed, or both before and after the components have been placed so as to sandwich the components between layers of Parylene™ film **250**. The photodetector can be placed in the mold **225** such that Parylene™ is coated on the detector and light transmitted through the Parylene™ when the output transducer assembly **100** is placed in the ear and used. In addition to providing the retention structure **110**, the sealing of the components can provide reliability and optical transmission through the protective coating.

FIG. **8B** shows a transducer **130** configured to receive a layer of a coating deposited with a vapor as described herein.

FIG. **8C** shows the transducer of FIG. **8B** with a deposited layer.

The transducer **130** may comprise an opening **131** formed in the casing **137** of the output transducer **130**. The reed **132** can extend through the opening **131** to couple to the post as described herein. The deposited layer **115** may comprise the second layer **115B**, for example when the components are placed on first layer **115A**. The vapor can pass through the opening **131** to form layer **115** on the reed. The opening **131** can be sized so as to decrease the thickness of the layer **115B** deposited on the reed **132**. Work in relation to embodiments as described herein indicate that layer **115** can affect tuning of the reed **132**. By sizing the opening **131** to decrease the thickness of the layer **115**, the output transducer **130** can be used with the coating **115B**, for example.

In many embodiments, the opening **131** is sized to inhibit passage of a liquid, for example water or oil, through the opening **131**. The opening **131** can be sized based on the contact angle of the liquid, so as to inhibit passage. For layer **115** providing a steep contact angle, the opening **131** can be larger than for a layer **115** providing small contact angle.

FIG. **8D** shows the output transducer **130** of FIG. **8B** with a blocking material **133** to inhibit formation of the deposited

layer on the reed **132** of the transducer. The blocking material may comprise the backing material as described herein, for example PEG, such that the Parylene™ deposited on the blocking material can be cut away.

FIG. **8E** shows the transducer of FIG. **8B** with a blocking material **133** placed over a bellows **139** to inhibit formation of the deposited layer on the bellows **139** of the transducer. The deposited layer **115** can decrease movement of the bellows, and the structure comprising blocking material **133** can be placed over the bellows to inhibit deposition of the material on the bellows. The structure comprising blocking material **133** can be placed before the output transducer **130** is placed in the transparent block **800**, for example. The layer **115** deposited on the structure comprising blocking material **133** can be cut away, so as to expose the bellows, for example.

Oleophobic Coatings

In many embodiments a coupling agent such as oil can be used to couple the output transducer assembly **100** to the eardrum TM and wall of the ear canal EC. Although oil can be helpful to maintain coupling, accumulation of excessive oil can decrease performance. The inhibition of oil accumulation on vibratory components can substantially decrease autophony when the output transducer **130** is coupled to the eardrum TM with coupling structure **136**, as microactuator of the output transducer **130** can be configured to allow the eardrum move in response to the user's self-generated sounds so as to decrease autophony. The formation of a puddle of oil under or over the microactuator can inhibit movement of the microactuator and contribute to autophony, and the oleophobic coating can be configured to inhibit formation of the puddle of oil so as to inhibit the autophony. An oleophobic coating can be provided on one or more locations to decrease accumulation of oil. The accumulation of oil may comprise a wetting of oil on the surfaces, and the wetting can be related to a contact angle of oil with the surface. The oleophobic coating can be provided on one or more of the microactuator, the resilient spring **140**, the stiff support **120**, the retention structure **110**, one or more surfaces of the retention structure **110**, or one or more surfaces of output transducer **130**, and combinations thereof, so as to inhibit accumulation of oil.

The oleophobic coating may comprise one or more known coatings, and can be provided over the layer **115**, for example. In many embodiments, the layer **115B** may comprise an oleophobic coating. Alternatively, the oleophobic coating can be provided over the second layer **115B**.

FIG. **8F** shows an oleophobic layer **135** deposited on the output transducer **130**. The oleophobic layer **135** can inhibit accumulation of oil on the housing. The oleophobic layer can be located on one or more of many surfaces of the output transducer assembly **100**.

The bellows **139** may comprise the oleophobic layer as described herein, so as to inhibit accumulation of oil on or near the bellows, for example.

FIG. **9A** shows a retention structure **110** comprising curved portion such as an arcuate portion **111** shaped to extend along a surface of the bony portion of the ear canal opposite the eardrum TM when placed. The retention structure **110** may comprise a stiff support **120**, as described herein, in combination with layer **115** so as to stiffen the retention structure **110**, for example. The stiff support **120** may comprise a pair of arms comprising a first arm **121**, a second arm **123** opposite the first arm, and an intermediate portion **125** extending between the first arm and the second arm. Alternatively or in combination, the arcuate portion **111** may comprise the stiff support in combination with the layer **115**. The arcuate portion **111** can be coupled to transducer **130** with at least one structure **199** extending between the coupling structure **136**

and the arcuate portion **111** so as to couple the arcuate portion **111** to the eardrum TM with transducer located in between. The coupling of the arcuate portion **111** to the transducer and to the eardrum can provide the opposing surfaces of the eardrum and the arcuate portion **111** for the transducer to push against. The at least one structure **199** may comprise the biasing structure **149** and at least one spring **140**, for example, in which the distance **149D** between the lower surface of coupling structure **136** and the lower surface of retention structure **110** can be adjusted prior to placement in an unloaded configuration as described herein. The at least one structure **199** comprising the biasing structure **149** and at least one spring can support the transducer **130** and the coupling structure **136** in the unloaded free standing configuration as described herein.

The at least one structure **199** may comprise one or more of many structures as described herein to couple the transducer **130** and the coupling structure **136** to the eardrum TM, and may comprise one or more of a biasing structure, a biasing mechanism, a spring, a coil spring, a telescopic spring, a leaf spring, a telescopic joint, a locking telescopic joint, or a transducer.

FIG. **9B** shows a dynamic biasing system **600** coupled to the arcuate portion **111** and the coupling structure **136**. The at least one structure **199** may comprise the at least one spring **140** and the dynamic biasing system **600**. The dynamic biasing system **600** can be configured to engage the eardrum TM with coupling structure **136** when transducer **130** vibrates and configured to disengage the coupling structure **136** from the eardrum TM when transducer **130** comprises a non-vibrating configuration, for example when no substantial signal energy is transmitted to the output transducer assembly **100**. The transducer **610** of biasing system **600** as described herein and may comprise rectification or other circuitry, so as to urge the output transducer **130** toward the eardrum so as to couple the output transducer to the eardrum in response to a signal transmitted to transducer **130**. The transducer **610** of the dynamic biasing system **600** may comprise one or more transducers as described herein, for example one or more of a microactuator, a photostrictive transducer, a piezoelectric transducer, an electromagnetic transducer, a solenoid, a coil and magnet, or artificial muscle, for example. The transducer **610** can be coupled to the photovoltaic with wires and rectification circuitry to dynamically bias the transducer **610** in response to light energy received by the photodetector **150**. Alternatively, the photostrictive material can receive electromagnetic light energy directed toward the photodetector and bias the transducer **130** in response to the light energy signal directed toward the photodetector **150** and received by the photostrictive material.

The arcuate portion provides a support for the transducer to be lifted away from the eardrum TM when the transducer **130** is not active, for example, and a support for the transducer to engage and couple to the eardrum when the transducer **130** is active, for example. The decoupling and coupling can decrease user perceived occlusion when the transducer **130** is not in use.

The at least one structure **199** coupled to the curved portion **111** can be combined with pivoting of the transducer **130** in relation to the stiff support **120** as described herein. For example, the at least one structure **199** can urge the transducer **130** toward the eardrum to couple to the eardrum, and the transducer **130** can be resiliently coupled to the support **120** with the at least one spring **140**, for example a cantilever as described herein.

The transducer **130** may comprise one or more transducers as described herein, such as one or more of a microactuator, a

photostrictive transducer, a piezoelectric transducer, artificial muscle, an electromagnetic transducer, a balanced armature transducer, a rod and coil transducer, a bimorph transducer, a bender, a bimorph bender, or a piezoelectric diaphragm, for example.

The at least one structure **199** may comprise one or more of many structures configured to couple the transducer to the eardrum and the arcuate portion **111**. For example, the at least one structure **199** may comprise a spring or an elastic material or a combination thereof. For example the spring may comprise a leaf spring or a coil spring. The at least one structure **199** may comprise an elastic material, such as silicone elastomer configured to stretch and push the transducer toward the eardrum when the support is positioned on the eardrum. The at least one structure may comprise a viscoelastic material. Alternatively or in combination, the post **134** may comprise the at least one structure **199**. The at least one structure **199** may comprise one or more of the tuning structures, for example. The at least one structure may comprise a hydraulic telescoping mechanism, for example, so as to decouple the transducer from the eardrum at low frequencies and couple the eardrum to the transducer at high frequencies. Additional structures suitable for use with at least one structure **199** in accordance with embodiments are described in U.S. Pat. App. No. 61,217,801, filed Jun. 3, 2009, entitled "Balanced Armature Device and Methods for Hearing"; and PCT/US2009/057719, filed 21 Sep. 2009, entitled "Balanced Armature Device and Methods for Hearing", published as WO 2010/033933, the full disclosures of which have been previously incorporated herein by reference as suitable for combination in accordance with embodiments described herein.

The transducer **130** may pivot about a pivot axis to couple to the eardrum as described herein.

FIG. **10A** shows machining such as laser sculpting **500** of a negative mold to provide a deflection of the epithelium contacting surface of the retention structure to receive migrating epithelium. The laser sculpting may comprise ablation, for example. A laser system **530** may comprise a laser to provide a source of laser energy, and a laser delivery system comprising scanning optics, for example. A laser beam **510** can be directed to the negative mold **210** to remove material from the negative mold, such that the positive mold comprises the deflection. The laser beam can be directed in a scan pattern **520** so as to ablate a predetermined profile **540** in the surface of the negative mold.

FIG. **10B** shows one or more deflections **550** of the epithelium contacting surface of the retention structure to receive migrating epithelium. The one or more deflections **550** can be shaped with a curved edge such that epithelium advancing toward the edge passes under the edge. The retention structure **110** may comprise an annular retention structure having an inner edge oriented toward the umbo and an outer edge oriented toward the canal wall. The inner edge may comprise the one or more deflections **550** to receive the migrating epithelium.

FIG. **10C** shows an epithelium **560** migrating under the one or more deflections **550** of FIG. **10B**. The retention structure may comprise an annular structure having an aperture positionable over the umbo. In many patients, the epithelium can migrate in a direction **570** outward from the umbo along the surface of the eardrum toward the eardrum annulus and canal wall. The epithelium can migrate from the eardrum annulus to the canal wall, and subsequently in a direction **570** along the canal wall toward the opening to the ear canal. The deflection **550** may comprise a portion of the retention structure having a thickness similar to a majority of the retention structure.

In many embodiments, the thickness of the retention structure **110** is within a range from about 5 to about 50 μm , such that the thickness of the retention structure is approximately to the thickness of the epithelium. The epithelium on the umbo can be about 15 μm thick, for example, and can be thicker on the ear canal, for example about 50 to 100 μm thick. The one or more deflections **550** can provide sufficient clearance to pass the epithelium under the edge of the deflection **550**. The amount of deflection may comprise a distance **580** corresponding to the profile of material removed from the negative mold, for example the ablation profile. The distance **580** can be proportional to the thickness of the epithelium at the location of placement, and the distance **580** can be at least as thick as the epithelium. The distance **580** can be at least about 15 μm , for example at least about 50 μm , and in many embodiments 100 μm or more. A similar deflection can be provided by depositing material on the positive mold, for example as an alternative to removal of material from the negative mold.

FIG. **11** shows a dynamic biasing system **600** comprising a transducer **620** configured to deflect the output transducer **130** toward the eardrum so as to couple the output transducer to the eardrum. The dynamic biasing system **600** comprising the transducer **620** can move one or more of the transducer **130**, the arm **134** or the structure **136**, or combinations thereof, toward the eardrum with a movement **610**. The at least one spring **140** can be coupled to the dynamic biasing system to allow movement of the coupling structure **136**. The biasing structure **149** of the at least one spring can be coupled to the at least one spring **140** as described herein. The dynamic biasing system **600** comprising the transducer **620** may comprise one or more of many known transducers, such as one or more of a piezoelectric transducer, a coil and magnet transducer, a photostrictive material, artificial muscle, or combinations thereof. The transducer **620** can be configured to couple the transducer to the eardrum when the transducer **130** transmits sound to the user. In many embodiments, the dynamic biasing system **600** comprising the transducer **620** is configured to couple to the eardrum in response to the signal transmitted to transducer **130**. For example, dynamic biasing system **600** comprising the transducer **620** may comprise rectification circuitry to provide a voltage to the transducer in response to an AC signal to transducer **130**. The transducer **620** may comprise photostrictive material configured to provide movement **610** when a light beam is transmitted to photodetector **150** and a portion of the light beam is absorbed by the photostrictive material. The transducer **620** may comprise artificial muscle, commercially available from Artificial Muscle, Inc., of Sunnyvale, Calif.

FIG. **12** shows a retention structure **110** comprising layer **115** configured for placement in the middle ear supporting an acoustic hearing aid **700**. The retention structure **110** comprising layer **115** can be manufactured as described herein and configured for placement in deep in the ear canal, so as to couple to the bony portion BP of the ear canal. The retention structure **110** may comprise a molded tubular structure having the shape of the ear canal, and can be manufactured from cut sections as described herein.

The retention structure **110** comprises one or more deflections **550** as described herein. The retention structure **110** may comprise a thickness within a range from about 1 μm to about 100 μm as described herein, for example within a range from about 5 μm to about 50 μm . The thickness of the ParyleneTM retention structure within this range can be sufficiently resilient so as to support the retention structure **110** and to deflect when inserted or the patient chews, for example. As the epithelium covering the bony portion of the ear canal may comprise a thickness within a range from about

50 um to about 100 um, the retention structure 110 may comprise a thickness less than the thickness of the epithelium.

The one or more deflections 550 can be oriented toward the eardrum of retention structure 110 and shaped so as to receive epithelium migrating outward toward the ear canal opening. The one or more deflections deflect away from the epithelium toward the source of epithelium so as to inhibit epithelial growth over an edge of the retention structure 550. The eardrum is located medially M to the retention structure 110 and the ear canal opening is located laterally L to the retention structure 110. The lateral side 110 may comprise deflections similar to the one or more deflections 550 to facilitate removal of the retention structure 110.

The retention structure 110 can be configured in one or more ways as described herein so as to retain the hearing aid 700 in the ear canal. The retention structure 110 can be placed in the ear canal without lubrication and can remain in the ear canal without application of a coupling agent such as an oil. Alternatively, the user can apply oil 750 to the ear canal, and the oil 750 can pass between the retention structure 110 and the ear canal EC. The presence of oil between the skin SK and the retention structure 110 can couple the retention structure to the skin SK, and can reduce adhesion of the skin to the retention structure 110. The oil can facilitate removal and can decrease adhesion of the skin SK to the retention structure, such that the retention structure 110 can be removed from the ear canal without tearing of the skin SK, for example. In many embodiments, the retention structure can remain placed in the ear canal EC for one or more months, for example about three or more months.

The acoustic hearing aid 700 may comprise one or more of many components to decrease occlusion and feedback, for example. The hearing aid 700 may comprise a microphone 710 on the temporal side T of the device, such that the microphone 710 can be positioned deep in the ear canal to provide sound localization. The hearing aid 700 may comprise an acoustic speaker 720 to vibrate the eardrum TM. The hearing aid 700 can decrease sound transmission from the acoustic speaker 720 to the microphone 710 in one or more of many ways. The molded fit of the retention structure 110 to the ear canal can inhibit the formation of sound conduction pathways such as gaps that can transmit sound from the acoustic speaker to the microphone. The hearing aid 700 can be configured further to inhibit sound transmission from the acoustic speaker to the microphone, for example by substantially inhibiting air flow from the medial side M to the lateral side L with a casing 730 and a support material 740 to couple the retention structure 110 to the casing 730. The casing 730 may comprise a rigid material, and support material 740 may comprise one or more of a compressible or an elastic material, such as a foam or elastomer or a combination thereof. The deep placement on the bony portion BP can inhibit user perceived occlusion when the hearing aid 700 occludes the ear canal and blocks sound transmission from the medial side M to the lateral side L.

The acoustic hearing aid 700 may comprise one or more components of a commercially available hearing aid, such as the Lyric™, commercially available from InSound Medical, Inc. (website www.lyrichearing.com), or a similar known hearing aid commercially available from Starkey, for example. The Lyric™ hearing aid can be combined with the retention structure 110 in accordance with embodiments as described herein. The hearing aid 700 can be placed deep into the bony portion of the ear canal so that the receiver resides approximately 4 mm from the eardrum, and the microphone

can be 4 mm or more from the opening of the ear canal. This placement deep in the ear canal provides a number of sound quality benefits.

The retention structure 110 comprising layer 115 can be well suited to fit many complex ear anatomies, including ear canals that are one or more of narrow, or short as compared to a population of patient and combinations thereof. Additional anatomies the retention structure 110 comprising layer 110 is well suited to fit include a significant step-up in the canal floor, extreme v-shaped canal, or a large bulge in the canal, and combinations thereof. These complex ear anatomies can be fit comfortably so as to decrease the chance of discomfort to the user. The retention structure 115 comprising layer 110 can provide a lateral seal of the ear canal so as to inhibit feedback and decrease occlusion.

The placement deep in the ear canal can provide improved directionality and localization (ability to tell where sounds are coming from). The hearing aid 700 placement deep in the ear canal can allow the pinna (outer part of the ear) to interact naturally with incoming sounds. The acoustic transformations produced by the pinna as sound enters the ear canal contribute to the ability to accurately determine where sounds are coming from in the environment, similar to assembly 100.

The hearing aid 700 can provide decreased user perceived occlusion and decreased feedback. As the receiver sits closer to the eardrum than with traditional hearing aids, less output can be used to accommodate hearing loss, which can decrease feedback.

The hearing aid 700 can reside substantially in the hard-walled bony portion BP of the ear canal, so as to decrease movement of the device. As the retention structure 110 can be molded, the fit between the ear canal and the device can inhibit sound transmission between the retention structure 110 and the ear canal so to inhibit feedback. The placement deep in the ear canal can allow the hearing aid 700 to be configured so as to inhibit sound transmission from the receiver end toward the microphone, similar to the Lyric™.

The hearing aid 700 can be retained anchored in the ear canal so as to inhibit slippage and also in a manner that fits irregular shapes and contours of various ear canals, as the retention structure 110 can be molded. As the retention structure 110 comprises a resilient structure capable of changing shape, the fit to the ear canal can be maintained when the ear changes shape during chewing and talking. This can prevent slippage of the hearing aid 110 and inhibit sound leakage and feedback.

Deep canal fitting of hearing aid 700 can result in an increase in sound pressure level at the eardrum as compared with a conventional hearing aid. This increase can be up to 15 dB in the high frequencies, and can be caused by a combination of reduced residual ear canal volume between the receiver and the eardrum and the microphone location deeper in the ear canal allowing for pinna effects.

Security of fit and retention of the molded retention structure 110 can provide improved patient comfort with hearing aid 700.

EXPERIMENTAL

Output transducer assemblies as described herein have been placed in many ears of many users to evaluate comfort, sound quality and retention. In many embodiments, the retention structure comprises a Parylene™ coating having a thickness of about 20 um.

The retention structure having this thickness can deform when advanced along the ear canal of the user and can expand to the wide profile configuration comprising the shape of the

ear canal based on the vapor deposition to the positive mold as described herein. The resistance to deflection can be determined with concentrated loads on opposite sides of the retention structure similar to the inward deflection provided by ear canal, for example.

The resistance to deflection can be determined based on material properties and dimensions of the retention structure **110** as described herein. Non-limiting examples of numerical calculations to determine the approximate resistance to deflection include calculations for the following two embodiments:

Embodiment 1

The retention structure **110** comprises a flat ribbon 2 mm high and 18 μm thick. The radius is 5 mm and the elastic modulus is about 1 GPa. The resistance to deflection of the stiff retention structure is about 5 N/m. In many embodiments, a lower resistance to deflection can be used, for example about 1 N/m.

Embodiment 2

The retention structure comprises a c channel 2 mm high (with a radius of 1 mm) and 18 μm thick. The overall radius is 5 mm and the elastic modulus is about 1 GPa. The resistance to deflection of the stiff retention structure is about 27,000 N/m. As the asymmetric shape of the anatomy of the ear canal may result in varying resistance to deflection along the perimeter of the retention structure, local areas of the retention structure may absorb a substantial majority of the deflection, such that a resistance to deflection of about 10,000 N/m may be appropriate. The resistance to deflection can be within a range from about 1 N/m to about 10,000 N/m, for example.

In many embodiments, the eardrum comprises a resistance to deflection of about 250 N/mm. In some embodiments, it can be helpful to provide the retention structure with a resistance to deflection within a range from about 250 N/m to about 10,000 N/m, for example.

While the exemplary embodiments have been described in some detail, by way of example and for clarity of understanding, those of skill in the art will recognize that a variety of modifications, adaptations, and changes may be employed. Hence, the scope of the present invention shall be limited solely by the appended claims.

What is claimed is:

1. An apparatus for placement with a user, the apparatus comprising:

a transducer;

a retention structure, the retention structure comprising a layer of polymer having a shape profile corresponding to a tissue of the user to couple the transducer to the user, wherein the layer comprises one or more of poly(chloro-p-xylylene), poly(p-xylylene), poly(dichloro-p-xylylene), or fluorinated poly(p-xylylene) and wherein the retention structure comprises a resilient retention structure to maintain a location of the transducer when coupled to the user,

wherein the layer comprising the one or more of poly(chloro-p-xylylene), poly(p-xylylene), poly(dichloro-p-xylylene), or fluorinated poly(p-xylylene) has a thickness to resist deflection away from the shape profile and wherein the layer comprises the shape profile in an unloaded configuration.

2. The apparatus of claim 1, wherein the retention structure comprises a curved portion having an inner surface toward an eardrum when placed and wherein the curved portion couples

to an ear canal wall oriented toward the eardrum when placed to couple the transducer to the eardrum.

3. The apparatus of claim 2, wherein the curved portion couples to the ear canal on a first side of the ear canal opposite the eardrum and wherein a second portion of the retention structure couples to a second side of the ear canal opposite the first side to hold the retention structure in the ear canal.

4. The apparatus of claim 2, wherein the curved portion and the second portion are connected so as to define an aperture extending therebetween to view at least a portion of the eardrum when the curved portion couples to the first side of the ear canal and the second portion couples to the second side.

5. The apparatus of claim 1, further comprising a support to couple the transducer to the retention structure, wherein the support comprises a first layer of a polymerizable material and a second layer of a polymerizable material, the apparatus comprising components of a hearing device situated between the first layer and the second layer.

6. The apparatus of claim 1, further comprising an oleophobic coating on one or more of the transducer or the retention structure.

7. The apparatus of claim 1, wherein the tissue comprises an eardrum having a first resistance to deflection and a bony portion of the ear canal having a second resistance to deflection greater than the first resistance and wherein the layer comprises a resistance to deflection greater than the eardrum and less than the bony portion of the ear canal.

8. The apparatus of claim 1, wherein the transducer couples to a tissue structure having a resistance to deflection and wherein the layer comprises a resistance to deflection greater than the tissue structure.

9. The apparatus of claim 1, wherein the layer comprises a thickness within a range from about 1 μm to about 100 μm .

10. The apparatus of claim 1, wherein the layer comprises a substantially uniform thickness to provide the resistance to deflection and the shape profile in the unloaded configuration.

11. The apparatus of claim 1, wherein the substantially uniform thickness of the layer is uniform to within about ± 25 percent of an average thickness to provide the shape profile.

12. The apparatus of claim 1, wherein the retention structure comprises a resilient retention structure to maintain a location of the transducer when coupled to the user.

13. The apparatus of claim 12 wherein the resilient retention structure is sized to fit within an ear canal of the user and contact one or more of a skin of the ear canal or an eardrum annulus so as to maintain a location of the transducer when placed in the ear canal.

14. The apparatus of claim 1, wherein the layer comprises poly(p-xylylene) and poly(chloro-p-xylylene) based polymer to maintain a location of the transducer when coupled to the user and wherein the thickness is within a range from about 5 μm to about 50 μm .

15. The apparatus of claim 1, further comprising:
a support to couple the transducer to the retention structure.

16. The apparatus of claim 15, wherein the support comprises a stiff support having a pair of curved arms extending substantially along outer portions of the retention structure and wherein the curved arms are configured to deflect inward with the retention structure when the support is advanced along an ear canal of the user.

17. The apparatus of claim 15, wherein the transducer is supported with at least one spring extending between the support and the transducer.

18. The apparatus of claim 17, wherein support comprises an intermediate portion extending between the arms and

39

wherein the at least one spring extends from the intermediate portion to the transducer to support the transducer.

19. The apparatus of claim 18, wherein the at least one spring comprises a cantilever extending from the intermediate portion to the transducer to support the transducer.

20. The apparatus of claim 19, wherein the at least one spring and the support comprising the arms and the intermediate section comprise a single part manufactured with a material.

21. The apparatus of claim 20, wherein a projection extends from the single part to place the retention structure in the ear canal of the user.

22. The apparatus of claim 20, wherein the single part comprises one or more of a molded part, an injection molded part, or a machined part.

23. The apparatus of claim 17, wherein the at least one spring comprises a pair of springs, a first spring of the pair coupled to a first side of the transducer, a second spring of the pair coupled to a second side of the transducer opposite the first side, so as to support the transducer with springs coupled to the support on opposing sides.

24. The apparatus of claim 15, further comprising:
a coupling structure shaped to engage an eardrum to vibrate the eardrum; and
a biasing structure to adjust an offset between the support and the coupling structure.

25. The apparatus of claim 24, wherein the biasing structure is configured to adjust a separation distance extending between a lower surface of the retention structure and a lower surface of the coupling structure in an unloaded configuration and wherein the coupling structure is coupled to the support with at least one spring such that the separation distance decreases when the coupling structure contacts the eardrum.

26. The apparatus of claim 25, wherein the biasing structure, the support, and the coupling structure are coupled to the at least one spring so as to provide about one mm or more of deflection of the coupling structure toward the support when the coupling structure engages the eardrum in a loaded configuration.

27. The apparatus of claim 26, wherein the biasing structure is configured to adjust a position of the transducer in relation to the support so as to position the coupling structure with the offset.

28. The apparatus of claim 15, further comprising:
a photodetector attached to a casing of the transducer.

29. The apparatus of claim 28, wherein the transducer is configured to pivot relative to the support and wherein the photodetector pivots with the transducer.

30. The apparatus of claim 1, wherein the shape profile corresponds to a shape profile of a tissue surface and wherein the shape profile comprises a portion having a deflection away from the shape profile of the tissue surface.

31. The apparatus of claim 29, wherein the tissue surface comprises an epithelial surface and wherein the deflection is configured to extend away from the epithelial surface when the support is placed and wherein the deflection is oriented on the support so as to receive advancing epithelium under the deflection.

32. A method of manufacturing an output transducer assembly for placement within a canal of an ear of a user, the user having an eardrum, the method comprising:

providing a retention structure sized to fit within the ear canal and contact one or more of a skin of the ear canal or an eardrum annulus, the retention structure comprising a layer of polymer having a shape profile corresponding to a tissue of the user to couple the transducer to the user, wherein the layer comprises one or more of

40

poly(chloro-p-xylylene), poly(p-xylylene), poly(dichloro-p-xylylene), or fluorinated poly(p-xylylene);
coupling a support to the retention structure, wherein the support is sized to fit within the ear canal and defines an aperture; and

coupling a transducer to the support, the transducer comprising an elongate vibratory structure, and wherein the transducer is coupled to the support such that the elongate vibratory structure extends through the aperture to couple the transducer to the eardrum when the elongate structure is placed within the ear canal.

33. The method of claim 32 wherein the layer of polymer material comprising the one or more of poly(chloro-p-xylylene), poly(p-xylylene), poly(dichloro-p-xylylene), or fluorinated poly(p-xylylene) has been separated from a mold having the shape profile.

34. The method of claim 32, further comprising placing an oleophobic coating on the transducer, the retention structure, or both.

35. The method of claim 32, further comprising shaping the retention structure based on a mold corresponding to an anterior sulcus of the ear canal of the user.

36. The method of claim 32, further comprising coupling a photo transducer to the support and the transducer.

37. The method of claim 32, wherein the retention structure is compressible between a first wide profile configuration and a narrow profile configuration.

38. The apparatus of claim 1, wherein the retention structure comprises a transparent material.

39. The apparatus of claim 26, wherein the apparatus is a hearing device, a communication system, or an entertainment system.

40. An apparatus for placement with a user, the apparatus comprising:

a transducer;
a retention structure, the retention structure comprising a layer of polymer having a shape profile corresponding to a tissue of the user to couple the transducer to the user, wherein the layer comprises one or more of poly(chloro-p-xylylene), poly(p-xylylene), poly(dichloro-p-xylylene), or fluorinated poly(p-xylylene) and has a thickness to resist deflection away from the shape profile and wherein the layer comprises the shape profile in an unloaded configuration;

a support;
a coupling structure shaped to engage an eardrum to vibrate the eardrum; and
a biasing structure to adjust an offset between the support and the coupling structure.

41. The apparatus of claim 40, further comprising a photodetector.

42. The apparatus of claim 40, wherein the support comprises a first layer of a polymerizable material and a second layer of a polymerizable material, the apparatus comprising components of a hearing device situated between the first layer and the second layer.

43. An apparatus for placement with a user, the apparatus comprising:

a transducer;
a retention structure, the retention structure comprising a layer of polymer having a shape profile corresponding to a tissue of the user to couple the transducer to the user, wherein the layer comprises one or more of poly(chloro-p-xylylene), poly(p-xylylene), poly(dichloro-p-xylylene), or fluorinated poly(p-xylylene) and wherein the

41

retention structure comprises a resilient retention structure to maintain a location of the transducer when coupled to the user,

wherein the tissue comprises an eardrum having a first resistance to deflection and a bony portion of the ear canal having a second resistance to deflection greater than the first resistance and wherein the layer comprises a resistance to deflection greater than the eardrum and less than the bony portion of the ear canal.

44. An apparatus for placement with a user, the apparatus comprising:

a transducer;

a retention structure, the retention structure comprising a layer of polymer having a shape profile corresponding to a tissue of the user to couple the transducer to the user, wherein the layer comprises one or more of poly(chloro-p-xylylene), poly(p-xylylene), poly(dichloro-p-xylylene), or fluorinated poly(p-xylylene) and wherein the retention structure comprises a resilient retention struc-

42

ture to maintain a location of the transducer when coupled to the user, wherein the retention structure comprises a transparent material.

45. An apparatus for placement with a user, the apparatus comprising:

a transducer;

a retention structure, the retention structure comprising a layer of polymer having a shape profile corresponding to a tissue of the user to couple the transducer to the user, wherein the layer comprises one or more of poly(chloro-p-xylylene), poly(p-xylylene), poly(dichloro-p-xylylene), or fluorinated poly(p-xylylene) and wherein the retention structure comprises a resilient retention structure to maintain a location of the transducer when coupled to the user, wherein the apparatus is a hearing device, a communication system, or an entertainment system.

* * * * *