



US009400952B2

(12) **United States Patent**  
**Nemet**

(10) **Patent No.:** **US 9,400,952 B2**  
(45) **Date of Patent:** **\*Jul. 26, 2016**

(54) **TAMPER-PROOF QUALITY MANAGEMENT  
BARCODE INDICATORS**

(71) Applicant: **VARCODE LTD.**, Rosh Ha'ain (IL)

(72) Inventor: **Yaron Nemet**, Kedumim (IL)

(73) Assignee: **Varcode Ltd.**, Rosh Ha'ayin (IL)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/823,758**

(22) Filed: **Aug. 11, 2015**

(65) **Prior Publication Data**

US 2016/0042260 A1 Feb. 11, 2016

**Related U.S. Application Data**

(63) Continuation of application No. 14/461,778, filed on Aug. 18, 2014, now Pat. No. 9,122,963, which is a continuation of application No. 13/657,185, filed on Oct. 22, 2012, now Pat. No. 8,807,422.

(51) **Int. Cl.**

**G06K 19/06** (2006.01)

**G01D 7/00** (2006.01)

(52) **U.S. Cl.**

CPC ..... **G06K 19/0615** (2013.01); **G01D 7/005** (2013.01); **G06K 19/06028** (2013.01); **G06K 19/06046** (2013.01)

(58) **Field of Classification Search**

USPC ..... 235/375  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,057,029 A 11/1977 Seiter  
4,059,407 A 11/1977 Hochstrasser

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1720180 1/2006  
CN 1914621 2/2007

(Continued)

OTHER PUBLICATIONS

A European Search Report dated Apr. 6, 2011, which issued during the prosecution of European Patent Application No. 07827384.4.

(Continued)


*Primary Examiner* — Christle I Marshall

(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(57) **ABSTRACT**

A tamper-proof barcoded quality indicator operative to provide a machine-readable indication of exceedance of time and temperature thresholds following actuation thereof, including a first barcode including a first colorable area and being machine-readable before exceedance of the time and temperature thresholds, a second barcode including a second colorable area and not being machine-readable before exceedance of the time and temperature thresholds, a coloring agent located at a first location on the indicator, a coloring agent pathway operative to allow the coloring agent to move, at a rate which is at least partially a function of time, from the first location to the first and second colorable areas simultaneously for simultaneous coloring thereof upon exceedance of the time and temperature thresholds, thereby causing the first barcode to become unreadable and at the same time causing the second barcode to become machine-readable, and a tamper-proof actuator element operative to actuate the indicator.

**7 Claims, 4 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS

RE31,586 E	5/1984	Magnussen	7,587,217 B1	9/2009	Laakso et al.
4,674,065 A	6/1987	Lange et al.	7,590,626 B2	9/2009	Li et al.
5,053,339 A	10/1991	Patel	7,702,680 B2	4/2010	Yih et al.
5,084,143 A	1/1992	Smith	7,747,427 B2	6/2010	Lee et al.
5,085,802 A	2/1992	Jalinski	7,813,916 B2	10/2010	Bean
5,146,405 A	9/1992	Church et al.	7,917,355 B2	3/2011	Wu et al.
5,254,473 A	10/1993	Patel	8,005,664 B2	8/2011	Hanumanthappa
5,369,577 A	11/1994	Kadashevich et al.	8,091,776 B2	1/2012	Nemet et al.
5,485,372 A	1/1996	Golding et al.	8,196,821 B2	6/2012	Nemet et al.
5,591,952 A	1/1997	Krichever et al.	8,271,266 B2	9/2012	Gallagher et al.
5,600,119 A	2/1997	Dvorkis et al.	8,341,520 B2	12/2012	Iakobashvili et al.
5,617,488 A	4/1997	Hong et al.	8,365,070 B2	1/2013	Song et al.
5,634,195 A	5/1997	Sawyer	8,473,278 B2	6/2013	Futagi et al.
5,659,771 A	8/1997	Golding	8,500,014 B2	8/2013	Nemet et al.
5,752,227 A	5/1998	Lyberg	8,528,808 B2	9/2013	Nemet
5,805,245 A	9/1998	Davis	8,540,156 B2	9/2013	Nemet
5,822,728 A	10/1998	Applebaum et al.	8,579,193 B2	11/2013	Nemet
5,828,991 A	10/1998	Skiena et al.	8,626,786 B2	1/2014	Halcrow et al.
5,882,116 A	3/1999	Backus	8,807,422 B2 *	8/2014	Nemet ..... G06K 19/06046 235/375
5,895,075 A	4/1999	Edwards	8,950,664 B2	2/2015	Nemet et al.
5,899,973 A	5/1999	Bandara et al.	8,960,534 B2	2/2015	Nemet et al.
5,902,982 A	5/1999	Lappe	8,967,467 B2	3/2015	Nemet et al.
5,907,839 A	5/1999	Roth	9,122,963 B2 *	9/2015	Nemet ..... G06K 19/06046
5,956,739 A	9/1999	Golding et al.	2002/0012332 A1	1/2002	Tiedemann et al.
6,006,221 A	12/1999	Liddy et al.	2002/0032564 A1	3/2002	Ehsani et al.
6,009,400 A	12/1999	Blackman	2002/0056756 A1	5/2002	Cameron et al.
6,036,092 A	3/2000	Lappe	2002/0128821 A1	9/2002	Ehsani
6,085,206 A	7/2000	Domini et al.	2002/0169595 A1	11/2002	Agichtein et al.
6,098,034 A	8/2000	Razin et al.	2003/0187632 A1	10/2003	Menich
6,154,722 A	11/2000	Bellegarda	2003/0204569 A1	10/2003	Andrews et al.
6,173,261 B1	1/2001	Arai et al.	2003/0210249 A1	11/2003	Simske
6,190,610 B1	2/2001	Goldsmith et al.	2003/0227392 A1	12/2003	Ebert et al.
6,214,623 B1	4/2001	Simons et al.	2003/0233222 A1	12/2003	Soricut et al.
6,272,242 B1	8/2001	Saitoh et al.	2004/0002849 A1	1/2004	Zhou
6,314,400 B1	11/2001	Klakow	2004/0018641 A1	1/2004	Goldsmith et al.
6,335,922 B1	1/2002	Tiedemann et al.	2004/0030540 A1	2/2004	Ovil et al.
6,366,759 B1	4/2002	Burstein et al.	2004/0093567 A1	5/2004	Schabes et al.
6,424,983 B1	7/2002	Schabes et al.	2004/0138869 A1	7/2004	Heinecke
6,456,972 B1	9/2002	Gladstein et al.	2004/0215514 A1	10/2004	Quinlan et al.
6,479,016 B1	11/2002	Goldsmith et al.	2004/0260543 A1	12/2004	Horowitz
6,495,368 B1	12/2002	Wallach	2005/0043940 A1	2/2005	Elder
6,544,925 B1	4/2003	Prusik et al.	2005/0044495 A1	2/2005	Lee et al.
6,685,094 B2	2/2004	Cameron	2005/0053900 A1	3/2005	Kaufmann
6,751,584 B2	6/2004	Bangalore	2005/0091030 A1	4/2005	Jessee et al.
6,758,397 B2	7/2004	Catan	2005/0091088 A1	4/2005	Peterson
6,920,420 B2	7/2005	Lin	2005/0108001 A1	5/2005	Aarskog
6,982,640 B2	1/2006	Lindsay et al.	2005/0120002 A1	6/2005	Behbehani
7,017,806 B2	3/2006	Peterson	2005/0139686 A1	6/2005	Helmer et al.
7,020,338 B1	3/2006	Cumbee	2005/0143971 A1	6/2005	Burstein
7,030,863 B2	4/2006	Longe et al.	2005/0162274 A1	7/2005	Shniberg et al.
7,053,777 B2	5/2006	Allen	2005/0209844 A1	9/2005	Wu et al.
7,054,293 B2	5/2006	Tiedemann et al.	2005/0257146 A1	11/2005	Ashcraft et al.
7,057,495 B2	6/2006	Debord	2006/0003297 A1	1/2006	Wiig et al.
RE39,226 E	8/2006	Lappe	2006/0032427 A1	2/2006	Ishii et al.
7,092,567 B2	8/2006	Ma et al.	2006/0048055 A1	3/2006	Wu et al.
RE39,266 E	9/2006	Lohray	2006/0057022 A1	3/2006	Williams et al.
7,117,144 B2	10/2006	Goodman et al.	2006/0074655 A1	4/2006	Bejar et al.
7,156,597 B2	1/2007	Goldsmith et al.	2006/0081711 A1	4/2006	Zhao et al.
7,157,048 B2	1/2007	Goldsmith et al.	2006/0110714 A1	5/2006	Symmes
7,165,019 B1	1/2007	Lee et al.	2006/0129381 A1	6/2006	Wakita
7,166,345 B2	1/2007	Myers et al.	2006/0247914 A1	11/2006	Brener et al.
7,184,950 B2	2/2007	Weise	2006/0260958 A1	11/2006	Brunner
7,224,346 B2	5/2007	Sheng	2007/0067177 A1	3/2007	Martin et al.
7,262,792 B2	8/2007	Shniberg et al.	2007/0094024 A1	4/2007	Kristensson et al.
7,277,088 B2	10/2007	Robinson et al.	2007/0106937 A1	5/2007	Cucerzan et al.
7,295,965 B2	11/2007	Haigh et al.	2007/0141544 A1	6/2007	Nakane
7,295,968 B2	11/2007	Bietrix et al.	2007/0238084 A1	10/2007	Maguire et al.
7,296,019 B1	11/2007	Chandrasekar et al.	2007/0265831 A1	11/2007	Dinur et al.
7,340,388 B2	3/2008	Soricut	2007/0271089 A1	11/2007	Bates et al.
7,386,442 B2	6/2008	Dehlinger et al.	2008/0059151 A1	3/2008	Chen
7,457,808 B2	11/2008	Gaussier	2008/0077859 A1	3/2008	Schabes et al.
7,475,015 B2	1/2009	Epstein et al.	2008/0154600 A1	6/2008	Tian et al.
7,558,725 B2	7/2009	Greenwald et al.	2008/0167858 A1	7/2008	Christie et al.
7,562,811 B2	7/2009	Nemet et al.	2008/0173712 A1	7/2008	Nemet et al.
7,584,093 B2	9/2009	Potter et al.	2008/0189106 A1	8/2008	Low et al.
			2008/0195940 A1	8/2008	Gail et al.
			2008/0208567 A1	8/2008	Brockett et al.
			2008/0208582 A1	8/2008	Gallino

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2008/0249773 A1 10/2008 Bejar et al.  
 2008/0270897 A1 10/2008 Jawerth et al.  
 2009/0083028 A1 3/2009 Davtchev et al.  
 2009/0198671 A1 8/2009 Zhang  
 2009/0230182 A1 9/2009 Nemet et al.  
 2009/0302102 A1 12/2009 Nemet et al.  
 2009/0319257 A1 12/2009 Blume et al.  
 2010/0020970 A1 1/2010 Liu et al.  
 2010/0050074 A1 2/2010 Nachmani et al.  
 2010/0219235 A1 9/2010 Nemet et al.  
 2010/0275118 A1 10/2010 Iakobashvili et al.  
 2010/0286979 A1 11/2010 Zangvil et al.  
 2011/0006109 A1 1/2011 Nemet et al.  
 2011/0006115 A1 1/2011 Nemet et al.  
 2011/0093268 A1 4/2011 Gorin et al.  
 2011/0184720 A1 7/2011 Zangvil  
 2012/0104105 A1 5/2012 Nemet et al.  
 2012/0104106 A1 5/2012 Nemet et al.  
 2012/0145781 A1 6/2012 Nemet et al.  
 2012/0305637 A1 12/2012 Nemet et al.  
 2013/0024185 A1 1/2013 Parikh  
 2013/0138641 A1 5/2013 Korolev et al.  
 2013/0334301 A1 12/2013 Nemet et al.  
 2014/0001256 A1 1/2014 Nemet et al.  
 2014/0110486 A1 4/2014 Nemet  
 2014/0252096 A1 9/2014 Nemet et al.  
 2014/0353385 A1 12/2014 Nemet  
 2015/0053776 A1 2/2015 Nemet et al.  
 2015/0122880 A1 5/2015 Nemet et al.  
 2015/0193677 A1 7/2015 Nemet et al.  
 2015/0220877 A1 8/2015 Nemet et al.

## FOREIGN PATENT DOCUMENTS

CN 101365934 2/2009  
 EP 936753 8/1999  
 JP 63-094383 4/1988  
 JP 63-118894 5/1988  
 JP 3-53281 3/1991  
 JP 5-6470 A 1/1993  
 JP 05-19695 1/1993  
 JP 5-67253 3/1993  
 JP 9-504858 11/1994  
 JP 2001-502794 2/2001  
 JP 2002-40012 2/2002  
 JP 2002504684 2/2002  
 JP 2003-203210 7/2003  
 JP 2003525464 8/2003  
 JP 2004-184920 7/2004  
 JP 2005-518320 6/2005  
 JP 2006-18782 1/2006  
 JP 2006-522933 10/2006  
 JP 2007-121017 5/2007  
 WO 9427144 11/1994  
 WO 9427155 11/1994  
 WO WO 9711535 3/1997  
 WO 9814777 4/1998  
 WO WO 9814777 4/1998  
 WO WO 9835514 12/1998  
 WO WO 9942822 8/1999  
 WO WO 0148680 7/2001  
 WO WO 0164430 9/2001  
 WO WO 03060626 7/2003  
 WO 2004038535 5/2004  
 WO WO 2004038353 5/2004  
 WO WO 2004092697 10/2004  
 WO 2006086053 8/2006  
 WO 2007049792 5/2007  
 WO 2008022140 2/2008  
 WO 2009016631 2/2009  
 WO WO 2007129316 4/2009  
 WO WO 2008135962 4/2009  
 WO WO 2009063464 5/2009  
 WO WO 2009063465 5/2009

WO 2009144701 12/2009  
 WO WO 2009150641 12/2009  
 WO 2010013228 2/2010  
 WO WO 2010134061 11/2010  
 WO WO 2010134062 11/2010

## OTHER PUBLICATIONS

A European Search Report dated Aug. 23, 2012, which issued during the prosecution of European Patent Application No. 08849330.9.  
 A European Search Report dated Aug. 24, 2011, which issued during the prosecution of European Patent Application No. 0 773 6287.  
 A Notice of Allowance dated Apr. 14, 2014, which issued during the prosecution of U.S. Appl. No. 13/657,185.  
 A Notice of Allowance dated Apr. 26, 2013, which issued during the prosecution of U.S. Appl. No. 12/598,979.  
 A Notice of Allowance dated Feb. 15, 2012, which issued during the prosecution of U.S. Appl. No. 12/471,798.  
 A Notice of Allowance dated Jul. 11, 2013, which issued during the prosecution of U.S. Appl. No. 13/321,477.  
 A Notice of Allowance dated May 13, 2015, which issued during the prosecution of U.S. Appl. No. 14/461,778.  
 A Notice of Allowance dated Sep. 9, 2011, which issued during the prosecution of U.S. Appl. No. 12/469,309.  
 An English Translation of an Office Action dated Aug. 27, 2013 which issued during the prosecution of Japanese Patent Application No. 2010-507054.  
 An English Translation of an Office Action dated Feb. 7, 2012, which issued during the prosecution of Japanese Patent Application No. JP2009-508663.  
 An English Translation of an Office Action dated Feb. 21, 2013 which issued during the prosecution of Japanese Patent Application No. JP2009-508663.  
 An English Translation of an Office Action dated Jan. 15, 2013 which issued during the prosecution of Japanese Patent Application No. JP2010-507054.  
 An English Translation of an Office Action dated Sep. 10, 2013 which issued during the prosecution of Japanese Patent Application No. 2011-513110.  
 An Extended European Search Report dated Feb. 11, 2013, which issued during the prosecution of European Application No. 08848845.  
 An Extended European Search Report dated Feb. 18, 2013, which issued during the prosecution of European Application No. 09762166.  
 An International Preliminary Report on Patentability dated Dec. 13, 2010, which issued during the prosecution of Applicant's PCT/IL2009/000503.  
 An International Preliminary Report on Patentability dated Mar. 10, 2009, which issued during the prosecution of Applicant's PCT/IL2007000547.  
 An International Preliminary Report on Patentability dated May 18, 2010, which issued during the prosecution of Applicant's PCT/IL2008/001495.  
 An International Preliminary Report on Patentability dated May 18, 2010, which issued during the prosecution of Applicant's PCT/IL2008/001494.  
 An International Preliminary Report on Patentability dated Nov. 10, 2009, which issued during the prosecution of Applicant's PCT/IL2007/001411.  
 An International Preliminary Report on Patentability dated Nov. 22, 2011, which issued during the prosecution of Applicant's PCT/IL2009/001167.  
 An International Preliminary Report on Patentability dated Nov. 22, 2011, which issued during the prosecution of Applicant's PCT/IL2010/000205.  
 An International Search Report and a Written Opinion both dated Aug. 31, 2009, which issued during the prosecution of Applicant's PCT/IL2009/000503.  
 An International Search Report and a Written Opinion both dated Apr. 5, 2010, which issued during the prosecution of Applicant's PCT/IL2009/001167.

(56)

**References Cited**

## OTHER PUBLICATIONS

An International Search Report and a Written Opinion both dated Jul. 17, 2008, which issued during the prosecution of Applicant's PCT/IL2007000547.

An International Search Report and a Written Opinion both dated Jan. 9, 2009, which issued during the prosecution of Applicant's PCT/IL2007/001411.

An International Search Report and a Written Opinion both dated Jun. 3, 2009, which issued during the prosecution of Applicant's PCT/IL2008/001494.

An International Search Report and a Written Opinion both dated Jun. 8, 2010, which issued during the prosecution of Applicant's PCT/IL2010/000205.

An International Search Report and a Written Opinion both dated Mar. 9, 2009, which issued during the prosecution of Applicant's PCT/IL2008/001495.

An Office Action dated Apr. 19, 2011, which issued during the prosecution of U.S. Appl. No. 12/469,309.

An Office Action dated Apr. 25, 2012, which issued during the prosecution of U.S. Appl. No. 12/598,979.

An Office Action dated Dec. 19, 2012, which issued during the prosecution of U.S. Appl. No. 12/742,650.

An Office Action dated Jan. 21, 2015, which issued during the prosecution of U.S. Appl. No. 14/461,778.

An Office Action dated Jul. 12, 2013, which issued during the prosecution of European Patent Application No. 07 736 287.9.

An Office Action dated Jun. 20, 2008, which issued during the prosecution of U.S. Appl. No. 11/852,911.

An Office Action dated Mar. 9, 2012, which issued during the prosecution of U.S. Appl. No. 12/743,209.

An Office Action dated Mar. 15, 2013, which issued during the prosecution of U.S. Appl. No. 13/321,467.

An Office Action dated Mar. 20, 2013, which issued during the prosecution of U.S. Appl. No. 13/321,477.

An Office Action dated May 3, 2011, which issued during the prosecution of U.S. Appl. No. 12/471,798.

An Office Action dated Nov. 7, 2011, which issued during the prosecution of U.S. Appl. No. 12/598,979.

An Office Action dated Nov. 7, 2012, which issued during the prosecution of U.S. Appl. No. 12/743,209.

An Office Action dated Sep. 10, 2013, which issued during the prosecution of U.S. Appl. No. 13/657,185.

An Office Action dated Sep. 25, 2014, which issued during the prosecution of U.S. Appl. No. 14/461,778.

An Office Action together with the English translation dated Jun. 25, 2013 which issued during the prosecution of Japanese Patent Application No. 2012-511406.

An Office Action together with the English translation dated Oct. 25, 2012 which issued during the prosecution of Israel Patent Application No. 201958.

U.S. Appl. No. 60/746,646, filed May 7, 2006.

U.S. Appl. No. 60/804,072, filed Jun. 6, 2006.

U.S. Appl. No. 61/131,644, filed Jun. 10, 2008.

U.S. Appl. No. 61/231,799, filed Aug. 6, 2009.

An Office Action dated Nov. 4, 2013, which issued during the prosecution of U.S. Appl. No. 13/323,906.

A Notice of Allowance dated Nov. 18, 2014, which issued during the prosecution of U.S. Appl. No. 13/323,906.

A Notice of Allowance dated Apr. 23, 2014, which issued during the prosecution of U.S. Appl. No. 13/323,906.

A Notice of Allowance dated Apr. 25, 2014, which issued during the prosecution of U.S. Appl. No. 13/490,705.

A Notice of Allowance dated Nov. 7, 2014, which issued during the prosecution of U.S. Appl. No. 13/490,705.

An English translation of an Office Action dated Feb. 3, 2014 which issued during the prosecution of Japanese Patent Application No. 2012-511407.

An English translation of an Office Action dated Aug. 26, 2014 which issued during the prosecution of Japanese Patent Application No. 2012-511407.

An Office Action dated Mar. 6, 2015, which issued during the prosecution of U.S. Appl. No. 14/055,422.

An English Translation of an Office Action dated Dec. 24, 2013 which issued during the prosecution of Chinese Patent Application No. 200980160387.4.

An Office Action dated Jan. 16, 2013, which issued during the prosecution of U.S. Appl. No. 12/598,979.

An Office Action dated Mar. 20, 2012, which issued during the prosecution of U.S. Appl. No. 13/321,477.

An Office Action dated Aug. 14, 2015, which issued during the prosecution of U.S. Appl. No. 14/055,422.

An English Translation of an Office Action dated Feb. 26, 2013 which issued during the prosecution of Japanese Patent Application No. JP2009-508663.

An Office Action dated Oct. 28, 2013, which issued during the prosecution of U.S. Appl. No. 14/017,545.

European Search Report dated Aug. 18, 2011, which issued during the prosecution of European Patent Application No. 0 773 6287.

A Notice of Allowance dated Apr. 2, 2013, which issued during the prosecution of U.S. Appl. No. 12/743,209.

An English Translation of an Office Action dated May 22, 2015 which issued during the prosecution of Chinese Patent Application No. 200980160387.4.

An Examiner Interview Summary Report dated Nov. 7, 2008, which issued during the prosecution of U.S. Appl. No. 11/852,911.

A Notice of Allowance dated Feb. 25, 2009, which issued during the prosecution of U.S. Appl. No. 11/852,911.

A Notice of Allowance dated May 16, 2013, which issued during the prosecution of U.S. Appl. No. 12/742,650.

An Office Action dated Sep. 18, 2014, which issued during the prosecution of U.S. Appl. No. 14/143,827.

A Notice of Allowance dated Oct. 15, 2014, which issued during the prosecution of U.S. Appl. No. 14/017,545.

A Notice of Allowance dated Apr. 17, 2009, which issued during the prosecution of U.S. Appl. No. 11/852,911.

An Office Action dated Sep. 9, 2011, which issued during the prosecution of U.S. Appl. No. 12/471,798.

An Office Action dated Oct. 12, 2012, which issued during the prosecution of U.S. Appl. No. 12/669,175.

An Office Action dated Aug. 5, 2013, which issued during the prosecution of U.S. Appl. No. 12/669,175.

An Office Action dated Feb. 5, 2013, which issued during the prosecution of U.S. Appl. No. 12/669,175.

An Office Action dated Mar. 7, 2014, which issued during the prosecution of U.S. Appl. No. 12/669,175.

A Notice of Allowance dated Aug. 4, 2014, which issued during the prosecution of U.S. Appl. No. 12/669,175.

An English Translation of an Office Action dated Apr. 22, 2014 which issued during the prosecution of Israeli Patent Application No. 205687.

An English Translation of an Office Action dated Oct. 27, 2014 which issued during the prosecution of Israeli Patent Application No. 209901.

An Office Action dated Jul. 1, 2014, which issued during the prosecution of U.S. Appl. No. 13/576,330.

An English Translation of an Office Action dated Jun. 13, 2014 which issued during the prosecution of Chinese Patent Application No. 200880101405.7.

Letter submitted on Jul. 17, 2009 in U.S. Appl. No. 11/852,911.

An Office Action dated May 9, 2013, which issued during the prosecution of U.S. Appl. No. 12/937,618.

An English Translation of an Office Action dated Jan. 25, 2013 which issued during the prosecution of Chinese Patent Application No. 200880101405.7.

An English Translation of an Office Action dated Apr. 28, 2012 which issued during the prosecution of Chinese Patent Application No. 200880101405.7.

A Notice of Allowance dated Jun. 27, 2014, which issued during the prosecution of U.S. Appl. No. 14/017,545.

A Supplementary European Search Report dated Jul. 5, 2012, which issued during the prosecution of European Patent Application No. 08789727.

(56)

**References Cited**

## OTHER PUBLICATIONS

An English Translation of an Office Action dated Jun. 23, 2011 which issued during the prosecution of Chinese Patent Application No. 200880101405.7.

An International Search Report and a Written Opinion both dated May 25, 2011, which issued during the prosecution of Applicant's PCT/IL2011/00088.

An International Search Report dated May 11, 2009, which issued during the prosecution of Applicant's PCT/IL2009/00130.

An International Search Report dated Jun. 26, 2009, which issued during the prosecution of Applicant's PCT/IL2009/00317.

An International Preliminary Examination Report dated Oct. 19, 2010, which issued during the prosecution of Applicant's PCT/IL2009/00317.

Bick, E., "A Constraint Grammar Based Spellchecker for Danish with a Special Focus on Dyslexics" SKY Journal of Linguistics, vol. 19:2006 (ISSN 1796-279X), pp. 387-396 (retrieved Jan. 12, 2009 from the internet). <URL [http://www.ling.helsinki.fi/sky/julkaisut/SKY2006\\_1/1.6.1.%20BICK.pdf](http://www.ling.helsinki.fi/sky/julkaisut/SKY2006_1/1.6.1.%20BICK.pdf)>.

An International Search Report and Written Opinion both dated Feb. 3, 2009 which issued during the prosecution of Applicant's PCT/IL08/01051.

An Office Action dated Jan. 10, 2014, which issued during the prosecution of European Patent Application No. 08848845.

An Office Action dated Jun. 5, 2014, which issued during the prosecution of U.S. Appl. No. 14/017,545.

A Supplementary European Search Report dated Apr. 13, 2011, which issued during the prosecution of European Patent Application No. 07827384.

An Office Action dated Feb. 11, 2015, which issued during the prosecution of U.S. Appl. No. 13/958,893.

An English Translation of an Office Action dated Feb. 18, 2014 which issued during the prosecution of Japanese Patent Application No. JP2009-508663.

U.S. Appl. No. 60/963,956, filed May 7, 2006.

U.S. Appl. No. 60/959,120, filed Jun. 6, 2006.

An English Translation of an Office Action dated Nov. 4, 2014 which issued during the prosecution of Chinese Patent Application No. 201080030956.6.

An English Translation of an Office Action dated Apr. 19, 2015 which issued during the prosecution of Israeli Patent Application No. 216396.

An English Translation of an Office Action dated Nov. 15, 2014 which issued during the prosecution of Chinese Patent Application No. 200980160387.4.

An English Translation of an Office Action dated Jan. 6, 2014 which issued during the prosecution of Chinese Patent Application No. 201080030956.6.

An English translation of an Office Action dated Jul. 28, 2015 which issued during the prosecution of Japanese Patent Application No. 2014-125707.

An Office Action dated May 29, 2015, which issued during the prosecution of U.S. Appl. No. 13/958,893.

An Office Action dated Jul. 28, 2015, which issued during the prosecution of U.S. Appl. No. 14/595,412.

U.S. Appl. No. 62/163,193, filed May 18, 2015.

U.S. Appl. No. 62/189,367, filed Jul. 7, 2015.

An English translation of an Office Action dated Aug. 27, 2015 which issued during the prosecution of Japanese Patent Application No. 2014-218223.

An English Translation of an Office Action dated Dec. 31, 2015 which issued during the prosecution of Israeli Patent Application No. 209901.

An English Translation of an Office Action dated Apr. 20, 2015 which issued during the prosecution of Israeli Patent Application No. 216397.



A Supplementary European Search Report dated Sep. 16, 2015, which issued during the prosecution of European Patent Application No. 10777451.5.


European Search Report dated Sep. 16, 2015, which issued during the prosecution of European Patent Application No. 09844849.

A Notice of Allowance dated Dec. 8, 2015, which issued during the prosecution of U.S. Appl. No. 14/055,422.

An Office Action dated Nov. 19, 2013, which issued during the prosecution of European Application No. 07827384.4.

\* cited by examiner








FIG. 4

FIG. 5






FIG. 6B

FIG. 6A




FIG. 6C

FIG. 6D

FIG. 6E

1

## TAMPER-PROOF QUALITY MANAGEMENT BARCODE INDICATORS

### REFERENCE TO RELATED APPLICATIONS

Reference is made to the following patent and patent application, owned by assignee, the disclosures of which are hereby incorporated by reference:

U.S. Pat. Nos. 7,562,811 and 8,091,776; and  
U.S. Published Patent Application Nos.: 2009/0230182; 2010/0219235; 2011/0006109 and 2011/0006115; and  
U.S. patent application Ser. Nos. 13/321,467; 13/321,477 and 13/323,906.

### FIELD OF THE INVENTION

The present invention relates to tamper-proof quality management barcode indicators.

### BACKGROUND OF THE INVENTION

The following publications are believed to represent the current state of the art:

U.S. Pat. Nos. 5,805,245; 6,009,400; 6,685,094; 6,758,397; 7,562,811; 8,091,776 and RE 39,266; and  
U.S. Published Patent Application Nos.: 2009/0230182, 2010/0219235, 2011/0006109 and 2011/0006115.

### SUMMARY OF THE INVENTION

The present invention seeks to provide tamper-proof quality management barcode indicators.

There is thus provided in accordance with a preferred embodiment of the present invention a tamper-proof bar-coded quality indicator operative to provide a machine-readable indication of exceedance of at least one time and temperature threshold following actuation thereof, the indicator including a first barcode including at least one first colorable area, the first barcode being machine-readable before exceedance of the at least one time and temperature threshold, at least a second barcode including at least one second colorable area, the second barcode not being machine-readable before exceedance of the at least one time and temperature threshold, a coloring agent located at a first location on the indicator, a coloring agent pathway operative, following actuation of said quality indicator, to allow the coloring agent to move, at a rate which is at least partially a function of time, from the first location to the first and second colorable areas simultaneously for simultaneous coloring thereof upon exceedance of the time and temperature threshold, thereby causing the first barcode to become unreadable and at the same time causing the second barcode to become machine-readable, and a tamper-proof actuator element operative to actuate the quality indicator upon removal thereof from said quality indicator.

Preferably, the tamper-proof actuator element is disposed between the coloring agent and the coloring agent pathway prior to actuation of the quality indicator, thereby preventing passage of the coloring agent to the coloring agent pathway. Preferably, the tamper-proof actuator element is formed of a thin flexible material. Preferably, the tamper-proof actuator element includes a pullable actuator tab which protrudes from the quality indicator prior to actuation of the tamper-proof bar-coded quality indicator. Preferably, the actuation of the quality indicator includes irreversibly removing the tamper-proof actuator element from the quality indicator, thereby irreversibly enabling passage of the coloring agent to the coloring agent pathway.

2

Preferably, the quality indicator also includes a release layer which is adhered to an adhesive back surface of the quality indicator. Preferably, removal of the release layer is operative to expose the adhesive back surface which is operable for adhering the quality indicator to a product for which quality is to be monitored. Preferably, the release layer includes a release tab operable for enabling release of the release layer from the adhesive back surface.

There is also provided in accordance with another preferred embodiment of the present invention a barcoded quality indicator operative to provide a machine-readable indication of exceedance of at least one time and temperature threshold following actuation thereof, the indicator including a first barcode including at least one first colorable area, the first barcode being machine-readable before exceedance of the at least one time and temperature threshold, at least a second barcode including at least one second colorable area, the second barcode not being machine-readable before exceedance of the at least one time and temperature threshold, a coloring agent located at a first location on the indicator, a coloring agent pathway operative, following actuation of said quality indicator, to allow the coloring agent to move, at a rate which is at least partially a function of time, from the first location to the first and second colorable areas simultaneously for simultaneous coloring thereof upon exceedance of the time and temperature threshold, thereby causing the first barcode to become unreadable and at the same time causing the second barcode to become machine-readable, an actuator element operative to actuate the quality indicator upon removal thereof from said quality indicator, and a sealing element operative to seal the coloring agent pathway subsequent to removal of the actuator element.

Preferably, the actuator element is disposed between the coloring agent and the coloring agent pathway prior to actuation of the quality indicator, thereby preventing passage of the coloring agent to the coloring agent pathway. Preferably, the actuator element includes a pullable actuator tab which protrudes from the quality indicator prior to actuation of the barcoded quality indicator. Preferably, the actuation of the quality indicator includes irreversibly removing the actuator element from the quality indicator, thereby irreversibly enabling passage of the coloring agent to the coloring agent pathway.

Preferably, the quality indicator also includes a release layer which is adhered to an adhesive back surface of the quality indicator. Preferably, removal of the release layer is operative to expose the adhesive back surface which is operable for adhering the quality indicator to a product for which quality is to be monitored. Preferably, the release layer includes a release tab operable for enabling release of the release layer from the adhesive back surface.

Preferably, the sealing element includes a sealing tab operable for foldable sealing of the coloring agent pathway. Preferably, the sealing tab is operable for selectable adherence to the adhesive back surface, thereby sealing the coloring agent pathway.

### BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be understood more fully from the following detailed description, taken in conjunction with the drawings in which:

FIG. 1 is a simplified illustration of the structure of a tamper-proof bar-coded quality indicator, constructed and operative in accordance with a preferred embodiment of the present invention;

3

FIG. 2 is a simplified illustration of the assembled tamper-proof barcoded quality indicator of FIG. 1;

FIGS. 3A, 3B and 3C are simplified pictorial illustrations of steps in the actuation of the tamper-proof barcoded quality indicator of FIGS. 1 and 2;

FIG. 4 is a simplified illustration of the structure of a barcoded quality indicator, constructed and operative in accordance with another preferred embodiment of the present invention;

FIG. 5 is a simplified illustration of the assembled barcoded quality indicator of FIG. 4; and

FIGS. 6A, 6B, 6C, 6D and 6E are simplified pictorial illustrations of steps in the actuation of the barcoded quality indicator of FIGS. 4 and 5.

#### DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

Reference is now made to FIG. 1, which is a simplified illustration of the structure of a tamper-proof barcoded quality indicator, constructed and operative in accordance with a preferred embodiment of the present invention, and to FIG. 2, which is a simplified illustration of the assembled tamper-proof barcoded quality indicator of FIG. 1.

The tamper-proof barcoded quality indicator of FIGS. 1 & 2 is preferably operative to provide a machine-readable indication of exceedance of at least one time and temperature threshold following actuation thereof, and includes a first barcode including at least one first colorable area, the first barcode being machine-readable before exceedance of the at least one time and temperature threshold and at least a second barcode including at least one second colorable area, the second barcode not being machine-readable before exceedance of the at least one time and temperature threshold.

Preferably, the indicator also includes a coloring agent located at a first location on the indicator and a coloring agent pathway operative to allow the coloring agent to move, at a rate which is at least partially a function of time, from the first location to the first and second colorable areas simultaneously for simultaneous coloring thereof upon exceedance of the time and temperature threshold, thereby causing the first barcode to become unreadable and at the same time causing the second barcode to become machine-readable.

A system and method for quality management which utilizes the barcoded quality indicator of FIGS. 1 & 2 is clearly described, inter alia, in U.S. Pat. No. 8,091,776 of the applicant, which is incorporated herein by reference.

It is a particular feature of this embodiment of the present invention that the tamper-proof barcoded quality indicator of FIG. 1 also includes a tamper-proof actuator element operative to prevent passage of the coloring agent to the coloring agent pathway prior to removal thereof, and to irreversibly enable passage of the coloring agent to the coloring agent pathway following removal thereof.

As shown in FIGS. 1 & 2, tamper-proof barcoded quality indicator 100 preferably includes a barcode defining layer 102 having a multiplicity of barcodes 110 printed thereupon. Barcode defining layer 102 is preferably formed of a transparent substrate.

A coloring agent pathway 120 is preferably disposed behind barcode defining layer 102. A tamper-proof actuator pull strip 122 is preferably disposed between coloring agent pathway 120 and a back layer 130 having a coloring element 132 mounted thereupon, which coloring element 132 preferably contains coloring agents. Tamper-proof actuator pull strip 122 preferably prevents the passage therethrough of

4

coloring agents from coloring element 132 to coloring agent pathway 120 when quality indicator 100 in a pre-actuated state.

A release layer 134 is preferably adhered to an adhesive back surface 136 of back layer 130. Removal of release layer is operative to expose adhesive back surface 136 which is operable for adhering quality indicator 100 to a product for which quality is to be monitored. Release layer 140 preferably includes a release tab 138 operable for easy release of release layer 140 from back surface 142.

FIG. 2 illustrates tamper-proof barcoded quality indicator 100 in an assembled, pre-actuated state. As shown particularly in FIG. 2, an actuator tab 140 of tamper-proof actuator pull strip 122 preferably protrudes from quality indicator 100, between coloring agent pathway 120 and back layer 130.

Reference is now made to FIGS. 3A, 3B and 3C, which are simplified pictorial illustrations of steps in the actuation of the tamper-proof barcoded quality indicator of FIGS. 1 & 2. As shown in FIGS. 3A-3C, after affixing tamper-proof barcoded quality indicator 100 to a product 190, indicator 100 is actuated by pulling on actuator tab 140 of tamper-proof actuator pull strip 122 and removing tamper-proof actuator pull strip 122 from between coloring agent pathway 120 and back layer 130. It is appreciated that removal of tamper-proof actuator pull strip 122 from between coloring agent pathway 120 and back layer 130 allows the passage of coloring agents contained in coloring element 132 to coloring agent pathway 120, thereby actuating proof barcoded quality indicator 100.

It is appreciated that tamper-proof actuator pull strip 122 is formed of a flexible material, such as a thin paper. Therefore, as shown in particular in FIG. 3C, it is a particular feature of this embodiment of the present invention that once removed from between coloring agent pathway 120 and back layer 130, tamper-proof actuator pull strip 122 cannot be re-inserted between coloring agent pathway 120 and back layer 130 due to the flexible nature of tamper-proof actuator pull strip 122, thereby preventing indicator 100 from returning to a pre-actuated state.

Reference is now made to FIG. 4, which is a simplified illustration of the structure of a barcoded quality indicator, constructed and operative in accordance with another preferred embodiment of the present invention, and to FIG. 5, which is a simplified illustration of the assembled barcoded quality indicator of FIG. 4.

The barcoded quality indicator of FIGS. 4 & 5 is preferably operative to provide a machine-readable indication of exceedance of at least one time and temperature threshold following actuation thereof, and includes a first barcode including at least one first colorable area, the first barcode being machine-readable before exceedance of the at least one time and temperature threshold and at least a second barcode including at least one second colorable area, the second barcode not being machine-readable before exceedance of the at least one time and temperature threshold.

Preferably, the indicator also includes a coloring agent located at a first location on the indicator and a coloring agent pathway operative to allow the coloring agent to move, at a rate which is at least partially a function of time, from the first location to the first and second colorable areas simultaneously for simultaneous coloring thereof upon exceedance of the time and temperature threshold, thereby causing the first barcode to become unreadable and at the same time causing the second barcode to become machine-readable.

A system and method for quality management which utilizes the barcoded quality indicator of FIGS. 4 & 5 is clearly described, inter alia, in U.S. Pat. No. 8,091,776 of the applicant, which is incorporated herein by reference.

## 5

Preferably, the barcoded quality indicator of FIGS. 4 and 5 also includes an actuator element operative to prevent passage of the coloring agent to the coloring agent pathway prior to removal thereof, and to irreversibly enable passage of the coloring agent to the coloring agent pathway following removal thereof.

It is a particular feature of this embodiment of the present invention that the barcoded quality indicator of FIGS. 4 and 5 also includes a sealing element operative to seal the coloring agent pathway subsequent to removal of the actuator element.

As shown in FIGS. 4 & 5, barcoded quality indicator 200 preferably includes a barcode defining layer 202 having a multiplicity of barcodes 210 printed thereupon. Barcode defining layer 202 is preferably formed of a transparent substrate, and is preferably formed with a foldable sealing tab 212.

A coloring agent pathway 220 is preferably disposed behind barcode defining layer 202. An actuator pull strip 222 is preferably disposed between coloring agent pathway 220 and a back layer 230 having a coloring element 232 mounted thereupon, which coloring element 232 preferably contains coloring agents. Actuator pull strip 222 preferably prevents the passage therethrough of coloring agents from coloring element 232 to coloring agent pathway 220 when quality indicator 200 in a pre-actuated state.

A release layer 234 is preferably adhered to an adhesive back surface 236 of back layer 230. Removal of release layer is operative to expose adhesive back surface 236 which is operable for adhering quality indicator 200 to a product for which quality is to be monitored. Release layer 234 preferably includes a release tab 238 operable for easy release of release layer 234 from back surface 236.

FIG. 5 illustrates barcoded quality indicator 200 in an assembled, pre-actuated state. As shown particularly in FIG. 5, an actuator tab 240 of actuator pull strip 222 preferably protrudes from quality indicator 200, between coloring agent pathway 220 and back layer 230.

Reference is now made to FIGS. 6A, 6B, 6C, 6D and 6E, which are simplified pictorial illustrations of steps in the actuation of the barcoded quality indicator of FIGS. 4 and 5. As shown in FIGS. 6A & 6B, indicator 200 is actuated by pulling on actuator tab 240 of actuator pull strip 222 and removing actuator pull strip 222 from between coloring agent pathway 220 and back layer 230. It is appreciated that removal of actuator pull strip 222 from between coloring agent pathway 220 and back layer 230 allows the passage of coloring agents contained in coloring element 232 to coloring agent pathway 220, thereby actuating proof barcoded quality indicator 200. It is also appreciated that removal of actuator pull strip 222 from between coloring agent pathway 220 and back layer 230 is operative to expose an open slit 250 formed between coloring agent pathway 220 and back layer 230.

Thereafter, as shown in FIG. 6C, release layer 234 is removed from adhesive back surface 236, thereby exposing adhesive back surface 236 which is operable for adhering quality indicator 200 to a pallet of produce 260 for which quality is to be monitored. Thereafter, as shown in FIG. 6D, slit 250 is sealed by folding foldable sealing tab 212 over slit 250 and adhering tab 212 to adhesive back surface 236.

It is a particular feature of this embodiment of the present invention that sealing of slit 250 by folding sealing tab 212 over slit 250 onto adhesive back surface 236 is operative to prevent environmental elements, such as moisture, from entering slit 250. It is appreciated that entry of moisture into slit 250 may damage, for example, any one of barcode defining layer 202, barcodes 210, and coloring agents contained in

## 6

coloring element 232 or located in coloring agent pathway 220, thereby rendering quality indicator 200 inaccurate.

As shown in FIG. 6E, after sealing of slit 250, indicator 200 is adhered to pallet 260.

It will be appreciated by persons skilled in the art that the present invention is not limited by what has been particularly shown and described hereinabove. Rather the scope of the present invention includes both combinations and subcombinations of various features described hereinabove and variations and modifications thereof which would occur to persons skilled in the art upon reading the foregoing, which are not in the prior art.

The invention claimed is:

1. A barcoded quality indicator operative to provide a machine-readable indication of exceedance of at least one threshold following actuation thereof, said indicator comprising:

a first barcode including at least one first colorable area, said first barcode being machine-readable before exceedance of said at least one threshold;

at least a second barcode including at least one second colorable area, said second barcode not being machine-readable before exceedance of said at least one threshold;

a coloring agent located at a first location on said indicator;

a coloring agent pathway operative, following actuation of said quality indicator, to allow said coloring agent to move from said first location to said first and second colorable areas simultaneously for simultaneous coloring thereof upon exceedance of said threshold, thereby causing said first barcode to become unreadable and at the same time causing said second barcode to become machine-readable;

an actuator element operative to actuate said quality indicator upon removal thereof from said quality indicator; and

a sealing element operative to seal said coloring agent pathway subsequent to removal of said actuator element, said sealing element comprising a foldable sealing tab operative to prevent damage to said barcoded quality indicator.

2. A barcoded quality indicator according to claim 1 and wherein said actuator element is disposed between said coloring agent and said coloring agent pathway prior to actuation of said quality indicator, thereby preventing passage of said coloring agent to said coloring agent pathway.

3. A barcoded quality indicator according to claim 1 and wherein said actuator element comprises a pullable actuator tab which protrudes from said quality indicator prior to actuation of said barcoded quality indicator.

4. A barcoded quality indicator according to claim 1 and wherein said actuation of said quality indicator comprises irreversibly removing said actuator element from said quality indicator, thereby irreversibly enabling passage of said coloring agent to said coloring agent pathway.

5. A barcoded quality indicator according to claim 1 and wherein said quality indicator also comprises a release layer which is adhered to an adhesive back surface of said quality indicator.

6. A barcoded quality indicator according to claim 5 and wherein removal of said release layer is operative to expose said adhesive back surface which is operable for adhering said quality indicator to a product for which quality is to be monitored.

7

8

7. A barcoded quality indicator according to claim 5 and wherein said release layer comprises a release tab operable for enabling release of said release layer from said adhesive back surface.

\* \* \* \* \*

5