



US009414674B2

(12) **United States Patent**  
**Park et al.**

(10) **Patent No.:** **US 9,414,674 B2**  
(45) **Date of Patent:** **Aug. 16, 2016**

(54) **AUTOMATIC CLOSING APPARATUS**

(71) Applicants: **SEGOS CO.,LTD.**, Incheon (KR); **Yoon Sig Park**, Seoul (KR)

(72) Inventors: **Yoon Sig Park**, Seoul (KR); **Hyun ho Cha**, Gyeonggi-do (KR); **Jae Won Kim**, Incheon (KR)

(73) Assignees: **SEGOS CO., LTD.**, Incheon (KR); **Yoon Sig Park**, Seoul (KR)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/438,578**

(22) PCT Filed: **Oct. 8, 2013**

(86) PCT No.: **PCT/KR2013/008978**

§ 371 (c)(1),  
(2) Date: **Apr. 24, 2015**

(87) PCT Pub. No.: **WO2014/065523**

PCT Pub. Date: **May 1, 2014**

(65) **Prior Publication Data**

US 2015/0230603 A1 Aug. 20, 2015

(30) **Foreign Application Priority Data**

Oct. 24, 2012 (KR) ..... 10-2012-0118311

(51) **Int. Cl.**

**A47B 88/00** (2006.01)  
**A47B 88/04** (2006.01)  
**A47B 96/00** (2006.01)  
**A47B 88/16** (2006.01)

(52) **U.S. Cl.**

CPC ..... **A47B 88/047** (2013.01); **A47B 88/04** (2013.01); **A47B 88/16** (2013.01); **A47B 96/00** (2013.01)

(58) **Field of Classification Search**

CPC ..... **A47B 88/04**; **A47B 88/0422**; **A47B 2210/0054**; **A47B 2088/0433**; **A47B 2088/0437**; **A47B 88/047**; **A47B 88/16**; **A47B 96/00**

USPC ..... **312/334.4**, **334.6**  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

5,439,283 A \* 8/1995 Schroder et al. .... 312/334.4  
5,580,139 A \* 12/1996 Grabher ..... 312/333  
5,588,729 A \* 12/1996 Berger ..... 312/334.4  
6,913,334 B2 \* 7/2005 Weichelt ..... 312/334.4  
7,226,139 B2 \* 6/2007 Salice ..... 312/334.4  
7,549,712 B2 \* 6/2009 Booker et al. .... 312/334.6  
8,056,994 B2 \* 11/2011 Chen et al. .... 312/334.6  
8,449,051 B2 \* 5/2013 Lam et al. .... 312/333  
8,727,460 B2 \* 5/2014 Grabher ..... 312/333

(Continued)

**FOREIGN PATENT DOCUMENTS**

JP 3053935 U 9/1998  
KR 10-2004-0042843 A 5/2004

(Continued)



*Primary Examiner* — Hanh V Tran

(74) *Attorney, Agent, or Firm* — The PL Law Group, PLLC

(57) **ABSTRACT**

A slide attachment and detachment device for a drawer. The slide attachment and detachment device for a drawer is formed as one member, thereby reducing time and costs consumed for manufacturing the slide attachment and detachment device for the drawer, improving hygienic properties, and enabling use in environments with high humidity.

**8 Claims, 8 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

8,764,136 B2 \* 7/2014 Grabherr ..... 312/334.4  
8,919,711 B2 \* 12/2014 Holzer et al. .... 248/201  
8,979,223 B2 \* 3/2015 Huang ..... 312/334.4  
8,991,952 B2 \* 3/2015 Salice ..... 312/334.4  
9,060,604 B2 \* 6/2015 Salice  
2008/0265729 A1 \* 10/2008 Netzer et al. .... 312/330.1

2009/0236959 A1 \* 9/2009 Liang et al. .... 312/334.4  
2009/0251037 A1 \* 10/2009 Berger ..... 312/334.1

FOREIGN PATENT DOCUMENTS

KR 10-2007-0116962 A 12/2007  
KR 10-2012-0113151 A 10/2012

\* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7





FIG. 8



**AUTOMATIC CLOSING APPARATUS****CROSS REFERENCE TO RELATED APPLICATIONS AND CLAIM OF PRIORITY**

This patent application claims benefit under 35 U.S.C. 119(e), 120, 121, or 365(c), and is a National Stage entry from International Application No. PCT/KR2013/008978, filed Oct. 8, 2013, which claims priority to Korean Patent Application No. 10-2012-0118311, filed July Oct. 24, 2012, the entire contents of which are incorporated herein by reference.

**TECHNICAL FIELD**

The present invention relates to a slide attachment and detachment device for a drawer that can connect the drawer to a slide intended for guiding pushing or pulling of the drawer or that can separate the drawer from the slide.

**BACKGROUND ART**

Generally, a receiving means for furniture such as a wardrobe, a cabinet or the like, and electrical appliances such as a refrigerator or the like includes: a drawer in which a storage product can be received; and a receiving body in which the drawer is received, wherein a slide intended for guiding pulling and pushing of the drawer is installed between the drawer and the receiving body so that the drawer can easily open and close.

There may be generated a case where a portion of the drawer is damaged during use of the drawer, and thus components should be replaced, or a case where the drawer should be completely separated from the slide in order to easily arrange products received in the drawer or to clean an inner portion of the drawer.

Meanwhile, when the drawer is large in size, or a storage product received in the drawer is heavy in weight, a load applied to the drawer is increased. In such a case, an undermount slide supporting the load of the drawer from a lower side may be applied.

Due to the reason described above, various types of slide attachment and detachment devices for a drawer intended for connecting the drawer to which the undermount slide is applied to the slide, or separating the drawer from the slide have been researched and developed. As a part thereof, the inventors of the present application have also suggested a relevant technology through Korean Utility Model No. 20-0396803 (Reg. Date: Sep. 20, 2005, Title of the device: Apparatus for adjusting horizontal tilting in drawer).

The slide attachment and detachment devices for a drawer, which have been suggested up to date, use a latch connection structure in which an elastic body is used in the slide attachment and detachment device so that the slide can be easily attached to or detached from the drawer. At this time, in order for the slide to be easily attached to or detached from the drawer, an elastic force of the elastic body should be weak. However, in a case where the elastic body having a weak elastic force is used, when the drawer is pulled at a rapid speed, the drawer pulled by a pulling limitation of the slide, and storage products cause a large impact force on a connecting part of the slide attachment and detachment device due to an inertia force thereof. Due to this, a connection of the slide and the slide attachment and detachment device may be released.

Also, since a plurality of components, including a metal elastic body, is mainly used, an assembly step should be necessarily included in a process for manufacturing the com-

ponents, so a cost resulting therefrom may be generated. Furthermore, in the slide attachment and detachment devices for a drawer including the metal elastic body, when the drawer is installed in an environment with high humidity and is used for a long time, corrosion is generated from the metal elastic body so that storage products can be contaminated, and elasticity can be reduced. When foreign substances are inserted into a moving portion, the foreign substances can be mixed with the storage products, or the drawer cannot be smoothly attached to or detached from the slide.

**SUMMARY**

An object of an exemplary embodiment of the present invention is to provide a slide attachment and detachment device for a drawer capable of saving production time and cost consumed for manufacturing the slide attachment and detachment device for the drawer.

Also, another object of the exemplary embodiment of the present invention is to provide a slide attachment and detachment device for a drawer that can be used in environments having high humidity.

Also, a further object of the exemplary embodiment of the present invention is to a slide attachment and detachment device for a drawer in which an elastic support part supports a pulling shock of the drawer and enables an attachment and detachment function to be smoothly performed.

According to an aspect of the present invention, a slide attachment and detachment device for a drawer, which connects the drawer to a slide intended for supporting the drawer and a bottom part of the drawer and for guiding pulling or pushing of the drawer, or which separates the drawer from the slide, may include: a connecting part fixedly connected to at least one selected from a front part and a bottom part of the drawer; a fixation support part formed to protrude from the connecting part in a direction parallel to a pulling or pushing direction of the drawer, and having an operation hole formed to pass through a direction parallel to a direction toward one side of the slide in its central portion when the slide is positioned to support the drawer; an elastic support part formed to protrude from one edge of the operation hole and to cover the operation hole; and a level part formed to extend from an end of the elastic support part, one end of which has a coupling protrusion formed to protrude toward the slide by passing through the operation hole, and the other end of which protrudes in a direction opposite to the coupling protrusion, wherein when an external force parallel to the bottom part of the drawer and toward the slide is applied to the lever part, the elastic support part is elastically changed, so the coupling protrusion is pulled back into the operation hole, and when the external force applied to the lever part is released, the elastic support part is elastically returned, so the coupling protrusion protrudes to an outer portion of the operation hole.

Here, a portion of the elastic support part connected to the fixation support part may be positioned in the pushing direction of the drawer within the operation hole.

Also, a connecting neck having a minimum cross-sectional area may be formed in the elastic support part.

As described above, the slide attachment and detachment device for the drawer further include: an inclination control member connecting groove parallel to the operation hole and having one side opened toward the slide, and formed in the coupling part; an inclination control member slidably movably connected to the inclination control member connecting groove; and a wedge protrusion protruding toward an opening portion of the inclination control member connecting groove, and formed in the inclination control member, wherein the

wedge protrusion is interposed between a bottom surface of the drawer and the slide when the slide is positioned to support the drawer, and the inclination control member is slidably moved in a direction toward the slide, so a distance between the bottom surface of the drawer and the slide is extended.

Also, the slide attachment and detachment device for the drawer may further include a shock absorbing part formed to protrude from the coupling part and disposed between the end of the slide and the front part of the drawer when the slide is positioned to support the drawer.

Also, as described above, with regard to the slide attachment and detachment device for the drawer, the connecting part, the fixation support part, the elastic support part, and the lever part may be made of a synthetic resin.

According to an exemplary embodiment of the present invention, a slide attachment and detachment device for a drawer is formed as one member so that time and costs consumed for manufacturing the slide attachment and detachment device for the drawer can be saved, and a moving portion into which foreign substances may be inserted is not formed so that hygienic properties can be improved.

Also, according to the exemplary embodiment of the present invention, a metal elastic body is not included in the slide attachment and detachment device for the drawer, thereby enabling use in environments with high humidity.

Also, according to the exemplary embodiment of the present invention, an elastic support part of the slide attachment and detachment device for the drawer disperses a pulling shock of the drawer as compressive stress so that a connection of the drawer and the slide can be prevented from being unintentionally released, and an attachment and detachment function can be easily performed.

#### DESCRIPTION OF DRAWINGS

FIG. 1 is a bottom perspective view illustrating an appearance in which a slide attachment and detachment device for a drawer according to one exemplary embodiment of the present invention is connected to the drawer;

FIG. 2 is a perspective view showing the slide attachment and detachment device for the drawer according to the one exemplary embodiment of the present invention;

FIG. 3 is an exploded perspective view showing the slide attachment and detachment device for the drawer according to the one exemplary embodiment of the present invention;

FIG. 4 is a side view illustrating an appearance of the slide attachment and detachment device for the drawer as viewed from direction IV;

FIG. 5 is a cross-sectional view taken along straight line V-V indicated in FIG. 4;

FIGS. 6 and 7 are perspective views illustrated for describing an operation of the slide attachment and detachment device for the drawer according to the one exemplary embodiment of the present invention; and

FIG. 8 is a perspective view illustrated for describing an operation of an inclination control member of the slide attachment and detachment device for the drawer according to the one exemplary embodiment of the present invention.

#### DETAILED DESCRIPTION

Exemplary embodiments of the present invention are capable of various modifications and alternative forms, embodiments of the present invention are shown by way of example in the drawings and will herein be described in detail. It should be understood, however, that there is no intent

to limit example embodiments of the invention to the particular forms disclosed, but on the contrary, example embodiments of the invention are to cover all modifications, equivalents, and alternatives falling within the scope of the invention. In the following description, it is to be noted that, when the functions of conventional elements and the detailed description of elements related with the present invention may make the gist of the present invention unclear, a detailed description of those elements will be omitted.

Hereinafter, an exemplary embodiment of the present invention will be described in detail with reference to the accompanying drawings.

FIG. 1 illustrates an appearance in which a slide attachment and detachment device for a drawer according to one exemplary embodiment of the present invention is connected to the drawer.

Referring to FIG. 1, the slide attachment and detachment device for the drawer 1 according to the one exemplary embodiment is connected to the drawer 80. The slide attachment and detachment device for the drawer 1 is fixedly connected to at least one selected from a bottom part 81 and a front part 82 so that a slide 90 supporting the drawer 80 can be connected to or separated from the drawer 80.

For reference, as previously described, the slide 80 supports the bottom part 81 of the drawer. The slide 80 may include: a fixing rail 91 fixedly connected to a receiving body (not drawn) in which the drawer 80 is received; a moving rail 93 moved along with the drawer 80 upon pulling or pushing the drawer 80 and intended for supporting the bottom part 81 of the drawer 80; and a middle rail 92 slidably movably connected to the fixing rail 91 and the moving rail 93 so that the moving rail 93 can be slidably movable in a pulling direction A or a pushing direction B with respect to the fixing rail 91.

Here, the middle rail 92 is added for extending a pulled distance of the drawer 80, namely, an operating distance of the slide 90, and according to the need, the moving rail 93 may be directly slidably and movably connected to the fixing rail 91.

That is, a slide in other types may be used as the slide 90 as needed. Since this fact is well known, the description of the slide 90 itself is omitted.

For reference, as illustrated, with regard to the slide attachment and detachment device for the drawer 1 according to the one exemplary embodiment, even though a pair of slide attachment and detachment devices for a drawer is generally installed in one drawer 90, since the pair of slide attachment and detachment devices for the drawer 1 is only formed symmetrically and is identical to each other with respect to a structure and an operation thereof, the description of one slide attachment and detachment device for the drawer 1 may replace the description of another one.

FIG. 2 is a perspective view showing the slide attachment and detachment device for the drawer according to the one exemplary embodiment of the present invention, and FIG. 3 is an exploded perspective view showing the slide attachment and detachment device for the drawer according to the one exemplary embodiment of the present invention. The slide attachment and detachment device for the drawer will be described with reference to FIGS. 2 and 3.

Referring to FIGS. 2 and 3, the slide attachment and detachment device for the drawer 1 according to the one exemplary embodiment of the present invention includes a main body 10 and an inclination control member 20.

The main body 10 may include a connecting part 11, a fixation support part 12, a lever part 13, an elastic support part 14, and a shock absorbing part 15.

The connecting part **11** is fixed to at least one selected from the bottom part (reference numeral **81** of FIG. **1**) and the front part (reference numeral **82** of FIG. **1**) of the drawer (reference numeral **80** of FIG. **1**). As illustrated, the connecting part may be formed to be simultaneously adhered to the bottom part **81** and the front part **82**, and a bottom connecting hole **111** and a front connecting hole **113** may be formed in the connecting part **11**.

A coupling member, such as a screw not illustrated, is inserted into the bottom connecting hole **111** and the front connecting hole **113** to be connected to at least one selected from the bottom part **81** and the front part **82** so that the connecting part **11** can be fixedly connected to at least one selected from the bottom part **81** and the front part **82**.

The fixation support part **12** is formed to protrude from the connecting part **11**. The fixation support part **12** is shaped to protrude in a direction parallel to a pulling direction (A of FIG. **1**) and a pushing direction (B of FIG. **1**) of the drawer **80**.

An operating hole **121** is formed in a middle portion of the fixation support part **12**. As illustrated in FIG. **1**, when the moving rail **93** of the slide (reference numeral **90** of FIG. **1**) is positioned to support the bottom part **81** of the drawer **80**, the operating hole **121** may be formed in the fixation support part **12** in a direction parallel to a direction toward one side of the moving rail and an opposite direction of the direction. That is, the operating hole **121** may be formed on a virtual plane parallel to the bottom part **81** in a direction vertical to the moving rail **93**.

For reference, the terms 'parallel to' and 'vertical' mean 'parallel to' and 'vertical' in consideration of a processing error and the like rather than 'parallel to' and 'vertical' in terms of mathematics.

The elastic support part **14** may be formed to protrude from one edge of the operating hole **121** and may be shaped to cover the operating hole **121**. The shape of the elastic support part **14** will be described with reference to FIGS. **4** and **5**.

FIG. **4** is a side view illustrating the shape of the elastic support part as viewed from direction IV indicated in FIG. **2**, and FIG. **5** illustrates a cross-sectional view taken along straight line V-V indicated in FIG. **4**.

Referring to FIGS. **4** and **5**, the elastic support part **14** is formed to protrude from one edge of the operating hole **121** of the fixation support part **12** and is formed to cover the operating hole **121**, and a remaining portion except for a portion connected to the fixation support part **12** is separated from the other edge of the operating hole **121**.

Here, as illustrated, the portion of the elastic support part **14** connected to the fixation support part **12** may be positioned in the operating hole **121** in the pushing (B) direction of the drawer.

Referring to FIGS. **2** and **3** again, the lever part **13** is protrudly formed at the end of the elastic support part **14**, namely, at the best protruding portion from the fixation support part **12** in a portion which is not connected to the fixation support part **12**.

As illustrated, based on the fixation support part **12**, the lever part **13** protrudes in a direction opposite to a portion in which the moving rail **93** is disposed. At this time, the lever part **13** protrudes to a space between a direction parallel to the fixation support part **12** and a direction parallel to the operating hole **121**. The fixation support part **12** and the lever part **13** may form a fixed angle. Such an angle may be designed so that a user can easily grasp the lever part **13**.

A coupling protrusion **131** protruding in a direction toward the moving rail **93** by passing through the operating hole **121** may be formed in one end of both ends of the lever part **13**, the one end being disposed on a side at which the operating hole

**121** is positioned. A guide surface **132** may be formed on the coupling protrusion **131**. As illustrated, the guide surface **132** may be shaped to be inclined in a direction far away from the moving rail **93** as the guide surface becomes close from the end of the coupling protrusion **131** to the pushing (B) direction of the drawer **80** gradually.

Accordingly, the coupling protrusion **131** protrudes roughly in a direction opposite to an extending direction of the lever part **13**. Each operation of the lever part **13**, the coupling protrusion **131** and the elastic support part **14** will be described later again.

The shock absorbing part **15** is formed to protrude from the connecting part **11**. As illustrated in FIG. **1**, when the moving rail **93** of the slide **90** is positioned to support the drawer **80**, the shock absorbing part **15** is formed to be interposed between an end of the moving rail **93** and the front part front **82**.

A shock absorbing piece **151** is protrudly formed in the shock absorbing part **15**. The shock absorbing piece **151** is formed so as to absorb a shock generated from between the front part **82** of the drawer **80** and the end of the moving rail **93**. The operation of the shock absorbing part **15** will be described later again.

Meanwhile, an inclination control member connecting groove **115** to which the inclination control member **20** is slidably movably connected is formed in the connecting part **11**. The inclination control member connecting groove **115** is formed in a direction parallel to the operating hole **121** as illustrated, a wedge protrusion projecting groove **117** opened in a direction at which the moving rail **93** is disposed is formed to extend on one side of the inclination control member connecting groove **115**.

A wedge protrusion **211**, a knob **213**, a guide protrusion **215**, and a supporting protrusion **217** are formed in the inclination control member **20**.

The wedge protrusion **211** is formed to protrude in a direction toward the wedge protrusion projecting groove **117** when the inclination control member **20** is connected to the inclination control member connecting groove **115**. A portion of the wedge protrusion in which the wedge protrusion projecting groove **117** is in contact with the bottom part **81** may be formed to have a plan shape, and the remaining portion except for the portion may have inclined surface-like shape so that a thickness of the wedge protrusion **211** can be gradually reduced toward a protruding direction of the wedge protrusion **211**.

The guide protrusion **215** may be formed in a direction parallel to a direction in which the inclination control member **20** connected to the inclination control member connecting groove **115** is slidably moved. The guide protrusion **215** may enable the inclination control member **20** connected to the inclination control member connecting groove **115** to be smoothly slidably moved along the inclination control member connecting groove **115**.

That is, a guide groove (not drawn) having a shape corresponding to the guide protrusion **215** is formed in the inclination control member connecting groove **115**. The guide protrusion **215** is inserted into and supported by the guide groove (not drawn) so that sliding movement according to the inclination control member connecting groove **115** of the inclination control member **20** can be guided.

The knob **213** is a portion intended for enabling the inclination control member **20** to be slidably moved along the inclination control member connecting groove **115**. The knob **213** may be shaped to protrude in a fixed height from the bottom part **81** to a lower side of the drawer **80**, and at least

one groove, protrusion, or the like may be formed at an end of the knob **213** so that a user can easily apply a force to the knob with his or her finger.

Accordingly, as the user applies the force to the knob **213**, when the inclination control member **20** is slidably moved to the direction at which the moving rail **93** is disposed, namely, the inclination control member is slidably moved toward the protruding direction of the wedge protrusion **211**, the wedge protrusion **211** protrudes to the outside via the wedge protrusion projecting groove **117**. Also, when the inclination control member **20** is slidably moved in an opposite direction thereof, the wedge protrusion **211** may be pulled back into the wedge protrusion projecting groove **117**.

The supporting protrusion **217** functions to support the inclination control member **20** so that the inclination control member **20** cannot be separated from the inclination control member connecting groove **115**. That is, the supporting protrusion **217** prevents the inclination control member **20** from being separated from the main body **10** during a process for connecting the slide attachment and detachment device for the drawer **1** to the drawer **80**.

To do so, the supporting protrusion **217** is formed to further protrude to both sides than a width formed between both sides of the inclination control member connecting groove **115** so that the inclination control member **20** can be supported by the supporting protrusion **217**, as well as the guide protrusion **215** after the inclination control member **20** has been connected to the inclination control member connecting groove **115**. As a result, the inclination control member **20** can be prevented from being separated from the main body **10**.

Each operation of the lever part **13**, the coupling protrusion **131**, and the elastic support part **14** will be described with reference to FIG. **5** again.

Referring to FIG. **5**, a modified appearance of the elastic support part **14** resulting from applying an external force **F** to the lever part is indicated by a dotted line. That is, as illustrated, when the external force **F** is applied to the lever part **13** in a direction parallel to the bottom part **81** of the drawer, and toward the moving rail **93** of the slide from the fixation support part **12**, the external force **F** is transmitted to the elastic support part **14** via the lever part so that the elastic support part **14** can be elastically modified.

At this time, in order for the elastic support part **14** to be elastically modified as indicated by the dotted line, the elastic support part **14** may have smaller flexural rigidity than that of the lever part **13**.

Also, in order to minimize a change in a position of the lever part **13** generated when the coupling protrusion **131** is pulled back into the operating hole (reference numeral **121** of FIG. **2**) according to the elastic modification of the elastic support part **14**, the elastic modification of the elastic support part **14** may be mainly generated from a portion connected to the fixation support part **12**. To do so, as illustrated, a connecting neck **141** may be formed in the elastic support part **14**.

As previously described, the connecting neck **141** is a portion from which the largest elastic modification is generated when the external force **F** is applied to the lever part **13**. The connecting neck **141** may be formed to have a small cross-sectional area compared to different portions of the elastic support part **14**. In such a case, when the external force **F** is applied to the lever part **13**, the connecting neck **141** is elastically modified based on a portion **C** of the connecting neck **141** having a minimum cross-sectional area so that a position of the lever part **13** and a position of the elastic support part **14** can be changed in a shape resulting from being rotated with respect to the fixation support part **12**.

For reference,  $T_m$  corresponding to a sign, which is not described, represents a width of the portion **C** of the connecting neck **141** having the minimum cross-sectional area. For manufacturing convenience of the elastic support part **14**, a portion **C** having a minimum cross-sectional area may be formed in the connecting neck **141** in such a manner that a thickness of the elastic support part **14** is regularly formed, and a minimum width  $T_m$  is formed in the connecting neck **141**.

Meanwhile, when the external force **F** applied to the lever part **13** is released, the connecting neck **141**, which has been elastically modified, is elastically returned to a position before the external force **F** is applied. Accordingly, the positions of the remaining portions of the lever part **13** and the elastic support part **14** are also returned, so that the coupling protrusion **131** protrudes to the outside of the operating hole **121**.

As previously described, the main body of the slide attachment and detachment device for the drawer **1** according to the one exemplary embodiment is formed in integral form. At this time, in order for the connecting neck **141** of the elastic support part **14** to be elastically modified by the external force **F** or to be returned to its original position according to release of the external force and to have enough strength to prevent from being damaged during using it, the main body should be made of a material having high strength and sufficient elasticity.

Examples of the material having these properties include, but not is limited to, synthetic resin having high strength, fatigue resistance, hardness, wear resistance, and the like, such as polyoxymethylene, poly acetal and ABS resin, nylon, and the like.

When the process for applying the external force **F** to the lever part **13** or for releasing the external force from the lever part is repeated, tensile stress and compressive stress are repeatedly applied to the connecting neck **141** of the elastic support part **14**. When the tensile stress and the compressive stress is intensively applied to a specific portion of the connecting neck **141**, a lifespan of the connecting neck **141** may be reduced.

In order to prevent this, the connecting neck **141** may be shaped such that the tensile stress and the compressive stress are dispersively operated. That is, an outline of the elastic support part **14** including the connecting neck **141** may have a flexible curved shape in which a vertex is not formed between a portion of the elastic support part connected to the fixation support part **12** and a portion of the elastic support part connected to the lever part **13**.

An operation of the slide attachment and detachment device for the drawer **1** according to the one exemplary embodiment of the present invention having the structure as described above will be hereinafter described with reference to FIGS. **6** to **8**.

FIGS. **6** and **7** illustrate perspective views for explaining the operation of the slide attachment and detachment device for the drawer **1** according to the one exemplary embodiment of the present invention. The operation will be described with reference to FIG. **1**, as well as these drawings.

Referring to FIGS. **6** and **7**, the main body **10** of the slide attachment and detachment device for a drawer **1** according to the one exemplary embodiment of the present invention, and the moving rail **93** are illustrated. For convenience, in FIGS. **6** and **7**, the drawer **80** is not illustrated.

The moving rail **93** includes a moving rail body **931**. As illustrated, a coupling hole **932** is formed in the moving rail body **931**. The coupling hole **932** may be formed at a position corresponding to the coupling protrusion **131**.

In order for the moving rail **93** to support the bottom part **81** of the drawer **80**, one side of the moving rail **93** is coupled to the main body **10** by moving the moving rail from a position in the state illustrated in FIG. 6 to a position in the state illustrated in FIG. 7.

In such a process, when the end of the moving rail body **931** is moved toward the shock absorbing part **15**, the coupling protrusion **131** in a state of further protruding than the fixation support part **12** is in contact with the moving rail body **931**.

At this time, as the end of the moving rail body **931** is moved toward the shock absorbing part **15** by a shape of the guide surface **132**, a force toward an inner direction of the operating hole (reference numeral **121** of FIG. 2) is applied to the coupling protrusion **131**. Due to this force, the connecting neck **141** is elastically modified, the coupling protrusion **131** is pulled back into the operating hole **121**.

Then, the moving rail body **931** is further moved toward the shock absorbing part **15**, so when the coupling hole **932** is positioned at the coupling protrusion **131**, the force applied to the coupling protrusion **131** is released. Thus, while the connecting neck **141** is elastically returned, the coupling protrusion **131** protrudes to the outside of the operating hole **121** again. Accordingly, the coupling protrusion **131** is inserted into the coupling hole **932**, and accordingly, the main body **10** is coupled to the moving rail body **931**.

As such, after the main body **10** and the moving rail body **931** have been coupled to each other, when the user applies a force A to the drawer **80** in a pulling direction of the drawer, an edge of the coupling hole **932** is supported by an opposite portion of a portion in which the guide surface **132** of the coupling protrusion **131** is formed so that the coupling protrusion **131** can be maintained in a state of being coupled to the coupling hole **932**. When the user applies a force to the drawer in a pushing direction B of the drawer, an end of the moving rail body **931** is pressurized by the front part **82** of the drawer **80** so that the coupling protrusion **131** can be maintained in a state of being coupled to the coupling hole **932**.

Accordingly, when the drawer **80** is pulled (A) or pushed (B) after the coupling protrusion **131** has been coupled to the coupling hole **932**, the main body **10** and the moving rail **93** are maintained in a state of being coupled so that pulling (A) and pushing (B) of the drawer **80** can be guided by the slide **90**.

At this time, the shock absorbing part **15** is interposed between the end of the moving rail **93** and the front part **82** of the drawer **80**. The end of the moving rail **93** and the front part **82** of the drawer are elastically supported by the shock absorbing piece (reference numeral **151** of FIG. 2) in a spaced direction between the end of the moving rail and the front part.

This is intended to constantly bring an edge of the coupling hole **932** into contact with the coupling protrusion **131** when the coupling protrusion **131** is coupled to the coupling hole **932**. Thus, a stable coupling state of the coupling protrusion **131** and the coupling hole **932** is maintained so that noise resulting from movement of the coupling protrusion **131** in the coupling hole **932** can be prevented from being generated, or movement of the drawer **80** with respect to the moving rail **93** can be prevented from being generated.

Also, when the user stops his or her action in the middle of pulling (A) the drawer **80** at a rapid speed, or the user pushes (B) the drawer **80** strongly, the end of the moving rail **93** may collide with the front part **82** due to an inertia force generated by movement of the moving rail **93**. Thus, the shock absorbing piece **151** of the shock absorbing part **15** interposed between the end of the moving rail **93** and the front part **82** is compressed and modified so as to absorb an impulsive force.

As such, the shock absorbing part **15** may enable the slide attachment and detachment device for the drawer **1** and the moving rail **93** to be stably coupled, may prevent the occurrence of noise upon pulling (A) or pushing the drawer **80**, and may enable the extension of a lifespan by absorbing an impact applied to the drawer **80** and the moving rail **93**.

Meanwhile, as previously described, when the drawer **80** is separated from the slide **90**, the user takes a motion to pull (A) the drawer **80**, and thereafter, he or she grasps both sides of the drawer **80** with both hands and holds the lever part **13** with fingers to apply a force (see F of FIG. 5) so that the coupling protrusion **131** can be pulled back into the operating hole **121**, and thus can be separated from the coupling hole **932**, thereby enabling the main body **10** to be separated from the slide **90**.

Furthermore, when the drawer **80** is connected to the slide **90**, the bottom part **81** of the drawer **80** is mounted on the moving rail **93**, and thereafter, the drawer **80** is moved in the pushing (B) direction so that the moving rail body **931** can be relatively moved with respect to the main body **10** as illustrated in FIGS. 6 and 7, and as a result, the coupling protrusion **131** can be coupled to the coupling hole **932**.

For reference, in order to prevent a pain or an inconvenient touch sensation from being generated from the lever part when the user applies a force to the lever part **13**, a finger-shaped groove may be formed in the lever part **13**.

FIG. 8 is a perspective view illustrated for describing an operation of an inclination control member of the slide attachment and detachment device for the drawer according to the one exemplary embodiment of the present invention.

Referring to FIG. 8, the inclination control member **20** is slidably moved in a direction toward the moving rail **93** so that the wedge protrusion **211** can protrude through the wedge protrusion projecting groove **117**. The operation of the inclination control member will be described with reference to FIG. 1, as well as FIG. 8.

A tolerance resulting from a processing error and the like may be generated between the drawer **80**, the slide **90**, and a receiving body (not drawn) during a process for connecting the drawer **80** to the receiving body (not drawn).

For example, with respect to a connection angle of the bottom part **81** and the front part **82** corresponding to constitutive elements of the drawer **80**, a position in which the fixing rail **91** is fixed to an inner side of the receiving body (not drawn), a relative portion between the fixing rail **91** and the moving rail **93**, and the like, a fine tolerance may be generated.

Accordingly, during a process for assembling the drawer **80** with the receiving body (not drawn), the front part **82** may form a slope in a specific direction due to the tolerance as described above.

In such a case, since the front part **82** causes interference with a front part of another drawer which is not illustrated, pulling (A) and pushing (B) may not be smoothly performed, or noise may be generated. Also, since an arrangement state of the front part **82** is not regular, the appearance of a receiving means (not drawn) may not be beautiful.

At this time, an angle and a balance of the front part **82** may be amended by adjusting a position of the inclination control member **20**.

That is, as the inclination control member **20** is slidably moved toward the slide **90**, the wedge protrusion **211** protrudes to the outside of the wedge protrusion projecting groove **117**. The protruding wedge protrusion **211** is interposed between the bottom part **81** of the drawer **89** and the moving rail **93**. Accordingly, a distance between the bottom part **81** and the moving rail **93** may be extended. Here, since a level of the extension of the distance between the bottom

11

part **81** and the moving rail **93** is relative to a protruding level of the wedge protrusion **211**, the level of the extension of the distance described above may be adjusted by adjusting a sliding level of the inclination control member **20** performed toward the slide **90**.

Meanwhile, as described above, since the inclination control member **20** is slidably moved to an appropriate position, after an angle and a balance state of the front part **82** have been adjusted, such a state should be maintained.

Accordingly, even though it is not illustrated, a plurality of unevennesses is formed in any one of the guide protrusion **215** and the guide groove (not drawn) along a lengthwise direction, and unevennesses corresponding thereto are also formed in another one so that the inclination control member **20** can be fixed at a position set by the user, and thus can be prevented from being arbitrarily moved. Also, a plurality of supporting grooves (not drawn) having a shape corresponding to the supporting protrusion **217** may be formed in a direction parallel to a direction at which the inclination control member **20** is slidably moved along both sides of the inclination control member connecting groove **115**.

As described above, in the slide attachment and detachment device for the drawer **1** according to the one exemplary embodiment of the present invention, since the main body **10** may be formed as one member, namely, may be formed in an integral form, the time and costs consumed for manufacturing the slide attachment and detachment device for the drawer **1** can be saved.

Furthermore, as described above, since the main body **10** is formed in the integral form, a moving portion into which foreign substances may be inserted is not formed so that hygienic properties can be improved. Accordingly, the slide attachment and detachment device for the drawer **1** according to the one exemplary embodiment of the present invention can be stably used even in devices for which hygienic properties are required, such as a refrigerator and the like.

Also, since a separate metal elastic body and the like are not included, and there is no possibility that the main body **10** itself will corrode, the slide attachment and detachment device for the drawer can be used even in environments having high humidity.

Although the slide attachment and detachment device for the drawer according to the exemplary embodiment of the present invention has been described, an idea of the present invention should not be limited to the exemplary embodiment presented in the specification, and those skilled in the art who understand the idea of the present invention will appreciate that other exemplary embodiments by various additions, modifications, deletions and substitutions of the constitutive elements can be easily suggested, without departing from the scope and spirit of the invention as disclosed in the accompanying claims.

<Description of the Reference Numerals>	
1: Slide attachment and detachment device for a drawer	
10: Main body	
11: Connecting part	111: Bottom connecting hole
115: Inclination control member connecting groove	
117: Wedge protrusion projecting groove	
12: Fixation support part	121: Operating hole
13: Lever part	131: Coupling protrusion
132: Guide surface	14: Elastic support part
141: Connecting neck	15: Shock absorbing part
151: Shock absorbing piece	
20: Inclination control member	
211: Wedge protrusion	213: Knob
215: Guide protrusion	217: Supporting protrusion

12

-continued

<Description of the Reference Numerals>	
80: Drawer	81: Bottom part
82: Front part	90: Slide
91: Fixing rail	92: Middle rail
93: Moving rail	931: Moving rail body
932: Coupling hole	

The invention claimed is:

**1.** A slide attachment and detachment device for a drawer, which connects the drawer to a slide intended for supporting the drawer and a bottom part of the drawer and for guiding pulling or pushing of the drawer, or which separates the drawer from the slide, the slide attachment and detachment device, comprising:

a connecting part fixedly connected to at least one selected from a front part and a bottom part of the drawer;

a fixation support part formed to protrude from the connecting part in a direction parallel to a pulling or pushing direction of the drawer, and having an operation hole formed to pass through a direction parallel to a direction toward one side of the slide in its central portion when the slide is positioned to support the drawer;

an elastic support part formed to protrude from one edge of the operation hole and to cover the operation hole; and

a lever part formed to extend from an end of the elastic support part, one end of which has a coupling protrusion formed to protrude toward the slide by passing through the operation hole, and the other end of which protrudes in a direction opposite to the coupling protrusion,

wherein a connecting neck having a minimum cross-sectional area is formed in the elastic support part, and the elastic support part have smaller flexural rigidity than that of the lever part, and

wherein when an external force parallel to the bottom part of the drawer and toward the slide is applied to the lever part, the connecting neck of the elastic support part is elastically changed, so the coupling protrusion is pulled back into the operation hole, and when the external force applied to the lever part is released, the connecting neck of the elastic support part is elastically returned, so the coupling protrusion protrudes to an outer portion of the operation hole.

**2.** The slide attachment and detachment device of claim **1**, wherein a portion of the elastic support part connected to the fixation support part is positioned in the pushing direction of the drawer within the operation hole.

**3.** The slide attachment and detachment device of claim **1**, further comprising: an inclination control member connecting groove parallel to the operation hole and having one side opened toward the slide, and formed in the coupling part; an inclination control member slidably movably connected to the inclination control member connecting groove; and a wedge protrusion protruding toward an opening portion of the inclination control member connecting groove, and formed in the inclination control member,

wherein the wedge protrusion is interposed between a bottom surface of the drawer and the slide when the slide is positioned to support the drawer, and the inclination control member is slidably moved in a direction toward the slide, so a distance between the bottom surface of the drawer and the slide is extended.

**4.** The slide attachment and detachment device of claim **1**, further comprising a shock absorbing part formed to protrude

from the coupling part and disposed between the end of the slide and the front part of the drawer when the slide is positioned to support the drawer.

5. The slide attachment and detachment device of claim 1, wherein the connecting part, the fixation support part, the elastic support part, and the lever part are made of a synthetic resin.

6. The slide attachment and detachment device of claim 2, further comprising: an inclination control member connecting groove parallel to the operation hole and having one side opened toward the slide, and formed in the coupling part; an inclination control member slidably movably connected to the inclination control member connecting groove; and a wedge protrusion protruding toward an opening portion of the inclination control member connecting groove, and formed in the inclination control member, wherein the wedge protrusion is interposed between a bottom surface of the drawer and the slide when the slide is positioned to support the drawer, and the inclination control member is slidably moved in a direction toward the slide, so a distance between the bottom surface of the drawer and the slide is extended.

7. The slide attachment and detachment device of claim 2, further comprising a shock absorbing part formed to protrude from the coupling part and disposed between the end of the slide and the front part of the drawer when the slide is positioned to support the drawer.

8. The slide attachment and detachment device of claim 2, wherein the connecting part, the fixation support part, the elastic support part, and the lever part are made of a synthetic resin.

\* \* \* \* \*