



US009436641B2

(12) **United States Patent**
Calvin et al.

(10) **Patent No.:** **US 9,436,641 B2**
(45) **Date of Patent:** ***Sep. 6, 2016**

(54) **SWITCH FABRIC HAVING A SERIAL COMMUNICATIONS INTERFACE AND A PARALLEL COMMUNICATIONS INTERFACE**

(58) **Field of Classification Search**
CPC G06F 13/20; G06F 3/014; G06F 13/00; G06F 15/16
See application file for complete search history.

(71) Applicant: **Bedrock Automation Platforms Inc.,**
San Jose, CA (US)

(56) **References Cited**

(72) Inventors: **James G. Calvin,** Attleboro, MA (US);
Albert Rooyakkers, Sunnyvale, CA (US)

U.S. PATENT DOCUMENTS

4,628,308 A 12/1986 Robert
4,656,622 A 4/1987 Lea

(Continued)

(73) Assignee: **Bedrock Automation Platforms Inc.,**
San Jose, CA (US)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 156 days.

EP 2317743 5/2011

OTHER PUBLICATIONS

This patent is subject to a terminal disclaimer.

Pending U.S. Appl. No. 14/502,006, filed Sep. 30, 2014.

(Continued)

(21) Appl. No.: **14/501,974**

Primary Examiner — Henry Tsai

Assistant Examiner — Christopher A Daley

(22) Filed: **Sep. 30, 2014**

(74) *Attorney, Agent, or Firm* — Advent, LLP

(65) **Prior Publication Data**

US 2015/0019778 A1 Jan. 15, 2015

(57) **ABSTRACT**

Related U.S. Application Data

(63) Continuation of application No. 13/341,161, filed on Dec. 30, 2011, now Pat. No. 8,862,802.

(51) **Int. Cl.**

G06F 13/00 (2006.01)

G06F 13/40 (2006.01)


(Continued)

A switch fabric is disclosed that includes a serial communications interface and a parallel communications interface. The serial communications interface is configured for connecting a plurality of slave devices to a master device in parallel to transmit information between the plurality of slave devices and the master device, and the parallel communications interface is configured for separately connecting the plurality of slave devices to the master device to transmit information between the plurality of slave devices and the master device, and to transmit information between individual ones of the plurality of slave devices. The parallel communications interface may comprise a dedicated parallel communications channel for each one of the plurality of slave devices. The serial communications interface may comprise a multidrop bus, and the parallel communications interface may comprise a cross switch.

(52) **U.S. Cl.**

CPC **G06F 13/4022** (2013.01); **G06F 13/20** (2013.01); **G06F 15/16** (2013.01); **G06F 2213/0004** (2013.01); **G06F 2213/0022** (2013.01); **G06F 2213/0024** (2013.01)

20 Claims, 10 Drawing Sheets



- (51) **Int. Cl.**
G06F 13/20 (2006.01)
G06F 15/16 (2006.01)
G06F 3/14 (2006.01)

- 7,529,862 B2 5/2009 Isani et al.
 7,774,074 B2 8/2010 Davlin et al.
 8,266,360 B2 9/2012 Agrawal
 8,310,380 B2 11/2012 Aria et al.
 8,380,905 B2 2/2013 Djabbari et al.
 8,868,813 B2 10/2014 Calvin et al.
 2002/0086678 A1 7/2002 Salokannel et al.
 2002/0171525 A1 11/2002 Kobayashi et al.
 2003/0202330 A1 10/2003 Lopata et al.
 2007/0076768 A1 4/2007 Chiesa et al.
 2008/0123669 A1 5/2008 Oliveti et al.
 2008/0194124 A1 8/2008 Di Stefano
 2009/0245245 A1 10/2009 Malwankar et al.
 2010/0052428 A1 3/2010 Imamura et al.
 2011/0296066 A1 12/2011 Xia
 2012/0284354 A1 11/2012 Mukundan et al.
 2012/0297101 A1 11/2012 Neupartl et al.

- (56) **References Cited**
 U.S. PATENT DOCUMENTS

- 4,691,384 A 9/1987 Jobe
 4,882,702 A 11/1989 Struger et al.
 4,929,939 A 5/1990 Varma et al.
 5,590,284 A 12/1996 Crosetto
 5,602,754 A 2/1997 Beatty et al.
 5,951,666 A 9/1999 Ilting et al.
 6,680,904 B1 1/2004 Kaplan et al.
 6,812,803 B2 11/2004 Goergen
 6,988,162 B2 1/2006 Goergen
 7,200,692 B2 4/2007 Singla et al.
 7,254,452 B2 8/2007 Davlin et al.
 7,526,676 B2 4/2009 Chou et al.

OTHER PUBLICATIONS

Search Report and Written Opinion dated Apr. 29, 2013 in International Application # PCT/US2012/072056.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

1000




FIG. 10

1

**SWITCH FABRIC HAVING A SERIAL
COMMUNICATIONS INTERFACE AND A
PARALLEL COMMUNICATIONS
INTERFACE**

BACKGROUND

One of the most common communication architectures is the multidrop serial communication bus. A Multidrop Bus (MDB) is a bus in which various components are connected to a common set of electrical connectors. This type of bus architecture typically uses a master device and multiple slave devices that communicate with the master device. An arbitration process is used to determine which component can send information on the MDB at a given instant in time. The other devices are then configured to listen for the data that is intended for them. Peripheral Component Interconnect (PCI) is one type of computer bus multidrop standard, used for attaching hardware devices in a computer. Multidrop buses may also be used with vending machine controllers to communicate with vending machine components, such as coin readers and/or note readers. Redundant multidrop buses can be used to prevent a single failure from interrupting communication between the master device and the slave devices. For example, dual multidrop bus configurations can be used in distributed control systems.

SUMMARY

A switch fabric is disclosed. In one or more implementations, the switch fabric includes a serial communications interface and a parallel communications interface. The serial communications interface is configured to connect a plurality of slave devices to a master device in parallel to transmit information between the plurality of slave devices and the master device. In implementations, the serial communications interface may comprise a multidrop bus. The parallel communications interface is configured to separately connect the plurality of slave devices to the master device to transmit information between the plurality of slave devices and the master device, and to transmit information between individual ones of the plurality of slave devices. The parallel communications interface may comprise a dedicated parallel communications channel for each one of the plurality of slave devices. In implementations, the parallel communications interface may comprise a cross switch.

This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.

DRAWINGS

The Detailed Description is described with reference to the accompanying figures. The use of the same reference numbers in different instances in the description and the figures may indicate similar or identical items.

FIG. 1 is a block diagram illustrating a switch fabric in accordance with example implementations of the present disclosure.

FIG. 2 is a circuit diagram illustrating a switch fabric in accordance with example implementations of the present disclosure.

2

FIG. 3 is a block diagram illustrating a communications control system comprising a switch fabric in accordance with example implementations of the present disclosure.

FIG. 4 is an isometric view illustrating a communications control system comprising a switch fabric in accordance with example implementations of the present disclosure.

FIG. 5 is a side elevation view of the communications control system illustrated in FIG. 4.

FIG. 6 is an end view of the communications control system illustrated in FIG. 4.

FIG. 7 is a partial cross-sectional end view of the communications control system illustrated in FIG. 4.

FIG. 8 is a cross-sectional view illustrating an input/output module for the communications control system illustrated in FIG. 4.

FIG. 9 is an isometric view illustrating a support frame for the communications control system illustrated in FIG. 4.

FIG. 10 is a flow diagram illustrating a process for furnishing communication between multiple slave devices and one or more master devices in accordance with example implementations of the present disclosure.

DETAILED DESCRIPTION

Overview

In a typical multidrop bus configuration, the master device communicates with the slave devices by polling each slave device one at a time. However, as the number of slave devices increases, the turnaround time for communication increases as well. For example, the total communication turnaround time for a multidrop bus is equal to the sum of each of the times for the master device to send a command to a slave device and receive a response from the slave device, and is thus proportional to the number of slave devices on the network. For high speed control systems applications with many slave devices, this can make communication too slow to be useful. Additionally, this type of bus is half-duplex, and communication between the slave devices further slows the bus and requires complex collision detection. This not only makes the bus slower, but causes the system to be nondeterministic with respect to communication turnaround times, making such a configuration unsuitable for control systems.

Accordingly, a switch fabric is described that has a serial communications interface (e.g., a serial or Multidrop Bus (MDB) with a master device and multiple slave devices) and a parallel communications interface (e.g., a parallel or point-to-point bus implemented using a cross switch, or the like). A switch fabric configured in accordance with the present disclosure may increase communication response time over a standard multidrop architecture. The switch fabric may also provide deterministic communication (e.g., with respect to communication turnaround time) between a master device and slave devices, as well as between the slave devices themselves. Further, the switch fabric may eliminate communication collisions between a master device and the slave devices, as well as eliminating collisions between the slave devices themselves.

In some implementations, the serial communications interface and the parallel communications interface may be formed on a single printed circuit board. The serial communications interface may be configured for connecting the plurality of slave devices to a second master device in parallel, and the parallel communications interface may be configured for separately connecting the plurality of slave devices to the second master device. Information transmitted via the serial communications interface and/or the parallel

communications interface may be packetized. The switch fabric may comprise a network interface for transmitting information collected from the plurality of slave devices via a network, and so forth.

A switch assembly is also described that includes a multidrop bus for connecting a plurality of slave devices to a master device in parallel to transmit information between the plurality of slave devices and the master device. The switch assembly also includes a cross switch for separately connecting the plurality of slave devices to the master device to transmit information between the plurality of slave devices and the master device, and to transmit information between individual ones of the plurality of slave devices.

Example Implementations

FIGS. 1 and 2 illustrate an example switch fabric **100** in accordance with example implementations of the present disclosure. In implementations, the switch fabric **100** may be configured for use with any systems technology, such as telecommunications network technology, computer network technology, process control systems technology, and so forth. For example, the switch fabric **100** may be used with a distributed control system comprised of controller elements and subsystems, where the subsystems are controlled by one or more controllers distributed throughout the system. The switch fabric **100** includes a serial communications interface **102** and a parallel communications interface **104** for furnishing communications with a number of slave devices **106**. The serial communications interface **102** may be implemented using a group of connectors connected in parallel with one another. For example, the serial communications interface **102** may be implemented using a multidrop bus **108**, or the like. In implementations, the multidrop bus **108** may be used for configuration and diagnostic functions of the slave devices **106**.

The parallel communications interface **104** allows multiple signals to be transmitted simultaneously over multiple dedicated high speed parallel communication channels. For instance, the parallel communications interface **104** may be implemented using a cross switch **110**, or the like. In a particular implementation, as described in FIG. 2, the parallel communications interface **104** can be implemented using a four (4) wire full duplex cross switch **110** with a dedicated connection to each slave device **106**. For example, the cross switch **110** can be implemented as a programmable cross switch connecting point-to-point busses and allowing traffic between the slave devices **106**.

The cross switch **110** may be configured by a master device **112**. For example, the master device **112** may configure one or more sets of registers included in the cross switch **110** to control traffic between the slave devices **106**. In implementations, a master device **112** may comprise a rule set dictating how the slave devices **106** are interconnected. For example, a master device **112** may comprise a set of registers, where each register defines the operation of a particular switch (e.g., with respect to how packets are forwarded, and so forth). Thus, the cross switch **110** may not necessarily auto-configure, instead implementing a configuration provided by the master device **112**. However, this configuration is provided by way of example only and is not meant to be restrictive of the present disclosure. Thus, in other implementations, the cross switch **110** may auto-configure.

The parallel communications interface **104** may be used for data collection from the slave devices **106**. Further, because each slave device **106** has its own private bus to the master (e.g., master device **112**), each slave device **106** can communicate with the master at the same time. Thus, the

total response time for the switch fabric **100** may be limited to that of the slowest slave device **106**, instead of the sum of all slave devices, as previously discussed in relation to a typical multidrop bus.

In implementations, the switch fabric **100**, the serial communications interface **102**, and the parallel communications interface **104** may be implemented in a single, monolithic circuit board. However, this configuration is provided by way of example only and is not meant to be restrictive of the present disclosure. Thus, the serial communications interface **102** and the parallel communications interface **104** may be implemented using different arrangements of multiple components, such as multiple discrete semiconductor devices for implementing the serial communications interface **102** and the parallel communications interface **104** separately, and so forth.

Referring now to FIGS. 3 through 9, a communications control system **114** using switch fabric **100** is described. The switch fabric **100** may be configured for connecting one or more I/O modules **116** as slave devices and transmitting data to and from the I/O modules **116**. The I/O modules **116** may comprise input modules, output modules, and/or input and output modules. For instance, input modules can be used to receive information from input instruments in the process or the field, while output modules can be used to transmit instructions to output instruments in the field. For example, an I/O module **116** can be connected to a process sensor, such as a sensor **118** for measuring pressure in piping for a gas plant, a refinery, and so forth. In implementations, the I/O modules **116** may be used to collect data and control systems in applications including, but not necessarily limited to: industrial processes, such as manufacturing, production, power generation, fabrication, and refining; infrastructure processes, such as water treatment and distribution, wastewater collection and treatment, oil and gas pipelines, electrical power transmission and distribution, wind farms, and large communication systems; facility processes for buildings, airports, ships, and space stations (e.g., to monitor and control Heating, Ventilation, and Air Conditioning (HVAC) equipment and energy consumption); large campus industrial process plants, such as oil and gas, refining, chemical, pharmaceutical, food and beverage, water and wastewater, pulp and paper, utility power, mining, metals; and/or critical infrastructures.

In implementations, the I/O module **116** may be configured to convert analog data received from the sensor **118** to digital data (e.g., using Analog-to-Digital Converter (ADC) circuitry, and so forth). An I/O module **116** may also be connected to a motor **120** and configured to control one or more operating characteristics of the motor **120**, such as motor speed, motor torque, and so forth. Further, the I/O module **116** may be configured to convert digital data to analog data for transmission to the motor **120** (e.g., using Digital-to-Analog (DAC) circuitry, and so forth). In implementations, one or more of the I/O modules **116** may comprise a communications module configured for communicating via a communications sub-bus, such as an Ethernet bus, an H1 field bus, a Process Field Bus (PROFIBUS), a Highway Addressable Remote Transducer (HART) bus, a Modbus, and so forth. Further, two or more of the I/O modules **116** can be used to provide fault tolerant and redundant connections for a communications sub-bus.

Each I/O module **116** may be provided with a unique identifier (ID) for distinguishing one I/O module **116** from another I/O module **116**. In implementations, an I/O module **116** may be identified by its ID when it is connected to the communications control system **114**. Multiple I/O modules

116 can be used with the communications control system **114** to provide redundancy. For example, two or more I/O modules **116** can be connected to the sensor **118** and/or the motor **120**, as described in FIG. 3. Each I/O module **116** can include one or more ports **122** furnishing a physical connection to hardware and circuitry included with the I/O module **116**, such as a Printed Circuit Board (PCB) **124**, and so forth.

One or more of the I/O modules **116** may include an interface for connecting to other networks, including but not necessarily limited to: a wide-area cellular telephone network, such as a 3G cellular network, a 4G cellular network, or a Global System for Mobile communications (GSM) network; a wireless computer communications network, such as a Wi-Fi network (e.g., a Wireless LAN (WLAN) operated using IEEE 802.11 network standards); a Personal Area Network (PAN) (e.g., a Wireless PAN (WPAN) operated using IEEE 802.15 network standards); a Wide Area Network (WAN); an intranet; an extranet; an internet; the Internet; and so on. Further, one or more of the I/O modules **116** may include a connection for connecting an I/O module **116** to a computer bus, and so forth.

The switch fabric **100** may be coupled with one or more communications/control modules **126**, which can be used as master devices for monitoring and controlling the I/O modules **116**, and for connecting the I/O modules **116** together. The communications/control module(s) **126** may be used to configure the cross switch **110**. For example, the communications/control module **126** may update a routing table when an I/O module **116** is connected to the communications control system **114** based upon a unique ID for the I/O module **116**. Further, when multiple redundant I/O modules **116** are used, each communications/control module **126** can implement mirroring of informational databases regarding the I/O modules **116** and update them as data is received from and/or transmitted to the I/O modules **116**. In some implementations, two or more communications/control modules **126** may be used to provide redundancy.

Data transmitted using the switch fabric **100** may be packetized, i.e., discrete portions of the data may be converted into data packets comprising the data portions along with network control information, and so forth. The switch fabric **100** may use one or more protocols for data transmission, including a bit-oriented synchronous data link layer protocol such as High-Level Data Link Control (HDLC). In a specific instance, the switch fabric **100** may implement HDLC according to an International Organization for Standardization (ISO) 13239 standard, or the like. Further, two or more communications/control modules **126** can be used to implement redundant HDLC. However, it should be noted that HDLC is provided by way of example only and is not meant to be restrictive of the present disclosure. Thus, the communications control system **114** may use other various communications protocols in accordance with the present disclosure.

One or more of the communications/control modules **126** may be configured for exchanging information with components used for monitoring and/or controlling the instrumentation connected to the switch fabric **100** via the I/O modules **116**, such as one or more control loop feedback mechanisms/controllers **128**. In implementations, a controller **128** can be configured as a microcontroller/Programmable Logic Controller (PLC), a Proportional-Integral-Derivative (PID) controller, and so forth. One or more of the communications/control modules **126** may include a network interface **130** for connecting the communications control system **114** to a controller **128** via a network **132**. In

implementations, the network interface **130** may be configured as a Gigabit Ethernet interface for connecting the switch fabric **100** to a Local Area Network (LAN). Further, two or more communications/control modules **126** can be used to implement redundant Gigabit Ethernet. However, it should be noted that Gigabit Ethernet is provided by way of example only and is not meant to be restrictive of the present disclosure. Thus, the network interface **130** may be configured for connecting the communications control system **114** to other various networks, including but not necessarily limited to: a wide-area cellular telephone network, such as a 3G cellular network, a 4G cellular network, or a Global System for Mobile communications (GSM) network; a wireless computer communications network, such as a Wi-Fi network (e.g., a Wireless LAN (WLAN) operated using IEEE 802.11 network standards); a Personal Area Network (PAN) (e.g., a Wireless PAN (WPAN) operated using IEEE 802.15 network standards); a Wide Area Network (WAN); an intranet; an extranet; an internet; the Internet; and so on. Additionally, the network interface **130** may be implemented using computer bus. For example, the network interface **130** can include a Peripheral Component Interconnect (PCI) card interface, such as a Mini PCI interface, and so forth. Further, the network **132** may be configured to include a single network or multiple networks across different access points.

The communications control system **114** may include one or more power modules **134** for supplying electrical power to field devices via the I/O modules **116**. One or more of the power modules **134** may include an AC-to-DC (AC/DC) converter for converting Alternating Current (AC) (e.g., as supplied by AC mains, and so forth) to Direct Current (DC) for transmission to a field device, such as the motor **120** (e.g., in an implementation where the motor **120** comprises a DC motor). Two or more power modules **134** can be used to provide redundancy. For example, as shown in FIG. 3, two power modules **134** can be connected to each of the I/O modules **116** using a separate power backplane **136** for each power module **134**.

The communications control system **114** may be implemented using a support frame **138**. The support frame **138** may be used to support and/or interconnect the communications/control module(s) **126**, the power module(s) **134**, the switch fabric **100**, the power backplane(s) **136**, and/or the I/O modules **116**. For example, the switch fabric **100** may be comprised of a circuit board **140**, which may be mounted to the support frame **138** using a fastener, such as, for example, double sided tape, adhesive, or mechanical fasteners (screws, bolts, etc.). The support frame **138** may include slots **142** to provide registration for the I/O modules **116**, such as for aligning connectors of the I/O modules **116** with connectors included with the circuit board **140** and/or connectors of a power backplane **136**. For example, an I/O module **116** may include connectors **144** having tabs/posts **146** for inserting into slots **142** and providing alignment of the I/O module **116** with respect to the circuit board **140**. In implementations, one or more of the connectors **144** may be constructed from a thermally conductive material (e.g., metal) connected to a thermal plane of PCB **124** to conduct heat generated by components of the PCB **124** away from the PCB **124** and to the support frame **138**, which itself may be constructed of a thermally conductive material (e.g., metal). Further, the communications control system **114** may associate a unique physical ID with each physical slot **142** to uniquely identify each I/O module **116** coupled with a particular slot **142**. For example, the ID of a particular slot **142** can be associated with an I/O module **116** coupled with

the slot **142** and/or a second ID uniquely associated with the I/O module **116**. Further, the ID of a particular I/O module **116** can be used as the ID for a slot **142** when the I/O module **116** is coupled with the slot **142**. The support frame **138** can be constructed for cabinet mounting, rack mounting, wall mounting, and so forth.

Example Process

Referring now to FIG. **10**, example techniques for furnishing communication between multiple slave devices and one or more master devices using a switch fabric that includes a serial communications interface and a parallel communications interface are described.

FIG. **10** depicts a process **1000**, in an example implementation, for furnishing a switch fabric, such as the switch fabric **100** illustrated in FIGS. **1** through **9** and described above. In the process **1000** illustrated, slave devices are connected to a master device in parallel for transmitting information between the slave devices and the master device (Block **1010**). In one or more implementations, the slave devices can be connected to the master device using a multidrop bus (Block **1012**). For example, with reference to FIG. **2**, the serial communications interface **102** of the switch fabric **100** may be implemented using a multidrop bus **108**. The slave devices are separately connected to the master device for transmitting information between the slave devices and the master device, and for transmitting information between individual ones of the slave devices (Block **1020**). In one or more implementations, the slave devices can be separately connected to the master device using a cross switch (Block **1022**). For instance, with continuing reference to FIG. **2**, the parallel communications interface **104** of the switch fabric **100** may be implemented using a cross switch **110** comprising a four (4) wire full duplex system with a dedicated connection to each slave device **106**.

In some implementations, the slave devices can be connected to a second master device in parallel (Block **1030**). The slave devices can also be separately connected to the second master device (Block **1040**). For example, with continuing reference to FIGS. **1** through **9**, two or more communications/control modules **126** can be used to implement a redundant HDLC data link layer protocol. It should be noted that connecting the slave devices to a second master device is provided by way of example only and is not meant to be restrictive of the present disclosure. Thus, the slave devices may be connected to more than two master devices in parallel and/or separately.

CONCLUSION

Although the subject matter has been described in language specific to structural features and/or process operations, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described above. Rather, the specific features and acts described above are disclosed as example forms of implementing the claims.

What is claimed is:

1. A switch fabric for an industrial control system, the switch fabric comprising:

a serial communications interface for connecting a plurality of slave devices to a master device in parallel, the serial communications interface configured for transmitting information between the plurality of slave devices and the master device;

a parallel communications interface for separately connecting the plurality of slave devices to the master

device, the parallel communications interface configured for simultaneously transmitting information between the plurality of slave devices and the master device, and transmitting information between individual ones of the plurality of slave devices; and a support frame to facilitate interconnection of the plurality of slave devices and the master device, the support frame comprising a plurality of slots, each slot of the plurality of slots for receiving a respective one of the plurality of slave devices, each slot of the plurality of slots associated with a unique identification, wherein a slave device coupled with the support frame at a respective slot can identify itself to the master device using the unique identification associated with the respective slot.

2. The switch fabric as recited in claim **1**, wherein the parallel communications interface comprises a dedicated parallel communications channel for each one of the plurality of slave devices.

3. The switch fabric as recited in claim **1**, wherein the serial communications interface comprises a multidrop bus.

4. The switch fabric as recited in claim **1**, wherein the parallel communications interface comprises a cross switch.

5. The switch fabric as recited in claim **1**, wherein the serial communications interface and the parallel communications interface are formed on a single printed circuit board.

6. The switch fabric as recited in claim **1**, wherein the serial communications interface is configured for connecting the plurality of slave devices to a second master device in parallel, and the parallel communications interface is configured for separately connecting the plurality of slave devices to the second master device.

7. The switch fabric as recited in claim **1**, wherein information transmitted via at least one of the serial communications interface or the parallel communications interface is packetized.

8. The switch fabric as recited in claim **1**, further comprising a network interface for transmitting information collected from the plurality of slave devices via a network.

9. A process comprising:

coupling a plurality of slave devices and a master device to a support frame in an industrial control system, the support frame comprising a plurality of slots, each slot of the plurality of slots for receiving a respective one of the plurality of slave devices, each slot of the plurality of slots associated with a unique identification;

connecting a plurality of slave devices to a master device in parallel for transmitting information between the plurality of slave devices and the master device; and

separately connecting the plurality of slave devices to the master device for simultaneously transmitting information between the plurality of slave devices and the master device, and transmitting information between individual ones of the plurality of slave devices, wherein a slave device coupled with the support frame at a respective slot can identify itself to the master device using the unique identification associated with the respective slot.

10. The process as recited in claim **9**, wherein separately connecting the plurality of slave devices to the master device comprises furnishing a dedicated parallel communications channel for each one of the plurality of slave devices.

11. The process as recited in claim **9**, wherein connecting the plurality of slave devices to the master device in parallel comprises connecting the plurality of slave devices to the master device using a multidrop bus.

9

12. The process as recited in claim 9, wherein separately connecting the plurality of slave devices to the master device comprises separately connecting the plurality of slave devices to the master device using a cross switch.

13. The process as recited in claim 9, wherein connecting the plurality of slave devices to the master device in parallel and separately connecting the plurality of slave devices to the master device comprises connecting the plurality of slave devices to the master device using a single printed circuit board.

14. The process as recited in claim 9, further comprising: connecting the plurality of slave devices to a second master device in parallel; and separately connecting the plurality of slave devices to the second master device.

15. The process as recited in claim 9, wherein at least one of transmitting information between the plurality of slave devices and the master device or transmitting information between individual ones of the plurality of slave devices comprises packetizing the transmitted information.

16. A switch assembly for an industrial control system, the switch assembly comprising:

a multidrop bus for connecting a plurality of slave devices to a master device in parallel, the multidrop bus configured for transmitting information between the plurality of slave devices and the master device;

a cross switch for separately connecting the plurality of slave devices to the master device, the cross switch configured for simultaneously transmitting information

10

between the plurality of slave devices and the master device, and transmitting information between individual ones of the plurality of slave devices; and a support frame to facilitate interconnection of the plurality of slave devices and the master device, the support frame comprising a plurality of slots, each slot of the plurality of slots for receiving a respective one of the plurality of slave devices, each slot of the plurality of slots associated with a unique identification, wherein a slave device coupled with the support frame at a respective slot can identify itself to the master device using the unique identification associated with the respective slot.

17. The switch assembly as recited in claim 16, wherein the multidrop bus and the cross switch are formed on a single printed circuit board.

18. The switch assembly as recited in claim 16, wherein the multidrop bus is configured for connecting the plurality of slave devices to a second master device in parallel, and the cross switch is configured for separately connecting the plurality of slave devices to the second master device.

19. The switch assembly as recited in claim 16, wherein information transmitted via at least one of the multidrop bus or the cross switch is packetized.

20. The switch assembly as recited in claim 16, further comprising a network interface for transmitting information collected from the plurality of slave devices via a network.

* * * * *