

US009438543B2

(12) **United States Patent**
Goncalves et al.

(10) **Patent No.:** **US 9,438,543 B2**
(45) **Date of Patent:** ***Sep. 6, 2016**

(54) **GESTURE-BASED CONTENT SHARING**

USPC 345/156; 455/414.1; 715/753, 800, 863
See application file for complete search history.

(71) Applicant: **Google Technology Holdings LLC**,
Mountain View, CA (US)

(56) **References Cited**

(72) Inventors: **Alex G. Goncalves**, Sunnyvale, CA
(US); **Edward Judalevitch**, Santa
Clara, CA (US)

U.S. PATENT DOCUMENTS

7,636,794 B2 12/2009 Ramos et al.
8,260,883 B2 9/2012 Mooring et al.

(73) Assignee: **Google Technology Holdings LLC**,
Mountain View, CA (US)

(Continued)

OTHER PUBLICATIONS

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 262 days.

Patent Cooperation Treaty, International Search Report and Written
Opinion of the International Searching Authority for International
Application No. PCT/US2014/012863, Apr. 7, 2014, 9 pages.

This patent is subject to a terminal dis-
claimer.

(Continued)

(21) Appl. No.: **13/783,506**

Primary Examiner — Kevin Bates

(22) Filed: **Mar. 4, 2013**

Assistant Examiner — Emad Siddiqi

(65) **Prior Publication Data**

US 2014/0250193 A1 Sep. 4, 2014

(74) *Attorney, Agent, or Firm* — McDermott Will & Emery
LLP

(51) **Int. Cl.**

G06F 15/16 (2006.01)
G06F 3/048 (2013.01)
G06F 3/02 (2006.01)
G06F 5/08 (2006.01)
H04L 12/58 (2006.01)
H04W 4/20 (2009.01)
G06F 1/16 (2006.01)
G06F 3/01 (2006.01)
H04L 29/08 (2006.01)

(57) **ABSTRACT**

A user selects a content item that he wishes to send. He then
performs a gesture to specify a direction toward which the
content item is to be sent. For example, he pretends to
“throw” his portable communications device toward the
West. To receive the content item, potential recipients also
make gestures that specify receiving directions. For
example, a recipient pretends to “catch” a ball thrown from
the East. If the sending and receiving directions are com-
patible, then the content item is sent from the sender’s
device to the recipient’s device. Enhancements to the basic
scheme described above can be made to, for example,
specify a dispersion angle for the sending or receiving
directions or to include other restrictions so that, for
example, only intended recipients can receive the content
even if other potential recipients are in the specified sending
direction and make appropriate receiving gestures.


(52) **U.S. Cl.**

CPC **H04L 51/046** (2013.01); **G06F 1/1694**
(2013.01); **G06F 1/1698** (2013.01); **G06F**
3/017 (2013.01); **H04W 4/206** (2013.01);
H04L 67/04 (2013.01)

(58) **Field of Classification Search**

CPC .. H04L 29/08; H04N 21/47202; H04W 4/20

15 Claims, 8 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

8,312,392 B2 * 11/2012 Forutanpour et al. 715/863
 8,339,363 B2 * 12/2012 Krum G06F 1/1626
 345/158
 8,532,675 B1 * 9/2013 Pasquero H04M 1/72572
 345/158
 2007/0146347 A1 6/2007 Rosenberg
 2009/0017799 A1 * 1/2009 Thorn G06F 3/017
 455/414.1
 2009/0295753 A1 12/2009 King et al.
 2011/0065459 A1 3/2011 Cheng et al.
 2011/0088002 A1 4/2011 Freer
 2011/0209098 A1 8/2011 Hinckley et al.
 2011/0209104 A1 8/2011 Hinckley et al.
 2012/0077436 A1 * 3/2012 Konded G06F 3/04883
 455/41.2
 2012/0262379 A1 10/2012 King

2013/0130758 A1 * 5/2013 Moore A63F 13/12
 463/2
 2014/0062854 A1 * 3/2014 Cho G06F 3/017
 345/156
 2014/0229858 A1 * 8/2014 Bleker H04W 4/206
 715/753

OTHER PUBLICATIONS

Tushar Tajane, Hoccer Fun: Use Slide, Throw Gestures to Transfer Files Between iPhone, Android and Computer, <http://techzoom.org/hoccer-fun-use-slide-throw-gestures-to-transfer-files-between-iphone-android-and-computer/>, Jun. 6, 2011, all pages.
 Adi Robertson, 'Tangible' transfer concept would let you swipe files directly from MacBook to iPhone, <http://www.theverge.com/2012/5/3/2996448/ishac-bertran-tangible-file-transfer-concept>, Jun. 3, 2012, all pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3a




FIG. 3b





FIG. 4a

**FIG. 4b**




FIG. 5a




FIG. 5b

GESTURE-BASED CONTENT SHARING

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is related to U.S. Patent Applications (PCT/US2014/012850 and PCT/US2014/012853), filed on an even date herewith.

TECHNICAL FIELD

The present disclosure is related generally to media-content delivery and, more particularly, to social communications.

BACKGROUND

People are sharing more and more information electronically. They send e-mails and short text messages to friends and colleagues. Photographs, videos, and sound clips are often posted to social-networking sites. In social situations, people often want to quickly share photographs or other content with their friends.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

While the appended claims set forth the features of the present techniques with particularity, these techniques, together with their objects and advantages, may be best understood from the following detailed description taken in conjunction with the accompanying drawings of which:

FIG. 1 is an overview of a representative environment in which the present techniques may be practiced;

FIG. 2 is a generalized schematic of some of the devices of FIG. 1;

FIGS. 3a and 3b are flowcharts of representative methods for using a gesture to send content;

FIGS. 4a and 4b are flowcharts of representative methods for using a gesture to receive content; and

FIGS. 5a and 5b are flowcharts of representative methods usable by a server to transmit content.

DETAILED DESCRIPTION

Turning to the drawings, wherein like reference numerals refer to like elements, techniques of the present disclosure are illustrated as being implemented in a suitable environment. The following description is based on embodiments of the claims and should not be taken as limiting the claims with regard to alternative embodiments that are not explicitly described herein.

While many content-sharing applications exist, they are often designed for personal computers that have large screens and a full keyboard. When a user wishes to, for example, send a photograph from his smartphone to a couple of friends in the same room, the limited user interface of the smartphone (small screen, very small or non-existent keyboard) makes these conventional content-sharing applications seem clumsy and intrusive. Also, most conventional content-sharing applications require the sender to navigate through the application's user interface once for each intended recipient.

Consider the communications environment 100 of FIG. 1. The user 102 wishes to send some content (e.g., a photograph) from his portable communications device 104 to his friend's device 106. According to aspects of the present

disclosure, after selecting the content item that he wishes to send, the user 102 performs a gesture to specify a direction toward which the content item is to be sent. For example, he pretends to "throw" his device 104 (e.g., like throwing a ball or like throwing a flying disc) toward the West. To receive the content item, potential recipients also make gestures that specify receiving directions. For example, a potential recipient moves her device 106 to pretend to "catch" a ball thrown from the East. If the sending and receiving directions are compatible (as explained below), then the content item is sent from the sender's device 104 to the recipient's device 106.

Enhancements to the basic scheme described above can be made to, for example, specify a maximum sending distance or a dispersion angle for the sending or receiving directions (as shown by dotted lines in FIG. 1). A sending dispersion angle is specified by the sender 102 to exclude other people 108 from receiving the content. Other restrictions can be stated so that, for example, only intended recipients can receive the content even if other potential recipients are in the specified sending direction and make appropriate receiving gestures.

The function of the optional content server 110 is discussed below with reference to FIGS. 5a and 5b.

FIG. 2 shows the major components of a representative electronics device 104, 106, 110. A portable communications device 104, 106 could be, for example, a smartphone, tablet, personal computer, electronic book, or gaming controller. The content server 110 could be any of these and could also be a set-top box, a compute server, or a coordinated group of compute servers.

The CPU 200 of the electronics device 104, 106, 110 includes one or more processors (i.e., any of microprocessors, controllers, and the like) or a processor and memory system which processes computer-executable instructions to control the operation of the device 104, 106, 110. In particular, the CPU 200 supports aspects of the present disclosure as illustrated in FIGS. 3 through 5, discussed below. The device 104, 106, 110 can be implemented with a combination of software, hardware, firmware, and fixed-logic circuitry implemented in connection with processing and control circuits, generally identified at 202. Although not shown, the device 104, 106, 110 can include a system bus or data-transfer system that couples the various components within the device 104, 106, 110. A system bus can include any combination of different bus structures, such as a memory bus or memory controller, a peripheral bus, a universal serial bus, and a processor or local bus that utilizes any of a variety of bus architectures.

The electronics device 104, 106, 110 also includes one or more memory devices 204 that enable data storage, examples of which include random-access memory, non-volatile memory (e.g., read-only memory, flash memory, EPROM, and EEPROM), and a disk storage device. A disk storage device may be implemented as any type of magnetic or optical storage device, such as a hard disk drive, a recordable or rewriteable disc, any type of a digital versatile disc, and the like. The device 104, 106, 110 may also include a mass-storage media device.

The memory system 204 provides data-storage mechanisms to store device data 212, other types of information and data, and various device applications 210. An operating system 206 can be maintained as software instructions within the memory 204 and executed by the CPU 200. The device applications 210 may also include a device manager, such as any form of a control application or software application. The utilities 208 may include a signal-process-

ing and control module, code that is native to a particular component of the electronics device **104**, **106**, **110**, a hardware-abstraction layer for a particular component, and so on.

The electronics device **104**, **106**, **110** can also include an audio-processing system **214** that processes audio data and controls an audio system **216** (which may include, for example, speakers). A visual-processing system **218** processes graphics commands and visual data and controls a display system **220** that can include, for example, a display screen. The audio system **216** and the display system **220** may include any devices that process, display, or otherwise render audio, video, display, or image data. Display data and audio signals can be communicated to an audio component or to a display component via a radio-frequency link, S-video link, High-Definition Multimedia Interface, composite-video link, component-video link, Digital Video Interface, analog audio connection, or other similar communication link, represented by the media-data ports **222**. In some implementations, the audio system **216** and the display system **220** are components external to the device **104**, **106**, **110**. Alternatively (e.g., in a cellular telephone), these systems **216**, **220** are integrated components of the device **104**, **106**, **110**.

The electronics device **104**, **106**, **110** can include a communications interface which includes communication transceivers **224** that enable wired or wireless communication. Example transceivers **224** include Wireless Personal Area Network radios compliant with various IEEE 802.15 standards, Wireless Local Area Network radios compliant with any of the various IEEE 802.11 standards, Wireless Wide Area Network cellular radios compliant with 3GPP standards, Wireless Metropolitan Area Network radios compliant with various IEEE 802.16 standards, and wired Local Area Network Ethernet transceivers.

The electronics device **104**, **106**, **110** may also include one or more data-input ports **226** via which any type of data, media content, or inputs can be received, such as user-selectable inputs (e.g., from a keyboard, from a touch-sensitive input screen, or from another user-input device), messages, music, television content, recorded video content, and any other type of audio, video, or image data received from any content or data source. The data-input ports **226** may include USB ports, coaxial-cable ports, and other serial or parallel connectors (including internal connectors) for flash memory, storage disks, and the like. These data-input ports **226** may be used to couple the device **104**, **106**, **110** to components, peripherals, or accessories such as microphones and cameras.

Finally, the electronics device **104**, **106**, **110** may include any number of "other sensors" **228**. These sensors **228** can include, for example, accelerometers, a GPS receiver, compass, magnetic-field sensor, and the like.

FIG. **3a** presents a first method for sending a content item. In step **300**, the user **102** uses any known technique for selecting a content item to send. He may, for example, touch an icon corresponding to the content item to select it. If he takes a picture with his portable communications device **104**, and that picture is displayed on a screen of the device **104**, then that picture may be selected by default until unselected. The user **102** may even select multiple content items, such as a directory and all its contents. In some cases, he can run a specific application on his device **104** that presents possible content items to him for his selection.

The user **102** then makes a "sending" gesture using his portable communications device **104** (step **302**). The sending gesture specifies a sending direction. For example, he may pretend to throw his device **104** to the West. Position

sensors (e.g., accelerometers, a compass, or a magnetic-field sensor **228**) on the device **104** note the movement and send their data to the CPU **200** which interprets the gesture, recognizes it as a sending gesture, and notes the direction specified. In another example, he can select a content item by touching its icon on the display screen of his device **104** and move his finger as if to "flick" the icon in a specified direction. Other gestures are possible.

In addition to selecting a content item and specifying a sending direction, the user **102** may specify other characteristics of the sending. For clarity's sake, the discussion of these other characteristics is postponed until step **308**, below.

The content item and the sending direction are associated in step **304**. This is meant simply as shorthand for a memory operation. As discussed below, the content item may not be sent immediately, so it may be important to remember the association of the content item with the sending direction for later use.

In step **306**, the user's portable communications device **104** receives a request that includes a receiving direction. As discussed in more detail below with respect to FIGS. **4a** and **4b**, a potential recipient made a receiving gesture that specifies a receiving direction. In the particular embodiment of FIG. **3a**, that information is sent in a request and is received by the sender's device **104** in step **306**.

While optional step **308** logically precedes step **310**, for clarity's sake the discussion of step **308** follows that of step **310**.

In step **310**, the sending direction specified by the sender's sending gesture (step **302**) and the receiving direction contained in the request received in step **306** are compared. If these two directions are "compatible" (as discussed below), then (if all other restriction elements from optional step **308** are satisfied) the selected content item is sent from the sender's portable communications device **104** to another device, generally the device that sent the request received in step **306**. In a very simple example, if the content item is "thrown" to the West, and if the potential recipient's gesture indicates that it wishes to receive content coming from the East, then the sending and receiving directions are compatible, and the content item is sent.

The example just given, though useful, is perhaps too simple. More realistically, the sending process is associated with one or more optional "restriction elements" (step **308**). First, there should be some allowance for directional variations. Rather than simply throwing to the West, for example, the user **102** (or the sending application itself) can specify that the content item is being "sprayed" out in directions from 45° North of West to 45° South of West. Similarly, the receiving direction of step **306** can come with an angular dispersion. These angles are indicated by the dotted lines in FIG. **1**. When the directions are compared in step **310**, any pair of directions within the two angular dispersions is considered to be "compatible." The angles can also be intentionally narrowed to exclude other recipients.

(Note that in general, the methods of the present disclosure do not require detecting the location or even the presence of another device in order to communicate with that device: A comparison of the sending and receiving directions is sufficient. However, location-detection can be added to the basic methods, for example when setting the angular dispersion or distance to exclude some potential recipients.)

A sending distance can be specified as a second restriction element, again limiting the range of potential recipients. This makes the present methods more robust than previous

5

methods, especially in environments (e.g., indoors or in an environment with significant electrical interference) where location detection is unreliable.

Another potential restriction element is a time limit. According to aspects of the present disclosure, there is no requirement that the sending **104** and receiving **106** devices actually be physically near one another at the time of transmission. There is no need for the two devices **104**, **106** to use a “handshake” to set up the potential transfer. (In these cases, an intermediary content server **110** can be used. Please see the discussion accompanying FIGS. **5a** and **5b** below.) Thus, the sender **102** can specify that the selected content item is available for reception for only, say, the next five minutes.

As a final example of a restriction element, known techniques of encryption, security, and privacy can be applied to the potential transfer. Thus, a potential recipient device **106** may need to identify itself to the sending device **104** before the content is transferred. The sender **102** himself may specify, e.g., in a profile setting, that content transferred using the present techniques can only go to those people identified in a contacts list on his device **104**.

As mentioned above, the transfer of the content item in step **310** only proceeds if the restriction elements in place (if any) are satisfied.

In some embodiments, when the content item is sent in step **310**, along with it is sent an identifier of the user **102** or of his sending device **104**. This information can be used by the receiving device **106** as discussed below.

FIG. **3b** presents another method for sending a content item. The first steps **300** through **304** are the same as in the method of FIG. **3a**. Then, however, instead of receiving a reception request (as in step **306** of FIG. **3a**), this method transmits the selected content item along with information about the sending direction in step **312**. The implication is that the comparison of the sending and receiving directions (done in step **310** in the method of FIG. **3a**) will be done by a device other than the sending device **104**. (Some possibilities for those other devices are discussed below in reference to FIGS. **4** and **5**.) To make sure that that device has all necessary information, the sender can also send an identification of the sender **102** or of his device **104** (optional step **314**) and any restriction elements (optional step **316**).

A potential receiving device **106** can perform the method of FIG. **4a**. In step **400**, the device **106** detects a receiving gesture that specifies a receiving direction. Gesture-detection can be performed using the techniques discussed above in relation to step **302** of FIG. **3a**. However, there is no requirement that the receiving gesture be complementary to the sending gesture. Thus, the sender **102** may pretend to “throw” the selected content item, while the receiver can make a reverse “flick” on a touch-screen to receive it.

Note that there is no requirement that a potential recipient make the receiving gesture of step **400** in response to seeing the sender’s sending gesture. There need be no “handshaking” either of devices or of people for the present techniques to work. Indeed, the sender **102** may make his sending gesture and then leave the premises long before the potential recipient makes her receiving gesture.

In step **402**, the potential receiving device **106** sends a request that includes the receiving gesture. This may (or may not) be the same request received in step **306** of FIG. **3a**. In any case, a content item is received in step **404**. Note that in the particular method of FIG. **4a**, the receiving device **106** does not need to compare the sending and receiving directions for compatibility. It is assumed that this comparison is

6

done on another device, and that only a content item sent with a compatible direction is received in step **404**.

In optional steps **406** and **408**, the potential recipient device **106** receives other information such as a sender or device identifier and a restriction element. The potential recipient **106** can use this information in deciding whether or not to accept the content item received in step **404**. For example, the potential recipient **106** may be configured to only accept content items from known senders **102**. As another use of a restriction element, the content item may be received in an encrypted form, and only authorized recipients **106** are given access to the decryption key.

FIG. **4b** presents another method for receiving a content item. A receiving gesture specifying a receiving direction is detected in step **400**, as discussed above in reference to FIG. **4a**. Then, in step **410**, a content item is received along with its associated sending direction. This step may correspond to the sending step **312** of FIG. **3b**. The receiving device **106** may also receive identification information and restriction elements in optional steps **406** and **408**, also as discussed above. Finally, in step **412** the receiving device **106** compares the receiving direction detected in step **400** with the sending direction received in step **410**. If they are compatible (please see the discussion of step **310** of FIG. **3a**, above), then the content item is accepted (assuming that the restriction requirements, if any, are also satisfied).

In some cases, the content item is not transmitted directly from the sending device **104** to the receiving device **106**. Instead, a content server **110** mediates the transmission. A first method usable by the content server **110** is illustrated in FIG. **5a**. The method begins in step **500** when the content server **110** receives a content item and its associated sending direction. This step may correspond to the sender’s sending step **312** of FIG. **3b**.

In steps **502** and **504**, the content server **110** receives the further information and restriction requirements, if any, sent by the sending device **104**.

A request from a potential recipient **106** is received in step **506**, the request including a receiving direction. This request may correspond to the request sent in step **402** of FIG. **4a**. As in steps **310** of FIGS. **3a** and **412** of FIG. **4b**, the sending and receiving directions are compared and, if compatible (and if the restriction elements, if any, are satisfied), then the content item and associated information are sent to the potential recipient **106** in step **508**. This sending may correspond to the receiving of step **404** of FIG. **4a**.

Note that the request of step **506** may be received long after (or, theoretically, even before), the content item is received in step **500**. That is, the presence of the content server **110** removes any necessity of concurrency between the methods of the sending **104** and receiving **106** devices.

FIG. **5b** presents a variant method practicable by the content server **110**. Here, the content server **110** receives the content item, its associated sending direction, and any further information and restriction elements in steps **500** through **504**, as discussed above. The content server **110** then sends all of this along in step **510**. Presumably, the recipient of this information would compare sending and receiving directions for compatibility. (Please see the receiving method of FIG. **4b**).

While FIGS. **3** through **5** present distinct methods, note that elements of these methods can be combined as necessary for different situations. So, for example, a sending device **104** would probably implement the methods of both FIGS. **3a** and **3b**, applying them as needed. As another example, a sender **102** may use one method when he wishes to restrict the distribution of his content and use another

method to broadcast the content broadly, giving full control to the potential recipients to decide whether they wish to accept the content or not.

In view of the many possible embodiments to which the principles of the present discussion may be applied, it should be recognized that the embodiments described herein with respect to the drawing figures are meant to be illustrative only and should not be taken as limiting the scope of the claims. Therefore, the techniques as described herein contemplate all such embodiments as may come within the scope of the following claims and equivalents thereof.

We claim:

1. A method for accepting a content item on a receiving portable communications device, the method comprising:

detecting, by the receiving portable communications device, a receiving gesture, the receiving gesture specifying a sending angular dispersion originating from a sending location, the sending angular dispersion comprising a first direction and a second direction defining a first angle;

sending, by the receiving portable communications device to a device distinct from the receiving portable communications device, a request comprising a receiving angular dispersion, the receiving angular dispersion comprising a third direction and a fourth direction defining a second angle; and

receiving, by the receiving portable communications device, the content item based on the first and second angle when at least a portion of the sending angular dispersion overlaps at least a portion of the receiving angular dispersion, from opposing directions, when the sending location is within a predetermined distance of the receiving portable communication device,

wherein the content is not received by the receiving portable communications device when the receiving and sending angular dispersions do not overlap from the opposing directions.

2. The method of claim **1** wherein the content item comprises an element selected from the group consisting of: a social-networking post, a message, a file, a link to a file, an address, and a directory.

3. The method of claim **1** wherein the device distinct from the receiving portable communications device is selected from the group consisting of: a content server and a sending portable communications device.

4. The method of claim **1** further comprising receiving an element selected from the group consisting of: an identifier of a sending portable communications device and an identifier of a user of a sending portable communications device.

5. The method of claim **1** further comprising receiving a restriction element selected from the group consisting of: a time limit, a recipient-identification requirement, an angular dispersion, and a distance.

6. A receiving portable communications device configured for accepting a content item, the receiving portable communications device comprising:

a communications interface; and

a processor operatively connected to the communications interface and configured for:

detecting a receiving gesture, the receiving gesture specifying a sending angular dispersion originating at a sending location, the sending angular dispersion comprising a first direction and a second direction defining a first angle;

sending, via the communications interface to a device distinct from the receiving portable communications device, a request comprising a receiving angular

dispersion, the receiving angular dispersion comprising a third direction and a fourth direction defining a second angle; and

receiving, via the communications interface, the content item when at least a portion of the sending angular dispersion overlaps at least a portion of the receiving angular dispersion, from opposing directions, when the sending location is within a predetermined range of the receiving portable communications device, wherein the content is not received by the receiving portable communications device when the receiving and sending angular dispersions do not overlap from the opposing directions.

7. The receiving portable communications device of claim **6** wherein the device is selected from the group consisting of: a personal communications device, a mobile telephone, a personal digital assistant, a tablet computer, and a gaming controller.

8. A method for accepting a content item on a receiving portable communications device, the method comprising:

detecting, by the receiving portable communications device, a receiving gesture, the receiving gesture specifying a first angular dispersion comprising a first direction and a second direction defining a first angle originating from a source location;

receiving, by the receiving portable communications device from a device distinct from the receiving portable communications device, the content item and a sending gesture, the sending gesture comprising a second angular dispersion comprising a third direction and a fourth direction defining a second angle; and

if the first angular dispersion and the second angular dispersion are compatible, then accepting, by the receiving portable communications device, the content item,

wherein the first and second angular dispersions are compatible when at least a portion of the sending angular dispersion overlaps at least a portion of the receiving angular dispersion, from opposing directions, when the source location is within a predetermined distance of the receiving portable communication device, wherein the content is not accepted by the receiving portable communications device when the receiving and sending angular dispersions do not overlap from the opposing directions.

9. The method of claim **8** wherein the content item comprises an element selected from the group consisting of: a social-networking post, a message, a file, a link to a file, an address, and a directory.

10. The method of claim **8** wherein the device distinct from the receiving portable communications device is selected from the group consisting of: a content server and a sending portable communications device.

11. The method of claim **8** further comprising receiving an element selected from the group consisting of: an identifier of a sending portable communications device and an identifier of a user of a sending portable communications device.

12. The method of claim **8** further comprising: receiving a restriction element selected from the group consisting of: a time limit and a recipient-identification requirement;

wherein accepting is only performed if the received restriction element is satisfied.

13. The method of claim **8** further comprising: receiving a distance restriction element; and detecting a distance between a sending and the receiving portable communications devices;

9

wherein accepting is only performed if the detected direction satisfies the specified distance restriction element.

14. A receiving portable communications device configured for accepting a content item, the receiving portable communications device comprising: 5
 a communications interface; and
 a processor operatively connected to the communications interface and configured for:
 detecting a receiving gesture, the receiving gesture 10
 specifying a first angular dispersion comprising a first direction and a second direction defining a first angle originating from a source location;
 receiving, via the communications interface from a device distinct from the receiving portable communications device, the content item and a sending 15
 gesture, the sending gesture comprising a second angular dispersion comprising a third direction and a fourth direction defining a second angle; and

10

if the first angular dispersion and the second angular dispersion are compatible, then accepting the content item,

wherein the first and second angular dispersions are compatible when at least a portion of the sending angular dispersion overlaps at least a portion of the receiving angular dispersion, from opposing directions, when the source location is within a predetermined range of the receiving portable communications device, wherein the content is not accepted when the receiving and sending angular dispersions do not overlap from the opposing directions.

15. The receiving portable communications device of claim **14** wherein the device is selected from the group consisting of: a personal communications device, a mobile telephone, a personal digital assistant, a tablet computer, and a gaming controller.

* * * * *