



US009446195B2

(12) **United States Patent**
Kramer et al.

(10) **Patent No.:** **US 9,446,195 B2**
(45) **Date of Patent:** ***Sep. 20, 2016**

(54) **INJECTION DEVICE WITH CAMMED RAM ASSEMBLY**

A61M 5/3146; A61M 5/31585; A61M 2005/3247; A61M 5/3007

See application file for complete search history.

(71) Applicant: **Antares Pharma, Inc.**, Ewing, NJ (US)

(56) **References Cited**

(72) Inventors: **Thomas E. Kramer**, Coon Rapids, MN (US); **Matthew H. Rust**, Hudson, WI (US); **Paul M. Goudreau**, St. Paul, MN (US); **Peter A. Hoefft**, Seattle, WA (US); **Julius C. Sund**, Plymouth, MN (US); **Peter L. Sadowski**, Woodbury, MN (US)

U.S. PATENT DOCUMENTS

547,370 A 10/1895 Chalefou
1,465,793 A 8/1923 Schilling

(Continued)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Antares Pharma, Inc.**, Ewing, NJ (US)

AR 00081651 10/2012
AR 082053 11/2012

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 411 days.

OTHER PUBLICATIONS

This patent is subject to a terminal disclaimer.

International Search Report and Written Opinion issued on Nov. 16, 2012 in counterpart International Application No. PCT/US12/46742.

(Continued)

(21) Appl. No.: **13/930,166**

Primary Examiner — Aarti B Berdichevsky

(22) Filed: **Jun. 28, 2013**

(74) *Attorney, Agent, or Firm* — Morgan Lewis & Bockius LLP

(65) **Prior Publication Data**

US 2013/0289491 A1 Oct. 31, 2013

Related U.S. Application Data

(63) Continuation of application No. 13/184,229, filed on Jul. 15, 2011, now Pat. No. 8,496,619.

(51) **Int. Cl.**

A61M 5/24 (2006.01)

A61M 5/20 (2006.01)

(Continued)

(57) **ABSTRACT**

An exemplary embodiment of the present disclosure can provide an injector including a trigger mechanism, an energy source, and a user-operable firing-initiation member. The trigger member can include a trigger member having a retainer portion, and a ram assembly having a ram configured to pressurize a medicament container for expelling a medicament therefrom and a trigger engagement member configured to engage the retainer portion of the trigger member in a pre-firing condition. The energy source can be associated with the ram for powering the ram to expel the medicament, and the user-operable firing-initiation member can be operable for causing an axial rotation between the trigger engagement member and the retainer portion from the pre-firing condition to a firing condition in which the trigger engagement member is released from the retainer portion to allow the energy source to fire the ram.

(52) **U.S. Cl.**

CPC *A61M 5/2033* (2013.01); *A61M 5/30*


(2013.01); *A61M 5/3007* (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC *A61M 5/24*; *A61M 5/2033*; *A61M 5/326*;

20 Claims, 28 Drawing Sheets



(51)	Int. Cl.		4,634,027 A	1/1987	Kanarvogel
	<i>A61M 5/30</i>	(2006.01)	4,661,098 A	4/1987	Bekkering et al.
	<i>A61M 5/32</i>	(2006.01)	4,662,878 A	5/1987	Lindmayer
	<i>A61M 5/50</i>	(2006.01)	4,664,653 A	5/1987	Sagstetter et al.
(52)	U.S. Cl.		4,664,655 A	5/1987	Orentreich et al.
	CPC	<i>A61M 5/3204</i> (2013.01); <i>A61M 5/326</i> (2013.01); <i>A61M 5/5086</i> (2013.01); <i>A61M</i> <i>2005/206</i> (2013.01); <i>A61M 2005/2013</i> (2013.01); <i>A61M 2005/2073</i> (2013.01); <i>A61M</i> <i>2005/3247</i> (2013.01)	4,678,461 A	7/1987	Mesa
			4,719,825 A	1/1988	LaHaye et al.
			4,722,728 A	2/1988	Dixon
			4,774,772 A	10/1988	Vetter et al.
			4,790,824 A	12/1988	Morrow et al.
			4,818,517 A	4/1989	Kwee et al.
			4,820,286 A	4/1989	van der Wal
			4,822,340 A	4/1989	Kamstra
(56)	References Cited		4,830,217 A	5/1989	Dufresne et al.
	U.S. PATENT DOCUMENTS		4,874,381 A	10/1989	Vetter
			4,883,472 A	11/1989	Michel
			4,913,699 A	4/1990	Parsons
			4,915,701 A	4/1990	Halkyard
			4,929,238 A	5/1990	Baum
			4,936,833 A	6/1990	Sams
			4,940,460 A	7/1990	Casey et al.
			4,966,581 A	10/1990	Landau
			4,968,302 A	11/1990	Schluter et al.
			4,973,318 A	11/1990	Holm et al.
			4,976,701 A	12/1990	Ejlersen et al.
			4,982,769 A	1/1991	Fournier et al.
			4,986,816 A	1/1991	Steiner et al.
			5,042,977 A	8/1991	Bechtold et al.
			5,062,830 A	11/1991	Dunlap
			5,064,413 A	11/1991	McKinnon et al.
			5,069,670 A	12/1991	Vetter et al.
			5,078,680 A	1/1992	Sarnoff
			5,080,648 A	1/1992	D'Antonio
			5,080,649 A	1/1992	Vetter
			5,085,641 A	2/1992	Sarnoff et al.
			5,085,642 A	2/1992	Sarnoff et al.
			5,092,842 A	3/1992	Bechtold et al.
			5,102,388 A	4/1992	Richmond
			5,102,393 A	4/1992	Sarnoff et al.
			5,104,380 A	4/1992	Holman et al.
			5,114,406 A	5/1992	Gabriel et al.
			5,137,516 A	8/1992	Rand et al.
			5,137,528 A	8/1992	Crose
			5,139,490 A	8/1992	Vetter et al.
			5,163,907 A	11/1992	Szuskiewicz
			5,176,643 A	1/1993	Kramer et al.
			5,180,370 A	1/1993	Gillespie
			5,185,985 A	2/1993	Vetter et al.
			5,195,983 A	3/1993	Boese
			5,221,348 A	6/1993	Masano
			5,226,895 A	7/1993	Harris
			5,232,459 A	8/1993	Hjertman
			5,256,142 A	10/1993	Colavecchio
			5,263,934 A	11/1993	Haak
			5,271,744 A	12/1993	Kramer et al.
			5,279,543 A	1/1994	Glikfeld et al.
			5,279,576 A	1/1994	Loo et al.
			5,279,585 A	1/1994	Balkwill
			5,279,586 A	1/1994	Balkwill
			5,281,198 A	1/1994	Haber et al.
			5,290,228 A	3/1994	Uemura et al.
			5,295,965 A	3/1994	Wilmot
			5,300,030 A	4/1994	Crossman et al.
			5,304,128 A	4/1994	Haber et al.
			5,304,152 A	4/1994	Sams
			5,308,341 A	5/1994	Chanoch
			5,318,522 A	6/1994	D'Antonio
			5,320,603 A	6/1994	Vetter et al.
			5,330,431 A	7/1994	Herskowitz
			5,332,399 A	7/1994	Grabenkort et al.
			5,334,144 A	8/1994	Alchas et al.
			5,342,308 A	8/1994	Boschetti
			5,350,367 A	9/1994	Stiehl et al.
			5,354,286 A	10/1994	Mesa et al.
			5,358,489 A	10/1994	Wyrick
			RE34,845 E	1/1995	Vetter et al.
			5,391,151 A	2/1995	Wilmot
			5,405,362 A	4/1995	Kramer et al.
			5,415,648 A	5/1995	Malay et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

5,425,715	A	6/1995	Dalling et al.	6,203,529	B1	3/2001	Gabriel et al.
5,451,210	A	9/1995	Kramer et al.	6,210,369	B1	4/2001	Wilmot et al.
5,478,316	A	12/1995	Bitdinger et al.	6,221,046	B1	4/2001	Burroughs et al.
5,505,694	A	4/1996	Hubbard et al.	6,221,053	B1	4/2001	Walters et al.
5,514,097	A	5/1996	Knauer	6,223,408	B1	5/2001	Vetter et al.
5,514,107	A	5/1996	Haber et al.	6,231,540	B1	5/2001	Smedegaard
5,540,664	A	7/1996	Wyrick	6,241,709	B1	6/2001	Bechtold et al.
5,542,760	A	8/1996	Chanoch et al.	6,245,347	B1	6/2001	Zhang et al.
5,544,234	A	8/1996	Terajima et al.	6,258,078	B1	7/2001	Thilly
5,549,561	A	8/1996	Hjertman	6,264,629	B1	7/2001	Landau
5,554,134	A	9/1996	Bonnichsen	6,270,479	B1	8/2001	Bergens et al.
5,562,625	A	10/1996	Stefancin, Jr.	6,309,371	B1	10/2001	Deboer et al.
5,567,160	A	10/1996	Massino	6,319,224	B1	11/2001	Stout et al.
5,569,190	A	10/1996	D'Antonio	6,371,939	B2	4/2002	Bergens et al.
5,569,192	A	10/1996	van der Wal	6,383,168	B1	5/2002	Landau et al.
5,569,236	A	10/1996	Kriesel	6,391,003	B1	5/2002	Lesch, Jr.
5,573,042	A	11/1996	De Haen	6,406,456	B1	6/2002	Slate et al.
5,593,388	A	1/1997	Phillips	6,428,528	B2	8/2002	Sadowski et al.
5,599,302	A	2/1997	Lilley et al.	6,471,669	B2	10/2002	Landau
5,599,309	A	2/1997	Marshall et al.	6,494,865	B1	12/2002	Alchas
5,605,542	A	2/1997	Tanaka et al.	6,517,517	B1	2/2003	Farrugia et al.
5,637,094	A	6/1997	Stewart, Jr. et al.	6,530,904	B1	3/2003	Edwards et al.
5,637,100	A	6/1997	Sudo	6,544,234	B1	4/2003	Gabriel
5,649,912	A	7/1997	Peterson	6,562,006	B1	5/2003	Hjertman et al.
5,658,259	A	8/1997	Pearson et al.	6,565,553	B2	5/2003	Sadowski et al.
5,665,071	A	9/1997	Wyrick	6,568,259	B2	5/2003	Saheki et al.
5,688,251	A	11/1997	Chanoch	6,569,123	B2	5/2003	Alchas et al.
5,695,472	A	12/1997	Wyrick	6,569,143	B2	5/2003	Alchas et al.
5,704,911	A	1/1998	Parsons	6,584,910	B1	7/2003	Plass
5,725,508	A	3/1998	Chanoch et al.	6,589,210	B1	7/2003	Rolfe
5,730,723	A	3/1998	Castellano et al.	6,607,508	B2	8/2003	Knauer
5,743,889	A	4/1998	Sams	6,620,137	B2	9/2003	Kirchhofer et al.
5,769,138	A	6/1998	Sadowski et al.	6,641,561	B1	11/2003	Hill et al.
5,785,691	A	7/1998	Vetter et al.	6,645,170	B2	11/2003	Landau
5,788,670	A	8/1998	Reinhard et al.	6,656,150	B2	12/2003	Hill et al.
5,801,057	A	9/1998	Smart et al.	6,673,035	B1	1/2004	Rice et al.
5,807,309	A	9/1998	Lundquist et al.	6,682,504	B2	1/2004	Nelson et al.
5,820,602	A	10/1998	Kovelman et al.	6,689,092	B2	2/2004	Zierenberg et al.
5,820,622	A	10/1998	Gross et al.	6,706,000	B2	3/2004	Perez et al.
5,827,232	A	10/1998	Chanoch et al.	6,746,429	B2	6/2004	Sadowski et al.
5,836,911	A	11/1998	Marzynski et al.	6,767,336	B1	7/2004	Kaplan
5,843,036	A	12/1998	Olive et al.	6,805,686	B1	10/2004	Fathallah et al.
5,846,233	A	12/1998	Lilley et al.	6,830,560	B1	12/2004	Gross et al.
5,851,197	A	12/1998	Marano et al.	6,899,698	B2	5/2005	Sams
5,851,198	A	12/1998	Castellano et al.	6,932,793	B1	8/2005	Marshall et al.
5,860,456	A	1/1999	Bydlon et al.	6,932,794	B2	8/2005	Giambattista et al.
5,865,795	A	2/1999	Schiff et al.	6,936,032	B1	8/2005	Bush, Jr. et al.
5,865,799	A	2/1999	Tanaka et al.	6,969,370	B2	11/2005	Langley et al.
5,868,711	A	2/1999	Kramer et al.	6,969,372	B1	11/2005	Halseth
5,873,857	A	2/1999	Kriesel	6,979,316	B1	12/2005	Rubin et al.
5,875,976	A	3/1999	Nelson et al.	6,986,758	B2	1/2006	Schiffmann
5,879,327	A	3/1999	DeFarges et al.	6,997,901	B2	2/2006	Popovsky
5,891,085	A	4/1999	Lilley et al.	7,018,364	B2	3/2006	Giambattista et al.
5,891,086	A	4/1999	Weston	7,066,907	B2	6/2006	Crossman et al.
5,893,842	A	4/1999	Imbert	7,112,187	B2	9/2006	Karlsson
5,919,159	A	7/1999	Lilley et al.	7,118,552	B2	10/2006	Shaw et al.
5,921,966	A	7/1999	Bendek et al.	7,118,553	B2	10/2006	Scherer
5,925,017	A	7/1999	Kriesel et al.	7,169,132	B2	1/2007	Bendek et al.
5,928,205	A	7/1999	Marshall	7,195,616	B2	3/2007	Diller et al.
5,935,949	A	8/1999	White	7,218,962	B2	5/2007	Freyman
5,951,528	A	9/1999	Parkin	7,220,247	B2	5/2007	Shaw et al.
5,957,897	A	9/1999	Jeffrey	7,247,149	B2	7/2007	Beyerlein
5,960,797	A	10/1999	Kramer et al.	7,291,132	B2	11/2007	DeRuntz et al.
5,989,227	A	11/1999	Vetter et al.	7,292,885	B2	11/2007	Scott et al.
6,004,297	A	12/1999	Steenfeldt-Jensen et al.	7,297,136	B2	11/2007	Wyrick
6,045,534	A	4/2000	Jacobson et al.	7,341,575	B2	3/2008	Rice et al.
6,056,716	A	5/2000	D'Antonio et al.	7,361,160	B2	4/2008	Hommann et al.
6,077,247	A	6/2000	Marshall et al.	7,390,314	B2	6/2008	Stutz, Jr. et al.
6,083,201	A	7/2000	Skinkle	7,390,319	B2	6/2008	Friedman
6,090,070	A	7/2000	Hager et al.	7,407,492	B2	8/2008	Gurtner
6,099,504	A	8/2000	Gross et al.	7,416,540	B2	8/2008	Edwards et al.
6,123,684	A	9/2000	Deboer et al.	7,442,185	B2	10/2008	Amark et al.
6,132,395	A	10/2000	Landau et al.	7,449,012	B2	11/2008	Young et al.
6,159,181	A	12/2000	Crossman et al.	7,488,308	B2	2/2009	Lesch, Jr.
6,171,276	B1	1/2001	Lippe et al.	7,488,313	B2	2/2009	Segal et al.
				7,488,314	B2	2/2009	Segal et al.
				7,500,964	B2	3/2009	Shaw et al.
				7,517,342	B2	4/2009	Scott et al.
				7,519,418	B2	4/2009	Scott et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,544,188 B2	6/2009	Edwards et al.	8,277,412 B2	10/2012	Kronestedt
7,547,293 B2	6/2009	Williamson et al.	8,277,413 B2	10/2012	Kirchhofer
7,569,035 B1	8/2009	Wilmot et al.	8,298,175 B2	10/2012	Hirschel et al.
7,611,491 B2	11/2009	Pickhard	8,298,194 B2	10/2012	Moller
7,621,887 B2	11/2009	Griffiths et al.	8,300,852 B2	10/2012	Terada
7,621,891 B2	11/2009	Wyrick	RE43,834 E	11/2012	Steenfeldt-Jensen et al.
7,635,348 B2	12/2009	Raven et al.	8,308,232 B2	11/2012	Zamperla et al.
7,635,350 B2	12/2009	Scherer	8,308,695 B2	11/2012	Laios
7,637,891 B2	12/2009	Wall	8,313,466 B2	11/2012	Edwards et al.
7,648,482 B2	1/2010	Edwards et al.	8,317,757 B2	11/2012	Plumptre
7,648,483 B2	1/2010	Edwards et al.	8,323,237 B2	12/2012	Radmer et al.
7,654,983 B2	2/2010	De La Sema et al.	8,333,739 B2	12/2012	Moller
7,658,724 B2	2/2010	Rubin et al.	8,337,472 B2	12/2012	Edginton et al.
7,670,314 B2	3/2010	Wall et al.	8,343,103 B2	1/2013	Moser
7,704,237 B2	4/2010	Fisher et al.	8,343,109 B2	1/2013	Marshall et al.
7,717,877 B2	5/2010	Lavi et al.	8,348,905 B2	1/2013	Radmer et al.
7,722,595 B2	5/2010	Pettis et al.	8,353,878 B2	1/2013	Moller et al.
7,731,686 B2	6/2010	Edwards et al.	8,357,120 B2	1/2013	Moller et al.
7,731,690 B2	6/2010	Edwards et al.	8,357,125 B2	1/2013	Grunhut et al.
7,736,333 B2	6/2010	Gillespie, III	8,361,036 B2	1/2013	Moller et al.
7,744,582 B2	6/2010	Sadowski et al.	8,366,680 B2	2/2013	Raab
7,749,194 B2	7/2010	Edwards et al.	8,372,031 B2	2/2013	Elmen et al.
7,749,195 B2	7/2010	Hommann	8,372,042 B2	2/2013	Wieselblad
7,762,996 B2	7/2010	Palasis	8,376,993 B2	2/2013	Cox et al.
7,776,015 B2	8/2010	Sadowski et al.	8,398,593 B2	3/2013	Eich et al.
7,794,432 B2	9/2010	Young et al.	8,409,149 B2	4/2013	Hommann et al.
7,811,254 B2	10/2010	Wilmot et al.	8,435,215 B2	5/2013	Abry et al.
7,862,543 B2	1/2011	Potter et al.	8,496,619 B2*	7/2013	Kramer A61M 5/2033 604/135
7,896,841 B2	3/2011	Wall et al.	2001/0039394 A1	11/2001	Weston
7,901,377 B1	3/2011	Harrison et al.	2001/0049496 A1	12/2001	Kirchhofer et al.
7,905,352 B2	3/2011	Wyrick	2002/0007149 A1	1/2002	Nelson et al.
7,905,866 B2	3/2011	Haider et al.	2002/0045866 A1	4/2002	Sadowski et al.
7,918,823 B2	4/2011	Edwards et al.	2002/0173752 A1	11/2002	Polzin
7,927,303 B2	4/2011	Wyrick	2002/0183690 A1	12/2002	Arnisolle
7,931,618 B2	4/2011	Wyrick	2002/0188251 A1	12/2002	Staylor et al.
7,947,017 B2	5/2011	Edwards et al.	2003/0040697 A1	2/2003	Pass et al.
RE42,463 E	6/2011	Landau	2003/0083621 A1	5/2003	Shaw et al.
7,955,304 B2	6/2011	Guillermo	2003/0105430 A1	6/2003	Lavi et al.
7,967,772 B2	6/2011	McKenzie et al.	2003/0130619 A1	7/2003	Safabash et al.
7,988,675 B2	8/2011	Gillespie, III et al.	2003/0158523 A1	8/2003	Hjertman et al.
8,016,774 B2	9/2011	Freeman et al.	2003/0171717 A1	9/2003	Farrugia et al.
8,016,788 B2	9/2011	Edwards et al.	2003/0229330 A1	12/2003	Hickle
8,021,335 B2	9/2011	Lesch, Jr.	2003/0236502 A1	12/2003	La Serna et al.
8,048,035 B2	11/2011	Mesa et al.	2004/0039336 A1	2/2004	Amark et al.
8,048,037 B2	11/2011	Kohlbrener et al.	2004/0039337 A1	2/2004	Letzing
8,057,427 B2	11/2011	Griffiths et al.	2004/0097783 A1	5/2004	Peters et al.
8,066,659 B2	11/2011	Joshi et al.	2004/0097883 A1	5/2004	Roe
8,083,711 B2	12/2011	Enggaard	2004/0143213 A1	7/2004	Hunter et al.
8,100,865 B2	1/2012	Spofforth	2004/0220524 A1	11/2004	Sadowski et al.
8,105,272 B2	1/2012	Williamson et al.	2004/0267207 A1	12/2004	Veasey et al.
8,105,281 B2	1/2012	Edwards et al.	2004/0267355 A1	12/2004	Scott et al.
8,110,209 B2	2/2012	Prestrelski et al.	2005/0020979 A1	1/2005	Westbye et al.
8,123,719 B2	2/2012	Edwards et al.	2005/0027255 A1	2/2005	Lavi et al.
8,123,724 B2	2/2012	Gillespie, III	2005/0033234 A1	2/2005	Sadowski et al.
8,162,873 B2	4/2012	Muto et al.	2005/0080377 A1	4/2005	Sadowski et al.
8,162,886 B2	4/2012	Sadowski et al.	2005/0101919 A1	5/2005	Brunnberg
8,167,840 B2	5/2012	Matusch	2005/0165360 A1	7/2005	Stamp
8,167,866 B2	5/2012	Klein	2005/0165363 A1	7/2005	Judson et al.
8,177,758 B2	5/2012	Brooks, Jr. et al.	2005/0209569 A1	9/2005	Ishikawa et al.
8,187,224 B2	5/2012	Wyrick	2005/0215955 A1	9/2005	Slawson
8,216,180 B2	7/2012	Tschirren et al.	2005/0240145 A1	10/2005	Scott et al.
8,216,192 B2	7/2012	Burroughs et al.	2005/0256499 A1	11/2005	Pettis et al.
8,226,618 B2	7/2012	Geertsen	2005/0261634 A1	11/2005	Karlsson
8,226,631 B2	7/2012	Boyd et al.	2005/0273054 A1	12/2005	Asch
8,233,135 B2	7/2012	Jansen et al.	2006/0025747 A1	2/2006	Sullivan et al.
8,235,952 B2	8/2012	Wikner	2006/0106362 A1	5/2006	Pass et al.
8,246,577 B2	8/2012	Schrul et al.	2006/0129122 A1	6/2006	Wyrick
8,251,947 B2	8/2012	Kramer et al.	2006/0224124 A1	10/2006	Scherer
8,257,318 B2	9/2012	Thogersen et al.	2006/0258988 A1	11/2006	Keitel et al.
8,257,319 B2	9/2012	Plumptre	2006/0258990 A1	11/2006	Weber
8,267,899 B2	9/2012	Moller	2007/0017533 A1	1/2007	Wyrick
8,267,900 B2	9/2012	Harms et al.	2007/0025890 A1	2/2007	Joshi et al.
8,273,798 B2	9/2012	Bausch et al.	2007/0027430 A1	2/2007	Hommann
8,275,454 B2	9/2012	Adachi et al.	2007/0088288 A1	4/2007	Barron et al.
8,276,583 B2	10/2012	Farieta et al.	2007/0093775 A1	4/2007	Daly
			2007/0100288 A1	5/2007	Bozeman et al.
			2007/0123818 A1	5/2007	Griffiths et al.
			2007/0123829 A1	5/2007	Atterbury et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2007/0129686	A1	6/2007	Daily	2011/0224620	A1	9/2011	Johansen et al.
2007/0129687	A1	6/2007	Marshall et al.	2011/0238003	A1	9/2011	Bruno-Raimondi et al.
2007/0185432	A1	8/2007	Etheredge et al.	2011/0269750	A1	11/2011	Kley et al.
2007/0191784	A1	8/2007	Jacobs et al.	2011/0319864	A1	12/2011	Beller et al.
2007/0219498	A1	9/2007	Malone et al.	2012/0004608	A1	1/2012	Lesch, Jr.
2008/0059133	A1	3/2008	Edwards et al.	2012/0016296	A1	1/2012	Charles
2008/0154199	A1	6/2008	Wyrick	2012/0046609	A1	2/2012	Mesa et al.
2008/0154200	A1	6/2008	Lesch, Jr.	2012/0053563	A1	3/2012	Du
2008/0185069	A1	8/2008	Clark	2012/0059319	A1	3/2012	Segal
2008/0262427	A1	10/2008	Hommann	2012/0071829	A1	3/2012	Edwards et al.
2008/0262436	A1	10/2008	Olson	2012/0095443	A1	4/2012	Ferrari et al.
2008/0262445	A1	10/2008	Hsu et al.	2012/0101475	A1	4/2012	Wilmot et al.
2009/0124981	A1	5/2009	Evans	2012/0116318	A1	5/2012	Edwards et al.
2009/0124997	A1	5/2009	Pettis et al.	2012/0123350	A1	5/2012	Giambattista et al.
2009/0204062	A1	8/2009	Muto et al.	2012/0123385	A1	5/2012	Edwards et al.
2009/0254027	A1	10/2009	Moller	2012/0130318	A1	5/2012	Young
2009/0254035	A1	10/2009	Kohlbrenner et al.	2012/0130342	A1	5/2012	Cleathero
2009/0292240	A1	11/2009	KraMer et al.	2012/0136303	A1	5/2012	Cleathero
2009/0299278	A1	12/2009	Lesch, Jr. et al.	2012/0136318	A1	5/2012	Lanin et al.
2009/0304812	A1	12/2009	Staniforth et al.	2012/0143144	A1	6/2012	Young
2009/0312705	A1	12/2009	Grunhut et al.	2012/0157931	A1	6/2012	Nzike
2009/0318361	A1	12/2009	Noera et al.	2012/0157965	A1	6/2012	Wotton et al.
2010/0016326	A1	1/2010	Will	2012/0172809	A1	7/2012	Plumptre
2010/0036318	A1	2/2010	Raday et al.	2012/0172811	A1	7/2012	Enggaard et al.
2010/0049125	A1	2/2010	James et al.	2012/0172812	A1	7/2012	Plumptre et al.
2010/0069845	A1	3/2010	Marshall et al.	2012/0172813	A1	7/2012	Plumptre et al.
2010/0076378	A1	3/2010	Runfolo	2012/0172814	A1	7/2012	Plumptre et al.
2010/0076400	A1	3/2010	Wall	2012/0172815	A1	7/2012	Holmqvist
2010/0087847	A1	4/2010	Hong	2012/0172816	A1	7/2012	Boyd et al.
2010/0094214	A1	4/2010	Abry et al.	2012/0172818	A1	7/2012	Harms et al.
2010/0094324	A1	4/2010	Huang et al.	2012/0172885	A1	7/2012	Drapeau et al.
2010/0100039	A1	4/2010	Wyrick	2012/0179100	A1	7/2012	Sadowski et al.
2010/0114058	A1	5/2010	Weitzel et al.	2012/0179137	A1	7/2012	Bartlett et al.
2010/0121272	A1	5/2010	Marshall et al.	2012/0184900	A1	7/2012	Marshall et al.
2010/0137798	A1	6/2010	Streit et al.	2012/0184917	A1	7/2012	Bom et al.
2010/0152699	A1	6/2010	Ferrari et al.	2012/0184918	A1	7/2012	Bostrom
2010/0152702	A1	6/2010	Vigil et al.	2012/0186075	A1	7/2012	Edginton
2010/0160894	A1	6/2010	Julian et al.	2012/0191048	A1	7/2012	Eaton
2010/0168677	A1	7/2010	Gabriel et al.	2012/0191049	A1	7/2012	Harms et al.
2010/0174268	A1	7/2010	Wilmot et al.	2012/0197209	A1	8/2012	Bicknell et al.
2010/0191217	A1	7/2010	Hommann et al.	2012/0197213	A1	8/2012	Kohlbrenner et al.
2010/0204678	A1	8/2010	Imran	2012/0203184	A1	8/2012	Selz et al.
2010/0217105	A1	8/2010	Yodfat et al.	2012/0203185	A1	8/2012	Kristensen et al.
2010/0228193	A1	9/2010	Wyrick	2012/0203186	A1	8/2012	Vogt et al.
2010/0249746	A1	9/2010	Klein	2012/0209192	A1	8/2012	Alexandersson
2010/0256570	A1	10/2010	Maritan	2012/0209200	A1	8/2012	Jones et al.
2010/0258631	A1	10/2010	Rueblinger et al.	2012/0209210	A1	8/2012	Plumptre et al.
2010/0262082	A1	10/2010	Brooks et al.	2012/0209211	A1	8/2012	Plumptre et al.
2010/0262083	A1	10/2010	Grunhut et al.	2012/0209212	A1	8/2012	Plumptre et al.
2010/0268170	A1	10/2010	Carrel et al.	2012/0215162	A1	8/2012	Nielsen et al.
2010/0274198	A1	10/2010	Bechtold	2012/0215176	A1	8/2012	Veasey et al.
2010/0274273	A1	10/2010	Schraga et al.	2012/0220929	A1	8/2012	Nagel et al.
2010/0288593	A1	11/2010	Chiesa et al.	2012/0220941	A1	8/2012	Jones
2010/0292643	A1	11/2010	Wilmot et al.	2012/0220953	A1	8/2012	Holmqvist
2010/0292653	A1	11/2010	Maritan	2012/0220954	A1	8/2012	Cowe
2010/0298780	A1	11/2010	Laios	2012/0226226	A1	9/2012	Edwards et al.
2010/0312196	A1	12/2010	Hirschel et al.	2012/0230620	A1	9/2012	Holdgate et al.
2010/0318035	A1	12/2010	Edwards et al.	2012/0232517	A1	9/2012	Saiki
2010/0318037	A1	12/2010	Young et al.	2012/0245516	A1	9/2012	Tschirren et al.
2010/0324480	A1	12/2010	Chun	2012/0245532	A1	9/2012	Frantz et al.
2011/0021989	A1	1/2011	Janek et al.	2012/0253274	A1	10/2012	Karlsson et al.
2011/0034879	A1	2/2011	Crow	2012/0253287	A1	10/2012	Giambattista et al.
2011/0054414	A1	3/2011	Shang et al.	2012/0253288	A1	10/2012	Dasbach et al.
2011/0077599	A1	3/2011	Wozencroft	2012/0253289	A1	10/2012	Cleathero
2011/0087192	A1	4/2011	Uhland et al.	2012/0253290	A1	10/2012	Geertsen
2011/0098655	A1	4/2011	Jennings et al.	2012/0253314	A1	10/2012	Harish et al.
2011/0098656	A1	4/2011	Burnell et al.	2012/0259285	A1	10/2012	Schabbach et al.
2011/0125076	A1	5/2011	Kraft et al.	2012/0265153	A1	10/2012	Jugl et al.
2011/0125100	A1	5/2011	Schwartz et al.	2012/0267761	A1	10/2012	Kim et al.
2011/0137246	A1	6/2011	Cali et al.	2012/0271233	A1	10/2012	Bruggemann et al.
2011/0137247	A1	6/2011	Mesa et al.	2012/0271243	A1	10/2012	Plumptre et al.
2011/0144594	A1	6/2011	Sund et al.	2012/0277724	A1	11/2012	Larsen et al.
2011/0190725	A1	8/2011	Pettis et al.	2012/0283645	A1	11/2012	Veasey et al.
2011/0196300	A1	8/2011	Edwards et al.	2012/0283648	A1	11/2012	Veasey et al.
2011/0196311	A1	8/2011	Bicknell et al.	2012/0283649	A1	11/2012	Veasey et al.
				2012/0283650	A1	11/2012	MacDonald et al.
				2012/0283651	A1	11/2012	Veasey et al.
				2012/0283652	A1	11/2012	MacDonald et al.
				2012/0283654	A1	11/2012	MacDonald et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

			AU	2010233924	11/2011
			AU	2010239762	12/2011
			AU	2010242096	12/2011
			AU	2010254627	1/2012
			AU	2010260568	2/2012
			AU	2010260569	2/2012
			AU	2010287033	4/2012
			AU	2010303987	5/2012
			AU	2010332857	7/2012
			AU	2010332862	7/2012
			AU	2010337136	7/2012
			AU	2010338469	7/2012
			AU	2010314315	8/2012
			AU	2011212490	8/2012
			AU	2011212556	8/2012
			AU	2011212558	8/2012
			AU	2011212561	8/2012
			AU	2011212564	8/2012
			AU	2011212566	8/2012
			AU	2011212567	8/2012
			AU	2011214922	8/2012
			AU	2011221472	8/2012
			AU	2011231688	9/2012
			AU	2011231691	9/2012
			AU	2011224884	10/2012
			AU	2011231570	10/2012
			AU	2011231697	10/2012
			AU	2011233733	10/2012
			AU	2011234479	10/2012
			AU	2011238967	11/2012
			AU	2011244232	11/2012
			AU	2011244236	11/2012
			AU	2011244237	11/2012
			AU	2011249098	11/2012
			AU	2011262408	12/2012
			AU	2011270934	1/2013
			AU	2011273721	1/2013
			AU	2011273722	1/2013
			AU	2011273723	1/2013
			AU	2011273724	1/2013
			AU	2011273725	1/2013
			AU	2011273726	1/2013
			AU	2011273727	1/2013
			AU	2011273728	1/2013
			BR	0208013	3/2004
			BR	0308262	1/2005
			BR	PI712805	10/2012
			BR	PI0713802-4	11/2012
			BR	0214721	12/2012
			CA	2552177	7/1999
			CA	2689022	11/2002
			CA	2473371	7/2003
			CA	2557897	10/2005
			CA	02702412	12/2008
			CN	101094700	12/2007
			CN	101128231	2/2008
			CN	101184520	5/2008
			CN	101400394	4/2009
			CN	101405582	4/2009
			CN	101479000	7/2009
			CN	101511410	8/2009
			CN	101516421	8/2009
			CN	101557849	10/2009
			CN	101563123	10/2009
			CN	101563124	10/2009
			CN	101594898	12/2009
			CN	101600468	12/2009
			CN	101605569	12/2009
			CN	101610804	12/2009
			CN	101626796	1/2010
			CN	101678166	3/2010
			CN	101678172	3/2010
			CN	101678173	3/2010
			CN	101687078	3/2010
			CN	101687079	3/2010
			CN	101687080	3/2010
			CN	101715371	5/2010
			CN	101909673	12/2010
			CN	101912650	12/2010

FOREIGN PATENT DOCUMENTS

AU	2007253481	11/2007
AU	2007301890	4/2008
AU	2008231897	10/2008
AU	2008309660	4/2009
AU	2009217376	10/2009
AU	2009272992	1/2010
AU	2009299888	4/2010
AU	2009326132	8/2011
AU	2009326321	8/2011
AU	2009326322	8/2011
AU	2009326323	8/2011
AU	2009326324	8/2011
AU	2009326325	8/2011
AU	2009341040	9/2011

(56)

References Cited

FOREIGN PATENT DOCUMENTS

CN	101939034	1/2011	EP	1307012	5/2003
CN	101939036	1/2011	EP	1518575	3/2005
CN	102548599	7/2012	EP	1140260	8/2005
CN	102548601	7/2012	EP	1944050	7/2008
CN	102548602	7/2012	EP	2174682	4/2010
CN	102573955	7/2012	EP	2258424	12/2010
CN	102573958	7/2012	EP	2258425	12/2010
CN	102573960	7/2012	EP	02275158	1/2011
CN	102573963	7/2012	EP	2364742	9/2011
CN	102630172	8/2012	EP	2393062	12/2011
CN	102630173	8/2012	EP	2471564	7/2012
CN	102630174	8/2012	EP	02477681	7/2012
CN	102639170	8/2012	EP	02484395	8/2012
CN	102639171	8/2012	EP	2526987	11/2012
CN	102648014	8/2012	EP	02529773	12/2012
CN	102655899	9/2012	EP	02529774	12/2012
CN	102665800	9/2012	EP	02529775	12/2012
CN	102665802	9/2012	EP	2549789	1/2013
CN	102686255	9/2012	ES	02385630	7/2012
CN	102686256	9/2012	ES	2389866	11/2012
CN	102686258	9/2012	ES	2392667	12/2012
CN	102695531	9/2012	ES	02393173	12/2012
CN	102695532	9/2012	ES	2394556	2/2013
CN	102711878	10/2012	FR	2506161	11/1982
CN	102727965	10/2012	FR	2635009	2/1990
CN	102740907	10/2012	FR	6677523	8/1952
CN	102753222	10/2012	GB	1181037	2/1970
CN	102753223	10/2012	GB	1216813	12/1970
CN	102753224	10/2012	GB	2463034	3/2010
CN	102753227	10/2012	IL	171247	8/2012
CN	102770170	11/2012	IL	198750	10/2012
CN	102770173	11/2012	JP	10-507935	8/1998
CN	102781499	11/2012	JP	11-347121	12/1999
CN	102781500	11/2012	JP	2000-245839	9/2000
CN	102802699	11/2012	JP	2001-523485	11/2001
CN	102802702	11/2012	JP	5016490	5/2008
CN	102802703	11/2012	JP	5026411	11/2008
CN	102665801	12/2012	JP	5033792	11/2008
CN	102821801	12/2012	JP	5074397	2/2009
CN	102821802	12/2012	JP	2009-529395	8/2009
CN	102821805	12/2012	JP	5066177	9/2009
CN	102834133	12/2012	JP	5039135	11/2009
CN	102869399	1/2013	JP	5044625	12/2009
CN	102895718	1/2013	JP	2010-005414	1/2010
CN	102905613	1/2013	JP	2010-046507	3/2010
CN	102905742	1/2013	JP	4970282	7/2012
CN	102905743	1/2013	JP	4970286	7/2012
CN	102905744	1/2013	JP	4972147	7/2012
CN	102905745	1/2013	JP	4977209	7/2012
CN	102917738	2/2013	JP	4977252	7/2012
CN	102917743	2/2013	JP	4979686	7/2012
DE	102006041809	3/2008	JP	4982722	7/2012
DE	202011110155	12/2012	JP	2012515566	7/2012
DK	1646844	12/2009	JP	2012515585	7/2012
DK	2229201	7/2012	JP	2012515587	7/2012
DK	2023982	10/2012	JP	2012516168	7/2012
DK	2274032	10/2012	JP	2012516736	7/2012
DK	02346552	11/2012	JP	2012516737	7/2012
DK	1888148	1/2013	JP	4990151	8/2012
DK	2288400	1/2013	JP	4992147	8/2012
DK	2373361	1/2013	JP	4994370	8/2012
DK	1885414	2/2013	JP	5001001	8/2012
DK	2174682	2/2013	JP	2012143646	8/2012
DK	2310073	2/2013	JP	2012148198	8/2012
EG	25844	9/2012	JP	2012519508	8/2012
EP	0072057	2/1983	JP	2012519511	8/2012
EP	0103664	3/1984	JP	2012519514	8/2012
EP	1752174	3/1986	JP	2012176295	9/2012
EP	245895	11/1987	JP	2012183322	9/2012
EP	255044	2/1988	JP	2012520128	9/2012
EP	361668	4/1990	JP	2012521821	9/2012
EP	0518416	12/1992	JP	2012521825	9/2012
EP	525525	2/1993	JP	2012521826	9/2012
EP	1067823	1/2001	JP	2012521827	9/2012
EP	1161961	12/2001	JP	2012521828	9/2012
			JP	2012521828	9/2012
			JP	2012521828	9/2012
			JP	2012521828	9/2012
			JP	2012521829	9/2012
			JP	2012521830	9/2012
			JP	2012521831	9/2012
			JP	2012521834	9/2012

(56)

References Cited

FOREIGN PATENT DOCUMENTS			WO	WO	
			WO	91/13430	9/1991
			WO	92/19296	11/1992
			WO	94/09839	5/1994
			WO	94/11041	5/1994
			WO	95/29720	11/1995
			WO	95/29730	11/1995
			WO	96/21482	7/1996
			WO	97/14455	4/1997
			WO	97/21457	6/1997
			WO	97/41907	11/1997
			WO	97/48430	12/1997
			WO	98/31369	7/1998
			WO	98/32451	7/1998
			WO	9831369	7/1998
			WO	9832451	7/1998
			WO	99/03521	1/1999
			WO	99/10030	3/1999
			WO	99/22790	5/1999
			WO	9922789	5/1999
			WO	99/62525	12/1999
			WO	9962525	12/1999
			WO	0006228	2/2000
			WO	00/24441	5/2000
			WO	00/29050	5/2000
			WO	01/93926	12/2001
			WO	02/083216	10/2002
			WO	02/089805	11/2002
			WO	2089805	11/2002
			WO	03047663	6/2003
			WO	03/070296	8/2003
			WO	03068290	8/2003
			WO	03070296	8/2003
			WO	03/097133	11/2003
			WO	03097133	11/2003
			WO	2004/028598	4/2004
			WO	2004/041331	5/2004
			WO	2004/047892	6/2004
			WO	2004/108194	12/2004
			WO	2005/002653	1/2005
			WO	2005/005929	1/2005
			WO	2005/009515	2/2005
			WO	2005/053778	6/2005
			WO	2006/079064	7/2006
			WO	2006/086899	8/2006
			WO	2006/125328	11/2006
			WO	2006/130098	12/2006
			WO	2007/047200	4/2007
			WO	2007063342	6/2007
			WO	2007/063342	6/2007
			WO	2007/100899	9/2007
			WO	2007131013	11/2007
			WO	2006/079064	11/2007
			WO	2007/129106	11/2007
			WO	2007/131013	11/2007
			WO	2007/131025	11/2007
			WO	2007/143676	12/2007
			WO	2008/005315	1/2008
			WO	2008/009476	1/2008
			WO	2008/058666	5/2008
			WO	2008/071804	6/2008
			WO	2008089886	7/2008
			WO	2008/089886	7/2008
			WO	2008/100576	8/2008
			WO	2008/107378	9/2008
			WO	2008/112472	9/2008
			WO	2007/104636	12/2008
			WO	2009049885	4/2009
			WO	2009/114542	9/2009
			WO	2009/132778	11/2009
			WO	2009/141005	11/2009
			WO	2010/003569	1/2010
			WO	2010/043533	4/2010
			WO	2010/046394	4/2010
			WO	2010/097116	9/2010
			WO	2010/108116	9/2010
			WO	2011/023736	3/2011
			WO	2011/023882	3/2011
			WO	2011/035877	3/2011
			WO	2011/036133	3/2011
			WO	88/08724	11/1988
			WO	91/13299	9/1991

(56)

References Cited

FOREIGN PATENT DOCUMENTS		
WO	WO 2011/036134	3/2011
WO	WO 2011/039163	4/2011
WO	WO 2011/039201	4/2011
WO	WO 2011/039202	4/2011
WO	WO 2011/039207	4/2011
WO	WO 2011/039208	4/2011
WO	WO 2011/039209	4/2011
WO	WO 2011/039211	4/2011
WO	WO 2011/039216	4/2011
WO	WO 2011/039217	4/2011
WO	WO 2011/039218	4/2011
WO	WO 2011/039219	4/2011
WO	WO 2011/039228	4/2011
WO	WO 2011/039231	4/2011
WO	WO 2011/039232	4/2011
WO	WO 2011/039233	4/2011
WO	WO 2011/039236	4/2011
WO	WO 2011/040861	4/2011
WO	WO 2011/042537	4/2011
WO	WO 2011/042540	4/2011
WO	WO 2011/043714	4/2011
WO	WO 2011/045385	4/2011
WO	WO 2011/045386	4/2011
WO	WO 2011/045611	4/2011
WO	WO 2011/046756	4/2011
WO	WO 2011/048223	4/2011
WO	WO 2011/048422	4/2011
WO	WO 2011/050359	4/2011
WO	WO 2011/053225	5/2011
WO	WO 2011/054648	5/2011
WO	WO 2011/054775	5/2011
WO	WO 2011/056127	5/2011
WO	WO 2011/060087	5/2011
WO	WO 2011/067187	6/2011
WO	WO 2011/067268	6/2011
WO	WO 2011/067320	6/2011
WO	WO 2011/067615	6/2011
WO	WO 2011/068253	6/2011
WO	WO 2011/069936	6/2011
WO	WO 2011/073302	6/2011
WO	WO 2011/073307	6/2011
WO	WO 2011/076280	6/2011
WO	WO 2011/080092	7/2011
WO	WO 2011/081867	7/2011
WO	WO 2011/081885	7/2011
WO	WO 2011/089206	7/2011
WO	WO 2011/089207	7/2011
WO	WO 2011/095478	8/2011
WO	WO 2011/095480	8/2011
WO	WO 2011/095483	8/2011
WO	WO 2011/095486	8/2011
WO	WO 2011/095488	8/2011
WO	WO 2011/095489	8/2011
WO	WO 2011/095503	8/2011
WO	WO 2011/099918	8/2011
WO	WO 2011/101349	8/2011
WO	WO 2011/101351	8/2011
WO	WO 2011/101375	8/2011
WO	WO 2011/101376	8/2011
WO	WO 2011/101377	8/2011
WO	WO 2011/101378	8/2011
WO	WO 2011/101379	8/2011
WO	WO 2011/101380	8/2011
WO	WO 2011/101381	8/2011
WO	WO 2011/101382	8/2011
WO	WO 2011/101383	8/2011
WO	WO 2011/107805	9/2011
WO	WO 2011/109205	9/2011
WO	WO 2011/110464	9/2011
WO	WO 2011/110465	9/2011
WO	WO 2011/110466	9/2011
WO	WO 2011/111006	9/2011
WO	WO 2011/112136	9/2011
WO	WO 2011/113806	9/2011
WO	WO 2011/117212	9/2011

WO	WO 2011/117284	9/2011
WO	WO 2011/117404	9/2011
WO	WO 2011/121003	10/2011
WO	WO 2011/121061	10/2011
WO	WO 2011/123024	10/2011
WO	WO 2011/124634	10/2011
WO	WO 2011/126439	10/2011
WO	WO 2012020084	2/2012
WO	WO 2012022771	2/2012
WO	WO 2012/090186	7/2012
WO	WO 2011/051366	9/2012
WO	WO 2012/122643	9/2012

OTHER PUBLICATIONS

“Skin”, American Medical Association (AMA) Current Procedural Terminology, 1998, <http://www.ama-assn.org/ama/pub/category/print/7176.html>, 1 page.

Becks et al., “Comparison of Conventional Twice-Daily Subcutaneous Needle Injections to Multiple Jet Injections of Insulin in Insulin-Dependent Diabetes”, *Clinical and Investigative Medicine*, 1981, p. 33B.

Binder, “Absorption of Injected Insulin”, *ACTA Pharmacologica ET Toxicologica*, 1969, 27(Supp 2), 3 pages.

Bonetti et al., “An Extended-Release formulation of Methotrexate for Subcutaneous Administration”, *Cancer Chemotherapy Pharmacology*, 1994, 33, 303-306.

Braun et al., “Comparison of the Clinical Efficacy and Safety of Subcutaneous Versus Oral Administration of Methotrexate in Patients with Active Rheumatoid Arthritis”, *Arthritis and Rheumatism*, Jan. 2008, 58(1), pp. 73-81.

Chen et al., “Blood Lipid Profiles and Peripheral Blood Mononuclear Cell Cholesterol Metabolism Gene Expression in Patients with and Without Methotrexate” *BMC Medicine*, 2011, 9(4), 9 pages.

Chiasson et al., “Continuous Subcutaneous Insulin Infusion (Mill-Hill Infuser) Versus Multiple Injections (Medi-Jector) in the Treatment of Insulin-Dependent Diabetes Mellitus and the Effects of Metabolic Control on Microangiopathy” *Diabetes Care*, Jul.-Aug. 1984, 7(4), pp. 331-337.

Cohn et al., “Clinical Experience with Jet Insulin Injection in Diabetes Mellitus Therapy: A Clue to the Pathogenesis of Lipodystrophy”, *Ala. J. Med. Sci.*, 1974, 11(3), pp. 265-272.

Cowie et al., “Physical and Metabolic Characteristics of Persons with Diabetes”, *National Institutes of Health/National Institute of Diabetes and Digestive and Kidney Diseases*, 1995, 95(1468), pp. 117-120.

European Patent Application No. 03707823.5, Supplementary European Search Report, dated Mar. 30, 2005 with Communication dated Apr. 25, 2005 regarding Proceeding Further with the European Patent Application Pursuant to Article 96(1), and Rule 51(1) EPC, 3 pages.

European Patent Application No. 00976612.2, Communication Pursuant to Article 96(2) EPC, dated May 10, 2004, 5 pages.

Hingson et al., “A Survey of the Development of Jet Injection in Parenteral Therapy”, *Nov./Dec. 1952*, 31(6), pp. 361-366.

Hoekstra et al., Bioavailability of Higher Dose Methotrexate Comparing Oral and Subcutaneous Administration in Patients with Rheumatoid Arthritis, *The Journal of Rheumatology*, 2004, 31(4), pp. 645-648.

International Patent Application No. PCT/US2012/46742, International Search Report and Written Opinion dated Nov. 16, 2012, 11 pages.

International Patent Application No. PCT/US2009/052835, International Search Report dated Mar. 15, 2010, 5 pages.

International Patent Application No. PCT/US2013/029085, International Search Report dated May 13, 2013, 2 pages.

International Patent Application No. PCT/US2010/028011, International Search Report, dated Jun. 29, 2010, 5 pages.

International Patent Application No. PCT/US2009/036682, International Search Report, dated Jul. 7, 2009, 5 pages.

International Patent Application No. PCT/US2007/068010, International Search Report, dated Sep. 24, 2007, 3 pages.

(56)

References Cited

OTHER PUBLICATIONS

International Patent Application No. PCT/US03/03917, International Search Report, dated Nov. 26, 2003, 1 page.

Jansen et al., *Methotrexat Buiten de Kliniek*, Pharmaceutisch Weekblad, Nov. 1999, 134(46), pp. 1592-1596.

Japanese Patent Application No. 2007-552367, Office Action dated Apr. 9, 2011.

Katoulis et al., Efficacy of a New Needleless Insulin Delivery System Monitoring of Blood Glucose Fluctuations and Free Insulin Levels, *The International Journal of Artificial Organs*, 1989, 12(5), 333-339.

Kurnik et al., "Bioavailability of Oral vs. Subcutaneous low-dose Methotrexate in Patients with Crohn's Disease", *Aliment Pharmacol Ther.*, Apr. 2003, 18, pp. 57-63.

Malone et al., "Comparison of Insulin Levels After Injection by Jet Stream and Disposable Insulin Syringe", *Diabetes Care*, Nov.-Dec. 1986, 9(6), 637-640.

"The Historical Development of Jet Injection and Envisioned Uses in Mass Immunization and Mass Therapy Based Upon Two Decades' Experience", *Military Medicine*, Jun. 1963, 128, pp. 516-524.

Pehling et al., "Comparison of Plasma Insulin Profiles After Subcutaneous Administration of Insulin by Jet Spray and Conventional Needle Injection in Patients with Insulin-Dependent Diabetes Mellitus", *Mayo Clin. Proc.*, Nov. 1984, 59, pp. 751-754.

Reiss et al., "Atheroprotective Effects of Methotrexate on Reverse Cholesterol Transport Proteins and Foam Cell Transformation in Human THP-1 Monocyte/Macrophages", *Arthritis and Rheumatism*, Dec. 2008, 58(12), pp. 3675-3683.

Taylor et al., "Plasma Free Insulin Profiles After Administration of Insulin by Jet and Conventional Syringe Injection", *Diabetes Care*, May-Jun. 1981, 4(3), 337-339.

Weller et al., "Jet Injection of Insulin vs the Syringe-and-Needle Method", *JAMA*, Mar. 1966, 195(10), pp. 844-847.

Westlake et al., "The Effect of Methotrexate on Cardiovascular Disease in Patients with Rheumatoid Arthritis: A Systematic Literature Review", *Rheumatology*, Nov. 2009, 49, pp. 295-307.

Worth, "Jet Injection of Insulin: Comparison with Conventional Injection by Syringe and Needle", *British Medical Journal*, Sep. 1980, 281, pp. 713-714.

International Patent Application No. PCT/US2013/029085, Written Opinion, dated May 13, 2013, 5 pages.

International Patent Application No. PCT/US2010/028011, Written Opinion, dated Jun. 29, 2010, 5 pages.

Zachheim et al., "Subcutaneous Administration of Methotrexate", *Journal of the American Academy of Dermatology*, 1992, 26(6), p. 1008.

Halle et al., "Twice-Daily Mixed Regular and NPH Insulin Injections with New Jet Injector Versus Conventional Syringes: Pharmacokinetics of Insulin Absorption", *Diabetes Care*, May-Jun. 1986 9(3), pp. 279-282.

International Patent Application No. PCT/US2012/046639, International Search Report and Written Opinion dated Apr. 22, 2013, 8 pages.

Glynn-Barnhart et al., "Pharmacotherapy: The Journal of Human Pharmacology and Drug Therapy", 1992, 12(5), abstract only, 2 pages.

Hamilton et al., "Why Intramuscular Methotrexate May be More Efficacious Than Oral Dosing in Patients with Rheumatoid Arthritis", *British Journal of Rheumatology*, 1997, 36(1), pp. 86-90.

Stamp et al., "Effects of Changing from Oral to Subcutaneous Methotrexate on Red Blood Cell Methotrexate Polyglutamate Concentrations and Disease Activity in Patients with Rheumatoid Arthritis", *The Journal of Rheumatology*, 2011, 38(12), 2540-2547.

Tukova et al., "Methotrexate Bioavailability after Oral and Subcutaneous Administration in Children with Juvenile Idiopathic Arthritis", *Clinical and Experimental Rheumatology*, 2009, 27, 1047-1053.

Wright et al., "Stability of Methotrexate Injection in Prefilled Plastic Disposable Syringes", *International Journal of Pharmaceutics*, Aug. 1988, 45(3), 237-244.

Lunenfeld, "Stable Testosterone Levels Achieved with Subcutaneous Testosterone Injections", *The aging Male*, Mar. 2006, 9(1), 70 pages.

International Patent Application No. PCT/US14/23883, International Search Report, dated Jul. 10, 2014, 3 pages.

International Patent Application No. PCT/US14/23485, International Search Report, dated Jul. 7, 2014, 2 pages.

International Patent Application No. PCT/US14/24530, International Search Report, dated Jul. 15, 2014, 2 pages.

International Patent Application No. PCT/US14/24543, International Search Report, dated Jul. 28, 2014, 2 pages.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2A




FIG. 2B




FIG. 3

FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 6A





FIG. 6B






FIG. 7




FIG. 8A




FIG. 8B




FIG. 9A




FIG. 9B




FIG. 10A




FIG. 10B




FIG. 11A




FIG. 11B




FIG. 12A




FIG. 12B




FIG. 13A




FIG. 13B




FIG. 13C




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18

1

INJECTION DEVICE WITH CAMMED RAM ASSEMBLY

RELATED APPLICATION

This application is a continuation of pending U.S. application Ser. No. 13/184,229, filed Jul. 15, 2011, which is hereby incorporated by reference in its entirety. All patents, patent applications, and references cited anywhere in this specification are hereby incorporated by reference in their entirety.

FIELD OF THE DISCLOSURE

The present disclosure relates to injection devices, and in particular to a needle assisted jet injector.

BACKGROUND INFORMATION

Various injection devices exist that employ an automated mechanism to actuate injection of a liquid medicament into a patient. Examples of such devices include jet injectors (both needle-free and needle-assisted) and traditional, low-pressure auto-injectors (that provide, for example, mechanized delivery of a traditional, finger-powered hypodermic syringe injection). Although the precise mechanisms used to complete an injection can vary, most include a feature that stores kinetic energy that can be used to drive an injection mechanism during use. Further, many injectors include a trigger mechanism configured to ensure that the kinetic energy remains stored until an injection is desired, whereby actuation of the trigger releases the injection mechanism, allowing the stored kinetic energy to drive the injection mechanism to cause injection.

Examples of needle-free jet injectors are described, for example, in U.S. Pat. Nos. 5,599,302; 5,062,830; and 4,790,824. These injectors administer medication as a fine, high velocity jet delivered under sufficient pressure to enable the jet to pass through the skin. The injection mechanism in such needle-free jet injectors can apply a force to a medicament storing chamber within the device such that the pressure required to inject the medicament is created within the chamber.

Traditional self-injectors or auto-injectors like the ones described, for example, in U.S. Pat. Nos. 4,553,962 and 4,378,015 and PCT Publications WO/9929720 and WO/9714455 inject medicament at a rate and in a manner similar to hand-operated hypodermic syringes. The described self-injectors or auto-injectors have needles that are extended at the time of activation to penetrate the user's skin to deliver medicament through movement of the drug container and related needle. Thus, the mechanism that provides the force to deliver the medicament in traditional, low-pressure self-injectors and auto-injectors can also be used to extend the needle and displace the drug container to cause the insertion of the needle through the user's skin and to apply a force to a plunger movably disposed within the drug container to cause the medicament to be expelled from the container through the needle. The auto-injectors manufactured, for example by Owen Mumford, thus use very low pressures to inject the medicament, which is typically injected through a needle in a relatively slow stream. Another self-injector includes the Simponi injector, which includes a window in the housing through which a yellow ram is visible inside a clear medicament container once the injector has been used.

2

Additionally, needle-assisted jet injectors have also been developed that utilize a needle to initially penetrate the skin, to the higher injection forces allowing but not restricted to an insertion depth less than that of a traditional hypodermic injector or low-pressure auto-injectors. Once the skin is penetrated with the needle, a jet mechanism is activated, causing the medicament containing liquid within the injector to be pressurized and expelled through the needle and into the skin. The injection mechanism in needle-assisted jet injectors can be configured to move the drug container and the needle forward to penetrate the skin and exert the necessary injection force to a plunger moveably disposed within the container. Alternatively, the needle and drug container can be positioned to penetrate the skin while keeping the needle and drug container in a stationary position, and the injection mechanism can be structured to pressurize the container. The pressure applied to the medicament within the injector can be less than that of a traditional jet injector, because the outer layers of the skin have already been penetrated by the needle. Similarly, the pressure applied to the medicament is preferably higher than that of a traditional auto-injector or the like, causing the medicament to penetrate the skin or the tissue below the skin to a depth that is sufficient so that the medicament remains substantially within the body. An additional benefit of the higher pressure includes a faster time of injection resulting in less psychological trauma to the patient and a decreased likelihood of the user inadvertently terminating the injection prematurely by removing the injector from the injection site.

Because of the stored energy associated with the trigger and injection mechanisms, accidental firing can occur due to sudden movements during shipping or due to mishandling of the device by a user including accidental actuation of the trigger mechanism. Accidental firing of the injection mechanism can cause the medicament to be expelled from the device, which can be at a dangerously high pressure, depending on the type of injection device. Further, accidental firing can cause an injection needle to move forward with respect to the device with sufficient force to penetrate the skin.

Additionally, the dimensions of many components incorporated in injectors typically constrain the design of many injectors. For example, many injectors utilize front triggering mechanisms that typically require an axial translation and engagement with a triggering structure located at the back of the injector. However, this configuration typically prevents binding of the communicating triggering components, which can be advantageous for, e.g., reducing the size of the injection device, being able to view the drug container within the device, etc.

SUMMARY

Exemplary embodiments of the present disclosure are directed to injection devices. An exemplary embodiment of the present disclosure can provide an injector including a trigger mechanism, an energy source, and a user-operable firing-initiation member. The trigger member can include a trigger member having a retainer portion, and a ram assembly having a ram configured to pressurize a medicament container for expelling a medicament therefrom and a trigger engagement member configured to engage the retainer portion of the trigger member in a pre-firing condition. The energy source can be associated with the ram for powering the ram to expel the medicament, and the user-operable firing-initiation member can be operable for causing an axial rotation between the trigger engagement member and the

retainer portion from the pre-firing condition to a firing condition in which the trigger engagement member is released from the retainer portion to allow the energy source to fire the ram. The exemplary injector can further include an injection housing, where the trigger engagement member and the ram are in fixed association, such that rotation of the trigger engagement member rotates the ram, and the ram assembly is associated with the firing-initiation member such that operation of the firing-initiation member rotates the ram assembly within the housing to the firing condition.

The exemplary injector can further include an injector housing. The firing initiation member can also include a skin-contacting member disposed at a distal end of the injector that is movable proximally with respect to the housing when a force is applied to the skin-contacting member at the distal end of the injector. Further, the firing initiation member can be associated with the trigger mechanism and configured to cause the axial rotation between the trigger engagement member and the retainer portion from the pre-firing condition to the firing condition upon a proximal movement of the skin-contacting member with respect to housing. Additionally, the skin-contacting member can include a needle guard that is retractable and is configured to expose a needle connected to the medicament container upon the proximal movement of the skin-contacting member.

According to another exemplary embodiment of the present disclosure, the needle can be in fluid communication with the medicament container for injecting the medicament expelled therefrom during the firing. Further, the energy source and the needle can be configured for jet injecting the medicament through the needle. The energy source can be configured to pressurize the medicament to between about 90 p.s.i. and about 500 p.s.i. to jet inject the medicament, and the energy source and needle can be configured for injecting the medicament at an average velocity of at least about 1,000 cm/sec within the needle.

According to another exemplary embodiment of the present disclosure, the skin contacting member can include a first cam, and the ram assembly can include a second cam. The first cam can be operatively associated with the second cam for camming the second cam upon the axial movement to rotate the ram assembly with respect to the retainer portion so as to position the ram assembly in the firing condition. The trigger mechanism can include a ram holding member that axially retains the ram assembly in a proximal position against action of the energy source in the pre-firing position, the retainer portion retaining the trigger engagement member engaged and held against firing by the ram holding member. Additionally, in the firing condition, the ram can be disengaged from the retainer portion, and the energy source overcomes an engagement between the trigger engagement member and the ram holding member. Further, the ram holding member can include a projection that includes a bulge and a groove engaged with the trigger engagement member, and the retainer portion retaining said engagement of the trigger engagement member with the bulge and groove, in the pre-firing condition.

According to certain exemplary embodiments of the present disclosure, the ram assembly can be of unitary construction.

According to yet another exemplary embodiment of the present disclosure, the injector can further include a container support that is configured for holding the medicament container during injection, and wherein the ram assembly is configured to engage the container support to lock-out the injector after an injection. Further, proximal movement of

the user-operable firing-initiation member can be blocked by the ram assembly when the injector is locked-out.

According to yet another exemplary embodiment of the present disclosure, a pre-firing color gamut is visible from the exterior of the injector in the pre-firing condition. Further, the injector can further include a housing including a window; and an indicator having an indicator color that is absent from the pre-firing color gamut, which color is hidden from view within the housing in the pre-fired condition, and in the fired condition, the indicator color is visible through the window from the exterior of the injector for indicating the fired condition. In certain embodiments, the ram assembly can include the indicator, and the ram assembly can entirely occlude the window in the fired condition.

Yet another exemplary embodiment of the present disclosure can provide an injector including a trigger mechanism having a trigger member having a retainer portion, and a ram assembly having a ram configured to pressurize a medicament container for expelling a medicament therefrom and at least one first camming surface. The ram assembly can further include a trigger engagement member configured to engage the retainer portion of the trigger member in a pre-firing condition. The injector can further include an energy source associated with the ram for powering the ram to expel the medicament, and a needle guard including a user-operable firing-initiation member operable having at least one second camming surface configured to operatively associate with the at least one first camming surface so as to cause an axial rotation between the trigger engagement member and the retainer portion from the pre-firing condition to a firing condition in which the trigger engagement member is released from the retainer portion to allow the energy source to fire the ram. The injector can further include a container support, and the ram assembly can be configured to engage the container support to lock-out the injector after an injection.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects, features and advantages of the invention will be apparent from a consideration of the following non-limiting detailed description considered in conjunction with the drawing figures, in which:

FIG. 1A is a side view of an exemplary injection device according to an exemplary embodiment of the present disclosure;

FIG. 1B is a cross-sectional view of an exemplary injection device according to an exemplary embodiment of the present disclosure;

FIG. 1C is a side view of a housing of an exemplary injection device according to an exemplary embodiment of the present disclosure;

FIG. 2A is a perspective view of a proximal portion of an exemplary injection device according to an exemplary embodiment of the present disclosure;

FIG. 2B is another perspective view of a proximal portion of an exemplary injection device according to an exemplary embodiment of the present disclosure;

FIG. 3 is a side view of an end housing portion of an exemplary injection device according to an exemplary embodiment of the present disclosure;

FIGS. 4A and 4B are side and perspective views of a front housing portion and a sleeve of an exemplary injection device according to an exemplary embodiment of the present disclosure;

5

FIGS. 5A and 5B are side and perspective views of a needle guard of an exemplary injection device according to an exemplary embodiment of the present disclosure;

FIGS. 6A and 6B are side and perspective views of a ram assembly of an exemplary injection device according to an exemplary embodiment of the present disclosure;

FIG. 7 is an exploded view of an exemplary injection device according to an exemplary embodiment of the present disclosure;

FIGS. 8A-13C are side, cross-sectional, and internal views of an operation of an exemplary injection device according to an exemplary embodiment of the present disclosure;

FIG. 14 shows a cross sectional view of a cap of an exemplary injection device according to an exemplary embodiment of the present disclosure;

FIG. 15 shows a close-up view of an engagement of a trigger engagement member and a ram retaining member of an exemplary injection device according to an exemplary embodiment of the present disclosure;

FIG. 16 shows a side view of an exemplary injection device according to an exemplary embodiment of the present disclosure;

FIG. 17 shows a top view of a ram assembly of an exemplary injection device according to an exemplary embodiment of the present disclosure; and

FIG. 18 shows a cut-away perspective view of a proximal portion of an exemplary injection device according to another embodiment of the present disclosure.

Throughout the drawings, the same reference numerals and characters, unless otherwise stated, are used to denote like features, elements, components, or portions of the illustrated embodiments. Moreover, while the present disclosure will now be described in detail with reference to the figures, it is done so in connection with the illustrative embodiments and is not limited by the particular embodiments illustrated in the figures.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

FIG. 1A shows an exemplary injection device 100 according to an exemplary embodiment of the present disclosure. It is noted that, in the context of this disclosure, the terms “distal” and “proximal” are used in reference to the position of the injection device relative to a user of the injection device when merely held by a user. Accordingly, a point located distal to a second point would be further from the user (i.e., towards an injection end of the injection device) and vice versa. As shown in the drawings, the exemplary injection device 100 is preferably a needle assisted jet injection device, although a person having ordinary skill in the art will understand alternative embodiments employing certain features herein can be configured as needle-free jet injectors, or as low-pressure auto-injectors or other mechanized injectors. According to certain exemplary embodiments, injection device 100 can be a one-time disposable needle-assisted jet injector with a lock-out feature. For example, injection device 100 can facilitate a jet injection of medicament stored within injection device 100 and can include a locking feature that prevents a user from attempting to use injection device 100 once the medicament has been dispensed. Preferably, the locking feature is activated upon dispensing of the medicament and not upon use of injection device 100. For example, the locking feature can be activated, thus preventing injection device 100 from a subsequent attempted use by a user, even in the case where

6

the injection device was not used by a user for an injection, but where a firing mechanism was inadvertently activated (e.g., during transport, handling, etc. of the device) and the medicament was dispensed. Operation of injection device 100, including the locking feature, is described in further detail below.

According to certain exemplary embodiments, injection device 100 can deliver any suitable liquid drug or medicament. Further, injection device 100 can enable allow the injection to be administered by individuals that do not have formal training (e.g., self-administered or administered by another individual family member or other caregiver who may not be a formally trained healthcare provider, such as a parent administering a drug to a child). Accordingly, injection device 100 can be useful in situations where self-injections/caregiver administered injections would be beneficial, including, but not limited to, diabetes, infertility treatment, sexual dysfunction, cardiovascular disease, oncology supportive care, allergic reaction, multiple sclerosis, rheumatoid arthritis, psoriasis, other autoimmune conditions including Crohn's disease and SLE, chronic pain, migraine, epileptic seizure, kidney disease, and the like. Further, injection device 100 can be used to inject a wide range of drugs. For example, injection device 100 can be used to inject drugs dissolved in oil instead of aqueous solutions, including hormone drugs used in men and women; small molecule injectable drugs such as, methotrexate (see, e.g., International Publication No. WO 2010/108116, which is incorporated by reference herein in its entirety); and/or biological drugs, including those having a high viscosity. While injection device 100 can deliver an injection of up to approximately 1 mL per injection, other volumes can be injected in alternative embodiments.

According to certain exemplary embodiments, injection device 100 can be configured to inject medicament stored within a prefilled syringe. Prefilled syringes that are manufactured by a blown glass process can have significant dimensional tolerances and unevenness. Accordingly, features of injection device 100 can serve to accommodate the shape irregularities and to properly position and locate a prefilled syringe within injection device 100. Further, injection device 100 can be configured as a needle-assisted jet injector, providing a peak pressure during the injection of less than about 1,000 p.s.i., preferably less than 500 p.s.i., and more preferably less than about 350 p.s.i. At an end of an injection, the pressure applied to the medicament is preferably at least about 80 p.s.i., more preferably at least about 90 p.s.i., and most preferably at least about 100 p.s.i. In one embodiment, the initial pressure can be around 330 p.s.i., and the final pressure can be about 180 p.s.i., while in another embodiment the initial pressure can be about 300 p.s.i., dropping to around 110 p.s.i. at the end of the injection. These exemplary pressures can, for example, result in a flow rate of about 0.2 mL/sec to 0.75 mL/sec, and preferably about 0.5 mL/sec. The needles used are preferably between 26 and 28 gauge, and are most preferably around 27 gauge, but alternatively other needle gauges can be used where the other components are cooperatively configured to produce the desired injection. In preferred jet injector embodiments firing aqueous medicaments, the firing mechanism, medicament container, needle, and energy source are configured to produce an average stream velocity within the needle of at least about 1,000 cm/sec, and more preferably at least about 1,500 cm/sec, up to about 5,000 cm/sec, and more preferable up to about 3,000 cm/sec. In one embodiment, the average stream velocity during injection is about or reaches between about 1,800 and 2,200

cm/sec or approximately 2,000 cm/sec. The velocities used to produce a jet injection will vary for other types of medicaments, such as based on their viscosities. Weaker energy sources, and/or larger needles, for example, can be used to obtain lower velocities and lower pressures and/or flow rates for traditional, low-pressure autoinjector embodiments. Such embodiments can also benefit from the axial rotation between the trigger engagement member and the retainer portion, while moving from the pre-firing condition to the firing condition upon a proximal movement of the skin-contacting member with respect to housing.

As shown in FIG. 1B, the exemplary injection device 100 can include an outer housing 102, a cap 104, and a housing end/end cap 106. Injection device 100 can further include various components and/or assemblies housed within outer housing 102. As shown in FIG. 1B, these components can include a guard 108, a container support, such as, e.g., a sleeve 110, a firing mechanism 112, a medicament chamber 114, a needle 116, and a spring 118. As shown in FIG. 1A, outer housing 102 can be a single piece component, or alternatively, outer housing 102 multiple piece assembly that can be coupled together, for example, via a snap-fit connection, a press-fit connection, a threaded engagement, adhesives, welding, or the like.

As shown in FIG. 1B, cap 104 is removably affixable to a distal end of outer housing 102, and housing end/end cap 106 is coupled to a proximal end of housing 102. For example, cap 104 can be removably affixed to the distal end of housing 102 via a threaded engagement and housing end 106 can include features (e.g., projections) configured to engage a portion of the proximal end of housing 102 (e.g., openings) to couple housing end/end cap 106 to housing 102. When affixed to injection device 100, cap 104 can ensure that an injection is not triggered by an inadvertent application of a force to guard 108. Preferably, cap 104 includes two engagement features. As shown in FIG. 14, cap 104 can include engagement features 1040 and 1042. Engagement features 1040 and 1042 can be threads configured to threadedly engage other features of injection device 100. For example, engagement feature 1040 can be configured secure cap 104 to the distal end of housing 102 (e.g., via a threaded engagement with a distal portion of sleeve 110), and engagement feature 1042 can be configured to threadedly engage features of guard 108 to prevent proximal displacement of guard 108. For example, FIG. 1B shows feature 1042 engaged with feature 1080a of guard 108, thereby preventing proximal movement of guard 108, such as may occur if the injector is accidentally dropped or otherwise jolted.

Additionally, cap 104 is preferably non-circular in cross-section viewed along its axis and in the initial, closed position aligns with or substantially matches the shape of the portion of the housing adjacent thereto. Features 1040 can include a plurality of threads, having more than one thread starting point, only one of which will result in the cap lining up with the housing as in the initial closed position. Consequently, if the cap is removed and replaced, there is a chance that an incorrect starting point will be selected by the user, resulting in the cap no longer aligning with the injector housing, and providing an indication of tampering. In one embodiment, three threads are used, so there is a two in three chance that a removed and replaced cap will become immediately obvious based on an ill-fitting cap.

As shown in FIG. 1A, housing 102 can include openings 1024 configured to engage with sleeve 110 to couple and secure sleeve 110 to housing 102 and can include at least one window 1020 that can provide a visual indication of whether

or not injection device 100 has been fired. For example, in an unfired state, window 1020 can allow a user to see medicament chamber 114, along with the stored medicament, and in a fired state, window 1020 can show one or more internal components, such as a portion of firing mechanism 112, which can be a color specifically selected to alert the user that injection device 100 has been fired, and is preferably sufficiently different than other colors visible to a user (preferably having ordinary eyesight) on the injector prior to firing, so as to be conspicuously different to, or contrast from, any other colors present or significantly present. For example, the color can differ from all the other components of injection device 100 pre-firing, or visible by the user pre-firing, so as to be conspicuous (e.g., introducing an entirely new color family). The new color appearing after firing, can be from a non-analogous part of the color wheel, or can contrast, or can be a complementary color, with respect to the colors visible on injection device 100. The new color can signify caution, such as red or orange, etc. In one embodiment, the colors visible on the injector in the pre-firing condition, preferably including when the cap 104 is on and/or off the injector, are grays and blues, for instance. When the injector is fired, the color red can be introduced. Preferably, this new color can be introduced after firing but prior to guard 108 being locked-out in the extended position.

A proximal end of housing 102 can also include a trigger member, which can include a trigger member retaining portion 1022. For example, trigger member retaining portion 1022 can include an opening configured to receive and engage at least a trigger engagement member of firing mechanism 112 (e.g., projections) in facilitating firing of injection device 100. Opening 1022 is preferably configured to engage a trigger engagement member, e.g., projections 1134 of firing mechanism 112, for example latch tabs, such that they are aligned in one of two positions. For example, in first position 1022a (e.g., retaining position), the opening can include retaining portions so that projections 1134 of firing mechanism 112 are aligned so that they can be restrained by lateral sides of opening 1022, thereby preventing firing mechanism 112 from firing (e.g., by preventing projections 1134 from splaying open firing mechanism 112 is prevented from slidably displacing under a force exerted by an energy source) and dispensing the medicament. In second position 1022b (e.g., firing position), the opening can include firing portions such that the projections of firing mechanism 112 are aligned such that projections can splay apart, thereby permitting firing mechanism 112 to fire. FIG. 2B shows projections 1134 aligned in the first position (1022a) and FIG. 2C shows projections 1134 aligned in the second position (1022b). Further, the lateral walls of the retaining portions of the opening (e.g., in the first position 1022a) are preferably curved to facilitate rotation of projections 1134 between the first and second positions.

Injection device 100 also preferably includes housing end/end cap 106. As shown in FIG. 3, housing end/end cap 106 preferably includes a body portion 1060 and a ram holding member 1062. Ram holding member 1062 can be a projection, and can be configured to engage a trigger engagement member of firing mechanism 112. For example, ram holding member 1062 can be a bell-shaped projection, and can engage a complementary shaped feature (e.g., projections) of firing mechanism 112. In an exemplary embodiment, ram holding member 1062 can include a groove 1062a and a bulge 1062b, and features of firing mechanism 112 can be configured to align with groove 1062a so as to hold bulge 1062b to prevent firing of injection device 100. Preferably, ram holding member 1062 and the

features of firing mechanism 112 engaging with ram holding member 1062 include a circular cross section to allow rotation of the features of firing mechanism 112 relative to ram holding member 1062 during firing of injection device 100. Further, body portion 1060 can include projections 1060a configured to engage openings in outer housing 102 to couple housing end/end cap 106 to housing 102. In an exemplary embodiment,

As shown in FIG. 1B, sleeve 110 is preferably at least partially housed within outer housing 102 and mounted to outer housing 102 via, for example, a snap-fit connection, a press-fit connection, a threaded engagement, adhesives, welding, or the like. As shown in FIGS. 4A and 4B, for example, sleeve 110 can include projections 1108 configured to engage openings 1024 of housing 102. Sleeve 110 is configured to hold a medicament chamber 114, which can include a needle 116 at a distal end of medicament chamber 114. In certain exemplary embodiments, medicament chamber 114 can include, for example, a separate glass ampule and a needle, or a pre-filled syringe, or sleeve 110 itself can include an integral medicament chamber. Preferably, a plunger 1140 is provided in the medicament chamber 114. Plunger 1140 is in association with a ram 1132 of firing mechanism 112. During an injection, ram 1132 is urged by an energy source of firing mechanism 112 to displace plunger 1140 distal, deeper into medicament chamber 114, dispensing the medicament through needle 116. Needle 116 can include an injecting tip 1160 that can be configured to penetrate the skin of a user and a hollow bore that is in fluid communication with medicament chamber 114 to facilitate delivery of medicament from medicament chamber 114 to a user during an injection. FIGS. 1A and 1B show injection device 100 in a pre-firing state, with cap 104 secured to outer housing 102 and injection device 100 in a pre-firing position. The operation of injection device 100, including its various stages and positions, are described in further detail below.

As shown in FIGS. 4A and 4B, sleeve 110 can include a ring-like structure 1100, a coupling arrangement 1102, and a body portion 1104. Coupling arrangement 1102 can be disposed at a distal portion of sleeve 110 and can be configured to releasably engage cap 104. For example, coupling arrangement 1102 can include threads configured to provide threaded engagement between sleeve 110 and cap 104. Further, sleeve 110 can include a body portion 1104 configured to secure medicament chamber 114. Body portion 1104 can include guides, such as grooves 1104a, configured to engage with features of guard 108 to align and guide axial displacement of guard 108. A proximal end of sleeve 110 can include a medicament chamber support 1106 configured to support and secure a proximal portion of medicament chamber 114. For example, support 1106 can be configured as a syringe support configured to hold a proximal end of syringe (e.g., finger flanges of a prefilled syringe) and can support medicament chamber 114 during the forces exerted on it during firing. Further, support 1106 can include an elastomer or a rubber, and can be configured to at least partially absorb the shock or a force exerted on medicament chamber 114 during an injection. Additionally, sleeve 110 can include various features, such as projections 1108, configured to couple sleeve 110 to outer housing 102. For example, projections 1108 can be concentrically symmetrical and configured to engage openings 1024 in outer housing 102 to secure sleeve 110 to outer housing 102. In an exemplary embodiment, projections 1108 can be disposed on legs 1110, which can be concentrically symmetrical and configured to engage with features of guard 108. Additionally, sleeve 110 can include locking features, such as locking

projections 1112, disposed on legs 1114, which can be concentrically symmetrical, and can be configured to engage firing mechanism 112 in locking out injection device 100 to prevent a user from attempting to use an already-fired injection device 100.

Ring-like structure 1100 can include several features configured to engage sleeve 110 with glass medicament chamber 114, firing mechanism 112, and guard 108. For example, ring-like structure 1100 can include an opening 1116 through which needle 116 can be received. Further, ring-like structure 1100 can include concentrically symmetrical openings 1118 which can be configured to receive legs of guard 108. Additionally, ring-like structure 1100 can be configured to support a distal portion of medicament chamber 114 and engage firing mechanism 112 in preventing further axial displacement of firing mechanism 112 during dispensing of the medicament. Operation of these components are described in further detail below.

As shown in FIGS. 5A and 5B, injection device 100 preferably includes a guard 108 slidably mounted at least partially within outer housing 102 and configured to engage firing mechanism 112 to actuate firing of injection device 100. Preferably, guard 108 is slidably movable relative to outer housing 102 between an extended (e.g., a distal, protective) position and a retracted (e.g., proximal) position. In the extended position, guard 108 preferably covers needle 116, and in the retracted position, needle 116 is not covered by guard 108 and is thereby exposed. For example, FIG. 9A shows guard 108 in the extended position, and FIG. 10A shows guard 108 in the retracted position. Preferably, guard 108 is resiliently biased toward the extended position via a spring 118, which can be disposed, for example, between a distal surface of ring-like structure 1100 of sleeve 110 and an interior surface of a distal end of guard 108.

In an exemplary embodiment, guard 108 includes a distal portion 1080 and legs 1082. In an exemplary embodiment, the distal end of guard 108 preferably includes a skin-contacting member. Distal portion 1080 includes an opening through which needle 116 can pass and projections 1080a. Projections 1080a can be configured to abut a distal edge of sleeve 110 so as to limit the proximal displacement of guard 108. For example, as guard 108 is proximally displaced under a force applied by a user during an injection, projections 1080a will come into contact with the proximal edge of sleeve 110 so that guard 108 cannot be further proximally displaced. Further, projection 1080a can be configured to engage engagement feature 1042 of cap 104 so that guard 108 cannot be proximally displaced when engaged with engagement feature 1042 of cap 104.

Legs 1082 of guard 108 are preferably configured to be received in openings 1118 of ring-like structure 1100. Further, legs 1082 can include ridges 1082a configured to engage grooves 1104a of sleeve 110, to facilitate alignment and guiding of legs 1082 as guard 108 is axially displaced. As shown in the exemplary embodiments of FIGS. 5A and 5B, legs 1082 also preferably include firing-initiation members, such as camming surfaces 1084 at a proximal end of legs 1082. In an exemplary embodiment, legs 1082 and camming surface 1084 can be concentrically symmetrical. Camming surfaces 1084 are configured to engage firing mechanism 112 in initiating a firing of injection device 100 and performing an injection of the medicament stored in medicament chamber 114. The proximal ends of legs 1082 can also be sloped to facilitate legs 1082 being received within firing mechanism 112 when guard 108 is displaced from the extended position to the retracted position. Preferably, legs 1082 include projections 1086 disposed on

11

springs **1088** which can also include sloped surfaces **1088a**. Projections **1086** can be configured to engage proximal surfaces of legs **1110** of sleeve **110** to oppose a force exerted by spring **118**, which biases guard **108** in the extended position. Further, sloped surfaces **1088a** can be configured to engage an interior surface of legs **1110** of sleeve **110** so that as guard **108** is displaced from the extended position to the retracted position, sloped surfaces **1088a** engage the interior surfaces of legs **1110** so as to bias springs **1088** towards an interior of injection device **100**.

As shown in FIG. 1B, injection device **100** also preferably includes firing mechanism **112**. Firing mechanism **112** can include a ram assembly **1120** slidably mounted within housing **102** and an energy source **1122**. In an exemplary embodiment, the energy source **1122** preferably includes a compression spring **1122**, however, other suitable energy source can be used, such as an elastomer or compressed-gas spring, or a gas generator, or other suitable energy storage members. In FIG. 1A, ram assembly **1120** is in a pre-firing proximal-most position. During an injection, ram assembly **1120** is urged distally by energy released by energy source **1122**. Once an injection is completed, firing ram assembly **1120** is disposed in a distal position (as shown in FIG. 12B). In this distal position, guard **108** is locked-out so that a user cannot attempt a subsequent injection. Although shown as a single piece, ram assembly **1120** can be a multiple piece assembly that can be coupled together, for example, via a snap-fit connection, a press-fit connection, a threaded engagement, adhesives, welding, or other suitable couplings. Ram assembly **1120** preferable includes various features that can be configured to facilitate firing of injection device **100** to dispense the medicament stored in medicament chamber **114**. According to certain exemplary embodiments of the present disclosure, a trigger mechanism of injection device **100** can include ram assembly **1120**, the trigger member and trigger retaining portion **1022**, and ram retaining holding member **1060**.

In an exemplary embodiment, ram assembly **1120** can include a distal portion **1124** and a proximal portion **1126** separated by a feature **1138**, such as a lip, a ledge, that can be configured to act as a seat for energy source **1122**. In an exemplary embodiment, compression spring **1122** can be disposed between a proximal end of housing **102** and feature **1138**. Distal portion **1124** can be substantially cylindrical and can be configured to concentrically receive at least a portion of sleeve **110** and guard **108**. Distal portion **1124** can also include openings **1128** configured to receive legs **1110** of sleeve **110** and projection **1086** of guard **108**. An interior surface of distal portion **1124** can include camming surfaces **1124a** configured to engage camming surfaces **1084** of guard **108**. FIG. 16 shows engagement of camming surfaces **1124a** with camming surfaces **1084** of guard **108** in a pre-fired state. As guard **108** is moved in the direction A during an injection, the axial movement of guard **108** is translated into a rotational movement of ram assembly **1120** via the engagement of camming surfaces **1124a** and **1084**.

Proximal portion **1126** preferably includes legs **1130**, a ram **1132**, and a trigger engagement member, such as, e.g., projections **1134**. Although the trigger engagement member is shown as projections **1134**, alternative implementations are contemplated. The trigger engagement member can include any feature (e.g., an elongated tab, a recess, a protrusion, a bulge, a thread, etc.) that can be held by ram retaining member in the pre-firing state, and released upon rotation of the trigger engagement member. For example, the ram retaining member can be shaped such that it prevents axial movement of the trigger engagement member in a first

12

position, but releases trigger engagement member in a rotationally translated second position. Camming surfaces **1124a** and **1084** are preferably oriented at an angle with respect to the longitudinal axis of the device to achieve a selected force and throw required to depress the guard **108** from the extended to the retracted position to fire the device. In some embodiments, the camming surfaces are angled at between 15° and 75° with respect to the axis, and more preferably between about 20° and 45°. In one embodiment, the camming surfaces are angled at about 30° with respect to the axis.

As shown in FIGS. 6A and 6B, legs **1130** include openings **1136** configured to engage locking projections **1112** of sleeve **110**. For example, locking projections **1112** of sleeve **110** can engage openings **1136** of firing mechanism **112** after injection device **100** has been fired, locking-out injection device **100** so that a user cannot initiate another firing of injection device **100**. Ram **1132** is configured to be in association with plunger **1140**, and distally displace plunger **1140** under the force of energy source **1122** to dispense the medicament contained in medicament chamber **114** during an injection. Additionally, projections **1134** can be disposed at a proximal end of proximal portion **1126** and can be configured to engage opening **1022** of housing **102** and ram holding member **1062** of housing end/end cap **106**. The engagement of projections **1134** with opening **1022** and ram holding member **1062**, as well as the alignment of projections **1134** within opening **1022** can control and enable firing of injection device **100**. For example, projections **1134** can include bulges **1134a** configured to engage groove **1062a** of ram holding member **1062**, and shapes **1134b** configured to engage bulge **1062b** of ram holding member **1062**. As noted above, projections **1134** and ram holding member **1062** preferably include circular cross-sections to allow rotation of ram assembly **1120** during firing of injection device **100**. FIG. 15 shows a closeup view of the engagement of trigger engagement member (e.g., projections **1134**) with ram holding member **1062**.

FIGS. 8A-12B show the various stages and states of exemplary injection device **100**. FIGS. 8A and 8B show injection device **100** in a pre-firing “safeties-on” configuration. For example, in the pre-firing “safeties-on” configuration, injection device **100** is in a pre-firing state and cap **104** is affixed to injection device **100**. In this configuration, guard **108** is in the extended position under force of spring **118** covering needle **116**, ram assembly **1120** is in its proximal position, and energy source **1122** has not released its energy. Further, in this state, projections **1134** of ram assembly **1120** are engaged with opening **1022** and aligned in the first position **1022a** (e.g., pre-firing condition) of opening **1022**. Further, projection **1134** are also engaged with ram holding member **1062** of housing end/end cap **106**. In this position, the engagement of projections **1134** with ram holding member **1062** of housing end/end cap **106** oppose the force of energy source **1122**. Further, with projections **1134** aligned within the first position **1022a** of opening **1022**, the lateral sides of opening **1022** (formed by the proximal end of housing **102**) prevent projections **1134** from splaying open and disengaging ram holding member **1062** under the force of energy source **1122**.

In FIGS. 9A and 9B, injection device **100** is shown in a pre-firing “ready-to-use” state. FIG. 13A shows many of the internal components of injection device **100** in this pre-firing “ready-to-use” state without showing housing **102**. For example, safety member **104** has been removed, but the user has not otherwise initiated an injection. Accordingly, in this state, the medicament is still in medicament chamber **114**,

guard 108 remains in an extended position covering needle 116, energy source 1122 has not released the energy that it has stored, and projections 1134 of ram assembly 1120 remains engaged with ram holding member 1062 and aligned in the first position (1022a) of opening 1022.

FIGS. 10A and 10B show injection device 100 in a triggered or “just-used” state. FIG. 13B shows many of the internal components of injection device 100 in this triggered or “just-used” state without showing housing 102. In this state, guard 108 has been proximally slidably displaced (e.g., by application of a force on the distal end of guard 108) from the extended position to the retracted position, thereby exposing needle 116. Energy source 1122 is just beginning to release its stored energy (e.g., the exemplary compression spring remains compressed), and ram assembly 1120 remains in the proximal-most position. Injection device 100 may be in this state, for example, during an initial stage of use by a user. For example, this can be observed when the user has pressed guard 108 of injection device 100 against an injection site to perform an injection. Accordingly, the force exerted by the user in pressing guard 108 of injection device 100 against the injection site may have proximally displaced guard 108 against the force of spring 118, thereby displacing guard 108 into the retracted position and exposing needle 116 to penetrate the user’s skin at the injection site.

In this triggered state shown in FIG. 10B, guard 108 has been displaced into the retracted position, camming surfaces 1084 of guard 108 engage camming surfaces 1024a disposed on the interior of ram assembly 1120, thereby camming ram assembly 1120 (see FIG. 16). This camming action rotates ram assembly 1120, causing projections 1134 to become unaligned with the first position of opening 1022 and become aligned with the second position of opening 1022. In this position, projections 1134 are no longer restrained from splaying open by the lateral walls of opening 1022. Accordingly, projections 1134 splay open under the force of, energy source 1122, causing projections 1134 to disengage with ram holding member 1062 of housing end/end cap 106. The disengagement of projections 1134 with ram holding member 1062 allows ram assembly 1120 to be distally slidably displaced relative to housing 102 under the force generated by energy source 1122. The distal displacement of ram assembly 1120 is preferably restrained by ram assembly 1120 abutting a proximal surface of ring-like structure 1100 of sleeve 110.

FIGS. 11A and 11B show injection device 100 in a “just-injected” state. This state follows the disengagement of projections 1134 with ram holding member 1062 and the distal displacement of ram assembly 1120 described above. In this state, energy source 1122 (e.g., a compression spring) has released its energy, thereby distally displacing ram assembly 1120. Further, guard 108 remains compressed in the refracted position. This state may be observed during use of injection device 100 immediately following the state shown in FIGS. 10A and 10B. As described above, camming of ram assembly 1120 aligns projections 1134 with the second position defined by opening 1022, allowing projections 1134 to splay open and disengage ram holding member 1062 under the force released by energy source 1122. Accordingly, energy source 1122 has released at least some, if not all, of its stored energy (e.g., compression spring is less compressed), and ram assembly 1120, as well as ram 1132, has been distally displaced into a distal position. The distal displacement of ram 1132 urges plunger 1140 in a distal direction, injecting the medicament into the user by dispensing the medicament in medicament chamber 114

through needle 116 and into the user. Although the injection has preferably been completed in this state, injection device 100 is still likely pressed against the injection site since guard 108 remains in a retracted position exposing needle 116. Further, this distal displacement of ram assembly 1120 preferably positions ram assembly 1120 such that it is displayed in window 1020 of housing 102. In an exemplary embodiment, after the distal displacement of ram assembly 1120, it is disposed between medicament container 114 and housing 102 such that it is entirely occluding window 1020 so that only ram assembly 1120 is visible through window 1020, and medicament container 114 is no longer visible (e.g., ram assembly is disposed between medicament container 114 and window 1020). Further, ram assembly 1120 can have a color (as described above) that would be a clear indicator to a user that injection device 100 has been used, and different than the other colors visible from the outside of the injector before firing.

FIGS. 12A and 12B show injection device 100 in a “locked-out” state. FIG. 13C shows many of the internal components of injection device 100 in this “locked-out” state without housing 102. The state can be observed, for example, after the user has removed injection device 100 from the injection site. In this state, nothing is restraining guard 108 in the retracted position against the force of spring, and accordingly, guard 108 is distally displaced from the retracted position to the extended position under the force of spring 118, thereby covering needle 116. As guard 108 moves distally from the retracted position to the extended position under the force of spring 118, projections 1086, which are disposed on springs 1088 biased in an outward direction, engage an openings created between proximal surfaces of legs 1110 of sleeve 110 and proximal walls of openings 1128. Accordingly, the association of projections 1086 with the proximal walls of openings 1128 prevents guard 108 from being displaced proximally, and the association of projections 1086 with the proximal surfaces of legs 1110 prevents guard 108 from being displaced distally. Thus, guard 108 is in a locked position, thereby “locking-out” injection device 100 such that needle 116 is covered and guard 108 is locked in place so that a user cannot attempt a subsequent injection. Afterwards, the user may affix cap 104 back onto the distal end of injection device 100.

Advantageously, this “locked-out” state is preferably not dependent on displacement of guard 108, but rather, is preferably dependent on dispensing of the medicament stored in medicament chamber 114 and/or movement of ram assembly 1120. For example, injection device 100 become locked-out in situations where the medicament is inadvertently dispensed, even if guard 108 has not been displaced. Injection device 100 can become locked-out in any instance where energy source 1122 is activated and ram assembly 1120 is distally displaced, causing ram 1132 to displace plunger 1140, thereby dispensing the medicament in medicament chamber 114. This can occur, for example, if injection device 100 is mishandled, dropped, broken, or if housing 102 is defective (e.g., the tolerances of opening 1022 are incorrect, housing 102 is cracked or otherwise compromised, etc.) such that the lateral walls of opening 1022 cannot prevent projections 1134 from splaying outward under the force of energy source 1122. Accordingly, the lock-out feature prevents a user from unknowingly performing an “injection” with an empty injection device 100, even if injection device 100 appears to be new and not used. This

can be important in preventing patients from believing that they have administered an injection when in fact the injector was empty.

In an exemplary embodiment, many of the components of injection device **100** are preferably made of a resilient plastic or polymer, or a metal. Preferably, projections **1134** of ram assembly **1120** are oriented so that ram assembly **1120** can be molded using a single mold. For example, as shown in FIGS. **6B** and **13C**, projections **1134** (which are preferably concentrically symmetrical to each other) can be aligned at an angle relative to the alignment of the other features of ram assembly **1120**, such as legs **1130** (which are preferably concentrically symmetrical to each other). For example, as shown in FIG. **17**, a single mold can form the portion of ram assembly **1120** designated A (including all the features, components, openings, etc. **1130A**), and a single mold can form the portion of ram assembly designated B (including all the features, components, openings, etc. **1130B**). Thus, each surface of projections **1134** is preferably accessible along a direction of separating the two molds, and the two molds can be separated linearly without a concave portion of projections **1134** facing orthogonal to the separation direction impeding separation and removal of the molds.

Further, cap **104** can be configured helically so that it can be molded without a hole/opening. For example, cap **104** can include threads **1044** that permit cap **104** to be threadedly removed from a mold. Further, outer housing **102** can include a translucent material to allow users to view the inner workings of injection device **100**, and ascertain if it is malfunctioning (e.g., as shown in FIGS. **1A**, **7**, **8A**, **9A**, **10A**, **11A**, **12A**, and **16**). Additionally, injection device **100** can include various gripping elements, such as ridges, pads, contours, or the like, to make injection device **100** more ergonomic, easy to use, and comfortable to the user. Further, injection device **100** can include markings, such as a sticker, brand markings, drug information, numerals, arrows, or the like, to indicate the steps needed to perform an injection, and areas for promotional markings such as brand and logo designations.

FIG. **18** shows another exemplary embodiment of injection device. As shown in FIG. **18**, ram assembly **1120** can include trigger engagement member that takes the form of a seat or ledge **1120b**. Seat **1120b** can engage a retaining portion, such as ledges **102a**, of housing **102** in the pre-fired condition such that the engagement of ledges **102a** with the seat **1120b** in the pre-fired condition opposes the force of energy source **1122**. When a firing of injection device **100** is initiated, ram assembly **1120** can be rotated, for example, via a camming association of guard **108** and ram assembly (such as described with respect to exemplary embodiments above) until recesses **1120°** between the seats **1120b** align with projections **102a** in the firing condition. In the firing condition, the force of energy source **1122** is no longer opposed, allowing ram assembly **1120** to be distally displaced and dispensing the medicament in performing an injection.

All of the references specifically identified in the detailed description section of the present application are expressly incorporated herein in their entirety by reference thereto. The term "about," as used herein, should generally be understood to refer to both the corresponding number and a range of numbers. Moreover, all numerical ranges herein should be understood to include each whole integer within the range.

While illustrative embodiments of the invention are disclosed herein, it will be appreciated that numerous modifications and other embodiments may be devised by those

skilled in the art. For example, the features for the various embodiments can be used in other embodiments. In an alternative embodiment, the hosing can be fixed to the bracket, and the inner portion, defining at least the bottom of the chutes can slide in and out of the housing. Other embodiments can include different mechanisms to cause the rotation of the ram assembly to release it from the retainer portion, such as by direct rotation of the ram by a user, such as via a slide or other element accessible on the outside of the housing, or by a button that is pushed with a finger, or another transmission mechanism to rotate the ram or ram assembly. Therefore, it will be understood that the appended claims are intended to cover all such modifications and embodiments that come within the spirit and scope of the present invention.

The invention claimed is:

1. An injector, comprising:

a trigger mechanism including:

a trigger member having a retainer portion, and
a ram assembly having a ram configured to pressurize a medicament container for expelling a medicament therefrom, the ram assembly further having a trigger engagement member configured to engage the retainer portion of the trigger member in a pre-firing condition;

an energy source associated with the ram for powering the ram to expel the medicament; and

a user-operable firing-initiation member operable for causing an axial rotation between the trigger engagement member and the retainer portion from the pre-firing condition to a firing condition in which the trigger engagement member is released from the retainer portion to allow the energy source to fire the ram.

2. The injector of claim **1**, wherein the ram assembly is of unitary construction.

3. The injector of claim **1**, further comprising a container support that is configured for holding the medicament container during injection, and wherein the ram assembly is configured to engage the container support to lock-out the injector after dispensing of the medicament.

4. The injector of claim **3**, wherein proximal movement of the user-operable firing-initiation member is blocked by the ram assembly when the injector is locked-out.

5. The injector of claim **1**, wherein the firing initiation member comprises a skin-contacting member, the skin-contacting member comprising a needle guard that is retractable and is configured to expose a needle connected to the medicament container upon the proximal movement of the skin-contacting member.

6. The injector of claim **5**, wherein the needle is in fluid communication with the medicament container for injecting the medicament expelled therefrom during the firing.

7. The injector of claim **5**, wherein the skin contacting member comprises a first cam, and the ram assembly comprises a second cam, the first cam being operatively associated with the second cam for camming the second cam upon the axial movement to rotate the ram assembly with respect to the retainer portion so as to position the ram assembly in the firing condition.

8. The injector of claim **1**, wherein the energy source is configured to pressurize the medicament to between about 90 p.s.i. and about 500 p.s.i.

9. The injector of claim **8**, wherein the energy source and the needle are configured for jet injecting the medicament through the needle.

17

10. The injector of claim 8, wherein the energy source and needle are configured for injecting the medicament at an average velocity of at least about 1,000 cm/sec within the needle.

11. The injector of claim 8, wherein the energy source and needle are configured to result in a medicament flow rate of about 0.2 mL/sec to about 0.75 mL/sec.

12. The injector of claim 1, further comprising an injection housing, wherein:

the trigger engagement member and the ram are in fixed association, such that rotation of the trigger engagement member rotates the ram; and

the ram assembly is associated with the firing-initiation member such that operation of the firing-initiation member rotates the ram assembly within the housing to the firing condition.

13. The injector of claim 12, wherein the trigger mechanism comprises a ram holding member that axially retains the ram assembly in a proximal position against action of the energy source in the pre-firing position, the retainer portion retaining the trigger engagement member engaged and held against firing by the ram holding member.

14. The injector of claim 13, wherein in the firing condition, the ram is disengaged from the retainer portion, and the energy source overcomes an engagement between the trigger engagement member and the ram holding member.

15. The injector of claim 13, wherein the ram holding member includes a projection that includes a bulge and a groove engaged with the trigger engagement member, and the retainer portion retains the engagement of the trigger engagement member with the bulge and groove in the pre-firing condition.

16. The injector of claim 1, wherein a pre-firing color gamut is visible from the exterior of the injector in the pre-firing condition, the injector further comprising:

a housing including a window; and

18

an indicator having an indicator color that is absent from the pre-firing color gamut, which color is hidden from view within the housing in the pre-fired condition, wherein in the fired condition, the indicator color is visible through the window from an exterior of the injector for indicating the fired condition.

17. The injector of claim 16, wherein the ram assembly includes the indicator.

18. The injector of claim 17, wherein the ram assembly entirely occludes the window in the fired condition.

19. An injector, comprising:

a trigger mechanism including:

a trigger member having a retainer portion, and

a ram assembly having a ram configured to pressurize a medicament container for expelling a medicament therefrom and at least one first camming surface, the ram assembly further having a trigger engagement member configured to engage the retainer portion of the trigger member in a pre-firing condition;

an energy source associated with the ram for powering the ram to expel the medicament; and

a needle guard including a user-operable firing-initiation member having at least one second camming surface configured to operatively associate with the at least one first camming surface so as to cause an axial rotation between the trigger engagement member and the retainer portion from the pre-firing condition to a firing condition in which the trigger engagement member is released from the retainer portion to allow the energy source to fire the ram.

20. The injector of claim 19, further comprising a container support, and wherein the ram assembly is configured to engage the container support to lock-out the injector after dispensing of the medicament.

* * * * *