



US009454686B2

(12) **United States Patent**
Wang

(10) **Patent No.:** **US 9,454,686 B2**
(45) **Date of Patent:** **Sep. 27, 2016**

(54) **APPARATUS HAVING HYBRID MONOCHROME AND COLOR IMAGE SENSOR ARRAY**

(52) **U.S. Cl.**
CPC **G06K 7/10722** (2013.01); **G06K 7/10** (2013.01); **G06K 7/10732** (2013.01); **G06K 7/10752** (2013.01); **G06K 7/12** (2013.01); **G06K 7/14** (2013.01); **G06K 7/1417** (2013.01); **G06K 7/1443** (2013.01); **H04N 9/045** (2013.01)

(71) Applicant: **HAND HELD PRODUCTS, INC.**, Skaneateles Falls, NY (US)

(72) Inventor: **Ynjiun P. Wang**, Cupertino, CA (US)

(58) **Field of Classification Search**
CPC G06K 7/10881; G06K 7/10891; G06K 7/10851; G06K 17/0022; G06K 7/10772
USPC 235/462.44, 462.45, 462.46, 472.01, 235/472.02, 472.03
See application file for complete search history.

(73) Assignee: **Hand Held Products, Inc.**, Skaneateles Falls, NY (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(56) **References Cited**

(21) Appl. No.: **14/684,609**

U.S. PATENT DOCUMENTS

(22) Filed: **Apr. 13, 2015**

3,684,868 A 8/1972 Christie et al.
3,716,669 A 2/1973 Watanabe et al.

(65) **Prior Publication Data**

US 2016/0004895 A1 Jan. 7, 2016

(Continued)

Related U.S. Application Data

FOREIGN PATENT DOCUMENTS

(60) Continuation of application No. 14/221,874, filed on Mar. 21, 2014, now Pat. No. 9,058,527, which is a continuation of application No. 13/493,348, filed on Jun. 11, 2012, now Pat. No. 8,720,785, which is a division of application No. 12/853,090, filed on Aug. 9, 2010, now Pat. No. 8,196,839, which is a division of application No. 11/445,930, filed on Jun. 2, 2006, now Pat. No. 7,770,799.

CN 1504824 A 6/2004
CN 1511412 A 7/2004

(Continued)

OTHER PUBLICATIONS

(60) Provisional application No. 60/687,606, filed on Jun. 3, 2005, provisional application No. 60/690,268, filed on Jun. 14, 2005, provisional application No. 60/692,890, filed on Jun. 22, 2005, provisional application No. 60/694,371, filed on Jun. 27, 2005.

US 8,038,065, 9/2011, Wang et al. (withdrawn).
(Continued)

Primary Examiner — Karl D Frech


(74) *Attorney, Agent, or Firm* — Alston & Bird LLP

(51) **Int. Cl.**
G06K 7/10 (2006.01)
G06K 7/14 (2006.01)
G06K 7/12 (2006.01)
H04N 9/04 (2006.01)

(57) **ABSTRACT**

There is provided in one embodiment an apparatus having an image sensor array. In one embodiment, the image sensor array can include monochrome pixels and color sensitive pixels. The monochrome pixels can be pixels without wavelength selective color filter elements. The color sensitive pixels can include wavelength selective color filter elements.

51 Claims, 36 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

3,971,065 A	7/1976	Bayer	5,717,195 A	2/1998	Feng et al.
4,047,203 A	9/1977	Dillon	5,739,518 A	4/1998	Wang
4,121,244 A	10/1978	Nakabe et al.	5,756,981 A	5/1998	Roustaei et al.
4,253,447 A	3/1981	Moore et al.	5,763,864 A	6/1998	O'Hagan et al.
4,261,344 A	4/1981	Moore et al.	5,763,866 A	6/1998	Seo et al.
4,350,418 A	9/1982	Taguchi et al.	5,770,847 A	6/1998	Olmstead
RE31,289 E	6/1983	Moore et al.	5,773,810 A	6/1998	Hussey et al.
RE31,290 E	6/1983	Moore et al.	5,773,814 A	6/1998	Phillips
4,390,895 A	6/1983	Sato et al.	5,777,314 A	7/1998	Roustaei
4,437,112 A	3/1984	Tanaka et al.	5,783,811 A	7/1998	Feng et al.
4,491,865 A	1/1985	Danna et al.	5,784,102 A	7/1998	Hussey et al.
4,516,017 A	5/1985	Hara et al.	5,786,582 A	7/1998	Roustaei et al.
4,523,224 A	6/1985	Longacre, Jr.	5,786,586 A	7/1998	Pidhirny et al.
4,546,379 A	10/1985	Sarofeen et al.	5,793,033 A	8/1998	Feng et al.
4,605,956 A	8/1986	Cok	5,811,774 A	9/1998	Ju et al.
4,630,307 A	12/1986	Cok	5,811,784 A	9/1998	Tausch et al.
4,760,411 A	7/1988	Ohmura et al.	5,811,828 A	9/1998	Laser
4,793,689 A	12/1988	Aoyagi et al.	5,814,801 A	9/1998	Wang et al.
4,806,776 A	2/1989	Kley	5,815,200 A	9/1998	Ju et al.
4,807,981 A	2/1989	Takizawa et al.	5,818,023 A	10/1998	Meyerson et al.
4,823,186 A	4/1989	Muramatsu	5,818,028 A	10/1998	Meyerson et al.
4,853,774 A	8/1989	Danna et al.	5,821,518 A	10/1998	Sussmeier et al.
4,854,302 A	8/1989	Allred, III	5,831,254 A	11/1998	Karpen et al.
4,858,020 A	8/1989	Homma	5,834,754 A	11/1998	Feng et al.
4,862,253 A	8/1989	English et al.	5,837,987 A	11/1998	Koenck et al.
4,877,949 A	10/1989	Danielson et al.	5,841,121 A	11/1998	Koenck
4,941,456 A	7/1990	Wood et al.	5,861,960 A	1/1999	Suzuki et al.
4,957,346 A	9/1990	Wood et al.	5,877,487 A	3/1999	Tani et al.
4,962,419 A	10/1990	Hibbard et al.	5,883,375 A	3/1999	Knowles et al.
4,963,756 A	10/1990	Quan et al.	5,914,476 A	6/1999	Gerst, III et al.
5,018,006 A	5/1991	Hashimoto	5,917,913 A	6/1999	Wang
5,019,699 A	5/1991	Koenck	5,936,218 A	8/1999	Ohkawa et al.
5,059,146 A	10/1991	Thomas et al.	5,940,163 A	8/1999	Byrum
5,144,190 A	9/1992	Thomas et al.	5,949,052 A	9/1999	Longacre, Jr. et al.
5,222,477 A	6/1993	Lia	5,949,056 A	9/1999	White
5,227,614 A	7/1993	Danielson et al.	5,979,753 A	11/1999	Roslak
5,278,642 A	1/1994	Danna et al.	5,979,757 A	11/1999	Tracy et al.
5,291,008 A	3/1994	Havens et al.	5,979,763 A	11/1999	Wang et al.
5,305,122 A	4/1994	Hayashi et al.	5,986,297 A	11/1999	Guidash et al.
5,308,962 A	5/1994	Havens et al.	5,988,506 A	11/1999	Schaham et al.
5,323,233 A	6/1994	Yamagami et al.	5,992,744 A	11/1999	Smith et al.
5,337,361 A	8/1994	Wang et al.	6,003,008 A	12/1999	Postrel et al.
5,374,956 A	12/1994	D'Luna	6,006,990 A	12/1999	Ye et al.
5,378,883 A	1/1995	Batterman et al.	6,010,070 A	1/2000	Mizuochi et al.
5,393,965 A	2/1995	Bravman et al.	6,010,073 A	1/2000	Bianchi
5,399,846 A	3/1995	Pavlidis et al.	6,019,286 A	2/2000	Li et al.
5,401,944 A	3/1995	Bravman et al.	6,042,012 A	3/2000	Olmstead et al.
5,406,032 A	4/1995	Clayton et al.	6,045,047 A	4/2000	Pidhirny et al.
5,406,062 A	4/1995	Hasegawa et al.	6,045,238 A	4/2000	Wheeler et al.
5,410,141 A	4/1995	Koenck et al.	6,049,813 A	4/2000	Danielson et al.
5,471,533 A	11/1995	Wang et al.	6,053,407 A	4/2000	Wang et al.
5,504,322 A	4/1996	Pavlidis et al.	6,053,408 A	4/2000	Stoner
5,506,619 A	4/1996	Adams, Jr. et al.	6,058,498 A	5/2000	Nagasaki et al.
5,513,264 A	4/1996	Wang et al.	6,060,722 A	5/2000	Havens et al.
5,521,366 A	5/1996	Wang et al.	6,062,455 A	5/2000	Giannuzzi et al.
5,527,262 A	6/1996	Monroe et al.	6,062,475 A	5/2000	Feng
5,541,777 A	7/1996	Sakamoto et al.	6,062,477 A	5/2000	Wike, Jr. et al.
5,572,006 A	11/1996	Wang et al.	6,073,851 A	6/2000	Olmstead et al.
5,576,529 A	11/1996	Koenck et al.	6,075,240 A	6/2000	Watanabe et al.
5,591,955 A	1/1997	Laser	6,084,528 A	7/2000	Beach et al.
5,602,377 A	2/1997	Beller et al.	6,097,835 A	8/2000	Lindgren
5,602,379 A	2/1997	Uchimura et al.	6,102,295 A	8/2000	Ogami
5,608,204 A	3/1997	Hofflinger et al.	6,105,869 A	8/2000	Scharf et al.
5,629,734 A	5/1997	Hamilton, Jr. et al.	6,118,552 A	9/2000	Suzuki et al.
5,637,849 A	6/1997	Wang et al.	6,123,261 A	9/2000	Roustaei
5,646,390 A	7/1997	Wang et al.	6,123,263 A	9/2000	Feng
5,652,621 A	7/1997	Adams, Jr. et al.	6,142,934 A	11/2000	Lagerway et al.
5,654,533 A	8/1997	Suzuki et al.	6,152,368 A	11/2000	Olmstead et al.
5,659,167 A	8/1997	Wang et al.	6,155,488 A	12/2000	Olmstead et al.
5,662,586 A	9/1997	Monroe et al.	6,155,491 A	12/2000	Dueker et al.
5,691,773 A	11/1997	Wang et al.	6,157,027 A	12/2000	Watanabe et al.
5,702,058 A	12/1997	Dobbs et al.	6,179,208 B1	1/2001	Feng
5,702,059 A	12/1997	Chu et al.	6,184,534 B1	2/2001	Stephany et al.
5,703,349 A	12/1997	Meyerson et al.	6,186,404 B1	2/2001	Ehrhart et al.
5,714,745 A	2/1998	Ju et al.	6,223,988 B1	5/2001	Batterman et al.
			6,230,975 B1	5/2001	Colley et al.
			6,234,394 B1	5/2001	Kahn et al.
			6,247,645 B1	6/2001	Harris et al.
			6,254,003 B1	7/2001	Pettinelli et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,262,804 B1	7/2001	Friend et al.	7,159,783 B2	1/2007	Walczyk et al.
6,276,605 B1	8/2001	Olmstead et al.	7,187,442 B2	3/2007	Chinnock
6,289,176 B1	9/2001	Mutter et al.	7,219,841 B2	5/2007	Biss et al.
6,298,176 B2	10/2001	Longacre, Jr. et al.	7,219,843 B2	5/2007	Havens et al.
6,304,660 B1	10/2001	Ehrhart et al.	7,222,789 B2	5/2007	Longacre, Jr. et al.
6,311,895 B1	11/2001	Olmstead et al.	7,234,641 B2	6/2007	Olmstead
6,311,896 B1	11/2001	Mulla et al.	7,268,924 B2	9/2007	Hussey et al.
6,313,917 B1	11/2001	Tang et al.	7,270,273 B2	9/2007	Barber et al.
6,315,203 B1	11/2001	Ikeda et al.	7,270,274 B2	9/2007	Hennick et al.
6,315,204 B1	11/2001	Knighton et al.	7,276,025 B2	10/2007	Roberts et al.
6,318,635 B1	11/2001	Stoner	7,277,562 B2	10/2007	Zyzdryn
6,340,114 B1	1/2002	Correa et al.	7,287,696 B2	10/2007	Attia et al.
6,347,163 B2	2/2002	Roustaei	7,293,712 B2	11/2007	Wang
6,375,075 B1	4/2002	Ackley et al.	7,303,126 B2	12/2007	Patel et al.
6,386,452 B1	5/2002	Kawamura	7,327,504 B2	2/2008	Gallagher
6,405,929 B1	6/2002	Ehrhart et al.	7,343,865 B2	3/2008	Shuert
6,419,157 B1	7/2002	Ehrhart et al.	7,446,753 B2	11/2008	Fitch et al.
6,452,153 B1	9/2002	Lauxtermann et al.	7,568,628 B2	8/2009	Wang et al.
6,456,798 B1	9/2002	Keech et al.	7,611,060 B2	11/2009	Wang et al.
6,460,766 B1	10/2002	Olschafskie et al.	7,636,486 B2	12/2009	Steinberg et al.
6,474,865 B2	11/2002	Nakajo	7,637,430 B2	12/2009	Hawley et al.
6,476,865 B1	11/2002	Gindele et al.	7,639,888 B2	12/2009	Steinberg et al.
6,491,223 B1	12/2002	Longacre, Jr. et al.	7,639,889 B2	12/2009	Steinberg et al.
6,522,323 B1	2/2003	Sasaki et al.	7,660,478 B2	2/2010	Steinberg et al.
6,522,441 B1	2/2003	Rudeen	7,690,572 B2	4/2010	Meier et al.
6,533,168 B1	3/2003	Ching	7,717,342 B2	5/2010	Wang
6,552,323 B2	4/2003	Guidash et al.	7,740,176 B2	6/2010	Wang et al.
6,561,428 B2	5/2003	Meier et al.	7,770,799 B2	8/2010	Wang
6,575,367 B1	6/2003	Longacre, Jr.	7,773,118 B2	8/2010	Florea et al.
6,575,368 B1	6/2003	Tamburrini et al.	7,780,089 B2	8/2010	Wang
6,598,797 B2	7/2003	Lee	7,784,696 B2	8/2010	Wang
6,621,598 B1	9/2003	Oda	7,874,483 B2	1/2011	Wang et al.
6,637,658 B2	10/2003	Barber et al.	7,909,257 B2	3/2011	Wang et al.
6,646,246 B1	11/2003	Gindele et al.	7,984,855 B2	7/2011	Wang
6,654,062 B1	11/2003	Numata et al.	8,002,188 B2	8/2011	Wang et al.
6,655,597 B1	12/2003	Swartz et al.	8,016,196 B2	9/2011	Meier et al.
6,676,016 B1	1/2004	Coskrev, IV	8,025,232 B2	9/2011	Wang
6,681,994 B1	1/2004	Koenck	8,146,820 B2	4/2012	Wang et al.
6,694,064 B1	2/2004	Benkelman	8,169,486 B2	5/2012	Corcoran et al.
6,695,209 B1	2/2004	La	8,196,839 B2	6/2012	Wang
6,714,239 B2	3/2004	Guidash	8,218,027 B2	7/2012	Wang
6,722,569 B2	4/2004	Ehrhart et al.	8,720,784 B2	5/2014	Wang
6,752,319 B2	6/2004	Ehrhart et al.	8,720,785 B2 *	5/2014	Wang G06K 7/10722 235/462.44
6,811,088 B2	11/2004	Lanzaro et al.	8,978,985 B2	3/2015	Wang et al.
6,813,046 B1	11/2004	Gindele et al.	2001/0003071 A1	6/2001	Mansutti et al.
6,814,290 B2	11/2004	Longacre	2001/0003346 A1	6/2001	Feng
6,821,810 B1	11/2004	Hsiao et al.	2001/0013549 A1	8/2001	Harris et al.
6,824,059 B2	11/2004	Jam et al.	2001/0027999 A1	10/2001	Lee
6,832,725 B2	12/2004	Gardiner et al.	2002/0125317 A1	9/2002	Hussey et al.
6,834,807 B2	12/2004	Ehrhart et al.	2002/0130957 A1	9/2002	Gallagher et al.
6,877,664 B1	4/2005	Oliva	2002/0171745 A1	11/2002	Ehrhart
6,879,340 B1	4/2005	Chevallier	2002/0179713 A1	12/2002	Pettinelli et al.
6,880,759 B2	4/2005	Wilde et al.	2003/0004827 A1	1/2003	Wang
6,889,904 B2	5/2005	Bianculli et al.	2003/0018897 A1	1/2003	Bellis et al.
6,910,633 B2	6/2005	Swartz et al.	2003/0019934 A1	1/2003	Hunter et al.
6,917,381 B2	7/2005	Acharya et al.	2003/0022144 A1	1/2003	Cliff
6,937,774 B1	8/2005	Specht et al.	2003/0022147 A1	1/2003	Segall et al.
6,956,544 B2	10/2005	Valliath et al.	2003/0029917 A1	2/2003	Hennick et al.
6,959,865 B2	11/2005	Walczyk et al.	2003/0034394 A1	2/2003	Gannon et al.
6,976,626 B2	12/2005	Schmidt et al.	2003/0062413 A1	4/2003	Gardiner et al.
6,976,631 B2	12/2005	Kashi et al.	2003/0086008 A1	5/2003	Nagano
7,009,638 B2	3/2006	Gruber et al.	2003/0089775 A1	5/2003	Yeakley et al.
7,044,378 B2	5/2006	Patel et al.	2003/0095299 A1	5/2003	Oda et al.
7,055,747 B2	6/2006	Havens et al.	2003/0102376 A1	6/2003	Meier et al.
7,057,654 B2	6/2006	Roddy et al.	2003/0127519 A1	7/2003	Ehrhart et al.
7,073,715 B2	7/2006	Patel et al.	2003/0132292 A1	7/2003	Gomez et al.
7,083,098 B2	8/2006	Joseph et al.	2003/0168512 A1	9/2003	Longacre et al.
7,086,595 B2	8/2006	Zhu et al.	2003/0178492 A1	9/2003	Tamburrini et al.
7,086,596 B2	8/2006	Meier et al.	2003/0197063 A1	10/2003	Longacre
7,090,132 B2	8/2006	Havens et al.	2003/0201328 A1	10/2003	Jam et al.
7,111,787 B2	9/2006	Ehrhart	2003/0206150 A1	11/2003	Hussey et al.
7,121,470 B2	10/2006	McCall et al.	2003/0210332 A1	11/2003	Frame
7,128,266 B2	10/2006	Zhu et al.	2003/0222144 A1	12/2003	Meier et al.
7,130,047 B2	10/2006	Chinnock	2003/0222147 A1	12/2003	Havens et al.
7,148,923 B2	12/2006	Harper et al.	2003/0226895 A1	12/2003	Havens et al.
			2004/0004128 A1	1/2004	Pettinelli et al.
			2004/0020990 A1	2/2004	Havens et al.
			2004/0026510 A1	2/2004	Cheung et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2004/0031851 A1 2/2004 Bianculli et al.
 2004/0035933 A1 2/2004 Havens et al.
 2004/0046881 A1 3/2004 Utagawa
 2004/0109081 A1 6/2004 Sumi
 2004/0118921 A1 6/2004 Breytman et al.
 2004/0129783 A1 7/2004 Patel
 2004/0155110 A1 8/2004 Ehrhart et al.
 2004/0164165 A1 8/2004 Havens et al.
 2004/0174576 A1 9/2004 Kamisuwa et al.
 2004/0190092 A1 9/2004 Silverbrook
 2004/0206825 A1 10/2004 Schmidt et al.
 2004/0251394 A1 12/2004 Rhodes et al.
 2005/0001035 A1 1/2005 Hawley et al.
 2005/0041296 A1 2/2005 Hsiao et al.
 2005/0052554 A1 3/2005 Sakurai et al.
 2005/0072847 A1 4/2005 Barkan et al.
 2005/0103846 A1 5/2005 Zhu et al.
 2005/0103854 A1 5/2005 Zhu et al.
 2005/0103864 A1 5/2005 Zhu et al.
 2005/0121519 A1 6/2005 Shinohara
 2005/0134936 A1 6/2005 Haug et al.
 2005/0145698 A1 7/2005 Havens et al.
 2005/0161511 A1 7/2005 Parker et al.
 2005/0167507 A1 8/2005 Swartz et al.
 2005/0276475 A1 12/2005 Sawada
 2005/0279836 A1 12/2005 Havens et al.
 2005/0281474 A1 12/2005 Huang
 2006/0011724 A1 1/2006 Joseph et al.
 2006/0016335 A1 1/2006 Cox et al.
 2006/0043194 A1 3/2006 Barkan et al.
 2006/0071081 A1 4/2006 Wang
 2006/0098954 A1 5/2006 Takagi
 2006/0113386 A1 6/2006 Olmstead
 2006/0119738 A1 6/2006 Kido
 2006/0163355 A1 7/2006 Olmstead et al.
 2006/0180670 A1 8/2006 Acosta et al.
 2006/0202036 A1 9/2006 Wang et al.
 2006/0202038 A1 9/2006 Wang et al.
 2006/0249581 A1 11/2006 Smith
 2006/0255144 A1 11/2006 Meier et al.
 2006/0274171 A1 12/2006 Wang
 2006/0283952 A1 12/2006 Wang
 2007/0002153 A1 1/2007 Dierickx
 2007/0045424 A1 3/2007 Wang
 2007/0108284 A1 5/2007 Pankow et al.
 2007/0135866 A1 6/2007 Baker et al.
 2007/0158428 A1 7/2007 Havens et al.
 2007/0158535 A1 7/2007 Waktins
 2007/0164111 A1 7/2007 Wang et al.
 2007/0181692 A1 8/2007 Barkan et al.
 2007/0205272 A1 9/2007 Daddabbo et al.
 2007/0219417 A1 9/2007 Roberts et al.
 2007/0242297 A1 10/2007 Eki
 2007/0267501 A1 11/2007 Jovanovski et al.
 2007/0284448 A1 12/2007 Wang
 2007/0285698 A1 12/2007 Wang et al.
 2008/0219581 A1 9/2008 Albu et al.
 2008/0223933 A1 9/2008 Smith
 2008/0239352 A1 10/2008 Jun
 2008/0267495 A1 10/2008 Shimura
 2008/0291499 A1 11/2008 Chang
 2008/0296393 A1 12/2008 Jovanovski et al.
 2008/0309769 A1 12/2008 Albu et al.
 2008/0309770 A1 12/2008 Florea et al.
 2009/0026267 A1 1/2009 Wang et al.
 2009/0032597 A1 2/2009 Barber et al.
 2009/0046185 A1 2/2009 Ota
 2009/0072038 A1 3/2009 Li et al.
 2009/0073516 A1 3/2009 Tanaka
 2009/0086294 A1 4/2009 Sakakibara
 2009/0121021 A1 5/2009 Wang et al.
 2009/0179999 A1 7/2009 Albu et al.
 2009/0212911 A1 8/2009 Min et al.
 2009/0213811 A1 8/2009 Wang et al.
 2010/0044440 A1 2/2010 Wang et al.

2010/0090007 A1 4/2010 Wang et al.
 2010/0140356 A1 6/2010 Hawley et al.
 2010/0141812 A1 6/2010 Hirota
 2010/0219250 A1 9/2010 Wang
 2010/0226345 A1 9/2010 Qu et al.
 2010/0258633 A1 10/2010 Wang
 2010/0259638 A1 10/2010 Wang
 2010/0289915 A1 11/2010 Wang
 2010/0309340 A1 12/2010 Border et al.
 2010/0315536 A1 12/2010 Wang
 2010/0316291 A1 12/2010 Deng et al.
 2011/0049245 A1 3/2011 Wang
 2011/0057039 A1 3/2011 Wang
 2011/0073654 A1 3/2011 Wang et al.
 2011/0080500 A1 4/2011 Wang et al.
 2011/0102638 A1 5/2011 Susanu et al.
 2011/0163166 A1 7/2011 Wang et al.
 2011/0168779 A1 7/2011 Wang et al.
 2011/0303750 A1 12/2011 Wang
 2012/0002066 A1 1/2012 Wang
 2012/0187190 A1 7/2012 Wang et al.
 2012/0248196 A1 10/2012 Wang
 2012/0293699 A1 11/2012 Blanquart et al.
 2013/0010138 A1 1/2013 Bigioi et al.
 2013/0021507 A1 1/2013 Wang et al.
 2013/0112753 A1 5/2013 Wang
 2013/0113967 A1 5/2013 Wang

FOREIGN PATENT DOCUMENTS

CN 1564996 A 1/2005
 CN 100334499 C 8/2007
 CN 101031930 A 9/2007
 CN 101069190 11/2007
 CN 101147157 A 3/2008
 CN 101171597 A 4/2008
 CN 201117008 9/2008
 CN 101171587 B 4/2011
 DE 19581524 6/1997
 EP 0 119 862 A2 9/1984
 EP 0 472 299 A1 2/1992
 EP 498 366 A2 8/1992
 EP 690 403 A2 1/1996
 EP 0 809 303 A 11/1997
 EP 0 858 212 A1 8/1998
 EP 917 087 A1 5/1999
 EP 1 152 472 A1 7/2001
 EP 1 436 768 A1 7/2004
 EP 1 784 761 A1 5/2007
 EP 1 828 957 A2 9/2007
 EP 1 856 651 A2 11/2007
 EP 2 364 026 A2 9/2011
 GB 2105143 A 3/1983
 GB 2301691 A 12/1996
 JP 63-185285 7/1988
 JP H03-250764 A 11/1991
 JP H03-250983 A 11/1991
 JP H-06-231466 A 8/1994
 JP H07-506932 A 7/1995
 JP 95-12372 T 12/1997
 JP H10-70261 A 3/1998
 JP 10106919 A 4/1998
 JP 10-223875 A 8/1998
 JP 2000-050028 A 2/2000
 JP 2000-165754 A 6/2000
 JP 2000-165755 A 6/2000
 JP 2000-293622 A 10/2000
 JP 2002-268201 A 9/2002
 JP 2002-368201 A 12/2002
 JP 2003-017677 A 1/2003
 JP 2003-132301 A 5/2003
 JP 2004-533031 A 10/2004
 JP 2005-505061 2/2005
 JP 2005-050506 A 9/2006
 JP 2008-511917 A 4/2008
 JP 2008-533590 A 8/2008
 SE 103286 C1 4/2003
 WO WO-86/01678 A2 3/1986
 WO WO-86/01965 A2 3/1986

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	WO-96/20454	A1	7/1996
WO	WO-00/16241	A1	3/2000
WO	WO-01/46899	A2	6/2001
WO	WO-02/063543	A2	8/2002
WO	WO-03/001435	A1	1/2003
WO	WO-03/030082	A1	4/2003
WO	WO-03/081520	A1	10/2003
WO	WO-03/081521	A1	10/2003
WO	WO-03/087713	A1	10/2003
WO	WO-2004/064382	A1	7/2004
WO	WO-2006/026141	A1	3/2006
WO	WO-2006/057863	A2	6/2006
WO	WO-2006/065450	A2	6/2006
WO	WO-2006/081466	A2	8/2006
WO	WO-2006/098954	A2	9/2006
WO	WO-2006/098955	A2	9/2006
WO	WO-2008/131438	A2	10/2008

OTHER PUBLICATIONS

Aboushady, H.; "Single Stamp Amplifiers;" University of Paris VI, slides 1-24; dated 2001; retrieved on Oct. 8, 2013 from <http://www.soc.lip6.fr/~hassan/lec3_single_stage.pdf>.

Adam, J. E.; "Design of practical color filter array interpolation algorithms for digital cameras;" SPIE, vol. 3028; pp. 117-125; dated 1997.

Adams, J. E., et al.; "Color Processing in Digital Cameras;" IEEE Magazine, Eastman Kodak Company; dated 1998.

Berezin, V., et al.; "Dynamic Range Enlargement in CMOS Imagers with Buried Photodiode;" Micron Imaging, Micron Technology; pp. 1-3; dated 2003; retrieved on Oct. 8, 2013 from <<http://www.imagesensors.org/Past%20Workshops/2003%20Workshop/2003%20Papers/47%20Berezin%20et%20al.pdf>>.

Fossum, E. R.; "CMOS Image Sensors: Electronic Camera-on-a-Chip;" IEEE Transactions on Electron Devices, vol. 44, No. 10; pp. 1689-1698; dated Oct. 1997.

Fowler, B., et al.; "A CMOS Area Image Sensor with Pixel Level A/D Conversion;" Information Systems Laboratory, Electrical Engineering Department, Stanford University; dated Nov. 20, 1995.

Gunturk, B. K., et al.; "Demosaicking: Color Filter Array Interpolation;" IEEE Signal Processing Magazine; dated Jan. 2005.

Hamami, S., et al.; "CMOS APS Imager Employing 3.3V 12 Bit 6.3 MS/S Pipelined ADC;" The VLSI Systems Center, Ben-Gurion University; ISCAS '04. Proceedings of the 2004 International Symposium on Circuits and Systems; dated May 2004.

Heimann, T. K., et al.; "Color Filter Array and Color Correction for High Dynamic Range CMOS Image Sensors;" European Conference on Circuit Theory and Design; dated Aug. 2001.

Henderson, R. K., et al.; "Pixel-Pixel Fixed Pattern Noise in CMOS Image Sensors due to Readout Parasitic Capacitance;" School of Engineering and Electronics, University of Edinburgh; dated 2005; retrieved on Oct. 9, 2013 from <<http://www.imagesensors.org/Past%20Workshops/2005%20Workshop/2005%20Papers/07%20Henderson%20et%20al.pdf>>.

Lam, S. H., et al.; "Demosaic: Color Filter Array Interpolation for Digital Cameras;" PCM 2001, LNCS 2195; pp. 1084-1089; dated 2001.

"1/2-Inch 3-Megapixel CMOS Digital Image Sensor;" Micron, pp. 1-41; dated 2004; retrieved on Oct. 8, 2013 from <<http://www.neodomains.ca/domains/content/customizedTemplate/kinko/pdf/mt9t001p12stc.pdf>>.

"1/2-Inch VGA (With Freeze Frame) CMOS Active-Pixel Digital Image Sensor;" pp. 33; dated 2004; retrieved on Oct. 8, 2013 from <http://www.datasheet4u.com/datasheet/M/T/9/MT9V403_Micron.pdf.html>.

"1/3-Inch Wide-VGA CMOS Digital Image Sensor—MT9V022;" Aptina Imaging; 56 pages; dated 2005.

"1.3-Megapixel CMOS Active-Pixel Digital Image Sensor;" pp. 30; dated 2004; retrieved on Oct. 8, 2013 from <<http://www.digchip.com/datasheets/parts/datasheet/301/MT9M413-pdf.php>>.

"417 Bar Code;" dated Dec. 25, 1997.

"2003 IEEE Workshop on CCDs and Advanced Image Sensors Program," Schloss Elmau; pp. 1-5; dated May 15-17, 2003; retrieved on Oct. 8, 2013 from <<http://www.imagesensors.org/Past%20Workshops/2003%20Workshop/2003%20Papers/2003%20Program.htm>>.

"4000 OEM 2D Image Engine;" IMAGETEAM™ from Hand Held Products, Inc.; dated 2005.

"4410 Image Reader;" IMAGETEAM™ from Hand Held Products, Inc.; retrieved on Oct. 8, 2013 from <<http://www.barcoding.com/prodpages/HHP/4410hd.pdf>>.

"4600 Image Reader;" IMAGETEAM™ from Hand Held Products, Inc.; retrieved on Oct. 8, 2013 from <<http://www.barcoding.com/prodpages/HHP/4600.pdf>>.

"4800 Image Reader;" IMAGETEAM™ from Hand Held Products, Inc.; retrieved on Oct. 8, 2013 from <<http://www.barcoding.com/prodpages/HHP/4800.pdf>>.

A first invalidity request filed by Fujian Newland Auto-ID Tech. Co., Ltd. ("Newland") in China, dated Apr. 18, 2012, 670 pages.

A second invalidity request filed by Fujian Newland Auto-ID Tech. Co., Ltd. ("Newland") in China, dated Mar. 4, 2013.

Agilent Technologies, Pulsed Operating Ranges for AllnGap LEDs vs. Projected Long Term Light Output Performance, Nov. 1999, pp. 1-6.

"CompactFlash Specification;" Version 2.0 <<http://www.compactflash.org>>; dated 2003.

"Design and Implementation of Driving Timing for High Frame Rate Video Camera;" Northwest Institute of Nuclear Technology; dated 2004; pp. 2; abstract retrieved on Oct. 8, 2013 from <http://en.cnki.com.cn/Article_en/CJFDTOTAL-DSSS200402031.htm>.

Dolphin 7200 Series Mobile Computer available from Hand Held Products, Inc.; retrieved on Oct. 8, 2013 from <<http://www.barcoding.com/prodpages/HHP/7200rf.pdf>>.

Dolphin 7300 Series Mobile Computer available from Hand Held Products, Inc.; retrieved on Oct. 8, 2013 from <<http://www.legacyglobal.com/Uploads/ProductPDF/Honeywell%20-%20Dolphin%207300%20Series.pdf>>.

Dolphin 7400 Series Mobile Computer available from Hand Held Products, Inc.; retrieved on Oct. 8, 2013 from <<http://www.barcoding.com/prodpages/HHP/7400.pdf>>.

Dolphin 7900 Series Mobile Computer available from Hand Held Products, Inc.; retrieved on Oct. 8, 2013 from <<http://www.barcodesinc.com/pdf/Hand-Held/7900.pdf>>.

Dolphin 9500 Series Mobile Computer available from Hand Held Products, Inc.; retrieved on Oct. 8, 2013 from <<http://www.barcoding.com/prodpages/HHP/9500-9550.pdf>>.

Eastman Kodak Company, Kodak Digital Science KAC-0311 Image Sensor, Fully Integrated Timing, Analog Signal Processing & 10 bit ADC, Technical Data; Revision 1; dated Aug. 5, 2002, pp. 1-56.

Eastman Kodak Company, Ultra Sensitive Global Shutter 580 fps Monochrome CIS, Device Performance Specification, Sep. 2004, pp. 1-22; retrieved on Oct. 9, 2013 from <<http://www.datasheetarchive.com/dl/Datasheets-IS20/DSA00392870.pdf>>.

IMAGETEAM 3800E linear image engine available from Hand Held Products, Inc.; retrieved on Oct. 8, 2013 from <<http://www.barcoding.com/prodpages/HHP/3800vhd.pdf>>.

IMAGETEAM 4710 two-dimensional reader available from Hand Held Products, Inc.; retrieved on Oct. 8, 2013 from <<http://www.barcoding.com/prodpages/HHP/4710hd.pdf>>.

Intel® PXA255 Processor with Intel® XScale™ Technology; Intel; dated 2003; retrieved on Oct. 8, 2013 from <http://int.xscale-freak.com/XSDoc/PXA255/Technical_Documents/Product_Briefs/PXA255_Processor_with_Intel_XScaleR_Technology.pdf>.

Intel® Strong ARM RISC Processor; Intel; dated 2000; retrieved on Oct. 8, 2013 from <http://pdf.datasheetcatalog.com/datasheets/90/361041_DS.pdf>.

"IT4000 Imaging Module & IT4300Laser Aiming Imaging Module;" Hand Held Products Inc.; Hand Held Products IMAGETEAM 4X00 Optical Subassembly; retrieved on Oct. 8, 2013 from <<http://www.racoindustries.com/hhpit4x00opt.htm>>.

"IT4200 Image Engine & IT4250 Image Engine with decoder board;" IMAGETEAM 4200/4250 OEM 2D Image Engine; Hand

(56)

References Cited

OTHER PUBLICATIONS

Held Products, Inc.; dated 2001; retrieved on Oct. 8, 2013 from <ftp://www.scansource.us/HandHeld%20Products/Data%20Sheets/Scanners%20&%20Input%20Devices/English/4200-SS%20Rev%20B.pdf>.

Kodak Image Sensor Soluctins, Device Performance Specifacaiton for Kodak KAI0340S and Kodak KAI-0340D Image Sensor, pp. 1-54, Revision 1.0, Aug. 6, 2004.

Kodak Image Sensor Soluctins, Device Performance Specification for Kodak DAC9630 CMOS Image Sensor, pp. 1-22, Revision 1.1, Sep. 2004.

Kodak Image Sensor Solutiion, Color Better Through CMY Filters, www.kodak.com/go/ccd, pp. 1-2. Month and year unavailable but known to be published prior to earliest priority date of Jun. 3, 2005. Kodak KLI-4104 Image Sensor Device Performance Specification dated Oct. 27, 2003.

“LM9630 100×128 580 fps Ultra Sensitive Monochrome CMOS Image Sensor;” National Semiconductor; dated May 2002; retrieved on Oct. 8, 2013 from <http://doc.chipfind.ru/pdf/nsc/lm9630.pdf>.

“Lumenera USB Camera User’s Manual—Release 3.5;” Lumenera Corporation; dated 2004.

“Micron image sensor with TrueSNAP technology,” pp. 1-3; dated Oct. 21, 2004; originally retrieved from <www.eetasia.comART_8800349851_765245_NP_d8379d7c.htm>; presently retrieved from <http://www.eetasia.com/articleLogin.do?artId=8800349851&fromWhere=/ART_8800349851_765245_NP_e5a216a1.HTM&catId=765245&newsType=NP&pageNo=null&encode=e5a216a1> on Oct. 8, 2013.

Micron Technology, Inc., MT9M111 SOC Megapixel Digital Image Sensor, Products and Specifications Preliminary Manual, pp. 1-61, 2004.

Micron Technology, Inc., MT9M413 1.3-Megapixel CMO ActivePixel Digital Image Sensor, Specification manual, Version 3.0, pp. 1-30, Jan. 2004.

“MT9V022 Image Sensor IC Chip;” Micron, Inc.; dated Oct. 2, 2004; originally retrieved from <http://download.micron.com/pdf/flyers/mt9v022_(m-0350)_flyer.pdf>; currently retrieved from <http://web.archive.org/web/20070404011812/http://download.micron.com/pdf/flyers/mt9v022_(mi-0350)_flyer.pdf> on Oct. 8, 2013.

Panasonic’s Integrated Smart Card Reader model No. ZU-9A36CF4 available from Matsushita Electrical Industrial Company, Ltd.

Panasonic’s Specification No. MIS-DG60C194 entitled, “Manual Insertion Type Integrated Smart Reader” dated Mar. 2004, revision 1.00.

“PB-MV13 20mm CMOS Active-Pixel Digital Image Sensor;” Photobit; pp. 33; dated Aug. 2000; retrieved on Oct. 8, 2013 from <http://fast-vision.com/clientuploads/PDFs/PB-MV13_Product_Specification.pdf>.

“PC Card Standard 8.0 Release—Apr. 2001;” Personal Computer Memory Card International Association (PCMCIA) Version 2.0 <http://www.pcmcia.org>; retrieved on Oct. 8, 2013 from <affon.narod.ru/09gu80.pdf>.

STMicroelectronics, STMicroelectronic Introduces Low-Cost High-Quality Mega Pixel CMOS Sensor for Digital Still Cameras and Camcorders, Introduction article on website http://www.st.com/stonline/press/news/year2002/p1239p.htm, p. 1, Oct. 9, 2002.

Affidavit of Christopher Butler dated Jun. 12, 2013.

“VV6600 1.3 Megapixel CMOS Image Sensor IC Chip;” STMicroelectronics.

www.fillfactory.com, Dual Slope Dynamic Range Expansion, Website, Feb. 28, 2005 pp. 1-3.

www.micron.com, Introducing a CMOS Image Sensor Specifically Designed for Automotive Scene-Understanding Systems, Website, Oct. 2, 2004, pp. 1-2.

www.photonfocus.com, LINOG™ Technology the Key to Programmabel Linear, Logarithmic, or Combined Linera and Logarithmic Response Without Image Lag or Distortion, Website, Feb. 28, 2005, pp. 1-6.

“XSCALE PXA25X Processor IC Chip including Central Processing Unit (CPU)” Intel; retrieved on Oct. 8, 2013 from <http://www.datasheetarchive.com/dlmain/Datasheets-14/DSA-276710.pdf>.

“XSCALE PXA27X Processor IC Chip with ‘Quick Capture Camera Interface;” Intel; retrieved on Oct. 8, 2013 from <int.xscale-freak.com/XSDoc/PXA27X/28000304.pdf>.

Report by Applicants (Reporting divisional application filings in SIPO); dated Sep. 15, 2011.

“The Text of Observation,” Beijing ZBSD Patent & Trademark Agent LTD; dated Nov. 8, 2012; 29 pages; full translation.

“The Text of Observation,” Beijing ZBSD Patent & Trademark Agent LTD; dated Oct. 11, 2012; 233 pages; full translation.

Transaction Terminal Image Kiosk 8870 available from Hand Held Products, Inc.; retrieved on Oct. 8, 2013 from <http://www.legacyglobal.com/Uploads/ProductPDF/Honeywell%20-%20Transaction%20Team%20TT8870%20Series.pdf>.

International Search Report for Application No. PCT/US2006/008113; dated Aug. 7, 2006.

International Search Report and Written Opinion for Application No. PCT/US2006/008113; dated Oct. 26, 2006.

International Search Report and Written Opinion for Application No. PCT/US2006/008114; dated Jul. 14, 2006.

Validity Search Report from the Chinese Patent Office for Application No. 200680016023.5; dated Mar. 15, 2012.

Chinese Office Action (Notification of Acceptance of Request for Invalidation) and Translation for Chinese Patent Application No. 200680016023.5; dated Jul. 3, 2012, 2 pages.

Notification of Acceptance for Request for Invalidation for Chinese Application No. 200680016023.5; dated Jul. 3, 2012.

Observations by the Petitioner; Proceedings on the Invalidation of Chinese Application No. 200680016023.5; dated Oct. 16, 2012 (submitted with corresponding Notification of Transfer of Document and English Translation of corresponding Notification of Transfer of Document, dated Oct. 24, 2012).

Notification of Oral Proceedings on the Request for Invalidation issued in Chinese Patent Application No. 200680016023.5; dated Oct. 23, 2012; 5 pages. full translation.

Notification of Transfer of Documents issued in Chinese Patent Application No. 200680016023.5; dated Oct. 24, 2012; 281 pages; partial translation.

Observations by the Patentee; Proceedings on the Invalidation of Chinese Application No. 200680016023.5; dated Nov. 2, 2012.

Patentee Response to Observations by Petitioner, Proceedings on the Invalidation of Chinese Application No. 200680016023.5; dated Nov. 9, 2012.

“Observation,” Application No. 200680016023.5; Title of invention “Bar Code Reading Device with Global Electronic Shutter Control,” State observation directed to the Notification of Acceptance of Request for Invalidation, which was issued by the Patent Reexamination Board on Nov. 27, 2012; 15 pages; dated Dec. 4, 2012; partial translation.

“Observation,” Application No. 200680016023.5; Title of invention “Bar Code Reading Device with Global Electronic Shutter Control,” State observation directed to the Notification of Transferring the document (issue No. 2012111300206340) which was issued by the Patent Reexamination Board on Nov. 16, 2012; 134 pages; dated Dec. 14, 2012; full translation.

Observations by the Petitioner; Proceedings on the Invalidation of Chinese Application No. 200680016023.5; dated May 29, 2013.

Notification of First Office Action in Chinese Application No. 201110220834.X; dated Aug. 14, 2013.

Office Action for Chinese Application No. 201110220834.X dated May 27, 2014.

Chinese Office Action from Chinese Patent Application No. 201110220834.X dated Nov. 3, 2014.

Office Action for Chinese Application No. 201110220834.X dated Sep. 18, 2015.

Office Action for Chinese Application No. 200680000050.3; dated Mar. 22, 2009 (including English translation thereof, and translated version of pending claims of Chinese Patent Application No. 2006800000503 (26 pages)).

Pending claims for Chinese Application No. 2006800000503; dated May 13, 2009.

(56)

References Cited

OTHER PUBLICATIONS

Office Action for Chinese Application No. 200680000050.3; dated Feb. 13, 2012.

Office Action for Chinese Application No. 201110220832.0; dated Aug. 26, 2013.

Office Action for Chinese Application No. 201110220832.0 dated May 30, 2014.

Chinese Office Action from Chinese Patent Application No. 201110220832.0 dated Nov. 3, 2014.

Office Action for Chinese Application No. 201110220832.0 dated Sep. 29, 2015.

Office Action for Chinese Application No. 2006800160235; dated Jan. 23, 2009 (translation).

Text of Observation by Patentee to Request for Invalidity Action in Chinese Application No. 200680016023.5; dated Aug. 20, 2012.

Supplemental Observations by the Patentee; Proceedings on the Invalidation of Chinese Application No. 200680016023.5; dated Nov. 2, 2012.

Supplemental Observations by the Patentee; Proceedings on the Invalidation of Chinese Application No. 200680016023.5; dated Nov. 9, 2012.

Written Response to Request for Invalidation of Chinese Application No. 200680016023.5; dated Apr. 19, 2013.

Office Action for Chinese Application No. 200680016023.5; dated Oct. 24, 2013.

Office Action for Chinese Application No. 200680016023.5; dated Oct. 30, 2013.

Office Communication (Notice of Transmission of Documents) for Chinese Application No. 200680016023.5 dated Jun. 4, 2015.

Communication Pursuant to Article 94(3) EPC for European Application No. 06 737 299.5; dated Jan. 11, 2008.

Communication Pursuant to Article 94(3) EPC for European Application No. 06 737 299.5; dated Sep. 3, 2010.

Office Action for European Application No. 06737299.5; dated Jul. 10, 2013.

Response and European Communication Pursuant to Article 94(3) EPC in European Application No. 06737300.0; dated Jul. 29, 2011.

Communication Pursuant to Article 94(3) EPC in European Application No. 06737300.1; dated Jan. 19, 2011.

Communication Pursuant to Article 94(3) EPC for European Application No. 06 737 300.1; dated Oct. 30, 2013.

Communication Partial Search Report, European Patent Application No. 10012906.3; dated May 13, 2011 (5 pages).

Communication Extended Search Report for European Application No. 10012906.3; dated Oct. 10, 2011.

Office Action for European Application No. 10012906.3; dated Oct. 9, 2012.

Search Report for European Application No. 13 15 3147 dated Oct. 29, 2015.

Search Report for European Application No. 15 16 7739 dated Oct. 30, 2015.

Office Action for Japanese Application No. 2008-500843; dated Jun. 22, 2012; translation.

Office Action for Japanese Application No. 2008-500843; dated May 14, 2013; translation.

Office Action for Japanese Application No. 2008-500844; dated Jan. 24, 2012; translation.

Office Action for Japanese Application No. 2008-500844; dated Sep. 14, 2012; translation.

Office Action for Japanese Application No. 2013-003616; dated Oct. 8, 2013.

Office Action for Japanese Application No. 2013-003616; dated May 19, 2014.

Appeal Decision for Japanese Application No. 2013-003616; dated Sep. 29, 2015.

Office Action for Japanese Application No. 2014-046409; dated Jan. 5, 2015.

Office Action for Japanese Application No. 2014-046409; dated Jul. 17, 2015.

Japanese Patent Application No. 63-185285 (cited with English Abstract and translation in corresponding U.S. Appl. No. 4,858,020).

U.S. Appl. No. 60/632,696, filed Dec. 1, 2004.

U.S. Appl. No. 60/692,890, filed Jun. 22, 2005.

U.S. Appl. No. 60/694,371, filed Jun. 27, 2005.

Exhibit A./Pat-B of ex parte Request for Reexamination of U.S. Pat. No. 7,568,628; dated Apr. 23, 2012 (including Feb. 25, 2008 Non-Final Office Action; Aug. 21, 2008 Response to Non-Final Office Action; Dec. 10, 2008 Final Office Action; and Apr. 10, 2009 Notice of Allowance for corresponding U.S. Appl. No. 11/077,975—now U.S. Pat. No. 7,568,628).

Request for Ex Parte Reexamination Transmittal Form of U.S. Pat. No. 7,568,628; dated Apr. 23, 2012.

Order Granting/Denying Request for Ex Parte Reexamination in U.S. Appl. No. 90/009,996; dated Jun. 1, 2012.

Ex Parte Reexamination Office Action in U.S. Appl. No. 90/009,996; dated Aug. 3, 2012.

Response by Patent Owner with Exhibits as files in U.S. Appl. No. 90/009,996; dated Oct. 3, 2012.

Ex Parte Reexamination Certificate in 90/009,996 (Reissue U.S. Pat. No. 7,586,628 C1); dated Nov. 29, 2012.

Applicants' Summary of Interview in U.S. Appl. No. 90/009,996 (U.S. Pat. No. 7,568,628); dated Dec. 14, 2012.

Ex Parte Reexamination Interview Summary in 90/009,996 (Reissue U.S. Pat. No. 7,586,628 C1); dated Mar. 26, 2013.

Comments of Statements of Reasons for Patentability and/or Confirmation in U.S. Appl. No. 90/009,996; dated Mar. 26, 2013.

Decision on Appeal for U.S. Pat. No. 7,568,628; dated Feb. 28, 2014.

Final Written Decision from U.S. Pat. No. 7,568,628, dated Feb. 18, 2015.

Office Action for U.S. Appl. No. 11/077,975; dated Feb. 25, 2008.

Office Action for U.S. Appl. No. 11/077,975; dated Dec. 10, 2008.

Office Action for U.S. Appl. No. 11/077,975; Notice of Allowance; dated Apr. 10, 2009.

Office Action for U.S. Appl. No. 11/077,976; dated Apr. 2, 2008.

Office Action for U.S. Appl. No. 11/077,976; dated Aug. 6, 2008.

Office Action for U.S. Appl. No. 11/077,976; dated Dec. 10, 2008.

Office Action for U.S. Appl. No. 11/077,976; Notice of Allowance; dated May 29, 2009.

Office Action for U.S. Appl. No. 11/174,447; dated Jan. 16, 2009.

Office Action for U.S. Appl. No. 11/174,447 dated Aug. 20, 2009.

Notice of Allowance for U.S. Appl. No. 11/174,447 dated Mar. 5, 2010.

Office Action for U.S. Appl. No. 11/445,930 dated May 13, 2009.

Notice of Allowance for U.S. Appl. No. 11/445,930 dated Nov. 17, 2009.

Notice of Allowance for U.S. Appl. No. 11/445,930 dated Mar. 5, 2010.

Office Action for U.S. Appl. No. 11/495,417; dated Dec. 19, 2007.

Office Action for U.S. Appl. No. 11/495,417; dated Apr. 15, 2008.

Claim set of U.S. Appl. No. 12/132,462, filed Jun. 3, 2008, 15 pages.

Claim set of U.S. Appl. No. 12/132,480, filed Jun. 3, 2008, 18 pages.

Office Action for U.S. Appl. No. 12/190,145; dated Mar. 31, 2009.

Office Action for U.S. Appl. No. 12/190,145; dated Oct. 22, 2009.

Office Action for U.S. Appl. No. 12/190,145; Advisory Action; dated Feb. 2, 2010.

Office Action for U.S. Appl. No. 12/190,145; dated Jul. 18, 2012.

Office Action for U.S. Appl. No. 12/190,145; dated May 9, 2013.

Office Action for U.S. Appl. No. 12/190,145 dated Nov. 14, 2013.

U.S. Appl. No. 12/326,443, filed Dec. 2, 2008.

Office Action for U.S. Appl. No. 12/403,459 dated Mar. 7, 2012.

Office Action for U.S. Appl. No. 12/403,459 dated Oct. 2, 2012.

Office Action for U.S. Appl. No. 12/403,459; dated Feb. 5, 2013.

Notice of Allowance for U.S. Appl. No. 12/403,459 dated Aug. 5, 2013.

U.S. Appl. No. 12/421,457, filed Apr. 9, 2009.

U.S. Appl. No. 12/421,476, filed Apr. 9, 2009.

Office Action for U.S. Appl. No. 12/534,664; Notice of Allowance; dated Aug. 6, 2010.

U.S. Appl. No. 12/573,663, filed Oct. 5, 2009.

U.S. Appl. No. 12/637,528, filed Dec. 14, 2009.

(56)

References Cited

OTHER PUBLICATIONS

Office Action for U.S. Appl. No. 12/610,892; Notice of Allowance; dated Jun. 15, 2011.

Office Action for U.S. Appl. No. 12/610,892; Notice of Allowance; dated Nov. 10, 2011.

Office Action for U.S. Appl. No. 12/853,090 dated Mar. 3, 2011.

Notice of Allowance for U.S. Appl. No. 12/853,090 dated Sep. 6, 2011.

Notice of Allowance for U.S. Appl. No. 12/853,090 dated Jan. 27, 2012.

U.S. Appl. No. 12/827,619, filed Jun. 30, 2010.

Office Action for U.S. Appl. No. 12/861,461 dated Oct. 19, 2010.

Notice of Allowance for U.S. Appl. No. 12/861,461 dated Apr. 4, 2011.

Office Action for U.S. Appl. No. 13/052,768; dated Jun. 15, 2011.

Office Action for U.S. Appl. No. 13/052,768; Notice of Allowance; dated Feb. 6, 2012.

Notice of Allowance for U.S. Appl. No. 13/052,768 dated Jul. 13, 2012.

Office Action for U.S. Appl. No. 13/052,768; Notice of Allowance; dated Mar. 21, 2013.

Office Action for U.S. Appl. No. 13/052,768; Notice of Allowance; dated Sep. 18, 2013.

Office Action for U.S. Appl. No. 13/188,696; dated Jan. 4, 2013.

Office Action for U.S. Appl. No. 13/188,696; dated Apr. 24, 2013.

Office Action for U.S. Appl. No. 13/213,543; dated Mar. 30, 2012.

Office Action for U.S. Appl. No. 13/213,543; dated Sep. 20, 2012.

Notice of Allowance for U.S. Appl. No. 13/213,543; dated Feb. 19, 2013.

Notice of Allowance for U.S. Appl. No. 13/213,543 dated Jul. 10, 2013.

Notice of Allowance for U.S. Appl. No. 13/213,543 dated Oct. 30, 2013.

Notice of Allowance for U.S. Appl. No. 13/213,543 dated Jan. 3, 2014.

Office Action for U.S. Appl. No. 13/289,795; dated Aug. 7, 2013.

Notice of Allowance for U.S. Appl. No. 13/289,795 dated Dec. 16, 2013.

Office Action for U.S. Appl. No. 13/437,439; dated Aug. 31, 2012.

Office Action for U.S. Appl. No. 13/437,439; dated May 15, 2013.

Office Action for U.S. Appl. No. 13/437,439; Notice of Allowance; dated Aug. 27, 2013.

Notice of Allowance for U.S. Appl. No. 13/437,439 dated Dec. 26, 2013.

Office Action for U.S. Appl. No. 13/447,393 dated Jul. 16, 2012.
Office Action for U.S. Appl. No. 13/447,393; Notice of Allowance; dated Dec. 28, 2012.

U.S. Appl. No. 13/493,348, filed Jun. 11, 2012.

Office Action for U.S. Appl. No. 13/493,348 dated Aug. 17, 2012.
Notice of Allowance for U.S. Appl. No. 13/493,348 dated Apr. 26, 2013.

Notice of Allowance for U.S. Appl. No. 13/493,348 dated Nov. 5, 2013.

Notice of Allowance for U.S. Appl. No. 13/493,348 dated Dec. 23, 2013.

Office Action for U.S. Appl. No. 13/586,420; dated Apr. 17, 2013.

Office Action for U.S. Appl. No. 13/586,420 dated Sep. 5, 2013.

Notice of Allowance for U.S. Appl. No. 13/586,420 dated Oct. 24, 2013.

Office Action from U.S. Appl. No. 14/273,631, dated Jul. 7, 2014.

Office Action for U.S. Appl. No. 14/221,857 dated May 9, 2014.

Office Action for U.S. Appl. No. 14/221,857 dated Sep. 3, 2014.

Notice of Allowance for U.S. Appl. No. 14/221,857 dated Jan. 22, 2015.

Office Action for U.S. Appl. No. 14/221,874 dated May 9, 2014.

Office Action for U.S. Appl. No. 14/221,874 dated Sep. 15, 2014.

Notice of Allowance from U.S. Appl. No. 14/221,874, dated Jan. 14, 2015.

Office Action from U.S. Appl. No. 14/221,886, dated Feb. 25, 2015.

Notice of Allowance for U.S. Appl. No. 14/221,886 dated Aug. 18, 2015.

Office Action for U.S. Appl. No. 14/221,903 dated Apr. 16, 2015.

Notice of Allowance for U.S. Appl. No. 14/221,903 dated Oct. 5, 2015.

Office Action for U.S. Appl. No. 14/273,631 dated Jul. 7, 2014.

Notice of Allowance for U.S. Appl. No. 14/273,631 dated Oct. 29, 2014.

Office Action for U.S. Appl. No. 14/690,653 dated Nov. 19, 2015.

Notice of Allowance for U.S. Appl. No. 14/221,886 dated Nov. 27, 2015.

Notice of Allowance for U.S. Appl. No. 14/221,903 dated Nov. 30, 2015.

Notice of Allowance for U.S. Appl. No. 14/690,653 dated Apr. 26, 2016.

Invalidation Decision for Chinese Application No. 200680016023.5 dated Mar. 29, 2016.

Office Action for U.S. Appl. No. 15/016,927 dated May 3, 2016.

Office Action for U.S. Appl. No. 14/925,447 dated May 20, 2016.

Notice of Allowance for U.S. Appl. No. 14/221,903 dated Jun. 3, 2016.

* cited by examiner








FIG. 1A






FIG. 2C








FIG. 2D






FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5A







FIG. 5B






FIG. 5F




FIG. 5G










FIG. 5J








FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8E




FIG. 8D




FIG. 8F




FIG. 9A




FIG. 9B

FIG. 9C




FIG. 10




FIG. 11




FIG. 12A






FIG. 13B




FIG. 13C




FIG. 13D




FIG.13E




FIG.14A




FIG.18A




FIG.14B




FIG.14C




FIG.14D




FIG.14E

FIG.14F




FIG. 14G









FIG. 14H

FIG. 14I





P ₁₁ M	P ₂₁	P ₃₁ M	P ₄₁	P ₅₁ M
P ₁₂ M	P ₂₂ M	P ₃₂ M	P ₄₂ M	P ₅₂ M
P ₁₃ M	P ₂₃	P ₃₃ M	P ₄₃	P ₅₃ M
P ₁₄ M	P ₂₄ M	P ₃₄ M	P ₄₄ M	P ₅₄ M
P ₁₅ M	P ₂₅	P ₃₅ M	P ₄₅	P ₅₅ M
P ₁₆ M	P ₂₆ M	P ₃₆ M	P ₄₆ M	P ₅₆ M

5202

FIG. 16A

G ^{P₁₁}	B ^{P₂₁}	G ^{P₃₁}	B ^{P₄₁}	G ^{P₅₁}	B ^{P₆₁}
R ^{P₁₂}	G ^{P₂₂}	R ^{P₃₂}	G ^{P₄₂}	R ^{P₅₂}	G ^{P₆₂}
G ^{P₁₃}	B ^{P₂₃}	G ^{P₃₃}	B ^{P₄₃}	G ^{P₅₃}	B ^{P₆₃}
R ^{P₁₄}	G ^{P₂₄}	R ^{P₃₄}	G ^{P₄₄}	R ^{P₅₄}	G ^{P₆₄}

5204

FIG. 16B

P ₁₁ Cy	P ₂₁ Mg	P ₃₁ Cy	P ₄₁ Mg	P ₅₁ Cy	P ₆₁ Mg
P ₁₂ Mg	P ₂₂ Cy	P ₃₂ Mg	P ₄₂ Cy	P ₅₂ Mg	P ₆₂ Cy
P ₁₃ Cy	P ₂₃ Mg	P ₃₃ Cy	P ₄₃ Mg	P ₅₃ Cy	P ₆₃ Mg
P ₁₄ Mg	P ₂₄ Cy	P ₃₄ Mg	P ₄₄ Cy	P ₅₄ Mg	P ₆₄ Cy
P ₁₅ Cy	P ₂₅ Mg	P ₃₅ Cy	P ₄₅ Mg	P ₅₅ Cy	P ₆₅ Mg

5206

FIG. 16C




FIG. 17A

FIG.17B










FIG.17C










FIG. 19B




FIG. 20A




FIG. 20B




FIG. 21




FIG.22A




FIG.22B




FIG.22C




FIG.22D





FIG. 22F




FIG. 22G




FIG. 22H




FIG. 22I

**APPARATUS HAVING HYBRID
MONOCHROME AND COLOR IMAGE
SENSOR ARRAY**

CROSS REFERENCE TO RELATED
APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 14/221,874 filed Mar. 21, 2014 entitled, "Apparatus Having Hybrid Monochrome and Color Image Sensor Array", is a continuation of U.S. patent application Ser. No. 13/493,348 filed Jun. 11, 2012, and entitled "Apparatus Having Hybrid Monochrome and Color Image Sensor Array" (now U.S. Pat. No. 8,720,785), which is a divisional of U.S. patent application Ser. No. 12/853,090 filed Aug. 9, 2010 entitled, "Optical Reader Having Reduced Specular Reflection Read Failures" (now U.S. Pat. No. 8,196,839), which is a divisional of U.S. patent application Ser. No. 11/445,930 filed Jun. 2, 2006 entitled, "Optical Reader Having Reduced Specular Reflection Read Failures" (now U.S. Pat. No. 7,770,799) which claims priority under 35 U.S.C. §119(e) to U.S. Provisional Patent Application No. 60/687,606, filed Jun. 3, 2005 and titled "Digital Picture Taking Optical Reader Having Hybrid Monochrome And Color Image Sensor Array," and to U.S. Provisional Patent Application No. 60/690,268, filed Jun. 14, 2005 and titled "Digital Picture Taking Optical Reader Having Hybrid Monochrome And Color Image Sensor Array," and to U.S. Provisional Patent Application No. 60/692,890 filed Jun. 22, 2005, entitled "Digital Picture Taking Optical Reader Having Hybrid Monochrome And Color Image Sensor Array" and to U.S. Provisional Patent Application No. 60/694,371 filed Jun. 27, 2005 entitled "Digital Picture Taking Optical Reader Having Hybrid Monochrome And Color Image Sensor Array", all of which are incorporated by reference herein. The referenced U.S. patent application Ser. No. 12/853,090 and the referenced U.S. patent application Ser. No. 11/445,930 and all of the aforementioned patent applications specifically reference (Provisional Patent Application No. 60/694,371, Provisional Patent Application No. 60/692,890, Provisional Patent Application No. 60/690,268 and Provisional Patent Application No. 60/687,606) are herein incorporated by reference in their entirety. The aforementioned U.S. patent application Ser. No. 11/445,930 is also related to U.S. patent application Ser. No. 11/174,447 filed Jun. 30, 2005 entitled, "Digital Picture Taking Optical Reader Having Hybrid Monochrome And Color Image Sensor" (now U.S. Patent Publication No. 2006/0274171) which is also incorporated herein by reference in its entirety.

FIELD OF THE INVENTION

The present invention relates to optical readers in general and specifically, to an optical reader having an image sensor array.

BACKGROUND OF THE PRIOR ART

Designs have been proposed for bar code decoding devices having picture taking functionality.

In U.S. Pat. No. 6,298,176, a picture taking bar code reading device is described that is equipped to output bar code data and associated image data. In one example described in U.S. Pat. No. 6,298,176, output image data is image data representing a handwritten signature. The image data output by the bar code decoding device may be subject to size correction, image orientation adjustment and image

distortion correction image processing for correcting distortion resulting from an image being captured at an angle.

In U.S. Publication No. US2002/0171745, a picture taking bar code reading device is described which is in communication with a remote computer. The bar code reading device sends image data and associated bar code data to the remote computer. In one combined bar code/image data transmission scheme described in U.S. Publication No. US2002/0171745, an image data file in .PDF, .TIFF, or .BMP filed format is created at a data collection device which includes an image representation of a decoded bar code message and an image representation of the package including the bar code encoding the decoded message.

In U.S. Pat. No. 6,722,569 a picture taking bar code reading device is described that includes a color image sensor and a classification circuit which classifies image data as being either bi-tonal image data or color image data.

In U.S. Publication No. US2005/0001035 a picture taking bar code reading device is described which executes either a picture taking exposure control algorithm or bar code decoding exposure control algorithm depending on which mode is selected.

While the above references describe significant improvements in the art, there remains a need for improvement in the art of a picture taking optical reader which is capable of picture taking functionality and excellent bar code decoding functionality.

Performance of an optical reader may be hindered where an optical reader is operated to read bar code symbols or other indicia of a substrate having a "shiny" surface. Such substrates can include, e.g., metal, glass, and laminated plastic. Light rays emanating from a reader that are projected on a highly reflective shiny surface of a substrate may be substantially entirely reflected directly onto a reader image sensor array. Artisans skilled in the art of optical readers regard a "specular reflection" read condition to have occurred where a substantial percentage of light rays are reflected from a substrate and directed onto a reader image sensor array. Light rays are said to be reflected at a "specular" angle when light rays are reflected from a substrate at about the angle of incidence. Specular reflection tends to saturate a reader image sensor array to cause decoding failures. There is a need for an optical reader configured so that specular reflection read errors are reduced.

BRIEF DESCRIPTION OF THE DRAWINGS

The objects and features of the invention can be better understood with reference to the drawings described below, and the claims.

FIG. 1a is an electrical block diagram of a hand held optical reader of the invention including a hybrid monochrome and a color sensing solid state image sensor array;

FIG. 1b is a block diagram of an alternative image sensor array which may be incorporated into an optical reader according to the invention;

FIG. 1c is a schematic block diagram illustrating an RF communications circuit according to the invention;

FIG. 1d is a schematic block diagram illustrating a display according to the invention;

FIG. 1e is a schematic view illustrating incorporation of a decode circuit, a signature autodiscrimination circuit, a demosaicing circuit, and a fusion circuit into an optical reader according to the invention;

FIG. 2a-2d are various partial exploded top views of an embodiment of a solid state image sensor array according to the invention;

FIG. 3a is a cutaway exploded side view of a monochrome pixel according to one embodiment of the invention;

FIG. 3b is a top view of the pixel shown in FIG. 3a;

FIG. 3c is a cutaway exploded side view of a color sensitive pixel in one embodiment of the invention;

FIG. 3d is a top view of the pixel shown in FIG. 3c;

FIG. 4a is an electrical block diagram of an embodiment of an image sensor according to the invention;

FIG. 4b is an electrical block diagram of an image sensor array of the invention showing incorporation of reset control lines in the image sensor array;

FIG. 4c is a timing diagram illustrating coordinated exposure control timing pulses and reset control timing pulses according to the invention;

FIGS. 5a-5e are various partial exploded top views of an embodiment of a solid state image sensor array according to the invention;

FIG. 5f is a top perspective view of an image sensor integrated circuit chip incorporating an image sensor array according to the invention with an exploded view portion illustrating a pixel pattern of color sensitive "clusters" of pixels which pattern may be distributed throughout the array;

FIGS. 5g-5i are top perspective views of image sensor integrated circuit chips incorporating a linear bar code symbol optimized image sensor array according to the invention with respective exploded view portions illustrating pixel patterns including "zones" of monochrome pixels and "zones" of color sensitive pixels;

FIG. 5j is a top perspective view of an image sensor integrated circuit chip incorporating a linear symbol optimized image sensor array according to the invention;

FIG. 6a is a cutaway exploded side view of a monochrome pixel according to one embodiment of the invention;

FIG. 6b is a top view of the pixel shown in FIG. 6a;

FIG. 6c is a cutaway exploded side view of a color sensitive pixel in one embodiment of the invention;

FIG. 6d is a top view of the pixel shown in FIG. 6c;

FIG. 7a is an electrical block diagram of an embodiment of an image sensor according to the invention;

FIG. 7b is an electrical block diagram of an image sensor array of the invention showing incorporation of reset control lines in the image sensor array;

FIGS. 7c and 7d are schematic top views illustrating alternative configurations for a reset control system including separate sets of reset control lines for resetting a first subset of rows of pixels independent of resetting second subset of rows of pixels of an image sensor array according to the invention;

FIG. 8a is an exploded perspective view of an imaging module according to the invention;

FIGS. 8b and 8c are front and side views, respectively, of the imaging module shown in FIG. 8a;

FIG. 8d shows an illumination and aiming pattern which may be projected by an optical reader according to the invention;

FIG. 8e is a top view of an alternative imaging module incorporating a laser based aiming pattern generating system;

FIG. 8f is a front view of a polarizer plate which may be included as part of an imaging module herein, e.g., the imaging middle shown in FIG. 8a;

FIGS. 9a and 9b are physical form views of various hand held optical readers according to the invention;

FIG. 9c is a perspective view of a hand held mobile telephone (a "cell phone") which may incorporate a hybrid

monochrome and color image sensor array according to the invention and which may be configured according to the invention;

FIG. 10 is a schematic view of a system incorporating a plurality of optical readers according to the invention;

FIG. 11 is an application schematic view illustrating an optical reader according to the invention being operated to capture image data representing a parcel that carries a plurality of bar code symbols;

FIG. 12a is an application schematic view illustrating a first optical reader according to the invention and a second remotely located optical reader according to the invention being operated to take first and second digital pictures of a parcel at first and second locations that are a distance apart for purposes of determining whether the parcel was damaged during delivery from the first location to the second location;

FIG. 12b is another application schematic view illustrating an optical reader being used to take a color picture of a delivery vehicle;

FIG. 13a is an application schematic diagram according to the invention illustrating an optical reader according to the invention being used to read bar codes of a vehicle and to take color pictures of a vehicle;

FIG. 13b is a view of a VIN sticker which may be disposed on the vehicle of FIG. 13a;

FIG. 13c is a view of a VIN plate which may be disposed on the vehicle of FIG. 13a;

FIG. 13d is a view of a vehicle registration sticker which may be disposed on the vehicle of FIG. 13a;

FIG. 13e is a view of an optical reader programmed to display a GUI form assisting an application wherein an optical reader, according to the invention, is utilized to decode bar code symbols and to take color pictures of a vehicle;

FIGS. 14a-14c are various flow diagrams illustrating the invention;

FIGS. 14d-14f are additional flow diagrams illustrating examples of operation of an optical reader according to the invention in an indicia decode mode of operation;

FIGS. 14g and 14h are additional flow diagrams illustrating examples of operation of an optical reader according to the invention in a picture taking mode of operation;

FIG. 14i is a flow diagram illustrating operation of a fusion circuit of an optical reader according to the invention which processes monochrome and color image data to produce a high resolution visual display color frame of image data;

FIGS. 15a-15e are various image capture initiation control signal timing diagrams illustrating the invention;

FIGS. 16a-16c illustrate various pixelized frames of image data which may be captured by an optical reader according to the invention;

FIG. 17a is an electrical block diagram of an optical reader according to the invention having a plurality of imaging modules;

FIGS. 17b and 17c illustrate alternative hardware blocks that can be utilized with the electrical circuit of FIG. 17a;

FIGS. 17d and 17e illustrate imaging modules which may be utilized with the reader of FIG. 17a;

FIGS. 17f and 17g illustrate exemplary optical readers incorporating a pair of imaging modules;

FIG. 18a is a schematic view of a cyan-magenta-yellow (CMY) image sensor array in accordance with the invention which may be incorporated into an optical reader according

to the invention and which may be controlled to generate both a decode frame of image data and a visual display color frame of image data;

FIG. 19a is a schematic view of a hybrid monochrome and polarizer image sensor array in accordance with the invention which may be incorporated in an optical reader according to the invention;

FIG. 19b is a top perspective view of a hybrid monochrome and polarizer image sensor array according to the invention with an exploded view section illustrating a pattern of light polarizing pixels that may be distributed throughout the image sensor array;

FIG. 19c is a flow diagram illustrating an exemplary operational mode of an optical reader according to the invention which incorporates a hybrid monochrome and polarizer image sensor array according to the invention;

FIGS. 20a and 20b are top perspective views of a monochrome polarizer and color sensitive image sensor array according to the invention with an exploded view section illustrating a pattern of light polarizing pixels and color sensitive pixels that may be distributed throughout the array;

FIG. 21 is a schematic view of an image sensor integrated circuit chip incorporating an image sensor array having color sensitive pixels disposed therein with two different periods of distribution;

FIG. 22a is a schematic block diagram of an autodiscrimination circuit which may be utilized with the invention;

FIG. 22b is a process for practicing principles of the invention including automatically discriminating between different dataform types;

FIG. 22c shows one embodiment of a plurality of curvelent detector maps which may be utilized with the invention;

FIG. 22d shows another embodiment of a plurality of curvelent detector maps which may be utilized with the invention;

FIG. 22e is a diagrammatic representation of a histogram analysis which may be performed in one embodiment of the invention;

FIGS. 22f-22i are diagrammatic representations of an image data segmentation process according to embodiments of the invention.

DETAILED DESCRIPTION OF THE INVENTION

There is provided in one embodiment an optical reader having an image sensor array. In one embodiment, the image sensor array can include a first subset of pixels and a second subset of pixels. The first subset of pixels can be devoid of light polarizing filter elements, and the second subset of pixels can be light polarizing pixels including light polarizing filter elements. An optical reader can be configured to selectively read out image data from an image sensor array's light polarizing pixels.

An optical reader image sensor array of the invention can include light polarizing pixels, each light polarizing pixel having a light polarizing filter element (light polarizing filter) that significantly attenuates polarized light rays generated from an appropriately polarized light source and reflected at a specular angle; thus, reducing the contribution of specularly reflected light rays to generated image signals from the polarizing pixels. In one embodiment, a first subset of pixels of an optical reader image sensor array are monochrome pixels and a second subset of pixels are light polarizing pixels. For decoding decodable indicia in specular reflection read conditions, image data corresponding to

the light polarizing pixels can be selectively transferred to a decode circuit, either by way of selecting reading out image data from the light polarizing pixels, or by selectively extracting image data corresponding to light polarizing pixels from a frame of image data including image data in addition to image data corresponding to light polarizing pixels.

In another embodiment, there is provided a picture taking optical reader having a hybrid monochrome and color (monochrome) solid state image sensor array. The hybrid image sensor array comprises a plurality of pixels including a first subset of pixels and a second subset of pixels, wherein the first subset of pixels are monochrome pixels and the second subset of pixels are color sensitive pixels having wavelength selective color filter elements.

In one embodiment, the monochrome first subset of pixels is formed in a checkerboard pattern, and voids are formed at the corners of pixels of the first subset, such that combinations of voids of adjacent pixels define open areas. Pixels of the color sensitive second subset of pixels are formed at the open areas, and wavelength selective filter elements are formed on pixels of the second subset but not on pixels of the first subset.

In another embodiment, an optical reader solid state image sensor array includes a plurality of pixels formed in a plurality of rows on an IC chip in a checkerboard pattern wherein each pixel has approximately the same dimension. The majority of pixels of the image sensor array are monochrome pixels of the first subset. Color sensitive pixels of the second subset are at spaced apart positions and are uniformly or substantially uniformly distributed throughout the image sensor array. Color sensitive pixels may be distributed in the array in a specific pattern of uniform distribution such as a period of $P=2$, where every other pixel of every other row of the image sensor array is a color sensitive pixel, or a period of $P=4$ where, for every fourth row of pixels of the array, every fourth pixel is a color sensitive pixel.

A hybrid monochrome and color sensing solid state image sensor array of the invention may be incorporated in an imaging module which, in addition to having an image sensor array constructed in accordance with the invention includes such elements as an imaging lens, an illumination assembly including a field illumination assembly, an aiming illumination assembly and a support member for supporting the above elements. An imaging module, in turn, may be incorporated into a hand held housing which encapsulates and supports the imaging assembly.

Utilizing complementary metal-oxide-silicon (CMOS) integrated circuit fabrication technologies the image sensor array in one embodiment can be made to have selectively addressable pixels. Where the image sensor array is constructed to have selectively addressable pixels, pixels of the first subset of pixels can be selectively addressed independent of the second subset of pixels so that image data corresponding to the first subset of pixels is selectively read out independent of the second subset of pixels. Image sensor arrays having selective read out capability can be provided utilizing alternative fabrication technologies.

In a further aspect, an optical reader according to the invention includes separate and independently controllable reset control lines for resetting monochrome pixels and color sensitive pixels of the image sensor array. During exposure periods for exposing color sensitive pixels, monochrome pixels may be driven into reset. During exposure periods for exposing monochrome pixels, color sensitive pixels may be driven into reset. Driving pixels not being selectively

addressed for image data read out into a reset state reduces cross-talk between pixels of the image sensor array.

By incorporating within a single low cost image sensor array a combination of monochrome pixels and color sensitive pixels, an optical reader according to the invention provides indicia decoding performance approximately equal to the performance of an optical reader having an all monochrome image sensor array, and picture taking performance (i.e., the ability to obtain visual display quality color frames of image data) approximately equal to or superior to that of a digital camera incorporating an all color pixel image sensor array, wherein each pixel of the array includes a wavelength selective filter element.

An electrical block diagram of an optical reader **100** according to the invention is shown in FIG. **1a**. Reader **100** includes a solid state image sensor array **182A**, incorporated on an image sensor integrated circuit chip **1082A** shown in FIG. **1a** as a CMOS image sensor integrated circuit (IC) chip. In an important aspect, as will be described herein, image sensor array **182A** includes a plurality of pixels and wavelength sensitive color filter elements associated with a color sensitive subset of the pixels, wherein the remaining pixels external to the color sensitive subset of pixels are devoid of associated wavelength selective filter elements. Because image sensor array **182A** includes both monochrome pixels and color sensitive pixels, image sensor array **182A** may be termed a hybrid monochrome and color image sensor array. Reader **100** further includes a processor IC chip **548** and a control circuit **552**. Control circuit **552** in the embodiment of FIG. **1a** is shown as being provided by a central processing unit (CPU) of processor IC chip **548**. In other embodiments, control circuit **552** may be provided by e.g., a programmable logic function execution device such as a field programmable gate array (FPGA) or an application specific integrated circuit (ASIC). Imaging lens **212** focuses images onto an active surface of image sensor array **182A** and together with image sensor array **182A** forms an imaging assembly **200**. Control circuit **552** executes picture taking and indicia decoding algorithms in accordance with instructions stored in program memory EPROM **562** which together with RAM **560** and Flash memory **564** forms a reader memory **566**. Reader memory **566** is in communication with processor IC chip **548** via system bus **570**. Main processor IC chip **548** may be a multifunctional IC chip such as an XSCALE PXA25x processor IC chip including central processing unit (CPU) **552**. Reader **100** further includes a field programmable gate array (FPGA) **580**. Operating under the control of control circuit **552**, FPGA **580** receives digital image data from image sensor IC chip **1082A** and transfers that image data into RAM **560** so that the image data can be further processed (e.g., by the decoding of a bar code symbol). Processor IC chip **548** can include an integrated frame grabber. For example, processor IC chip **548** can be an XSCALE PXA27X processor IC chip with "Quick Capture Camera Interface" available from INTEL. Where processor IC chip **548** includes an integrated frame grabber, the integrated frame grabber may provide the frame acquisition functionality of FPGA **580**. Reader **100** further includes an illumination assembly **104** and a manual trigger **216**. Image sensor IC chip **1082A** in the embodiment of FIG. **1a** includes an on-chip control/timing circuit **1092**, an on-chip gain circuit **1084**, an on-chip analog-to-digital converter **1086** and an on-chip line driver **1090**. An image sensor array which is incorporated into optical reader **100** may take on a variety of forms. In FIG. **1a** reader **100** includes first image sensor array **182A**. However, as indicated by hardware block **208**, the image sensor array **182A** may be replaced. For

example, in the embodiment of FIG. **1b**, reader **100** incorporates image sensor array **182B**. In other embodiments, optical reader **100** incorporates more than one image sensor array. Various embodiments of image sensor arrays which may be incorporated into reader **100** are described herein.

In a further aspect, reader **100** includes a radio frequency (RF) communication interface **571**. Radio frequency communication interface **571** may include one or more radio transceivers. Referring to the schematic diagram of FIG. **1c**, radio frequency communication interface **571** may include one or more of an 802.11 radio transceiver **5712**, a Bluetooth radio transceiver **5714**, a GSM/GPS radio transceiver **5716** or a WIMAX (802.16) radio transceiver **5718**. Radio frequency communication interface **571** facilitates wireless communication of data between device **100** and a spaced apart device **150**. I/O communication interface **572** includes one or more serial or parallel hard-wired communication interfaces facilitating communication with a spaced apart device **150** as will be described further in connection with FIG. **10**. I/O communication interface **572** may include one or more of an Ethernet communication interface, a universal serial bus (USB) interface, or an RS-232 communication interface. Optical reader **100** may further include a keyboard **508** for entering data, a pointer mover **512** for moving a pointer of a graphical user interface (GUI) and a trigger **216** for initiating bar code reading and/or picture taking. Optical reader **100** may also include a display **504**, such as a monochrome or color LED display and a touch screen **504T** overlaid over display **504**. As shown in the schematic block diagram of FIG. **1d**, display **504** may include a display screen **5042** coupled to display controller **5044** for displaying color image data. Display controller **5044** receives a visual display color frame of image data from control circuit **552**, and reformats that data for display depending on the particular requirements of display screen **5042**, including the pixel resolution of display screen **5042**. All of the components of FIG. **1a** can be encapsulated and supported by a hand held housing **101**, e.g., as shown in FIGS. **9a-9c**. Additional features and functions of the components of reader **100** shown in FIG. **1a** are described herein.

Referring to FIG. **1e**, optical reader **100** may be regarded as having various processing circuits (modules). Indicia decode circuit **1702** receives image data and decodes decodable indicia therein such as bar code indicia and OCR character data. Optical reader **100** can be configured so that indicia decode module **1702** decodes such bar code symbols UPC/EAN, Code 11, Code 39, Code 128, Codabar, Interleaved 2 of 5, MSI, PDF417, MicroPDF417, Code 16K, Code 49, MaxiCode, Aztec, Aztec Mesa, Data Matrix, Qcode, QR Code, UCC Composite, Snowflake, Vericode, Dataglyphs, RSS, BC 412, Code 93, Codablock, Postnet (US), BPO4 State, Canadian 4 State, Japanese Post, MX (Dutch Post), Planet Code and the like, and such OCR character forms as OCR A, OCR B, and the like. Autodiscrimination circuit **1704** processes received image data and distinguishes between handwritten character data and decodable indicia. Autodiscrimination circuit **1704** may include indicia decode circuit **1702**. Autodiscrimination circuit **1704** and indicia decode circuit **1702** may be physically embodied by a combination of control circuit **552** and memory **566**. Specifically, control circuit **552** operating under the control of a program stored in memory **562** may process image data stored in memory **560** to decode decodable indicia therein or to discriminate between handwritten character data and decodable indicia. Further aspects of indicia decode circuit **1702** and autodiscrimination circuit **1704** are described in copending U.S. patent application Ser.

No. 10/958,779 entitled, System And Method To Automatically Discriminate Between A Signature And A Barcode, filed Oct. 5, 2004 and U.S. patent application Ser. No. 11/077,975, filed Mar. 11, 2005 entitled, Bar Code Reading Device With Global Electronic Shutter Control, both of which are incorporated herein by reference. As will be described further herein, optical reader **100** may further include a demosaicing circuit **1706**, and a fusion circuit **1708**. Demosaicing circuit **1706** receives as an input a color filter array image data frame (e.g., a Bayer pattern image) and produces as an output a visual display color frame of image data. Fusion circuit **1708** receives as inputs both monochrome and color image data and produces as an output a visual display color frame of image data having a spatial resolution at or on the order of the pixel resolution of the optical reader's hybrid monochrome and color image sensor array. Like circuit **1702**, **1704**, circuits **1706** and **1708** may be physically embodied by the combination of control circuit **552** and memory **566**. Control circuit **552** as well as circuits **1702**, **1704**, **1706**, and **1708** may be incorporated within hand held housing **101** (e.g., as shown in FIGS. **9a-9c**) or else one or more of circuits **552**, **1702**, **1704**, **1706**, and **1708** can be incorporated in a housing of a spaced apart device **150** as described in connection with FIG. **10**.

A visual display color frame of image data as referred to herein, in one embodiment is an image frame including a set of color indicating data at each of a plurality of pixel positions, wherein each set of color indicating data represents a color at a discrete position of a target **1850** (shown in FIG. **8d**). Each set of color indicating data includes three color values, e.g., a color scale value representing red, a color scale value representing blue, and a color scale value representing green. Alternatively, the set of color indicating data for each pixel position may include a cyan value, a magenta value and a value representing yellow.

In one specific example, the set of color indicating data for each pixel position of a visual display color frame of image data output by demosaicing circuit **1706** or fusion circuit **1708** are RGB data sets including 24 bits of information, wherein the first 8 bits represent a red color scale value (red value) for the pixel position, the second 8 bits represent a green color scale value (green value) for the pixel position and the third 8 bits represent a blue color scale value (blue value) for the pixel position.

A major feature of the invention is the construction of the optical reader's image sensor array various embodiments of which are shown and described throughout several views including the views of FIGS. **2a-7d**.

A first embodiment of a hybrid monochrome and color sensitive (monochrome) solid state image sensor array is shown and described in FIG. **1a** and FIGS. **2a-4b**.

Referring to FIG. **1a** and FIGS. **2a-4b**, solid state image sensor array **182A** includes a monochrome first subset of pixels **250M** and a color sensitive second subset of pixels **250C**. The first subset of monochrome pixels **250M** is formed in a checkerboard pattern and voids **253** as shown in FIG. **2a** are formed at the corners of pixels of the first subset, such that combinations of voids, e.g., voids **253-1**, **253-2**, **253-3**, **253-4** of adjacent pixels define open areas, e.g., open area **255**, each open area bounded by four pixels of the first subset. With further reference to image sensor array **182A**, pixels **250C** forming a second subset of pixels **250C** are disposed in the open areas **255**, and wavelength selective filter elements, e.g., filter element **260C**, **260M**, as shown in FIG. **2b** are formed on pixels of the second subset but not on pixels of the first subset. Monochrome pixels **250M** as described herein are devoid of color filter elements (color

filters). Pixels of the first monochrome pixel subset are in the shape of twelve sided polygons. The pixels are cross-shaped as seen from the top view that is indicated by FIGS. **2a-2d** (the monochrome pixels are square shaped as modified by the presence of voids **253**). Pixels of the color sensitive second subset are square as seen from a top view.

In the version of image sensor array **182A** shown in FIG. **2b**, color sensitive pixels **250C** of image sensor array **182A** include either a cyan (Cy) filter element **260C** or magenta (Mg) filter element **260M**. In the version of FIG. **2c**, color sensitive pixels **250C** of image sensor array **182A** include either a red filter element **260R**, a green filter element **260G** or a blue color filter element **260B** (RGB filters). The color sensitive pixels **250C** can be distributed throughout image sensor array **182** according to a Bayer pattern wherein there are N blue pixels, N red pixels and 2N green pixels. Color filter elements of any image sensor array pixel as described herein can be deposited on the major body of color sensitive pixels **250C** by way of a depository process. As will be explained herein, visual display color image data can be obtained utilizing either the version of image sensor array **182A** shown in FIG. **2b** or the version of image sensor array **182A** shown in FIG. **2c**, or another version of image sensor array **182A** such as a version including cyan, magenta and yellow (CMY) color sensitive pixels. Because cyan and magenta filters require only one dye and not two dyes (as in red, green, and blue filters) a version of image sensor array **182A** including cyan and magenta filter elements in place of red, green and blue filter elements allows more light to pass through to a photodetector of the pixels and exhibits a higher signal to noise ratio than a version including red, green and blue filters. Nevertheless, an image sensor array having a combination of red, green and blue (RGB) filter elements may be preferred for certain applications. Referring to FIG. **2d**, image sensor array **182A** may include microlenses **320** for directing of light rays incident on image sensor array **182A**. Further aspects of microlenses **320**, including monochrome pixels, microlenses **320M**, and color sensitive pixel microlenses **320C** are described herein.

Exploded physical form views of an image sensor pixel array **182A**, where array **182A** is configured to operate in a global electronic shutter operating mode are shown and described in FIGS. **3a-3d**. A monochrome pixel **250M** of image sensor array **182A** is shown in FIGS. **3a** and **3b**. Monochrome pixel **250M** includes a photodetector **302** which may be of photodiode or photogate construction, a transfer gate **304**, a floating diffusion **306**, a reset transistor **307** including reset gate **308**, a row select transistor **309** including row select gate **310** and a source follower amplifier transistor **311** including amplifier gate **312**. An important feature of pixel **250M** is opaque optical shield **316**. Opaque optical shield **316**, typically comprising metal, shields light rays from components of pixel **250M** other than photodetector **302**. Accordingly, pixels from each of several rows of image sensor array **182A** can be simultaneously exposed to light in a global electronic shutter operating mode without the light rays modulating charges stored in floating diffusion **306** or another storage region. Further aspects of image sensor arrays capable of operating in a global electronic shutter operating mode are described in U.S. patent application Ser. No. 11/077,975 incorporated herein by reference. Referring to additional aspects of pixel **250M**, pixel **250M** includes microlens **320** which may be disposed on light transmissive protective layer **322**. Microlens **320** collects light from a larger surface area than photodetector **302** and directs light toward photodetector **302**.

A color sensitive pixel **250C** of image sensor array **182A** is described with reference to FIGS. **3c** and **3d**. Color sensitive pixel **250C** is similar in construction to monochrome pixel **250M**. Color sensitive pixel **250C** includes a photodetector **302** which may be of photodiode or photogate construction, a transfer gate **304** for transferring charge from photodetector **250C**, a floating diffusion **306**, a reset transistor **307** including reset gate **308**, a row select transistor **309** including row select gate **310** and a source follower transistor amplifier **311** including amplifier gate **312**. Color sensitive pixel **250C** also includes opaque shield **320** which shields light from light sensitive components of pixel **250C** other than photodetector **302**. Pixel **250C** may also include microlens **320** for increasing the amount of light incident on photodetector **302**. In addition to the above elements color sensitive pixel **250C** includes a wavelength selective color filter element **260** formed thereon. Wavelength selective color filter element **260** may be disposed intermediate microlens **320** and protective layer **322**. In the versions of FIGS. **2a-2d**, it is seen that each color sensitive pixel **250C** has four adjacent monochrome pixels **250M**.

Microlenses **320** as shown in FIGS. **3a** and **3c** are also shown in the view of FIG. **2d**. Monochrome pixel microlens **320**, **320M** and color sensitive microlens **320**, **320C** may be formed on a microlens array included a plurality of microlenses. With the architecture described wherein color sensitive pixels **250C** are disposed in open areas defined by voids of checkerboard pattern of a first monochrome subset of pixels **250M**, microlenses **320C** of color sensitive pixels **250**, **250C** have very little (e.g., less than 3.4%) of overlap relative to microlenses **320M**.

Color sensitive pixel **250C** of image sensor array **182A** as best seen by a comparison between FIGS. **3b** and **3d** and consumes a smaller surface area than pixel **250M**. In one version, pixel **250M** includes an area, as seen from a top view, of about 12 μm by 12 μm while pixel **250C** includes an area, as seen from a top view, of about 6 μm by 6 μm . In another version, pixel **250M** includes a top surface area of about 6 μm by 6 μm , while pixel **250C** includes a top surface area of about 3 μm or 3 μm . Size reductions of pixel **250M** or pixel **250**, **250C** may be made at low cost by reducing the number of transistors of pixel **250M** and/or pixel **250C**.

A transistor count of a pixel **250C** of image sensor array **182A** may readily be reduced by eliminating optically shielded floating diffusion **306** in which charges are stored on a temporary basis to facilitate global electronic shutter operation. Accordingly, in one embodiment, monochrome pixels **250M** of image sensor array **182A** have more transistors than color sensitive pixels **250C** but are capable of being exposed on a global electronic shutter basis, whereas color sensitive pixels **250C** have fewer transistors than monochrome pixels **250M** but are not capable of being exposed on a global electronic shutter basis. In yet another embodiment with reference to image sensor array **182A** having smaller dimensioned color sensitive pixels than monochrome pixels, the relatively larger monochrome pixels **250M** have a transistor count sufficient to facilitate global shutter operation, but the relatively smaller color sensitive pixels **250C** are passive pixels requiring off-pixel amplification, and comprise a single transistor each. Further aspects of global electronic shutter and rolling shutter operations relative to image sensor arrays which may be incorporated into reader **100** are described herein.

Referring to FIG. **4a**, a high level electrical block diagram of image sensor array **182A** is shown. According to one version, image sensor array **182A** is an active pixel image sensor array of complementary metal oxide semiconductor

(CMOS) construction such that each pixel **250M**, **250C**, whether from the monochrome first subset of pixels or the color sensitive second subset of pixels is an active pixel including a pixel amplifier **311** for amplifying signals corresponding to light incident on photosensitive region **252**. Each pixel **250M**, **250C** may also include an optically shielded storage element **306**. Image sensor array **182A** further includes two-dimensional grid of interconnects **262** which are in electrical communication with respective column circuitry **270** and row circuitry **296**. Row circuitry **296** and column circuitry **270** enable such processing and operational tasks as selectively addressing pixels, decoding pixels, amplification of signals, analog-to-digital conversion, applying timing, read out and reset signals and the like.

Among the control lines forming interconnect grid **262** of image sensor array **182A** are pixel reset control lines. When pixels are reset by application of an appropriate control signal on a reset control line, residual charges which have accumulated on the pixels are connected temporarily to VDD so that built up charges on pixels of the image sensor array drain out of the pixels. In accordance with the invention, image sensor array **182A** includes separate reset control lines for monochrome pixels **250M** and color pixels **250C**. Referring to FIG. **4b**, image sensor array **182A** may be constructed so that image sensor array **182A** has a first set of reset control lines **262R-M** for resetting monochrome pixels **250M** and a second set of reset control lines **262R-C** for resetting color pixels **250C**.

In certain operating modes optical reader **100** selectively reads out a windowed frame of image data comprising image data from monochrome pixels **250M**. In other operating modes, optical reader **100** selectively reads out a windowed frame of image data comprising image data from color pixels **250C**. In accordance with the invention, a reset control timing pulse can be applied to image sensor array **182A** during the time that a windowed frame of image data is being captured to reset pixels of image sensor array **182A** that are not being selectively addressed for image data read out. As shown by the timing diagram of FIG. **4c**, an exposure control timing pulse **354** can be coordinated with a reset control timing pulse **370**.

With further reference to FIG. **4c**, exposure control timing pulse **354** may control exposure of monochrome pixels **250M** of image sensor array **182A** (or alternatively, color pixels **250C**) of image sensor array **182A**, while reset control timing pulse **370** drives pixels not being selectively addressed into a reset state. When pixels are reset, charges built up on pixels tend to be drained out of the pixels. Further, it is believed that photons entering pixels driven into reset may be refracted so that fewer photons become incident on neighboring pixels being exposed for image data read out. Accordingly, coordinating the timing of an exposure control pulse **354** for exposing selectively addressed pixels and a reset control timing pulse **370** for resetting pixels not being selectively addressed reduces cross talk between pixels.

Referring again to the view of FIG. **4b**, image sensor array **182A** may be constructed so that the presence of multiple reset control lines **162R-C**, **162R-M** do not substantially decrease the fill factor of pixels of image sensor array **182A**. FIG. **4b** shows a schematic top view of multiple reset control lines **162R-M**, **162R-C** incorporated in image sensor array **182**, **182A**. According to the invention, control lines **162R-M**, **162R-C** can be incorporated in image sensor array **182A** in a layered manner so that for a substantial portion of image sensor array **182A**, control lines **164R-M** have x, y positions that coincide with x, y positions of control line **164R-C** (axes

are defined in FIG. 8a). Control lines 164R-C in the embodiments of FIG. 4b are installed at a different height (a different Z axis position) within image sensor array 182A such that control lines 162R-M and 162R-C, for substantial length of the control lines, have common x, y positions. Installing the multiple control lines to be on top of one another so that the control lines have a common x, y axis position within image sensor array 182A reduces the amount of fill factor degradation which would otherwise result from installation of an additional set of reset control lines within image sensor array 182A.

An alternative construction for an image sensor array according to the invention is described with reference to FIGS. 5a-7b. In the embodiment of FIGS. 5a-7b image sensor array 182B includes a plurality of square shaped pixels (as seen from a top view) in a checkerboard pattern, each of the pixels having substantially the same dimensions. Each pixel 250M, 250C of image sensor array 182B may be constructed to have approximately the same top surface dimensions as seen from the top views of FIGS. 5a-5i and approximately the same side view cross-sectional dimensions as seen from the cross-sectional views of FIGS. 6a-6d. Image sensor array 182B is similar to the construction of a standard off-the-shelf monochrome image sensor array except that select ones of the pixels of the image sensor array have an associated wavelength selective color filter element. Solid state image sensor array 182B includes a plurality of pixels formed in a plurality of rows. In the version of FIGS. 5a-5e, a monochrome first subset of pixels 250M comprise the majority of pixels of the array. Wavelength selective color filter elements 260 are included in the second subset of color sensitive pixels 250C. The color sensitive second subset of pixels 250C comprises pixels at spaced apart pixel positions uniformly distributed or substantially uniformly distributed throughout the plurality of pixels forming the image sensor array 182B. In the embodiment of FIGS. 5a and 5b, every other pixel in every other row of pixels (e.g., pixel row 2, 4, 6 . . .) has an associated wavelength selective color filter element. In one example of the invention, image sensor array 182B can be provided by including an appropriately designed color filter array on an image sensor array of an MT9M111 Digital Clarity SOC 1.3 megapixel CMOS image sensor IC chip of the type available from Micron, Inc., an MT9V022 image sensor IC chip also available from Micron, Inc. or a VV6600 1.3 megapixel CMOS image sensor IC chip of the type available from STMicroelectronics. Other image sensor IC chips which can be utilized to provide image sensor array 182B include MT9M413 image sensor IC chip available from Micron, Inc., a KAC-0311 image sensor IC chip manufactured by Kodak, Inc. and a KAI-0340 image sensor IC chip also manufactured by Kodak, Inc. Operational aspects of the referenced KAI-0340 image sensor IC chip are described further herein. Various manufacturer product description materials respecting certain of the above image sensor IC chips are appended to Provisional patent application No. [not yet assigned] filed Jun. 22, 2005 (Express Mail Label No. EV554216715US) and Provisional patent application No. [not yet assigned] filed Jun. 27, 2005 (Express Mail Label No. EV554216661US) which are incorporated herein by reference. The above commercially sold image sensor IC chips can be utilized (with additions or replacements of filter elements as are necessary) to provide any one of image sensor arrays 182B, 182C, 182D, 182F, 182G, 182H described herein.

The above referenced MT9V022 and MT9M413 image sensor IC chips manufactured by Micron, Inc., and KAC-

0311 image sensor IC chip by Kodak, Inc. are CMOS image sensor IC chips that may be operated in a global electronic shutter mode such that all rows of pixels subject to image data read out have common exposure periods; that is, all rows of pixels subject to image data read out for reading out a frame of image data (i.e., full frame or "windowed frame") have a common exposure start time and a common exposure stop time. For global electronic shutter operation, an exposure control timing pulse, as will be described herein is applied to the image sensor array. Exposure of each row of pixels subject to image data read out begins at the leading edge of the exposure control timing pulse and ends at the falling edge of the exposure control timing pulse. In its technical literature, Micron, Inc. uses the trademark TRUESNAP with reference to a global electronic shutter operating mode.

Referring to FIG. 5b, wavelength selective color filter elements (filters) formed on color sensitive pixels 250, 250C may be a combination of cyan filter elements 260C and magenta color filter elements 260M. As shown in FIG. 5a, wavelength sensitive filters of color sensitive pixels 250C may also be a combination of red filter elements 260R, green filter elements 260G and blue filter elements 260B. Because cyan and magenta filters require only one dye and not two dyes (as in red green and blue filters), the version of FIG. 5b allows more light to pass through to a photodetector (e.g., photodetector 302 as shown in FIG. 6c) and exhibits a higher signal to noise ratio than the embodiment of FIG. 5b. Nevertheless, the version of FIG. 5a may be preferred for certain applications.

In the embodiment of FIGS. 5a-7d, hybrid monochrome and color image sensor 182B can be made by including an appropriately designed color filter array on a commonly available, off-the-shelf image sensor array in a standardly known checkerboard pattern, each pixel of the array having substantially the same dimensions. A larger portion of image sensor array 182B is shown in FIG. 5c, where pixels designated by the letter "c" are color sensitive pixels 250C and pixels not designated by the letter "c" are monochrome pixels 250M. In the example of FIG. 5c, color sensitive pixels are formed on array 182B with a period of P=2, meaning the every other pixel of every other row of pixels is a color sensitive pixel 250C. In the version of FIG. 5d, color sensitive pixels are formed on array 182B with a period of P=3, meaning that every third pixel of every third row is a color sensitive pixel 250C. In the version of FIG. 5e, color sensitive pixels, c, are formed with a period of P=4, meaning that every fourth pixel from every fourth row of pixels is a color sensitive pixel 250C. In the versions of FIGS. 5a-5e, each color sensitive pixel 250C has eight adjacent monochrome pixels 250M (two side adjacent, one top adjacent, one bottom adjacent and four corner adjacent).

Additional views of image sensor array 182B including a subset of monochrome pixels 250M and a subset of color sensitive pixels 250C, wherein each pixel of the image sensor array has substantially equal dimensions are shown and described in connection with FIGS. 5f-5j.

Referring to the version of FIG. 5f, image sensor array 182B includes the first subset of monochrome pixels 250M and a second subset of color sensitive pixels 250C. The color sensitive pixels 250C of image sensor array 182B in the version of FIG. 5f are formed in clusters such as cluster 257R, cluster 257G and cluster 257B.

Each cluster 257 in the version of FIG. 5f includes a plurality of pixels in successive horizontally adjacent pixel positions, such that each pixel of the cluster is horizontally adjacent to at least one other color sensitive pixel. Color

sensitive clusters of pixels are distributed uniformly or substantially uniformly throughout image sensor array **182B**. Clusters may be formed in accordance with the standardized color filter pattern such as an RGB Bayer pattern or a cyan-magenta-yellow (CMY) pattern. Each cluster may have a plurality of pixels with each pixel of every individual cluster having a filter element of the same wavelength rating. In the specific version shown in FIG. **5f**, clusters are distributed throughout image sensor array **182B** in a pattern that is accordance with the pattern of Bayer color filter array.

Cluster **257G** includes three horizontally adjacent green pixels. Cluster **257R** includes three horizontally adjacent red pixels. Cluster **257B** includes three horizontally adjacent blue pixels. As will be described further in connection with FIG. **7c**, the version of image sensor array **182B** including a distribution of color sensitive pixels in horizontally arranged clusters as shown in FIG. **5f** is particularly useful where it is desired to include in image sensor array **182B** separate and independently controllable reset control lines **262R-M** and **262R-C** for separately and independently resetting monochrome pixels of image sensor array **182B** and color sensitive pixels of image sensory array **182B** without increasing the thickness of image sensor array **182B**.

Referring now to the versions of image sensor array **182B** shown in FIG. **5g-5j**, image sensor array **182B** having a subset of monochrome pixels in a subset of color sensitive pixels may be configured to include "zones" of monochrome pixels and "zones" of color sensitive pixels. A "zone" of pixels herein is a collection of positionally related pixels at a specified area of an image sensor array each having a color filter element or alternatively, each being without a color element. Examples of zones described herein comprise all pixels of one row of pixels or all pixels of each of several consecutive rows of pixels. In the version of FIG. **5g**, image sensor array **182B** includes two color sensitive zones of pixels **2500C** and a single monochrome zone of pixels **2500M**. Each zone of pixels comprises a plurality of horizontally, vertically or diagonally adjacent pixels. The plurality of pixels of a monochrome zone of pixels, e.g., zone **2500M** are all devoid of a color sensitive filter element. The plurality of adjacent pixels in a color sensitive zone of pixels, e.g., zone **2500C**, all include a color sensitive filter element.

Referring to the version of FIG. **5g**, monochrome zone of pixels **2500M** is interposed between a pair of color sensitive zones of pixels **2500C**. Monochrome zone of pixels **2500M** in the version of FIG. **5g** comprises a single row of pixels of image sensor array **182B** at or approximately the center of image sensor array **182B**. The first color sensitive zone of pixels of an image sensor array **182B** includes all pixels from the row of pixels of zone **2500M** up to the top row of image sensor array **182B**. The second color sensitive zone of pixels **2500C** in the version of FIG. **5g** includes all pixels from all rows from the center row monochrome zone of pixels **2500M** down to the bottom row of pixels of image sensor array **182B**. The color filter elements of color sensitive pixels **250C** of image sensor array **182B** may be formed in a standard color filter pattern, e.g., an RGM Bayer color filter pattern or a CMY pattern.

Referring to FIG. **5h**, another version of image sensor array **182B** is shown and described. The version of FIG. **5h** is similar to the version of FIG. **5g** except that the monochrome zone of pixels **2500M** is expanded to include ten consecutive rows of pixels at the center or approximately the center of image sensor array **182B**.

In the version of image sensor array **182B** as shown in FIG. **5i**, a single color sensitive zone of pixels **2500C** is interposed between two relatively small width monochrome zones of pixels **2500M** formed at the top and bottom of image sensor array **182B** respectively. In the version of image sensor array **182B** shown in FIG. **5a**, the first monochrome zone of pixels **2500M** comprises the first ten rows of pixels of image sensor array **182B** and a second monochrome zone of pixels **2500M** includes pixels of the bottom ten rows of image sensor array **182B**. Color sensitive zone of pixels **2500C** in the version of FIG. **5i** includes all pixels of the array excluding the first ten and the last ten rows of pixels of image sensor array **182B**. In the versions of FIG. **5h** and FIG. **5i**, the pixels of the color sensitive zones **2500C** shown may include color filter elements in accordance with the pattern of a standardized color filter array, e.g., an RGB Bayer pattern or a CMY pattern.

The version of image sensor array **182B** shown in FIG. **5j** is similar in construction to the version of FIG. **5g** except that the version of FIG. **5j** includes additional monochrome zones of pixels **2500M**. In the version of FIG. **5j** image sensor array **182B** includes a pair of diagonal zones of monochrome pixels **2500M-D** extending through a center (actual or approximate) of image sensor array **182B** and a vertically extending zone of monochrome pixels **2500M-V** extending through a center of image sensor array **182B**. The linear zones of monochrome pixels **2500M** shown in the version of FIG. **5j** may include a minor dimension equal to one pixel width or more than one pixel width. For example, the vertically extending monochrome zone of pixels **2500M** of FIG. **5j** may include pixel positions of one column of pixels or of a plurality of columns of pixels. Likewise, the diagonally extending linear monochrome zones of pixels **2500M** of FIG. **5g** may include pixel positions of a single diagonal row of pixels or alternatively, of a plurality of diagonal rows of pixels.

It will be seen that the versions of image sensor array **182B** shown in FIGS. **5g-5j** are particularly well suited for use in picture taking optical readers which in bar code decoding applications are expected to decode linear bar code symbols. The image sensor arrays of FIGS. **5g-5j** may be referred to as linear symbol optimized image sensor arrays. As will be described in further detail herein, image data corresponding to monochrome zones of pixels **2500M** in the versions of FIGS. **5g-5j** can be selectively addressed and read out independently of image data from rows from color sensitive zones **2500C** of pixels. In bar code decoding applications, control circuit **552** may selectively address pixels of monochrome zones **2500M** and read out image data from monochrome zones of pixels **2500M** as shown in FIGS. **5g-5i** and transfer such image data to indicia decode circuit **1702** for decoding of a linear bar code symbol. For picture taking applications, control circuit **552** may selectively address pixels of a color sensitive zone or zones of pixels **2500C** and selectively read out image data from color sensitive zone or zones **2500C** and process such color image data into a visual display color frame of image data. The processing as will be explained further herein may include such steps as executing a demosaicing routine to convert color filter pattern image data into a visual display format and interpolation of color pixel values corresponding to the missing pixel positions at the pixel positions occupied by a monochrome zone or zones **2500M** of pixels.

In FIGS. **6a-6d**, exploded physical form view of pixels of image sensor array **182**, **182B** are shown. A monochrome pixel **250M** of image sensor array **182B** is shown in FIGS. **6a** and **6b**. Pixel **250M** includes a photodetector **302** which

may be of photodiode or photogate construction, a transfer gate **304**, a floating diffusion **306**, a reset transistor **307** including reset gate **308**, a row select transistor **309** including row select gate **310** and a source follower amplifier transistor **311** including amplifier gate **312**. An important feature of pixel **250M** is opaque optical shield **316**. Opaque optical shield **316**, typically comprising metal, shields light rays from components of pixel **250M** other than photodetector **302**. Accordingly, pixels from each of several rows of image sensor array **182A** can be simultaneously exposed to light in a global electronic shutter operating mode without the light rays modulating charges stored in floating diffusion **306** or another storage region. Further aspects of image sensor arrays capable of operating in a global electronic shutter operating mode are described in U.S. patent application Ser. No. 11/077,975 incorporated herein by reference. Referring to additional aspects of pixel **250M**, pixel **250M** includes microlens **320** which may be disposed on light transmissive protective layer **322**. Microlens **320** collects light from a larger surface area than photodetector **302** and directs light toward photodetector **302**.

A color sensitive pixel **250C** of image sensor array **182B** is described with reference to FIGS. **6c** and **6d**. Color sensitive pixel **250C** is similar in construction to monochrome pixel **250M**. Color sensitive pixel **250C** includes a photodetector **302** which may be of photodiode or photogate construction, a transfer gate **304** for transferring charge from photodetector **250C**, a floating diffusion **306**, a reset transistor **307** including reset gate **308**, a row select transistor **309** including row select gate **310** and a source follower transistor amplifier **311** including amplifier gate **312**. Color sensitive pixel **250C** also includes opaque shield **320** which shields light from light sensitive components of pixel **250C** other than photodetector **302**. Pixel **250C** may also include microlens **320** for increasing the amount of light incident on photodetector **302**. In addition to the above elements, color sensitive pixel **250C** includes a wavelength selective color filter element **260** formed thereon. Wavelength selective color filter element **260** may be disposed intermediate microlens **320** and protective layer **322**.

A high level electrical block diagram of image sensor array **182B** is shown in FIG. **7a**. Image sensor array **182B** may be of CMOS construction and may be an active pixel image sensor array such that each pixel **250** of image sensor array **182B** includes a pixel amplifier **311**. Each pixel **250** of image sensor array may further have a photosensitive region **252** and an optically shielded storage element **306**. Image sensor array **182B** further includes a two-dimensional grid of interconnects **262** which are in electrical communication with respective column circuitry **270** and row circuitry **296**. Row circuitry **296** and column circuitry **270** enable such processing and operational tasks as selectively addressing pixels, decoding pixels, amplification of signals, analog-to-digital conversion, and applying timing, read out and reset signals.

Reset control lines of interconnect grid **262** are shown in FIG. **7b**. Image sensor array **182B** may have multiple sets of reset control lines so that monochrome pixels **250M** of image sensor array **182B** can be reset independently of color sensitive pixels **250C** of image sensor array **182B** as described previously in connection with the description of image sensor array **182B**. According to the invention, control lines **262R-M**, **262R-C** can be incorporated in image sensor array **182B** in a layered manner so that for a substantial portion of image sensor array **182B**, control lines **262R-M** have x, y positions that coincide with x, y positions of control line **262R-C** (axes are defined in FIG. **8a**). Control

lines **262R-C** in the embodiment of FIG. **7b** are installed at a different height (a different Z axis position) within image sensor array **182B** relative to control lines **262R-C** such that control lines **262R-M** and **262R-C**, for substantial length of the control lines, have common x, y positions. Installing the multiple control lines to be on top of one another so that the control lines have a common x, y axis position within image sensor array **182B** reduces the amount of fill factor degradation which would otherwise result from installation of an additional set of reset control lines within image sensor array **182B**.

Referring to FIGS. **7c** and **7d**, image sensor array **182B** may be configured to include separate and independent reset control lines for separately and independently resetting monochrome pixels **250M** and color sensitive pixels **250C** without increasing the overall thickness of image sensor array **182B**. While disposing reset control lines on top of one another as described in connection with FIGS. **4b** and **7b** provides significant advantages; the image sensor array is made thicker with such arrangement which adds to manufacturing costs. Referring to FIG. **7c**, a version of image sensor array **182B** is illustrated having a first set of reset control lines **262**, **262R-M** for resetting monochrome pixels **250M** and a second set of reset control lines **262**, **262R-C** for resetting color sensitive pixels **250C** of image sensor array **182B**. The reset control line configuration of FIG. **7c** may be utilized with the color sensitive pixel distribution shown in FIG. **5f** to provide an image sensor array **182B** having separate and independently controllable reset control lines for separately resetting monochrome pixels **250M** and color sensitive pixels **250C** and which exhibits a thickness equal to a thickness of a commonly available off-the-shelf image sensor array. In the version of image sensor array **182B** shown in FIG. **7c**, the reset control lines of monochrome pixel rows are electrically connected together and the reset control lines of rows of pixels including color sensitive pixels are electrically connected together. The commonly connected reset control lines of the monochrome pixel rows are designated with the reference numeral **262**, **262R-M**, while the commonly reset control lines of the rows including color sensitive pixels are designated with the reference numeral **262**, **262R-C**. In the version of FIG. **5f** and FIG. **7c**, every fourth row of pixels of image sensor array **182B** includes clusters of color sensitive pixels **257R**, **257G**, **257B**. As shown in FIG. **7c**, with reset control lines **262**, **262R-C** of rows including color sensitive pixels **250C** electrically connected together, all rows of image sensor array **182B** including color sensitive pixels **250C** may be driven into reset by application of a reset control signal on common reset control line **262**, **262R-C**. Likewise, all rows of pixels including only monochrome pixels **250M** (the monochrome row of pixels) can be driven into reset by applying a reset control signal on common monochrome pixel reset control line **262**, **262R-M**. With further reference to the version of image sensor array **182B** shown in FIG. **7c**, monochrome pixels **250M** of image sensor array **182B** may be driven into reset when pixels **250C** are exposed for image data read out of color image data.

It is noted that with the configuration of FIG. **7c**, adjacent monochrome pixels **250M-A** adjacent to an end pixel, e.g., pixel **250C-E** of a color sensitive pixel cluster, e.g., cluster **257R** are not driven into reset during exposure periods of color sensitive pixels **250C**. However, according to the invention in one example, image data corresponding only to a center pixel **250C-I** of each color sensitive horizontally arranged cluster (and not the end pixels **250C-E**) may be selectively addressed during read out of color image data.

The presence of each lateral color filter element at the end pixels **250C-E**, which are not addressed for image data read out, reduces the effect of cross talk attributable to photons entering image sensor array **182B** at an angle through end pixels **250C**, **250C-E**.

Another configuration for providing separately and independently resetting monochrome pixels **250M** and color sensitive pixels **250C** of image sensor array **182B** is shown and described with reference to FIG. **7d**. In the version of FIG. **7d**, image sensor array **182B** includes a plurality of rows of pixels including all monochrome pixels **250M** followed by a plurality of rows of pixels that include color sensitive pixels **250C** only. The monochrome rows of pixels **250M** form a first subset of pixels and the color sensitive pixels **250C** form a second subset of pixels. The reset control lines for resetting the first subset of pixels can be made separate and independent of the reset control lines for controlling the second subset of pixels by electrically connecting the reset control lines of the first subset of pixels together and then separately electrically connecting together the reset control lines of the second subset of pixels. The common control lines of the first subset of monochrome pixels **250M** in the version of FIG. **7d** are designated with reference numeral **262**, **262R-M** while the common control lines of the second subset of color sensitive pixels **250C** in the version of FIG. **7d** are designated with the reference numeral **262**, **262R-C**. It will be seen that the configuration of FIG. **7d** facilitating separate and independent control of monochrome pixels **250M** and color sensitive pixels **250C** can be utilized with the line art symbol optimized versions of image sensor array **182B** shown and described in FIGS. **5g-5i** having "zones" of monochrome or alternatively color sensitive pixels **250C** that extend entire rows of image sensor array **182B**.

Referring to FIG. **7d**, color sensitive pixels **250C** may be driven to reset during exposure periods for monochrome pixels **250M** by application of a common reset control signal on reset control line **262**, **262R-M** during exposure of color sensitive pixels **250C** for read out of color image data. Similarly color sensitive pixels **250C** may be driven into reset by application of a reset control signal on common reset control line **262**, **262R-C** during exposure periods of monochrome pixels **250M** for read out of image data from monochrome pixels **250M**.

Features respecting specific embodiments of an image sensor array according to the invention have been described in connection with the views of FIGS. **2a-4c** (image sensor array **182A**), and the views of FIGS. **5a-7d** (image sensor array **182B**). General features of an image sensor array which may be incorporated into optical reader **100** (that is, features which can be incorporated in the image sensor array, whether of the embodiment labeled **182A**, the embodiment labeled **182B**, or another embodiment such as CMY image sensor array **182C**, RGB image sensor array **182D**, monochrome linear image sensor array **182E**, monochrome area image sensor array **182F**, monochrome and polarizer image sensor array **182G**, or monochrome color and polarizer image sensor array **182H**) are now described.

Optical reader **100** can be programmed or otherwise be configured to selectively address a first plurality of pixels in an image sensor array **182A**, **182B**, **182C**, **182D**, **182E**, **182F**, **182G**, **182H** independently of selectively addressing a second plurality of pixels of the image sensor array so that image data can be read out of the first plurality of pixels independently of the second plurality of pixels. In one operating mode optical reader **100** selectively addresses the first subset of pixels and reads out image data from first

subset of pixels independently of the second color sensitive subset of pixels. In another operating mode optical reader **100** selectively addresses the second subset of pixels and reads out image data from the second subset of pixels independently of the first subset of pixels **250M**. Where optical reader **100** selectively addresses and selectively reads out only a subset of pixels of an image sensor array, the resulting frame of image data read out of the image sensor array may be referred to as a "windowed frame" of image data. When a windowed frame of image data is read out, the frame rate of the image sensor array is normally increased relative to a normal frame rate of the image sensor array.

Image sensor array **182A**, **182B**, **182C**, **182D**, **182E**, **182F**, **182G**, **182H** can be configured to have a rolling shutter operating mode and a global shutter operating mode. When a rolling shutter operating mode is entered, rows of pixels of image sensor array are exposed sequentially. The term "rolling" shutter is used because when in a rolling shutter operating mode an exposure period for a row of pixels generally begins prior to a time an exposure period for a previous row has ended.

When operated in a global electronic shutter operating mode, pixels from several rows of an image sensor array are exposed simultaneously. That is, when operated in a global electronic shutter operating mode, transistor components (for example, transfer gates **304** and reset gates **308** of the array as shown in the embodiments of FIGS. **3a** and **6a**) forming an electronic shutter an image sensor array are controlled in a coordinated manner so that a plurality of rows of pixels are exposed simultaneously and have common exposure periods. In a global electronic shutter operating mode, electronic shutter components of the array are controlled so that the common exposure period for each of the plurality of rows of pixels begins at a common exposure start time (via control of reset gates **308**) and ends at a common exposure stop time (via control of transfer gates **304**). As explained herein, each pixel of the array may store a charge in an optically shielded storage region during the common exposure period. For facilitating a global electronic shutter operating mode, an exposure control timing pulse **354**, **354'**, **354''**, **354'''** can be applied to an image sensor array **182A**, **182B**, **182C**, **182D**, **182E**, **182F**, **182G**, **182H**, as is described in further detail in connection with the timing diagrams of FIGS. **15a-15e**. An exposure control timing pulse **354**, **354'**, **354''**, **354'''** controls the timing for exposure of each row of pixels of image sensor array **182A**, **182B**, **182C**, **182D**, **182E**, **182F**, **182G**, **182H** being exposed. The exposure period for each row of pixels the image sensor array being subject to image data read out begins at the leading edge of exposure control timing pulse **354**, **354'**, **354''**, **354'''** and ends at the falling edge of exposure control timing pulse **354**, **354'**, **354''**, **354'''**. For construction of an image sensor array having a global electronic shutter operating mode each pixel of the array is equipped with additional circuit elements as is described herein.

Image sensor array **182A**, **182B**, **182C**, **182D**, **182E**, **182F**, **182G**, **182H** of optical reader **100** may be constructed to be operated in a rolling shutter mode of operation only; that is, in one specific embodiment an image sensor array of optical reader **100** can only be controlled to expose pixels of the image sensor array on a rolling shutter basis and cannot be controlled so that pixels of image sensor array are exposed on a global electronic shutter basis. In another embodiment, an image sensor array incorporated in optical reader **100** is constructed to be operated in a global elec-

tronic shutter operational mode only and is incapable of operation in a rolling shutter mode.

Image sensor array **182A**, **182B**, **182C**, **182D**, **182E**, **182F**, **182G**, **182H** can be constructed to be operated in either of a global electronic shutter operation mode or a rolling shutter operational mode. Where an image sensor array incorporated in optical reader **100** is constructed to be operational in either of a rolling shutter operational mode or a global shutter operational mode, the switching between rolling shutter and global shutter operational modes may be made in response to a receipt of operator instructions to change the shutter mode. The switching between rolling shutter and global shutter operational modes may also be automatic and dynamic in response to the sensing of a predetermined criteria being satisfied. An image sensor array equipped optical reader **100** having both rolling shutter and global shutter operational modes is described in U.S. patent application Ser. No. 11/077,975, filed Mar. 11, 2005 entitled, Bar Code Reading Device With Global Electronic Shutter Control, which is incorporated herein by reference. An image sensor array constructed to be operated in either of a rolling shutter or global shutter operational mode is described in U.S. Pat. No. 6,552,323 entitled, "Image Sensor With A Shared Output Signal Line" which is incorporated by reference.

Image sensor array **182A**, **182B**, **182C**, **182D**, **182E**, **182F**, **182G**, **182H** can be constructed so that certain pixels of the image sensor array are capable of being exposed on either a rolling shutter basis or a global shutter basis and certain other pixels of the image sensor array are capable of being exposed only on a rolling shutter basis and are not capable of being exposed on a global electronic shutter basis.

It has been described with reference specifically to image sensor array **182A**, and image sensor array **182B** that it may be advantageous to incorporate into an image sensor array of optical reader **100** separately controllable reset control lines **262**, **262R-M** and **262**, **262R-C** for resetting monochrome pixels separately and independently of color sensitive pixels to thereby reduce pixel cross talk. It will be understood that it may be advantageous to incorporate separately and independently controllable reset control lines into an image sensor array **182A**, **182B**, **182C**, **182D**, **182E**, **182F**, **182G**, **182H** according to the invention whenever image data is selectively read out of a first subset of image data and it is desired to reduce cross talk from pixels of the image sensor array external to the first subset of pixels. For example, in optical reader **100** incorporating a cyan-magenta-yellow (CMY) image sensor array **182C** as shown in FIG. **18c**, it may be advantageous to incorporate separate reset control lines for resetting magenta and cyan pixels separately from yellow pixels so that when yellow pixels are exposed for read out of decode frame yellow pixel image data for transmission to decode circuit **1792**, the remainder of the pixels of the array, i.e., the cyan and magenta pixels can be set to reset to eliminate electron diffusion cross talk and to reduce photon penetration cross talk. When hand held optical reader **100** incorporates a hybrid monochrome and polarizer image sensor array **182G** as shown in FIG. **19b** or the monochrome color and polarizer image sensor array **182H** as shown in FIGS. **20a** and **20b**, it may be beneficial to incorporate into image sensor array **182** separately controllable reset control lines for controlling the reset of pixels external to the polarizing pixels so that when the polarizing pixels are exposed for read out of image data from the polarizing pixels, the remaining pixels of the image sensor

array are set to reset to reduce cross talk from the pixels external to the polarizing pixels.

While an image sensor array **182A**, **182B**, **182C**, **182D**, **182E**, **182F**, **182G**, **182H** is conveniently provided by a CMOS image sensor array fabricated utilizing complementary metal-oxide-silicon integrated circuit fabrication technologies, an image sensor array **182A**, **182B**, **182C**, **182D**, **182E**, **182F**, **182G**, **182H** may also be a charge coupled device (CCD) image sensor array, or a CID image sensor array or an image sensor array of another fabrication technology. In various embodiments of the invention described herein, it is advantageous to read out less than a full frame of image data, i.e., a read out of a "windowed frame" of image data which may also be referred to as an image region of interest (ROI). An example of a CCD image sensor array integrated circuit chip having windowing capability is the KODAK KAI-0340 image sensor array IC chip available from Eastman Kodak Corporation of Rochester, N.Y. The KAI-0340 image sensor array IC chip has various operational modes that are selectable utilizing various input switch setups. For example, setting a SW1 switch to the HIGH position causes charge in outer vertical registers of the image sensor array to be dumped before it reaches the horizontal register, facilitating the selective read out of image data from center columns of the array only. Setting the SW2 switch of the KAI-0340 image sensor array chip changes diode transfer clock timing such that only charge from the center rows is transferred to vertical registers, facilitating the selective read out of image data from center rows of the image sensor array only. Accordingly, where image sensor array **182B** is configured according to the version shown in FIG. **5h** having center rows of monochrome pixels defining a monochrome pixel zone **2500M** and where the image sensor array is a CCD KAI-0340 image sensor array, image data from the center rows can be read out by selecting a preconfigured operating mode of the image sensor array chip. Additional "windowed frame" patterns can be selectively read out of a CCD image sensor array by varying the speed of a pixel clock timing control timing pulse that controls the speed with which a pixel is clocked. Invalid or null data can be clocked out of a CCD pixel by speeding up a pixel clock signal. Varying a pixel clock control signal between valid data yielding rates and invalid data yielding rates during the reading out of image data from a CCD image sensor array yields a windowed frame of image data comprising valid image data clocked out at normal speed and invalid image data clocked out at high speed. Image data can also be selectively read out of a CCD image sensor array by selectively gating to output circuitry of the CCD image sensor array image data corresponding to select pixels of the image sensor array. It will be seen that for any application described herein wherein a windowed frame of image data is read by selective addressing of pixels from a CMOS image array, a CCD image sensor array supporting windowing capability may be substituted therefore to provide selective read out functionality.

Additional aspects of the invention are described with reference to the physical form views of FIGS. **8a-8c** and the physical form views **9a**, **9b** and **9c**. In the physical views of FIGS. **8a-8c**, an imaging module onto which an image sensor chip may be incorporated is described. With reference to FIGS. **9a**, **9b** and **9c**, hand held housings for supporting and encapsulating an imaging module including an image sensor chip are described.

An optical reader **100** of the invention, as shown in the embodiment of FIGS. **8a-8c**, may include an imaging module such as imaging module **1802A**. Imaging module **1802A**

as shown in FIGS. **8a-8c** incorporates certain features of an IT4000 imaging module herein and additional features. IT4000 imaging modules are available from Hand Held Products, Inc. of Skaneateles Falls, N.Y. Imaging module **1802A** includes first circuit board **1804** carrying light sources **160a, 160b**, while second circuit board **1806** carries light sources **160c, 160d, 160e, 160f, 160g, 160h, 160i, 160j, 160k, 160l, 160m, 160n, 160o, 160p, 160q, 160r, 160s**, and **160t** (hereinafter **160c** through **160t**). First circuit board **1804** also carries image sensor array **182**, which is integrated onto image sensor IC chip **1082**. Image sensor IC chip **1082** and image sensor array **182** in FIG. **8a** are generically labeled with the reference numerals “**1082**” and “**182**” respectively in FIGS. **8a-8d** to indicate that any one of the specifically described image sensor IC chips **1082A, 1082B, 1082C, 1082D, 1082E, 1082F, 1082G, 1082H** described herein or any one of the specifically described image sensor arrays **182A, 182B, 182C, 182D, 182E, 182F, 182G, 182H** described herein may be incorporated into imaging module **1802A**. The various image sensor IC chips and image sensor arrays can also be incorporated in another imaging module described herein such as imaging module **1802B, 1802C, 1802D**, and **1802E**. Imaging module **1802C** shown in FIG. **8e** is a laser aiming IT4300 imaging module of the type available from Hand Held Products, Inc. The laser aiming IT4300 imaging module includes a plurality of illumination LEDs e.g., LED **160**, and an aiming pattern generator comprising a laser diode assembly **1872** in combination with a diffractive element **1873**, wherein the diffractive element of the imaging module diffracts laser light from the laser diode assembly to project a two-dimensional aiming pattern onto a substrate, s. Imaging module **1802A** also includes support assembly **1810** including lens holder **1812**, which holds lens barrel **1814** that carries imaging lens **212** that focuses images onto an active surface of image sensor array **182**. Lens **212** may be e.g., a single lens (a lens singlet), a lens doublet or a lens triplet. Light sources **160a, 160b** are aiming illumination light sources whereas light sources **160c** through **160t** are illumination light sources. Referring to FIG. **8d**, illumination light sources **160c** through **160t** project a two-dimensional illumination pattern **1830** over a substrate, s, that carries a decodable indicia such as a bar code symbol **1835** whereas aiming illumination light sources **160a, 160b** project an aiming pattern **1838**. In the embodiments shown and described in connection with FIGS. **8a-8c**, light from aiming illumination light sources **160a, 160b** is shaped by slit apertures **1840** in combination with lenses **1842** which image slits **1840** onto substrate, s, to form aiming pattern **1838** which in the embodiment of FIGS. **8a-8c** is a line pattern **1838**. Illumination pattern **1830** substantially corresponds to a full frame field of view of image reader **100** designated by box **1850**. The present field of view of optical reader **100** is herein referred to as the “target” of optical reader **100**. Aiming pattern **1838** is in the form of a line that extends horizontally across a center of field of view of image reader **100**. Illumination pattern **1830** may be projected when all of illumination light sources **160c** through **160t** are operated simultaneously. Illumination pattern **1830** may also be projected when a subset of light sources **160c** through **160t** are simultaneously energized. Illumination pattern **1830** may also be projected when only one of light sources **160c** through **160t** is energized such as LED **160s** or LED **160t**. LEDs **160s** and **160t** of imaging module **1802** have a wider projection angle than LEDs **160c** through **160t**. In an optical reader **100** incorporating imaging module **1802, 1802A** illumination assembly **104** includes

LEDs **160a, 160b**, LEDs **160c** through **160t** and slit apertures **1840** in combination with lenses **1842**.

A reader imaging module may be incorporated into one of a hand held housing as shown in FIGS. **9a, 9b** and **9c**. In the embodiment of FIG. **9a**, hand held housing **101** is a gun style housing. In the embodiment of FIG. **9b**, hand held housing **101** supporting imaging module **1802** is in the form factor of a portable data terminal (PDT). In the embodiment of FIG. **9c**, hand held housing **101** supporting imaging module is in the form factor of a mobile telephone, often referred to as a “cell phone.” When optical reader **100** is a cell phone, optical reader **100** is configured to send voice data over GSM/GPRS transceiver **571** to GSM/GPRS network **198** (FIG. **10**) and to receive over GSM/GPRS transceiver **571** voice data from GSM/GPRS network **198**. Further, where optical reader **100** is a cell phone, optical reader **100** may be configured so that an operator inputs telephone numbers via keyboard **508**. The specific imaging module **1802A** described in connection with FIGS. **8a-8c** may be incorporated in the optical reader shown in FIG. **9a** or the optical reader **100** shown in FIG. **9b** or the optical reader **100** shown in FIG. **9c**. However, in the embodiment shown in FIG. **9a**, housing **101** supports and encapsulates imaging module **1802B** an imaging module of construction similar to imaging module **1802A**, except that only two light sources **160** are incorporated into the imaging module. Housing **101** of the reader of FIG. **9b** supports imaging module **1802** which is generically labeled element **1802** to indicate that any one of the specific imager modules described herein, e.g., **1802, 1802A, 1802B, 1802D, 1802E** may be incorporated into an optical reader according to the invention.

Referring to further aspects of optical reader **100**, optical reader **100** may incorporate a graphical user interface (GUI) **3170** enabling selection between various operating modes. With GUI **3170** an operator moves pointer **3172** to a selected icon and clicks on the icon to configure optical reader **100** in accordance with an operating mode associated with the selected icon. Reader **100** may include pointer mover **512** (otherwise termed a navigation matrix) to facilitate movement of the pointer **3172**. Buttons **512B** of pointer mover **512** facilitate selection of an icon of a GUI interface that is supported by incorporating a multitasking operating system (OS) into reader **100** such as WINDOWS CE. GUI **3172** may be developed using various open standard languages as HTML/Java or XML/Java.

In the embodiment of FIG. **9b**, GUI **3170** includes a plurality of virtual selection buttons **3152, 3154, 3156, 3158, 3162, 3164**. Selection of rolling shutter icon **3152** configures reader **100** so that during a next exposure period image sensor array **182** is operated in a rolling shutter mode. Selection of global shutter icon **3154** configures optical reader **100** so that during a next exposure period image sensor array **182** is operated in a global electronic shutter mode.

Selection of decode icon **3162** drives optical reader **100** into an indicia decode mode so that a next time a trigger signal is received, optical reader **100** captures a frame of image data and attempts to decode a bar code symbol or other decodable indicia (e.g., an OCR character) represented therein and outputs a decoded out message to display **504**, or a spaced apart device **150**, as is described with reference to FIG. **10**. Selection of image capture (which may otherwise be referred to a picture taking) icon **3164** configures optical reader **100** so that next time a trigger signal is received, optical reader **100** captures image data and outputs the image data to one or more of a display **504**, a specified memory address, or to a spaced apart device **150** without

attempting to decode decodable indicia therein. Optical reader 100 may also be constructed so that optical reader 100 can be configured in accordance with a selected operating mode by sending to reader 100 a serial command from a spaced apart device, or by the reading of a specially configured programming bar code symbol.

Optical reader 100 is configured so that optical reader 100 receives a trigger signal when manual trigger 216 is manually depressed by an operator. Optical reader 100 may also be configured so that a trigger signal is received by the sensing of an object in the proximity of reader 100 or by the sending of a serial trigger command to reader 100 from a spaced apart device, 150, as shown in FIG. 10.

A flow diagram illustrating operation of optical reader 100 in one embodiment is described with reference to FIGS. 14a, 14b, and 14c. At step 1100 an operator selects between an indicia decode mode and a picture taking mode. At step 1100 an operator may select icon 3162 (FIG. 9b) to drive optical reader 100 into an indicia decode mode, or alternatively icon 3164 to drive optical reader 100 into a digital picture taking mode of operation. These modes may also be selected by sending to reader 100 a serial command from a spaced apart device 150 or by the reading of a programming bar code symbol. If an indicia decode mode of operation is selected, optical reader 100 executes an indicia decode process 1102. If a picture taking mode is selected, optical reader 100 executes picture taking process 1400.

An example of an indicia decode process 1200 is described with reference to FIG. 14b. At step 1202 a trigger signal is received by one of the methods described (depressing trigger 216, object sensing, serial trigger command) to commence a decode process. At step 1203, control circuit 552 of optical reader 100 captures a plurality of "parameter determination" or test frames of image data. The frames of image data captured at step 1203 are not subject to indicia decode processing, but rather, are processed for parameter determination (e.g., exposure, gain, illumination). Alternatively, parameter determining step 1203 may be avoided. For example, control circuit 552 may apply parameters determined from a previous image capture operation rather than determining parameters at step 1203. At step 1204 control circuit 552 obtains a decode frame of image data details of which are explained herein.

For the capturing of frames of image data (i.e., "test" frames and/or frames for use in decoding, picture taking or other processing or storage) control circuit 552 (FIG. 1a) may send an illumination control signal to illumination assembly 104 and various image capture initiation control signals to control/timing circuit 1092 of image sensor chip 1082 (labeled generically to refer to any of the image sensor chips described herein).

Image capture initiation control signals are described in greater detail with reference to FIGS. 15a-15e. For the capturing of image data, control circuit 552 may send to illumination assembly 104 an illumination control timing pulse 350 to energize at least one light source 160 such that illumination pattern 1830 is projected (as shown in FIG. 8d). Control circuit 552 may also send to image sensor IC chip 1082 an exposure control timing pulse 354 and a read out control timing pulse 368, and a reset control timing pulse 370 (that is, control circuit 552 sends appropriate signals to image sensor IC chip 1082 to initiate exposure control timing pulse 354, read out control timing pulse 368 and reset control timing pulse 370).

In one embodiment as shown in FIG. 15a, the exposure control timing pulse 354 begins after and finishes before the illumination control timing pulse 350. The read out control

timing pulse 368 begins at the conclusion of the illumination control timing pulse 350. In another embodiment as shown in FIG. 15b, the illumination control timing pulse 350' begins after and finishes before the exposure control timing pulse 354'. In this embodiment, the read out control timing pulse 368' begins at the conclusion of the exposure control timing pulse 354'. In further embodiments the exposure control timing pulse and the illumination control timing pulse overlap each other while occurring sequentially. In one such embodiment as shown in FIG. 15c, this sequential operation can include the illumination control timing pulse 350" starting, the exposure control timing pulse 354" starting, the illumination control timing signal pulse 350" ending, and then the exposure control timing pulse 354" ending. In this embodiment, the read out control timing pulse 368" begins at the conclusion of the exposure control timing pulse 354". In a further such embodiment as shown in FIG. 15d, the sequential operation can include the exposure control timing pulse 354'" starting, the illumination control timing pulse 350' starting, the exposure control timing pulse 354'" ending, and then the illumination control timing signal pulse 350'" ending. In this embodiment, the read out control timing pulse 368' begins at the conclusion of the illumination control timing signal pulse 350'. Each illumination control timing pulse 350, 350', 350", 350' described herein may comprise a plurality of short duration individual pulses, sometimes referred to as a "strobed" pulse, as is indicated by FIG. 15e.

When exposure control timing pulse 354 is received by an image sensor IC chip and optical reader 100 is configured in a global electronic shutter operating mode, pixels from several rows of image sensor array 182A, 182B, 182C, 182D, 182E, 182F, 182G, 182H are simultaneously exposed to light for the duration of the pulse. That is, when optical reader 100 is configured in an global electronic shutter operating mode, each of several rows of image sensor array 182A, 182B, 182C, 182D, 182E, 182F, 182G, 182H that are subject to image data read out have common exposure periods such that the exposure period for each row of pixels the image sensor array subject to image data read out begins at a common exposure start time and ends at a common exposure stop time. The exposure period for each row of pixels image sensor array 182A, 182B, 182C, 182D, 182E, 182F, 182G, 182H subject to image data read out begins at the leading edge of exposure control timing pulse 354, 354', 354", 354'" and ends at the falling edge of exposure control timing pulse 354, 354', 354", 354'.

When read out control timing pulse 368 is received by image sensor IC chip 1082B, image data is read out from the image sensor array. Image signals corresponding to pixels of the image sensor array are converted into digital form by analog-to-digital converter 1086 and transferred into memory 560 by FPGA 580.

Optical reader 100 may be configured so that at step 1204 when reading out image data, optical reader 100 reads a "windowed frame" of image data. As indicated herein, a windowed frame of image data may be read out by selectively addressing pixels of a desired region of interest or window. A windowed frame of image data read out during frame capture at step 1204 may comprise pixel values corresponding to all or substantially all monochrome pixels 250M of an image sensor array. With further reference to the timing diagrams of FIGS. 15a, 15b, 15c and 15d, a reset control timing pulse 370 for resetting pixels that are not selectively addressed may be coordinated with the exposure control timing pulse 354 for controlling exposure of pixels that are selectively addressed for reading out a windowed

frame of image data. Thus, for reading out a monochrome frame of image data from a hybrid monochrome and color image sensor array, e.g., image sensor array **182A** or image sensor array **182B**, reset control timing pulse **3709** is applied to reset color pixels of the image sensor array **182** while exposure control timing pulse **354** is applied to enable exposure of monochrome pixels of the image sensor array. To facilitate resetting of color pixels of an image sensor array independent of resetting of monochrome pixels, an image sensor array may be configured to include a reset control line grid specifically adapted to enable resetting of color pixels. Applying reset control pulse **370** to drive color pixels into reset while monochrome pixels are being exposed to light can be expected to eliminate electron diffusion cross talk and to reduce cross talk resulting from light rays angularly entering the color pixels during exposure.

When frames are obtained at step **1204**, they are obtained in a form suitable to facilitate indicia decoding such as bar code symbol decoding or OCR decoding. With the windowed frame of image data read out at step **1204** from a hybrid monochrome and color image sensor array **182A**, **182B** including only image data corresponding to monochrome pixels and no image data corresponding to color sensitive pixels **250C**, control circuit **552** at step **1204** may store gray scale values into RAM **560**, each pixel value representing an intensity of light at a particular monochrome pixel of image sensor array **182A**, **182B**. The frame of image data obtained at step **1204** may include e.g., 8 bit gray scale pixel values, 10 bit gray scale pixel values or 12 bit gray scale pixel values. Since numerous legacy bar code decoding and OCR decoding schemes are designed to operate on monochrome gray scale image data or binarized image data derived from gray scale image data, the selective addressing of monochrome pixels **250M** in the capturing of a monochrome image frame yields a frame that is well suited for being subjected to indicia decoding processing. Of course, in certain applications, control circuit **552** at step **1204** may obtain a decode frame of image data including color image data. For example, where decode circuit **1702** is configured to decode color encoded bar code symbols, it is advantageous for control circuit **552** to obtain a decode frame of image data including color image data at step **1204**.

In the execution of step **1204**, control circuit **552** may carry out a plurality of alternative processes in obtaining a decode frame of image data. Referring to the flow diagram of FIG. **14d**, optical reader **100** at step **1204** may simply capture a single windowed frame of image data which has been described herein above. As indicated by process step **1205** of FIG. **14d**, control circuit **552** may carry out process step **1204** by selectively addressing monochrome pixels **250M** of a hybrid monochrome and color image sensor array such as image sensor array **182A** or image sensor array **182B** and reading out image data from monochrome pixels **250M** only; i.e., a windowed frame of image data comprising image data from monochrome pixels **250M** only.

Referring to the flow diagram of FIG. **14e**, the obtaining a decode frame step **1204** may be carried out in the alternative by the execution of steps **1206** and **1207**. At step **1206** optical reader **100** may generate a frame of image data that includes image data corresponding to monochrome pixels **250M** and color sensitive pixels **250C** and at step **1207** image sensor array **182A**, **182B** may convert pixel values of the frame generated at step **1206** into gray scale values. The frame generated at step **1206** may be generated by exposing color and monochrome pixels of image sensor array **182A**, **182B** during a single exposure period, and reading out image

data from both color and monochrome pixels **250M**, **250C** of image sensor array **182A**, **182B** during a single pixel read out period. Alternatively, at step **1206** control circuit **552** of optical reader **100** may combine image data from two different frames such as two successive frames, wherein a first of the captured frame is a windowed frame of image data including image data from color sensitive pixels **250C** only and a second of the frames is a frame of image data including image data read out from monochrome pixels **250M** only.

Referring to the flow diagram of FIG. **14f**, optical reader **100** may also obtain a decode frame at step **1204** by carrying out steps **1208** and step **1209**. At step **1208** optical reader **100** may capture a windowed frame of image data including image data corresponding to monochrome pixels **250M** only and at step **1209** control circuit **552** may interpolate pixel values corresponding to color pixel positions of image sensor array **182A**, **182B** utilizing the monochrome pixel values from the windowed monochrome frame captured at step **1208**. For example, control circuit **552** may capture a gray scale pixel value frame **5202** as illustrated in FIG. **16a** that includes a gray scale pixel value for each monochrome pixel position of the image sensor array **182A**, **182B**. Optical reader **100** may interpolate a monochrome pixel value for any "missing pixel" color pixel position of the frame **5202**. Referring to frame **5202**, frame **5202** is a gray scale frame of image data captured by selecting reading out image data from an image sensor array **182B** constructed in accordance with FIGS. **4a-7b** (Period=2). Pixel positions P_{11} , P_{31} , P_{51} , P_{12} , P_{22} , P_{32} , P_{42} , P_{52} , P_{13} , P_{33} , P_{63} . . . are pixel positions corresponding to monochrome pixels **250M** of image sensor array **182** for which individual frame image data has been read out. Pixel positions P_{21} , P_{41} , P_{23} , P_{43} , . . . are missing pixel positions corresponding to color sensitive pixels, **250C** of image sensor array **182B**. Referring to the frame of image data represented at FIG. **16a** an optical reader **100** may calculate a gray scale pixel value for color pixel positions, e.g., position P_{23} , by averaging the gray scale values for each pixel position that is adjacent to pixel position P_{23} and each pixel position that is corner adjacent to color pixel position P_{23} . For example, referring to the frame represented in FIG. **16a**, a gray scale value for color pixel position P_{23} can be interpolated by averaging pixel values of pixel positions P_{12} , P_{22} , P_{32} , P_{13} , P_{33} , P_{14} , P_{24} , P_{34} . A pixel value for "missing pixel" position P_{23} can also be interpolated utilizing more than 8 neighboring pixel positions. Also, corner adjacent pixels may be weighted less than side, top or bottom adjacent pixels during averaging. In one simple averaging method, only four surrounding pixels are averaged; namely, the top and bottom adjacent pixels and the two side adjacent pixels adjacent to the pixel position for which a gray scale value is being interpolated. In a still further interpolation method, only two pixels are used for averaging; namely either the two side adjacent pixels adjacent to the pixel position being interpolated or the top and bottom adjacent pixels. A two-dimensional image representation of a linear bar code symbol can be expected to have several consecutive pixel positions along a column with similar gray scale values, if the representation of the symbol is oriented with 0° or 180° angle of rotation (i.e., the symbol is right side up or upside down). If the symbol representation has a 90° or 280° angle of rotation, several consecutive pixel positions along rows of pixel positions can be expected to have similar valued gray scale values. Accordingly, it can be seen that interpolating pixel values of adjacent pixel position values running in the direction of bars in a symbol representation

yields truer edge information than utilizing all surrounding pixel positions for interpolation.

In one method of the invention, the correlation between a pair of horizontally oriented scan lines is calculated along with a correlation between a pair of vertically oriented scan lines. The two correlation measurements are then compared. If row scan lines are more closely correlated, column adjacent pixels are selected for interpolation. If column scan lines are more closely correlated, row adjacent pixels are selected for interpolation. An exemplary set of code for calculating a first derivative correlation for a pair of scan lines (horizontal or vertical) is presented by Table 1.

TABLE 1

Exemplary Code For Performing First Derivative Correlation Calculation

```
%OneDcorelate: correlates two 1D 1st derivative signals to report the
%correlation
%input a,b: 1D array
%output c: 1st derivative correlation
function c=OneDcorelate(a,b)
% "diff" is the first derivative calculation.
%for an input array a=[ai]i=1n-1 then diff(a)=[ai - ai+1]i=1n-1
da=diff(double(a));
db=diff(double(b));
n=length(da);
c=0;
for i=1:n
    c=c+da(i)*db(i);
end
```

[End Table 1]

A set of code for interpolating missing color pixel position values by one of three methods (simple averaging, first derivative correlation, and simple correlations) wherein "M-set" refers to the monochrome set of pixels is presented in Table 2.

TABLE 2

Exemplary Code For Interpolating Missing Pixels
Corresponding To Color Pixel Positions

```
% MsetInterpolation: interpolates missing M-set pixels
%input I_Mset: M-set image
%input method: 1:first derivative correlation; 2: simple correlation; 3:
%simple averaging
%input p: sample period
%output Im: interpolated monochrome image
function Im=MsetInterpolation(I_Mset,method,p)
Isz=size(I_Mset);
%M-set topology
%
% M M M M M M M M M M
% M x M x M x M x M
% M M M M M M M M M M
% M x M x M x M x M
%(M M M M M M M M M M)
% v
Im=double(I_Mset);
m=Isz(1);
n=Isz(2);
%correlated averaging
for i=p:p:m
    for j=p:p:n
        if i+1 <=m & j+1 <=n
            if method == 2
                %simple correlation
                if abs(Im(i-1,j)-Im(i+1,j)) < abs(Im(i,j-1)-Im(i,j+1))
                    Im(i,j)=(Im(i-1,j)+Im(i+1,j))/2;
                else
                    Im(i,j)=(Im(i,j-1)+Im(i,j+1))/2;
                end
            end
```

TABLE 2-continued

Exemplary Code For Interpolating Missing Pixels
Corresponding To Color Pixel Positions

```
5 else if method == 1
    %first derivative correlation
    if OneDcorelate(Im(i-1,j-1:j+1),Im(i+1,j-1:j+1)) >
OneDcorelate(Im(i-1:i+1,j-1),Im(i-1:i+1,j+1))
        Im(i,j)=(Im(i-1,j)+Im(i+1,j))/2;
    else
10 Im(i,j)=(Im(i,j-1)+Im(i,j+1))/2;
    end
    else %method==3
        %simple averaging
        Im(i,j)=(Im(i-1,j)+Im(i+1,j)+Im(i,j-1)+Im(i,j+1))/4;
    end
15 else if i+1 <=m & j+1 > n
        Im(i,j)=(Im(i-1,j)+Im(i+1,j))/2;
    else if i+1 > m & j+1 <=n
        Im(i,j)=(Im(i,j-1)+Im(i,j+1))/2;
    else if i+1 > m & j+1 > n
        Im(i,j)=(Im(i-1,j)+Im(i,j-1))/2;
    end
20 end
end
Im=uint8(Im);
```

[End Table 2]

At step 1210, optical reader 100 transfers the frame of image data obtained at step 1204, to an indicia decode circuit 1702 which may be a bar code symbol decoding circuit or autodiscrimination circuit 1704 including an indicia decode circuit 1702. In one embodiment, decode circuit 1702 decodes 1D and 2D bar code symbols and OCR characters. Autodiscrimination circuit 1704 may decode 1D and 2D bar code symbols and OCR characters (decodable indicia) and automatically discriminate between decodable indicia and handwritten characters. In the event that autodiscrimination circuit 1704 recognizes the presence of handwritten character information, autodiscrimination circuit 1704 automatically outputs to display 504 and/or a spaced apart device 150 image data representing the handwritten character image data. Further details of indicia decode circuit 1702 and autodiscrimination circuit 1704 are described in copending U.S. patent application Ser. No. 11/077,975, filed Mar. 11, 2005, incorporated by reference and U.S. application Ser. No. 10/958,779, filed Oct. 5, 2004, also incorporated herein by reference.

In general, indicia decoding accuracy is expected to increase with an increase in the percentage of monochrome pixels of image sensor array 182A, 182B. With image sensor array 182B having a period of P=2, every other row of pixels of image sensor array 182B are all monochrome pixels. Thus, horizontal scan lines can be launched through horizontal rows of pixel values of a frame of image data obtained utilizing a P=2 image sensor array 182B during attempts to decode a linear bar code symbol without substantial reduction in performance relative to a frame obtained utilizing an all monochrome pixel image sensor array. For decoding linear bar code symbols, control circuit 552 may read image data along scan lines, such as scan lines defined by a horizontal row of pixel positions to determine the relative widths of bars and spaces of a symbol and then decode the symbol through table lookup to determine a set of decoded character data corresponding to the bar space information.

At step 1212 control circuit 552 receives a decoded output message from decode circuit 1702 or autodiscrimination circuit 1704. The message received by control circuit 552 at step 1212 may be e.g., a decoded bar code message or a set of decoded OCR characters. At step 1214 optical reader 100

outputs a decoded out message. At step 1214 control circuit 552 may send decoded out bar code data and/or decoded OCR data to display 504 or to a spaced apart device 150 or to a data storage memory location of reader 100, or system 145 as described in FIG. 10.

Examples of spaced apart devices 150 which may be in communication with optical reader 100 are shown and described in connection with FIG. 10. Optical reader 100 may be part of a system 145 and may be included in a local area network (LAN) 170 which comprises, in addition to reader 100, such spaced apart devices as other portable readers 100', 100", network access point 174, personal computers 172 and central server 176 that are spaced apart from hand held housing 101 of reader 100, all of which are connected together via backbone 177. Server 176 in turn is in communication with a variety of additional spaced apart devices 150 that are spaced apart from hand held housing 101 of reader 100 and which through server 176 are in communication with optical reader 100. Server 176 may be connected via gateways 179, 180 and network 181 to a first distant remote local area network 185 located miles to thousands of miles away from local area network 170 and a second distant local area network 2170 also located miles to thousands of miles away from local area network. Network 170 may be located at a supplier's warehouse. Network 2170 may be located at a delivery destination; and network 185 may be located at a data processing/data archiving facility. Network 185 can be configured to assemble, store and maintain in server 184 various web pages accessible with use of optical reader 100, that summarize data that has been collected by various optical readers 100, 100', 100", 100R. Server 176 may alternatively or redundantly be connected to remote network 185 via private communication line 190. IP network 181 may be the Internet or a virtual private network (VPN). Remote LAN 185 may include a personal computer 186 and a remote server 184 connected via backbone 191. Remote LAN 185 may also include a wireless communication access point 193. Remote LAN 185 may also include a personal data assistant (PDA) 189. Remote LAN 2170 may include a server 2176, connected to IP network 181 via gateway 2179, backbone 2177, access point 2174, PC 2172, and optical reader 100, 100R. System 145 may be configured so that a display equipped device, e.g., device 100', 172, 186, 189 automatically displays data, such as decoded out bar code message data of a visual display color image frame of image data, received from optical reader 100 on its associated display 1504 when receiving that data.

All of the steps of process 1200 are carried out automatically in response to the receipt of a trigger signal. The steps of process 1200 continue automatically until a stop condition is satisfied. A stop condition may be e.g., the receipt of a trigger stop signal as may be generated by release of trigger 216 or the successful decoding of a predetermined number of bar code symbols. As indicated by return line 1211 of FIG. 14b, control circuit 552 may repeatedly attempt to obtain image data and attempt to decode decodable indicia therein until a stop condition is satisfied.

Interpolating monochrome pixel values for "missing pixels" pixel positions is particularly advantageous where a hybrid monochrome and color image sensor array according to the invention includes a high number of color sensitive pixels distributed at spaced apart pixel positions throughout image sensor array. In other instances as alluded to previously in connection with the flow diagram of FIG. 14b, control circuit 552 may obtain a decode frame of image data at step 1204 that is suitable for transferring to decode circuit 1702 by simply reading from an image sensor array image

data from monochrome pixels 250M without interpolation of any pixel values at "missing pixel" pixel positions where an image sensor array of reader 100 is constructed in accordance with image sensor array 182A, and monochrome pixels 250M form a complete checkerboard pattern, (there are no "missing" monochrome pixels positions in the MxN matrix of monochrome pixels within image sensor array 182A). Accordingly, where optical reader 100 includes image sensor 182A, the decode frame of image data at step 1204 is advantageously obtained by reading out from image sensor array 182A image data from monochrome pixels 250M without interpolation of any further monochrome pixel values.

It may also be useful to obtain a decode frame of image data at step 1204 without interpolation of monochrome pixel values where optical reader 100 includes a linear bar code symbol optimized image sensor array 182B of one of the versions described in connection with FIGS. 5g-5j. In the versions of image sensor array 182B shown and described in connection with FIGS. 5g-5j, image sensor array 182B includes at least one "zone" of monochrome pixels 2500M and at least one "zone" of color sensitive pixels 2500C. Monochrome zone of pixels 2500M of a linear symbol decoding optimized version of image sensor array 182B generally comprises an elongated line of monochrome of pixels 250M having a minor dimension of one to a limited number of rows of pixels (which may be diagonal rows). Where optical reader 100 includes a linear symbol optimized version of image sensor array 182B a reduced area decode frame of image data at step 1204 without any "missing pixel" pixel positions can be obtained by selectively addressing pixels of monochrome zone 2500M and selectively reading out of image data from the pixels of monochrome zone 2500M without reading any image data from the pixels of color sensitive zone of pixels 2500C. More specifically, where optical reader 100 comprises a linear symbol optimized version of image sensor array 182B, control circuit 552 at step 1204 may obtain a reduced area monochrome frame of image data at step 1204 (FIG. 14b) and then transfer the reduced area monochrome frame of image data to decode circuit 1702 at step 1210. A reduced area frame of image data is further explained with reference to FIG. 11 illustrating an application where an optical reader 100 is utilized to collect decoded bar code data and image data from a parcel 1260 carrying various bar code symbols, e. g., linear bar code symbol 1266 and two-dimensional bar code symbol 1270. A full area frame of image data that may be obtained by optical reader 100 represents the scene area indicated by rectangular border 1276 of FIG. 11. Where image data from all pixels of image sensor array 182B are read out, a full area frame of image data is obtained. When optical reader 100 obtains a reduced area frame of image data, a reduced area frame of image data representing the reduced scene area as indicated by dashed-in border 1278 may be obtained. In the example of FIG. 11, optical reader 100 may incorporate one of the linear symbol optimized image sensor arrays 182B as shown in FIGS. 5g and 5h. A reduced area frame of image data representing the reduced scene area 1278 may be obtained by reading out image data from monochrome zone of thin center line monochrome zone 2500M of image sensor array 182B according to one of the versions of FIGS. 5g and 5h. It is seen with reference to FIG. 11 that when optical reader 100 obtains a reduced area frame of image data at step 1204 representing the reduced scene area 1278, the reduced area frame of image data, though reduced, can be of sufficient size to include a representation of linear bar code symbol 1266 carried by

parcel 1260. Imaging module 1802 such as module 1802A (FIG. 8a) of reader 100 can be constructed so that aiming pattern 1838 (FIG. 8d) is projected onto scene area 1278 at expected reading angles, while aiming light sources 160a, 160b, and remaining light sources 160c-160t are energized simultaneously during the time that pixels of zone 2500M are exposed for read out of image data from zone 2500M. Simultaneously projecting aiming pattern 1838 and illumination pattern 1830 onto scene area 1278 improves the signal strength of image data corresponding to pixels of zone 2500M. After receiving the thin line reduced area frame of image data at step 1210, decode circuit 1702 may process the thin line reduced area decode frame of image data to decode linear bar code symbol 1266 by calculating the bar space widths of the bars and spaces of linear bar code symbol 1266 and then determining the characters of the symbol through table lookup. In a further aspect, optical reader 100 may be configured so that aiming pattern 1838 (FIG. 8d) is projected horizontally at a center of a field of view 1276 of optical reader 100 to coincide with area 1278 represented by the reduced area image obtained at step 1204 to aid an operator in obtaining an image that includes a representation of linear bar code symbol 1266. The frame rate of optical reader 100 when obtaining the reduced area decode frame of image data at step 1204 may be significantly reduced relative to the frame rate of optical reader 100 when obtaining a full frame of image data. Accordingly, a method of the invention where optical reader 100 at step 1204 obtains a reduced area frame of image data which is transferred to decode circuit 1702 is optimized for fast (“snappy”) decoding. As has been described herein, color sensitive pixels 250C may be set to reset while monochrome pixels 250M are exposed for selective read out of image data from monochrome pixels 250M.

With further reference to the application view of FIG. 11, it is seen that the reduced area frame of image data representing scene area 1278 may not include a complete representation of linear bar code symbol 1266 and it is further seen that parcel 1260 may include or carry additional bar code symbols such as two-dimensional bar code symbol 1270 that is part of postal area 1268 of parcel 1260. According to the invention in another aspect, optical reader 100 can be configured so that where indicia decode circuit 1702 cannot successfully decode a bar code symbol via processing of a reduced area frame of image data or where control circuit 552 is programmed to search and decode multiple bar code symbols, control circuit 552 executes return line (FIG. 14b) to re-execute the obtaining of a decode frame of image data at step 1204. However, when control circuit 552 executes step 1204 the second time, control circuit 552 captures a frame of image data that represents a scene area that is larger than the scene area represented by the frame obtained during the first execution of step 1204. The decode frame of image data obtained by a second execution of step 1204 may be a full area image data frame representing the full field of view of optical reader 100 indicated by dashed-in border 1276 of FIG. 11. Where color zones 2500C of image sensor array 182B are distributed in a Bayer pattern, control circuit 552 during the second execution of obtain step 1204 may selectively read out image data from the green pixels of color sensitive zones of image sensor array of 2500C and interpolate green pixel values at non-green pixel positions utilizing the green pixel values so that the decode frame of image data obtained at step 1204 includes all green pixel values. Further, the missing pixel positions corresponding to monochrome zone 2500M can be filled in utilizing the image data obtained

during the previous execution of step 1204 as scaled based on a relationship between the color scale values of pixels corresponding to zone 2500M and the color scale values of pixels surrounding zone 2500M. At step 1210, larger area green image data is transferred to indicia decode circuit 1702. Indicia decode circuit 1702 may attempt to decode linear bar code symbol 1266 and all other bar code symbols such as two-dimensional bar code symbol 1270 that may be represented in the image obtained during the second execution of step 1204. With reference to the application view of FIG. 11, optical reader 100 incorporating a linear symbol decode optimized to image sensor array 182B may attempt to decode linear symbol 1266 utilizing small area image representing area 1278 and then subsequently attempt to decode a two-dimensional bar code symbol, e.g., symbol 1270, utilizing a larger area frame of image data representing scene area 1276. It will be seen that the method described where control circuit 552 obtains a reduced area frame of image data, attempts to decode, then subsequently obtains a larger frame of image data and attempts to decode utilizing the larger image may be practiced utilizing an “all monochrome” image sensor array 182F as shown and described in connection with FIG. 17b. Where optical reader 100 incorporates an all monochrome image sensor array 182F as shown in FIG. 17b, it is particularly useful to set monochrome pixels 250M to reset that are not being selected for read out of a reduced area decode frame of image data at step 1204 during exposure periods for selected monochrome pixels 250M that are being selectively addressed for image data read out.

Monochrome pixels 250M transmit more light than color sensitive pixels 250C. Therefore, resetting monochrome pixels 250M that are not selectively addressed and which are adjacent to a region of interest during an exposure period can be expected to have a greater benefit in terms of improving the overall signal to noise ratio of reader 100 than resetting color sensitive pixels 250C that are adjacent to a region of interest during an exposure period.

With still further reference to the application view of FIG. 11, it may be advantageous to utilize optical reader 100 to obtain a visual display color frame of image data representing parcel 1260. For example, parcel 1260 may include a damaged area 1272. Obtaining a visual display color frame of image data corresponding to parcel 1260 creates a record documenting parcel damage. Referring to the application view of FIG. 12a, different optical readers 100 and 100R at different locations A and B located miles apart along a delivery route may be utilized to document physical transformations of parcel 1260 when parcel 1260 is carried along a delivery route. Optical reader 100 at location A including LAN 170 (FIG. 10) may be operated to obtain a visual display color frame of image data of parcel 1260 when parcel 1260 is located at location A. Further, the color frame may automatically be transferred to remote server 184 (FIG. 10) having a database 187 of color frames of image data that are indexed by a parcel identifier decoded in a parcel bar code symbol 1266 which identifier is also transmitted to remote server 184 automatically when optical reader 100 reads bar code symbol 1266. At location B remote optical reader 100, 100R (FIG. 10) may be utilized to again decode bar code symbol 1266 and capture visual display color frame of image data representing parcel 1266 and automatically transfer the parcel identifier corresponding to bar code 1266 and the color frame of image data to remote server 184. With reference to the application view of FIG. 12a the color frame of image data transmitted to remote server 184 from location B will include a representation of damaged area 1272 that is

not included in the color frame of image data transmitted to remote server 184 from location A. Accordingly, a person (for example, at PC 172 viewing web pages of server 184) reviewing the parcel identifier indexed color frame data of database 187 can determine that the damage to parcel 1260 occurred during the time that the parcel was delivered from location A to location B. Referring to FIG. 12b, optical reader 100 can also be utilized to take color pictures of a delivery vehicle 1282 that carried parcel 1260 from location A to location B. In the example of FIG. 12b, a picture being taken by optical reader 100 has the field of view indicated by rectangle 1286. The field of view encompasses parcel 1260, and delivery vehicle 1282, including a license plate 1284. Trigger 216 can be actuated a first time to decode bar code symbols 1266, 1267 and then an additional time or times to have a picture of parcel 1260 and/or vehicle 1272 including a picture of license plate 1284. The decoded bar code data and multiple color frames of image data may be associated with one another into a single transaction data set, and then via a packet based transmission scheme, the transaction data set may be sent to remote server 184, which may organize the data into viewable web pages viewable at PC 172. Optical reader 100, which may be incorporated in hand held housing 101, can be configured so that all of the data of the transaction data set is sent to remote server 184 in response to a single command input to optical reader 100 via a user interface of reader 100 (e.g., 3170). Further aspects of optical reader 100 operating in a picture taking mode of operation are described with reference to the flow diagrams of FIGS. 14c, 14g and 14h.

Referring again to the flow diagram of FIG. 14a, a digital picture taking process 1400 is executed when optical reader 100 is configured to operate in a picture taking mode of operation. At step 1100, a picture taking mode of operation may be selected, e.g., by clicking on "image capture" icon 3164 (FIG. 9b) and at step 1104 picture taking process 1400 is executed.

Referring to the steps of picture taking process 1400, optical reader 100 at step 1402 receives a trigger signal as may be generated e.g., by depression of a manual trigger an object in the proximity of reader 100 being sensed or receipt of a serial command. At step 1403 control circuit 552 captures a plurality of "test" or parameter determination frames of image data. The frames of image data captured at step 1403 are not output for visual display; but rather are processed in order to determine operational parameters (exposure setting, gain illumination). Alternatively, step 1404 can be avoided and control circuit 552 can instead load operational parameters that were derived during a past image capture operation. At step 1404 control circuit 552 obtains a "visual display" image frame of image data. A visual display color frame of image data is one that is generated for visual display on a display and may include three color scale values for each pixel position of the plurality of pixel positions of the frame. A visual display frame after being obtained is sent to a display for visual display of an image or to a memory location for future display. In the embodiment of FIG. 14c, the image data obtained at step 1404 is not transferred to decode circuit 1702.

An image captured as part of obtaining at step 1404 may be one that is captured in accordance with the timing diagrams of FIGS. 15a-15e. In an alternative embodiment, the control signals input into image sensor IC chip 1082 for the capture of a frame of image data may not include illumination control timing pulse e.g., pulse 350. In many applications an object subject to image capture by optical

reader 100 during a picture taking mode will be a long range image (an object will be subject to image capture is one that is one to several feet from image reader). Light from light sources 160 may have little affect on an image captured that corresponds to a long range object; thus, optical reader 100, in one embodiment may not send an illumination control timing pulse at step 1404.

However, depending on the application, it may be desirable to increase the illumination intensity of optical reader 100 during capture of color image data relative to the intensity during capture of monochrome image data to compensate for the signal reduction affect of color filter elements 260R, 260G, 260B, 260M, 260C. In a further aspect, optical reader 100 can have a plurality of operator selectable configuration settings. Optical reader 100 can be configured so that activation of button 3150 toggles through a sequence of options one of which may be selected by actuation of a key of keyboard 508. As shown by Table 3, where e=exposure, g=gain, and i=illumination intensity, a selection of a configuration setting can result in a differentiation between the imaging parameters of reader 100 during read out of monochrome image data at step 1204 and the imaging parameters of reader 100 during read out of color image data at step 1404. Configuration setting 1 is a base line setting wherein there is no differentiation between monochrome read out and color image data read out imaging parameters. Configuration setting 2 has been described above. With configuration setting 2, there is no illumination during read out of color image data at step 1404. Configuration setting 3 has also been described above. With configuration setting 3, illumination intensity is increased for read out of color image data. With configuration setting 4, illumination intensity for read out of monochrome image data can be increased. For example, as described herein, illumination pattern 1830 and aiming pattern 1838 can be projected simultaneously during read out of monochrome image data corresponding to a monochrome zone 2500M of pixels. With configuration setting 5, exposure time is boosted for read out of color image data and with configuration setting 6, gain is boosted for read out of color image data. Configuration setting 3 is highly useful where optical reader 100 includes a long distance flash illumination light source 160, 160X or where optical reader 100 is used for picture taking at close range.

TABLE 3

Configuration	Imaging Parameters When Reading Out Monochrome Image Data At Decode Frame Obtain Step 1204	Imaging Parameters When Reading Out Color Image Data At Visual Display Obtain Step 1404
1	$e = e_0$ $g = g_0$ $i = i_0$	$e = e_0$ $g = g_0$ $i = i_0$
2	$e = e_0$ $g = g_0$ $i = i_0$	$e = e_0$ $g = g_0$ $i = 0$ (Illumination Off)
3	$e = e_0$ $g = g_0$ $i = i_0$	$e = e_0$ $g = g_0$ $i = i_1, i_1 > i_0$
4	$e = e_0$ $g = g_0$ $i = i_2, i_2 > i_0$	$e = e_0$ $g = g_0$ $i = i_0$
5	$e = e_0$ $g = g_0$ $i = i_0$	$e = e_1, e_1 > e_0$ $g = g_0$ $i = i_0$
6	$e = e_0$ $g = g_0$ $i = i_0$	$e = e_0$ $g = g_1, g_1 > g_0$ $i = i_0$

In executing the obtaining visual display color frame of image data step **1404**, optical reader **100** may carry out a variety of alternative processes. With reference to the flow diagram of FIG. **14g**, a process is described wherein optical reader **100** may obtain a visual display color frame of image data utilizing image data read out from color sensitive pixels **250C** only. With reference to the flow diagram of FIG. **14h**, a process is described wherein control circuit **552** obtains a visual display color frame of image data utilizing image data derived by reading out of image data from both monochrome pixels and color sensitive pixels of image sensor array **182**.

Referring to the flow diagram of FIG. **14g**, control circuit **552** at step **1405** captures a windowed frame of image data by selectively addressing color pixels **250C** and by selectively reading out image data from color pixels **250C** of image sensor array **182A**, **182B**. As explained previously herein, image sensor array **182A**, **182B** may include a separate reset control grid for resetting monochrome pixels **250M** independent of color sensitive pixels **250C**. At step **1405** while color sensitive pixels are exposed for read out of image data, monochrome pixels **250M** may be reset with use of a reset control timing pulse **370**, **370'**, **370"**, **370'''** (FIGS. **15a-15d**). Coordinating a reset control timing pulse **370**, **370'**, **370"**, **370'''** for resetting monochrome pixels with an exposure control timing pulse **354**, **354'**, **354"**, **354'''** for controlling exposure of color sensitive pixels **250**, **250C** reduces cross talk resulting from light rays entering monochrome pixels **250M**, i.e., by eliminating electron diffusion cross talk and by reducing cross talk attributable to light rays angularly penetrating through monochrome **250M**.

At step **1406**, optical reader **100** automatically transfers the color filter array image data frame captured at step **1405** to a demosaicing circuit **1706** (FIG. **1e**). Taking as an input a color filter array image data frame, demosaicing circuit **1706** outputs a visual display color frame of image data. Where display **504** is a color display configured to receive red, green and blue (RGB) signals for each pixel of display **504**, demosaicing circuit **1706** at step **1406** may generate RGB color scale values for each pixel of display **504** so that a frame output by demosaicing circuit **1706** is compatible with display **504**. The color scale values may comprise e.g., 8 bits, 10 bits, or 12 bits of data. At step **1407**, optical reader **100** receives a visual display color frame of image data from demosaicing circuit **1706**.

A particular example of optical reader **100** executing step **1404** is described with reference to FIG. **16b**. At step **1406** where optical reader **100** includes a hybrid monochrome color image sensor array **182A**, **182B** including a Bayer pattern color filter array as shown in FIG. **2c** and FIG. **5a**, optical reader **100** may read out an RGB Bayer pattern frame of image data as shown in FIG. **16b**. Where a reader image sensor array is provided by image sensor array **182B** including a 1280×1024, array of pixels, with a 320×256 subset array (P=4) of color sensitive pixels **250**, **250C** (P=4) dispersed in array **182B** optical reader **100** at step **1405** captures a 320×256 Bayer pattern of pixels. Demosaicing circuit **170** processes the Bayer pattern frame **1502** as shown in FIG. **16b** to output a visual display color frame of image data including a 320×256 color image, wherein each pixel of the frame includes a red color scale value, a green color scale value, and a blue color scale value. In such an embodiment, demosaicing circuit **1706**, for each pixel of the Bayer pattern color filter array image data frame **5204**, interpolates red, green, and blue values. Referring to frame **5204** shown in FIG. **16b**, optical reader **100** determines a red value for red pixel position P_{32} simply by reading the color scale value of

pixel position P_{32} . Optical reader **100** determines a green value for red pixel P_{32} by averaging the values of green pixel positions P_{31} , P_{22} , P_{42} and P_{33} . Optical reader **100** may interpolate a blue value for red pixel position P_{32} by averaging the values of blue pixel positions P_{14} , P_{41} , P_{23} , P_{43} . It will be seen that red, green, and blue values can be determined for each pixel position interpolating the pixel values as necessary. With increased processing speeds, it is possible to utilize dozens or more surrounding pixel values for interpolation of a red, green, or blue pixel for each pixel position.

In another aspect of the invention, the accuracy with which color scale values for each pixel position may be interpolated can be enhanced by utilizing monochrome pixel values in the color scale value interpolation process. Referring to red pixel position P_{32} of frame **5204**, it has been described that color scale values at green pixel positions P_{31} , P_{22} , P_{42} , P_{33} may be averaged for interpolating a green color scale value at pixel position P_{32} . In another method, monochrome pixel values at positions P_{33} , P_{22} , P_{42} , P_{33} may be utilized for enhancing the interpolation of a green pixel value at position P_{32} . The monochrome pixel values at positions P_{33} , P_{22} , P_{42} , P_{33} may be interpolated from monochrome pixel values by one of the monochrome pixel interpolation methods described herein. Then, the color scale value at each pixel position, P_{32} , P_{22} , P_{42} , P_{33} may be offset by a value, Delta, equal to the difference between the interpolated monochrome pixel values at the position being interpolated and the monochrome pixel value at the position contributing to the interpolation calculation. Thus, a green color scale value at position P_{32} may be calculated according to Eq. A.

$$G(P_{32}) = \frac{[G(P_{31}) + \text{Delta}_{31}] + [G(P_{22}) + \text{Delta}_{22}] + [G(P_{42}) + \text{Delta}_{42}] + [G(P_{33}) + \text{Delta}_{33}]}{4} \quad (\text{Eq. A})$$

Where

$$\text{Delta}_{31} = M(P_{32}) - M(P_{31}),$$

$$\text{Delta}_{22} = M(P_{32}) - M(P_{22}),$$

$$\text{Delta}_{42} = M(P_{32}) - M(P_{42}),$$

$$\text{Delta}_{33} = M(P_{32}) - M(P_{33}).$$

Similarly, a blue color scale value at position P_{42} may be interpolated according to the formula of Equation B.

$$B(P_{42}) = \frac{[B(P_{41}) + \text{Delta}_{41}] + [B(P_{43}) + \text{Delta}_{43}]}{2} \quad (\text{Eq. 1B})$$

Where

$$\text{Delta}_{41} = M(P_{42}) - M(P_{41})$$

and

$$\text{Delta}_{43} = M(P_{42}) - M(P_{43}).$$

An exemplary algorithm for interpolating a color scale value at a color pixel position utilizing monochrome pixel values is presented in Table 4 where "C-set" refers to color pixel values and "M-set" refers to monochrome pixel values.

TABLE 4

Algorithm For Interpolating Color Scale Values Utilizing Monochrome Image Data	
1)	For each color pixel C for interpolation, select the missing color neighborhood C-set pixel values C_i and select the corresponding neighborhood M-set pixel values M_i . Select corresponding M-set pixel value M to color pixel C.
2)	let $C = 0$
3)	for $i = 1$ to n where n is the number of neighborhood pixel C_i
4)	$C = C + C_i + M - M_i$
5)	end
6)	$C = C/n$

Regarding step 1, it is noted that there will normally be two neighborhood color or "C-set" pixels where blue or red values are interpolated at a green pixel position, and in other cases four neighborhood color pixels.

Another particular example of optical reader 100 executing steps 1405 and 1406 is explained with reference to FIG. 16c. Where a reader image sensor array is provided by image sensor array 182B including 1280×1024 array of pixels, and a period $P=4$ of color sensitive pixels formed with a Cyan-Magenta (Cy-Mg, or "CM") color filter array as shown in FIG. 5b, optical reader 100 at step 1405 reads out a color filter array image data frame 5206 as shown in FIG. 16c. Color filter array image data frame 5206 includes a 320×256 pattern of Cy-Mg pixel values. Demosaicing circuit 1706 may process image data frame 5206 into a visual display frame such as a visual display color frame of image data where each pixel position of frame 5206 is represented by a combination of red, green and blue values. In processing the Cy-Mg visual display color frame 5206 into a frame of image data including red, green, and blue values for each pixel position, optical reader 100 may first calculate white, cyan and magenta values for each pixel position of frame 5206. Where an original pixel position such as pixel position P_{53} (FIG. 16c) is a cyan pixel, the cyan value is determined by directly reading the pixel value of the cyan pixel. A magenta value for cyan pixel at position P_{53} is calculated by interpolation utilizing the magenta values of surrounding pixel positions of magenta pixels such as positions P_{52} , P_{43} , P_{63} , P_{54} (FIG. 16c). A white value for cyan pixel at position P_{35} is calculated by interpolation using pixel values from monochrome pixel positions that surround cyan pixel P_{53} . Referring to FIG. 5b, a supplemental frame including monochrome pixel values may be captured, e.g., successively before or after frame 5206 is captured for purposes of interpolating a white value for each color pixel of the color filter array windowed frame 5206. Alternatively, the color filter array frame 5206 captured at step 1405 may include monochrome pixel image data for purposes of interpolating a white value for each color pixel value. When white, cyan and magenta values are calculated for each pixel of frame 5206, the white, cyan, and magenta values are readily converted into red, green, and blue values. Alternatively, display 504 can be configured to be responsive to white, cyan and magenta signals for each pixel of display 504. A set of transform equations for transforming a set of white, cyan and magenta values for a given pixel of a frame into a set of red, green and blue values for that pixel is given as follows.

$$R=W-Cy \quad (\text{Eq. 1})$$

$$G=Mg+Cy-W \quad (\text{Eq. 2})$$

$$B=W-Mg \quad (\text{Eq. 3})$$

In the process described relative to the flow diagram of FIG. 14g, an original color filter array frame is processed

into a visual display color frame of image data of reduced spatial resolution (a reduced spatial resolution 320×256 visual display color frame of image data may be produced using a hybrid monochrome and color image sensor array having a 1280×1024 pixel resolution). With reference to FIG. 14h, a process for producing a high spatial resolution visual display color image is described. In the process described relative to the flow diagram of FIG. 14h, optical reader 100 utilizes image data from both monochrome pixels 250M and color pixels 250C from a hybrid monochrome and color image sensor array such as image sensor array 182A or image sensor array 182B in the generation of a visual display color image having spatial resolution equal to or on the order of the overall pixel resolution of the image sensor array.

At step 1408 control circuit 552 captures a color filter array image data frame by selectively addressing color pixels 250C of an image sensor array and selectively reading out image data from color sensitive pixels 250M. The frame of image data captured at step 1408 is a windowed frame of image data. For reduction of cross talk resulting from light entering monochrome pixels 250M, the monochrome pixels of image sensor array 182A, 182B may be reset using reset control timing pulse 370, 370', 370'', 370''' at the time that exposure control timing pulse 354, 354', 354'', 354''' is applied to expose color pixels for capture of a color filter pattern image frame at step 1408.

At step 1409 control circuit 552 captures a monochrome frame of image data by selectively addressing monochrome pixels 250M of array 182A, 182B and selectively reading out image data from monochrome 280M pixels. The frame of image data captured at step 1409 is a windowed frame of image data. For reduction of cross-talk resulting from light entering color pixels 250C the color pixels of image sensor array 182 may be reset using reset control timing pulse 370, 370', 370'', 370''' at the time that exposure control timing pulse 354, 354', 354'', 354''' is applied to expose monochrome pixels for capture of a monochrome, typically gray scale or binarized image frame at step 1409.

At step 1410 control circuit 552 transfers both the color filter array frame captured at step 1408 and the monochrome image frame captured at step 1409 to fusion circuit 1708. Fusion circuit 1708 takes as inputs the color filter array image data frame and the monochrome image data frame and processes them into a high resolution visual display color frame of image data.

Referring to FIG. 14i, an example of the process 1440 which may be executed by fusion circuit 1708 (FIG. 1e) to process a combination of monochrome image data and color image data into a visual display color frame of image data is described. As explained with reference to FIG. 1e, fusion circuit 1708 may be physically embodied by the combination of a control circuit provided by a CPU 552 operating in combination with memory 566 that stores an executable program. The specific process described with reference to FIG. 14i is executed utilizing an optical reader 100 including substantially uniform dimensional pixel image sensor array 182B. At step 1442 of process 1440 control circuit 552 generates color filter array image data and monochrome gray scale image data. Where optical reader 100 includes image sensor array 182B, control circuit 552 may execute step 1442 by reading out from image sensor array 182B a single frame of image data comprising both monochrome image data and color image data. Control circuit 552 may also execute step 1442 by successively capturing a first monochrome frame comprising monochrome image data and then a second color frame comprising color image data. Control

circuit 552 at step 1442 may drive monochrome pixels 250M into reset during an exposure period for read out of color image data from color sensitive pixels 250C. When generating a frame of monochrome image data at step 1442, control circuit may interpolate monochrome pixel values for “missing pixel” positions occupied by color sensitive pixels 250C.

At step 1446 control circuit 552 generates an RGB image having resolution equal to the color sensitive subset of pixels of image sensor array 182B. In an RGB image, each pixel of the image is represented by a red color value, a green color value and a blue color value. The RGB image generated at step 1446 may have the same characteristics as the visual display image received by optical reader 100 at step 1407 of the alternative process described in connection with FIG. 14g. Where a color filter array image captured at step 1442 is a Bayer pattern image, the RGB image generated at step 1446 is derived by executing a demosaicing routine as described herein. Where the color filter array image captured at step 1442 is a CMY image or a CM image (cyan and magenta only) image as described in connection with FIGS. 2b and 2d, the RGB image generated at step 1446 is derived by way of a transformation process as described herein in connection with equations 1, 2 and 3. With further reference to process 1440 which may be executed by fusion circuit 1708 control circuit 552 at step 1450 expands the pixel count of the RGB image generated at step 1446 so that the pixel count of the color image is equal to the pixel count of the monochrome image captured at step 1442 (at step 1442 monochrome pixels from the captured monochrome image may be interpolated as described with FIG. 16a). When control circuit 552 executes step 1450, the monochrome gray scale image generated at step 1442 and the color image at that stage of the processing have equal numbers of pixels such that each pixel position e.g., pixel of the monochrome image has a corresponding pixel position in the color image. With reference to image sensor array 182B having a period of P=2, there are four times as many monochrome pixels as there are color sensitive pixels. Accordingly, with image sensor array 182B having a period of P=2, control circuit 552 at step 1450 expands each pixel into a 2x2 pixel block. Where image sensor array 182B has a period P=3, control circuit 552 at step 1450 expands each pixel into a 3x3 pixel block. Where image sensor array 182B includes the period of P=4, control circuit 552 at step 1450 expands each pixel into a 4x4 pixel pixel block. At step 1454 control circuit 552 calculates an intensity value I_c for each pixel position of the expanded color image. Control circuit 552 at step 1454 calculates an intensity value for each pixel position of the expanded color image according to the formula.

$$I_c = 0.299R + 0.587G + 0.144B \quad (\text{Eq. 4})$$

Control circuit 552 at step 1460 then calculates an intensity value delta, D, for each pixel position, (Px, Py) utilizing a monochrome image intensity value I_m and an expanded image color intensity value, I_c , at each pixel position. Control circuit 552 at step 1460 may calculate an intensity value delta for each pixel position of the monochrome and expanded color image according to the formula

$$D(P_x, P_y) = I_m(P_x, P_y) - I_c(P_x, P_y) \quad (\text{Eq. 5})$$

At step 1464, control circuit 552 updates the RGB data set color scale values of the expanded RGB color image using the set of formulas

$$R'(P_x, P_y) = R(P_x, P_y) + D(P_x, P_y) \quad (\text{Eq. 6})$$

$$G'(P_x, P_y) = G(P_x, P_y) + D(P_x, P_y) \quad (\text{Eq. 7})$$

$$B'(P_x, P_y) = B(P_x, P_y) + D(P_x, P_y) \quad (\text{Eq. 8})$$

At step 1468 control circuit 552 truncates RGB data set color scale values that are greater than 255 (where an 8 bit gray scale is used). After control circuit 552 truncates RGB values greater than 255, control circuit 552 at step 1770 outputs a visual display color frame of image data having a spatial resolution equal to or approximately equal to the overall pixel resolution of image sensor array 182B. The visual display color frame of image data output at step 1770 may have a number of RGB data sets equal to the overall pixel count (e.g., monochrome pixels plus color sensitive pixels) of image sensor array 182B.

At step 1411 optical reader 100 receives from fusion circuit 1708 a high resolution visual display color frame of image data. The visual display color frame of image data received at step 1411 may include a pixel resolution equal to or on the order of the pixel resolution of image sensor array 182B. Optical reader 100 may be regarded as having received a visual display color frame of image data when fusion circuit 1708 outputs a visual display color frame of image data at step 1470.

When executing process 1440, control circuit 552 fuses monochrome and color image data to produce a high resolution visual display color frame of image data. When executing the alternative process described with reference to the flow diagram of FIG. 14j, control circuit 552 fuses monochrome and color image data in such a manner that color reproduction is optimized.

In general, increasing the percentage of monochrome pixels 250M in image sensor array 182A, 182B increases indicia decoding accuracy, while increasing the percentage distribution of color sensitive pixels 250C in image sensor array increases color reproduction accuracy. Because of the light transmissivity of monochrome pixels, an image obtained utilizing an image sensor array having a higher percentage of monochrome pixels 250M has a higher signal to noise ratio than an image obtained utilizing an image sensor array having a smaller percentage of monochrome pixels 250M. Accordingly, an image obtained utilizing an image sensor array having a higher percentage of monochrome pixels often produces an image with greater detail and improved overall visual quality.

Optical reader 100 in another aspect may incorporate the structure shown in FIG. 21. In FIG. 21, center pixels 2072 of reader image sensor array 182B have a higher percentage of monochrome pixels 250M, i.e., a period of P=4, as shown in FIG. 5e, while outer pixels 2074 have a lower percentage of monochrome pixels 250M, i.e., a period of P=2, as shown and described in FIG. 5c. The image sensor array 182B is constructed such that center pixels 2072 are optimized for providing image data yielding increased decoding accuracy while outer pixels 2074 are optimized for providing image data yielding increased color reproduction accuracy.

Referring to further steps of process 1400, control circuit 552 at step 1412 outputs the visual display color frame of image data obtained at step 1404. At step 1412 control circuit 552 may output a visual display color frame of image data to display 504 for visual observation by an operator or to a designated color frame storage memory location of

reader 100 such as a designated frame memory storage location of Flash memory 564 or to another frame memory location of system 145. Where control circuit 552 is incorporated in hand held housing 101, control circuit 552 at step 1410 may also send a visual display color frame of image data to spaced apart device 150, as shown in FIG. 10. For sending a frame of image data to a spaced apart device 150, optical reader 100, the spaced apart device 150, and a communication link there between may be configured to transmit data packets in accordance with a protocol of the TCP/IP suite of protocols. Further, optical reader 100 may format the visual display color frame of image data obtained at step 1412 in a suitable image file format (e.g., .BMP, .TIFF, .PDF, .JPG, .GIF) and optical reader 100 may automatically send the visual display color frame of image data at step 1412 utilizing the file transfer protocol (FTP). Optical reader 100 at output step 1212 may format the visual display color frame of image data in a suitable image file format (e.g., .BMP, .TIFF, .PDF, .JPG, .GIF) when storing the visual display color frame of image data in memory 566 (which can be incorporated in hand held housing 101) or when sending the visual display color frame of image data to a spaced apart device 150 for storage. Optical reader 100 may also transmit a visual display color frame of image data utilizing a suitable markup language such as .XML. Referring to FIG. 10, system 145 may be configured so that when a display equipped spaced apart device 150 receives a visual display color frame of image data from optical reader 100, the spaced apart device 150 automatically displays that received visual display color frame of image data on a display 1504 associated with that device.

Optical reader 100 can be configured so that all the steps of process 1400 are carried out automatically in response to receipt of a trigger signal until a stop condition is satisfied. A stop condition may be the receipt of a trigger stop signal such as may be generated by the release of trigger 216.

In the embodiments of FIGS. 14a-14c, two actuations of a reader control button are made to carry out an indicia decode process and two actuations of a reader control button are made to carry out a picture taking process (one actuation of button 3162 or button 3164 to configure the reader 100 and then another actuation of trigger 216 to capture an image). It will be understood that optical reader 100 can be configured to carry out indicia decoding or picture taking with a single actuation of a reader control button. For example, optical reader 100 can be configured so that actuation of virtual button 3162 both configures reader 100 to decode and simultaneously generates a trigger signal to immediately commence image capture and decoding. Optical reader 100 can also be configured so that actuation of virtual icon button 3164 both configures a reader 100 for picture taking and simultaneously generates a trigger signal to immediately commence image capture.

While process 1200 and process 1400 may be carried out in the alternative, process 1200 and process 1400 may also be executed contemporaneously. For example, while control circuit 552 obtains a decode frame at step 1204, control circuit 552 may obtain a visual display color frame of image data at step 1404. Control circuit 552 may obtain a color frame of image data as a decode frame at step 1204 and then outputs that frame at step 1212 as visual display color frame of image data. Control circuit 552 at step 1412 may output a visual display color frame of image data and contemporaneously transfer that frame of image data to decode circuit 1702. In general, reader 100 may be configured so that whenever control circuit 552 obtains a decode frame at step 1204, control circuit 552 may store that frame for later

processing, which processing may include processing for generating a visual display color frame of image data and which processing may be responsive to an operator input command to perform such processing. Optical reader 100 may also be configured so that when control circuit 552 obtains a visual display color frame of image data at step 1404, control circuit may store that frame for further processing, which processing may include transferring that frame to decode circuit 1702 or autodiscrimination circuit 1704, and which processing may be responsive to an operator input command to perform such processing.

Another embodiment of the invention is described with reference to FIGS. 17a-17g. In the embodiment of FIGS. 17a-17g optical reader 100 includes a pair of imaging modules 1802D and 1802E. Imaging module 1802D is a color imaging module having color image sensor array 182D. Color image sensor array 182D includes a Bayer pattern color filter with one of red, green or blue wavelength selective filter disposed on each pixel. Imaging module 1802E as shown in FIG. 17e is a monochrome imaging module having a one-dimensional solid state image sensor array 182E. One-dimensional monochrome image sensor array 182E in the embodiment of FIGS. 17a, 17e, 17f, and 17g includes an Mx1 (one row) array of monochrome (without color filter) pixels. One-dimensional image sensor array 182E may also include and MxN array of pixels, where $M \gg N$, e.g., an Mx2 (2 rows) of pixels.

The reader 100 shown in the electrical block diagram of FIG. 17a has many of the same components as shown in optical reader 100 of FIG. 1a. Namely, optical reader 100 of FIG. 17a includes a control circuit 552 provided in the example by a CPU, which operates under the control of program data stored in EPROM 562. Control circuit 552 is in communication with a memory unit 566 that includes in addition to EPROM 562, RAM 560, and Flash memory 564. Control circuit 552 further receives input control data from various user input devices such as manual trigger 216, pointer controller 512, keyboard 508 and touch screen 504T. Control circuit 552 may also output data such as decoded output data and visual display image data to color display 504. For capturing image data, control circuit 552 may control either image sensor array 182E or image sensor array 182D. For capturing one-dimensional image data corresponding to a one-dimensional slice image of a target, control circuit 552 sends various image capture initiating control signals to one-dimensional image sensor array 182E. In response to the image capture initiation control signals, image sensor array 182E sends analog image signals to signal processing circuit 591 which among various processing functions amplifies the signals and feeds the signals to analog-to-digital converter 592. Analog-to-digital converter 592 converts the signals into digital form and routes the digital image data to FPGA 593 which under the control of control circuit 552, manages the transfer of the digital information into RAM 560, where the monochrome image data can be accessed for decoding processing by control circuit 552. For capturing two-dimensional frames of color image data, control circuit 552 sends appropriate image capture initiation control signals (e.g., exposure, read out) to image sensor chip 1082. FPGA 580 receives digital image data from image sensor IC chip 1082, 1082D and under the control of control circuit 552 manages the transfer of color image data into RAM 560. Illumination assembly 104 for each module 1802D, 1802E may be controlled during image acquisition as explained with reference to the timing diagrams of FIGS. 15a-15e.

Optical reader **100** as shown in FIGS. **17a-17g** may be operated in accordance with the flow diagram of FIGS. **17a-17g**. Namely, by a suitable selection method such as by depressing icon **3162** or icon **3164** (FIG. **9b**) one of a decode mode of operation and a color image capture mode of operation can be selected. However, in the dual imaging module embodiment of FIGS. **17a-17g**, the imaging module which is utilized for capturing image data depends on which mode (indicia decoding, or picture taking) is selected. If the indicia decode mode is selected at step **1100** (FIG. **14a**) and a trigger signal is received, optical reader **100** proceeds to step **1102** to execute indicia decode process **1200** (FIG. **14a**). At step **1204** of indicia decode process **1200**, control circuit **552** obtains a decode frame of image data. If the picture taking mode of operation is selected at step **1100** (FIG. **14a**) and a trigger signal is received, control circuit **552** proceeds to step **1404** (FIG. **14c**) to obtain a visual display color frame of image data. Where reader **100** includes two imaging modules, one color such as module **1802**, **1802D** having color image sensor array **182**, **182D** and one monochrome such as module **1802**, **1802E** having monochrome image sensor **182**, **182E**, the particular image sensor array **182** to which control circuit **552** sends control signals for initiating image capture depends on whether optical reader **100** is operating in a decode mode of operation or a picture taking mode of operation. With reference to the reader **100** of FIGS. **17a-17g**, and the flow diagrams of FIGS. **14a**, **14b** and **14c**, reader **100** at step **1204** sends image capture initiation control signals to monochrome one-dimensional image sensor array **182**, **182E** to initiate image capture without sending any image capture initiation control signals to color image sensor array **182**, **182D** if the reader **100** is operating in a decode mode operation. Reader **100** at step **1404** sends image capture initiation control signals to color image sensor array **182**, **182D** without sending any image capture initiation control signals to monochrome image sensor array **182**, **182E** if reader **100** is operating in a picture taking mode operation. Accordingly, where optical reader **100** is in an indicia decode mode and receives a trigger signal, a monochrome frame of image data is sent to RAM **560** for further processing by decode circuit **1702** (FIG. **10**). Where optical reader **100** is in a picture taking mode and receives a control signal, a color image is sent to RAM **560**. The color image if a Bayer pattern image is subject to a demosaicing process as described herein for generating a visual display color frame of image data, which visual display color frame of image data may be output by control circuit **552** e.g., to display **504** and/or a designated memory address of system **145** (e.g., memory **566** or another memory such as a memory of a spaced apart device **150**), and/or to a display **1504** of a spaced apart device **150** of system **145** (FIG. **5**).

When an image is captured by the two imaging module readers of FIGS. **17a-17g**, the type of image capture (monochrome or color) depends on a selected operating mode. When an indicia decode mode is selected, a monochrome gray scale image well suited for decode processing is captured. When a picture taking mode is selected, a color image is captured which is well suited for visual display.

Further aspects of a dual imaging module reader are described with reference to FIGS. **17b-17g**. FIGS. **17b** and **17c** illustrate that the hardware block **598** of reader **100** shown in FIGS. **17a**, **17f**, and **17g** may be replaced with alternative hardware blocks. As indicated by FIG. **17b**, hardware block **398** which in FIG. **17a** includes a CCD one-dimensional solid state image sensor array **182E** and off-board signal processing circuit **591**, analog-to-digital

converter **592** and FPGA **593** may be replaced by a hardware block including an CMOS image sensor IC chip **1082F** including a monochrome image sensor array **182F**. Image sensor IC chip **1082**, **1082F** is of construction similar to image sensor IC chip **1082**, **1082A** and IC chip **1082**, **1082D** except that image sensor array **182F** of chip **1082F** includes monochrome pixels **250**, **250M** only and is devoid of color sensitive pixels **250**, **250C**. FIG. **17c** illustrates that imaging assembly hardware block **598** can be replaced with a laser scanning bar code engine **594** and an associated decode circuit **595**. Laser scanning bar code engine **594** and associated decode circuit **595** may be available in a package known as an SE **923** decoded out scan engine available from Symbol Technologies. In the embodiment of FIG. **17c**, steps **1210**, **1212**, **1214** of decode process **1200** are carried out by decode circuit **595**.

Exemplary imaging modules supporting various types of image sensor IC chips are shown in FIGS. **17d** and **17e**. FIG. **17d** shows an exemplary imaging module for supporting image sensor IC chip **182D**. Imaging module **1082D** includes the elements shown and described with reference to FIGS. **8a-8d** except that imaging module **1082D** includes image sensor IC chip **182D** and further except that certain light sources are optionally deleted. Imaging module **1082E** includes the elements shown and described with reference to FIGS. **8a-8e** except that imaging module **1082E** includes one-dimensional monochrome image sensor chip **182E** and further except that certain light sources of illumination block **104** are optionally deleted. With module **1802E**, aiming pattern **1838** (FIG. **8d**) may serve as an aiming and illumination pattern. Further, it will be noted that illumination assembly **104** of an imaging module herein may include a flash illumination light source, **160**, **160X** (FIG. **9a**). It may be particularly useful to incorporate a flash illumination into illumination assembly **104**, where an imaging module **1082** is used primarily for capture of visual display color image.

Referring to FIGS. **17f** and **17g** construction views of dual imaging module readers incorporated in various optical reader housings are shown and described. In FIG. **17f** a gun style optical reader **100** is shown having color two-dimensional imaging module **1802D** and one-dimensional monochrome imaging module **1082E** supported therein. In FIG. **17g** a portable data terminal (PDT) optical reader **100** is shown having color two-dimensional imaging module **1802D** and one-dimensional monochrome imaging module **1082E** supported therein. The dual modules can also be installed in other types of housings such as cell phone housings (FIG. **9c**) and personal data assistant housings (PDAs). In the examples of FIGS. **17f** and **17g**, imaging modules **1802** are supported by struts **597** formed on an interior wall **1802** of housing **101**. Via ribbon connectors **598**, the modules **1802** in each example are in communication with a main printed circuit board **599** which includes various electrical components including processor IC chip **548**.

In one application, the optical reader **100** of FIGS. **17a-17g** is operated in the following manner. An operator actuates color image sensor array **182D** to take a color picture of parcel **1260** (FIGS. **11** and **12**) carrying a bar code symbol **1266**, **1270**. Such actuation may be carried out, e.g., by depressing decode button **3164** and then trigger **216** or button **3164** only. An operator then actuates monochrome image sensor array **182E** (or alternatively image sensor array **182F**, or laser scan engine **594**) to decode bar code symbol **1266**, **1270**. Such actuation may be carried out e.g., by depressing button **3162** and then trigger **216** or by depressing button **3162** only. Further, control circuit **552**, which

may be incorporated in hand held housing **101**, may transmit a visual display color frame of image data representing parcel **1260** and decoded out messages corresponding to one or more of symbols **1266**, **1270** to remote server **184** (FIG. **10**). System **145** can be configured so that such transmission is automatic in response to trigger signals being received, or optical reader **100** can be configured so that associated color picture data and decoded out bar code message data are transmitted in response to receipt of a user-initiated command input into a user-interface of optical reader **100** to transmit associated picture and decoded bar code message data.

With further reference to the reader electrical block diagram shown in FIG. **1a**, various useful optical reader embodiments may be yielded by reconfiguration of hardware block **208** including an image sensor array. With reference to FIG. **18a**, an optical reader **100** having the hardware components shown in FIG. **1a** may be modified to include an image sensor array **182C** as shown and described in connection with FIG. **18a**. In the embodiment of FIG. **18a**, optical reader **100** includes cyan—magenta—yellow (CMY) color filter array **182C**. Each pixel **250** of image sensor array **182C** includes a color filter element; namely one of a cyan color filter element, a magenta color filter element or a yellow color filter element. Yellow color filter elements have excellent light transmittance (approaching the transmittance of a monochrome pixel). Further, it is seen that in accordance with the CMY color filter pattern shown in FIG. **18a** that approximately 50% of all pixels of image sensor array **182C** are yellow pixels (pixels having a yellow light wavelength sensitive filter element). In the specific example of FIG. **18a**, image sensor array **182C** having cyan, magenta and yellow pixels is devoid of green pixels. However, image sensor arrays are available which have green pixels in addition to cyan, magenta and yellow pixels. Image sensor array **182C** may be incorporated into an optical reader **100** that operates in accordance with the picture taking mode/indicia decode mode flow diagram described in connection with FIG. **14a**. That is, when driven into a indicia decode mode of operation as described in connection with FIG. **14b**, optical reader **100** including CMY color image sensor array **182C** obtains a decode frame of image data whereas when optical reader **100** including image sensor array **182C** is driven into a picture taking mode of operation, optical reader **100** obtains a visual display color image frame of image data as described in connection with FIG. **14c** herein.

According to the invention, an optical reader including a CMY image sensor array **182C** as shown in FIG. **18a** may obtain image data in a manner that depends on which operational mode (indicia code or picture taking) is selected. Where optical reader **100** including CMY image sensor array **182C** obtains a decode frame of image data at step **1204**, control circuit **552** of optical reader **100** can selectively address yellow color pixels of CMY image sensor array **182C** and selectively read out image data only from yellow colored pixels of image sensor array **182C**. With further reference to a reader including image sensor array **182C**, control circuit **552** at step **1204** may interpolate missing pixel values corresponding to the pixel positions of magenta and cyan pixels of image sensor array **182C**. After interpolating the missing pixel positions, control circuit **552** at step **1210** may transfer the interpolated decode frame to one of indicia decode circuit **1702** or autodiscrimination circuit **1704**.

In a further aspect of the optical reader described in connection with FIG. **18a** including a CMY color image

sensor array **182C**, image sensor array **182C** may include separate and independent reset control lines for facilitating the reset of magenta (labeled “Mg”) and cyan (labeled “Cy”) pixels independent from the resetting of yellow pixels (labeled “Y”). Accordingly, when image data at step **1204** is read out selectively from yellow pixels, the magenta and cyan pixels of image sensor array **182C** may be driven into reset to eliminate electron diffusion cross talk and to reduce cross talk attributable to photons entering image sensor array **182C** through magenta and cyan color pixels **250C**.

When obtaining a visual display color frame of image data as described at step **1404** of the flow diagram FIG. **14c** an optical reader including image sensor array **182C** may simply read out image data from all of the pixels of the array **182C** and execute a simple demosaicing algorithm to convert a single color value for each pixel of image sensor array **182C** into a visual display color image wherein each pixel of image sensor array **182C** is represented by a data set including three color scale values, e.g., a cyan color scale value, a magenta color scale value and a yellow color scale value.

Control circuit **552** at step **1404** where the reader includes a CMY image sensor array **182C** may transform the CMY visual display image into an RGB visual display image utilizing a CMY to RGB transformation process as described herein.

The performance of optical reader **100** may be hindered where optical reader **100** is operated to read bar code symbols or other indicia disposed on a substrate having a shiny surface (e.g., metal, glass, laminated, plastic, etc.). Light rays emanating from light sources **160** of reader **100** that are projected on a highly reflective shiny surface of a substrate, *s*, may be substantially entirely reflected directly on to image sensor array **182**. “Specular” reflection is said to occur where a substantial percentage of light rays are reflected and directed onto image sensor array **182**. Light rays are said to be reflected at a “specular angle” when light rays are reflected from a surface at about the angle of incidence. Specular reflection tends to saturate image sensor array **182** to cause decoding failures. The optical reader **100** described in connection with FIGS. **19a-c** is configured so that read errors resulting from specular reflection are reduced. As shown and described in connection with FIG. **19a**, hardware block **208** shown in FIG. **1a** as including a hybrid monochrome in color image sensor array **182A** can be replaced with hardware block **208** as shown in FIG. **19a** including a hybrid monochrome and polarizer filter image sensor array **182G**.

Image sensor array **182G** includes a first subset of monochrome pixels **250M** and a second subset of light polarizing pixels **250P**. Light polarizing pixels **250P** of image sensor array **182G** include light polarizing filter elements **261** (alternatively termed “light polarizing filters,” or simply “light polarizers”) typically formed at each polarizing pixel **250P** in the position of filter **260** as shown in the color pixel views of FIGS. **3c** and **6c**. Light polarizing filter elements **261** of image sensor array **182G**, **182H** can be deposited onto the major body of light polarizing pixels **250P** by way of a depositing process. Light polarizing filter elements **261** of image sensor array **182G** can be constructed to attenuate polarized light rays generated from an appropriately polarized light source and reflected at a specular angle. Accordingly, polarized light rays incident on the image sensor array on the polarizing pixels **250P** are attenuated significantly; thus, reducing the contribution of specularly reflected light rays to generated image signals from the polarizing pixels **250P**.

According to the invention, optical reader 100 including image sensor array 182G may be configured to selectively address light polarizing pixels 250P and selectively read out image data from light polarizing pixels 250P to generate image data for subjecting to decoding which is likely to result in successful reading of bar codes or other indicia notwithstanding the image data being obtained during specular reflections read conditions.

Referring to FIG. 19b, a perspective view of light polarizing image sensor array 182G is shown with an exploded view showing a pattern which may be repeated throughout the array. In the version of FIG. 19b, light polarizing pixels 250P having light polarizing light filter elements 261 are uniformly distributed throughout image sensor array 182G with a period of $P=2$. It will be understood that light polarizing pixels 250P may also be distributed throughout image sensor array 182G in a uniform or substantially uniform distribution pattern other than the pattern shown in FIG. 19b. For example, light polarizing pixels 250P may be distributed throughout image sensor array 182G with a distribution pattern of $P=3$, (as described in connection with FIG. 5d showing a hybrid monochrome and color image sensor array) or a distribution pattern having the period of $P=4$, as illustrated with reference to hybrid monochrome and color image sensor array as shown in FIG. 5e.

Referring to the view of FIG. 9b, optical reader 100 may be operated in a mode in which optical reader 100 captures image data by selectively addressing polarizing pixels 250P and selectively reading out image data from light polarizing pixels 250P only. Optical reader 100 may be configured to have a reduced specular reflection read error decode mode. Optical reader 100 can be configured so that when button 3156 is actuated, optical reader 100 receives a trigger signal to obtain image data that is likely to result in successful reading notwithstanding specular reflection reading conditions.

Referring to the flow diagram of FIG. 19c, optical reader 100 at step 1902 may receive a trigger signal to commence operation in a reduced specular reflection read error decode mode. The trigger signal may be received pursuant to a manual control by an operator such as an actuation of control button 3156. Control circuit 552 may also be configured to receive the trigger signal at step 1902 when control circuit 552 automatically senses a predetermined condition such as a saturation condition. Control circuit 552 at step 1902 may determine that a saturation condition is present by analysis of image data at step 1204 (FIG. 14b) during normal decoding operations so that when a saturation condition is detected, optical reader 100 automatically commences operation in a reduced specular reflection read error decode mode. In a specific embodiment of the invention, control circuit 552 may determine that a saturation condition is present when an average white value of monochrome image data is below a predetermined level.

At step 1904 optical reader 100 obtains a specular reflection read condition decode frame of image data. Control circuit 552 obtains a specular reflection condition decode frame of image data at step 1902 by selectively addressing light polarizing pixels 250P of image sensor array 182G and selectively reading out image data from light polarizing pixels 250P only. In another aspect of image sensor array 182G that may be incorporated in optical reader 100, image sensor array 182G may include separate reset control lines for resetting monochrome pixels 250M separately and independently of light polarizing pixels 250P. Image sensor array 182G may have separate sets of reset control lines as

described in connection with image sensor array 182G, particularly in connection with FIG. 7a.

Accordingly, when control circuit 552 selectively addresses light polarizing pixels 250P for read out of image data from light polarizing pixels 250P, control circuit 552 drives monochrome pixels 250M into reset. Resetting of monochrome pixels 250M is synchronized with the exposure period for exposing light polarizing pixels 250P as described herein. Driving monochrome pixels 250M into reset while light polarizing pixels 250P are exposed eliminates electron diffusion cross talk and reduces cross talk resulting from photon penetration to image sensor array 182G.

At step 1904, control circuit 552 may interpolate pixel values at pixel positions corresponding to missing pixel positions. At step 1906 control circuit 552 transfers the specular reflection condition decode frame of image data obtained at step 1904 to indicia decode circuits 1702 or autodiscrimination circuit 1704 as are described in connection with FIG. 1e.

At step 1908 control circuit 552 receives decoded output data output by decode circuit 1702 or signature autodiscrimination circuit 1704. At step 1910 control circuit 552 outputs decoded out data, e.g., by transferring decoded out data to an on reader display 504 or to a spaced apart display 1504 or else stores decoded data in appropriate memory address location of system 145 (FIG. 10).

A process has been described with reference to the flow diagram of FIG. 19c wherein control circuit 552 selectively reads out monochrome pixel image data from monochrome pixels 250M and selectively reads out image data from light polarizing pixels 250P. An optical reader including hybrid monochrome and light polarizing image sensor array 182G may also be operated without selectively reading out image data from image sensor array 182G. An optical reader incorporating hybrid monochrome and light polarizing image sensor array 182G can be operated to decode decodable indicia and to take pictures in accordance with the process described with reference to the flow diagrams of FIGS. 14a, 14b, and 14c. In obtaining a decode frame of image data (step 1204, FIG. 14b), control circuit 552 may read out image data from all pixels of hybrid monochrome and light polarizing image sensor array 182G including image data from all monochrome pixels 250M and all light polarizing pixels 250P in a single frame capture step. The full frame monochrome and light polarizer pixel image data can also be captured with two frame capture steps. At step 1210, control circuit 552 may transfer to decode circuit 1702 or autodiscrimination circuit 1704 the full frame of monochrome and polarized pixel image data obtained at step 1204. If decode circuit 1702 or autodiscrimination circuit 1704 fails to decode or fails to detect the presence of handwritten characters, control circuit 552 may, after step 1210, transfer a subset of full frame of image data originally transferred at step 1210. Namely, after step 1210, if decoding or autodiscrimination fails, control circuit 552 may transfer to decode circuit 1702, or autodiscrimination circuit 1704 a reduced resolution image extracted from a full frame image by selectively extracting monochrome image data from the full frame of image data. The reduced resolution frame of image data includes only image data corresponding to light polarizing pixels 250P of image sensor array 182G. The failure of decode circuit 1702 to decode or autodiscrimination circuit to recognize may be regarded as a determination by control circuit 552 that a saturation condition is present.

The elements of a hybrid monochrome and color image sensor array (such as image sensor array **182A** or **182B**) as described herein can be combined with the elements of a hybrid monochrome and light polarizing image sensor array **182G** into a single image sensor array. FIGS. **20a** and **20b** show an image sensor array **182H** including a first subset of monochrome pixels **250M**, a second subset of color sensitive pixels **250C** and a third subset of light polarizing pixels **250P**. Image sensor array **182H** may include three separate sets of reset control lines to enable separate and independent of resetting of monochrome pixels **250M**, of color sensitive pixels **250C** and of light polarizing pixels **250P**. Image sensor array **182H** may be incorporated in hand held optical reader **100** and may be substituted for hardware block **208** as shown in FIG. **1a**. Optical reader **100** incorporating image sensor array **182H** may have operating modes in which optical reader separately addresses monochrome pixels **250M** for read out of image data from monochrome pixels **250M** only. Optical reader **100** including image sensor array **182H** may also have an operating mode in which optical reader **100** selectively addresses color sensitive pixels **250C** and selectively reads out image data from color sensitive **250C**. Optical reader **100** may also have an operating mode in which optical reader **100** selectively addresses light polarizing pixels **250P** and selectively reads out image data from light polarizing pixels **250P**. Optical reader **100** may obtain a full frame of image data including monochrome, color and light polarizing pixels image data (obtained with one, two, or three frame capture steps) and then utilize the image data on an as needed basis. For example, if a decode attempt utilizing the full frame image data fails, optical reader **100** may selectively extract light polarizing pixel image data from the full frame image data and transfer the extracted image data to decode circuit **1702**.

In general, optical reader **100** including image sensor array **182H** selectively reads out image data from monochrome pixels **250M** in obtaining a decode frame of image data for transferring to a decode circuit **1702** under normal read conditions. Optical reader **100** selectively reads out image data from color sensitive pixels **250C** when obtaining image data for use when obtaining a visual display color frame of image data. Optical reader **100** selectively reads out image data from light polarizing pixels **250P**, or selectively extracts image data corresponding to pixels **250P** from a frame of image data when optical reader **100** senses that a specular reflection is present or when an operator pursuant to operator control drives optical reader **100** into a reduced specular reflection read error decode mode of operation. An optical reader **100** including image sensor array **182H** may operate in accordance with the picture taking and decode mode flow diagram as described in connection with FIG. **14a** and may execute the reduced specular reflection read error decode mode decoding process described in connection with FIG. **19c**.

For enhancing the performance of an optical reader according to the invention, having an image sensor array such as image sensor array **182G**, **182H** including light polarizing filters, optical reader **100** may incorporate emit optics light polarizers (which may alternatively be termed "light polarizing filter elements" or "light polarizing filters"). For example, a reader imaging module, e.g., module **1802A** can include an optical plate **1962** as shown in FIG. **8f** which may be disposed forwardly of circuit board **1806** as shown in FIG. **8a**. Optical plate **1962** can incorporate light polarizers **1963** which polarize light from light sources **160S**, **160T**, that can be selectively energized when capturing images utilizing polarizing image sensor array **182G**, **182H**.

Light polarizers **1963** can be cross-polarized relative to the polarizing filter elements **261** of image sensor array **182G**, **182H**. Optical plate **1962** can include other such elements as optical diffusers (not shown) for diffusing light rays emitted by light sources **160C-160T**.

Further aspects of indicia decode circuit module **1702** and autodiscrimination circuit module **1704** are described with reference to FIGS. **22a-22i**. Indicia decode circuit **1702** (which may be a bar code symbol dataform decode circuit) when receiving image data transferred by control circuit **552** may search the image data for markers, such as a quiet zone, indicative of the presence of a dataform, such as a one or two-dimensional bar code. If a potential decodable indicia (dataform) is located, the decode circuit **1702** applies one or more indicia decoding algorithms to the image data. If the decode attempt is successful, the optical reader outputs decoded dataform data. All of the circuits (modules) described with reference to FIG. **22a** can be incorporated in housing **101**. Further, all of the circuits of FIG. **22a** can be embodied by the combination of control circuit **552** and memory **566**.

Optical reader **100** may also include an autodiscriminating circuit **1704**. Referring to FIG. **22a**, autodiscriminating circuit **1704** may incorporate a decode circuit **1702** and an image processing and analysis circuit **21208**, that are in communication with one another.

As shown in this embodiment, the image processing and analysis circuit **21208** comprises a feature extraction circuit **21212**, a generalized classifier circuit **21216**, a signature data processing circuit **21218**, an OCR decode circuit **21222**, and a graphics analysis circuit **21224** that are in communication with each other. In addition, as shown in FIG. **22a**, the feature extraction circuit **21212** comprises a binarizer circuit **21226**, a line thinning circuit **21228**, and a convolution circuit **21230** that are in communication with each other.

FIG. **22b** shows a process **21300** for employing one embodiment of the invention utilizing the autodiscrimination circuit shown in FIG. **22a**. The process **21300** comprises an image reader recording an actuation event (step **21302**), such as a receipt of a trigger signal, and in response at step **21304**, collecting (obtaining) image data from a target with the optical reader **100**. The collecting of image data step may be in accordance with step **1204** (FIG. **14b**). After collection, the image data is transferred (step **21308**) to the decode circuit **1702**. The dataform decode circuit searches (step **21310**) the image data for markers, such as a quiet zone, indicative of the presence of a dataform, such as a one or two-dimensional bar code. If a potential dataform is located, the decode circuit **1702** applies (step **21314**) one or more dataform decoding algorithms to the ensuing image data. If the decode attempt is successful, the optical reader **100** outputs (step **21318**) decoded dataform data and signals (step **21322**) a successful read with an alert, such as a beep tone.

In one embodiment if the decode attempt is not successful, the image data is transferred (step **21326**) to the image processing and analysis circuit **21208**. In another embodiment, the image data is processed in parallel with the attempt to decode the dataform data. In one such embodiment, the process that completes first (i.e., dataform decode attempt or the image processing) outputs its data (e.g., a decoded bar code or a captured signature) and the other parallel process is terminated. In a further embodiment, the image data is processed in response to the decoding of the dataform. In one such embodiment, a bar code encodes item information such as shipping label number and information indicating that a signature should be captured.

Within the image processing and analysis circuit **21208**, the image data is processed by the feature extraction circuit **21212**. In general, the feature extraction circuit generates numeric outputs that are indicative of the texture of the image data. As indicated above, the texture of the image data refers to the characteristics of the type of data contained in the image data. Common types of texture include one or two-dimensional bar code texture, signature texture, graphics texture, typed text texture, handwritten text texture, drawing or image texture, photograph texture, and the like. Within any category of texture, sub-categories of texture are sometimes capable of being identified.

As part of the processing of the image data by the feature extraction circuit **21212**, the image data is processed (step **21328**) by the binarizer circuit **21226**. The binarizer circuit **21226** binarizes the grey level image into a binary image according to the local thresholding and target image size normalization. With the image data binarized, the image data is processed (step **21332**) by the line thinning circuit **21228** to reduce multi-pixel thick line segments into single pixel thick lines. With binarized line thinned image data, the image data is processed (step **21336**) by the convolution circuit **21230**.

In general, the convolution circuit **21230** convolves the processed image data with one or more detector maps designed according to the invention to identify various textural features in the image data. In one embodiment, the convolution circuit **21230** generates a pair of numbers, the mean and variance (or standard deviation), for each convolved detector map. FIG. **22c** shows a set of 12 2×3 binary curvelet detector maps **21250** used to detect curved elements present in image data. As each of the curvelet detector maps **21250** is convolved with the image data, the mean value and the variance generated provide an indication of the presence or density of elements in the binarized line thinned image data having similar shapes to the curvelet detector maps **21250**. As each pixel map generates a pair of numbers, the 12 curvelet detector maps **21250** generate a total of 24 numbers. According to one embodiment, these 24 numbers are representative of the curved or signature texture of the processed image data.

Further processing of the image data includes the outputs from the feature extraction circuit **21212** being fed (step **21340**) into the generalized classifier circuit **21216**. The generalized classifier circuit **21216** uses the numbers generated by the feature extraction circuit as inputs to a neural network, a mean square error classifier or the like. These tools are used to classify the image data into general categories. In embodiments employing neural networks, different neural network configurations are contemplated in accordance with the invention to achieve different operational optimizations and characteristics. In one embodiment employing a neural network, the generalized classifier circuit **21216** includes a $24+12+6+1=43$ nodes Feedforward, Back Propagation Multilayer neural network. The input layer has 24 nodes for the 12 pairs of mean and variance outputs generated by a convolution circuit **21230** employing the 12 curvelet detector maps **21250**. In the neural network of this embodiment, there are two hidden layers of 12 nodes and 6 nodes respectively. There is also one output node to report the positive or negative existence of a signature.

In another embodiment employing a neural network, the 20 curvelet detector maps **21260** shown in FIG. **22d** are used by the convolution circuit **21230**. As shown, the 20 curvelet detector maps **21260** include the original 12 curvelet detector maps **21250** of FIG. **22c**. The additional 8 pixel maps **21260** are used to provide orientation information regarding

the signature. In one embodiment employing the 20 curvelet detector maps **21260**, the generalized classifier circuit **21212** is a $40+40+20+9=109$ nodes Feedforward, Back Propagation Multiplayer neural network. The input layer has 40 nodes for the 20 pairs of mean and variance outputs generated by a convolution circuit **21230** employing the 20 curvelet detector maps **21260**. In the neural network of this embodiment, there are two hidden layers of 40 nodes and 20 nodes respectively, one output node to report the positive or negative existence of a signature, and 8 output nodes to report the degree of orientation of the signature. The eight output nodes provide $2^8=256$ possible orientation states. Therefore, the orientation angle is given in degrees between 0 and 360 in increments of 1.4 degrees.

In some embodiments, the generalized classifier circuit **21216** is capable of classifying data into an expanded collection of categories. For example, in some embodiments the generalized classifier circuit **21216** specifies whether the image data contains various data types such as a signature; a dataform; handwritten text; typed text; machine readable text; OCR data; graphics; pictures; images; forms such as shipping manifest, bill of lading, ID cards, and the like; fingerprints, biometrics such as fingerprints, facial images, retinal scans and the like, and/or other types of identifiers. In further additional embodiments, the generalized classifier circuit **21216** specifies whether the image data includes various combinations of these data types. In some embodiments, the general classifier circuit **21216** specifies whether the image data contains a specified type of data or not. In one such embodiment the image processing and analysis circuit **21208** is contained within an identification circuit that outputs an affirmative or negative response depending on the presence or absence of the specified data type, such as a signature or a biometric in the image data.

In one embodiment once the presence of a signature has been confirmed and its general orientation determined, image data is transferred (step **21344**) to the signature data processing circuit **21218**. In one embodiment, the signature data processing circuit **21218** is used to detect the boundaries of the signature in the image data. In one embodiment, the signature boundary is detected using a histogram analysis. As shown in FIG. **22e**, a histogram analysis consists of a series of one-dimensional slices along horizontal and vertical directions defined relative to the orientation of the signature. In one embodiment, the value for each one-dimensional slice corresponds to the number of black (i.e., zero valued) pixels along that pixel slice. In some embodiments if no bar codes have been decoded, then some specified region of the full frame of image data, such as a central region is captured for signature analysis. Once completed, the histogram analysis provides a two-dimensional plot of the density of data element pixels in the image data. The boundary of the signature is determined with respect to a minimum density that must be achieved for a certain number of sequential slices. In one embodiment, the histogram analysis searches inwardly along both horizontal and vertical directions until the pixel density rises above a predefined cutoff threshold. So that the signature data is not inadvertently cropped, it is common to use low cutoff threshold values.

In one embodiment, once the boundaries of the signature have been determined, the signature data processing circuit **21218** crops the image data and extracts the signature image data. In one such embodiment, the cropping is performed by an image modification circuit that generates modified image data in which a portion of the image data not including the signature has been deleted. In other embodiments, various

compression techniques are employed to reduce the memory requirements for the signature image data. One such technique includes the encoding of the signature image data by run length encoding. According to this technique, the length of each run of similar binarized values (i.e., the length of each run of 1 or 0) for each scan line is recorded as a means of reconstructing a bit map. Another encoding technique treats the signature image data as a data structure where the elements of the data structure consist of vectors. According to this encoding technique, the signature is broken down into a collection of vectors. The position of each vector in combination with the length and orientation of each vector is used to reconstruct the original signature. In one such embodiment, the encoding process generates a new vector whenever the curvature for a continuous pixel run exceeds a specified value. A further compression technique employs B-Spline curve fitting. This technique has the capacity to robustly accommodate curvature and scaling issues.

In various embodiments, the signature image data or a compressed or encoded version of the signature image data is stored locally on a dedicated memory device. In one such embodiment, the local memory device can be a detachable memory device such as a CompactFlash memory card or the like described in more detail below. In another embodiment, the signature image data is stored in a volatile or non-volatile portion of general purpose memory and downloaded at a future time. In a further embodiment, the signature image data can be transmitted via wired or wireless means either at the time of capture or at a later point, such as when a data collection session has been completed.

In another embodiment, the signature data processing circuit **21218** does not perform a histogram analysis but simply stores in memory the entire image or a compressed version once the presence of a signature has been determined. In a further embodiment to save processing time, the initial image analysis is performed on a lower resolution image. Once the presence of a signature is determined in this embodiment, a higher resolution image is taken. In one embodiment, a signature extraction histogram analysis is performed on this image. Next, the image is stored in memory in either compressed or original format. In some embodiments, the image data is combined with other data to form a record for a particular item such as a package or shipping envelope. As mentioned above, some of the additional data that can be collected by the optical reader **100** and stored with or separate from the signature data includes but is not limited to dataform data, handwritten text data, typed text data, graphics data, image or picture data, and the like.

As part of its operations, the image processing and analysis circuit **21208** can be designed to perform specialized tasks for different data types. For example, if the generalized classifier circuit **21216** determines that the image data contains typed or machine readable text, the image data can be collected, possibly histogram analyzed, and stored or alternatively, the image data can be transferred to the OCR decoding circuit **21222**. Similarly, if the generalized classifier circuit **21216** determines that the image data includes a graphic element, the image data can be transferred to the graphics analysis circuit **21224** for processing. In one embodiment, the graphics analysis circuit **21224** is configured to recognize and decode predefined graphics. In one such embodiment, the graphics analysis can include determining which, if any, boxes have been selected in the billing and shipping instructions on a shipping label. In a further embodiment, the graphics analysis can include locating and decoding the typed or handwritten text contained in the zip code box on a shipping label. In an alternative embodiment,

the optical reader **100** can be configured to automatically attempt decode operations in addition to the dataform decode, such as OCR decoding or graphics decoding, prior to the activation of the feature extraction circuit **21212**.

In another embodiment, the image processing and analysis circuit **21208** segments the image data into regions and performs a feature extraction and general classification analysis on each region. In one embodiment as shown in FIG. **22f**, the standard rectangular image data window is divided into four equal sized sub-rectangles. In another embodiment shown in FIG. **22g**, the segmentation consists of overlapping regions so that the total area of the segmented regions is larger than that of the complete field of the image data. In FIG. **22g** there are seven shown overlapping regions where each identifying numeral is shown in the center of its region. In a further embodiment shown in FIGS. **22h** and **22i**, the segmentation consists of sample regions (shown as cross-hatched) within the complete field of the image data. In another embodiment, the sampled regions can be based on a preloaded user template that, for example, identifies regions of interest such as a signature region and/or a bar code region, in for example, a shipping label.

In one embodiment, the segmentation process is used to identify the location of a signature in image data the might include additional elements such as dataforms including bar code dataforms, text, graphics, images and the like. In one such embodiment the generalized classifier circuit **21216** classifies the contents of each region of the segmented image data. The region containing the signature is then extracted by the signature data processing circuit **21218**. In one embodiment if multiple regions are indicated as containing signature data, the signature data processing circuit **21218** analyzes the arrangement of these regions to identify the region most likely to contain the image data. In a further embodiment when multiple regions are indicated as containing signature data, the image processing and analysis circuit **21208** establishes a feedback loop where additional segmented regions are generated and analyzed until a single segmented region containing signature data is located.

Additional image processing operations which may be carried out by optical reader **100** are described in U.S. patent application Ser. No. 10/958,779, filed Oct. 5, 2004 entitled, "System And Method To Automatically Discriminate Between A Signature And A Barcode" and incorporated herein by reference in its entirety.

Various applications which may be carried out by any of the optical readers **100** that have been described herein have been described with reference to FIGS. **10**, **11**, **12a** and **12b**. Another application which can be carried out with any optical reader **100** described herein is described with reference to FIGS. **13a-13e**. In FIG. **13a** a motor vehicle **1282** is shown which may be a delivery vehicle or a passenger vehicle. Vehicle **1282** has a license plate **1314**, a vehicle identification number (VIN) sticker **1306**, typically located on the driver's side door jam. The VIN sticker **1306** carries a printed VIN number **1308** and a bar code symbol **1310**. A VIN number is an alphanumeric unique vehicle identification number assigned at the time of manufacture of the vehicle. Vehicle **1282** may further include a VIN plate **1314** (FIG. **13c**) carrying the characters of the VIN number etched on a metal plate and located under the vehicle windshield **1351**, and a vehicle registration sticker **1320**. Vehicle **1282** has a plurality of machine readable vehicle identifiers. Specifically, the characters of license plate **1284** can be OCR decoded by optical reader. Further, VIN sticker **1308** has a VIN bar code **1310** and registration sticker **1320** which may include a plurality of bar code symbols **1322**, **1324** encoding

the vehicle registration number and possibly redundantly encoding the VIN number of vehicle **1282**. The characters etched on VIN plate **1314** can also be subject to OCR decoding by optical reader **100**. Further, the VIN characters of VIN sticker **1306** can be subject to OCR decoding by optical reader **100**. It may be advantageous to utilize an optical reader including light polarizing pixels **250P** having light polarizing filter elements **261** when reading VIN plate **1314** given that specular reflection read conditions are more prevalent when decoding indicia encoded by etching on metal surface.

In an application for utilizing optical reader **100** relative to vehicle **1282**, several identifiers of vehicle **1282** may be decoded and several color pictures of vehicle **1282** may be taken. The decoded message data together with the color picture data may then be uploaded to a remote server **184** (FIG. **10**) which archives and creates accessible web pages containing reports summarizing the identifier and picture information. In one application LAN **170** (FIG. **10**) is a LAN at an automobile insurance claim center, LAN **185** is a distant data archiving center operated by the automobile insurance provider and LAN **2170** is a LAN apart from LAN **170** and LAN **185** and may be located, e.g., at a claim center of the insurance provider other than the claim center in which LAN **170** is located.

Optical reader **100** may be configured so that when an operator actuates a designated user interface control button such as button **3158** (FIG. **9b**) an auto insurance application form **1362** is displayed on display **504** which aids an operator of optical reader **100** in entering data into reader **100**. Form **1362** first prompts an operator to read several machine readable identifiers of vehicle **1282**. Form **1362** prompts an operator to read VIN bar code symbol **1310**, then characters of VIN plate **1314**, then the first registration sticker bar code symbol **1310**, then the second registration sticker bar code symbol **1324**, then the character of the license plate **1284**. The text corresponding to each identifier may be highlighted when data corresponding to the identifier is read. When data corresponding to identifier decode section **1363** of form **1362** is being entered, optical reader **100** is in a decode mode of operation such that actuation of trigger **216** causes optical reader **100** to obtain a decode frame at step **1204** and transfer the decode frame to decode circuit **1702**. The decode frame may contain monochrome image data read from a hybrid monochrome image sensor array **182**, **182A**. Where optical reader **100** has separate picture taking and decoding imaging assemblies as described in connection with FIGS. **17a-17g**, the decode frame at step **1204** is obtained by actuation of the imaging assembly within block **598** (FIG. **17a**). When entry of decoded vehicle identifier information is complete, an operator toggles to line **1365** and clicks an appropriate key of keyboard **508** to indicate that identifier decoding is complete. Form **1362** then prompts an operator to take pictures of vehicle **1282** for purposes of making a record of the damage to vehicle **1282**. The inventor discovered that the incorporation of color filter elements into an image sensor array **182** of optical reader **100** facilitates the obtaining of visual display frames of image data that accurately record damage to a vehicle. With visual display color frames of image data corresponding to vehicle **1282** being stored and/or displayed for visual display, damage to vehicle **1282** can readily be assessed by visual inspection of the visual display frames when displayed on a display **504**, **1504**. When damage records are recorded with color image data, the amount of paint scratched from a vehicle, for example, can readily be assessed by visual inspection. Section **1364** of

display form **1362** prompts an operator to take several color pictures of vehicle. When picture entry section **1364** of form **1362** is being executed, optical reader **100** is in a picture taking mode such that actuation of trigger **216** causes a visual display frame of image data to be obtained at step **1404** (FIG. **14c**). The visual display frame of image data may be output to e.g., a storage device and/or a display device. When data corresponding to form section **1364** is being entered, an operator may use optical reader **100** to take several color pictures of damaged area **1370** of vehicle **1282**. While executing obtain step **1404**, control circuit **552** may selectively read out color image data from color sensitive pixels **250C** as described herein and possibly utilize monochrome image data for enhancement of the information content of the color image data. Where optical reader **100** includes a pair of imaging assemblies as described in connection with FIGS. **17a-17g**, control circuit **552** at step **1404** may actuate color image sensor array **182D** for execution of obtain step **1404**. When an operator inputs a confirmation that all necessary pictures of vehicle **1282** have been taken by toggling to line **1367** and clicking an appropriate key of keyboard **508**, control circuit **552**, which may be incorporated in hand held housing **101**, may format obtained visual display color frames of image data in one or more suitably image file formats, (e.g., .BMP, .TIFF, .PDF, .JPG, .GIF) assemble all the collected decoded vehicle identifier data and all of the visual display color frames of image data corresponding to vehicle **1282** into a transaction data set, and send the transaction data set to distant remote server **184**. Control circuit **552** may date/time stamp the transaction data set on sending. The File Transfer Protocol (FTP) may be utilized to send the transaction data set or another suitable file transferring protocol configured to carry associated decoded vehicle identifier data (such as decoded VIN bar code data and decode vehicle registration bar code data) and color image data. Server **184** may store the received transaction data set into a database as indicated by database **187** including similar information from other vehicles at other claim centers. Server **184** may be configured to create viewable web pages summarizing the transaction set data (e.g., the date/time stamped combined VIN, registration number, license plate number and record-of damage visual display color frames of image data). These web pages may be viewed using any PC in communication with IP network, e.g., PC **172** and PC **2172**.

While the present invention has necessarily been described with reference to a number of specific embodiments, it will be understood that the time, spirit, and scope of the present invention should be determined only with reference to the following claims:

I claim:

1. A bar code reading device comprising:
 - a two-dimensional image sensor array comprising:
 - a first subset of pixels comprising a plurality of monochrome pixels; and
 - a second subset of pixels;
 wherein the first subset of pixels is configured to be addressed independently of the second subset of pixels by the device to read out a plurality of monochrome pixel values;
 wherein the device is configured to interpolate one or more missing pixel values based upon at least a portion of the monochrome pixel values;
 wherein the one or more missing pixel values correspond to positions of one or more pixels from the second subset of pixels; and

59

wherein the device is configured to generate a frame of image data based upon the plurality of monochrome pixel values and the one or more missing pixel values.

2. The device according to claim 1, wherein the device is configured to interpolate the one or more pixels as monochrome pixel values.

3. The device according to claim 1, wherein each of the one or more pixels from the second subset of pixels corresponding to the one or more missing pixel values is disposed adjacent to one or more pixels of the first subset of pixels.

4. The device according to claim 3, wherein the device is configured to interpolate the pixel values of the one or more adjacent pixels to generate each respective missing pixel value.

5. The device according to claim 3, wherein each of the one or more pixels from the second subset of pixels corresponding to the one or more missing pixel values is disposed corner-adjacent to one or more pixels of the first subset of pixels.

6. The device according to claim 3, wherein each of the one or more pixels from the second subset of pixels corresponding to the one or more missing pixel values is disposed side-adjacent to one or more pixels of the first subset of pixels.

7. The device according to claim 1, wherein the device is configured to interpolate a respective missing pixel value of the one or more missing pixel values by combining the monochrome pixel values of at least two of the first subset of pixels.

8. The device according to claim 7, wherein the device is configured to combine the monochrome pixel values of the at least two of the first subset of pixels by averaging the monochrome pixel values for the at least two of the first subset of pixels.

9. The device according to claim 7, wherein the device is configured to combine the monochrome pixel values of the at least two of the first subset of pixels by derivative correlating the monochrome pixel values for the at least two of the first subset of pixels.

10. The device according to claim 7, wherein the at least two of the first subset of pixels are disposed adjacent a position of the respective missing pixel value.

11. The device according to claim 10, wherein the first subset of pixels defines at least two rows of pixels and at least two columns of pixels; wherein the rows are disposed perpendicular to the columns on the image sensor array; wherein the device is further configured to correlate the at least two rows of pixels; wherein the device is further configured to correlate the at least two columns of pixels; wherein, in an instance in which the at least two rows of pixels are more closely correlated than the at least two columns of pixels, the at least two of the first subset of pixels are disposed column-adjacent to the respective missing pixel value; and

wherein, in an instance in which the at least two columns of pixels are more closely correlated than the at least two rows of pixels, the at least two of the first subset of pixels are disposed row-adjacent to the respective missing pixel value.

12. The device according to claim 1 further comprising a bar code decode circuit, wherein the device is configured to decode representations of a decodable indicia captured in the frame of image data.

13. The device according to claim 12, wherein the device is configured to interpolate a respective missing pixel value of the one or more missing pixel values by combining the monochrome pixel values for at least two of the first subset

60

of pixels; wherein the device is configured to determine a longitudinal axis of the decodable indicia; and wherein the at least two of the first subset of pixels are disposed adjacent a position of the respective missing pixel value in a direction of the longitudinal axis.

14. The device according to claim 1, wherein at least the first subset of pixels is configured to be operated in a global shutter mode, wherein all or substantially all of at least the first subset of pixels in the image sensor array are configured to be exposed in the image sensor array in response to an exposure control timing pulse.

15. The device according to claim 1, wherein the second subset of pixels are color-sensitive pixels, each of which includes a wavelength selective filter element.

16. The device according to claim 1, wherein the second subset of pixels are uniformly distributed throughout the image sensor array.

17. The device according to claim 1, wherein the first subset of pixels are uniformly distributed throughout the image sensor array.

18. A method comprising:

providing an optical reading device including a two-dimensional image sensor array, wherein the image sensor array comprises a first subset of pixels comprising a plurality of monochrome pixels, and a second subset of pixels;

addressing the first subset of pixels independently of the second subset of pixels to read out a plurality of monochrome pixel values;

interpolating one or more missing pixel values based upon at least a portion of the monochrome pixel values, wherein the one or more missing pixel values correspond to positions of one or more pixels from the second subset of pixels; and

generating a frame of image data based upon the plurality of monochrome pixel values and the one or more missing pixel values.

19. The method according to claim 18, wherein interpolating one or more missing pixel values comprises interpolating the one or more pixels as monochrome pixel values.

20. The method according to claim 18, wherein each of the one or more pixels from the second subset of pixels corresponding to the one or more missing pixel values is disposed adjacent to one or more pixels of the first subset of pixels.

21. The method according to claim 20, wherein interpolating one or more missing pixel values comprises interpolating the pixel values of the one or more adjacent pixels to generate each respective missing pixel value.

22. The method according to claim 20, wherein each of the one or more pixels from the second subset of pixels corresponding to the one or more missing pixel values is disposed corner-adjacent to one or more pixels of the first subset of pixels.

23. The method according to claim 20, wherein each of the one or more pixels from the second subset of pixels corresponding to the one or more missing pixel values is disposed side-adjacent to one or more pixels of the first subset of pixels.

24. The method according to claim 18, wherein interpolating one or more missing pixel values comprises interpolating a respective missing pixel value of the one or more missing pixel values by combining the monochrome pixel values of at least two of the first subset of pixels.

25. The method according to claim 24, wherein combining the monochrome pixel values of the at least two of the

61

first subset of pixels comprises averaging the monochrome pixel values for the at least two of the first subset of pixels.

26. The method according to claim 24, wherein combining the monochrome pixel values of the at least two of the first subset of pixels comprises derivative correlating the monochrome pixel values for the at least two of the first subset of pixels.

27. The method according to claim 24, wherein the at least two of the first subset of pixels are disposed adjacent a position of the respective missing pixel value.

28. The method according to claim 27, wherein the first subset of pixels defines at least two rows of pixels and at least two columns of pixels; wherein the rows are disposed perpendicular to the columns on the image sensor array; wherein the method further comprises:

correlating the at least two rows of pixels;

correlating the at least two columns of pixels;

determining, in an instance in which the at least two rows of pixels are more closely correlated than the at least two columns of pixels, that the at least two of the first subset of pixels are disposed column-adjacent to the respective missing pixel value; and

determining, in an instance in which the at least two columns of pixels are more closely correlated than the at least two rows of pixels, that the at least two of the first subset of pixels are disposed row-adjacent to the respective missing pixel value.

29. The method according to claim 18, wherein the optical reading device further comprising a bar code decode circuit, and wherein the method further comprises decoding representations of a decodable indicia captured in the frame of image data.

30. The method according to claim 29 wherein interpolating one or more missing pixel values comprises interpolating a respective missing pixel value of the one or more missing pixel values by:

combining the monochrome pixel values for at least two of the first subset of pixels; and

determining a longitudinal axis of the decodable indicia; wherein the at least two of the first subset of pixels are disposed adjacent a position of the respective missing pixel value in a direction of the longitudinal axis.

31. The method according to claim 18, wherein at least the first subset of pixels is configured to be operated in a global shutter mode, wherein all or substantially all of at least the first subset of pixels in the image sensor array are configured to be exposed in the image sensor array in response to an exposure control timing pulse.

32. The method according to claim 18, wherein the second subset of pixels are color-sensitive pixels, each of which includes a wavelength selective filter element.

33. The method according to claim 18, wherein the second subset of pixels are uniformly distributed throughout the image sensor array.

34. The method according to claim 18, wherein the first subset of pixels are uniformly distributed throughout the image sensor array.

35. A computer program product comprising a non-transitory computer readable storage medium and computer program instructions stored therein, the computer program instructions comprising program instructions configured to:

address a first subset of pixels of a two-dimensional image sensor array independently of a second subset of pixels of the image sensor array to read out a plurality of monochrome pixel values;

interpolate one or more missing pixel values based upon at least a portion of the monochrome pixel values,

62

wherein the one or more missing pixel values correspond to positions of one or more pixels from the second subset of pixels; and

generate a frame of image data based upon the plurality of monochrome pixel values and the one or more missing pixel values.

36. The computer program product according to claim 35, wherein interpolating one or more missing pixel values comprises interpolating the one or more pixels as monochrome pixel values.

37. The computer program product according to claim 35, wherein each of the one or more pixels from the second subset of pixels corresponding to the one or more missing pixel values is disposed adjacent to one or more pixels of the first subset of pixels.

38. The computer program product according to claim 37, wherein interpolating one or more missing pixel values comprises interpolating the pixel values of the one or more adjacent pixels to generate each respective missing pixel value.

39. The computer program product according to claim 37, wherein each of the one or more pixels from the second subset of pixels corresponding to the one or more missing pixel values is disposed corner-adjacent to one or more pixels of the first subset of pixels.

40. The computer program product according to claim 37, wherein each of the one or more pixels from the second subset of pixels corresponding to the one or more missing pixel values is disposed side-adjacent to one or more pixels of the first subset of pixels.

41. The computer program product according to claim 35, wherein interpolating one or more missing pixel values comprises interpolating a respective missing pixel value of the one or more missing pixel values by combining the monochrome pixel values of at least two of the first subset of pixels.

42. The computer program product according to claim 41, wherein combining the monochrome pixel values of the at least two of the first subset of pixels comprises averaging the monochrome pixel values for the at least two of the first subset of pixels.

43. The computer program product according to claim 41, wherein combining the monochrome pixel values of the at least two of the first subset of pixels comprises derivative correlating the monochrome pixel values for the at least two of the first subset of pixels.

44. The computer program product according to claim 41, wherein the at least two of the first subset of pixels are disposed adjacent a position of the respective missing pixel value.

45. The computer program product according to claim 44, wherein the first subset of pixels defines at least two rows of pixels and at least two columns of pixels; wherein the rows are disposed perpendicular to the columns on the image sensor array; wherein the computer program product is further configured to:

correlate the at least two rows of pixels;

correlate the at least two columns of pixels;

determine, in an instance in which the at least two rows of pixels are more closely correlated than the at least two columns of pixels, that the at least two of the first subset of pixels are disposed column-adjacent to the respective missing pixel value; and

determine, in an instance in which the at least two columns of pixels are more closely correlated than the at least two rows of pixels, that the at least two of the

first subset of pixels are disposed row-adjacent to the respective missing pixel value.

46. The computer program product according to claim **35**, further configured to decode, via a bar code decode circuit, representations of a decodable indicia captured in the frame 5 of image data.

47. The computer program product according to claim **46** wherein interpolating one or more missing pixel values comprises interpolating a respective missing pixel value of the one or more missing pixel values by: 10

combining the monochrome pixel values for at least two of the first subset of pixels; and

determining a longitudinal axis of the decodable indicia; wherein the at least two of the first subset of pixels are disposed adjacent a position of the respective missing 15 pixel value in a direction of the longitudinal axis.

48. The computer program product according to claim **35**, wherein at least the first subset of pixels is configured to be operated in a global shutter mode, wherein all or substantially all of at least the first subset of pixels in the image 20 sensor array are configured to be exposed in the image sensor array in response to an exposure control timing pulse.

49. The computer program product according to claim **35**, wherein the second subset of pixels are color-sensitive pixels, each of which includes a wavelength selective filter 25 element.

50. The computer program product according to claim **35**, wherein the second subset of pixels are uniformly distributed throughout the image sensor array.

51. The computer program product according to claim **35**, 30 wherein the first subset of pixels are uniformly distributed throughout the image sensor array.

* * * * *