



US009456661B2

(12) **United States Patent**  
**Dieter et al.**

(10) **Patent No.:** **US 9,456,661 B2**  
(45) **Date of Patent:** **Oct. 4, 2016**

(54) **STEAMING BAG FOR FOOTWEAR  
CUSTOMIZATION**

(71) Applicant: **NIKE, Inc.**, Beaverton, OR (US)  
(72) Inventors: **William M. Dieter**, Portland, OR (US);  
**Alexandre Baudouin**, Portland, OR  
(US); **Brian D. Baker**, Portland, OR  
(US)

(73) Assignee: **NIKE, Inc.**, Beaverton, OR (US)

(\* ) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 338 days.

(21) Appl. No.: **14/188,816**

(22) Filed: **Feb. 25, 2014**

(65) **Prior Publication Data**

US 2014/0169704 A1 Jun. 19, 2014

**Related U.S. Application Data**

(62) Division of application No. 14/033,656, filed on Sep.  
23, 2013, now Pat. No. 8,720,835, which is a division  
of application No. 13/475,538, filed on May 18, 2012,  
now Pat. No. 8,579,241, which is a division of

(Continued)

(51) **Int. Cl.**  
*A43D 95/12* (2006.01)  
*A43D 95/10* (2006.01)

(Continued)

(52) **U.S. Cl.**  
CPC ..... *A43D 95/12* (2013.01); *A43B 7/28*  
(2013.01); *A43B 23/0215* (2013.01); *A43D*  
*999/00* (2013.01); *A47J 36/06* (2013.01);  
*A47J 36/20* (2013.01); *B65D 85/187*  
(2013.01)

(58) **Field of Classification Search**  
CPC .... *A43D 95/10*; *A43D 95/12*; *A43D 999/00*;  
*A47J 36/20*  
USPC ..... 383/41, 102, 902  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,170,541 A 2/1916 Jacobus  
1,733,486 A \* 10/1929 Eager ..... A43D 95/12  
12/142 K

(Continued)

FOREIGN PATENT DOCUMENTS

CN 200973696 11/2007  
DE 19825615 7/1999  
KR 20080001508 6/2008

OTHER PUBLICATIONS

“Comment agrandir des chaussures-Questions Trucs, Astuces ou  
Remedes de Grand-mere maison”, Sep. 8, 2008. Retrieved from the  
Internet: [http://www.trucmania.com/Questions/Vetements/Com-  
ment-agrandir-des-chaussures.html](http://www.trucmania.com/Questions/Vetements/Comment-agrandir-des-chaussures.html). Retrieved on Mar. 2, 2011.

(Continued)


*Primary Examiner* — Robert B Davis

(74) *Attorney, Agent, or Firm* — Plumsea Law Group,  
LLC

(57) **ABSTRACT**

A footwear customization kit is disclosed. The kit comprises  
a container including an article of footwear, a stand, a  
steaming bag and a set of instructions. The article of  
footwear includes a customizable portion that can be  
deformed when heated. The stand and the steaming bag can  
be used to heat the article of footwear in a steam environ-  
ment. The steaming bag includes a central portion and a  
peripheral portion. The central portion of the steaming bag  
defines an interior cavity for receiving the article of foot-  
wear. The peripheral portion can include grasping holes for  
grabbing the steaming bag in the steam environment. The  
steaming bag can expand from a flattened configuration  
when filled with the article of footwear in the steam envi-  
ronment.

**20 Claims, 19 Drawing Sheets**



**Related U.S. Application Data**

application No. 13/069,460, filed on Mar. 23, 2011, now Pat. No. 8,251,207, which is a division of application No. 12/562,897, filed on Sep. 18, 2009, now Pat. No. 7,958,993.

(51) **Int. Cl.**

*A43B 7/28* (2006.01)  
*A43B 23/02* (2006.01)  
*A43D 999/00* (2006.01)  
*A47J 36/06* (2006.01)  
*A47J 36/20* (2006.01)  
*B65D 85/18* (2006.01)

(56)

**References Cited**

U.S. PATENT DOCUMENTS

1,822,297	A	9/1931	Kemery	
2,098,735	A	11/1937	Yentis	
2,440,393	A	4/1948	Clark	
2,617,204	A	11/1952	Mann	
2,648,854	A	8/1953	Otsuka	
2,767,855	A	10/1956	Brown	
3,058,237	A	10/1962	King	
3,172,796	A *	3/1965	Gulker .....	B31B 19/36 156/269
3,241,660	A	3/1966	Cathcart, Jr. et al.	
3,407,421	A	10/1968	Butlin	
3,535,418	A	10/1970	Daum et al.	
3,586,279	A	6/1971	Benson	
3,611,501	A	10/1971	Daum et al.	
3,848,287	A	11/1974	Simonsen	
3,860,115	A *	1/1975	Laske .....	A46B 17/04 15/247
4,428,089	A	1/1984	Dawber et al.	
4,499,817	A *	2/1985	Janssen .....	A47J 36/022 99/403
4,889,238	A	12/1989	Batchelor	
4,901,390	A	2/1990	Daley	
4,964,229	A	10/1990	Laberge	
5,003,708	A	4/1991	Daley	
5,080,237	A	1/1992	Hefner	
5,083,910	A	1/1992	Abshire et al.	

5,123,180	A	6/1992	Nannig et al.
5,127,529	A	7/1992	Martinez et al.
5,188,244	A	2/1993	Hollstegge
5,516,072	A	5/1996	Shinno
5,714,098	A	2/1998	Potter
5,733,647	A	3/1998	Moore, III et al.
5,746,015	A	5/1998	Clement et al.
5,797,862	A	8/1998	Lamont
5,879,725	A	3/1999	Potter
5,885,622	A	3/1999	Daley
6,026,595	A	2/2000	Curry
6,247,250	B1	6/2001	Hauser
6,346,210	B1	2/2002	Swartz et al.
6,703,142	B2	3/2004	Snow
7,008,386	B2	3/2006	Alaimo et al.
7,257,907	B2	8/2007	Green
7,458,173	B2	12/2008	Kielt et al.
7,958,993	B2	6/2011	Baker et al.
8,251,207	B2	8/2012	Baker et al.
8,579,241	B2	11/2013	Baker et al.
2002/0050080	A1	5/2002	Vasyli
2004/0031169	A1	2/2004	Jensen et al.
2004/0194348	A1	10/2004	Campbell et al.
2004/0194352	A1	10/2004	Campbell et al.
2005/0262757	A1	12/2005	Wong et al.
2006/0006079	A1	1/2006	Brooks
2006/0049181	A1	3/2006	Tuhkru et al.
2008/0034616	A1	2/2008	Rhenter
2009/0044426	A1	2/2009	Levine
2009/0119950	A1	5/2009	Kohatsu et al.
2011/0068023	A1	3/2011	Baker et al.
2011/0167573	A1	7/2011	Baker et al.
2012/0227191	A1	9/2012	Baker et al.

OTHER PUBLICATIONS

Invitation to Pay Additional Fees and, Where Applicable, Protest Fee (with Search Report) mailed Mar. 18, 2011 in PCT Application No. PCT/US2010/049059.

The International Search Report and Written Opinion mailed May 25, 2011 in International Application No. PCT/US2010/049059.

International Preliminary Report on Patentability (including Written Opinion of the ISA) mailed Mar. 29, 2012 in International Application No. PCT/US2010/049059.

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3






FIG. 5




FIG. 6




FIG. 7






FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16






FIG. 17






FIG. 19




FIG. 20




FIG. 21

## STEAMING BAG FOR FOOTWEAR CUSTOMIZATION

### CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a division of U.S. application Ser. No. 14/033,656, entitled "Footwear Customization Kit Including a Stand", filed on Sep. 23, 2013 and allowed on Jan. 9, 2014, which application is a division of U.S. Pat. No. 8,579,241, currently U.S. application Ser. No. 13/475,538, entitled "Footwear Customization Kit", filed on May 18, 2012 and issued on Nov. 12, 2013, which application is a division of U.S. Pat. No. 8,251,207, currently U.S. application Ser. No. 13/069,460, entitled "Footwear Customization Kit", filed on Mar. 23, 2011, and issued on Aug. 28, 2012, which application is a division of U.S. Pat. No. 7,958,993, entitled "Footwear Customization Kit", filed on Sep. 18, 2009, and issued on Jun. 14, 2011, the disclosure of which applications are hereby incorporated by reference in their entirety.

### BACKGROUND

The present invention relates generally to an article of footwear, and in particular to a customization kit for an article of footwear.

Tuhkru et al. (U.S. patent application publication number 2006/0049181) teaches a perfect fit system for leather shoes. Tuhkru teaches a system that uses two heating bags filled with sea salt. Tuhkru teaches microwaving the bags for several minutes and then placing the bags inside of a pair of shoes. The shoes can be placed in a heat conservation bag. The process is completed by cooling the heated shoes on the foot.

Laberge (U.S. Pat. No. 4,964,229) teaches a method and apparatus for vacuum molding multi-layer footwear. Laberge teaches multi-layer footwear formed of laminated layers of material. The layers are capable of being heated to a degree at which the footwear, when placed in a vacuum bag or compression chamber, is molded to adopt the shape of the foot inside the footwear. The footwear is heated to the point where the synthetic components of the layers of material are flexible under thermoforming conditions.

Simonsen (U.S. Pat. No. 3,848,287) teaches a method and apparatus for custom molding boots and shoes. Simonsen teaches a boot or shoe formed of a thermoplastic material. To better conform it to the wearer's foot, the wearer puts his foot within the boot and places it within a bag of a plastic material having a melting temperature higher than the molding temperature of the boot. A vacuum line is also placed within the bag and the top of the bag is sealed around the user's leg.

The related art lacks provisions for allowing a user to easily customize an article of footwear. There is a need for a design that addresses this problem of the related art.

### SUMMARY

In one aspect, the invention provides a kit of parts, comprising: an article of footwear including a customizable portion, the customizable portion being customizable when heated above a predetermined temperature; a stand for holding the article of footwear in a steam environment; a steaming bag configured to cover the article of footwear and the stand in the steam environment; a set of instructions; and where the set of instructions includes information for heat-

ing the article of footwear and the customizable portion in the steam environment using the stand and the steaming bag.

In another aspect, the invention provides a kit of parts, comprising: an article of footwear including a customizable portion, the customizable portion being customizable when heated above a predetermined temperature; a stand for holding the article of footwear in a steam environment; a steaming bag configured to cover the article of footwear and the stand in the steam environment; and where the stand includes a base portion that is configured to fit inside of a steaming device.

In another aspect, the invention provides a kit of parts, comprising: an article of footwear including a customizable portion; a stand for holding the article of footwear in a steam environment; a steaming bag configured to cover the article of footwear and the stand in the steam environment; a container for storing the article of footwear, the steaming bag and the stand, the container having an open position and a closed position; and where the stand is configured to fit inside the container with the article of footwear in the closed position.

In another aspect, the invention provides a kit of parts, comprising: an article of footwear including a customizable portion, the customizable portion being customizable when heated above a predetermined temperature; the article of footwear including a throat opening having a first width; a stand for holding the article of footwear in a steam environment; the stand comprising a base portion and a footwear engaging portion; the footwear engaging portion further including a lower portion attached to the base portion and an upper portion disposed adjacent to the lower portion; a steaming bag configured to cover the article of footwear and the stand in the steam environment; and where the upper portion has a second width that is substantially less than the first width of the throat opening and wherein the lower portion has a third width that is substantially greater than the first width and wherein the upper portion can be inserted through the throat opening.

In another aspect, the invention provides a stand for holding an article of footwear in a steam environment, comprising: a base portion for supporting the stand; a footwear engaging portion oriented in at an angle with respect to the base portion; the footwear engaging portion further including a first end portion, a second end portion and an intermediate portion disposed between the first end portion and the second end portion; a detachable portion; the stand having a first position for storing the stand in a container with the article of footwear and a second position for holding the article of footwear in the steam environment; and where the detachable portion is attached to the base portion in the first position and wherein the detachable portion is attached to the intermediate portion in the second position.

In another aspect, the invention provides a stand for holding an article of footwear in a steam environment, comprising: a base portion for supporting and a footwear engaging portion; the footwear engaging portion having a folded position for storing the stand in a container with the article of footwear and a raised position for holding the article of footwear in the steam environment; and where the footwear engaging portion is substantially angled with respect to the base portion in the raised position and wherein the base portion and the footwear engaging portion have a substantially flattened configuration when the footwear engaging portion is in the folded position.

In another aspect, the invention provides a steaming bag for use with an article of footwear in a steam environment,

3

comprising: a central portion including an interior cavity for receiving the article of footwear; a peripheral portion extending outwardly from the central portion; the central portion having a first temperature when the steaming bag is placed over an article of footwear in the steam environment and the peripheral portion having a second temperature; and where the first temperature is substantially greater than the second temperature.

In another aspect, the invention provides a steaming bag for use with an article of footwear in a steam environment, comprising: a central portion including an interior cavity for receiving the article of footwear; a first peripheral edge including a peripheral opening in fluid communication with the interior cavity, the peripheral opening extending through a substantial majority of the first peripheral edge; a second peripheral edge disposed opposite of the first peripheral edge; and where the width of the interior cavity decreases from the first peripheral edge to the second peripheral edge.

In another aspect, the invention provides An article of footwear, comprising: an upper comprising a customizable portion that is made of a first material; the article of footwear comprising a portion that is made of a second material that is different from the first material; the first material and the second material configured to be deformed when heated above a predetermined temperature; where the first material has a first rigidity after being heated above the predetermined temperature and cooled below the predetermined temperature; and where the second material has a second rigidity after being heated above the predetermined temperature and cooled below the predetermined temperature, the second rigidity being substantially different from the first rigidity.

Other systems, methods, features and advantages of the invention will be, or will become, apparent to one of ordinary skill in the art upon examination of the following figures and detailed description. It is intended that all such additional systems, methods, features and advantages be included within this description and this summary, be within the scope of the invention, and be protected by the following claims.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The invention can be better understood with reference to the following drawings and description. The components in the figures are not necessarily to scale, emphasis instead being placed upon illustrating the principles of the invention. Moreover, in the figures, like reference numerals designate corresponding parts throughout the different views.

FIG. 1 is an isometric view of an embodiment of a container for a footwear customization kit;

FIG. 2 is a top down view of an embodiment of a footwear customization kit;

FIG. 3 is an isometric view of an embodiment of a footwear customization kit with the components packed in a container;

FIG. 4 is an isometric view of an embodiment of a footwear customization kit with the components outside of the container;

FIG. 5 is an isometric enlarged view of an embodiment of a set of instructions associated with a footwear customization kit;

FIG. 6 is an exploded isometric view of an embodiment of the components of a footwear customization kit being positioned in a steam environment;

4

FIG. 7 is an isometric view of an embodiment of the components of a footwear customization kit positioned within a steam environment;

FIG. 8 is an isometric view of an embodiment of a steaming bag being removed from an article of footwear;

FIG. 9 is an isometric view of an embodiment of an article of footwear in a heated condition and a foot preparing to insert into the article of footwear;

FIG. 10 is an isometric view of an embodiment of an article of footwear with a customizable portion conforming to the contours of a foot;

FIG. 11 is an isometric view of an embodiment of an article of footwear with a customizable portion retaining a customized geometry after a foot has been removed;

FIG. 12 is an isometric view of an embodiment of a stand for a footwear customization system including a detachable portion attached to a base portion of the stand;

FIG. 13 is an isometric view of an embodiment of a stand for a footwear customization system including a detachable portion that has been removed;

FIG. 14 is an isometric view of an embodiment of a stand for a footwear customization system including a detachable portion that has been placed at an intermediate portion;

FIG. 15 is an isometric view of an embodiment of a stand for a footwear customization system in a folded position;

FIG. 16 is an isometric view of an embodiment of a stand for a footwear customization system in a raised position;

FIG. 17 is an isometric view of an embodiment of an article of footwear including a customizable portion and a customizable insert;

FIG. 18 is an isometric view of an embodiment of an article of footwear including a customizable portion and a customizable insert being heated in a steam environment;

FIG. 19 is an isometric view of an embodiment of an article of footwear including a customizable portion and a customizable insert in a heated condition prior to a foot being inserted;

FIG. 20 is an isometric view of an embodiment of an article of footwear including a customizable portion and a customizable insert in a heated condition as a foot has been inserted; and

FIG. 21 is an isometric view of an embodiment of an article of footwear including a customizable portion and a customizable insert in a cooled condition after a foot has been removed.

#### DETAILED DESCRIPTION

FIGS. 1 through 5 illustrate an embodiment of footwear customization kit 100, also referred hereafter as kit 100. Footwear customization kit 100 can be used with any type of footwear. In addition, the principles discussed throughout this detailed description may not be limited in use to footwear. Similar principles could be applied to customization kits for various different types of apparel as well.

In some embodiments, footwear customization kit 100 may be used by a customer at home. For example, in some cases, a customer could purchase footwear customization kit 100 at a retail location and bring kit 100 home. In other cases, kit 100 may be shipped to an address associated with the customer. In other embodiments, footwear customization kit 100 could be used at any other location, such as a retail store or a kiosk.

Kit 100 may include container 102, which is shown in a closed position in FIG. 1. Container 102 can be any type of container configured to store at least one article of footwear. In some cases, container 102 may be a box. In an exemplary

embodiment, container **102** may be a shoebox that is configured to store footwear. In particular, container **102** may have a generally rectangular shape and can include lower portion **104** and lid **106**.

Referring to FIGS. **2** through **5**, kit **100** can include various different components for customizing one or more articles of footwear. In one embodiment, kit **100** can include pair of footwear **200**. Pair of footwear **200** may further comprise first article of footwear **202** and second article of footwear **204**. Generally, articles of footwear associated with kit **100** can be any type of footwear. For clarity, the following detailed description discusses articles of footwear in the form of sports shoes, but it should be noted that in other embodiments any other type of footwear could be used including, but not limited to: hiking boots, soccer shoes, football shoes, sneakers, rugby shoes, basketball shoes, baseball shoes as well as other kinds of shoes. Articles of footwear associated with kit **100** may also take the form of any non-athletic shoe, including, but not limited to, dress shoes, loafers, sandals, and boots. An individual skilled in the relevant art will appreciate, therefore, that the concepts disclosed herein apply to a wide variety of footwear styles, in addition to the specific style discussed in the following material and depicted in the accompanying figures.

First article of footwear **202** and second article of footwear **204** may be oriented for a left foot and a right foot, respectively. For purposes of clarity, the following detailed description discusses first article of footwear **202**, but it will be understood that each of the features discussed for first article of footwear **202** could also apply to second article of footwear **204**. Furthermore, first article of footwear **202** may also be referred to as article **202** throughout the remainder of this detailed description.

Referring to FIG. **4**, for purposes of reference, article **202** may be divided into forefoot portion **10**, midfoot portion **12** and heel portion **14**. Forefoot portion **10** may be generally associated with the toes and joints connecting the metatarsals with the phalanges. Midfoot portion **12** may be generally associated with the arch of a foot. Likewise, heel portion **14** may be generally associated with the heel of a foot, including the calcaneus bone. In addition, article **202** may include lateral side **16** and medial side **18**. In particular, lateral side **16** and medial side **18** may be opposing sides of article **202**. Furthermore, both lateral side **16** and medial side **18** may extend through forefoot portion **10**, midfoot portion **12** and heel portion **14**.

It will be understood that forefoot portion **10**, midfoot portion **12** and heel portion **14** are only intended for purposes of description and are not intended to demarcate precise regions of article **202**. Likewise, lateral side **16** and medial side **18** are intended to represent generally two sides of an article, rather than precisely demarcating article **202** into two halves. In addition, forefoot portion **10**, midfoot portion **12** and heel portion **14**, as well as lateral side **16** and medial side **18**, can also be applied to individual components of an article, such as a sole structure and/or an upper.

For consistency and convenience, directional adjectives are employed throughout this detailed description corresponding to the illustrated embodiments. The term “longitudinal” as used throughout this detailed description and in the claims refers to a direction extending a length or major axis of an article. In some cases, the longitudinal direction may extend from a forefoot portion to a heel portion of the article. Also, the term “lateral” as used throughout this detailed description and in the claims refers to a direction extending a width or minor axis of an article. In other words, the lateral direction may extend between a medial side and

a lateral side of an article. Furthermore, the term “vertical” as used throughout this detailed description and in the claims refers to a direction generally perpendicular to a lateral and longitudinal direction. For example, in cases where an article is planted flat on a ground surface, the vertical direction may extend from the ground surface upward. In addition, the term “proximal” refers to a portion of a footwear component that is closer to a portion of a foot when an article of footwear is worn. Likewise, the term “distal” refers to a portion of a footwear component that is further from a portion of a foot when an article of footwear is worn. It will be understood that each of these directional adjectives may be applied to individual components of an article, such as an upper and/or a sole structure.

Referring to FIGS. **2** through **4**, article **202** can include upper **222**. Generally, upper **222** may be any type of upper. In particular, upper **222** may have any design, shape, size and/or color. For example, in embodiments where article **202** is a basketball shoe, upper **222** could be a high top upper that is shaped to provide high support on an ankle. In embodiments where article **202** is a running shoe, upper **222** could be a low top upper.

Article **202** can include sole structure **224**. In some embodiments, sole structure **224** may be configured to provide traction for article **202**. In addition to providing traction, sole structure **224** may attenuate ground reaction forces when compressed between the foot and the ground during walking, running or other ambulatory activities. The configuration of sole structure **224** may vary significantly in different embodiments to include a variety of conventional or non-conventional structures. In some cases, the configuration of sole structure **224** can be configured according to one or more types of ground surfaces on which sole structure **224** may be used. Examples of ground surfaces include, but are not limited to: natural turf, synthetic turf, dirt, as well as other surfaces.

Sole structure **224** extends between the foot and the ground when article **202** is worn. In different embodiments, sole structure **224** may include different components. For example, sole structure **224** may include an outsole, a midsole, and/or an insole. In some cases, one or more of these components may be optional.

Article **202** can be configured with one or more customizable portions. The term “customizable portion” as used throughout this detailed description and in the claims refers to a portion with characteristics that can be customized. Examples of such characteristics include, but are not limited to, size, shape, material properties (such as rigidity and/or flexibility) as well as other properties. In an exemplary embodiment, a customizable portion may be a portion with a size and/or shape that can be adjusted. In addition, in some cases, the material properties of a customizable portion could also be adjusted.

The characteristics of customizable portions can be varied in different ways. In some embodiments, a customizable portion can be varied through a curing process. In other words, the customizable portion may be heated above a predetermined temperature and modified before cooling the customizable portion so that the modifications are retained. In other embodiments, the characteristics of customizable portions can be varied through the use of pressure, chemical additives or other known methods of changing the characteristics of material including the size, shape, rigidity, flexibility and/or other properties. In still other embodiments, a combination of heat, pressure and/or chemicals could be used to modify the customizable portion.



Generally, article **202** can comprise one or more customizable portions. In some embodiments, sole structure **224** may be associated with one or more customizable portions. In other embodiments, upper **222** may be associated with one or more customizable portions. In some cases, a customizable portion may be associated with forefoot portion **10**, midfoot portion **12** and/or heel portion **14** of upper **222**. In other cases, a customizable portion may be associated with any combination of different portions of upper **222**. In an exemplary embodiment, upper **222** may include customizable portion **230**. In particular, customizable portion **230** may extend through a substantial majority of upper **222**. In some cases, customizable portion **230** may coincide with upper **222**. Using this arrangement, upper **222** may be custom shaped to the specific geometry of the foot of a user to enhance comfort and fit.

In different embodiments, customizable portions can be made from any known materials or combination of materials. Examples of materials that may be used include, but are not limited to: any kind of thermoset polymers, thermoplastics, thermoset resins (such as epoxy, vinyl ester and polyester), synthetic leathers including polymeric leathers and loric, as well as any other kinds of materials with customizable characteristics. In an exemplary embodiment, a customizable portion may be constructed as a synthetic leather comprising two polymer layers that sandwich a canvas sheet. Moreover, a glue used to bond the polymer layers to the canvas may be configured with a relatively low melting point. When steamed, this glue can stretch or shrink to accommodate a customized shape. Although the current embodiment discusses a three-layered construction, other customizable portions could incorporate any other number of layers including a single layer construction.

In order to modify customizable portion **230**, article **202** may be heated above a predetermined temperature. For example, in embodiments where a customizable portion may transition between a crystalline phase and a liquid like phase, the predetermined temperature can be a glass transition temperature. In some cases, the glass transition temperature is useful in characterizing amorphous solids such as plastics or similar materials that may not have a true melting point. However, in other cases, the predetermined temperature can be some other temperature at which a customizable portion may become substantially more deformable. In some cases, article **202** may be placed in an oven. In other cases, article **202** may be heated using steam. In an exemplary embodiment, article **202** may be heated in any steam environment. A steam environment can be created in different ways. In some cases, a steam environment can be created using a pot with water that may be boiled to create steam. In other cases, any other devices or mechanisms for creating steam can be used. By selecting materials for a customizable portion that become substantially more deformable at temperatures less than or equal to the temperature of steam, a customizable portion can be activated by applying steam to an article of footwear.

A footwear customization kit can include provisions to facilitate steaming an article of footwear for modifying one or more customizable portions. In one embodiment, footwear customization kit **100** can include stand **302** for holding article **202** above or within a steaming device. Stand **302** can include base portion **304** and footwear engaging portion **306**. Base portion **304** may be configured to engage a portion of a steaming device that is used for creating a steam environment. For example, in embodiments where the steaming device is a pot, base portion **304** may engage a

bottom interior surface of the pot. In some cases, footwear engaging portion **306** may extend generally perpendicularly from base portion **306**.

Referring now to FIG. **4**, in different embodiments, the shape of base portion **304** and/or footwear engaging portion **306** may vary. Base portion **304** may have an approximately two dimensional shape. Examples of different shapes for base portion **304** include, but are not limited to, rounded shapes, rectangular shapes, polygonal shapes, regular shapes, irregular shapes as well as any other kind of shapes. In the current embodiment, base portion **304** may have an approximately rectangular shape. In addition, footwear engaging portion **306** may have an approximately two dimensional shape that extends from base portion **304** in a perpendicular manner. Examples of different shapes for footwear engaging portion **306** include, but are not limited to any of the shapes discussed above for base portion **304**. In an exemplary embodiment, footwear engaging portion **306** may have an irregular shape.

In some cases, footwear engaging portion **306** can comprise distinct portions that are associated with different portions of an article of footwear. In some embodiments, footwear engaging portion **306** may include lower portion **310** and upper portion **312**. Lower portion **310** may be disposed adjacent to base portion **304**. In some cases, lower portion **310** may have a substantially larger width than upper portion **312**. In particular, upper portion **312** may be narrow enough to insert into a throat opening of an article. In contrast, lower portion **310** may be substantially wider than upper portion **312**. In particular, lower portion **310** may be wider than the throat opening of an upper. In some cases, footwear engaging portion **306** can also include shoulder portion **314** that extends between lower portion **310** and upper portion **312**. In one embodiment, the width of shoulder portion **314** may vary between lower portion **310** and upper portion **312**. With this arrangement, the throat opening of an article may rest against shoulder portion **314** to help hold article **202** in place and in a generally upright position.

Stand **302** may be associated with width  $W1$ , length  $L1$  and height  $H1$ . In particular, the dimensions of base portion **304** may be characterized width  $W1$  and length  $L1$ . In addition, the dimensions of footwear engaging portion **306** may be characterized by height  $H1$  and width  $W1$ . In some cases, lower portion **310** may be associated with width  $W1$  and upper portion **312** may be associated with width  $W2$  that substantially less than width  $W1$ .

In different embodiments, the dimensions of stand **302** can vary. In some cases, width  $W1$  of stand **302** and width  $W2$  of upper portion **312** can be varied in order to accommodate articles of varying sizes. In some cases, width  $W2$  of upper portion **312** may be substantially smaller than width  $W4$  throat opening **250** of article **202**. This allows upper portion **312** to insert into forefoot portion **10** of article **202** through throat opening **250**. In addition, in some cases, width  $W1$  of lower portion **310** may be substantially larger than width  $W4$  of throat opening **250** of article **202**. This arrangement may prevent article **202** from sliding too far down footwear engaging portion **306**.

In addition, in some cases, the values of width  $W1$  and length  $L1$  may be selected so that base **304** is large enough to maintain an article of footwear in an upright position. In other words, length  $L1$  and width  $W1$  may be chosen to prevent footwear engaging portion **306** and an article of footwear disposed on footwear engaging portion **306** from tipping over. Additionally, length  $L1$  and width  $W1$  may be selected so that base portion **304** fits within a portion of a steaming device. For example, in embodiments where the

steaming device is a pot with a predetermined diameter, length L1 and width W1 may be selected to fit within the diameter of the pot.

In some embodiments, stand 302 may be configured to fit within container 102. In other words, the dimensions of stand 302 may be selected to allow stand 302 to be packed within container 102. In particular, the length, width and height of stand 302 may be selected to be smaller than a first dimension, a second dimension and a third dimension of container 102. Referring to FIG. 3, container 102 includes length L2, width W3 and height H2. To fit stand 302 within container 102, stand 302 may be oriented so that footwear engaging portion 306 extends along the length of container 102. Furthermore, stand 302 may be oriented so that length L1 and width W1 of stand 302 may be oriented along the width and height of container 102, respectively. In order to ensure that stand 302 fits within container 102 when container 102 is in the closed position, the dimensions of stand 302 may be selected so that length L1 is substantially less than width W3, width W1 is substantially less than height H2 and height H1 is substantially less than length L2. Moreover, the overall shape of stand 302 allows for easy insertion of footwear engaging portion 306 between first article of footwear 202 and second article of footwear 204 within container 102.

In the current embodiment, stand 302 may be configured as a wired frame. In other embodiments, however, stand 302 could be configured in any other manner. Further examples of different configurations for stand 302 are discussed later in this detailed description.

Referring back to FIG. 4, kit 100 can include steaming bag 402. In some embodiments, steaming bag 402 may comprise first peripheral edge 421, second peripheral edge 422, third peripheral edge 423 and fourth peripheral edge 424. Furthermore, steaming bag 402 may comprise central portion 404 that includes interior cavity 410. In some cases, steaming bag 402 may further comprise first peripheral portion 406 and second peripheral portion 408 that extend from central portion 404 to first peripheral edge 421 and second peripheral edge 422, respectively. First peripheral portion 406 and second peripheral portion 408 may include first end portions 436 disposed adjacent to fourth peripheral edge 424 and second end portions 438 disposed adjacent to third peripheral edge 426. In addition, third peripheral edge 423 may include peripheral opening 414 that provides access to interior cavity 410 of central portion 404. In some, but not all embodiments, fourth peripheral edge 424 may include vent 416 that provides a secondary access for central portion 404. In other words, vent 416 is an optional opening and may not be included in all embodiments.

In some embodiments, the shapes of first peripheral portion 406 and second peripheral portion 408 may vary. In some cases, first peripheral portion 406 and second peripheral portion 408 may be substantially rectangular portions or strip like portions with constant widths. In other cases, first peripheral portion 406 and second peripheral portion 408 may have variable widths. In an exemplary embodiment, for example, first end portions 436 of first peripheral portion 406 and second peripheral portion 408 may be substantially wider than second end portions 438 of first peripheral portion 406 and second peripheral portion 408. In other words, first peripheral portion 406 and second peripheral portion 408 are much larger at first end portions 436 than at second end portions 438. Moreover, this arrangement may provide central portion with a width that tapers from the widest point at third peripheral edge 423 to the narrowest point at fourth peripheral edge 424.

Steaming bag 402 may comprise a substantially elastic material that can be expanded and collapsed when filled with fluids or solid materials. In a first position, steaming bag 402 may have a substantially flat or planar geometry. Furthermore, steaming bag 402 may obtain a three dimensional geometry when filled with a solid object or fluid.

The two dimensional shape corresponding to the first position of steaming bag 402 can vary in different embodiments. In some cases, steaming bag 402 may have a substantially rectangular shape. In other cases, steaming bag 402 may have an approximately trapezoidal shape. Examples of other shapes for steaming bag 402 include, but are not limited to rounded shapes, triangular shapes, polygonal shapes, regular shapes, irregular shapes as well as any other kinds of shapes. In an exemplary embodiment, steaming bag 402 has an approximately trapezoidal shape.

In a second, or expanded, position of steaming bag 402, first side 430 and second side 432 (which is disposed opposite of first side 430) of steaming bag 402 may be separated at central portion 404. In other words, central interior cavity 410 may expand outwardly. In some cases, central portion 404 may have an approximately conical shape when expanded. In contrast to central portion 404, first peripheral portion 406 and second peripheral portion 408 may retain a substantially flattened geometry in this second position. In particular, first side 430 and second side 432 may not separate at first peripheral portion 406 and second peripheral portion 408. Instead, first side 430 and second side 434 may be fixedly attached to one another at first peripheral portion 406 and second peripheral portion 408. This arrangement allows first peripheral portion 406 and second peripheral portion 408 to be used as handles for steaming bag 402. In particular, first peripheral portion 406 and second peripheral portion 408 may retain substantially flattened geometries that may be easier to grasp than central portion 404.

The arrangement discussed here can also provide differing thermal properties for various portions of steaming bag 402. In some cases, first peripheral portion 406 and second peripheral portion 408 may have lower temperatures in a steam environment than central portion 404. This may occur as central portion 404 is filled with steam and thereby heated to a greater temperature than first peripheral portion 406 and second peripheral portion 408 which are not filled with steam.

In some embodiments, steaming bag 402 can include additional provisions for facilitating ease of use. In some cases, steaming bag 402 can include one or more holes that are easily grasped by a user. In an exemplary embodiment, steaming bag 402 can include first grasping hole 440 and second grasping hole 442 that are disposed on first peripheral portion 406 and second peripheral portion 408, respectively. In some cases, first grasping hole 440 and second grasping hole 442 may be disposed adjacent to fourth peripheral edge 424.

As seen in the Figures, container 102 comprises a convenient way of storing each of the components of kit 100. In some cases, each of the components discussed above can be packed into container 102 in the manner illustrated in FIG. 2. In particular, first article of footwear 202 and second article of footwear 204 can be placed into interior compartment 105 of container 102. Next, stand 302 can be placed with base portion 304 along first sidewall 107 of container 102. Additionally, footwear engaging portion 306 can be placed or inserted between first article of footwear 202 and second article of footwear 204. Finally, steaming bag 402 can be placed in a flattened position over first article of

footwear **202**, second article of footwear **204** and stand **302**. With this arrangement, each of the components of kit **100** may be easily stored within container **102**.

A footwear customization kit may include provisions for instructing a user about how to customize an article of footwear. In the current embodiment, kit **100** can include set of instructions **500**. Generally, set of instructions **500** can be supplied in any format. In some cases, set of instructions **500** may be a printed copy of instructions. For example, in one embodiment, set of instructions **500** could be provided as a booklet that is packed within container **102**. In other cases, set of instructions **500** may be associated with a digital storage device. Examples of digital storage devices include, but are not limited to CD's, flash drives, memory disks as well as other types of digital storage devices. In an exemplary embodiment, set of instructions **500** may be given as a set of printed directions. Although the current embodiment illustrates set of instructions **500** as being located on interior surface **502** of lid **106**, in other embodiments, set of instructions **500** could be disposed on another portion of container **102**. Furthermore, in some cases, set of instructions **500** could be printed in a separate sheet and stored within container **102** rather than being affixed to a portion of container **102**. In some embodiments, the instructions may be placed on portions of the device itself, for example, the instructions may be placed on steaming bag **402**. In other embodiments, a notice may be placed on the device itself, for example, steaming bag **402**, which informs the user to read and follow the instructions. It is possible to provide the instructions in more than one location, for example, set of instructions **500** may be both located on lid **106** and provided as a booklet packed in container **102**.

Referring now to FIG. **5**, set of instructions **500** may schematically illustrate the steps for customizing an article of footwear. In the current embodiment, set of instructions **500** illustrates four steps for customizing an article of footwear. First panel **510** schematically illustrates the first step, in which a stand is placed in a pot of water. Next, as illustrated in second panel **512**, an article may be placed onto the stand and a steaming bag may then be placed over both the stand and the article of footwear. At this point, the water may be boiled and steam may be applied to the article of footwear including the customizable portion. Next, as illustrated in third panel **514**, the bag may be removed from the article of footwear and the article may be removed from the stand. Finally, as illustrated in fourth panel **516**, a user may insert a foot into the article of footwear. At this point, the customizable portion may conform to the shape of the foot as the article of footwear cools.

In some cases, set of instructions **500** can include pictures. In other cases, set of instructions **500** can include written instructions. In other cases, set of instructions **500** can include a combination of pictures and written instructions. Moreover, it will be understood that the instructions discussed and shown in FIG. **5** are only intended to be illustrative and in other embodiments additional steps can be removed or added.

FIGS. **6** through **11** illustrate an exemplary embodiment of a method of customizing article **202** using the components of kit **100**. For purposes of clarity, the method is only illustrated using article **202**, however it will be understood that similar steps may be repeated to customize second article of footwear **204**.

Referring to FIGS. **6** and **7**, stand **302**, article **202** and steaming bag **402** may be associated with a steam environment. In the current embodiment, the steam environment comprises pot **600**, which is filled with water **602** and further

placed on burner **604**. Generally, any kind of pot may be used. In some cases, a user may select a pot that is large enough to accommodate the components of kit **100**. In addition, in other embodiments a user may not use a pot. Instead, a user could use any container that is capable of containing boiling water. Furthermore, in still other embodiments other types of steaming devices could be used for producing a steam environment.

As water **602** is boiled, steam can be produced for heating article **202** and specifically customizable portion **230**. The components shown here can be assembled in any order. In the exemplary embodiment, stand **302** may be first placed within pot **600** and then article **202** can be placed on stand **302**. As previously discussed, upper portion **312** of stand **302** may be inserted into throat opening **250** of article **202**. As seen in FIG. **7**, the increased width of shoulder portion **314** may help prevent article **202** from sliding all the way down footwear engaging portion **306** of stand **302**.

Following this, steaming bag **402** may be placed over article **202** and portions of stand **302**. As previously discussed, base portion **304** of stand **302** is configured to rest against interior lower surface **620** of pot **600**. In the current embodiment, peripheral opening **414** may be placed within pot **600** towards interior lower surface **620**. In an exemplary embodiment, peripheral opening **414** may cover a substantial majority of the surface area of water **602** in order to collect a majority of the steam coming from water **602**. In some other embodiments, first peripheral opening **414** of steaming bag **402** can be configured to engage outer periphery **622** of pot **600** so that no steam escapes around steaming bag **402**.

In some embodiments, base portion **304** of stand **302** may be disposed within water **602**. In some cases, therefore, it is desirable that base portion **304** comprise a material that will withstand the high temperatures of water **602**. In some cases, base portion **304** may be capable of being heated above the boiling point of water.

It is desirable that the components are assembled within pot **600** prior to water **602** boiling. Therefore, once the components of kit **100** are assembled within pot **600**, a user may turn on burner **604** to heat water **602** and create a steam environment for article **202**.

Referring now to FIG. **8**, steam may be collected within steaming bag **402** in order to heat customizable portion **230**. In some embodiments, steam may be applied for a predetermined amount of time. For example, in one embodiment set of instructions **500** (see FIG. **5**) can include information about the amount of time that article **202** should be steamed.

In some cases, a user could use a timer to keep track of the length of time that article **202** is exposed to steam. In other embodiments, a user may take temperature measurements inside of steaming bag **402** to determine if customizable portion **230** has been heated above a predetermined temperature. For example, in one embodiment set of instructions **500** can include information about the predetermined temperature so that a user can determine when an article has been heated to a temperature that is above the predetermined temperature. In still other embodiments, a combination of timing methods and temperature measuring methods could be used to determine when an article has been heated above a predetermined temperature.

In some cases, vent **416** may be provided to release steam from steaming bag **402**. In other cases, however, no vent may be provided on fourth peripheral edge **424**. In still other cases, other vents or holes could be provided at different locations on steaming bag **402**.

After a predetermined period of time, steaming bag **402** may be removed from article **202** and stand **302**. In some cases, a user can grasp first peripheral portion **406** and/or second peripheral portion **408** to avoid grasping central portion **404** directly. With central portion **404** filled with steam, first peripheral portion **406** and second peripheral portion **408** may have substantially lower temperatures than central portion **404**. In addition, in some cases, a user may place his or her fingers through first grasping hole **440** and/or second grasping hole **442**. This configuration allows a user to remove steaming bag **402** easily in a safe and effective manner.

FIGS. **9** through **11** illustrate isometric views of an embodiment of a customizable portion of an article conforming to the shape of a foot. As previously discussed, the current embodiment includes customizable portion **230** that comprises a substantial majority of upper **222** of article **202**. Therefore, as a foot is inserted into upper **222**, a substantial majority of upper **222** may conform to the shape of the foot.

Referring to FIG. **9**, the temperature of article **202** may be above the predetermined temperature at which customizable portion **230** softens substantially. In this heated state, customizable portion **230** may be partially deformable. Initially, customizable portion **230** has a substantially smooth shape. In particular, forefoot portion **10** is generally smooth on both lateral side **16** and medial side **18** of upper **222**.

Foot **900** is illustrated as inserting into article **202**. In contrast to the substantially smooth shape of customizable portion **230**, foot **900** has a substantially irregular shape. In this case, foot **900** includes first protrusion **902** and second protrusion **904** associated with medial side **918** and lateral side **916**, respectively, of foot **900**. These protrusions could be associated with any type of irregularities in the shape of foot **900** including any kinds of bony protrusions, calluses or other types of protrusions.

Referring now to FIG. **10**, foot **900** has been fully inserted into upper **222**. Furthermore, the temperature of article **202** is still above the predetermined temperature associated with customizable portion **230**. In this heated state, customizable portion **230** may be deformed. In an exemplary embodiment, customizable portion **230** may deform so as to adapt to the shape of foot **900**. Customizable portion **230** may be reshaped due the pressure applied by foot **900**. For example, first contoured portion **1002** of customizable portion **230** may be formed from the local pressure applied by first protrusion **902**. In other words, first contoured portion **1002** may be configured with a substantially similar geometry to first protrusion **902**. In particular, first contoured portion **1002** may form a protrusion on upper **222** that corresponds to first protrusion **902** on foot **900**. In a similar manner, second contoured portion **1004** of customizable portion **230** may be formed from the local pressure applied by second protrusion **904**. In other words, second contoured portion **1004** may be configured with a substantially similar geometry to second protrusion **904**. In particular, second contoured portion **1004** may form a protrusion on upper **222** that corresponds to second protrusion **904** on foot **900**.

It should be understood that a customizable portion could adapt to any geometric features of a foot. In some cases, the customizable portion may adapt to protrusions of various kinds. Additionally a customizable portion can adapt to the overall shape and geometry of a foot. For example, in an embodiment where a user has relatively wide arch, a customizable portion comprising a portion of the upper may be configured to expand at the arch to provide a better fit for the user. In other words, a customizable portion can be

deformed to accommodate global geometric features of a foot in addition to local geometric features such as protrusions.

In order to ensure that customizable portion **230** is substantially permanently deformed in a manner that corresponds to foot **900**, it is desirable that article **202** cool below the predetermined temperature before removing foot **900**. In some cases, a user could make a temperature measurement of article **202**. In other cases, a user may wait a predetermined period of time before removing article **202** to ensure that article **202** has sufficiently cooled. In some embodiments, a set of instructions could provide information for a user including a desired amount of time for keeping a foot inserted inside an article of footwear.

After article **202** has cooled below the predetermined temperature, foot **900** can be removed from upper **222**, as illustrated in FIG. **11**. Customizable portion **230** may substantially retain the shape corresponding to foot **900** following the removal of foot **900**. In this case, customizable portion **230** retains first contoured portion **1002** and second contoured portion **1004** even after foot **900** as been removed. With this arrangement, upper **222** may be substantially permanently reshaped to provide a better fit and enhanced comfort for the user.

In some embodiments, the process of reshaping a customizable portion may only occur once over the lifetime of an article. In some cases, for example, a customizable portion may be made of a material that can only be cured a single time. In other words, the cycle of heating the customizable portion above a predetermined temperature, deforming the customizable portion and then cooling the customizable portion below the predetermined temperature can only occur once. Such materials may not return to a substantially deformable state after being reheated above the predetermined temperature. In other embodiments, however, the process of reshaping a customizable portion could occur two or more times over the lifetime of an article.

FIGS. **12** through **16** illustrate alternative embodiments of stands that may be used with a footwear customization kit. It will be understood that the examples of stands given here are not intended to be limiting and in other embodiments still other kinds of stands can be used with a footwear customization kit. Referring now to FIGS. **12** through **14**, a customization kit may be provided with stand **1202**. Stand **1202** can include base portion **1204** and footwear engaging portion **1206**. Base portion **1204** may be configured to engage a portion of a steaming device that is used for creating a steam environment. For example, in embodiments where the steaming device is a pot, base portion **1204** may engage a bottom interior surface of the pot. In some cases, footwear engaging portion **1206** may extend at an angle from base portion **1204**. In one embodiment, footwear engaging portion **1206** may extend generally perpendicularly from base portion **1204**. Footwear engaging portion **1206** may include first end portion **1207** that is disposed adjacent to base portion **1204** and second end portion **1208** that is disposed furthest from base portion **1204**.

In different embodiments, the shape of base portion **1204** and/or footwear engaging portion **1206** may vary. In some cases, base portion **1204** may have an approximately two dimensional shape. Examples of different shapes for base portion **1204** include, but are not limited to, rounded shapes, rectangular shapes, polygonal shapes, regular shapes, irregular shapes as well as any other kind of shapes. In the current embodiment, base portion **1204** may have an approximately oval-like or elliptic shape. In addition, footwear engaging portion **1206** may have an approximately two dimensional

shape that extends from base portion **1204** in a perpendicular manner. Examples of different shapes for footwear engaging portion **1206** include, but are not limited to any of the shapes discussed above for base portion **1204**. In an exemplary embodiment, footwear engaging portion **1206** may have an irregular shape.

In some cases, footwear engaging portion **1206** can comprise distinct portions that are associated with different portions of an article of footwear. In some embodiments, footwear engaging portion **1206** may include lower portion **1210** and upper portion **1212**. Lower portion **1210** may be disposed adjacent to base portion **1204**. In some cases, lower portion **1210** may have a substantially larger width than upper portion **1212**. In particular, upper portion **1212** may be narrow enough to insert into a throat opening of an article. In contrast, lower portion **1210** may be substantially wider than upper portion **1212**. In particular, lower portion **1210** may be wider than the throat opening of an upper. In some cases, footwear engaging portion **1206** can also include shoulder portion **1214** that extends between lower portion **1210** and upper portion **1212**. In one embodiment, the width of shoulder portion **1214** may vary between lower portion **1210** and upper portion **1212**. With this arrangement, the throat opening of an article may rest against shoulder portion **1214** to help hold an article in place and in a generally upright position.

In some embodiments, footwear engaging portion **1206** may further comprise intermediate portion **1215** that is disposed between first end portion **1207** and second end portion **1208**. In some cases, intermediate portion **1215** may be disposed within lower portion **1210**. In other cases, intermediate portion **1215** could be disposed within upper portion **1212**. In an exemplary embodiment, intermediate portion **1215** may be disposed within lower portion **1210**.

Intermediate portion **1215** may comprise first cross bar **1216** and second cross bar **1218**. First cross bar **1216** may extend across lower portion **1210** in a generally widthwise direction. In other words, first cross bar **1216** may extend from lateral side **1286** to medial side **1288** of stand **1202**. Similarly, second cross bar **1218** may extend from lateral side **1286** to medial side **1288** of lower portion **1210**. In some cases, first cross bar **1216** and second cross bar **1218** can comprise substantially rounded cross sectional shapes. In other cases, however, first cross bar **1216** and second cross bar **1218** may have any other kinds of cross sectional shapes.

In some embodiments, first cross bar **1216** and second cross bar **1218** may provide enhanced strength for stand **1202**. In addition, in some cases, first cross bar **1216** and second cross bar **1218** may provide means for attaching a detachable portion to stand **1202**, as discussed in further detail below.

In some embodiments, a stand can include provisions for protecting the laces of an article. In some cases, a stand can include features to prevent the laces of an article from hanging down below the heel portion of the article. For example, in embodiments where an article may be placed within a pot of boiling water, a stand can include provisions for preventing the laces from contacting the boiling water directly. In one embodiment, a stand can include a detachable portion that can be used to secure the laces above the boiling water.

In the current embodiment, stand **1202** may include detachable portion **1220**. Detachable portion **1220** may include lace receiving portion **1222** and peripheral portion **1224**. Peripheral portion **1224** may extend around lace receiving portion **1222**.

In some cases, lace receiving portion **1222** may include plurality of holes **1240** that allow steam to pass through detachable portion **1220**. However, it will be understood that in other embodiments other provisions could be used including slots, meshes or any other provisions that allow steam to pass through portions of detachable portion **1220**. Moreover, in other embodiments detachable portion **1220** may not include any holes, slots or meshes.

Generally, the geometry of detachable portion **1220** can vary. Examples of different shapes for detachable portion **1220** include, but are not limited to, rounded shapes, rectangular shapes, polygonal shapes, regular shapes, irregular shapes as well as any other kind of shapes. In some cases, detachable portion **1220** could have an approximately half oval or half elliptic shape that is associated with the shape of base portion **1204**.

In some embodiments, detachable portion **1220** can be configured to attach to stand **1202** at various locations. In order to facilitate placing stand **1202** within a container, detachable portion **1220** may initially be attached to base portion **1204**. This arrangement corresponds to a first position of stand **1202** that is illustrated in FIG. **12**. In this case, peripheral portion **1224** may be configured to engage outer frame portion **1230** of base portion **1204**. In an exemplary embodiment, peripheral portion **1224** may be configured to snap into place within outer frame portion **1230**. In other embodiments, however, detachable portion **1220** may be configured to attach to base portion **1204** in any other manner. In another embodiment, detachable portion **1220** may be removably attached to base portion **1204** using a clip. With this arrangement, stand **1202** can easily be placed between two adjacent articles of footwear in a container in a similar manner to the arrangement discussed for stand **302** in the previous embodiment.

In order to help protect the laces of an article while the article is placed in a steam environment, detachable portion **1220** can be removed from base portion **1204**, as illustrated in FIG. **13**. In cases where peripheral portion **1224** snaps into outer frame portion **1230**, detachable portion **1220** can be removed by applying pressure to lace receiving portion. Once detachable portion **1220** is detached from base portion **1204**, detachable portion **1220** may be reattached to stand **1202** at intermediate portion **1215**. This configuration corresponds to a second position of stand **1202** that is illustrated in FIG. **14**. In this case, detachable portion **1220** may be attached to stand **1202** between first cross bar **1216** and second cross bar **1218** of intermediate portion **1215**. In some cases, detachable portion **1220** could include recessed portions **1228** for engaging with first cross bar **1216** (see FIG. **13**). In an exemplary embodiment, detachable portion **1220** may connect to intermediate portion **1215** in a manner so that detachable portion **1220** extends generally perpendicularly from footwear engaging portion **1206**. In particular, in some cases, detachable portion **1220** may be substantially parallel to base portion **1204**.

As seen in FIG. **14**, article **202** has been placed onto stand **1202**. In this case, laces **1400** of article **202** may hang down from upper **222**. Using the arrangement discussed here, detachable portion **1220** helps to protect laces **1400**. Laces **1400** may be gathered on lace receiving portion **1222**. This arrangement may prevent laces **1400** from contacting boiling water. In addition, plurality of holes **1240** help steam to pass through lace receiving portion **1222** and onto article **202**.

FIGS. **15** and **16** illustrate another embodiment of a stand for a footwear customization kit. Referring to FIGS. **15** and **16**, a footwear customization kit can be provided with stand

**1502.** Stand **1502** can include base portion **1504** and footwear engaging portion **1506**. Base portion **1504** may be configured to engage a portion of a steaming device that is used for creating a steam environment. For example, in embodiments where the steaming device is a pot, base portion **1504** may engage a bottom interior surface of the pot. In some embodiments, footwear engaging portion **1506** may extend at an angle from base portion **1504**. In some cases, footwear engaging portion **1506** may extend generally perpendicularly from base portion **1504**. In some cases, footwear engaging portion **1506** may include first end portion **1507** that is disposed adjacent to base portion **1504** and second end portion **1508** that is disposed furthest from base portion **1504**.

In different embodiments, the shape of base portion **1504** and/or footwear engaging portion **1506** may vary. In some cases, base portion **1504** may have an approximately two dimensional shape. Examples of different shapes for base portion **1504** include, but are not limited to, rounded shapes, rectangular shapes, polygonal shapes, regular shapes, irregular shapes as well as any other kind of shapes. In the current embodiment, base portion **1504** may have an approximately circular shape. In addition, footwear engaging portion **1506** may have an approximately two dimensional shape that extends from base portion **1504** in a perpendicular manner. Examples of different shapes for footwear engaging portion **1506** include, but are not limited to any of the shapes discussed above for base portion **1504**. In an exemplary embodiment, footwear engaging portion **1504** may have an irregular shape.

A base portion and/or a footwear engaging portion can include provisions for reducing the weight of a stand. In some embodiments, base portion **1504** may comprise one or more slots. In the exemplary embodiment, base portion **1504** may include plurality of slots **1520**. Plurality of slots **1520** comprise generally parallel slots extending from forward portion **1522** to rearward portion **1524** of base portion **1504**. In some cases, plurality of slots **1520** may help to decrease the weight of stand **1502**. Additionally, in some cases where base portion **1504** may be raised above the surface of water in a pot, plurality of slots **1520** may also allow steam to pass through base portion **1504** to contact an article of footwear.

Footwear engaging portion **1506** can comprise one or more gaps. In the exemplary embodiment, footwear engaging portion **1506** may include first gap **1530** and second gap **1532**. Second gap **1532** may be associated with second end portion **1508**. First gap **1530** may be disposed within intermediate portion **1515**, which is disposed between first end portion **1507** and second end portion **1508**. In some cases, first gap **1530** and second gap **1532** can help reduce the weight of stand **1502**. Additionally, in some cases, first gap **1530** and second gap **1532** may allow steam to pass through footwear engaging portion **1506**.

Footwear engaging portion **1506** can include provisions for holding an article of footwear. In some embodiments, footwear engaging portion **1506** can include first flange portion **1550** and second flange portion **1552** at intermediate portion **1515**. First flange portion **1550** and second flange portion **1552** may generally extend outwardly in a widthwise direction from footwear engaging portion **1506**. In particular, first flange portion **1550** and second flange portion **1552** may provide an increased width for intermediate portion **1515** over first end portion **1507** and second end portion **1508**. In some cases, intermediate portion **1515** may have a substantially larger width than second end portion **1508**. In particular, second end portion **1508** may be narrow enough to insert into a throat opening of an article. In contrast,

intermediate portion **1515** may be substantially wider than second end portion **1508**. In particular, intermediate portion **1515** may be wider than the throat opening of an upper. With this arrangement, the throat opening of an article may generally rest against first flange portion **1550** and second flange portion **1552** of footwear engaging portion **1506** in order to hold the article in a generally upright position.

A stand can include provisions for reducing the amount of space required to fit the stand in a container associated with a footwear customization kit. In some embodiments, a stand can be provided with detachable portions. In other embodiments, a stand can be configured to fold.

In one embodiment, first end portion **1507** of footwear engaging portion **1506** may be attached to base portion **1504**. In some cases, first end portion **1507** may be connected to base portion **1504** using a hinge-like arrangement. In some embodiments, first end portion **1507** may join base portion **1504** at folding crease **1560**. Folding crease **1560** may be a region of connection that provides for bending between base portion **1504** and footwear engaging portion **1506**. In some cases, folding crease **1560** may be a substantially continuous region of connection. In other cases, folding crease **1560** may comprise gaps or spacing between portions of first end portion **1507** and base portion **1504**. In still other cases, folding crease **1560** can have any other configuration that allows for bending between footwear engaging portion **1506** and base portion **1504**.

Although the current embodiment illustrates a folding crease between first end portion **1507** and base portion **1504**, in other embodiments any other arrangement that provides bending between first end portion **1507** and base portion **1504** can be used. In other cases, for example, first end portion **1507** and base portion **1504** could be joined together using a mechanical hinge of some kind.

The arrangement discussed allows footwear engaging portion **1506** to be configured in various positions with respect to base portion **1504**. In some cases, footwear engaging portion **1506** can be moved between a first position **1570** (seen in FIG. 15) and a second position **1572** (seen in FIG. 16). In first position **1570**, footwear engaging portion **1506** is disposed in a generally parallel manner with base portion **1504**. Furthermore, with footwear engaging portion **1506** in first position **1570**, stand **1502** has a substantially flattened configuration. As footwear engaging portion **1506** is folded upwards to second position **1572**, footwear engaging portion **1506** may be disposed at an angle to base portion **1504**. In some cases, in this second position, footwear engaging portion **1506** may be approximately perpendicular to base portion **1504**. In this second position, footwear engaging portion **1506** may be configured to hold an article of footwear in a steam environment. This arrangement allows stand **1502** to be packed in a flattened configuration within a container and then folded into a raised position for use with an article.

In some embodiments, stand **1502** can include provisions for increasing the height of base portion **1504**. In the current embodiment, base portion **1504** can be provided with one or more folding tab portions. In this case, base portion **1504** includes first folding tab portion **1581**, second folding tab portion **1582**, third folding tab portion **1583** and fourth folding tab portion **1584** that may be collectively referred to as folding tab set **1580**. Each folding tab of folding tab set **1580** may be configured to fold outwardly from base portion **1504** in the manner illustrated in FIGS. 15 and 16. In some cases, each folding tab of folding tab set **1580** may fold to

a substantially perpendicular position with respect to base portion **1504** in order to increase the height of base portion **1504**.

In different embodiments, stands can be made of different materials. Examples of different materials that could be used include, but are not limited to: metallic materials, polymer materials including plastics and/or rubbers, wooden materials, composite materials, as well as any other kinds of materials. In some cases, the material used for a stand can be selected according to various features of the stand. For example, in embodiments where a stand comprises a monolithic frame-like stand, a metallic material such as aluminum, steel, iron or any other kind of metallic material could be used. In other cases, however, a monolithic frame-like stand could be made of any other kind of material. In embodiments where a stand includes a detachable portion, a plastic material may be used since plastic pieces can be designed for detachable assembly. In other cases, however, stands using detachable portions could be made of any other kind of material. In embodiments where a stand comprises one or more folding portions, a deformable sheet material could be used, such as a deformable plastic sheet material or a deformable metallic sheet material. In other cases, however, stands including folding portions could be made of any other kind of material.

An article of footwear can be provided with two or more distinct materials that can be deformed when heated above a predetermined temperature and then retain differing rigidities when cooled below the predetermined temperature. For example, in one embodiment, an upper may comprise a first material that is customizable and an insert may comprise a second material that is customizable. Moreover, the second material may be substantially more rigid than the first material after both materials are heated above a predetermined temperature and then cooled again. In another embodiment, an upper may comprise a first material that is customizable and a sole structure may comprise a second material that is customizable. Moreover, the first material and the second material may have substantially different rigidities after both materials are heated above a predetermined temperature and then cooled again. Still further, in other embodiments, three or more customizable materials could be used for different portions of an article of footwear.

FIGS. **17** through **21** illustrate another embodiment of a customization system for customizing an article of footwear. Referring to FIGS. **17** and **18**, customization kit **1700** includes first article of footwear **1802**, second article of footwear **1804**, stand **1702** and steaming bag **1704**. Kit **1700** further includes container **1706** for storing each of these components. These components are substantially similar to the components discussed in the previous embodiments. Kit **1700** may also include a set of optional customizable inserts. In this case, kit **1700** includes first customizable insert **1710** and second customizable insert **1712**. First customizable insert **1710** and second customizable insert **1712** may be used with first article of footwear **1802** and second article of footwear **1804**, respectively.

Although the current embodiment illustrates removable inserts, in other cases other types of inserts could be used. For example, in another embodiment, an insert could be embedded or integrally formed with an article of footwear. In one embodiment, an insert could be integrally formed with an interior portion of an upper. In another embodiment, an insert could be integrally formed with an interior surface of a sole structure. In still other embodiments, an insert could be embedded or integrally formed with any other component of an article of footwear.

For purposes of clarity, only first customizable insert **1710** is discussed in detail, however it should be understood that the same principles may apply to second customizable insert **1712** that is configured to be used with second article of footwear **1804**. Furthermore, throughout the remainder of this detailed description first article of footwear **1802** and first customizable insert **1710** may be referred to as article **1802** and customizable insert **1710**, respectively.

Article **1802** may be substantially similar to article **202** discussed in the previous embodiments. Article **1802** may comprise upper **1822** and sole structure **1824**. For purposes of locating different features of article **1802**, article **1802** may be associated with forefoot portion **10**, midfoot portion **12** and heel portion **14** as well as with lateral side **16** and medial side **18**.

In some embodiments, upper **1822** may be associated with one or more customizable portions. In some cases, a customizable portion may be associated with forefoot portion **10**, midfoot portion **12** and/or heel portion **14** of upper **1822**. In other cases, a customizable portion may be associated with any combination of different portions of upper **1822**. In an exemplary embodiment, upper **1822** may include customizable portion **1830**. In particular, customizable portion **1830** may extend through a substantial majority of upper **1822**. In some cases, customizable portion **1830** may coincide with upper **1822**.

The characteristics of customizable portions can be varied in different ways. In some embodiments, a customizable portion can be varied through a curing process. In other words, the customizable portion may be heated above a predetermined temperature and modified before cooling the customizable portion so that the modifications are retained. In other embodiments, the characteristics of customizable portions can be varied through the use of pressure, chemical additives or other known methods of changing the characteristics of material including the size, shape, rigidity, flexibility and/or other properties. In still other embodiments, a combination of heat, pressure and/or chemicals could be used to modify the customizable portion.

In order to modify customizable portion **1830**, article **1802** may be heated above a predetermined temperature. In some cases, article **1802** may be placed in an oven. In other cases, article **1802** may be heated using steam. In an exemplary embodiment, article **1802** may be heated in any steam environment. A steam environment can be created in different ways. In some cases, a steam environment can be created using a pot with water that may be boiled to create steam. In other cases, any other devices or mechanisms for creating steam can be used.

In different embodiments, customizable insert **1710** can be associated with different portions of article **1802**. In some cases, customizable insert **1710** may be associated with forefoot portion **10**. In other cases, customizable insert **1710** may be associated with midfoot portion **12**. In still other cases, customizable insert **1710** may be associated with heel portion **14**. In an exemplary embodiment, customizable insert **1710** may be configured as a heel insert that is associated with heel portion **14** of article **1802**. In some cases, customizable insert **1710** may be removably inserted from article **1802** through throat opening **1828**.

Customizable insert **1710** may comprise base portion **1720** and sidewall portion **1722**. Sidewall portion **1722** may be disposed at an angle with respect to base portion **1720**. In some cases, sidewall portion **1722** may be configured to contact the sides and rear of a heel. Likewise, base portion **1720** may be configured to receive the bottom surface of a heel.

In some embodiments, customizable insert **1710** may be customized using heat. In some cases, the shape of customizable insert **1710** may be changed by raising the temperature of customizable insert **1710** above a predetermined temperature. In one embodiment, the shape of customizable insert **1710** may be changed by applying steam to customizable insert **1710**.

In some embodiments, the material properties of customizable portion **1830** and customizable insert **1710** may vary. In some cases, customizable portion **1830** and customizable insert **1710** may be made of substantially similar materials. In other cases, customizable portion **1830** and customizable insert **1710** may be made of substantially different materials. In an exemplary embodiment, customizable portion **1830** and customizable insert **1710** may be made of substantially different materials.

As previously discussed, customizable portions can be made from any known materials or combination of materials. Examples of materials that may be used include, but are not limited to: any kind of thermoplastics, thermoset polymers, thermoset resins (such as epoxy, vinyl ester and polyester), synthetic leathers including polymeric leathers and lorica, as well as any other kinds of materials with customizable characteristics. In an exemplary embodiment, a customizable portion may be constructed as a synthetic leather comprising two polymer layers that sandwich a canvas sheet. Moreover, a glue used to bond the polymer layers to the canvas may be configured with a relatively low melting point. When steamed, this glue can stretch or shrink to accommodate a customized shape. Although the current embodiment discusses a three-layered construction, other customizable portions could incorporate any other number of layers including a single layer construction.

Customizable inserts can be made of any known materials or combinations of materials. Examples of materials that may be used for a customizable insert include, but are not limited to: any kind of thermoset polymers, thermoset resins (such as epoxy, vinyl ester and polyester), synthetic leathers, as well as any other materials with customizable characteristics. In some embodiments, a customizable insert can be made from a thermoset foam. In one embodiment, a customizable insert can be made of a modified ethyl-vinyl acetate (EVA) material that has thermoset properties.

In some embodiments, materials for a customizable portion of an article and a customizable insert can be selected according to material characteristics such as durability, rigidity and/or flexibility. In an exemplary embodiment, materials for a customizable portion that is used with an upper and a customizable insert may be selected so that the customizable portion is substantially less rigid than the customizable insert after curing. This arrangement may allow for a greater degree of flexibility for the customizable portion as the foot moves. In contrast, the customizable insert may be relatively rigid after curing to ensure good support for a heel during use.

Referring now to FIG. **18**, the components of kit **1700** may be assembled within a steam environment in order to customize article **1802**. In the current embodiment, pot **1850** and burner **1852** are used to boil water **1854** for creating steam. Furthermore, article **1802** has been placed on stand **1702** within pot **1850**. Steaming bag **1704** has been placed over stand **1702** and article **1802** to capture the steam. With this arrangement, both customizable portion **1830** of upper **1822** and customizable insert **1710** may be heated above the predetermined temperature.

In this exemplary embodiment, article **1802** is held in a substantially vertical position. In other words, heel portion

**14** is substantially closed to water **1854** than forefoot portion **10**. In some cases, this arrangement can help ensure that customizable insert **1710** is heated above the predetermined temperature.

FIGS. **19** through **21** illustrate isometric views of an embodiment of a customizable portion of an article and a customizable insert simultaneously conforming to the shape of a foot. As previously discussed, the current embodiment includes customizable portion **1830** that comprises a substantial majority of upper **1822** of article **1802**. Therefore, as a foot is inserted into upper **1822**, a substantial majority of upper **1822** may conform to the shape of the foot. Additionally, article **1802** includes customizable insert **1710** that can be customized to the shape of a heel.

Referring to FIG. **19**, the temperature of article **1802** may be above the predetermined temperature at which customizable portion **1830** softens substantially. In this heated state, customizable portion **1830** may be partially deformable. Initially, customizable portion **1830** has a substantially smooth shape. In particular, forefoot portion **10** is generally smooth on both lateral side **16** and medial side **18** of upper **1822**.

Foot **1900** is illustrated as inserting into article **1802**. In contrast to the substantially smooth shape of customizable portion **1830**, foot **1900** has a substantially irregular shape. In this case, foot **1900** includes first protrusion **1902** and second protrusion **1904** associated with medial side **1918** and lateral side **1916**, respectively, of foot **1900**. These protrusions could be associated with any type of irregularities in the shape of foot **1900** including any kinds of bony protrusions, calluses or other types of protrusions.

The temperature of customizable insert **1710** may also be above the predetermined temperature at which customizable insert **1710** softens substantially. Initially, customizable insert **1710** has a substantially smooth shape. In particular, base portion **1720** has a substantially constant thickness. Also, sidewall portion **1722** has a substantially constant height. It will be understood that in some cases, customizable insert **1710** and customizable portion **1830** may be associated with substantially similar predetermined temperatures or glass transition temperatures. However, in other cases, customizable insert **1710** and customizable portion **1830** may be associated with substantially different predetermined temperatures. In such cases, as long as the steam environment is able to raise the temperature of article **1802** above both predetermined temperatures, customizable insert **1710** and customizable portion **1810** may both be cured during a single process.

Referring now to FIG. **20**, foot **1900** has been fully inserted into upper **1822**. Furthermore, the temperature of article **1802** is still above the predetermined temperature associated with customizable portion **1830**. In this heated state, customizable portion **1830** may be deformed. In an exemplary embodiment, customizable portion **1830** may deform so as to adapt to the shape of foot **1900**. Specifically, in this case, customizable portion **1830** may be reshaped due the pressure applied by foot **1900**. For example, first contoured portion **2002** of customizable portion **1930** may be formed from the local pressure applied by first protrusion **1902**. In other words, first contoured portion **2002** may be configured with a substantially similar geometry to first protrusion **1902**. In particular, first contoured portion **2002** may form a protrusion on upper **1822** that corresponds to first protrusion **1902** on foot **1900**. In a similar manner, second contoured portion **2004** of customizable portion **1830** may be formed from the local pressure applied by second protrusion **1904**. In other words, second contoured



portion **2004** may be configured with a substantially similar geometry to second protrusion **1904**. In particular, second contoured portion **2004** may form a protrusion on upper **1822** that corresponds to second protrusion **1904** on foot **1900**.

It should be understood that a customizable portion could adapt to any geometric features of a foot. In some cases, the customizable portion may adapt to protrusions of various kinds. Additionally a customizable portion can adapt to the overall shape and geometry of a foot. For example, in an embodiment where a user has relatively wide arch, a customizable portion comprising a portion of the upper may be configured to expand at the arch to provide a better fit for the user. In other words, a customizable portion can be deformed to accommodate global geometric features of a foot in addition to local geometric features such as protrusions.

Also, with foot **1900** fully inserted into upper **1822**, customizable insert **1710** may adapt to the shape of foot **1900**. In some cases, base portion **1720** may be deformed under the weight of heel **1910** (see FIG. **21**). In particular, base portion **1720** may be compressed so that the thickness of base portion **1720** varies in a widthwise direction. Also, sidewall portion **1722** may conform to the shape of the side portions and rear portions of heel **1910**. It will be understood that the variations in the geometry of customizable insert **1710** illustrated and discussed in this embodiment are only intended to be exemplary. In other embodiments, any other kinds of deformations are possible. In particular, both global geometric properties and local geometric properties of customizable insert **1710** could be varied.

In order to ensure that customizable portion **1830** and customizable insert **1710** are substantially permanently deformed in a manner that corresponds to foot **1900**, it is desirable that article **1802** cool below the predetermined temperature before removing foot **1900**. In some cases, a user could make a temperature measurement of article **1802**. In other cases, a user may wait a predetermined period of time before removing article **1802** to ensure that article **1802** has sufficiently cooled. In some embodiments, a set of instructions could provide information for a user including a desired amount of time for keeping a foot inserted inside an article of footwear.

After article **1802** has cooled below the predetermined temperature, foot **1900** can be removed from upper **1822**, as illustrated in FIG. **21**. Customizable portion **1830** may substantially retain the shape corresponding to foot **1900** following the removal of foot **1900**. In this case, customizable portion **1830** retains first contoured portion **2002** and second contoured portion **2004** even after foot **1900** as been removed. With this arrangement, upper **1822** may be substantially permanently reshaped to provide a better fit and enhanced comfort for the user. In a similar manner, customizable insert **1710** may also substantially retain the shape corresponding to heel portion **1910** of foot **1900**.

Furthermore, after cooling, customizable portion **1830** and customizable insert **1710** may acquire substantially different rigidities. In some cases, customizable portion **1830** may be substantially less rigid than customizable insert **1710**. This arrangement allows customizable portion **1830**, which comprises a substantial majority of upper **1822**, to flex and accommodate movement of a foot during use. In contrast, customizable insert **1710** may be relatively rigid to increase support for a heel.

While various embodiments of the invention have been described, the description is intended to be exemplary, rather than limiting and it will be apparent to those of ordinary skill in the art that many more embodiments and implementations

are possible that are within the scope of the invention. Accordingly, the invention is not to be restricted except in light of the attached claims and their equivalents. Also, various modifications and changes may be made within the scope of the attached claims.

What is claimed is:

1. A steaming bag for use with an article of footwear in a steam environment, comprising:
  - a central portion including an interior cavity for receiving the article of footwear;
  - a peripheral portion extending outwardly from the central portion;
  - the central portion having a first temperature when the steaming bag is placed over an article of footwear in the steam environment and the peripheral portion having a second temperature;
  - wherein the first temperature is substantially greater than the second temperature;
  - wherein a width of the peripheral portion varies and wherein the width of the peripheral portion is smallest adjacent to a peripheral opening that is in fluid communication with the interior cavity; and
  - wherein the peripheral portion includes a grasping hole.
2. The steaming bag according to claim 1, wherein the interior cavity is filled with steam in the steam environment.
3. The steaming bag according to claim 1, wherein a width of the interior cavity varies and wherein the width of the interior cavity is largest adjacent to the peripheral opening.
4. The steaming bag according to claim 1, wherein a first side of the steaming bag and a second side of the steaming bag are separated at the central portion to form the interior cavity.
5. The steaming bag according to claim 4, wherein the first side and the second side are fixedly attached at the peripheral portion.
6. The steaming bag according to claim 1, wherein the steaming bag has a flattened configuration in a first position; wherein the central portion expands to have a conical shape in a second position when the steaming bag is filled with a solid or fluid; and wherein the peripheral portion retains the flattened configuration in the second position.
7. A steaming bag for use with an article of footwear in a steam environment, comprising:
  - a central portion including an interior cavity for receiving the article of footwear;
  - a first peripheral edge including a peripheral opening in fluid communication with the interior cavity, the peripheral opening extending through a substantial majority of the first peripheral edge;
  - a second peripheral edge disposed opposite of the first peripheral edge;
  - a first peripheral portion and a second peripheral portion disposed on opposite sides of the interior cavity and extending along a length of the steaming bag between the first peripheral edge and the second peripheral edge;
  - the first peripheral portion extending outward from the interior cavity to a third peripheral edge;
  - the second peripheral portion extending outward from the interior cavity to a fourth peripheral edge;
  - wherein a width of the interior cavity decreases from the first peripheral edge to the second peripheral edge;
  - wherein a width of the first peripheral portion and a width of the second peripheral portion varies along the length of the steaming bag; and

## 25

wherein the width of the first peripheral portion and the width of the second peripheral portion is smallest adjacent to the peripheral opening at the first peripheral edge of the steaming bag.

8. The steaming bag according to claim 7, wherein the central portion including the interior cavity has an approximately conical shape.

9. The steaming bag according to claim 7, wherein the second peripheral edge comprises a vent.

10. The steaming bag according to claim 9, wherein the vent is substantially smaller than the peripheral opening.

11. The steaming bag according to claim 7, wherein the peripheral opening is configured to cover the top of a pot.

12. A steaming bag for use with an article of footwear in a steam environment, comprising:

a central portion including an interior cavity for receiving the article of footwear;

a first peripheral portion extending outwardly from the central portion to a first peripheral edge of the steaming bag;

a second peripheral portion extending outwardly from the central portion to a second peripheral edge of the steaming bag opposite the first peripheral edge;

wherein the first peripheral portion and the second peripheral portion extend along a length of the steaming bag between a third peripheral edge and a fourth peripheral edge, the third peripheral edge and the fourth peripheral edge extending between the first peripheral edge and the second peripheral edge on opposite ends of the steaming bag;

wherein the first peripheral portion and the second peripheral portion include first end portions disposed adjacent to the fourth peripheral edge and second end portions disposed adjacent to the third peripheral edge;

wherein a width of the first peripheral portion and a width of the second peripheral portion varies along the length of the steaming bag;

wherein the width of the first peripheral portion and the width of the second peripheral portion is wider at the first end portions than at the second end portions;

the steaming bag being configured to expand or collapse between a first position associated with a substantially flat configuration and a second position associated with a three dimensional geometry when filled with the article of footwear and/or steam from the steam environment;

## 26

wherein the central portion has a two dimensional geometry in the first position and a three dimensional geometry in the second position; and

wherein the first peripheral portion and the second peripheral portion have a two dimensional geometry in the first position and a two dimensional geometry in the second position.

13. The steaming bag according to claim 12, further including a peripheral opening disposed along the third peripheral edge of the steaming bag, the peripheral opening being in fluid communication with the interior cavity, the peripheral opening extending through a substantial majority of the third peripheral edge.

14. The steaming bag according to claim 12, wherein a width of the interior cavity decreases from the third peripheral edge to the fourth peripheral edge.

15. The steaming bag according to claim 12, wherein the first peripheral portion and the second peripheral portion includes a grasping hole.

16. The steaming bag according to claim 12, wherein the first peripheral edge, the second peripheral edge, the third peripheral edge, and the fourth peripheral edge define a four sided polygonal shape associated with the steaming bag.

17. The steaming bag according to claim 16, wherein the steaming bag has an approximately trapezoidal shape.

18. The steaming bag according to claim 17, wherein the third peripheral edge is larger than the fourth peripheral edge to define the approximately trapezoidal shape of the steaming bag.

19. The steaming bag according to claim 12, wherein a first side of the steaming bag and a second side of the steaming bag are separated at the central portion to form the interior cavity when the steaming bag is in the second position.

20. The steaming bag according to claim 19, wherein the first side and the second side are fixedly attached at the first peripheral portion from the interior cavity to the first peripheral edge when the steaming bag is in the second position; and

wherein the first side and the second side are fixedly attached at the second peripheral portion from the interior cavity to the second peripheral edge when the steaming bag is in the second position.

\* \* \* \* \*