

US009468551B2

(12) **United States Patent**
Batterson et al.

(10) **Patent No.:** **US 9,468,551 B2**
(45) **Date of Patent:** **Oct. 18, 2016**

(54) **ORTHOPEDIC WALKING BRACE HAVING A CURVED SOLE**

A43B 1/0081; A43B 5/00; A43B 7/141;
A43B 7/142; A43B 7/143; A43B 7/01;
A61F 5/0127; A61F 5/0111; A61F 5/0195

(71) Applicant: **DJO, LLC**, Vista, CA (US)

USPC 602/16, 23-28, 60-62; 128/882
See application file for complete search history.

(72) Inventors: **Benjamin Batterson**, San Marcos, CA (US); **Manikandan Sasidharan**, South Portland, ME (US); **Christopher P. Loughnane**, Nashua, NH (US); **Derek Hugger**, Goffstown, NH (US); **Lee Panecki**, Somerville, MA (US); **Chris Aiston**, Mont Vernon, NH (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

8,313,451 B2 *	11/2012	Cox	A61F 5/0127
				602/23
2007/0293798 A1	12/2007	Hu et al.		
2009/0306565 A1	12/2009	Chan		
2010/0186255 A1 *	7/2010	Avar	A43B 3/0036
				36/10
2012/0209163 A1	8/2012	Phillips		

(73) Assignee: **DJO, LLC**, Vista, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 215 days.

OTHER PUBLICATIONS

International Search Report and Written Opinion received in corresponding International Patent Application No. PCT/US2014/026642 dated Jun. 27, 2014.

(21) Appl. No.: **14/211,097**

* cited by examiner

(22) Filed: **Mar. 14, 2014**

Primary Examiner — Michael Brown

(65) **Prior Publication Data**

US 2014/0276317 A1 Sep. 18, 2014

(74) *Attorney, Agent, or Firm* — EIP US LLP

Related U.S. Application Data

(57) **ABSTRACT**

(60) Provisional application No. 61/792,129, filed on Mar. 15, 2013.

Described herein are systems and devices for providing an orthopedic walking brace having a housing and a sole with a curved distal surface. The housing is configured to encompass and immobilize a patient's ankle against flexion. The distal surface of the sole has a posterior region, a mid region, and an anterior region. The posterior region is configured to lie under a heel portion of the patient's foot, and the mid region is configured to lie under a center portion of the patient's foot. The anterior region is configured to lie under an anterior metatarsal and toe portion of the patient's foot, and has an Anterior-Posterior curvature that increases from a posterior side of the anterior region toward a middle portion of the anterior region and decreases from the middle portion toward an anterior side of the anterior region.

(51) **Int. Cl.**

A61F 5/00 (2006.01)

A61F 5/01 (2006.01)


(52) **U.S. Cl.**

CPC **A61F 5/0111** (2013.01); **A61F 5/0195** (2013.01)

(58) **Field of Classification Search**

CPC A43B 13/14; A43B 13/141; A43B 17/16; A43B 23/088; A43B 3/0036; A43B 13/143; A43B 7/14; A43B 7/144; A43B 7/1445; A43B 11/00; A43B 13/148; A43B 13/18; A43B 13/181; A43B 13/189; A43B 13/26;

18 Claims, 11 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

ORTHOPEDIC WALKING BRACE HAVING A CURVED SOLE

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. Provisional Patent Application No. 61/792,129, filed Mar. 15, 2013, which is hereby incorporated by reference herein in its entirety.

BACKGROUND

Orthopedic ankle casts and braces are designed to restrict ankle movement during recovery from injuries such as torn ligaments, sprained ankles, tibial stressed fractures and ankle fractures. An ankle cast is typically molded from rigid materials such as plaster or fiberglass. It supports the lower limb, holds the foot in a neutral position, and immobilizes the ankle. Casts are often worn for several weeks or months, preferably without any weight on the joint to allow proper healing of broken bones and torn ligaments.

During further rehabilitation and strengthening of the ankle after initial stabilization of the injury, walking braces are used instead of casts to continue immobilization of the ankle while allowing gradual increase in weight-bearing exercises such as walking. Some walking braces have a flat sole that is useful for standing, but difficult for walking. Some walking braces have a rocker sole to create a rolling-forward motion during stride, partially replacing lost functions of the ankle joint. Nonetheless, other joints in the hip and the knee often need to compensate for lost ankle movements, making the use of walking braces fatiguing. In addition, walking braces are large and heavy, with stiff brace housings, and large soles to accommodate the size of the housing. Some walking braces with a rocking bottom have a thick sole, which can cause hip displacement when the thickness is not matched on the patient's other foot. The added weight and height make it difficult to use a walking brace, and the resulting unnatural gait can lead to further knee or hip discomfort.

Thus, there is a need for a walking brace that will allow the patient to approximate a natural gait.

SUMMARY

Disclosed herein are systems and devices for providing walking braces having a sole with a curved distal surface. The sole thus provided has a distal surface with changing Anterior-Posterior (AP) curvatures and changing Medial-Lateral (ML) curvatures to enable a natural gait when walking and to enhance stability when the patient is in a standing position. Such curvature changes across the distal surface enable large AP curvatures without large increases in the overall thickness of the sole.

According to one aspect, an orthopedic walking brace includes a housing and a sole having a proximal surface and a distal surface. The housing is configured to encompass and immobilize a patient's ankle against flexion. The proximal surface of the sole is configured to receive the patient's foot. The distal surface of the sole has a posterior region, a mid region, and an anterior region. The posterior region is configured to lie under a heel portion of the patient's foot, and has a first anterior-posterior (AP) curvature. The mid region is configured to lie under a center portion of the patient's foot, and has a second AP curvature. The anterior region is configured to lie under an anterior metatarsal and

toe portion of the patient's foot, and has a third AP curvature that increases from a posterior side of the anterior region toward a middle portion of the anterior region and decreases from the middle portion toward an anterior side of the anterior region. The mid region may lie directly beneath of the patient's midfoot.

According to one implementation, the anterior region of the sole comprises about 35% of the AP length of the distal surface. In another implementation, the mid region of the sole comprises about 40% of the AP length of the distal surface.

In some implementations, the third AP curvature has a maximum value greater than about 0.100 inch^{-1} . A product of the AP length of the anterior region and the maximum value of the AP curvature of the anterior region may be greater than about 0.35. In certain implementations, the AP curvature of the mid region has a maximum value less than about 0.030 inch^{-1} . A product of the AP length of the mid region and the maximum value of the AP curvature of the mid region may be about 0.15 or less than about 0.15. In some implementations, the AP curvature of the posterior region has a maximum value less than about 0.25 inch^{-1} . A product of the AP length of the posterior region and the maximum value of the AP curvature of the posterior region may be less than about 0.7. In addition, the distance between the highest point on the distal surface and a ground surface may be less than about 0.75 inches.

In certain configurations, the distal surface has a Medial-Lateral (ML) curvature with two peaks. The first peak is adjacent to a medial edge of the distal surface, while the second peak is adjacent to a lateral edge of the distal surface. The ML curvature in between these two peaks is substantially flat.

In certain implementations, the proximal surface is rigid, and the distal surface is flexible. The distal surface may comprise two materials of different densities. For example, the proximal surface may be formed of a plastic material, while the distal surface may be formed of rubber and EVA.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing and other objects and advantages will be appreciated more fully from the following description, with reference to the accompanying drawings. These depicted embodiments are to be understood as illustrative and not as limiting in any way.

FIG. 1 is a diagram showing the shank angle;

FIG. 2 is a plot showing illustrative measurements of shank angle and ground reaction force when walking;

FIG. 3 illustrates the relationship between shank angle, curvature, and sole thickness;

FIG. 4 is a plot showing illustrative shank angular velocity during a normal walking gait cycle;

FIG. 5 is a side view of an illustrative walking brace having a curved sole, in accordance with one embodiment;

FIG. 6 is a side view of an illustrative curved sole, in accordance with one embodiment, with a curvature plot for its distal surface;

FIG. 7 is a projection of the proximal surface of the illustrative curved sole in FIG. 6, in accordance with one embodiment;

FIG. 8 is a projection of the distal surface of the illustrative curved sole in FIG. 6, in accordance with one embodiment;

FIG. 9 is an anterior-posterior cross-sectional view of the illustrative curved sole in FIG. 6, in accordance with one embodiment;

FIG. 10 is a medial-lateral cross-sectional view of the illustrative curved sole in FIG. 6, in accordance with one embodiment; and

FIG. 11 is an exploded view of the curved sole in FIG. 6, showing an illustrative segmented and layered structure of the distal surface, with segments formed by different materials, in accordance with one embodiment.

DETAILED DESCRIPTION

To provide an overall understanding of the systems and devices described herein, certain illustrative embodiments will now be described. For the purpose of clarity and illustration, these systems and devices will be described with respect to an orthopedic walking brace applied to a patient's lower leg and ankle. It will be understood by one of ordinary skill in the art that the systems and devices described herein may be adapted and modified as appropriate. These systems and devices may be employed in other suitable applications, such as for other types of braces that include a curved sole, and other such additions and modifications will not depart from the scope hereof.

FIG. 1 shows the shank angle 120 and FIG. 2 provides a corresponding curved line graph 220 of the shank angle 120 during the stance phase of the gait cycle. In FIG. 1, the lower limb of a person in a walking position is illustrated, with the anterior metatarsal and toe portion of the foot in contact with the ground. The shank angle 120 is measured clockwise from the vertical axis 130 when at least a portion of the distal surface of the foot is in contact with the ground. The shank angle 120 attains a value of 0 degrees if the shank and the thigh are aligned, as in an upright standing position; the shank angle 120 attains a positive value when the knee is flexed to the back as shown in FIG. 1 and attains a negative value when the lower leg is extended to the front beyond the upper thigh.

A gait cycle begins when a foot strikes the ground, and ends when the same foot strikes the ground again. The motion of a lower limb in a normal walking gait cycle can be divided into two phases, a stance phase during which the foot is in contact with and supported by the ground, and a swing phase during which the lower limb is swung forward by the hip and knee. The stance phase begins when the heel of the foot 100 strikes the ground, and ends when the toe 105 of the same foot leaves the ground. The stance phase can be further divided into three stages: heel-strike, mid-stance, and toe-off. As the name implies, heel-strike occurs when the heel strikes the ground and rolls forward. Mid-stance occurs when the foot is flat on the ground, with the body center of gravity directly above the foot. Toe-off follows mid-stance, and occurs when the anterior metatarsal, or the ball of the foot, and the toes push off the ground to propel the body forward. During the stance phase, the ankle and midtarsal joints provides dorsiflexion and plantar flexion movements, while the anterior metatarsal and toe portion of the foot provides forward propulsion.

The shank angle 120, and the foot center of pressure 135 continuously change throughout the stance phase, with larger changes in the shank angle 120 during heel-strike and toe-off, as indicated by the curved line graph 220 in FIG. 2. The horizontal axis 210 of this graph corresponds to the time span of the stance phase in percentages, or the percentage of the stance phase that has been completed. The primary vertical axis 222 represents the shank angle 120 in degrees. Shadings are used in FIG. 2 to approximate the three stages of the stance phase: regions 210, 212, and 214 correspond to heel-strike, mid-stance, and toe-off, respectively. Although

measurements of shank angles for different individuals are expected to follow the same general pattern as the line graph 220 through the stance phase, individual variations and step-wise variations exist. The curved line graph 220 is presented as an illustrative example. Similar graphs can be drawn on an individual or other basis. As a person walks, the shank angle changes in a fashion similar to the curved line graph 220. Together, the ankle, tarsal, and metatarsal joints support such movements with a rolling motion of the foot while the foot is in contact with the ground. For a patient wearing an orthopedic walking brace, however, ankle movements are restricted. As a result, either the patient takes smaller steps, or the knee and hip joints compensate with additional flexion and extension. Both situations result in an unnatural gait that deviates significantly from the curved line graph 220. Knee and hip discomforts also occur after prolonged periods of use.

To help patients wearing a walking brace achieve a rolling motion of the foot to better approximate a natural gait, soles for walking braces are often designed to have a rocker bottom, or curved distal surface, to facilitate changes in the shank angle as it would during natural gait. FIG. 3 illustrates the relationship between the shank angle and the AP curvature of the sole in an abstract fashion. Circular arcs 334 and 314 correspond to the same Anterior-Posterior (AP) length 340 but different curvatures, where curvature is defined as the reciprocal of the corresponding radii 336 and 338. In the case of non-circular arcs, curvatures change from point to point on the arc. The arcs 334 and 314 represent side views of the anterior portions of curved soles, with the point 305 corresponding to where the anterior portion joins a substantially flat mid portion. It is easy to see from FIG. 3 that a small curvature (e.g., a large radius 338) in the AP direction provides a flatter sole, while a large AP curvature (e.g., a small radius 336) supports a larger change in shank angle and propels the user forward. Angles 310 and 320 in FIG. 3 represent the amount of change in shank angle required to approximate toe-off during natural gait. These two angles are of the same value. The angle 320 corresponds to the arc 334.

Analogous to the arc 314, in many walking braces, the AP curvature at the anterior end is too small to provide sufficient change in shank angle, causing the patient to take smaller and uneven steps. Analogous to the arc 334 where the corresponding height 332 is larger than the height 330 of the arc 314, in many walking braces that do provide a more ideal curvature in the anterior portion or throughout the distal surface of the sole, the sole is substantially thicker, since the foot needs to lie on a flat surface when standing. A thicker sole leads to uneven leg lengths and hip displacement if this thickness is not matched on the patient's other foot. In yet some other walking braces where thickness is controlled with smaller curvature but a given change in shank angle is still desired, the anterior portion of the sole has a longer AP length, analogous to extending the arc 314 towards the point 325 to approach the angle 310. The AP length 344 of the arc between the point 305 and the point 325, with the larger radius 338 and corresponding to the angle 310, is much larger than the AP length 340 corresponding to arcs 334 and 314. A longer anterior portion pushes the mid portion of the sole towards the back, possibly affecting stability when a patient is in a standing position.

Unlike previous walking braces, in one aspect of the systems and devices described herein, the distal surface of the sole is designed according to the rate at which the shank angle changes throughout the stance phase. In other words, in addition to achieving a particular change in shank angle,

5

some embodiments allow rolling motion of the walking brace to occur at an angular velocity that mimics a natural walking gait cycle, as shown in FIG. 4. These embodiments are advantageous over previous curved soles for walking braces because these embodiments provide sufficient acceleration in the anterior and posterior portions of the sole to propel the user forward without incurring excessive thickness. These embodiments also allow the mid portion of the sole to span over a longer length, and to lie beneath the center portion of the foot for improved stability. In addition, with such designs where the distal surface curves according to the rate at which the shank angle changes throughout the stance phase, the mid portion of the sole has a small but nonzero curvature, so that transitions from heel-strike to mid-stance and from mid-stance to toe-off are both gradual and smooth. Such small curvatures in the mid-portion of the sole do not cause stability problems when a user is standing, in part because a combination of semi-rigid and flexible materials causes the weight-bearing mid portion to become essentially flat when the body mass stays directly on top.

FIG. 4 provides a curved line graph 410 of typical shank angular velocity during a normal walking gait cycle. The horizontal axis 430 represents the span of the gait cycle using percentages, with regions 434, 436 and 438 approximate the heel-strike, mid-stance, and toe-off stages of the stance phase, respectively. Regions 432 and 440 correspond to the swing phase during which changes in shank angle are facilitated by hip and knee joints directly. The vertical axis 420 extends downward and shows that the shank angular velocity varies between about 20 deg/s and about 180 deg/s. The curved line graph 410 shown in FIG. 4 is obtained by averaging angular velocity measurements from a plurality of individuals. In some embodiments of the walking brace where the sole is customized individually or customized for a particular group of patients, the desired angular velocity graph may differ from the curved line plot 410, while still retaining a similar shape, with one valley in the heel-strike stage, one hill in the mid-stance stage, and one valley in the toe-off stage.

Returning to FIG. 2, also shown is a curved line graph 230 on the secondary vertical axis 232, representing the ground reaction force 140 (see FIG. 1), which is the force exerted by the ground on the foot during the stance phase of the gait cycle, when body weight passes over the foot as the shank and the rest of body move forward. The horizontal axis 210 represents the percentage of the stance phase that has been completed. At the beginning of heel-strike (approximately 0%) and the end of toe-off (approximately 100%), the reaction force is about 0 Newton (N). Since in general, the amount of force going through the foot is dependent on the patient's body weight, the curved line graph 230 is presented as an illustrative example only. During heel-strike and toe-off, the foot serves as a rigid lever to propel the body forward, causing the force 140 to be much larger than the patient's body weight. During mid-stance, the other foot is off the ground, and the patient's center of gravity is directly over the foot in the walking brace. Thus, the mid portion of the sole, corresponding to mid-stance, should be substantially flat in the AP direction to provide stability, whether the patient is walking or standing. In some embodiments, the mid portion of the sole is substantially flat, and configured to lie under a center portion of the patient's foot, without comprising maximum curvature achievable in the anterior or posterior end. In some embodiments, the mid portion of the sole is configured to lie directly beneath the midfoot.

Furthermore, although not shown explicitly in a figure here, normally the foot center of pressure flows through the

6

foot continuously starting from the slightly lateral side of the heel towards the front in a medial direction, exiting between the first and the second metatarsal and through the big toe. For walking braces with soles flat in the Medial-Lateral (ML) direction, any slight inversion or eversion of the lower leg results in the foot center of pressure jumping out to the edge of the sole, a discrete event that interrupts a smooth gait. In one aspect of the systems and devices described herein, the ML curvature is large enough to accommodate a normal gait, and also small enough to allow stable standing. Such a feature is approximated by having, at each ML cross-section, an ML curvature that has a peak adjacent to the medial edge and another peak adjacent to the lateral edge of the distal surface, while being substantially flat in between the two peaks. To further mimic the progression of the foot center of pressure, ML curvatures vary gradually from the posterior of the sole to the anterior, with larger peak values near the heel and smaller peak values at the mid portion.

FIG. 5 shows an embodiment of an orthopedic walking brace 500 with a brace housing 510 and a sole 520, which has a curved distal surface 522. The brace housing 510 can have any suitable form for providing support to the lower leg and the foot. In this embodiment, the brace housing 510 is a rigid shell that has a footbed portion 514, a heel portion 516, and an upright support portion 518. The footbed portion 514 has a planar surface on the bottom for direct attachment to the sole 520, and may enclose the patient's foot entirely or partially. The inside of the housing 510 may be lined with cushioning material such as foam pads and inflatable components to provide comfort and to allow the user to adjust compression level provided by the housing. In some embodiments, instead of a rigid shell that immobilizes the ankle entirely, the housing can be made of a semi-rigid material to allow small ankle movements during the recovery process.

FIG. 6 shows an illustrative embodiment 600 of a curve sole, with proximal surface 610 and distal surface 620. The distal surface 620 has a curvature that approximates the angular velocity graph 410 plotted in FIG. 4. Starting from the most posterior point, the sole 600 can be divided into three regions: a posterior region 630, a mid region 632, and an anterior region 634. The posterior region 630 extends from the most posterior point of the sole 600 to the mid region 632. The mid region 632 extends from the posterior region 630 to the anterior region 634. The anterior region 634 extends from the mid region 632 to the most anterior point of the sole 600. The AP length 625 of the sole 600 is dependent on the size of the orthopedic walking brace. For example, a medium-sized men's walking brace may have an AP length 625 of about 11 inches. Walking braces designed for children are made proportionately smaller. The mid region 632 provides stability support to the patient when standing. The AP length 633 of the mid region 632 may be within the range of about 35% to about 45% of the AP length 625 of the sole 600, and in one example, is about 40% of the AP length 625 of the sole 600. The AP length 635 of the anterior region 634 may be within the range of about 30% to about 40% of the AP length 625 of the sole 600, and in one example, is about 35% of the AP length 625 of the sole 600. The length 631 of the posterior region 630 can be derived if both the AP length 633 of the mid region 632 and the AP length 635 of the anterior region 634 are known. According to various examples, the AP length 631 of the posterior region 630 is within the range between about 15% to about 35% of the AP length 625 of the sole 600. In some embodiments, the AP length 631 of the posterior region 630

is about 25% of the AP length **625** of the sole **600**. The posterior region **630**, the mid region **632**, and the anterior region **634** correspond to the heel-strike, mid-stance, and toe-off stages of the stance phase of the gait cycle, respectively.

As shown in FIG. 6, in some implementations, the toe-off anterior region **634** has an A/P curvature **644** that increases from a posterior side **652** to reach a maximum value **648**, then decreases towards the anterior side **656**. The maximum value **648** lies approximately within the middle portion **654** of the anterior region **634**. In some implementations, the maximum AP curvature **648** is greater than about 0.10 inch⁻¹. For example, it may be about 0.11 inch⁻¹.

When the size of a walking brace changes, the size of the sole changes as well. Shank angular velocity measurements for patients requiring walking braces of different sizes may or may not differ from the curved line graph **410** shown in FIG. 4, in part or entirely. Accordingly, when the AP length **625** of the sole **600** in FIG. 6 changes, the AP curvature of the distal surface **620** may be a scaled version of the AP curvatures **644**, **642**, and **640** for the embodiment shown in FIG. 6. For example, the AP curvature **644** of the anterior region **634** may retain the same shape, range of values, and maximum value **648**, when the AP length **635** of the anterior region **634** changes in proportion to the AP length **625** of the sole **600**. Similar rules may apply to the curvature **642** of the mid region **632** and the curvature **640** of the posterior region **630**.

In some implementations, when the AP length **635** of the anterior region **634** changes in proportion to the AP length **625** of the sole **600**, the AP curvature **644** of the anterior region **634** also changes according to a desired scaled factor. For example, in FIG. 3, the ratio between the AP length **340** and the radius **336** is the sine function of the angle **320**. Therefore, this ratio remains constant when the AP length **340** and the radius **336** change in value, as long as the angle **320** stays constant. Similarly, in some implementations of the sole **600** shown on FIG. 6, the ratio between the AP length **635** of the anterior region **634** and the radius corresponding to the maximum curvature **648** of the anterior region **634** stays approximately the same when the sole **600** changes in size. In some implementations, the product of the maximum AP curvature **648** of the anterior region **634** and the AP length **635** of the anterior region **634** is greater than about 0.35.

In some other implementations, the net forward velocity of the patient's body is assumed to follow approximately the same pattern and range of values throughout the gait cycle among all people. The net forward velocity is also the tangential velocity at the sole, and the tangential velocity at the sole is the product of shank angular velocity and the radius of the curvature measured at the tangential point. Accordingly, when the sole **600** changes in size, the ratio of measured shank angular velocities and corresponding curvature of the sole retains approximately the same pattern and range of values.

In some embodiments, the heel-strike posterior region **630** has an AP curvature **640** that increases from a posterior side of the posterior region **630** to reach a maximum value **646**, then decreases towards the mid region **642**. The maximum value **646** lies approximately within the middle portion of the posterior region **630**. In some implementations, the AP curvature **640** of the posterior region **630** attains a value **650** much larger than zero at the most posterior point of the sole **600**. The maximum AP curvature **646** may be less than about 0.25 inch⁻¹. In one example, it is about 0.21 inch⁻¹. According to one implementation, the product of the maxi-

imum AP curvature **646** of the posterior region **630** and the AP length **631** of the posterior region **630** is less than about 0.7.

As discussed above with respect to FIG. 2, the mid region **632** of the sole **600** is configured to lie under a center portion of the patient's foot, and may lie directly beneath the midfoot. Additionally, the mid region **632** is substantially flat. Thus, the mid region **632** has an AP curvature **642** that stays approximately constant over the region. According to one example, the mid region **632** has an AP curvature **642** between about 0.024 inch⁻¹ and about 0.026 inch⁻¹. In some embodiments, the AP curvature **642** of the mid region **632** has a maximum value less than about 0.030 inch⁻¹. According to one implementation, the product of the maximum value of the AP curvature **642** of the mid region **632** and the AP length **633** of the mid region **632** is less than about 0.15.

FIG. 7 shows the projection of the proximal surface **610** of the curved sole **600** in FIG. 6, according to one embodiment. The proximal surface **610** is configured to receive the patient's foot and the footbed **514** (see FIG. 5). According to various implementations, the sole **600** can be attached to the footbed **514** by adhesive, by interlocking mechanisms that allow the sole **600** to be removed and changed if necessary, or by both an adhesive and an interlocking mechanism. As shown in the illustrative embodiment in FIG. 7, the proximal surface **610** includes a circumferential rim **710**, a circumferential groove **720**, a raised platform **750** with recessed volumes **760**, positioned under the heel, and circular notches **740**, **742**, **744**, and **746**. The circumferential rim **710**, the circumferential groove **720**, the raised platform **750**, and the circular notches **740**, **742**, **744** and **746**, on the proximal surface **610**, can be coupled to corresponding structures (not shown) on the bottom of the footbed **514** to allow precise and secure attachment of the sole **600** to the footbed **514**, which is part of the upper housing **510**. The upper housing **510** supports the ankle and the lower leg. The AP length **625** of the sole **600** is dependent on the size of the upper housing **510**. In other embodiments, the proximal surface **610** includes different structures for securing the sole **600** to the footbed **514**. For example, the proximal surface **610** may include protrusions that couple with indents in the footbed **514**.

In FIG. 7, the proximal surface **610** is symmetrical around the longitudinal axis. In one implementation, the distal surface **620** of the sole **600** shown in FIG. 6 is also symmetrical, allowing the sole **600** to be used for either a left or a right foot. In other implementations, the proximal surface **610** is designed with asymmetric structures. For example, instead of having a notch **742** as a mirror image of the notch **746**, and a notch **740** as a mirror image of the notch **744**, in some embodiments, notches on the proximal surface **610** may be located at asymmetric positions around the longitudinal axis. In other examples, the proximal surface **610** may include more than four notches or less than four notches. Furthermore, in other embodiments, the proximal surface **610** is constructed asymmetrically, shaped conform to the shape of a patient's foot, or with raised portions to compensate for a patient's walking gait characteristics, such as pronation.

FIG. 8 is a projection of the distal surface **620** of the illustrative curved sole **600**, according to one embodiment. The anterior-posterior axis **810** divides the sole **600** into two halves, and passes through the posterior point of the sole **600**. In some embodiments, the two halves are identical, i.e., the distal surface is symmetric. The distal surface may also be asymmetric. For example, the distal surface **620** may be designed to include arch support, and/or to accommodate

pronation of a left or a right foot. The width **830** of the sole **600** is measured across the widest medial-lateral cross-section of the sole **600**. In this embodiment, the width **830** is about 45% of the full AP length **625** (see FIG. 6) of the sole **600**. When a walking brace is customized according to injury type or user preferences, the ratio between the width **830** of the sole **600** and the full AP length **625** of the sole **600** may be in the range between about 35% to about 55%.

FIG. 9 is an anterior-posterior cross-sectional view of the curved sole **600**, according to one embodiment. The cross-section is taken at the anterior-posterior axis **810** shown in FIG. 8. The raised platform **750** has a length **910** and a height **915**. According to one example, the length **910** is about 2.6 inches and the height **915** is about 0.25 inches. The raised platform **750** is spaced apart from the circumferential rim **710** by a distance **920**. In one example, the distance **920** is about 0.5 inches. The rim **710** has a rim height **925** of about 0.4 inches. The rim height **925** of the rim **710** may vary along the edge of the distal surface **620**. The thickness **940** of the sole **600** is approximately the same as the distance between the highest point on the distal surface **620** and the ground level. In some embodiments, the thickness **940** of the sole **600** is about 0.75 inches. The thickness **940** of the sole **600** may vary depending on the size of the sole **600**.

FIG. 10 is a medial-lateral cross-sectional view of the curved sole **600**, wherein the cross-section is made at the medial-lateral line **820** of FIG. 8, perpendicular to the anterior-posterior axis **810**. The circumferential groove **720** has a width **1010** and a depth **1020** at the medial-lateral line **820**. According to one example, the width **1010** is about 0.25 inches and the depth **1020** is about 0.15 inches. As shown in FIG. 10, the medial-lateral width **1030** of the raised platform **750** is about 3.0 inches at the medial-lateral line **820**.

FIG. 11 is an exploded view of the distal surface **620** of the curved sole **600** shown in FIG. 6. In practice, the sole **600** can be manufactured using various materials and various processes. In one implementation, the sole **600** is manufactured from a mold using one type of material, for example, vulcanized natural rubber, which is preferred for its anti-slip and shock-absorbing properties. Natural rubber has a high density, and thus adds significant weight to the walking brace. To reduce the overall weight of the sole **600** yet providing shock absorbance and wear resistance, in some implementations, the sole **600** is made by fusing an outsole layer and a midsole layer into a single piece, where the outsole layer corresponds to the distal surface **620** of the sole **600**, and the midsole layer corresponds to the proximal surface **610** of the sole **600**. The distal surface **620** and the proximal surface **610** can be made of materials with different densities and rigidities.

In some implementations, the distal surface **620** is made of two different types of materials in a segmented and layered structure. As shown in FIG. 11, thin layers of inserts **1120**, **1130**, and **1140** are made of natural rubber, while the main body **1110** is made of a lighter material such as 100% EVA (Ethyl-Vinyl Acetate), known for its durability and shock-absorbency. The first insert **1120** is placed at around the posterior region of the distal surface **620** to reduce skid during heel-strike, while the second insert **1130** and the third insert **1140** are placed below the anterior region and part of the mid region to minimize slippage during mid-stance and toe-off. The first insert **1120** has a horseshoe shape, which reduces its overall surface area and its weight, without comprising anti-slip and shock-absorbing properties. The second insert **1130** is also shaped like a horse-shoe, with a central hollow portion configured to fit the third insert **1140**. The third insert **1140** is shaped like an isosceles trapezoid in

this example. All of the three inserts **1120**, **1130**, and **1140** include patterned grooves. Different shapes for the inserts and different patterns for the grooves can be used in other embodiments. According to various examples, the inserts **1120**, **1130** and **1140** may have different colors, possibly matching the colors of other parts of the walking brace. In some configurations, more than, or less than three inserts are included in the distal surface **620**. For example, instead of the second insert **1130** and the third insert **1140**, a single large insert (not shown) may be placed below the anterior region and part of the mid region of the distal surface **620**.

It is to be understood that the foregoing is merely illustrative, and is not to be limited to the details given herein. While several embodiments have been provided by the present disclosure, it should be understood that the disclosed systems and devices and their components may be embodied in any other specific forms without departing from the scope of the disclosure.

Variations and modifications will occur to those of skill in the art after reviewing this disclosure, where disclosed features may be implemented in any combination and sub-combinations (including multiple dependent combinations and subcombinations), with one or more other features described herein. The various features described or illustrated above, including any components thereof, may be combined or integrated in other devices, systems, or methods; moreover, certain features may be omitted or not implemented.

Examples of changes, substitutions and alternations are ascertainable by one skilled in the art and to be made without departing from the scope of the information disclosed herein. All references cited herein are incorporated by reference in their entirety and made part of this application.

What is claimed is:

1. An orthopedic walking brace, comprising:

a housing configured to encompass and immobilize a patient's ankle against flexion, and a sole having a proximal surface and a distal surface, the proximal surface configured to receive the patient's foot, and the distal surface having a posterior region, a mid region, and an anterior region, wherein

the posterior region is configured to lie under a heel portion of the patient's foot, and has a first anterior-posterior (AP) curvature,

the mid region is configured to lie under a center portion of the patient's foot, and has a second AP curvature, and

the anterior region is configured to lie under an anterior metatarsal and toe portion of the patient's foot, and has a third AP curvature that increases from a posterior side of the anterior region toward a middle portion of the anterior region and decreases from the middle portion toward an anterior side of the anterior region.

2. The orthopedic walking brace of claim 1, wherein the anterior region comprises about 35% of the AP length of the distal surface.

3. The orthopedic walking brace of claim 1, wherein the mid region comprises about 40% of the AP length of the distal surface.

4. The orthopedic walking brace claim 1, wherein the mid region lies directly beneath the midfoot.

5. The orthopedic walking brace of claim 1, wherein the third AP curvature has a maximum value greater than about 0.100 inch⁻¹.

11

6. The orthopedic walking brace of claim 1, wherein a product of the AP length of the anterior region and a maximum of the third AP curvature is greater than about 0.35.

7. The orthopedic walking brace of claim 1, wherein the second AP curvature has a maximum value less than about 0.030 inch⁻¹.

8. The orthopedic walking brace of claim 1, wherein a product of the AP length of the mid region and a maximum value of the second AP curvature has a maximum value less than about 0.15.

9. The orthopedic walking brace of claim 1, wherein the first AP curvature increases from a posterior side of the posterior region toward a middle portion of the posterior region and decreases from the middle portion toward an anterior side of the posterior region.

10. The orthopedic walking brace of claim 9, wherein the first AP curvature has a maximum value less than about 0.25 inch⁻¹.

11. The orthopedic walking brace of claim 9, wherein a product of the AP length of the posterior region and a maximum value of the first AP curvature has a maximum value less than about 0.7.

12

12. The orthopedic walking brace of claim 1, wherein the distal surface has a first medial-lateral (ML) curvature that has a first peak adjacent to a medial edge and a second peak adjacent to a lateral edge of the distal surface, and is substantially flat in between the first and the second peaks.

13. The orthopedic walking brace of claim 1, wherein the distal surface is symmetric.

14. The orthopedic walking brace of claim 1, wherein the proximal surface is rigid, and the distal surface is flexible, and wherein the distal surface comprises a first material having a first density, and a second material having a second density, wherein the second density is smaller than the first density.

15. The orthopedic walking brace of claim 14, wherein the proximal surface is formed of a plastic material.

16. The orthopedic walking brace of claim 14, wherein the first material is rubber.

17. The orthopedic walking brace of claim 14, wherein the second material is EVA.

18. The orthopedic walking brace of claim 1, wherein a distance between the highest point on the distal surface and a ground surface defines a thickness and a maximum value of the thickness is about 0.75 inches.

* * * * *