



US009474385B2

(12) **United States Patent**
Oh

(10) **Patent No.:** **US 9,474,385 B2**
(45) **Date of Patent:** **Oct. 25, 2016**

(54) **FOLDABLE BED FRAME STRUCTURE**

(71) Applicant: **GRANTEC (XIAMEN) CO., LTD.**,
Xiamen (CN)

(72) Inventor: **Suk Kan Oh**, Xiamen (CN)

(73) Assignee: **GRANTEC (XIAMEN) CO., LTD.**,
Xiamen, Fujian (CN)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/664,938**

(22) Filed: **Mar. 23, 2015**

(65) **Prior Publication Data**

US 2016/0206112 A1 Jul. 21, 2016

(30) **Foreign Application Priority Data**

Jan. 19, 2015 (CN) 2015 2 0034549 U

(51) **Int. Cl.**

A47C 19/00 (2006.01)
A47C 19/12 (2006.01)
A47C 17/64 (2006.01)
A47C 19/14 (2006.01)
A47C 17/70 (2006.01)
A47C 17/74 (2006.01)

(52) **U.S. Cl.**

CPC *A47C 19/126* (2013.01); *A47C 17/64*
(2013.01); *A47C 17/70* (2013.01); *A47C 17/74*
(2013.01); *A47C 19/12* (2013.01); *A47C*
19/122 (2013.01); *A47C 19/124* (2013.01);
A47C 19/14 (2013.01)

(58) **Field of Classification Search**

CPC *A47C 19/126*; *A47C 19/12*; *A47C 19/14*;
A47C 19/122; *A47C 19/124*; *A47C 17/70*;
A47C 17/74; *A47C 17/64*; *A47C 19/00*;
A47C 19/021

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,659,941	A *	2/1928	Cable	A47C 19/122
				5/117
2,772,424	A *	12/1956	Roche	A47C 19/124
				5/176.1
2,790,185	A *	4/1957	Fox	A47C 19/021
				5/174
8,312,576	B1 *	11/2012	Oh	A47C 23/005
				5/174
8,370,973	B1 *	2/2013	Oh	A47C 19/122
				5/174
8,832,876	B1 *	9/2014	Oh	A47C 17/64
				5/116
8,978,176	B1 *	3/2015	Oh	A47C 19/005
				5/200.1
2003/0011219	A1 *	1/2003	Chun-Yueh	A47C 1/143
				297/51
2003/0200608	A1 *	10/2003	Polevoy	A47C 19/005
				5/201

(Continued)

Primary Examiner — David E Sosnowski


Assistant Examiner — Morgan McClure

(74) *Attorney, Agent, or Firm* — Leong C. Lei

(57) **ABSTRACT**

A foldable bed frame structure includes two longitudinal supports, three transverse supports, and a plurality of legs. Each longitudinal support includes a first longitudinal pole and a second longitudinal pole which are symmetrically disposed and have connecting ends connected with each other. Each transverse support includes two transverse poles which are symmetrically disposed and have connecting ends pivotally connected through a U-shaped fixing plate. Free ends of the transverse poles are connected with the first longitudinal pole and the second longitudinal pole through connecting seats, respectively. The legs are pivotally connected to the transverse poles through the U-shaped fixing plate and the connecting seats, respectively. The foldable bed frame structure is convenient for transportation and use.

7 Claims, 5 Drawing Sheets



US 9,474,385 B2

Page 2

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0278848	A1 *	12/2005	Polevoy	A47C 19/005 5/201	2010/0299831	A1 *	12/2010	Lee	A47C 19/126 5/202
2009/0249545	A1 *	10/2009	Lee	A47C 19/122 5/111	2012/0246826	A1 *	10/2012	Jin	A47C 19/04 5/400
2010/0235989	A1 *	9/2010	Jin	A47C 19/126 5/174	2012/0304380	A1 *	12/2012	Jin	A47C 19/126 5/400
					2013/0025051	A1 *	1/2013	Syrowitz	A47C 19/021 5/400

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

FOLDABLE BED FRAME STRUCTURE

BACKGROUND OF THE INVENTION

(a) Technical Field of the Invention

The present invention relates to a bed, and more particularly to a foldable bed frame structure.

(b) Description of the Prior Art

A conventional wooden bed frame is composed of a frame and a bed board. The frame and the bed board are an integral one when the bed frame leaves the factory. The entire bed frame occupies large space for transportation, and it is very inconvenient for removal. Besides, when the user purchases the bed frame, he/she is unable to complete the removal and needs the aid of a porter. For a large bed frame, it is limited to the size of a corridor, an elevator or a door. This brings quite inconvenience to the porter. For a bed frame composed of a separate frame and a separate bed board, the longitudinal bed board also has the problem of inconvenient removal. When the frame is folded or unfolded, the parts of the frame must be disassembled or assembled one by one.

Accordingly, the inventor of the present invention has devoted himself based on his many years of practical experiences to solve these problems.

SUMMARY OF THE INVENTION

The primary object of the present invention is to provide a foldable bed frame structure which occupies less space for convenient transportation and use.

In order to achieve the aforesaid object, the foldable bed frame structure of the present invention comprises two longitudinal supports, three transverse supports connected at front and rear ends and middle portions of the two longitudinal supports, and a plurality of legs. Each longitudinal support comprises a first longitudinal pole and a second longitudinal pole. The first longitudinal pole and the second longitudinal pole are symmetrically disposed, and have connecting ends connected with each other and free ends opposite the connecting ends. The connecting ends of the first longitudinal pole and the second longitudinal pole are connected through a connecting plate. The connecting ends of the first longitudinal pole and the second longitudinal pole have notches, respectively. Each transverse support comprises two transverse poles which are symmetrically disposed and have connecting ends pivotally connected through a U-shaped fixing plate. Each transverse pole is a U-shaped pole with an opening facing downward. Free ends of the two transverse poles of each transverse support, opposite to the connecting ends of the two transverse poles, are connected with the free ends of the first longitudinal poles of the two longitudinal supports, the free ends of the second longitudinal poles of the two longitudinal supports, and the connecting ends of the first longitudinal pole and the second longitudinal pole of each longitudinal support through connecting seats, respectively. The legs are pivotally connected to the free end of each transverse pole and the bottom of the connecting ends of the two transverse poles through the U-shaped fixing plate and the connecting seats, respectively.

Preferably, the connecting ends of the first longitudinal pole and the second longitudinal pole are provided with a pivot member. The pivot member is an h-like configuration and comprises a long side and a short side connected with a lower end of the long side through a curved portion thereof. An upper end of the long side has a pivot hole. The connecting ends of the first longitudinal pole and the second longitudinal pole each have a first connecting hole corre-

sponding to the pivot hole and a recess adapted to accommodate the short side of the pivot member.

Preferably, each U-shaped transverse pole has pivotal holes disposed at two ends thereof and communicating with two side walls thereof. The U-shaped fixing plate has an opening facing downward and two connecting holes at two side walls thereof corresponding to the pivotal holes at the connecting ends of the two transverse poles. The two transverse poles are pivotally connected by a pin inserted through the pivotal holes and the connecting holes. The bottom of the U-shaped fixing plate directly leans against the U-shaped bottom ends of the two transverse poles.

Preferably, each connecting seat comprises a U-shaped connecting plate and two tabs extending outward from two side walls of the U-shaped connecting plate. The two side walls of the U-shaped connecting plate and the two tabs have shaft holes. The U-shaped connecting plate has an opening facing the transverse poles. The connecting seat and the transverse poles are fixed by a pin inserted through the shaft holes of the U-shaped connecting plate and the pivotal holes at the free ends of the U-shaped transverse poles. The tabs face downward. Each leg is fixed to the fixing plate by a bolt cooperating with a nut to connect the shaft holes of the tabs.

Preferably, the first longitudinal pole and the second longitudinal pole are L-shaped poles each having a bottom and an upright side.

Preferably, the upright side at the free end of the first longitudinal pole or the second longitudinal pole is movably connected with an L-shaped headboard stopper. One end of the headboard stopper is connected to the upright side of the first longitudinal pole or the second longitudinal pole. Another end of the headboard is adapted to retain the bottom of the first longitudinal pole or the second longitudinal pole.

According to the foldable bed frame structure of the present invention, the longitudinal supports and the transverse supports at two ends of the longitudinal supports are pivotally connected with each other. The middle portions of the longitudinal supports are connected with the middle transverse support. Each support is composed of two poles which are pivotally connected through a pivot member. When folded, the poles are folded and the legs are folded in the U-shaped transverse supports, so that the poles of the bed frame are folded together for convenient storage, transportation and use.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of the present invention in an unfolded state;

FIG. 2 is a first schematic view of the present invention when folded;

FIG. 3 is a second schematic view of the present invention when folded;

FIG. 4 is a third schematic view of the present invention when folded; and

FIG. 5 is a perspective view of the present invention in a folded state.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiments of the present invention will now be described, by way of example only, with reference to the accompanying drawings.

As shown in FIG. 1 and FIG. 2, the present invention discloses a foldable bed frame structure. The foldable bed frame structure comprises two longitudinal supports 1, three

3

transverse supports **2** connected at front and rear ends and middle portions of the two longitudinal supports **1**, and a plurality of legs **3**. It is noted that the supports of the foldable bed frame structure of the present invention are made of wood and pivot members and connecting members are made of a metallic material, which is beneficial for production and operation of the bed frame.

Each longitudinal support **1** comprises a first longitudinal pole **11** having a bottom **111** and an upright side **112** and a second longitudinal pole **12** having a bottom **121** and an upright side **122**. The first longitudinal pole **11** and the second longitudinal pole **12** are symmetrically disposed, and have connecting ends connected with each other and free ends opposite the connecting ends. The connecting ends of the first longitudinal pole **11** and the second longitudinal pole **12** have notches and are connected through a pivot member **13** and a connecting plate **14**. The pivot member **13** is an h-like configuration, and comprises a long side **131** and a short side **132** connected with a lower end of the long side **131** through a curved portion thereof. An upper end of the long side **131** has a pivot hole **133**. The upright sides **112**, **122** at the connecting ends of the first longitudinal pole **11** and the second longitudinal pole **12** each have a first connecting hole **113** and a recess **114** corresponding to the pivot hole **133**. The recess **114** is adapted to accommodate the short side **132** of the pivot member **13**. The bottoms **111**, **121** at the connecting ends of the first longitudinal pole **11** and the second longitudinal pole **12** have second connecting holes **115**, **125**. The connecting plate **14** has installation holes **141** corresponding to the second connecting holes **115**, **125**. The bottoms **111**, **121** at the free ends of the first longitudinal pole **11** and the second longitudinal pole **12** have third connecting holes **116**, **126**. The upright side **112** or **122** at the free end of the first longitudinal pole **11** or the second longitudinal pole **12** has a fourth connecting hole **117** or **127** for connecting a headboard stopper **4**. The headboard stopper **4** has an L shape with one side connected to the upright side **112** or **122** of the first longitudinal pole **11** or the second longitudinal pole **12** and another side adapted to retain the bottom **111** or **121**.

Each transverse support **2** comprises two transverse poles **21** which are symmetrically disposed and have connecting ends pivotally connected through a U-shaped fixing plate **22**. Each transverse pole **21** is a U-shaped pole. Each transverse pole **21** has an opening **23** facing downward and pivotal holes **24** disposed at two ends thereof and communicating with two side walls thereof. The U-shaped bottom of each transverse pole **21** has a fixing hole **25** at a free end thereof. The U-shaped fixing plate **22** has an opening facing downward and two connecting holes **221** at two side walls thereof corresponding to the pivotal holes **24** at the connecting ends of the two transverse poles **21**. The bottom of the U-shaped fixing plate **22** directly leans against the U-shaped bottom ends of the two transverse poles. The free ends of the two transverse poles **21**, opposite to the connecting ends, are respectively connected with the longitudinal supports **1** and the legs **3** through connecting seats **26**. Each connecting seat **26** comprises a U-shaped connecting plate **261** and two tabs **262** extending outward from two side walls of the U-shaped connecting plate **261**. The two side walls of the U-shaped connecting plate **261** and the two tabs **262** have shaft holes **263**.

The legs **3** are disposed in the openings **23** of the U-shaped transverse poles **21** respectively and connected by the connecting seats **26**. Each leg **3** has opposing ends at a top thereof and coupling holes **31** corresponding to the two

4

shaft hole **263** of the connecting seat **26**. The bottom of each leg **3** can be provided with a leg sleeve.

When the present invention is installed, the L-shaped first longitudinal pole **11** and the L-shaped second longitudinal pole **12** are placed symmetrically. Through rivets, the pivot hole **133** of the pivot member **13** is pivotally connected with the first connecting hole **113** of the first longitudinal pole **11**. The curved trough formed by the long side **131** and the short side **132** of the pivot member **13** is fitted on the second longitudinal pole **12** from the top of the upright side **122** of the second longitudinal pole **12**. The installation holes **141** of the connecting plate **14** correspond to the second connecting holes **115**, **125** of the first longitudinal pole **11** and the second longitudinal pole **12**. The connecting plate **14** is fixed on the longitudinal support **1** through a pin. The headboard stopper **4** is locked to the fourth connecting hole **117** or **127**. The openings of the two U-shaped transverse poles **21** approach each other. The top of the U-shaped fixing plate **22** with the leg **3** holds against the joint of the two transverse poles **21**. A rivet is inserted through the pivotal holes **24** and the connecting holes **221** to fix the U-shaped fixing plate **22** with the leg **3** to the transverse poles **21**. The free ends of the two transverse poles **21** located at the two ends of the longitudinal supports **1** are locked to the free ends of the first longitudinal pole **11** and the second longitudinal pole **12**. The free ends of the two transverse poles **21** located at the middle portions of the longitudinal supports **1** are locked on the connecting plates **14** connected to the first longitudinal pole **11** and the second longitudinal pole **12**. A hexagonal bolt cooperates with a T-shaped nut to connect the shaft holes **263** of the tabs **262** of the connecting seat **26** and one coupling hole **31** of the leg **3**. The connecting seat **26** with the leg **3** is disposed at the free end of each transverse pole **21**. The opening of the U-shaped connecting plate **261** of the connecting seat **26** faces the other end of the transverse pole **21**. The two tabs **262** are disposed downward. The shaft holes **263** of the side walls of the U-shaped connecting plate **261**, the other coupling hole **31** of the leg **3**, and pivotal holes **24** of the transverse poles **21** are pivotally connected with rivets. FIG. 1 show an unfolded state after installed.

As shown in FIG. 2 to FIG. 5, when the present invention is folded, the headboard stopper **4** is disassembled and the hexagonal bolt and the T-shaped nut to fix the connecting seat **26** and the leg **3** at the free end of each transverse pole **21** are disassembled, so that the leg **3** can be turned toward the connecting end of the transverse pole **21** until all the legs **3** are folded in the openings **23** of the transverse poles **21**, respectively. As shown in FIG. 2, with the middle leg **3** fixed at the connecting ends of the two transverse poles **21** as a pivot, the longitudinal supports **1** and the transverse poles **21** fixed at the two sides of the middle legs **3** are folded toward the middle legs **3** until the two U-shaped openings of the two transverse poles **21** leans against each other to wrap the middle leg **3** therein to form an E shape as shown in FIG. 3. After that, the legs **3** at the two sides are folded toward the longitudinal supports **1** to form a T shape as shown in FIG. 4. Finally, the connecting plates **14** pivotally connected with the first longitudinal pole **11** is turned 180 degrees to disengage from the second longitudinal pole **12**. The short side **142** of the connecting plate **14** is accommodated in the recess **114** of the first longitudinal pole **11**. The first longitudinal poles **11** and the second longitudinal poles **12** with the folded transverse supports **2** and the legs **3** are folded toward the middle legs **3**, as shown in FIG. 5. In this way to fold the bed frame, the poles of the bed frame can be folded together to reduce the size of the bed frame for convenient transportation and use. When the user wants to unfold the

5

bed frame, the operation is done reversely, without the need to connect the poles one by one.

Although particular embodiments of the present invention have been described in detail for purposes of illustration, various modifications and enhancements may be made without departing from the spirit and scope of the present invention. Accordingly, the present invention is not to be limited except as by the appended claims.

I claim:

1. A foldable bed frame structure, comprising two longitudinal supports, three transverse supports connected at front and rear ends and middle portions of the two longitudinal supports, and a plurality of legs;

characterized by: each longitudinal support comprising a first longitudinal pole and a second longitudinal pole, the first longitudinal pole and the second longitudinal pole being symmetrically disposed and having connecting ends connected with each other and free ends opposite the connecting ends, the connecting ends of the first longitudinal pole and the second longitudinal pole being connected through a connecting plate, the connecting ends of the first longitudinal pole and the second longitudinal pole having notches respectively; each transverse support comprising two transverse poles which are symmetrically disposed and have connecting ends pivotally connected through a U-shaped fixing plate, each transverse pole being a U-shaped pole with an opening facing downward, free ends of the two transverse poles of each transverse support, opposite to the connecting ends of the two transverse poles, being connected with the free ends of the first longitudinal poles of the two longitudinal supports, the free ends of the second longitudinal poles of the two longitudinal supports, and the connecting ends of the first longitudinal pole and the second longitudinal pole of each longitudinal support through connecting seats respectively; the legs being pivotally connected to the free end of each transverse pole and the bottom of the connecting ends of the two transverse poles through the U-shaped fixing plate and the connecting seats, respectively, wherein the connecting ends of the first longitudinal pole and the second longitudinal pole are provided with a pivot member, the pivot member being an h-like configuration and comprising a long side and a short side connected with a lower end of the long side through a curved portion thereof, an upper end of the long side having a pivot hole, the connecting ends of the first longitudinal pole and the second longitudinal pole each having a first connecting hole corresponding to the pivot hole and a recess adapted to accommodate the short side of the pivot member.

6

2. The foldable bed frame structure as claimed in claim 1, wherein the first longitudinal pole and the second longitudinal pole are L-shaped poles each having a bottom and an upright side.

3. The foldable bed frame structure as claimed in claim 2, wherein the upright side at the free end of the first longitudinal pole or the second longitudinal pole is movably connected with an L-shaped headboard stopper, one end of the headboard stopper being connected to the upright side of the first longitudinal pole or the second longitudinal pole, another end of the headboard being adapted to retain the bottom of the first longitudinal pole or the second longitudinal pole.

4. The foldable bed frame structure as claimed in claim 1, wherein each U-shaped transverse pole has pivotal holes disposed at two ends thereof and communicating with two side walls thereof, the U-shaped fixing plate having an opening facing downward and two connecting holes at two side walls thereof corresponding to the pivotal holes at the connecting ends of the two transverse poles, the two transverse poles being pivotally connected by a pin inserted through the pivotal holes and the connecting holes, the bottom of the U-shaped fixing plate directly leaning against the U-shaped bottom ends of the two transverse poles.

5. The foldable bed frame structure as claimed in claim 1, wherein each connecting seat comprises a U-shaped connecting plate and two tabs extending outward from two side walls of the U-shaped connecting plate, the two side walls of the U-shaped connecting plate and the two tabs having shaft holes, the U-shaped connecting plate having an opening facing the transverse poles, the connecting seat and the transverse poles being fixed by a pin inserted through the shaft holes of the U-shaped connecting plate and the pivotal holes at the free ends of the U-shaped transverse poles, the tabs facing downward, each leg being fixed to the fixing plate by a bolt cooperating with a nut to connect the shaft holes of the tabs.

6. The foldable bed frame structure as claimed in claim 1, wherein the first longitudinal pole and the second longitudinal pole are L-shaped poles each having a bottom and an upright side.

7. The foldable bed frame structure as claimed in claim 6, wherein the upright side at the free end of the first longitudinal pole or the second longitudinal pole is movably connected with an L-shaped headboard stopper, one end of the headboard stopper being connected to the upright side of the first longitudinal pole or the second longitudinal pole, another end of the headboard being adapted to retain the bottom of the first longitudinal pole or the second longitudinal pole.

* * * * *