



US009510671B2

(12) **United States Patent**
Ergun et al.

(10) **Patent No.:** **US 9,510,671 B2**
(45) **Date of Patent:** ***Dec. 6, 2016**

(54) **HEIGHT ADJUSTABLE DESK SYSTEM AND METHOD**

(71) Applicant: **Ergotron, Inc.**, St. Paul, MN (US)

(72) Inventors: **Mustafa A. Ergun**, Plymouth, MN (US); **Robert William Fluhner**, Prior Lake, MN (US); **Scott Trish**, Lakeville, MN (US); **Jeffrey Randall Mensing**, Blaine, MN (US)

(73) Assignee: **Ergotron, Inc.**, St. Paul, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/883,010**

(22) Filed: **Oct. 14, 2015**

(65) **Prior Publication Data**

US 2016/0029783 A1 Feb. 4, 2016

Related U.S. Application Data

(63) Continuation of application No. 14/461,932, filed on Aug. 18, 2014.

(Continued)

(51) **Int. Cl.**

A47B 9/00 (2006.01)

A47B 9/02 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC . **A47B 9/02** (2013.01); **A47B 9/10** (2013.01);
A47B 9/12 (2013.01); **A47B 9/20** (2013.01)

(58) **Field of Classification Search**

CPC **A47B 9/00**; **A47B 9/10**; **A47B 9/12**;
A47B 9/20; **F16M 11/32**

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,675,597 A 7/1972 Oddsen et al.
3,856,252 A * 12/1974 Regis F16B 7/14
108/147

(Continued)

FOREIGN PATENT DOCUMENTS

DE 1529723 1/1970
DE 3406669 A1 8/1985

(Continued)

OTHER PUBLICATIONS

“U.S. Appl. No. 14/461,932, Non Final Office Action mailed May 6, 2015”, 9 pgs.

(Continued)


Primary Examiner — Jose V Chen

(74) *Attorney, Agent, or Firm* — Schwegman Lundberg & Woessner, P.A.

(57) **ABSTRACT**

A height adjustable desk can include a work surface; and at least one leg assembly connected to the work surface. The at least one leg assembly can include: a first member; and a second member moveable relative to the first member along a longitudinal axis; and a counterbalance mechanism connected to the desk and configured to counteract a force exerted on the work surface. The counterbalance mechanism can include: a wheel; a gas spring having a cylinder and a moveable piston; a wheel moveably connected to the gas spring; and the tension member is connected to the leg assembly.

18 Claims, 42 Drawing Sheets



Related U.S. Application Data

- (60) Provisional application No. 61/867,308, filed on Aug. 19, 2013.
- (51) **Int. Cl.**
A47B 9/10 (2006.01)
A47B 9/12 (2006.01)
A47B 9/20 (2006.01)
- (58) **Field of Classification Search**
 USPC 108/147, 144.11; 248/188.5, 188.2, 157, 248/439
 See application file for complete search history.

7,752,932 B2	7/2010	Chen et al.	
8,177,174 B2	5/2012	Griepentrog	
8,286,927 B2	10/2012	Sweere et al.	
8,333,159 B2	12/2012	Schroer et al.	
8,342,465 B2 *	1/2013	Koder	A47B 9/04 108/147
9,232,855 B2	1/2016	Ergun et al.	
2005/0002591 A1	1/2005	Buitmann	
2006/0075941 A1	4/2006	Seidl et al.	
2008/0250989 A1	10/2008	Kozlowski et al.	
2009/0072101 A1 *	3/2009	Stoelinga	A47B 9/12 248/188.5
2011/0001032 A1	1/2011	Gardner	
2011/0023758 A1 *	2/2011	Overgaard	A47B 9/06 108/147
2011/0225903 A1 *	9/2011	Lounis	B66F 11/00 52/122.1
2012/0043436 A1 *	2/2012	Atkinson	A47B 9/20 248/188.5
2012/0227642 A1 *	9/2012	Sekikawa	A47B 9/10 108/147
2012/0248273 A1	10/2012	Singer	
2013/0126682 A1	5/2013	Tholkes et al.	
2014/0034799 A1	2/2014	Fallows et al.	
2015/0047538 A1	2/2015	Ergun et al.	

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,651,652 A *	3/1987	Wyckoff	A47B 9/12 108/147
5,114,109 A	5/1992	Fitz et al.	
5,129,611 A *	7/1992	Grover	F16M 11/26 108/147
5,282,593 A *	2/1994	Fast	A47B 9/04 108/147
5,400,721 A	3/1995	Greene	
5,495,811 A *	3/1996	Carson	A47B 9/20 108/147
5,553,550 A *	9/1996	Doyle	A47B 9/00 108/147
5,682,825 A *	11/1997	Manner	A47B 9/02 108/144.11
5,715,759 A *	2/1998	Lee	A47B 9/12 108/147
5,941,182 A *	8/1999	Greene	A47B 9/12 108/147
6,085,670 A *	7/2000	Genov	B23Q 1/032 108/144.11
6,152,049 A *	11/2000	Schmidt	A47B 9/12 108/147
6,474,246 B2 *	11/2002	Hsu	A47B 9/04 108/147
6,484,648 B1 *	11/2002	Long	A47B 9/04 108/147
6,494,005 B2 *	12/2002	Zimmerman	B66F 3/10 108/147
7,204,193 B2	4/2007	Scherrer et al.	
7,364,124 B2	4/2008	Yuasa et al.	
7,412,931 B2 *	8/2008	Seidl	A47B 9/02 108/147
7,658,359 B2	2/2010	Jones et al.	
7,743,716 B1	6/2010	Burka	

FOREIGN PATENT DOCUMENTS

DE	19626855 A1	1/1998
EP	1987734 B1	12/2010
EP	2422647 A1	2/2012
WO	WO-9919247 A1	4/1999
WO	WO-2008145399 A1	12/2008
WO	WO-2012025593 A1	3/2012
WO	WO-2015026714 A1	2/2015

OTHER PUBLICATIONS

- “U.S. Appl. No. 14/461,932, Notice of Allowance mailed Aug. 27, 2015”, 5 pgs.
- “U.S. Appl. No. 14/461,932, Notice of Allowance mailed Oct. 2, 2015”, 7 pgs.
- “U.S. Appl. No. 14/461,932, Response filed Jul. 30, 2015 to Non Final Office Action mailed May 6, 2015”, 8 pgs.
- “International Application Serial No. PCT/US2014/051473, International Search Report mailed Nov. 21, 2014”, 4 pgs.
- “International Application Serial No. PCT/US2014/051473, Written Opinion mailed Nov. 21, 2014”, 6 pgs.
- “International Application Serial No. PCT/US2014/051473, International Preliminary Report on Patentability mailed Mar. 3, 2016”, 8 pgs.

* cited by examiner




FIG. 1




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 6A





FIG. 6B




FIG. 7A

FIG. 7B




FIG. 8A




FIG. 8B




FIG. 9A




FIG. 9B




FIG. 10




FIG. 11




FIG. 12




FIG. 13A




FIG. 13B




FIG. 13C




FIG. 14A




FIG. 14B




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23A




FIG. 23B




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33A

FIG. 33B




FIG. 34




FIG. 35A

FIG. 35B




FIG. 36




FIG. 37A




FIG. 37B




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42

HEIGHT ADJUSTABLE DESK SYSTEM AND METHOD

CLAIM OF PRIORITY

This patent application is a continuation application and claims the benefit of priority to U.S. patent application Ser. No. 14/461,932, entitled "HEIGHT ADJUSTABLE DESK SYSTEM AND METHOD," filed Aug. 18, 2014, which claims the benefit of priority to U.S. Provisional Patent Application Ser. No. 61/867,308, entitled "HEIGHT ADJUSTABLE DESK SYSTEM AND METHOD," filed on Aug. 19, 2013, which are hereby incorporated by reference herein in their entirety.

FIELD

The disclosure generally relates to systems and methods for height adjustable desks.

BACKGROUND

Height adjustable desks can be used in sit-to-stand applications.

SUMMARY

Examples of this disclosure include leg assemblies or risers comprising at least two or more tubes or "members". Tubes can have various diameters so that they can be located inside each other. Tubes can be slidably engaged and connected together via a telescoping mechanism. Tubes or members can be slidably engaged and connected together via a non-telescoping mechanism. One of the tubes can be fixed, and the other tube or tubes can slide out of the fixed tube to provide a height adjustment. When combined, the leg assemblies can provide a highest desk height required for tall users in a standing position, and, when the smaller tubes collapse, the leg assemblies can provide a lowest desk height required by shorter users in a seated position.

In some examples, the leg assemblies or risers can include a counterbalancing mechanism. The counterbalancing mechanism can include a spring such as a coil or gas spring, a wheel, such as a pulley or a rotary cam mechanism, and a tension member. The counterbalancing mechanism can be configured to counteract a force provided by the weight of a desk or work surface attached to one or more leg assemblies and the weight of any components which can be supported by the work surface. In some examples, a counterbalancing mechanism can be included in each leg assembly of the height adjustable desk. The leg assemblies can be used individually as a single leg assembly centered under a desk surface, or two or more synchronized leg assemblies can be used under the desk surface for height adjustment. In other examples, the counterbalancing mechanism can be located between the leg assemblies and parallel to the desk surface, such as underneath a work surface.

In another example, an adjustable desk can include a weight counterbalance mechanism that uses a gas spring and a pulley assembly. This example can be applied to two member or three member telescoping leg assemblies or risers, as well as non-telescoping leg assemblies or risers to support a work surface. In this disclosure, a leg or riser can be any generally vertical supporting structure and the terms can be used interchangeably. A work surface can be supported by a single leg assembly or multiple leg assemblies. In this disclosure, using a pulley arrangement in association

with a gas spring, a total height adjustment of four times the gas spring stroke can be achieved.

In another example, the leg assembly can be a lift mechanism, that can provide support and counteract a downward force for numerous applications including a work surface, table, or desk.

To further illustrate the HEIGHT ADJUSTABLE DESK SYSTEM AND METHOD disclosed herein, a non-limiting list of examples is provided here:

In Example 1, a height adjustable desk can comprising: a work surface; and at least one leg assembly connected to the work surface, the at least one leg assembly including: a first member; and a second member moveable relative to the first member along a longitudinal axis; and a counterbalance mechanism connected to the desk and configured to counteract a force exerted on the work surface. The counterbalance mechanism can include: a gas spring having a cylinder and a moveable piston; a wheel moveably connected to the gas spring; and a tension member engaged to the wheel, the tension member connected to the leg assembly.

In Example 2, the height adjustable desk of Example 1 can optionally be configured such that the cylinder extends from a closed end to a piston end, the closed end being attached to one of a first member upper end, a first member lower end, a second member upper end, and a second member lower end.

In Example 3, the height adjustable desk of any one or any combination of Examples 1-2 can optionally be configured to comprise a third member moveable relative to the second member along a longitudinal axis.

In Example 4, the height adjustable desk of Example 3 can optionally be configured such that the cylinder extends from a closed end to a piston end, the closed end being attached to one of a third member upper end, and a third member lower end.

In Example 5, the height adjustable desk of any one or any combination of Examples 3-4 can optionally be configured to comprise a synchronization assembly configured to balance movement between the first and second members with movement between the second and third members, wherein the synchronization assembly includes a first pulley moveably connected to an upper end of the second member and a second pulley moveably connected to the lower end of the second member.

In Example 6, the height adjustable desk of any one or any combination of Examples 1-5 can optionally be configured such that the wheel is moveably connected to an outer end of the piston.

In Example 7, the height adjustable desk of any one or any combination of Examples 1-6 can optionally be configured such that the wheel and the gas spring are contained within the at least one leg assembly.

In Example 8, the height adjustable desk of any one or any combination of Examples 1-7 can optionally be configured such that the wheel and the gas spring are external to the at least one leg assembly and the wheel and the gas spring are located under the work surface.

In Example 9, the height adjustable desk of any one or any combination of Examples 1-8 can optionally be configured such that the wheel is a first wheel, and wherein the counterbalance mechanism can include: a pulley bracket having one end connected to the gas spring near the first wheel, the pulley bracket having a second wheel at an opposing end of the pulley bracket; and a second tension member engaged to the second wheel.

In Example 10, the height adjustable desk of any one or any combination of Examples 1-9 can optionally be config-

ured such that the second member is configured to fit inside the first member and form a telescoping assembly.

In Example 11, the height adjustable desk of any one or any combination of Examples 1-10 can optionally be configured such that the at least one leg assembly is a first leg assembly, comprising a second leg assembly connected to the work surface, the second leg assembly including: a second leg first member; and a second leg second member moveable relative to the second leg first member along a longitudinal axis.

In Example 12, a lift mechanism can comprise: a first member; and a second member moveable relative to the first member along a longitudinal axis; and a counterbalance mechanism configured to counteract a force exerted on the lift mechanism. The counterbalance mechanism can include: a gas spring having a moveable piston slidably attached to a cylinder, the cylinder attached to the lift mechanism; a wheel moveably connected to an outer end of the piston; and a tension member engaged to the wheel, the tension member having a first end and a second end, the first end attached to the lift mechanism.

In Example 13, the lift mechanism of Example 12 can optionally be configured such that the cylinder extends from a closed end to a piston end, the closed end being attached to one of a first member upper end, a first member lower end, a second member upper end, and a second member lower end.

In Example 14, the lift mechanism of any one or any combination of Examples 12-13 can optionally be configured to comprise a third member moveable relative to the second member along a longitudinal axis.

In Example 15, the lift mechanism of Example 14 can optionally be configured such that the cylinder extends from a closed end to a piston end, the closed end being attached to one of a third member upper end, and a third member lower end.

In Example 16, the lift mechanism of any one or any combination of Examples 14-15 can optionally be configured to comprise a synchronization assembly configured to partially transfer one of: a) movement between the first member and the second member to movement between the second member and the third member, and b) movement between the second member and the third member to movement between the first member and the second member, wherein the synchronization assembly includes a first pulley moveably connected to an upper end of the second member and a second pulley moveably connected to the lower end of the second member.

In Example 17, the lift mechanism of any one or any combination of Examples 12-16 can optionally be configured to comprise a work surface attached to an upper end of the lift mechanism.

In Example 18, the lift mechanism of any one or any combination of Examples 12-16 can optionally be configured such that the second member is configured to fit inside the first member and form a telescoping assembly.

In Example 19, the lift mechanism of any one or any combination of Examples 12-16 can optionally be configured such that the wheel is a first wheel and wherein the counterbalance mechanism can include: a pulley bracket having one end connected to the gas spring near the first wheel, the pulley bracket having a second wheel at the opposing end of the pulley bracket; and a second tension member engaged to the second wheel.

In Example 20, the lift mechanism of any one or any combination of Examples 12-16 can optionally be configured such that the gas spring is a first gas spring, the lift

mechanism comprising a second gas spring extending in an opposite direction from the first gas spring.

In Example 21 height adjustable desk or lift mechanism of any one or any combination of Examples 1-20 can optionally be configured such that all elements, operations, or other options recited are available to use or select from.

These and other examples and features of the present height adjustable desk and lift mechanisms will be set forth in part in the following Detailed Description. This Overview is intended to provide non-limiting examples of the present subject matter—it is not intended to provide an exclusive or exhaustive explanation. The Detailed Description below is included to provide further information about the present height adjustable desk and lift mechanisms.

BRIEF DESCRIPTION OF THE DRAWINGS

The following drawings are illustrative of particular examples of the present invention and therefore do not limit the scope of this disclosure. The drawings are not to scale (unless so stated) and are intended for use in conjunction with the explanations in the following detailed description. Examples of the present invention will hereinafter be described in conjunction with the appended drawings, wherein like numerals denote like elements.

FIG. 1 is a perspective view of a height adjustable desk with leg assemblies in accordance with at least one example of this disclosure.

FIGS. 2A-2B are side elevation views of leg assemblies in accordance with at least one example of this disclosure.

FIG. 3 is a cross-section side elevation view and top plan views of a leg assembly in accordance with at least one example of this disclosure.

FIG. 4 is a cross-section side elevation view of a leg assembly in accordance with at least one example of this disclosure.

FIGS. 5A-5B are cross-section side elevation views of a leg assembly with a counterbalance mechanism in accordance with at least one example of this disclosure.

FIGS. 6A-6B are cross-section side elevation views of a leg assembly with a counterbalance mechanism in accordance with at least one example of this disclosure.

FIGS. 7A-7B are cross-section side elevation views of a leg assembly with a counterbalance mechanism in accordance with at least one example of this disclosure.

FIGS. 8A-8B are cross-section side elevation views of a leg assembly with a counterbalance mechanism in accordance with at least one example of this disclosure.

FIGS. 9A-9B are side elevation views of a leg assembly with a counterbalance mechanism comprising a cam housing in accordance with at least one example of this disclosure.

FIG. 10 is a cross-section of a side elevation view of a leg assembly in accordance with at least one example of this disclosure.

FIG. 11 is a cross-section of a side elevation view of a leg assembly with a brake mechanism in accordance with at least one example of this disclosure.

FIG. 12 is a perspective view of a spring adjustment assembly in accordance with at least one example of this disclosure.

FIGS. 13A-C are front elevation views of a spring adjustment assembly in accordance with at least one example of this disclosure.

FIGS. 14A-B are front elevation views of a spring adjustment assembly in accordance with at least one example of this disclosure.

5

FIG. 15 is a perspective view of selected details of a spring adjustment assembly in accordance with at least one example of this disclosure.

FIG. 16 is a perspective view of a height adjustable desk with leg assemblies in accordance with at least one example of this disclosure.

FIG. 17 is a front elevation view of a height adjustable desk with leg assemblies in accordance with at least one example of this disclosure.

FIG. 18 is a perspective view of a height adjustable desk with leg assemblies in accordance with at least one example of this disclosure.

FIG. 19 is a front elevation view of a height adjustable desk with leg assemblies in accordance with at least one example of this disclosure.

FIG. 20 is a bottom plan view of a height adjustable desk with leg assemblies in accordance with at least one example of this disclosure.

FIG. 21 is a top view of a counterbalance mechanism in accordance with at least one example of this disclosure.

FIG. 22 is a front elevation view of a counterbalance mechanism in accordance with at least one example of this disclosure.

FIG. 23A-B are elevation views of a cam/wheel assembly of a counterbalance mechanism in accordance with at least one example of this disclosure.

FIG. 24 is front elevation view of the cam/wheel assembly of a counterbalance mechanism in accordance with at least one example of this disclosure.

FIG. 25 is a perspective view of a cam/wheel assembly of a counterbalance mechanism in accordance with at least one example of this disclosure.

FIG. 26 is a front elevation view of a height adjustable desk with the cam/wheel assembly of a counterbalance mechanism in accordance with at least one example of this disclosure.

FIG. 27 is a side elevation view of a height adjustable desk in accordance with at least one example of this disclosure.

FIG. 28 is a side elevation view of a brake assembly in accordance with at least one example of this disclosure.

FIG. 29 is a front elevation view of a secondary brake assembly in accordance with at least one example of this disclosure.

FIG. 30 is a side elevation view of a secondary brake assembly in accordance with at least one example of this disclosure.

FIG. 31 is a front elevation view of a secondary brake assembly in accordance with at least one example of this disclosure.

FIG. 32 illustrates a side view of a height adjustable desk with a fixed height leg assembly and a moving bracket in accordance with at least one example of this disclosure.

FIGS. 33A-33B illustrate a side view of a counterbalance mechanism in accordance with at least one example of this disclosure.

FIG. 34 illustrates a side view of a height adjustable work surface with a two member leg assembly in accordance with at least one example of this disclosure.

FIGS. 35A-35B illustrate a side view of a counterbalance mechanism using a gas spring in accordance with at least one example of this disclosure.

FIG. 36 illustrates a force distribution diagram for a gas spring counterbalance mechanism in accordance with at least one example of this disclosure.

6

FIGS. 37A-37B illustrate a side view of a counterbalance mechanism using a gas spring in accordance with at least one example of this disclosure.

FIG. 38 illustrates a side view of a height adjustable work surface with a two member leg assembly and a gas spring attached to a second member in accordance with at least one example of this disclosure.

FIG. 39 illustrates a side view of a counterbalance mechanism using a gas spring in a three member leg assembly in accordance with at least one example of this disclosure.

FIG. 40 illustrates a side view of a counterbalance mechanism using a gas spring in a three member leg assembly in accordance with at least one example of this disclosure.

FIG. 41 illustrates a side view of a counterbalance mechanism using a gas spring in a three member leg assembly in accordance with at least one example of this disclosure.

FIG. 42 illustrates a side view of a counterbalance mechanism using a gas spring in a three member leg assembly in accordance with at least one example of this disclosure.

DETAILED DESCRIPTION

The following detailed description is exemplary in nature and is not intended to limit the scope, applicability, or configuration of this disclosure in any way. Rather, the following description provides some practical illustrations for implementing exemplary examples of the present invention. Examples of constructions, materials, dimensions, and manufacturing processes are provided for selected elements, and all other elements employ that which is known to those of ordinary skill in the field of this disclosure. Those skilled in the art will recognize that many of the noted examples have a variety of suitable alternatives.

FIG. 1 is a perspective view of a height adjustable desk 100. The height adjustable desk 100 can include one or more leg assemblies 109 that can support a work surface 106. The work surface 106 can be a table top, a desk surface or other horizontal member. The leg assembly 109 can be used as a lift mechanism 999 that can be used to provide support and counteract a downward force for numerous applications including a work surface 106, table, or desk 100. The height adjustable desk 100 is illustrated including two leg assemblies 109, a first leg assembly 110, and a second leg assembly 120 located under the work surface 106. In this disclosure the words “leg” and “riser” are used interchangeably. Each leg assembly 109 can include two or more tubes or members and in FIG. 1 height adjustable desk 100 is illustrated having three tubes or members: a first member 112, a second member 114 and a third member 116 in a telescopic nested arrangement. Although “telescoping” tubes or members are illustrated and described, non-telescoping configurations of sliding members are also contemplated by this disclosure (see FIG. 32). In another example, each leg assembly can include two tubes (see FIGS. 34-38). In some examples, the first and second leg assemblies 110, 120 can be connected together with a cross bar 108. In other examples, the cross bar 108 may not be needed. Each of the first and second leg assemblies 110, 120 can be attached to a first foot 102 and a second foot 104 respectively at the bottom end of the leg assembly 109. Each leg assembly 109 can be attached to a bottom surface (not shown) of the work surface 106 at the upper end of the leg assembly 109. The feet can add greater stability. One or both leg assemblies 109 can include a brake mechanism 200 (see FIG. 11) to secure the work surface 106 at a desired height. When needed, a user can squeeze a brake handle 140 to unlock the brake mechanism and move the work surface 106 to a second

height. Such a movement can be described as a height adjustment 98. When the brake handle 140 is released, the work surface 106 can be secured at the second height. In some examples, a counterbalancing mechanism 151 (see FIGS. 6-8) can be located inside one or more leg assemblies. In other examples, portions of the counterbalancing mechanism can be located under the work surface 106 and external to either leg assembly 109.

FIGS. 2A and 2B illustrate a leg assembly 109 of a height adjustable desk 100 (see FIG. 1) according to one example of this disclosure. FIG. 2A shows the leg assembly 109 with three telescoping tubes in an extended position 107, and FIG. 2B shows the three telescoping tubes in a collapsed position 105. In this application tubes can also be referred to as "members". The three member leg assembly 109 can include a first member 112, a second member 114 and a third member 116 and the first, second and third members, 112, 114, 116 can be tubular in cross-section, and they can have any cross-sectional shape including but not limited to round, square, rectangular, oval or other profiles. The second member 114 can be slidably engaged with the first member 112, and the third member 116 can be slidably engaged with the second member 114. Although the leg assembly 109 is illustrated with the first member 112 at the bottom and the second member 114 sliding into the first member 112, the leg assembly 109 can be reversed and have the narrowest member at the bottom and larger members sliding over each other (see FIG. 7A-B). The movement or sliding of each member relative to an adjacent member can be synchronized as described in the following paragraphs. If the second member 114 slides X distance relative to the first member 112, then the third member 116 can also slide X distance relative to the second member 114, and total travel for the third member 116 relative to the first member 112 can be equal to 2X distance. In the collapsed position 105, the tubes/members can nest inside one another providing a smaller overall height "Y". In the extended position 107, the second member 114 can extend out of the first member 112, and the third member 116 can extend out of the second member 114.

The tubes/members can include glides 122 (described in more detail below) that can be located between each member at certain locations to provide smooth gliding between the first, second and third members, 112, 114, 116, and to provide structural support for a height adjustable desk 100 (see FIG. 1) to prevent any undesired wobble. In this disclosure, the term "glide" can also be described as a "guide". A set of glides 122 can be attached to a third member bottom outer edge 123, a second member top inner edge 124, a second member bottom outer edge 125, and a first member top inner edge 126 as illustrated in FIG. 2A according to an example of this disclosure. However, other glide orientations are also possible. In some configurations, vertical slides can be used between members instead of glides 122. In the extended position 107, a distance between adjacent glides 122 can be the smallest. The extended position 107 can provide a first minimum overlap 127 between the adjacent glides 122 at the second member bottom outer edge 125 and the first member top inner edge 126. The extended position 107 can provide second minimum overlap 128 between the adjacent glides 122 at the third member bottom outer edge 123 and the second member top inner edge 124.

In the collapsed position 105, adjacent glides 122 can move away from each other. This can provide a maximum distance between the adjacent glides 122, and the collapsed position 105 can provide a first maximum overlap 129

between the adjacent glides 122 at the second member bottom outer edge 125 and the first member top inner edge 126. The collapsed position 105 can provide second maximum overlap 130 between the adjacent glides 122 at the third member bottom outer edge 123 and the second member top inner edge 124. In the collapsed position 105, telescoping members of the leg assembly 109 nest inside one another, and provide the smallest overall height Y of the leg assembly 109. Such a configuration can be advantageous because lower work surface heights can be achievable without decreasing the overlap between the members or without reducing the distance of total height adjustment for the work surface 106 (see FIG. 1). Distance X can be a travel distance of the third member 116 relative to the second member 114 and also a similar distance X can be the travel of the second member 114 relative to the first member 112. Distance 2X can be the travel distance of the third member 116 relative to the first member 112.

FIG. 3 illustrates glides 122 for upper and lower telescoping members 132 in accordance with at least one example of this disclosure. Glides 122 can be made of one-piece molded plastic. However, in some configurations, multiple pieces of molded plastic glides, or tapes made up of low friction materials such as Teflon can be used as gliding surfaces between the adjacent telescoping members. Molded plastics can include bumps 131 to provide smaller contact surfaces between the telescoping members 132 to lower the friction as illustrated in FIG. 3. Grease can be used over the gliding surfaces to reduce friction. In other configurations, glides 122 can be replaced by vertical slides to guide the telescoping members 132 relative to each other. In an example, cross-sectional configurations of an outer glide 122 and an inner glide 122 can include a rectangular shape. In another example, cross-sectional configurations of glides 122 can match any curved, oval, polygonal, or irregular shape of a tube/member. The inner glide 133 can be attached to an inner surface of an outer tube 136, while an outer glide 134 can be attached to the outer surface of an inner tube 135. The bumps 131 can engage a gliding surface of an adjacent tube.

FIG. 4 illustrates a side view of a three member leg assembly 109 having a synchronization assembly 165 including an idler pulley assembly 137 in accordance with at least one example of this disclosure. An idler pulley assembly 137 can include a first idler pulley 138 and a second idler pulley 139, and a first tension member 141 and a second tension member 142. Tension members can be a flexible longitudinal connecting element such as rope, chain, cable, or belting. Tension members can be manufactured from metals, metal alloys, polymers, rubber, leather, fibers or combinations of the previous materials. Telescoping members 132 of the leg assembly 109 can be connected to each other via the idler pulley assembly 137 to ensure that second and third members 114, 116 move in synchronization, and to ensure that the second and third members 114, 116 do not slip relative to each other. Both the first and second idler pulleys 138, 139 can be rotatably coupled to the second member 114. A first tension member 141 can be routed around the first idler pulley 138 and can be attached to the first member 112 on one end at a first crimp 143 location, and can be attached to the third member 116 on the other end at a second crimp 144 location. A second tension member 142 can be routed around the second idler pulley 139 and can be attached to the first member 112 on one end at the first crimp 143 locations, and attached to the third member 116 on the other end at the second crimp 144 location. The configuration shown in FIG. 4 is for illustrative purposes only and should not be construed as limiting this disclosure.

The idler pulleys **138**, **139** can be attached to the second member **114** in many different locations to satisfy the geometric restrictions of the design. In some configurations, the first tension member **141** and the second tension member **142** can be portions of one continuous loop, and the one continuous loop can be attached to the first member **112** and third member **116** at the first crimp **143** and the second crimp **144** locations, respectively. In other configurations, the idler pulleys **138**, **139** can be located on opposite sides of the telescoping members **132**, and the first crimp **143** and second crimp **144** locations can be different for the first tension member **141** and the second tension member **142**.

FIGS. **5A** and **5B** show a counterbalance mechanism **151** according to an example of this disclosure. A counterbalance mechanism **151** can be a combination of one or more energy storage members, one or more wheels/pulleys and one or more tension members. A counterbalance mechanism **151** can provide a force to counteract a force created by the weight of a work surface **106** (see FIG. **1**) and any components such as documents, computers, tools, books etc. that may be supported by the work surface **106**. The energy storage member can be a gas spring, a rubber strap, a resilient member, or spring. The spring can be an extension spring or a compression spring. In the alternative, a counterbalance mechanism can have a force providing device which can function essentially as an energy storage member such as an electric motor, a linear actuator, a hydraulic actuator, or other similar devices. In this disclosure, although a coil spring or gas spring may be illustrated or described; other energy storage members or force providing devices can be substituted without changing the general intent of this disclosure. A leg assembly **109** can include three nesting members such as a lower tube **112'**, a middle tube **114'** and an upper tube **116'**. A cam/wheel assembly **153** can be attached close to the top end of the upper tube **116'**. A cam housing **150** can be located on top of the upper tube **116'** and can at least partially contain the cam/wheel assembly **153**. An idler pulley **166** can be attached close to the bottom end of the upper tube **116'**. A wheel tension member **156** can be routed around the idler pulley **166** and it can be attached to the middle tube **114'** at a third crimp **164** on one end, and attached to the wheel **154** on the other end. A spring **162** can be located approximately in the middle of the upper tube **116'**. A bottom end of the spring **162** can be attached to an adjustment screw **168**. The adjustment screw **168** can be attached to a spring adjustment assembly **170** at the other end. The spring adjustment assembly **170** can be fixed to the upper tube **116'**. A first end of a cam tension member **160** can be connected to the top end of the spring **162**. The cam tension member **160** can be routed around the tension member routing pulley **158** and connected to the cam **152** on a second end of the cam tension member **160**.

At the top of the travel range when the tubes are extended as illustrated in FIG. **5A**, the wheel tension member **156** can be wrapped around the wheel **154**. There can be a small extension of the wheel tension member **156** between the idler pulley **166** and the third crimp **164**. As the upper tube **116'** moves downwardly relative to the middle tube **114'**, the length of the wheel tension member **156** between the idler pulley **166** and the third crimp **164** can increase. If a weight "W" acts on the work surface **106** of height adjustable desk **100** (see FIG. **1**), the counterbalance mechanism **151** located inside the upper tube **116'** can resist the downward force due to the weight "W", and prevent relative motion between the upper tube **116'** and middle tube **114'**. During a height adjustment **98**, as the upper tube **116'** moves relative to the middle tube **114'**, the section of the wheel tension member

156 between the idler pulley **166** and the third crimp **164** extends by allowing the wheel **154** to rotate and unwrap the wheel tension member **156**. Since the cam **152** and the wheel **154** are attached together, the cam **152** also rotates, and thus, the cam tension member **160** wraps around the cam **152** and pulls the upper end of the spring **162** upwards, and stretches the spring **162**, which can cause a greater spring tension.

As illustrated in FIG. **5B**, in the collapsed position, as the spring force increases, the cam radius decreases to provide a constant torque around the wheel/cam assembly. The torque balance provides a constant force lift. This method of weight counterbalance using rotary cam is also explained in the patent, U.S. Pat. No. 8,286,927, the relevant contents of which are hereby incorporated by reference. In some examples, the counterbalance mechanism **151** can be completely positioned inside the upper tube **116'** as illustrated in FIG. **6A-B**. In some examples, the counterbalance mechanism **151** may also be included inside the lower tube **112'** (as illustrated in FIG. **7A-B**) or middle tube **114'** (as illustrated in FIG. **8A-B**) in other configurations. FIG. **7A-B** illustrate examples of a set of telescoping tubes having a smaller diameter tube at the base and a larger diameter tube at the upper end. The cam **152** can be located on the upper end of the tube (as illustrated in FIGS. **6A**, **7B**, and **8A**), or on the lower end of the tube (as illustrated in FIGS. **6B**, **7A**, and **8B**).

FIG. **9** shows a leg assembly according to an example of this disclosure. The cam housing **150** can be located on top of the upper tube **116'**. A cam axle **190** can be exposed on one side of the cam housing **150**. The cam axle **190** can be used to synchronize the cam/wheel rotations if both the leg assemblies **110**, **120** (see FIG. **1**) are used to provide the height adjustment **98** (see FIG. **5A**).

FIG. **10** shows a guide structure for the leg assemblies according to an example of this disclosure. The guides can be molded components. They provide smooth low friction surfaces between the tubes. In some configurations, vertical slides may be used. The middle and lower tubes **114'**, **112'** are shown as transparent to expose the guide members **172**, **174**, **176**, **178**. An upper tube guide member **172** can be located near the bottom end of the upper tube **116'**. A top middle tube guide member **174** can be located near the top of the middle tube **114'**. A bottom middle tube guide member **176** can be located near the bottom of the middle tube **114'**. A lower tube guide member **178** can be located near the upper end of the lower tube **112'**.

FIG. **11** shows an upper tube assembly. The cam housing **150** including the wheel **154** can be attached to the top of the upper tube **116'**. A brake assembly **200** can be located at the bottom of the upper tube **116'** as in the example shown, however other positions in a leg assembly **109** (see FIG. **1**) are possible for a brake assembly **200**.

FIG. **12** illustrates a perspective view of a spring assembly **171**. The cam/wheel assembly **153** can be located inside a cam housing **150** as in FIG. **5**. The rest of the components, including the mandrel **192**, springs **162**, and spring adjustment assembly **170** can be located inside the upper tube **116'**. In another example, all of the components can be located within members of a leg assembly **109** (see FIG. **1**). Depending on the lift force requirement, a number of springs may be used in the spring assembly **171**. The number of springs **162** can vary, e.g., between 1 and 4. In some examples, four or more springs **162** may be included. The upper spring holding block **194** can be attached to the upper end of the springs **162**, and the lower spring holding block **196** can be attached to the lower end of the springs **162**. One or more cam tension members **160** may be attached to the upper

spring holding block **194**. These tension members are routed around the mandrel **192** and attached to one or more cams **152**. In some examples, if only one spring **162** is used, the upper spring holding block **194** can be eliminated, and the cam tension member **160** can be directly attached to a hook (not shown) at the end of the spring **162**. The lower spring holding block **196** has a threaded hole (not shown) at the center. An adjustment screw **168** can be threadingly engaged with the lower spring holding block **196** through this hole. The bottom end of the adjustment screw **168** can be attached to the spring adjustment assembly **170**. By rotating the adjustment screw **168** via the spring adjustment assembly **170**, it can be possible to pull the bottom end of the springs **162** down and increase the spring tension to counterbalance a larger weight.

FIG. **13A** illustrates adjustment of the spring assembly **171** for the minimum weight, when the desk leg assemblies can be in an extended position **107** (see FIGS. **2A**, **5A**). There is no cam rotation yet, and therefore, upper end of the spring assembly **171** is not stretched towards the cam **152**. At this orientation, the cam tension member **160** can be in contact with the starting point of a cam profile **163**. The cam profile **163** can be an eccentric shape that can be designed to allow smoothly operating height adjustments. As the leg assemblies **109** (see FIG. **1**, **3**) are compressed, the wheel/cam assembly rotates, and the cam tension member **160** can be wrapped around the cam **152**, and the upper end of the spring assembly **171** can be pulled up as shown in FIG. **13B**. As the cam tension member **160** wraps around the cam **152**, the wheel tension member **156** can be moving in the opposite direction. FIG. **13C** shows the side view of the spring assembly **171** at the collapsed position **105** of the tubes **112'**, **114'**, **116'** (see FIGS. **2B**, **5B**). As shown in the side view of FIG. **13C**, the spring assembly **171** can include multiple cam tension members **160** and a cam **152** can be configured for more than one cam tension member **160**. The adjustment screw **168** can be at an extended length as in FIGS. **13A-C**.

FIGS. **14A-B** are front elevation views of a spring adjustment assembly **170** in accordance with at least one example of this disclosure. To counterbalance larger weights, the lower end of the springs **162** can be pulled down by turning the adjustment screw **168** as shown in FIGS. **14A** and **14B**, for extended position **107** and collapsed position **105** of the leg assemblies **109**, respectively (see FIGS. **2A-B**, **5A-B**).

FIG. **15** is a perspective view of selected details of a spring adjustment assembly **170** in accordance with at least one example of this disclosure. All the components are attached to a cast block **406**, and the block **406** can be attached to the bottom end of the upper tube **116'** (see FIG. **5A**). The bottom end of the adjustment screw **168** can be attached to a gear **402**. The gear **402** can be operably coupled to a worm gear **404**. One end of the worm gear **404** has a recessed hole **408**. The shape of the hole **408** can be hexagonal. The hole **408** can be in line with an access hole **180** located on the middle tube **114'** at a certain position of the first and second leg assemblies **110**, **120**. The position of the access hole **180** is shown in FIG. **9**. The recessed hole **408** can be in line with the access hole **180** at the extended position **107** of the first and second leg assemblies **110**, **120** (see FIG. **1**) since this also corresponds to the lowest spring tension. By accessing the recessed hole **408** and turning the worm gear **404** using a tool (e.g.: a wrench), a user can increase or decrease the tension on the extension springs **162** (see FIGS. **14A-B**), and increase or decrease the lift capacity of the counterbalance mechanism **151** (see FIGS. **5**, **13**, **14**).

FIG. **16** is a perspective view of a height adjustable desk **100** with leg assemblies **99** in accordance with at least one example of this disclosure. In some examples, a synchronization bar **502** can be provided as shown in FIG. **16**. When more than one leg assembly **99** is used to lift the desk surface, the wheel rotations can be synchronized by the synchronization bar **502** on the first and second leg assemblies **110**, **120** so that both leg assemblies extend or collapse to the same amount to keep the desk surface horizontal. The synchronization bar **502** can be inserted into a square recessed hole **198** located on the cam axle **190** of each lift mechanism. The square recessed hole **198** can be best seen in FIG. **12**. A front view of a height adjustable desk **100** including a work surface **106**, a synchronization bar **502**, a brake handle **140**, first and second leg assemblies **110**, **120** each including three telescoping tubes and a cross bar **108** is shown in FIG. **17**.

FIG. **18** is a perspective view of a height adjustable desk **100** with leg assemblies **99** in accordance with at least one example of this disclosure. In this configuration, the counterbalance mechanism **500** is attached to the bottom of the work surface **106**. The first and second leg assemblies **110**, **120** can include a synchronization assembly **165** (see FIG. **4**) for the telescoping tubes. A front view of the same height adjustable desk **100** is shown in FIG. **19**.

FIG. **20** is a bottom plan view of a height adjustable desk **100** with leg assemblies **99** in accordance with at least one example of this disclosure. FIG. **20** illustrates main sub-assemblies of the height adjustable desk **100** with the counterbalance mechanism **500** located under the height adjustable desk **100**. The work surface **106** is shown as transparent to make the rest of the components visible. The counterbalance mechanism **500**, as shown, can be contained inside a metal box which can be attached to the bottom of the work surface **106**. First and second leg assemblies **110**, **120** can be attached to left and right sides of the work surface **106** close to the edges. A brake handle **140** can be located under the desk surface close to a front right corner. First and second foot **102**, **104** are shown at the base of the leg assemblies **99**.

FIG. **21** shows a top view of an example of a counterbalance mechanism **500**. All the components can be attached to a structural bracket **512**, and the structural bracket **512** can be attached under the work surface **106**. A number of springs **562** can be used in the system depending on the amount of the weight to be counterbalanced. One end of the springs **562** can be attached to the right spring holding bracket **572**. The right spring holding bracket **572** can be threadingly attached to the adjustment screw **568** at its center. The adjustment screw **568** can be rotatably connected to the spring adjustment assembly **570**. The spring adjustment assembly **570** is similar to the design shown in FIG. **15**. By turning the adjustment screw **568** via the spring adjustment assembly **570**, the right spring holding bracket **572** can be moved to adjust the tension on the springs **562**. The right spring holding bracket **572** can move along a direction indicated by the line "c-d" on FIG. **21**. The left ends of the springs **562** are attached to the left spring holding bracket **566**. The left spring holding bracket **566** has two sides. In the right side it can be attached to the extension springs **562**. Two hooks, an upper hook **559** and a lower hook **560**, are positioned on the left side of the left spring holding bracket, and the third and fourth tension members **540**, **550** are attached to these hooks as illustrated in FIG. **22**. As shown in FIGS. **21** and **22**, the third tension member **540** and the fourth tension members **550** may be positioned in a plane, one above the other. As shown in FIG. **21**, an axle **591** of the

cam/wheel assembly **590** can be attached to the structural bracket **512** in a vertical direction. The cam/wheel assembly **590** can be allowed to rotate in a horizontal plane.

FIG. **23A-B** are elevation and top views of a cam/wheel assembly **590** of a counterbalance mechanism **500** (see FIG. **18**) in accordance with at least one example of this disclosure. The upper cam **552** and the upper wheel **554** can be molded together as shown in FIG. **23A-B**. An upper cam **552** and upper wheel **554** assembly, and a lower cam **556** and lower wheel **558** assembly can be connected together as shown in FIG. **22**. They can be fixed to each other, and they can rotate in unison. The third tension member **540** can be attached to the upper hook **559** on the left spring holding bracket **566**, and stretched towards the cam/wheel assembly **590** and connected to the upper cam **552**. The fourth tension member **550** can be attached to the lower hook **560** on the left spring holding bracket **566**, and stretched towards the cam/wheel assembly and connected to the lower cam **556**. During the height adjustment, cam/wheel assembly **590** can rotate in clockwise direction, third tension member **540** and fourth tension member **550** can be wrapped around upper and lower cams **552** and **556**, respectively, while pulling the left end of the spring **562** towards the cam/wheel assembly **590**. This increases the tension on third tension member and fourth tension member **540**, **550**, but this increase in the tension member tension can be balanced by reducing the cam radius at the tension member contact point.

FIG. **24** is front elevation view of the cam/wheel assembly **590** of a counterbalance mechanism in accordance with at least one example of this disclosure. FIG. **25** is a perspective view of a cam/wheel assembly **590** of a counterbalance mechanism in accordance with at least one example of this disclosure. A close-up view of the cam/wheel assembly **590** and adjacent spools are shown in FIGS. **24** and **25**. In this disclosure, a spool can function as a pulley and can provide a rotatable surface to aid in guiding a tension member. In the alternative, a stationary guide member can be used to provide a low friction direction changing or guiding device for a tension member. All the components shown in FIG. **25** can be attached to the structural bracket **512**. A plurality of spools such as a first spool **506**, a second spool **504**, and a third spool **508**, can be rotatably coupled with the structural bracket **512** in the horizontal plane, and left pulley **514** can be rotatably coupled with the structural bracket **512** in the vertical plane. Some of the attachment brackets are removed from the picture to make the spools **506**, **508**, **510** and left pulley **514** visible. Also, the upper cam **552** (see FIG. **22**) is not visible in FIG. **25** under the upper wheel **554**. Although second and third spools **504**, **508** can be located on the same axis, they can be independently rotatable. One end of first tension member **510** can be attached to the upper wheel **554** and it can be routed around the second spool **504** and first spool **506** towards the left pulley **514**. The left pulley **514** can be located over the first leg assembly **110** (see FIG. **26**), and it can route the first tension member **510** downwards to attach to the leg assembly components. One end of second tension member **520** can be attached to lower wheel **558** and it can be routed around the third spool **508** towards right pulley **518** (see FIG. **21**). The right pulley **518** can be located over the second leg assembly **120** (see FIG. **18**), and it can route the second tension member **520** downwards to attach to the leg assembly components. A top view of tension member routing is shown in FIG. **24**. FIGS. **24-25** show an example tension member routing according to one example of this disclosure. Other tension member routing configurations are also possible without changing the general intent of this disclosure.

FIG. **26** illustrates how the first tension member **510** can be routed downwards over left pulley **514** to attach to the components of the first leg assembly **110** as explained in later figures. The top end of the upper tube **116'** can be attached to a surface attachment bracket **580**. The structural bracket **512** can be attached to the surface attachment bracket **580** as well. The work surface **106** can be attached to both the surface attachment bracket **580** and the structural bracket **512**. The holding bracket **582** for the left pulley **514** can be attached to the surface attachment bracket **580**. A similar arrangement can be used with respect to second leg assembly **120** (see FIG. **18**).

An example of a three member leg assembly is shown in FIG. **27**. A plurality of guide members **582**, **584**, **586**, **588** can be located between the telescoping tubes similar to the example shown in FIG. **10**. An upper tube guide member **584** can be attached to the lower end of the upper tube **116'**. A top middle tube guide member **582** can be located near the top of the middle tube **114'**. A bottom middle tube guide member **588** can be located near the bottom of the middle tube **114'**. A lower tube guide member **586** can be attached to the upper end of the lower tube **112'**. The guides can be molded components. They provide smooth low friction surfaces between the tubes. In some configurations, vertical slides may be used. FIG. **27** illustrates a side view of the work surface **106**, the surface attachment bracket **580**, the structural bracket **512**, the brake handle **140**, and the first foot **102**.

FIG. **28** illustrates an example of routing of the first tension member **510** inside the upper tube **116'**. The first tension member **510** can be routed downwards over the left pulley **514**. The first tension member **510** can be routed around an idler pulley **608**, and the end of first tension member **510** can be attached to a top bracket **602**. The idler pulley **608** can be rotatably coupled with a brake bracket **664** at a first axle **624**. The brake bracket **664** can be rotatably coupled with the upper tube **116'** at the second axle **626**, and mounting bracket **614**. When there is tension on the first tension member **510**, the tension can rotate the brake bracket **664** in counter-clockwise direction until it stops against a stop surface **642**. This can provide a control surface for the brake.

The top bracket **602** shown in FIG. **28** can be located inside the upper tube **116'**, and attached to the middle tube **114'** via first and second rods **610**, **620**. The brake bracket **664** and the idler pulley **608** can be attached to the upper tube **116'**. The first section "a" of the first tension member **510** can be between the left pulley **514** and the idler pulley **608**, and the second section "b" of the first tension member **510** can be between the idler pulley **608** and the top bracket **602**. During a downward height adjustment, the upper tube **116'** moves down relative to the middle tube as explained in association with FIG. **4**. The first section "a" of first tension member stays constant in length. The second section "b" of the first tension member increases in length as the work surface **106** moves down. Due to increased length of the second section "b" of the first tension member **510**, more first tension member **510** can be pulled in to the upper tube **116'** and the upper wheel **554** (see FIG. **25**) can rotate to allow this change in length.

FIG. **29** is a front elevation view of a lower secondary brake assembly **700** in accordance with at least one example of this disclosure. Movement of upper, middle and lower tubes **116'**, **114'**, **112'** can be synchronized as explained in association with FIG. **4**. When the tension members involved in this synchronization are broken, tubes can be locked, and the height adjustment mechanism can be dis-

abled. This synchronization and a secondary brake for the height adjustable desk 100 shown in FIG. 18 are illustrated in FIG. 29. A bottom bracket 802 can be attached to the bottom end of the middle tube 114'. A top bracket 702 can be attached to the middle tube 114' via a first rod 710 and a second rod 810. The first rod 710 and the second rod 810 can be attached to the bottom bracket 802. The first and second rods 710, 810 can extend upwards to the inside of the upper tube 116'. The top bracket 702 can be attached to the top ends of the first and second rods 710, 810, and the top bracket 702 can be located inside the upper tube 116'. A first pulley 704 can be attached to the top bracket 702, and the second pulley 804 can be attached to the bottom bracket 802. The first pulley 704 and second pulley 804 can be rotatably coupled to the top and bottom brackets 702, 802, respectively.

A first brake bracket 706 can be attached to upper tube 116', and second brake bracket 708 can be attached on top of the third rod 850. The bottom of the third rod 850 can be attached to the lower tube 112' as shown in FIG. 30, and the third rod 850 can extend upwards inside the middle tube 114'. Returning to FIG. 29, the first and second hooks 712, 714 can be attached to the lower secondary brake assembly 700, and the third and fourth hooks 812, 814 can be attached to and upper secondary brake mechanism 800. A first end of a fifth tension member 730 can be attached to the first hook 712, and the fifth tension member 730 can be stretched upwards and routed around the first pulley 704, and the second end of fifth tension member 730 can be attached to the third hook 812. A first end of the sixth tension member 830 can be attached to the second hook 714, and the sixth tension member 830 can be stretched downwards and routed around the second pulley 804, and the second end of the sixth tension member 830 can be attached to the fourth hook 814. During the height adjustment, the fifth and sixth tension members 730, 830 slide over the first and second pulleys 704, 804, respectively, but their overall lengths do not change, therefore, the motion of the middle tube 114' and the upper tube 116' can be synchronized. If the middle tube moves a distance "X" relative to the lower tube 112', the upper tube 116' can also move a distance "X" relative to the middle tube 114' in this example.

FIG. 31 is a front elevation view of a lower secondary brake assembly 700 in accordance with at least one example of this disclosure. The second brake bracket 708 can be attached on top of the third rod 850. The first hook 712 can be attached to the upper tab 766. The second hook 714 can be attached to the flat bracket 740. The fifth tension member 730 can be attached to the first hook 712 and the sixth tension member 830 can be attached to the second hook 714. A compression spring 760 can be coaxial with first rod 710, and it can be located between the flat bracket 740 and lower tab 762. The first rod 710 and the second rod 810 can be attached to the bottom bracket 802. During the normal operation of the lift mechanism, there can be tension in the fifth and sixth tension members 730, 830. Therefore, flat brackets are pulled downwards against the lower tab 762. In this configuration, the compression spring 760 can be compressed between the flat bracket 740 and the lower tab 762. If tension is inadvertently lost on the sixth tension member 830, the flat bracket 740 will be angled relative to the first rod 710 due to the force of the compression spring 760, and the flat bracket 740 will grab on to the first rod 710.

FIG. 32 illustrates a side view of a height adjustable desk 910 with a fixed height leg assembly and a moving bracket in accordance with at least one example of this disclosure. In an example, leg assembly 909 can be at a fixed height, and

a moveable bracket 922 can be slidably engaged with the leg assembly 909 and can provide the height adjustment 911 as illustrated in FIG. 32. The leg assembly 909 can be used as a lift mechanism 999 that can be used to provide support and counteract a downward force for numerous applications including a work surface, table, or desk 910. A fixed height first member 923 can be attached to the top of a base 924. The base 924 can include casters 925 that can provide mobility to the unit. A second member 916, such as the moveable bracket 922, can be slidably engaged with the fixed height first member 923. A work surface 914 can be attached to the moveable bracket 922. The moveable bracket 922 can be supported by a counterbalance mechanism 926 (see FIG. 33) located inside the fixed height first member 923. The counterbalance mechanism 926 can be any one of a gas spring, a pulley system attached to an energy storage member, an electric motor, a linear actuator, a hydraulic actuator, or other similar devices or methods.

FIGS. 33A-33B illustrate a side view of a counterbalance mechanism 926 using a gas spring 927 in accordance with at least one example of this disclosure. The gas spring 927 can include a cylinder 928 and a piston 929 and the piston 929 can move in and out of the cylinder 928. The cylinder 928 can include a closed end 998 that can be attached to a leg assembly 99, 909, 938 (see FIGS. 1, 32, 34, 38, 41). Opposite the closed end 998, the cylinder 928 can include a piston end 997 from which a piston 928 can extend and retract. The gas spring 927 can be attached to the fixed height first member 923 via a support bracket 930. The support bracket 930 can be fixedly attached to the fixed height first member 923, and it can be located anywhere along the length of the fixed height first member 923. A cylinder base 931 can be attached to the support bracket 930. The piston 929 can be freely allowed to move in and out of the gas spring 927 during a height adjustment 911. A pulley 932 can be rotatably coupled with the piston 929 on a piston outer end 933. An interface bracket (not shown in FIG. 33) may be used to provide coupling between the pulley 932 and the piston 929. An additional support bracket (not shown in the FIG. 33) can also be attached between fixed height first member 923 and the cylinder 928 close to the cylinder upper end 934 to make sure that the gas spring 927 maintains its orientation relative to the fixed height first member 923 during the height adjustment 911. A tension member 935 can be attached between fixed height first member 923 and a second member 916 which can be moveable. The tension member 935 can be any linear connecting member such as a rope, a chain, a wire, a cable or belt. A tension member first end 936 can be fixedly attached to the fixed height first member 923. The tension member 935 can be routed around the pulley 932, and a tension member second end 937 can be attached to the second member 916. In an example configuration such as illustrated in FIG. 33A-B, when the piston 929 of the gas spring 927 moves a distance of X distance, the second member 916 can travel a distance of 2X distance.

FIG. 34 illustrates a side view of a height adjustable desk 910 with a two member leg assembly 938 in accordance with at least one example of this disclosure. The leg assembly 938 can include a first member 915 and a second member 916 and the second member 916 can be slidably engaged with first member 915. The first member 915 can be fixedly attached to a base 924 at a first member bottom end 939. The second member 916 can move in and out of the first member 915 during a height adjustment 911 thereby changing the total height of the leg assembly 938. A work surface 914 can be attached to a second member upper end 940. The height of the work surface 914 can be adjusted as the height of the

leg assembly 938 is varied. A counterbalance mechanism 926 (See FIG. 33) can be contained inside the leg assembly 938 and can provide lift assist during the height adjustment 911. The counterbalance mechanism 926 can carry at least part of the combined weight of the second member 916; work surface 914, and any components that may be located on the work surface 914. The base 924 can include casters 925 to provide a moveable unit. If a synchronization assembly 165 such as described in FIG. 4 is removed from any of the previously described three member leg assemblies, the counterbalance mechanism for any of the three-member leg assemblies described in previous sections can be used in a two-member leg assembly. One of the first or second members can contain the counterbalance mechanism, and the other member can be immediately adjacent to the member containing the counterbalance mechanism. The other member can be connected to the counterbalance mechanism through a tension member.

FIGS. 35A-35B illustrate a side view of a leg assembly 938 having a counterbalance mechanism 926 using a gas spring 927 in accordance with at least one example of this disclosure. The leg assembly 938 can include a telescoping configuration of a first member 915 and a second member 916. A cylinder base 931 or closed end 998 can be fixedly attached to a first member bottom end 939. A piston 929 can be allowed to move in/out of the piston end 997 of the cylinder 928 during a height adjustment 911. A pulley 932 can be rotatably coupled with the piston 929 on a piston outer end 933. An interface bracket (not shown in the FIGS. 35A-B) may be used to provide coupling between the pulley 932 and the piston 929. A tension member 935 can be attached between the first member 915 and the second member 916. A tension member first end 936 can be fixedly attached to the second member 916. The tension member 935 can be routed around the pulley 932, and a tension member second end 937 can be fixedly attached to the first member 915. Attachment locations for the tension member 935 to the first member 915 and second member 916 can vary depending on the application. With the configuration illustrated in FIGS. 35A-B, when the piston 929 of the gas spring 927 can move X distance, the second member 916 of the leg assembly 938, and thus, the work surface 914 (see FIG. 34) can move 2X distance. The gas spring 927 can be locked and the piston 929 will not move in or out of the cylinder 928. Since the pulley 932 can be fixedly attached to the piston 929, it will not be possible to lower the second member 916 when the gas spring 927 is locked. Locking the gas spring 927 in this configuration can still allow upward movement of the second member 916. The gas spring 927 can be unlocked, and the piston 929 can move out of the cylinder 928, and thus, push the second member 916 upwardly.

FIG. 36 illustrates a force distribution diagram for a gas spring 927 counterbalance mechanism 926 in accordance with at least one example of this disclosure. A counterbalance mechanism 926 can carry at least part of a combined weight W of the second member 916, work surface 914 (see FIGS. 32, 34, 38, and components located on the work surface 914. With a pulley and tension member assembly, half of the total lift force (or F/2) provided by the gas spring 927 is transferred to the second member 916. Therefore, gas spring lift force F must be properly set such that half of the gas spring force (or F/2) is approximately equal to the combined weight W of the second member 916, work surface 914, and any components that are located on the work surface. If the counterbalance mechanism 926 provides less force than W to counteract weight W, the desk user

can provide additional force to move the work surface 914 upwards. Counterbalance mechanisms can be selected or adjusted to fit a particular desk or work surface 914 and to fit particular loads the work surface 914 might support.

FIGS. 37A-37B illustrate a side view of a counterbalance mechanism 926 using a gas spring 927 in accordance with at least one example of this disclosure. A pulley bracket 941 can be attached to the piston outer end 933, and the pulley bracket 941 can move with the piston 929 during a height adjustment 911 (see FIG. 34). At least part of the pulley bracket 941 can overlap with the cylinder 928. A first pulley 942 can be attached to a pulley bracket upper end 943, and a second pulley 944 can be attached to a pulley bracket lower end 945. A first tension member 946 and a second tension member 947 can engage the first pulley 942 and the second pulley 944. A first tension member first end 948 can be fixedly attached to the second member 916. The first tension member 946 can be routed up and around the first pulley 942, and a first tension member second end 949 can be fixedly attached to the cylinder upper end 934. Since the cylinder 928 can be fixedly attached to the first member 915, attaching the first tension member 946 to the cylinder 928 is similar to attaching the first tension member 946 to the first member 915. In other examples, various other means such as a separate rod, or bracket may be employed to attach the first tension member second end 949 to the first member 915. A second tension member first end 950 can be fixedly attached to second member 916. The second tension member 947 can be routed down and around the second pulley 944, and a second tension member second end 951 can be fixedly attached to the cylinder 928. The counterbalance mechanism 926 illustrated in FIGS. 37A-B can operate in a similar manner as the counterbalance mechanism 926 illustrated in FIGS. 35A-B. In the configuration illustrated in FIGS. 37A-B, the cylinder 928 can be locked and a work surface 914 (see FIG. 34) cannot be moved upwardly or downwardly.

FIG. 38 illustrates a side view of a height adjustable desk 100 with a two member leg assembly 938 and a gas spring 927 attached to a second member 916 in accordance with at least one example of this disclosure. In the counterbalance mechanisms illustrated in FIGS. 34-37, the cylinder 928 can be fixedly attached to the first member 915. In alternative examples, the cylinder 928 of FIGS. 34-37 can be attached to the second member 916 as illustrated in FIG. 38 without changing the general intent of this disclosure. The counterbalance mechanism 926 can still function in a similar manner. As illustrated in FIG. 38, a leg assembly 938 can include a first member 915 and a second member 916 attached to a base 924. The base 924 can include casters 925. The cylinder base 931 can be attached to a work surface 914 or the upper end of the second member 916. The piston 929 can move outwardly from the bottom of the second member 916 and include a pulley 932 and a tension member 935. The tension member 935 can be attached to the first member 915 at a tension member first end 936 and attached to the second member 916 at a tension member second end 937.

FIG. 39 illustrates a side view of a counterbalance mechanism 926 using a gas spring 927 in a three member leg assembly 938 in accordance with at least one example of this disclosure. Movement of the telescoping members 973 of the leg assembly 938 can be synchronized by an idler pulley assembly 970 as explained in association with FIG. 4. All of the previously described two member leg assemblies can add a moveable third member 917, by adding a synchronization assembly 165, such as the idler pulley assembly 970 as explained in association with FIG. 4. A gas spring 927 can

be attached between the first member **915** and the second member **916**. A cylinder base **931** can be fixedly attached to the first member bottom end **939**. The piston outer end **933** can be attached to a second member upper end **940**. The second member **916** can move with the piston **929** during a height adjustment **911**. In this configuration, a total travel **976** of the third member **917** can be twice as long as a stroke **977** of the piston **929** and a gas spring force $2W$ can be two times the desired weight W that can be counterbalanced.

FIG. **40** illustrates a side view of a counterbalance mechanism **926** using a gas spring **927** in a three member leg assembly **938** in accordance with at least one example of this disclosure. Movement of the telescoping members **973** of the leg assembly **938** can be synchronized by the idler pulley assembly **970** as explained in association with FIG. **4**. A gas spring **927** can be attached between a second member **916** and a third member **917**. The cylinder base **931** can be fixedly attached to the second member bottom end **979**. The piston outer end **933** can be attached to a third member upper end **978**. A displacement or travel of the third member **917** relative to the second member **916** can be the same displacement as the stroke **977** of the piston **929** during the height adjustment **911**. In this configuration, total travel **976** of the third member **917** can be twice as long as the stroke **97** and gas spring force $2W$ can be two times the desired weight W that can be counterbalanced.

FIG. **41** illustrates a side view of a counterbalance mechanism **926** using a gas spring **927** in a three member leg assembly **938** in accordance with at least one example of this disclosure. The leg assembly **938** can also function as a lift mechanism **999**. Movement of the telescoping members **973** of the leg assembly **938** can be synchronized by the idler pulley assembly **970** as explained in association with FIG. **4**. The synchronization assembly **165** (see FIG. **4**), can also be called an idler pulley assembly **970** and can partially transfer one of: a) movement between the first member **915** and the second member **916** to movement between the second member **916** and the third member **917**, or b) movement between the second member **916** and the third member **917** to movement between the first member **915** and the second member **916**. The idler pulley assembly **970** can balance movement between the first and second members **915**, **916** with movement between the second and third members **916**, **917**.

In the configuration illustrated in FIG. **41**, the cylinder base **931** can be fixedly attached to the first member bottom end **939**. The piston **929** can be free to move in/out of the cylinder **928**. A pulley **932** can be rotatably coupled to the piston outer end **933**. A tension member **935** can be attached between the first member **915** and the second member **916**. The tension member first end **936** can be fixedly attached to the first member **915**. The tension member **935** can be routed up and around the pulley **932** and the tension member second end **937** can be fixedly attached to the second member **916**. In this configuration, the second member **916** can include a displacement **980** that is twice the distance of the stroke **977** of the piston **929**. The total travel **976** of the third member **917** can be four times the stroke **977** of the piston **929**, and gas spring force $4W$ can be four times the desired weight W that can be counterbalanced.

Although FIG. **41** is illustrated having the cylinder **928** attached to the first member bottom end **939**, configurations such as illustrated in FIGS. **6A**, **6B**, **7A**, **7B**, **8A** and **8B** are also fully contemplated by this disclosure. The cylinder base **931** can be attached to the top or bottom of the third member as in FIGS. **6A-B**. The cylinder base **931** can be attached to the top or bottom of the first member that slides internally to

a second member, that slides internally to a third member as in FIGS. **7A-B**. The cylinder base **931** can be attached to the top or bottom of the second member as in FIGS. **8A-B**. In each of the previous three member examples, the tension member can engage the pulley wheel attached to the piston and each end of the tension member can be attached to adjacent members. For example in a configuration similar to that illustrated in FIG. **6A**, the tension member can be attached to the second member and the third member. In each of the previous three member examples, the synchronization assembly can include a first pulley near the top of the second member and a second pulley near the bottom of the second member. Each synchronization pulley can engage a tension member that can be attached to non-adjacent leg members, such as to the first member and the third member.

FIG. **42** illustrates a three member leg assembly **938** in another example that can include two gas springs. A counterbalance mechanism **926** can include a first gas spring **981** and second gas spring **982**. The first gas spring **981** can include a first piston **987** and a first cylinder **989**. The second gas spring **982** can include a second piston **988** and a second cylinder **990**. In this configuration, first and second gas springs **981**, **982** can be attached to the second member **916**. A first cylinder base **983** can be fixedly attached to the second member bottom end **979**. A first piston outer end **984** can be fixedly attached to the third member upper end **978**. The displacement **980** of the third member **917** relative to the second member **916** can be the same as the stroke **977** of the first gas spring **981**. The second gas spring **982** can be oriented upside down relative to the first gas spring **981**. The second cylinder base **985** can be fixedly attached to the second member upper end **940**. The second piston outer end **986** can be fixedly attached to the first member bottom end **939**. The displacement **980** of the second member **916** relative to the first member **915** can be the same as the stroke **977** of the second gas spring **982**. Each gas spring force can be equivalent to the desired weight W that can be counterbalanced. An idler pulley assembly **970** is not needed to build this lift mechanism. The counterbalance mechanism **926** will function without the idler pulley assembly **970**. However, to synchronize the telescoping motion between the first member **915** and the second member **916** with the telescoping motion between the second member **916** and the third member **917**, an idler pulley assembly **970** can be used.

Various examples of the height adjustment mechanisms are described in previous sections in association with FIGS. **32-42** for a work surface **914** supported by a single leg assembly **909**. However, multiple leg assemblies **99**, **909**, **938** can be used for a height adjustment **911** as described earlier in this disclosure and whether illustrated as a single leg assembly or a multiple leg assembly either can be used without changing the general intent of this disclosure. The leg assemblies **99**, **909**, **938** can be used as a lift mechanism **999** that can be used to provide support and counteract a downward force for numerous applications including a work surface **914**, a table, or desk **100**.

Thus, examples of this disclosure are disclosed. Although the present invention has been described in considerable detail with reference to certain disclosed examples, the disclosed examples are presented for purposes of illustration and not limitation and other examples of this disclosure are possible. One skilled in the art will appreciate that various changes, adaptations, and modifications may be made without departing from the spirit of this disclosure.

What is claimed is:

1. A height adjustable desk comprising:
 - a work surface; and

21

at least one leg assembly configured to attach to the work surface, the at least one leg assembly including a lift mechanism, the lift mechanism including:

- a first member;
- a second member moveable relative to the first member along a longitudinal axis, wherein the second member is configured to form a telescoping assembly;
- a pulley assembly including:
 - a pulley bracket, the pulley bracket having a first end and extending along the longitudinal axis to a second end;
 - a first wheel rotatably attached near the first end of the pulley bracket;
 - a second wheel rotatably attached near the second end of the pulley bracket;
 - a first tension member extending around the first wheel, the first tension member attached to the second member and to the first member; and
 - a second tension member extending around the second wheel, the second tension member attached to the second member and to the first member; and
 - a counterbalance mechanism configured to counteract a force exerted on the lift mechanism, the counterbalance mechanism including:
 - a gas spring having a cylinder and a moveable piston slidably attached to the cylinder, wherein the cylinder is coupled to one of the first member, and the pulley bracket, and wherein the moveable piston has a piston end coupled to another one of the first member, and the pulley bracket.

2. The height adjustable desk of claim 1, wherein the cylinder extends from a closed end to the piston end, the closed end being coupled to the first member.

3. The height adjustable desk of claim 1, comprising: a base, wherein the second member is attached to the base, wherein the cylinder is coupled to the first member, and wherein the worksurface is attached to the first member.

4. The height adjustable desk of claim 1, comprising: a base, wherein the first member is attached to the base, wherein the cylinder is coupled to the first member, and wherein the worksurface is attached to the second member.

5. The height adjustable desk of claim 1, wherein the cylinder extends from a closed end to a piston end, the closed end being coupled to the second member.

6. A height adjustable desk comprising: a work surface; and at least one leg assembly configured to attach to the work surface, the at least one leg assembly including a lift mechanism, the lift mechanism including:

- a first member;
- a second member moveable relative to the first member along a longitudinal axis;
- a third member moveable relative to the second member along the longitudinal axis;
- a synchronization assembly configured to balance movement between the first and second members with movement between the second and third members, wherein the synchronization assembly includes a first pulley wheel moveably connected to a first end of the second member and a second pulley wheel moveably connected to the second end of the second member; and

22

a counterbalance mechanism configured to counteract a force exerted on the lift mechanism, the counterbalance mechanism including:

- a gas spring having a cylinder and a moveable piston slidably attached to the cylinder.

7. The height adjustable desk of claim 6, wherein the cylinder is coupled to one of the first member, the second member, and the third member, and wherein the moveable piston has a piston end coupled to another one of the first member, the second member, and the third member.

8. A height adjustable desk comprising: a work surface; and at least one leg assembly configured to attach to the work surface, the at least one leg assembly including a lift mechanism, the lift mechanism including:

- a first member;
- a second member moveable relative to the first member along a longitudinal axis;
- a third member moveable relative to the second member along the longitudinal axis;
- a synchronization assembly configured to balance movement between the first and second members with movement between the second and third members, wherein the synchronization assembly includes a first pulley wheel moveably connected to a first end of the second member and a second pulley wheel moveably connected to a second end of the second member; and
- a counterbalance mechanism configured to counteract a force exerted on the lift mechanism, the counterbalance mechanism including:
 - a gas spring having a cylinder and a moveable piston slidably attached to the cylinder, the cylinder coupled to the lift mechanism;
 - a counterbalance pulley wheel rotatably coupled to the gas spring; and
 - a tension member coupled to the first member and the second member and extending around the counterbalance pulley wheel.

9. The height adjustable desk of claim 8, wherein the cylinder is coupled to one of the first member, the second member, and the third member.

10. The height adjustable desk of claim 8, further comprising a locking mechanism configured to lock the gas spring.

11. The height adjustable desk of claim 8, wherein the second member is configured to fit inside the first member and the third member is configured to fit inside the second member and form a telescoping assembly.

12. The height adjustable desk of claim 8, wherein the first member is configured to fit inside the second member and the second member is configured to fit inside the third member and form a telescoping assembly.

13. The height adjustable desk of claim 6, further comprising a locking mechanism configured to lock the gas spring.

14. The height adjustable desk of claim 6, wherein the second member is configured to fit inside the first member and the third member is configured to fit inside the second member and form a telescoping assembly.

15. The height adjustable desk of claim 6, wherein the first member is configured to fit inside the second member and the second member is configured to fit inside the third member and form a telescoping assembly.

16. The height adjustable desk of claim 1, wherein the first tension member and the second tension member are portions of a single tension member.

23

17. The height adjustable desk of claim 1, further comprising a locking mechanism configured to lock the gas spring.

18. A height adjustable desk comprising:

a work surface; and

5

at least one leg assembly configured to attach to the work surface, the at least one leg assembly including a lift mechanism, the lift mechanism including:

a first member;

10

a second member moveable relative to the first member along a longitudinal axis, wherein the second member is configured to form a telescoping assembly;

a pulley assembly including:

a pulley bracket, the pulley bracket having a first end and extending along the longitudinal axis to a second end;

15

a first wheel rotatably attached near the first end of the pulley bracket;

24

a second wheel rotatably attached near the second end of the pulley bracket;

a first tension member extending around the first wheel, the first tension member attached to the second member and to the first member; and

a second tension member extending around the second wheel, the second tension member attached to the second member and to the first member; and

a counterbalance mechanism configured to counteract a force exerted on the lift mechanism, the counterbalance mechanism including:

a gas spring having a cylinder and a moveable piston slidably attached to the cylinder, wherein the cylinder is attached to one of the first member, and the pulley bracket, and wherein the moveable piston has a piston end attached to another one of the first member, and the pulley bracket.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 9,510,671 B2
APPLICATION NO. : 14/883010
DATED : December 6, 2016
INVENTOR(S) : Ergun et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Specification

In Column 5, Line 25, delete "FIG." and insert --FIGS.-- therefor

In Column 7, Line 28, delete "FIG." and insert --FIGS.-- therefor

In Column 10, Line 17, delete "FIG." and insert --FIGS.-- therefor

In Column 10, Line 19, delete "FIG." and insert --FIGS.-- therefor

In Column 10, Line 20, delete "FIG." and insert --FIGS.-- therefor

In Column 10, Line 20, delete "FIG." and insert --FIGS.-- therefor

In Column 13, Line 4, delete "FIG." and insert --FIGS.-- therefor

In Column 13, Line 8, delete "FIG." and insert --FIGS.-- therefor

In Column 16, Line 27, delete "928" and insert --929-- therefor

In Column 16, Line 53, delete "FIG." and insert --FIGS.-- therefor

In Column 19, Line 25, delete "97" and insert --977-- therefor

Signed and Sealed this
Tenth Day of August, 2021



Drew Hirshfeld
*Performing the Functions and Duties of the
Under Secretary of Commerce for Intellectual Property and
Director of the United States Patent and Trademark Office*