



US009514827B1

(12) **United States Patent**  
**Nam et al.**

(10) **Patent No.:** **US 9,514,827 B1**  
(45) **Date of Patent:** **Dec. 6, 2016**

(54) **MEMORY DEVICE, MEMORY SYSTEM AND METHOD OF OPERATING MEMORY DEVICE**

(71) Applicant: **SAMSUNG ELECTRONICS CO., LTD.**, Suwon-Si, Gyeonggi-Do (KR)

(72) Inventors: **Sang-Wan Nam**, Hwaseong-si (KR);  
**Doo-Hyun Kim**, Ansan-si (KR);  
**Dae-Seok Byeon**, Seongnam-si (KR);  
**Chi-Weon Yoon**, Seoul (KR)

(73) Assignee: **SAMSUNG ELECTRONICS CO., LTD.**, Suwon-Si, Gyeonggi-Do (KR)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/018,925**

(22) Filed: **Feb. 9, 2016**

(30) **Foreign Application Priority Data**

Jul. 2, 2015 (KR) ..... 10-2015-0094938

(51) **Int. Cl.**

**G11C 11/34** (2006.01)  
**G11C 16/04** (2006.01)  
**G11C 16/16** (2006.01)  
**G11C 16/34** (2006.01)  
**G11C 16/26** (2006.01)  
**G11C 16/06** (2006.01)  
**G11C 16/10** (2006.01)  
**G11C 16/12** (2006.01)

(52) **U.S. Cl.**

CPC ..... **G11C 16/16** (2013.01); **G11C 16/0483** (2013.01); **G11C 16/06** (2013.01); **G11C 16/10** (2013.01); **G11C 16/12** (2013.01); **G11C 16/26** (2013.01); **G11C 16/34** (2013.01); **G11C 16/344** (2013.01)

(58) **Field of Classification Search**

CPC ..... G11C 16/06; G11C 16/10; G11C 16/12;  
G11C 16/34; G11C 16/16; G11C 16/0483;  
G11C 16/344

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,239,557 B2 7/2007 Ha  
7,453,737 B2 11/2008 Ha  
7,663,934 B2 2/2010 Ha  
7,876,623 B2 1/2011 Ha  
8,488,402 B2 7/2013 Shim et al.  
8,902,661 B1\* 12/2014 Raghu ..... G11C 16/10  
365/185.05

(Continued)

FOREIGN PATENT DOCUMENTS

KR 1020080019713 3/2008  
KR 1020080113919 12/2008

(Continued)



*Primary Examiner* — Toan Le

(74) *Attorney, Agent, or Firm* — F. Chau & Associates, LLC

(57) **ABSTRACT**

A memory device is provided as follows. A memory cell region includes a plurality of blocks, each block including a plurality of NAND strings. A control logic divides the plurality of blocks into a plurality of block regions based on a smaller distance of a first distance with respect to a first edge of the memory cell region and a second distance with respect to a second edge of the memory cell region and controls an operation performed on the memory cell region using a plurality of bias sets of operation parameters for the operation. Each bias set is associated with one of the block regions.

**20 Claims, 81 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS

8,996,838 B1 3/2015 D'Abreu et al.  
2009/0307413 A1 12/2009 Chu  
2014/0063938 A1\* 3/2014 Oh ..... H01L 27/11524  
365/185.02  
2014/0160846 A1 6/2014 Lee et al.  
2014/0281769 A1\* 9/2014 Ohshima ..... G11C 29/42  
714/721  
2014/0351496 A1 11/2014 Avila et al.  
2014/0362642 A1 12/2014 Dong et al.  
2014/0369124 A1\* 12/2014 Moon ..... G11C 16/16  
365/185.11  
2015/0117099 A1\* 4/2015 Raghu ..... G11C 29/82  
365/185.03  
2015/0121156 A1 4/2015 Raghu et al.  
2015/0138890 A1\* 5/2015 Kang ..... G11C 16/0483  
365/185.11  
2015/0143025 A1 5/2015 Gorobets et al.  
2015/0325303 A1\* 11/2015 Hashimoto ..... G11C 16/16  
365/185.11  
2016/0141046 A1\* 5/2016 Khandelwal ..... G11C 16/3427  
365/185.02  
2016/0189801 A1\* 6/2016 Yamaguchi ..... G11C 29/76  
365/200

FOREIGN PATENT DOCUMENTS

KR 1020110111166 10/2011  
KR 1020120042415 5/2012  
KR 1020130097562 9/2013

\* cited by examiner

FIG. 1




FIG. 2




FIG. 3





FIG. 4







FIG. 5




FIG. 6






FIG. 7




FIG. 8




FIG. 9




FIG. 10A






FIG. 10B




FIG. 11




FIG. 12




FIG. 13A






FIG. 13B




FIG. 14A




FIG. 14B




FIG. 15







FIG. 16

REG\_TABLE1

BLOCK	BLOCK REGION
BLK1	REG1
BLK2	
BLK3	REG2
BLK4	
...	...
BLK5	REG_N
BLK6	
...	...
BLK7	REG2
BLK8	
BLK9	REG1
BLK10	

FIG. 17




FIG. 18

REG\_TABLE2

BLOCK	BLOCK REGION
BLK1	REG1
BLK2	
BLK3	REG2
BLK4	
...	...
BLK7	REG_M-1
BLK8	
BLK9	REG_M
BLK10	

FIG. 19






FIG. 20

REG\_TABLE3

BLOCK	BLOCK REGION
BLK1	REG1
BLK2	
BLK3	
BLK4	REG2
...	...
BLK5	REG_L
BLK6	
...	...
BLK7	REG3
BLK8	REG2
BLK9	
BLK10	




FIG. 21




FIG. 22A



110a''

FIG. 22B




FIG. 23

REG\_TABLE4

BLOCK	BLOCK REGION	BLOCK	BLOCK REGION
BLKb1	REG1	BLKu1	REG1
BLKb2		BLKu2	
BLKb3	REG2	BLKu3	REG2
BLKb4		BLKu4	
...	...	...	...
BLKb7	REG_M-1	BLKu7	REG_M-1
BLKb8		BLKu8	
BLKb9	REG_M	BLKu9	REG_M
BLKb10		BLKu10	

FIG. 24






FIG. 25

REG\_TABLE5

BLOCK	BLOCK REGION	BLOCK	BLOCK REGION
BLKb1	REG1	BLKu1	REG1
BLKb2		BLKu2	
BLKb3	REG2	BLKu3	
BLKb4		BLKu4	REG2
...	...	...	...
BLKb7	REG_M-1	BLKu7	REG_L-1
BLKb8		BLKu8	REG_L
BLKb9	REG_M	BLKu9	
BLKb10		BLKu10	

FIG. 26




FIG. 27




FIG. 28

REG\_TABLE6

	PROGRAM	ERASE	READ	READ RECOVERY
BLK1	REG1	REG1	REG1	REG1
BLK2				
BLK3	REG2	REG2	REG2	
BLK4				
BLK5	REG3		REG2	REG2
BLK6				
BLK7	REG4	REG2	REG3	REG3
BLK8				
BLK9	REG5	REG3	REG3	
BLK10				

FIG. 29

PAR\_TABLE1

	REG1	REG_N
WL_sel	Vpgm1	Vpgm2 (>Vpgm1)
WL_unsel	Vinhp1	Vinhp2 (>Vinhp1)
PGM VERIFY VOLTAGE	Vpvr1	Vpvr2 (> Vpvr1)
PGM DURATION	Tpgm1	Tpgm2 (> Tpgm1)
PGM DURATION TIME INCREMENT OF EACH LOOP	Tinc1	Tinc2 (> Tinc1)
PGM VOLTAGE INCREMENT OF EACH LOOP	Vinc1	Vinc2 (> Vinc1)
verify skip loop	Ls1	Ls2 (> Ls1)
MAXIMUM LOOP	Lm1	Lm2 (> Lm1)

↑  
OPERATION  
PARAMETERS

↑  
BIAS SET

FIG. 30A






FIG. 30B




FIG. 31A




FIG. 31B




FIG. 32




FIG. 33




FIG. 34






FIG. 35




FIG. 36

PAR\_TABLE2

	REG1	REG_N
BL	Float	Float
SSL	Float	Float
WL	Vwe1	Vwe2 (< Vwe1)
GSL	Float	Float
SUB	Vers1	Vers2 (> Vers1)
ERASE DURATION	Ters1	Ters2 (> Ters1)
ERASE VERIFY VOLTAGE	Vevrf1	Vevrf2(> Vevrf1)

FIG. 37




FIG. 38




FIG. 39




FIG. 40

PAR\_TABLE3

	REG1	REG_N
SSL	Vcc	Vcc
WL_sel	Vrd1	Vrd2 (> Vrd1)
WL_unsel	Vinhr1	Vinhr2 (> Vinhr1)
GSL	Vcc	Vcc
SUB	Vss	Vss



FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47

PAR\_TABLE4

	REFERENCE BIAS CONDITION		FIRST BIAS CONDITION		SECOND BIAS CONDITION	
	REG1 및 REG_N	REG_N	REG1	REG_N	REG1	REG_N
WL_sel	Vpgm	Vpgm2 (>Vpgm1)	Vpgm1	Vpgm2 (>Vpgm1)	Vpgm1' (< Vpgm1)	Vpgm2
WL_unsel	Vinhp	Vinhp2 (>Vinhp1)	Vinhp1	Vinhp2 (>Vinhp1)	Vinhp1' (< Vinhp1)	Vinhp2
PGM VERIFY VOLTAGE	Vpvr1	Vpvr12 (> Vpvr1)	Vpvr1	Vpvr12 (> Vpvr1)	Vpvr1' (>Vpvr1)	Vpvr12
PGM DURATION	Tpgm	Tpgm2 (> Tpgm1)	Tpgm1	Tpgm2 (> Tpgm1)	Tpgm1' (< Tpgm1)	Tpgm2
PGM DURATION TIME INCREMENT OF EACH LOOP	Tinc	Tinc2 (> Tinc1)	Tinc1	Tinc2 (> Tinc1)	Tinc1' (< Tinc1)	Tinc2
PGM VOLTAGE INCREMENT OF EACH LOOP	Vinc	Vinc2 (> Vinc1)	Vinc1	Vinc2 (> Vinc1)	Vinc1' (< Vinc1)	Vinc2
verify skip loop	Ls	Ls2 (> Ls1)	Ls1	Ls2 (> Ls1)	Ls1' ( $\leq$ Ls1)	Ls2
MAXIMUM LOOP	Lm	Lm2 (> Lm1)	Lm1	Lm2 (> Lm1)	Lm1' ( $\leq$ Lm1)	Lm2



FIG. 48

PAR\_TABLE5

	REFERENCE BIAS CONDITION		FIRST BIAS CONDITION		SECOND BIAS CONDITION	
	REG1	REG_N	REG1	REG_N	REG1	REG_N
BL	Float		Float	Float	Float	Float
SSL	Float		Float	Float	Float	Float
WL	Vwe		Vwe1	Vwe2 (< Vwe1)	Vwe1' (< Vwe1)	Vwe2
GSL	Float		Float	Float	Float	Float
SUB	Vers		Vers1	Vers2 (> Vers1)	Vers1' (> Vers1)	Vers2
ERASE DURATION	Ters		Ters1	Ters2 (> Ters1)	Ters1' (> Ters1)	Ters2
ERASE VERIFY VOLTAGE	Vevrf		Vevrf1	Vevrf2 (>Vevrf1)	Vevrf1' (>Vevrf1)	Vevrf2

FIG. 49

PAR\_TABLE6

	REFERENCE BIAS CONDITION		FIRST BIAS CONDITION		SECOND BIAS CONDITION	
	REG1	REG_N	REG1	REG_N	REG1	REG_N
SSL	Vcc	Vcc	Vcc	Vcc	Vcc	Vcc
WL_sel	Vrd	Vrd	Vrd1	Vrd2 (> Vrd1)	Vrd1' (> Vrd1)	Vrd2
WL_unsel	Vinhr	Vinhr	Vinhr1	Vinhr2 (> Vinhr1)	Vinhr1' (> Vinhr1)	Vinhr2
GSL	Vcc	Vcc	Vcc	Vcc	Vcc	Vcc
SUB	Vss	Vss	Vss	Vss	Vss	Vss

FIG. 50




FIG. 51




FIG. 52




FIG. 53A






FIG. 53B






FIG. 54




FIG. 55




FIG. 56




FIG. 57




FIG. 58




FIG. 59

ALG\_TABLE1

	REG1	REG_N
PRE PROGRAM	0	X
POST PROGRAM	0	X
SUB-BLOCK	X	0
COUNT PULSE PROGRAM	0	X
SOFT PROGRAM	0	X
OFF STRING SEARCH	0	X
RETENTION PDT	0	X
ENDURANCE PDT	X	0



FIG. 60






FIG. 61




FIG. 62

ALG\_TABLE2

	FIRST ALGORITHM TABLE		SECOND ALGORITHM TABLE	
	REG1	REG_N	REG1	REG_N
PRE PROGRAM	0	X	0	0
POST PROGRAM	0	X	0	0
SUB-BLOCK	X	0	X	0
COUNT PULSE PROGRAM	0	X	0	0
SOFT PROGRAM	0	X	0	0
OFF STRING SEARCH	0	X	0	0
RETENTION PDT	0	X	0	X
ENDURANCE PDT	X	0	X	0

FIG. 63




FIG. 64




FIG. 65




FIG. 66





FIG. 67








FIG. 69




FIG. 70




FIG. 71




FIG. 72




FIG. 73





FIG. 74





# MEMORY DEVICE, MEMORY SYSTEM AND METHOD OF OPERATING MEMORY DEVICE

## CROSS-REFERENCE TO RELATED APPLICATION

This application claims priority under 35 U.S.C. 119 to Korean Patent Application No. 10-2015-0094938, filed on Jul. 2, 2015, in the Korean Intellectual Property Office, the disclosure of which is incorporated by reference herein in its entirety.

## TECHNICAL FIELD

The present inventive concept relates to a memory device and a memory system including the memory device.

## DISCUSSION OF RELATED ART

A memory device is used to store data, and is classified as a volatile memory device and a non-volatile memory device. A flash memory device is an example of the non-volatile memory device and may be used in portable phones, digital cameras, portable digital assistants (PDA), mobile computing devices, fixed computing devices, and other devices.

## SUMMARY

According to an exemplary embodiment of the present inventive concept, a memory device is provided as follows. A memory cell region includes a plurality of blocks, each block including a plurality of NAND strings. A control logic divides the plurality of blocks into a plurality of block regions based on a smaller distance of a first distance with respect to a first edge of the memory cell region and a second distance with respect to a second edge of the memory cell region and controls an operation performed on the memory cell region using a plurality of bias sets of operation parameters for the operation. Each bias set is associated with one of the block regions.

According to an exemplary embodiment of the present inventive concept, a memory system is provided as follows. A memory device includes a memory cell region including a plurality of blocks, each block including a plurality of NAND strings. A memory controller divides the plurality of blocks into a plurality of block regions based on a distance with respect to a smaller distance with respect to a first edge and a second edge of the memory cell region, determines a plurality of bias sets of operation parameters, and transmits the operation parameters to the memory device. Each bias set is associated with one of the block regions.

A method of operating a memory device is provided as follows. The memory device has a memory cell region including a plurality of blocks, each block including a plurality of channel holes in which a plurality of NAND strings are formed. The blocks are set to a plurality of block regions. A plurality of bias sets is applied to the memory cell region to perform an operation. A first bias set of the bias sets is applied to a first block region of the block regions, and a second bias set of the bias sets is applied to a second block region of the block regions. The first block region includes at least one block positioned within a first distance from an edge of the memory cell region. The second block region includes at least one block positioned between the first distance and a second distance from the edge of the memory

cell region, the second distance being greater than the first distance. The second bias set is different from the first bias set.

## BRIEF DESCRIPTION OF DRAWINGS

These and other features of the inventive concept will become more apparent by describing in detail exemplary embodiments thereof with reference to the accompanying drawings of which:

FIG. 1 is a schematic block diagram illustrating a memory system according to an exemplary embodiment of the present inventive concept;

FIG. 2 is a detailed block diagram illustrating a memory device of FIG. 1;

FIG. 3 illustrates an example of the memory device of FIG. 2;

FIG. 4 illustrates an example of the memory device of FIG. 2;

FIG. 5 is a perspective view of a first block, which is one of blocks of FIG. 3, according to an exemplary embodiment;

FIG. 6 is a circuit diagram illustrating an equivalent circuit of the first block of FIG. 5;

FIG. 7 illustrates an example of a cell region according to an exemplary embodiment of the present inventive concept;

FIG. 8 illustrates an example of a cell region according to an exemplary embodiment of the present inventive concept;

FIG. 9 illustrates an example of a cell region according to an exemplary embodiment of the present inventive concept;

FIGS. 10A and 10B illustrate cross-sections of strings respectively included in first and second blocks of FIG. 9;

FIG. 11 is a graph showing a result of performing a program operation and an erase operation on the first and second blocks of FIG. 9;

FIG. 12 is a graph showing a first distribution of the first and second blocks of FIG. 9 according to a threshold voltage;

FIG. 13A illustrates a reference bias condition according to respective layers regarding a program operation of a memory device;

FIG. 13B illustrates a modified bias condition according to respective layers regarding a program operation of a memory device;

FIG. 14A illustrates an example of a bias condition of respective blocks regarding a program operation of a memory device, according to an exemplary embodiment of the present inventive concept;

FIG. 14B illustrates an example of a bias condition of respective blocks regarding a program operation of a memory device, according to an exemplary embodiment of the present inventive concept;

FIG. 15 illustrates a memory device according to an exemplary embodiment of the present inventive concept;

FIG. 16 is a table showing an example of block region information stored in a block region storing unit of FIG. 15;

FIG. 17 illustrates a first modified example of the memory device of FIG. 15;

FIG. 17 is a flowchart of a method of operating a memory device according to an exemplary embodiment of the present inventive concept;

FIG. 18 is a table showing an example of block region information stored in a block region storing unit of FIG. 17;

FIG. 19 illustrates a second modified example of the memory device of FIG. 15;

FIG. 20 is a table showing an example of block region information stored in a block region storing unit of FIG. 19;



FIG. 21 illustrates a third modified example of the memory device of FIG. 15;

FIGS. 22A and 22B are circuit diagrams illustrating examples of a memory cell array of FIG. 21;

FIG. 23 is a table showing an example of block region information stored in a block region storing unit of FIG. 21;

FIG. 24 illustrates a modified example of the memory device of FIG. 21;

FIG. 25 is a table showing an example of block region information stored in a block region storing unit of FIG. 24;

FIG. 26 is a flowchart of a method of operating a memory device according to an exemplary embodiment of the present inventive concept;

FIG. 27 is a flowchart of a method of operating a memory device according to an exemplary embodiment of the present inventive concept;

FIG. 28 is a table showing an example of block region information stored in a block region storing unit according to an exemplary embodiment of the present inventive concept;

FIG. 29 is a table showing bias conditions of a program operation according to an exemplary embodiment of the present inventive concept;

FIG. 30A is a graph showing program start voltage levels of respective blocks according to an exemplary embodiment of the present inventive concept;

FIG. 30B is a graph showing program start voltages with respect to different block regions according to an exemplary embodiment of the present inventive concept;

FIG. 31A is a graph showing program durations of respective blocks according to an exemplary embodiment of the present inventive concept;

FIG. 31B is a graph showing program durations with respect to different block regions according to an exemplary embodiment of the present inventive concept;

FIG. 32 is a graph showing program inhibit voltages of respective blocks, according to an exemplary embodiment of the present inventive concept;

FIG. 33 is a graph showing programming verify voltages of respective blocks according to an exemplary embodiment of the present inventive concept;

FIG. 34 is a graph showing program time increments according to loops of respective blocks according to an exemplary embodiment of the present inventive concept;

FIG. 35 is a graph showing verify skip loops of respective blocks according to an exemplary embodiment of the present inventive concept;

FIG. 36 is a table showing bias conditions of an erase operation according to an exemplary embodiment of the present inventive concept;

FIG. 37 is a graph showing erase voltages of respective blocks according to an exemplary embodiment of the present inventive concept;

FIG. 38 is a graph showing word line erase voltages of respective blocks according to an exemplary embodiment of the present inventive concept;

FIG. 39 is a graph showing erase verify voltages of respective blocks according to an exemplary embodiment of the present inventive concept;

FIG. 40 is a table showing bias conditions of a read operation according to an exemplary embodiment of the present inventive concept;

FIG. 41 is a graph showing read determination voltages of respective blocks according to an exemplary embodiment of the present inventive concept;

FIG. 42 is a graph showing reading inhibit voltages of respective blocks according to an exemplary embodiment of the present inventive concept;

FIG. 43 illustrates a memory device according to an exemplary embodiment of the present inventive concept;

FIG. 44 is a graph showing a second distribution of the first and second blocks of FIG. 9 according to a threshold voltage;

FIG. 45 is a flowchart of an example of a method of operating a memory device according to an exemplary embodiment of the present inventive concept;

FIG. 46 is a flowchart of an example of a method of operating a memory device according to an exemplary embodiment of the present inventive concept;

FIG. 47 is a table showing bias conditions of a program operation according to an exemplary embodiment of the present inventive concept;

FIG. 48 is a table showing bias conditions of an erase operation according to an exemplary embodiment of the present inventive concept;

FIG. 49 is a table showing bias conditions of an erase operation according to an exemplary embodiment of the present inventive concept;

FIG. 50 is a flowchart of an example of a method of operating a memory device according to an exemplary embodiment of the present inventive concept;

FIG. 51 is a flowchart of an example of a method of operating a memory device according to an exemplary embodiment of the present inventive concept;

FIG. 52 illustrates a memory device according to an exemplary embodiment of the present inventive concept;

FIG. 53A is a graph showing a distribution according to a threshold voltage after programming of a memory device is completed;

FIG. 53B is a graph showing a distribution according to a threshold voltage after a predetermined duration passes after programming of the memory device having the distribution of FIG. 53A is completed;

FIG. 54 is a flowchart of an example of a method of operating a memory device according to an exemplary embodiment of the present inventive concept;

FIG. 55 is a flowchart of an example of a method of operating a memory device according to an exemplary embodiment of the present inventive concept;

FIG. 56 is a flowchart of an example of a method of operating a memory device according to an exemplary embodiment of the present inventive concept;

FIG. 57 illustrates a memory device according to an exemplary embodiment of the present inventive concept;

FIG. 58 illustrates a memory device according to an exemplary embodiment of the present inventive concept;

FIG. 59 illustrates an example of a table stored in an algorithm table storing unit of FIG. 58;

FIG. 60 is a flowchart of a method of operating a memory device according to an exemplary embodiment of the present inventive concept;

FIG. 61 is a flowchart of a method of operating a memory device according to an exemplary embodiment of the present inventive concept;

FIG. 62 illustrates an example of a table stored in the algorithm table storing unit of FIG. 58;

FIG. 63 is a flowchart of a method of operating a memory device according to an exemplary embodiment of the present inventive concept;

FIG. 64 is a schematic block diagram illustrating a memory system according to an exemplary embodiment of the present inventive concept;



## 5

FIG. 65 is a flowchart of operations of a memory controller and a memory device according to an exemplary embodiment of the present inventive concept;

FIG. 66 is a flowchart of operations of a memory controller and a memory device according to an exemplary embodiment of the present inventive concept;

FIG. 67 is a block diagram illustrating a modified example of a memory system according to an exemplary embodiment of the present inventive concept;

FIG. 68 is a flowchart of operations of a memory controller, a memory device, and a non-volatile memory according to an exemplary embodiment of the present inventive concept;

FIG. 69 is a schematic block diagram illustrating a memory system according to an exemplary embodiment of the present inventive concept;

FIG. 70 is a block diagram illustrating a modified example of a memory system according to an exemplary embodiment of the present inventive concept;

FIG. 71 is a block diagram illustrating a memory card system to which a memory device according to exemplary embodiments of the present inventive concept is applied;

FIG. 72 is a block diagram illustrating a computing system including a memory device according to exemplary embodiments of the present inventive concept;

FIG. 73 is a block diagram illustrating a solid state disk (SSD) system to which a memory device according to exemplary embodiments of the present inventive concept is applied; and

FIG. 74 is a block diagram illustrating a Universal Flash Storage (UFS) system to which a memory device according to exemplary embodiments of the present inventive concept is applied.

#### DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

Exemplary embodiments of the inventive concept will be described below in detail with reference to the accompanying drawings. However, the inventive concept may be embodied in different forms and should not be construed as limited to the embodiments set forth herein. In the drawings, the thickness of layers and regions may be exaggerated for clarity. It will also be understood that when an element is referred to as being “on” another element or substrate, it may be directly on the other element or substrate, or intervening layers may also be present. It will also be understood that when an element is referred to as being “coupled to” or “connected to” another element, it may be directly coupled to or connected to the other element, or intervening elements may also be present. Like reference numerals may refer to the like elements throughout the specification and drawings.

FIG. 1 is a schematic block diagram of a memory system 10 according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 1, the memory system 10 may include a memory device 100 and a memory controller 200, and the memory device 100 may include a memory cell array 110 and a control logic 120.

The memory cell array 110 may include a plurality of memory cells, which may be, for example, flash memory cells. Hereinafter, for the convenience of description, it is assumed that the memory cells are NAND flash memory cells. However, the present inventive concept is not limited thereto. For example, the plurality of memory cells may be resistive memory cells such as a resistive RAM (RRAM), a phase change RAM (PRAM) or a magnetic RAM (MRAM).

## 6

The memory cell array 100 may be a three-dimensional (3D) memory array. The 3D memory array is monolithically formed in one or more physical levels of arrays of memory cells having an active area disposed above a silicon substrate and circuitry associated with the operation of those memory cells, whether such associated circuitry is above or within such substrate. The term “monolithic” means that layers of each level of the array are directly deposited on the layers of each underlying level of the array.

The 3D memory array includes vertical NAND strings that are vertically oriented such that at least one memory cell is located over another memory cell. In an exemplary embodiment, the memory cell may include a charge trap layer.

The following patent documents, which are hereby incorporated by reference, describe suitable configurations for three-dimensional memory arrays, in which the three-dimensional memory array is configured as a plurality of levels, with word lines and/or bit lines shared between levels: U.S. Pat. Nos. 7,679,133; 8,553,466; 8,654,587; 8,559,235; and US Pat. Pub. No. 2011/0233648.

The memory cell array 110 may include at least one cell region, and each cell region may include a plurality of blocks. Each block may include a plurality of NAND strings, and each NAND string may include a plurality of memory cells that are vertically stacked on a substrate. In an exemplary embodiment, the plurality of blocks of each cell region may be divided into at least two block regions based on a distance of the blocks with respect to edges of the cell region.

Here, a cell region may be referred to as a MAT or a bank. A cell region may be a unit in terms of the manufacturing process. For example, a cell region may be defined as a well region formed in a substrate. In this case, different cell regions may be formed in different well regions. In an exemplary embodiment, at least one cell regions may be formed in the same well region. The cell region may be referred to as a “memory cell region”.

The control logic 120 may control an operation performed on each block region of the memory cell array 110 using bias conditions (which may be referred to as bias sets) respectively corresponding to the at least two block regions. The control logic 120 may control an operation performed on the memory cell array for each block region by using block region information and parameter information. Block region information refers to information about a plurality of block regions each including at least one block. The block region information may be information about block regions corresponding to a plurality of blocks disposed in a cell region. Edges of a cell region may be parallel to an extension direction of a word line. Parameter information may be information about operation parameters indicating bias conditions according to respective block regions.

In response to a write/read request from a host, the memory controller 200 may read data stored in the memory device 100 or may control the memory device 100 to write data to the memory device 100. For example, the memory controller 200 may provide an address ADDR, a command CMD, and a control signal CTRL to the memory device 100 and thus may control a program (or write) operation, a read operation, and an erase operation with respect to the memory device 100. Also, write-target data DATA and read data DATA may be transmitted or received between the memory controller 200 and the memory device 100.

Although not illustrated, the memory controller 200 may include a Random Access Memory (RAM), a processing unit, a host interface, and a memory interface. The RAM



may be used as an operation memory of the processing unit. The processing unit may control operations of the memory controller **200**. The host interface may include a protocol for exchanging data between the host and the memory controller **200**. For example, the memory controller **200** may communicate with an external source (i.e., the host) by using at least one of various interface protocols including USB, MMC, PCI-E, ATA (Advanced Technology Attachment), Serial-ATA, Parallel-ATA, SCSI, ESDI, and Integrated Drive Electronics (IDE).

FIG. **2** is a detailed block diagram illustrating the memory device **100** of FIG. **1**.

Referring to FIG. **2**, the memory device **100** may include a memory cell array **110**, a control logic **120**, a voltage generator **130**, a row decoder **140**, and a page buffer **150**. Although not illustrated, the memory device **100** may further include a data input/output circuit or an input/output interface.

The memory cell array **110** may include a plurality of memory cells, and may be connected to word lines WL, string selection lines SSL, ground selection lines GSL, and bit lines BL. For example, the memory cell array **110** may be connected to the row decoder **140** via the word lines WL, the string selection lines SSL, and the ground selection lines GSL, and may be connected to the page buffer **150** via the bit lines BL.

The memory cell array **110** may include at least one of a single-level cell block including single-level cells, a multi-level cell block including multi-level cells, and a triple-level cell block including triple level cells. In an exemplary embodiment, all blocks of the memory cell array **110** may be the same level cell blocks. For example, all blocks of the memory cell array **110** may be multi-level cell blocks. In an exemplary embodiment, the blocks may be different level cell blocks. For example, some of the blocks of the memory cell array **110** may be single-level cell blocks, and the other blocks may be multi-level cell blocks or triple-level cell blocks.

The control logic **120** may output various control signals to write data to the memory cell array **110** or read data from the memory cell array **110** based on a command CMD, an address ADDR, and a control signal CTRL received from the memory controller **200**. Accordingly, the control logic **120** may control various operations in the memory device **100** overall.

Various control signals generated from the control logic **120** may be provided to the voltage generator **130**, the row decoder **140**, and the page buffer **150**. For example, the control logic **120** may provide a voltage control signal CTRL\_vol to the voltage generator **130**, may provide a row address X-ADDR to the row decoder **140**, and may provide a column address Y-ADDR to the page buffer **150**. However, the present inventive concept is not limited thereto, and the control logic **120** may further provide other control signals to the voltage generator **130**, the row decoder **140**, and the page buffer **150**.

The voltage generator **130** may generate various types of voltages for performing program, read, and erase operations on the memory cell array **110** based on a voltage control signal CTRL\_vol. For example, the voltage generator **130** may generate a word line driving voltage for driving word lines WL, for example, a program voltage (or a write voltage), a read voltage, a program inhibit voltage, an erase verify voltage, or a program verify voltage. Also, the voltage generator **130** may further generate a string selection line driving voltage for driving string selection lines SSL and a ground selection line driving voltage for driving ground

selection lines GSL. Also, the voltage generator **130** may further generate an erase voltage to be provided to the memory cell array **110**.

The row decoder **140** may select some word lines WL from among the word lines WL in response to the row address X-ADDR received from the control logic **120**. For example, during a read operation, the row decoder **140** may apply a read voltage to the selected word line and apply a read inhibit voltage to unselected word lines. Also, during a program operation, the row decoder **140** may apply a program voltage to the selected word line and apply a program inhibit voltage to the unselected word lines. Furthermore, the row decoder **140** may select some string selection lines SSL from among the string selection lines SSL or select some ground selection lines GSL from among the ground selection lines GSL in response to the row address X-ADDR received from the control logic **120**.

The page buffer **150** may be connected to the memory cell array **110** via the bit lines BL, and select some bit lines among the bit lines BL in response to the column address Y-ADDR received from the control logic **120**. For example, during the read operation, the page buffer **150** may operate as a sense amplifier and sense data DATA stored in the memory cell array **110**. Meanwhile, during a program operation, the page buffer **150** may operate as a write driver and input desired data DATA in the memory cell array **110**.

FIG. **3** illustrates a memory device **100A** which is an exemplary embodiment of the memory device **100** of FIG. **2** according to the present inventive concept.

Referring to FIG. **3**, the memory device **100A** may include a memory cell array **110a**, a control logic **120**, a row decoder **140a**, and a page buffer **150a**. The memory cell array **110a** may include a cell region CR1, and the cell region CR1 may be connected to the row decoder **140a** and the page buffer **150a**.

The cell region CR1 may include a plurality of blocks BLK1 through BLKz, and each block may have a three-dimensional structure (or a vertical structure). For example, each block includes structures extending in first through third directions. For example, each block includes a plurality of strings or NAND strings extending in the third direction (e.g., a Z direction). The plurality of strings may be spaced apart from one another by a predetermined distance in the first and second directions (e.g., an X direction and a Y direction).

The blocks BLK1 through BLKz may be selected by the row decoder **140a**. For example, the row decoder **140a** may select a block corresponding to a block address from among the blocks BLK1 through BLKz. Each block is connected to a plurality of bit lines BL, a plurality of string selection lines SSL, a plurality of word lines WL, a ground selection line GSL, and a common source line CSL. The blocks BLK1 through BLKz will be described in detail later with reference to FIG. **5**.

FIG. **4** illustrates an exemplary memory device **100B** of the memory device **100** of FIG. **2** according to the present inventive concept.

Referring to FIG. **4**, the memory device **100B** may include a memory cell array **110b**, a control logic **120**, first through fourth row decoders **140a** through **140d**, and first through fourth page buffers **150a** and **150d**. The memory cell array **110b** may include four cell regions CR1 through CR4. Each cell region has substantially the same structure as the cell region CR1 of FIG. **3**, and detailed descriptions provided with reference to FIG. **3** may also be applied to the present exemplary embodiment, and thus repeated description will be omitted.



The first cell region CR1 may be connected to the first row decoder 140a and the first page buffer 150a. The second cell region CR2 may be connected to the second row decoder 140b and the second page buffer 150b. The third cell region CR3 may be connected to the third row decoder 140c and the third page buffer 150c. The fourth cell region CR4 may be connected to the fourth row decoder 140d and the fourth page buffer 150d.

The first through fourth row decoders 140a through 140d may operate independently of each other, and the first through fourth page buffers 150a through 150d may also operate independently of each other. Thus, operations for the first through fourth cell regions CR1 through CR4 may be performed independently of each other. Accordingly, a cell region may be an independently operable unit, and a program, read, or erase operation may be simultaneously performed on at least one cell regions.

FIG. 5 is a perspective view of the first block BLK1 in FIG. 3, according to an exemplary embodiment.

Referring to FIG. 5, the first block BLK1 may be formed in a vertical direction to a substrate SUB. Although FIG. 5 illustrates a case in which the first block BLK1 includes two selection lines GSL and SSL, eight word lines WL1 to WL8, and three bit lines BL1 to BL3, the first block BLK1 is not limited thereto and may include more or fewer lines.

The substrate SUB may be doped with impurities having a first conductivity type (e.g., p type) and extend in a first direction on the substrate SUB, and a common source line CSL doped with impurities of a second conductivity type (e.g., n type) may be provided. A plurality of insulating layers IL may be provided on a region of the substrate SUB between two adjacent common source lines CSL. The plurality of insulating layers IL may extend in the first direction (e.g., X direction) and be sequentially disposed in a third direction (e.g., Z direction). The plurality of insulating layers IL may be spaced apart from one another in a predetermined distance in the third direction. For example, the plurality of insulating layers IL may include an insulating material such as silicon oxide.

A plurality of pillars P may be provided on a region of the substrate SUB between two adjacent common source lines CSL. The plurality of pillars P may be sequentially arranged in the first direction and penetrate the plurality of insulating layers IL in the third direction. For example, the plurality of pillars P may penetrate the plurality of insulating layers IL and contact the substrate SUB. For example, a surface layer S of each of the pillars P may include silicon and be doped with impurities having a first conductivity type. The surface layer S may function as a channel region. Meanwhile, an internal layer I of each of the pillars P may include an insulating material such as silicon oxide, or an air gap.

A charge storage layer CS may be provided on a region between two adjacent common source lines CSL along exposed surfaces of the insulating layers IL, the pillars P, and the substrate SUB. For example, the charge storage layer CS may have an oxide-nitride-oxide (ONO) structure. Also, a gate electrode GE may be provided on an exposed surface of the charge storage layer CS in the region between the two adjacent common source lines CSL.

Drains or drain contacts DR may be respectively provided on the plurality of pillars P. For example, the drains or drain contacts DR may include a silicon material doped with impurities having a second conductivity type. Bit lines BL may be provided on the drains DR. The bit lines BL may extend in a second direction (e.g., Y direction) and be spaced apart from one another by a predetermined distance in the first direction.

FIG. 6 is a circuit diagram of the first block BLK1 of FIG. 5 according to an exemplary embodiment.

Referring to FIG. 6, the first block BLK1 may be a vertical NAND flash memory, and each of the blocks BLK1 to BLKz shown in FIG. 3 may be embodied as in FIG. 6. The first block BLK1 may include a plurality of NAND strings NS11 to NS33, a plurality of word lines WL1 to WL8, a plurality of bit lines BL1 to BL3, a plurality of ground selection lines GSL1 to GSL3, a plurality of string selection lines SSL1 to SSL3, and a common source line CSL. The present inventive concept is not limited thereto. For example, the number of NAND strings, the number of word lines, the number of bit lines, the number of ground selection lines, and the number of string selection lines may be variously changed according to an exemplary embodiment.

NAND strings NS11, NS21, and NS31 may be provided between a first bit line BL1 and the common source line CSL, NAND strings NS12, NS22, and NS32 may be provided between a second bit line BL2 and the common source line CSL, and NAND strings NS13, NS23, and NS33 may be provided between a third bit line BL3 and the common source line CSL. Each of the NAND strings (e.g., NS11) may include a string selection transistor SST, a plurality of memory cells MC1 to MC8, and a ground selection transistor GST, which are connected in series. Hereinafter, the NAND string will be referred to as a string for the convenience of description.

Strings that are connected in common to one bit line may constitute one column. For example, the strings NS11, NS21, and NS31 commonly connected to the first bit line BL1 may correspond to a first column, and the strings NS12, NS22, and NS32 commonly connected to the second bit line BL2 may correspond to a second column. The strings NS13, NS23, and NS33 commonly connected to the third bit line BL3 may correspond to a third column.

Strings connected to one string selection line may constitute one row. For example, the strings NS11, NS12, and NS13 connected to a first string selection line SSL1 may correspond to a first row, and the strings NS21, NS22, and NS23 connected to a second string selection line SSL2 may correspond to a second row. The strings NS31, NS32, and NS33 connected to a third string selection line SSL3 may correspond to a third row.

The string selection transistor SST may be connected to the string selection lines SSL1 to SSL3. The plurality of memory cells MC1 to MC8 may be respectively connected to the word lines WL1 to WL8. The ground selection transistor GST may be connected to the ground selection line GSL. The string selection transistor SST may be connected to the corresponding bit line BL, and the ground selection transistor GST may be connected to the common source line CSL.

Word lines (e.g., WL1) disposed at the same level may be commonly connected, and the string selection lines SSL1 to SSL3 may be separated from one another. The ground selection lines GSL1 to GSL3 may be separated from one another. For example, when memory cells that are connected to the first word line WL1 and belong to the strings NS11, NS12, and NS13 are programmed, the first word line WL1 and the first string selection line SSL1 may be selected.

FIG. 7 illustrates a cell region CR1\_A according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 7, the cell region CR1\_A may be defined by a well region formed on a substrate (for example, the substrate SUB of FIG. 5) and may be defined by four edges. Hereinafter, edges that are in a first direction (e.g., X direction) from among the four edges will be referred to as



## 11

first and second edges EDG1 and EDG2. The first and second edges EDG1 and EDG2 may be parallel to an extension direction of the word lines WL1 and WL8. Also, the first and second edges may be a boundary of a P well region including the cell region CR1\_A on the substrate.

The cell region CR1\_A may include a plurality of gate electrodes GE that are vertically stacked on the substrate, and the plurality of gate conductive layers may include a ground selection line GSL, a plurality of word lines WL1 and WL8, and a string selection line SSL. An insulation layer may be disposed under or on each of the gate electrodes GE. Meanwhile, the word lines WL1 and WL8, the string selection line SSL, and the ground selection line GSL may be separated by a word line cut WLC.

A surface of the gate electrodes GE may be reduced away from the substrate, and thus, the gate electrodes GE may be stacked in a step manner. A step-shaped pad structure as above may be referred to as a word line pad WLP. A contact may be formed on the word line pad WLP, and as the word line pad WLP is connected to a wiring line via the contact, the word line pad WLP may receive an electric signal from a peripheral circuit. In an exemplary embodiment, the cell region CR1\_A may include the word line pad WLP.

In an exemplary embodiment, the word lines WL1 and WL8 may extend in the first direction, and accordingly, a length of the word lines WL1 and WL8 in the first direction may be longer than a length thereof in the second direction (e.g., Y direction). Likewise, a length of each of the blocks BLK1 through BLKz in the first direction may be longer than a length thereof in the second direction. An exemplary embodiment in which a length of the cell region CR1\_A in the first direction is longer than a length thereof in the second direction will be described below. However, the present inventive concept is not limited thereto, and the length of the cell region CR1\_A in the second direction may be varied based on the number of blocks needed according to memory capacity. Thus, in an exemplary embodiment, the length of the cell region CR1\_A in the first direction may be shorter than the length thereof in the second direction.

FIG. 8 illustrates a cell region CR1\_B which is an example of a cell region according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 8, the cell region CR1\_B may be defined by a well region formed on a substrate (for example, the substrate SUB of FIG. 5) and may be defined by four edges. Unlike the cell region CR1\_A of FIG. 7, the cell region CR1\_B need not include a word line pad. The present inventive concept is not limited to those illustrated in FIG. 7 or FIG. 8. For example, a cell region may be defined in various manners.

FIG. 9 illustrates a cell region CR1\_C according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 9, the cell region CR1\_C further includes a plurality of channel holes CH compared to the cell regions CR1\_A illustrated in FIG. 7 or the CR1\_B illustrated in FIG. 8. Pillars (e.g., the pillars P of FIG. 5) may be respectively formed in the plurality of channel holes. The gate electrodes GE illustrated in FIGS. 7 and 8 are not illustrated for the convenience of description.

In the present exemplary embodiment, a channel hole size, for example, a channel hole diameter, may be varied according to positions within the cell region CR1\_C. For example, channel holes CH adjacent to the first and second edges EDG1 and EDG2 have a low peripheral density, and thus may have a different diameter from those of other channel holes CH. Hereinafter, a channel hole diameter will

## 12

be described as an example of a channel hole size. However, the channel hole size is not limited to the channel hole diameter.

In an exemplary embodiment, a diameter of channel holes CH in a center region of the cell region CR1\_C may be greater than a diameter of the channel holes CH adjacent to the first and second edges EDG1 and EDG2. An exemplary embodiment in which the diameter of the channel holes CH in the center region of the cell region CR1\_C is greater than the diameter of the channel holes CH adjacent to the first and second edges EDG1 and EDG2 will be described below.

However, the present inventive concept is not limited thereto. For example, the diameter of the channel holes CH in the center region of the cell region CR1\_C may be smaller than the diameter of the channel holes CH adjacent to the first and second edges EDG1 and EDG2. In this case, operation parameter conditions which will be described below may be reversely applied to compensate for a difference in terms of operating characteristics of a memory device due to a difference in channel hole sizes.

A memory device may be manufactured by performing a process such as a molding process and an etching process. Channel holes CH may be formed by performing an etching process on the gate electrodes GE and the insulation layers illustrated in FIG. 7 or FIG. 8 to thereby remove a portion of each of the gate electrode layers GE and the insulation layers. For example, the channel holes CH may be formed using a plasma etching process. Here, a center portion of the cell region CR1\_C may be etched more than an edge portion thereof, and thus, a diameter D1 of the channel holes CH in the edge portion of the cell region CR1\_C may be smaller than a diameter D2 of the channel holes CH in the center portion of the cell region CR1\_C.

In the present exemplary embodiment, a first block BLKa may be adjacent to the second edge EDG2, and may be spaced apart from the second edge EDG2 by a first distance d1. A second block BLKb may not be adjacent to the first and second edges EDG1 and EDG2, and be in a center of the cell region CR1\_C, and may be spaced apart from the second edge EDG2 by a second distance d2. The second distance d2 may be greater than the first distance d1. A first diameter D1 of a first channel hole CHa included in the first block BLKa may be smaller than a second diameter D2 of a second channel hole CHb included in the second block BLKb.

FIGS. 10A and 10B illustrate cross-sections of strings of the first and the second blocks BLKa and BLKb of FIG. 9, respectively.

Referring to FIG. 10A, a pillar including a surface layer S and an internal layer I may be formed in the first channel hole CHa included in the first block BLKa, and a charge storage layer CS may be formed around the first channel hole CHa, and the charge storage layer CS may have an (oxide-nitride-oxide) ONO structure.

Referring to FIG. 10A, a pillar including a surface layer S and an internal layer I may be formed in the second channel hole CHb included in the second block BLKb, and a charge storage layer CS may be formed around the second channel hole CHb, and the charge storage layer CS may have an ONO structure. In an exemplary embodiment, a thickness of the charge storage layer CS included in the second block BLKb may be different from a thickness of the charge storage layer CS included in the first block BLKa.

Characteristics of memory cells may vary due to the difference in the channel hole diameters. For example, in a 3D memory device having a gate all around structure in which a gate electrode is disposed around a circumference of



a channel hole, if a channel hole diameter is reduced, the magnitude of an electric field formed between a gate electrode (e.g., the gate electrode GE of FIG. 5) and a channel region S is increased. Thus, program and erase speeds of a memory cell having a relatively small channel hole diameter like the first channel hole CHa may be higher than those of a memory cell having a relatively large channel hole diameter like the second channel hole CHb.

The difference in operating characteristics of memory cells as above is not caused just due to the difference in the channel hole diameters. For example, a difference in operating characteristics of memory cells may be generated by a channel hole shape or a thickness of a charge storage layer or the like. In an exemplary embodiment, a difference in channel hole shapes or a difference in thicknesses of charge storage layers may vary according to respective blocks.

For example, thicknesses and composition ratios of respective layers that constitute a charge storage layer disposed between a gate electrode and a channel region may be different according to channel hole diameters. For example, when depositing a charge storage layer having an ONO structure into a channel hole, deposition areas and deposition surface roughness of respective channel holes may be different according to channel hole diameters, and accordingly, a speed at which a deposition gas contacts a deposition surface to be deposited may vary. A difference in geometrical shapes such as a thickness of an ONO layer may cause a difference in operating characteristics of memory cells.

Thus, characteristics of memory cells according to block positions may have characteristics to be described below, based on a channel hole size, but characteristics thereof after a predetermined number of programming or after a predetermined number of operations may be changed and the changed different characteristics may include opposite characteristics to previous characteristics. Change in characteristics of memory cells will be described below with respect to geometrical shapes of memory cells including, but is not limited thereto, a channel hole size, channel hole shapes, or a thickness of a charge storage layer. For the convenience of description, it will be described about change in characteristics of memory cells with respect to channel hole sizes.

Referring back to FIG. 9, a block is formed in the cell region CR1\_C to include all memory cells corresponding to one page in the first direction, that is, in a word line direction, and to include some strings in the second direction, that is, in a bit line direction. Thus, each block extends in the first direction, and channel hole sizes, that is, channel hole diameters may differ in units of blocks.

In the present exemplary embodiment, diameters of channel holes included in blocks adjacent to the first edge EDG1 of the cell region CR1\_C and blocks adjacent to the second edge EDG2 of the cell region CR1\_C may be regarded as being smaller than diameters of channel holes included in blocks in a center of the cell region CR1\_C. Thus, program and erase speeds with respect to the blocks adjacent to the first edge EDG1 and the blocks adjacent to the second edge EDG2 of the cell region CR1\_C may be higher than program and erase speeds with respect to the blocks in the center of the cell region CR1\_C. For example, program and erase speeds of memory cells included in the first block BLKa may be higher than program and erase speeds of memory cells included in the second block BLKb.

FIG. 11 is a graph showing a result of performing a program operation and an erase operation on the first and second blocks BLKa and BLKb of FIG. 9.

Referring to FIG. 11, a horizontal axis denotes positions of blocks in the second direction, that is, a bit line direction,

and a vertical axis denotes a threshold voltage. For example, a solid line 11a denotes a central value of threshold voltages according to block positions of a programmed memory cell, and a dotted line 11b denotes a central value of threshold voltages according to block positions of an erased memory cell.

As described above with reference to FIG. 9, the memory cells adjacent to the first and the second edges EDG1 and EDG2 of the cell region CR1\_C have a smaller channel hole diameter than the memory cells in the center of the cell region CR1\_C. Thus, when a program operation is performed according to a single well bias condition, a program speed of the memory cells adjacent to the first and the second edges EDG1 and EDG2 of the cell region CR1\_C is faster than a program speed of the memory cells disposed in the center of the cell region CR1\_C. Accordingly, if all memory cells within the cell region CR1\_C are subject to the same program operation, threshold voltages of memory cells adjacent to edges EDG1 and EDG2, after the program operation, are higher than threshold voltages of memory cells at the center region of the cell region CR1\_C. Accordingly, the threshold voltage distribution, solid line 11a, of programmed memory cells may have a U shape.

Also, when an erase operation is performed on all memory cells within the cell region CR1\_C which has a single well bias condition, an erase speed of the memory cells adjacent to the first and second edges EDG1 and EDG2 is higher than the memory cells at the center region of the cell region CR1\_C. Accordingly, the threshold voltage distribution, dotted line 11b, of erased memory cells may have an inverted U.

FIG. 12 is a graph showing a first distribution of the first and second blocks BLKa and BLKb of FIG. 9 according to programmed states.

Referring to FIG. 12, a horizontal axis denotes a threshold voltage  $V_{th}$ , and a vertical axis denotes the number of memory cells. For example, if a memory cell is a multi-level cell programmed to two bits, the memory cell may have one of an erase state E, a first program state P1, a second program state P2, and a third program state P3.

The first distribution refers to an initial distribution of a program operation and an erase operation on the first and second blocks BLKa and BLKb. For example, the first distribution denotes a distribution of the first and second blocks BLKa and BLKb when a program/erase (P/E) cycle with respect to the first and second blocks BLKa and BLKb is equal to or less than a threshold value. Here, a dotted line 12a denotes a distribution with respect to the first block BLKa, and a solid line 12b denotes a distribution with respect to the second block BLKb.

As described above with reference to FIG. 9, since the channel hole diameter D1 of the memory cells included in the first block BLKa is smaller than the channel hole diameter D2 of the memory cells of the memory cells included in the second block BLKb, an erase speed with respect to the memory cells included in the first block BLKa is higher than an erase speed of the second block BLKb. Thus, a threshold voltage of the erase state E of the first block BLKa may be lower than a threshold voltage of the erase state E of the second block BLKb. Accordingly, an EP1 valley (A\_init) between the erase state E and the first program state P1 with respect to the first block BLKa may be greater than an EP1 valley (B\_init) of the second block BLKb (i.e.,  $A_{init} > B_{init}$ ). In this case, the EP1 valley may refer to a threshold difference between a peak threshold voltage of the erased state E and a peak threshold voltage of the first program state P1. The peak threshold voltage may



refer to a threshold voltage at which the number of memory cells is maximum within a distribution. In determining the EP1 valley, memory cells that are correctable via error correction code (ECC) may be included.

Meanwhile, as described above with reference to FIG. 9, since the channel hole diameter D1 of the memory cells included in the first block BLKa is smaller than the channel hole diameter D2 of the memory cells included in the second block BLKb, a program speed with respect to the memory cells included in the first block BLKa is higher than a program speed with respect to the memory cells included in the second block BLKb. Thus, a threshold voltage of the first program state P1 of the first block BLKa may be higher than a threshold voltage of the first program state P1 of the second block BLKb. Accordingly, a P1P2 valley between the first program state P1 and the second program state P2 with respect to the first block BLKa may be smaller than a P1P2 valley of the second block BLKb. The P1P2 valley refer to a threshold difference between a peak threshold voltage of the first program state P1 and a peak threshold voltage of the second program state P2.

As described above, channel hole diameters vary according to respective blocks in a 3D memory device. Thus, if a program operation and an erase operation are performed using a single bias condition regardless of the blocks and regardless of the channel hole diameters, performance of the memory device may be degraded.

FIG. 13A illustrates a reference bias condition according to respective layers with respect to a program operation of a memory device.

Referring to FIG. 13A, a channel hole CH1 corresponding to a string included in a 3D memory device is illustrated. As described above, the channel hole CH1 is formed by etching portions of gate electrodes and insulation layers stacked on a substrate, and thus, the channel hole CH1 may be a tapered etching profile where a diameter of the channel hole CH1 is becoming downwardly smaller. The tapered sidewall of the channel hole CH1 may be due to reduction of influx of etchants into the channel hole CH1 as the channel hole CH1 is deeper. Thus, a diameter of the channel hole CH1 may be smaller towards the substrate.

In an exemplary embodiment, the channel hole CH1 may be divided into four zones according to channel hole diameters. For example, a zone in which a channel hole diameter is smaller than 40 nm may be referred to as a first zone Z1, and a zone in which a channel hole diameter is equal to or greater than 40 nm and smaller than 60 nm may be referred to as a second zone Z2, and a zone in which a channel hole diameter is equal to or greater than 60 nm and smaller than 80 nm may be referred to as a third zone Z3, a zone in which a channel hole diameter is equal to or greater than 80 nm and smaller than 100 nm may be referred to as a fourth zone Z4.

In a programming operation, different program start voltages may be applied according to where memory cells are positioned among the four zones. A first program start voltage V1 applied to word lines connected to the first zone Z1 may be set to be the smallest, and a second program start voltage V2 applied to word lines connected to the second zone Z2 may be set to be higher than the first program start voltage V1. A third program start voltage V3 applied to word lines connected to the third zone Z3 may be set to be higher than the second program start voltage V2, and a fourth program start voltage V4 applied to word lines connected to the fourth zone Z4 may be set to be higher than the third program start voltage V3. A difference in operating characteristics of memory cells due to a difference in channel hole diameters of respective layers may be compensated for by

differentiating first programming voltage of the respective layers as described above. In this case, the program start voltage may refer to a starting voltage of an incremental-step-pulse programming (ISPP) operation.

The channel hole CH1 illustrated in FIG. 13A shows the reference bias condition of respective layers. Hereinafter, the channel hole CH1 will be referred to as a reference channel hole. When a channel hole size is changed, positions of respective zones may be changed, and even though the positions are changed, respective program start voltages applied to the respective zones are identical. This is shown in FIG. 13B.

FIG. 13B shows a bias condition of layers in a program operation of a memory device, according to an exemplary example of the present inventive concept.

Referring to FIG. 13B, when a diameter of a channel hole CH2 is smaller than the reference channel hole CH1, bias zones of layers are changed. For example, a partial region Za within the second zone Z2 of the reference channel hole CH1 may be included in the first zone Z1' of which word lines are applied with the first start program voltage V1. A partial region Zb within the third zone Z3 of the reference channel hole CH1 may be included in the second zone Z2'. A partial region Zc within the fourth zone Z4 of the reference channel hole CH1 may be included in the third zone Z3'.

The first through fourth program start voltages V1 through V4 are applied to word lines positioned within the first through fourth zones Z1' through Z4', respectively. As described above, the modified bias conditions according to the respective layers modify positions of zones according to a change in a channel hole diameter, and program start voltages of the respective zones are maintained. According to the modified bias conditions according to the respective layers, compared to the reference bias condition according to the respective layers, only program start voltages applied to word lines connected to the some zones Za, Zb, and Zc may be modified.

FIG. 14A illustrates a bias condition of layers in a program operation of a memory device, according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 14A, when a diameter of the channel hole CH2 is smaller than that of the reference channel hole CH1, a first offset  $\alpha$  may be applied to each of the program start voltages applied to word lines of the first through fourth zones Z1 through Z4. Thus, a voltage V1- $\alpha$  may be applied to word lines connected to the first zone Z1; a voltage V2- $\alpha$  may be applied to word lines connected to the second zone Z2; a voltage V3- $\alpha$  may be applied to word lines connected to the third zone Z3; and a voltage V4- $\alpha$  may be applied to word lines connected to the fourth zone Z4.

In FIG. 13B, the bias zones Z1' through Z4' are adjusted based on the bias zones Z1 through Z4 of the reference channel hole CH1 to apply a different reference bias condition to some word lines within partial regions Za to Zc. In FIG. 13B, the bias condition of the channel hole CH1 is adjusted to have the offset reference bias condition of the reference channel hole CH1 without adjusting bias zones of the channel hole CH2. As described, according to the present exemplary embodiment, a difference in operating characteristics of a memory cell due to a difference in channel hole diameters of respective blocks may be compensated for by adjusting bias conditions according to the respective blocks.

FIG. 14B illustrates a bias condition of layers in a program operation of a memory device according to an exemplary embodiment of the present inventive concept.



Referring to FIG. 14B, if a diameter of the channel hole CH2 is smaller than that of the reference channel hole CH1, the first through fourth zones Z1 through Z4 are the same as those of the reference channel hole CH1, and a first offset  $\alpha$  may be applied to a program start voltage applied to word lines connected to the first zone Z1, and a second offset  $\beta$  may be applied to each of program start voltages applied to word lines connected to each of the second through fourth zones Z2 through Z4. For example, the first offset  $\alpha$  may be greater than the second offset  $\beta$ . Accordingly, a voltage  $V1-\alpha$  may be applied to word lines connected to the first zone Z1, and a voltage  $V2-\beta$  may be applied to word lines connected to the second zone Z2, and a voltage  $V3-\beta$  may be applied to word lines connected to the third zone Z3, and a voltage  $V4-\beta$  may be applied to word lines connected to the fourth zone Z4.

In FIG. 14B, a different offset may be set with respect to zones. As described above, a difference in operating characteristics of a memory cell due to a difference in channel hole diameters of blocks may be compensated for by adjusting bias conditions according to the respective blocks.

FIG. 15 illustrates a memory device 100a according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 15, the memory device 100a may include a memory cell array 110a, a control logic 120a, a row decoder 140a, and a page buffer 150a. The memory cell array 110a may include a cell region CR1, and the cell region CR1 may include a plurality of blocks BLK1 through BLK10. The memory cell array 110a of FIG. 15 corresponds to the memory cell array 110a of FIG. 3. For the convenience of description, the memory cell array 110a of FIG. 3 has a single cell region CR1. The present inventive concept is not limited thereto. For example, the memory cell array 110a in FIG. 15 may be set to have four cell regions CR1 through CR4 as in FIG. 4.

In an exemplary embodiment, a plurality of blocks may be divided into N block regions based on a distance with respect to each of the first and the second edges EDG1 and EDG2 of the cell region CR1. For example, a plurality of blocks may be divided into N block regions based on a distance with respect to a relatively close edge among the first and the second edges EDG1 and EDG2, and N may be an integer equal to or greater than 2. Thus, blocks that are substantially at the same distance from the relatively close edge may be included in the same block region.

In an exemplary embodiment, a plurality of blocks may be divided into N block regions based on an absolute distance with respect to the first and the second edges EDG1 and EDG2 of the cell region CR1. In an exemplary embodiment, a plurality of blocks may be divided into N block regions based on a relative distance with respect to the first and the second edges EDG1 and EDG2 of the cell region CR1. The plurality of blocks may be divided into N block regions according to an order in which they are disposed with respect to the first and the second edges EDG1 and EDG2.

For example, a block BLK1 that is most adjacent to the first edge EDG1 and a block BLK2 that is second most adjacent to the first edge EDG1 may be included in a first block region REG1. Also, a block BLK10 that is most adjacent to the second edge EDG2 and a block BLK9 that is second most adjacent to the second edge EDG2 may be included in the first block region REG1. A block BLK3 that is third most adjacent to the first edge EDG1 and a block BLK4 that is fourth most adjacent to the first edge EDG1 may be included in a second block region REG2, and a block BLK8 that is third most adjacent to the second edge EDG2 and a block BLK7 that is fourth most adjacent to the second

edge EDG2 may be included in the second block region REG2. Also, blocks BLK5 and BLK6 in a center of the cell region CR1 may be included in an Nth block region REG\_N. However, the present inventive concept is not limited thereto, and according to an exemplary embodiment, a reference used to set block regions need not be the first and the second edges EDG1 and EDG2. For example, an arbitrary position in the cell region CR1 may be set to a reference to set block regions. For example, a predetermined line in the cell region CR1 may be set as a reference, and block regions may be divided with respect to a distance from the line. As an example, two lines in the cell region CR1 may be set as references, and block regions may be divided with respect to an order in which blocks are disposed with respect to the lines.

In an exemplary embodiment, the reference to set block regions may be chosen to reflect trends in change of channel hole size within a cell region. In FIG. 15, the channel hole sizes are symmetric with respect to a center region, and the channel hole size may increase toward the center region. Accordingly, two edges EDG1 and EDG2 in parallel to a word line may be chosen as the reference. Alternatively, a center line extending in parallel to a word line may be chosen as the reference.

FIG. 16 is a table REG\_TABLE1 illustrating block region information stored in a block region storing unit 121 of FIG. 15 according to an exemplary embodiment.

Referring to FIG. 16, the table REG\_TABLE1 stores information about block regions of FIG. 15. The first block BLK1 that is most adjacent to the first edge EDG1 and the tenth block BLK10 that is most adjacent to the second edge EDG2 may correspond to the first block region REG1, and the second block BLK2 that is second most adjacent to the first edge EDG1 and the ninth block BLK9 that is second most adjacent to the second edge EDG2 may also correspond to the first block region REG1.

Referring back to FIG. 15, the control logic 120a may include the block region information storing unit 121, a parameter information storing unit 122, and an operation controller 123. The block region information storing unit 121 and the parameter information storing unit 122 may be implemented using latches, for example. The present inventive concept is not limited thereto. For example, block region information and parameter information may be stored in a region of the memory cell array 110a. In an exemplary embodiment, block region information and parameter information may be stored in a buffer memory of a memory controller. In an exemplary embodiment, block region information and parameter information may be stored in an additional non-volatile memory included in a memory system.

The block region information storing unit 121 may store information about block regions of the cell region CR1 included in the memory cell array 110a. Block region information may be generated by dividing a plurality of blocks into at least two block regions based on a distance with respect to a relatively close edge among the first and second edges EDG1 and EDG2 of the cell region CR1. In an exemplary embodiment, block region information may be stored as a table showing block regions for corresponding blocks.

In an exemplary embodiment, the block region information storing unit 121 may store block region information that is modified according to an operation cycle count. For example, the block region information storing unit 121 may store first block region information corresponding to an operation cycle count that is equal to or less than a threshold



value, and may store second block region information corresponding to an operation cycle count that is greater than the threshold value. Thus, a single block may correspond to different block regions according to an operation cycle count. This will be further described For example with reference to FIGS. 50 and 51.

In an exemplary embodiment, the block region information storing unit 121 may store block region information that is modified according to a data retention period. For example, the block region information storing unit 121 may store first block region information corresponding to a data retention period that is equal to or smaller than a threshold value and second block region information corresponding to a data retention period that is greater than the threshold value. Thus, a single block may correspond to different block regions according to a data retention period. This will be further described with reference to FIG. 56. [Note to client]

In an exemplary embodiment, the block region information storing unit 121 may store block region information that is modified according to an operation mode. For example, the block region information storing unit 121 may store first block region information corresponding to a program operation, second block region information corresponding to an erase operation, third block region information corresponding to a read operation, and fourth block region information corresponding to a read recovery operation. Accordingly, a single block may correspond to different block regions according to an operation mode. This will be further described For example with reference to FIGS. 27 and 28.

The parameter information storing unit 122 may store information about operation parameters respectively corresponding to at least two block regions. The operation parameters represent parameters that constitute bias conditions for program, erase, and read operations. In this case, the operation parameters may have a plurality of bias sets, each bias set including bias values for the operation parameters. Hereinafter, for the convenience of a description, the operation parameters and the bias sets may be interchangeably used. In an exemplary embodiment, parameter information may be stored as a table showing operation parameters corresponding to respective block regions.

In the present exemplary embodiment, operation parameters may be determined according to block regions. Thus, the same operation parameters may apply to the same block region, and accordingly, program, erase, and read operations on different blocks included in the same block region may be performed using the same operation parameters.

In an exemplary embodiment, the parameter information storing unit 122 may store operation parameters that are modified according to an operation cycle count. For example, the parameter information storing unit 122 may store parameter information corresponding to an operation cycle count that is equal to or less than a threshold value and modified parameter information corresponding to an operation cycle count that is greater than the threshold value. Accordingly, different bias conditions may be applied to the same block according to an operation cycle count. This will be further described in detail with reference to FIGS. 43 through 49.

In an exemplary embodiment, the parameter information storing unit 122 may store operation parameters that are changed according to a data retention period. For example, the parameter information storing unit 122 may store parameter information corresponding to a data retention period that is equal to or less than a threshold value and modified parameter information corresponding to a data retention

period that is greater than the threshold value. Accordingly, different bias conditions may be applied to the same block according to a data retention period. This will be further described For example with reference to FIGS. 52 through 55.

In an exemplary embodiment, the parameter information storing unit 122 may store parameters for, for example, modifying a type of an algorithm corresponding to an auxiliary operation that may be additionally performed in respective operation modes with respect to the memory cell array 110a, a detailed condition of the algorithms, and whether to perform an algorithm or not. This will be further described For example with reference to FIGS. 58 through 63.

The operation controller 123 may control an operation performed on each block region of the memory cell array 110a using block region information and parameter information. For example, if a program command is received, the operation controller 123 may search block region information for a block corresponding to an address, and may control a program operation by using an operation parameter corresponding to the block region.

FIG. 17 illustrates a memory device 100a\_1 which is a first modified example of the memory device 100a of FIG. 15.

Referring to FIG. 17, the memory device 100a\_1 may include a memory cell array 110a, a control logic 120a, a row decoder 140a, and a page buffer 150a. The memory cell array 110a may include a cell region CR1\_1, and the cell region CR1\_1 may include a plurality of blocks BLK1 through BLK10. The memory cell array 110a according to the present exemplary embodiment corresponds to the memory cell array 110a of FIG. 3, and block regions may also be set with respect to the first through fourth cell regions CR1 through CR4 included in the memory cell array 110b of FIG. 4 as in the present exemplary embodiment.

According to the present exemplary embodiment, a plurality of blocks may be divided into M block regions based on a distance with respect to one of first and second edges EDG1 and EDG2 of the cell region CR1\_1. For example, a plurality of blocks may be divided into M block regions based on a distance with respect to one of the first and second edges EDG1 and EDG2, and M may be an integer equal to or greater than 2. Thus, blocks that are substantially at the same distance from a relatively close edge may be included in different block regions.

In an exemplary embodiment, a plurality of blocks may be divided into M block regions based on an absolute distance with respect to the first edge EDG1 of the cell region CR1\_1. In an exemplary embodiment, a plurality of blocks may be divided into M block regions based on a relative distance with respect to the first edge EDG1 of the cell region CR1\_1. The plurality of blocks may be divided into M block regions according to an order in which they are disposed with respect to the first edge EDG1.

However, the exemplary embodiments are not limited thereto, and according to an exemplary embodiment, a reference used to set block regions may not be the first and second edges EDG1 and EDG2 but an arbitrary position in the cell region CR1\_1. For example, a predetermined line in the cell region CR1\_1 may be set as a reference, and block regions may be divided with respect to a distance from the line. As an example, two lines in the cell region CR1\_1 may be set as references, and block regions may be divided with respect to an order in which blocks are disposed with respect to the lines.



A block region information storing unit **121** may store information about block regions of the cell region **CR1\_1** included in the memory cell array **110a**. In the present exemplary embodiment, block region information may be generated by dividing a plurality of blocks into at least two block regions based on a distance with respect to one of the first and second edges **EDG1** and **EDG2** of the cell region **CR1**. In an exemplary embodiment, block region information may be stored as a table showing block regions for corresponding blocks.

FIG. **18** is a table **REG\_TABLE2** illustrating block region information stored in the block region storing unit **121** of FIG. **17** according to an exemplary embodiment

Referring to FIG. **18**, the table **REG\_TABLE2** stores information about block regions corresponding to respective blocks according to the method of setting block regions illustrated in FIG. **17**. In the present exemplary embodiment, the first block **BLK1** that is most adjacent to the first edge **EDG1** and the second block **BLK2** that is second most adjacent to the first edge **EDG1** may correspond to the first block region **REG1**, and the third block **BLK3** that is third most adjacent to the first edge **EDG1** and the fourth block **BLK4** that is fourth most adjacent to the first edge **EDG1** may correspond to the second block region **REG2**. The tenth block **BLK10** that is farthest from the first edge **EDG1** and the ninth block **BLK9** that is second farthest from the first edge **EDG1** may correspond to an Mth block region **REG\_M**.

In the present exemplary embodiment, operation parameters may be determined according to a distance with respect to a relatively close edge among the first and second edges **EDG1** and **EDG2**. Thus, the same operation parameters may apply to different block regions. Accordingly, program, erase, and read operations on different blocks included in different block regions may be performed using the same operation parameters. Accordingly, the parameter information storing unit **122** may store information about operation parameters determined based on a distance with respect to the relatively close edge among the first and second edges **EDG1** and **EDG2** according to respective block regions.

For example, while the first block **BLK1** and the tenth block **BLK10** are included in the first block region **REG1** and the Mth block region **REG\_M**, respectively, the first block **BLK1** and the tenth block **BLK10** are respectively adjacent to the first and second edges **EDG1** and **EDG2**. Thus, channel hole diameters of memory cells included in the first block **BLK1** and the tenth block **BLK10** may be substantially the same. Thus, although the tenth block **BLK10** is included in a different block region from the first block **BLK1**, the same operation parameters as those with respect to the first block **BLK1** may be applied to the tenth block **BLK10**.

FIG. **19** illustrates a memory device **100a\_2** which is a second modified example of the memory device **100a** of FIG. **15**.

Referring to FIG. **19**, the memory device **100a2** may include a memory cell array **110a**, a control logic **120a**, a row decoder **140a**, and a page buffer **150a**. The memory cell array **110a** may include a cell region **CR1\_2**, and the cell region **CR1\_2** may include a plurality of blocks **BLK1** through **BLK10**. The memory cell array **110a** according to the present exemplary embodiment corresponds to the memory cell array **110a** of FIG. **3**, and block regions may also be set with respect to the first through fourth cell regions **CR1** through **CR4** included in the memory cell array **110b** of FIG. **4** as in the present exemplary embodiment.

According to the present exemplary embodiment, a plurality of blocks may be divided into L block regions based on a distance with respect to one of first and second edges **EDG1** and **EDG2** of the cell region **CR1\_2** and a distance with respect to the page buffer **150a**. L may be an integer equal to or greater than 2. Thus, blocks that are substantially at the same distance from a relatively close edge may be included in different block regions.

As described above, operation parameters according to a geometrical shape of a memory cell may be different according to a distance with respect to the first and second edges **EDG1** and **EDG2**. However, bias voltages to be applied to memory cells in reality may be different according to the distance with respect to the page buffer **150a**. For example, the greater a distance between the page buffer **150a** and a block, the higher may be a resistance component and a capacitance component of each bit line, and accordingly, a precharge voltage applied to a bit line via the page buffer **150a** during a program operation may not be properly transmitted.

Thus, according to the present exemplary embodiment, unlike FIG. **17**, some of operation parameters with respect to respective blocks may not be symmetrically determined with respect to a distance with respect to each of the first and second edges **EDG1** and **EDG2**. According to the present exemplary embodiment, a bias condition with respect to an memory cell in reality may be determined by also considering a position of the page buffer **150a**. However, the exemplary embodiments are not limited thereto, and block regions may also be set by considering not only the position of the page buffer **150a** but also positions of other peripheral circuits such as the row decoder **140a**.

The peripheral circuits such as the control logic **120a**, the row decoder **140a**, and the page buffer **150a** may be asymmetrically arranged with respect to the cell region **CR1\_2**. Thus, a distance between respective blocks and the peripheral circuits may be different according to the respective blocks so that other parameters that consider a distance between respective block regions and the peripheral circuits may be required in addition to parameters according to channel hole diameters of the respective block regions. Thus, in the present exemplary embodiment, block regions may be set by considering the parameters described above.

FIG. **20** is a table **REG\_TABLE3** illustrating block region information stored in a block region storing unit of FIG. **19** according to an exemplary embodiment

Referring to FIG. **20**, the table **REG\_TABLE3** stores information about block regions corresponding to respective blocks according to the method of setting block regions illustrated in FIG. **19**. In the present exemplary embodiment, the first block **BLK1** that is most adjacent to the first edge **EDG1**, the second block **BLK2** that is second most adjacent to the first edge **EDG1**, and the third block **BLK3** that is third most adjacent to the first edge **EDG1** may correspond to the first block region **REG1**. The fourth block **BLK4** that is fourth most adjacent to the first edge **EDG1** may correspond to the second block region **REG2**. The tenth block **BLK10** that is most adjacent to the second edge **EDG2**, the ninth block **BLK9** that is second most adjacent to the second edge **EDG2**, and the eighth block **BLK8** that is third most adjacent to the second edge **EDG2** may correspond to the second block region **REG2**.

In the present exemplary embodiment, operation parameters may be determined according to block regions. Thus, the same operation parameters may apply to the same block region, and accordingly, program, erase, and read operations on different blocks included in the same block region may be



performed using the same operation parameters. Accordingly, a parameter information storing unit **122** may store information about operation parameters according to respective block regions.

For example, as the first block **BLK1** and the tenth block **BLK10** are respectively adjacent to the first and second edges **EDG1** and **EDG2**, memory cells included in the first block **BLK1** and the tenth block **BLK10** may have substantially the same channel hole diameters. However, since the first block **BLK1** is disposed adjacent to the page buffer **150a**, and the tenth block **BLK10** is disposed relatively far from the page buffer **150a**, a resistance component and a capacitance component of a bit line regarding the tenth block **BLK10** may be higher than those of a bit line regarding the first block **BLK1**.

Thus, although the tenth block **BLK10** is adjacent to the second edge **EDG2**, the tenth block **BLK10** is included in a second block region **REG1**, which is different from a block region of the first block **BLK1**, and thus, different bias conditions (or bias sets) may be applied to the tenth block **BLK10** from those applied to the first block **BLK1**. For example, parameter **A** may be applied to the first block **BLK1** included in the first block region **REG1**, and parameter **13** may be applied to the tenth block **BLK10** included in the second block region **REG2**.

**FIG. 21** illustrates a memory device **100a\_3** which is a modified example of the memory device **100a** of **FIG. 15**.

Referring to **FIG. 21**, the memory device **100a\_3** may include a memory cell array **110a'**, a control logic **120a**, a row decoder **140a**, and a page buffer **150a**. The memory cell array **110a'** may include a cell region **CR1\_3**, and the cell region **CR1\_3** may include a plurality of lower blocks **BLKb1** through **BLKb10** disposed in a lower layer **Lb** and a plurality of upper blocks **BLKu1** through **BLKu10** disposed in an upper layer **Lu**. The memory cell array **110a'** may correspond to the memory cell array **110a** of **FIG. 3**, and block regions may also be set with respect to the first through fourth cell regions **CR1** through **CR4** of **FIG. 4** included in the memory cell array **110b** of **FIG. 4** as in the present exemplary embodiment. For the convenience of description, the lower layer **Lb** and the upper layer **Lu** are in a planar drawing, but the upper layer **Lu** is vertically stacked on the lower layer **Lb**.

**FIGS. 22A** and **22B** are circuit diagrams illustrating memory cell arrays **110a'** and **110a''** which are examples of the memory cell array of **FIG. 21**.

Referring to **FIG. 22A**, the memory cell array **110a'** may include a plurality of blocks **BLKb** and **BLKu** that are vertically stacked. For example, the memory cell array **110a'** may include a lower block **BLKb** disposed on a substrate and an upper block **BLKu** disposed on the lower block **BLKb**. The lower block **BLKb** and the upper block **BLKu** may be each a vertical NAND flash memory.

The lower block **BLKb** may include a plurality of NAND strings **NSb**, a plurality of word lines **Wlb0** to **Wlb3**, a plurality of bit lines **BLb0** to **BLb2**, a plurality of ground selection lines **GSLb0** through **GSLb2**, a plurality of string selection lines **SSLb0** through **SSLb2**, and a common source line **CSLb**. The number of NAND strings, the number of word lines, the number of bit lines, the number of ground selection lines, and the number of string selection lines may be variously changed according to exemplary embodiments.

The upper block **BLKu** may include a plurality of NAND strings **NSu**, a plurality of word lines **WLu0** to **WLu3**, a plurality of bit lines **BLu0** to **BLu2**, a plurality of ground selection lines **GSLu0** through **GSLu2**, a plurality of string selection lines **SSLu0** through **SSLu2**, and a common source

line **CSLu**. The number of NAND strings, the number of word lines, the number of bit lines, the number of ground selection lines, and the number of string selection lines may be variously changed according to exemplary embodiments.

As described above, the lower block **BLKb** and the upper block **BLKu** may have a substantially similar form, and may have a substantially similar form to that of the first block **BLK1** illustrated in **FIG. 6**. Thus, description provided with reference to **FIG. 6** may also apply to the present exemplary embodiment, and thus repeated description will be omitted.

Referring to **FIG. 22B**, the memory cell array **110a''** may include a plurality of blocks **BLKb'** and **BLKu'** that are vertically stacked. For example, the memory cell array **110a''** may include a lower block **BLKb'** disposed on a substrate and an upper block **BLKu'** disposed on the lower block **BLKb'**. The lower block **BLKb'** and the upper block **BLKu'** may be each a vertical NAND flash memory. The memory cell array **110a''** is a modified embodiment of the memory cell array **110a''** of **FIG. 22A**, except that the memory cell array **110a''** shares a plurality of bit lines **BL0** to **BL3**, and here description will focus on differences only.

The lower block **BLKb'** may include a plurality of NAND strings **NSb**, a plurality of word lines **Wlb0** to **Wlb3**, the plurality of bit lines **BL0** to **BL3**, a plurality of ground selection lines **GSLb0** through **GSLb2**, a plurality of string selection lines **SSLb0** through **SSLb2**, and a common source line **CSLb**. The number of NAND strings, the number of word lines, the number of bit lines, the number of ground selection lines, and the number of string selection lines may be variously changed according to exemplary embodiments.

The upper block **BLKu'** may include a plurality of NAND strings **NSu**, a plurality of word lines **WLu0** to **WLu3**, the plurality of bit lines **BL0** to **BL3**, a plurality of ground selection lines **GSLu0** through **GSLu2**, a plurality of string selection lines **SSLu0** through **SSLu2**, and a common source line **CSLu**. The number of NAND strings, the number of word lines, the number of bit lines, the number of ground selection lines, and the number of string selection lines may be variously changed according to exemplary embodiments.

As described above, the upper block **BLKu'** may have a form corresponding to the lower block **BLKb'** that is inverted in a vertical direction with respect to the substrate, and the upper block **BLKu'** and the lower block **BLKb'** may share the plurality of bit lines **BLb0** through **BLb2**.

Referring to **FIG. 21** again, the plurality of lower blocks **BLKb1** through **BLKb10** disposed in the lower layer **Lb** may be divided into **M** block regions based on a distance with respect to one of the first and second edges **EDG1** and **EDG2** of the cell region **CR1\_3**, and the plurality of upper blocks **BLKu1** through **BLKu10** disposed in the upper layer **Lu** may also be divided into **M** block regions based on a distance with respect to one of the first and second edges **EDG1** and **EDG2** of the cell region **CR1\_3**. **M** may be an integer equal to or greater than 2.

In an exemplary embodiment, the same method of setting block regions may be applied to the plurality of lower blocks **BLKb1** through **BLKb10** disposed in the lower layer **Lb** and the plurality of upper blocks **BLKu1** through **BLKu10** disposed in the upper layer **Lu**. Accordingly, lower blocks and upper blocks that are substantially at the same distance with respect to the first edge **EDG1** or the second edge **EDG2** may be included in the same block regions.

The block region information storing unit **121** may store information about block regions of the cell region **CR1\_3** included in the memory cell array **110a'**. In an exemplary embodiment, block region information may be generated by dividing a plurality of blocks into at least two block regions



based on a distance with respect to one of the first and second edges EDG1 and EDG2 of the cell region CR1\_3. In an exemplary embodiment, block region information may be stored as a table showing block regions for corresponding blocks.

FIG. 23 is a table REG\_TABLE4 showing an example of block region information stored in the block region storing unit of FIG. 21.

Referring to FIG. 23, the table REG\_TABLE4 stores information about block regions of blocks according to the method of setting block regions illustrated in FIG. 21. In an exemplary embodiment, the lower block BLKb1 and the upper block BLKu1 that are most adjacent to the first edge EDG1 and the lower block BLKb2 and the upper block BLKu2 that are second most adjacent to the first edge EDG1 may correspond to a first block region REG1. Also, the lower block BLKb3 and the upper block BLKu3 that are third most adjacent to the first edge EDG1 and the lower block BLKb4 and the upper block BLKu4 that are fourth most adjacent to the first edge EDG1 may correspond to a second block region REG2. Also, the lower block BLKb10 and the upper lower BLKu10 that are farthest from the first edge EDG1 and the lower block BLKb9 and the upper block BLKu9 that are second farthest from the first edge EDG1 may correspond to an Mth block region REG\_M.

In an exemplary embodiment, operation parameters may be determined according to a distance with respect to a relatively close edge among the first and second edges EDG1 and EDG2. Thus, the same operation parameters may apply to different block regions. Accordingly, program, erase, and read operations on different blocks included in different block regions may be performed using the same operation parameters. Accordingly, the parameter information storing unit 122 may store information about operation parameters for each block regions determined based on a distance with respect to the relatively close edge among the first and second edges EDG1 and EDG2.

FIG. 24 illustrates a memory device 100a 4 which is a modified example 100a\_3 of the memory device of FIG. 21.

Referring to FIG. 24, the memory device 100a4 may include a memory cell array 110a', a control logic 120a, a row decoder 140a, and a page buffer 150a. The memory cell array 110a' may include a cell region CR1\_4, and the cell region CR1\_4 may include a plurality of lower blocks BLK1 through BLK10 disposed in a lower layer Lb and a plurality of upper blocks BLKu1 through BLKu10 disposed in an upper layer Lu. The memory cell array 110a' may have a substantially similar form to the memory cell array 110a' of FIG. 22A or the memory cell array 110a" of FIG. 22B.

The plurality of lower blocks BLKb1 through BLKb10 disposed in the lower layer Lb may be divided into M block regions based on a distance with respect to one of the first and second edges EDG1 and EDG2 of the cell region CR1\_4, and the plurality of upper blocks BLKu1 through BLKu10 disposed in the upper layer Lu may be divided into L block regions based on a distance with respect to one of the first and second edges EDG1 and EDG2 of the cell region CR1\_4. M and L may each be an integer equal to or greater than 2. In an exemplary embodiment, M and L may be identical, or in an exemplary embodiment, M and L may be different from each other.

According to an exemplary embodiment, different methods of setting block regions may be applied to the plurality of lower blocks BLKb1 through BLKb10 disposed in the lower layer Lb and the plurality of upper blocks BLKu1 through BLKu10 disposed in the upper layer Lu. Accordingly, lower blocks and upper blocks that are substantially at

the same distance from the first edge EDG1 or the second edge EDG2 may be included in different block regions.

The block region information storing unit 121 may store information about block regions of the cell region CR1\_4 included in the memory cell array 110a'. In an exemplary embodiment, block region information may be generated by dividing a plurality of blocks into at least two block regions based on a distance from one of the first and second edges EDG1 and EDG2 of the cell region CR1\_4. In an exemplary embodiment, block region information may be stored as a table showing block regions for corresponding blocks.

FIG. 25 is a table REG\_TABLE5 showing an example of block region information stored in a block region storing unit 121 of FIG. 24.

Referring to FIG. 25, the table REG\_TABLE5 stores information about block regions for blocks according to the method of setting block regions illustrated in FIG. 24. The lower block BLKb1 that is most adjacent to the first edge EDG1, the lower block BLKb2 that is second most adjacent to the first edge EDG1, the upper block BLKu1 that is most adjacent to the first edge EDG1, the upper block BLKu2 that is second most adjacent to the first edge EDG1, and the upper block BLKu3 that is third most adjacent to the first edge EDG1 may correspond to a first block region REG1. Also, the lower block BLKb3 that is third most adjacent to the first edge EDG1, the lower block BLKb4 that is fourth most adjacent to the first edge EDG1, and the upper block BLKu4 that is fourth most adjacent to the first edge EDG1 may correspond to a second block region REG2. Also, the lower block BLKb10 that is farthest from the first edge EDG1 and the lower block BLKb9 that is second farthest from the first edge EDG1 may correspond to an Mth block region REG\_M. Also, the upper lower BLKu10 that is farthest from the first edge EDG1 and the upper block BLKu9 that is second farthest from the first edge EDG1 and the upper block BLKu8 that is third farthest from the first edge EDG1 may correspond to an Lth block region REG\_L.

In an exemplary embodiment, information of operation parameters may be determined based on a distance with respect to a relatively close edge among the first and second edges EDG1 and EDG2. Thus, the same information of the operation parameters may apply to different block regions. Accordingly, program, erase, and read operations on different blocks included in different block regions may be performed using the same operation parameters. Accordingly, the parameter information storing unit 122 may store information about operation parameters determined based on the distance with respect to the relatively close edge among the first and second edges EDG1 and EDG2 according to respective block regions.

FIG. 26 is a flowchart of a method of operating a memory device according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 26, the method of operating a memory device may include controlling an operation on a memory cell array performed in a control logic when a command and an address are received from a memory controller. The method may include, for example, operations that are sequentially performed in the control logic 120a of FIG. 15. The description provided with reference to FIGS. 1 through 25 may also apply to the method of the present exemplary embodiment, and repeated description will be omitted.

In operation S110, a command and an address are received from a memory controller. For example, the control logic 120a may receive a command and an address from the memory controller to thereby initiate an operation of the control logic 120a. In operation S130, a block region



corresponding to the received address is searched for. For example, the operation controller **123** may search the block region information storing unit **121** for a block corresponding to the address. In operation **S150**, operation parameter information corresponding to the block region is searched for. For example, the operation controller **123** may search the parameter information storing unit **122** for the operation parameter information corresponding to the block region.

In operation **S170**, an operation on a memory cell array is controlled using operation parameter information. For example, the operation controller **123** may generate a voltage control signal CTRL\_vol according to operation parameter information, and may provide the voltage generator **130** (see FIG. 2) with the voltage control signal CTRL\_vol. Also, the operation controller **123** may generate a row address X-ADDR that is activated during an operation according to the operation parameter information, and provide the row decoder **140a** with the row address X-ADDR. Also, the operation controller **132** may generate a column address Y-ADDR that is activated during an operation according to the operation parameter information, and provide the page buffer **150a** with the column address Y-ADDR.

FIG. 27 is a flowchart of a method of operating a memory device according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 27, the method may include controlling an operation on a memory cell array performed in a control logic when a command and an address are received from a memory controller. The method may include, for example, operations that are sequentially performed in the control logic **120a** of FIG. 15. The method according to the present exemplary embodiment is a modified example of the method illustrated in FIG. 26, and the description provided with reference to FIGS. 1 through 26 may apply to the method of the present exemplary embodiment, and repeated description will be omitted.

In operation **S210**, a command and an address are received from a memory controller. For example, the control logic **120a** may receive a command and an address from the memory controller to thereby initiate an operation of the control logic **120a**.

In operation **S220**, block region information corresponding to the command is selected from a plurality of pieces of block region information. In an exemplary embodiment, different methods of setting block regions may be applied according to commands, and the block region information storing unit **121** may store block region information according to the commands. For example, the block region information storing unit **121** may divide blocks included in a cell region into block regions according to a first method of setting block regions if a program command is received. The block region information storing unit **121** may divide blocks included in a cell region into block regions according to a second method of setting block regions if an erase command is received. The block region information storing unit **121** may divide blocks included in a cell region into block regions according to a third method of setting block regions if a read command is received. The block region information storing unit **121** may divide blocks included in a cell region into block regions according to a fourth method of setting block regions if a read recovery command is received.

FIG. 28 is a table REG\_TABLE6 showing an example of block region information stored in a block region storing unit according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 28, the table REG\_TABLE6 includes block region information for a plurality of operations, and

each piece of block region information stores information about block regions assigned to blocks. The plurality of pieces of block region information may be stored in the block region information storing unit **121** illustrated in FIG. 15, 17, 19, 21 or 24.

In an exemplary embodiment, the plurality of pieces of block region information may include block region information regarding a program operation, block region information regarding an erase operation, block region information regarding a read operation, and block region information regarding a read recovery operation. A read recovery operation is an operation to correct or restore a read error occurred in a memory device, and may be performed using an algorithm referred to as a 'defence code'. Various defence code algorithms corresponding to a read recovery operation will be described in detail later with reference to FIG. 59.

When a program command is received from a memory controller, the operation controller **123** may select block region information regarding a program operation from the block region information unit **121**. For example, according to block region information regarding a program operation, first and second blocks BLK1 and BLK2 may correspond to a first block region REG1; third and fourth blocks BLK3 and BLK4 may correspond to a second block region REG2; fifth and sixth blocks BLK5 and BLK6 may correspond to a third block region REG3; seventh and eighth blocks BLK7 and BLK8 may correspond to a fourth block region REG4; and ninth and tenth blocks BLK9 and BLK10 may correspond to a fifth block region REG5.

When an erase command is received from a memory controller, the operation controller **123** may select block region information regarding an erase operation from the block region information unit **121**. For example, according to block region information regarding an erase operation, first and second blocks BLK1 and BLK2 may correspond to a first block region REG1; third through eighth blocks BLK3 through BLK8 may correspond to a second block region REG2; and ninth and tenth blocks BLK9 and BLK10 may correspond to a third block region REG3.

When a read command is received from a memory controller, the operation controller **123** may select block region information regarding a read operation from the block region information unit **121**. For example, according to block region information regarding a read operation, first through third blocks BLK1 through BLK3 may correspond to a first block region REG1; fourth through seventh blocks BLK4 through BLK7 may correspond to a second block region REG2; and eighth through tenth blocks BLK8 through BLK10 may correspond to a third block region REG3.

When a read recovery command is received from a memory controller, the operation controller **123** may select block region information regarding a read recovery operation from the block region information unit **121**. For example, according to block region information regarding a read recovery operation, first through fourth blocks BLK1 through BLK4 may correspond to a first block region REG1; fifth and sixth blocks BLK5 and BLK6 may correspond to a second block region REG2; and seventh through tenth blocks BLK7 through BLK10 may correspond to a third block region REG3.

Read error may occur for various causes, and such causes may be different according to positions of blocks in a cell region. For example, when a read operation is performed several times on memory cells included in a first block BLK1 having a first channel hole diameter, an upper voltage



level of the memory cells in an erase state may increase due to a read inhibit voltage, thereby causing a read error. Meanwhile, in regard to memory cells included in a fifth block BLK5 having a second channel hole diameter greater than the first channel hole diameter, a lower voltage level of the memory cells in an upper program state such as first through third program states may be decreased according to passage of time, thereby causing a read error.

Thus, a read recovery operation to correct a read error may be performed based on block region information. A method of setting block regions for a read recovery operation may be different from a method of setting block regions with respect to program, erase, and read operations. Accordingly, different block regions having, for example, the same operation cycles or having the same data retention periods, may have different operation parameter information.

As described above, the block region storing unit 121 may store block region information according to commands, and thus, a block may be allocated to different block regions according to program, erase, read, and read recovery operations.

Referring to FIG. 27 again, in operation S230, selected block region information is searched for a block corresponding to the address. In operation S240, operation parameter information corresponding to the block region is searched for. In operation S250, an operation on a memory cell array is controlled using the operation parameter information.

In an exemplary embodiment, when a program command is applied, the operation controller 123 may search block region information regarding a program operation for a block corresponding to an address. For example, if the address corresponds to a fifth block BLK5, a third block region REG3 corresponding to the fifth block BLK5 is searched for, and next, operation parameter information corresponding to the third block region REG3 may be searched for. Next, a program operation on the fifth block BLK5 may be performed using the operation parameter information.

In an exemplary embodiment, if a read command is applied, the operation controller 123 may search block region information regarding a read operation for a block corresponding to an address. For example, if the address corresponds to a fifth block BLK5, a second block region REG2 corresponding to the fifth block BLK5 is searched for, and next, an operation parameter corresponding to the second block region REG2 may be searched for. Next, a read operation on the fifth block BLK5 may be performed using the operation parameter.

FIG. 29 is a table PAR\_TABLE1 showing bias conditions of a program operation according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 29, the table PAR\_TABLE1 shows bias conditions of a program operation on a first block region REG1 and an Nth block region REG\_N, for example, of a cell region CR1 of FIG. 15. The table PAR\_TABLE1 may be stored in the parameter information storing unit 122 of FIG. 15. The present inventive concept is not limited thereto, and in an exemplary embodiment, the table PAR\_TABLE1 may further include bias conditions of a program operation on the other block regions REG2 to REGN-1 of the cell region CR1 of FIG. 15, for example.

The first block region REG1 may include, for example, blocks adjacent to the first and second edges EDG1 and EDG2 of the cell region CR1, and the Nth block region REG\_N may include, for example, blocks in a center of the cell region CR1. Accordingly, a channel hole diameter of strings included in the first block region REG1 may be

smaller than a channel hole diameter of strings included in the Nth block region REG\_N. Accordingly, if a same bias condition for a program operation is applied to the first block region REG1 and the Nth block region REG\_N, program speeds with respect to memory cells included in the first block region REG1 may be higher than a program speed with respect to memory cells included in the Nth block region REG\_N.

In an exemplary embodiment, bias conditions of a program operation may be set for each block region to reduce a difference of program speeds between the first block region REG1 and the Nth block region REG\_N. For example, the bias conditions of the program operation may be set such that the program speed of the first block region REG1 may be reduced. Accordingly, a program distribution of memory cells included in the first block region REG1 may be adjusted to be similar to a program distribution of memory cells included in the Nth block region REG\_N. Hereinafter, bias conditions according to each block region of a program operation will be described. The bias conditions described below include various operation parameters. According to an exemplary embodiment, some of the operation parameters may be applied only, or other operation parameters may be additionally applied.

In an exemplary embodiment, during a program operation on the first block region REG1, a first program voltage Vpgm1 less than a second program voltage Vpgm2 may be applied to a selected word line WL\_sel, and during a program operation on the Nth block region REG\_N, the second program voltage Vpgm2 that is higher than the first program voltage Vpgm1 may be applied. Accordingly, memory cells in a same page or in a same height may have different program voltages according to block locations of the memory cells. For example, a first memory cell disposed in a block adjacent to an edge of a cell region is subject to a program voltage lower than a program voltage for a second memory cell disposed in a block in a centre region of the cell region. The first and the second memory cells are disposed within the same page.

In an exemplary embodiment, a program operation may be performed using an incremental step pulse programming (ISPP) method in which a program voltage applied to a word line is increased stepwise as a value of a program loop increases. Here, a program voltage may be increased with respect to the first block region REG1 by a first program voltage increment Vinc1 as a value of a loop increases, and a program voltage may be increased with respect to the Nth block region REG\_N by a second program voltage increment Vinc2 that is greater than the first program voltage increment Vinc1, as a value of a loop increases.

In an exemplary embodiment, a program operation may be performed on the first block region REG1 during a first program duration Tpgm1, and a program operation may be performed on the Nth block region REG\_N during a second program duration Tpgm2 that is longer than the first program duration Tpgm1. In an exemplary embodiment, a program operation may be performed such that a program duration increases stepwise as a value of a loop increases. Here, a program duration may be increased with respect to the first block region REG1 by a first time increment Tinc1, as a value of a loop increases, and a program duration may be increased with respect to the Nth block region REG\_N by a second time increment Tinc2 which is longer than the first time increment Tinc1, as a value of a loop increases.

In an exemplary embodiment, a program loop includes a program operation and a verify operation that are sequentially performed, and the verify operation may be omitted in



a predetermined number of initial program loops. The initial program loop without the verify operation may be referred to as a 'verify skip loop.' As a program speed with respect to the first block region REG1 is relatively high, a verify operation may be omitted only during a first verify skip loop Ls1, and a verify operation may be omitted with respect to the Nth block region REG\_N during a second verify skip loop Ls2 which is greater than the first verify skip loop Ls1.

In an exemplary embodiment, the number of maximum loops according to ISPP may be preset. A first maximum loop Lm1 may be set with respect to the first block region REG1, and a second maximum loop Lm2 that is greater than the first maximum loop Lm1 may be set with respect to the Nth block region REG\_N.

In an exemplary embodiment, a first program inhibit voltage Vinhp1 may be applied to a non-selected word line WL\_unsel included in the first block region REG1, and a second program inhibit voltage Vinhp2 that is higher than the first program inhibit voltage Vinhp1 may be applied to a non-selected word line WL\_unsel included in the Nth block region REG\_N. In an exemplary embodiment, a first program verify voltage Vpvrfl may be applied during a program verify operation on the first block region REG1, and a second program verify voltage Vpvrfl that is higher than the first program verify voltage Vpvrfl may be applied during a program verify operation on the Nth block region REG\_N.

As described above, as at least one block or each block is set to have different bias conditions of operation parameters due to a difference in channel hole diameters, performance of memory cells may also be different deepening on the memory cells' block regions. In an exemplary embodiment, to reduce a difference in performance of the block regions, the operation controller 123 may check an address input from the outside and perform an auxiliary operation on some of the block regions by modifying an algorithm regarding a program operation. In an exemplary embodiment, the operation controller 123 may additionally perform an operation on some of block regions according to a command input from the outside by using a difference in performance of the block regions. In an exemplary embodiment, to reduce a difference in performance of block regions, the operation controller 123 may perform a background operation such as a garbage collection operation, on some of the block regions.

However, the present inventive concept is not limited thereto. For example, if blocks of cell regions CR1 through CR4 of the memory cell array 110b illustrated in FIG. 4 are simultaneously selected during a program operation, and if the memory device 100a does not have voltage sources allocated to each cell region, different parameters need not be applied to respective block regions.

FIG. 30A is a graph showing program start voltage levels of blocks according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 30A, a horizontal axis denotes positions of blocks in the second direction of FIG. 9. The second direction may be in parallel to an extension direction of a bit line, and a vertical axis denotes a program start voltage. As described above with reference to FIG. 11, a threshold voltage of programmed memory cells included in a cell region may have a U shape along the second direction. To compensate for a program speed according to the block positions, a first program start voltage may be set with respect to block regions disposed in an edge region of a cell region, for example, block regions adjacent to an edge, and a second program start voltage may be set with respect to block regions in a center of the cell region. In an exemplary

embodiment, the first program start voltage may be lower than the second program start voltage. The difference between the first program start voltage and the second program start voltage may be set to the extent that a program speed may be compensated for the blocks disposed in the edge region of the cell region.

For example, blocks included in a cell region may be divided into three block regions based on a distance with respect to two edges of the cell region. Block regions may be set such that blocks that are most adjacent to the two edges of the cell region are included in a first block region, and blocks that are second most adjacent to the two edges of the cell region are included in a second block region, and blocks in a center of the cell region are included in a third block region. Hereinafter, program operation parameters regarding the first through third block regions will be described.

In an exemplary embodiment, the lowest program start voltage may be set with respect to the first block region, and an intermediate program start voltage may be set with respect to the second block region, and the highest program start voltage may be set with respect to the third block region. In an exemplary embodiment, a program start voltage may be increased stepwise from an edge towards the center of the cell region.

FIG. 30B is a graph showing program start voltages with respect to different block regions according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 30B, blocks included in a cell region may be divided into a first block region REG1 adjacent to two edges of the cell region and a second block region REG2 in a center of the cell region. In an exemplary embodiment, the same program duration may be set with respect to the first and second block regions REG1 and REG2, and a program start voltage Vpgm1 regarding the first block region REG1 may be set to be lower than a program start voltage Vpgm2 regarding the second block region REG2.

FIG. 31A is a graph showing program duration of respective blocks according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 31A, a horizontal axis denotes positions of blocks according to an extension direction of a bit line, and a vertical axis denotes a program duration, for example, a program execution time. In the present exemplary embodiment, to compensate for differences of program speeds among blocks, a first program duration may be set with respect to block regions adjacent to an edge of a cell region, and a second program duration may be set with respect to block regions in a center of the cell region. In an exemplary embodiment, the first program duration time may be shorter than the second program duration time.

In an exemplary embodiment, the shortest program duration may be set with respect to a first block region, and an intermediate program duration may be set with respect to a second block region, and the longest program duration may be set with respect to a third block region. In an exemplary embodiment, a program duration may be increased stepwise from an edge to a center of a cell region.

FIG. 31B is a graph showing program duration with respect to different block regions according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 31B, blocks included in a cell region may be divided into a first block region REG1 adjacent to two edges of the cell region and a second block region REG2 in a center of the cell region. In an exemplary embodiment, the same program start voltage Vpgm1 may be set with respect to the first and the second block regions REG1 and



33

REG2, and a program duration regarding the first block region REG1 may be set to be from a first time t1 to a second time t2, and a program duration regarding the second block region REG2 may be set to be from the first time t1 to a third time t3. As described above, the program duration regarding the first block region REG1 may be set to be shorter than the program duration regarding the second block region REG2.

FIG. 32 is a graph showing program inhibit voltages of respective blocks, according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 32, a horizontal axis denotes positions of blocks according to an extension direction of a bit line, and a vertical axis denotes a program inhibit voltage. In the present exemplary embodiment, to compensate for a program speed with respect to respective block positions, a first program inhibit voltage may be set with respect to block regions adjacent to an edge of a cell region, and a second program inhibit voltage may be set with respect to block regions in a center of the cell region. In an exemplary embodiment, the second program inhibit voltage may be higher greater than the first program inhibit voltage.

In an exemplary embodiment, the lowest program inhibit voltage may be set with respect to a first block region, and an intermediate program inhibit voltage may be set with respect to a second block region, and the highest program inhibit voltage may be set with respect to a third block region. In an exemplary embodiment, a program inhibit voltage may be increased stepwise from an edge of a cell region towards a center of the cell region.

FIG. 33 is a graph showing programming verify voltages of blocks according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 33, a horizontal axis denotes positions of blocks according to an extension direction of a bit line, and a vertical axis denotes a program verify voltage. In the present exemplary embodiment, in order to compensate for a program speed with respect to respective block positions, a first program verify voltage may be set with respect to block regions adjacent to an edge of a cell region, and a second program verify voltage may be set with respect to block regions in a center of the cell region. In an exemplary embodiment, the second program verify voltage may be greater than the first program verify voltage.

In an exemplary embodiment, the lowest program verify voltage may be set with respect to a first block region, and an intermediate program verify voltage may be set with respect to a second block region, and the highest program verify voltage may be set with respect to a third block region. In an exemplary embodiment, a program verify voltage may be increased stepwise from an edge of a cell region towards a center of the cell region.

FIG. 34 is a graph showing program time increments according to loops of respective blocks according to an exemplary embodiment of the present inventive concept

Referring to FIG. 34, a horizontal axis denotes positions of blocks according to an extension direction of a bit line, and a vertical axis denotes a program time increment. In the present exemplary embodiment, to compensate for a program speed with respect to respective block positions, a first program time increment for each loop may be set with respect to block regions adjacent to an edge of a cell region, and a second program time increment for each loop may be set with respect to block regions in a center of the cell region. In an exemplary embodiment, the second program time increment may be greater than the first program time increment.

34

In an present exemplary embodiment, the shortest program time increment may be set with respect to a first block region, and the intermediate program time increment may be set with respect to a second block region, and the longest program time increment may be set with respect to a third block region. In an exemplary embodiment, a program time increment may be increased stepwise from an edge of a cell region to a center of the cell region.

FIG. 35 is a graph showing verify skip loops of respective blocks according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 35, a horizontal axis denotes positions of blocks according to an extension direction of a bit line, and a vertical axis denotes a verify skip loop. Here, the verify skip loop refers to the number of loops in which a verify operation is omitted but only a program operation is performed during an ISPP operation. In an exemplary embodiment, to compensate for a program speed with respect to respective block positions, a verify skip loop having a first value may be set with respect to block regions adjacent to an edge of a cell region, and a verify skip loop having a second value may be set with respect to block regions in a center of the cell region. In an exemplary embodiment, the second value may be greater than the first value.

In an exemplary embodiment, a verify skip loop of a smallest value may be set with respect to a first block region, and a verify skip loop of an intermediate value may be set with respect to a second block region, and a verify skip loop of a greatest value may be set with respect to a third block region. In an exemplary embodiment, a value of a verify skip loop may be increased stepwise from an edge to a center of a cell region.

FIG. 36 is a table PAR\_TABLE2 showing bias conditions of an erase operation according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 36, the table PAR\_TABLE2 shows bias conditions of an erase operation with respect to a first block region REG1 and an Nth block region REG\_N. For example, the table PAR\_TABLE2 may be stored in the parameter information storing unit 122 of FIG. 15. The present inventive concept is not limited thereto, and in an exemplary embodiment, the table PAR\_TABLE2 may further include bias conditions of an erase operation on other block regions.

The first block region REG1 may include, for example, blocks adjacent to the first and second edges EDG1 and EDG2 of a cell region CR1, and the Nth block region REG\_N may include, for example, blocks in a center of the cell region CR1. Accordingly, a channel hole diameter of strings included in the first block region REG1 may be smaller than a channel hole diameter of strings included in the Nth block region REG\_N. Thus, under the same bias condition, an erase speed with respect to memory cells included in the first block region REG1 may be faster than an erase speed with respect to memory cells included in the Nth block region REG\_N.

According to an exemplary embodiment, bias conditions of an erase operation may be set with respect to each block region to reduce the erase speed with respect to the first block region REG1. Accordingly, a threshold voltage distribution of erased memory cells included in the first block region REG1 may be adjusted to be similar to a threshold voltage distribution of erased memory cells included in the Nth block region REG\_N. Hereinafter, bias conditions for block regions of an erase operation will be described. The bias conditions described below include various operation



parameters. According to exemplary embodiments, some of the operation parameters may be applied only, or other operation parameters may be additionally applied.

In an exemplary embodiment, during an erase operation on the first block region REG1, a first erase voltage Vers1 may be applied to a substrate SUB, and during an erase operation on the Nth block region REG\_N, a second erase voltage Vers2 that is higher than the first erase voltage Vers1 may be applied to the substrate SUB. In an exemplary embodiment, during the erase operation on the first block region REG1, a first word line erase voltage Vwe1 may be applied to a word line WL, and during the erase operation on the Nth block region REG\_N, a second word line erase voltage Vwe2 that is lower than the first word line erase voltage Vwe1 may be applied to the word line WL.

In an exemplary embodiment, an erase operation may be performed on the first block region REG1 during a first erase duration Ters1, and an erase operation may be performed on the Nth block region REG\_N during a second erase duration Ters2 that is longer than the first erase duration Ters1. In an exemplary embodiment, during an erase verify operation on the first block region REG1, a first erase verify voltage Vevr1 may be applied, and during an erase verify operation on the Nth block region REG\_N, a second erase verify voltage Vevr2 that is higher than the first erase verify voltage Vevr1 may be applied.

However, the present inventive concept is not limited to the above, and if blocks included in the plurality of cell regions CR1 through CR4 of the memory cell array 110b illustrated in FIG. 4 are simultaneously selected during an erase operation, since the memory device 100a may not include a constant voltage source separately allocated to each cell regions, different parameters need not be applied according to the block regions.

FIG. 37 is a graph showing erase voltages of blocks according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 37, a horizontal axis denotes positions of blocks in the second direction of FIG. 9, that is, an extension direction of a bit line, and a vertical axis denotes an erase voltage. As described above with reference to FIG. 11, a threshold voltage of erased memory cells included in a cell region may have an inverted U shape according to block positions. In an exemplary embodiment, to compensate for an erase speed with respect to the block positions as described above, a first erase voltage may be set with respect to block regions disposed in an edge region of a cell region, for example, block regions adjacent to an edge, and a second erase voltage may be set with respect to block regions in a center of the cell region. In an exemplary embodiment, the second erase voltage may be greater than the first erase voltage.

For example, blocks included in a cell region may be divided into three block regions based on a distance with respect to two edges of the cell region. Block regions may be set such that blocks that are most adjacent to the two edges of the cell region are included in a first block region, and blocks that are second most adjacent to the two edges of the cell region are included in a second block region, and blocks in a center of the cell region are included in a third block region. Hereinafter, erase operation parameters regarding the first through third block regions will be described.

In an exemplary embodiment, the lowest erase voltage may be set with respect to the first block region, and an intermediate erase voltage may be set with respect to the second block region, and the highest erase voltage may be

set with respect to the third block region. In an exemplary embodiment, an erase voltage may be increased stepwise from an edge of a cell region towards a center of the cell region.

FIG. 38 is a graph showing word line erase voltages of respective blocks according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 38, a horizontal axis denotes positions of blocks in an extension direction of a bit line, and a vertical axis denotes a word line erase voltage. In an exemplary embodiment, to compensate for an erase speed with respect to the block positions as described above, a first word line erase voltage may be set with respect to block regions adjacent to an edge of a cell region, and a second word line erase voltage may be set with respect to block regions in a center of the cell region. In an exemplary embodiment, the second word line erase voltage may be smaller than the first word line erase voltage.

In an exemplary embodiment, to reduce an erase speed with respect to a first block region, a highest word line erase voltage may be set as a word line erase voltage applied to word lines connected to the first block region. Accordingly, as a difference between a word line erase voltage and an erase voltage applied to a substrate is reduced, an erase speed with respect to the first block region may be reduced. Also, an intermediate word line erase voltage may be set as a word line erase voltage with respect to a second block region, and a lowest word line erase voltage may be set as a word line erase voltage with respect to a third block region. In an exemplary embodiment, a word line erase voltage may be reduced stepwise from an edge of a cell region towards a center of the cell region.

FIG. 39 is a graph showing erase verify voltages of blocks according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 39, a horizontal axis denotes positions of blocks in an extension direction of a bit line, and a vertical axis denotes an erase verify voltage. In an exemplary embodiment, to compensate for an erase speed according to the block positions as described above, a first erase verify voltage may be set with respect to block regions adjacent to an edge of a cell region, and a second erase verify voltage may be set with respect to block regions in a center of the cell region.

In an exemplary embodiment, as an erase speed with respect to a first block region is high and thus a threshold voltage level of the first block region after an erase operation under the same bias conditions may be lower than blocks closer to the center of the cell region. Accordingly, a lowest erase verify voltage may be set as an erase verify voltage with respect to the first block region. Also, an intermediate erase verify voltage may be set as an erase verify voltage with respect to a second block region, and a highest erase verify voltage may be set as an erase verify voltage with respect to a third block region. In an exemplary embodiment, an erase verify voltage may be increased stepwise from an edge towards a center of the cell region.

FIG. 40 is a table PAR\_TABLE3 showing bias conditions of a read operation according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 40, the table PAR\_TABLE3 shows bias conditions of a read operation with respect to a first block region REG1 and an Nth block region REG\_N. For example, the table PAR\_TABLE3 may be stored in the parameter information storing unit 122 of FIG. 15. The present inventive concept is not limited thereto, and in an



exemplary embodiment, the table PAR\_TABLE3 may further include bias conditions of a read operation on other block regions.

The first block region REG1 may include, for example, blocks adjacent to first and second edges EDG1 and EDG2 of a cell region CR1, and the Nth block region REG\_N may include, for example, blocks in a center of the cell region CR1. Accordingly, a channel hole diameter of strings included in the first block region REG1 may be smaller than a channel hole diameter of strings included in the Nth block region REG\_N. Thus, a probability of a read disturb with respect to memory cells included in the first block region REG1 due to Fowler-Nordheim (FN) stress may be higher than a probability of a read disturb with respect to memory cells of the other block regions closer to a center of the cell region CR1.

According to an exemplary embodiment, bias conditions of a read operation may be set with respect to respective block regions to compensate for a read disturb with respect to the first block region REG1. Hereinafter, bias conditions of a read operation according to positions of block regions will be described. The bias conditions described below include various operation parameters. According to an exemplary embodiment, some of the operation parameters may be applied only or other operation parameters may be additionally applied.

In an exemplary embodiment, during a read operation on the first block region REG1, a first read determination voltage Vrd1 may be applied to a selected word line WL\_sel, and during a read operation on the Nth block region REG\_N, a second read determination voltage Vrd2 that is higher than the first read determination voltage Vrd1 may be applied to the selected word line WL\_sel. In an exemplary embodiment, during a read operation on the first block region REG1, a first read inhibit voltage Vinhr1 may be applied to a non-selected word line WL\_unsel, and during a read operation on the Nth block region REG\_N, a second read inhibit voltage Vinhr2 that is higher than the first read inhibit voltage Vinhr1 may be applied to the non-selected word line WL\_unsel.

For example, during a read operation, a plurality of memory cells included in a page connected to one word line may be simultaneously read or only some of the memory cells may be read. As distances between each memory cell of one page and a peripheral circuit are different, read environments with respect to the memory cells may vary due to a difference in word line resistance or noise. Thus, if the number of memory cells to be read among a plurality of memory cells included in one page is modified, operation parameters corresponding to block regions may be modified or operation parameters determined for each block region may not be applied.

However, the present inventive concept is not limited to the above, and if blocks included in the plurality of cell regions CR1 through CR4 of the memory cell array 110b illustrated in FIG. 4 are simultaneously selected during a read operation, since the memory device 100a need not include a constant voltage source separately allocated to each cell region, different parameters need not be applied according to a position of each block region.

FIG. 41 is a graph showing read determination voltages of respective blocks according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 41, a horizontal axis denotes positions of blocks in the second direction of FIG. 9, for example, an extension direction of a bit line, and a vertical axis denotes a read determination voltage. As described above with

reference to FIG. 9, diameters of channel holes included in a cell region may be different according to block positions. In an exemplary embodiment, to compensate for a difference in channel hole diameters according to block positions, a first read determination voltage may be set with respect to block regions disposed in an edge region of a cell region, that is, block regions adjacent to an edge, and a second read determination voltage may be set with respect to block regions in a center of the cell region. In an exemplary embodiment, the second read determination voltage may be greater than the first read determination voltage.

For example, blocks included in a cell region may be divided into three block regions based on a distance with respect to two edges of the cell region. Block regions may be set such that blocks that are most adjacent to the two edges of the cell region are included in a first block region, and blocks that are second most adjacent to the two edges of the cell region are included in a second block region, and blocks in a center of the cell region are included in a third block region. Hereinafter, read operation parameters regarding the first through third block regions will be described.

In an exemplary embodiment, the lowest read determination voltage may be set with respect to the first block region, and an intermediate read determination voltage may be set with respect to the second block region, and the highest read determination voltage may be set with respect to the third block region. In an exemplary embodiment, a read determination voltage may be increased stepwise from an edge towards a center of a cell region.

FIG. 42 is a graph showing read inhibit voltages of blocks according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 42, a horizontal axis denotes positions of blocks in an extension direction of a bit line, and a vertical axis denotes a read inhibit voltage. In an exemplary embodiment, to compensate for a difference in channel hole diameters according to block positions, a first read inhibit voltage may be set with respect to block regions adjacent to an edge of a cell region, and a second read inhibit voltage may be set with respect to block regions in a center of the cell region. In an exemplary embodiment, the second read inhibit voltage may be greater than the first read inhibit voltage.

In an exemplary embodiment, a lowest read inhibit voltage may be set with respect to a first block region, an intermediate read inhibit voltage may be set with respect to a second block region, and a highest read inhibit voltage may be set with respect to a third block region. In an exemplary embodiment, a read inhibit voltage may be increased stepwise from an edge towards a center of a cell region.

FIG. 43 illustrates a memory device 100b according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 43, the memory device 100b may include a memory cell array 110a, a control logic 120b, a row decoder 140a, and a page buffer 150a. The memory device 100b is similar to the memory device 100a of FIG. 15, and description will focus on differences from FIG. 15. In an exemplary embodiment, the memory device 100b may include the memory cell array illustrated in FIG. 17, FIG. 19, FIG. 21 or FIG. 24, and a method of setting block regions in a memory cell array may vary according to an exemplary embodiment.

According to an exemplary embodiment, a control logic 120b may include a block region information storing unit 121, a parameter information storing unit 122a, an operation controller 123a, and a cycle information storing unit 124.



Compared with the control logic **120** of FIG. **15**, the control logic **120b** may further include the cycle information storing unit **124**.

The block region information storing unit **121** may store information about block regions of a cell region **CR1** included in the memory cell array **110a**. The block region information may be generated by dividing a plurality of blocks into at least two block regions based on a distance with respect to a relatively close edge among first and second edges **EDG1** and **EDG2** of the cell region **CR1**. In an exemplary embodiment, block region information may be stored as a table showing block regions for corresponding blocks.

The cycle information storing unit **124** may store information about a P/E cycle count with respect to a plurality of blocks **BLK1** through **BLK10** included in the memory cell array **110a**. The P/E cycle count refers to the number of times of P/E cycles. The cycle information storing unit **124** may be implemented using a latch. In an exemplary embodiment, cycle information may be stored in a region of the memory cell array **110a**. In an exemplary embodiment, cycle information may be stored in a buffer memory of a memory controller. In an exemplary embodiment, cycle information may be stored in an additional non-volatile memory included in a memory system.

FIG. **44** is a graph showing a threshold voltage distribution of the first and second blocks **BLKa** and **BLKb** of FIG. **9**.

Referring to FIG. **44**, a horizontal axis denotes a threshold voltage  $V_{th}$ , and a vertical axis denotes the number of memory cells. The threshold voltage distribution denotes a distribution of the first and second blocks **BLKa** and **BLKb** corresponding to a P/E cycle count with respect to the first and second blocks **BLKa** and **BLKb**, which is equal to or higher than a threshold value. A dotted line **431** denotes a threshold voltage distribution with respect to the first block **BLKa**, and a solid line **432** denotes a threshold voltage distribution with respect to the second block **BLKb**.

An erase speed with respect to memory cells included in the first block **BLKa** may be initially relatively high, but may be relatively reduced as the P/E cycle count increases because a program speed and an erase speed of the memory cells included in the first block **BLKa** are relatively high so that a variation in a threshold voltage in the memory cells increases according to an increase in the P/E cycle count, thereby speeding up deterioration of the memory cells.

As a result, data in the memory cells may not be easily erased due to charges trapped in a charge storage layer included in the memory cells (for example, the charge storage layer **CS** of FIG. **5**). Consequently, if a P/E cycle count is equal to or higher than a threshold value, as an upper voltage level of an erase state **E** of the first block **BLKa** increases, an EPI valley ( $A_{cycled}$ ) of the first block **BLKa** may be smaller than an EPI valley ( $B_{cycled}$ ) of the second block **BLKb** (i.e.,  $A_{cycled} < B_{cycled}$ ).

On the other hand, a program speed with respect to the memory cells included in the first block **BLKa** may be further increased according to an increase in the P/E cycle count. In addition, an upper voltage level of the first through third program states **P1** through **P3** may be further increased due to charges trapped in the charge storage layer included in the memory cells included in the first block **BLKa**. As a result, if a P/E cycle count is equal to or higher than a threshold value, as an upper voltage level of the first through third program states **P1** through **P3** of the first block **BLKa** increases, valleys between the first through third program states **P1** through **P3** may be moved to be higher.

As described above, as a P/E cycle count increases, a deterioration speed of memory cells having a relatively small channel hole diameter may be increased. In the present exemplary embodiment, a channel hole diameter of the first block region **REG1** adjacent to the first and second edges **EDG1** and **EDG2** of the cell region **CR1** may be smaller than that of the  $N$ th block region **REG\_N** in a center of the cell region **CR1**. Accordingly, the memory cells included in the first block region **REG1** may be deteriorated further as the P/E cycle count increases.

Referring to FIG. **43** again, in the present exemplary embodiment, operation parameters to be applied may be modified based on a P/E cycle count. In an exemplary embodiment, an increase in a program speed of the first block region **REG1** according to an increase in a P/E cycle count may be reduced by changing program operation parameters. In an exemplary embodiment, a slowdown in an erase operation due to deterioration of the first block region **REG1** according to an increase in a P/E cycle count may be reduced by changing erase operation parameters. In an exemplary embodiment, a read error due to a shift of a valley according to an increase in a P/E cycle count may be reduced by changing read operation parameters.

In an exemplary embodiment, if a P/E cycle count is equal to or less than a threshold value, a reference bias condition in which the same operation parameters are commonly applied to block regions may be applied, and if a P/E cycle count is greater than the threshold value, each block region may have bias condition of operation parameters different from each other. In an exemplary embodiment, if a P/E cycle count is equal to or less than a threshold value, each block region may have a first bias condition of operation parameters different from each other, and if a P/E cycle count is greater than the threshold value, each block region may have a second bias condition of operation parameters different from each other. The second bias condition may be generated by modifying some of the operation parameters having the first bias condition.

The parameter information storing unit **122a** may store information about operation parameters of at least two block regions. The operation parameters may have bias conditions for program, erase, and read operations. In an exemplary embodiment, parameter information may be stored as a table including bias conditions of the operation parameters for each block region.

In an exemplary embodiment, the parameter information storing unit **122a** may store a first table including reference operation parameters according to the reference bias condition that is commonly applied to a plurality of block regions and a second table including different bias conditions with respect to each block region according to the first bias condition. In an exemplary embodiment, the parameter information storing unit **122a** may store a second table including different bias conditions with respect to each block region according to the first bias condition and a third table including different bias conditions with respect to each block region according to the second bias condition. In an exemplary embodiment, the parameter information storing unit **122a** may store all of the first through third tables.

The operation controller **123a** may control an operation on each block region of the memory cell array **110a** using block region information, parameter information, and cycle information. For example, the operation controller **123a** may select bias conditions for operation parameters according to a P/E cycle count, and control an operation performed on each block region of the memory cell array **110a** using the selected bias conditions.



In an exemplary embodiment, the operation controller **123a** may determine a P/E cycle count, and if the P/E cycle count is equal to or less than a threshold value, the operation controller **123a** may select parameter information for a reference operation parameter and control an operation using the reference operation parameter. If the P/E cycle count is greater than the threshold value, the operation controller **123a** may search block region information for a block corresponding to an address, search parameter information, for example, bias conditions, for an operation parameter corresponding to the block region, and control an operation by using the selected bias conditions.

In an exemplary embodiment, the operation controller **123a** may search block region information for a block corresponding to an address, and determine a P/E cycle count. If the P/E cycle count is equal to or less than a threshold value, the operation controller **123a** may search parameter information for an operation parameter corresponding to the block region, and control an operation by using the operation parameter corresponding to the block region. If a P/E cycle count is greater than the threshold value, the operation controller **123a** may search modified parameter information for operation parameters corresponding to a block region and control an operation by using the modified operation parameter information corresponding to the block region.

FIG. **45** is a flowchart of an example of a method of operating a memory device according to an exemplary embodiment of the present inventive concept.

According to operation steps of FIG. **45**, a control logic may control an operation on a memory cell array when a command and an address are received from a memory controller. The method may include, for example, operations that are sequentially performed in the control logic **120b** of FIG. **43**. The description provided with reference to FIG. **43** may also apply to the method of the present exemplary embodiment, and repeated description will be omitted.

In operation **S310**, a command and an address are received from a memory controller. In operation **S320**, whether an operation cycle is equal to or less than a threshold value is determined. In an exemplary embodiment, the operation cycle may be a P/E cycle count. In an exemplary embodiment, the operation cycle may be a read cycle count. If the operation cycle is equal to or less than the threshold value, operation **S330** is performed, and otherwise, operation **S340** is performed. However, the present inventive concept is not limited thereto, and in an exemplary embodiment, whether an operation cycle is less than a threshold value may be determined in operation **S320**. In this case, if the operation cycle is less than the threshold value, operation **S330** may be performed, and otherwise, operation **S340** may be performed.

In operation **S330**, an operation on a memory cell array is controlled using a reference operation parameter. If the P/E cycle count is less than the threshold value, the operation controller **123a** may perform a program, erase or read operation on memory cells disposed in the cell region **CR1** of the memory cell array **110a** by using the same reference operation parameter, regardless of block positions in the cell region **CR1**. The threshold value may be set to a P/E cycle count below which the characteristics of memory cells are not deteriorated to cause errors. For example, if the P/E cycle count increases beyond the threshold number, memory cells closest to the edges **EDG1** and **EDG2** may start to deteriorate due to the small channel hole diameter sizes.

In operation **S340**, a block region corresponding to the received address is searched for. For example, the operation

controller **123a** may search the block region information storing unit **121** for a block region corresponding to the address.

In operation **S350**, an operation parameter corresponding to the block region is searched for. For example, the operation controller **123a** may search the parameter information storing unit **122a** for an operation parameter corresponding to the block region.

In operation **S360**, an operation on a memory cell array is performed using the operation parameter chosen in operation **S350**.

FIG. **46** is a flowchart of a method of operating a memory device according to an exemplary embodiment of the present inventive concept.

According to an exemplary operation steps of FIG. **46**, the control logic **120b** of FIG. **43** may operate a memory device. The description provided with reference to FIG. **43** may apply to the method of the present exemplary embodiment, and repeated description will be omitted.

In operation **S410**, a command and an address are received from a memory controller. In operation **S420**, a block region corresponding to the received address is searched for. For example, the operation controller **123a** may search the block region information storing unit **121** for a block region corresponding to the address.

In operation **S430**, whether an operation cycle is equal to or less than a threshold value is determined. [Note to client: operation cycle is counted per block region?] In an exemplary embodiment, the operation cycle may be a P/E cycle count. In an exemplary embodiment, the operation cycle may be a read cycle count. If the operation cycle is equal to or less than the threshold value, operation **S440** is performed, and otherwise, operation **S460** is performed. However, the present inventive concept is not limited thereto, and in an exemplary embodiment, whether an operation cycle is less than a threshold value may be determined in operation **S430**. In this case, if the operation cycle is less than the threshold value, operation **S440** may be performed, and otherwise, operation **S460** may be performed.

In operation **S440**, an operation parameter corresponding to a block region is searched for. For example, the operation controller **123a** searches the parameter information storing unit **122a** for an operation parameter. The operation parameter may correspond to the first bias condition illustrated in FIG. **47**, FIG. **48** or FIG. **49**. In operation **S450**, an operation on a memory cell array is controlled using the operation parameter chosen in the operation **S440**.

In operation **S460**, modified operation parameter information corresponding to the block region is searched for. For example, the operation controller **123a** searches the parameter information storing unit **122a** to select modified operation parameter information corresponding to the selected block region. The modified operation parameter information may include the second bias condition illustrated in FIG. **47**, FIG. **48** or FIG. **49**. In operation **S470**, an operation on a memory cell array is controlled using the modified operation parameter information.

FIG. **47** is a table **PAR\_TABLE4** showing bias conditions of a program operation according to an exemplary embodiment of the present inventive concept.

Referring to FIG. **47**, the table **PAR\_TABLE4** shows bias conditions of a program operation on the first block region **REG1** and the Nth block region **REG\_N**. For example, the table **PAR\_TABLE4** may be stored in the parameter information storing unit **122a** of FIG. **43**. The present inventive concept is not limited thereto, and in an exemplary embodi-



ment, the table PAR\_TABLE4 may further include bias conditions of a program operation on other block regions.

The table PAR\_TABLE4 may include a reference bias condition that is commonly applied to block regions, irrespective of the locations of the block regions, a first bias condition that is applied to each block region, and a second bias condition that is applied to each block region. The second bias condition may be generated by modifying some of operation parameters included in the first bias condition. In an exemplary embodiment, the table PAR\_TABLE4 may include only the reference bias condition and the first bias condition. In an exemplary embodiment, the table PAR\_TABLE4 may include only the first and the second bias conditions.

The reference bias condition may be applied commonly to a plurality of block regions included in a cell region. In an exemplary embodiment, a program operation may be performed on a memory cell array by using the reference bias condition during an initial program loop. The first bias condition may be differently set for each block region. The first bias condition of the table PAR\_TABLE4 is the same as the bias condition of FIG. 29, and thus detailed description thereof will be omitted.

The second bias condition may be different for each block region, and may be applied when a P/E cycle count is greater than a threshold value. In an exemplary embodiment, the second bias condition may be generated by modifying some of operation parameters with respect to the first block region REG1, included in the first bias condition. In an exemplary embodiment, the second bias condition may be generated by modifying some of operation parameters with respect to the Nth block region REG\_N, included in the first bias condition. In an exemplary embodiment, the second bias condition may be generated by modifying some of operation parameters with respect to the first block region REG1 and the Nth block region REG\_N, included in the first bias condition.

As a P/E cycle count increases, a program speed of memory cells included in the first block region REG1 may be further increased due to deterioration of the memory cells included in the first block region REG1 having a relatively small channel hole diameter. Thus, in the present exemplary embodiment, if a P/E cycle count is greater than a threshold value, a difference between a program voltage with respect to the first block region REG1 and a program voltage with respect to the Nth block region REG\_N may be further increased, thereby compensating for a difference in program speeds of each block region. For example, a difference in program speed of each block may be compensated for by slowing down a program speed with respect to the first block region REG1.

Hereinafter, a second bias condition of block regions of a program operation will be described. The second bias condition described below includes various operation parameters. According to an exemplary embodiment, some of the operation parameters may be applied, or other operation parameters may be additionally applied.

In an exemplary embodiment, during a program operation on the first block region REG1, a first modified program voltage Vpgm1' that is lower than a first program voltage Vpgm1 may be applied to a selected word line WL\_sel, and during a program operation on the Nth block region REG\_N, a second program voltage Vpgm2 may be applied to the selected word line WL\_sel. Accordingly, a difference between the first modified program voltage Vpgm1' and the second program voltage Vpgm2 may be greater than a difference between the first program voltage Vpgm1 and the

second program voltage Vpgm2. For example, the first program voltage Vpgm1 may be lower than the second program voltage Vpgm2 by 1 V under the first bias condition, and the modified first program voltage Vpgm1' may be lower than the second program voltage Vpgm2 by 1.5 V.

In an exemplary embodiment, a program operation may be performed on the first block region REG1 during a first modified program duration Tpgm1' that is shorter than a first program duration Tpgm1, and a program operation may be performed on the Nth block region REG\_N during a second program duration Tpgm2. Accordingly, a difference between the first modified program duration Tpgm1' and the second program duration Tpgm2 may be greater than a difference between the first program duration Tpgm1 and the second program duration Tpgm2.

According to an exemplary embodiment, a program voltage may be increased with respect to the first block region REG1 by a first modified program voltage increment Vinc1' that is smaller than a first program voltage increment Vinc1 as a value of a loop increases. In an exemplary embodiment, a program duration may be increased with respect to the first block region REG1 by a first modified time increment Tinc1' that is shorter than the first time increment Tinc1, as a value of a loop increases.

In an exemplary embodiment, a verify operation may be skipped only during a first modified verify skip loop Ls1' that is of a value equal to or smaller than a first verify skip loop Ls1 with respect to the first block region REG1. In an exemplary embodiment, a first modified maximum loop Lm1' that is of a value equal to or smaller than a first maximum loop may be set with respect to the first block region REG1.

In an exemplary embodiment, a first modified Vinhp1' that is lower than a first program inhibit voltage Vinhp1 may be applied to a non-selected word line WL\_unsel included in the first block region REG1. In an exemplary embodiment, during a program verify operation on the first block region REG1, a first modified program verify operation voltage Vpvrfl' that is higher than a first program verify voltage Vpvrfl may be applied.

FIG. 48 is a table PAR\_TABLE5 showing bias conditions of an erase operation according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 48, the table PAR\_TABLE5 shows bias conditions with respect to an erase operation on the first block region REG1 and the Nth block region REG\_N. For example, the table PAR\_TABLE5 may be stored in the parameter information storing unit 122a of FIG. 43. The present inventive concept is not limited thereto, and in an exemplary embodiment, the table PAR\_TABLE5 may further include bias conditions with respect to an erase operation on other block regions.

According to an exemplary embodiment, the table PAR\_TABLE5 may include a reference bias condition that is commonly applied to block regions, a first bias condition that is applied to each block region, and a second bias condition that is applied to each block region. The second bias condition may be generated by modifying some of operation parameters included in the first bias condition. In an exemplary embodiment, the table PAR\_TABLE5 may include only the reference bias condition and the first bias condition. In an exemplary embodiment, the table PAR\_TABLE5 may include only the first and second bias conditions.

The reference bias condition may be applied commonly to a plurality of block regions included in a cell region. In an exemplary embodiment, an erase operation may be per-



formed on a memory cell array by using the reference bias condition during an initial program loop. The first bias condition may be differently set according to positions of block regions. The first bias condition may be substantially the same as the bias condition described with reference to FIG. 25, and thus detailed description thereof will be omitted.

The second bias condition may be differently set according to positions of block regions, and may be applied when a P/E cycle count is greater than a threshold value. In an exemplary embodiment, the second bias condition may be generated by modifying some of the first bias condition of the first block region REG1. In an exemplary embodiment, the second bias condition may be generated by modifying some of the first bias condition of the Nth block region REG\_N. In an exemplary embodiment, the second bias condition may be generated by modifying some of the first bias conditions of the first block region REG1 and the Nth block region REG\_N.

As a P/E cycle count increases, charges may be trapped in a charge storage layer of memory cells included in the first block region REG1 due to deterioration of the memory cells included in the first block region REG1 having a first channel hole diameter smaller than a second channel hole diameter of memory cells in the Nth block region REG\_N, and accordingly, a threshold voltage of erased memory cells may be increased. Thus, in an exemplary embodiment, if a P/E cycle count is greater than a threshold value, an erase voltage with respect to the first block region REG1 may be further increased, thereby compensating for a difference in channel hole diameters of block regions.

Hereinafter, the second bias condition with respect to respective block regions of an erase operation will be described. The second bias condition described below includes various operation parameters. According to an exemplary embodiment, some of the operation parameters may be applied, or other operation parameters may be further applied.

In an exemplary embodiment, during an erase operation on the first block region REG1, a first modified erase voltage Vers1' that is higher than a first erase voltage Vers1 may be applied to a substrate SUB, and during an erase operation on the Nth block region REG\_N, a second erase voltage Vers2 may be applied to the substrate SUB. In an exemplary embodiment, during an erase operation on the first block region REG1, a first modified word line erase voltage Vwe1' that is lower than a first word line erase voltage Vwe1 may be applied to a word line WL, and during an erase operation on the Nth block region REG\_N, a second word line erase voltage Vwe2 may be applied to the word line WL. In an exemplary embodiment, an erase operation may be performed on the first block region REG1 during a first modified erase duration Ters1' that is longer than a first erase duration Ters1, and an erase operation may be performed on the Nth block region REG\_N during a second erase duration Ters2. In an exemplary embodiment, during an erase verify operation on the first block region REG1, a first modified erase verify voltage Vevrf1' that is higher than a first erase verify voltage Vevrf1 may be applied.

FIG. 49 is a table PAR\_TABLE6 showing bias conditions of a read operation according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 49, the table PAR\_TABLE6 shows bias conditions of a read operation on the first block region REG1 and the Nth block region REG\_N. For example, the table PAR\_TABLE6 may be stored in the parameter information storing unit 122a of FIG. 43. The present inventive concept

is not limited thereto, and in an exemplary embodiment, the table PAR\_TABLE6 may further include bias conditions of a read operation on other block regions.

According to an exemplary embodiment, the table PAR\_TABLE6 may include a reference bias condition that is commonly applied to block regions, a first bias condition that is applied according to positions of block regions, and a second bias condition that is applied according to positions of block regions. The second bias condition may be generated by modifying some of operation parameters included in the first bias condition. In an exemplary embodiment, the table PAR\_TABLE6 may include only the reference bias condition and the first bias condition. In an exemplary embodiment, the table PAR\_TABLE6 may include only the first and second bias conditions.

The reference bias condition may be applied commonly to a plurality of block regions included in a cell region. In an exemplary embodiment, if a read cycle count is equal to or less than a threshold value, a read operation may be performed on a memory cell array by using the reference bias condition. The first bias condition may be differently set according to positions of block regions. The first bias condition of FIG. 49 is the same as the bias condition described with reference to FIG. 28, and thus detailed description thereof will be omitted.

The second bias condition may be differently set according to positions of block regions, and may be applied when a P/E cycle count or a read count is greater than a threshold value. In an exemplary embodiment, the second bias condition may be generated by modifying some of operation parameters with respect to the first block region REG1, included in the first bias condition. In an exemplary embodiment, the second bias condition may be generated by modifying some of operation parameters with respect to the Nth block region REG\_N, included in the first bias condition. In an exemplary embodiment, the second bias condition may be generated by modifying some of operation parameters with respect to the first block region REG1 and the Nth block region REG\_N, included in the first bias condition.

As described above with reference to FIG. 44, as a P/E cycle count increases, a program speed with respect to memory cells included in the first block region REG1 having a first channel hole diameter may be further increased so that upper levels of respective program states P1, P2, and P3 are further increased, in compared with memory cells of the Nth block region REG\_N having a second channel hole diameter greater than the first channel hole diameter. Meanwhile, as a P/E cycle count increases, an erase operation on the memory cells included in the first block region REG1 may be improperly performed so that an upper level of the memory cells in an erase level E may also be further increased. Thus, in an exemplary embodiment, if a P/E cycle count is greater than a threshold value, a read determination voltage with respect to the first block region REG1 may be further increased, thereby compensating for a difference in channel hole diameters of block regions.

Hereinafter, a second bias condition of block regions of a read operation will be described. The second bias condition described below includes various operation parameters. According to an exemplary embodiment, some of the operation parameters may be applied, or other operation parameters may be additionally applied.

In an exemplary embodiment, during a read operation on the first block region REG1, a first modified read determination voltage Vrd1' that is higher than a first read determination voltage Vrd1 may be applied to a selected word line WL\_sel, and during a read operation on the Nth block region



47

REG\_N, a second read determination voltage Vrd2 may be applied to the selected word line WL\_sel. In an exemplary embodiment, during a read operation on the first block region REG1, a first modified read inhibit voltage Vinhr1' that is higher than a first read inhibit voltage Vinhr1 may be applied to a non-selected word line WL\_unsel, and during a read operation on the Nth block region REG\_N, a second read inhibit voltage Vinhr2 may be applied to the non-selected word line WL\_unsel.

FIG. 50 is a flowchart of a method of operating a memory device according to an exemplary embodiment of the present inventive concept.

The method of FIG. 50 may include operations that are sequentially performed in the control logic 120b of FIG. 43. The description provided with reference to FIG. 43 may apply to the method of FIG. 50, and repeated description will be omitted.

In operation S510, a command and an address are received from a memory controller. In operation S520, whether an operation cycle is equal to or less than a threshold value is determined. In an exemplary embodiment, the operation cycle may be a P/E cycle count. In an exemplary embodiment, the operation cycle may be a read cycle count. As a result of determining, if the operation cycle is equal to or less than the threshold value, operation S530 is performed, and otherwise, operation S540 is performed. However, the present inventive concept is not limited thereto, and in an exemplary embodiment, whether an operation cycle is less than a threshold value may be determined in operation S520. As a result of determining, if the operation cycle is less than the threshold value, operation S530 may be performed, and otherwise, operation S540 may be performed.

In operation S530, first block region information is searched for a block region corresponding to the address. The first block region information may be information indicating a plurality of blocks in a cell region CR1, divided into at least two block regions according to a first method of setting block regions. In an exemplary embodiment, the first block region information may be applied to an initial cycle stage of a program operation or a read operation. For example, the operation controller 123a may search the first block region information stored in the block region information storing unit 121 for a block region corresponding to the address.

In operation S540, second block region information is searched for a block region corresponding to the address. The second block region information may be information indicating a plurality of blocks in the cell region CR1, divided into at least two block regions according to a second method of setting block regions. In an exemplary embodiment, the second block region information may be applied to an operation after a predetermined cycle of the program operation or the read operation, that is, an operation after a cycle corresponding to a threshold value. For example, the operation controller 123a may search the second block region information stored in the block region information storing unit 121 for a block region corresponding to the address.

In operation S550, an operation parameter corresponding to the block region is searched for. For example, the operation controller 123a searches the parameter information storing unit 122a for the operation parameter. In an exemplary embodiment, the operation controller 123a may search the parameter information storing unit 122a for operation parameters corresponding to a reference bias condition. In

48

operation S560, an operation on a memory cell array is controlled using the operation parameters.

As described above, according to an exemplary embodiment, block regions may be differently set according to operation cycles. For example, according to the first block region information applied to operations prior to a P/E cycle corresponding to a threshold value, a third block BLK3 that is third most adjacent to the first edge EDG1 may correspond to the second block region REG2; according to the second block region information applied to operations after the P/E cycle corresponding to the threshold value, the third block BLK3 may correspond to the first block region REG1. Accordingly, a program operation may be performed on the third block BLK3 by using operation parameters according to the second block region REG2 before prior to the P/E cycle corresponding to the threshold value, and after the P/E cycle corresponding to the threshold value, a program operation may be performed on the third block BLK3 by using operation parameters according to the first block region REG1. [Note to client: Need elaboration]

FIG. 51 is a flowchart of an example of a method of operating a memory device according to an exemplary embodiment of the present inventive concept.

The method of FIG. 51 may include, for example, operations that are sequentially performed in the control logic 120b of FIG. 43. The description provided with reference to FIG. 43 may apply to the method of FIG. 51, and repeated description will be omitted.

In operation S610, a command and an address are received from a memory controller. In operation S620, block region information corresponding to the command is selected from among a plurality of pieces of block region information. For example, if the received command is a program command, block region information corresponding to a program operation may be selected from among the plurality of pieces of block region information included in the table REG\_TABLE6 illustrated in FIG. 28.

In operation S630, the selected block region information is searched for a block region corresponding to the address. For example, if the received address is the third block BLK3, the block region information with respect to the program operation included in the table REG\_TABLE6 illustrated in FIG. 28 may be searched for the second block region REG2 corresponding to the third block BLK3.

In operation S640, whether an operation cycle is equal to or less than a threshold value is determined. In an exemplary embodiment, the operation cycle may be a P/E cycle count. In an exemplary embodiment, the operation cycle may be a read cycle count. As a result of determining, if the operation cycle is equal to or less than the threshold value, operation S650 is performed, and otherwise, operation S670 is performed. However, the inventive concept is not limited thereto, and in an exemplary embodiment, whether an operation cycle is less than a threshold value may be determined in operation S640. As a result of determining, if the operation cycle is less than the threshold value, operation S650 may be performed, and otherwise, operation S670 may be performed.

In operation S650, an operation parameter corresponding to the block region is searched for. For example, the operation controller 123a searches the parameter information storing unit 122a for the operation parameter. The operation parameter may correspond to the first bias condition illustrated in FIG. 47, FIG. 48 or FIG. 49. In operation S660, an operation on a memory cell array is controlled using the operation parameter.



In operation S670, modified operation parameter information is searched for. For example, the operation controller 123a searches the parameter information storing unit 122a to select the modified operation parameter information corresponding to the selected block region. The modified operation parameter information may include the second bias condition illustrated in FIG. 47, FIG. 48 or FIG. 49. In operation S680, an operation on a memory cell array is controlled using the modified operation parameter information.

As described above, according to the present exemplary embodiment, block regions may be differently set according to commands, and different bias conditions may be set according to operation cycles. Thus, performance and reliability of a memory device may be further increased.

FIG. 52 illustrates a memory device 100c according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 52, the memory device 100c may include a memory cell array 110a, a control logic 120c, a row decoder 140a, and a page buffer 150a. The memory device 100c is a modified example of the memory device 100a of FIG. 15, and description provided with reference to FIG. 15 may also apply to the present exemplary embodiment. Here, description will focus on differences from the exemplary embodiment of FIG. 15. In an exemplary embodiment, the memory device 100c may include the memory cell array illustrated in FIG. 17, FIG. 19, FIG. 21 or FIG. 24, and a method of setting block regions in a memory cell array may be modified in various manners.

According to an exemplary embodiment, the control logic 120c may include a block region information storing unit 121, a parameter information storing unit 122b, an operation controller 123b, and a data retention period information storing unit 125. Compared with the control logic 120 illustrated in FIG. 15, the control logic 120c of FIG. 52 may further include the data retention period information storing unit 125.

The block region information storing unit 121 may store information about block regions of a cell region CR1 included in the memory cell array 110a. In an exemplary embodiment, block region information may be generated by dividing a plurality of blocks into at least two block regions based on a distance with respect to a relatively close edge among first and second edges EDG1 and EDG2 of the cell region CR1. In an exemplary embodiment, block region information may be stored as a table showing block regions for corresponding blocks.

The data retention period information storing unit 125 may store information about a data retention period with respect to each block of a plurality of blocks BLK1 through BLK10 included in the memory cell array 110a. The data retention period information storing unit 125 may be implemented using a latch. In an exemplary embodiment, data retention period information may be stored in a region of the memory cell array 110a. In an exemplary embodiment, data retention period information may be stored in a buffer memory of a memory controller. In an exemplary embodiment, data retention period information may be stored in an additional non-volatile memory included in a memory system.

In an exemplary embodiment, a data retention period may be determined based on a program order stamp (POS) indicating a relative order among program operations. For example, the data retention period information storing unit 125 may store a POS allocated to a memory cell when a program operation or an erase operation is performed on the memory cell, and when a new POS is allocated to a memory

cell, the data retention period information storing unit 125 may update the data retention period information. In an exemplary embodiment, the data retention period information storing unit 125 may sequentially store POSs according to respective block regions. In an exemplary embodiment, the data retention period information storing unit 125 may sequentially store block regions according to respective POSs.

FIG. 53A is a graph showing a threshold voltage distribution after programming of a memory device is completed.

Referring to FIG. 53A, a horizontal axis denotes a threshold voltage  $V_{th}$ , and a vertical axis denotes the number of memory cells. The memory cells may be the memory cells illustrated in FIG. 5 or FIG. 6. When a memory cell is a multi-level cell that is programmed to two bits, the memory cell may have one of an erase state E, a first program state P1, a second program state P2, and a third program state P3.

Each of first through third read voltages Vr1, Vr2, and Vr3 corresponds to an initially set default level. For example, the first read voltage Vr1 has a voltage level between a distribution of memory cells MC having the erase state E and a distribution of memory cells MC having the first program state P1. The second read voltage Vr2 has a voltage level between a distribution of memory cell MC having the first program state P1 and a distribution of memory cell MC having the second program state P2. The third read voltage Vr3 has a voltage level between a distribution of memory cell MC having the second program state P2 and a distribution of memory cell MC having the third program state P3.

FIG. 53B is a graph showing a threshold voltage distribution according to a threshold voltage after a predetermined duration has passed after programming of the memory device having the threshold voltage distribution of FIG. 53A is completed.

Referring to FIG. 53B, the two adjacent threshold voltage distributions may overlap each other. For example, the shaded portion indicates the overlapped portion of two adjacent threshold voltage distribution due to the increase of data retention periods. Since the read voltages Vr1 to Vr3 fall to the shaded regions, a read error may be caused in memory cells corresponding to the shaded portion of FIG. 53B, and accordingly, reliability of the memory device may be decreased.

For example, when performing a read operation on a memory device by using the first read voltage Vr1, even though memory cells MC corresponding to the shaded portion are programmed to the first program state P1, they may be determined to be in the erase state E. Consequently, an error may be generated in a read operation, and reliability of the memory device may decrease.

Referring to FIG. 52 again, operation parameters to be applied may be modified based on a data retention period. In an exemplary embodiment, to compensate for a reduction in a threshold voltage of the first through third program states P1, P2, and P3 due to an increase in a data retention period, a program voltage may be further increased as the data retention period increases, thereby increasing lower voltage levels of the first through third program states P1, P2, and P3. In an exemplary embodiment, to compensate for an increase in a threshold voltage of the erase state E due to an increase in a data retention period, an erase voltage applied to a substrate may be further increased as the data retention period increases, thereby increasing an upper voltage level of the erase state E. In an exemplary embodiment, to compensate for a shift of a valley due to an increase in a data



retention period, a read determination voltage may be further reduced as the data retention period increases.

In an exemplary embodiment, if a data retention period is equal to or less than a threshold value, a reference bias condition in which the same operation parameters are commonly applied to block regions, and if a data retention period is greater than the threshold value, a first bias condition in which operation parameters are different according to positions of block regions may be applied. In an exemplary embodiment, if a data retention period is equal to or less than a threshold value, the first bias condition in which operation parameters are different according to positions of block regions may be applied, and if a data retention period is greater than the threshold value, a second bias condition in which operation parameters are different according to positions of block regions may be applied. The second bias condition may be generated by modifying some of the operation parameters included in the first bias condition.

The parameter information storing unit **122b** may store information about operation parameters respectively corresponding to at least two block regions. The operation parameters represent parameters that constitute bias conditions for program, erase, and read operations. In an exemplary embodiment, parameter information may be stored as a table showing operation parameters for each block region.

In an exemplary embodiment, the parameter information storing unit **122b** may store a first table including a reference bias condition that is commonly applied to a plurality of block regions and a second table including a first bias condition for each block region. In an exemplary embodiment, the parameter information storing unit **122b** may store a second table including a first bias condition for each block region and a third table including a second bias condition for each block region. In an exemplary embodiment, the reference bias condition, the first bias condition may be different from the second bias condition. In an exemplary embodiment, the parameter information storing unit **122b** may store all of the first through third tables.

The operation controller **123b** may control an operation performed on each block region in the memory cell array **110a** according to block region information, parameter information (bias conditions for operation parameters), and data retention period information. For example, the operation controller **123b** may select bias conditions for operation parameters based on a data retention period, and control an operation performed on each block region of the memory cell array **110a** using the selected bias conditions.

In an exemplary embodiment, the operation controller **123b** may determine a data retention period, and if the data retention period is equal to or less than a threshold value, the operation controller **123a** may search parameter information, for example, reference bias conditions, for a reference operation parameter and control an operation by using the reference bias conditions. If the data retention period is greater than the threshold value, the operation controller **123b** may search block region information for a block corresponding to an address, search parameter information, for example, bias conditions, for an operation parameter corresponding to the block region, and control an operation by using the operation parameter corresponding to the block region.

In an exemplary embodiment, the operation controller **123b** may search block region information for a block corresponding to an address, and determine a data retention period. If the data retention period is equal to or less than a threshold value, the operation controller **123b** may search parameter information for an operation parameter corre-

sponding to the block region, and control an operation by using the operation parameter corresponding to the block region. If the data retention period is greater than the threshold value, the operation controller **123b** may search modified parameter information for operation parameters corresponding to the block region and control an operation by using the modified operation parameter information corresponding to the block region. In an exemplary embodiment, the parameter information may include bias conditions for operation parameters.

Although not illustrated, in an exemplary embodiment, the control logic **120c** may further include the cycle information storing unit **124** illustrated in FIG. **43**. The control logic **120c** may select a bias condition based on cycle information and data retention period information, and may control an operation performed on each block region in a memory cell array by using the selected bias condition.

FIG. **54** is a flowchart of an example of a method of operating a memory device according to an exemplary embodiment of the present inventive concept.

Referring to FIG. **54**, a method of controlling an operation on a memory cell array may be performed in a control logic when a command and an address are received from a memory controller. The method may include, for example, operations that are sequentially performed in the control logic **120c** of FIG. **52**. The description provided with reference to FIG. **52** may apply to the method of the present exemplary embodiment, and repeated description will be omitted.

In operation **S710**, a command and an address are received from a memory controller. In operation **S720**, whether a POS is equal to or less than a threshold value is determined. As a result of determining, if the POS is equal to or less than the threshold value, operation **S730** is performed, and otherwise, operation **S740** is performed. However, the present inventive concept is not limited thereto, and in an exemplary embodiment, whether a POS is less than a threshold value may be determined in operation **S720**. As a result of determining, if the POS is less than the threshold value, operation **S730** may be performed, and otherwise, operation **S740** may be performed.

In operation **S730**, an operation on a memory cell array is controlled using reference operation parameter information. If a POS is less than a threshold value, spreading of threshold voltage distributions of memory cells may be relatively small to the extent that no overlaps between adjacent threshold voltage distributions occur. Thus, the operation controller **123b** may control a program, erase or read operation on performed the cell region **CR1** of the memory cell array **110a** using the same reference operation parameter information.

In operation **S740**, a block region corresponding to the received address is searched for. For example, the operation controller **123b** may search the block region information storing unit **121** for a block corresponding to the address. In operation **S750**, an operation parameter corresponding to the block region is searched for. For example, the operation controller **123b** may search the parameter information storing unit **122b** for operation parameter information corresponding to the block region. In operation **S760**, an operation on a memory cell array is controlled using the operation parameter information.

FIG. **55** is a flowchart of an example of a method of operating a memory device according to an exemplary embodiment of the present inventive concept.

Referring to FIG. **55**, operations may be sequentially performed in the control logic **120c** of FIG. **52**. The descrip-



tion provided with reference to FIG. 52 may apply to the method of the present exemplary embodiment, and repeated description will be omitted.

In operation S810, a command and an address are received from a memory controller. In operation S820, a block region corresponding to the received address is searched for. For example, the operation controller 123b may search the block region information storing unit 121 for a block corresponding to the address. In operation S830, whether a POS is equal to or less than a threshold value is determined. As a result of determining, if the POS is equal to or less than the threshold value, operation S840 is performed, and otherwise, operation S860 is performed. However, the present inventive concept is not limited thereto, and in an exemplary embodiment, whether a POS is less than a threshold value may be determined in operation S830. As a result of determining, if the POS is less than the threshold value, operation S840 may be performed, and otherwise, operation S860 may be performed.

In operation S840, operation parameter information corresponding to the block region is searched for. For example, the operation controller 123b searches the parameter information storing unit 122b for the operation parameter information. In operation S850, an operation on a memory cell array is controlled using the operation parameter information.

In operation S860, modified operation parameter information is searched for. For example, the operation controller 123b may search the parameter information storing unit 122b for the modified operation parameter information. In operation S870, an operation on a memory cell array is controlled using the modified operation parameter information. In an exemplary embodiment, the modified operation parameter information may include bias condition for operations parameters.

FIG. 56 is a flowchart of an example of a method of operating a memory device according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 56, the method of operating a memory device according to the present exemplary embodiment may include, for example, operations that are sequentially performed in the control logic 120c of FIG. 52. The description provided with reference to FIG. 52 may apply to the method of the present exemplary embodiment, and repeated description will be omitted.

In operation S910, a command and an address are received from a memory controller. In operation S920, whether a POS is equal to or less than a threshold value is determined. As a result of determining, if the POS is equal to or less than the threshold value, operation S930 is performed, and otherwise, operation S940 is performed. However, the present inventive concept is not limited thereto, and in an exemplary embodiment, whether a POS is less than a threshold value may be determined in operation S920. As a result of determining, if the POS is less than the threshold value, operation S930 may be performed, and otherwise, operation S940 may be performed.

In operation S930, first block region information is searched for a block corresponding to the address. The first block region information may be information indicating a plurality of blocks in a cell region CR1, divided into at least two block regions according to a first method of setting block regions. In an exemplary embodiment, the first block region information may be applied when a data retention period is a first period. For example, the operation controller

123b may search the first block region information stored in the block region information storing unit 121 for a block corresponding to the address.

In operation S940, second block region information is searched for a block corresponding to the address. The second block region information may be information indicating to a plurality of blocks in the cell region CR1, divided into at least two block regions according to a second method of setting block regions. In the present exemplary embodiment, the second block region information may be applied when a data retention period is a second period greater than the first period. For example, the operation controller 123b may search the second block region information stored in the block region information storing unit 121 for a block corresponding to the address. In an exemplary embodiment, the first and the second block region information may include a block region assigned to a block corresponding to an address.

In operation S950, an operation parameter information corresponding to the block region is searched for. For example, the operation controller 123b searches the parameter information storing unit 122b for the operation parameter information. In an exemplary embodiment, the operation controller 123b may search the parameter information storing unit 122b for operation parameter information, for example, reference bias conditions. In operation S960, an operation on a memory cell array is controlled using the operation parameter information.

As described above, block regions may be differently set according to POSs. For example, according to the first block region information applied to operations prior to a POS corresponding to a threshold value, a third block BLK3 that is third most adjacent to the first edge EDG1 may correspond to the second block region REG2; according to the second block region information applied to operations after the POS corresponding to the threshold value, the third block BLK3 may correspond to the first block region REG1. Accordingly, a program operation may be performed on the third block BLK3 by using operation parameters according to the second block region REG2 before the POS corresponding to the threshold value, and after the POS corresponding to the threshold value, a program operation may be performed on the third block BLK3 by using operation parameters according to the first block region REG1.

FIG. 57 illustrates a memory device 100d according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 57, the memory device 100d may include a memory cell array 110a, a control logic 120d, a row decoder 140a, and a page buffer 150a. The memory device 100d is a modified example of the memory device 100a of FIG. 15, and description provided with reference to FIG. 15 may also apply to the present exemplary embodiment. Here, description will focus on differences from the exemplary embodiment of FIG. 15. In an exemplary embodiment, the memory device 100d may include the memory cell array illustrated in FIG. 17, FIG. 19, FIG. 21 or FIG. 24, and a method of setting block regions in a memory cell array may be modified in various manners.

According to an exemplary embodiment, the control logic 120d may include a block region information storing unit 121, a parameter information storing unit 122c, an operation controller 123c, and a chip information storing unit 126. Compared with the control logic 120 illustrated in FIG. 15, the control logic 120d may further include the chip information storing unit 126.

The block region information storing unit 121 may store information about block regions of a cell region CR1



included in the memory cell array **110a**. In the an embodiment, block region information may be generated by dividing a plurality of blocks into at least two block regions based on a distance with respect to a relatively close edge among first and second edges EDG1 and EDG2 of the cell region CR1. In an exemplary embodiment, block region information may be stored as a table showing block regions for corresponding blocks.

The parameter information storing unit **122c** may store information about operation parameters respectively corresponding to at least two block regions. The operation parameters refer to parameters that constitute bias conditions for program, erase, and read operations. In an exemplary embodiment, parameter information may be stored as a table including bias conditions for operation parameters corresponding to each block region.

The chip information storing unit **126** may store information of a chip in which the memory device **100d** is implemented. The chip information storing unit **126** may be implemented using a latch. In an exemplary embodiment, chip information may be stored in a region of the memory cell array **110a**. In an exemplary embodiment, chip information may be stored in a buffer memory of a memory controller. In an exemplary embodiment, chip information may be stored in an additional non-volatile memory included in a memory system.

The difference in channel hole diameters of blocks described with reference to FIG. 9 may be generated due to process variations of manufacturing the memory device **100d**. To accommodate such difference of channel hole diameters due to process variations, bias conditions of operation parameters applied to the memory device **100d** may be controlled with reference to chip information related to the manufacturing the memory device **100d**. In this case, reliability of the memory device **100d** may be further increased. For example, the chip information may include information indicating a chip position in a wafer, a wafer position in a lot or information about equipment used in the manufacturing processes of the chip.

The operation controller **123c** may control an operation performed on each block region of the memory cell array **110a** using block region information, parameter information, and chip information. For example, the operation controller **123c** may select bias conditions for operation parameters based on chip information, and control an operation performed on each block region of the memory cell array **110a** using the selected bias conditions.

Although not illustrated, in an exemplary embodiment, the control logic **120d** may further include the cycle information storing unit **124** illustrated in FIG. 43. The control logic **120d** may select a bias condition based on cycle information and chip information, and may control an operation performed on each block region in a memory cell array using the selected bias condition. In an exemplary embodiment, the control logic may further include the data retention period information storing unit **125**. The control logic **120d** may select a bias condition based on data retention period information and chip information, and may control an operation on each block region in a memory cell array using the selected bias condition.

FIG. 58 illustrates a memory device **100e** according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 58, the memory device **100e** may include a memory cell array **110a**, a control logic **120e**, a row decoder **140a**, and a page buffer **150a**. The memory device **100e** is a modified example of the memory device **100a** of FIG. 15, and description provided with reference to

FIG. 15 may also apply to the present exemplary embodiment. Here, description will focus on differences from the exemplary embodiment of FIG. 15. In an exemplary embodiment, the memory device **100e** may include the memory cell array illustrated in FIG. 17, FIG. 19, FIG. 21 or FIG. 24, and a method of setting block regions in a memory cell array may be modified in various manners.

The control logic **120e** may include a block region information storing unit **121**, a parameter information storing unit **122d**, a basic operation controller **123d**, an algorithm table storing unit **127**, and an auxiliary operation controller **128**. Compared with the control logic **120** illustrated in FIG. 15, the control logic **120e** may further include the algorithm table storing unit **127** and the auxiliary operation controller **128**.

The block region information storing unit **121** may store information about block regions of a cell region CR1 included in the memory cell array **110a**. In an exemplary embodiment, block region information may be generated by dividing a plurality of blocks into at least two block regions based on a distance with respect to a relatively close edge among first and second edges EDG1 and EDG2 of the cell region CR1. In an exemplary embodiment, block region information may be stored as a table showing block regions for corresponding blocks. For example, the block information storing unit **121** may store the table REG\_TABLE1 illustrated in FIG. 16.

In an exemplary embodiment, the memory cell array **110a** may include a plurality of lower blocks disposed on a substrate and a plurality of upper blocks disposed on the plurality of lower blocks as illustrated in FIG. 22A or FIG. 22B. The plurality of lower blocks and the plurality of upper blocks may be divided into block regions according to different methods of setting block regions, and accordingly, lower blocks and upper blocks that are substantially at the same distance with respect to the first edge EDG1 or the second edge EDG2 may be included in different block regions and different algorithm information may be respectively applied to the lower blocks and the upper blocks.

[Note to client: . . . ]

The parameter information storing unit **122d** may store information about operation parameters for at least two block regions. The operation parameters represent parameters that constitute bias conditions for basic operations such as program, erase, and read operations. In an exemplary embodiment, parameter information may be stored as a table showing bias conditions for block regions.

In addition, the parameter information storing unit **122d** may store, according to block regions, parameters for modifying a type of an algorithm corresponding to an auxiliary operation that may be additionally performed in each operation mode on the memory cell array **110a** or a detailed condition of the algorithm or modifying whether the algorithm is to be performed or not.

The algorithm table storing unit **127** may store algorithm information of block regions in the form of a table. Algorithm information may indicate whether algorithms are applied to block regions or not. An algorithm may include a series of operation sequences to perform an auxiliary operation on the memory cell array **110a**. In an exemplary embodiment, an auxiliary operation may be an operation that is additionally performed in an operation mode of an operation (hereinafter, referred to as a 'basic operation') such as a program, erase or read operation on the memory cell array **110a**. Operation circuits used in the memory device **100d** may vary according to whether an algorithm is applied or not or according to a type of an algorithm.



In an exemplary embodiment, algorithm information may be determined according to block regions. Thus, the same algorithms may be applied to the same block regions, and accordingly, an auxiliary operation may be performed by using the same algorithm with respect to different blocks included in the same block region.

For example, the first block region REG1 has a first channel hole diameter, and the Nth block region REG\_N has a second channel hole diameter which is greater than the first channel hole diameter. Memory cells included in the Nth block region REG\_N has a first word line resistance greater than a second word line resistance of memory cells included in the first block region REG1. In an exemplary embodiment, the first word line resistance may be greater than the second word line resistance. Thus, in a word line set up operation, an over-drive algorithm is applied to the Nth block region REG\_N, and an over-drive algorithm need not be applied to the first block region REG1. Accordingly, different operation circuits may be performed during program operations on the first block region REG1 and the Nth block region REG\_N.

In an exemplary embodiment, the algorithm table storing unit 127 may be implemented using a latch. In an exemplary embodiment, an algorithm table may be stored in a region of the memory cell array 110a. In an exemplary embodiment, an algorithm table may be stored in a buffer memory of a memory controller. In an exemplary embodiment, an algorithm table may be stored in an additional non-volatile memory included in a memory system.

In an exemplary embodiment, the algorithm table storing unit 127 may store algorithm information that is modified according to an operation cycle count. For example, the algorithm table storing unit 127 may store algorithm information corresponding to an operation cycle count that is equal to or less than a threshold value, and modified algorithm information corresponding to an operation cycle count that is greater than the threshold value. Accordingly, different operation algorithms may be applied according to operation cycle counts. In an exemplary embodiment, operation cycle count information may be stored in a region of the memory cell array 110a. In an exemplary embodiment, operation cycle count information may be stored in a buffer memory of a memory controller. In an exemplary embodiment, operation cycle count information may be stored in an additional non-volatile memory included in a memory system. This will be described further in detail with reference to FIGS. 61 and 62.

In an exemplary embodiment, the algorithm table storing unit 127 may store algorithm information that is modified according to a data retention period. For example, the algorithm table storing unit 127 may store algorithm information corresponding to a data retention period that is equal to or less than a threshold value, and modified algorithm information corresponding to a data retention period that is greater than the threshold value. Accordingly, different operation algorithms may be applied according to data retention periods. In an exemplary embodiment, data retention period information may be stored in a region of the memory cell array 110a. In an exemplary embodiment, data retention period information may be stored in a buffer memory of a memory controller. In an exemplary embodiment, data retention period information may be stored in an additional non-volatile memory included in a memory system.

FIG. 59 illustrates an example of an algorithm table ALG\_TABLE1 stored in the algorithm table storing unit 127 of FIG. 58.

Referring to FIG. 59, the algorithm table ALG\_TABLE1 may include first algorithm information indicating whether algorithms are applied to the first block region REG1 and second algorithm information indicating whether algorithms are applied to the Nth block region REG\_N. The present inventive concept is not limited thereto, and in an exemplary embodiment, the table ALG\_TABLE1 may further include information indicating whether algorithms are applied to other block regions. In an exemplary embodiment, the table ALG\_TABLE1 may further include information indicating whether other algorithms are applied to the first block region REG1 and the Nth block region REG\_N.

The first block region REG1 may include, for example, blocks adjacent to the first and second edges EDG1 and EDG2 of the cell region CR1, and the Nth block region REG\_N may include, for example, blocks in a center of the cell region CR1. Accordingly, a channel hole diameter of strings included in the first block region REG1 may be smaller than a channel hole diameter of strings included in the Nth block region REG\_N. Thus, a program speed and an erase speed with respect to memory cells included in the first block region REG1 may be higher than a program speed and an erase speed with respect to memory cells included in the Nth block region REG\_N.

Applying of various algorithms to block regions may reduce a difference in operating characteristics between the first block region REG1 and the Nth block region REG\_N. Thus, a threshold voltage distribution of memory cells included in the first block region REG1 may be similar to a distribution of memory cells included in the Nth block region REG\_N. Hereinafter, various algorithms are described. According to exemplary embodiments, only some of the various algorithms may be applied or other algorithms may be additionally applied.

In an exemplary embodiment, a pre-program algorithm may be applied to the first block region REG1 so that a pre-program operation is performed on the first block region REG1, and the pre-program algorithm need not be applied to the Nth block region REG\_N. The pre-program operation is an operation of programming all memory cells in a block to a preset level or higher before performing an erase cycle, to limit the number of over erased memory cells in the block. The pre-program operation may cause charge storage layers of all memory cells in the block to have an identical amount of charges.

In an exemplary embodiment, a post-program algorithm may be applied to the first block region REG1 so that a post-program operation is performed on the first block region REG1, and the post-program operation need not be applied to the Nth block region REG\_N. The post-program operation is an operation of programming some memory cells in a block to a preset level or higher after performing an erase cycle, to limit the number of over erased memory cells in the block.

An erase speed with respect to the memory cells included in the first block region REG1 may be relatively higher than an erase speed of the memory cells included in the Nth block region REG\_N, which have a greater channel hole diameter than that of the memory cells in the first block region REG1. Thus, the number of over erased memory cells in the first block region REG1 may be reduced by applying a pre-program algorithm or a post-program algorithm to the first block region REG1, thereby increasing reliability of the memory device. In an exemplary embodiment, to increase reliability of a memory device in regard to an erase operation, another algorithm may be further applied to the first block region REG1.



In an exemplary embodiment, sub-blocks need not be applied to the first block region REG1 but sub-blocks may be applied to the Nth block region REG\_N. A block may be divided into at least two sub-blocks. For example, memory cells disposed at levels adjacent to a ground selection line may be allocated to a first sub-block, and memory cells disposed adjacent to a string selection line may be allocated to a second sub-block. Accordingly, an erase operation may be performed according to sub-blocks in a block of the Nth block region REG\_N.

As the memory cells included in the first block region REG1 have a first channel hole diameter to the extent that a read disturb may be generated. As such, a threshold voltage distribution is spread due to a read inhibit voltage applied during repeated read operations. A read inhibit voltage is applied in units of physical blocks to the first block region REG1, and a read inhibit voltage is applied in units of sub-blocks to the Nth block region REG\_N. If a read cycle is not controlled in units of sub-blocks which are each a logically single block, a reclaim operation may frequently occur, resulting in degradation of performance of a memory device. For example, a read reclaim cycle period of memory cells included in the first block region REG1 is shorter than a read reclaim cycle period of memory cells included in the Nth block region REG\_N. In an exemplary embodiment, sub-blocks need not be applied to the first block region REG1.

In an exemplary embodiment, a count pulse program algorithm may be applied to the first block region REG1 so that a count pulse program operation is performed on the first block region REG1, and a count pulse program algorithm need not be applied to the Nth block region REG\_N. In an exemplary embodiment, a time when to apply a count pulse program algorithm may be differently set with respect to the first block region REG1 and the Nth block region REG\_N.

A count pulse program operation may be referred to as a detrapping operation and is an operation of supplying a detrapping voltage to a selected memory cell between a program operation and a verify operation to move charges trapped in a programmed memory cell. After a program operation is completed, charges trapped in a charge storage layer are rearranged in several to several tens of seconds, and this rearrangement is referred to as an initial verify shift (IVS). By applying a count pulse between a program operation and a verify operation, an electric field which is in an opposite direction to a direction of a program operation may be applied between a gate electrode and a channel region of a memory cell so that IVS is generated relatively early.

In an exemplary embodiment, a soft program algorithm may be applied to the first block region REG1 so that a soft program operation is performed on the first block region REG1, and a soft program algorithm need not be applied to the Nth block region REG\_N. As a result of performing a verify operation, a threshold voltage of a verify-passed memory cell may be reduced, and thus, a soft program operation may be performed again in a next program loop of the memory cell.

In an exemplary embodiment, an off string search algorithm may be applied to the first block region REG1 so that an off string search operation is performed on the first block region REG1, and an off string search algorithm need not be applied to the Nth block region REG\_N. Due to a variation of a manufacturing process, some pillars are formed in channel holes such that the pillars are not in contact with a substrate. In this case, such pillars may be defective, and may form an off string pillar having a non-contact state

between a channel region formed in the pillars and the substrate. In addition, when a drain is formed, the drain is not in contact with the pillars having the non-contact state. For example, if a channel hole is small to the extent that a pillar does not fill the channel hole or if the channel hole is not open to expose the drain, an off string pillar may be formed. The off string pillar may cause a malfunction in a program, erase or read operation on a memory block, and thus, an operation of detecting an off string pillar may be performed in advance.

In an exemplary embodiment, a priority may be given to a retention table among the operation parameters with respect to the first block region REG1 to perform a read recovery operation on the first block region REG1. For example, if a channel hole diameter is small to the extent that a displacement with respect to charge shift is relatively great and thus a probability of read errors increases as a data retention period increases. Thus, for the first block region REG1, a priority may be given to a retention table in a predefined table (PDT) to perform a read recovery operation on the first block region REG1.

In an exemplary embodiment, a priority may be given to an endurance table with respect to the Nth block region REG\_N to perform a read recovery operation on the Nth block region REG\_N. For example, if a channel hole diameter is large to the extent that a program operation or an erase operation is not properly performed for a P/E cycle count, a probability of read errors may increase. Thus, with respect to the Nth block region REG\_N, a priority may be given to an endurance table to perform a read recovery operation on the Nth block region REG\_N.

In an exemplary embodiment, if a read error is caused due to a shift in a threshold voltage distribution (or overlapping of neighbouring threshold voltage distributions), a valley search operation may be performed by using different methods of searching for valleys according to block regions and different valley search orders according to block regions. For example, characteristics of a read error generated in a block may be recognized according to positions of block regions, and a read recovery operation may be performed using different methods and different orders according to block regions.

Hereinafter, various examples of a read recovery operation will be described. As will be described later, a read recovery operation may be performed using various algorithms, and here, types of algorithms applied to the read recovery operation and an application order of the algorithms may be different according to block regions in a cell region.

In an exemplary embodiment, a read recovery operation may be performed using a read retry operation in which a read operation is repeated by changing a read level until correction of a read error is completed, and here, a read retry algorithm may be applied. In an exemplary embodiment, a read recovery operation may be performed using a history level read retry operation in which a read operation is performed again using a read level that has been used in a previous successful read operation. Here, a history level read retry algorithm may be applied.

In an exemplary embodiment, a read recovery operation may be performed using a predefined table (PDT) read retry operation in which a read operation is performed again based on a table including information about previously-set read levels, and here, a PDT read retry algorithm may be applied. The PDT may include information about read voltage levels that are determined according to predicted



## 61

distortion in a threshold voltage distribution of memory cells. [Note to client: how predicted?]

As an example, a read recovery operation may be performed using a minimum error search (MES) operation in which memory cells are read using read levels spaced apart from each other at equal intervals around a valley, and a read level having a smallest value between pieces of read data is used as a final read voltage, and here a MES algorithm may be applied. As an example, a read recovery operation may be performed using a read level swing operation in which a memory cell is read using voltage levels around a read level determined as an optimum read level in a previous operation, and here a read level swing algorithm may be applied.

As an example, a read recovery operation may be performed using a monitoring cell search operation in which monitoring cells are read, and distortion of a distribution of memory cells is measured based on a result of reading, and a read voltage is adjusted based on a result of measuring. Here, a monitoring cell search algorithm may be performed. The monitoring cells may be cells that are previously set to measure distortion of a distribution. The monitoring cells may be cells that have the same structure as memory cells, are at previously set locations, and are programmed to previously set data.

As an example, a read recovery operation may be performed using a Last Sector Count of One/Read Voltage Tracking Loop (LSCO/RVTL) operation in which the number of '1's of read data and a reference value are compared, distortion of a threshold voltage distribution is measured based on a result of comparing; and a read voltage level is determined based on a result of measuring. Here, a LSCO/RVTL algorithm may be applied. The reference value may be programmed to memory cells together with data, and may include information about a prediction value of data read as '1' in a read operation.

Whether an algorithm is to be applied or not to block regions is described above based on correlation between a difference in geometrical shapes such as a channel hole diameter and characteristics of memory cells. Thus, if bias conditions regarding basic operations such as a program, erase or read operation are applied according to respective block regions in order to compensate for a difference in characteristics of memory cells due to a difference in geometrical shapes, the above-described algorithm table ALG\_TABLE1 may be modified. For example, whether to apply algorithms to the first block region REG1 may be changed the other way around.

Referring to FIG. 58 again, the basic operation controller 123d may control a basic operation such as a program operation, a read operation, or an erase operation on the memory cell array 110a, according to block regions, based on block region information and operation parameter information. For example, when a program command is received, the basic operation controller 123d may search block region information for a block corresponding to an address, search parameter information for an operation parameter corresponding to the block region, and control a program operation by using the operation parameter information corresponding to the block region.

The auxiliary operation controller 128 may control an auxiliary operation on the memory cell array 110a according to block regions, based on block region information and an algorithm table. For example, when an erase command is received, the auxiliary operation controller 128 may search the block region information for a block corresponding to an address, determine whether an algorithm corresponding to a block region is applied, based on the algorithm table, and

## 62

selectively apply an auxiliary operation such as a pre-program operation or a post-program operation by using a selected algorithm.

FIG. 60 is a flowchart of a method of operating a memory device according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 60, the method of operating a memory device according to the present exemplary embodiment may include controlling an operation on a memory cell array performed in a control logic when a command and an address are received from a memory controller. The method may include, for example, operations that are sequentially performed in the control logic 120e of FIG. 58. The description provided with reference to FIGS. 58 and 59 may apply to the method of the present exemplary embodiment, and repeated description will be omitted.

In operation S1010, a command and an address are received from a memory controller. For example, the control logic 120d may receive a command and an address from the memory controller to thereby initiate an operation of the control logic 120d. In operation S1020, a block region corresponding to the received address is searched for. For example, the basic operation controller 123d and the auxiliary operation controller 128 may search the block region information storing unit 121 for the block region corresponding to the address.

In operation S1030, an algorithm table is searched for an auxiliary operation corresponding to the block region. For example, the auxiliary operation controller 128 may search the algorithm table storing unit 127 regarding whether algorithms are to be applied to block regions, and determine an auxiliary operation corresponding to the selected algorithms.

In operation S1040, an auxiliary operation on a memory cell array is controlled based on the algorithm table. For example, the auxiliary operation controller 128 may control the row decoder 140a and the page buffer 150a such that the row decoder 140a and the page buffer 150a perform an auxiliary operation corresponding to the selected algorithm on the memory cell array.

FIG. 61 is a flowchart of a method of operating a memory device according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 61, the method of operating a memory device is a modified example of the method illustrated in FIG. 60, and description provided with reference to FIGS. 58 and 59 may also apply to the present exemplary embodiment, and repeated description will be omitted.

In operation S1110, a command and an address are received from a memory controller. In operation S1120, a block region corresponding to the received address is searched for. In operation S1130, whether an operation cycle is equal to or less than a threshold value is determined. In an exemplary embodiment, the operation cycle may be a P/E cycle count. In an exemplary embodiment, the operation cycle may be a read cycle count. As a result of determining, if the operation cycle is equal to or less than the threshold value, operation S1140 is performed, and otherwise, operation S1160 is performed. However, the present inventive concept is not limited thereto, and in an exemplary embodiment, whether an operation cycle is less than a threshold value may be determined in operation S1130. As a result of determining, if the operation cycle is less than the threshold value, operation S1140 may be performed, and otherwise, operation S1160 may be performed.

However, the present inventive concept is not limited thereto, and in an exemplary embodiment, different algo-



rithm tables may be applied according to data retention periods. For example, whether a POS is equal to or less than a threshold value is determined, and if the POS is less than the threshold value as a result of determining, operation S1140 may be performed, and otherwise operation S1160 may be performed.

In operation S1140, a first algorithm table corresponding to a block region is searched for. For example, the auxiliary operation controller 128 searches the algorithm table storing unit 127 for the first algorithm table. The first algorithm table may correspond to a first algorithm table illustrated in FIG. 62. In operation S1150, an auxiliary operation on a memory cell array is controlled based on the first algorithm table.

In operation S1160, a second algorithm table corresponding to a block region is searched for. For example, the auxiliary operation controller 128 searches the algorithm table storing unit 127 for the second algorithm table. The second algorithm table may correspond to a second algorithm table illustrated in FIG. 62. In operation S1170, an auxiliary operation on a memory cell array is controlled based on the second algorithm table.

As a P/E cycle count increases, charges may unintentionally be trapped in a charge storage layer, which may result in an error in an erase verify operation. For example, an erase operation on a predetermined word line may be unsuccessful during a P/E cycle, and here, if an erase verify operation is performed by applying an erase verify voltage to each of all word lines at the same time, erase failure of a predetermined word line may be undetected. Thus, in addition to a method of applying an erase verify voltage to all word lines, a method of performing an erase verify operation by applying an erase verify voltage only to a predetermined word line may be additionally performed. Here, different algorithms for performing an erase verify operation on a predetermined word line may be applied according to block regions. Accordingly, when blocks having identical P/E cycles correspond to different block regions, algorithms applied to the blocks may be different.

However, the present inventive concept is not limited thereto, and in an exemplary embodiment, if an operation cycle is equal to or less than a threshold value, an auxiliary operation on a memory cell array may be controlled based on a reference algorithm table according to reference algorithm information. The reference algorithm information may be information that is commonly applied to block regions. If an operation cycle is greater than the threshold value, an auxiliary operation on a memory cell array may also be controlled based on algorithm tables according to block regions.

FIG. 62 illustrates an example of an algorithm table ALG\_TABLE2 stored in the algorithm table storing unit 127 of FIG. 58.

Referring to FIG. 62, the algorithm table ALG\_TABLE2 shows whether a plurality of algorithms is applied to the first block region REG1 and the Nth block region REG\_N. The present inventive concept is not limited thereto, and in an exemplary embodiment, the table ALG\_TABLE2 may further include information indicating whether algorithms are applied to other block regions. In an exemplary embodiment, the table ALG\_TABLE2 may further include information indicating whether other algorithms are applied to the first block region REG1 and the Nth block region REG\_N.

In an exemplary embodiment, the table ALG\_TABLE2 may include first and second algorithm tables. The second algorithm table may be generated by modifying whether some of the algorithms included in the first algorithm table

are to be applied or not. The first algorithm table may show whether a plurality of algorithms is to be applied to block regions. The first algorithm table of FIG. 62 is substantially the same as the algorithm table described above with reference to FIG. 59, and thus, detailed description thereof will be omitted.

The second algorithm table may show whether a plurality of algorithms is to be applied or not according to respective block regions. In an exemplary embodiment, the second algorithm table may be applied when a P/E cycle count is greater than a threshold value. In an exemplary embodiment, the second algorithm table may be applied when a read cycle count is greater than a threshold value. In an exemplary embodiment, the second algorithm table may be applied when a data retention period, that is, a POS, is greater than a threshold value.

In an exemplary embodiment, the second algorithm table may be generated by modifying whether some of the algorithms included in the first algorithm table are to be applied to the first block region REG1. In an exemplary embodiment, the second algorithm table may be generated by modifying whether some of the algorithms included in the first algorithm table are to be applied to the Nth block region REG\_N. In an exemplary embodiment, the second algorithm table may be generated by modifying whether some of the algorithms included in the first algorithm table are to be applied to the first block region REG1 and the Nth block region REG\_N.

As a P/E cycle count increases, a program speed with respect to memory cells included in the first block region REG1 having a first channel hole diameter may be further increased due to deterioration of the memory cells included in the first block region REG1. In addition, as a P/E cycle increases, due to deterioration of the memory cells included in the first block region REG1, charges may be trapped in a charge storage layer of the memory cells included in the first block region REG1, and accordingly, a threshold voltage of erased memory cells may be increased. In addition, as a P/E cycle count increases, a program speed with respect to memory cells included in the first block region REG1 are further increased so that upper levels of the program states P1, P2, and P3 are further increased. Meanwhile, as a P/E cycle count increases, an erase operation on memory cells included in the first block region REG1 having a first channel hole diameter may be improperly performed so that an upper level of the erase level E is also further increased.

Accordingly, if a P/E cycle count is greater than a threshold value, algorithms applied to the first block region REG1 and algorithms applied to the Nth block region REG\_N may be modified as described below to thereby compensate for a difference in operating characteristics between block regions.

In an exemplary embodiment, a pre-program operation and a post-program operation may be applied to the first block region REG1 and the Nth block region REG\_N. In an exemplary embodiment, a count pulse program operation, a soft program operation, and an off string search operation may be applied to the first block region REG1 and the Nth block region REG\_N. However, the exemplary embodiments are not limited thereto, and various types of algorithms may be determined to be applied to the Nth block region REG\_N.

FIG. 63 is a flowchart of a method of operating a memory device according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 63, the method of operating a memory device is a modified example of the method illustrated in



65

FIG. 60, and description provided with reference to FIGS. 58 through 60 may also apply to the present exemplary embodiment, and repeated description will be omitted.

In operation S1210, a command and an address are received from a memory controller. In operation S1220, whether an operation cycle is equal to or less than a threshold value is determined. In an exemplary embodiment, the operation cycle may be a P/E cycle count. In an exemplary embodiment, the operation cycle may be a read cycle count. As a result of determining, if the operation cycle is equal to or less than the threshold value, operation S1230 is performed, and otherwise, operation S1240 is performed. However, the present inventive concept is not limited thereto, and in an exemplary embodiment, whether an operation cycle is less than a threshold value may be determined in operation S1220. As a result of determining, if the operation cycle is less than the threshold value, operation S1230 may be performed, and otherwise, operation S1240 may be performed.

However, the present inventive concept is not limited thereto, and in an exemplary embodiment, different algorithm tables may be applied according to data retention periods. For example, whether a POS is equal to or less than a threshold value may be determined, and if the POS is less than the threshold value as a result of determining, operation S1230 may be performed, and otherwise operation S1240 may be performed.

In operation S1230, first block region information is searched for a block corresponding to the address. The first block region information may be information indicating a plurality of blocks in a cell region CR1, divided into at least two block regions according to a first method of setting block regions. In an exemplary embodiment, the first block region information may be applied to an initial cycle stage of a program operation or a read operation. For example, the operation controller 123d may search the first block region information stored in the block region information storing unit 121 for a block corresponding to the address.

In operation S1240, second block region information is searched for a block corresponding to the address. The second block region information may be information indicating a plurality of blocks in the cell region CR1, divided into at least two block regions according to a second method of setting block regions. In an exemplary embodiment, the second block region information may be applied to operations after a predetermined cycle of a program operation or a read operation, that is, after a cycle corresponding to a threshold value. For example, the operation controller 123d may search the second block region information stored in the block region information storing unit 121 for a block corresponding to the address.

In operation S1250, an algorithm table corresponding to a block region is searched for. For example, the operation controller 123d searches the algorithm table storing unit 127 for an algorithm to be applied. In operation S1260, an auxiliary operation on a memory cell array is controlled based on the algorithm table.

As described above, different block regions may be set according to operation cycles. For example, according to the first block region information applied to operations prior to a P/E cycle corresponding to a threshold value, a third block BLK3 that is third most adjacent to the first edge EDG1 may correspond to the second block region REG2; according to the second block region information applied to operations after the P/E cycle corresponding to the threshold value, the third block BLK3 may correspond to the first block region REG1. Accordingly, an auxiliary operation may be per-

66

formed on the third block BLK3 based on whether algorithms are to be applied, according to the second block region REG2 prior to the P/E cycle corresponding to the threshold value, and after the P/E cycle corresponding to the threshold value, an auxiliary operation may be performed on the third block BLK3 based on whether algorithms are to be applied, using operation parameters according to the first block region REG1.

FIG. 64 is a schematic block diagram illustrating a memory system 20 according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 64, the memory system 20 may include a memory device 100 and a memory controller 200a. The memory device 100 may include a memory cell array 100 and a control logic 120. In an exemplary embodiment, the memory device 100 may be substantially similarly implemented as the memory device 100 of FIG. 1. Thus, description provided above with reference to FIGS. 1 through 63 may also apply to the present exemplary embodiment, and repeated description will be omitted.

The memory controller 200a may determine bias conditions of operation parameters for block regions included in a cell region of the memory cell array 110, and transmit the determined bias conditions of the operation parameters to the memory device 100. The memory controller 200a may transmit the bias conditions of the operation parameters to the memory device 100 via a command, an address or data.

For example, the memory controller 200a may include a parameter determining unit 210 and a buffer memory 220. The buffer memory 220 may temporarily store at least one of block region information, parameter information, cycle information, data retention period information, and chip information. The buffer memory 220 may receive data from the memory device 100 or obtain data via firmware from the outside.

The parameter determining unit 210 may determine bias conditions of operation parameters for block regions included in a cell region of the memory cell array 110. The parameter determining unit 210 may determine bias conditions of operation parameters such that program, erase, and read operations are performed by using the same bias conditions of the program operation parameter, the same erase operation parameter, and the same read operation parameter on different blocks assigned to the same block region.

In an exemplary embodiment, the parameter determining unit 210 may determine bias conditions of operation parameters according to an operation requested by a host and an address. In an exemplary embodiment, the parameter determining unit 210 may determine bias conditions of operation parameters based on block region information, parameter information, cycle information, data retention period information, or chip information.

In an exemplary embodiment, operation parameters may be modified based on operation cycle information or data retention period information. In an exemplary embodiment, the parameter determining unit 210 may determine reference operation parameters according to a reference bias condition that is commonly applied to block regions when a P/E cycle count or a POS is equal to or less than a threshold value, and determine bias conditions of operation parameters to be applied to block regions when a P/E cycle count or a POS is greater than the threshold value.

In an exemplary embodiment, the parameter determining unit 210 may determine bias conditions of operation parameters to be applied to block regions when a P/E cycle count or a POS is equal to or less than a threshold value, and



determine modified bias conditions of operation parameters that are applied to block regions when a P/E cycle count or a POS is greater than the threshold value. In an exemplary embodiment, the parameter determining unit **210** may transmit modified bias conditions to the memory device **100** if an operation cycle count or a data retention period is greater than a threshold value.

In addition, some of the operations parameters determined by the parameter determining unit **210** may be stored in the memory controller **200a**, and accordingly, a control operation may be performed using the memory controller **200a**, and other operation parameters may be provided to the memory device **100** so that an operation may be performed in the memory device **100**.

In an exemplary embodiment, cycle information and data retention period information or the like may be stored in the memory controller **200a**, and the parameter determining unit **210** may determine an operation parameter according to an operation requested by a host and an address. The memory controller **200a** may transmit an operation parameter to the memory controller **200a** via a command, an address, or data. Accordingly, the memory device **100** may perform an operation according to an operation parameter based on the received command, address or data.

In an exemplary embodiment, bias conditions of operation parameters such as a program voltage and a program inhibit voltage or the like according to a P/E cycle count which is equal to or less than a threshold value may be stored in the memory device **100**. Accordingly, the memory device **100** may perform an operation by using the bias conditions of the operation parameters. Meanwhile, operation parameters such as a program voltage and a program inhibit voltage or the like according to a modified bias condition corresponding to a P/E cycle count that is greater than the threshold value may be stored in the memory controller **200a**. Accordingly, the memory controller **200a** may transmit operation parameters corresponding to a modified bias condition to the memory device **100** via a command, an address or data.

In an exemplary embodiment, a channel hole diameter of blocks adjacent to edges of a cell region may be smaller than a channel hole diameter of blocks in a center of the cell region. Accordingly, operating characteristics of the blocks adjacent to the edges of the cell region may be different from operating characteristics of the blocks in the center of the cell region. To compensate for a difference in the operating characteristics of each block region due to the difference in the channel hole diameters, different bias conditions may be applied to each block regions according to the present exemplary embodiment.

In an exemplary embodiment, the parameter determining unit **210** may determine program operation parameters such that a program start voltage, a program duration, a program inhibit voltage, a program verify voltage, a time increment of a program duration of each loop, a program voltage increment of each loop, a verify skip loop or a maximum loop is reduced from a center to an edge of a cell region. For example, the program operation parameters may be determined as illustrated in FIGS. **29** through **35**.

In an exemplary embodiment, the parameter determining unit **210** may determine erase operation parameters such that an erase voltage applied to a substrate and an erase duration are reduced and a word line erase voltage applied to a word line is increased from a center to an edge of a cell region. For example, the erase operation parameters may be determined as illustrated in FIGS. **36** through **38**.

In an exemplary embodiment, the parameter determining unit **210** may be determined such that read operation parameters are determined such that a read determination voltage and a read voltage that are applied to a substrate are reduced from a center to an edge of a cell region. For example, the read operation parameters may be determined as illustrated in FIGS. **40** through **42**.

In an exemplary embodiment, the memory controller **200a** may further include an algorithm determining unit. The algorithm determining unit may generate algorithm information by determining algorithms that are applied to block regions. Accordingly, the memory device **100** may additionally perform an auxiliary operation according to the algorithms in respective operation modes with respect to the memory cell array **110**. In an exemplary embodiment, the algorithm determining unit may modify some of pieces of algorithm information based on operation cycle information or data retention period information. In an exemplary embodiment, the algorithm determining unit may transmit algorithm information to the memory device **100** if an operation cycle count or data retention period is greater than a threshold value. In an exemplary embodiment, the algorithm determining unit may transmit algorithm information to the memory device **100** via a command, an address or data.

FIG. **65** is a flowchart of operations of a memory controller **200a** and a memory device **100** according to an exemplary embodiment of the present inventive concept.

Referring to FIG. **65**, in operation **S1310**, the memory controller **200a** is turned on. In operation **S1320**, the memory controller **200a** requests block region information from the memory device **100**. In operation **S1330**, the memory device **100** transmits the block region information to the memory controller **200a**. In an exemplary embodiment, the block region information may be stored in a partial region of a memory cell array **110**, for example, in a meta region. The block region information transmitted by the memory device **100** may be loaded to a buffer memory of the memory controller **200a**.

However, the present inventive concept is not limited thereto, and in an exemplary embodiment, the memory cell array **110** may further include parameter information, cycle information, data retention period information or chip information. The memory controller **200a** may further request parameter information, cycle information, data retention period information or chip information from the memory device **100**. The memory device **100** may further transmit parameter information, cycle information, data retention period information or chip information to the memory controller **200a**.

In operation **S1340**, the memory controller **200a** generates a command such as a program command, an erase command, or a read command. In operation **S1350**, the memory controller **200a** determines operation parameters based on the block region information loaded to the buffer memory. In operation **S1360**, the memory controller **200a** transmits the command, address or data to the memory device **100**. The operation parameters may be transmitted to the memory device **100** via a command, address or data.

In operation **S1370**, the memory device **100** performs a basic operation such as a program operation, an erase operation or a read operation according to blocks by using the received operation parameters. In an exemplary embodiment, the memory device **100** may perform an auxiliary operation by applying different algorithms to blocks by using the received operation parameters.



69

FIG. 66 is a flowchart of operations of a memory controller 200a and a memory device 100 according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 66 in operation S1410, the memory controller 200a is turned on. In operation S1420, the memory controller 200a requests block region information from a host. However, the present inventive concept is not limited thereto, and in an exemplary embodiment, operation S1420 may be omitted. In operation S1430, the host transmits the block region information to the memory controller 200a. In an exemplary embodiment, the host may transmit a program, read or erase request together with the block region information. The block region information transmitted by the host may be loaded to a buffer memory of the memory controller 200a.

However, the present inventive concept is not limited thereto, and in an exemplary embodiment, the memory controller 200a may further request parameter information, cycle information, data retention period information or chip information from the memory device 100, and the host may further transmit parameter information, cycle information, data retention period information or chip information to the memory controller 200a.

In operation S1440, the memory controller 200a generates a command such as a program command, an erase command, or a read command. In operation S1450, the memory controller 200a determines (or set) operation parameters based on the block region information loaded to the buffer memory. In operation S1460, the memory controller 200a transmits the command, address or data to the memory device 100. The parameter may be transmitted to the memory device 100 via a command, address or data. [Note to client: . . . ]

In operation S1470, the memory device 100 performs a basic operation such as a program operation, an erase operation or a read operation according to respective blocks by using the received parameter. In an exemplary embodiment, the memory device 100 may perform an auxiliary operation by applying different algorithms to respective blocks by using the received parameter.

FIG. 67 is a block diagram illustrating a memory system according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 67, the memory system 20a may include a memory device 100, a memory controller 200a, and a non-volatile memory 300. The memory device 100 may include a memory cell array 100 and a control logic 120. The memory system 20a is a modified embodiment of the memory system 20 of FIG. 64, and description provided with reference to FIGS. 64 through 66 may also apply to the present exemplary embodiment.

The non-volatile memory 300 may include at least one of a block region information storing unit 310, a parameter information storing unit 320, a cycle information storing unit 330, and a data retention period storing unit 340. In an exemplary embodiment, a buffer memory 220 may temporarily store at least one of block region information, parameter information, cycle information, and data retention period information that is loaded from the non-volatile memory 300. In an exemplary embodiment, the buffer memory 220 may temporarily store at least one of block region information, parameter information, cycle information, and data retention period information that is loaded from the memory device 100. In an exemplary embodiment, the buffer memory 220 may temporarily store at least one of block region information, parameter information, cycle information, and data retention period information.

70

FIG. 68 is a flowchart of operations of a memory controller 200a, a memory device 100, and a non-volatile memory 300 according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 68, in operation S1510, the memory controller 200a is turned on. In operation S1520, the memory controller 200a requests block region information from the non-volatile memory 300. In operation S1530, the non-volatile memory 300 transmits the block region information to the memory controller 200a.

However, the present inventive concept is not limited thereto, and in an exemplary embodiment, the memory controller 200a may further request parameter information, cycle information or data retention period information from the non-volatile memory 300, and the non-volatile memory 300 may further transmit parameter information, cycle information or data retention period information to the memory controller 200a.

In operation S1540, the memory controller 200a generates a command. In operation S1550, the memory controller 200a determines operating parameters based on block region information. In operation S1560, the memory controller 200a transmits a command, an address, and data to the memory device 100. The determined operation parameters may be transmitted to the memory device 100 via a command, an address or data. In operation S1570, the memory device 100 performs a basic operation such as a program operation, an erase operation, or a read operation on block regions. In an exemplary embodiment, the memory device 100 may perform an auxiliary operation by using different algorithms according to blocks by using the received operation parameters.

FIG. 69 is a schematic block diagram illustrating a memory system 30 according to an exemplary embodiment of the present inventive concept.

Referring to FIG. 69, the memory system 30 may include a memory device 100 and a memory controller 200b. The memory device 100 may include a memory cell array 100 and a control logic 120. The memory device 100 may be substantially similarly implemented as the memory device 100 of FIG. 1. Thus, description provided above with reference to FIGS. 1 through 63 may also apply to the present exemplary embodiment, and repeated description will be omitted.

The memory controller 200b may include a block region determining unit 230, a parameter determining unit 210, and a buffer memory 220. The buffer memory 220 may temporarily store at least one of block region information, parameter information, cycle information, data retention period information, and chip information. The memory controller 200b according to the present exemplary embodiment is a modified embodiment of the memory controller 200a of FIG. 64, and thus description provided with reference to FIGS. 64 through 68 may also apply to the present exemplary embodiment, and repeated description will be omitted.

The block region determining unit 230 may determine block regions with respect to at least one cell region included in the memory cell array 110. If a plurality of cell regions are included in the memory cell array 110, the block region determining unit 230 may determine block regions with respect to each of the plurality of cell regions.

In an exemplary embodiment, block region information may be stored in the memory controller 200b, and the memory controller 200b may transmit the block region information to the memory device 100 via a command, an address or data. Accordingly, the memory device 100 may



perform an operation on each of the block regions based on the received command, address or data.

In an exemplary embodiment, block region information corresponding to a P/E cycle count that is equal to or less than a threshold value may be stored in the memory device **100**. Accordingly, the memory device **100** may perform an operation by using operation parameters according to respective block regions. Meanwhile, modified block region information corresponding to a P/E cycle count that is greater than the threshold value may be stored in the memory controller **200b**. Accordingly, the memory controller **200b** may transmit the modified block region information to the memory device **100** via a command, an address or data.

According to the present exemplary embodiment, the block region determining unit **230** may determine positions of block regions according to positions in a cell region. For example, the block region determining unit **230** may determine positions of the block regions based on distances with respect to first and second edges that are parallel to an extension direction of a word line from among edges of a cell region.

In an exemplary embodiment, the block region determining unit **230** may determine block regions based on an absolute distance with respect to the first and second edges. In an exemplary embodiment, the block region determining unit **230** may determine block regions based on a relative distance with respect to the first and second edges. For example, the block region determining unit **230** may determine positions of the block regions based on an order in which the block regions are arranged from the first and second edges.

In an exemplary embodiment, the block region determining unit **230** may determine positions of block regions based on a distance with respect to a relatively close edge among the first and second edges. Accordingly, a block adjacent to the first edge and a block adjacent to the second edge may be determined to be in the same block region. Operation parameters may be determined according to respective block regions, and thus, the same operation parameters may be applied to the same block region.

In an exemplary embodiment, the block region determining unit **230** may determine positions of block regions based on a distance with respect to one of the first and second edges. Thus, a block adjacent to the first edge and a block adjacent to the second edge may be determined to be in different block regions. Operation parameters may be determined based on a distance with respect to a relatively close edge among the first and second edges, and accordingly, the same operation parameters may be applied to the block adjacent to the first edge and the block adjacent to the second edge, which are determined to be in different block regions.

In an exemplary embodiment, the block region determining unit **230** may determine positions of block regions based on a distance with respect to a relatively close edge among the first and second edges and a distance with respect to a peripheral circuit. The peripheral circuit may be, for example, a page buffer or a row decoder connected to the memory cell array **110**. Accordingly, a block adjacent to the first edge and a block adjacent to the second edge may be determined to be in different block regions. Operation parameters may be determined according to respective block regions, and thus, the same operation parameters may be applied to the same block region.

The block region determining unit **230** may divide a plurality of blocks into respective block regions according to different methods of setting block regions corresponding to

respective operation modes and store block region information indicating the division as a table showing the block regions respectively corresponding to the blocks according to the respective operation modes. For example, the block region determining unit **230** may divide a plurality of blocks into block regions according to different methods of setting block regions according to a program operation, an erase operation, a read operation, and a read recovery operation. Accordingly, a single block may correspond to different block regions according to operation modes.

In an exemplary embodiment, when the memory cell array **110** includes a plurality of lower blocks disposed on a substrate and a plurality of upper blocks disposed on the lower blocks, the block region determining unit **230** may generate block region information by dividing a plurality of lower blocks and a plurality of upper blocks into block regions according to different methods of setting block regions. However, the exemplary embodiments are not limited thereto, and in an exemplary embodiment, the block region determining unit **230** may generate block region information by dividing a plurality of lower blocks and a plurality of upper blocks into block regions according to a single method of setting block regions.

The parameter determining unit **210** may determine operation parameters respectively corresponding to block regions included in a cell region of the memory cell array **110**. For example, the parameter determining unit **210** may determine operation parameters such that program, erase and read operations are respectively performed on different blocks included in the same block region by using the same program operation parameter, the same erase operation parameter, and the same read operation parameter.

In the present exemplary embodiment, a channel hole diameter of blocks adjacent to edges of a cell region may be smaller than a channel hole diameter of blocks in a center of the cell region. Accordingly, operating characteristics of blocks adjacent to edges of the cell region may be different from operating characteristics of blocks in a center of the cell region. To compensate for a difference in the operating characteristics due to a difference in the channel hole diameter, different bias conditions may be determined to be assigned to each block region.

In an exemplary embodiment, the memory controller **200b** may further include an algorithm determining unit. The algorithm determining unit may generate algorithm information by determining algorithms to be applied to respective block regions. Accordingly, the memory device **100** may additionally perform an auxiliary operation according to the algorithms in respective operation modes. In an exemplary embodiment, the algorithm determining unit may modify some of pieces of algorithm information based on operation cycle information or data retention period information. In an exemplary embodiment, the algorithm determining unit may transmit algorithm information to the memory device **100** if an operation cycle count or a data retention period is greater than a threshold value. In an exemplary embodiment, the algorithm determining unit may transmit algorithm information to the memory device **100** via a command, an address or data.

FIG. **70** is a block diagram illustrating a memory system **30a** which is a modified example of the memory system **30**, according to an exemplary embodiment of the present inventive concept.

Referring to FIG. **70**, the memory system **30a** may include a memory device **100**, a memory controller **200b**, and a non-volatile memory **300**, and the memory device **100** may include a memory cell array **110** and a control logic



120. The memory system **30a** according to the present exemplary embodiment is a modified embodiment of the memory system **30** of FIG. **69**, and description provided with reference to FIG. **69** may also be applied to the present exemplary embodiment.

According to the present exemplary embodiment, the non-volatile memory **300** may include at least one of a block region information storing unit **310**, a parameter information storing unit **320**, a cycle information storing unit **330**, and a data retention period storing unit **340**. In an exemplary embodiment, a buffer memory **220** may temporarily store at least one of block region information, parameter information, cycle information, and data retention information loaded from the non-volatile memory **300**. In an exemplary embodiment, the buffer memory **220** may temporarily store at least one of block region information, parameter information, cycle information, and data retention information loaded from the memory device **100**. In an exemplary embodiment, the buffer memory **220** may temporarily store at least one of block region information, parameter information, cycle information, and data retention information loaded from a host.

FIG. **71** is a block diagram illustrating a memory card system **1000**, to which a memory device according to exemplary embodiments of the present inventive concept is applied.

Referring to FIG. **71**, the memory card system **1000** may include a host **1100** and a memory card **1200**. The host **1100** may include a host controller **1110** and a host connector **1120**. The memory card **1200** may include a card connector **1210**, a card controller **1220**, and a memory device **1220**. In this case, the memory card **1200** may be embodied according to the exemplary embodiments shown in FIGS. **1** to **70**. For example, the memory device **1220** may divide blocks included in a cell region into at least two block regions, and control operations according to respective block regions by using operation parameters respectively corresponding to the block regions.

The host **1100** may write data to the memory card **1200** or read data stored in the memory card **1200**. The host controller **1110** may transmit a command **CMD**, a clock signal **CLK** generated by a clock generator (not shown) of the host **1100**, and data **DATA** through the host connector **1120** to the memory card **1200**.

In response to a command received through the card connector **1210**, the card controller **1220** may be synchronized with a clock signal generated by a clock generator (not shown) of the card controller **1220** and store data in the memory device **1220**. The memory device **1220** may store data transmitted from the host **1100**.

The memory card **1220** may be embodied by a compact flash card (CFC), a microdrive, a smart media card (SMC), a multimedia card (MMC), a security digital card (SDC), a memory stick, or a universal serial bus (USB) flash memory driver.

FIG. **72** is a block diagram illustrating a computing system **2000** including a memory device according to exemplary embodiments of the present inventive concept.

Referring to FIG. **72**, the computing system **2000** may include a memory system **2100**, a processor **2200**, a random access memory (RAM) **2300**, an input/output (I/O) device **2400**, and a power supply **2500**. Although not shown in FIG. **72**, the computing system **2000** may further include ports, which may communicate with a video card, a sound card, a memory card, or a universal serial bus (USB) device or communicate with other electronic devices. The computing system **2000** may be embodied by a personal computer (PC)

or a portable electronic device, such as a laptop computer, a portable phone, a personal digital assistant (PDA), and a camera.

The processor **2200** may perform specific calculations or tasks. According to an exemplary embodiment, the processor **2200** may be a microprocessor or a central processing unit (CPU). The processor **2200** may communicate with the RAM **2300**, the I/O device **2400**, and the memory system **2100** through a bus **2600**, such as an address bus, a control bus, and a data bus. According to an exemplary embodiment, the processor **2200** may be also connected to an expansion bus, such as a peripheral component interconnect (PCI) bus.

The memory system **2100** may be implemented using the exemplary embodiments illustrated in FIGS. **1** through **71**. For example, a memory device **2110** may divide blocks included in a cell region into at least two block regions, and control operations according to respective block regions by using operation parameters respectively corresponding to the block regions.

The RAM **2300** may store data required for an operation of the computing system **2000**. For example, the RAM **2300** may be embodied by a dynamic random access memory (DRAM), a mobile DRAM, a static RAM (SRAM), a phase-change RAM (PRAM), a ferroelectric RAM (FRAM), a resistive RAM (RRAM), and/or a magnetic RAM (MRAM). The I/O device **2400** may include an input unit, such as a keyboard, a keypad, and a mouse, and an output unit, such as a printer and a display. The power supply **2500** may supply an operating voltage required for an operation of the computing system **2000**.

FIG. **73** is a block diagram illustrating a solid-state disk (SSD) system **3000** to which a memory device according to exemplary embodiments of the present inventive concept is applied.

Referring to FIG. **73**, the SSD system **3000** may include a host **3100** and an SSD **3200**. The SSD **3200** may exchange signals with the host **3100** through a signal connector and receive power through a power connector. The SSD **3200** may include an SSD controller **3210**, an auxiliary power supply **3220**, and a plurality of memory devices **3230**, **3240**, and **3250**. In this case, the SSD **3200** may be embodied according to the exemplary embodiments shown in FIGS. **1** to **72**. For example, the flash memories **3230** to **3250** may divide blocks included in a cell region into at least two block regions, and may control operations according to the respective block regions by using operation parameters respectively corresponding to the block regions.

FIG. **74** is a block diagram illustrating a Universal Flash Storage (UFS) system **4000**, to which a memory device according to exemplary embodiments of the present inventive concept is applied.

Referring to FIG. **74**, the UFS system **4000** may include a UFS host **4100**, UFS devices **4200** and **4300**, an embedded UFS device **4400**, and a removable UFS card **4500**. The UFS host **4100** may be an application processor of a mobile device. The UFS host **4100**, the UFS devices **4200** and **4300**, the embedded UFS device **4400**, and the removable UFS card **4500** may each perform communication with external devices according to the UFS protocol. At least one of the UFS devices **4200** and **4300**, the embedded UFS device **4400**, and the removable UFS card **4500** may include the memory device **100** illustrated in FIGS. **1** through **70**.

Meanwhile, the embedded UFS device **4400** and the removable UFS card **4500** may perform communication according to other protocols that are different from the UFS protocol. The UFS host **5100** and the removable UFS card



4500 may perform communication according to various card protocols (e.g., UFDs, MMC, SD, mini SD, or Micro SD).

The memory card, the non-volatile memory device, the card controller according to the present inventive concept may be mounted using packages of various shapes. For example, the flash memory device and/or the memory controller according to the present inventive concept may be mounted using packages such as a Package on Package (PoP), Ball grid arrays (BGAs), Chip scale packages (CSPs), Plastic Leaded Chip Carrier (PLCC), Plastic Dual In-Line Package (PDIP), Die in Waffle Pack, Die in Wafer Form, Chip On Board (COB), Ceramic Dual In-Line Package (CERDIP), Plastic Metric Quad Flat Pack (MQFP), Thin Quad Flatpack (TQFP), Small Outline (SOIC), Shrink Small Outline Package (SSOP), Thin Small Outline (TSOP), System In Package (SIP), Multi Chip Package (MCP), Wafer-level Fabricated Package (WFP), or Wafer-Level Processed Stack Package (WSP).

While the present inventive concept has been shown and described with reference to exemplary embodiments thereof, it will be apparent to those of ordinary skill in the art that various changes in form and detail may be made therein without departing from the spirit and scope of the inventive concept as defined by the following claims.

What is claimed is:

1. A memory device comprising:

a memory cell region including a plurality of blocks, each block including a plurality of NAND strings; and  
a control logic configured to divide the plurality of blocks into a plurality of block regions based on a smaller distance of a first distance with respect to a first edge of the memory cell region and a second distance with respect to a second edge of the memory cell region and to control an operation performed on the memory cell region using a plurality of bias sets of operation parameters for the operation, wherein each bias set is associated with one of the block regions.

2. The memory device of claim 1,

wherein the memory cell region includes a plurality of word lines and a plurality of bit lines,  
wherein each of the word lines is extended in a first direction and each of the bit lines is extended in a second direction crossing the first direction, and  
wherein the first and the second edges of the memory cell region are in parallel to the first direction.

3. The memory device of claim 1,

wherein the control logic comprises:  
an operation controller configured to, in response to an address, select one of the bias sets of the operation parameter and apply the selected bias set to a block region associated with the address.

4. The memory device of claim 3,

wherein the control logic further comprises:  
a block region storing unit configured to store a plurality of block region information about relationships between the block regions and the blocks, wherein each block is selected using the address; and  
a parameter storing unit configured to store the bias sets associated with the block regions.

5. The memory device of claim 4,

wherein the block region information of the second block is changed if an operation cycle count of the block or a data retention period of the block exceeds a threshold.

6. The memory device of claim 4,

wherein the operation controller receives the plurality of block region information or the bias sets from the outside.

7. The memory device of claim 3,

wherein the block regions include a first block region including a first block that is adjacent to the first edge and a second block region including a second block that is positioned in a center of the memory cell region,  
wherein the bias sets include a first bias set associated with the first block region and a second bias set associated with the second block region.

8. The memory device of claim 7,

wherein at least one of the first and the second bias sets is modified according to an operation cycle count or a data retention period to reduce difference in speed of the operation between the first block and the second block if the operation cycle count or the data retention period exceeds a threshold.

9. The memory device of claim 7,

wherein if an operation cycle count is equal to or less than a threshold value, the operation controller controls such that the operation is performed on the first block region and the second block region using the first bias set and the second bias set, respectively, and

wherein if the operation cycle count is greater than the threshold value, the operation controller controls such that the operation is performed on the first block region and second block region using a third bias set and the second bias set, respectively, and

wherein the third bias set is determined by modifying the first bias set such that difference in speed of the operation performed on the first block due to increase of the operation cycle count is reduced.

10. The memory device of claim 7,

wherein if an operation cycle count is equal to or less than a threshold value, the operation controller controls such that the operation is performed on the first block region and the second block region using a reference bias set of the operation parameters, and

wherein if the operation cycle count is greater than the threshold value, the operation controller controls such that the operation is performed on the first block region and the second block region using the first bias set and the second bias set, respectively.

11. The memory device of claim 7,

wherein if the operation is a program operation, the operation parameters include at least one of a program start voltage, a program duration, a program inhibit voltage, a program verify voltage, a time increment of a program duration of each loop, a program voltage increment of each loop, the number of program verify skip loops, and the number of maximum loops,

wherein each value of the first bias set is smaller than a corresponding value of the second bias set.

12. The memory device of claim 7,

wherein if the operation is a read operation, the operation parameters include at least one of a read determination voltage, a read inhibit voltage and a read verify voltage, and

wherein a value of the read determination voltage in the first bias set is smaller than a value of the read determination voltage in the second bias set, and

wherein a value of the read inhibition voltage in the first bias set is smaller than a value of the read inhibition voltage in the second bias.

13. The memory device of claim 7,

wherein if the operation is an erase operation, the operation parameters include at least one of a substrate erase voltage, a word line erase voltage, and an erase duration,



77

wherein a first substrate erase voltage, a first erase duration, or a first erase verify voltage of the first bias set is smaller than a second substrate erase voltage, a second erase duration, or a second erase verify voltage of the second bias set, and

wherein a first word line erase voltage of the first bias set is greater than a second word line erase voltage of the second bias set.

**14.** The memory device of claim **3**,

wherein the memory cell region stores a plurality of block region information about relationships between the block regions and the blocks or the bias sets associated with the block regions.

**15.** The memory device of claim **14**,

wherein the memory cell region further stores an operation cycle count of each block, and

wherein each bias set is adjusted based on a value of the operation cycle count of each block.

**16.** The memory device of claim **14**,

wherein the memory cell region further stores data retention period of each block, and

wherein each bias set is adjusted based on a value of the data retention period of each block.

**17.** The memory device of claim **3**,

wherein a first block and a second block having the same distance from the first edge and the second edge, respectively, are included in a same block region, and

wherein the bias sets includes different bias sets of the operation parameters for each block region.

78

**18.** The memory device of claim **3**,

wherein a first block and a second block having different distances from the first edge and the second edge, respectively, are included in different block regions, and

wherein the bias sets includes different bias sets of the operation parameters for each block region.

**19.** The memory device of claim **1**,

wherein the control logic comprises:

an operation controller, in response to an address and an operation mode, configured to select one of the bias sets of the operation parameter and apply the selected bias set to a block region associated with the address,

wherein the operation mode includes a programming operation, an erase operation, a read operation or a read recovery operation.

**20.** The memory device of claim **1**,

wherein the memory cell region includes a plurality of lower blocks and a plurality of upper blocks,

wherein the lower blocks are interposed between a substrate and the upper blocks,

wherein the lower blocks are divided into a plurality of block regions based on the distance with respect to the first edge, and

wherein the upper blocks are divided into a plurality of block regions based on the distance with respect to the first edge so that lower blocks and upper blocks that are substantially at the same distance with respect to the first edge or the second edge are included in different block regions and different bias conditions are applied to the lower blocks and the upper blocks.

\* \* \* \* \*