



US009521946B2

(12) **United States Patent**
Jacobsen et al.

(10) **Patent No.:** **US 9,521,946 B2**
(45) **Date of Patent:** **Dec. 20, 2016**

(54) **TRANSPARENT ENDOSCOPE HEAD
DEFINING A FOCAL LENGTH**

USPC 600/116
See application file for complete search history.

(71) Applicant: **Sarcos LC**, Salt Lake City, UT (US)

(56) **References Cited**

(72) Inventors: **Stephen C. Jacobsen**, Salt Lake City, UT (US); **Fraser M. Smith**, Salt Lake City, UT (US)

U.S. PATENT DOCUMENTS

(73) Assignee: **Sarcos LC**, Salt Lake City, UT (US)

3,787,121 A 1/1974 Lowy et al.
3,817,635 A 6/1974 Kawahar
3,856,000 A 12/1974 Chikama
3,886,933 A 6/1975 Mori et al.
3,918,438 A 11/1975 Hayamizu et al.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(Continued)

(21) Appl. No.: **14/248,184**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Apr. 8, 2014**

CN 1481753 3/2004
DE 19742973 4/1998

(65) **Prior Publication Data**

US 2014/0371529 A1 Dec. 18, 2014

Related U.S. Application Data

(Continued)

(63) Continuation of application No. 12/487,495, filed on Jun. 18, 2009, now Pat. No. 8,690,762.

(60) Provisional application No. 61/132,566, filed on Jun. 18, 2008.

OTHER PUBLICATIONS

Jacobsen, Stephen C., U.S. Appl. No. 10/391,489, filed Mar. 17, 2003.

(Continued)

(51) **Int. Cl.**

A61B 1/00 (2006.01)
A61B 1/05 (2006.01)
A61B 1/015 (2006.01)

Primary Examiner — Clayton E Laballe

Assistant Examiner — Fang-Chi Chang

(74) *Attorney, Agent, or Firm* — Thorpe North & Western LLP

(52) **U.S. Cl.**

CPC **A61B 1/00188** (2013.01); **A61B 1/0008** (2013.01); **A61B 1/00082** (2013.01); **A61B 1/00147** (2013.01); **A61B 1/00177** (2013.01); **A61B 1/015** (2013.01); **A61B 1/05** (2013.01); **A61B 1/051** (2013.01)



(57) **ABSTRACT**

A catheter configured for imaging objects substantially in focus is described herein. An imaging device is disposed on the distal end of the catheter. The imaging device has an effective focal plane that is located in front of the imaging device. The catheter also includes a transparent focal instrument that has an outer periphery that is positioned at the effective focal plane of the imaging device, to enable objects in contact with the outer periphery of the transparent focal instrument to be imaged substantially in focus.

(58) **Field of Classification Search**

CPC A61M 25/00; A61M 25/10; A61M 25/04; A61B 1/005; A61B 1/04; A61B 1/045; A61B 1/05

14 Claims, 8 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

3,971,065 A	7/1976	Bayer	5,190,523 A	3/1993	Lindmayer
4,277,168 A	7/1981	Oku	5,191,203 A	3/1993	McKinley
4,283,115 A	8/1981	Fraissl	5,198,894 A	3/1993	Hicks
4,349,456 A	9/1982	Sowman	5,209,219 A	5/1993	Hollobaugh
4,360,275 A	11/1982	Louderback	5,220,198 A	6/1993	Tsuji
4,403,985 A	9/1983	Boretos	5,222,477 A	6/1993	Lia
4,475,902 A	10/1984	Schubert	5,228,430 A	7/1993	Sakamoto
4,487,206 A	12/1984	Aagard	5,258,834 A	11/1993	Tsuji et al.
4,491,865 A	1/1985	Danna et al.	5,289,434 A	2/1994	Berni
4,515,444 A	5/1985	Prescott et al.	5,290,555 A	3/1994	Guthauser et al.
4,573,450 A	3/1986	Arakawa	5,291,010 A	3/1994	Tsuji
4,585,349 A	4/1986	Gross et al.	5,298,741 A	3/1994	Walt et al.
4,588,294 A	5/1986	Siegmund	5,304,173 A	4/1994	Kittrell et al.
4,589,404 A	5/1986	Barath et al.	5,305,098 A	4/1994	Matsunaka et al.
4,593,313 A	6/1986	Nagasaki et al.	5,318,024 A	6/1994	Kittrell et al.
4,594,613 A	6/1986	Shinbori et al.	5,361,166 A	11/1994	Atkinson et al.
4,600,831 A	7/1986	Hutley	5,365,268 A	11/1994	Minami
4,604,992 A	8/1986	Sato	5,376,960 A	12/1994	Wurster
4,620,534 A	11/1986	Zartman	5,377,047 A	12/1994	Broome et al.
4,621,284 A	11/1986	Nishioka et al.	5,381,784 A	1/1995	Adair
4,622,954 A	11/1986	Arakawa et al.	5,396,366 A	3/1995	Brown et al.
4,626,079 A	12/1986	Nakamura et al.	5,398,685 A	3/1995	Wilk et al.
4,641,927 A	2/1987	Prescott et al.	5,402,769 A	4/1995	Tsuji
4,646,724 A	3/1987	Sato et al.	5,408,999 A	4/1995	Singh et al.
4,672,218 A	6/1987	Chrisman et al.	5,430,475 A	7/1995	Goto et al.
4,706,118 A	11/1987	Kato et al.	5,434,615 A	7/1995	Matumoto
4,707,134 A	11/1987	McLachlan et al.	5,436,655 A	7/1995	Hiyama et al.
4,723,843 A	2/1988	Zobel	5,438,975 A	8/1995	Miyagi et al.
4,725,721 A	2/1988	Nakamura et al.	5,440,669 A	8/1995	Rakuljie et al.
4,745,470 A	5/1988	Yabe et al.	5,450,243 A	9/1995	Nishioka
4,745,471 A	5/1988	Takamura et al.	5,455,455 A	10/1995	Badehi
4,783,591 A	11/1988	Sullivan	5,458,612 A	10/1995	Chin
4,785,815 A	11/1988	Cohen	5,459,570 A	10/1995	Swanson et al.
4,790,624 A	12/1988	Van Hoye et al.	5,469,841 A	11/1995	Kobayashi et al.
4,791,479 A	12/1988	Ogiu et al.	5,494,483 A	2/1996	Adair
4,802,487 A	2/1989	Martin et al.	5,512,940 A	4/1996	Takasugi et al.
4,803,562 A	2/1989	Eino	5,517,997 A	5/1996	Fontenot
4,832,003 A	5/1989	Yabe	5,531,664 A	7/1996	Adachi et al.
4,843,416 A	6/1989	Brower	5,547,455 A	8/1996	McKenna et al.
4,846,785 A	7/1989	Cassou et al.	5,547,906 A	8/1996	Badehi
4,859,040 A	8/1989	Kitagishi et al.	5,594,497 A	1/1997	Ahern
4,867,137 A	9/1989	Takahashi	5,603,687 A	2/1997	Hori et al.
4,867,138 A	9/1989	Kubota et al.	5,607,435 A	3/1997	Sachdeva et al.
4,867,174 A	9/1989	Skribiski	5,621,574 A	4/1997	Foo
4,880,298 A	11/1989	Takada	5,630,788 A	5/1997	Forkner et al.
4,895,138 A	1/1990	Yabe	5,647,368 A	7/1997	Zeng et al.
4,916,534 A	4/1990	Takhashi et al.	5,662,621 A	9/1997	Lafontaine
4,926,257 A	5/1990	Miyazaki	5,673,083 A	9/1997	Izumi et al.
4,930,880 A	6/1990	Miyauchi	5,685,311 A	11/1997	Hara
4,932,394 A	6/1990	Nanaumi	5,693,043 A	12/1997	Kittrell et al.
4,934,340 A	6/1990	Ebling et al.	5,704,892 A	1/1998	Adair
4,941,457 A	7/1990	Hasegawa	5,716,323 A	2/1998	Lee
4,998,807 A	3/1991	Uzawa et al.	5,716,759 A	2/1998	Badehi
5,006,928 A	4/1991	Kawajiri et al.	5,722,403 A	3/1998	McGee et al.
5,009,483 A	4/1991	Rockwell, III	5,732,150 A	3/1998	Zhou et al.
5,021,888 A	6/1991	Kondou et al.	5,740,808 A	4/1998	Panescu et al.
5,022,972 A	6/1991	David et al.	5,749,827 A	5/1998	Minami
5,032,913 A	7/1991	Hattori et al.	5,751,340 A	5/1998	Strobl et al.
5,040,069 A	8/1991	Matsumoto et al.	5,752,518 A	5/1998	McGee et al.
5,061,036 A	10/1991	Gordon	5,769,792 A	6/1998	Palcic et al.
5,093,719 A	3/1992	Prescott	5,772,597 A	6/1998	Goldberger et al.
5,105,269 A	4/1992	Nakamura et al.	5,776,049 A	7/1998	Takahashi
5,106,387 A	4/1992	Kittrell et al.	5,783,829 A	7/1998	Sealock et al.
5,109,859 A	5/1992	Jenkins	5,784,098 A	7/1998	Shoji et al.
5,111,804 A	5/1992	Funakoshi	5,792,984 A	8/1998	Bloom
5,113,254 A	5/1992	Kanno et al.	5,800,341 A	9/1998	McKenna et al.
5,121,213 A	6/1992	Nishioka	5,807,261 A	9/1998	Benaron et al.
5,126,639 A	6/1992	Srivastava	5,808,665 A	9/1998	Green
5,130,804 A	7/1992	Tamura et al.	5,818,644 A	10/1998	Noda
5,152,277 A *	10/1992	Honda A61B 1/00082 600/106	5,827,172 A	10/1998	Takahashi et al.
5,165,063 A	11/1992	Strater et al.	5,827,531 A	10/1998	Morrison et al.
5,166,656 A	11/1992	Badehi et al.	5,840,017 A	11/1998	Furusawa et al.
5,182,672 A	1/1993	Mukai et al.	5,846,185 A	12/1998	Carollo
5,188,093 A	2/1993	Lafferty et al.	5,848,969 A	12/1998	Panescu et al.
			5,865,729 A	2/1999	Meehan et al.
			5,870,229 A	2/1999	Tsuchida
			5,873,816 A	2/1999	Kagawa et al.
			5,879,285 A	3/1999	Ishii
			5,904,651 A	5/1999	Swanson et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

5,908,445 A	6/1999	Whayne et al.	6,727,313 B2	4/2004	Zhou et al.
5,913,817 A	6/1999	Lee	6,756,437 B1	6/2004	Xue et al.
5,916,155 A	6/1999	Levinson et al.	6,761,684 B1	7/2004	Speier
5,929,900 A	7/1999	Yamanaka et al.	6,785,048 B2	8/2004	Yamaguchi et al.
5,940,126 A	8/1999	Kimura	6,826,422 B1	11/2004	Modell et al.
5,947,894 A	9/1999	Chapman et al.	6,827,683 B2	12/2004	Otawara
5,951,462 A	9/1999	Yamanaka	6,833,916 B2	12/2004	Osipchuk et al.
5,957,849 A	9/1999	Munro	6,834,158 B1	12/2004	Templeton
5,971,915 A	10/1999	Yamamoto et al.	6,842,288 B1	1/2005	Liu et al.
5,973,779 A	10/1999	Ansari et al.	6,850,659 B2	2/2005	Han
5,980,663 A	11/1999	Badehi	6,879,851 B2	4/2005	McNamara et al.
5,989,185 A	11/1999	Miyazaki	6,881,448 B1	4/2005	Hattori
5,998,878 A	12/1999	Johnson	6,891,984 B2	5/2005	Petersen et al.
5,999,327 A	12/1999	Nagaoka	6,893,432 B2	5/2005	Intintoli et al.
6,008,123 A	12/1999	Kook et al.	6,894,729 B2	5/2005	Hirata et al.
6,014,919 A	1/2000	Jacobsen et al.	6,898,458 B2	5/2005	Zeng et al.
6,022,758 A	2/2000	Badehi	6,900,913 B2	5/2005	Chen
6,040,235 A	3/2000	Badehi	6,930,705 B2	8/2005	Tanaka
6,059,760 A	5/2000	Sandmore et al.	6,937,268 B2	8/2005	Ogawa
6,095,970 A	8/2000	Hidaka et al.	6,939,348 B2	9/2005	Malecki et al.
6,117,707 A	9/2000	Badehi	6,941,041 B2	9/2005	Yamaguchi et al.
6,118,476 A	9/2000	Morito et al.	6,944,204 B2	9/2005	Zhou et al.
6,133,637 A	10/2000	Hikita et al.	6,953,432 B2	10/2005	Schiefer
6,134,003 A	10/2000	Tearney et al.	6,956,624 B2	10/2005	Hirata et al.
6,139,489 A	10/2000	Wampler et al.	6,960,165 B2	11/2005	Ueno et al.
6,139,819 A	10/2000	Unger et al.	6,982,740 B2	1/2006	Adair et al.
6,142,930 A	11/2000	Ito et al.	6,990,271 B2	1/2006	Gafsi et al.
6,161,035 A	12/2000	Furusawa	7,030,904 B2	4/2006	Adair et al.
6,184,923 B1	2/2001	Miyazaki	7,033,317 B2	4/2006	Pruitt
6,193,685 B1 *	2/2001	Goodin A61M 25/1006 604/102.01	7,058,294 B2	6/2006	Nakahara
6,193,908 B1	2/2001	Hampden-Smith et al.	7,075,576 B2	7/2006	Creasey et al.
6,211,955 B1	4/2001	Basiji et al.	7,081,927 B2	7/2006	Hirata et al.
6,224,969 B1	5/2001	Steenbergen et al.	7,091,500 B2	8/2006	Schnitzer
6,261,226 B1	7/2001	McKenna et al.	7,098,871 B1	8/2006	Tegreene et al.
6,262,855 B1	7/2001	Greisz	7,102,817 B1	9/2006	Wu
6,271,206 B1	8/2001	Pillai et al.	7,108,657 B2	9/2006	Irion et al.
6,280,960 B1	8/2001	Carr	7,153,299 B1	12/2006	Tu et al.
6,288,172 B1	9/2001	Goetz et al.	7,165,552 B2	1/2007	Deem et al.
6,319,745 B1	11/2001	Bertin et al.	7,166,537 B2	1/2007	Jacobsen et al.
6,322,498 B1	11/2001	Gravenstein et al.	7,167,317 B2	1/2007	Jung et al.
6,327,096 B1	12/2001	Tsuchida	7,186,251 B2	3/2007	Malecki et al.
6,352,503 B1	3/2002	Matsui et al.	7,218,822 B2	5/2007	Treado et al.
6,361,491 B1	3/2002	Hasegawa et al.	7,221,388 B2	5/2007	Sudo et al.
6,366,726 B1	4/2002	Wach et al.	7,234,816 B2	6/2007	Bruzzzone et al.
6,375,635 B1	4/2002	Moutafis et al.	7,247,847 B2	7/2007	Webb et al.
6,384,397 B1	5/2002	Takiar et al.	7,304,310 B1	12/2007	Shortt et al.
6,384,884 B1	5/2002	Nakamura et al.	7,393,321 B2	7/2008	Doguchi et al.
6,396,116 B1	5/2002	Kelly et al.	7,420,675 B2	9/2008	Giakos
6,407,768 B1	6/2002	Ishikawa	7,433,552 B2	10/2008	Kiesel
6,445,939 B1	9/2002	Swanson et al.	7,511,891 B2	3/2009	Messerschmidt
6,456,423 B1	9/2002	Nayfeh et al.	7,554,597 B2	6/2009	Scherling
6,471,636 B1	10/2002	Sano et al.	7,591,780 B2	9/2009	Jacobsen
6,485,413 B1	11/2002	Boppart et al.	7,629,659 B2	12/2009	Jacobsen
6,522,913 B2	2/2003	Panescu et al.	7,787,939 B2	8/2010	Jacobsen et al.
6,525,866 B1	2/2003	Lin et al.	7,823,215 B2	10/2010	Giakos
6,533,722 B2	3/2003	Nakashima	7,835,074 B2	11/2010	Jacobsen et al.
6,537,205 B1	3/2003	Smith	7,842,046 B1	11/2010	Nakao
6,551,302 B1	4/2003	Rosinko et al.	7,901,870 B1	3/2011	Wach
6,552,796 B2	4/2003	Magnin et al.	2001/0007051 A1	7/2001	Nakashima
6,561,972 B2	5/2003	Ooshima et al.	2001/0007511 A1	7/2001	Minami et al.
6,570,659 B2	5/2003	Schmitt	2001/0012053 A1	8/2001	Nakamura
6,573,950 B1	6/2003	Hirata et al.	2001/0024848 A1	9/2001	Nakamura
6,585,717 B1	7/2003	Wittenberg et al.	2001/0049509 A1	12/2001	Sekine et al.
6,595,913 B2	7/2003	Takahashi	2002/0007110 A1	1/2002	Irion
6,618,614 B1	9/2003	Chance et al.	2002/0034537 A1	3/2002	Schulze et al.
6,622,367 B1	9/2003	Bolduc et al.	2002/0039594 A1	4/2002	Unger
6,622,373 B1	9/2003	Tu et al.	2002/0080248 A1	6/2002	Adair et al.
6,624,138 B1	9/2003	Tu et al.	2002/0109774 A1	8/2002	Meron et al.
6,643,071 B2	11/2003	Schnitzer	2002/0111534 A1	8/2002	Suzuki et al.
6,658,279 B2	12/2003	Swanson et al.	2002/0166946 A1	11/2002	Iizuka et al.
6,659,941 B2	12/2003	Weber et al.	2002/0166949 A1	11/2002	Machida
6,695,787 B2	2/2004	Hogendijk et al.	2002/0168776 A1	11/2002	Cizdziel et al.
6,710,919 B1	3/2004	Clausen	2002/0188204 A1	12/2002	McNamara
6,719,686 B2	4/2004	Coakley et al.	2002/0193660 A1	12/2002	Weber
			2003/0071342 A1	4/2003	Honda et al.
			2003/0092995 A1	5/2003	Thompson
			2003/0114732 A1	6/2003	Webler et al.
			2003/0197812 A1	10/2003	Hirata et al.
			2003/0199761 A1	10/2003	Yock

(56)

References Cited

U.S. PATENT DOCUMENTS

2003/0202127 A1 10/2003 Hirata et al.
 2003/0208211 A1 11/2003 Kortenbach
 2003/0220574 A1 11/2003 Markus et al.
 2003/0222325 A1 12/2003 Jacobsen et al.
 2004/0006274 A1 1/2004 Giller et al.
 2004/0015049 A1 1/2004 Zaar
 2004/0017961 A1 1/2004 Petersen et al.
 2004/0059204 A1 3/2004 Marshall
 2004/0097788 A1* 5/2004 Mourlas A61B 1/00082
 600/116
 2004/0097804 A1 5/2004 Sobe
 2004/0111031 A1 6/2004 Alfano et al.
 2004/0115955 A1 6/2004 Motoyama et al.
 2004/0165858 A1 8/2004 Curatolo
 2004/0181148 A1 9/2004 Uchiyama et al.
 2004/0222031 A1 11/2004 Szalony et al.
 2004/0225222 A1 11/2004 Zeng et al.
 2004/0257566 A1 12/2004 Chism
 2004/0260148 A1 12/2004 Schnitzer
 2005/0004453 A1 1/2005 Tearney et al.
 2005/0054902 A1 3/2005 Konno
 2005/0065504 A1 3/2005 Melsky et al.
 2005/0084229 A1 4/2005 Babbitt et al.
 2005/0088576 A1 4/2005 Hirata et al.
 2005/0099824 A1 5/2005 Dowling et al.
 2005/0110892 A1 5/2005 Yun
 2005/0124875 A1 6/2005 Kawano et al.
 2005/0152421 A1 7/2005 Fujitani
 2005/0154277 A1 7/2005 Tang et al.
 2005/0158899 A1 7/2005 Jacobsen et al.
 2005/0171521 A1 8/2005 Brucker et al.
 2005/0174649 A1 8/2005 Okada et al.
 2005/0187568 A1 8/2005 Klenk et al.
 2005/0197534 A1 9/2005 Barbato et al.
 2005/0226636 A1 10/2005 Hiramatsu et al.
 2005/0231718 A1 10/2005 Goodall et al.
 2005/0234345 A1 10/2005 Yang
 2005/0264813 A1 12/2005 Giakos
 2005/0267340 A1 12/2005 Ishihara et al.
 2005/0288555 A1 12/2005 Binmoeller
 2006/0009682 A1 1/2006 Nagasawa et al.
 2006/0013593 A1 1/2006 Yokoo et al.
 2006/0017928 A1 1/2006 Crowther
 2006/0051036 A1 3/2006 Treado
 2006/0069312 A1 3/2006 O'Connor
 2006/0079835 A1 4/2006 Frassica
 2006/0106283 A1 5/2006 Wallace et al.
 2006/0135921 A1 6/2006 Wiercinski et al.
 2006/0142700 A1 6/2006 Sobelman et al.
 2006/0146172 A1 7/2006 Jacobsen et al.
 2006/0161048 A1 7/2006 Squicciarini
 2006/0181774 A1 8/2006 Ojima et al.
 2006/0252994 A1 11/2006 Ratnakar
 2006/0253088 A1 11/2006 Chow et al.
 2007/0010709 A1* 1/2007 Reinschke 600/116
 2007/0032796 A1 2/2007 Chin-Chen et al.
 2007/0066869 A1* 3/2007 Hoffman 600/121
 2007/0073321 A1 3/2007 Mikkaichi et al.
 2007/0083232 A1 4/2007 Lee
 2007/0088276 A1 4/2007 Stubbs et al.
 2007/0135803 A1 6/2007 Belson
 2007/0146887 A1 6/2007 Ikeda et al.
 2007/0208252 A1 9/2007 Makower
 2007/0228300 A1 10/2007 Smith
 2007/0233187 A1 10/2007 Lobello
 2007/0239066 A1 10/2007 Laham et al.
 2007/0255392 A1 11/2007 Johnson
 2007/0293727 A1 12/2007 Goldfarb et al.
 2008/0045794 A1 2/2008 Belson
 2008/0058601 A1 3/2008 Fujimori
 2008/0071141 A1 3/2008 Gattani et al.
 2008/0094326 A1 4/2008 Yamaki et al.
 2008/0114309 A1 5/2008 Zuckerman
 2008/0143822 A1 6/2008 Wang et al.
 2008/0160257 A1 7/2008 Takada et al.

2008/0177141 A1* 7/2008 Wu et al. 600/112
 2008/0183080 A1 7/2008 Abraham
 2008/0188767 A1 8/2008 Oaki et al.
 2008/0227893 A1 9/2008 Tamori et al.
 2008/0267562 A1 10/2008 Wang et al.
 2009/0027765 A1 1/2009 Kamijima
 2009/0036764 A1 2/2009 Rivas et al.
 2009/0054791 A1 2/2009 Flusberg
 2009/0082626 A1* 3/2009 Ichimura et al. 600/109
 2009/0119808 A1 5/2009 Giakos
 2009/0137928 A1 5/2009 Quick et al.
 2009/0143645 A1 6/2009 Matthes
 2009/0155371 A1 6/2009 Sojka et al.
 2009/0156899 A1 6/2009 Konishi
 2009/0180197 A1 7/2009 Jacobsen et al.
 2009/0213894 A1 8/2009 Grapov et al.
 2009/0234325 A1 9/2009 Rozenberg et al.
 2009/0267270 A1 10/2009 Murakami et al.
 2009/0287048 A1* 11/2009 Jacobson et al. 600/109
 2009/0306474 A1 12/2009 Wilson
 2010/0016662 A1 1/2010 Salsman et al.
 2010/0085567 A1 4/2010 Dottery et al.
 2010/0106134 A1 4/2010 Jolly et al.
 2010/0134872 A1 6/2010 Johnson et al.
 2010/0171821 A1 7/2010 Jacobsen et al.
 2010/0188492 A1 7/2010 Jacobsen et al.
 2010/0248178 A1 9/2010 Nahlieli
 2011/0204265 A1 8/2011 Smith et al.

FOREIGN PATENT DOCUMENTS

DE 19859434 7/2000
 EP 0482997 10/1991
 EP 0550 995 7/1993
 EP 0639043 2/1995
 EP 0681809 11/1995
 EP 1104182 5/2001
 EP 1195130 4/2002
 EP 1477104 11/2004
 EP 1488737 12/2004
 EP 1626436 2/2006
 EP 1647569 4/2006
 EP 1880656 1/2008
 JP 58-046924 3/1983
 JP S61-261713 11/1986
 JP 63-155115 6/1988
 JP H01-282514 11/1989
 JP H05-039501 2/1993
 JP 5 -049602 3/1993
 JP H05-197828 8/1993
 JP H07-148105 6/1995
 JP H07-222712 8/1995
 JP 08076028 3/1996
 JP 08084700 4/1996
 JP H09-021963 1/1997
 JP 11 137512 5/1999
 JP 2001008083 1/2001
 JP 2001314365 11/2001
 JP 2004004929 1/2004
 JP 2004086553 3/2004
 JP 2004094873 3/2004
 JP 2004329700 11/2004
 JP 2005006725 1/2005
 JP 2005334462 8/2005
 JP 2005533530 11/2005
 JP 2006162418 6/2006
 JP 2006314459 11/2006
 JP 2006320369 11/2006
 JP 2007167387 7/2007
 JP 2007312290 11/2007
 JP 2009067946 4/2009
 KR 10-20080027935 3/2008
 WO WO 98/38907 9/1998
 WO WO 99/40624 8/1999
 WO WO 00/54033 9/2000
 WO WO 03/081831 10/2003
 WO WO 2006/060777 6/2006
 WO WO 2007008876 1/2007
 WO WO 2007138889 A1* 12/2007 G02B 23/24

(56)

References Cited

FOREIGN PATENT DOCUMENTS

OTHER PUBLICATIONS

Jacobsen, Stephen C., U.S. Appl. No. 10/391,490, filed Mar. 17, 2003.

Jacobsen, Stephen C., U.S. Appl. No. 10/391,513, filed Mar. 17, 2003.

Jacobsen, Stephen C., U.S. Appl. No. 11/292/902, filed Dec. 1, 2005.

Jacobsen, Stephen C., U.S. Appl. No. 11/810,702, filed Jun. 5, 2007.

Jacobsen, Stephen C., U.S. Appl. No. 12/008,486, filed Jan. 11, 2008.

Jacobsen, Stephen C., U.S. Appl. No. 12/079,741, filed Mar. 27, 2008.

Jacobsen, Stephen C., U.S. Appl. No. 12/152,730, filed May 16, 2008.

Jacobsen, Stephen C., U.S. Appl. No. 12/487,481, filed Jun. 18, 2009.

Jacobsen, Stephen C., U.S. Appl. No. 12/512,188, filed Jul. 30, 2009.

Jacobsen, Stephen C.; U.S. Appl. No. 12/611,776, filed Nov. 3, 2009.

Jacobsen, Stephen C.; U.S. Appl. No. 12/792,562, filed Jun. 2, 2010.

Jacobsen, Stephen C.; U.S. Appl. No. 12/896,731, filed Oct. 1, 2010.

Jacobsen, Stephen C.; U.S. Appl. No. 12/896,732, filed Oct. 1, 2010.

Jacobsen, Stephen C.; U.S. Appl. No. 12/896,737, filed Oct. 1, 2010.

Jacobsen, Stephen C.; U.S. Appl. No. 12/896,743, filed Oct. 1, 2010.

Jacobsen, Stephen C.; U.S. Appl. No. 12/938,672, filed Nov. 3, 2010.

Jacobsen, Stephen C.; U.S. Appl. No. 12/946,442, filed Nov. 15, 2010.

Notice of Allowance for U.S. Appl. No. 12/611,776 dated Mar. 17, 2015, 18 pages.

Notice of Allowance for U.S. Appl. No. 12/896,732 dated May 18, 2015, 6 pages.

Notice of Allowance for U.S. Appl. No. 12/938,672 dated May 6, 201, 39 pages.

Notice of Allowance for U.S. Appl. No. 13/940,791 dated Oct. 28, 2015, 12 pages.

Office action for U.S. Appl. No. 12/896,731 dated Jan. 27, 2015, 19 pages.

Office action for U.S. Appl. No. 12/896,731 dated Jun. 26, 2014, 18 pages.

Office action for U.S. Appl. No. 12/896,731 dated Sep. 2, 2015, 14 pages.

Office action for U.S. Appl. No. 13/940,791 dated Jan. 5, 2015, 31 pages.

Office action for U.S. Appl. No. 13/940,791 dated Jun. 27, 2014, 38 pages.

Office action for U.S. Appl. No. 13/940,791 dated May 8, 2015, 28 pages.

Office action for U.S. Appl. No. 13/966,030 dated Aug. 6, 2015, 28 pages.

PCT Application PCT/US2010/051188; filed Oct. 1, 2010; Stephen C. Jacobsen; International Search Report mailed Jul. 13, 2011.

PCT Application PCT/US2010/051192; filed Oct. 1, 2010; Stephen C. Jacobsen; ISR mailed May 30, 2011.

PCT Application PCT/US2010/051198; filed Oct. 1, 2010; Stephen C. Jacobsen; ISR mailed Jun. 3, 2011.

PCT Application PCT/US2010/051200; filed Oct. 1, 2010; Stephen C. Jacobsen; ISR mailed Jun. 3, 2011.

Subrahmanyam et al, "A Text Book of Optics", XP055126947, Jan. 2004, ISBN: 978-8-12-192611-9, pp. 199-200, Retrieved on Jul. 4, 2014.

Tsuchida et al., "Design of Imaging Lens Systems That Use Low Dispersive Radial Gradient-Index Rod", Jun. 1998, pp. 3633-3637, vol. 37, No. 6B, Fig. 1,7,9, Japan Journal Appl. Phys., Japan.

U.S. Appl. No. 12/487,481, filed Jun. 18, 2009; Stephen C. Jacobsen; office action dated Oct. 12, 2012.


U.S. Appl. No. 12/512,188, filed Jul. 30, 2009; Stephen C. Jacobsen; office action dated Nov. 19, 2012.







U.S. Appl. No. 12/152,730, filed May 16, 2008; Stephen C. Jacobsen; office action issued Sep. 16, 2011.

Anonymous: "In vivo—Wikipedia, the free encyclopedia", Sep. 27, 2007 (Sep. 27, 2007), XP055244092, Retrieved from the Internet: URL:http://web.archive.org/web/20070927001435/http://en.wikipedia.org/wiki/In_vivo [retrieved on Jan. 22, 2016].

J. C. Jung: "In Vivo Mammalian Brain Imaging Using One- and Two-Photon Fluorescence Microendoscopy", Journal of Neurophysiology, val. 92, No. 5, Jul. 7, 2004 (Jul. 7, 2004), pp. 3121-3133.

* cited by examiner








FIG. 4




FIG. 5




FIG. 6a




FIG. 6b




FIG. 6c




FIG. 6d




FIG. 7a




FIG. 7b





FIG. 8

**FIG. 9**

TRANSPARENT ENDOSCOPE HEAD DEFINING A FOCAL LENGTH

PRIORITY

This application is a continuation of U.S. Ser. No. 12/487,495 filed on Jun. 18, 2009 entitled, "Transparent Endoscope Head Defining a Focal Length" and given patent number U.S. Pat. No. 8,690,762 claims priority to U.S. Provisional Ser. No. 61/132,566 filed on Jun. 18, 2008 entitled "Transparent Endoscope Head Defining a Focal Length" which are both incorporated herein by reference in their entirety.

FIELD OF THE INVENTION

The present invention relates to medical devices, and more particularly to miniaturized in-situ imaging devices and methods of operation of said devices.

BACKGROUND

The present invention relates generally to the field of endoscopy. More particularly, the present invention relates to improved endoscopic and catheter imaging.

Small imaging devices have become particularly useful in medical diagnostic and treatment applications. Portions of human anatomy previously viewable only by a surgical procedure can be viewed now by a minimally invasive catheterization, provided an imaging device can be made that is small enough to view the target anatomy.

Other uses for very small imaging devices are recognized. For example, such devices can be used and are desirable for surveillance applications, for monitoring of conditions and functions within devices, and for size and weight-critical imaging needs as are present in aerospace applications, to name a few.

While the present invention has applications in these aforementioned fields and others, the medical imaging application can be used to favorably illustrate unique advantages of the invention. The desirability of providing imaging at sites within the anatomy of living creatures, especially humans, distal of a small orifice or luminal space has long been recognized. A wide variety of types and sub-types of endoscopes have been developed for this purpose,

One advance in imaging technology which has been significant is the increased reduction of individual component sizes. Presently, charged coupled devices (CCD) such as miniature cameras can be manufactured so as to fit on the end of a catheter approximately the size of a couple of strands of wire. Lenses, optical fiber, and miniature surgical equipment can also be produced in miniature dimensions. However, these devices although functional and increasingly effective, can be difficult to position in order to appropriately image small areas of a target tissue.

For example, small cell carcinoma tends to start in the larger breathing tubes of the lungs. In its early stages it may only affect a small number of cells, covering a distance of only 20-40 microns across. Because it could be advantageous to image and diagnose this problem in this early stage before it rapidly grows and becomes quite large it is important to be able to access, locate and image these small areas. High resolution imaging can effectively view these cells if such locations can be found and if the imaging device can be appropriately positioned, focused, and imaged. This process is increasingly complicated in cases, such as small cell carcinoma, wherein the cell clusters are located in large passageways. While a larger endoscope could be used for

this procedure, a small catheter will substantially minimize patient trauma and duress. Presently, a user will be required to repeatedly move a small catheter or endoscope forward-and-backward, side-to-side in a trial and error fashion in attempts to acquire the target area within focus of the miniature camera. Typically, this process results in images that are not in complete focus and that can be difficult to diagnose.

SUMMARY

It has been recognized that it would be advantageous to develop a catheter that can be easily and effectively positioned so that a target object can be imaged substantially in focus.

Briefly, and in general terms, the invention is directed to a catheter configured for imaging objects substantially in focus. An imaging device is disposed on the distal end of the catheter. The imaging device has an effective focal plane that is located in front of the imaging device. The catheter also includes a transparent focal instrument that has an outer periphery that is positioned at the effective focal plane of the imaging device, to enable objects in contact with the outer periphery of the transparent focal instrument to be imaged substantially in focus.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will become more fully apparent from the following description and appended claims, taken in conjunction with the accompanying drawings. Understanding that these drawings merely depict exemplary embodiments of the present invention they are, therefore, not to be considered limiting of its scope. It will be readily appreciated that the components of the present invention, as generally described and illustrated in the figures herein, could be arranged and designed in a wide variety of different configurations. Nonetheless, the invention will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

FIG. 1 is a schematic illustration of an exemplary catheter in accordance with principles of the invention;

FIG. 2a is a side view of one embodiment of the catheter of FIG. 1;

FIGS. 2b-2d are side views of other embodiments of the catheter of FIG. 1;

FIGS. 3a -3b are side views of yet other embodiments of the catheter of FIG. 1;

FIG. 4 is a schematic illustration of a catheter having an inflatable balloon to position the imaging device in accordance with one embodiment of the invention;

FIG. 5 is a schematic illustration of an exemplary catheter having an inflatable balloon as a transparent focal instrument, in accordance with one embodiment of the invention;

FIGS. 6a and 6b are side views of one embodiment of the catheter of FIG. 4;

FIGS. 6c and 6d are side views of an additional embodiment of the catheter of FIG. 4;

FIGS. 7a-7b are side views of one embodiment of the catheter of FIG. 5;

FIG. 8 is a perspective view of one embodiment of the imaging device of FIG. 2a; and

FIG. 9 is a flowchart of a method for imaging with a catheter according to one embodiment of the present invention.

Reference will now be made to the exemplary embodiments illustrated, and specific language will be used herein

to describe the same. It will nevertheless be understood that no limitation of the scope of the invention is thereby intended.

DETAILED DESCRIPTION OF EXAMPLE EMBODIMENT(S)

The following detailed description of exemplary embodiments of the invention makes reference to the accompanying drawings, which form a part hereof and in which are shown, by way of illustration, exemplary embodiments in which the invention may be practiced. While these exemplary embodiments are described in sufficient detail to enable those skilled in the art to practice the invention, it should be understood that other embodiments may be realized and that various changes to the invention may be made without departing from the spirit and scope of the present invention. Thus, the following more detailed description of the embodiments of the present invention, as represented in FIGS. 1 through 9, is not intended to limit the scope of the invention, as claimed, but is presented for purposes of illustration only and to sufficiently enable one skilled in the art to practice the invention. Accordingly, the scope of the present invention is to be defined solely by the appended claims.

The following detailed description and exemplary embodiments of the invention will be best understood by reference to the accompanying drawings, wherein the elements and features of the invention are designated by numerals throughout. In describing and claiming the present invention, the following terminology will be used.

The singular forms “a,” “an,” and “the” include plural referents unless the context clearly dictates otherwise. Thus, for example, reference to “a camera device” includes reference to one or more of such camera devices, and reference to “an inflatable balloon” includes reference to one or more of such inflatable balloons.

As used herein, “catheter” refers to any one of a variety of catheter or endoscopic systems designed to imaging within the anatomy of living creatures or other appropriate system wherein imaging, surveillance, or other need is present. In one embodiment the catheter can comprise a miniature catheter having a SSID chip and a GRIN lens for imaging small locations with high resolution. Other imaging systems can be incorporated as will be apparent to one of ordinary skill in the art.

As used herein, “effective focal plane” or “main focal plane” refers to forward location in front of a camera/imaging device at which an object(s) is/are substantially in sharp focus or “in focus”. It is not intended that this location be a single point in space, rather it is intended that this focal point refer to the two or three-dimensional area in which an imaging device can image an object substantially in focus. An object imaged at this distance from the camera, given the proper lighting conditions, can have higher resolution and increased clarity than an object imaged at a closer or further distance. This effective focal plane will vary with different camera and imaging devices, as will be appreciated by one of ordinary skill in the art.

As used herein, “imaging device” refers to any one of the variety of catheter and endoscopic imaging devices, camera systems, fiber bundles, and other such devices known in the art. For example, the imaging device can include a SSID having an imaging array and a lens, as will be described in greater detail below.

As used herein, “solid state imaging device” or SSID in the exemplary embodiments generally comprises an imag-

ing array or pixel array for gathering image data, and can further comprise conductive pads electrically coupled to the imaging array, which facilitates electrical communication therebetween. In one embodiment, the SSID can comprise a silicon or other semiconductor substrate or amorphous silicon thin film transistors (TFT) having features typically manufactured therein. In another embodiment, the SSID can comprise a non-semiconductor substrate coated with a semiconductor material, or other equivalent structure. Features can include the imaging array, the conductive pads, metal traces, circuitry, etc. Other integrated circuit components can also be present for desired applications. However, it is not required that all of these components be present, as long as there is a means of gathering visual or photon data, and a means of sending that data to provide a visual image or image reconstruction.

“GRIN lens” or “graduated refractive index lens” refers to a specialized lens that has a refractive index that is varied radially from a center optical axis to the outer diameter of the lens. In one embodiment, such a lens can be configured in a cylindrical shape, with the optical axis extending from a first flat end to a second flat end. Thus, because of the differing refractive index in a radial direction from the optical axis, a lens of this shape can simulate the affects of a more traditionally shaped lens. In one embodiment, this is referred to as a GRIN rod lens. However, use of other suitable GRIN lens systems is contemplated for use herein.

As used herein, a plurality of items, structural elements, compositional elements, and/or materials may be presented in a common list for convenience. However, these lists should be construed as though each member of the list is individually identified as a separate and unique member. Thus, no individual member of such list should be construed as a de facto equivalent of any other member of the same list solely based on their presentation in a common group without indications to the contrary.

With reference to FIG. 1, the invention is embodied in a catheter, shown generally at **100**, including an imaging device and a transparent focal instrument **102** coupled to the catheter **100**, at a distal tip of the catheter **100**. The transparent focal instrument **102** has an outer periphery that is positioned at the effective focal plane of the imaging device. As shown, the outer periphery of the transparent focal instrument **102** can be placed in contact with bodily tissue **104** so that the bodily tissue can be in position to be “in focus” for imaging.

Because a target bodily tissue can be located in a relatively large bodily passage and because the catheter **100** is relatively small, as shown in FIG. 1, it is often difficult to position the catheter **100** in proper position, such as in the free space of a large bodily passage, so that it can position the target area “in focus” with respect to the camera. However, due to the nature of catheter systems the distal end of a catheter is frequently in contact with bodily tissue as it is directed along curved bodily passages and cavities. When a semi-flexible catheter is directed along a bodily passage, for example, the lungs, veins, or gastrointestinal (GI) tract, the distal end of the catheter will typically be in contact with the outer edge of these passages when being directed around a turn. At these points of contact, the catheter having the transparent focal instrument can effectively image the outer walls of these passages in detailed and accurate focus.

The imaging device can include various camera and lens devices. In one exemplary embodiment the imaging device can include a SSID chip **132** and GRIN rod lens **130**, as shown in FIG. 8. The SSID **132** can comprise a silicon or other semiconductor substrate or amorphous silicon thin film

transistors (TFT) having features typically manufactured therein. In another embodiment, the SSID **132** can comprise a non-semiconductor substrate coated with a semiconductor material, or other equivalent structure. Features including the imaging array **134**, the conductive pads (not shown), metal traces (not shown), circuitry (not shown), etc., can be fabricated therein. With respect to the conductive pads, the connection between conductive pads and a conductive line of an umbilical or catheter body can be through soldering, wire bonding, solder bumping, eutectic bonding, electroplating, and conductive epoxy. However, a direct solder joint having no wire bonding between the electrical umbilical and the conductive pads can be preferred as providing good steerability can be achieved with less risk of breaking electrical bonding. In one embodiment, the conductive line of the umbilical can provide power, ground, clock signal, and output signal with respect to the SSID **132**. Other integrated circuit components can also be present for desired applications, such as light emitting diodes (LEDs), for providing light to areas around the GRIN rod lens **130**.

It is not required that all of these components be present, as long as there is a visual data gathering and sending image device present, and some means provided to connect the data gathering and sending device to a visual data signal processor. Other components, such as the umbilical, housing, adaptors, utility guides, and the like, can also be present, though they are not shown in FIG. **8**. The SSID **132** can be any solid state imaging device, such as a CCD, a CID, or a CMOS imaging device. Also, the GRIN rod lens **130** can be coated with an opaque coating on the curved surface to prevent light from entering the lens at other than the flat surface that is most distal with respect to the SSID **132**. Additional principles of operation and details of construction of similar micro-camera assemblies can be found in U.S. patent application Ser. Nos. 10/391,489, 10/391,490, 11/292,902, and 10/391,513 each of which are incorporated herein by reference in their entireties.

Reference will now be made to FIGS. **2a-3b**, which depict various embodiments of transparent focal instruments, in accordance with the principles of the invention. The catheter **100** includes an imaging device **106**. A transparent focal instrument **102** is coupled to the camera, for instance, the transparent focal instrument **102** can be coupled to the imaging device **106**, as shown in FIGS. **2a-2b**, or coupled to the catheter body as shown in FIGS. **2c-3b**. The transparent focal instrument **102** is configured to have an outer periphery that is positioned at a distance approximately equal to the distance from the imaging device **106** to the effective focal plane of the imaging device **106**. This distance is represented at **103**.

As different camera systems can have varying angles of view, the transparent focal instrument can have respectively varied shapes, contours, lengths, and other such properties. The exemplary embodiments of FIGS. **2a-3b** are intended to be presented herein as examples and are not intended to be all inclusive regarding the type, shape, or dimensions of potential transparent focal instruments.

The transparent focus instrument **102** can be a hollow spacer, solid spacer, inflatable or inflated balloon, or other such device as will be apparent to one of ordinary skill in the art. The spacer can be composed of glass or a transparent polymer which includes common transparent plastics such as polystyrene, polycarbonate, or PET.

Multiple imaging devices **106** can be included on a single catheter **100**, as shown in FIGS. **3a-3b**. Accordingly, the transparent focus instrument **102** can be configured to have an outer periphery at the effective focal plane of each

imaging device **106**. When conducting certain endoscopic procedures it may be advantageous to include imaging devices that can image in lateral directions. Typically, catheter devices have a limit to the flexibility of the catheter body which limits the device's ability to turn and face a lateral object when in small or narrow passageways. As such, by including an imaging device that faces in one or more lateral directions as well as one or more transparent focal instruments, respectively, the catheter can be directed down a narrow passage of the body while imaging "in focus" the wall of the bodily passage.

In another embodiment the catheter **100** can include a turning device, as is known in the art. The turning device (not shown) can assist the catheter **100** to be directed to a target area of the body as well as turning the distal end of the catheter **100**, including the imaging device **106** and transparent focal instrument **102** towards a target object or area. This turning device can assist a user to accurately position the periphery of the transparent focal instrument **102** in contact with a desired tissue.

FIG. **4** depicts the catheter **100** according to one embodiment of the present invention, being directed through a bodily passage **104**. In this exemplary situation, the bodily passage **104** is substantially larger than the catheter **100** such that the transparent focal instrument **102** is not naturally in contact with the passage wall. An inflatable balloon **110**, coupled to the catheter **100**, which can be inflated to force the transparent focal instrument **102** in contact with the passage wall. Such a balloon can be designed and constructed by methods and materials currently known in the art.

FIGS. **6a-6b** illustrate a function of the inflatable balloon **116** represented in FIG. **4**. As shown, the catheter **100** can include a laterally-oriented imaging device **106** having a transparent focal instrument **102g**. The inflatable balloon **116** is disposed on the side opposite the imaging device **106** and is attached to a fluid source **118** configured to inflate and deflate the balloon **116** with a fluid. As shown in FIG. **6a**, the transparent focal instrument **102g** is not initially in contact with the bodily passage wall **104**. FIG. **6b** shows a fluid **120** being inserted into the balloon. The fluid **120** can include air, oxygen, saline solution, or other fluid known in the art. As the balloon **116** is filled with the fluid **120**, the transparent focal instrument **102g** is positioned in contact with the passage wall **104**. As will be apparent, the balloon **116** can include a variety of shapes and sizes according to the needs of the user. In one embodiment, the balloon **116** can be non-spherically shaped when inflated, to allow the passage of fluids within the bodily passage, as shown in FIG. **4**. In another embodiment, the catheter **100** can include more than one inflatable balloon **116**, which can each selectively be inflated to position the transparent focal instrument **102g** in contact with a target object/location. In another embodiment, the balloon **116** comprises a toroidal or torus structure to allow the passage of fluids through the otherwise occluded vessel.

Referring now to FIGS. **6c** through **6d**, a different method of laterally positioning the transparent focal instrument **102g** is illustrated. In this embodiment the balloon shown in FIGS. **6a** and **6b** is replaced with a piece of preformed wire **117**, which when extended from the catheter **100** forms a coil which moves the transparent focal instrument **102g** into contact with a target object/location. In one embodiment, the preformed wire **117** comprises a shape memory alloy such as Nitinol. In one aspect of the invention a plurality of imaging devices **106** may be disposed lengthwise along a side of the catheter body with corresponding focal instruments **102g**

and positioning devices. In this manner, a practitioner may capture numerous images of an interior of a patient as the catheter **100** is advanced within the patient.

FIG. **5** depicts the catheter **100** according to one embodiment of the present invention, wherein the transparent focal instrument is in the form of a transparent inflatable balloon **112**. When inflated the transparent inflatable balloon **112** has an outer periphery that is positioned at the effective focal plane of the imaging device, to enable objects in contact with the outer periphery of the transparent focal instrument to be imaged substantially in focus. The use of a flexible, transparent balloon **112** as a transparent focal instrument allows the catheter to maintain miniature dimensions due to the relatively low volume and flexibility of the balloon. Additionally, the transparent balloon **112** can act as an optical environment for the imaging device, displacing the fluids and other material that can obstruct the imaging path of the imaging device.

FIGS. **7a-7b** illustrate a function of the transparent balloon of FIG. **5** according to one embodiment of the present invention. In one aspect of the invention, catheter **100** comprises a lumen **124** extending from a distal end of the catheter **100** to a side portion of the catheter **100**. When deflated the transparent balloon **122** can be positioned along the catheter body, as shown in FIG. **7a** effectively blocking the opening of lumen **124** on the lateral portion of the catheter body. As illustrated in FIG. **7b**, when inflated, the transparent balloon **122** can form a transparent focal instrument wherein the distance **103** from the imaging device **106** to the outer periphery of the inflatable balloon **122** is equal to the distance **103** of the imaging device **106** to its focal plane. When in its inflated state, lumen **124** is open to the passage of fluids **126** through the vessel of the patient. Advantageously, while the distal end of the catheter **100** effectively occludes passage of any fluids **126** through the vessel of the patient, lumen **124** acts a temporary passageway for the fluids **126**. While a single balloon-imaging device combination is shown, it will be understood that a plurality of such combinations can be included with the present invention. In one exemplary embodiment of the invention the catheter **100** can include four such combinations positioned around the circumference of the catheter body. Each of these four transparent balloons can be selectively inflated, either synchronously or separately in order to image the walls of a bodily passage or bodily organ. Additionally, the transparent balloon-imaging device combination can be positioned in a forward facing orientation, as shown in FIG. **5**. The balloon can be inflated with air, oxygen, saline solution, or other fluid common to the art of balloon catheterization.

In another embodiment, the imaging device comprises a plurality of micro-cameras each having a different effective focal length and corresponding transparent focal instrument attached thereto. In one aspect, one of the plurality of imaging devices has a field of view that is larger than the other imaging devices. In yet another aspect, one of the plurality of imaging devices has magnification capabilities. In yet another aspect, the plurality of imaging devices may be oriented parallel to one another or may be configured in a non-parallel orientation as suits a particular application. Additional principles of operation and details of construction of GRIN lens microscope assemblies can be found in U.S. patent application Ser. No. 12/008,486 filed Jan. 1, 2008 and entitled "Grin Lens Microscope System" which is incorporated herein by reference in its entirety.

FIG. **9** is a flowchart of a method for imaging with a catheter. The method first includes providing a catheter with

a transparent focal instrument having an outer periphery that is positioned at the effective focal plane of an imaging device **210**. The transparent focal instrument can be of a variety of configurations as described in detail above. Next, the method includes positioning the outer periphery of the transparent focal instrument in contact with a target object, to enable a target object in contact with the outer periphery of the transparent focal instrument to be imaged substantially in focus **220**. Various methods and devices can be used to position the transparent focal instrument in contact with a target object. In addition to the methods and devices described above, the catheter body can be rotated around its longitudinal axis and/or the imaging device can include turning devices, such as piezoelectric actuators, for tilting and/or moving the imaging device. Additionally, the focal length of the camera can be modified in certain cameras, while the distance between the imaging device and the outer periphery of the transparent focal instrument is respectively modified. Lastly, the target object is imaged by the imaging device **230**. In one embodiment of the present invention, the imaging device can be constantly imaging, so as to record and display live images to a user. Alternatively, the imaging device can include an additional feature, wherein enhanced images are selectively taken, that can be analyzed and viewed to assist in diagnosis and analysis.

Advantageously, embodiments of the present invention include a transparent focal instrument for a catheter to assist a medical practitioner to image objects that are in contact with the transparent focal instrument substantially "in focus." Thus, improved catheter imaging can be achieved by maneuvering the transparent focal instrument in contact with a target tissue/object. Such a maneuver can reduce the trial-and-error procedure of maneuvering the distal end of a catheter within a bodily passage/cavity. This can allow a user to image more tissue in less time and with higher resolution because the transparent focal instrument can be passed over a potentially diseased area or quickly and repeatedly positioned against a passage wall as it is directed down the passage. Additionally, this device can substantially enhance a catheter's ability to image critical tissue, such as potentially cancerous cells/regions in higher definition and with increased clarity, thus increasing a user's ability to diagnose and treat problems. As such this device can dramatically improve a doctor's ability to detect various illnesses and diseases at their early stages.

While the forgoing examples are illustrative of the principles of the present invention in one or more particular applications, it will be apparent to those of ordinary skill in the art that numerous modifications in form, usage and details of implementation can be made without the exercise of inventive faculty, and without departing from the principles and concepts of the invention. Accordingly, it is not intended that the invention be limited, except as by the claims set forth below.

What is claimed is:

1. A catheter configured for imaging objects substantially in focus, comprising:

- a) an imaging device disposed on a distal end of the catheter, the imaging device having an effective focal plane;
- b) a transparent focal instrument coupled to the catheter, the transparent focal instrument having an outer periphery, wherein a length from the imaging device to the outer periphery of the transparent focal instrument is equal to the distance from the imaging device to the effective focal plane of the imaging device; wherein when the outer periphery is positioned at the effective

focal plane of the imaging device, it enables objects in contact with the outer periphery of the transparent focal instrument to be imaged substantially in focus; and

c) an open channel having a first orifice disposed about a side surface of the catheter in fluid communication with a second orifice on a distal end of the catheter, wherein the imaging device is located inside an inflatable balloon and wherein the inflatable balloon is configured to cover the first orifice of the catheter when deflated for limiting fluid communication in the open channel.

2. The catheter of claim 1, wherein the imaging device comprises a solid state imaging device including an imaging array and a graduated refractive index lens optically coupled to the imaging array of the solid state imaging device.

3. The catheter of claim 2, wherein the transparent focal instrument is coupled to the graduated refractive index lens.

4. The catheter of claim 1, wherein the imaging device includes at least two imaging devices.

5. The catheter of claim 1, wherein the imaging device is configured to image in a lateral direction with respect to a longitudinal axis of the catheter.

6. A catheter configured for imaging objects substantially in focus, comprising: a) an imaging device disposed on a distal end of the catheter, the imaging device having an effective focal plane; b) a transparent focal instrument coupled to the catheter, the transparent focal instrument having first and second positions, wherein when disposed in the second position, the transparent focal instrument has a length that is equal to the distance between the imaging device and the effective focal plane of the imaging device and is positioned at the effective focal plane of the imaging device to enable a target object in contact with an outer periphery of the transparent focal instrument to be imaged substantially in focus, wherein the transparent focal instrument comprises an inflatable balloon; and c) a channel having a first orifice disposed about a side surface of the catheter adjacent a distal end of the catheter, and a second orifice disposed about a distal end of the catheter, the first orifice being in fluid communication with the second orifice, wherein when the inflatable balloon is disposed in the second position, the channel extends from a first side of the inflatable balloon to a second side of the inflatable balloon to permit fluids within a vessel of a patient to pass from one side of the inflatable balloon to the second side of the inflatable balloon, wherein when the inflatable balloon is disposed in the first position, the inflatable balloon is configured to cover the first orifice of the catheter for limiting fluid communication in the channel.

7. A method for imaging with a catheter, comprising:

a) providing a catheter having a channel disposed therein and a transparent focal instrument, the transparent focal instrument comprising first and second positions wherein when the transparent focal instrument is disposed in the first position, the transparent focal instrument covers an opening of the channel and wherein when the transparent focal instrument is disposed in the second position, the transparent focal instrument does not cover the opening of the channel and has an outer periphery with a length equal to the length of the effective focal plane, the transparent focal instrument being positioned at an effective focal plane of an imaging device;

b) inserting the catheter into a cavity of a patient while the transparent focal instrument is disposed in the first position;

c) after inserting the catheter into the cavity of the patient, disposing the transparent focal instrument in the second position thereby occluding the cavity of the patient with the transparent focal instrument and removing the transparent focal instrument from the opening of the channel; and

d) imaging a target object.

8. The method of claim 7, wherein the transparent focal instrument comprises a balloon.

9. The method of claim 8, wherein positioning the outer periphery of the transparent focal instrument includes inflating the balloon disposed on the catheter to move a distal end of the balloon in contact with the target object.

10. The method of claim 7, wherein the transparent focal instrument comprises a transparent balloon having an inflated length substantially equivalent to the effective focal plane of the imaging device.

11. The method of claim 7, wherein the imaging device is configured to image objects lateral to a longitudinal axis of the catheter.

12. The method of claim 7, wherein positioning the outer periphery of the transparent focal instrument includes inflating a balloon disposed on the catheter to move a distal end of the balloon in contact with the target object.

13. The method of claim 12, wherein the transparent focal instrument is substantially solid.

14. The method of claim 12, further comprising a plurality of imaging devices disposed about an exterior of the catheter and a plurality of balloons, each balloon enclosing a single imaging device.

* * * * *