



US009526940B2

(12) **United States Patent**
Renk

(10) **Patent No.:** **US 9,526,940 B2**
(45) **Date of Patent:** **Dec. 27, 2016**

(54) **MULTI-HANDLED WEIGHTED FITNESS DEVICE**

USPC D21/680-682
See application file for complete search history.

(71) Applicant: **Martin P Renk**, Winona, MN (US)

(56) **References Cited**

(72) Inventor: **Martin P Renk**, Winona, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

U.S. PATENT DOCUMENTS

(21) Appl. No.: **14/146,318**

1,877,218	A *	9/1932	Blank	482/126
3,536,326	A *	10/1970	Yatrides	A63B 21/0004 482/126
4,018,442	A *	4/1977	Galler	482/106
4,333,645	A *	6/1982	Wu	A63B 21/00043 482/112
4,461,473	A *	7/1984	Cole	482/106
4,822,035	A *	4/1989	Jennings et al.	482/106
5,031,906	A *	7/1991	Jang	A63B 21/0004 482/125
5,735,779	A *	4/1998	Lay	482/93
7,097,601	B1 *	8/2006	Ronnow	482/106
2010/0323854	A1 *	12/2010	Brandenburg	482/106

(22) Filed: **Jan. 2, 2014**

(65) **Prior Publication Data**

US 2014/0187392 A1 Jul. 3, 2014

Related U.S. Application Data

(60) Provisional application No. 61/748,610, filed on Jan. 3, 2013.

(51) **Int. Cl.**

A63B 21/062 (2006.01)
A63B 21/072 (2006.01)
A63B 21/075 (2006.01)
A63B 21/078 (2006.01)

* cited by examiner

Primary Examiner — Loan H Thanh

Assistant Examiner — Nyca T Nguyen

(74) *Attorney, Agent, or Firm* — Geiser Law, PLLC; Greg N. Geiser

(52) **U.S. Cl.**

CPC *A63B 21/0724* (2013.01); *A63B 21/072* (2013.01); *A63B 21/0726* (2013.01); *A63B 21/4035* (2015.10)


(57) **ABSTRACT**

A multi-handled weighted fitness device. The device is a free weight comprised of a rectangular frame connected by a pair of opposing Y-shaped weighted members. The rectangular frame is comprised of four cylindrical side members that can be variously gripped by a user. The size of the opposing Y-shaped weighted members can be varied to alter the weight of the device. A central connecting member is joined to a base stem of each of the opposing Y-shaped weighted members. A user can also optionally grip the central connecting member.

(58) **Field of Classification Search**

CPC A63B 21/0004; A63B 21/00079; A63B 21/00094; A63B 21/00101; A63B 21/00116; A63B 21/0013; A63B 21/06; A63B 21/072; A63B 21/0722; A63B 21/0724; A63B 21/0726; A63B 21/0728; A63B 21/14; A63B 21/1453; A63B 21/1465; A63B 21/1469; A63B 21/148; A63B 21/1484; A63B 21/075; A63B 21/0786

4 Claims, 2 Drawing Sheets






Fig. 1




Fig. 2

1**MULTI-HANDLED WEIGHTED FITNESS
DEVICE****CROSS REFERENCE TO RELATED
APPLICATIONS**

This application claims the benefit of provisional patent application Ser. No. 61/748,610 filed 2013 Jan. 3 by the present inventor.

**FEDERALLY SPONSORED RESEARCH OR
DEVELOPMENT**

Not Applicable

**SEQUENCE LISTING, A TABLE, OR A
COMPUTER PROGRAM**

Not Applicable

FIELD OF THE INVENTION

The present invention relates to a weighted device for strength-building exercises.

BACKGROUND OF THE INVENTION

Free weights familiar in this field of invention, such as kettlebells, dumbbells, and straight bars combined with weighted plates, generally provide only a very limited number of gripping options for a user engaged in strength-building exercises. A user can benefit, however, from gripping the free weights in a variety of different ways while exercising. These grip changes allow a user to lift the free weights in different ways to exercise a wider variety of muscle groups. Additionally, most free weights that can be used without a straight bar do not allow the option of being used in combination with a straight bar.

SUMMARY OF THE INVENTION

In a free weight embodying the principles of the invention, a user can grip the free weight in a wide variety of different ways. Also, the free weight is designed to be attached, at the user's option, to an Olympic-sized barbell.

The free weight is comprised of a pair of opposing Y-shaped weighted members connected by opposed side members and a central connecting member forming a coplanar rectangular frame. The four sides being a first side member, a second side member, a third side member, and a fourth side member, in the same plane. The four side members being cylindrical, have substantially the same diameter. The first side member and the second side member, having the same length, oppose each other across the rectangular frame. The third side member and the fourth side member, having the same length, oppose each other across the rectangular frame. The four side members function as handles for use in gripping and lifting the free weight and define the perimeter of the rectangle exclusive of four corner joints.

A first Y-shaped weighted member has three stems, the three stems being a first stem, a second stem, and a third stem. The three stems radiate outward from a central point on the first Y-shaped weighted member. The first stem forming a base of the Y, and the second stem and the third stem forming together an upper V-shaped element of the Y and forming the corners of device.

2

The first stem of the first Y-shaped weighted member is positioned equidistant between the third side member and the fourth side member, projecting perpendicularly away from the first side member and toward the second side member. The first stem has a first distal end opposite the first side member.

The second stem of the first Y-shaped weighted member projects away from the central point of the first Y-shaped weighted member culminating to form a first corner joint connecting the first side member and the third side member. The third stem projects away from the central point of the first Y-shaped weighted member culminating to form a fourth corner joint connecting the first side member and the fourth side member.

A second Y-shaped weighted member has a mirror image structure of the first Y-shaped weighted member, having three stems, the three stems being a first stem, a second stem, and a third stem, the stems radiating outward from a central point of the second Y-shaped weighted member. The first stem forming a base of the Y, and the second stem and the third stem forming together an upper V-shaped element of the Y and forming the corners of device.

The second first stem of the second Y-shaped weighted member is positioned equidistant between the third side member and the fourth side member, projecting perpendicularly away from the second side member and toward the first side member. The second first stem has a distal end opposite the second side member.

The second stem of the second weighted member projects away from the central point of the second Y-shaped weighted member culminating to form a second corner joint connecting the second side member and the third side member. The third stem projects away from the central point of the second Y-shaped member culminating to form a third corner joint connecting the second side member and the fourth side member.

Preferably, the side members are received by boreholes in the corner joints sized to tightly receive the side members.

The central connecting member, having substantially the same diameter as the four side members, is centrally adjoined to both the first distal end and the second distal end of the opposing mirror-image Y-shaped weighted members, wherein the length of the central connecting member is selected to maintain the rectangular shape of the free weight. The central connecting member functions as a handle for use in gripping and lifting the free weight.

Preferably, the central connecting member is received by boreholes, sized to tightly receive the central connecting member, bored into the first distal end and the second distal end of the opposing mirror-image Y-shaped weighted members.

In the preferred embodiment shown, a circular aperture is placed near the central point of both Y-shaped weighted members. Ideally, the circular aperture has a diameter of two inches, allowing a user to slide the free weight onto an Olympic-sized barbell.

The Y-shaped weighted members can be varied in thickness to alter the overall mass of the free weight.

The free weight is designed to be a weighted exercise device so it is preferably constructed of a durable, heavy material such as steel. Although steel is preferred, other similar metals and other materials may be used to construct the free weight, including a combination of different materials for the Y-shaped weighted members, side members, and central connecting member. To improve comfort and grip, the side members and central connecting member may also

be taped, coated, or wrapped with a rubber or a rubber-like material, or some other cushioned material such as foam.

Although several varying thicknesses and overall dimensions of the free weight device may be used, it is preferred that the length of the device be thirty (30) inches and the width of the device be nine (9) inches. The length and width being defined by the length of the side member plus the length of the pair of opposed corner joints connected to the side member. Further, it is preferred that the Y-shaped weighted members and have a thickness varying between one and one quarter (1.25) inches and two (2) inches.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

The accompanying drawings are included to provide a further understanding of the present invention and are incorporated in and constitute a part of this specification. The drawings illustrate exemplary embodiments of the present invention and together with the description serve to further explain the principles of the invention. Other aspects of the invention and the advantages of the invention will be better appreciated as they become better understood by reference to the Detailed Description when considered in conjunction with accompanying drawings, and wherein:

FIG. 1 is an isometric side view of the free weight, according to the present invention;

FIG. 2 is a top view of the free weight, according to the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Referring now to FIG. 1-2, a free weight is generally referred to as **10**. The free weight **10** is comprised of a pair of opposing Y-shaped weighted members **300** and **400** connected by opposed side members **101**, **102**, **201**, **202** and a central connecting member **500** and forming a co-planar rectangular frame. The four sides being a first side member **101**, a second side member **102**, a third side member **201**, and a fourth side member **202**, in the same plane. The four side members (**101**, **102**, **201**, and **202**), being cylindrical, have substantially the same diameter. The first side member **101** and the second side member **102**, having the same length, oppose each other across the rectangular frame. The third side member **201** and the fourth side member **202**, having the same length, oppose each other across the rectangular frame. The four side members (**101**, **102**, **201**, and **202**) function as handles for use in gripping and lifting the free weight **10** and define the perimeter of the rectangle exclusive of four corner joints.

A first Y-shaped weighted member **300**, has three stems, the three stems being a first stem **301**, a second stem **302**, and a third stem **303**. The three stems radiate outward from a central point on the first Y-shaped weighted member **300**. The first stem **301** forming a base of the Y, and the second stem **302** and the third stem **303** forming together an upper V-shaped element of the Y and forming the corners of device **10**.

The first stem **301** of the first Y-shaped weighted member **300** is positioned equidistant between the third side member **201** and the fourth side member **202**, projecting perpendicularly away from the first side member **101** and toward the second side member **102**. The first stem **301** has a first distal end **310** opposite the first side member **101**.

The second stem **302** of the first Y-shaped weighted member **300** projects away from the central point of the first

Y-shaped weighted member **300** culminating to form a first corner joint **320** connecting the first side member **101** and the third side member **201**. The third stem **303** projects away from the central point of the first Y-shaped weighted member **300** culminating to form a fourth corner joint **330** connecting the first side member **101** and the fourth side member **202**.

A second Y-shaped weighted member **400** has a mirror image structure of the first Y-shaped weighted member **300**, having three stems, the three stems being a first stem **401**, a second stem **402**, and a third stem **403**, the stems radiating outward from a central point of the second Y-shaped weighted member **400**. The first stem **401** forming a base of the Y, and the second stem **402** and the third stem **403** forming together an upper V-shaped element of the Y and forming the corners of device **10**.

The second first stem **401** of the second Y-shaped weighted member **400** is positioned equidistant between the third side member **201** and the fourth side member **202**, projecting perpendicularly away from the second side member **102** and toward the first side member **101**. The second first stem **401** has a distal end **410** opposite the second side member **102**.

The second stem **402** of the second weighted member **400** projects away from the central point of the second Y-shaped weighted member **400** culminating to form a second corner joint **420** connecting the second side member **102** and the third side member **201**. The third stem **403** projects away from the central point of the second Y-shaped member **400** culminating to form a third corner joint **430** connecting the second side member **102** and the fourth side member **202**.

Preferably, the side members are received by boreholes in the corner joints (**320**, **330**, **420**, and **430**) sized to tightly receive the side members (**101**, **102**, **201**, and **202**).

The central connecting member **500**, having substantially the same diameter as the four side members (**101**, **102**, **201**, and **202**), is centrally adjoined to both the first distal end **310** and the second distal end **410** of the opposing mirror-image Y-shaped weighted members **300** and **400**, wherein the length of the central connecting member **500** is selected to maintain the rectangular shape of the free weight **10**. The central connecting member **500** functions as a handle for use in gripping and lifting the free weight **10**.

Preferably, the central connecting member **500** is received by boreholes, sized to tightly receive the central connecting member **500**, bored into the first distal end **310** and the second distal end **410** of the opposing mirror-image Y-shaped weighted members **300** and **400**.

In the preferred embodiment shown, a circular aperture **600** is placed near the central point of both Y-shaped weighted members **300** and **400**. Ideally, the circular aperture **600** has a diameter of two inches, allowing a user to slide the free weight **10** onto an Olympic-sized barbell.

The Y-shaped weighted members **300** and **400** can be varied in thickness to alter the overall mass of the free weight **10**.

The free weight **10** is designed to be a weighted exercise device so it is preferably constructed of a durable, heavy material such as steel. Although steel is preferred, other similar metals and other materials may be used to construct the free weight **10**, including a combination of different materials for the Y-shaped weighted members **300** and **400**, side members (**101**, **102**, **201**, and **202**), and connecting member **500**. To improve comfort and grip, the side members (**101**, **102**, **201**, and **202**) and central connecting member **500** may also be taped, coated, or wrapped with a rubber or a rubber-like material, or some other cushioned material such as foam.

5

Although several varying thicknesses and overall dimensions of the free weight device **10** may be used, it is preferred that the length of the device be thirty (30) inches and the width of the device be nine (9) inches. The length and width being defined by the length of the side member plus the length of the pair of opposed corner joints connected to the side member. Further, it is preferred that the Y-shaped weighted members **300** and **400** have a thickness varying between one and one quarter (1.25) inches and two (2) inches.

While the invention has been described with reference to an exemplary embodiment(s), it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted for elements thereof without departing from the scope of the invention. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the invention without departing from the essential scope thereof. Therefore, it is intended that the invention not be limited to the particular embodiment(s) but that the invention will include all embodiments falling with the scope of the appended claims.

What is claimed is:

1. A free weight device, the device comprising:

a pair of Y-shaped weighted members, each Y-shaped weighted member of the pair of Y-shaped weighted members having a stem portion, an upper-V portion, and being a mirror image of each other, each Y-shaped weighted member of the pair of Y-shaped weighted members containing an aperture;

four side members, each side member of the four side members are cylindrical and having an identical diameter, each side member of the four side members attached co-planar to the upper-V portions of the Y-shaped weighted members and forming a rectangular shaped periphery of the device; and

a central connecting member, the central connecting member is cylindrical and having a diameter, the diameter identical to the diameter of the four side members,

6

the central connecting member connecting each Y-shaped member of the pair of Y-shaped members at the stem portion.

2. The device as in claim 1, wherein the four side members and the central connecting member each have a gripping surface.

3. A free weight device, the free weight device having a rectangular shaped periphery and comprising:

a pair of Y-shaped weighted members, each Y-shaped weighted member of the pair of Y-shaped weighted members being a mirror image of each other, each Y-shaped member having a stem portion and an upper-V portion, each of the upper-V portions forming four corners of the rectangular shaped periphery;

a first pair of side members, the first pair of side members are cylindrical and having a diameter, each side member of the first pair of side members attached co-planar to the opposed upper-V portions of the Y-shaped weighted members and forming two sides of the rectangular shaped periphery of the device;

a second pair of side members, the second pair of side members are cylindrical and having a diameter identical to the diameter of the first pair of side members, each side member of the second pair of side members attached co-planar to the upper-V portions of the Y-shaped weighted members and connected to the upper-V portion of the same Y-shaped weighted member and forming two sides of the rectangular shaped periphery of the device; and

a central connecting member, the central connecting member cylindrical and having a diameter identical to the first pair of side members and the second pair of side members, the central connecting member connecting each of the Y-shaped members at the stem portion.

4. The device as in claim 3, wherein the first pair of side members, the second pair of side members, and the central connecting member each have a gripping surface.

* * * * *