



US009527565B1

(12) **United States Patent**
Guidry

(10) **Patent No.:** **US 9,527,565 B1**
(45) **Date of Patent:** **Dec. 27, 2016**

(54) **THRUSTER AIDED STEERING SYSTEM**

5,642,684 A 7/1997 Aker
6,325,010 B1 12/2001 Gruenwald
6,350,164 B1* 2/2002 Griffith, Sr. B63H 5/08
114/144 B

(71) Applicant: **Luke Guidry**, Larose, LA (US)

2009/0072084 A1 3/2009 Hankinson

(72) Inventor: **Luke Guidry**, Larose, LA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

FR 1441046 A 6/1966

OTHER PUBLICATIONS

Fleeting Up, retrieved from <http://www.mcdermott.com/SiteCollectionDocuments/Pipeline%20-%20McDERMOTT%20vessel%20upgrades.pdf> on Jul. 25, 2014, McDermott Today, pp. 30-36.
Shipbuilding 101, retrieved from http://comeroids.wikia.com/wiki/Shipbuilding_101 on Jul. 25, 2014, pp. 1-2.
OmniTHRUSTER, Marine Maneuvering and Propulsion Systems, retrieved from www.omnithruster.com/htbrochure.pdf on Jan. 15, 2015, pp. 1-4.

* cited by examiner

Primary Examiner — Anthony Wiest

(74) *Attorney, Agent, or Firm* — Jones Walker, LLP

(21) Appl. No.: **14/872,562**

(22) Filed: **Oct. 1, 2015**

Related U.S. Application Data

(60) Provisional application No. 62/059,689, filed on Oct. 3, 2014.

(51) **Int. Cl.**

B63H 11/107 (2006.01)
B63H 11/113 (2006.01)
B63H 11/117 (2006.01)
B63H 25/46 (2006.01)

(52) **U.S. Cl.**

CPC **B63H 11/117** (2013.01); **B63H 11/113** (2013.01)

(58) **Field of Classification Search**

CPC B63H 11/117; B63H 11/113; B63H 25/46
See application file for complete search history.

(56) **References Cited**


U.S. PATENT DOCUMENTS

3,237,585 A * 3/1966 Winter B63H 11/117
114/151
4,056,073 A * 11/1977 Dashew B63H 25/46
114/151
4,522,141 A 6/1985 Aker
5,016,553 A 5/1991 Spencer
5,282,763 A 2/1994 Dixon

(57) **ABSTRACT**

A vessel with auxiliary steering includes a vessel hull with a bow/stern centerline and a port and starboard side. The vessel has (i) a main propulsion unit including at least one propeller and at least one main rudder, and (ii) a secondary propulsion unit including at least one directional water jet thruster on each of the port and starboard side of the vessel hull. The water jet thrusters are configured to direct water outwardly and perpendicularly to the centerline of the hull, and a control system coordinates the direction of the main rudder and the flow direction of at least one water jet thruster.

18 Claims, 4 Drawing Sheets






FIG. 1




FIG. 3




FIG. 4

THRUSTER AIDED STEERING SYSTEMCROSS-REFERENCE TO RELATED
APPLICATION

This application claims the benefit under 35 USC §119(e) of U.S. Provisional Application Ser. No. 62/059,689 filed Oct. 3, 2014, which is incorporated by reference herein in its entirety.

BACKGROUND OF INVENTION

The present invention relates to steerage and propulsion of maritime vessels, with particular embodiments relating to steerage of towboats.

Towboats or push-boats are specialized tugs often used in inland or coastal waterways to propel a series of unpowered barges. As one example, the towboat **1** shown in FIG. **1** is pushing two barges **100** in-line, but it is common for a towboat to push additional barges both in-line and side-by-side. Because the navigation channels of inland waterways are often narrow with comparatively sharp bends (especially in relation to a lengthy chain or “tow” of barges), precision steering is of the utmost importance. FIG. **1** suggests one problem encountered where a turn (to port in FIG. **1**) results in the stern of towboat **1** moving in the starboard direction (i.e., “sliding”) to a much greater degree than the head of the tow. This excessive slide can be problematic from the standpoint of the towboat stern moving outside the navigation channel or striking other nearby objects/vessels. Techniques for enhancing vessel steerage offer considerable advantages in this industry.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. **1** illustrates a towboat pushing a series of barges.

FIG. **2** illustrates a vessel layout for one embodiment of the present invention.

FIG. **3** illustrates the vessel of FIG. **2** steering to port.

FIG. **4** illustrates one embodiment of the thruster steering assembly.

DETAILED DESCRIPTION

One embodiment of the present invention is a vessel with an auxiliary steering system as suggested in FIG. **2**. FIG. **2** illustrates a towboat **1** having the stern **3**, bow **4**, and a center-line **5**. The main propulsion and steering elements of towboat **1** include a main propulsion unit formed of two main engines **4** driving propellers **8** (sometimes also referred to as “screws” or “wheels”). A main rudder **7** is associated with each propeller **8** with the power for operating the main rudders being supplied by the rudder hydraulic unit **10**. Naturally, other embodiments could utilize a single main engine/rudder or more than two main engines/rudders. The directional valves **11** direct the flow of hydraulic fluid to position the rudders **7** with control lines **12** connecting the directional valves to pilothouse steering controls **40**.

In the illustrated embodiment, the auxiliary steering system includes a secondary propulsion unit formed by at least one directional water jet thruster **15** on each of the port and starboard side of towboat **1**. The water jet thrusters generally consist of an engine/pump assembly (referred to as a “thruster engine”) **18** taking in water from thruster intakes **20** and directing the water at high pressure through thruster pipes **16** through the thruster steerage assembly **22**. In the illustrated embodiment, it is thruster steerage assembly **22** which

provides the direction component to the water jet thrusters. The FIG. **4** embodiment of thruster steerage assembly **22** includes the thruster housing **25** which contains three rudders **26** capable of rotating within housing **25** on rudder shafts **31**. Rudder links **27** connect on one end to shafts **31** and are rotatively pinned on their other end to jockey bar **28**. The drive link **29** is pinned on one end to jockey bar **28** and to connector block **30** on its other end. The ram **39** of double-acting piston and cylinder assembly **23** engages connector block **30** and the fluid lines **24** supply the hydraulic fluid for extending and retracting the ram **39**. Thus, it can be envisioned how extension and retraction of the ram **39** acts through the above described linkage to rotate the rudders **26**. The angle through which thruster rudders **26** rotate may vary in different embodiments. In the FIG. **2** example, the rearmost angle of thruster rudders **26** is 22.5°, i.e. the rudders **26** direct water from thruster engine **18** rearward at an angle of 22.5° relative to the centerline **5** of towboat **1**. When the thruster rudders **26** are at an angle of 90°, they direct water outwardly from the hull perpendicular to centerline **5**. At angles of over 90° (e.g., is 90° to 157.5°), thruster rudders **26** direct water forward, i.e., placing reverse thrust on towboat **1**. In the illustrated embodiment, the thruster rudders are positioned within inset **36** on the side of the hull. Preferably, the insets **36** will be sufficiently deep such that the thruster rudders do not extend beyond a side plane of the hull at any point during their operation. Alternatively, the thruster rudders will not extend beyond the side plane of the vessel hull when the thruster rudders are in their rearward position (i.e., 22.5° in the FIG. **2** example). However, the foregoing does not necessarily preclude the thruster rudders from extending beyond the side plane of the vessel in certain specialized embodiments.

Returning to FIG. **2**, it may be seen how thruster hydraulic supply **32** provides hydraulic fluid to operate the piston and cylinder assemblies **23**. The thruster directional valves **33** control fluid flow to the piston and cylinder assemblies **23** and directional valves **33** are in turn connected to the pilothouse steering controls **40** via control lines **34**. It can be visualized from the control line arrangement of FIG. **2** that when pilothouse steering controls **40** provide steering input to the main rudders, the same signals may provide steering input to the thruster rudders **26**. A control system acting on directional valves **33** and **11** to synchronize the relative position of main rudders **7** to thruster rudders **26** may be implemented by many different conventional or future developed methods. Nonlimiting examples include electrical relay networks or a programmable logic controller controlling directional valves **33** and **11**.

Although not explicitly shown in the Figures, certain embodiments of thruster engine **18** may include a flow control or flow divider valve which selectively directs a greater portion of the pumped water from thruster engine **18** to one thruster pipe **16** (e.g., the port thruster pipe) than the other (e.g., starboard) thruster pipe **16**, thereby producing greater thrust at the port thruster than the starboard thruster. However, in other embodiments, the water flow may be fixed and equally divided between the two thrusters. Likewise, many different conventional or future developed thruster engines may be employed. In one embodiment, the power rating of thruster engine **18** will be approximately 15% to 30%, and more preferably 20% to 25%, of the vessel’s main engine power. For example, if the main engine(s) were rated for 1,800 HP, the thruster engine could be rated for approximately 400 to 500 HP. However, thruster to main engine power ratios could also be outside the ratios given above.

In the illustrated embodiment, the thrusters **15** are located along the port and starboard side of the hull at approximately the “pivot point” or “pivoting point” of the vessel. In many embodiments, the pivot point may be defined as the point of contact between the turning circle and the middle line of a vessel. It is situated forward of midships, the distance being greatest in vessels having the least resistance to lateral drift. The position of the pivot point varies in different vessels and also at different points of the turn. It depends upon the underwater form of the hull and especially upon the comparative draft forward and aft, and also upon the distribution of weights. In most vessels, the pivot point may be taken as two-third to five-sixth of the vessel’s length from the stern.

As suggested above, many embodiments of the present invention will link selective control of the port or starboard thruster rudders **26** to the control of main rudders **7**. FIG. **3** illustrates one example of relative position of the thruster rudders in relation to the main rudders. In FIG. **3**, main rudders **7** are shown as having moved to 45° port rudder. Simultaneously, the steering control system has moved starboard thruster rudders **26** to the 90° position while maintaining port thruster rudders **26** at their rearmost position of 22.5°. The effect of the starboard thruster delivering thrust in the direction shown will be to lessen starboard stern slide of towboat **1** as towboat **1** and its tow execute a turn to port. In the example of FIG. **3**, it is the thruster **15** opposite the direction of turn which adjusts its flow direction. In other words, when main rudders **7** turn to port, starboard thruster **15** adjusts its flow direction and when main rudders **7** turn to starboard, port thrusters **15** adjust its flow direction. Additionally, in this example, the ratio of main rudder direction to thruster rudder direction will be approximately 1:2 for most main rudder positions under 45°. For clarity, Table 1 gives a series of main rudder directions and the corresponding direction of the port and starboard thruster direction.

TABLE 1

Main Rudder Angle	Port Thruster Angle	STBD Thruster Angle
0°	22.5°	22.5°
11.5° Port	22.5°	45°
22.5° Port	22.5°	67.5°
45° Port	22.5°	90°
11.5° STBD	45°	22.5°
22.5° STBD	67.5°	22.5°
45° STBD	90°	22.5°

Thus, at 11.5° port main rudder, 22.5° of starboard thruster angle is added to the initial thruster angle of 22.5°. It can be seen from table 1 that this ratio is maintained until the thruster angle reaches 90°, which is the maximum thruster rudder angle in this example. Naturally, there may be other embodiments where the maximum thruster angle exceeds 90°, for example when applying astern propulsion or when in particular vessel maneuvering situations. Likewise, the ratio of main rudder direction to thruster direction is not limited to 1:2 and in other embodiments may range anywhere between 1:1.5 and 1:2.5 (or even ratios outside this range).

In addition to use of the thrusters **15** to reduce stern slide in turns, the operation of the thrusters in their rearward position (e.g., 22.5° in FIG. **2**) can provide certain hydrodynamic efficiencies when the towboat is moving in a generally straight line at normal towing speeds (e.g., approximately four to eight miles per hour). It is believed

that the bow moving through water at normal towing speeds creates a semi-circular flow which directs water back toward the stern of the boat and tends to draw surface air into the propeller area, thereby reducing the propulsion efficiency of the propellers. However, if the thrusters **15** are directing water rearward along the side of the hull, this thruster flow will tend to disrupt the semi-circular flow and prevent the drawing of air under the stern and potentially implode air bubbles that would otherwise be drawn into the propellers.

The main propulsion unit of the towboats described above may vary considerably in horsepower, with smaller canal towboats being in the 200 to 600 horsepower range and some larger river towboats being in excess of 10,000 horsepower. However, the auxiliary steering system described herein may have application to many different types of vessels, regardless of main propulsion horsepower rating or the intended use of the vessel.

Although the present invention has been described in terms of specific embodiments, those skilled in the art will recognize many obvious modifications and variations. All such variations and modifications are intended to come within the scope of the following claims.

The invention claimed is:

1. A vessel with auxiliary steering comprising;
 - a. a vessel hull with a bow/stern centerline and a port and starboard side;
 - b. a main propulsion unit including at least one propeller and at least one main rudder;
 - c. a secondary propulsion unit including at least one directional water jet thruster on each of the port and starboard side of the vessel hull, the water jet thrusters including a plurality of adjustable rudders to control the flow direction of the water;
 - d. wherein the water jet thrusters are configured to direct water outwardly and perpendicularly to the centerline of the hull; and
 - e. a control system coordinating a position of the main rudder to a position of the water jet thruster rudders of at least one water jet thruster.
2. The vessel of claim 1, wherein the water jet thrusters are positioned at an approximate pivot point of the vessel.
3. The vessel of claim 2, wherein the pivot point is located approximately 2/3rd a length of the hull from a stern of the hull.
4. The vessel of claim 1, wherein the control system is configured to adjust the starboard water jet thruster flow direction in conjunction with port main rudder direction.
5. The vessel of claim 1, wherein the control system is configured to adjust the port water jet thruster in conjunction with a starboard main rudder direction.
6. The vessel of claim 1, wherein a ratio of a position change of the main rudder to a position change of the water jet thruster rudders is between 1:1.5 and 1:2.5.
7. The vessel of claim 1, wherein a ratio of a position change of the main rudder to a position change of the water jet thruster rudders is about 1:2.
8. A vessel with auxiliary steering comprising;
 - a. a vessel hull with a bow/stern centerline and a port and starboard side;
 - b. a main propulsion unit including at least one propeller and at least one main rudder;
 - c. a secondary propulsion unit including at least one directional water jet thruster on each of the port and starboard side of the vessel hull, the water jet thrusters including a plurality of adjustable rudders to control the flow direction of the water;

5

d. a control system configured to coordinate the position of the thruster rudders of the water jet thruster on the vessel side opposing a direction of the main rudder.

9. The vessel of claim 8, wherein a ratio of a position change of the main rudder to a position change of the water jet thruster rudders is between 1:1.5 and 1:2.5.

10. The vessel of claim 8, wherein a double acting piston acts to adjust a position of the thruster rudders.

11. The vessel of claim 8, wherein the secondary propulsion unit includes a flow divider capable of adjusting relative flow between the port and starboard water jet thrusters.

12. The vessel of claim 8, wherein the thruster rudders are positioned within an inset on the hull such that the thruster rudders have at least one position not extending beyond a side plane of the hull.

13. The vessel of claim 8, wherein the power of the secondary propulsion unit is between about 15% and about 30% of the main propulsion unit.

14. The vessel of claim 13, wherein the main propulsion unit is between 200 and 15,000 horsepower.

15. A method of operating a vessel wherein the vessel comprises (i) a main propulsion unit including at least one propeller and at least one main rudder, (ii) a secondary propulsion unit including at least one directional water jet

6

thruster on each of the port and starboard side of the vessel hull, the water jet thrusters including a plurality of adjustable rudders to control the flow direction of the water;

and (iii) a control system coordinating a position of the main rudder to a position of the water jet thruster rudders to control a flow direction of the water jet thrusters, the method comprising the steps of:

a. operating the main propulsion unit to impart a forward speed to the vessel of at least five knots; and

b. operating the water jet thrusters to direct thrust predominantly toward the stern of the vessel.

16. The method of claim 15, wherein the water jet thrusters direct thrust between 10° and 35° of a bow/stern centerline of the vessel.

17. The method of claim 15, further comprising the steps of subsequently applying left rudder and changing the direction of thrust of the starboard water jet thruster to a greater angle with respect to a bow/stern centerline of the vessel.

18. The method of claim 17, wherein the change in direction of thrust of the starboard water jet thruster is approximately twice the change in left rudder.

* * * * *