



US009528561B2

(12) **United States Patent**
Nichols et al.

(10) **Patent No.:** **US 9,528,561 B2**
(45) **Date of Patent:** **Dec. 27, 2016**

(54) **CONTINUOUSLY VARIABLE TRANSMISSION**

(71) Applicant: **Fallbrook Intellectual Property Company LLC**, Cedar Park, TX (US)
(72) Inventors: **Jon M. Nichols**, Georgetown, TX (US); **Matthew P. Simister**, Austin, TX (US); **Daniel J. Dawe**, Austin, TX (US); **Charles B. Lohr**, Austin, TX (US); **Timothy M. Obrzut**, Parma, OH (US)

(73) Assignee: **Fallbrook Intellectual Property Company LLC**, Cedar Park, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/790,475**

(22) Filed: **Jul. 2, 2015**

(65) **Prior Publication Data**

US 2015/0377305 A1 Dec. 31, 2015

Related U.S. Application Data

(63) Continuation of application No. 14/171,025, filed on Feb. 3, 2014, now Pat. No. 9,074,674, which is a (Continued)

(51) **Int. Cl.**
F16H 15/48 (2006.01)
F16D 41/064 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **F16D 41/064** (2013.01); **B62M 11/04** (2013.01); **B62M 11/12** (2013.01); **F16D 41/061** (2013.01);
(Continued)

(58) **Field of Classification Search**
None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,963 A 2/1847 Armstrong et al.
719,595 A 2/1903 Huss

(Continued)

FOREIGN PATENT DOCUMENTS

CH 118064 12/1926
CN 1054340 9/1991

(Continued)

OTHER PUBLICATIONS

Office Action dated May 31, 2013 in U.S. Appl. No. 13/796,452.
(Continued)


Primary Examiner — Dirk Wright

(74) *Attorney, Agent, or Firm* — Knobbe Martens Olson & Bear LLP

(57) **ABSTRACT**

Inventive embodiments are directed to components, subassemblies, systems, and/or methods for continuously variable transmissions (CVT). In one embodiment, a main axle is adapted to receive a carrier assembly to facilitate the support of components in a CVT. In another embodiment, a carrier includes a stator support member and a stator interfacial member. In some embodiments, the stator interfacial member is configured to interact with planet subassemblies of a CVT. Various inventive planet subassemblies and idler assemblies can be used to facilitate shifting the ratio of a CVT. In some embodiments, the planet subassemblies include legs configured to have a sliding interface with a carrier assembly. Embodiments of a hub shell, a hub cover are adapted to house components of a CVT and, in some embodiments, to cooperate with other components of the CVT to support operation and/or functionality of the CVT. Among other things, shift control interfaces and braking features for a CVT are disclosed.

10 Claims, 50 Drawing Sheets



Related U.S. Application Data

continuation of application No. 13/796,452, filed on Mar. 12, 2013, now Pat. No. 8,641,572, which is a continuation of application No. 12/999,586, filed as application No. PCT/US2008/067940 on Jun. 23, 2008, now Pat. No. 8,398,518.

(51) **Int. Cl.**

B62M 11/04 (2006.01)
B62M 11/12 (2006.01)
F16H 15/28 (2006.01)
F16H 15/52 (2006.01)
F16H 15/50 (2006.01)
F16H 53/02 (2006.01)
F16D 41/061 (2006.01)

(52) **U.S. Cl.**

CPC **F16H 15/28** (2013.01); **F16H 15/50** (2013.01); **F16H 15/52** (2013.01); **F16H 53/02** (2013.01); **Y10T 29/49826** (2015.01); **Y10T 74/18304** (2015.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

1,121,210 A	12/1914	Techel	2,901,924 A	9/1959	Banker
1,175,677 A	3/1916	Barnes	2,913,932 A	11/1959	Oehrli
1,207,985 A	12/1916	Null et al.	2,931,234 A	4/1960	Hayward
1,380,006 A	5/1921	Nielsen	2,931,235 A	4/1960	Hayward
1,390,971 A	9/1921	Samain	2,949,800 A	8/1960	Neuschatz
1,558,222 A	10/1925	Beetow	2,959,063 A	11/1960	Perry
1,629,902 A	5/1927	Arter et al.	2,959,972 A	11/1960	Madson
1,631,069 A	5/1927	Smith	2,964,959 A	12/1960	Beck
1,683,715 A	9/1928	Erban	3,008,061 A	11/1961	Mims et al.
1,686,446 A	10/1928	Gilman	3,048,056 A	8/1962	Wolfram
1,774,254 A	8/1930	Daukus	3,051,020 A	8/1962	Hartupee
1,793,571 A	2/1931	Vaughn	3,071,194 A	1/1963	Geske
1,847,027 A	2/1932	Thomsen of al.	3,086,704 A	4/1963	Hurt
1,850,189 A	3/1932	Weiss	3,087,348 A	4/1963	Kraus
1,858,696 A	5/1932	Weiss	3,154,957 A	11/1964	Kashihara
1,865,102 A	6/1932	Hayes	3,163,050 A	12/1964	Kraus
1,903,228 A	3/1933	Thomson	3,176,542 A	4/1965	Monch
1,978,439 A	10/1934	Sharpe	3,184,983 A	5/1965	Kraus
2,030,203 A	2/1936	Gove et al.	3,204,476 A	9/1965	Rouverol
2,060,884 A	11/1936	Madle	3,209,606 A	10/1965	Yamamoto
2,086,491 A	7/1937	Dodge	3,211,364 A	10/1965	Wentling et al.
2,100,629 A	11/1937	Chilton	3,216,283 A	11/1965	General
2,109,845 A	3/1938	Madle	3,246,531 A	4/1966	Kashihara
2,112,763 A	3/1938	Cloudsley	3,248,960 A	5/1966	Schottler
2,134,225 A	10/1938	Christiansen	3,273,468 A	9/1966	Allen
2,152,796 A	4/1939	Erban	3,280,646 A	10/1966	Lemieux
2,196,064 A	4/1940	Erban	3,283,614 A	11/1966	Hewko
2,209,254 A	7/1940	Ahnger	3,292,443 A	12/1966	Felix
2,230,398 A	2/1941	Benjafield	3,340,895 A	9/1967	Osgood, Jr. et al.
2,259,933 A	10/1941	Holloway	3,374,009 A	3/1968	Jeunet
2,269,434 A	1/1942	Brooks	3,407,687 A	10/1968	Hayashi
2,325,502 A	7/1943	Auguste	3,440,895 A	4/1969	Fellows
RE22,761 E	5/1946	Wemp	3,464,281 A	9/1969	Hiroshi et al.
2,461,258 A	2/1949	Brooks	3,477,315 A	11/1969	Macks
2,469,653 A	5/1949	Kopp	3,487,726 A	1/1970	Burnett
2,480,968 A	9/1949	Ronai	3,487,727 A	1/1970	Gustafsson
2,586,725 A	2/1952	Henry	3,574,289 A	4/1971	Scheiter et al.
2,596,538 A	5/1952	Dicke	3,661,404 A	5/1972	Bossaer
2,597,849 A	5/1952	Alfredeen	3,695,120 A	10/1972	Titt
2,675,713 A	4/1954	Acker	3,707,888 A	1/1973	Schottler
2,696,888 A	12/1954	Chillson et al.	3,727,473 A	4/1973	Bayer
2,868,038 A	5/1955	Billeter	3,727,474 A	4/1973	Fullerton
2,730,904 A	1/1956	Rennerfelt	3,736,803 A	6/1973	Horowitz et al.
2,748,614 A	6/1956	Weisel	3,768,715 A	10/1973	Tout
2,959,070 A	1/1959	Flinn	3,769,849 A	11/1973	Hagen
2,873,911 A	2/1959	Perrine	3,800,607 A	4/1974	Zurcher
2,874,592 A	2/1959	Oehrli	3,802,284 A	4/1974	Sharpe et al.
2,883,883 A	4/1959	Chillson	3,810,398 A	5/1974	Kraus
2,891,213 A	6/1959	Kern	3,820,416 A	6/1974	Kraus
			3,866,985 A	2/1975	Whitehurst
			3,891,235 A	6/1975	Shelly
			3,934,493 A	1/1976	Hillyer
			3,954,282 A	5/1976	Hege
			3,984,129 A	10/1976	Hege
			3,987,681 A	10/1976	Keithley et al.
			3,996,807 A	12/1976	Adams
			4,053,173 A	10/1977	Chase, Sr.
			4,086,026 A	4/1978	Tamanini
			4,098,146 A	7/1978	McLarty
			4,103,514 A	8/1978	Grosse-Entrup
			4,159,653 A	7/1979	Koivunen
			4,169,609 A	10/1979	Zampedro
			4,177,683 A	12/1979	Moses
			4,227,712 A	10/1980	Dick
			4,314,485 A	2/1982	Adams
			4,345,486 A	8/1982	Olesen
			4,369,667 A	1/1983	Kemper
			4,382,188 A	5/1983	Cronin
			4,391,156 A	7/1983	Tibbals
			4,459,873 A	7/1984	Black
			4,464,952 A	8/1984	Stubbs
			4,468,984 A	9/1984	Castelli et al.
			4,493,677 A	1/1985	Ikenoya
			4,494,524 A	1/1985	Wagner
			4,496,051 A	1/1985	Ortner
			4,501,172 A	2/1985	Kraus
			4,526,255 A	7/1985	Hennessey et al.
			4,546,673 A	10/1985	Shigematsu et al.
			4,549,874 A	10/1985	Wen

(56)

References Cited

U.S. PATENT DOCUMENTS

4,560,369 A	12/1985	Hattori	5,722,502 A	3/1998	Kubo
4,567,781 A	2/1986	Russ	5,746,676 A	5/1998	Kawase et al.
4,574,649 A	3/1986	Seol	5,755,303 A	5/1998	Yamamoto et al.
4,585,429 A	4/1986	Marier	5,799,541 A	9/1998	Arbeiter
4,617,838 A	10/1986	Anderson	5,823,052 A	10/1998	Nobumoto
4,628,766 A	12/1986	De Brie Perry	5,846,155 A	12/1998	Taniguchi et al.
4,630,839 A	12/1986	Seol	5,888,160 A	3/1999	Miyata et al.
4,631,469 A	12/1986	Tsuboi et al.	5,899,827 A	5/1999	Nakano et al.
4,647,060 A	3/1987	Tomkinson	5,902,207 A	5/1999	Sugihara
4,651,082 A	3/1987	Kaneyuki	5,927,207 A	10/1999	Valdenaire
4,663,990 A	5/1987	Itoh et al.	5,984,826 A	11/1999	Nakano
4,700,581 A	10/1987	Tibbals, Jr.	5,995,895 A	11/1999	Watt et al.
4,713,976 A	12/1987	Wilkes	6,000,707 A	12/1999	Miller
4,717,368 A	1/1988	Yamaguchi et al.	6,004,239 A	12/1999	Makino
4,725,258 A	2/1988	Joanis, Jr.	6,006,151 A	12/1999	Graf
4,735,430 A	4/1988	Tomkinson	6,015,359 A	1/2000	Kunii
4,738,164 A	4/1988	Kaneyuki	6,019,701 A	2/2000	Mori et al.
4,744,261 A	5/1988	Jacobson	6,029,990 A	2/2000	Busby
4,756,211 A	7/1988	Fellows	6,042,132 A	3/2000	Suenaga et al.
4,781,663 A	11/1988	Reswick	6,045,477 A	4/2000	Schmidt
4,806,066 A	2/1989	Rhodes et al.	6,045,481 A	4/2000	Kumagai
4,838,122 A	6/1989	Takamiya et al.	6,050,854 A	4/2000	Fang et al.
4,856,374 A	8/1989	Kreuzer	6,053,833 A	4/2000	Masaki
4,857,035 A	8/1989	Anderson	6,053,841 A	4/2000	Kolde et al.
4,869,130 A	9/1989	Wiecko	6,054,844 A	4/2000	Frank
4,881,925 A	11/1989	Hattori	6,066,067 A	5/2000	Greenwood
4,900,046 A	2/1990	Aranceta-Angoitia	6,071,210 A	6/2000	Kato
4,909,101 A	3/1990	Terry	6,076,846 A	6/2000	Clardy
4,918,344 A	4/1990	Chikamori et al.	6,079,726 A	6/2000	Busby
4,961,477 A	10/1990	Sweeney	6,086,506 A	7/2000	Petersmann et al.
4,964,312 A	10/1990	Kraus	6,095,940 A	8/2000	Ai et al.
5,006,093 A	4/1991	Itoh et al.	6,099,431 A	8/2000	Hoge et al.
5,020,384 A	6/1991	Kraus	6,113,513 A	9/2000	Itoh et al.
5,025,685 A	6/1991	Kobayashi et al.	6,119,539 A	9/2000	Papanicolaou
5,033,322 A	7/1991	Nakano	6,119,800 A	9/2000	McComber
5,033,571 A	7/1991	Morimoto	6,155,132 A	12/2000	Yamane
5,037,361 A	8/1991	Takahashi	6,159,126 A	12/2000	Oshidan
5,044,214 A	9/1991	Barber	6,171,210 B1	1/2001	Miyata et al.
5,059,158 A	10/1991	Bellio et al.	6,174,260 B1	1/2001	Tsukada et al.
5,069,655 A	12/1991	Schievelbusch	6,186,922 B1	2/2001	Bursal et al.
5,099,710 A	3/1992	Nakano	6,201,315 B1	3/2001	Larsson
5,121,654 A	6/1992	Fasce	6,217,473 B1	4/2001	Ueda et al.
5,125,677 A	6/1992	Ogilvie et al.	6,241,636 B1	6/2001	Miller
5,138,894 A	8/1992	Kraus	6,243,638 B1	6/2001	Abo et al.
5,156,412 A	10/1992	Meguerditchian	6,251,038 B1	6/2001	Ishikawa et al.
5,230,258 A	7/1993	Nakano	6,258,003 B1	7/2001	Hirano et al.
5,236,211 A	8/1993	Meguerditchian	6,261,200 B1	7/2001	Miyata et al.
5,236,403 A	8/1993	Schievelbusch	6,293,575 B1	9/2001	Burrows et al.
5,267,920 A	12/1993	Hibi	6,311,113 B1	10/2001	Danz et al.
5,273,501 A	12/1993	Schievelbusch	6,312,358 B1	11/2001	Goi et al.
5,318,486 A	6/1994	Lutz	6,322,475 B2	11/2001	Miller
5,319,486 A	6/1994	Vogel et al.	6,325,386 B1	12/2001	Shoge
5,323,570 A	6/1994	Kuhlman et al.	6,340,067 B1	1/2002	Fujiwara
5,330,396 A	7/1994	Lohr et al.	6,358,174 B1	3/2002	Folsom et al.
5,355,749 A	10/1994	Obara et al.	6,358,178 B1	3/2002	Wittkopp
5,356,348 A	10/1994	Bellio et al.	6,375,412 B1	4/2002	Dial
5,375,865 A	12/1994	Terry, Sr.	6,390,945 B1	5/2002	Young
5,379,661 A	1/1995	Nakano	6,390,946 B1	5/2002	Hibi et al.
5,383,677 A	1/1995	Thomas	6,406,399 B1	6/2002	Ai
5,387,000 A	2/1995	Sato	6,414,401 B1	7/2002	Kuroda et al.
5,401,221 A	3/1995	Fellows et al.	6,419,608 B1	7/2002	Miller
5,451,070 A	9/1995	Lindsay et al.	6,425,838 B1	7/2002	Matsubara et al.
5,489,003 A	2/1996	Ohyama et al.	6,434,960 B1	8/2002	Rousseau
5,508,574 A	4/1996	Vlock	6,440,037 B2	8/2002	Takagi et al.
5,562,564 A	10/1996	Folino	6,461,268 B1	10/2002	Milner
5,564,998 A	10/1996	Fellows	6,482,094 B2	11/2002	Kefes
5,601,301 A	2/1997	Liu	6,492,785 B1	12/2002	Kasten et al.
5,607,373 A	3/1997	Ochiai et al.	6,494,805 B2	12/2002	Ooyama et al.
5,645,507 A	7/1997	Hathaway	6,499,373 B2	12/2002	Van Cor
5,651,750 A	7/1997	Imanishi et al.	6,514,175 B2	2/2003	Taniguchi et al.
5,664,636 A	9/1997	Ikuma et al.	6,523,223 B2	2/2003	Wang
5,669,758 A	9/1997	Williamson	6,532,890 B2	3/2003	Chen
5,669,845 A	9/1997	Muramoto et al.	6,551,210 B2	4/2003	Miller
5,690,346 A	11/1997	Keskitalo	6,571,726 B2	6/2003	Tsai et al.
5,701,786 A	12/1997	Kawakami	6,575,047 B2	6/2003	Reik et al.
			6,659,901 B2	12/2003	Sakai et al.
			6,672,418 B1	1/2004	Makino
			6,676,559 B2	1/2004	Miller
			6,679,109 B2	1/2004	Gierling et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,682,432 B1	1/2004	Shinozuka	7,238,137 B2	7/2007	Miller et al.
6,689,012 B2	2/2004	Miller	7,238,138 B2	7/2007	Miller et al.
6,721,637 B2	4/2004	Abe et al.	7,238,139 B2	7/2007	Roethler et al.
6,723,016 B2	4/2004	Sumi	7,246,672 B2	7/2007	Shirai et al.
6,805,654 B2	10/2004	Nishii	7,250,018 B2	7/2007	Miller et al.
6,808,053 B2	10/2004	Kirkwood et al.	D548,655 S	8/2007	Barrow et al.
6,839,617 B2	1/2005	Mensler et al.	7,261,663 B2	8/2007	Miller et al.
6,849,020 B2	2/2005	Sumi	7,275,610 B2	10/2007	Kuang et al.
6,859,709 B2	2/2005	Joe et al.	7,285,068 B2	10/2007	Hosoi
6,931,316 B2	8/2005	Joe et al.	7,288,042 B2	10/2007	Miller et al.
6,932,739 B2	8/2005	Miyata et al.	7,288,043 B2	10/2007	Shioiri et al.
6,942,593 B2	9/2005	Nishii et al.	7,320,660 B2	1/2008	Miller
6,945,903 B2	9/2005	Miller	7,322,901 B2	1/2008	Miller et al.
6,949,049 B2	9/2005	Miller	7,343,236 B2	3/2008	Wilson
6,958,029 B2	10/2005	Inoue	7,347,801 B2	3/2008	Guenter et al.
6,991,575 B2	1/2006	Inoue	7,384,370 B2	6/2008	Miller
6,991,579 B2	1/2006	Kobayashi et al.	7,393,300 B2	7/2008	Miller et al.
7,000,496 B2	2/2006	Wessel et al.	7,393,302 B2	7/2008	Miller
7,011,600 B2	3/2006	Miller et al.	7,393,303 B2	7/2008	Miller
7,011,601 B2	3/2006	Miller	7,395,731 B2	7/2008	Miller et al.
7,014,591 B2	3/2006	Miller	7,396,209 B2	7/2008	Miller et al.
7,029,418 B2	4/2006	Taketsuna et al.	7,402,122 B2	7/2008	Miller
7,032,914 B2	4/2006	Miller	7,410,443 B2	8/2008	Miller
7,036,620 B2	5/2006	Miller et al.	7,419,451 B2	9/2008	Miller
7,044,884 B2	5/2006	Miller	7,422,541 B2	9/2008	Miller
7,063,640 B2	6/2006	Miller	7,422,546 B2	9/2008	Miller et al.
7,074,007 B2	7/2006	Miller	7,427,253 B2	9/2008	Miller
7,074,154 B2	7/2006	Miller	7,431,677 B2	10/2008	Miller et al.
7,074,155 B2	7/2006	Miller	D579,833 S	11/2008	Acenbrak
7,077,777 B2	7/2006	Miyata et al.	7,452,297 B2	11/2008	Miller et al.
7,086,979 B2	8/2006	Frenken	7,455,611 B2	11/2008	Miller et al.
7,086,981 B2	8/2006	Ali et al.	7,455,617 B2	11/2008	Miller et al.
7,094,171 B2	8/2006	Inoue	7,462,123 B2	12/2008	Miller et al.
7,111,860 B1	9/2006	Grimaldos	7,462,127 B2	12/2008	Miller et al.
7,112,158 B2	9/2006	Miller	7,470,210 B2	12/2008	Miller et al.
7,112,159 B2	9/2006	Miller et al.	7,478,885 B2	1/2009	Urabe
7,125,297 B2	10/2006	Miller et al.	7,481,736 B2	1/2009	Miller et al.
7,131,930 B2	11/2006	Miller et al.	7,510,499 B2	3/2009	Miller et al.
7,140,999 B2	11/2006	Miller	7,540,818 B2	6/2009	Miller et al.
7,147,586 B2	12/2006	Miller et al.	7,547,264 B2	6/2009	Usoro
7,153,233 B2	12/2006	Miller et al.	7,574,935 B2	8/2009	Rohs et al.
7,156,770 B2	1/2007	Miller	7,591,755 B2	9/2009	Petrzik et al.
7,160,220 B2	1/2007	Shinojima et al.	7,600,771 B2	10/2009	Miller et al.
7,160,222 B2	1/2007	Miller	7,632,203 B2	12/2009	Miller
7,163,485 B2	1/2007	Miller	7,651,437 B2	1/2010	Miller et al.
7,163,486 B2	1/2007	Miller et al.	7,654,928 B2	2/2010	Miller et al.
7,166,052 B2	1/2007	Miller et al.	7,670,243 B2	3/2010	Miller
7,166,056 B2	1/2007	Miller et al.	7,686,729 B2	3/2010	Miller et al.
7,166,057 B2	1/2007	Miller et al.	7,727,101 B2	6/2010	Miller
7,166,058 B2	1/2007	Miller et al.	7,727,107 B2	6/2010	Miller
7,169,076 B2	1/2007	Miller et al.	7,727,108 B2	6/2010	Miller et al.
7,172,529 B2	2/2007	Miller et al.	7,727,110 B2	6/2010	Miller et al.
7,175,564 B2	2/2007	Miller	7,727,115 B2	6/2010	Serkh
7,175,565 B2	2/2007	Miller et al.	7,731,615 B2	6/2010	Miller et al.
7,175,566 B2	2/2007	Miller et al.	7,762,919 B2	7/2010	Smithson et al.
7,192,381 B2	3/2007	Miller et al.	7,762,920 B2	7/2010	Smithson et al.
7,197,915 B2	4/2007	Luh et al.	7,785,228 B2	8/2010	Smithson et al.
7,198,582 B2	4/2007	Miller et al.	7,828,685 B2	11/2010	Miller
7,198,583 B2	4/2007	Miller et al.	7,837,592 B2	11/2010	Miller
7,198,584 B2	4/2007	Miller et al.	7,871,353 B2	1/2011	Nichols et al.
7,198,585 B2	4/2007	Miller et al.	7,882,762 B2	2/2011	Armstrong et al.
7,201,693 B2	4/2007	Miller et al.	7,883,442 B2	2/2011	Miller et al.
7,201,694 B2	4/2007	Miller et al.	7,885,747 B2	2/2011	Miller et al.
7,201,695 B2	4/2007	Miller et al.	7,887,032 B2	2/2011	Malone
7,204,777 B2	4/2007	Miller et al.	7,909,723 B2	3/2011	Triller et al.
7,214,159 B2	5/2007	Miller et al.	7,909,727 B2	3/2011	Smithson et al.
7,217,215 B2	5/2007	Miller et al.	7,914,029 B2	3/2011	Miller et al.
7,217,216 B2	5/2007	Inoue	7,959,533 B2	6/2011	Nichols et al.
7,217,219 B2	5/2007	Miller	7,963,880 B2	6/2011	Smithson et al.
7,217,220 B2	5/2007	Careau et al.	7,967,719 B2	6/2011	Smithson et al.
7,232,395 B2	6/2007	Miller et al.	7,976,426 B2	7/2011	Smithson et al.
7,234,873 B2	6/2007	Kato et al.	8,066,613 B2	11/2011	Smithson et al.
7,235,031 B2	6/2007	Miller et al.	8,066,614 B2	11/2011	Miller et al.
D546,741 S	7/2007	Iteya et al.	8,070,635 B2	12/2011	Miller
7,238,136 B2	7/2007	Miller et al.	8,087,482 B2	1/2012	Miles et al.
			8,123,653 B2	2/2012	Smithson et al.
			8,133,149 B2	3/2012	Smithson et al.
			8,142,323 B2	3/2012	Tsuchiya et al.
			8,167,759 B2	5/2012	Pohl et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,171,636	B2	5/2012	Smithson et al.	2004/0058772	A1	3/2004	Inoue et al.
8,230,961	B2	7/2012	Schneidewind	2004/0067816	A1	4/2004	Taketsuna et al.
8,262,536	B2	9/2012	Nichols et al.	2004/0082421	A1	4/2004	Wafzig
8,267,829	B2	9/2012	Miller et al.	2004/0092359	A1	5/2004	Imanishi et al.
8,313,404	B2	11/2012	Carter et al.	2004/0119345	A1	6/2004	Takano
8,313,405	B2	11/2012	Bazyn et al.	2004/0171457	A1	9/2004	Fuller
8,317,650	B2	11/2012	Nichols et al.	2004/0204283	A1	10/2004	Inoue
8,317,651	B2	11/2012	Lohr	2004/0231331	A1	11/2004	Iwanami et al.
8,321,097	B2	11/2012	Vasiliotis et al.	2004/0237698	A1	12/2004	Hilsky et al.
8,342,999	B2	1/2013	Miller	2004/0254047	A1	12/2004	Frank et al.
8,360,917	B2	1/2013	Nichols et al.	2005/0037876	A1	2/2005	Unno et al.
8,376,889	B2	2/2013	Hoffman et al.	2005/0085979	A1	4/2005	Carlson et al.
8,376,903	B2	2/2013	Pohl et al.	2005/0172752	A1	8/2005	Florczyk et al.
8,382,631	B2	2/2013	Hoffman et al.	2005/0184580	A1	8/2005	Kuan et al.
8,382,637	B2	2/2013	Tange	2005/0227809	A1	10/2005	Bitzer et al.
8,393,989	B2	3/2013	Pohl	2006/0006008	A1	1/2006	Brunemann et al.
8,398,518	B2*	3/2013	Nichols B62M 11/04 475/189	2006/0052204	A1	3/2006	Eckert et al.
8,469,853	B2	6/2013	Miller et al.	2006/0108956	A1	5/2006	Clark
8,469,856	B2	6/2013	Thomassy	2006/0111212	A9	5/2006	Ai et al.
8,480,529	B2	7/2013	Pohl et al.	2006/0154775	A1	7/2006	Ali et al.
8,496,554	B2	7/2013	Pohl et al.	2006/0172829	A1	8/2006	Ishio
8,506,452	B2	8/2013	Pohl et al.	2006/0180363	A1	8/2006	Uchisasai
8,512,195	B2	8/2013	Lohr et al.	2006/0223667	A1	10/2006	Nakazeki
8,535,199	B2	9/2013	Lohr et al.	2006/0234822	A1	10/2006	Morscheck et al.
8,550,949	B2	10/2013	Miller	2006/0276299	A1	12/2006	Imanishi
8,585,528	B2	11/2013	Carter et al.	2007/0004552	A1	1/2007	Matsudaira et al.
8,622,866	B2	1/2014	Bazyn et al.	2007/0004556	A1	1/2007	Rohs et al.
8,626,409	B2	1/2014	Vasiliotis et al.	2007/0041823	A1	2/2007	Miller
8,628,443	B2	1/2014	Miller et al.	2007/0099753	A1	5/2007	Matsui et al.
8,641,572	B2	2/2014	Nichols et al.	2007/0149342	A1	6/2007	Guenter et al.
8,641,577	B2	2/2014	Nichols et al.	2007/0155567	A1	7/2007	Miller et al.
8,663,050	B2	3/2014	Nichols et al.	2007/0193391	A1	8/2007	Armstrong et al.
8,678,974	B2	3/2014	Lohr	2007/0228687	A1	10/2007	Parker
8,708,360	B2	4/2014	Miller et al.	2008/0032852	A1	2/2008	Smithson et al.
8,721,485	B2	5/2014	Lohr et al.	2008/0032854	A1	2/2008	Smithson et al.
8,738,255	B2	5/2014	Carter et al.	2008/0039269	A1	2/2008	Smithson et al.
8,776,633	B2	7/2014	Armstrong et al.	2008/0039273	A1	2/2008	Smithson et al.
8,784,248	B2	7/2014	Murakami et al.	2008/0039276	A1	2/2008	Smithson et al.
8,790,214	B2	7/2014	Lohr et al.	2008/0070729	A1	3/2008	Miller et al.
8,818,661	B2	8/2014	Keilers et al.	2008/0073137	A1	3/2008	Miller et al.
8,845,485	B2	9/2014	Smithson et al.	2008/0073467	A1	3/2008	Miller et al.
8,852,050	B2	10/2014	Thomassy	2008/0079236	A1	4/2008	Miller et al.
8,870,711	B2	10/2014	Pohl et al.	2008/0081715	A1	4/2008	Miller et al.
8,888,643	B2	11/2014	Lohr et al.	2008/0081728	A1	4/2008	Faulring et al.
8,900,085	B2	12/2014	Pohl et al.	2008/0085795	A1	4/2008	Miller et al.
8,920,285	B2	12/2014	Smithson et al.	2008/0085796	A1	4/2008	Miller et al.
8,996,263	B2	3/2015	Quinn et al.	2008/0085797	A1	4/2008	Miller et al.
9,017,207	B2	4/2015	Pohl et al.	2008/0085798	A1	4/2008	Miller et al.
9,022,889	B2	5/2015	Miller	2008/0139363	A1	6/2008	Williams
9,046,158	B2	6/2015	Miller et al.	2008/0149407	A1	6/2008	Shibata et al.
9,074,674	B2	7/2015	Nichols et al.	2008/0200300	A1	8/2008	Smithson et al.
9,086,145	B2	7/2015	Pohl et al.	2008/0228362	A1	9/2008	Muller et al.
2001/0008192	A1	7/2001	Morisawa	2008/0284170	A1	11/2008	Cory
2001/0041644	A1	11/2001	Yasuoka et al.	2008/0305920	A1	12/2008	Nishii et al.
2001/0044361	A1	11/2001	Taniguchi et al.	2009/0023545	A1	1/2009	Beaudoin
2002/0019285	A1	2/2002	Henzler	2009/0082169	A1	3/2009	Kolstrup
2002/0028722	A1	3/2002	Sakai et al.	2009/0107454	A1	4/2009	Hiyoshi et al.
2002/0037786	A1	3/2002	Hirano et al.	2009/0251013	A1	10/2009	Vollmer et al.
2002/0045511	A1	4/2002	Geiberger et al.	2010/0093479	A1	4/2010	Carter et al.
2002/0128107	A1	9/2002	Wakayama	2011/0127096	A1	6/2011	Schneidewind
2002/0153695	A1	10/2002	Wang	2011/0230297	A1	9/2011	Shiina et al.
2002/0169051	A1	11/2002	Oshidari	2011/0291507	A1	12/2011	Post
2002/0189524	A1	12/2002	Chen	2011/0319222	A1	12/2011	Ogawa et al.
2003/0015358	A1	1/2003	Abe et al.	2012/0035015	A1	2/2012	Ogawa et al.
2003/0015874	A1	1/2003	Abe et al.	2012/0258839	A1	10/2012	Smithson et al.
2003/0022753	A1	1/2003	Mizuno et al.	2013/0035200	A1	2/2013	Noji et al.
2003/0036456	A1	2/2003	Skrabs	2013/0053211	A1	2/2013	Fukuda et al.
2003/0132051	A1	7/2003	Nishii et al.	2013/0146406	A1	6/2013	Nichols et al.
2003/0135316	A1	7/2003	Kawamura et al.	2013/0190123	A1	7/2013	Pohl et al.
2003/0160420	A1	8/2003	Fukuda	2013/0288848	A1	10/2013	Carter et al.
2003/0176247	A1	9/2003	Gottschalk	2013/0337971	A1	12/2013	Kolstrup
2003/0216216	A1	11/2003	Inoue et al.	2014/0073470	A1	3/2014	Carter et al.
2003/0221892	A1	12/2003	Matsumoto et al.	2014/0121922	A1	5/2014	Vasiliotis et al.
2004/0038772	A1	2/2004	McIndoe et al.	2014/0141919	A1	5/2014	Bazyn et al.
				2014/0148303	A1	5/2014	Nichols et al.
				2014/0179479	A1	6/2014	Nichols et al.
				2014/0206499	A1	7/2014	Lohr
				2014/0248988	A1	9/2014	Lohr et al.
				2014/0257650	A1	9/2014	Carter et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0323260	A1	10/2014	Miller et al.
2014/0329637	A1	11/2014	Thomassy et al.
2014/0335991	A1	11/2014	Lohr et al.
2014/0365059	A1	12/2014	Keilers et al.
2015/0018154	A1	1/2015	Thomassy
2015/0039195	A1	2/2015	Pohl et al.
2015/0051801	A1	2/2015	Quinn et al.
2015/0072827	A1	3/2015	Lohr et al.
2015/0080165	A1*	3/2015	Pohl F16H 15/50 475/186

FOREIGN PATENT DOCUMENTS

CN	2245830		1/1997	JP	52-35481	3/1977
CN	1157379		8/1997	JP	53-048166	1/1978
CN	1167221		12/1997	JP	55-135259	10/1980
CN	1204991		1/1999	JP	56-047231	4/1981
CN	1283258		2/2001	JP	56-127852	10/1981
CN	1300355		6/2001	JP	58-065361	4/1983
CN	1474917		2/2004	JP	59-069565	4/1984
CN	2714896		8/2005	JP	59-144826	8/1984
CN	1940348		4/2007	JP	59-190557	12/1984
DE	498 701		5/1930	JP	60-247011	12/1985
DE	1171692		6/1964	JP	61-031754	2/1986
DE	2 310880		9/1974	JP	61-053423	3/1986
DE	2 136 243		1/1975	JP	61-144466	7/1986
DE	2436496		2/1975	JP	61-173722	10/1986
DE	263566		1/1989	JP	61-270552	11/1986
DE	39 40 919	A1	6/1991	JP	62-075170	4/1987
DE	19851738		5/2000	JP	63-219953	9/1988
DE	10155372		5/2003	JP	63-160465	10/1988
EP	0 432 742		12/1990	JP	01-286750	11/1989
EP	0 528 381		2/1993	JP	01-308142	12/1989
EP	0 528 382		2/1993	JP	02-130224	5/1990
EP	0 635 639		1/1995	JP	02-157483	6/1990
EP	0 638 741		2/1995	JP	02-271142	6/1990
EP	0 831 249		3/1998	JP	02-182593	7/1990
EP	0 832 816		4/1998	JP	03-149442	6/1991
EP	0 976 956		2/2000	JP	03-223555	10/1991
EP	1 136 724		9/2001	JP	04-166619	6/1992
EP	1 366 978		3/2003	JP	04-272553	9/1992
EP	1 362 783		11/2003	JP	04-327055	11/1992
EP	1 433 641		6/2004	JP	04-351361	12/1992
EP	1 452 441		9/2004	JP	05-087154	4/1993
EP	1 518 785		3/2005	JP	06-050169	2/1994
EP	1 624 230		2/2006	JP	06-050358	2/1994
FR	620375		4/1927	JP	07-42799	2/1995
FR	2460427		1/1981	JP	07-133857	5/1995
FR	2590638		5/1987	JP	07-139600	5/1995
GB	14132		0/1910	JP	07-259950	10/1995
GB	391448		4/1933	JP	08-170706	7/1996
GB	592320		9/1947	JP	08-247245	9/1996
GB	906002		9/1962	JP	08-270772	10/1996
GB	919430		2/1963	JP	09-024743	1/1997
GB	1132473		11/1968	JP	09-089064	3/1997
GB	1165545		10/1969	JP	10-061739	3/1998
GB	1376057		12/1974	JP	10-089435	4/1998
GB	2031822		4/1980	JP	10-115355	5/1998
GB	2035482		6/1980	JP	10-115356	5/1998
GB	2080452		8/1982	JP	10-194186	7/1998
JP	38-025315		11/1963	JP	10-511621	11/1998
JP	41-3126		2/1966	JP	11-063130	3/1999
JP	42-2843		2/1967	JP	11-257479	9/1999
JP	42-2844		2/1967	JP	2000-46135	2/2000
JP	44-1098		1/1969	JP	2000-177673	6/2000
JP	47-000448		1/1972	JP	2001-027298	1/2001
JP	47-20535		6/1972	JP	2001-071986	3/2001
JP	47-29762		11/1972	JP	2001-107827	4/2001
JP	48-54371		7/1973	JP	2001-165296	6/2001
JP	49-12742		3/1974	JP	2002-147558	5/2002
JP	49-013823		4/1974	JP	2002-250421	6/2002
JP	50-114581		9/1975	JP	2002-307956	10/2002
JP	51-25903		8/1976	JP	2002-533626	10/2002
JP	51-150380		12/1976	JP	2002-372114	12/2002
				JP	2002-372114	12/2002
				JP	2003-028257	1/2003
				JP	2003-56662	2/2003
				JP	2003-161357	6/2003
				JP	2003-336732	11/2003
				JP	2004-011834	1/2004
				JP	2004-162652	6/2004
				JP	2004-189222	7/2004
				JP	2004-526917	9/2004
				JP	2005-003063	1/2005
				JP	2005-240928	9/2005
				JP	2006-015025	1/2006
				JP	2003-194207	10/2006
				JP	2006-283900	10/2006
				JP	2006-300241	11/2006
				JP	2008-002687	1/2008
				JP	2010-069005	4/2010
				NE	98467	7/1961
				TW	74007	1/1984

(56)

References Cited

OTHER PUBLICATIONS

FOREIGN PATENT DOCUMENTS

TW	175100	12/1991
TW	218909	1/1994
TW	227206	7/1994
TW	275872	5/1996
TW	360184	6/1999
TW	366396	8/1999
TW	512211	12/2002
TW	582363	4/2004
TW	590955	6/2004
TW	I225129	12/2004
TW	I225912	1/2005
TW	I235214	1/2005
TW	M294598	7/2006
TW	200637745	11/2006
WO	WO 99/20918	4/1999
WO	WO 01/73319	10/2001
WO	WO 03/100294	12/2003
WO	WO 2005/083305	9/2005
WO	WO 2005/108825	11/2005
WO	WO 2005/111472	11/2005
WO	WO 2006/091503	8/2006
WO	WO 2007/044128	4/2007
WO	WO 2007/133538	11/2007
WO	WO 2007/133681	11/2007
WO	WO 2008/078047	7/2008
WO	WO 2008/100792	8/2008
WO	WO 2010/135407	11/2010
WO	WO 2011/101991	8/2011
WO	WO 2012/030213	3/2012

Chinese Office Action dated Jan. 28, 2013 for Chinese Patent Application No. 200880129965.3.
 Chinese Office Action dated Sep. 18, 2013 for Chinese Patent Application No. 200880129965.3.
 Examination Report dated Dec. 20, 2013 in European Patent Application No. 08874837.1.
 International Preliminary Report on Patentability for Application No. PCT/US2008/067940 dated Jan. 13, 2011.
 International Search Report for International Application No. PCT/2008/067940 dated Jun. 15, 2009.
 Goi et al., Development of Traction Drive IDG (T-IDG), Proceedings of International Congress on Continuously Variable and Hybrid Transmissions, Sep. 2007, 6 pages.
 Pohl, Brad, CVT Split Power Transmissions, A Configuration versus Performance Study with an Emphasis on the Hydromechanical Type, Society of Automotive Engineers, Mar. 4, 2002, 11 pages.
 Pohl, et al., Configuration Analysis of a Spherical Traction Drive CVT/IVT, SAE International, 2004 International Continuously Variable and Hybrid Transmission Congress, Sep. 23, 2004, 6 pages.
 Smithson et al., Scalability for an Alternative Rolling Traction CVT, Society of Automotive Engineers, Mar. 8, 2004, 6 pages.
 Thomassy: An Engineering Approach to Simulating Traction EHL. CVT-Hybrid International Conference Mecc/Maastricht/The Netherlands, Nov. 17-19, 2010, p. 97.
 Examination Report dated Mar. 26, 2015 in European Patent Application No. 08874837.1.
 Office Action dated Nov. 13, 2014 in U.S. Appl. No. 14/171,025.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5






FIG. 6






FIG. 11




FIG. 10




FIG. 9





FIG. 12

FIG. 13






FIG. 14




FIG. 15A

FIG. 15B




FIG. 16A




FIG. 16B




FIG. 17




FIG. 18




FIG. 20




FIG. 21




FIG. 24
SECTION A-A




FIG. 22

FIG. 23




FIG. 25

FIG. 26




FIG. 27




FIG. 28

FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35

FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 41




FIG. 42





FIG. 40






FIG. 44




FIG. 45

FIG. 46






FIG. 47

FIG. 48






FIG. 51




FIG. 52




FIG. 53




FIG. 54




FIG. 56

FIG. 55




FIG. 57




FIG. 58




FIG. 60




FIG. 59




FIG. 62
DETAIL C




FIG. 61







FIG. 63

FIG. 64






FIG. 68




FIG. 67




FIG. 69




FIG. 70

FIG. 71







FIG. 72






FIG. 76




FIG. 75




FIG. 77




FIG. 78




FIG. 79




FIG. 80




FIG. 81




FIG. 83




FIG. 82

CONTINUOUSLY VARIABLE TRANSMISSION

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 14/171,025, filed Feb. 3, 2014 and scheduled to issue on Jul. 7, 2015 as U.S. Pat. No. 9,074,674, which is a continuation of U.S. patent application Ser. No. 13/796,452, filed Mar. 12, 2013 and issued as U.S. Pat. No. 8,641,572 on Feb. 4, 2014, which is a continuation of U.S. patent application Ser. No. 12/999,586, filed Mar. 23, 2011 and issued as U.S. Pat. No. 8,398,518 on Mar. 19, 2013, which is a national phase application of International Application No. PCT/US2008/067940, filed Jun. 23, 2008. The disclosures of all of the above-referenced prior applications, publications, and patents are considered part of the disclosure of this application, and are incorporated by reference herein in their entirety.

BACKGROUND OF THE INVENTION

Field of the Invention

The field of the invention relates generally to transmissions, and more particularly to continuously variable transmissions (CVTs).

Description of the Related Art

There are well-known ways to achieve continuously variable ratios of input speed to output speed. The mechanism for adjusting an input speed from an output speed in a CVT is known as a variator. In a belt-type CVT, the variator consists of two adjustable pulleys having a belt between them. The variator in a single cavity toroidal-type CVT has two partially toroidal transmission discs rotating about an axle and two or more disc-shaped power rollers rotating on respective axes that are perpendicular to the axle and clamped between the input and output transmission discs.

Embodiments of the invention disclosed here are of the spherical-type variator utilizing spherical speed adjusters (also known as power adjusters, balls, sphere gears or rollers) that each has a tiltable axis of rotation; the speed adjusters are distributed in a plane about a longitudinal axis of a CVT. The speed adjusters are contacted on one side by an input disc and on the other side by an output disc, one or both of which apply a clamping contact force to the rollers for transmission of torque. The input disc applies input torque at an input rotational speed to the speed adjusters. As the speed adjusters rotate about their own axes, the speed adjusters transmit the torque to the output disc. The input speed to output speed ratio is a function of the radii of the contact points of the input and output discs to the axes of the speed adjusters. Tilting the axes of the speed adjusters with respect to the axis of the variator adjusts the speed ratio.

SUMMARY OF THE INVENTION

The systems and methods herein described have several features, no single one of which is solely responsible for its desirable attributes. Without limiting the scope as expressed by the claims that follow, its more prominent features will now be discussed briefly. After considering this discussion, and particularly after reading the section entitled "Detailed Description of Certain Inventive Embodiments" one will understand how the features of the system and methods provide several advantages over traditional systems and methods.

One aspect of the invention relates to a continuously variable transmission having a group of balls that are arranged radially about a longitudinal axis. Each ball is configured to have a tiltable axis of rotation. In one embodiment, a leg is operably coupled to each of the balls. The leg can be configured to tilt the axis of rotation of the ball. The transmission can include a stator interfacial member slidably coupled to the leg. The transmission can also include a stator support member coupled to the stator interfacial member.

Another aspect of the invention concerns a transmission having a torque driver rotatable about a longitudinal axis. The torque driver can be configured to receive a power input. The transmission can include a torsion plate operably coupled to the torque driver. The torsion plate can have a splined inner bore and a group of triangular extensions extending radially from the splined inner bore. In one embodiment, the transmission includes a load cam ring operably coupled to the torsion plate. The transmission can include a load cam roller retainer assembly operably coupled to the load cam ring. The transmission includes a traction ring operably coupled to the load cam roller retainer assembly. The transmission also includes a group of balls arranged radially about a longitudinal axis. Each ball has a tiltable axis of rotation. Each ball can be operably coupled to the traction ring.

Yet another aspect of the invention involves a power input device that includes a torque driver rotatable about a longitudinal axis. The torque driver can be configured to receive a power input. In one embodiment, the power input device includes a torsion plate coupled to the torque driver. The torsion plate can have a splined inner bore and a number of triangular extensions extending radially from the splined inner bore. The power input device can include a load cam ring coupled to the torsion plate. In one embodiment, the power input device includes a load cam roller retainer subassembly coupled to the load cam ring. The power input device can also include a traction ring coupled to the load cam roller retainer subassembly.

One aspect of the invention concerns an assembly for an axial force generator that includes a first slotted ring configured to receive a number of load cam rollers. In one embodiment, the assembly includes a second slotted ring configured to receive the load cam rollers. The assembly can also include a spring configured to be retained in the first and/or second slotted ring.

Another aspect of the invention relates to a torsion plate having a substantially disc-shaped body with a splined inner bore. In one embodiment, the torsion plate has a number of structural ribs coupled to the disc-shaped body. The structural ribs extend radially from the spline inner bore. The torsion plate can also have a set of splines coupled to the outer periphery of the disc shaped body.

Yet one more aspect of the invention addresses a carrier for a continuously variable transmission having a group of planet subassemblies. Each planet subassembly has a ball configured to rotate about a tiltable axis. In one embodiment, the carrier includes a stator interfacial member configured to be operably coupled to a planet subassembly. The carrier can include a stator support member operably coupled to the stator interfacial member. The carrier can also include a stator torque reaction member operably coupled to the stator support member.

In another aspect, the invention concerns a transmission having a group of balls. Each ball is operably coupled to at least one leg. The transmission includes a stator interfacial member coupled to each leg. In one embodiment, the

transmission includes a stator support member coupled to the stator interfacial member. The transmission also includes a stator torque reaction member coupled to the stator support member.

Another aspect of the invention relates to a transmission having a group of planet assemblies arranged angularly about a longitudinal axis of the transmission. Each planet assembly has a leg. In one embodiment, the transmission includes a stator interfacial member coaxial with the longitudinal axis. The stator interfacial member has a number of radial grooves configured to slidably support the leg. The transmission also includes a stator support member coupled to the stator interfacial member. The stator support member is coaxial with the longitudinal axis.

One aspect of the invention relates to a stator assembly for a continuously variable transmission. The stator assembly includes a stator torque reaction insert having a number of torque reaction shoulders. In one embodiment, the stator assembly has a stator support member coupled to the stator torque reaction insert. The stator support member extends radially outward from the stator torque reaction insert. The stator support member can have a first face and a second face. The stator assembly can also include a stator interfacial member coupled to the stator support member. The stator interfacial member is substantially supported by the first face of the stator support member. The stator interfacial member has a number of radial grooves.

Another aspect of the invention addresses a stator support member for a continuously variable transmission (CVT). The stator support member can include a substantially disc-shaped body having an inner bore, a first face and a second face. The stator support member can also have a group of spacer support extensions arranged angularly on the first face. In one embodiment, the stator support member includes a number of guide support slots. Each guide support slot is arranged substantially between each of the spacer support extensions. The stator support member has a number of interlocking holes formed in each of the guide support slots. The stator support member also has a number of capture extensions formed on the outer periphery of the disc-shaped body.

One more aspect of the invention concerns a stator interfacial member for a continuously variable transmission. The stator interfacial member includes a substantially disc-shaped body having a central bore, a first face, and a second face. In one embodiment, the stator interfacial member includes a number of sliding guide slots that extend radially from the central bore. The guide slots can be arranged substantially on the first face. The stator interfacial member can include a set of interlocking tabs extending from the second face. The stator interfacial member has a capture ring formed around the outer circumference of the disc-shaped body. The stator interfacial member also has a group of capture cavities formed on the capture ring.

Yet another aspect of the invention involves a planet assembly for a continuously variable transmission (CVT) having a shift cam and a carrier assembly. The planet assembly has a ball with a through bore. In one embodiment, the planet assembly has a ball axle coupled to the through bore. The planet assembly also has a leg coupled to the ball axle. The leg has a first end configured to slidably engage the shift cam. The leg further has a face configured to slidably engage the carrier assembly.

Another aspect of the invention relates to a leg for a continuously variable transmission (CVT) having a carrier assembly. The leg includes an elongated body having a first end and a second end. In one embodiment, the leg has an

axle bore formed on the first end. The leg can have a shift cam guide surface formed on the second end. The shift cam guide surface can be configured to slidably engage a shift cam of the CVT. The leg can also have a sliding interface formed between the first end and the second end. The sliding interface can be configured to slidably engage the carrier assembly.

Yet another aspect of the invention involves a transmission. In one embodiment, the transmission includes a group of planet assemblies arranged angularly about, and on a plane perpendicular to, a longitudinal axis of the transmission. Each planet assembly has a leg. The transmission can include a set of stator interfacial inserts arranged angularly about the longitudinal axis. Each leg is configured to slidably couple to each of the stator interfacial inserts. The transmission can also include a stator support member mounted coaxially with the longitudinal axis. The stator support member can be configured to couple to each of the stator interfacial inserts.

In another aspect, the invention concerns a stator support member for a continuously variable transmission (CVT). The stator support member includes a generally cylindrical body having a central bore. In one embodiment, the stator support member has a number of insert support slots arranged angularly about, and extending radially from, the central bore. The stator support member can include a number of stator support extensions arranged coaxial with the insert support slots. The stator support extensions are arranged angularly about the central bore. Each of the stator support extensions has a fastening hole and a dowel pin hole.

Another aspect of the invention relates to a planet assembly for a continuously variable transmission (CVT) having a shift cam and a carrier assembly. The planet assembly includes a ball having a through bore. In one embodiment, the planet assembly includes a ball axle received in the through bore. The planet assembly can also include a leg coupled to the ball axle. The leg has a first end configured to slidably engage the shift cam. The leg has a face configured to slidably engage the carrier assembly. The leg has an axle bore formed on a second end. The leg has a bearing support extension extending from the axle bore.

One aspect of the invention relates to a shift cam for a continuously variable transmission (CVT). The shift cam has a number of leg contact surfaces arranged angularly about, and extending radially from, a longitudinal axis of the CVT. Each of the leg contact surfaces has a convex profile with respect to a first plane and a substantially flat profile with respect to a second plane. The shift cam also has a shift nut engagement shoulder formed radially inward of each of the leg contact surfaces.

Another aspect of the invention addresses a transmission having a group of planet assemblies arranged angularly about a longitudinal axis. Each planet assembly has a leg. The transmission can have a stator interfacial member operably coupled to each of the planet assemblies. The stator interfacial member can be coaxial with the group of planet assemblies. In one embodiment, the transmission has a stator support member coupled to the stator interfacial member. The stator support member includes a substantially bowl-shaped body having a central bore. The stator support member can have a fastening flange located on an outer periphery of the bowl-shaped body. The stator support member also includes a set of interlocking tabs located on an interior surface of the bowl-shaped body. The interlocking tabs are configured to couple to the stator interfacial member.

5

One more aspect of the invention concerns a stator support member for a continuously variable transmission having a stator interfacial member. In one embodiment, the stator support member has a substantially bowl-shaped body with a central bore. The stator support member includes a fastening flange located on an outer periphery of the bowl-shaped body. The stator support member also has a set of interlock tabs located on an interior surface of the bowl-shaped body.

Yet another aspect of the invention involves a stator interfacial member for a continuously variable transmission (CVT). The stator interfacial member includes a substantially disc-shaped body with an inner bore, a first face, and a second face. In one embodiment, the stator interfacial member has a number of guide slots arranged angularly about, and extending radially from the inner bore. The guide slots are formed on the first face. The stator interfacial member includes a set of interlock tabs substantially aligned with each of the guide slots. The interlock tabs are formed on the second face. The stator interfacial member can also include a number of stator support member extensions coupled to each of the guide slots. The stator support member extensions are located on an outer periphery of the disc-shaped body.

Another aspect of the invention relates to a transmission having a group of planet assemblies arranged angularly about a longitudinal axis of the transmission. Each planet assembly has a leg. In one embodiment, the transmission includes an axle arranged along the longitudinal axis. The transmission can include a first stator support member slidingly coupled to each of the planet assemblies. The first stator support member has a first central bore. The first central bore can be coupled to the axle. The transmission includes a second stator support member slidingly coupled to each of the planet assemblies. The second stator support member has a second central bore. The second central bore has a diameter larger than a diameter of the first central bore. The transmission can also include a set of stator spacers coupled to the first and second stator support members. The stator spacers are arranged angularly about the longitudinal axis.

Yet one more aspect of the invention addresses a stator support member for a continuously variable transmission (CVT). The stator support member has a generally disc-shaped body having a central bore. In one embodiment, the stator support member has a group of support extensions arranged angularly about the central bore. Each of the support extensions has a substantially triangular shape. Each of the support extensions is located radially outward of the central bore. The stator support member includes a number of stator spacer cavities coupled to the support extensions. The stator spacer cavities have a substantially triangular shape. The stator support member can also include a number of guide slots formed on the disc-shaped body. Each guide slot extends radially from the central bore. Each guide slot is substantially angularly aligned with each of the support extensions.

In another aspect, the invention concerns a stator spacer for a continuously variable transmission. The stator spacer includes an elongated body having a first end and a second end. In one embodiment, the stator spacer has a clearance neck formed between the first end and the second end. Each of the first and second ends has a substantially triangular cross-section. At least a portion of the clearance neck has a substantially diamond-shaped cross-section.

Another aspect of the invention relates to an idler assembly for a continuously variable transmission (CVT). The

6

idler assembly includes a substantially cylindrical idler having a central bore. The central bore defines a longitudinal axis. The idler is configured to rotate about the longitudinal axis. In one embodiment, the idler assembly includes first and second shift cams operably coupled respectively to a first and a second end of the idler. The first and second shift cams are configured to be substantially non-rotatable about the longitudinal axis. The idler assembly includes a first shift nut coupled to the first shift cam. The first shift nut has a threaded bore and a shift cam engagement shoulder extending radially from the threaded bore. The idler assembly also includes a second shift nut coupled to the second shift cam, the second shift nut comprising a second threaded bore and a second shift cam engagement shoulder extending radially from the second threaded bore.

One aspect of the invention relates to a method of manufacturing an idler assembly for a continuously variable transmission (CVT) having an axle arranged along a longitudinal axis. In one embodiment, the method includes providing a shift nut clearance slot in the axle. The method can include providing a substantially cylindrical idler having a central bore. The method includes operably coupling the idler to a first shift cam on a first end of the idler and to a second shift cam on a second end of the idler thereby yielding a subassembly including the idler, the first shift cam, and the second shift cam. The method includes placing a shift nut in the shift nut clearance slot. The shift nut has a shift cam engagement shoulder extending radially from a threaded bore. The method includes installing the subassembly of the idler, the first shift cam, and the second shift cam on the axle such that said subassembly substantially surrounds the shift nut. The method also includes coupling a shift rod to the threaded bore of the shift nut thereby coupling the shift nut engagement shoulder to the first or second shift cam.

Another aspect of the invention concerns a hub shell for a continuously variable transmission (CVT). The hub shell includes a generally hollow cylindrical body having a substantially closed end and a central bore. In one embodiment, the hub shell has first and a second spoke flanges coupled to an outer periphery of the hollow cylindrical body. The hub shell includes a set of brake splines coupled to the substantially closed end. The hub shell can have a locking chamfer coupled to the substantially closed end. The locking chamfer is located radially outward of, and coaxial with the brake splines. The hub shell can also include a set of splines coupled to the substantially closed end. The splines are located on an interior surface of the cylindrical body.

Yet another aspect of the invention involves a brake adapter kit for a continuously variable transmission (CVT) having a hub shell. The brake adapter kit includes a brake adapter ring having a brake alignment surface. The brake adapter ring has a locking chamfer configured to engage the hub shell. The brake adapter kit can include a roller brake adapter configured to couple to the brake adapter ring and to the hub shell. Once assembled the roller brake adapter is rigidly coupled to the hub shell.

One aspect of the invention concerns a brake adapter kit for a continuously variable transmission (CVT) having a hub shell. The brake adapter kit includes a brake adapter ring having a brake alignment surface. The brake adapter ring has a locking chamfer configured to engage the hub shell. In one embodiment, the brake adapter kit includes a disc brake adapter configured to couple to the brake adapter ring and to the hub shell. Once assembled the disc brake adapter is rigidly coupled to the hub shell.

Another aspect of the invention relates to a transmission having a group of planet assemblies arranged angularly about a longitudinal axis of the transmission. Each planet assembly has a leg. In one embodiment, the transmission includes a stator interfacial cap coupled to each leg. The transmission includes a stator support member coaxial with the planet assemblies. The stator support member has a number of guide grooves arranged angularly about, and extending radially from, the longitudinal axis. Each of the stator interfacial caps is configured to engage slidingly to the stator support member.

Yet one more aspect of the invention addresses a planet assembly for a continuously variable transmission. The planet assembly can include a ball with a through bore. The planet assembly includes an axle operably received in the through bore. The axle can be configured to provide a tiltable axis of rotation for the ball. In one embodiment, the planet assembly includes a leg coupled to the axle. The leg has an elongated body with a first end and a second end. The leg couples to the axle in proximity to the first end. The planet assembly also includes a stator interfacial cap coupled to the leg. The stator interfacial cap has a sliding interfacial surface.

BRIEF DESCRIPTION OF THE FIGURES

FIG. 1 is a perspective view of one embodiment of a bicycle having a continuously variable transmission (CVT) in accordance with inventive embodiments disclosed herein.

FIG. 2 is a partially cross-sectioned, perspective view of one embodiment of a (CVT).

FIG. 3 is a cross-sectional view of the CVT of FIG. 2.

FIG. 4 is a perspective, cross-sectional view of one embodiment of an input subassembly that can be used in the CVT of FIG. 2.

FIG. 5 is a perspective view of a torque driver that can be used in the input subassembly of FIG. 4.

FIG. 6 is a cross-sectional view of the torque driver of FIG. 5.

FIG. 7 is a perspective view of a torsion plate that can be used in the input subassembly of FIG. 4.

FIG. 8 is a cross-sectional view of the torsion plate of FIG. 7.

FIG. 9 is a perspective view of a load cam ring that can be used in the input subassembly of FIG. 4.

FIG. 10 is a cross-sectional view of the load cam ring of FIG. 9.

FIG. 11 is a perspective view of a traction ring that can be used in the input subassembly of FIG. 4.

FIG. 12 is an exploded, perspective, cross-sectional view of certain components of the CVT of FIG. 2.

FIG. 13 is a second exploded, perspective, cross-sectional view of certain of the components of FIG. 12.

FIG. 14 is a partial cross-section view of the components shown in FIG. 12.

FIG. 15A is a perspective view of one embodiment of a torsion plate that can be used in the input subassembly of FIG. 4.

FIG. 15B is a partially cross-sectioned perspective view of the torsion plate of FIG. 15A.

FIG. 16A is a cross-sectional perspective view of a torsion plate and traction ring that can be used with the CVT of FIG. 2.

FIG. 16B is an exploded cross-sectional perspective view of the torsion plate and traction ring of FIG. 16A.

FIG. 17 is a perspective view of one embodiment of an output load cam that can be used with the CVT of FIG. 2.

FIG. 18 is a block diagram showing one embodiment of a carrier assembly that can be used with the CVT of FIG. 2.

FIG. 19 is an exploded, partially-cross-sectioned, perspective view of the CVT of FIG. 2 employing an embodiment of a carrier assembly.

FIG. 20 is a cross-sectional view of the carrier assembly of FIG. 20.

FIG. 21 is an exploded, partially cross-sectioned, perspective view of one embodiment of a stator subassembly that can be used with the carrier assembly of FIG. 20.

FIG. 22 is a plan view of the stator subassembly of FIG. 21.

FIG. 23 is a second plan view of the stator subassembly of FIG. 21.

FIG. 24 is a cross-section of the stator subassembly of FIG. 21.

FIG. 25 is a perspective view of one embodiment of a stator support member that can be used with the stator subassembly of FIG. 21.

FIG. 26 is a second perspective view of the stator support member of FIG. 26.

FIG. 27 is a partially cross-sectioned, perspective view of a stator interfacial member that can be used with the stator subassembly of FIG. 21.

FIG. 28 is a perspective view of one embodiment of a planet subassembly that can be used in the CVT of FIG. 2.

FIG. 29 is a cross-sectional view of the planet subassembly of FIG. 28.

FIG. 30 is a perspective view of one embodiment of a leg that can be used with the planet subassembly of FIG. 28.

FIG. 31 is a cross-sectional view of the leg of FIG. 30.

FIG. 32 is a cross-sectional view of one embodiment of a leg that can be used with the planet subassembly of FIG. 28.

FIG. 33 is an exploded, partially cross-sectioned, perspective view of an embodiment of a carrier assembly that can be used with the CVT of FIG. 2.

FIG. 34 is a cross-sectional view of the carrier assembly of FIG. 33.

FIG. 35 is a perspective view of one embodiment of a stator support member that can be used with the carrier assembly of FIG. 33.

FIG. 36 is a partially cross-sectioned, perspective view of the stator support member of FIG. 35.

FIG. 37 is a plan view of the stator support member of FIG. 35.

FIG. 38 is a second plan view of the stator support member of FIG. 35.

FIG. 39 is a perspective view of one embodiment of a stator interfacial insert that can be used with the carrier assembly of FIG. 33.

FIG. 40 is a second perspective view of the stator interfacial insert of FIG. 39.

FIG. 41 is a cross-sectional view of the stator interfacial insert of FIG. 39.

FIG. 42 is a cross-sectional view of an embodiment of a stator interfacial insert that can be used with the carrier assembly of FIG. 33.

FIG. 43 is a partially cross-sectioned, exploded, perspective view of an embodiment of a carrier assembly that can be used with the CVT of FIG. 2.

FIG. 44 is a cross-sectional view of the carrier assembly of FIG. 43.

FIG. 45 is a perspective view of one embodiment of a stator support member that can be used in the carrier assembly of FIG. 43.

FIG. 46 is a second perspective view of the stator support member of FIG. 45.

FIG. 47 is a perspective view of one embodiment of a planet subassembly that can be used with the carrier assembly of FIG. 43.

FIG. 48 is a cross-sectional view of the planet subassembly of FIG. 47.

FIG. 49 is a partially cross-sectioned, perspective view of one embodiment of a shift cam that can be used in the CVT of FIG. 2.

FIG. 50 is a cross-sectional view of the shift cam of FIG. 49.

FIG. 51 is a partially cross-sectioned, exploded, perspective view of an embodiment of a carrier assembly that can be used in the CVT of FIG. 2.

FIG. 52 is a cross-sectional view of the carrier assembly of FIG. 51.

FIG. 53 is a perspective view of a stator support member that can be used in the carrier assembly of FIG. 51.

FIG. 54 is a second perspective view of the stator support member of FIG. 53.

FIG. 55 is a perspective view of one embodiment of a stator interfacial member that can be used in the carrier assembly of FIG. 51.

FIG. 56 is a second perspective view of the stator interfacial member of FIG. 55.

FIG. 57 is a partially cross-sectioned, exploded, perspective view of an embodiment of a carrier assembly that can be used in the CVT of FIG. 2.

FIG. 58 is a cross-sectional view of the carrier assembly of FIG. 57.

FIG. 59 is a perspective view of an embodiment of a stator support member that can be used in the carrier assembly of FIG. 57.

FIG. 60 is a perspective view of an embodiment of a stator support member that can be used in the carrier assembly of FIG. 57.

FIG. 61 is a perspective view of an embodiment of a stator spacer that can be used in the carrier assembly of FIG. 57.

FIG. 62 is a cross-sectional view of the stator spacer of FIG. 61.

FIG. 63 is a perspective view of an embodiment of a main axle that can be used in the CVT of FIG. 2.

FIG. 64 is a partially cross-sectioned, perspective view of a shift nut that can be used in the CVT of FIG. 2.

FIG. 65A is a partially cross-sectioned, exploded, perspective view of an embodiment of an idler assembly that can be used in the CVT of FIG. 2.

FIG. 65B is a cross-section of the idler assembly of FIG. 65A.

FIG. 66 is a perspective view of an embodiment of a shift nut that can be used in the idler assembly of FIG. 65A.

FIG. 67 is a perspective view of an embodiment of a hub shell that can be used in the CVT of FIG. 2.

FIG. 68 is a second perspective view of the hub shell of FIG. 67.

FIG. 69 is a cross-sectional view of the hub shell of FIG. 67.

FIG. 70 is a perspective view of an embodiment of a hub cover that can be used in the CVT of FIG. 2.

FIG. 71 is a second perspective view of the hub cover of FIG. 70.

FIG. 72 is a cross-sectional view of the hub cover of FIG. 70.

FIG. 73 is a perspective view of an embodiment of a brake adapter ring that can be used with the CVT FIG. 2.

FIG. 74 is a cross-sectional view of the brake adapter ring of FIG. 73.

FIG. 75 is a perspective view of an embodiment of a disc brake adapter that can be used with the CVT of FIG. 2.

FIG. 76 is a cross-section of the disc brake adapter of FIG. 75.

FIG. 77 is a perspective view of an embodiment of a roller brake adapter that can be used with the CVT of FIG. 2.

FIG. 78 is a second perspective view of the roller brake adapter of FIG. 77.

FIG. 79 is a cross-sectional view of the roller brake adapter of FIG. 77.

FIG. 80 is a partially cross-sectioned, exploded, perspective view of an embodiment of a carrier assembly that can be used with the CVT of FIG. 2.

FIG. 81 is a cross-sectional view of the carrier assembly of FIG. 80.

FIG. 82 is an exploded, perspective view of an embodiment of a planet subassembly that can be used with the carrier assembly of FIG. 80.

FIG. 83 is an exploded, perspective view of certain components of the planet subassembly of FIG. 82.

DETAILED DESCRIPTION OF CERTAIN INVENTIVE EMBODIMENTS

The preferred embodiments will be described now with reference to the accompanying figures, wherein like numerals refer to like elements throughout. The terminology used in the descriptions below is not to be interpreted in any limited or restrictive manner simply because it is used in conjunction with detailed descriptions of certain specific embodiments of the invention. Furthermore, embodiments of the invention can include several novel features, no single one of which is solely responsible for its desirable attributes or which is essential to practicing the inventions described. The CVT embodiments described here are generally of the type disclosed in U.S. Pat. Nos. 6,241,636; 6,419,608; 6,689,012; 7,011,600; 7,166,052; U.S. patent application Ser. Nos. 11/243,484; 11/543,311; 60/948,273; 60/864,941; and Patent Cooperation Treaty Patent Application PCT/US2007/023315. The entire disclosure of each of these patents and patent applications is hereby incorporated herein by reference.

As used here, the terms “operationally connected,” “operationally coupled,” “operationally linked,” “operably connected,” “operably coupled,” “operably linked,” and like terms, refer to a relationship (mechanical, linkage, coupling, etc.) between elements whereby operation of one element results in a corresponding, following, or simultaneous operation or actuation of a second element. It is noted that in using said terms to describe inventive embodiments, specific structures or mechanisms that link or couple the elements are typically described. However, unless otherwise specifically stated, when one of said terms is used, the term indicates that the actual linkage or coupling may take a variety of forms, which in certain instances will be readily apparent to a person of ordinary skill in the relevant technology.

For description purposes, the term “radial” is used here to indicate a direction or position that is perpendicular relative to a longitudinal axis of a transmission or variator. The term “axial” as used here refers to a direction or position along an axis that is parallel to a main or longitudinal axis of a transmission or variator. For clarity and conciseness, at times similar components labeled similarly (for example, stator assembly 200A and stator assembly 200B) will be referred to collectively by a single label (for example, stator assembly 200).

11

Embodiments of a continuously variable transmission (CVT), and components and subassemblies therefor, will be described now with reference to FIGS. 1-83. Referring now to FIG. 1, in one embodiment a bicycle 1 can include a continuously variable transmission (CVT) 100 supported in a frame 2. For simplification, only the rear portion of the bicycle 1 is shown FIG. 1. The frame 2 can include a set of dropouts 3 that are configured to support the CVT 100. A sprocket 4 can couple to the CVT 100, and the sprocket 4 further couples via a drive chain 5 to a crank sprocket 6. The crank sprocket 6 is typically coupled to a pedal and crank assembly 7. The CVT 100 can be coupled to a wheel 8 via a number of wheel spokes 9. For clarity, only a few of the wheel spokes 9 are shown in FIG. 1 as an illustrative example. In one embodiment, the transmission ratio of the CVT 100 can be adjusted via cables and a handle grip (not shown).

The CVT 100 can be used in many applications including, but not limited to, human powered vehicles, light electrical vehicles hybrid human-, electric-, or internal combustion powered vehicles, industrial equipment, wind turbines, etc. Any technical application that requires modulation of mechanical power transfer between a power input and a power sink (for example, a load) can implement embodiments of the CVT 100 in its power train.

Turning now to FIGS. 2 and 3, in one embodiment the CVT 100 includes a hub shell 102 coupled to a hub cover 104. The hub shell 102 substantially surrounds the internal components of the CVT 100. A brake adapter kit 106 couples to the hub shell 102. The CVT 100 can include a number of planet subassemblies 108 supported in a carrier assembly 101. The planet subassemblies 108 couple to an input subassembly 110, which input subassembly 110 is generally depicted in detail view A). In some embodiments, the planet subassemblies 108 are operably coupled to the hub shell 102 via a traction ring 145. The traction ring 145 can be configured to engage a cam roller retainer assembly 147, which couples to an output cam ring 149. The hub shell 102 couples to the output cam ring 149 in one embodiment. A main axle 112 can be arranged along the longitudinal axis of the CVT 100 and can be coupled to, for example, the dropouts 3 with no-turn-washers 114, axle nut 116, and lock-nut 118. In one embodiment, a shift rod 120 can be arranged along a central bore of the main axle 112 and can be coupled to an idler subassembly 109 via a shift nut 119. The idler subassembly 109 is arranged radially inward of, and in contact with, the planet subassemblies 108. The shift rod 120 can be axially constrained in the main axle 112 via a shift-rod-lock nut 122. In one embodiment, the shift rod 120 couples to, for example, cables (not shown) that are operationally coupled to a handle grip or user control interface (not shown). For descriptive purposes, the sprocket side of the CVT 100 can be referred to as the input side of the CVT 100, and the brake adapter kit 106 side of the CVT 100 can be referred to as the output side of the CVT 100.

During operation of CVT 100, an input power can be transferred to the input subassembly 110 via, for example, the sprocket 4. The input subassembly 110 can transfer power to the planet subassemblies 108 via a traction or friction interface between the input subassembly 110 and the planet subassemblies 108. The planet subassemblies 108 deliver the power to the hub shell 102 via the traction ring 145 and the output cam ring 149. A shift in the ratio of input speed to output speed, and consequently a shift in the ratio of input torque to output torque, is accomplished by tilting the rotational axis of the planet subassemblies 108. A shift in the transmission ratio involves actuating an axial or

12

rotational movement of the shift rod 120 in the main axle 112, which facilitates the axial translation of the idler assembly 109 and thereby motivates the tilting of the rotational axis of the planet subassemblies 108.

5 Passing now to FIG. 4, in one embodiment the input subassembly 110 includes a torque driver 140 coupled to a torsion plate 142. The torsion plate 142 can be attached to a load cam ring 144 with, for example, screw fasteners or rivets. In some embodiments, the torsion plate 142 can be coupled to the load cam ring 144 with a spline. In one embodiment, the load cam ring 144 couples to a load cam roller retainer subassembly 146. The load cam roller retainer subassembly 146 further couples to a traction ring 148. The load cam ring 144, the load cam roller retainer subassembly 146, and the traction ring 148 are preferably configured to produce axial force during operation of the CVT 100. In other embodiments, the load cam ring 144, the load cam roller retainer subassembly 146, and the traction ring 148 are substantially similar in function to the traction ring 145, the load cam roller retainer 147, and the output cam ring 149 that are located on the output side of the CVT 100.

Referring to FIGS. 5 and 6, in one embodiment the torque driver 140 can be a substantially hollow cylindrical body with a first end having a set of torsion plate engagement splines 130 and a second end having a set of sprocket engagement splines 132. In some embodiments, the torque driver 140 can include a sprocket support shoulder 134 located on the outer circumference of the cylindrical body and axially positioned between the torsion plate engagement splines 130 and the sprocket engagement splines 132. In other embodiments, the second end can have a standard bicycle freewheel thread to allow the coupling of a threaded freewheel or threaded sprocket. A first bearing bore 136 can be provided on the inner circumference of the cylindrical body in proximity to the first end. A first bearing support shoulder 137 can be arranged on the inner circumference of the cylindrical body in proximity to the first bearing bore 136. A second bearing bore 138 can be provided on the inner circumference of the cylindrical body in proximity to the sprocket engagement splines 132. A second bearing support shoulder 139 can be arranged on the inner circumference of the cylindrical body in proximity to the second bearing bore 138. In some embodiments, the torque driver 140 includes a number of service tool engagement splines 135 formed on the inner circumference of the cylindrical body. The service tool engagement splines 135 can be arranged in proximity to the sprocket engagement splines 132 and can generally be accessible to the exterior of the CVT 100.

Turning to FIGS. 7 and 8, in one embodiment the torsion plate 142 includes a splined inner bore 170 and a number of triangular extensions 172 extending radially from the splined inner bore 170. In some embodiments, the triangular extensions 172 are substantially axially aligned with a first end of the splined inner bore 170 so that the splined inner bore 170 and the triangular extensions 172 form a substantially flat face on the torsion plate 142. In other embodiments, the triangular extensions 172 extend from the splined inner bore 170 so that the radially outward end of the triangular extension 172 is angled relative to the splined inner bore 170 when viewed in the plane of the page of FIG. 8. In one embodiment, each of the triangular extensions 172 can be provided with a cutout 174. Each of the triangular extensions 172 can be provided with a fastening hole 176 positioned on a radially outward portion of the extension 172. The fastening holes 176 facilitate the coupling of the torsion plate 142 to the load cam ring 144. The splined inner bore 170 facilitates the coupling of the torsion plate 142 to

the torque driver 140. The triangular extensions 172 provide a lightweight and torsionally stiff structure to the torsion plate 142. The torsion plate 142 can be made from steel, aluminum, magnesium, plastic, or other suitable material.

Turning to FIGS. 9 and 10, in one embodiment the load cam ring 144 is a substantially annular ring with a number of ramps 152 formed on a first side of the annular ring. The load cam ring 144 can include a set of preload spring grooves 154, which can be formed on the first side of the annular ring. In some embodiments, the load cam ring 144 can have a bearing support surface 158 formed on a second side of the annular ring that is oppositely located from the first side of the annular ring. In one embodiment, the load cam ring 144 can include a number of fastening lugs 156 arranged on the inner circumference of the annular ring. The fastening lugs 156 can be substantially axially aligned with the second side of the annular ring. In some embodiments, the fastening lugs 156 can be used to support an over-molded plastic torsion plate that is substantially similar to torsion plate 142.

Referring to FIG. 11, the traction ring 148 can be a generally annular ring having a number of ramps 153 formed on one side. The traction ring 148 can be provided with a traction contact surface 1480 on the inner circumference of the annular ring that is substantially opposite the side having ramps 153. The traction contact surface 1480 is configured to contact the planet subassembly 108. A number of preload spring grooves 155 can be formed on the annular ring. In one embodiment, the preload spring grooves 155 are formed on the side having the ramps 153. In the embodiment shown in FIGS. 2 and 3, the traction ring 145 is substantially similar to the traction ring 148.

Referring now to FIGS. 12-14, in one embodiment, an axial force generator device includes, among other things, the load cam ring 144, the load cam roller retainer subassembly 146 and the traction ring 148. In one embodiment, the ramps 152 are arranged to contact a number of load cam rollers 160. The load cam rollers 160 are retained in the load cam roller retainer subassembly 146. A number of springs 162, for example two, can be retained in the load cam roller retainer subassembly 146 and can be arranged to simultaneously contact the load cam ring 144 and the traction ring 148. In the embodiment illustrated in FIG. 13, the load cam roller retainer subassembly 146 includes a first slotted ring 146A coupled to a second slotted ring 146B. In some embodiments, the first and second slotted rings 146A, 146B are received in a band 146C. The first slotted ring 146A and the second slotted ring 146B can be provided with slots 164. The slots 164 are configured to support the load cam rollers 160. The first slotted ring 146A and the second slotted ring 146B can be coupled together with, for example, a plurality of pegs 166A and bores 166B. In some embodiments, each of the slotted rings 146A and 146B have equally as many pegs 166A as bores 166B. The arrangement of the pegs 166A and the bores 166B around the face of the slotted rings 146A and 146B can be configured to accommodate various manufacturing methods, such as plastic injection molding. For example, the arrangement of the pegs 166A and the bores 166B can allow the slotted rings 146A and 146B to be substantially identical for manufacture while retaining features for alignment during assembly. In one embodiment, the pegs 166A are arranged around half the circumference of the slotted ring 146A while the bores 166B are arranged around the other half of the circumference. The arrangement of pegs 166A and 166B are substantially similar on slotted ring 146B, so that once assembled the slotted rings 146A and 146B are aligned when joined. In some embodiments, the

slotted rings 146A and 146B are further retained around their outer circumference or periphery with the band 146C. The band 146C can be a generally annular ring made from, for example, steel or aluminum. An outer circumference of the band 146C can have a number of holes 167. The holes 167 are generally aligned with the slotted rings 146A and 146B. The holes 167 are configured to, among other things, axially retain and align the slotted rings 146A and 146B. In some embodiments, the slotted rings 146A and 146B can be coupled to the band 146C with standard fasteners (not shown) via fastening the holes 167. In other embodiments, the fastening holes 167 can receive mating features formed onto outer periphery of the slotted rings 146.

Still referring to FIGS. 12-14, a plurality of springs 162, for example two, are retained in load cam roller retainer subassembly 146 and are arranged in such a way that one end of the spring 162 couples to the load cam ring 144 and the other end of the spring 162 couples to the traction ring 148. The springs 162 can be generally arranged 180-degrees with respect to each other for configurations provided with two springs. In one embodiment, a middle portion of the spring 162 is retained in the load cam roller retainer subassembly 146. Shoulders 177 and 173 formed on the slotted rings 146A and 146B, respectively, can be provided to capture the middle portion of the spring 162. In some embodiments, the spring 162 can be a coil spring of the compression type. In other embodiments, the spring 162 can be a wire spring. In yet other embodiments, the spring 162 can be a flat spring. It is preferable that the ends of spring 162 have rounded or curved surfaces that have generally the same shape as reaction surfaces 170 and 171.

A preload spring groove 154 can be formed onto the load cam ring 144. Similarly, a groove 155 can be formed onto the traction ring 148. Once assembled, the preload spring grooves 154 and 155 aid to, among other things, retain the spring 162 and provide the reaction surfaces 170 and 171, respectively. Channels 174 and 175 can be formed into the slotted rings 146A and 146B to provide clearance for the spring 162.

Preferably, once assembled, the springs 162 are configured to apply a force on the load cam ring 144 and the traction ring 148 that engages the load cam rollers 160 with the load cam ring 144 and the traction ring 148. The load cam rollers 160 are positioned generally on the flat portion of the ramps 152 and 153. The interaction between the traction ring 148, the load cam ring 144, and the springs 162 causes the load cam rollers 160 to roll up the ramps 152 and 153 for some distance to produce a preload that ensures that a certain minimum level of clamping force will be available during operation of the CVT 100.

Passing now to FIGS. 15A-15B, a torsion plate 1420 can include a substantially disc-shaped body having a splined inner bore 1422 configured to couple to, for example, the torque driver 140. The torsion plate 1420 can be provided with a bearing support surface 1424 on the outer periphery of one side of the disc-shaped body, and the torsion plate 1420 can be provided with a set of engagement splines 1426 located on the outer periphery of a second side of the disc-shaped body. The engagement splines 1426 can be configured to engage a cam ring such as cam ring 144. In one embodiment, the torsion plate 1420 can include a number of structural ribs 1428 arranged on the disc-shaped body. The structural ribs 1428 can form a lattice or triangulated pattern that connects the outer periphery of the disc-shaped body to the splined inner bore 1422.

Referring to FIGS. 16A and 16B, a torsion plate 1600 can couple to a load cam ring 1602. The load cam ring 1602 and

the torsion plate **1600** can generally be used in CVT **100** in a similar manner as the load cam ring **144** and the torsion plate **142**. In one embodiment, the torsion plate **1600** can be a generally disc shaped body **1604** having a splined central bore **1606**. The splined central bore **1606** can be configured to mate with the splines **130** of the torque driver **140**, for example. An outer periphery of the disc shaped body **1604** can be provided with a number of splines **1608**. In some embodiments, the torsion plate **1600** can include a number of structural ribs **1609** formed on a first side of the disc shaped body **1604**. The structural ribs **1609** can extend radially outward from the splined central bore **1606** and can be configured in a substantially triangulated pattern, such as the pattern shown in FIG. **16A**. Configuring the structural ribs **1609** in this way can, among other things, improve the torsional strength and stiffness to the torsion plate **1600**.

The load cam ring **1602** can include a substantially annular ring **1610** having a number of ramps **1612** formed on a first face. The ramps **1612** can be substantially similar to the ramps **152**. The inner circumference of the annular ring **1610** can be provided with a number of splines **1614** that can be adapted to mate with the splines **1608**. In one embodiment, the torsion plate **1600** can be made of a plastic material that is formed over the load cam ring **1602**. The splines **1608** and **1614** can be configured to rigidly couple the torsion plate **1600** to the traction ring **1602**. In one embodiment, the annular ring **1610** can be provided with a bearing support surface **1616** that can be substantially similar to the bearing support surface **158**. In some embodiments, the annular ring **1610** can include a number of preload spring grooves **1618** that are substantially similar to the preload spring grooves **155**.

Turning to FIG. **17**, in one embodiment the output cam ring **149** can be a generally annular ring, substantially similar to the load cam ring **144**. The output cam ring **149** can include a number of preload spring slots **1492** arranged substantially similar to the preload spring slots **154**. The output cam ring **149** can also be provided with ramps **1494** that are substantially similar to ramps **152**, and are configured to engage the load cam rollers **160**. In one embodiment, the output cam ring **149** includes lugs **1496** arranged on the inner circumference of the annular ring. The lugs **1496** are preferably adapted to couple to a mating feature on the hub shell **102**.

Referring now to the functional block diagram of FIG. **18**, in one embodiment a carrier assembly **50** can be configured to couple to, and/or to support, a planet subassembly **52**. The carrier assembly **50** can be functionally similar in some respects to the carrier assembly **101**. The planet subassembly **52** can be functionally similar in some respects to the planet subassembly **108**. The carrier assembly **50** includes a stator interfacial member **54** coupled to the stator support member **56**. In one embodiment, the stator support member **56** is further coupled to a stator torque reaction member **58**. The stator interfacial member **54** can be configured to provide a sliding interface between certain components of the planet subassembly **52** and the stator support member **56**. In one embodiment, the stator interfacial member **54** is a component that attaches to the stator support member **56**. In some embodiments, the stator interfacial member **54** is integral with the stator support member **56**. In yet other embodiments, the stator interfacial member **54** is integral with the planet subassembly **52**. The stator interfacial member **54** is preferably a low-friction interface and made from materials such as plastic, bronze, or polished metals.

The stator support member **56** can be configured to provide structural support for the carrier assembly **50**, and

the stator support member **56** can be adapted to react forces generated during operation of the CVT **100**. The stator support member **56** positions and supports the planet subassembly **52**. The stator torque reaction member **58** can be provided to transfer torque from the stator support member **56** to another component in, for example, the CVT **100** during operation of the CVT **100**. In one embodiment, the stator torque reaction member **58** is a component that can be coupled to the stator support member **56** so that the stator torque reaction member **58** can be made from a different material than the stator support member **56**. For example, the stator torque reaction member **58** can be made of steel and the stator support member **56** can be made of aluminum. It should be noted that the reference to steel and aluminum are exemplary only; in other embodiments, other materials can be used (such as, for example, plastics, alloys, ceramics, composites, etc.). In some embodiments, the stator torque reaction member **58** is integral with the stator support member **56**. In yet other embodiments, the stator interfacial member **54**, the stator support member **56**, and the stator torque reaction member **58** can be one integral component.

Turning now to FIGS. **19** and **20**, the carrier assembly **101** can include a first stator subassembly **200A** coupled with a number of stator spacers **202** to a second stator subassembly **200B**. The stator spacers **202** can be arranged angularly around the perimeter of the stator subassemblies **200**. In one embodiment, the stator spacers **202** can be attached to the stator subassemblies **200** with common fasteners. In the embodiment shown in FIG. **20**, the stator spacers **202** are orbit formed on stator spacer ends **203** for coupling the stator spacers **202** and the stator subassemblies **200**. The carrier assembly **101** supports and facilitates a tilting of the rotational axis of balls **240** of the planet subassemblies **108**. In some embodiments, the carrier assembly **101** is configured to couple to the main axle **112**. In one embodiment, for example, the carrier assembly **101** is rigidly and non-rotatably coupled to the main axle **112**.

Referring to FIGS. **21-27**, the stator subassembly **200** can include a stator torque reaction insert **204**, a stator support member **206**, and a stator interfacial member **208**. In one embodiment, the stator torque reaction insert **204** can be rigidly attached to the stator support member **206**, and the stator interfacial member **208** can be attached to the stator support member **206**.

The stator torque reaction insert **204** facilitates the coupling of the carrier assembly **101** to the main axle **112**. In one embodiment, the stator torque reaction insert **204** includes a number of torque reaction shoulders **210** that are adapted to engage mating surfaces on the main axle **112**. The stator torque reaction insert **204** prevents, among other things, rotation of the stator subassembly **200** with respect to the main axle **112**. In one embodiment, the stator torque reaction insert **204** has six torque reaction shoulders **210** that form a hexagonal body. A number of locking splines **212** can be provided on the periphery of the hexagonal body. The locking splines **212** can facilitate the rigid attachment of the stator torque reaction insert **204** to the stator support member **206**.

In one embodiment, the stator support member **206** includes a substantially disc-shaped body having an inner bore adapted to couple to the stator torque reaction insert **204**. In some embodiments, the stator support member **206** has an inner bore having a hexagonal shape. The stator support member **206** can be provided with a number of spacer support extensions **214** arranged angularly on a first face of the disc-shaped body about the longitudinal axis of the CVT **100**. The stator support extensions **214** are prefer-

ably positioned angularly about the longitudinal axis of the CVT 100 and, for example, can be placed angularly between the planet subassemblies 108 in the CVT 100. In one embodiment, each of the spacer support extensions 214 includes a stator spacer support hole 216. In some embodiments, the stator spacer support holes 216 are arranged on a radially outward periphery of the stator support extensions 214. In one embodiment, each of the stator spacer support holes 216 can be provided with a stator spacer end relief 217 (see FIG. 25, for example). The stator spacer end relief 217 substantially surrounds the stator spacer support hole 216. Once assembled, the stator spacer end 203 is substantially enclosed in the stator spacer end relief 217. The arrangement of stator spacers 200 on the outward periphery of the stator support extensions 214 maximizes torsional stiffness of the carrier assembly 101. The stator support member 206 can be provided with a number of structural ribs 218 arranged on a face of the disc-shaped body. The structural ribs 218 provide strength and stiffness to the disc-shaped body. The stator support member 206 provides structural support to the carrier assembly 101 for reacting forces generated during the operation of, for example, the CVT 100.

Referring to FIGS. 21-27, the stator support member 206 can be further provided with a number of guide support slots 220. The guide support slots 220 are substantially arranged between the spacer support extensions 214 around the disc-shaped body and extend radially outward from the inner bore. The number of guide support slots 220 provided on the stator support member 206 generally, though not necessarily, corresponds to the number of planet subassemblies provided in the CVT 100. Each of the guide support slots 220 can be provided with a leg clearance relief 222A positioned on a radially inward portion of the guide support slot 220. The leg clearance reliefs 222A provide clearance for certain components of the planet subassembly 108 during operation of the CVT 100. In some embodiments, the stator support member 206 can include a piloting shoulder 224 located radially inward of the guide support slots 220 and spacer support extensions 214. The piloting shoulder 224 facilitates alignment of the stator support member 206 to the stator interfacial member 208. In some embodiments, the stator support member 206 can have a uniform material thickness throughout the component, which aides manufacturing processes such as casting or forging.

In one embodiment, the stator interfacial member 208 is a substantially disc-shaped body having an inner bore. The stator interfacial member 208 can be provided with a number of sliding guide slots 226 arranged angularly about a longitudinal axis of the disc-shaped body. The disc-shaped body can include a number of interlocking tabs 228 formed on one side. The interlocking tabs 228 are configured to mate with a number of interlocking holes 229 on the stator support member 206. In some embodiments, a number of leg clearance reliefs 222B are formed toward the inner periphery of the guide slots 226. The stator interfacial member 208 can be provided with a capture ring 230 formed on the outer periphery of the disc-shaped body. The capture ring 230 is preferably formed on the side of the disc-shaped body with the interlocking tabs 228. The capture ring 230 can couple to a capture shoulder 231 formed on the stator support member 206. The interlocking tabs 228 and capture ring 230 facilitate a rigid coupling between the stator interfacial member 208 and the stator support member 206. A number of capture extensions 232 (see FIG. 26) can be provided on the outer periphery of the stator support member 206. The capture extensions 232 are generally concentric with the capture shoulder 231 and are configured to couple to capture

cavities 233 (FIG. 27) of the stator interfacial member 208. In one embodiment, the stator interfacial member 208 can be a plastic component, and can be pressed onto the stator support member 206 so that the capture ring 230 and the interlocking tabs 228 engage the corresponding mating capture shoulder 231 and the interlocking holes 229. In some embodiments, the stator interfacial member 208 can be plastic injection molded onto the stator support member 206. The stator interfacial member 208 facilitates a low friction, sliding coupling between the carrier assembly 101 and the planet subassemblies 108.

Turning now to FIGS. 28-29, the planet subassembly 108 can include a substantially spherical ball 240, a ball axle 242, and at least one leg 244. The ball 240 can be provided with a central bore. The ball 240 is supported on the ball axle 242 with ball support bearings 249 arranged in the central bore and positioned with spacers 245A, 245B, and 245C. In other embodiments, the spacers 245A, 245B, and 245C can be integral with the ball support bearings 249. The ball axle 242 can be supported on one end with one leg 244 and on a second end with another leg 244. In some embodiments, the leg 244 can be pressed onto the ball axle 242 so that there is no relative motion between the leg 244 and the ball axle 242 during operation of the CVT 100. The legs 244 can be configured to act as levers to pivot the ball axle 242 about the center of the ball 240.

Referring to FIGS. 30-32, in one embodiment the leg 244 includes a sliding interface 246 and a shift cam guide end 248. The leg 244 can be provided with a ball axle support bore 250. In some embodiments, the leg 244 can include a hole 252. The hole 252 can serve to, among other things, reduce the weight of the leg 244. In one embodiment, the sliding interface 246 can have a length L1 of about 12.5 mm and a width W1 of about 8 mm. In some embodiments, a leg 2444 can be substantially similar in function to the leg 244. The leg 2444 can be provided with a sliding interface 2466 that can be of a length L2 that can be about 7 mm, for example. The shift cam guide end 2488 can have a width w2, which is generally about 3.5 mm. The shift cam guide ends 248 and 2488 are preferably adapted to slide on the shift cams 260 (see FIG. 20, for example). The sliding interfaces 246 and 2466 are preferably adapted to slide in the carrier assembly 101. In some embodiments, the sliding interfaces 246 and 2466 have curved profiles as shown in the plane of the page of FIG. 31 or FIG. 32. Each of the curved profiles of the sliding interfaces 246 and 2466 are typically conformal to a mating surface of the carrier assembly 101. The legs 244 or 2444 are preferably adapted to transfer forces from the planet subassembly 108 to the carrier assembly 101.

Passing now to FIGS. 33-34, an alternative carrier assembly 300 includes a number of stator interfacial inserts 302 supported in a stator support member 304. The stator interfacial inserts 302 are slidingly coupled to legs 240 of the planet subassemblies 108. The carrier assembly 300 includes a retaining ring 306 configured to couple the stator interfacial inserts 302 to the stator support member 304. In one embodiment, the carrier assembly 300 includes two stator support members 304 rigidly coupled together. Preferably, each leg 240 of the planet subassemblies 108 is provided with a corresponding stator interfacial insert 302. It should be readily apparent to a person having ordinary skill in the relevant technology that the carrier assembly 300 is substantially similar in function to the carrier assembly 101.

Referring to FIGS. 35-38, the stator support member 304 can be a generally cylindrical body having a central bore. The stator support member 304 can include a number of

insert support slots **308**. The insert support slots **308** can be arranged angularly about, and extend radially from, the central bore of the cylindrical body. Preferably, though not necessarily, the stator support member **304** has at least one insert support slot **308** for each stator interfacial insert **302**. Each of the insert support slots **308** can have a tab engagement hole **310** formed on a radially inward portion of the insert support slot **308**. The tab engagement hole **310** can be configured to couple to a mating feature on the stator interfacial insert **302**. The stator support member **304** can be provided with a number of support extensions **312**. Each of the stator support extensions **312** includes a fastening hole **314** and a dowel pin hole **315**; each hole is configured to receive a fastener and a dowel pin, respectively. In one embodiment, the fastening hole **314** is arranged radially inward of the dowel pin hole **315**. The stator support member **304** can be provided with a number of cutouts **316** formed on one end of the cylindrical body. Preferably, the cutouts **316** reduce the weight of the stator support member **304** while retaining the strength and stiffness of the component. In one embodiment, the stator support member **304** can have a number of torque reaction shoulders **318** formed on the inner bore. The torque reaction shoulders **318** can be adapted to mate with corresponding shoulders on the main axle **112**. In some embodiments, the torque reaction shoulders **318** form a square bore. In one embodiment, the stator support member **304** is provided with a retaining ring groove **320** that is configured to couple to the retaining ring **306**.

Turning now to FIGS. **39-42**, the stator interfacial insert **302** can be a generally rectangular body having a back **322** with at least two side extensions **324** attached to the back **322**. A stator interlock tab **326** can be formed on the back **322**. In one embodiment, the stator interlock tab **326** can be substantially circular and extend from the back **322**. The stator interlock tab **326** can be configured to couple to the tab engagement hole **310** on the stator support member **304**. In one embodiment, the stator interfacial insert **302** includes a retaining shoulder **328** formed on an end of the back **322** at a distal location from the stator interlock tab **326**. The retaining shoulder **328** is configured to couple to the retaining ring **306**. In other embodiments, a stator interfacial insert **303** is not provided with a retaining shoulder such as the retaining shoulder **328**, but can share many other similar elements with the stator interfacial insert **302**.

The stator interfacial insert **302** can be provided with a sliding guide surface **330** formed between the two side extensions **324**. The sliding guide surface **330** is preferably adapted to couple to a leg **240** of the planet subassembly **108**. In one embodiment, the sliding guide surface **330** has a leg clearance recess **332** formed on an end of the rectangular body in proximity to the stator interlock tab **326**. The stator interfacial insert **302** preferably is made from a low-friction material with sufficient compressive strength. For example, the stator interfacial insert **302** can be made out of a variety of plastics that can include Fortron 1342L4, Nylon 6/6 resin, Vespel, Rulon, PEEK, Delrin or other materials. The materials listed here are merely examples and are not intended to be an exhaustive list of acceptable materials as many different types of materials can be used in the embodiments disclosed herein.

Passing now to FIGS. **43-44**, in one embodiment a carrier assembly **400** includes a stator support member **402** coupled a stator torque reaction insert **404**, which can be substantially similar to the stator torque reaction insert **204**. The stator support member **402** is adapted to slidably couple to a number of planet subassemblies **406**. Preferably, the

carrier assembly **400** includes two stator support members **402** coupled to each other with common screw fasteners, rivets, or welds.

Referring to FIGS. **45-46**, in one embodiment the stator support member **402** is a substantially bowl-shaped body having a central bore. The stator support member **402** can include a fastening flange **410** having a number of fastening holes **411**. The fastening flange **410** can be arranged on the outer periphery of the bowl-shaped body. A number of guide support slots **412** can be formed on the interior of the bowl-shaped body. The stator support member **402** can be provided with a number of ball clearance cutouts **414** configured to substantially surround each of the planet subassemblies **406**. The stator support member **402** can include a number of torque reaction shoulders **416** formed on the central bore of the bowl-shaped body. In one embodiment, the torque reaction shoulders **416** form a hexagonal pattern. The torque reaction shoulders **416** can be adapted to couple to the stator torque reaction insert **404**. The stator support member **402** can be provided with a number of structural ribs **418** arranged on the bottom of the bowl-shaped body. The structural ribs provide strength and stiffness to the stator support member **402**.

Referring to FIGS. **47** and **48**, in one embodiment the planet subassembly **406** includes a ball **420**, a ball axle **422**, and a leg **424**. The ball **420** has a bore and is supported on the ball axle **422** with support bearings **426**. In one embodiment, the support bearings **426** are positioned in on the ball axle **422** with at least one spacer **428**. The leg **424** can be pressed onto an end of the ball axle **422**. Each end of the ball axle **422** is coupled to a leg **424**. In one embodiment, the leg **424** includes a sliding interface guide **421**, a shift cam engagement surface **423**, and a bearing support extension **425** surrounding a ball axle bore **427**. In some embodiments, the leg **424** can include a press relief hole **429** arranged concentric with the ball axle bore **427**. The sliding interface guide **421** can have a curved profile when viewed in the plane of the page of FIG. **48**. The sliding interface guide **421** is preferably substantially conformal with the guide support slots **412** so that the forces transferred from the leg **424** to the stator support member **402** are distributed over a large surface area of contact between the leg **424** and the stator support member **402**. This arrangement minimizes stress and wear on the contacting components.

Turning to FIGS. **49-50**, in one embodiment a shift cam **430** includes a number of leg contact surfaces **432**. The leg contact surfaces **432** can have a profile that is substantially convex when viewed in the plane of the page in FIG. **50**, and the profile can be substantially flat when viewed in the plane of the cross-section in FIG. **49**. The substantially flat profile facilitates a line contact between the leg **424** and the shift cam **430**. The line contact is preferable for minimizing wear and stress on the leg **424** and the shift cam **430**. In one embodiment, the shift cam **430** includes a number of alignment extensions **436**. The alignment extensions **436** are arranged on each side of each of the leg contact surfaces **432**, so that the leg **424** is substantially flanked by the alignment extensions **436** when assembled. In some embodiments, the shift cam **430** is provided with a bearing race **438** that is adapted to support a bearing for facilitating the coupling of the shift cam **430** to, for example, the idler assembly **109**. The shift cam **430** can also be provided with a shift nut engagement shoulder **440** that extends axially from the leg contact surfaces **432**. The shift nut engagement shoulder **440** surrounds a hollow bore **442**, which is configured to provide

clearance to the main axle 112, for example. The shift nut engagement shoulder 440 can couple to the shift nut 119, for example.

Passing now to FIGS. 51-56, in one embodiment a carrier assembly 500 can include a stator support member 502 5 coupled to a stator interfacial member 504. A stator torque reaction insert 506 can be coupled to the inner bore of the stator support member 502. The stator support member 502 can be provided with a number of torque reaction shoulders 507 (see FIG. 53, for example). The torque reaction shoulders 507 are configured to engage a number of mating torque reaction shoulders 508 provided on the stator torque reaction insert 506. In one embodiment, the stator torque reaction insert 506 includes a piloting flange 510 that extends radially from the torque reaction shoulders 508. The piloting flange 510 is adapted to align and couple to the inner diameter of the stator interfacial member 504. In some embodiments, the piloting flange 510 can include a number of holes (not shown) configured to receive fasteners, such as rivets, to facilitate the coupling of the piloting flange 510 to the stator support member 502. In other embodiments, the piloting flange 510 can be welded to the stator support member 502. In yet other embodiments, the piloting flange 510 can be configured to couple to the stator support member 502 via the stator interfacial member 504. For example, the stator interfacial member 504 can be made of plastic, which can be formed around the piloting flange 510 and the stator support member 502 in such a way as to facilitate the coupling of the piloting flange 510 to the stator support member 502.

Referring now specifically to FIGS. 53-54, the stator support member 502 can be a generally bowl shaped body having a bottom face 512. In one embodiment, the torque reaction shoulders 507 are formed on the bottom face 512. It should be readily apparent that the torque reaction shoulders 507 can be, in some embodiments, knurls or splines (not shown) configured to facilitate the coupling of the stator support member 502 to, for example, the main axle 112. A number of interlock cavities 514 can be provided on the bottom face 512. The interlock cavities 514 are adapted to couple to mating features located on the stator interfacial member 504. In the embodiment shown in FIGS. 53 and 54, the interlock cavities 514 are arranged in groups of four interlock cavities 514 per planet assembly 108, and the groups of interlock cavities 514 are distributed angularly about the torque reaction shoulders 507 on the bottom face BF. In one embodiment, each of the interlock cavities 514 has a corresponding tab 515 that extends from the interlock cavity 514 towards the interior of the bowl shaped body. The tabs 515 are configured to align and couple to mating features of the stator interfacial member 504. The stator support member 502 can also be provided with a number of ball clearance cavities 516 formed on the outer periphery of the bowl shaped body. The number of ball clearance cavities 516 preferably, though not necessarily, corresponds to the number of planet subassemblies 108 provided in, for example, the CVT 100. The stator support member 502 can include a fastening flange 518 located on the outer periphery of the bowl-shaped body. The fastening flange 518 can have a number of fastening holes 519. In one embodiment, the stator support member 502 can be a stamped sheet metal component. Once assembled, carrier 500 can include two stator support members 502 coupled together at the respective fastening flange 518 with common screw fasteners or rivets.

Referring to now specifically to FIGS. 55 and 56, the stator interfacial member 504 can include a disk shaped body having an inner bore. In one embodiment, the disc

shaped body has a number of guide slots 520 arranged angularly about the inner bore so that each of the guide slots 520 extends radially from the inner bore to an outer periphery of the disc shaped body. In some embodiments, the guide slots 520 have a conformal profile configured to couple to the legs 240 of the planet assembly 108. The stator interfacial member 504 can include a number of interlock tabs 522 configured to mate with the interlock cavities 514 and tabs 515 of the stator support member 502. In one embodiment, interlock tabs 522 can be arranged in groups of four interlock tabs 522 located at each guide slot 520. For example, each of the guide slots 520 can be flanked on each side by at least two interlock tabs 522. In some embodiments, at least one interlock tab 522 is arranged on either side of the guide slot 520. The stator interfacial member 504 can be provided with a number of leg clearance slots 524. The leg clearance slots 524 are generally formed on the inner circumference of the disk shaped body and the leg clearance slots 524 are substantially aligned angularly with the guide slots 520. In some embodiments, the stator interfacial member 504 can include a number of stator support member extensions 526 that are configured to engage the stator support member 502. The stator support member extensions 526 are preferably substantially aligned with, and extend from, the guide slots 520.

Referring now to FIGS. 57-62, in one embodiment a carrier assembly 600 can include a first stator support member 602 coupled to a second stator support member 603 via a number of stator spacers 604. The carrier assembly 600 can be adapted to cooperate with planet subassemblies 406. The first stator support member 602 can be a generally disk-shaped body having a central bore 608. The central bore 608 is configured to couple to, for example, the main axle 112. In one embodiment, the main axle 112 is welded to the first stator support member 602, for example. In other embodiments, the main axle 112 can be coupled to the first stator support member 602 via torque reaction shoulders that are substantially similar to torque reaction shoulders 210 (see FIG. 21, for example) and the torque reaction shoulders 318 (see FIG. 35, for example).

Still referring to FIGS. 57-62, the second stator support member 603 can be a generally disc-shaped body having a central bore 610. The central bore 610 is configured to provide clearance between the disc-shaped body and the main axle 112. In one embodiment, the radial clearance between the disc-shaped body and the main axle 112 is large enough to allow the idler assembly 109, for example, to be removed from the main axle 112 while the second stator support member 603 and the first stator support member 602 remain assembled. The radial clearance between the second stator support member 603 and the main axle 112 facilitates, among other things, angular alignment between the first and second stator support members 602 and 603 that is independent from the alignment of the main axle 112 to the second stator support member 603, thereby simplifying assembly of the carrier 600 and the main axle 112.

In one embodiment, the first stator support member 602 is provided with a number of support extensions 612 and a number of guide slots 614 interposed between the support extensions 612. The guide slots 614 are arranged angularly about, and extend radially from, the central bore 608. The planet assemblies 406 are adapted to slide in the guide slots 614. The support extensions 612 substantially define the perimeter structure for a number of stator spacer cavities 616. Each of the stator spacer cavities 616 is adapted to receive an end of the stator spacer 604. The end of the stator spacer 604 can attach to the stator spacer cavity 616 with

common screw fasteners, press fit, or other suitable fastening means. Similarly, the second stator support member **603** can be provided with the support extensions **612**. The support extensions **612** form sides for the guide slots **614**. The guide slots **614** are arranged angularly about, and extend radially from, the central bore **610**. The support extensions **612** substantially define the perimeter structure for a number of stator spacer cavities **616**.

In one embodiment, the stator spacer **604** includes ends **620** and **622** connected by a clearance neck **624**. The clearance neck **624** is preferably configured to maximize torsional stiffness of the stator spacers **604** while maintaining adequate clearance between the planet subassemblies **406**. In one embodiment, the clearance neck **624** has a substantially diamond shaped cross-section **626** at the midpoint of the body while the ends **620** and **622** are substantially triangular in cross-section, when viewed in the plane of the page of FIG. **62**.

Turning to FIG. **63**, in one embodiment the main axle **112** can include a substantially elongated body with a shift nut clearance slot **1120** arranged in a middle portion of the elongated body. The shift nut clearance slot **1120** is an opening in the elongated body that is aligned axially in the elongated body. The shift nut clearance slot **1120** has a first axial end and a second axial end. A number of torque reaction shoulders **1122** can be formed in proximity to each axial end. In one embodiment, six torque reaction shoulders **1122** are formed at the first axial end, and six torque reaction shoulders **1122** are formed at the second axial end. In some embodiments, only four torque reaction shoulders **1122** are formed at each axial end. In other embodiments, as few as one torque reaction shoulder **1122**. In yet other embodiments, the torque reaction shoulders **1122** can be a knurled surface. The torque reaction shoulders **1122** are configured to couple to, for example, the carrier assembly **101**. The main axle **112** can also include frame support flats **1124** on each end of the elongated body. The frame support flats **1124** are configured to couple to, for example, dropouts **3** (see FIG. **1**, for example).

Referring to FIG. **64** now, a shift nut **119** can include a threaded bore **1190** configured to couple to the shift rod **120**, for example. The shift nut **119** can include at least two shift cam engagement faces **1192** that extend from the threaded bore **1190**. The shift cam engagement faces **1192** can be substantially flat surfaces that are configured to couple to, for example, the shift cam **430**. In one embodiment, the shift nut **119** can be provided with a bore **1194** that intersects the threaded bore **1190**. The bore **1194** can, among other things, reduce the weight of the shift nut **119**.

Passing now to FIGS. **65A-66**, in one embodiment an idler assembly **700** includes an idler **702**, a first and a second shift cam **704** and **706** operably coupled to the idler with a bearing **705**. In some embodiments, the bearing **705** has a flexible cage **707** that can be manipulated during assembly. In other embodiments, the bearing **705** can consist of two bearings that have independent cages. The idler assembly **700** can be coupled to, for example, the shift rod **120** with a first and a second shift nut **708A** and **708B**. The shift nuts **708** can be arranged in the shift nut clearance slot **1120** of the main axle **112** and couple to shift nut engagement shoulders **710** formed on the shift cams **704** and **706**. The shift nut **708** can be provided with a threaded bore **712** adapted to couple to a threaded portion of the shift rod **720**. The shift nut **708** can be configured to axially translate with a rotation of the shift rod **120**, and thereby axially translating the idler assembly **700**. In one embodiment, the shift nut **708** is provided with a shift cam engagement shoulder **714**

formed on a first end. The shift cam engagement shoulder **714** is configured to mate with the shift nut engagement shoulders **710**. The shift cam engagement shoulder **714** extends radially in one direction from the threaded bore **712** and is aligned axially with the first end of the body of the shift nut **708**. In some embodiments, the shift nut **708** is provided with a set of flats **716**.

During assembly, the first and the second shift nuts **708** are placed in the shift nut clearance slot **1120** and positioned to allow the idler assembly **700** to be placed onto the main axle **112**. In some embodiments, the first and the second shift nuts **708** are one integral component. Once the idler assembly **700** is placed onto the main axle **112**, the shift rod **120** is threaded into the first shift nut **708A**, which aligns the threaded bore **712** with the longitudinal axis of the transmission and facilitates the engagement of the shift cam engagement shoulder **714** with the shift nut engagement shoulder **710**. The second shift nut **708B** is threaded onto the shift rod **120** and couples to the second shift cam **706**. Once assembled, the two shift nuts **708** axially guide the idler assembly **700**. The shift nuts **708** allow the idler assembly **700** to be removed from the main axle **112** without disassembly of the idler assembly **700**.

Turning to FIGS. **67-69**, one embodiment of the hub shell **102** will be described. The hub shell **102** can include a first spoke flange **6700A** and a second spoke flange **6700B** arranged on the outer periphery of the hub shell **102**. The first and the second spoke flanges **6700** are provided with a number of spoke fastening holes **6702** to facilitate the coupling of the CVT **100** to a wheel of a bicycle, for example. The hub shell **102** can include a number of brake adapter splines **6704** formed on an exterior surface of the hub shell **102**. The brake adapter splines **6704** are encircled with a set of threads **6706**. The threads **6706** are configured to mate with a brake adapter ring **7300** (see FIG. **3**, for example). A second set of threads **6708** are provided on an end opposite the brake adapter splines **6704**. The second set of threads **6708** are configured to mate with the hub shell cover **104**. The hub shell **102** can be provided with an interior face **6710** having a central bore concentric with the brake adapter splines **6704**. The central bore can include a seal bore **6712**, a bearing bore **6714**, and a snap ring groove **6716**. Preferably, the seal bore **6712** is positioned axially outward of the bearing bore **6714**. The seal bore **6712** is configured to support, for example, an axle seal. The bearing bore **6714** is configured to support, for example, a bearing. The interior face **6710** can be provided with a set of splines **6718** configured to mate with the output cam ring **149**, for example.

Referring to FIGS. **70-72** now, one embodiment of the hub cover **104** includes a disc-shaped body **7000** having a central bore **7002**, an exterior face **7004**, and an interior face **7006**. The interior face **7006** is preferably arranged facing the interior of the CVT **100**, and the exterior face **7004** is preferably arranged facing the exterior of the CVT **100**. In some embodiments, the hub cover **104** is arranged on the input side of the CVT **100**. The hub cover **104** includes a threaded outer periphery **7008** configured to mate with the hub shell **102**. The central bore **7002** can be provided with a bearing support surface **7010** and a seal support bore **7012**. The bearing support surface **7010** and the seal support bore **7012** are coaxial with the main axle **112**. The interior face **7006** can be provided with a thrust reaction surface **7014** configured to support, for example, a thrust bearing of the CVT **100**. The hub cover **104** can be provided with a set of stiffening ribs **7016** extending radially from the central bore **7002** on the interior face **7006**. In some embodiments, the

hub cover **104** includes a set of tool engagement splines **7018** arranged on the exterior face **7004** and surrounding the central bore **7002**. The tool engagement splines **7018** facilitate, among other things, the coupling of the hub cover **104** to the hub shell **102**.

Passing to FIGS. **73-74**, in one embodiment a brake adapter ring **7300** can be a generally annular ring having a threaded perimeter **7302**. A first exterior face of the annular ring can include a number of tool engagement holes **7304** configured to facilitate the coupling of the brake adapter ring **7300** to, for example, the hub shell **102**. The brake adapter ring **7300** can be provided with a locking chamfer **7306** formed on the inner circumference of the annular ring. In some embodiments, the diameter of the annular ring is in the range of 1.25 to 3.25 inches.

Referring to FIGS. **75-76** now, in one embodiment a disc brake adapter **7500** includes a brake alignment surface **7502** and a number of torque reaction splines **7504**. The brake alignment surface **7502** is substantially configured to mate with a standard disc brake for a bicycle. The torque reaction splines **7504** are configured to mate with the brake adapter splines **6704** of the hub shell **102** (see FIG. **67**, for example). The disc brake adapter **7500** can be provided with a seal support surface **7506** that is configured to couple to a seal of the CVT **100**. A number of brake fastening holes **7508** can be provided on the disc brake adapter **7500**. The disc brake adapter **7500** can include a locking chamfer **7510** configured to engage the brake adapter ring **7300**. The engagement of the locking chamfer **7510** with the locking chamfer **7306** provides a rigid coupling between the disc brake adapter **7500** and the hub shell **102**.

Referring now to FIGS. **77-79**, in one embodiment a roller brake adapter **7700** can include a number of torque reaction splines **7702** that are substantially similar to torque reaction splines **7504**, and are configured to couple to the brake adapter splines **6704** of the hub shell **102**. The roller brake adapter **7700** can be provided with a splined extension **7704** that is configured to couple to a standard roller brake of a bicycle. The roller brake adapter **7700** can include a locking chamfer **7706** that is substantially similar to the locking chamfer **7510**, and is adapted to engage the locking chamfer **7306** of the brake adapter ring **7300**. The roller brake adapter **7700** can also be provided with a seal support surface **7708** that is configured to couple to a seal of the CVT **100**. Once assembled, the roller brake adapter **7700** can be coupled to, for example, the CVT **100** at substantially the same location on the hub shell **102** as the disc brake adapter **7500**. The engagement of the locking chamfer **7706** with the locking chamfer **7306** provides a rigid coupling between the roller brake adapter **7700** and the hub shell **102**. In one embodiment, the brake adapter kit **106** can include the brake adapter ring **7300** and the disc brake adapter **7500**. In other embodiments, the brake adapter kit **106** can include the brake adapter ring **7300** and the roller brake adapter **7700**.

Turning now to FIGS. **80** and **81**, in one embodiment a carrier assembly **800** can include a first stator support member **802A** coupled with a number of stator spacers **804** to a second stator support member **802B**. The stator spacers **804** can be arranged angularly around the perimeter of the stator support members **802**. In one embodiment, the stator support members **802** and the stator spacers **804** are substantially similar in function to the stator subassemblies **200** and the stator spacers **202**. The carrier assembly **800** supports and facilitates a tilting of the rotational axis of a number of planet subassemblies **806**. In some embodiments, the stator support member **802** can be coupled to a stator torque reaction insert **807** that is substantially similar to the

stator torque reaction insert **204**, for example. In other embodiments, the stator support member **802** is coupled directly to the main axle **112**.

Turning to FIGS. **82** and **83**, and still referring to FIGS. **80** and **81**, in one embodiment, the planet subassembly **806** includes a first stator interfacial cap **808A** coupled to a first leg **810A**. The planet subassembly **806** includes a ball **812** configured to rotate about a planet axle **814**. In one embodiment, the planet axle **814** is supported in the first leg **810A** and in a second leg **810B**. The second leg **810B** can be coupled to a second stator interfacial cap **808B**. Typically, each of the stator interfacial caps **808** are provided with a planet axle relief **816** that is configured to provide clearance between the planet axle **814** and the stator interfacial cap **808**. The stator interfacial cap **808** preferably includes a sliding interface surface **817** that is configured to contact the stator support member **802**. In one embodiment, the sliding interface surface **817** has a curved profile when viewed in the plane of the page of FIG. **81**. The sliding interface surface **817** is substantially similar in certain functional aspects to the sliding interface guides **421**. In some embodiments, the stator interfacial cap **808** includes sides **818** that extend from the sliding interface surface **817**. The sides **818** can be arranged to substantially flank the leg **810**. In some embodiments, the stator interfacial caps **808** are made of a plastic or other low-friction material. The legs **810** can be made of steel, for example. The stator interfacial cap **808** can be formed or assembled onto the legs **810** via a plastic molding process, for example. Once assembled, the stator interfacial cap **808A** and the leg **810** can be substantially similar in certain functional aspects to the leg **244**, **244A**, or **424**, for example. In some embodiments, the leg **810** can be adapted to couple to the shift cam **260** or **430**, for example.

It should be noted that the description above has provided dimensions for certain components or subassemblies. The mentioned dimensions, or ranges of dimensions, are provided in order to comply as best as possible with certain legal requirements, such as best mode. However, the scope of the inventions described herein are to be determined solely by the language of the claims, and consequently, none of the mentioned dimensions is to be considered limiting on the inventive embodiments, except in so far as anyone claim makes a specified dimension, or range of thereof, a feature of the claim.

The foregoing description details certain embodiments of the invention. It will be appreciated, however, that no matter how detailed the foregoing appears in text, the invention can be practiced in many ways. As is also stated above, it should be noted that the use of particular terminology when describing certain features or aspects of the invention should not be taken to imply that the terminology is being re-defined herein to be restricted to including any specific characteristics of the features or aspects of the invention with which that terminology is associated.

What we claim is:

1. A stator assembly for a continuously variable transmission, the stator assembly comprising:
 - a stator torque reaction insert having a plurality of torque reaction shoulders;
 - a stator support member coupled to the stator torque reaction insert, the stator support member extending radially outward from the stator torque reaction insert, the stator support member having a first face and a second face; and
 - a stator interfacial member coupled to the stator support member, the stator interfacial member substantially

27

supported by the first face of the stator support member, the stator interfacial member having a plurality of radial grooves.

2. The stator assembly of claim 1, wherein the stator support member comprises a plurality of interlocking holes. 5

3. The stator assembly of claim 2, wherein the stator interfacial member comprises a plurality of interlocking tabs configured to couple to the plurality of interlocking holes.

4. A stator support member for a continuously variable transmission (CVT), the stator support member comprising: 10
 a substantially disc-shaped body having an inner bore, a first face and a second face;
 a plurality of spacer support extensions arranged angularly on the first face;
 a plurality of guide support slots, each guide support slot 15
 arranged substantially between each of the spacer support extensions;
 a plurality of interlocking holes formed in each of the guide support slots; and
 a plurality of capture extensions formed on the outer 20
 periphery of the disc-shaped body.

5. The stator support member of claim 4, further comprising a piloting shoulder formed in proximity to the inner bore on the first face.

28

6. The stator support member of claim 4, further comprising a plurality of structural ribs formed on the second face.

7. The stator support member of claim 4, wherein each of the capture extensions is substantially aligned with one of the spacer support extensions.

8. The stator support member of claim 4, wherein the inner bore has a hexagonal shape.

9. A stator interfacial member for a continuously variable transmission, the stator interfacial member comprising: 10
 a substantially disc-shaped body having a central bore, a first face, and a second face;
 a plurality of sliding guide slots extending radially from the central bore, the guide slots arranged substantially 15
 on the first face;
 a plurality of interlocking tabs extending from the second face;
 a capture ring formed around the outer circumference of the disc-shaped body; and
 a plurality of capture cavities formed on the capture ring.

10. The stator interfacial member of claim 9, wherein the capture ring is aligned substantially on the second face.

* * * * *