



US009529749B2

(12) **United States Patent**
Hollis

(10) **Patent No.:** **US 9,529,749 B2**
(45) **Date of Patent:** **Dec. 27, 2016**

(54) **DATA BUS INVERSION (DBI) ENCODING
BASED ON THE SPEED OF OPERATION**

(71) Applicant: **QUALCOMM Incorporated**, San
Diego, CA (US)

(72) Inventor: **Timothy Mowry Hollis**, Poway, CA
(US)

(73) Assignee: **QUALCOMM Incorporated**, San
Diego, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 355 days.

(21) Appl. No.: **14/202,783**

(22) Filed: **Mar. 10, 2014**

(65) **Prior Publication Data**

US 2014/0281075 A1 Sep. 18, 2014

Related U.S. Application Data

(60) Provisional application No. 61/791,865, filed on Mar.
15, 2013.

(51) **Int. Cl.**
G06F 13/20 (2006.01)
G06F 13/28 (2006.01)
G06F 13/42 (2006.01)

(52) **U.S. Cl.**
CPC **G06F 13/287** (2013.01); **G06F 13/4221**
(2013.01)

(58) **Field of Classification Search**

CPC G06F 13/287; G06F 13/4221
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,280,412 B2	10/2007	Jang et al.
7,522,073 B1	4/2009	Kao
7,616,133 B2	11/2009	Hollis
8,094,045 B2	1/2012	Hollis
8,451,913 B2	5/2013	Oh et al.
8,510,490 B2	8/2013	Abbasfar
2009/0193319 A1	7/2009	Shen et al.
2011/0222623 A1	9/2011	Hollis
2013/0159818 A1	6/2013	O'Connor et al.

OTHER PUBLICATIONS

International Search Report and Written Opinion—PCT/US2014/
023508—ISA/EPO—Jun. 6, 2014.

Hollis T.M., et al., "Data Bus Inversion in High-Speed Memory
Applications," IEEE Transactions on Circuits and Systems—II:
Express Briefs, Apr. 2009, vol. 56 (4), pp. 300-304.


Primary Examiner — Glenn A Auve

(74) *Attorney, Agent, or Firm* — Austin Rapp & Hardman

(57) **ABSTRACT**

A method for data transmission is described. A signaling
speed of operation of an electronic device is determined. A
data bus inversion algorithm is selected based on the sig-
naling speed of operation. The selected data bus inversion
algorithm is used to encode data. The encoded data and a
data bus inversion flag are sent to a receiver over a trans-
mission medium.

30 Claims, 8 Drawing Sheets






FIG. 1




FIG. 2

300 ↗




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8

DATA BUS INVERSION (DBI) ENCODING BASED ON THE SPEED OF OPERATION

RELATED APPLICATION

This application is related to and claims priority from U.S. Provisional Patent Application Ser. No. 61/791,865, filed Mar. 15, 2013, for "FREQUENCY-DEPENDENT BUS INVERSION ENCODING."

TECHNICAL FIELD

The present disclosure relates generally to electronic communications. More specifically, the present disclosure relates to systems and methods for data bus inversion (DBI) encoding based on the speed of operation.

BACKGROUND

To increase signal and power integrity and reduce power consumption, data bus inversion (DBI) encoding may be employed. DBI encoding may be particularly useful for transferring large amounts of data quickly. For example, DBI encoding may be employed to facilitate high-speed data transfers between a central processing unit (CPU) and a dynamic random access memory (DRAM) device in a package-on-package (POP), a multi-chip package (MCP) or a variety of other memory interface configurations. DBI encoding may be particularly useful in mobile memory applications, such as Low Power Double Data Rate 4 (LPDDR4).

However, additional benefits may be realized by switching between different DBI encoding algorithms, based on the circumstances of the data. The different DBI encoding algorithms may provide a power reduction when used properly and a power penalty when used improperly. Benefits may be realized by selecting the DBI encoding algorithm based on signaling speed.

SUMMARY

A method for data transmission is described. A signaling speed of operation of an electronic device is determined. A data bus inversion algorithm is selected based on the signaling speed of operation. The selected data bus inversion algorithm is used to encode data. The encoded data and a data bus inversion flag are sent to a receiver over a transmission line.

The selected data bus inversion algorithm may be one of a DBI-AC algorithm and a DBI-DC algorithm. The selected data bus inversion algorithm may be DBI-AC when the signaling speed of operation is a low-speed mode. The selected data bus inversion algorithm may be DBI-DC when the signaling speed of operation is a high-speed mode. The signaling speed of operation may be communicated to an encoder by a dedicated signal. The dedicated signal may be provided through a command address bus or using an existing data line.

The signaling speed of operation may be autonomously determined by an encoder. The selected data bus inversion algorithm may be used to encode data using a topology that does not include feedback or using a topology that includes feedback. Data bus inversion algorithm encoding may be disabled autonomously based on a dynamic disable signal.

A termination control signal may be generated based on the selected data bus inversion algorithm. The termination control signal may be sent to the receiver. The method may

be performed by a data bus inversion encoder that includes an algorithm selection multiplexer, an XOR gate that receives parallel unencoded data of an upcoming burst and parallel data of a previous burst, an inverter, a majority detection circuit and a true/complement multiplexer. The data bus inversion encoder may also include a frequency detection circuit. The selected data bus inversion algorithm may be based on a relationship between a physical layer clock frequency and a reference frequency.

An apparatus for data transmission is also described. The apparatus includes a processor, memory in electronic communication with the processor and instructions stored in the memory. The instructions are executable by the processor to determine a signaling speed of operation of an electronic device. The instructions are also executable by the processor to select a data bus inversion algorithm based on the signaling speed of operation. The instructions are further executable by the processor to use the selected data bus inversion algorithm to encode data. The instructions are also executable to send the encoded data and a data bus inversion flag to a receiver over a transmission line.

An electronic device is described. The electronic device includes means for determining a signaling speed of operation of the electronic device. The electronic device also includes means for selecting a data bus inversion algorithm based on the signaling speed of operation. The electronic device further includes means for using the selected data bus inversion algorithm to encode data. The electronic device also includes means for sending the encoded data and a data bus inversion flag to a receiver over a transmission line.

A computer-program product for data transmission is also described. The computer-program product includes a non-transitory computer-readable medium having instructions thereon. The instructions include code for causing an electronic device to determine a signaling speed of operation of the electronic device. The instructions also include code for causing the electronic device to select a data bus inversion algorithm based on the signaling speed of operation. The instructions further include code for causing the electronic device to use the selected data bus inversion algorithm to encode data. The instructions also include code for causing the electronic device to send the encoded data and a data bus inversion flag to a receiver over a transmission line.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram illustrating data bus inversion (DBI) encoding/decoding circuitry;

FIG. 2 is a block diagram illustrating data bus inversion (DBI) encoding/decoding;

FIG. 3 is a flow diagram of a method for encoding data using a DBI algorithm that depends on the signaling speed of operation;

FIG. 4 is a block diagram illustrating high level DBI algorithm control;

FIG. 5 is a block diagram illustrating one example of DBI selection circuitry in a DBI encoder;

FIG. 6 is a block diagram illustrating another example of DBI selection circuitry in a DBI encoder;

FIG. 7 is a block diagram illustrating a channel configuration module that includes a frequency detection circuit; and

FIG. 8 shows part of a hardware implementation of an electronic device that uses speed-dependent data bus inversion (DBI) encoding.

DETAILED DESCRIPTION

FIG. 1 is a block diagram of an electronic device 102 for use in the present systems and methods. The electronic

device **102** may be a base station, a wireless communication device, or other device that uses electricity. The electronic device **102** may include a transmission line **110** (also referred to as a transmission medium) used to transmit data between a transmitter **104** and a receiver **112**. The transmitter **104** and the receiver **112** may also be located on different electronic devices (not shown). The data transmitted over the transmission line **110** may be encoded to reduce signaling power in the single-ended interface. For example, the data transmitted over the transmission line **110** may be encoded using data bus inversion (DBI) or bus-invert coding. DBI encoding is a technique where data bits may be inverted prior to transmission to maximize or minimize certain signaling characteristics. DBI encoding may include bit inversion encoding for any parallel interface, including commands, address information, etc. By adjusting the DBI algorithm used to encode data based on the speed of operation (e.g., the data rates used), benefits such as power savings or sufficient signal integrity may be achieved.

The transmitter **104** may include a DBI encoder **106**. The DBI encoder **106** may encode data using a DBI algorithm. The encoded data may then be transmitted to the receiver **112** via the transmission line **110**. The receiver **112** may use a DBI decoder **114** to decode the encoded data. In one configuration, the transmitter **104** and the receiver **112** may be located on a single chip. In another configuration, the transmitter **104** and the receiver **112** may each be located on different chips within an electronic device **102**.

The electronic device **102** may include a mode controller **118**. The mode controller **118** may be located on the same chip as the transmitter **104** and/or the receiver **112** or on a different chip. The mode controller **118** may instruct the transmitter **104** on which DBI algorithm **116** to use for encoding data on the transmission line **110**. The mode controller **118** may communicate with a channel configuration module **108** on the transmitter **104**. In one configuration, the channel configuration module **108** may receive instructions from the mode controller **118** to enable the proper encoding algorithm. In another configuration, the channel configuration module **108** may be capable of detecting the mode of operation and setting the proper encoding algorithm without external instruction from the mode controller **118**. The channel configuration module **108** is discussed in additional detail below in relation to FIG. 4.

FIG. 2 is a block diagram illustrating data bus inversion (DBI) encoding/decoding. As discussed above, DBI encoding is a technique wherein data bits may be inverted prior to transmission to maximize or minimize certain signaling characteristics. DBI encoding may include bit inversion encoding for any parallel interface, including commands, address information, etc. For example, DBI encoding may be used to invert data bits transferred between a transmitter **204** and a receiver **212**. DBI encoding is often used to reduce power consumption and to improve signal and power integrity. In some configurations, the transmitter **204** and the receiver **212** may both be located on the same electronic device **102**. The transmitter **204** may transfer large amounts of data to the receiver **212** over a small channel length (e.g., less than a few millimeters) or over longer lengths (e.g., several inches). The channel **210** may be a package/printed circuit board (PCB) transmission line **110**. In one configuration, the channel may be a wireless channel **210**. As an example, the channel **210** may be a coaxial cable, a silicon interposer trace or any other wireline interconnect technology.

The transmitter **204** may include a DBI encoder **206**. The DBI encoder **206** may apply DBI encoding to signals

transmitted from the transmitter **204** to the receiver **212**. Examples of DBI encoding algorithms include DBI-AC and DBI-DC. DBI-AC is an algorithm designed to limit the number of simultaneously transitioning data bits across the width of the interface. DBI-DC is an algorithm designed to limit the number of simultaneous data bits at one of the two binary levels.

The choice of DBI algorithm **216** may depend on the signaling environment. It may be advantageous to have the ability to enable either a DBI-AC algorithm or a DBI-DC algorithm. If the improper DBI algorithm **216** is chosen, a performance penalty may occur. The DBI algorithm **216** may be selected by a mode controller **218** (also referred to as a core). The mode controller **218** may instruct the DBI encoder **206** on whether to use DBI-AC or DBI-DC as the selected DBI algorithm **216**.

The mode controller **218** may also instruct the receiver **212** on whether to use an asymmetric load termination **228** (via a termination control signal **226**). The asymmetric load termination **228** may be used by the receiver **212** to limit reflections on the transmission line **110**. Applying DBI-DC to an asymmetrically-terminated channel may result in an 18% power reduction (assuming 1-DBI flag per byte). However, if an unterminated channel is used with DBI-DC, a 4% power penalty may occur. Conversely, applying DBI-AC to an unterminated channel may result in a 16% power reduction. However, if an asymmetrically-terminated channel is used with DBI-AC, a 4% power penalty may occur. Thus, in most cases, the termination control signal **226** may be coordinated with the DBI algorithm **216** used. There are configurations where the channel **210** is terminated through a symmetric connection to both the high and low voltage rails. In such instances, the DBI-AC algorithm may provide the best performance in terms of power and noise reduction.

In one configuration, the mode controller **218** may have the authority to override a channel configuration module **108** within the transmitter **204**. For example, the mode controller **218** may have additional information such as knowledge that the link will be rapidly switching and it is preferred to not have to wait for the load termination **228** to enable/disable. The mode controller **218** may also know that the data pattern to be sent is not stressful from a signal integrity perspective, so that even though the data is being sent at a higher rate, the load termination **228** may not be needed (and thus the mode controller **218** may override termination decisions made by the channel configuration module **108**).

It is important to note, however, that while there is a clear relationship between the DBI algorithm **216**, the load termination **228** and the signaling power, there may still be configurations in which DBI-AC is used in conjunction with a terminated channel and configurations in which DBI-DC is used in conjunction with an unterminated channel. For example, if the signal integrity of a particular channel environment is dominated by crosstalk, then an encoding algorithm which limits the number of transitions may be a better choice, in spite of the corresponding power penalty.

The transmitter **204** may transmit DBI algorithm encoded data **222** and a DBI flag **224** over the channel **210** to the receiver **212** using a driver **220**. The DBI flag **224** may be transmitted over the channel **210** in a variety of ways. For example, the DBI flag **224** may be driven between the transmitter **204** and receiver **212** using the same input/output circuitry as the other data bits. As another example, the DBI flags **224** corresponding to several sequential cycles may be accumulated and sent in parallel before or after the corresponding data burst, thereby not requiring any additional circuitry or substrate routing (only additional transmit

5

cycles). The termination control signal **226** may also be transmitted to the receiver **212** via the channel **210**. The receiver **212** may include a DBI decoder **214** that decodes the DBI algorithm encoded data **222** using the DBI flag **224**. The DBI flag **224** may indicate the DBI algorithm **216** used for encoding (since the DBI algorithm **216** used may vary from burst to burst), but this is not always necessary. In order for the DBI flag **224** to indicate the DBI algorithm **216** being used, the transmitter **204** needs to send an additional one or two bits of information to the receiver **212** (either in parallel with the data burst, or before/after the burst during an additional transmit cycle).

The incoming encoded data may be provided to a true/complement multiplexer along with the complement values (i.e., the inverted parallel encoded data). The true/complement multiplexer may be controlled by the DBI flag **224**, thereby de-inverting any inverted data. The decoding process may be independent of the encoding DBI algorithm **216**, as long as the DBI flag **224** is consistent between the DBI algorithms **216** used. It may be advantageous for the polarity of the DBI flag **224** to differ between DBI algorithms **216**. The DBI decoder **214** may output the parallel unencoded data **230**.

One example where it may be advantageous to have the ability to enable either a DBI-AC algorithm or a DBI-DC algorithm is low power double data rate (LPDDR4) memory. In LPDDR4 memory, it is anticipated that there will be two primary modes of signaling operation: high-speed and low-speed. High-speed operation is expected to run at data rates above 3.2 gigabits per second (Gb/s). As a result, the chip-to-chip transmission line **110** may need to be terminated with a load matched to the channel characteristic impedance in order to guarantee sufficient signal integrity. In other words, in high-speed mode, the use of DBI-DC (with a terminated channel) may provide substantive benefits.

Low-speed operation is expected to run at data rates near 0.2 Gb/s. The lower speed allows for the disabling of the matched channel termination (i.e., with a non-terminated channel), which saves considerable power. As a result, the application of the DBI-AC algorithm in low-speed mode may provide substantive benefits.

The mode controller **218** may initiate a change in the transmitter **204** to receiver **212** operation (e.g., speed, termination). Therefore, the mode controller **218** may also communicate directly with the DBI encoder **206** to dynamically select the DBI algorithm **216**. The mode controller **218** may also communicate with memory on the receiver **212** to enable/disable the load termination **228** by means of the command bus or some other signal (e.g., the termination control signal **226**). Some receivers **212** may store the load termination **228** in memory while other receivers **212** will not include memory for storing the load termination **228**.

FIG. 3 is a flow diagram of a method **300** for encoding data using a DBI algorithm **116** that depends on the signaling speed of operation. The method **300** may be performed by an electronic device **102**. In one configuration, the method **300** may be performed by a DBI encoder **106** on the electronic device **102** (e.g., within a transmitter **104** on the electronic device **102**). The electronic device **102** may determine **302** a signaling speed of operation. For example, the electronic device **102** may determine whether the electronic device **102** is using a high-speed operation or a low-speed operation.

In one configuration, the signaling speed of operation may be communicated to the DBI encoder **106** by a dedicated signal. The dedicated signal may be provided via a com-

6

mand address bus or an existing data line. The DBI encoder **106** may also autonomously determine **302** the signaling speed of operation.

The electronic device **102** may select **304** a DBI algorithm **116** based on the signaling speed of operation. As an example, if the signaling speed of operation is high-speed, the electronic device **102** may select **304** DBI-DC as the DBI algorithm **116**. If the signaling speed of operation is low-speed, the electronic device **102** may select **304** DBI-AC as the DBI algorithm **116**. The electronic device **102** may use **306** the selected DBI algorithm **116** to encode data. The electronic device **102** may also determine **308** a termination control signal **226** based on the selected DBI algorithm **116**. For example, the termination control signal **226** may indicate that a terminated channel is to be used if the DBI-DC algorithm is selected and an unterminated channel is to be used if the DBI-AC algorithm is selected. The electronic device **102** may send **310** the DBI algorithm encoded data **222**, the termination control signal **226** and a DBI flag **224** to a receiver **212**. As discussed above, the receiver **212** may be located on the same electronic device **102** or a different electronic device (not shown).

FIG. 4 is a block diagram illustrating high level DBI algorithm control. A transmitter **104** (on an electronic device **102**) may include a channel configuration module **408** and a DBI encoder **406**. The channel configuration module **408** may receive instructions from the core (e.g., a mode controller **118**). The instructions from the core may instruct the channel configuration module **408** on which DBI algorithm **416** to use and whether to enable/disable channel termination. The channel configuration module **408** may provide the selected DBI algorithm **416** to the DBI encoder **406**. The DBI encoder **406** may receive data in **432** (unencoded). The DBI encoder **406** may output data out **422** (encoded) and a DBI flag **424** (in accordance with the selected DBI algorithm **416**). The channel configuration module **408** may output the termination control signal **426**.

The channel configuration module **408** may be capable of detecting the mode of operation based on the relative frequency of the physical layer (PHY) clock (which may be used to synchronize input/output (I/O) activity (typically a sub-harmonic of the I/O data rate)) and a reference clock frequency. The frequency of the reference clock **434** should be independent of the data rate or the PHY clock. The channel configuration module **408** may include a frequency detection circuit **438** that receives the PHY clock via a PHY clock snoop line **436**. The frequency detection circuit **438** is discussed in additional detail below in relation to FIG. 7. The channel configuration module **408** may also receive a reference clock **434** signal for use in detecting the frequencies of the PHY clock.

In one configuration, the channel configuration module **408** may include an oscillator **440** with a known frequency of oscillation. The channel configuration module **408** may use the oscillator **440** to detect the mode of operation of the electronic device **102**. The frequency of the oscillator **440** may be independent of the data rate of the PHY clock. For systems with a large difference between high and low speeds (e.g., an order of magnitude), the precision of the oscillator **440** and/or the frequency detection scheme may not need to be precise. In other systems, where multiple speeds of operation are permissible and/or where the step in speed between different operating modes is more gradual, the overall frequency detection scheme may benefit from increased precision.

The channel configuration module **408** may set the proper DBI encoding algorithm **416** to use and enable/disable

channel termination (i.e., using the termination control signal **426**) without external instructions to do so.

FIG. **5** is a block diagram illustrating one example of DBI selection circuitry in a DBI encoder **506**. The memory interface shown is unidirectional. However, many applications of the DBI encoder **506** may be bidirectional. The DBI encoder **506** of FIG. **5** may be one configuration of the DBI encoder **106** of FIG. **1**. The DBI encoder **506** may receive parallel data in (unencoded) **532**. The parallel data in (unencoded) **532** may be provided to a first input of an algorithm multiplexer **540**. The algorithm multiplexer **540** may be controlled by an algorithm selection **539** signal that indicates to the DBI encoder **506** which DBI algorithm **116** to apply (e.g., based on the signaling speed mode). The parallel data out (encoded) **522** may be provided to an XOR gate **546** along with the parallel data in (unencoded) **532**. The output of the XOR gate **546** may be provided to a second input of the algorithm multiplexer **540**. The XOR gate **546** compares the incoming (next) cycle of parallel data with the feedback from the outgoing (last) cycle.

The output of the algorithm multiplexer **540** may be provided to majority detection circuitry **550**. The majority detection circuitry **550** is designed to indicate an imbalance between the number of logical ones or zeros at the multiple inputs. During DBI-DC operation, the input values represent the number of ones or zeros to be transmitted during the next cycle. During DBI-AC operation, the input values (which come from the XOR gate **546** operation) indicate the number of expected transitions during the next cycle. For the case of DBI-AC, if more than half the parallel data bits will transition during the next cycle, the majority detection circuitry **550** may indicate to a true/complement multiplexer **542** (via a true/complement signal **548**) to pass an inverted version of the parallel data in (unencoded) **532** (via an inverter **544**). If less than half the parallel data bits will transition during the next cycle, the majority detection circuitry **550** may indicate to the true/complement multiplexer **542** (via the true/complement signal **548**) to pass the parallel data in (unencoded) **532** without inverting (as the parallel data out (encoded) **522**).

The majority detection circuitry **550** may also generate a DBI flag **524**. In one configuration, the DBI flag **524** may be the same signal as the true/complement signal **548**. The DBI flag **524** may be sent to an additional off-chip driver.

In memory interfaces, data is generally transmitted in bursts, where all of the data in a given burst generally comes from one memory bank (region). However, there is no constraint on the physical and temporal proximity of consecutive bursts. The bursts may come from different regions of the memory, with an unpredictable separation in time. It may thus be difficult or impossible for the memory device to analyze the number of transitions occurring between the end of one burst and the beginning of the next burst in order to implement DBI-AC with a no-feedback encoder.

For the case of DBI-AC, when the state of the data preceding the current cycle is unknown, it may be advantageous to temporarily disable the DBI encoder **506**. This may be accomplished by disabling the DBI encoding at the end of each burst and then re-enabling the DBI encoding after (or as) the first edge of the new burst arrives at the DBI encoder **506**. This behavior would be consistent and could be controlled using a finite state machine. A more complicated approach would be to additionally consider the source of the two consecutive bursts. If the two bursts come from the same bank, without an intermediate timing bubble, the DBI encoder **506** may still be able to calculate the valid transition data. Therefore, the DBI encoder **506** can remain

enabled across the burst boundary. If the two bursts do not come from the same bank, or if there is an intermediate timing bubble, the DBI encoder **506** may be disabled after each burst and re-enabled in time for the second cycle of the subsequent burst.

In a third case, in between bursts, data may always be brought to a known value (e.g., all zeros). The DBI encoder **506** may then feed that known value to an XOR gate **546** as the preceding state of the bus at the beginning of each burst. For the case of LPDDR4, where the signals are explicitly referenced to ground and therefore naturally tend towards ground when not actively driven, the “preceding state” assumption may be clear and may thus not require additional circuitry to force the data state to a known value.

FIG. **6** is a block diagram illustrating another example of DBI selection circuitry in a DBI encoder **606**. The memory interface shown is unidirectional. However, many applications of the DBI encoder **606** may be bidirectional. The DBI encoder **606** of FIG. **6** may be one configuration of the DBI encoder **106** of FIG. **1**. The DBI encoder **606** may receive parallel data in (unencoded) **632**. The parallel data in (unencoded) **632** may be provided to a first input of an algorithm multiplexer **640**. The algorithm multiplexer **640** may be controlled by an algorithm selection **639** that indicates to the DBI encoder **606** which DBI algorithm **116** to apply (e.g., based on the signaling speed mode). The parallel data out (encoded) **622** may be provided to an XOR gate **646** along with the parallel data in (unencoded) **632**. The output of the XOR gate **646** may be provided to a second input of the algorithm multiplexer **640**. The XOR gate **646** compares the incoming (next) cycle of parallel data with the feedback from the outgoing (last) cycle.

In order to facilitate the application of DBI-AC, the output of the algorithm multiplexer **640** may be provided to majority detection circuitry **650**. The majority detection circuitry **650** may determine whether more than half of the parallel data bits will transition during the next cycle. If more than half the parallel data bits will transition during the next cycle, the majority detection circuitry **650** may output a true/complement signal **648** that is a digital logic 1. If less than half the parallel data bits will transition during the next cycle, the majority detection circuitry **650** may output a true/complement signal **648** that is a digital logic 0. The true/complement signal **648** and a dynamic disable signal **652** may be provided as inputs to an AND gate. The output of the AND gate may control a true/complement multiplexer **642**. One input of the true/complement multiplexer **642** may be the parallel data in (unencoded) **632**. A second input of the true/complement multiplexer **642** may be the parallel data in (unencoded) **632** passed through an inverter **644**. Thus, whenever the dynamic disable signal **652** is a digital logic of zero, the DBI encoder **606** will output unencoded data, regardless of the DBI calculation. The dynamic disable signal **652** may also be applied in an encoder with a topology that does not use feedback.

The majority detection circuitry **650** may also generate a DBI flag **624**. In one configuration, the DBI flag **624** may be the same signal as the true/complement signal **648**. The DBI flag **624** may be sent to an additional off-chip driver. In another configuration, the DBI flag **624** may be sent without an additional off-chip driver, by sending the DBI flag **624** during a transmit cycle either preceding or following the data burst.

FIG. **7** is a block diagram illustrating a channel configuration module **708** that includes a frequency detection circuit **738**. The frequency detection circuit **738** of FIG. **7** may be one configuration of the frequency detection circuit **438** of

FIG. 4. The frequency detection circuit **738** may include an edge counter **758** and an edge count and evaluation trigger **760**. The edge counter **758** may receive the PHY clock from the PHY clock snoop line **736**. The edge counter **758** may count the edges of the PHY clock. Periodically, the edge count and evaluation trigger **760** may evaluate the edge count and reset the edge counter **758** (using a reset signal **754**). The edge count and evaluation trigger **760** may receive a reference clock **734**. When triggered to reset the edge counter **758**, the current edge count **764** is provided to a results configuration module **762**. The results configuration module **762** may compare the edge count **764** with a predetermined threshold (e.g., using a lookup table or a register) to see if a frequency threshold has been crossed. More edges counted may indicate a higher speed of operation. The results configuration module **762** may then select the appropriate DBI encoding algorithm **716** and termination control signal **726** based on the determined frequency of operation.

FIG. 8 illustrates certain components that may be included within an electronic device **802** that uses frequency-dependent data bus inversion (DBI) encoding. The electronic device **802** may be an access terminal, a mobile station, a wireless communication device, a user equipment (UE), a base station, a Node B, a handheld electronic device, etc. The electronic device **802** includes a processor **803**. The processor **803** may be a general purpose single- or multi-chip microprocessor (e.g., an ARM), a special purpose microprocessor (e.g., a digital signal processor (DSP)), a microcontroller, a programmable gate array, etc. The processor **803** may be referred to as a central processing unit (CPU). Although just a single processor **803** is shown in the electronic device **802** of FIG. 8, in an alternative configuration, a combination of processors **803** (e.g., an ARM and DSP) could be used.

The electronic device **802** also includes memory **805**. The memory **805** may be any electronic component capable of storing electronic information. The memory **805** may be embodied as random access memory (RAM), read-only memory (ROM), magnetic disk storage media, optical storage media, flash memory devices in RAM, on-board memory included with the processor, EPROM memory, EEPROM memory, registers, and so forth, including combinations thereof.

Data **809a** and instructions **807a** may be stored in the memory **805**. The instructions **807a** may be executable by the processor **803** to implement the methods disclosed herein. Executing the instructions **807a** may involve the use of the data **809a** that is stored in the memory **805**. When the processor **803** executes the instructions **807a**, various portions of the instructions **807b** may be loaded onto the processor **803**, and various pieces of data **809b** may be loaded onto the processor **803**.

The electronic device **802** may also include a transmitter **811** and a receiver **813** to allow transmission and reception of signals to and from the electronic device **802**. The transmitter **811** and receiver **813** may be collectively referred to as a transceiver **815**. An antenna **817** may be electrically coupled to the transceiver **815**. The electronic device **802** may also include (not shown) multiple transmitters, multiple receivers, multiple transceivers and/or multiple antennas.

The electronic device **802** may include a digital signal processor (DSP) **821**. The electronic device **802** may also include a communications interface **823**. The communications interface **823** may allow a user to interact with the electronic device **802**.

The various components of the electronic device **802** may be coupled together by one or more buses, which may include a power bus, a control signal bus, a status signal bus, a data bus, etc. For the sake of clarity, the various buses are illustrated in FIG. 8 as a bus system **819**.

The techniques described herein may be used for various communication systems, including communication systems that are based on an orthogonal multiplexing scheme. Examples of such communication systems include Orthogonal Frequency Division Multiple Access (OFDMA) systems, Single-Carrier Frequency Division Multiple Access (SC-FDMA) systems, and so forth. An OFDMA system utilizes orthogonal frequency division multiplexing (OFDM), which is a modulation technique that partitions the overall system bandwidth into multiple orthogonal sub-carriers. These sub-carriers may also be called tones, bins, etc. With OFDM, each sub-carrier may be independently modulated with data. An SC-FDMA system may utilize interleaved FDMA (IFDMA) to transmit on sub-carriers that are distributed across the system bandwidth, localized FDMA (LFDMA) to transmit on a block of adjacent sub-carriers, or enhanced FDMA (EFDMA) to transmit on multiple blocks of adjacent sub-carriers. In general, modulation symbols are sent in the frequency domain with OFDM and in the time domain with SC-FDMA.

The term “determining” encompasses a wide variety of actions and, therefore, “determining” can include calculating, computing, processing, deriving, investigating, looking up (e.g., looking up in a table, a database or another data structure), ascertaining and the like. Also, “determining” can include receiving (e.g., receiving information), accessing (e.g., accessing data in a memory) and the like. Also, “determining” can include resolving, selecting, choosing, establishing and the like.

The phrase “based on” does not mean “based only on,” unless expressly specified otherwise. In other words, the phrase “based on” describes both “based only on” and “based at least on.”

The term “processor” should be interpreted broadly to encompass a general purpose processor, a central processing unit (CPU), a microprocessor, a digital signal processor (DSP), a controller, a microcontroller, a state machine, and so forth. Under some circumstances, a “processor” may refer to an application specific integrated circuit (ASIC), a programmable logic device (PLD), a field programmable gate array (FPGA), etc. The term “processor” may refer to a combination of processing devices, e.g., a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration.

The term “memory” should be interpreted broadly to encompass any electronic component capable of storing electronic information. The term memory may refer to various types of processor-readable media such as random access memory (RAM), read-only memory (ROM), non-volatile random access memory (NVRAM), programmable read-only memory (PROM), erasable programmable read-only memory (EPROM), electrically erasable PROM (EEPROM), flash memory, magnetic or optical data storage, registers, etc. Memory is said to be in electronic communication with a processor if the processor can read information from and/or write information to the memory. Memory that is integral to a processor is in electronic communication with the processor.

The terms “instructions” and “code” should be interpreted broadly to include any type of computer-readable statement (s). For example, the terms “instructions” and “code” may

11

refer to one or more programs, routines, sub-routines, functions, procedures, etc. "Instructions" and "code" may comprise a single computer-readable statement or many computer-readable statements.

The functions described herein may be implemented in software or firmware being executed by hardware. The functions may be stored as one or more instructions on a computer-readable medium. The terms "computer-readable medium" or "computer-program product" refers to any tangible storage medium that can be accessed by a computer or a processor. By way of example, and not limitation, a computer-readable medium may include RAM, ROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium that can be used to carry or store desired program code in the form of instructions or data structures and that can be accessed by a computer. Disk and disc, as used herein, includes compact disc (CD), laser disc, optical disc, digital versatile disc (DVD), floppy disk and Blu-ray® disc where disks usually reproduce data magnetically, while discs reproduce data optically with lasers. It should be noted that a computer-readable medium may be tangible and non-transitory. The term "computer-program product" refers to a computing device or processor in combination with code or instructions (e.g., a "program") that may be executed, processed or computed by the computing device or processor. As used herein, the term "code" may refer to software, instructions, code or data that is/are executable by a computing device or processor.

The methods disclosed herein comprise one or more steps or actions for achieving the described method. The method steps and/or actions may be interchanged with one another without departing from the scope of the claims. In other words, unless a specific order of steps or actions is required for proper operation of the method that is being described, the order and/or use of specific steps and/or actions may be modified without departing from the scope of the claims.

Further, it should be appreciated that modules and/or other appropriate means for performing the methods and techniques described herein, such as those illustrated by FIG. 3, can be downloaded and/or otherwise obtained by a device. For example, a device may be coupled to a server to facilitate the transfer of means for performing the methods described herein. Alternatively, various methods described herein can be provided via a storage means (e.g., random access memory (RAM), read-only memory (ROM), a physical storage medium such as a compact disc (CD) or floppy disk, etc.), such that a device may obtain the various methods upon coupling or providing the storage means to the device.

It is to be understood that the claims are not limited to the precise configuration and components illustrated above. Various modifications, changes and variations may be made in the arrangement, operation and details of the systems, methods, and apparatus described herein without departing from the scope of the claims.

What is claimed is:

1. A method for data transmission, comprising:

determining whether a signaling speed of operation of an electronic device is a high-speed mode or a low-speed mode;

selecting a data bus inversion algorithm based on whether the signaling speed of operation is the high-speed mode or the low-speed mode;

using the selected data bus inversion algorithm to encode data; and

12

sending the encoded data and a data bus inversion flag to a receiver over a transmission line.

2. The method of claim 1, wherein the selected data bus inversion algorithm is one of a DBI-AC algorithm and a DBI-DC algorithm.

3. The method of claim 2, wherein the selected data bus inversion algorithm is DBI-AC when the signaling speed of operation is the low-speed mode.

4. The method of claim 2, wherein the selected data bus inversion algorithm is DBI-DC when the signaling speed of operation is the high-speed mode.

5. The method of claim 1, wherein the signaling speed of operation is communicated to an encoder by a dedicated signal.

6. The method of claim 5, wherein the dedicated signal is provided through a command address bus.

7. The method of claim 5, wherein the dedicated signal is provided using an existing data line.

8. The method of claim 1, wherein the signaling speed of operation is autonomously determined by an encoder.

9. The method of claim 1, wherein the selected data bus inversion algorithm is used to encode data using a topology that does not comprise feedback.

10. The method of claim 1, wherein the data bus inversion algorithm is used to encode data using a topology that comprises feedback.

11. The method of claim 1, wherein data bus inversion algorithm encoding is disabled autonomously based on a dynamic disable signal.

12. The method of claim 1, further comprising:

generating a termination control signal based on the selected data bus inversion algorithm; and

sending the termination control signal to the receiver.

13. The method of claim 1, wherein the method is performed by a data bus inversion encoder comprising:

an algorithm selection multiplexer;

an XOR gate that receives parallel unencoded data of an upcoming burst and parallel data of a previous burst;

an inverter;

a majority detection circuit; and

a true/complement multiplexer.

14. The method of claim 13, wherein the data bus inversion encoder further comprises a frequency detection circuit, and wherein the selected data bus inversion algorithm is based on a relationship between a physical layer clock frequency and a reference frequency.

15. An apparatus for data transmission, comprising:

a processor;

memory in electronic communication with the processor; and

instructions stored in the memory, the instructions being executable by the processor to:

determine whether a signaling speed of operation of an electronic device is a high-speed mode or a low-speed mode;

select a data bus inversion algorithm based on whether the signaling speed of operation is the high-speed mode or the low-speed mode;

use the selected data bus inversion algorithm to encode data; and

send the encoded data and a data bus inversion flag to a receiver over a transmission line.

16. The apparatus of claim 15, wherein the selected data bus inversion algorithm is one of a DBI-AC algorithm and a DBI-DC algorithm.

13

17. The apparatus of claim 16, wherein the selected data bus inversion algorithm is DBI-AC when the signaling speed of operation is the low-speed mode.

18. The apparatus of claim 16, wherein the selected data bus inversion algorithm is DBI-DC when the signaling speed of operation is the high-speed mode.

19. The apparatus of claim 15, wherein the signaling speed of operation is communicated to an encoder by a dedicated signal.

20. The apparatus of claim 19, wherein the dedicated signal is provided through a command address bus.

21. The apparatus of claim 19, wherein the dedicated signal is provided using an existing data line.

22. The apparatus of claim 15, wherein the signaling speed of operation is autonomously determined by an encoder.

23. The apparatus of claim 15, wherein the selected data bus inversion algorithm is used to encode data using a topology that does not comprise feedback.

24. The apparatus of claim 15, wherein the data bus inversion algorithm is used to encode data using a topology that comprises feedback.

25. The apparatus of claim 15, wherein data bus inversion algorithm encoding is disabled autonomously based on a dynamic disable signal.

26. The apparatus of claim 15, wherein the instructions are further executable by the processor to:

generate a termination control signal based on the selected data bus inversion algorithm; and

send the termination control signal to the receiver.

27. The apparatus of claim 15, further comprising a data bus inversion encoder comprising:

an algorithm selection multiplexer;

an XOR gate that receives parallel unencoded data of an upcoming burst and parallel data of a previous burst;

an inverter;

a majority detection circuit; and

a true/complement multiplexer.

14

28. The apparatus of claim 27, wherein the data bus inversion encoder further comprises a frequency detection circuit, and wherein the selected data bus inversion algorithm is based on a relationship between a physical layer clock frequency and a reference frequency.

29. An apparatus for data transmission, comprising:

a processor;

memory in electronic communication with the processor; and

instructions stored in the memory, the instructions being executable by the processor to:

determine a signaling speed of operation of an electronic device;

select a data bus inversion algorithm based on the signaling speed of operation, wherein the selected data bus inversion algorithm is DBI-AC when the signaling speed of operation is the low-speed mode;

use the selected data bus inversion algorithm to encode data; and

send the encoded data and a data bus inversion flag to a receiver over a transmission line.

30. An apparatus for data transmission, comprising:

a processor;

memory in electronic communication with the processor; and

instructions stored in the memory, the instructions being executable by the processor to:

determine a signaling speed of operation of an electronic device;

select a data bus inversion algorithm based on the signaling speed of operation, wherein the selected data bus inversion algorithm is DBI-DC when the signaling speed of operation is the high-speed mode;

use the selected data bus inversion algorithm to encode data; and

send the encoded data and a data bus inversion flag to a receiver over a transmission line.

* * * * *