



US009529938B2

(12) **United States Patent**  
**Woodward**

(10) **Patent No.:** **US 9,529,938 B2**  
(45) **Date of Patent:** **Dec. 27, 2016**

(54) **UNIFIED FILE SEARCH**

(71) Applicant: **Google Inc.**, Mountain View, CA (US)

(72) Inventor: **Joshua Woodward**, Mountain View, CA (US)

(73) Assignee: **Google Inc.**, Mountain View, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 368 days.

(21) Appl. No.: **13/662,008**

(22) Filed: **Oct. 26, 2012**

(65) **Prior Publication Data**

US 2014/0122423 A1 May 1, 2014

(51) **Int. Cl.**

**G06F 7/00** (2006.01)

**G06F 17/30** (2006.01)

(52) **U.S. Cl.**

CPC ..... **G06F 17/30997** (2013.01); **G06F 17/301** (2013.01); **G06F 17/30389** (2013.01)

(58) **Field of Classification Search**

CPC ..... G06F 17/30442

USPC ..... 707/713

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

- 7,346,613 B2 3/2008 Hurst-Hiller et al.
- 7,930,301 B2 4/2011 Marcjan et al.
- 8,341,147 B2 12/2012 Hu et al.
- 2007/0033176 A1\* 2/2007 Enns ..... 707/3
- 2008/0109422 A1\* 5/2008 Dedhia ..... G06F 17/30867
- 2008/0281802 A1\* 11/2008 Peterson et al. .... 707/4

- 2012/0047168 A1 2/2012 Yokoi et al.
- 2012/0233209 A1 9/2012 Cheng et al.
- 2012/0233211 A1 9/2012 Hassan et al.

**FOREIGN PATENT DOCUMENTS**

- KR 20090066702 A 6/2009
- KR 20100051575 A 5/2010
- KR 20110129141 A 12/2011
- WO 2007094536 A1 8/2007
- WO 2012160567 A1 \* 11/2012

**OTHER PUBLICATIONS**

International Search Report and Written Opinion for International Application No. PCT/US2013/066799, mailed Feb. 28, 2014, 11 pages.

(Continued)


*Primary Examiner* — Ajith Jacob

(74) *Attorney, Agent, or Firm* — Brake Hughes Bellermann LLP

(57) **ABSTRACT**

The unified file search may be performed by a user device. The user device includes a processor and a memory. The memory includes code segments that when executed by the processor cause the processor to generate a search parameter; generate a first search metadata based on data stored in the memory and the search parameter, the first search metadata representing the data stored in the memory; generate a search request based on the search parameter; transmit the search request to at least one associated remote data storage resource; receive a second search metadata from the at least one associated remote data storage resource, the second search metadata representing data stored in the at least one associated remote data storage resource; and generate a unified search metadata including the first search metadata and the second search metadata.

**18 Claims, 9 Drawing Sheets**



(56)

**References Cited**

OTHER PUBLICATIONS

“Searching Time Machine backup data”, retrieved on Apr. 28, 2016 from <http://web.archive.org/web/20090831050901/http://superuser.com/questions/7518/searching-time-machine-backup-data>, Aug. 31, 2009, pp. 1-3.

Extended European Search Report for EP Application No. 13848208.8, mailed May 13, 2016, 10 pages.

Faas, “Apple Remote Desktop 3, Part 3 Gathering Information about Remote Computers”, retrieved on Apr. 28, 2016 from <http://www.peachpit.com/articles/printerfriendly/606977>, Sep. 15, 2006, pp. 1-9.

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 4






FIG. 5




FIG. 6




FIG. 7

# 1

## UNIFIED FILE SEARCH

### BACKGROUND

Embodiments relate to performing file searches on a plurality of computing systems.

### SUMMARY

One embodiment includes a user device. The user device includes a processor and a memory. The memory includes code segments that when executed by the processor cause the processor to generate a search parameter; generate a first search metadata based on data stored in the memory and the search parameter, the first search metadata representing the data stored in the memory; generate a search request based on the search parameter; transmit the search request to at least one associated remote data storage resource; receive a second search metadata from the at least one associated remote data storage resource, the second search metadata representing data stored in the at least one associated remote data storage resource; and generate a unified search metadata including the first search metadata and the second search metadata.

Another embodiment includes a server. The server includes a processor configured to receive user device metadata and a search parameter from a user device, the user device metadata representing data stored at the user device. The server includes a memory including code segments that when executed by the processor cause the processor to: generate first search metadata based on the received user device metadata and the search parameter; generate second search metadata based on data stored in the memory and the search parameters, the second metadata representing data stored in the memory; generate a search request based on the search parameter; transmit the search request to a remote data storage resource associated with the user device; receive third search metadata, in response to the search request, from the remote data storage resource, the third search metadata representing data stored at the remote data storage resource; generate unified search metadata including the first search metadata, the second search metadata, and the third search metadata; and transmit the unified search metadata to the user device.

### BRIEF DESCRIPTION OF THE DRAWINGS

Example embodiments will become more fully understood from the detailed description given herein below and the accompanying drawings, wherein like elements are represented by like reference numerals, which are given by way of illustration only and thus are not limiting of the example embodiments and wherein:

FIG. 1 illustrates a block diagram of a network system in accordance with an example embodiment.

FIG. 2 illustrates a block diagram of a computing device in accordance with an example embodiment.

FIG. 3A illustrates a unified file search in accordance with an example embodiment.

FIGS. 3B and 3C illustrate unified file search displays in accordance with at least one example embodiment.

FIG. 4 illustrates a method for generating a unified file search in accordance with an example embodiment.

FIG. 5 illustrates another method for generating a unified file search in accordance with an example embodiment.

# 2

FIG. 6 illustrates yet another method for generating a unified file search in accordance with an example embodiment.

FIG. 7 illustrates a block diagram of a system in accordance with an example embodiment.

It should be noted that these Figures are intended to illustrate the general characteristics of methods, structure and/or materials utilized in certain example embodiments and to supplement the written description provided below.

These drawings are not, however, to scale and may not precisely reflect the precise structural or performance characteristics of any given embodiment, and should not be interpreted as defining or limiting the range of values or properties encompassed by example embodiments. For example, the relative thicknesses and positioning of layers, regions and/or structural elements may be reduced or exaggerated for clarity. The use of similar or identical reference numbers in the various drawings is intended to indicate the presence of a similar or identical element or feature.

### DETAILED DESCRIPTION OF THE EMBODIMENTS

While example embodiments are capable of various modifications and alternative forms, embodiments thereof are shown by way of example in the drawings and will herein be described in detail. It should be understood, however, that there is no intent to limit example embodiments to the particular forms disclosed, but on the contrary, example embodiments are to cover all modifications, equivalents, and alternatives falling within the scope of the claims. Like numbers refer to like elements throughout the description of the figures.

FIG. 1 illustrates a block diagram of a network system in accordance with an example embodiment. As shown in FIG. 1, the network system 100 includes a user device 105, a first server storage system 115, and a second server storage system 120. The first server storage system 115 includes servers 125 and storage system 135. The second server storage system 120 includes servers 130 and storage system 140. The user device 105 may include at least one associated peripheral device 150. FIG. 1 further illustrates a user 110 of the user device 105 and communicative links 145 (e.g., wired or wireless communication links) that communicatively couple each of the user device 105, the first server storage system 115, and the second server storage system 120 to each other.

According to example embodiments, the first server storage system 115, and the second server storage system 120 may be third party cloud storage systems configured to store data and information related to the data. The information related to the data may be referred to metadata. The third party cloud storage systems may have different protocols for accessing, storing and/or sharing data. The third party cloud storage systems are typically independent (e.g., not interconnected) of each other and do not (on their own) share data between them. However, according to example embodiments, data and metadata on separate third party cloud storage systems may be searched and the results of the search may be combined as a unified search as described in more detail below. For example, the third party cloud storage systems may include a GOOGLE™, a Google Drive, a DROPBOX™ or some other remote (e.g., cloud network) data storage resource.

For the purposes of the description below, the first server storage system 115 and the second server storage system 120 are distinct third party cloud storage systems having differ-

ent protocols. However, the first server storage system **115** and the second server storage system **120** are not limited thereto. Each of the first server storage system **115** and the second server storage system **120** may have an associated protocol for accessing, storing and/or sharing data stored therein. The data being stored in, for example, storage system **135** and storage system **140**. Storage system **135** and storage system **140** being, for example, a magnetic storage device, an optical storage device, and/or solid state storage device. The peripheral device **150** may be configured to store data and/or information; the information may be associated with the data. The peripheral device may be a memory device (e.g., a magnetic storage device, an optical storage device, solid state storage device, and the like). The peripheral device may be a device including a memory (e.g., a digital camera, a cell phone, a PDA, and the like).

FIG. 2 illustrates a computing device in accordance with an example embodiment. The computing device **200** may be a server, a personal computer, a laptop, a smartphone and the like. The computing device **200** may be a part of a server, a personal computer, a laptop, a smartphone and the like. For example, the computing device **200** may be (or, alternatively, may be a part of) at least one of user device **105**, servers **125**, and servers **130**.

As shown in FIG. 2, the computing device **200** may include a processor **205**, a memory **210**, an interface **215** and a search module **220**. The processor **205**, the memory **210**, the interface **215** and the search module **220** are communicatively coupled via bus **225**. The processor **205** may execute instructions within the computing device **200**, including instructions stored in the memory **205**. The processor may be implemented as a chipset of chips that include separate and multiple analog and digital processors. The processor may provide, for example, for coordination of the other components of the device **200**, such as control of interface **215**, applications run by device **200**, and communication by device **200**.

The memory **210** may be configured to store information within the computing device **200**. The memory **210** may be implemented as one or more of a computer-readable medium or media, a volatile memory unit or units, or a non-volatile memory unit or units. The interface **215** may be configured to communicate with other devices. For example, interface **215** associated with a user device **105** may communicate with peripheral device **150**, storage system **135** and/or storage system **140**.

The search module **220** may be software module including code segments that when executed by processor **205** cause processor **205** to perform certain tasks for performing a unified search while interacting with memory **210** and interface **215**. Alternatively, or in addition, the search module may be an application specific integrated chip (ASIC) configured to perform certain tasks for performing a unified search. The ASIC may include a processor(s), a memory(s) and other components as necessary to perform tasks.

The search module **220** may be configured to generate a search parameter; generate a first search metadata based on data stored in the memory and the search parameter, the first search metadata representing the data stored in the memory; generate a search request based on the search parameter; transmit the search request to at least one associated remote data storage resource; receive a second search metadata from the at least one associated remote data storage resource, the second search metadata representing data stored in the at least one associated remote data storage resource; and generate a unified search metadata including the first search metadata and the second search metadata.

The search module **220** may be configured to generate first search metadata based on the received user device metadata and the search parameter; generate second search metadata based on data stored in the memory and the search parameters, the second metadata representing data stored in the memory; generate a search request based on the search parameter; transmit the search request to a remote data storage resource associated with the user device; receive third search metadata, in response to the search request, from the remote data storage resource, the third search metadata representing data stored at the remote data storage resource; generate unified search metadata including the first search metadata, the second search metadata, and the third search metadata; and transmit the unified search metadata to the user device.

Further details regarding search module **220** may be discussed below in more detail as discussing the methods associated with FIGS. 4-6.

FIG. 3A illustrates a unified file search in accordance with an example embodiment. As shown in FIG. 3A, search metadata **305**, **310** and **315** are combined (e.g., unified) to generate unified search metadata **320**. For example, search metadata **305** may represent data stored on user device **105**. Search metadata **310** may represent data stored in storage system **135**. The search metadata may represent various characteristics of stored data including, but not limited to, filetype, file name, file size, date created, date modified, and the like. Search metadata **315** may represent data stored in storage system **140**. Although three search metadata elements are shown, example embodiments are not limited to three. Each of search metadata **305**, **310** and **315** may be based on some search criteria generated on user device **305** based on input(s) from user **110**. Each of search metadata **305**, **310** and **315** may be combined by, for example, user device **105** in order to generate unified search metadata **320**. Accordingly, the unified search metadata **320** may represent data stored at various interconnected/networked devices including, but not limited to user device **105**, peripheral **150**, first server storage system **115**, and the second server storage system **120**.

The search metadata **305**, **310** and **315** may include fields such as name, type, size and date (e.g., last modified). The unified search metadata **320** may include fields such as name, location (e.g., data stored on user device **105** labeled as, for example "local"), type, size and date. The aforementioned fields are only examples and are not intended to limit the scope of example embodiments in any way. The unified search metadata **320** fields may be ordered (e.g., sorted) based on the metadata shown in the fields. For example, the unified search metadata **320** may be sorted alphabetically by name or sorted by location. In addition, the unified search metadata **320** may be sorted based on any combination of fields.

Search metadata **305**, **310** and **315** may be stored locally in a memory queue (e.g., a memory queue on user device **105** or server **130**). For example, search metadata **305**, **310** and **315** may be updated on a regular basis by refreshing the memory queue. In other words, search metadata **305**, **310** and **315** may be replaced by new metadata if, for example, the data that the search metadata **305**, **310** and **315** represents changes. Alternatively, metadata representing data stored in storage systems **135**, **140** and data on user device **105** may be stored in the memory queue. The metadata representing data stored in storage systems **135**, **140** and data on user device **105** may then be searched in order to generate search metadata **305**, **310** and **315**. Alternatively, data on user device **105** may be searched separately in order

to generate, for example, search metadata **305** representing the data on user device **105**. Alternatively, data stored in storage systems **135, 140** may be searched separately, based on search criteria received from user device **105** in order to generate, for example, search metadata **310** and **315** representing the data stored in storage systems **135, 140**.

FIG. **3B** illustrates unified file search display in accordance with an example embodiment. As shown in FIG. **3B**, a unified file search display **325** may include several features directed toward searching and displaying unified search metadata (e.g., unified search metadata **320**). The below described examples are for illustrative purposes and are not intended to limit the scope of the example embodiments in any way.

For example, the unified file search display **325** may include a drop down list **330** configured to list and select data storage locations (e.g., storage systems **135, 140** and data stored on user device **105**). For example, the unified file search display **325** may include a text box **335** configured to enter search parameters for searching, for example, the selected data storage locations. The unified file search display **325** may also include a drop down list **340** configured to list and select a view style for displaying the results of the search (e.g., unified search metadata **320**).

For example, the unified file search display **325** may include a display grid **350** configured to display the results of the search in a form based on the selected view style. As is shown in FIG. **3B** the display grid **350** may be displayed in more than one sectional display grid. For example, each selected data storage location (e.g., local, Remote-1 and Remote-2) may have an associated sectional display grid **350-1, 350-2** and **350-3**. Each sectional display grid **350-1, 350-2, 350-3** may include a selector **355-1, 355-2, 355-3** configured to select a number of search results (e.g., Show all, Top 5, etc.). The unified file search display **325** may also include selector boxes **345-1, 345-2, 345-3** configured to select a search result from the sectional display grid **350-1, 350-2, 350-3**. A number selector boxes **345-1, 345-2, 345-3** may be selected to, for example, compare search results. Alternatively, a single selector box **345-1, 345-2, 345-3** may be selected to, for example, select the metadata file for expanded display. Local, Remote-1 and Remote-2 may represent user device **105**, and storage systems **135, 140** respectively.

FIG. **3C** illustrates unified file search display in accordance with an example embodiment. As shown in FIG. **3C**, a unified file search display **360** may include several features directed toward searching and displaying unified search metadata (e.g., unified search metadata **320**).

The unified file search display **360** may include several features from the unified file search display **325** which are numbered the same and will not be described further. In addition, the unified file search display **360** may include a drop down list **365** configured to list metadata including data storage locations (e.g., storage systems **135, 140** and data stored on user device **105**).

FIG. **4** illustrates a method for generating a unified file search in accordance with an example embodiment. The steps of FIG. **4** may be performed by user device **105** as (or including) computing device **200** utilizing, for example, search module **220**. In step **S405**, the user device **105** generates search parameter(s). The Search parameters may be variable parameters entered as text by a user to generate a search string. For example, user **110** may enter a search string (e.g., “active” & “volcano”) into text box **335** on the unified file search display **325**. The user **110** may then use drop down list **330** to select “All My Files” on the unified file

search display **325**. As a result user device **105** may generate search parameter(s) that result in a search for “active”, “volcano” and “active volcano” on every associated drive (local and remote) of the user device **105**.

Associated drives may include memory associated with the user device (e.g., local memory devices), which may include hard drives, random access memories (RAM), processor memories, cache memories, peripheral memory and the like. Associated drives may include remote storage systems (e.g., storage systems **135, 140**) for which the user **110** has access to user credentials (e.g., user name and password) associated with the remote systems including the remote storage systems.

In step **S410**, the user device **105** generates first (e.g., local) search metadata based on data stored in a memory and the search parameter(s). For example, the user device **105** may search at least one of the associated local memory devices (e.g., hard drive or RAM) for content associated with the search parameter(s). Continuing the above example, the user device **105** may search the associated local memory for “active”, “volcano” and “active volcano”. The user device **105** may search, for example, the content of files stored on the associated local memory and/or names of files stored on the associated local memory. The results of the search may be stored as, for example, search metadata **305**.

In step **S415**, the user device **105** generates a search request based on the search parameter(s). For example, the user device **105** may determine the remote storage systems (e.g., storage systems **135, 140**) to be searched. Determining which remote storage systems to be searched may be based on the selection made by user **110** using drop down list **330**. For each of the remote storage systems to be searched, the user device **105** may determine a protocol and protocol definition associated with the remote storage system to perform a search of the data on the remote storage system. The user device **105** may generate a search request based on the search parameter(s) using each of the determined protocols and protocol definitions. Accordingly, different search requests may be created for each separate storage system based on the protocol specific to that storage system

In step **S420**, the user device **105** transmits the search request to at least one associated remote data storage resource. For example, the user device **105** may transmit the generated search request to each of the server storage system **115, 120** using a protocol associated with communication over communicative link **145**.

In step **S425**, the user device **105** receives second (e.g., remote) search metadata from the at least one associated remote data storage resource. The second search metadata is received in response to the transmitted search request. Continuing the above example, the user device **105** may receive from the at least one associated remote data storage resource results from a search of the associated remote storage system (e.g., storage systems **135, 140**) for “active”, “volcano” and “active volcano”. The search may include, for example, the content of files stored on the associated remote storage system and/or names of files stored on the associated remote storage system. The results of the search may be stored as, for example, search metadata **310, 315**.

In step **S430**, the user device **105** generates unified search metadata (e.g., unified search metadata **320**) including the first search metadata and the second search metadata. For example, the first (e.g., local) search metadata may represent data stored on the user device **105**. The second (e.g., remote) search metadata may represent data stored on (at least one of) the storage systems **135, 140**. The user device **105** may

generate unified search metadata by combining the search metadata representing data stored on the user device **105** with search metadata representing data stored on the storage systems **135, 140** as shown as unified search metadata **320** illustrated in FIG. 3A.

In step **S435**, the user device **105** displays the unified search metadata. For example, the user device **105** may display the unified search metadata on a display screen associated with user device **105** using the unified file search display **325** illustrated in FIG. 3B.

FIG. 5 illustrates another method for generating a unified file search in accordance with an example embodiment. The steps of FIG. 5 may be performed by user device **105** as (or including) computing device **200** utilizing, for example, search module **220**. In step **S505**, the user device **105** receives remote metadata from at least one associated remote data storage resource. The remote metadata may represent data stored in the at least one associated remote data storage resource. For example, the user device **105** may receive remote metadata from each of the server storage systems **115, 120** using a protocol associated with communication over communicative link **145**. The remote metadata may represent data stored in the storage systems **135, 140**. The remote metadata may have a protocol and/or protocol definition associated with the remote storage system **115, 120**, from which the remote metadata is received, in order to determine a format associated with the remote metadata.

In step **S510**, the user device **105** stores the remote metadata in the memory. For example, the remote metadata may be stored in a memory queue associated with the user device **105**. The memory queue may be an element of hard drives, random access memories (RAM), processor memories, cache memories and/or peripheral memory associated with the user device. For example, an application (or protocol) associated with the remote storage system **115, 120** and configured to provide functionality to store and access data on the remote storage system **115, 120** may have an associated queue generated at runtime of the application. Metadata from the remote storage system **115, 120** may be stored in the associated queue.

In step **S515**, the user device **105** generates search parameter(s). For example, user **110** may enter a search string (e.g., “active” & “volcano”) into text box **335** on the unified file search display **325**. The user **110** may then use drop down list **330** to select “All My Files” on the unified file search display **325**. As a result user device **105** may generate search parameter(s) that result in a search for “active”, “volcano” and “active volcano” on every associated drive (local and remote) of the user device **105**.

In step **S520**, the user device **105** generates unified search metadata (e.g., unified search metadata **320**) based on the search parameter(s), data stored in the memory and the stored remote metadata. For example, the user device **105** may search at least one of the associated local memory devices (e.g., hard drive or RAM) for content associated with the search parameter(s). Continuing the above example, the user device **105** may search the associated local memory for “active”, “volcano” and “active volcano”. The user device **105** may search, for example, the content of files stored on the associated local memory and/or names of files stored on the associated local memory. The results of the search may be stored as, for example, search metadata **305**.

Further, the user device **105** may search metadata from the remote storage system **115, 120** that is stored in the associated queue (e.g., application queue) for content associated with the search parameter(s). Continuing the above example, the user device **105** may search the associated queue for

“active”, “volcano” and “active volcano”. The user device **105** may search, for example, the content of files stored in the associated queue and/or names of files stored in the associated queue. The results of the search may be stored as, for example, search metadata **310, 315**. The user device **105** may generate unified search metadata by combining the search metadata representing data stored on the user device **105** (e.g., search metadata **305**) with search metadata representing data stored on the storage systems **135, 140** (e.g., search metadata **310, 315**) as shown as unified search metadata **320** illustrated in FIG. 3A.

In step **S525**, the user device **105** displays the unified search metadata. For example, the user device **105** may display the unified search metadata on a display screen associated with user device **105** using the unified file search display **325** illustrated in FIG. 3B.

FIG. 6 illustrates yet another method for generating a unified file search in accordance with an example embodiment. The steps of FIG. 6 may be performed by server **125** and/or server **135** as (or including) computing device **200** utilizing, for example, search module **220**. In step **S605**, the server **125, 135** receives user device metadata, search parameter(s), and information related to remote storage systems associated with a user device from a user device **105**. The user device metadata represents data stored at the user device **105**. For example, user **110** may enter a search string (e.g., “active” & “volcano”) into text box **335** on the unified file search display **325**. The user **110** may then use drop down list **330** to select “All My Files” on the unified file search display **325**. As a result user device **105** may generate search parameter(s) that result in a search for “active”, “volcano” and “active volcano”. The generated search parameter(s) may be transmitted by the user device **105** and received by the server **125, 135**.

The user device **105** may also transmit, and the server **125** receives, metadata representing data stored on associated drives of the user device **105**. Associated drives may include memory associated with the user device (e.g., local memory devices), which may include hard drives, random access memories (RAM), processor memories, cache memories, peripheral memory and the like. The user device **105** may also transmit, and the server **125** receives, information related to remote storage systems associated with the user device **105**. The information related to remote storage systems associated with the user device **105** may include a list of remote storage systems (e.g., server storage systems **115, 120**) and user credentials (e.g., user name and password) associated with each of the remote systems.

The generated search parameter(s), the metadata representing data stored on associated drive of the user device **105**, and the information related to remote storage systems associated with the user device **105** may be transmitted by the user device **105** and received by the server **125, 135** together (e.g., a single transmission packet) and/or alternatively separately (e.g., multiple transmission packets). The user device **105** may transmit and the server **125, 135** may receive remote the generated search parameter(s), the metadata representing data stored on associated drive of the user device **105**, and the information related to remote storage systems associated with the user device **105** using a protocol associated with communication over communicative link **145**.

In step **S610**, the server **125, 135** generates first search metadata based on the received user device metadata and the search parameter(s). For example, if server **125** receives the user device metadata and the search parameter(s) from the user device **105**, server **125** may search the user device

metadata using the search parameter(s). The result of the search may be the first search metadata. The results of the search may be stored by the server 125 as, for example, search metadata 305.

In step S615, the server 125, 135 generates second search metadata based on data stored in the memory and the search parameter(s). The second search metadata representing data stored in the memory. For example, if server 125 receives the user device metadata and the search parameter(s) from the user device 105, server 125 may search storage system 140 using the search parameter(s). The result of the search may be the second search metadata. The results of the search may be stored by the server 125 as, for example, search metadata 310.

In step S620, the server 125, 135 generates a search request based on the search parameter(s) and the information related to remote storage systems associated with the user device 105. For example, the server 125 may determine the remote storage systems (e.g., server storage system 120) to be searched based on the information related to remote storage systems associated with the user device 105. Determining which remote storage systems to be searched may be based on the selection made by user 110 using drop down list 330. For each of the remote storage systems to be searched, the server 125 may determine a protocol and protocol definition associated with the remote storage system to perform a search of the data on the remote storage system. The server 125 may generate a search request based on the search parameter(s) using each of the determined protocols and protocol definitions.

In step S625, the server 125, 135 transmits the search request to a remote data storage resource associated with the user device 105. For example, the server 125 may transmit the generated search request to server storage system 120 using a protocol associated with communication over communicative link 145.

In step S630, the server 125, 135 receives third search metadata, in response to the search request, from the remote data storage resource, the third search metadata representing data stored at the remote data storage resource. The third search metadata from the remote data storage resource is received in response to the transmitted search request. Continuing the above example, the server 125 may receive from the remote data storage resource results from a search of the associated remote storage system (e.g., storage system 140) for “active”, “volcano” and “active volcano”. The search may include, for example, the content of files stored on the remote storage system and/or names of files stored on the remote storage system. The results of the search may be stored by the server 125 as, for example, search metadata 315.

In step S635, the server 125, 135 generates unified search metadata (e.g., unified search metadata 320) including the first search metadata, the second search metadata, and the third search metadata. For example, the first (e.g., local) search metadata may represent data stored on the user device 105 (e.g., search metadata 305). The second (e.g., remote) search metadata may represent data stored on the storage system 135 (e.g., search metadata 310). The third (e.g., remote) search metadata may represent data stored on the storage system 140 (e.g., search metadata 315). The server 125 may generate unified search metadata by combining the search metadata representing data stored on the user device 105 with search metadata representing data stored on the storage systems 135, 140 as shown as unified search metadata 320 illustrated in FIG. 3A.

In step S640, the server 125, 135 transmits the unified search metadata to the user device 105. For example, the server 125 may transmit the generated unified search metadata to user device 105 using a protocol associated with communication over communicative link 145.

The user device 105 may display the unified search metadata. For example, the user device 105 may display the unified search metadata on a display screen associated with user device 105 using the unified file search display 325 illustrated in FIG. 3B.

FIG. 7 illustrates a block diagram of a system in accordance with an example embodiment. FIG. 7 shows an example of a generic computer device 700 and a generic mobile computer device 750, which may be used with the techniques described herein. Computing device 700 may represent various forms of digital computers, such as laptops, desktops, workstations, personal digital assistants, servers, blade servers, mainframes, and other appropriate computers. Computing device 750 may represent various forms of mobile devices, such as personal digital assistants, cellular telephones, smart phones, and other similar computing devices. The components shown here, their connections and relationships, and their functions, are meant to be exemplary only, and are not meant to limit implementations of example embodiments described and/or claimed in this document. For example, computing device 700 may represent at least one of user device 105 and servers 125, 130. Computing device 750 may include computing device 200.

Computing device 700 includes a processor 702, memory 704, a storage device 706, a high-speed interface 708 connecting to memory 704 and high-speed expansion ports 710, and a low speed interface 712 connecting to low speed bus 714 and storage device 706. Each of the components 702, 704, 706, 708, 710, and 712, are interconnected using various busses, and may be mounted on a common motherboard or in other manners as appropriate. The processor 702 can process instructions for execution within the computing device 700, including instructions stored in the memory 704 or on the storage device 706 to display graphical information for a graphical user interface (GUI) on an external input/output device, such as display 716 coupled to high speed interface 708. In other implementations, multiple processors and/or multiple buses may be used, as appropriate, along with multiple memories and types of memory. Also, multiple computing devices 700 may be connected, with each device providing portions of the necessary operations (e.g., as a server bank, a group of blade servers, or a multi-processor system, etc.).

The memory 704 stores information within the computing device 700. In one implementation, the memory 704 includes a volatile memory unit or units. In another implementation, the memory 704 includes a non-volatile memory unit or units. The memory 704 may also be another form of computer-readable medium, such as a magnetic or optical disk.

The storage device 706 is configured to provide mass storage for the computing device 700. In one implementation, the storage device 706 may be or may contain a computer-readable medium, such as a floppy disk device, a hard disk device, an optical disk device, or a tape device, a flash memory or other similar solid state memory device, or an array of devices, including devices in a storage area network or other configurations. A computer program product can be tangibly embodied in an information carrier. The computer program product may also contain (e.g., store) instructions that, when executed, perform one or more methods, such as those described above. The information



carrier is a computer- or machine-readable medium, such as the memory 704, the storage device 706, or memory on processor 702.

The high speed controller 708 manages bandwidth-intensive operations for the computing device 700, while the low speed controller 712 manages lower bandwidth-intensive operations. Such allocation of functions is exemplary only. In one implementation, the high-speed controller 708 is coupled to memory 704, display 716 (e.g., through a graphics processor or accelerator), and to high-speed expansion ports 710, which may accept various expansion cards (not shown). In the implementation, low-speed controller 712 is coupled to storage device 706 and low-speed expansion port 714. The low-speed expansion port, which may include various communication ports (e.g., USB, Bluetooth, Ethernet, wireless Ethernet) may be coupled to one or more input/output devices, such as a keyboard, a pointing device, a scanner, or a networking device such as a switch or router, e.g., through a network adapter.

The computing device 700 may be implemented in a number of different forms, as shown in the figure. For example, computing device 700 may be implemented as a standard server 720, or multiple times in a group of such servers. Computing device 700 may also be implemented as part of a rack server system 724. In addition, computing device 700 may be implemented in a personal computer such as a laptop computer 722. Alternatively, components from computing device 700 may be combined with other components in a mobile device (not shown), such as device 750. Each of such devices may contain one or more of computing device 700, 750, and an entire system may be made up of multiple computing devices 700, 750 communicating with each other.

Computing device 750 includes a processor 752, memory 764, an input/output (I/O) device such as a display 754, a communication interface 766, and a transceiver 768, among other components. The device 750 may also be provided with a storage device, such as a micro-drive or other device, to provide additional storage. Each of the components 750, 752, 764, 754, 766, and 768, are interconnected using various buses, and several of the components may be mounted on a common motherboard or in other manners as appropriate.

The processor 752 can execute instructions within the computing device 750, including instructions stored in the memory 764. The processor may be implemented as a chipset of chips that include separate and multiple analog and digital processors. The processor may provide, for example, for coordination of the other components of the device 750, such as control of user interfaces, applications run by device 750, and wireless communication by device 750.

Processor 752 may communicate with a user through control interface 758 and display interface 756 coupled to a display 754. The display 754 may be, for example, a TFT LCD (Thin-Film-Transistor Liquid Crystal Display) or an OLED (Organic Light Emitting Diode) display, or other appropriate display technology. The display interface 756 may comprise appropriate circuitry for driving the display 754 to present graphical and other information to a user. The control interface 758 may receive commands from a user and convert them for submission to the processor 752. In addition, an external interface 762 may be provide in communication with processor 752, so as to enable near area communication of device 750 with other devices. External interface 762 may provide, for example, for wired commu-

nication in some implementations, or for wireless communication in other implementations, and multiple interfaces may also be used.

The memory 764 stores information within the computing device 750. The memory 764 can be implemented as one or more of a computer-readable medium or media, a volatile memory unit or units, or a non-volatile memory unit or units. Expansion memory 774 may also be provided and connected to device 750 through expansion interface 772, which may include, for example, a SIMM (Single In Line Memory Module) card interface. Such expansion memory 774 may provide extra storage space for device 750, or may also store applications or other information for device 750. Specifically, expansion memory 774 may include instructions to carry out or supplement the processes described above, and may include secure information also. Thus, for example, expansion memory 774 may be provide as a security module for device 750, and may be programmed with instructions that permit secure use of device 750. In addition, secure applications may be provided via the SIMM cards, along with additional information, such as placing identifying information on the SIMM card in a non-hackable manner.

The memory may include, for example, flash memory and/or NVRAM memory, as discussed below. In one implementation, a computer program product is tangibly embodied in an information carrier. The computer program product contains instructions that, when executed, perform one or more methods, such as those described above. The information carrier is a computer- or machine-readable medium, such as the memory 764, expansion memory 774, or memory on processor 752, that may be received, for example, over transceiver 768 or external interface 762.

Device 750 may communicate wirelessly through communication interface 766, which may include digital signal processing circuitry where necessary. Communication interface 766 may provide for communications under various modes or protocols, such as GSM voice calls, SMS, EMS, or MMS messaging, CDMA, TDMA, PDC, WCDMA, CDMA2000, or GPRS, among others. Such communication may occur, for example, through radio-frequency transceiver 768. In addition, short-range communication may occur, such as using a Bluetooth, WiFi, or other such transceiver (not shown). In addition, GPS (Global Positioning System) receiver module 770 may provide additional navigation- and location-related wireless data to device 750, which may be used as appropriate by applications running on device 750.

Device 750 may also communicate audibly using audio codec 760, which may receive spoken information from a user and convert the spoken information to usable digital information. Audio codec 760 may likewise generate audible sound for a user, such as through a speaker, e.g., in a handset of device 750. Such sound may include sound from voice telephone calls, may include recorded sound (e.g., voice messages, music files, etc.) and may also include sound generated by applications operating on device 750.

The computing device 750 may be implemented in a number of different forms, as shown in the figure. For example, computing device 750 may be implemented as a cellular telephone 780. Computing device 750 may also be implemented as part of a smart phone 782, personal digital assistant, or other similar mobile device.

According to an example embodiment, the systems and methods described above provide a device (e.g., user device 105, servers 125, 130 and computing device 750) configured to trigger search request(s) may have, for example, the most up-to-date unified search metadata such that the device

queries the unified search metadata locally stored. According to another example embodiment, the systems and methods described above provide a device (e.g., user device **105**, servers **125**, **130** and computing device **750**) configured to trigger search request(s) (which can be protocol specific depending on the storage device to be searched) upon a determination that the device does not have all of the most up-to-date unified search metadata so the device generates the search request(s) to update the unified search metadata.

According to still another example embodiment, the systems and methods described above provide a user device (e.g., user device **105**, servers **125**, **130** and computing device **750**) configured to initiate a unified search, such that one or more search requests are generated at a different device other than the user device. According to still another example embodiment, the systems and methods described above provide a device (e.g., user device **105**, servers **125**, **130** and computing device **750**) configured to trigger a search request(s) (which can be protocol specific depending on the device) does an initial result view based on the locally stored unified search metadata and then updates the result view as results are received in response to the individual search requests.

According to still another example embodiment, the systems and methods described above unified search metadata is created based on metadata asynchronously pushed to the device creating and storing the unified search metadata. According to still another example embodiment, the systems and methods described above unified search metadata is created based on metadata pulled, in response to requests, to the device creating and storing the unified search metadata.

Some of the above example embodiments are described as processes or methods depicted as flowcharts. Although the flowcharts describe the operations as sequential processes, many of the operations may be performed in parallel, concurrently or simultaneously. In addition, the order of operations may be re-arranged. The processes may be terminated when their operations are completed, but may also have additional steps not included in the figure. The processes may correspond to methods, functions, procedures, subroutines, subprograms, etc.

Methods discussed above, some of which are illustrated by the flow charts, may be implemented by hardware, software, firmware, middleware, microcode, hardware description languages, or any combination thereof. When implemented in software, firmware, middleware or microcode, the program code or code segments to perform the necessary tasks may be stored in a machine or computer readable medium such as a storage medium. A processor(s) may perform the necessary tasks.

Specific structural and functional details disclosed herein are merely representative for purposes of describing example embodiments. Example embodiments may, however, be embodied in many alternate forms and should not be construed as limited to only the embodiments set forth herein.

It will be understood that, although the terms first, second, etc. may be used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first element could be termed a second element, and, similarly, a second element could be termed a first element, without departing from the scope of example embodiments. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

It will be understood that when an element is referred to as being “connected” or “coupled” to another element, it can be directly connected or coupled to the other element or intervening elements may be present. In contrast, when an element is referred to as being “directly connected” or “directly coupled” to another element, there are no intervening elements present. Other words used to describe the relationship between elements should be interpreted in a like fashion (e.g., “between” versus “directly between,” “adjacent” versus “directly adjacent,” etc.).

The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of example embodiments. As used herein, the singular forms “a,” “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises,” “comprising,” “includes” and/or “including,” when used herein, specify the presence of stated features, integers, steps, operations, elements and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components and/or groups thereof.

It should also be noted that in some alternative implementations, the functions/acts noted may occur out of the order noted in the figures. For example, two figures shown in succession may in fact be executed concurrently or may sometimes be executed in the reverse order, depending upon the functionality/acts involved.

Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which example embodiments belong. It will be further understood that terms, e.g., those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

Portions of the above example embodiments and corresponding detailed description are presented in terms of software, or algorithms and symbolic representations of operation on data bits within a computer memory. These descriptions and representations are the ones by which those of ordinary skill in the art effectively convey the substance of their work to others of ordinary skill in the art. An algorithm, as the term is used here, and as it is used generally, is conceived to be a self-consistent sequence of steps leading to a desired result. The steps are those requiring physical manipulations of physical quantities. Usually, though not necessarily, these quantities take the form of optical, electrical, or magnetic signals capable of being stored, transferred, combined, compared, and otherwise manipulated. It has proven convenient at times, principally for reasons of common usage, to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like.

In the above illustrative embodiments, reference to acts and symbolic representations of operations (e.g., in the form of flowcharts) that may be implemented as program modules or functional processes include routines, programs, objects, components, data structures, etc., that perform particular tasks or implement particular abstract data types and may be described and/or implemented using existing hardware at existing structural elements. Such existing hardware may include one or more Central Processing Units (CPUs), digital signal processors (DSPs), application-specific-integrated-circuits, field programmable gate arrays (FPGAs) computers or the like.

It should be borne in mind, however, that all of these and similar terms are to be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities. Unless specifically stated otherwise, or as is apparent from the discussion, terms such as “processing” or “computing” or “calculating” or “determining” or “displaying” or the like, refer to the action and processes of a computer system, or similar electronic computing device, that manipulates and transforms data represented as physical, electronic quantities within the computer system’s registers and memories into other data similarly represented as physical quantities within the computer system memories or registers or other such information storage, transmission or display devices.

Note also that the software implemented aspects of the example embodiments are typically encoded on some form of program storage medium or implemented over some type of transmission medium. The program storage medium may be magnetic (e.g., a floppy disk or a hard drive) or optical (e.g., a compact disk read only memory, or “CD ROM”), and may be read only or random access. Similarly, the transmission medium may be twisted wire pairs, coaxial cable, optical fiber, or some other suitable transmission medium known to the art. The example embodiments not limited by these aspects of any given implementation.

What is claimed is:

1. A user device including a processor, the user device comprising:
  - a memory including code segments that when executed by the processor cause the processor to:
    - generate a search parameter;
    - generate a first search metadata based on data stored on the user device and the search parameter, the first search metadata representing the data stored on the user device;
    - generate a search request based on the search parameter, the search request and the search parameter initiated through a single action by a user of the user device;
    - transmit the search request to at least one remote data storage resource associated with the user of the user device, the at least one remote data storage resource being configured as a file hosting service;
    - receive a second search metadata from the at least one remote data storage resource, the second search metadata representing data stored in the at least one remote data storage resource, the data being associated with the user of the user device; and
    - generate a unified search metadata including the first search metadata and the second search metadata.
2. The user device according to claim 1, wherein generating the search request includes:
  - determining a protocol associated with the at least one remote data storage resource; and
  - generating the search request for the at least one remote data storage resource using the associated protocol.
3. The user device according to claim 1, wherein the memory further includes code segments that when executed by the processor causes the processor to:
  - generate a second search request, the second search request including a request for metadata changes, the metadata changes being based on data changes over a time period;
  - transmit the second search request to the at least one remote data storage resource;
  - receive search metadata changes based on the second search request; and

update the unified search metadata based on the received search metadata changes.

4. The user device according to claim 1, wherein the memory further includes code segments that when executed by the processor causes the processor to:
  - synchronize metadata between the user device and the at least one remote data storage resource; and
  - update the unified search metadata using the synchronized metadata.
5. The user device according to claim 1, wherein the memory further includes code segments that when executed by the processor causes the processor to:
  - synchronize metadata between the user device and the at least one remote data storage resource; and
  - update the unified search metadata using the synchronized metadata, wherein the synchronized metadata only includes data associated with the second search metadata.
6. The user device according to claim 1, wherein the at least one remote data storage resource includes two remote data storage resources each having a different associated user credential for the user of the user device.
7. A server comprising:
  - a processor configured to receive user device metadata and a search parameter from a user device, the user device metadata representing data that is associated with a user of the user device stored on the user device; and
  - a memory including code segments that when executed by the processor cause the processor to:
    - generate first search metadata based on the received user device metadata and the search parameter;
    - generate second search metadata based on data stored in the memory that is associated with the user of the user device and the search parameters, the second metadata representing data stored in the memory that is associated with the user of the user device;
    - generate a search request based on the search parameter, the search request and the search parameter initiated through a single action by the user of the user device;
    - transmit the search request to a remote data storage resource that is associated with the user of the user device, the remote data storage resource being configured as a file hosting service associated with the user device;
    - receive third search metadata, in response to the search request, from the remote data storage resource, the third search metadata representing data stored at the remote data storage resource that is associated with the user of the user device;
    - generate unified search metadata including the first search metadata, the second search metadata, and the third search metadata; and
    - transmit the unified search metadata to the user device.
8. The server of claim 7, wherein the processor further receives update metadata from the user device, the update metadata being based on the unified search metadata,
  - generate delta unified search metadata based on the update metadata, and
  - transmit the delta unified search metadata to the user device.
9. The server of claim 7, wherein the processor further receives update metadata from the remote data storage resource, the update metadata being based on the search request,

17

generate delta unified search metadata based on the update metadata, and transmit the delta unified search metadata to the user device.

10. The server according to claim 7, wherein generating the search request includes, determining a protocol associated with the remote data storage resource, and generating the search request for the remote data storage resource using the associated protocol.

11. The server according to claim 7, wherein the memory further includes code segments that when executed by the processor causes the processor to:

synchronize metadata between the user device and the remote data storage resource;

update the unified search metadata using the synchronized metadata; and

transmit the updated unified search metadata to the user device.

12. The server according to claim 7, wherein the at least one remote data storage resource includes two remote data storage resources each having a different associated user credential.

13. A method comprising:

generating a search parameter;

generating a first search metadata based on data stored on a user device and the search parameter, the first search metadata representing the data stored on the user device;

generating a search request based on the search parameter, the search request and the search parameter initiated through a single action by a user of the user device; transmitting the search request to at least one remote data storage resource associated with the user of the user device, the at least one remote data storage resource being configured as a file hosting service;

receiving a second search metadata from the at least one remote data storage resource, the second search metadata representing data stored in the at least one remote data storage resource, the data being associated with the user of the user device; and

18

generating a unified search metadata including the first search metadata and the second search metadata.

14. The method according to claim 13, wherein generating the search request includes:

determining a protocol associated with the at least one remote data storage resource; and

generating the search request for the at least one remote data storage resource using the associated protocol.

15. The method according to claim 13, further comprising:

generating a second search request, the second search request including a request for metadata changes, the metadata changes being based on data changes over a time period;

transmitting the second search request to the at least one remote data storage resource;

receiving search metadata changes based on the second search request; and

updating the unified search metadata based on the received search metadata changes.

16. The method according to claim 13, further comprising:

synchronizing metadata between the user device and the at least one remote data storage resource; and

updating the unified search metadata using the synchronized metadata.

17. The method according to claim 13, further comprising:

synchronizing metadata between the user device and the at least one remote data storage resource; and

updating the unified search metadata using the synchronized metadata, wherein the synchronized metadata only includes data associated with the second search metadata.

18. The method according to claim 13, wherein the at least one-remote data storage resource includes two remote data storage resources each having a different associated user credential for the user of the user device.

\* \* \* \* \*