

US009531934B2

(12) **United States Patent**
Ma et al.

(10) **Patent No.:** **US 9,531,934 B2**
(45) **Date of Patent:** ***Dec. 27, 2016**

(54) **PHOTOGRAPHING DEVICE WITH
ROTATABLE ELECTRICAL CONNECTION
PORTION**

(58) **Field of Classification Search**

CPC H04N 5/2251-5/2254; H04N 5/2258;
H04N 5/332; G08B 13/19617-13/19632

See application file for complete search history.

(71) Applicant: **VIVOTEK INC.**, New Taipei (TW)

(72) Inventors: **Shyh-Yih Ma**, New Taipei (TW);
Jen-Chih Wu, New Taipei (TW);
ChaoTan Huang, New Taipei (TW)

(56) **References Cited**

U.S. PATENT DOCUMENTS

9,332,168 B2 * 5/2016 Ma H04N 5/2258
2011/0085036 A1 * 4/2011 Kong H04N 5/2251
348/143

(73) Assignee: **VIVOTEK INC.**, New Taipei (TW)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(Continued)

This patent is subject to a terminal dis-
claimer.

FOREIGN PATENT DOCUMENTS

WO 2008079862 A1 7/2008

(21) Appl. No.: **15/080,218**

Primary Examiner — Dennis Hogue

(22) Filed: **Mar. 24, 2016**

(74) *Attorney, Agent, or Firm* — Maschoff Brennan

(65) **Prior Publication Data**

US 2016/0205303 A1 Jul. 14, 2016

Related U.S. Application Data

(63) Continuation of application No. 14/325,778, filed on
Jul. 8, 2014, now Pat. No. 9,332,168.

(57) **ABSTRACT**

A photographing device includes a main body, a first video capturing unit, a second video capturing unit and a rotatable electrical connection portion. The first video capturing unit is disposed on the main body, a center of a first video capturing range of the first video capturing unit is located on a first axis. The second video capturing unit is rotatable about the first axis to be pivoted on the main body, the second video capturing unit and the first axis are separated by a distance. A second video capturing range of the second video capturing unit overlaps the first axis. The rotatable electrical connection portion includes a first and a second connection component pivoted and connected to each other. The second video capturing unit is disposed on and connected to the first connection component. The second connection component is disposed on and connected to the main body.

(30) **Foreign Application Priority Data**

Aug. 7, 2013 (TW) 102128354 A

(51) **Int. Cl.**

H04N 5/225 (2006.01)


G08B 13/196 (2006.01)

H04N 5/33 (2006.01)

(52) **U.S. Cl.**

CPC **H04N 5/2258** (2013.01); **G08B 13/1963**
(2013.01); **H04N 5/2251** (2013.01); **H04N**
5/332 (2013.01)

7 Claims, 14 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0206604 A1* 8/2012 Jones H04N 5/2251
348/159
2012/0257064 A1* 10/2012 Kim G08B 13/19626
348/159

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 2E




FIG. 2F




FIG. 2G




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6

1

**PHOTOGRAPHING DEVICE WITH
ROTATABLE ELECTRICAL CONNECTION
PORTION**

CROSS-REFERENCE TO RELATED
APPLICATIONS

This application is a continuation application of U.S. patent application Ser. No. 14/325,778, filed on Jul. 8, 2014, which claims priority under 35 U.S.C. §119(a) on Patent Application No(s). 102128354 filed in Taiwan, R.O.C. on Aug. 7, 2013, the entire contents of which are hereby incorporated by reference.

BACKGROUND

Technical Field

The disclosure relates to a photographing device, and more particularly to a photographing device having multiple video capturing units.

Related Art

In photographing technology, some kinds of lens assembly, such as a fish-eye lens or a wide-angle lens, may capture a wider image than common lens assemblies. However, these kinds of images have disadvantages of distortion in periphery region, being hard to zoom-in and lower resolution. For example, when this kind of lens assembly is utilized in a surveillance camera and a user or a surveillance software observes or detects a suspicious object so that the user or the software wants to zoom-in a portion of the field of view, the image may be distorted and its resolution may be too low to show a clear image. Especially when a portion of the field of view in a periphery region thereof needs to be zoomed-in, the distortion and unclear of the image are getting worse.

Although some manufactures develop an auxiliary lens assembly for assisting the main lens assembly (the fish-eye lens or the wide-angle lens) to capture the image which needs to be zoomed-in, a part of the viewing angle of the auxiliary lens assembly may be obscured by the main lens assembly.

In prior art, Patent WO2008079862 discloses a feature that an auxiliary lens assembly disposed away from above the main lens assembly on a track such that the viewing angle of the auxiliary lens assembly may not be obscured by the main lens assembly. However, WO2008079862 does not disclose when the auxiliary lens assembly spins several revolutions, how to deal the problem that if cables were connected to the auxiliary lens assembly, the cables may be tangled, even being snapped.

SUMMARY

One aspect of the disclosure provides a photographing device comprising a main body, a first video capturing unit, a second video capturing unit and a rotatable electrical connection portion. The first video capturing unit is disposed on the main body, and a center of a first video capturing range of the first video capturing unit is substantially located on a first axis. The second video capturing unit is pivotally disposed on the main body for being rotatable about the first axis, the second video capturing unit and the first axis are separated by a distance, and a second video capturing range of the second video capturing unit overlaps at least a portion of the first axis. The rotatable electrical connection portion includes a first connection component and a second connection component that are pivoted and electrically connected

2

to each other. The second video capturing unit is disposed on and electrically connected to the first connection component, and the second connection component is disposed on and electrically connected to the main body.

Another aspect of the disclosure provides a photographing device comprising a main body, a first video capturing unit, a second video capturing unit, a first rotatable electrical connection portion and a second rotatable electrical connection portion. The first video capturing unit is disposed on the main body, and a center of a first video capturing range of the first video capturing unit is substantially located on a first axis. The second video capturing unit is pivotally disposed on the main body for being rotatable about the first axis, the second video capturing unit and the first axis are separated by a distance, and a second video capturing range of the second video capturing unit overlaps at least a portion of the first axis. The first rotatable electrical connection portion includes a first connection component and a second connection component that are pivoted and electrically connected to each other, and the first video capturing unit is disposed on and electrically connected to the first connection component. The second rotatable electrical connection portion includes a third connection component and a fourth connection component that are pivoted and electrically connected to each other. The second connection component is affixed and electrically connected to the third connection component, the second video capturing unit is disposed on and electrically connected to the second connection component or the third connection component, and the fourth connection component is disposed on and electrically connected to the main body. One of the first connection component and the second connection component comprises a brush, and the other one of the first connection component and the second connection component comprises a current collector. One of the third connection component and the fourth connection component comprises a brush, and the other one of the third connection component and the fourth connection component comprises a current collector.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will become more fully understood from the detailed description given hereinbelow and the accompanying drawings which are given by way of illustration only and thus are not limitative of the present invention and wherein:

FIG. 1A is a cross-sectional side view of a photographing device according to an embodiment of the disclosure;

FIG. 1B is a cross-sectional side view of the photographing device in FIG. 1A when a second video capturing unit rotates;

FIG. 2A is a cross-sectional side view of a connection assembly of the photographing device according to a first embodiment of the disclosure;

FIG. 2B is a cross-sectional side view of a connection assembly according to a second embodiment of the disclosure;

FIG. 2C is a cross-sectional side view of a connection assembly according to a third embodiment of the disclosure;

FIG. 2D is a cross-sectional side view of a connection assembly according to a fourth embodiment of the disclosure;

FIG. 2E is a cross-sectional side view of a connection assembly according to a fifth embodiment of the disclosure;

FIG. 2F is a cross-sectional side view of a connection assembly according to a sixth embodiment of the disclosure;

3

FIG. 2G is a cross-sectional side view of a connection assembly according to a seventh embodiment of the disclosure;

FIG. 3 is a cross-sectional side view of a photographing device according to an eighth embodiment of the disclosure;

FIG. 4A is a cross-sectional side view of a connection assembly of the photographing device in FIG. 3 according to a ninth embodiment of the disclosure;

FIG. 4B is a cross-sectional side view of a connection assembly according to a tenth embodiment of the disclosure;

FIG. 5 is a cross-sectional side view of a photographing device according to an eleventh embodiment of the disclosure; and

FIG. 6 is a cross-sectional side view of a photographing device according to a twelfth embodiment of the disclosure.

DETAILED DESCRIPTION

In the following detailed description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the disclosed embodiments. It will be apparent, however, that one or more embodiments may be practiced without these specific details. In other instances, well-known structures and devices are schematically shown in order to simplify the drawing.

Please refer to FIG. 1A, which is a cross-sectional side view of a photographing device 10 according to an embodiment of the disclosure. In this embodiment, the photographing device 10 comprises a main body 11, a first video capturing unit 121, a second video capturing unit 122, a holder 13, a main body 131, a first driving module 141, a second driving module 142, a connection assembly 15, a plurality of cables 16, a fixation bracket 17, an installation component 18 and a shield 19.

The first video capturing unit 121 is disposed on the main body 11. A center of a first video capturing range R1 of the first video capturing unit 121 is substantially located on a first axis L1. The second video capturing unit 122 is pivotally disposed on the main body 11 for being rotatable about the first axis L1, and a surface of a lens of the second video capturing unit 122 and the first axis L1 are separated by a distance D1, and the distance D1 is varied according to the position of the second video capturing unit 122. Consequently, the second video capturing unit 122 is located above the first video capturing unit 121 but not on the upright position of the first video capturing unit 121 such that when the second video capturing unit 122 captures an image below, the first video capturing unit 121 may not obscure, block or interfere with the image capturing by the second video capturing unit 122. Moreover, a second video capturing range R2 of the second video capturing unit 122 overlaps at least a portion of the first video capturing range R1, and images captured in the first video capturing range R1 and the second video capturing range R2 which are overlapped may be zoomed-in (enlarged) because of the image capturing by the second video capturing unit 122.

In this disclosure, a video capturing range is defined as a field of view where a video capturing unit may capture.

The holder 13 is pivotally disposed on the main body 11 for being rotatable about the first axis L1. The second video capturing unit 122 is pivotally disposed on the holder 13 for being rotatable about a second axis L2, and the second video capturing unit 122 is also pivotally disposed on the main body 11 through the holder 13 for being rotatable about the first axis L1. A direction of the first axis L1 is perpendicular to but not intersected with a direction of the second axis L2.

4

When the holder 13 rotates (i.e., spins) about the first axis L1 relative to the main body 11, the second video capturing unit 122 rotates about the first axis L1 along with the holder 13 relative to the main body 11. Please refer to FIG. 1B, which is a cross-sectional side view of the photographing device in FIG. 1A when a second video capturing unit rotates. The second video capturing unit 122 is capable of being rotatable about the second axis L2 relative to the holder 13. Furthermore, the rotation of second video capturing unit 122 also allows the second video capturing range R2 to overlap at least a portion of the first axis L1. The distance D1 in FIG. 1A is shortened to a distance D1'. Thus, take a center of an image captured by the first video capturing unit 121 as a center of a circle. A direction from the center to a circumference of the circle is defined as a radial orientation, another direction which is rotating about the center of the circle is defined as a rotational orientation, and the first axis L1 penetrates through the center of the circle. The second video capturing unit 122 is capable of being rotatable about the first axis L1 to capture each and every image captured by the first video capturing unit 121 in every rotational orientation. The second video capturing unit 122 is capable of being rotatable (being tilting) about the second axis L2 to capture every image from every radial orientation. As a result, the second video capturing unit 122 is capable of capturing each and every image captured by the first video capturing unit 121 and there is no any blind spot in the image captured by the second video capturing unit 122.

The first driving module 141 is disposed on the main body 11 and capable of driving the second video capturing unit 122 to rotate (i.e., spin) about the first axis L1. The second driving module 142 is capable of driving the second video capturing unit 122 to rotate (i.e., tilt or pivot) about the second axis L2. The first driving module 141 may also drive the holder 13 to rotate (spin) about first axis L1 relative to the main body 11 so as to drive the second video capturing unit 122 to rotate about the first axis L1 relative to the main body 11 as well.

The connection assembly 15 is located on the first axis L1. The first video capturing unit 121 and the second video capturing unit 122 are electrically connected to the main body 11 via the connection assembly 15. The fixation bracket 17 is affixed to the connection assembly 15 and the main body 11 such that the first video capturing unit 121 may not rotate (i.e., spin) relative to the main body 11 (discussed further below). The installation component 18 is installed on the main body 11, and the main body 11 may be installed at a desired location, such as ceiling, wall or table, through the installation component 18. The shield 19 is disposed on the main body 11 and covers the first video capturing unit 121, the second video capturing unit 122, the holder 13, the first driving module 141, the second driving module 142, the connection assembly 15, the plurality of cables 16 and the fixation bracket 17.

In this embodiment, the first video capturing range R1 is greater than the second video capturing range R2 which may be varied. The first video capturing unit 121 may comprise a fish-eye lens or a wide-angle lens. The second video capturing unit 122 is capable of panning, tilting and zooming (i.e., PTZ). Thus, the photographing device 10 in this disclosure may utilize the first video capturing unit 121 to capture a panorama image or a wide-angle image. When a portion of this panorama or wide-angle image needs to be zoomed-in (i.e., being magnified), the first driving module 141 is utilized to drive the second video capturing unit 122 to rotate (i.e., spin) about the first axis L1 to the position corresponding to the portion of the image along the rota-

tional orientation. Also, the second driving module 142 is utilized to drive the second video capturing unit 122 to rotate (i.e., tilt) about the second axis L2 to the position corresponding to the portion of the image along the radial orientation. As a result, the target image (the portion of the image needs to be magnified) is located within a center portion of the second video capturing range R2 of the second video capturing unit 122. Then, the second video capturing unit 122 performs zoom-in, and therefore the captured image becomes the desired image (the image which is desired to be magnified). When the second video capturing range R2 is reduced, the image which the second video capturing unit 122 captures is magnified; when the second video capturing range R2 is increased, the image which the second video capturing unit 122 captures is minified.

Please refer to FIG. 2A, which is a cross-sectional side view of a connection assembly 15a of the photographing device 10 according to a first embodiment of the disclosure. In this embodiment, the connection assembly 15a includes a rotatable electrical connection portion 150. The rotatable electrical connection portion 150 includes a first connection component 151 and a second connection component 152 that are pivoted and electrically to each other. The first connection component 151 is pivotally disposed on the second connection component 152 for being rotatable about the first axis L1. The second video capturing unit 122 is disposed on and electrically connected to the first connection component 151. The second connection component 152 is disposed on and electrically connected to the main body 11. The first connection component 151 includes a first through hole 151a, and the second connection component 152 includes a second through hole 152a. The cables 16 penetrate through the first through hole 151a and the second through hole 152a in sequence. One end of the cable 16 is electrically connected to the first video capturing unit 121, and the other end of the cable 16 is electrically connected to the main body 11. The connection assembly 15a further comprises a housing which is affixed to the second connection component 152, and the fixation bracket 17 is affixed to the housing of the connection assembly 15a. Although the cable 16 is not in direct contact with the connection assembly 15a, the second connection component 152 which is fixed by the fixation bracket 17 prevents the connection assembly 15a from detaching to fall. However, the disclosure is no limited to the above-mentioned fixation of the connection assembly 15a and the fixation bracket 17.

The first connection component 151 comprises a plurality of brushes 151b, and the second connection component 152 comprises a plurality of current collectors 152b. Some of the cables 161 electrically connected to first connection component 151 and second video capturing unit 122 are electrically connected to the brushes 151b of the first connection component 151, respectively. Some other cables 162 electrically connected to the second connection component 152 and the main body 11 are electrically connected to the current collector 152b of the second connection component 152, respectively. The first connection component 151 may rotate (i.e., spin) about the first axis L1 along with the second video capturing unit 122. The first connection component 151 and the second connection component 152 are in electrical contact with each other via the brushes 151b and the current collector 152b, such that the first connection component 151 may still be electrically connected to the second connection component 152 when spinning along with the second video capturing unit 122 about the first axis L1. By the above-mentioned configuration, the first video capturing unit 121 is electrically connected to the main body

11 via the cables 16 penetrating through the first through hole 151a of the first connection component 151 and the second through hole 152a of the second connection component 152. The second video capturing unit 122 is electrically connected to the main body 11 via the electrical connections of the brushes 151b of the first connection component 151 and the current collectors 152b of the second connection component 152. The second driving module 142 in FIG. 1A is electrically connected to the main body 11 via the similar route of the second video capturing unit 122.

Please refer to FIG. 2B, which is a cross-sectional side view of a connection assembly 15b according to a second embodiment of the disclosure. In addition to utilizing connection assembly 15a shown in FIG. 2A, the photographing device 10 may utilize a connection assembly 15b in this embodiment. The first connection component 151 of the connection assembly 15b includes four brushes 151b, and the second connection component 152 includes four current collectors 152b. Two of the current collectors 152b are provided for two of the cables 161. A cable 16a1 of the cables 161 located between the main body 11 and the connection assembly 15b is electrically connected to a current collector 152b1 via the second through hole 152a of the second connection component 152. A cable 16a2 of the cables 161 is electrically connected to a current collector 152b2 via the second through hole 152a of the second connection component 152. A cable 16b1 of the cables 161 located between the first video capturing unit 121 and the connection assembly 15b is electrically connected to a current collector 152b1 via the second through hole 152a of the second connection component 152. A cable 16b2 of the cables 161 is also electrically connected to a current collector 152b2 of the second connection component 152 via the second through hole 152a of the second connection component 152. The above-mentioned method for connection is herein defined as an additional pair-of-current-collector-and-brush connection method. Since the second connection component 152 is fixed by the fixation bracket 17, the cables 16a1, 16a2, 16b1 and 16b2 and the first video capturing unit 121 may not rotated accordingly along with the rotation of the first connection component 151.

Please refer to FIG. 2C, which is a cross-sectional side view of a connection assembly 15c according to a third embodiment of the disclosure. In addition to utilizing the connection assembly 15a shown in FIG. 2A and the connection assembly 15b shown in FIG. 2B, the photographing device 10 may utilize the connection assembly 15c in this embodiment. The rotatable electrical connection portion 150 of the connection assembly 15c also includes a first connection component 151 and a second connection component 152 that are pivoted and electrically connected to each other. The first connection component 151 is pivotally disposed on the second connection component 152 for being rotatable about the first axis L1.

However, in this embodiment, the first connection component 151 comprises a plurality of current collectors 151c, and the second connection component 152 comprises a plurality of brushes 152c. Some of the cables 161 electrically connected to the first connection component 151 and the second video capturing unit 122 are electrically connected to the current collectors 151c of the first connection component 151 through interior wires of the first connection component 151, respectively. Some other cables 162 electrically connected to the second connection component 152 and the main body 11 are electrically connected to the brushes 152c of the second connection component 152, respectively. The first connection component 151 and the

second connection component **152** are in electrical contact with each other. Because the current collectors **151c** and the brushes **152c** are in direct contact with each other, when rotating about the first axis **L1** with the second video capturing unit **122**, the first connection component **151** is still electrically connected to the second connection component **152**. According to the above-mentioned configuration, the first video capturing unit **121** is electrically connected to the main body **11** via the cables **16** penetrating through the first through hole **151a** of the first connection component **151** and the second through hole **152a** of the second connection component **152**. Moreover, the second video capturing unit **122** is electrically connected to the main body **11** via the connection of the current collectors **151c** of the first connection component **151** and the brushes **152c** of the second connection component **152**. Since the cable **16** is not in contact with the connection assembly **15b**, both of the cables **16** and the first video capturing unit **121** may not be rotated accordingly with the rotation of the first connection component **151**. Moreover, the connection assembly **15b** may include a housing which is affixed to the second connection component **152**. The fixation bracket **17** is affixed to the housing of the connection assembly **15b**. The connection assembly **15b** may not be detached to fall because of the second connection component **152** being fixed by the fixation bracket **17**. However, the disclosure is not limited to the above-mentioned fixation of the connection assembly **15b** and the fixation bracket **17**.

Please refer to FIG. 2D, which is a cross-sectional side view of a connection assembly **15d** according to a fourth embodiment of the disclosure. In addition to utilizing the connection assemblies **15a**, **15b** and **15c**, the photographing device **10** in this disclosure may utilize the connection assembly **15d** in this embodiment. The connection assembly **15d** includes a first rotatable electrical connection portion **1501** and a second rotatable electrical connection portion **1502**. The first rotatable electrical connection portion **1501** includes a first connection component **151** and a second connection component **152** that are pivoted and electrically connected to each other. The second rotatable electrical connection portion **1502** includes a third connection component **153** and a fourth connection component **154** that are connected to each other. The third connection component **153** is pivotally disposed on the fourth connection component **154** for being rotatable about the first axis **L1**. The second connection component **152** is affixed and electrically connected to the third connection component **153**. The second connection component **152** is pivotally disposed on the first connection component **151** for being rotatable about the first axis **L1**. The first video capturing unit **121** is disposed on and electrically connected to the first connection component **151**. The second video capturing unit **122** is disposed on and electrically connected to the second connection component **152** or the third connection component **153**. The fourth connection component **154** is disposed on and electrically connected to the main body **11**.

The first connection component **151** comprises a plurality of current collectors **151c**. The second connection component **152** comprises a plurality of brushes **152c**. The third connection component **153** comprises a plurality of brushes **153b**. The fourth connection component **154** comprises a plurality of current collectors **154b**. Some of the cables **161** electrically connected to the first connection component **151** and the first video capturing unit **121** are electrically connected to the current collectors **151c** of the first connection component **151**, respectively. Two ends of some other cables **162** electrically connected to the second connection com-

ponent **152** and the third connection component **153** are electrically connected to the brushes **152c** of the second connection component **152** and the brushes **153b** of the third connection component **153**, respectively. Some other cables **163** electrically connected to the third connection component **153** (or the second connection component **152**) and the second video capturing unit **122** are electrically connected to the brushes **153b** of the third connection component **153** (or the brushes **152c** of the second connection component **152**), respectively. Some other cables **164** electrically connected to the fourth connection component **154** and the main body **11** are electrically connected to the current collector **154b** of the fourth connection component **154**.

The second connection component **152** and the third connection component **153** may rotate (i.e., spin) about first axis **L1** along with the rotation of the second video capturing unit **122**. Since the first connection component **151** is affixed to the main body **11** and the fourth connection component **154** is affixed to the fixation bracket **17** (not shown in FIG. 2D), the first connection component **151** and the fourth connection component **154** may not be rotated relative to the main body **11**. However, the disclosure is not limited to the above-mentioned fixation relationship. Moreover, the third connection component **153** and the fourth connection component **154** are in electrical contact with each other via the connection of the brushes **153b** and the current collectors **154b**, such that when the third connection component **153** rotates about the first axis **L1** along with the second video capturing unit **122**, the third connection component **153** may still be electrically connected to the fourth connection component **154**. The first connection component **151** and the second connection component **152** is in electrical contact with each other via the electrical connections of the current collectors **151c** and the brushes **152c**, such that when the second connection component **152** rotates about the first axis **L1** along with the second video capturing unit **122**, the second connection component **152** may still be electrically connected to the first connection component **151**.

According to the above-mentioned configuration, the first video capturing unit **121** is capable of being electrically connected to the main body **11** via the electrical connections of the current collectors **151c** of the first connection component **151** and the brushes **152c** of the second connection component **152**, the electrical connections of the second connection component **152** and the third connection component **153**, the electrical connections of the brushes **153b** of the third connection component **153** and the current collectors **154b** of the fourth connection component **154**, and the electrical connections of the fourth connection component **154** and the main body **11** in sequence. Furthermore, the second video capturing unit **122** is capable of being electrically connected to the main body **11** via the electrical connections of the brushes **153b** of the third connection component **153** and the current collectors **154b** of the fourth connection component **154**.

In addition to connecting each current collector **151c** of the first connection component **151** shown in FIGS. 2A, 2B and 2C (not shown in FIG. 2D), the cable **161** may directly connected to the main body **11**. Furthermore, under the circumstances that there are several through holes, the additional pair-of-current-collector-and-brush connection method described above may be also utilized to allow the cable **161** to connect the unused the current collector **151c** or allow the cable **164** to connect the unused current collector **154b**.

Please refer to FIG. 2E, which is a cross-sectional side view of a connection assembly **15e** according to a fifth

embodiment of the disclosure. In addition to utilizing the connection assemblies **15a**, **15b**, **15c** and **15d** in this disclosure, the photographing device **10** in this disclosure may utilize the connection assembly **15e** disclosed in this embodiment. The first rotatable electrical connection portion **1501** of the connection assembly **15e** includes a first connection component **151** and a second connection component **152** that are pivoted and electrically connected to each other. The second rotatable electrical connection portion **1502** includes a third connection component **153** and a fourth connection component **154** that are pivoted to and electrically connected to each other. The third connection component **153** is pivotally disposed on the fourth connection component **154** for being rotatable about the first axis L1. The second connection component **152** is affixed and electrically connected to the third connection component **153**. The second connection component **152** is pivotally disposed on the first connection component **151** for being rotatable about the first axis L1.

Furthermore, in this embodiment, the first connection component **151** comprises a plurality of current collectors **151c**. The second connection component **152** comprises a plurality of brushes **152c**. The third connection component **153** comprises a plurality of current collectors **153c**. The fourth connection component **154** comprises a plurality of brushes **154c**. Some of the cables **161** electrically connected to the first connection component **151** and the first video capturing unit **121** are electrically connected to the current collectors **151c** of the first connection component **151**, respectively. Two ends of some other cables **162** electrically connected to the second connection component **152** and the third connection component **153** are electrically connected to the brushes **152c** of the second connection component **152** and the current collectors **153c** of the third connection component **153**, respectively. Some other cables **163** electrically connected to the third connection component **153** and the second video capturing unit **122** are electrically connected to the current collectors **153c** of the third connection component **153**, respectively. In other embodiments, which are not shown in FIG. 2E, the second connection component **152** may be electrically connected to the third connection component **153**, and the cable **163** of the second video capturing unit **122** may be electrically connected to the second connection component **152**, and the cable **163** may be electrically connected to the third connection component **153** via the second connection component **152**. Alternatively, the cable **163** may be electrically connected to a node (i.e., joint) between the second connection component **152** and the third connection component **153**. Other cables **164** electrically connected to fourth connection component **154** and the main body **11** are electrically connected to the brushes **154c** of the fourth connection component **154**.

The third connection component **153** and the fourth connection component **154** are in electrical contact with each other via the connections of the current collectors **153c** and brushes **154c**, such that when the third connection component **153** rotates about the first axis L1 along with the second video capturing unit **122**, the third connection component **153** may still be electrically connected to the fourth connection component **154**. The first connection component **151** and the second connection component **152** are in electrical contact with each other via the connections of the current collectors **151c** and the brushes **152c**, such that when the second connection component **152** rotates about the first axis L1 along with the second video capturing unit **122**, the second connection component **152** may still be electrically connected to the first connection component **151**. Since the

first connection component **151** is affixed to the main body **131** and the fourth connection component **154** is affixed to the fixation bracket **17** (not shown in FIG. 2E), both of the first connection component **151** and the fourth connection component **154** may not be rotated with the main body **11**. However, the above-mentioned fixation relationship is not limited to the disclosure. Moreover, according to the above-mentioned configuration, the first video capturing unit **121** is capable of being electrically connected to the main body **11** via the electrical connections of the current collectors **151c** of the first connection component **151** and the brushes **152c** of the second connection component **152**, the electrical connections of the second connection component **152** and the third connection component **153**, the electrical connections of the current collectors **153c** of the third connection component **153** and the brushes **154c** of the fourth connection component **154**, and the electrical connections of the fourth connection component **154** and the main body **11** in sequence. The second video capturing unit **122** is capable of being electrically connected to the main body **11** via the current collectors **153c** of the third connection component **153** and the brushes **154c** of the fourth connection component **154**.

In addition to connecting the current collectors **151c** of the first connection component **151**, the cables **161** may still be directly and electrically connected to the main body **11** via the through holes shown in FIGS. 2A, 2B and 2C (not shown in FIG. 2E).

Please refer to FIG. 2F, which is a cross-sectional side view of a connection assembly **15f** according to a sixth embodiment of the disclosure. In addition to utilizing the above-mentioned connection assemblies **15**, **15b**, **15c**, **15d** and **15e**, the photographing device **10** may also utilize the connection assembly **15f** disclosed in this embodiment. The first rotatable electrical connection portion **1501** of the connection assembly **15f** includes a first connection component **151** and a second connection component **152** that are pivoted and electrically connected to each other. The second rotatable electrical connection portion **1502** includes a third connection component **153** and a fourth connection component **154** that are pivoted and electrically connected to each other. The third connection component **153** is pivotally disposed on the fourth connection component **154** for being rotatable about the first axis L1. The second connection component **152** is affixed and electrically connected to the third connection component **153**. The second connection component **152** is pivotally disposed on the first connection component **151** for being rotatable about the first axis L1.

In this embodiment, the first connection component **151** comprises a plurality of brushes **151b**. The second connection component **152** comprises a plurality of current collectors **152b**. The third connection component **153** comprises a plurality of current collectors **153c**. The fourth connection component **154** comprises a plurality of brushes **154c**. Some cables **161** electrically connected to the first connection component **151** and the first video capturing unit **121** are electrically connected to the brushes **151b** of the first connection component **151**, respectively. Two ends of some other cables **162** electrically connected to the second connection component **152** and the third connection component **153** are electrically connected to the current collectors **152b** of the second connection component **152** and the current collectors **153c** of the third connection component **153**, respectively. Some other cables **163** electrically connected to the third connection component **153** and the second video capturing unit **122** are electrically connected to the current collector **153c** of the third connection component **153**,

11

respectively. In other embodiments, which are not shown in FIG. 2F, the second connection component 152 may also be electrically connected to the third connection component 153, and the cables 163 connected to the second video capturing unit 122 are also electrically connected to second connection component 152, and the cables 163 are electrically connected to the third connection component 153 via the second connection component 152. Alternatively, the cables 163 may be electrically connected to nodes between the second connection component 152 and the third connection component 153. Some other cables 164 electrically connected to the fourth connection component 154 and the main body 11 are electrically connected to the brushes 154c of the fourth connection component 154, respectively.

The third connection component 153 and the fourth connection component 154 are in electrical contact with each other via the connections of the current collectors 153c and the brushes 154c, such that when the third connection component 153 rotates about the first axis L1 along with the second video capturing unit 122, the third connection component 153 may still be electrically connected to the fourth connection component 154. The first connection component 151 and the second connection component 152 are in electrical contact with each other via the connections of the brushes 151b and the current collectors 152b, such that when the second connection component 152 rotates about the first axis L1 with the second video capturing unit 122, the second connection component 152 may still be electrically connected to the first connection component 151. Since the first connection component 151 is affixed to the main body 131 as well as the fourth connection component 154 is affixed to the fixation bracket 17 (not shown in FIG. 2F), the first connection component 151 and the fourth connection component 154 may not be rotated relative to the main body 11. However, the disclosure is not limited to the above-mentioned fixation relationship. According to the above-mentioned configuration, the first video capturing unit 121 is capable of being electrically connected to the main body 11 via the electrical connections of the brushes 151b of the first connection component 151 and the current collectors 152b of the second connection component 152, the electrical connection of the second connection component 152 and the third connection component 153, the electrical connections of current collectors 153c of the third connection component 153 and the brushes 154c of the fourth connection component 154, and the electrical connection of the fourth connection component 154 and the main body 11 in sequence. Moreover, the second video capturing unit 122 is capable of being electrically connected to the main body 11 via the electrical connections of the current collectors 153c of the third connection component 153 and the brushes 154c of the fourth connection component 154.

In addition to connecting each brush 151b of the first connection component 151, the cable 161 may be electrically connected to the main body 11 via the through holes shown in FIGS. 2A, 2B and 2C (not shown in FIG. 2F).

Please refer to FIG. 2G, which is a cross-sectional side view of a connection assembly 15g according to a seventh embodiment of the disclosure. In addition to utilizing the connection assemblies 15a, 15b, 15c, 15d, 15e and 15f, the photographing device 10 in this disclosure may utilize the connection assembly 15g disclosed in this embodiment. The first rotatable electrical connection portion 1501 of the connection assembly 15g includes a first connection component 151 and a second connection component 152 that are pivoted and electrically connected to each other. The second rotatable electrical connection portion 1502 includes a third

12

connection component 153 and a fourth connection component 154 that are pivoted and electrically connected to each other. The third connection component 153 is pivotally disposed on the fourth connection component 154 for being rotatable about the first axis L1. The second connection component 152 is affixed and electrically connected to the third connection component 153. The second connection component 152 is pivotally disposed on the first connection component 151 for being rotatable about the first axis L1.

In this embodiment, the first connection component 151 comprises a plurality of brushes 151b. The second connection component 152 comprises a plurality of current collectors 152b. The third connection component 153 comprises a plurality of brushes 153b. The fourth connection component 154 comprises a plurality of current collectors 154b. Some cables 161 electrically connected to the first connection component 151 and the first video capturing unit 121 are electrically connected to the brush 151b of the first connection component 151, respectively. Two ends of some other cables 162 electrically connected to the second connection component 152 and the third connection component 153 are electrically connected to the current collector 152 of the second connection component 152 and the brushes 153b of the third connection component 153, respectively. Some other cables 163 electrically connected to the third connection component 153 and the second video capturing unit 122 are electrically connected to the brushes 153b of the third connection component 153. In other embodiments, which are not shown in FIG. 2G, the second connection component 152 may also be electrically connected to the third connection component 153, and some other cables 163 connected to the second video capturing unit 122 may also be electrically connected to the second connection component 152, and the second connection component 152 may also be electrically connected to the third connection component 153 via the second connection component 152. Alternatively, the cables 163 may be electrically connected to a node between the second connection component 152 and the third connection component 153. Some other cables 164 electrically connected to the fourth connection component 154 and the main body 11 are electrically connected to the current collectors 154b of the fourth connection component 154.

The third connection component 153 and the fourth connection component 154 are in electrical contact with each other via the electrical connections of the brushes 153b and the current collectors 154b, such that when the third connection component 153 rotates about the first axis L1 along with the second video capturing unit 122, the third connection component 153 may still be electrically connected to the fourth connection component 154. The first connection component 151 and the second connection component 152 are in electrical contact with each other via the electrical connections of the brushes 151b and the current collectors 152b, such that when the second connection component 152 rotates about the first axis L1 along with the second video capturing unit 122, the second connection component 152 may still be electrically connected to the first connection component 151. Since the first connection component 151 is affixed to the main body 131 and the fourth connection component 154 is affixed to the fixation bracket 17 (not shown in FIG. 2G), both of the first connection component 151 and the fourth connection component 154 may not be rotated relative to the main body 11. However, the disclosure is not limited to the above-mentioned fixation relationship. Moreover, according to the above-mentioned configuration, the first video capturing unit 121 is capable of

being electrically connected to the main body 11 via the electrical connections of the brush 151b of the first connection component 151 and the current collectors 152b of the second connection component 152, the electrical connection of the second connection component 152 and the third connection component 153, the electrical connections of the brushes 153b of the third connection component 153 and the current collectors 154b of the fourth connection component 154, and the electrical connection of the fourth connection component 154 and the main body 11 in sequence. Nevertheless, the second video capturing unit 122 is capable of being electrically connected to the main body 11 via the electrical connections of the brushes 153b of the third connection component 153 and the current collectors 154b of the fourth connection component 154.

In addition to connecting the above-mentioned brushes 151b of the first connection component 151, the cables 161 may be further directly connected to the main body 11 via the through holes shown in FIGS. 2A, 2B and 2C (not shown in FIG. 2G).

Please refer to FIG. 3, which is a cross-sectional side view of a photographing device 30 according to an eighth embodiment of the disclosure. In this embodiment, the photographing device 30 comprises a main body 31, a first video capturing unit 321, a second video capturing unit 322, a holder 33, a first driving module 341, a second driving module 342, a connection assembly 35, an installation component 38 and a shield 39. Moreover, the photographing device 30 further comprises an image processing module 37. However, the difference between this embodiment and the first embodiment shown in FIG. 1 is that the fixation bracket 17 is not used for fixing the first video capturing unit 321 and the main body 31 to allow them to not rotate relatively. The detailed operation will be described as follows.

In this embodiment, the first video capturing unit 321 is pivotally disposed on the main body 31 about the first axis L1. The connection assembly 35 is located on the first axis L1. The first video capturing unit 321 and the second video capturing unit 322 are electrically connected to each other via the connection assembly 35 and the main body 31. The image processing module 37 is electrically connected to the first video capturing unit 321 and the second video capturing unit 322 via the connection assembly 35. The image processing module 37 is capable of processing an image captured by the first video capturing unit 321 after rotation into a fixed-angle image (an image with fixed viewing angle).

The first video capturing unit 321 captures a fixed-angle baseline image at a baseline location, and let the coordinate of a certain point (x0, y0). After the first video capturing unit 321 rotates by an angle θ , let the coordinate of the certain point in a captured rotational image (x, y). The image processing module 37 utilizes a transformation matrix:

$$R = \begin{bmatrix} \cos\theta & -\sin\theta \\ \sin\theta & \cos\theta \end{bmatrix}$$

to calculate

$$\begin{bmatrix} x' \\ y' \end{bmatrix} = \begin{bmatrix} \cos\theta & -\sin\theta \\ \sin\theta & \cos\theta \end{bmatrix} \begin{bmatrix} x \\ y \end{bmatrix} = \begin{bmatrix} x0 \\ y0 \end{bmatrix}$$

wherein values of angle θ and each (x,y) are known.

Therefore, each (x0,y0) corresponding to (x,y) is obtained. Then, formula $x'=x \cos \theta - y \sin \theta = x0$ and $y'=x \sin \theta + y \cos \theta = y0$ are derived from the above-mentioned matrix. Therefore, after the rotational image is transformed by the image processing module 37, the viewing angle of the transformed rotational image is the same as the fixed-angle baseline image. No matter the rotational angles of the first video capturing unit 321 are, the viewing angle of the transformed image may still be maintained.

Please refer to FIG. 4A, which is a cross-sectional side view of a connection assembly 35a of the photographing device in FIG. 3 according to a ninth embodiment of the disclosure. In this embodiment, the connection assembly 35a comprises a rotatable electrical connection portion 350. The rotatable electrical connection portion 350 includes a first connection component 351 and a second connection component 352 that are pivoted and electrically connected to each other. The first connection component 351 is pivotally disposed on the second connection component 352 for being rotatable about the first axis L1. Both of the first video capturing unit 321 and the second video capturing unit 322 are disposed on and electrically connected to the first connection component 351. The second connection component 352 is disposed on and electrically connected to the main body 31.

The first connection component 351 comprises a plurality of brushes 351b, the second connection component 352 comprises a plurality of current collectors 352b. Some cables 361 electrically connected to first connection component 351 and the first video capturing unit 321 as well as electrically connected to the first connection component 351 and the second video capturing unit 322 are electrically connected to the brushes 351b of the first connection component 351. Some other cable 362 electrically connected to the second connection component 352 and the main body 31 are electrically connected to the current collectors 352b of the second connection component 352, respectively. The first connection component 351 rotates about the first axis L1 along with both of first video capturing unit 321 and the second video capturing unit 322. Since the second connection component 352 is affixed to the fixation bracket 17 (not shown in FIG. 4A), the second connection component 352 may not be rotated along with the rotation of the first connection component 351, which prevents the cable 362 from being snapped. The first connection component 351 and the second connection component 352 are in electrical contact with each other via the electrical connections of brushes 351b and the current collector 352b. Therefore, when the first connection component 351 rotates about the first axis L1 along with the first video capturing unit 321 and the second video capturing unit 322, the first connection component 351 may still be electrically connected to the second connection component 352. According to the above-mentioned configuration, both of the first video capturing unit 321 and the second video capturing unit 322 are electrically connected to the main body 31 via the electrical connections of the brushes 351b of the first connection component 351 and the current collectors 352b of the second connection component 352. The second driving module 342 in FIG. 3 is capable of being electrically connected to the main body 31 via the similar route of the first video capturing unit 321 and the second video capturing unit 322.

Please refer to FIG. 4B, which is a cross-sectional side view of a connection assembly 35b according to a tenth embodiment of the disclosure. In addition to utilizing the connection assembly 35a shown in FIG. 4A, the photographing device 30 may utilize the connection assembly 35b

15

disclosed in this embodiment. In this embodiment, the rotatable electrical connection portion **350** of the connection assembly **35b** also includes a first connection component **351** and a second connection component **352** that are pivoted and electrically connected to each other. The first connection component **351** is pivotally disposed on the second connection component **352** for being rotatable about the first axis **L1**. The second connection component **352** is affixed to the fixation bracket **17** (not shown in FIG. 4B), so that the second connection component **352** may not be rotated with the rotation of the first connection component **351**, which prevents the cable **362** from being snapped.

In this embodiment, the first connection component **351** comprises a plurality of current collectors **351c**. The second connection component **352** comprises a plurality of brushes **352c**. The cables **361** which are electrically connected to the first connection component **351** and the first video capturing unit **321** as well as electrically connected to the first connection component **351** and the second video capturing unit **322** are electrically connected to current collectors **351c** of the first connection component **351**, respectively. The other cables **362** which are electrically connected to the second connection component **352** and the main body **31** are electrically connected to the brushes **352c** of the second connection component **352**.

The first connection component **351** and the second connection component **352** are in electrical contact with each other via the electrical connections of the current collectors **351c** and the brushes **352c**. Therefore, when the first connection component **351** rotates about the first axis **L1** along with the first video capturing unit **321** and the second video capturing unit **322**, the first connection component **351** may still be electrically connected to the second connection component **352**. According to the above-mentioned configuration, the first video capturing unit **321** and the second video capturing unit **322** are electrically connected to the main body **31** via the electrical connections of the current collectors **351c** of the first connection component **351** and the brushes **352c** of the second connection component **352**.

In addition to utilizing the configuration shown in the FIGS. 4A and 4B, the connection assembly shown in FIG. 3 may utilize two similar rotatable electrical connection portions shown in FIGS. 2D through 2G which are needed to be slightly revised. Specifically, the cable **161** shown in FIG. 2D is altered to be connected to the second connection component **152** or the third connection component **153** and capable of rotating along with them. The cable **161** shown in FIG. 2E is altered to be connected to the second connection component **152** or the third connection component **153** and capable of rotating along with them. The cable **161** shown in FIG. 2F is altered to be connected to the second connection component **152** or the third connection component **153** and capable of rotating along with them. The cable **161** shown in FIG. 2G is altered to be connected to the second connection component **152** or the third connection component **153** and capable of rotating along with them.

The photographing device may comprise a hose or a tube for covering and supporting the above-mentioned cables which are connected to the main body or the first video capturing unit.

Rest of the operation of the photographing device **30** shown in FIG. 3 is similar to those of the photographing device **10** shown in FIGS. 1A and 1B, and therefore the description of the similar operation will not be repeated herein again.

16

Please refer to FIG. 5, which is a cross-sectional side view of a photographing device **50** according to an eleventh embodiment of the disclosure. The photographing device **50**, which is similar to the photographing device **30** shown in FIG. 3, comprises a main body **51**, a first video capturing unit **521**, a second video capturing unit **522**, a holder **53**, a first driving module **541**, a second driving module **542**, a connection assembly **55** and an image processing module **57**. The structure of the connection assembly **55** may be similar to those of the connection assemblies **35a** and **35b** shown in FIGS. 4A and 4B.

Moreover, the structure of the connection assembly **55** may also be similar to those of the connection assemblies **15a**, **15b**, **15c**, **15d**, **15e**, **15f** and **15g** shown in FIGS. 2A, 2B, 2C, 2D, 2E, 2F and 2G. Therefore, the image processing module **57** does not need to process to offset the image captured by the first video capturing unit **521** which is rotated.

In this embodiment, the photographing device **50** further comprises a weight balancer **59** which is disposed on the holder **53**. The holder **53** is pivotally disposed on the main body **51** for being rotatable about the first axis **L1**. The weight balancer **59** and the second video capturing unit **522** are located at two opposite sides of the first axis **L1**. The mass of the weight balancer **59** is substantially the same as that of the second video capturing unit **522**. The distance **D2** between the center of the mass of the weight balancer **59** and the first axis **L1** is substantially the same as the distance **D3** between the center of the mass of the second video capturing unit **522** and the first axis **L1**.

Please refer to FIG. 6, which is a cross-sectional side view of a photographing device **60** according to a twelfth embodiment of the disclosure. In this embodiment, the photographing device **60**, which is similar to the photographing device **50** shown in FIG. 5, comprises a main body **61**, a first video capturing unit **621**, a second video capturing unit **622**, a holder **63**, a first driving module **641**, a second driving module **642**, a connection assembly **65** and an image processing module **67**. The structure of the connection assembly **65** may be similar to those of the connection assemblies **35a** and **35b** shown in FIGS. 4A and 4B.

Moreover, the structure of connection assembly **65** may also be similar to those of the connection assemblies **15a**, **15b**, **15c**, **15d**, **15e**, **15f** and **15g** shown in FIGS. 2A, 2B, 2C, 2D, 2E, 2F and 2G, and therefore the image processing module **67** does not need to process to offset the image captured by the first video capturing unit **521** which is rotated.

Furthermore, the photographing device **60** comprises an infrared module **69** pivotally disposed on the holder **63** for being rotatable about the second axis **L2**. The holder **63** is pivotally disposed on the main body **61** for being rotatable about the first axis **L1**. The direction of the first axis **L1** is substantially perpendicular to the second axis **L2**. Also, the first axis **L1** is interested with the second axis **L2**. The infrared module **69** and second video capturing unit **622** are disposed on two opposite sides of the first axis **L1**. The mass of the infrared module **69** is substantially the same as the mass of the second video capturing unit **622**. The distance **D2** between the center of the mass of the infrared module **69** and the first axis **L1** is substantially equal to the distance **D3** between the center of the mass of the second video capturing unit **622** and the first axis **L1**.

To sum up, according to the photographing device of the disclosure, the center of the first video capturing range of the first video capturing unit is located at the first axis, the second video capturing unit rotates about the first axis, and

17

the second video capturing unit and the first axis are separated by a distance. Consequently, the second video capturing unit is located above the first video capturing unit but not on the upright position of the first video capturing unit, such that when the second video capturing unit captures an image below, the first video capturing unit may not obscure, block or interfere with the image capturing by the second video capturing unit. Thus, the image captured by the second video capturing unit does not have any blind spot.

The foregoing description of the exemplary embodiments of the disclosure has been presented only for the purposes of illustration and description and is not intended to be exhaustive or to limit the disclosure to the precise forms disclosed. Many modifications and variations are possible in light of the above teaching.

What is claimed is:

1. A photographing device, comprising:
 - a main body;
 - a first video capturing unit disposed on the main body, and a center of a first video capturing range of the first video capturing unit is substantially located on a first axis;
 - a second video capturing unit pivotally disposed on the main body for being rotatable about the first axis, the second video capturing unit and the first axis being separated by a distance, and a second video capturing range of the second video capturing unit overlapping at least a portion of the first axis;
 - a rotatable electrical connection portion including a first connection component and a second connection component that are pivoted and electrically connected to each other, the second video capturing unit being disposed on and electrically connected to the first connection component, and the second connection component being disposed on and electrically connected to the main body; and
 - a holder pivotally disposed on the main body for being rotatable about the first axis, the second video capturing unit being pivotally disposed on the holder for being rotatable about a second axis, and the second video capturing unit also being pivotally disposed on the main body through the holder for being rotatable about the first axis.
2. The photographing device according to claim 1, wherein a direction of the first axis is substantially perpendicular to a direction of the second axis.
3. The photographing device according to claim 1, further comprising a driving module disposed on the second video capturing unit for driving the second video capturing unit to rotate about the second axis.
4. A photographing device, comprising:
 - a main body;
 - a first video capturing unit disposed on the main body, and a center of a first video capturing range of the first video capturing unit is substantially located on a first axis;
 - a second video capturing unit pivotally disposed on the main body for being rotatable about the first axis, the

18

second video capturing unit and the first axis being separated by a distance, and a second video capturing range of the second video capturing unit overlapping at least a portion of the first axis;

- a rotatable electrical connection portion including a first connection component and a second connection component that are pivoted and electrically connected to each other, the second video capturing unit being disposed on and electrically connected to the first connection component, and the second connection component being disposed on and electrically connected to the main body; and
- a weight balancer pivotally disposed on the main body for being rotatable about the first axis, and the weight balancer and the second video capturing unit being located at two opposite sides of the first axis.

5. The photographing device according to claim 4, wherein a mass of the weight balancer is substantially equal to a mass of the second video capturing unit, and a distance between a center of the mass of the weight balancer and the first axis is substantially equal to a distance between a center of the mass of the second video capturing unit and the first axis.

6. A photographing device, comprising:
 - a main body;
 - a first video capturing unit disposed on the main body, and a center of a first video capturing range of the first video capturing unit is substantially located on a first axis;
 - a second video capturing unit pivotally disposed on the main body for being rotatable about the first axis, the second video capturing unit and the first axis being separated by a distance, and a second video capturing range of the second video capturing unit overlapping at least a portion of the first axis;
 - a rotatable electrical connection portion including a first connection component and a second connection component that are pivoted and electrically connected to each other, the second video capturing unit being disposed on and electrically connected to the first connection component, and the second connection component being disposed on and electrically connected to the main body; and
 - an infrared module pivotally disposed on the main body for being rotatable about the first axis, and the infrared module and the second video capturing unit are disposed on two opposite sides of the first axis.

7. The photographing device according to claim 6, wherein a mass of the infrared module is substantially equal to a mass of the second video capturing unit, and a distance between a center of the mass of the infrared module and the first axis is substantially equal to a distance between a center of the mass of the second video capturing unit and the first axis.

* * * * *