



US009543816B2

(12) **United States Patent**
Nakamura

(10) **Patent No.:** **US 9,543,816 B2**
(45) **Date of Patent:** **Jan. 10, 2017**

(54) **VIBRATION GENERATOR HAVING SWING UNIT, FRAME AND ELASTIC MEMBER**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **MINEBEA CO., LTD.**, Kitasaku-gun, Nagano (JP)

6,054,335 A * 4/2000 Sun H01S 5/18308
257/E27.12

(72) Inventor: **Manabu Nakamura**, Tokyo-to (JP)

7,671,493 B2 * 3/2010 Takashima et al. 310/15
8,269,379 B2 * 9/2012 Dong H02K 33/16
310/25

(73) Assignee: **MINEBEA CO., LTD.**, Kitasaku-gun (JP)

8,624,449 B2 * 1/2014 Kim H02K 33/18
310/25

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 356 days.

8,624,450 B2 * 1/2014 Dong H02K 33/16
310/15
2004/0169425 A1 * 9/2004 Aihara 310/15
2009/0267423 A1 * 10/2009 Kajiwara H02K 33/16
310/36
2010/0052474 A1 * 3/2010 Honma et al. 310/317

(21) Appl. No.: **13/891,656**

(Continued)

(22) Filed: **May 10, 2013**

FOREIGN PATENT DOCUMENTS

(65) **Prior Publication Data**

JP H11-214586 A 8/1999
JP 2000-021491 A 1/2000

US 2013/0313919 A1 Nov. 28, 2013

(Continued)

(30) **Foreign Application Priority Data**

OTHER PUBLICATIONS

May 22, 2012 (JP) 2012-116576

Mar. 22, 2016 Office Action issued in Japanese Patent Application No. 2012-116576.

(51) **Int. Cl.**

H02K 33/00 (2006.01)
H02K 33/16 (2006.01)
H02K 5/24 (2006.01)
B06B 1/04 (2006.01)
H02K 5/04 (2006.01)

Primary Examiner — Terrance Kenerly
Assistant Examiner — Rashad Johnson
(74) *Attorney, Agent, or Firm* — Oliff PLC

(52) **U.S. Cl.**

CPC **H02K 33/00** (2013.01); **H02K 33/16** (2013.01); **B06B 1/045** (2013.01); **H02K 5/04** (2013.01); **H02K 5/24** (2013.01)


(57) **ABSTRACT**

A vibrator includes a frame, a swing unit, and an elastic member. The swing unit is disposed within the frame and holds a magnet. The elastic member connects the swing unit and the frame. The swing unit is movable with respect to the frame while deforming the elastic member. The frame, the swing unit, and the elastic member are integrally molded with each other.

(58) **Field of Classification Search**

CPC H02K 33/00; H02K 5/04; H02K 5/24; B06B 1/045
USPC 310/15, 25, 91, 40 MM
See application file for complete search history.

2 Claims, 8 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2010/0213773 A1 8/2010 Dong et al.
 2011/0012441 A1* 1/2011 Oh B06B 1/045
 310/25
 2011/0101796 A1* 5/2011 Odajima et al. 310/25
 2011/0133577 A1* 6/2011 Lee 310/15
 2012/0108299 A1* 5/2012 Yang B06B 1/045
 455/567
 2012/0112565 A1* 5/2012 Lee H02K 33/16
 310/20
 2012/0169148 A1* 7/2012 Kim H02K 33/18
 310/25
 2012/0169151 A1* 7/2012 Dong H02K 33/16
 310/25
 2012/0187780 A1* 7/2012 Bang H02K 33/16
 310/25
 2012/0313459 A1* 12/2012 Zhang H02K 33/02
 310/25
 2013/0076178 A1* 3/2013 Kuroda et al. 310/81


2013/0099602 A1* 4/2013 Park H02K 33/16
 310/25
 2013/0193779 A1* 8/2013 Kuroda B06B 1/045
 310/15
 2013/0200732 A1* 8/2013 Jun H02K 33/00
 310/25
 2013/0229070 A1* 9/2013 Akanuma H02K 33/00
 310/25
 2013/0241321 A1* 9/2013 Akanuma H02K 5/24
 310/25
 2014/0056463 A1* 2/2014 Kim H04R 9/043
 381/398

FOREIGN PATENT DOCUMENTS


JP 2002-225067 A 8/2002
 JP 2004-261684 A 9/2004
 JP 2006-320887 A 11/2006
 JP A-2010-36131 2/2010
 JP 2010-094567 A 4/2010

* cited by examiner

FIG. 1 1



1 FIG.2






FIG. 4





FIG.5

80




FIG.6 101




FIG. 7






FIG. 8



1

VIBRATION GENERATOR HAVING SWING UNIT, FRAME AND ELASTIC MEMBER

This application is based on Japanese Patent Application No. 2012-116576 filed with the Japan Patent Office on May 22, 2012, the entire content of which is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to vibrators and vibration generators, and in particular to a vibrator capable of performing reciprocatory movement to generate vibration as well as to a vibration generator.

Description of the Related Art

A vibration generator that generates vibration by moving a vibrator is used. For example, a vibration generator that causes a vibrator having a magnet to perform a reciprocatory motion using a magnetic force is used.

The Document 1 listed below discloses a linear motor of a structure having a magnet as a moving unit within a frame unit as a stationary unit and a plate spring provided between the magnet and the frame unit to hold the magnet. In this linear motor, the magnet moves with respect to the frame unit by a coil unit disposed so as to sandwich the magnet from above and underneath being excited.

[Document 1] Japanese Patent Publication Laying-Open No. 2010-36131

In the meantime, the vibration generator as described in the Document 1 moves the magnet by urging the magnet by the plate spring. Accordingly, it is necessary to secure a relatively large space for the plate spring to deform. However, there is a limit to increase a size of the vibrator relative to the vibration generator, and it is difficult to increase a vibration amount. In other words, it is necessary to increase a size of the vibration generator itself in order to increase the vibration amount.

Further, the vibration generator as described in the Document 1 is configured by assembling the magnet, the plate spring, and the frame unit that are separate members from each other. Accordingly, the number of steps required in order to assemble the vibration generator is large, and a process for manufacturing the vibration generator becomes relatively complicated. Further, it is relatively difficult to ensure assembly accuracy, and variation in performance of vibration generators (individual variability) increases.

The present invention is made in order to address the above problems, and an object of the present invention is to provide a vibrator that can be easily and accurately assembled and provide a large vibration force relative to a size of the vibration generator, as well as a vibration generator.

SUMMARY OF THE INVENTION

In order to achieve the above object, according to one aspect of this invention, a vibrator is provided with: a frame; a swing unit disposed within the frame and for holding a magnet; and an elastic member connecting the swing unit and the frame, wherein the swing unit is movable with respect to the frame while deforming the elastic member, and the frame, the swing unit, and the elastic member are integrally molded with each other.

According to another aspect of this invention, a vibration generator is provided with: the vibrators described above; and a coil disposed so as to face toward the swing unit of the

2

vibrator, wherein the swing unit moves with respect to the frame according to excitation of the coil.

The foregoing and other objects, features, aspects and advantages of the present invention will become more apparent from the following detailed description of the present invention when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a plan view illustrating a vibration generator according to one embodiment of this invention.

FIG. 2 is a cross-sectional view taken along line A-A in FIG. 1.

FIG. 3 is a perspective view illustrating a structure of the vibration generator.

FIG. 4 is a perspective view illustrating a region of a weight where a groove is provided.

FIG. 5 is a perspective view illustrating an arm unit.

FIG. 6 is a plan view illustrating a vibration generator according to one modified example of this embodiment.

FIG. 7 is a perspective view illustrating an arm unit.

FIG. 8 is a perspective view illustrating a region of weight, where a groove is provided, of a vibration generator according to another modified example of this embodiment.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Hereinafter, a vibration generator according to one embodiment of this invention will be described.

The vibration generator has such a structure that a portion of a vibrator for holding a magnet is supported movably with respect to a different portion of the vibration generator. A coil is disposed near the magnet with a space from the magnet. The coil generates a magnetic field for changing at least one of a position and a posture of the magnet. The vibration generator generates a vibration force by the vibrator deforming according to excitation of the coil to cause the magnet to perform a reciprocatory motion. Specifically, the vibration generator is so-called linear type.

First Embodiment

FIG. 1 is a plan view illustrating the vibration generator according to the one embodiment of this invention. FIG. 2 is a cross-sectional view taken along line A-A in FIG. 1. FIG. 3 is a perspective view illustrating a structure of the vibration generator.

In order to facilitate understanding of a layout of components of a vibration generator 1, FIG. 1 shows a vibrator 50 and the like that are actually hidden behind a top plate 20 partially in solid lines. In FIG. 1, illustration of a flexible printed circuit (FPC: hereinafter also simply referred to as a circuit board) 10 is omitted except a part thereof.

In the following description, for vibration generator 1, there is a case in which a direction along an X axis in a coordinate system shown in FIG. 1 is referred to as a right-left direction (a positive direction along the X axis from the original point is the rightward direction). Further, there is a case in which a direction along a Y axis in the coordinate system shown in FIG. 1 is referred to as a front-back direction (a positive direction along the Y axis from the original point is the backward direction). Further, there is a case in which a direction along a Z axis in FIG. 2 (a vertical direction with respect to an XY plane in FIG. 1)

is referred to as an up-down direction (a positive direction along the Z axis from the original point is the upward direction).

[Overall Structure of Vibration Generator 1]

As illustrated in FIG. 3, vibration generator 1 generally includes circuit board 10, top plate 20, a bottom plate 30, a coil 40, and vibrator 50. As illustrated in FIG. 1, vibrator 50 in this embodiment includes a frame 55, a swing unit 60, and four arm units (one example of elastic members) 80 (80a, 80b, 80c, and 80d).

As will be described later, vibration generator 1 generates vibration by swing unit 60 swinging. Swing unit 60 swings in a manner moving mainly in the right-left direction with respect to a different region of vibration generator 1 including vibrator 50 such as frame 55. Specifically, in this embodiment, a swing direction of swing unit 60 is the right-left direction.

Vibration generator 1 as a whole is formed in a thin, substantial cuboid whose vertical dimension is relatively small. Vibration generator 1 is small such that external dimensions in the right-left direction and in the front-back direction are on the order of 10 millimeters to 20 millimeters. Vibration generator 1 has a box-shaped outline such that an upper surface and a lower surface of vibrator 50 having frame 55 enclosing a lateral circumference are covered by top plate 20 and bottom plate 30, respectively.

As illustrated in FIG. 3, vibrator 50 has a structure having swing unit 60 within frame 55. Frame 55 and swing unit 60 are connected via four arm units 80.

In this embodiment, frame 55 is formed in a rectangular and annular shape, for example, by bending one or more strip-shaped metal plates and the like. In other words, frame 55 has a quadrangular, hollow, and cylindrical shape, within which swing unit 60 is disposed. It should be noted that frame 55 may not be completely annular. For example, frame 55 can be partially discontinuous, or end portions of the one or more metal plates being partially overlapped with each other, so as to be formed annularly as a whole.

Swing unit 60 is formed substantially in a rectangular shape in a planar view. Swing unit 60 has a plate shape parallel to a horizontal plane (the XY plane in FIG. 1). Swing unit 60 is formed substantially in a rectangular shape whose sides are each parallel to the front-back direction or the right-left direction in the planar view except at four corners.

Swing unit 60 is disposed at a center portion of vibrator 50, that is, a center portion of vibration generator 1, in the planar view. As illustrated in FIG. 2, swing unit 60 is disposed substantially parallel to coil 40 and facing toward coil 40.

Top plate 20 is flat-plated, and in a rectangular shape that is substantially the same as that of an upper end portion of frame 55. Top plate 20 is disposed so as to be fitted in the upper end portion of frame 55. Bottom plate 30 is flat-plated, and in a rectangular shape that is substantially the same as that of a lower end portion of frame 55. Bottom plate 30 is disposed so as to be fitted in the lower end portion of frame 55. Top plate 20 and bottom plate 30 can be adhered or welded to frame 55.

In this embodiment, a cutout 35 is provided at a part of a short side of bottom plate 30. By providing cutout 35, an interior and an exterior of vibration generator 1 are communicated.

As illustrated in FIG. 2, circuit board 10 is configured such that a first portion 10a and a second portion 10b are connected to each other via a bent portion 10c. First portion 10a is provided with an electrode connected to coil 40.

Second portion 10b is provided with an electrode connected to a line for driving vibration generator 1. Bent portion 10c is configured to have a width that can pass through cutout 35. Circuit board 10 is disposed such that bent portion 10c is positioned in cutout 35, and that first portion 10a and second portion 10b sandwich bottom plate 30 from above and underneath. Using such flexible printed circuit 10 allows reducing the dimension of vibration generator 1 in the up-down direction as compared to a case in which a double-sided board is used. Further, since bottom plate 30 having a simple shape can be used, it is possible to reduce manufacturing cost of vibration generator 1. Since bottom plate 30 is provided with cutout 35, circuit board 10 may not stick out of a casing, and it is possible to ensure protection of circuit board 10.

Coil 40 is an air core coil configured by winding a conductive wire, and having a generally oval and flat plated shape. Specifically, coil 40 is a thin coil whose dimension in a direction of a winding axis is smaller than a dimension in a direction orthogonal to the direction of the winding axis. It should be noted that coil 40 can be configured by slicing a wound metallic foil, or by stacking sheet coils. Further, coil 40 can have a circular shape or a polygon shape such as a quadrangular shape in the planar view.

Coil 40 is disposed on first portion 10a of circuit board 10 such that the direction of the winding axis corresponds to the up-down direction. As illustrated in FIG. 1, coil 40 is disposed at the center portion of vibration generator 1 in the planar view so as to face toward swing unit 60 as will be described later. Coil 40 is connected to the electrode (not depicted) formed on first portion 10a of circuit board 10. It is possible to make coil 40 conductive by applying a current to the electrode (not depicted) formed on second portion 10b of circuit board 10 and exposed on an external surface of vibration generator 1.

As described above, swing unit 60 and coil 40 are covered by top plate 20, bottom plate 30, and frame 55. With this, it is possible to prevent a foreign matter such as dust from coming into vibration generator 1, and to keep vibration generator 1 operational. Further, since vibration generator 1 is surrounded by top plate 20, bottom plate 30, and frame 55 in a box-shaped manner, rigidity of vibration generator 1 itself increases. Therefore, it is possible to ensure that vibration generator 1 generates vibration. Further, vibration generator 1 becomes easy to be handled when installed to an external device and the like.

In this embodiment, frame 55 and top plate 20 are made of a soft magnetic body such as iron, for example. As having a structure of being surrounded by frame 55 and top plate 20, vibration generator 1 is insusceptible to a surrounding magnetic field and the like. Further, since a magnetic flux within vibration generator 1 may not easily leak outside, influences to external devices and circuits are prevented.

On the other hand, bottom plate 30 is made of a non-magnetic material. Bottom plate 30 is made of a non-magnetic metallic material such as non-magnetic stainless steel, for example. It should be noted that bottom plate 30 is not limited to that made of a metallic material, and can be made of a resin, for example. Further, frame 55 and top plate 20 are not limited to those made of a soft magnetic body, and can be made of a resin or a non-magnetic metallic material, for example.

[Detailed Structure of Vibrator 50]

As illustrated in FIG. 2, swing unit 60 includes a magnet 61, a back yoke 63, and a weight 65. Magnet 61 is a permanent magnet and disposed in substantial center of swing unit 60. Back yoke 63 is a soft magnetic body such as

iron, for example, and disposed on a top of magnet **61**. Weight **65** is disposed around magnet **61** and back yoke **63** so as to hold magnet **61** and back yoke **63**. Weight **65** is made of a metal having a relatively large specific gravity, for example.

In this embodiment, as magnet **61**, two magnets (magnets **61a**, **61b**) disposed respectively on right and left are provided. Magnet **61a** and magnet **61b** are configured to have polarities opposite from each other. Specifically, a direction of the magnetic pole of magnet **61a** with respect to coil **40** is opposite from that of magnet **61b**. It should be noted that, as magnet **61**, it is possible to provide a single magnet magnetized such that the magnetic directions with respect to coil **40** are different between the right side and the left side. For example, magnet **61** can be magnetized and polarized at a bottom side portion facing toward coil **40** such that the north pole and the south pole are opposite along the right-left direction. Further, three or more magnets **61** can be disposed.

As illustrated in FIG. 1, each arm unit **80** includes a weight joint portion **81**, a frame joint portion **83**, a beam portion **85**, and a gate portion **87**. Weight joint portion **81** is jointed to an outer circumferential surface of weight **65** out of swing unit **60**. Frame joint portion **83** is jointed to an inner side surface of frame **55**. Beam portion **85** connects between weight joint portion **81** and frame joint portion **83**. Gate portion **87** is formed on a side of weight joint portion **81**. Each arm unit **80** is integrally molded by an elastic resin, for example.

Beam portion **85** is a region of each arm unit **80** that mainly deflects when swing unit **60** moves with respect to frame **55**. Each arm unit **80** is disposed such that a longitudinal direction of corresponding beam portion **85** is substantially parallel to the Y axis direction. Specifically, beam portion **85** is formed such that its longitudinal direction corresponds to a direction vertical to the swing direction of swing unit **60**.

In this embodiment, a cross section perpendicular to the longitudinal direction of beam portion **85** (specifically, a cross section parallel to a ZX plane, hereinafter also simply referred to as the cross section of beam portion **85**) is rectangular. A short side of this cross section is substantially parallel to the swing direction of swing unit **60**.

Four arm units **80** are connected to four corners (right rear, right front, left front, and left rear) of swing unit **60**, respectively, such that swing unit **60** is supported in a well-balanced manner with respect to frame **55**. Arm unit **80a** is disposed at right rear of weight **65**. Arm unit **80b** is disposed at right front of weight **65**. Arm unit **80c** is disposed at left front of weight **65**. Arm unit **80d** is disposed at left rear of weight **65**.

Swing unit **60** has a shape symmetrical with respect both to a first plane and to a second plane. The first plane is a plane passing the center of swing unit **60** in the planar view and parallel to an YZ plane. The second plane is a plane passing the center of swing unit **60** and parallel to the ZX plane. Further, each of four arm units **80** is disposed at a position and in a posture both symmetrical with respect both to the first plane and to the second plane. Specifically, vibrator **50** is configured symmetrically with respect both to the first plane and to the second plane.

As illustrated in FIG. 1, grooves **67** (**67a**, **67b**, **67c**, and **67d**) are provided respectively in cutout portion **90** regions of weight **65** in which arm units **80** are disposed (joints connecting weight **65** to arm units **80**).

FIG. 4 is a perspective view illustrating the regions of weight **65** in which grooves **67** are provided.

Referring to FIG. 4, grooves **67** are provided such that their longitudinal directions correspond to a direction that is not parallel to the swing direction of swing unit **60** (here, mainly the X axis direction). Specifically, grooves **67** are provided such that their longitudinal directions correspond to the Z axis direction that is substantially perpendicular to the swing direction of swing unit **60**.

While grooves **67** are provided in this manner, arm units **80** are each provided with gate portion **87** projecting from weight joint portion **81** so as to be cut into corresponding grooves **67**. Specifically, a jointing surface between arm unit **80** and weight **65** is uneven along the direction vertical to the swing direction of swing unit **60**.

[Description of Manufacturing Method of Vibrator **50**]

In this embodiment, vibrator **50** is configured by frame **55**, swing unit **60** (magnet **61**, back yoke **63**, and weight **65**), and four arm units **80** that are integrally molded by insert molding. Vibrator **50** is manufactured in the following manner.

First, back yoke **63** and magnet **61** are applied to weight **65**. With this, swing unit **60** is configured. Further, frame **55** bent into a rectangular shape is prepared. Back yoke **63** and magnet **61** may be applied to each other by spot welding or adhesion, for example.

Next, frame **55** and swing unit **60** are set in a molding tool of vibrator **50**.

Then, a resin to form arm units **80** is injected into the molding tool. By removing the molding tool, vibrator **50** can be obtained.

It should be noted that back yoke **63** and magnet **61** can be applied to a portion of weight **65** after the integral molding.

As the resin used for arm units **80** and the like (the resin used in the integral molding), a silicon resin is used, for example. Alternatively, heat-resistant fluorine-based gum and the like can be used. By forming vibrator **50** using such gum, it is possible to improve heat resistance of vibration generator **1**. The elastic body is not limited to the above examples, and various types can be used.

As weight **65** is provided with grooves **67** as described above, the resin is injected using grooves **67** as gates when integrally molding vibrator **50**. Therefore, it is possible to further facilitate the molding.

[Description of Operation of Vibration Generator **1**]

In vibration generator **1**, swing unit **60** can be moved with respect to frame **55** while deforming beam portion **85** of arm unit **80**. Coil **40** generates a magnetic field for causing swing unit **60** to perform a reciprocatory motion with respect to frame **55**. Upon excitation of coil **40**, swing unit **60** moves with respect to frame **55** accordingly. Vibration generator **1** generates vibration by repeating the reciprocatory motion of swing unit **60**.

More specifically, when a current flows through coil **40**, coil **40** is excited, and a magnetic field is produced in the up-down direction. Upon production of the magnetic field, magnet **61** is affected by the magnetic field and a repelling and attracting force is produced. A force of displacing leftward or rightward acts on swing unit **60** depending on the direction of the magnetic field and an arrangement of the magnetic poles of magnet **61**. Accordingly, swing unit **60** is moved toward either side along the right-left direction while causing each beam portion **85** to deflect. By an alternate current flowing through coil **40**, swing unit **60** performs a reciprocatory linear motion with respect to frame **55** in the right-left direction in the planar view according to the alternate current. With this, vibration generator **1** generates a vibration force.

If a current value of the alternate current decreases and the magnetic field becomes smaller or vanishes, swing unit **60** attempts to return to the center portion of vibration generator **1** in the planar view by a restoring force of arm units **80**. At this time, as arm units **80** are elastic bodies, energy consumed by arm units **80** is relatively large. Therefore, the vibration is quickly attenuated.

In this embodiment, bottom plate **30** is configured by a non-magnetic material. Accordingly, a magnetic attracting force by magnet **61** is not generated between swing unit **60** and bottom plate **30**. Swing unit **60** is moved smoothly and efficiently according to the magnetic field generated by coil **40**. Therefore, it is possible to make vibration generator **1** thin even further and to operate appropriately.

[Description of Shape of Beam Portion **85**]

In this embodiment, the shape of beam portion **85** of each arm unit **80** is determined such that vibrator **50** efficiently operates as described below.

FIG. **5** is a perspective view illustrating arm unit **80**.

As illustrated in FIG. **5**, in this embodiment, a dimension h of beam portion **85** in a longitudinal direction (a dimension of a long side of a cross section of beam portion **85**) is larger than a dimension t of beam portion **85** in a lateral direction (a dimension of a short side of the cross section of beam portion **85**). For example, dimension h in the longitudinal direction is on the order of twice as large as dimension t in the lateral direction.

By setting the shape of beam portion **85** in this manner, a behavior of swing unit **60** in the Z axis direction is relatively suppressed, and a large vibration amount is obtained. Therefore, a force generated by excitation of coil **40** can be efficiently transmitted in a main swing direction of swing unit **60**. It should be noted that an optimal dimensional ratio between dimension h in the longitudinal direction and dimension t in the lateral direction of beam portion **85** is appropriately derived by such a way as a simulation while changing parameters of these dimensions.

Effects of Embodiment

As described above, in this embodiment, vibrator **50** is configured by integrally molding frame **55**, swing unit **60**, and arm unit **80**. Therefore, it is possible to assemble vibrator **50** easily and at high assembly accuracy. Since there is no time and effort for attachment of swing unit **60** to frame **55** and the number of components can be reduced, it is possible to reduce manufacturing cost of vibration generator **1**. Further, since swing unit **60** and frame **55** are integrally formed, an attachment between swing unit **60** and frame **55** may not become weak. Therefore, it is possible to improve reliability of vibration generator **1** against impact. As any separate member such as a screw is not necessary for attachment of swing unit **60** to frame **55**, it is possible to make vibration generator **1** further smaller, thinner, and lighter.

In this embodiment, as swing unit **60** and frame **55** are configured by separate members, the number of components is reduced. Further, it is possible to select the material of frame **55** appropriately while providing a plain structure that is easily assembled. Therefore, it is possible to provide a configuration in which frame **55** acts as a magnetic shield without additionally providing a member functioning as a magnetic shield, for example.

Vibrator **50** is integrally molded including frame **55**. Therefore, it is possible to achieve a sufficiently large vibration force while keeping the size of arm units **80** relatively small. It is possible to make the size of swing unit

60 relatively large in proportion to the size of vibrator **50**, that is, in proportion to the size of vibration generator **1** as a whole. Accordingly, it is also possible to achieve a relatively large vibration amount with small-sized vibration generator **1**. In particular, in each arm unit **80**, the longitudinal direction of beam portion **85** is the direction orthogonal to the swing direction, and beam portion **85** deforms efficiently in the swing direction. Therefore, it is possible to obtain the effect of this embodiment more effectively.

Arm units **80** are disposed symmetrically with respect both to the first plane and the second plane. Therefore, swing unit **60** is supported in a well-balanced manner, and vibration generator **1** can generate vibration more effectively.

A joint connecting arm unit **80** and weight **65** is uneven since groove **67** is provided. In particular, groove **67** is provided such that its longitudinal direction is a direction different from the swing direction of swing unit **60**. It is possible to achieve a joint strength between arm unit **80** and swing unit **60** sufficiently even without groove **67**. However, by providing groove **67** in this manner, it is possible to ensure prevention of such a trouble that swing unit **60** is misaligned with respect to arm unit **80** in the swing direction. Accordingly, it is possible to further improve durability of vibration generator **1**.

Description of Modified Examples

The vibrator can include a slit in the beam portion of the arm unit.

FIG. **6** is a plan view illustrating a vibration generator according to one modified example of this embodiment.

In FIG. **6**, a vibration generator **101** is illustrated in the same manner as in FIG. **1**. Vibration generator **101** is different from vibration generator **1** in that arm units **180** (**180a**, **180b**, **180c**, and **180d**) having a shape slightly different from that of arm units **80** are provided. It should be noted that illustration of groove **67** is omitted in FIG. **6**. Other than the difference between arm units **80** and arm units **180**, vibration generator **101** has substantially the same configuration as vibration generator **1**.

FIG. **7** is a perspective view illustrating arm unit **180**.

As illustrated in FIG. **7**, arm unit **180** has a beam portion **185** whose width in the X axis direction is wider than that of beam portion **85** of arm unit **80**. At a center portion in the X axis direction of beam portion **185**, a slit **186** is provided along a longitudinal direction of beam portion **185**. Slit **186** is provided so as to penetrate from an upper surface to a lower surface of beam portion **185**. Slit **186** is provided throughout an entire region between weight joint portion **81** and frame joint portion **83**. Specifically, providing slit **186** divides beam portion **185** into two beams whose width in the X axis direction is narrow. A dimension of the width of beam portion **185** in the X axis direction and a dimension of the width of slit **186** can be appropriately set such that a desired characteristic such as amplitude of vibrator **50** in vibration can be achieved.

By providing beam portion **185** with slit **186** in this manner, a stress produced in beam portion **185** when swing unit **60** is moved is reduced as compared to a case in which beam portion **85** without slit **186** is used. Therefore, it is possible to relatively increase the lifetime of beam portion **185**, and to further improve the durability of vibration generator **101**.

The groove can be provided only partially in the joint connecting the weight to the arm unit.

FIG. 8 is a perspective view illustrating a region of the weight, where the groove is provided, of the vibration generator according to another modified example of this embodiment.

As illustrated in FIG. 8, weight 65 can be provided with a groove 267 of a shape different from that of groove 67 according to the above embodiment. In this case, arm unit 80 is provided with a projecting portion 287 having a shape corresponding to the shape of groove 267 by using groove 267 as a gate in molding of arm unit 80.

Groove 267 has a shape engraved downward from the upper surface of weight 65 by a predetermined distance, for example. A lower end portion of groove 267 does not reach a lower surface of weight 65. Specifically, groove 267 is provided only partially in the joint connecting weight 65 to arm unit 80.

It is possible to provide the same effect as in the above embodiment by providing groove 267 having such a shape. Specifically, the jointing surface between weight 65 and arm unit 80 is uneven, and arm unit 80 does not easily misaligned with respect to weight 65 when swing unit 60 swings. Further, since groove 267 is used as the gate in molding of arm unit 80, it is possible to easily mold arm unit 80.

[Others]

It is not necessary to provide the groove of the weight and the projecting portion of the arm unit. It is possible to ensure a sufficient joint strength even if the gate position is not provided on a side of the weight.

It is possible to provide more than one coil. For example, it is possible to provide the coils aligned right and left along the swing direction of the swing unit. In this case, it is possible to use a magnet that is magnetized such that a side facing toward the coils is unipolar.

The shape of the frame and the shape of the vibrator are not limited to rectangular in the planar view. It is possible to provide the shape in various shapes such as an oval or polygonal shape for example.

The coil can be attached to a main circuit board of a device or the like that uses vibration, and the swing unit can be driven by attaching the vibrator to the main circuit board having the coil. In other words, the vibration generator can be configured by using a coil mounted on a circuit board of a different device.

It is not necessarily required to attach the top plate to the vibration generator. The top plate is useful for preventing dusts from coming into the vibrator. However, the top plate may not be used in a case in which the vibration generator is contained in a narrow space, for example.

It is possible to use a printed circuit board (such as a double-sided board) instead of the flexible printed circuit. In this case, a printed circuit board can be used instead both of the bottom plate and the flexible printed circuit, and the bottom plate may not be used.

According to these embodiments, the frame, the swing unit, and the elastic member are integrally molded with each other. Therefore, it is possible to assemble easily and accu-

ately, and to provide a vibrator with which a large vibration force in proportion to the size of the vibration generator can be obtained, as well as a vibration generator.

It should be understood that the embodiments described above are illustrative and non-restrictive in every respect. The scope of the present invention is defined by the terms of the claims, rather than the description above, and is intended to include any modifications within the scope and meaning equivalent to the terms of the claims.

What is claimed is:

1. A vibration generator comprising:

a frame;
a swing unit disposed within said frame and for holding a magnet;
a coil disposed so as to face toward said swing unit; and
an elastic member connecting said swing unit and said frame,

wherein:

said swing unit has a plate shape parallel to a horizontal plane,

said coil has a flat plate shape,

a largest surface of said coil is disposed facing a largest surface of said swing unit,

said swing unit is movable with respect to said frame while deforming said elastic member,

said swing unit reciprocates in a direction substantially parallel to said horizontal plane in response to excitation of said coil, and

said frame, said swing unit, and said elastic member are integrally molded with each other,

said elastic member is formed using a resin,

said swing unit includes a plurality of grooves used as a gate when injecting the resin for forming said elastic member,

at least one groove of said plurality of grooves is used as a joint connecting said swing unit to said elastic member,

said plurality of grooves are provided on a weight portion of said swing unit, said weight portion being a portion that is oriented in a manner so as to hold said magnet and a back yoke portion of said swing unit together, said weight portion includes a plurality of cutout portions, each of said cutout portions having at least one of said plurality of grooves disposed therein.

2. The vibration generator according to claim 1, wherein said elastic member includes a beam portion for deflecting when said swing unit moves with respect to said frame, said beam portion is formed such that a longitudinal direction thereof corresponds to a direction vertical to a swing direction of said swing unit,

a cross section of said beam portion taken perpendicular to the longitudinal direction of said beam portion is rectangular, and

a short side of said cross section is parallel to the swing direction of said swing unit.

* * * * *