



US009547417B2

(12) **United States Patent**  
**Meegan et al.**

(10) **Patent No.:** **US 9,547,417 B2**  
(45) **Date of Patent:** **Jan. 17, 2017**

(54) **RETRACTING SHORTCUT BARS, STATUS SHORTCUTS AND EDIT RUN PAGE SETS**

(71) Applicant: **DEERE & COMPANY**, Moline, IL (US)

(72) Inventors: **Robert Meegan**, Urbandale, IA (US); **Bruce Newendorp**, Cedar Falls, IA (US); **Joshua D. Hoffman**, Davenport, IA (US); **Kurtis Vander Wiel**, Cedar Falls, IA (US); **Sean McKay**, Iowa City, IA (US)

(73) Assignee: **DEERE & COMPANY**, Moline, IL (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 251 days.

(21) Appl. No.: **13/906,624**

(22) Filed: **May 31, 2013**

(65) **Prior Publication Data**

US 2014/0298259 A1 Oct. 2, 2014

**Related U.S. Application Data**

(60) Provisional application No. 61/806,642, filed on Mar. 29, 2013.

(51) **Int. Cl.**  
**G06T 11/00** (2006.01)  
**G06F 3/0482** (2013.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **G06F 3/0482** (2013.01); **B60K 35/00** (2013.01); **B60K 37/06** (2013.01); **G06F 3/0488** (2013.01);  
(Continued)

(58) **Field of Classification Search**  
None  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,854,988 A \* 12/1998 Davidson ..... E02F 9/26 37/414  
6,039,141 A \* 3/2000 Denny ..... 180/329  
(Continued)

FOREIGN PATENT DOCUMENTS

EP 2570909 A1 3/2013  
JP 2012248102 A 12/2012

OTHER PUBLICATIONS

SimFarm ("Sim Farm (PC) game, two nice fields and dumb livestock", video with runtime length of 9:59 minutes, uploaded on YouTube as of Dec. 9, 2007 at <https://www.youtube.com/watch?v=9p7JzhGxV2Y>).\*

(Continued)


*Primary Examiner* — William Beutel

(74) *Attorney, Agent, or Firm* — Harness, Dickey & Pierce, P.L.C.

(57) **ABSTRACT**

At least one example embodiment discloses a method for generating a touch screen display. The method includes establishing a first run screen associated with a first function of a work vehicle and establishing a second run screen associated with a second function of the work vehicle distinct from the first function and defining an order of appearance of the first run screen and the second run screen within a set of run screens that allows a user to select a run screen in the set of run screens that are displayable in accordance with the defined order.

**17 Claims, 18 Drawing Sheets**



412 415 420 410

- (51) **Int. Cl.**  
*G06F 3/0481* (2013.01)  
*G06F 3/0488* (2013.01)  
*G06F 3/0484* (2013.01)  
*B60K 35/00* (2006.01)  
*B60K 37/06* (2006.01)
- (52) **U.S. Cl.**  
 CPC ..... *G06F 3/04817* (2013.01); *G06F 3/04842*  
 (2013.01); *B60K 2350/1004* (2013.01); *B60K*  
*2350/1016* (2013.01); *B60K 2350/1032*  
 (2013.01)

(56) **References Cited**  
 U.S. PATENT DOCUMENTS

6,091,997	A	7/2000	Flamme et al.	
6,167,337	A	12/2000	Haack et al.	
6,275,231	B1 *	8/2001	Obradovich	345/156
6,343,237	B1 *	1/2002	Rossow et al.	700/83
6,826,465	B2 *	11/2004	Ishimoto et al.	701/50
7,259,729	B2 *	8/2007	Shastri et al.	345/1.3
7,548,804	B2 *	6/2009	Rossow et al.	701/36
7,880,728	B2 *	2/2011	de los Reyes et al.	345/173
8,351,915	B2	1/2013	Park et al.	
8,768,539	B1 *	7/2014	Clement et al.	701/2
8,930,039	B2 *	1/2015	Murray et al.	701/1
2007/0006101	A1 *	1/2007	Michaels	715/866
2007/0278320	A1 *	12/2007	Lunacek et al.	236/94

2008/0066007	A1 *	3/2008	Lau	G06F 3/0481 715/783
2008/0115091	A1 *	5/2008	Jung et al.	715/867
2008/0222675	A1 *	9/2008	Moshiri et al.	725/38
2008/0269956	A1 *	10/2008	Dix et al.	701/1
2009/0099737	A1 *	4/2009	Wendte et al.	701/50
2009/0150820	A1	6/2009	Hayman	
2010/0030525	A1 *	2/2010	Dong et al.	703/1
2010/0103125	A1 *	4/2010	Kim et al.	345/173
2011/0151072	A1 *	6/2011	Anderson	F24C 7/082 426/231
2011/0169868	A1	7/2011	Amemiya et al.	
2011/0238229	A1	9/2011	Woytowicz et al.	
2011/0314398	A1	12/2011	Yano	
2012/0053975	A1	3/2012	Lohn, Jr.	
2012/0081278	A1	4/2012	Freedman	
2012/0159364	A1 *	6/2012	Hyun	715/766
2013/0061169	A1	3/2013	Pearcy et al.	
2013/0174040	A1 *	7/2013	Johnson	715/733
2013/0218371	A1 *	8/2013	Simard et al.	701/2
2014/0096064	A1 *	4/2014	Suzuki	715/778
2014/0282013	A1 *	9/2014	Amijee	715/732

OTHER PUBLICATIONS

SigmaWorks (“[QuickTips] How to Look Cool with a Retracting Taskbar”, published on YouTube by SigmaWorks on Dec. 17, 2012 at <https://www.youtube.com/watch?v=KWomxUCQneo>).\*  
 International Search Report and Written Opinion dated Sep. 5, 2014.

\* cited by examiner






FIG. 1A




FIG. 1B






FIG. 2A




FIG. 2B






FIG. 3A




FIG. 3B






FIG. 4A

410





FIG. 4B

412 415 420 410





450

FIG. 4C




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D





FIG. 5E





610

FIG. 6



740

710a

710b

710c

730

735

FIG. 7A





745

750

FIG. 7B



FIG. 7C







FIG. 8



955

FIG. 9A







FIG. 9B



FIG. 9C





1010

FIG. 10A




FIG. 10B







FIG. 10C



1010

FIG. 10D






FIG. 10E




FIG. 10F










FIG. 10I





FIG. 10J





1112

FIG. 11A

1114




FIG. 11B

1114






FIG. 11C

1114




FIG. 11D






FIG. 11E



**1****RETRACTING SHORTCUT BARS, STATUS  
SHORTCUTS AND EDIT RUN PAGE SETS**

## PRIORITY

This non-provisional application claims priority under 35 U.S.C. §119 to provisional application No. 61/806,642 filed Mar. 29, 2013; the entire contents of which are hereby incorporated by reference.

## FIELD

Example embodiments are related to displays including touch screen displays for work vehicles such as off-road work vehicles, agricultural machines, forestry machines, construction machines and heavy equipment.

## BACKGROUND

Many work vehicles include displays for displaying a status of the vehicle and various functions of the vehicle. Many of these displays are operated by physical buttons and subject to requirements set by a standard.

## SUMMARY

At least one example embodiment discloses a retractable shortcut bar for a touch screen display. The retractable shortcut bar may be a component located at a bottom of a screen. The retractable shortcut bar may serve as a container for shortcut buttons serving various user interface functions.

At least one example embodiment discloses an edit run page set overlay. The edit run page set overlay may include design components for editing a current run page set. The edit run page set overlay gives the user the ability to change the name of the current run page set and to add, remove, and reorder pages within the run page set.

At least one example embodiment discloses a status shortcut for a touch screen display. The status shortcut is a component that may be located on a shortcut bar. The status shortcut allows an operator to observe and/or toggle the status of an application feature without opening the application.

At least one example embodiment discloses a method for generating a touch screen display. The method includes establishing a run screen on the touch screen display, the run screen associated with a function of a work vehicle, configuring the run screen with a retractable toolbar, the retractable toolbar responsive to an action of a user of the touch screen display and deployable over a first portion of the run screen upon the action of the user and otherwise hiding to display a second portion of the run screen, the second portion of the run screen being at least a majority portion of the run screen and defining one or more transient user-definable buttons on the retractable toolbar associated with at least one of the function and the run screen.

At least one example embodiment discloses a method for managing a display of a display system. The method includes establishing a run screen associated with a first function of a work vehicle, providing a location-determining receiver for potential guidance of the work vehicle, establishing a plurality of performance states associated with at least one of the location-determining receiver and a guidance controller and displaying one or more of the performance states by corresponding visually displayable states without changing to another screen of the display.

**2**

At least one example embodiment discloses a method for generating a touch screen display. The method includes establishing a first run screen associated with a first function of a work vehicle and establishing a second run screen distinct from the first function and defining an order of appearance of the first run screen and the second run screen within a set of run screens that allows a user to select a run screen in the set of run screens that are displayable in accordance with the defined order.

## BRIEF DESCRIPTION OF THE DRAWINGS

Example embodiments will be more clearly understood from the following detailed description taken in conjunction with the accompanying drawings. FIGS. 1-11E represent non-limiting, example embodiments as described herein.

FIG. 1A illustrates a vehicle according to an example embodiment;

FIG. 1B illustrates a system of a vehicle according to an example embodiment;

FIGS. 2A-2B illustrate a set of run pages for ten inch screen according to an example embodiment;

FIGS. 3A-3B illustrate a set of run pages for seven inch screen according to an example embodiment;

FIG. 4A illustrates an example embodiment of a screen with a shortcut bar retracted;

FIGS. 4B-4C illustrate example embodiments of a screen with a shortcut bar extended;

FIGS. 5A-5E illustrate an example embodiment of a status shortcut button;

FIG. 6 illustrates a menu according to an example embodiment;

FIGS. 7A-7C illustrate a layout manager according to an example embodiment;

FIG. 8 illustrates a select dashboard display according to an example embodiment;

FIGS. 9A-9C illustrate run page set displays according to an example embodiment;

FIGS. 10A-10J illustrates an example embodiment of adding and editing a run page; and

FIGS. 11A-11E illustrates an example embodiment of adding and editing a shortcut bar.

## DETAILED DESCRIPTION

Various example embodiments will now be described more fully with reference to the accompanying drawings in which some example embodiments are illustrated.

Accordingly, while example embodiments are capable of various modifications and alternative forms, embodiments thereof are shown by way of example in the drawings and will herein be described in detail. It should be understood, however, that there is no intent to limit example embodiments to the particular forms disclosed, but on the contrary, example embodiments are to cover all modifications, equivalents, and alternatives falling within the scope of the claims. Like numbers refer to like elements throughout the description of the figures.

It will be understood that, although the terms first, second, etc. may be used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first element could be termed a second element, and, similarly, a second element could be termed a first element, without departing from the scope of example



embodiments. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

It will be understood that when an element is referred to as being “connected” or “coupled” to another element, it can be directly connected or coupled to the other element or intervening elements may be present. In contrast, when an element is referred to as being “directly connected” or “directly coupled” to another element, there are no intervening elements present. Other words used to describe the relationship between elements should be interpreted in a like fashion (e.g., “between” versus “directly between,” “adjacent” versus “directly adjacent,” etc.).

The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of example embodiments. As used herein, the singular forms “a,” “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises,” “comprising,” “includes” and/or “including,” when used herein, specify the presence of stated features, integers, steps, operations, elements and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components and/or groups thereof.

It should also be noted that in some alternative implementations, the functions/acts noted may occur out of the order noted in the figures. For example, two figures shown in succession may in fact be executed substantially concurrently or may sometimes be executed in the reverse order, depending upon the functionality/acts involved.

Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which example embodiments belong. It will be further understood that terms, e.g., those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

Portions of example embodiments and corresponding detailed description are presented in terms a processor specifically programmed to execute software, or algorithms and symbolic representations of operation on data bits within a computer memory. These descriptions and representations are the ones by which those of ordinary skill in the art effectively convey the substance of their work to others of ordinary skill in the art. An algorithm, as the term is used here, and as it is used generally, is conceived to be a self-consistent sequence of steps leading to a result. The steps are those requiring physical manipulations of physical quantities. Usually, though not necessarily, these quantities take the form of optical, electrical, or magnetic signals capable of being stored, transferred, combined, compared, and otherwise manipulated. It has proven convenient at times, principally for reasons of common usage, to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like.

In the following description, illustrative embodiments will be described with reference to acts and symbolic representations of operations (e.g., in the form of flowcharts) that may be implemented as program modules or functional processes including routines, programs, objects, components, data structures, etc., that perform particular tasks or implement particular abstract data types and may be implemented using existing hardware. Such existing hardware may include one or more Central Processing Units (CPUs),

digital signal processors (DSPs), application-specific-integrated-circuits, field programmable gate arrays (FPGAs) computers or the like.

It should be borne in mind, however, that all of these and similar terms are to be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities. Unless specifically stated otherwise, or as is apparent from the discussion, terms such as “processing” or “computing” or “calculating” or “determining” or “displaying” or the like, refer to the action and processes of a computer system, or similar electronic computing device, that manipulates and transforms data represented as physical, electronic quantities within the computer system’s registers and memories into other data similarly represented as physical quantities within the computer system memories or registers or other such information storage, transmission or display devices.

Note also that the software implemented aspects of example embodiments are typically encoded on some form of tangible (or recording) storage medium or implemented over some type of transmission medium. The tangible storage medium may be magnetic (e.g., a floppy disk or a hard drive) or optical (e.g., a compact disk read only memory, or “CD ROM”), and may be read only or random access.

The term implement may refer to a particular piece of equipment or function of the vehicle including a plow, tillage equipment, harvesting head, planter and sprayer.

FIG. 1A illustrates a vehicle **60** in which at least one example embodiment is implemented. The vehicle **60** includes a display system **105** including a display **115**. The display **115** may display any features or parameters of the vehicle **60**, including, for example, speed and heading information. The display **115** may be used to enter user preference parameters described in further detail below. For example, the display **115** may be used to establish a retracting shortcut bar, status shortcuts and edit run page sets.

Features of the display system **105** are described in further detail with regard to FIG. 1B.

FIG. 1B illustrates a system of a vehicle according to an example embodiment. The vehicle may be a work vehicle such as an off-road work vehicle, agricultural machine, forestry machine, construction machine or heavy equipment vehicle. However, example embodiments are not limited thereto and may be implemented in other types of vehicles.

The system **100** includes electronic modules, software modules, or both. In an example embodiment, the system **100** includes a display system **105** to support storing, processing or execution of software instructions of one or more software modules. The display system **105** is indicated by the dashed lines in FIG. 1B. It should be understood that the system **100** may include other systems configured to support storing, processing or execution of software instructions of one or more software modules in the functioning of the machine. However, for the sake of brevity, they will not be described understanding that FIG. 1B is not limited just to the features shown in FIG. 1B.

The lines that are interconnecting the aforementioned devices may be physical data paths, logical data paths, or both. Physical data paths are defined by transmission lines or data buses. Data buses may be, for example, Control Area Network (CAN) buses or ISO buses. Logical data paths may comprise logical or virtual communications that take place within software or between software modules.

The display system **105** is configured receive data regarding systems (e.g., steering system **212**, braking system **214**, propulsion system **216**, vehicle sensor(s) **218**), components and implements via a communications interface **110** in the



display system **105** that accesses a vehicle data bus **210**. The vehicle data bus **210** may be a controller area network (CAN) data bus, for example.

The communications interface **110** may receive and transmit messages containing further data to/from the vehicle data bus **210** such as, for example, the steering system **212**, braking system **214**, propulsion system **216**, vehicle sensor (s) **218** or other controller of the vehicle connected on the data bus. The messages may be implemented using a protocol such as CAN. The messages may contain data including operational parameters or other parameters related to the vehicle provided by the sensors **218**, for example, temperature gauges, magnetic wheel speed sensors, traction control sensors, etc.

Each of the steering system **212**, braking system **214** and propulsion system **216** receives commands from and communicates data to a steering controller **222**, braking controller **224** and propulsion controller **226**, respectively.

The steering system **212** cooperatively operates with the steering controller **222** to control the steering of the vehicle. For example, if a user of the vehicle selects a certain track (route) to follow, the steering controller **222** receives commands from a guidance system **230** and controls the steering system **212** such that the vehicle follows the selected route. Moreover, the steering controller **222** may control the steering system **212** in a conventional manner when a user is manually driving. The steering system **212** may be an electrical steering system, a drive-by-wire steering system, an electro-hydraulic steering system, or a hydraulic steering system with an electronic control interface, for example.

The vehicle data bus **210** provides signals to the steering controller **222** from the display system **105**. For example, the vehicle data bus **210** may provide signals including CAN messages to the steering controller **222**. The messages may include, for example, commands such as steering angle commands or position data.

The braking system **214** cooperatively operates with the braking controller **224** to control the braking of the vehicle. For example, if a user of the vehicle selects a certain track (route) to follow, braking controller **224** receives commands from the guidance system **230** and controls the braking system **214** to brake when the vehicle is approaching a turn. Moreover, the braking controller **224** may control the braking system **214** in a conventional manner when a user is manually driving.

The propulsion controller **226** cooperatively operates with the propulsion system **216** to control the propulsion of the vehicle. The propulsion may be any known motor or engine, for example. For example, if a user of the vehicle selects a certain track (route) to follow, propulsion controller **226** receives commands from the guidance system **230** and controls the propulsion system **216** to move the vehicle along the selected route. Moreover, the propulsion controller **226** may control the propulsion system **216** in a conventional manner when a user is manually driving.

As described above, the steering controller **222**, braking controller **224** and propulsion controller **226** communicate with the guidance system **230**. The steering controller **222**, braking controller **224** and propulsion controller **226** may communicate with the guidance system **230** through a secondary data bus or transmission line **235**. The guidance system **230** provides information to the steering controller **222**, braking controller **224** and propulsion controller **226** regarding location and route. Moreover, the guidance system **230** is connected to the vehicle data bus **210** and obtains data and commands regarding which location and route to follow,

for example. The guidance system **230** may be a Global Positioning System (GPS) system or another type of guidance system.

The guidance system **230** may automatically steer the vehicle in accordance with a path plan (e.g., linear path or contour) based on GPS position measurements or navigation system measurements.

A location determining receiver **240** is connected to the vehicle data bus **210**, as well. The location determining receiver **240** may be a GPS receiver, for example. The location determining receiver **240** transmits the location to the display system **105** and guidance system **230** through the vehicle data bus **210**. The location-determining receiver **240** may provide one or more of the following data types: position data (e.g., expressed as geographic coordinates), velocity data, and acceleration data. Velocity data further comprises speed data and heading data for the vehicle. The location determining receiver **240** transmits the data to the display system **105** and guidance system **230** through the vehicle data bus **210**. The aforementioned data may further be displayed on the display **115** of the display system **105**.

The vehicle may include various actuators **220**. For example, an electrical steering system or a drive-by-wire steering system may include an electric motor or actuator that is mechanically coupled to rotate or steer at least one wheel of the vehicle.

As described, the display system **105**, transmits and receives data regarding the vehicle through the communications interface **110**. The communications interface is connected to a data bus **112**. In addition to the communications interface **110**, the display **115** and the data bus **112**, the display system **105** further includes a processor **120** and a data storage device **125**.

The communications interface **110**, the display **115**, the data bus **112**, the processor **120** and the data storage device **125** are connected to the data bus **112** and are configured to communicate through the data bus **112**.

The processor **120** implements algorithms and other functionality of the display system **105** described in further detail below.

The processor **120** may be any type of processor configured to execute program codes such as those stored in the data storage device **125**.

In an example embodiment, the processor **120** may include an electronic data processor, a digital signal processor, microprocessor, a microcontroller, a programmable logic array, a logic circuit, an arithmetic logic unit, an application specific integrated circuit, a digital signal processor, a proportional-integral-derivative (PID) controller, or another data processing device.

The data storage device **125** may include any magnetic, electronic, or optical device for storing data. For example, the data storage device **125** may include an electronic data storage device, an electronic memory, non-volatile electronic random access memory, one or more electronic data registers, data latches, a magnetic disc drive, a hard disc drive, an optical disc drive, or the like. The processor **120** outputs results of algorithms and other functionality of the display system **105** to the data bus **112**.

The data storage device **125** may store user profile data **126** and application module data **127**. The user profile data **126** may include data representing a skill level of the user and authorization level of the user. For example, the skill level may be beginner, intermediate and advanced. The application module data **127**, which is Run Screen Module or software module that is dedicated or programmed to perform, monitor and/or control a certain work task (e.g.,



planting, seeding, spraying, harvesting, leveling, tilling) of the work vehicle, includes data for the display 115 to display run screens and organizes run screens according to sets, as will be described in further detail below.

The processor 120 includes a shortcut manager 121, emulator 122 and run screen manager 123. The shortcut manager 121 manages the shortcut abilities of the display 115 such as the shortcut bar 116. The emulator 122 emulates other buttons on the display 115 that were conventionally represented by physical controls. With the shortcut manager 121, the emulator 122 emulates replaced user physical controls. The run screen manager 123 retrieves run screens and sets of run screens based on an action of the user. Moreover, the run screen manager 123 organizes the run screen modules into sets. The sets of run screen modules may be dictated by a user's selection and/or programmed by a manufacturer of the display system 105.

The display 115 may be a touch screen display with a user interface 117. The user interface 117 may act as a touch controller. The user interface 117 may communicate the actions of the user (e.g., touch) to the processor 120 through the data bus 112. While actions by the user are often described as touching, it should be understood that the user interface 117 may operate based on voice commands and/or other objects (e.g., stylus) touching the display. Moreover, other possible gestures include double tap, drag/slide, flick, nudge, pinch and spread. The display 115 displays the shortcut bar, status indicator 118 and run screen 119, as is illustrated in FIGS. 2A-3B.

#### Run Pages

The terms run pages, run screens and dashboards may be used interchangeably.

At least one example embodiment discloses an edit run page set overlay. The edit run page set overlay may include design components for editing a current run page set. The edit run page set overlay gives the user the ability to change the name of the current run page set and to add, remove, and reorder pages within the run page set.

A run screen provides a dedicated functionality or set of functions for a machine, such as planting, tilling, harvesting, spraying or another agricultural or other work task. Further, the run screen may provide diagnostics, or status messages on different components, systems, or the vehicle, or its implements (attached or operable connected to the vehicle).

Run screens are customizable with modular content for the display of vehicle status and control information. Run screens have custom user-programmable controls (e.g., guidance control) for vehicle components, systems or features that previously required separate physical controls (e.g., joystick, dials, levers, knobs or switches). Advantageously, the vehicle manufacturer does not need to provide physical controls for less popular or seldom ordered options on vehicles (e.g., front power take-off shaft on a tractor) because the display system can be customized to produce data messages that emulate such physical controls in communication with the vehicle data bus 210 (e.g., CAN data bus or ISO data bus).

The user may reprogram the vehicle to only have controls (icon buttons on the toolbar) that are relevant to a task at hand and the particular version of the vehicle, for a particular user, or for a particular season (e.g., harvesting buttons may be temporarily deleted for Spring planting, Fall Run screens can be optimized for harvesting, planting winter wheat or tillage; Spring Run Screens can be adjusted for tillage, fertilizing or planting; Summer Run Screens can be optimized for spraying).

FIGS. 2A-2B illustrate a set of run pages for a ten inch screen according to an example embodiment. FIGS. 3A-3B illustrate a set of run pages for a seven inch screen according to an example embodiment.

In FIG. 2A, a first run page for spraying is displayed on the display 115. In FIG. 2B, a second run page for spraying is displayed on the display 115. Edit page sets may be created by the run screen manager 123. Each edit run page set may be associated with a function and/or user. Example functions include planting, a spraying, and a harvesting.

The run screen manager 123 is configured to establish the set of run screens in a temporal sequence for performing seasonal operations in an agricultural field.

Moreover, a set of run pages may include a Spring run page, a Summer run page and a Fall run page, wherein each run page is associated with one or more seasonal work tasks in the foregoing sequential order of display.

In an example embodiment, the first and second run pages are selected by the user from a list consistent with a vehicle profile of the vehicle. In an example embodiment, the list is stored in the data storage device 125 associated with the display 115. In another example embodiment, includes accessing the list is accessed via one of the vehicle data bus 210 and the data bus 112 (ISO data bus).

In an example embodiment, the first and second run pages are selected by the user from a list consistent with an implement profile for the vehicle. In an example embodiment, the implement profile is stored in the data storage device 125 associated with the display 115. In another example embodiment, the list is accessed via one of the vehicle data bus 210 and data bus 112 (ISO data bus).

In an example embodiment, the first and second run pages are selected by the user from a list consistent with a user profile of the vehicle. In an example embodiment, the user profile is stored in the data storage device 125 associated with the display 115. In another example embodiment, includes accessing the list is accessed via one of the vehicle data bus 210 and data bus 112 (ISO data bus). The user profiles can be programmed to change with the seasons, such as having a Fall Run Screen, a Winter Run Screen and a Spring Run Screen and a Summer Run Screen.

In FIGS. 2A-2B, the user interface 117 produces a toggle 260 so a user may toggle between run pages in the set of run pages. The toggle 260 includes a right navigation button 260b and a left navigation button 260a. The user touches the right navigation button 260b to go to a next run page in the set. The taps the left navigation button 260a to a previous run page in the set. Since the run pages shown in FIGS. 2A-2B are both directed to spraying the run pages may be in the same set.

Additionally, the user interface produces a short cut bar 270. The short cut bar 270 includes one or more transient user-definable buttons 270a-270n on the short cut bar 270. The buttons 270a-270n may be programmed by a manufacturer and then altered by the user. The short cut bar 270 is described in greater detail below.

The button 270a opens an application for setting up a field operation by selecting vehicle, implement, field, and crop. The button 270b indicates the state of field operation recording and allows the operator to manually toggling the recording state on and off. The button 270c indicates the state of the automatic guidance system and allows the operator to toggle activation on and off. The button 270d opens the automatic guidance application. The button 270e indicates the state of the automatic section control and opens the application for changing settings for automatic section control. The button 270f opens a ISO 11783 part 6 virtual



terminal application. The button **270g** opens the application that allows adjustment of display brightness and speaker volume. The button **270n** opens an on-line help application.

FIG. 2A illustrates a run page for spraying as applied produced by the user interface **117**. As shown, the user interface **117** produces a title text area **252** and an identifier **250** for the field where the vehicle is present. Moreover, the display **115** shown in FIG. 2A includes a guidance portion **255** which illustrates the current track and track spacing. The user interface **117** produces a map portion **265** which illustrates the path of the vehicle.

In addition, the run page includes sections for fuel **267** and load depth **269**.

It should be understood, that the user interface **117** produces the field identifier **250**, the guidance portion **255** and the sections for fuel **267** and load depth **269** by the user selecting the field identifier **250**, the guidance portion **255** and the sections for fuel **267** and load depth **269** as parts of the run page for spraying. The operator may select different components to occupy the run page, including the option of leaving some areas unpopulated. The system ships with a standard set of run pages designed to serve as a starting point for this customization.

FIG. 2B illustrates a run page for spraying overview produced by the user interface **117**. As shown in FIG. 2B the user interface **117** produces a guidance section **280**. The guidance section **280** provides an overview of the current track and map of the vehicle. The user interface **117** also includes an operating overview section **290** which displays an amount of fuel remaining, a speed of the vehicle and amount of fuel used per amount of time, for example.

A section **285**, including buttons **272** is an ISO 11783 part 6 virtual terminal application. A square central area of 480×480 pixels is a data region, while the area encompassing buttons **272** is a soft key region.

Multiple run pages may be grouped together into a run page set. Because both displays in FIGS. 2A-2B illustrate spraying run pages, a user may group the spraying run pages into a run page set. Editing run page sets is described in further detail below. A user may select a run page by touching the title text area **252**.

In FIGS. 3A-3B, the user interface **117** produces a toggle **360** so a user may toggle between run pages in the set of run pages. Additionally, the user interface produces a retractable short cut button **370**. As will be further described below, the retractable short cut bar includes one or more transient user-definable buttons **270a-270n**. The buttons may be programmed by a manufacturer and then altered by the user.

FIG. 3A illustrates a run page for spraying as applied produced by the user interface **117**. As shown, the user interface **117** produces an identifier **350** for the field where the vehicle is present. Moreover, the display **115** shown in FIG. 3A includes a guidance portion **355**, which illustrates the current track and track spacing. The user interface **117** also produces a map portion **365** which illustrates the path of the vehicle and a coverage overview **370**. The map portion **365** may be 480×480 pixels.

It should be understood, that the user interface **117** produces the field identifier **350**, the guidance portion **355** and the coverage overview **370** by the user selecting the field identifier **350**, the guidance portion **355** and the coverage overview **370** as parts of the run page for spraying. Alternatively, the run page may be established by the manufacturer.

FIG. 3B illustrates a run page for spraying overview produced by the user interface **117**. Section **386** illustrates a condensed guidance view. Section **388** illustrates a module

displaying the status of the hydraulic control valves. Pressing any of the vertical bars (I-V) will allow the user to set the flow rate and duration for that valve. Section **390** illustrates a rear hitch position and settings. Section **392** illustrates engine power as a function of full power. Sections **394** and **396** show a value of machine parameters, including radar speed, wheel speed, fuel level and diesel exhaust fluid (DEF) level. Section **398** illustrates a speed for each field cruise setting.

Because both displays in FIGS. 3A-3B illustrate spraying run pages, a user may group the spraying run pages into a run page set. A user may navigate through the run page set by pressing the navigation button **360**.

As shown in FIGS. 2A-3B, the user interface **117** also produces a menu button **262**. When a user touches the menu button **262**, the user interface launches a menu stored in the data storage device **125** on the display **115**. The menu may include a list of applications to select such as guidance, reports work performed, vehicle monitoring and ISO (International Organization for Standardization) virtual terminal.

The user interface **117** is also configured to produce a status information bar **264** and **364** in FIGS. 2A-2B and 3A-3B, respectively. When a user touches one of the status information bars **264** and **364**, the user interface **117** launches a status center stored in the data storage device **125**. The status center stores data regarding messages, software downloaded and network connections, such a Wi-Fi.

By using the user interface **117**, a user may create, edit or delete a run page; create, edit or delete a run page set; select a run page/run page set to view; navigate through a run page set, access a menu, and view status information.

By exchanging information with the user interface **117**, the processor **120** is configured to establish a first run screen associated with a first function of a work vehicle and establish a second run screen associated with a second function of the work vehicle distinct from the first function and define an order of appearance of the first run screen and the second run screen within a set of run screens that allows a user to select a run screen in the set of run screens that are displayable in accordance with the defined order.

In example embodiment, the order of appearance is a user-definable sequence.

In example embodiment, the defining defines the order of appearance such that the order permits the user to toggle through the set of run screens.

In example embodiment, the run screen manager **123** may select a run page to delete from the set of run screens based on the user using the user interface **117**.

In example embodiment, the run screen manager **123** may add a third run screen in any position within the set to change the order of appearance of run screens within the set based on the user using the user interface **117**. The run screen manager **123** may change the order of the appearance of the run screens within the set.

#### Retractable Toolbar

A retractable shortcut bar may be a component located at a bottom of a screen. The retractable shortcut bar serves as a container for shortcut buttons serving various user interface functions. The shortcut bar allows one-touch access to commonly used functions of the vehicle. The retractable shortcut bar allows for a display of state indicators and system toggles. The retractable shortcut bar allows for access to low-take-rate vehicle and implement features without the costs and clutter of physical buttons.

In an example embodiment, the retracting feature allows the shortcut bar to remain hidden, permitting use of a



## 11

480×480 pixel map module or a full 480×480 pixel ISO 11783 part 6 virtual terminal.

As shown, in FIGS. 2A-2B, the shortcut bar 270 may be at the bottom of the display 115 in an example embodiment.

In an example embodiment, such as the seven inch screen shown in FIGS. 3A-3B, a shortcut bar may be retractable. The terms, toolbar and shortcut bar, may be used interchangeably.

FIG. 4A illustrates an example embodiment of a screen with the shortcut bar retracted and FIGS. 4B-4C illustrate example embodiments of the screen with the shortcut bar extended.

FIG. 4A illustrates a run page with a shortcut button 410. As shown in FIG. 4A, a shortcut bar is not extended.

FIG. 4B illustrates a shortcut bar 412 extended with two definable buttons for tracking a vehicle's movement 415 and for GPS guidance along a route 420. As shown, the shortcut bar 412 extends into a portion (e.g., first portion) of display area 425. The display area 425 may be defined by a standard. For example, the display area 425 may be a reserved area of 480 pixels by 480 pixels (e.g., second portion), which is defined by ISO. Consequently, the shortcut bar 412 extends over a portion of the reserved area.

The shortcut bar 412 becomes extended upon the user pressing the shortcut button 410. Based on the user's action, the user interface 117 communicates with the processor 120 to access the shortcut manager 121. The processor provides the user interface 117 with the data regarding the shortcut bar 412, such as the buttons within the shortcut bar 412. As shown, when the shortcut bar 412 becomes extended, an "X" icon appears. By a user pressing the "X", the user interface 117 retracts the shortcut bar 412. Additionally or alternatively, the shortcut bar 412 disappears after a timer initiated at the time of deployment expires such that the second portion of the run screen is displayed.

FIG. 4C illustrates an example embodiment showing a shortcut bar 450 with six definable buttons.

The processor 120 is configured to establish a run screen on the touch screen display 115 that is associated with a function of a work vehicle. The processor 120 instructs the user interface 117 to configure the run screen with a retractable toolbar. The retractable toolbar is deployed by the user interface in response to an action of a user of the touch screen display and deployable over a first portion of the run screen upon the action of the user and otherwise hides to display a second portion of the run screen, the second portion of the run screen being at least a majority portion of the run screen.

As described in further detail below, the definable buttons may be programmed initially by the manufacturer and/or selected by the user. The buttons on the retractable toolbar 412 are associated with at least one of the function and the run screen.

The processor is configured to allocate high priority status data associated with the function to a region other than the first portion of the run screen and allocate lower priority status data associated with the function to first portion of the run screen. Consequently, the high priority status data is not covered by the shortcut bar 412 is extended.

The user-definable buttons may be selected by the user and/or processor 120 from at least one of a list and a menu based on status data displayed on the run screen.

The user-definable buttons may be selected by the user and/or processor 120 from a list of options that are consistent with a vehicle profile of the vehicle. The vehicle profile may be stored in the data storage device 125 associated with the display.

## 12

The processor 120 may access the list of options through the vehicle data bus 210 and/or the data bus 112.

The user-definable buttons may be selected by the user and/or processor 120 from a list of options consistent with the profile of the user.

A run screen provides a dedicated functionality or set of functions for a machine, such as planting, tilling, harvesting, spraying or another agricultural or other work task. Further, the run screen may provide diagnostics, or status messages on different components, systems, or the vehicle, or its implements (attached or operable connected to the vehicle).

As described, when a user touches, taps, selects or activates the shortcut button 410, the toolbar is deployed with one or more user-definable buttons. The toolbar can be set to disappear after the expiration of timer or only when closed by a user (e.g., by touching, tapping, selecting or activating a close "X" symbol). When the shortcut bar 412 is inactive, the user can enjoy the full screen to display other information.

The user may use the toolbar or program it with links to custom user-programmable controls (e.g., run screens) for vehicle components, systems or features that previously required separate physical controls (e.g., joystick, dials, levers, knobs or switches). Advantageously, the vehicle manufacturer does not need to provide physical controls for less popular or seldom ordered options on vehicles (e.g., front power take-off shaft on a tractor) because the display system 105 can be customized to produce data messages that emulate such physical controls in communication with the vehicle data bus (e.g., CAN data bus or ISO data bus).

#### Status Shortcut

The status shortcut is a component that may be located on a shortcut bar. The status shortcut allows an operator to observe and/or toggle a status of an application feature without opening the application. The status shortcut may be added to the shortcut bar by a user.

The user interface 117 in conjunction with the processor 120 is configured to display buttons that provides both a status of a function and control of the function.

FIGS. 5A-5E illustrate an example embodiment of a status shortcut button that may be used in the shortcut bar 270 and the retractable shortcut bar 412. FIGS. 5A-5E illustrate various statuses of a guidance system, which is provided as button 270c in FIG. 2A. The user interface 117 adjusts the status of the buttons based on commands from the processor 120. The processor 120 is configured to monitor that status of various functions of the vehicle through the communications interface 110, as described above.

FIG. 5A illustrates the status of the guidance system, when the guidance system is not installed. The icon in FIG. 5A is shown by the user interface 117 in the shortcut bar when the guidance system is installed in a system of the vehicle.

FIG. 5B illustrates the status of the guidance system, when the guidance system is installed. The icon in FIG. 5B is shown by the user interface 117 in the shortcut bar when the guidance system is installed in a system of the vehicle.

FIG. 5C illustrates the status of the guidance system, when the guidance system is configured. The icon in FIG. 5C is shown by the user interface 117 in the shortcut bar when the guidance system is setup in the system of the vehicle. This includes specific routes, guidance the vehicle is to follow and/or spacing the vehicle is to follow, for example.

FIG. 5D illustrates the status of the guidance system, when the guidance system is enabled. The guidance system



is enabled when inputs are made and the guidance system may be activated by pushing the button **270c**.

FIG. **5E** illustrates the status of the guidance system, when the guidance system is activated. The icon in FIG. **5E** indicates that the guidance system is in use. The user interface **117** shows the icon in FIG. **5E** until the user deactivates the guidance system, touches the steering wheel or other conditions (e.g., out of seat, off GPS path, etc.). For example, the user interface **117** may transition from the icon shown in FIG. **5E** to the icon shown in FIG. **5D** when the user pushes the button **270c** to disengage the guidance system.

In an example embodiment, a different icon may be displayed if the guidance system is off.

The icons of FIGS. **5A-5E** may transition in response to a status message data provided by the location-determining receiver **240** and the guidance system **230**.

In addition to the guidance system **230**, icons may represent the status of at least one of planting, plowing, spraying and harvesting.

The processor **120** is configured to establish a run screen associated with a first function of a vehicle, provide a location-determining receiver for potential guidance of the work vehicle, establish a plurality of performance states associated with at least one of the location-determining receiver and a guidance controller and display one or more of the performance states by corresponding visually displayable states without changing to another screen of the display.

The processor **120** may issue a call from the display system **105** to the guidance system **230**, wherein the transition of the icon occurs in response to data transmitted from the guidance system **230** in reply to the call.

In an example embodiment, the guidance system **230** is one of (1) continuously active in a background data processing of the display system and (2) loaded into the data storage device **125** for the data processor.

The location-determining receiver **240** is coupled directly or indirectly to the vehicle data bus **210** to support communications with the display system **105**. The display system **105** can run multiple applications in the background and may use any suitable windowing operating system. For the guidance system **230** shortcut status, the status can be retrieved and displayed in the button (e.g., 5 different states possible) on the shortcut bar **270** or **412**. The status is displayed without displaying the entire guidance system **230** screen. A call regularly (e.g., after the expiration of a time interval) made to a guidance system software module, a guidance system program module or subroutine requests the update of status information for the shortcut button.

Referring back to FIGS. **2A-2B** and **3A-3B**, when a user presses the menu button **262**, the processor **120** retrieves the menu from the data storage device **125**. The processor **120** then provides the display with the menu, which is shown in FIG. **6**. As shown in FIG. **6**, the user may select settings, applications, implements or system information to display. In FIG. **6**, applications are selected for display.

By using the user interface **117**, a user may select one of the applications being displayed. In an example embodiment, the user selects a dashboard layout manager application to may create, edit or delete a run page; create, edit or delete a run page set; select a run page/run page set to view; and navigate through a run page set.

When a user touches a dashboard layout manager **610**, the user interface **117** provides the processor **120** with the user's selection. The run screen manager **123**, within the processor **120**, retrieves a layout manager application from the data

storage **125**. The processor **120** then provides the display **115** with a layout manager display, shown in FIG. **7A**.

As shown in FIG. **7A**, the user interface **117** provides the user the ability to select dashboard sets **710a**, shortcut bars **710b** or dashboard libraries **710c** for display. FIG. **7A** illustrates an embodiment where the dashboard sets are shown in a display area **725**, FIG. **7B** illustrates an embodiment with the short cut bars are shown in the display area **725** and FIG. **7C** illustrates an embodiment with the dashboard library shown in the display area **725**.

With the dashboard sets display shown in FIG. **7A**, the user may add a new dashboard set by pressing a button **730**, duplicate a dashboard set by pressing a button **735**, or edit a dashboard set by pressing an edit button **740**. The user interface **117** displays the edit button **740** when a user touches one of the dashboard sets displayed in the display area **725**. If the user selects the edit button **740**, the processor **120** retrieves an edit dashboard set overlay shown in FIG. **9A**. The editing of a dashboard is also described in greater detail below, with reference to FIGS. **10A-10J**.

When a user selects to add a new dashboard set, the user interface **117** provides the processor **120** with the user's selection. The processor **120** retrieves the dashboard set management overlay and provides the dashboard set management overlay to the user interface **117**, which is illustrated in FIGS. **9A-9C**. The selection of the button **730**, causes the display **115** to display the screen shown in FIG. **9B**.

When a user selects to duplicate a dashboard set, the user interface **117** provides the processor **120** with the user's selection. The selection of the button **735** causes the processor **120** to provided data to the display to display the screen shown in FIG. **9C**.

FIGS. **9A-9C** are described in greater detail below.

Referring back to FIG. **2A**, when a user presses the title text area **252**, the processor **120** retrieves select dashboard data from the data storage device **125**. The processor **120** then provides the display **115** with the select dashboard data, which is shown in FIG. **8**.

As shown in FIG. **8**, the user may select may select a dashboard within the run page set. The run page set is identified in area **810** and a user may select one of the run pages **815a**, **815b** and **815c** that are displayed by the display **115**. By tapping one of the run pages **815a**, **815b** and **815c**, the user interface **117** provides the processor **120** with the user's selection. This causes the processor **120** to retrieve the selected run page and provide the selected run page to the display **115**. If the user selects an edit button **810** (e.g., by touching), the user interface **117** provides the processor **120** with the user's selection. This causes the processor **120** to retrieve the dashboard set management overlay, which is illustrated in FIGS. **9A-9C**. The selection of the button **810**, causes the display **115** to display the screen shown in FIG. **9A**.

As shown in FIG. **9A**, a user may edit the dashboard set name by touching area **910**, select a shortcut bar to use with dashboard set by touching area **920**, edit, add, duplicate, remove or reorder the dashboards. The processor **120** removes the dashboard set from the data storage device **125** when a user presses a delete button **930**. When the user touches the touching area **920**, the processor **120** is configured to provide the user with a list of shortcut bars the user may select for the dashboard set. Upon selecting a shortcut bar, the processor **120** assigns the selected shortcut bar to the dashboard set and the user interface **117** returns to the display in FIG. **9A**.



When a user selects a dashboard from a list of dashboards **917**, the user interface produces an edit button **935**, a duplicate button **940**, a reorder button **945** and a delete button **950**. To add a dashboard to the dashboard set, the user presses button **955**. Consequently, the user may add dashboards to a set according to factors such as season and job type, for example. The dashboards are saved in the data storage device **125**.

The user may reorder the dashboards within the set by pressing the up/down arrows in the reorder button **945**.

FIGS. **9B-9C** illustrate similar functions as those shown in FIG. **9A** except FIGS. **9B-9C** are for new dashboard sets. Thus, for the sake of brevity, FIGS. **9B-9C** will not be described in greater detail.

FIGS. **10A-10J** illustrates an example embodiment of adding and editing a dashboard for a 7x7 display.

As described above, when a user selects to add a new dashboard, the user interface **117** via the processor **120**, produces the display shown in FIG. **10A**.

When creating a new dashboard, a module area **1005** is initially blank. The new dashboard includes the menu icon **262**, the retractable shortcut button **370** and a save button **1002**. When the user interface **117** senses that the save button **1002** has been touched, the processor **120** saves the dashboard. The processor **120** is configured to retrieve and add module overlay when the user selects the add module button **1010**. The add module overlay is shown in FIG. **10B**.

The user interface **117** produces tabs **1015a**, **1015b**, **1015c** and **1015d** in the add module overlay to select among recently used modules, tractor controls, applications and system modules.

The recently used modules tab **1015a** contains any dashboard module that have been added to or removed from a dashboard during a session. For example, a session may be a period of time from a last restart to a next restart. The contents of the recently used tab **1015a** may be sorted with a most recently used dashboard module at the top.

A content area **1020** of each tab contains a title icon grid with icons for each type of dashboard module that is available within that category.

In the add module overlay shown in FIG. **10B**, the user interface **117** displays a list of tractor controls in the content area **1020**.

When a module is selected, the processor **120** retrieves an add module type overlay. FIG. **10C** illustrates a module type overlay for a single-valve overview.

In FIG. **10C**, the user interface **117** produces a picture of the dashboard module **1025**, a graphic to show the size of the dashboard module **1030**, a description of the elements within the dashboard module and an add button. The processor **120** determines what space the dashboard module may fit into the dashboard. If the dashboard module will not fit in any available space of the dashboard, the user interface **117** produces a message and icon with the module graphic to notify the user.

When the user selects the add button **1035**, the processor **120** adds the selected module to the run screen by using the run screen manager **123** and returns to the new dashboard or edit dashboard overlay, as shown in FIG. **10D**.

In FIG. **10D**, the user interface **117** produces the new dashboard overlay with the selected module. Moreover, the user interface **117** provides the user with buttons for moving **1065** and adding a module **1010** in a message area frame **1060**. To move a module **1065**, the user may select the module **1065** by touching it. The user may move the module **1065** by dragging the module **1065** to a location within the area **1005**.

When the user has finished moving the module **1065**, the user interface **117** changes the message area frame **1606** to include a remove button **1067**, as shown in FIG. **10E**. The user may also edit the dashboard name by entering a name in the dashboard name area **1070**. To deselect the module **1065**, the user touches the display **117** anywhere except on the module **1065**, which returns the user interface to the user interface to FIG. **10F**.

A user may continue the same process to add more dashboard modules until the module area **1005** is filled.

When the processor **120** senses that an edit dashboard button is selected, the processor **120** causes the user interface **117** to display an edit dashboard overlay shown in FIG. **10G**.

The user may select a dashboard module by touching the dashboard module. For example, the user may touch the field module **1070**. By sensing the user's selection, the processor **120** provides data to and instructs the user interface **117** to allow the user to move or delete the selected field module **1070**, as shown in FIG. **10H**. If there is no space to move the selected module, the user interface notifies the user that no space is available, as shown in FIG. **10I**.

In FIG. **10J**, a portion of the display is removed by the processor **120**, which allows a user to move the field module **1070**, when the field module **1070** is selected by the user. To deselect the field module **1070**, the user taps anywhere on the dashboard except on the module **1070**.

With the shortcut bars display shown in FIG. **7B**, the user may add a new shortcut bar by pressing a button **745**, duplicate a shortcut bar by pressing a button **750**, or edit a shortcut bar set by pressing an edit button **760**. The user interface **117** display the edit button **760** when a user touches one of the shortcut bars displayed in the display area **725**. If the user selects the edit button **760**, the processor **120** retrieves an edit shortcut bar overlay. The editing of a shortcut bar is described in greater detail below, with reference to FIGS. **11A-11E**.

When a user selects to add a new shortcut bar or duplicate a shortcut bar, the user interface **117** provides the processor **120** with the user's selection.

If the user selects a shortcut bar edit button, the processor **120** retrieves the edit shortcut bar overlay. FIG. **11A** illustrates an example edit shortcut bar overlay.

As shown in FIG. **11A**, the user interface **117** displays a name of the shortcut bar in area **1102**. The shortcut bar name may be change by pressing the edit button **1104**. The user interface **117** may display a keyboard for the user to use to change the name of the shortcut bar.

The user interface **117** also displays a graphic of the shortcut bar **1106**. When a shortcut bar is not filled by shortcuts, empty spaces of the shortcut bar are displayed as add shortcut buttons **1108**. Moreover, shortcuts within the shortcut bar **1106** may be moved in a similar manner as the dashboard modules. In other words the shortcuts within the shortcut bar **1106** may be moved by pressing and sliding the shortcut to an empty area of the shortcut bar.

The user interface **117** also illustrates an assigned dashboard sets button **1112**. By a user pressing the assigned dashboard sets button **1112**, the processor **120** permits the user to view and edit the dashboard sets where the shortcut bar is used.

The processor **120** saves the shortcut bar in the data storage **125** when a user presses a save button **1114**. The shortcut manager **121** manages the storage of the shortcut bars.

Moreover, by pressing a shortcut, the user interface **117** highlights the pressed shortcut and displays a remove short-



17

cut button **1110**, which permits a user to delete the shortcut from the shortcut bar, as shown in FIG. **11B**.

When a user selects to add a new shortcut bar, the user interface **117** provides the processor **120** with the user's selection. The processor **120** provides the user interface **117** with data to display a new shortcut bar overlay, as shown in FIG. **11C**. The functionality of the user interface **117** with respect to the new shortcut bar overlay is the same as the functionality with respect to the edit shortcut bar overlay. Thus, for the sake of brevity, FIG. **11C** will not be described in greater detail.

When a user selects to duplicate a new shortcut bar, the user interface **117** provides the processor **120** with the user's selection. The processor **120** provides the user interface **117** with data to display a duplicate shortcut bar overlay, as shown in FIG. **11D**. The functionality of the user interface **117** with respect to the new shortcut bar overlay is the same as the functionality with respect to the edit shortcut bar overlay. Thus, for the sake of brevity, FIG. **11D** will not be described in greater detail.

The processor **120** saves the duplicated shortcut bar in the data storage **125** when a user presses a save button **1114**. The shortcut manager **121** manages the storage of the shortcut bars.

When a user presses the add a shortcut button **1108** in either the edit shortcut bar overlay or the new/duplicate shortcut bar overlay, the processor **120** provides the user interface **117** to display an add shortcut overlay, as shown in FIG. **11E**.

The user interface **117** produces tabs **1115a**, **115b** and **1115c** in the add shortcut overlay to select among recently used modules, tractor settings and system shortcuts.

The recent used shortcuts tab **1115a** contains any shortcut that have been added to or removed from a shortcut bar during a session. For example, a session may be a period of time from a last restart to a next restart. The contents of the recently used tab **1115a** may be sorted with a most recently used dashboard module at the top.

A content area **1120** of each tab contains a title icon grid with icons for each type of shortcut that is available within that category.

In the add shortcut overlay shown in FIG. **11E**, the user interface **117** displays a list of application shortcuts in the content area **1120**. When a user selects a shortcut to add, the processor **120** adds the shortcut to the shortcut bar and provides the user interface **117** to display an update shortcut bar with the selected shortcut bar in either the new/duplicate shortcut bar overlay or edit shortcut bar overlay.

Example embodiments being thus described, it will be obvious that the same may be varied in many ways. Such variations are not to be regarded as a departure from the spirit and scope of example embodiments, and all such modifications as would be obvious to one skilled in the art are intended to be included within the scope of the claims.

What is claimed is:

**1.** A method for generating a touch screen display, the method comprising:

establishing a first run screen associated with a first function of a work vehicle and establishing a second run screen associated with the first function, the first and second run screens illustrating information regarding the first function, the first function being at least one of agricultural, forestry and construction, the establishing the first run screen and the establishing the second run screen including,

18

establishing a retractable toolbar on the first run screen and the second run screen, the retractable toolbar being associated with at least one of the first function and modules in the first run screen and the second run screen; and

defining an order of appearance of the first run screen and the second run screen within a set of run screens associated with the first function that allows a user to select a run screen in the set of run screens that are displayable in accordance with the defined order, the defined order being associated with the first function, wherein the set of run screens includes a fall run screen, a winter run screen, a spring run screen and a summer run screen, harvesting is associated with the fall run screen, planting is associated with the spring run screen and the summer run screen is associated with spraying and the spring run screen does not include harvesting.

**2.** The method of claim **1**, wherein the order of appearance is a user-definable sequence.

**3.** The method of claim **1**, wherein the defining defines the order of appearance such that the order permits the user to toggle through the set of run screens.

**4.** The method according to claim **1**, further comprising: deleting the first run screen or the second run screen from the set of run screens.

**5.** The method according to claim **1**, further comprising: adding a third run screen in any position within the set to change the order of appearance of run screens within the set.

**6.** The method according to claim **1**, further comprising: changing the order of the appearance of the run screens within the set.

**7.** The method according to claim **1**, wherein the establishing includes, selecting the first and second run screens from a list consistent with a vehicle profile of the work vehicle.

**8.** The method according to claim **7**, wherein the list is stored in a data storage device associated with the display.

**9.** The method according to claim **7**, wherein the establishing includes accessing the list via one of a CAN vehicle data bus and ISO data bus.

**10.** The method according to claim **1**, wherein the establishing includes, selecting of the first and second run screens from a list consistent with an implement profile for the vehicle.

**11.** The method of claim **10**, wherein the list is stored in a data storage device associated with the display.

**12.** The method of claim **10**, wherein the establishing includes accessing the list via one of a CAN vehicle data bus and ISO data bus.

**13.** The method according to claim **1**, wherein the establishing includes selecting of the first and second run screens from a list consistent with a user profile of the work vehicle.

**14.** The method of claim **13**, wherein the list is stored in a data storage device associated with the display.

**15.** The method of claim **13**, wherein the establishing includes accessing the list via one of a CAN vehicle data bus and ISO data bus.

**16.** The method of claim **13**, wherein the user profile includes at least one of a skill level of the user and an authorization level of the user.

**17.** The method of claim **1**, wherein the set of run screens is established in a temporal sequence for performing seasonal operations in an agricultural field.