



US009554813B2

(12) **United States Patent**
Clever et al.

(10) **Patent No.:** **US 9,554,813 B2**
(45) **Date of Patent:** **Jan. 31, 2017**

(54) **PATELLA DRILL GUIDE AND TRIAL SURGICAL INSTRUMENT**

USPC 606/79, 82, 87, 83, 53, 88, 89, 96,
104,606/86 R; 623/20.19, 20.18, 20.2
See application file for complete search history.

(71) Applicant: **DEPUY IRELAND UNLIMITED COMPANY, CO Cork OT (IE)**

(56) **References Cited**

(72) Inventors: **Jennifer B. Clever**, Warsaw, IN (US);
Matthew S. Wallace, Huntertown, IN (US);
Michael J. Rock, Leeds (GB);
Abraham P. Wright, Winona Lake, IN (US);
Olen J. Borkholder, Warsaw, IN (US);
Robert S. Gorab, Orange, CA (US);
Rusty T. Meier, Warsaw, IN (US)

U.S. PATENT DOCUMENTS

2,181,746 A *	11/1939	Siebrandt	606/96
3,835,849 A	9/1974	McGuire		
4,191,861 A	3/1980	Walker, Jr.		
D260,927 S	9/1981	Glenn		
D281,622 S	12/1985	Diamond		
4,565,192 A	1/1986	Shapiro et al.		
4,633,862 A	1/1987	Petersen		

(Continued)

(73) Assignee: **DEPUY IRELAND UNLIMITED COMPANY (IE)**

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 72 days.

CN	101259044 A	9/2008
CN	101484085 A	7/2009

(Continued)

(21) Appl. No.: **13/630,951**

OTHER PUBLICATIONS

(22) Filed: **Sep. 28, 2012**

Depuy International, Ltd., PFC SIGMA Rotating Platform Knee System With MBT Tray, Surgical Technique Brochure, 2003 (43 Pages), Cat. No. 9068-96-000, Depuy International, Ltd., Leeds, England.

(65) **Prior Publication Data**

US 2014/0094820 A1 Apr. 3, 2014

(Continued)

(51) **Int. Cl.**

A61B 17/17	(2006.01)
A61B 17/88	(2006.01)
A61F 2/38	(2006.01)
A61F 2/46	(2006.01)
A61B 17/15	(2006.01)
A61B 17/16	(2006.01)

Primary Examiner — Eduardo C Robert

Assistant Examiner — Marcela I Shirsat

(74) *Attorney, Agent, or Firm* — Barnes & Thornburg LLP

(52) **U.S. Cl.**

CPC **A61B 17/1767** (2013.01); **A61B 17/8866** (2013.01); **A61F 2/3877** (2013.01); **A61F 2/4684** (2013.01); **A61B 17/157** (2013.01); **A61B 17/158** (2013.01); **A61B 17/1677** (2013.01)


(57) **ABSTRACT**

An orthopedic surgical instrument includes a patella trial and drill guide that may be used to both perform a surgical trial of the patellofemoral joint and guide the surgeon in drilling a number of anchor holes in the patella of the patient.

(58) **Field of Classification Search**

CPC . A61B 17/158; A61B 17/2812; A61F 2/3877; A61F 2/38; A61F 2002/3881; A61F 2002/30892; A61F 2310/00029

15 Claims, 16 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,692,073 A 9/1987 Martindell
 5,002,547 A 3/1991 Poggie et al.
 5,021,055 A 6/1991 Burkinshaw et al.
 5,108,401 A 4/1992 Insall et al.
 5,116,338 A 5/1992 Poggie et al.
 5,129,907 A 7/1992 Heldreth et al.
 5,129,908 A 7/1992 Petersen et al.
 5,147,365 A 9/1992 Whitlock et al.
 5,174,693 A 12/1992 Lee et al.
 5,222,955 A 6/1993 Mikhail et al.
 5,250,050 A 10/1993 Poggie et al.
 5,258,032 A 11/1993 Bertin
 5,284,482 A 2/1994 Mikhail et al.
 5,284,485 A 2/1994 Kammerer et al.
 5,312,409 A 5/1994 McLaughlin et al.
 5,382,254 A 1/1995 McGarry et al.
 5,415,663 A 5/1995 Luckman et al.
 5,470,328 A 11/1995 Furnish et al.
 5,484,451 A 1/1996 Akopov et al.
 D367,531 S 2/1996 Price
 5,520,692 A 5/1996 Ferrante et al.
 5,536,271 A 7/1996 Daly et al.
 5,542,947 A 8/1996 Treacy
 D373,635 S 9/1996 Price
 5,575,793 A 11/1996 Carls et al.
 5,582,615 A 12/1996 Foshee et al.
 5,593,450 A 1/1997 Scott et al.
 5,611,802 A 3/1997 Samuelson et al.
 5,626,607 A 5/1997 Malecki
 5,667,512 A 9/1997 Johnson
 5,716,361 A 2/1998 Masini
 5,716,362 A 2/1998 Treacy
 5,827,279 A 10/1998 Hughett et al.
 5,941,884 A 8/1999 Corvelli et al.
 5,944,723 A 8/1999 Colleran et al.
 5,957,926 A 9/1999 Masini
 5,968,051 A 10/1999 Luckman et al.
 6,010,509 A 1/2000 Delgado et al.
 6,056,754 A 5/2000 Haines et al.
 6,074,425 A 6/2000 Pappas
 6,080,162 A 6/2000 Dye et al.
 6,190,391 B1 2/2001 Stubbs
 6,205,884 B1 3/2001 Foley et al.
 D459,474 S 6/2002 Bratt et al.
 6,419,675 B1 7/2002 Gallo, Sr.
 D463,550 S 9/2002 Sherman
 6,551,316 B1 4/2003 Rinner
 6,589,248 B1 7/2003 Hughes
 6,851,150 B2 2/2005 Chiang et al.
 6,855,150 B1 2/2005 Linehan
 6,866,667 B2 3/2005 Wood et al.
 6,905,514 B2* 6/2005 Carignan et al. 623/20.35
 D549,331 S 8/2007 Tomatsu
 7,344,540 B2 3/2008 Smucker et al.
 7,356,902 B2 4/2008 Snider et al.
 7,566,335 B1 7/2009 Scott et al.
 7,632,279 B2 12/2009 Bastian
 7,780,594 B2 8/2010 Hutton
 7,806,899 B2 10/2010 Hogg et al.
 7,878,989 B2 2/2011 McMinn
 7,891,071 B2 2/2011 Collazo
 D634,011 S 3/2011 Phillips et al.
 D638,541 S 5/2011 Claypool
 7,972,383 B2 7/2011 Goldstein et al.
 D642,678 S 8/2011 Dockstader et al.
 D646,389 S 10/2011 Claypool et al.
 8,216,242 B2 7/2012 Marchyn et al.
 8,834,574 B2* 9/2014 Todd et al. 623/20.18
 8,951,262 B2 2/2015 Kecman et al.
 2002/0115987 A1 8/2002 Hildwein et al.
 2003/0069586 A1 4/2003 Errico et al.
 2003/0163137 A1 8/2003 Smucker et al.
 2004/0153066 A1 8/2004 Coon et al.
 2004/0162561 A1 8/2004 Marchyn et al.
 2005/0240196 A1 10/2005 Davis et al.

2006/0058886 A1 3/2006 Wozencroft
 2006/0142777 A1 6/2006 Bastian et al.
 2007/0118141 A1 5/2007 Marchyn et al.
 2007/0150066 A1* 6/2007 McMinn 623/20.19
 2007/0162031 A1 7/2007 Hogg et al.
 2007/0179626 A1 8/2007 de la Barrera et al.
 2007/0233142 A1 10/2007 Oliver
 2007/0260227 A1 11/2007 Phan
 2008/0097450 A1 4/2008 Brown et al.
 2008/0114366 A1 5/2008 Smucker et al.
 2008/0177394 A1 7/2008 Chauhan
 2008/0221569 A1* 9/2008 Moore et al. 606/53
 2008/0228190 A1 9/2008 Sherry et al.
 2008/0306484 A1 12/2008 Coon et al.
 2009/0088753 A1 4/2009 Aram et al.
 2009/0264737 A1 10/2009 Haechler et al.
 2009/0326661 A1 12/2009 Wright et al.
 2010/0030223 A1 2/2010 Keller
 2010/0121389 A1 5/2010 Librot
 2010/0152742 A1 6/2010 Nevelös et al.
 2010/0160924 A1* 6/2010 Soliman 606/96
 2010/0168753 A1 7/2010 Edwards et al.
 2010/0204701 A1 8/2010 Tallarida et al.
 2010/0249938 A1 9/2010 Gunther et al.
 2011/0066193 A1* 3/2011 Lang et al. 606/86 R
 2012/0078261 A1 3/2012 Kecman et al.
 2012/0179264 A1 7/2012 Todd et al.
 2013/0023883 A1 1/2013 Wright et al.
 2013/0023890 A1 1/2013 Kecman et al.
 2013/0030443 A1 1/2013 Wright et al.
 2013/0030539 A1 1/2013 Wright et al.
 2013/0035693 A1 2/2013 Wright et al.
 2013/0079787 A1 3/2013 Spencer Jones
 2013/0079788 A1 3/2013 Jones
 2013/0079789 A1 3/2013 Randle et al.
 2013/0211410 A1 8/2013 Landes et al.
 2014/0094818 A1 4/2014 Wallace et al.

FOREIGN PATENT DOCUMENTS

CN 101522114 A 9/2009
 CN 101617967 A 1/2010
 EP 791335 A1 8/1997
 EP 0992222 A2 4/2000
 EP 1723916 B1 11/2006
 EP 1967143 A2 9/2008
 EP 2140837 A1 1/2010
 EP 2574314 A1 4/2013
 FR 2737848 A1 2/1997
 WO 9945856 A1 9/1999
 WO 03071961 A1 9/2003
 WO 2005110249 A1 11/2005
 WO 2006027098 A1 3/2006
 WO 2008112996 A1 9/2008
 WO 2013003730 A1 1/2013

OTHER PUBLICATIONS

Depuy Orthopaedics, Inc., LCS High Performance Instruments, Surgical Technique Guide, 2008, (44 Pages), Pub. No. 0612-85-506, Depuy Orthopaedics, Inc., Warsaw, IN.
 Depuy Orthopaedics, Inc. SIGMA High Performance Instruments, Classic Surgical Technique, 2010, (52 Pages), Pub. No. 0612-89-510, Depuy Orthopaedics, Inc., Warsaw, IN.
 Depuy Orthopaedics, Inc., SIGMA High Performance Instruments, Design Rationale, 2007 (12 Pages), Pub. No. 0612-54-506 (Rev. 2), Depuy Orthopaedics, Inc., Warsaw, IN.
 European Search Report, European Pat. App. No. 11175824.9-2310, Dec. 16, 2011 (7 Pages).
 European Search Report, European Pat. App. No. 12191753.8-2310, Jan. 3, 2013 (6 Pages).
 European Search Report for European Application No. 12174683.8-2310, Sep. 3, 2012, 6 pages.
 European Search Report for European Application No. 12174682.0-2310, Sep. 5, 2012, 6 pages.
 International Search Report, International Application No. PCT/US12/44947, Oct. 12, 2012, 3 pages.

(56)

References Cited

OTHER PUBLICATIONS

European Search Report for European Application No. 12186675.
0-2310, Dec. 12, 2012, 7 pages.

European Search Report for European Application No. 12186700.
6-2310, Dec. 13, 2012, 8 pages.

European Search Report for European Application No. 12186728.
7-2310, Dec. 14, 2012, 8 pages.

European Search Report for European Application No. 13186401.
9-1654, Jan. 17, 2014, 7 pages.

European Search Report for European Application No. 13186416.
7-1654, Dec. 6, 2013, 7 pages.

Extended European Search Report, European Application No.
16160477.2-1654, dated May 11, 2016, 8 pages.

Chinese Search Report for Chinese Application No. 201310460722.
0, Oct. 17, 2016, 3 pages.

* cited by examiner




Fig. 1




Fig. 2




Fig. 4




Fig. 3




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 21




Fig. 20




Fig. 24




Fig. 23




Fig. 22




Fig. 25




Fig. 27




Fig. 26




Fig. 28




Fig. 29




Fig. 30




Fig. 31




Fig. 32

PATELLA DRILL GUIDE AND TRIAL SURGICAL INSTRUMENT

CROSS REFERENCE

Cross reference is made to each of copending U.S. patent application Ser. No. 13/630,935 entitled "ORTHOPAEDIC SURGICAL INSTRUMENT ASSEMBLY FOR IMPLANTING A PROSTHETIC PATELLA COMPONENT" by Jennifer B. Clever et al.; copending U.S. patent application Ser. No. 13/630,924 entitled "PATELLA DRILL GUIDE AND TRIAL SURGICAL INSTRUMENT HAVING AN ALIGNMENT BORE FORMED THEREIN AND METHOD OF USING THE SAME" by Matthew S. Wallace et al.; and copending U.S. patent application Ser. No. 13/630,965 entitled "METHOD FOR SURGICALLY IMPLANTING A PROSTHETIC PATELLA COMPONENT" by Jennifer B. Clever et al. Each of these copending applications is assigned to the same assignee as the present application, filed concurrently herewith, and hereby incorporated by reference.

TECHNICAL FIELD

The present disclosure relates generally to orthopaedic surgical instruments and, more particularly, to patella surgical instruments.

BACKGROUND

Joint arthroplasty is a well-known surgical procedure by which a diseased and/or damaged natural joint is replaced by a prosthetic joint. A typical knee prosthesis includes a tibial tray, a femoral component, and a polymer insert or bearing positioned between the tibial tray and the femoral component. In some cases, the knee prosthesis may also include a prosthetic patella component, which is secured to a posterior side of the patient's surgically-prepared patella. To secure the prosthetic component to the patella, an orthopaedic surgeon may resect the posterior side of the patient's natural patella to prepare the natural patella to receive the prosthetic component. In use, the patella prosthetic component articulates with the femoral component during extension and flexion of the patient's knee.

SUMMARY

According to one aspect, a patella drill guide and trial instrument includes a posterior trial bearing surface configured to articulate with a condylar surface of a prosthetic femoral component. The posterior trial bearing surface has a curved peak surface that defines the posterior-most surface of the patella drill guide and trial instrument. The patella drill guide and trial instrument also includes an anterior surface having a number of spikes extending outwardly therefrom, and a number of drill guide holes extending through the patella drill guide and trial instrument from the posterior trial bearing surface to the anterior surface.

In an embodiment, the posterior bearing surface includes a medial trial articular surface configured to articulate with a medial condyle surface of a prosthetic femoral component, and a lateral trial articular surface configured to articulate with a lateral condyle surface of the prosthetic femoral component.

In an embodiment, an imaginary line bisects the anterior surface in the medial/lateral direction, with the center of each of the number of spikes being positioned medially of the imaginary line.

In an embodiment, the number of spikes includes a center spike, a superior spike, and an inferior spike. A superior/inferior imaginary line bisects the anterior surface in the superior/inferior direction, with the center of the center spike being located on the superior/inferior imaginary line, the center of the superior spike being positioned superiorly of the superior/inferior imaginary line, and the center of the inferior spike being positioned inferiorly of the superior/inferior imaginary line.

The center spike may be longer than the superior spike and the inferior spike.

The number of drill guide holes may be counterbored holes.

The patella drill guide and trial instrument may further include a connecting slot positioned between the posterior trial bearing surface and the anterior surface. The connecting slot may be configured to receive a connecting tongue of a removable clamp so as to secure the patella drill guide and trial instrument to the removable clamp.

In an embodiment, the posterior trial bearing surface and the anterior surface define a monolithic body. In another embodiment, the posterior trial bearing surface and the anterior surface define a monolithic polymeric body, with a metallic sleeve inserted into each of the number of drill guide holes.

According to yet another aspect, a patella drill guide and trial instrument includes a posterior trial bearing surface configured to articulate with a condylar surface of a prosthetic femoral component. The posterior trial bearing surface has a curved peak surface that defines the posterior-most surface of the patella drill guide and trial instrument. The patella drill guide and trial instrument also includes an anterior surface having a center spike and a number of peripheral spikes extending outwardly therefrom. A superior/inferior imaginary line bisects the anterior surface in the superior/inferior direction, with the center of the center spike being located on the superior/inferior imaginary line. The center spike may be longer than the peripheral spikes. The patella drill guide and trial instrument further includes a number of drill guide holes extending through the patella drill guide and trial instrument from the posterior trial bearing surface to the anterior surface.

In an embodiment, the posterior bearing surface includes a medial trial articular surface configured to articulate with a medial condyle surface of a prosthetic femoral component, and a lateral trial articular surface configured to articulate with a lateral condyle surface of the prosthetic femoral component.

In an embodiment, an imaginary line bisects the anterior surface in the medial/lateral direction, with the center of each of the number of spikes being positioned medially of the imaginary line.

In an embodiment, the number of peripheral spikes includes a superior spike and an inferior spike, with the center of the superior spike being positioned superiorly of the superior/inferior imaginary line, and the center of the inferior spike being positioned inferiorly of the superior/inferior imaginary line.

In an embodiment, a medial/lateral imaginary line bisects the anterior surface in the medial/lateral direction, and the center of both of the center, superior, and inferior spikes is positioned medially of the medial/lateral imaginary line.

The number of drill guide holes may be counterbored holes.

The patella drill guide and trial instrument may further include a connecting slot positioned between the posterior trial bearing surface and the anterior surface. The connecting

slot may be configured to receive a connecting tongue of a removable clamp so as to secure the patella drill guide and trial instrument to the removable clamp.

In an embodiment, the posterior trial bearing surface and the anterior surface define a monolithic body. In another embodiment, the posterior trial bearing surface and the anterior surface define a monolithic polymeric body, with a metallic sleeve inserted into each of the number of drill guide holes.

BRIEF DESCRIPTION OF THE DRAWINGS

The detailed description particularly refers to the following figures, in which:

FIG. 1 is a perspective view of an orthopaedic surgical instrument assembly showing the patella drill guide and trial instrument secured to the removable clamp;

FIG. 2 is an enlarged perspective view of the patella drill guide and trial instrument of the orthopaedic surgical instrument assembly of FIG. 1;

FIG. 3 is a bottom elevation view of the patella drill guide and trial instrument of FIG. 2;

FIG. 4 is a top elevation view of the patella drill guide and trial instrument of FIG. 2;

FIG. 5 is a side elevation view of the patella drill guide and trial instrument of FIG. 2;

FIG. 6 is a cross section view of the patella drill guide and trial instrument taken along the line 6-6 of FIG. 7, as viewed in the direction of the arrows;

FIG. 7 is a side elevation view of the patella drill guide and trial instrument showing the instrument's connector;

FIG. 8 is a cross section view of the patella drill guide and trial instrument taken along the line 8-8 of FIG. 3, as viewed in the direction of the arrows;

FIG. 9 is a side elevation view of the orthopaedic surgical instrument assembly of FIG. 1;

FIG. 10 is an enlarged fragmentary perspective view of the connector of the removable clamp of the orthopaedic surgical instrument assembly of FIG. 1;

FIG. 11 is a fragmentary top elevation view showing the patella drill guide and trial instrument secured to the removable clamp;

FIG. 12 is a fragmentary perspective view showing the compression socket secured to the removable clamp;

FIG. 13 is a perspective view of the compression socket;

FIG. 14 is a side elevation view of the compression socket;

FIG. 15 is a perspective view of the alignment handle;

FIG. 16 is a perspective view showing the alignment handle secured to the patella drill guide and trial instrument;

FIG. 17 is a view similar to FIG. 1, but showing an anatomic patella drill guide and trial instrument;

FIG. 18 is a top perspective view of a modified dome patella component that may be implanted with the instruments and methods described herein;

FIG. 19 is a bottom perspective view of the modified dome patella component of FIG. 18;

FIG. 20 is an anterior view of the knee of a patient;

FIG. 21 is a lateral view of the knee of a patient;

FIG. 22 is a surgical view showing an alignment hole being drilled into the apex of the patient's natural patella;

FIGS. 23 and 24 are surgical views showing the generally planar surgically-resected patella surface of the patient's patella;

FIG. 25 is a surgical view showing alignment of the patella drill guide and trial instrument 14 over the surgically-resected patella surface of the patient's patella;

FIG. 26 is a surgical view showing the patella drill guide and trial instrument 14 being installed on the surgically-resected patella surface of the patient's patella;

FIG. 27 is a surgical view showing the patella drill guide and trial instrument 14 having been installed on the surgically-resected patella surface of the patient's patella;

FIGS. 28 and 29 are surgical views showing the alignment handle being used to assess rotational positioning of the patella drill guide and trial instrument 14 during trialing of the patellofemoral joint;

FIG. 30 is a surgical view showing the anchor holes being drilled in the patient's patella through the guide holes of the patella drill guide and trial instrument 14;

FIG. 31 is a view similar to FIG. 24, but showing the anchor holes having been drilled in the patient's patella; and

FIG. 32 shows the patella clamp and compression socket being used to clamp the patella component to the patient's patella during the bone cement polymerization process.

DETAILED DESCRIPTION OF THE DRAWINGS

While the concepts of the present disclosure are susceptible to various modifications and alternative forms, specific exemplary embodiments thereof have been shown by way of example in the drawings and will herein be described in detail. It should be understood, however, that there is no intent to limit the concepts of the present disclosure to the particular forms disclosed, but on the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the appended claims.

Terms representing anatomical references, such as anterior, posterior, medial, lateral, superior, inferior, etcetera, may be used throughout the specification in reference to the orthopaedic implants and surgical instruments described herein as well as in reference to the patient's natural anatomy. Such terms have well-understood meanings in both the study of anatomy and the field of orthopaedics. Use of such anatomical reference terms in the written description and claims is intended to be consistent with their well-understood meanings unless noted otherwise.

Referring to FIG. 1, an orthopaedic surgical instrument assembly 10 includes a removable patella clamp 12 and a patella drill guide and trial instrument 14 configured to be secured to the patella clamp 12. As described in greater detail below, the instrument assembly 10 is utilized to surgically prepare a patient's patella 16 for implantation of a prosthetic patella component 18 (see FIGS. 18 and 19). To do so, the patella drill guide and trial instrument 14 may be used as both a trial instrument to trial the patellofemoral joint and as a drill guide to drill anchor holes into the planar, resected posterior surface of the patient's patella 16. The surgeon may also use the patella drill guide and trial instrument 14 to size and select a patella prosthetic component suitable for use with the particular patient's patella.

As shown in FIG. 1, the patella clamp 12 of the instrument assembly 10 includes a pair of levers 20, 22 pivoted together with a pivot pin 24. The proximal end of the lever 20 includes an upper handle 26, with the distal end of the lever 20 having a retaining socket 28. The proximal end of the lever 22 includes a lower handle 30, with the distal end of the lever 22 having a connector 32 (see FIG. 10). The lever 22 is modular in design in that the connector 32 is not integrally formed with the lower handle 30. A proximal end 34 of the connector 32 is captured in a slot 36 formed in a cylinder housing 38. As shown in FIG. 9, the proximal end 34 of the connector 32 is coupled to the distal end 40 of the

lower handle 30 within the cylinder housing 38 such that the connector 32 is maintained in substantially parallel relationship with the distal end 42 of the lever 20 as it translates upwardly and downwardly within the cylinder housing 38. A compression spring 44 (see FIG. 9) is positioned in the cylinder housing 38 and exerts a spring bias on the proximal end 34 of the connector 32 so as to urge the connector 32 in a direction away from the retaining socket 28.

When a surgeon squeezes or otherwise urges the two handles 26, toward one another, the levers 20, 22 pivot about the pin 24 thereby causing the connector 32 and the retaining socket 28 to move toward one another. When the surgeon releases the two handles 26, 30, the spring bias of the compression spring 44 urges the connector 32 away from the retaining socket 28 thereby causing the levers 20, 22 to pivot about the pin 24 so as to move the two handles 26, 30 away from one another.

As can be seen in FIG. 9, the lever 22 has a number of ratchet teeth 46 formed therein. A button 48 is secured to the lever 20 near its upper handle 26. The button 48 engages a locking pawl 50 such that the locking pawl 50 is moved into engagement with the ratchet teeth 46 by sliding the button 48 in a direction toward the cylinder housing 38, and disengaged from the ratchet teeth 46 by sliding it in the opposite direction. When the locking pawl 50 engages ratchet teeth 46, the levers 20, 22 of the patella clamp 12 are locked and therefore prevented from moving relative to one another. When the locking pawl 50 is disengaged from the ratchet teeth 46, the levers 20, 22 of the patella clamp 12 are free to move relative to one another.

As can be seen in FIG. 1, in the illustrative embodiment described herein, the clamp's retaining socket 28 is embodied as a ring 58 having a number of spikes 60 extending outwardly therefrom. The spikes 60 face toward a number of spikes of the patella drill guide and trial instrument 14 when the instrument 14 is secured to the clamp 12. In such an arrangement the clamp's spikes 60 cooperate with the spikes of the patella drill guide and trial instrument 14 to capture the patella 16 therebetween.

The patella clamp 12 may be constructed from a medical-grade metal such as stainless steel, cobalt chrome, or titanium, although other metals or alloys may be used.

Referring now to FIGS. 2-8, the patella drill guide and trial instrument 14 is shown in greater detail. As alluded to above, the patella drill guide and trial instrument 14 is used for fit assessment during a surgical procedure to implant the prosthetic patella component 18 into a patient's surgically-prepared patella 16. In essence, the patella drill guide and trial instrument 14 is used to ensure proper size selection of the ultimate patella component 18 (i.e., the patella component 18 that is ultimately implanted in the patient's patella 16). As will be discussed below in greater detail, the patella drill guide and trial instrument 14 also functions as a drill guide for guiding a drill bit used to drill the anchor holes in the patient's surgically-prepared patella 16 to receive the anchor pegs of the patella component 18 (see FIG. 30).

As shown in FIGS. 2, 5, 7, and 8, the patella drill guide and trial instrument 14 includes a posterior trial bearing surface 52 in the form of a curved peak surface configured to articulate with the condylar surface of the a prosthetic femoral component 154 (see FIGS. 28 and 29). In particular, the posterior trial bearing surface 52 of the patella drill guide and trial instrument 14 includes a lateral trial articular surface 54 and a medial trial articular surface 56. The trial articular surfaces 54, 56 are configured to articulate with a lateral condyle surface 172 and a medial condyle surface 174, respectively, of the femoral component 154. The femo-

ral component 154 is configured to emulate the configuration of the patient's natural femoral condyles, and, as such, the lateral condyle surface 172 and the medial condyle surface 174 are configured (e.g., curved) in a manner which mimics the condyles of the natural femur. The lateral condyle surface 172 and the medial condyle surface 174 are spaced apart from one another thereby defining trochlear groove 176 therebetween.

As can be seen in FIGS. 3, 5, 7, and 8, the patella drill guide and trial instrument 14 also includes a flat anterior surface 62 having a number of fixation members, such as spikes 64, extending anteriorly away therefrom. The spikes 64 are configured to be inserted into a surgically prepared posterior surface of the patient's natural patella (not shown). In such a way, the posterior trial bearing surface 52 of the patella drill guide and trial instrument 14 faces toward the femoral component 154 thereby allowing the posterior trial bearing surface 52 to articulate with the femoral condyle surfaces 172, 174 during flexion and extension of the patient's knee during a patellofemoral trialing procedure.

As shown in FIGS. 3, 5, 7, and 8, in the exemplary embodiment described herein, the spikes 64 of the patella drill guide and trial instrument 14 include a center spike 66 that is centered in the superior/inferior direction. This is shown geometrically in FIG. 3 where an imaginary line 72 bisects the anterior surface 62 of the patella drill guide and trial instrument 14 in the superior/inferior direction. As can be seen, the center of the center spike 66 is located on the imaginary line 72 thereby centering the center spike 66 in the superior/inferior direction. The spikes 64 of the patella drill guide and trial instrument 14 also include a pair of peripheral spikes 68, 70. As can be seen in FIG. 3, the center of the peripheral spike 68 is located on the superior half of the anterior surface 62 of the patella drill guide and trial instrument 14 (i.e., it is located superiorly of the imaginary line 72), with the other peripheral spike 70 being located on the inferior half of the anterior surface 62 of the patella drill guide and trial instrument 14 (i.e., it is located inferiorly of the imaginary line 72).

As can be seen in FIG. 3, in the exemplary embodiment described herein, each of the spikes 64 is medially located on the anterior surface 62 of the patella drill guide and trial instrument 14. In particular, the respective centers of each of the center spike 66 and the peripheral spikes 68, 70 are located on the medial half of the anterior surface 62 of the patella drill guide and trial instrument 14. This is shown geometrically in FIG. 3 where an imaginary line 74 bisects the anterior surface 62 of the patella drill guide and trial instrument 14 in the medial/lateral direction. The centers of each of the center spike 66 and a pair of peripheral spikes 68, 70 is positioned medially of the imaginary line 74 (i.e., positioned between the imaginary line 74 and the medial-most edge of the patella drill guide and trial instrument 14). Such medial positioning of the spikes 64 allows for fixation to the less sclerotic (i.e., softer) bone tissue generally present on the medial side of the patella 16.

As can be seen in FIGS. 5, 7, and 8, the center spike 66 is longer than both the peripheral spikes 68, 70. In such a way, rotational positioning of the patella drill guide and trial instrument 14 can be achieved prior to securing it in its final position on the resected posterior surface of the patient's patella 16. In particular, as will be described in more detail below, the surgeon may first insert the tip of the center spike 66 into the resected posterior surface of the patient's patella 16 and then alter the rotational position of the patella drill guide and trial instrument 14 by rotating it relative to the resected posterior surface of the patient's patella 16 about its

central axis defined by the center spike 66. Once the patella drill guide and trial instrument 14 has been rotated into a desired alignment position, the instrument 14 may be pressed into the resected posterior surface of the patient's patella 16 such that the peripheral spikes 68, 70 engage the bone tissue of the resected patella surface thereby preventing further rotation and maintaining the patella drill guide and trial instrument 14 in its desired rotational position relative to the resected posterior surface of the patient's patella 16.

The patella drill guide and trial instrument's body has a number of drill guide holes 76 formed therein. The drill guide holes 76 extend throughout the entire thickness of the patella drill guide and trial instrument's body. That is, a posterior end 78 of the drill guide holes 76 opens into the posterior trial bearing surface 52 of the patella drill guide and trial instrument 14, with the opposite anterior end 80 of the drill guide holes 76 opening into the instrument's anterior surface 62. The guide holes 76 function as drill guides for guiding a drill bit 84 used to drill the anchor holes 180 in the patient's surgically-prepared patella 16 to receive the anchor pegs of the patella component 18 (see FIGS. 30 and 31). As such, the size and position of each of the drill guide holes 76 coincides with the size and position of the anchor pegs 182 of the patella component 18 (see FIG. 19).

As can be seen best in FIGS. 2, 4, and 8, in the exemplary embodiment described herein, each of the drill guide holes 76 is counterbored. As such, the drill guide holes 76 have a larger diameter at their posterior ends 78 than they do at their anterior ends 80 thereby defining a shoulder 82 therebetween. The shoulder 82 functions as a depth stop to ensure the surgical drill bit 84 used to drill the anchor holes 182 in the patient's patella 16 drills to the desired depth. In particular, as can be seen in FIG. 30, the surgical drill bit 84 used to drill the anchor holes in the patient's patella 16 includes an annular collar 86 positioned above the upper end of the bit's cutting flutes 88. During use, the drill bit 84 may be advanced through one of the drill guide holes 76 and into the bone tissue of the patient's patella 16 until the lower surface of the collar 86 bottoms out or otherwise engages the shoulder 82 of the counterbored guide hole 76.

As shown best in FIGS. 1-3, the patella drill guide and trial instrument 14 has an alignment bore 90 formed therein. Like the drill guide holes 76, the alignment bore 90 extends throughout the entire thickness of the patella drill guide and trial instrument's body. That is, a posterior end 92 of the alignment bore 90 opens into the posterior trial bearing surface 52 of the patella drill guide and trial instrument 14, with the opposite anterior end 94 of the alignment bore 90 opening into a slot 102 of the instrument's connector.

The alignment bore 90 functions as a visual alignment guide that allows the surgeon to align the apex of the patella drill guide and trial instrument 14 with the former location of the apex of the patient's natural patella 16 prior to resection of the patella 16. In particular, a tip 96 of the curved peak surface of the posterior trial surface 52 defines the posterior-most point 98 of the patella drill guide and trial instrument 14. The alignment bore is formed in (i.e., opens into) the tip 96 of the posterior trial surface 52. As will be described below in greater detail, a surgeon may form (e.g., drill) a hole in the apex of the patient's natural patella 16 before resecting it. The hole is drilled to a depth that is deeper than the thickness of the bone to be removed during patella resection. As such, a shallow hole or indentation is still visible in the planar surgically-resected patella surface subsequent to bone removal. The surgeon may align the alignment bore 90 with this remaining hole in the patellar

bone to align the apex of the patella drill guide and trial instrument 14 with the former location of the apex of the patient's natural patella 16.

As can be seen in FIGS. 2-4 and 6, the alignment bore 90 has a diameter that is smaller than the diameter of each of the drill guide holes 76. In such a way, the surgical drill bit 84 cannot inadvertently be passed through the alignment bore 90.

As alluded to above, the patella drill guide and trial instrument 14 may be selectively secured to the removable patella clamp 12. In that regard, the patella drill guide and trial instrument 14 includes a female connector geometry configured to receive the male geometry of the connector 32 of the patella clamp 12 (see FIG. 10). Specifically, the body of the patella drill guide and trial instrument 14 has a connecting slot 102 formed therein. As can be seen in FIGS. 7 and 8, the connecting slot 102 is positioned between the posterior trial bearing surface 52 and the anterior surface 62. The connecting slot 102 is shaped and sized to receive a connecting tongue 104 of the patella clamp's connector 32. As can be seen in FIGS. 10 and 11, the connecting tongue 104 includes a tip 106 which extends outwardly from a rounded surface of the main body of the connector 32. As can be seen in FIG. 6, the connecting slot 102 of the patella drill guide and trial instrument 14 has a similar shape, including a tip recess 108 that is sized and shaped to receive the tip 106 of the patella clamp's connecting tongue 104.

As can be seen in FIGS. 6 and 8, the upper sidewall 110 that defines the upper surface of the connecting slot 102 has a locking recess 112 defined therein. In the exemplary embodiment described herein, the locking recess 112 is generally hemispherical in shape. The locking recess 112 is sized and positioned to receive a locking mechanism of the patella clamp's connector 32 to secure the patella clamp 12 to the patella drill guide and trial instrument 14. In an embodiment, the locking mechanism is embodied as a biased plunger positioned on the tip 106 of the patella clamp's connecting tongue 104. In a specific embodiment, the biased plunger may be embodied as a spring-biased ball plunger 114. As the patella clamp's connector 32 is inserted in the connecting slot, the ball plunger 114 is urged downwardly against its spring bias by the upper sidewall 110 until it reaches a position in which the ball plunger 114 is moved into the locking recess 112 by its spring bias. When the ball plunger 114 is positioned in the locking recess 112, the patella clamp 12 is firmly secured to the patella drill guide and trial instrument 14 until sufficient force is applied to pull the two components apart by urging the ball plunger 114 downwardly out of the locking recess 112 to allow the patella clamp 12 to be separated from the patella drill guide and trial instrument 14.

As can be seen in FIG. 6, the alignment bore 90 of the patella drill guide and trial instrument 14 passes through the tip recess 108 of the connecting slot 102. As noted above, when the patella clamp 12 is secured to the patella drill guide and trial instrument 14, the tip 106 of the patella clamp's connecting tongue 104 is positioned in the tip recess 108 of the connecting slot 102. As shown in FIG. 11, when so positioned, the tip 106 of the patella clamp's connecting tongue 104 blocks the alignment bore 90 or otherwise prevents passage through it. More specifically, when the tip 106 of the patella clamp's connecting tongue 104 is positioned in the tip recess 108, a drill bit or other instrument is prevented from passing through the alignment bore 90.

In order to fit the needs of a given patient's anatomy, the patella drill guide and trial instrument 14 may be provided in a number of different sizes. For example, in the illustrative

embodiment described herein, the patella drill guide and trial instrument **14** may be embodied in five different medial/lateral lengths (e.g., 29 mm, 32 mm, 35 mm, 38 mm, and 41 mm) so as to mimic the various sizes of the prosthetic patella components **18**.

In the exemplary embodiment described herein, the patella drill guide and trial instrument **14** is embodied as a monolithic metal body constructed with a biocompatible metal that allows for smooth articulation between the patella drill guide and trial instrument **14** and the femoral component **154**. Examples of such biocompatible metals include stainless steel, cobalt chrome, or titanium, although other metals or alloys may be used. The patella drill guide and trial instrument **14** may also be embodied as a monolithic polymer trial instrument. As such, the patella drill guide and trial instrument **14** may be made of any suitable medical-grade polymeric material. Examples of such polymeric materials include polyetheretherketone (PEEK), ultrahigh molecular weight polyethylene (UHMWPE), or acetal. In such an embodiment, the monolithic polymer trial may include metallic inserts (e.g., sleeves) positioned in the drill guide holes **76**.

As can be seen in FIGS. **12-14**, the removable clamp **12** may also be secured to a compression socket **120**. The compression socket **120** may be used to assert clamping pressure on the patella component **18** as it is cemented in place on the patient's resected patella **16**. The compression socket **120** includes a base in the form of a ring **122**. The ring **122** has a ring-shaped compressible cushion **124** secured thereto. The compression cushion **124** is constructed of a deformable material and functions to engage the posterior bearing surface **188** of the patella component **18** thereby urging it toward the patella **16** when a clamping force is applied by use of the patella clamp **12**.

The compression socket **120** includes a female connector geometry that is similar to that of the patella drill guide and trial instrument **14** and, as a result, configured to receive the male geometry of the connector **32** of the patella clamp **12** (see FIG. **12**). Specifically, the ring **122** of the compression socket **120** has a connecting slot **126** formed therein. As can be seen in FIGS. **13** and **14**, the connecting slot **126** is shaped and sized to receive the connecting tongue **104** of the patella clamp's connector **32**. As can be seen in FIG. **12**, the tip **106** of the connecting tongue **104** extends beyond the inner annular-shaped wall **128** of the compression socket's ring **122** such that the spring-biased ball plunger **114** engages the annular wall **128** of the ring **122** to secure clamp **12** to the compression socket **120**. In particular, as the patella clamp's connector **32** is inserted into and through the compression socket's connecting slot **126**, the ball plunger **114** is urged downwardly against its spring bias by the upper sidewall **130** until it exits the connecting slot **126** into the ring's center at which time the ball plunger **114** is moved upwardly by its spring bias. When the ball plunger **114** is so positioned, the patella clamp **12** is firmly secured to the compression socket **120** until sufficient force is applied to pull the two components apart by urging the ball plunger **114** downwardly and back into the connecting slot **126** thereby allowing the patella clamp **12** to be separated from the compression socket **120**.

The ring **122** of the compression socket **120** may be embodied as a monolithic metal body constructed with a biocompatible such as stainless steel, cobalt chrome, or titanium, although other metals or alloys may be used. The ring **122** may also be embodied as a monolithic polymer trial instrument constructed with any suitable medical-grade polymeric material such as polyetheretherketone (PEEK),

ultrahigh molecular weight polyethylene (UHMWPE), or acetal. The compressible cushion **124** may be constructed with any suitable medical-grade compressible material such as silicone.

As can be seen in FIGS. **15** and **16**, the patella drill guide and trial instrument **14** may also be secured to an alignment handle **140**. Use of the alignment handle **140** allows the surgeon to assess the rotational alignment of the patella drill guide and trial instrument **14** as it articulates in the trochlear groove of the femoral component **154** during trialing of the patellofemoral joint. The alignment handle **140** includes a relatively flat elongated flange **142** having a connector **144** formed in one end thereof. The connector **144** of the alignment handle is identical to the patella clamp's connector **32** so as to mate with the connector of the patella drill guide and trial instrument **14** in an identical manner as the patella clamp **12**. As such, the alignment handle's connector **144** has a connecting tongue **146** that includes a tip **148** which extends outwardly from a rounded surface of the main body of the connector **144**. The connecting tongue **146** and its tip **148** are received into the connecting slot **102** of the patella drill guide and trial instrument **14** in a similar manner as the similar structures of the patella clamp's connector **32**.

Likewise, the alignment handle's connector **144** includes a locking mechanism to secure the alignment handle **140** to the patella drill guide and trial instrument **14**. In an embodiment, the locking mechanism is embodied as a biased plunger positioned on the tip **148** of the alignment handle's connector **144**. In a specific embodiment, the biased plunger may be embodied as a spring-biased ball plunger **152**. The ball plunger **152** may be captured in the locking recess **112** of the connecting slot **102** of the patella drill guide and trial instrument **14** to firmly secure the alignment handle **140** to the patella drill guide and trial instrument **14** in an identical manner to as described above in regard to attachment of the patella clamp **12**. The alignment handle **140** remains secured to the patella drill guide and trial instrument **14** by the ball plunger **152** until sufficient force is applied to pull the two components apart by urging the ball plunger **152** downwardly out of the locking recess **112** to allow the alignment handle **140** to be separated from the patella drill guide and trial instrument **14**.

Referring now to FIG. **17**, there is shown another embodiment of the patella drill guide and trial instrument **14**. In particular, whereas the patella drill guide and trial instrument **14** of FIGS. **1-9** is embodied as a trial instrument mimicking a modified dome patella component, the patella drill guide and trial instrument **14** may be embodied to mimic other types of patella components. For example, as shown in FIG. **17**, the patella drill guide and trial instrument **14** may be embodied to mimic "conforming" or "anatomic" patella components which are designed to conform with the condylar surfaces of the femur. Whereas modified dome patella components allow for greater movement between the patella component and the femoral component of the knee prosthesis, anatomic patella components are more constrained relative to the femoral component. As shown in FIG. **17**, such an "anatomic" patella drill guide and trial instrument **14** may be embodied with similar features to as described above in regard to the "modified dome" patella drill guide and trial instrument **14**.

Referring now to FIGS. **20-32**, there is shown a surgical procedure in which the various instruments described herein in regard to FIGS. **1-17** are used to surgically prepare the patient's patella **16** for implantation of the prosthetic patella component **18** of FIGS. **19** and **20**. The surgical procedure begins with preoperative planning in which, amongst other

things, a CT scan or other type of preoperative image may be obtained to plan the placement location and orientation of the patella component 18. With the preoperative planning complete, the patient's soft tissue is dissected and retracted in order to allow access to the knee. Full exposure of the patient's joint is typically achieved so as to expose, in addition to the patella 16, the patient's femur 150 and tibia 152 (see FIGS. 20 and 21).

In addition to implantation of the patella component 18, the surgical procedure also replaces the patient's natural distal femur 150 with a prosthetic femoral component 154 and the patient's natural proximal tibia 152 with a tibial tray 156 and tibial bearing 158 (see FIGS. 28 and 29). However, the surgical implantation of the femoral component 154, the tibial tray 156, and tibial bearing 158 is not described in detail herein. Moreover, although the patella 16 is shown in its anatomical position relative to the femur 150 and the tibia 152 in FIGS. 20 and 21, the patella 16 is shown in isolation from its anatomical position in the remaining figures (with the exception of FIGS. 28 and 29) for clarity of description.

As shown in FIG. 22, prior to resection of the patient's patella 16, the surgeon first forms an alignment feature in the apex 160 of the patella's posterior surface 162. In particular, the surgeon may drill a hole 164 in the apex 160 of the posterior surface 162 of the patient's natural patella 16 with a drill 166 before resecting it. As can be seen in a comparison of FIGS. 22 and 23, the alignment hole 164 is drilled to a predetermined depth that is deeper than the thickness of the bone to be removed during patella resection. As such, the hole 164 (or a slight indentation depending on the depth of the drill) is still visible in the planar surgically-resected patellar surface 170 subsequent to bone removal.

Once the alignment hole 164 has been drilled in the posterior surface 162 of the patient's natural patella 16, the surgeon may then resect the patient's natural patella 16. Specifically, the surgeon may use a resection guide (not shown) and a bone saw (also not shown) to produce a generally planar surgically-resected patellar surface 170 onto which the patella component 18 will be subsequently implanted. Although numerous different instruments and methods may be used to resect the patient's natural patella 16, illustrative instruments and methods for doing so are described in commonly-owned, co-pending U.S. patent application Ser. No. 13/533,607 which is entitled "Patella Orthopaedic Surgical Method" and was filed on Jun. 26, 2012.

As alluded to above and as shown in FIGS. 23 and 24, the alignment hole 164 drilled by the surgeon prior to resection is still visible in the planar surgically-resected patellar surface 170 subsequent to bone removal. Depending on the depth of the drill procedure utilized to form the alignment hole 164, it may appear as a slight indentation in the surgically-resected patellar surface 170.

Once the resection of the patient's natural patella 16 is completed, the surgeon determines the appropriate size patella component 18 to implant on the surgically-resected patellar surface 170. To do so, the surgeon uses the patella drill guide and trial instrument 14. Specifically, as will now be described in more detail, the patella drill guide and trial instrument 14 may be secured to the patient's surgically-resected patellar surface 170 to function as both a sizing trial and a drill guide. To do so, the surgeon selects an initial one of the differently-sized patella drill guide and trial instruments 14 that the surgeon estimates is the proper size for the patient. As shown in FIGS. 25 and 26, the surgeon then positions the selected patella drill guide and trial instrument 14 over the surgically-resected patellar surface 170 and

assesses coverage. Specifically, the surgeon first aligns the alignment bore 90 of the selected patella drill guide and trial instrument 14 with the alignment hole 164 drilled by the surgeon (prior to resection) in the planar surgically-resected patellar surface 170. To do so, the surgeon visualizes the drilled alignment hole 164 of the planar surgically-resected patellar surface 170 through the instrument's alignment bore 90 and adjusts the position of the selected patella drill guide and trial instrument 14 such that the drilled alignment hole 164 and the instrument's alignment bore 90 are aligned with one another. Once aligned in such a manner, the surgeon may then assess the coverage of the selected patella drill guide and trial instrument 14. If the surgeon determines the selected patella drill guide and trial instrument 14 is not the proper size, the initial patella drill guide and trial instrument 14 is removed and a patella drill guide and trial instrument 14 having a different size is selected, aligned over the surgically-resected patellar surface 170, and assessed.

Once the patella drill guide and trial instrument 14 of the proper size has been determined, the surgeon secures the patella drill guide and trial instrument 14 to the surgically-resected patellar surface 170. To do so, the surgeon positions the patella drill guide and trial instrument 14 in a desired location and orientation for the final implant (i.e., the patella component 18) by aligning the alignment bore 90 of the selected patella drill guide and trial instrument 14 with the drilled alignment hole 164 of the planar surgically-resected patellar surface 170. So positioned, the spikes 64 of the patella drill guide and trial instrument 14 face downwardly toward the surgically-resected patellar surface 170. As can be seen in FIG. 26, when aligned over the surgically-resected patellar surface 170, the peripheral spikes 68, 70 of the patella drill guide and trial instrument 14 are medially positioned relative to the center of the patella 16.

As can also be seen in FIG. 26, as the patella drill guide and trial instrument 14 is urged toward the patella 16, the center spike 66, which is longer than both the peripheral spikes 68, 70, is first to contact the surgically-resected patellar surface 170. In such a way, rotational positioning of the patella drill guide and trial instrument 14 can be achieved prior to securing it in its final position on the surgically-resected patellar surface 170. In particular, the surgeon may first insert the tip of the center spike 66 into the surgically-resected patellar surface 170 of the patient's patella 16. The surgeon may then adjust the rotational position of the patella drill guide and trial instrument 14 by rotating it relative to the surgically-resected patellar surface 170 about its central axis defined by the center spike 66.

As shown in FIG. 27, once the patella drill guide and trial instrument 14 has been rotated into a desired alignment position, the patella drill guide and trial instrument 14 may be pressed into the surgically-resected patellar surface 170 such that the peripheral spikes 68, 70 engage and seat in the bone tissue of the surgically-resected patellar surface 170. Doing so prevents further rotation of the patella drill guide and trial instrument 14 and maintains it in its desired position relative to the surgically-resected patellar surface 170 of the patient's patella 16.

It should be appreciated that the surgeon may press the patella drill guide and trial instrument 14 into the bone tissue of the surgically-resected patellar surface 170 by hand with the application of finger pressure alone. However, in certain cases, it may be necessary to utilize additional force in order to fully seat the patella drill guide and trial instrument 14 in the surgically-resected patellar surface 170. In such cases, the surgeon may install the removable clamp 12 to the patella drill guide and trial instrument 14 and use the clamp

13

12 to apply a clamping force which urges the instrument's spikes 64 into the bone tissue of the surgically-resected patellar surface 170 so as to fully seat the patella drill guide and trial instrument 14.

Once the patella drill guide and trial instrument 14 has been installed on the surgically-resected patellar surface 170, the surgeon may then perform a trial of the patellofemoral joint to assess size and positioning. To do so, the surgeon first installs the alignment handle 140 to the patella drill guide and trial instrument 14. Use of the alignment handle 140 allows the surgeon to assess the rotational alignment of the patella drill guide and trial instrument 14 as it articulates in the trochlear groove of the femoral component 154 during trialing of the patellofemoral joint. To secure the alignment handle 140 to the patella drill guide and trial instrument 14, the surgeon inserts the handle's connector 144 into the connecting slot 102 of the patella drill guide and trial instrument 14. In doing so, the handle's ball plunger 152 is captured in the locking recess 112 of the connecting slot 102 of the patella drill guide and trial instrument 14 to firmly secure the alignment handle 140 to the patella drill guide and trial instrument 14.

Once the alignment handle 140 is installed, the surgeon may then position the patella drill guide and trial instrument 14 such that its posterior trial bearing surface 52 is positioned to articulate within the trochlear groove 176 of the femoral condyle surfaces 172, 176 of the femoral component 154. The surgeon may then manipulate the patient's leg so as to perform a trial articulation of the patellofemoral joint. In doing so, the surgeon may use the alignment handle 140 as a visual indicator of the rotational alignment of the patella drill guide and trial instrument 14 as it articulates in the trochlear groove 176 of the femoral component 154. Specifically, as can be seen in FIG. 28, if the medial edge of the patella drill guide and trial instrument 14 (i.e., the edge into which the connecting slot 102 is formed) is properly aligned, the alignment handle 140 extends outwardly in a direction generally perpendicular to the long axis of the femur and tibia. That is, it extends outwardly generally in the medial/lateral direction.

However, if the rotational position of the patella drill guide and trial instrument 14 is not properly aligned, the alignment handle extends outwardly at an angle which is skewed, such as shown in FIG. 29. That is, if not properly aligned, the alignment handle 140 extends outwardly in a direction that is not generally perpendicular to the long axis of the femur and tibia. As such, the alignment handle 140 is not arranged generally in the medial/lateral direction.

Based on the above, the surgeon may assess the rotational position and alignment of the patella drill guide and trial instrument 14 throughout a trial articulation of the patellofemoral joint by monitoring the position of the alignment handle 140. If at any time during the trialing procedure the alignment handle 140 does not maintain the desired angle relative to the long axis of the femur and tibia (i.e., it does not extend generally in the medial/lateral direction), the surgeon may perform a corrective procedure on the positioning of the patella drill guide and trial instrument 14 to improve the rotational positioning thereof.

Once the surgeon has completed the trial articulation of the patellofemoral joint and made any necessary adjustments to the position of the patella drill guide and trial instrument 14, the surgeon may then drill a number of anchor holes 180 in the surgically-resected patellar surface 170. The anchor holes 180 are sized and positioned to receive the anchor pegs 182 of the patella component 18 (see FIG. 19). To do so, the surgeon first secures the removable clamp 12 to the patella

14

drill guide and trial instrument 14 by advancing the clamp's connector 32 into the connecting slot 102 of the patella drill guide and trial instrument 14. In doing so, the handle's ball plunger 114 is captured in the locking recess 112 of the connecting slot 102 of the patella drill guide and trial instrument 14 to firmly secure the patella clamp 12 to the patella drill guide and trial instrument 14.

The surgeon then squeezes the clamp's handles 26, 30 toward one another, thereby moving the patella drill guide and trial instrument 14 and the retaining socket 28 toward one another so as to clamp the patella 16 therebetween. With the patella 16 secured by the clamp 12, the surgeon may now drill the anchor holes 180. To do so, the surgeon advances the rotating tip 184 of the surgical drill's bit 84 into the opening formed in the posterior trial bearing surface 52 of one of the drill guide holes 76 and through the patella drill guide and trial instrument 14 so that it exits the guide hole 76 through the instrument's anterior surface 62 and enters the bone tissue of the surgically-resected patellar surface 170. The surgeon continues to advance the drill bit 84 into the patella 16 until the lower surface of the bit's collar 86 bottoms out or otherwise engages the depth stop (i.e., the shoulder 82) of the counterbored guide hole 76. The surgeon then drills the remaining anchor holes 180 in a similar manner.

As noted above, the size and position of each of the drill guide holes 76 coincides with the size and position of the anchor pegs 182 of the patella component 18 (see FIG. 19). As such, once the surgeon has advanced the drill's surgical bit 84 through each of the guide holes 76, the surgically-resected patellar surface 170 is prepared for implantation of the patella component 18, as shown in FIG. 31.

It should be appreciated that during such drilling of the anchor holes 180, the surgeon is prevented from advancing the drill's surgical bit 84 through the alignment bore 90 of the patella drill guide and trial instrument 14 since the bore's diameter is smaller than the bit's diameter. Moreover, as described above, when the patella clamp 12 is secured to the patella drill guide and trial instrument 14, the tip 106 of the patella clamp's connecting tongue 104 is positioned in the tip recess 108 of the instrument's connecting slot 102. As shown in FIG. 11, when so positioned, the tip 106 of the patella clamp's connecting tongue 104 blocks the alignment bore 90 or otherwise prevents passage through it. As such, not only is the drill bit 84 used for drilling the anchor holes 180 prevented from advancing through the alignment bore 90 due to the bore's smaller diameter, other instruments are likewise prevented from passing through the alignment bore 90 to the surgically-resected patellar surface 170 by the presence of the tip 106 of the patella clamp's connecting tongue 104 being positioned in the tip recess 108 of the instrument's connecting slot 102.

It should also be appreciated that in some cases, the surgeon may desire to utilize the patella drill guide and trial instrument 14 to drill the anchor holes 180 without using the patella clamp 12. In such a case, the surgeon may maintain the patella drill guide and trial instrument 14 with the application of finger pressure alone.

Referring now to FIG. 32, once the anchor holes 180 have been drilled in the surgically-resected patellar surface 170, the surgeon implants the appropriately sized patella component 18 (i.e., a component 18 having a size (i.e., medial/lateral length) selected through trialing as described above) in the patient's patella 16. The surgeon may first apply bone cement to the anterior surface 190 of the patella component 18. The patella component 16 is then positioned over the surgically-resected patellar surface 170 such that the com-

15

ponent's anchor pegs **182** are aligned with their respective anchor holes **180**. Thereafter, the patella component **12** may be advanced such that the anchor pegs **182** are received into the anchor holes **180** and the anterior surface **190** is positioned in contact with the surgically-resected patellar surface **170**.

The removable clamp **12** may then be secured to the compression socket **120** by inserting the clamp's connector **32** into the socket's connecting slot **126**. The compression socket **120** may then be used to assert clamping pressure on the patella component **18** as it is cemented in place on the patient's resected patella **16**. That is, the compression socket **120** and clamp **12** may be used to maintain clamping pressure on the patella component **18** as the bone cement polymerizes. To do so, the ring-shaped compressible cushion **124** of the compression socket **120** is positioned over the posterior bearing surface **188** of the patella component **18**. The surgeon then squeezes the clamp's handles **26**, **30** toward one another, thereby moving the compression socket **120** and the retaining socket **28** toward one another. During such movement, the compressible cushion **120** of the compression socket **120** is advanced into contact with the posterior bearing surface **188** of the patella component **16**. The patella component **16** is seated within and stabilized by a concave surface **192** of the compressible cushion **120** (see FIG. **14**) such that the patella component **16** is clamped firmly to the resected patella **16** until polymerization is complete and the patella component **16** is secured thereto. The surgeon may slide the patella clamp's button **48** forward to lock the clamp **12** in its current position during the polymerization process.

While the disclosure has been illustrated and described in detail in the drawings and foregoing description, such an illustration and description is to be considered as exemplary and not restrictive in character, it being understood that only illustrative embodiments have been shown and described and that all changes and modifications that come within the spirit of the disclosure are desired to be protected.

There are a plurality of advantages of the present disclosure arising from the various features of the method, apparatus, and system described herein. It will be noted that alternative embodiments of the method, apparatus, and system of the present disclosure may not include all of the features described yet still benefit from at least some of the advantages of such features. Those of ordinary skill in the art may readily devise their own implementations of the method, apparatus, and system that incorporate one or more of the features of the present invention and fall within the spirit and scope of the present disclosure as defined by the appended claims.

The invention claimed is:

1. A patella drill guide and trial instrument, comprising: a single monolithic polymeric body, comprising:

- (i) a posterior trial bearing surface configured to articulate with a condylar surface of a prosthetic femoral component, the posterior trial bearing surface comprising a curved peak surface that defines the posterior-most surface of the patella drill guide and trial instrument,
- (ii) an anterior surface having a plurality of spikes extending outwardly therefrom that are configured to engage a surgically-prepared posterior surface of a patient's patella to prevent the patella drill guide and trial instrument from rotating with respect to the patient's patella when the anterior surface is engaged with the surgically-prepared posterior surface of the patient's patella, and

16

(iii) a number of drill guide holes extending through the patella drill guide and trial instrument from the posterior trial bearing surface to the anterior surface, and a metallic sleeve inserted into each of the number of drill guide holes,

wherein the plurality of spikes includes a center spike and a number of peripheral spikes, the center spike is longer than the number of peripheral spikes,

wherein the patella drill guide and trial instrument is configured to be positioned in a first position where only the center spike engages the surgically-prepared posterior surface of a patient's patella to allow rotational positioning of the patella drill guide and trial instrument relative to the patient's patella about a central axis defined by the center spike, and

wherein the patella drill guide and trial instrument is configured to be positioned in a second position where both the center spike and the number of peripheral spikes engage the surgically-prepared posterior surface of a patient's patella to prevent the patella drill guide and trial instrument from rotating with respect to the patient's patella.

2. The patella drill guide and trial instrument of claim **1**, wherein the posterior bearing surface comprises:

- a medial trial articular surface configured to articulate with a medial condyle surface of a prosthetic femoral component, and
- a lateral trial articular surface configured to articulate with a lateral condyle surface of the prosthetic femoral component.

3. The patella drill guide and trial instrument of claim **1**, wherein:

- an imaginary line bisects the anterior surface in the medial/lateral direction, and
- the center of each of the number of spikes is positioned medially of the imaginary line.

4. The patella drill guide and trial instrument of claim **1**, wherein:

- the number of peripheral spikes comprises a superior spike and an inferior spike,
- a superior/inferior imaginary line bisects the anterior surface in the superior/inferior direction,
- the center of the center spike is located on the superior/inferior imaginary line,
- the center of the superior spike is positioned superiorly of the superior/inferior imaginary line, and
- the center of the inferior spike is positioned inferiorly of the superior/inferior imaginary line.

5. The patella drill guide and trial instrument of claim **4**, wherein:

- a medial/lateral imaginary line bisects the anterior surface in the medial/lateral direction, and
- the center of each of the center, superior, and inferior spikes is positioned medially of the medial/lateral imaginary line.

6. The patella drill guide and trial instrument of claim **1**, wherein the number of drill guide holes are counterbored holes.

7. The patella drill guide and trial instrument of claim **1**, further comprising a connecting slot positioned between the posterior trial bearing surface and the anterior surface, the connecting slot being configured to receive a connecting tongue of a removable clamp so as to secure the patella drill guide and trial instrument to the removable clamp.

8. A patella drill guide and trial instrument, comprising: a single monolithic body, comprising:

17

a posterior trial bearing surface configured to articulate with a condylar surface of a prosthetic femoral component, the posterior trial bearing surface comprising a curved peak surface that defines the posterior-most surface of the patella drill guide and trial instrument, an anterior surface having a center spike and a plurality of peripheral spikes extending outwardly therefrom that are configured to engage a surgically-prepared posterior surface of a patient's patella to prevent the patella drill guide and trial instrument from rotating with respect to the patient's patella when the anterior surface is engaged with the surgically-prepared posterior surface of the patient's patella, wherein (i) a superior/inferior imaginary line bisects the anterior surface in the superior/inferior direction, (ii) the center of the center spike is located on the superior/inferior imaginary line, and (iii) the center spike is longer than the peripheral spikes, and

a number of drill guide holes extending through the patella drill guide and trial instrument from the posterior trial bearing surface to the anterior surface, wherein the patella drill guide and trial instrument is configured to be positioned in a first position where only the center spike engages the surgically-prepared posterior surface of a patient's patella to allow rotational positioning of the patella drill guide and trial instrument relative to the patient's patella about a central axis defined by the center spike, and

wherein the patella drill guide and trial instrument is configured to be positioned in a second position where both the center spike and the peripheral spikes engage the surgically-prepared posterior surface of a patient's patella to prevent the patella drill guide and trial instrument from rotating with respect to the patient's patella.

9. The patella drill guide and trial instrument of claim **8**, wherein the posterior bearing surface comprises:

a medial trial articular surface configured to articulate with a medial condyle surface of a prosthetic femoral component, and

18

a lateral trial articular surface configured to articulate with a lateral condyle surface of the prosthetic femoral component.

10. The patella drill guide and trial instrument of claim **8**, wherein:

an imaginary line bisects the anterior surface in the medial/lateral direction, and

the center of the center spike and each of the number of peripheral spikes is positioned medially of the imaginary line.

11. The patella drill guide and trial instrument of claim **8**, wherein:

the number of peripheral spikes comprises a superior spike and an inferior spike,

the center of the superior spike is positioned superiorly of the superior/inferior imaginary line, and

the center of the inferior spike is positioned inferiorly of the superior/inferior imaginary line.

12. The patella drill guide and trial instrument of claim **11**, wherein:

a medial/lateral imaginary line bisects the anterior surface in the medial/lateral direction, and

the center of both of the center, superior, and inferior spikes is positioned medially of the medial/lateral imaginary line.

13. The patella drill guide and trial instrument of claim **8**, wherein the number of drill guide holes are counterbored holes.

14. The patella drill guide and trial instrument of claim **8**, further comprising a connecting slot positioned between the posterior trial bearing surface and the anterior surface, the connecting slot being configured to receive a connecting tongue of a removable clamp so as to secure the patella drill guide and trial instrument to the removable clamp.

15. The patella drill guide and trial instrument of claim **8**, wherein the posterior trial bearing surface and the anterior surface comprise a monolithic polymeric body, further comprising a metallic sleeve inserted into each of the number of drill guide holes.

* * * * *