



US009554903B2

(12) **United States Patent**  
**Rowe et al.**

(10) **Patent No.:** **US 9,554,903 B2**  
(45) **Date of Patent:** **\*Jan. 31, 2017**

(54) **RAPID DEPLOYMENT PROSTHETIC HEART VALVE**

(71) Applicant: **Edwards Lifesciences Corporation**, Irvine, CA (US)

(72) Inventors: **Stanton J. Rowe**, Newport Coast, CA (US); **Larry L. Wood**, Coto de Caza, CA (US); **Henry Bourang**, Irvine, CA (US); **George Bakis**, La Habra Heights, CA (US); **Benjamin Spenser**, D.N. Hof HaCarmel (IL); **Netanel Benichou**, D.N. Hof HaCarmel (IL); **Assaf Bash**, Benyamina-Givat Ada (IL); **Yaron Keidar**, Irvine, CA (US)

(73) Assignee: **Edwards Lifesciences Corporation**, Irvine, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.  
This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/571,141**

(22) Filed: **Dec. 15, 2014**

(65) **Prior Publication Data**  
US 2015/0105856 A1 Apr. 16, 2015

**Related U.S. Application Data**  
(63) Continuation of application No. 13/954,822, filed on Jul. 30, 2013, now Pat. No. 8,911,493, which is a (Continued)

(51) **Int. Cl.**  
*A61F 2/24* (2006.01)  
*A61F 2/90* (2013.01)

(52) **U.S. Cl.**  
CPC ..... *A61F 2/2418* (2013.01); *A61F 2/2409* (2013.01); *A61F 2/2412* (2013.01); *A61F 2/2445* (2013.01); (Continued)

(58) **Field of Classification Search**  
CPC ..... *A61F 2/24*; *A61F 2/2412*; *A61F 2/2415*; *A61F 2/2418*  
See application file for complete search history.


(56) **References Cited**  
U.S. PATENT DOCUMENTS  
3,143,742 A 8/1964 Cromie  
3,320,972 A 5/1967 High et al.  
(Continued)

FOREIGN PATENT DOCUMENTS  
CN 2356656 Y 1/2000  
EP 0125393 A1 11/1984  
(Continued)

OTHER PUBLICATIONS  
Krakow, "3F Therapeutics, Inc. Announces the First Clinical Implantation of the 3F Enable Aortic Heart Valve.TM., a Patented, Sutureless Implantation, Replacement Heart Valve Intended to Save Valuable Surgery Time and Reduce Time Related Complications . . ." Healthcare Sales & Marketing Network News Feed, Jan. 18, 2005, pp. 1-2.  
(Continued)

*Primary Examiner* — Jason-Dennis Stewart  
(74) *Attorney, Agent, or Firm* — Guy Cumberbatch; Pui Tong Ho

(57) **ABSTRACT**  
A heart valve prosthesis that can be quickly and easily implanted during a surgical procedure is provided. The prosthetic valve comprises a support structure that is deployed at a treatment site. The prosthetic valve further comprises a valve member configured to be quickly connected to the support structure. The support structure may take the form of a stent that is expanded at the site of a native valve. If desired, the native leaflets may remain and the stent may be used to hold the native valve open. In this case, the stent may be balloon expandable and configured to resist the powerful recoil force of the native leaflets. The support (Continued)



structure is provided with a coupling means for attachment to the valve member, thereby fixing the position of the valve member in the body. The valve member may be expandable or a non-expandable type.

**9 Claims, 26 Drawing Sheets**

**Related U.S. Application Data**

continuation of application No. 11/441,406, filed on May 24, 2006, now Pat. No. 8,500,798.

(60) Provisional application No. 60/684,443, filed on May 24, 2005.

(52) **U.S. Cl.**

CPC ..... *A61F 2/90* (2013.01); *A61F 2220/0008* (2013.01); *A61F 2220/0016* (2013.01); *A61F 2220/0025* (2013.01); *A61F 2220/0041* (2013.01); *A61F 2220/0066* (2013.01); *A61F 2220/0075* (2013.01); *A61F 2220/0083* (2013.01); *A61F 2230/0078* (2013.01); *A61F 2250/006* (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,371,352 A 3/1968 Siposs et al.  
 3,409,013 A 11/1968 Berry  
 3,546,710 A 12/1970 Shumakov et al.  
 3,574,865 A 4/1971 Hamaker  
 3,628,535 A 12/1971 Ostrowsky et al.  
 3,657,744 A 4/1972 Ersek  
 3,686,740 A 8/1972 Shiley  
 3,755,823 A 9/1973 Hancock  
 3,839,741 A 10/1974 Haller  
 3,997,923 A 12/1976 Possis  
 4,035,849 A 7/1977 Angell et al.  
 4,078,468 A 3/1978 Civitello  
 4,079,468 A 3/1978 Liotta et al.  
 4,084,268 A 4/1978 Ionescu et al.  
 4,106,129 A 8/1978 Carpentier et al.  
 4,172,295 A 10/1979 Batten  
 4,211,325 A 7/1980 Wright  
 4,217,665 A 8/1980 Bex et al.  
 4,218,782 A 8/1980 Rygg  
 4,259,753 A 4/1981 Liotta et al.  
 4,340,091 A 7/1982 Skelton et al.  
 4,343,048 A 8/1982 Ross et al.  
 4,364,126 A 12/1982 Rosen et al.  
 4,388,735 A 6/1983 Ionescu et al.  
 4,441,216 A 4/1984 Ionescu et al.  
 4,451,936 A 6/1984 Carpentier et al.  
 4,470,157 A 9/1984 Love  
 4,490,859 A 1/1985 Black et al.  
 4,501,030 A 2/1985 Lane  
 4,506,394 A 3/1985 Bedard  
 4,535,483 A 8/1985 Klawitter et al.  
 4,605,407 A 8/1986 Black et al.  
 4,626,255 A 12/1986 Reichart et al.  
 4,629,459 A 12/1986 Ionescu et al.  
 4,680,031 A 7/1987 Alonso  
 4,687,483 A 8/1987 Fisher et al.  
 4,702,250 A 10/1987 Ovil et al.  
 4,705,516 A 11/1987 Barone et al.  
 4,725,274 A 2/1988 Lane et al.  
 4,731,074 A 3/1988 Rousseau et al.  
 4,778,461 A 10/1988 Pietsch et al.  
 4,790,843 A 12/1988 Carpentier et al.  
 4,851,000 A 7/1989 Gupta  
 4,865,600 A 9/1989 Carpentier et al.  
 4,888,009 A 12/1989 Lederman et al.

4,914,097 A 4/1990 Oda et al.  
 4,960,424 A 10/1990 Grooters  
 4,993,428 A 2/1991 Arms  
 5,010,892 A 4/1991 Colvin et al.  
 5,032,128 A 7/1991 Alonso  
 5,037,434 A 8/1991 Lane  
 5,147,391 A 9/1992 Lane  
 5,163,953 A 11/1992 Vince  
 5,163,955 A 11/1992 Love et al.  
 5,258,023 A 11/1993 Reger  
 5,316,016 A 5/1994 Adams et al.  
 5,326,370 A 7/1994 Love et al.  
 5,326,371 A 7/1994 Love et al.  
 5,332,402 A 7/1994 Teitelbaum  
 5,360,444 A 11/1994 Kusuhara  
 5,370,685 A 12/1994 Stevens  
 5,376,112 A 12/1994 Duran  
 5,396,887 A 3/1995 Imran  
 5,397,351 A 3/1995 Pavcnik et al.  
 5,411,522 A 5/1995 Trott  
 5,411,552 A 5/1995 Andersen et al.  
 5,423,887 A 6/1995 Love et al.  
 5,425,741 A 6/1995 Lemp et al.  
 5,431,676 A 7/1995 Dubrul et al.  
 5,449,384 A 9/1995 Johnson  
 5,449,385 A 9/1995 Religa et al.  
 5,469,868 A 11/1995 Reger  
 5,476,510 A 12/1995 Eberhardt et al.  
 5,488,789 A 2/1996 Religa et al.  
 5,489,297 A 2/1996 Duran  
 5,489,298 A 2/1996 Love et al.  
 5,500,016 A 3/1996 Fisher  
 5,533,515 A 7/1996 Coller et al.  
 5,549,665 A 8/1996 Vesely et al.  
 5,562,729 A 10/1996 Purdy et al.  
 5,571,215 A 11/1996 Serman et al.  
 5,573,007 A 11/1996 Bobo, Sr.  
 5,578,076 A 11/1996 Krueger et al.  
 5,584,803 A 12/1996 Stevens et al.  
 5,618,307 A 4/1997 Donlon et al.  
 5,626,607 A 5/1997 Malecki et al.  
 5,628,789 A 5/1997 Vanney et al.  
 5,693,090 A 12/1997 Unsworth et al.  
 5,695,503 A 12/1997 Krueger et al.  
 5,713,952 A 2/1998 Vanney et al.  
 5,716,370 A 2/1998 Williamson, IV et al.  
 5,728,064 A 3/1998 Burns et al.  
 5,728,151 A 3/1998 Garrison et al.  
 5,735,894 A 4/1998 Krueger et al.  
 5,752,522 A 5/1998 Murphy  
 5,755,782 A 5/1998 Love et al.  
 5,766,240 A 6/1998 Johnson  
 5,776,187 A 7/1998 Krueger et al.  
 5,776,188 A 7/1998 Shepherd et al.  
 5,800,527 A 9/1998 Jansen et al.  
 5,814,097 A 9/1998 Serman et al.  
 5,814,098 A 9/1998 Hinnenkamp et al.  
 5,824,064 A 10/1998 Taheri  
 5,824,068 A 10/1998 Bugge  
 5,840,081 A 11/1998 Andersen et al.  
 5,848,969 A 12/1998 Panescu et al.  
 5,855,563 A 1/1999 Kaplan et al.  
 5,855,601 A 1/1999 Bessler et al.  
 5,865,801 A 2/1999 Houser  
 5,891,160 A 4/1999 Williamson, IV et al.  
 5,895,420 A 4/1999 Mirsch, II et al.  
 5,902,308 A 5/1999 Murphy  
 5,908,450 A 6/1999 Gross et al.  
 5,919,147 A 7/1999 Jain  
 5,921,934 A 7/1999 Teo  
 5,921,935 A 7/1999 Hickey  
 5,924,984 A 7/1999 Rao  
 5,928,281 A 7/1999 Huynh et al.  
 5,957,949 A 9/1999 Leonhardt et al.  
 5,972,004 A 10/1999 Williamson, IV et al.  
 5,984,959 A 11/1999 Robertson et al.  
 5,984,973 A 11/1999 Girard et al.  
 6,010,531 A 1/2000 Donlon et al.  
 6,042,607 A 3/2000 Williamson, IV et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,059,827 A	5/2000	Fenton, Jr.	7,445,631 B2	11/2008	Salahieh et al.
6,066,160 A	5/2000	Colvin et al.	7,524,330 B2	4/2009	Berrekouw
6,074,418 A	6/2000	Buchanan et al.	7,569,072 B2	8/2009	Berg et al.
6,081,737 A	6/2000	Shah	7,591,848 B2	9/2009	Allen
6,083,179 A	7/2000	Oredsson	7,618,446 B2	11/2009	Andersen et al.
6,099,475 A	8/2000	Seward et al.	7,618,447 B2	11/2009	Case et al.
6,106,550 A	8/2000	Magovern et al.	7,625,403 B2	12/2009	Krivoruchko
6,110,200 A	8/2000	Hinnenkamp	7,641,687 B2	1/2010	Chinn et al.
6,117,091 A	9/2000	Young et al.	7,704,277 B2	4/2010	Zakay et al.
6,126,007 A	10/2000	Kari et al.	7,708,775 B2	5/2010	Rowe et al.
6,162,233 A	12/2000	Williamson, IV et al.	7,740,655 B2	6/2010	Birdsall
6,168,614 B1	1/2001	Andersen et al.	7,799,069 B2	9/2010	Bailey et al.
6,176,877 B1	1/2001	Buchanan et al.	7,822,414 B2	10/2010	Bender et al.
6,197,054 B1	3/2001	Hamblin, Jr. et al.	7,887,583 B2	2/2011	Macoviak
6,217,611 B1	4/2001	Klostermeyer	7,896,913 B2	3/2011	Damm et al.
6,231,561 B1	5/2001	Frazier et al.	7,947,072 B2	5/2011	Yang et al.
6,241,765 B1	6/2001	Griffin et al.	7,967,857 B2	6/2011	Lane
6,245,102 B1	6/2001	Jayaraman	7,998,151 B2	8/2011	St. Goar et al.
6,264,611 B1	7/2001	Ishikawa et al.	8,062,355 B2	11/2011	Figulla et al.
6,264,691 B1	7/2001	Gabbay	8,246,675 B2	8/2012	Zegdi
6,283,127 B1	9/2001	Serman et al.	8,246,678 B2	8/2012	Salahieh et al.
6,287,339 B1	9/2001	Vazquez et al.	8,308,798 B2	11/2012	Pintor et al.
6,290,674 B1	9/2001	Roue et al.	8,323,337 B2	12/2012	Gurskis et al.
6,312,447 B1	11/2001	Grimes	8,348,998 B2	1/2013	Pintor et al.
6,312,465 B1	11/2001	Griffin et al.	8,500,798 B2	8/2013	Rowe et al.
6,322,526 B1	11/2001	Rosenman et al.	2001/0007956 A1	7/2001	Letac et al.
6,328,727 B1	12/2001	Frazier et al.	2001/0021872 A1	9/2001	Bailey et al.
6,350,282 B1	2/2002	Eberhardt	2001/0039435 A1	11/2001	Roue et al.
6,402,780 B2	6/2002	Williamson, IV et al.	2001/0039436 A1	11/2001	Frazier et al.
6,425,916 B1	7/2002	Garrison et al.	2001/0041914 A1	11/2001	Frazier et al.
6,440,164 B1	8/2002	DiMatteo et al.	2001/0041915 A1	11/2001	Roue et al.
6,454,799 B1	9/2002	Schreck	2001/0049492 A1	12/2001	Frazier et al.
6,458,100 B2	10/2002	Roue et al.	2002/0026238 A1	2/2002	Lane et al.
6,458,153 B1	10/2002	Bailey et al.	2002/0032481 A1	3/2002	Gabbay
6,468,305 B1	10/2002	Otte	2002/0058995 A1	5/2002	Stevens
6,491,624 B1	12/2002	Lotfi	2002/0077698 A1	6/2002	Peredo
6,530,952 B2	3/2003	Vesely	2002/0123802 A1	9/2002	Snyders
6,569,196 B1	5/2003	Vesely	2002/0138138 A1	9/2002	Yang
6,582,462 B1	6/2003	Andersen et al.	2002/0151970 A1	10/2002	Garrison et al.
6,652,578 B2	11/2003	Bailey et al.	2002/0188348 A1	12/2002	DiMatteo et al.
6,685,739 B2	2/2004	DiMatteo et al.	2002/0198594 A1	12/2002	Schreck
6,702,825 B2	3/2004	Frazier et al.	2003/0014104 A1	1/2003	Cribier
6,712,804 B2	3/2004	Roue et al.	2003/0023300 A1	1/2003	Bailey et al.
6,730,118 B2	5/2004	Spenser et al.	2003/0023303 A1	1/2003	Palmaz et al.
6,733,525 B2	5/2004	Yang et al.	2003/0036795 A1	2/2003	Andersen et al.
6,746,472 B2	6/2004	Frazier et al.	2003/0040792 A1	2/2003	Gabbay
6,764,508 B1	7/2004	Roehe et al.	2003/0055495 A1	3/2003	Pease et al.
6,767,362 B2	7/2004	Schreck	2003/0105519 A1	6/2003	Fasol et al.
6,773,457 B2	8/2004	Ivancev et al.	2003/0109924 A1	6/2003	Cribier
6,786,925 B1	9/2004	Schoon et al.	2003/0114913 A1	6/2003	Spenser et al.
6,790,229 B1	9/2004	Berrekouw	2003/0130729 A1	7/2003	Paniagua et al.
6,790,230 B2	9/2004	Beyersdorf et al.	2003/0149477 A1	8/2003	Gabbay
6,805,711 B2	10/2004	Quijano et al.	2003/0149478 A1	8/2003	Figulla et al.
6,893,459 B1	5/2005	Macoviak	2003/0153974 A1	8/2003	Spenser et al.
6,893,460 B2	5/2005	Spenser et al.	2003/0167089 A1	9/2003	Lane
6,908,481 B2	6/2005	Cribier	2003/0236568 A1	12/2003	Hojeibane et al.
6,939,365 B1	9/2005	Fogarty et al.	2004/0019374 A1	1/2004	Hojeibane et al.
7,011,681 B2	3/2006	Vesely	2004/0034411 A1	2/2004	Quijano et al.
7,025,780 B2	4/2006	Gabbay	2004/0039436 A1	2/2004	Spenser et al.
7,037,333 B2	5/2006	Myers et al.	2004/0044406 A1	3/2004	Woolfson et al.
7,070,616 B2	7/2006	Majercak et al.	2004/0093075 A1	5/2004	Kuehne
7,097,659 B2	8/2006	Woolfson et al.	2004/0106976 A1	6/2004	Bailey et al.
7,101,396 B2	9/2006	Artof et al.	2004/0122514 A1	6/2004	Fogarty et al.
7,147,663 B1	12/2006	Berg et al.	2004/0122516 A1	6/2004	Fogarty et al.
7,153,324 B2	12/2006	Case et al.	2004/0122526 A1	6/2004	Imran
7,186,265 B2	3/2007	Sharkawy et al.	2004/0167573 A1	8/2004	Williamson et al.
7,195,641 B2	3/2007	Palmaz et al.	2004/0186563 A1	9/2004	Lobbi
7,201,772 B2	4/2007	Schwammenthal et al.	2004/0186565 A1	9/2004	Schreck
7,252,682 B2	8/2007	Seguin	2004/0193261 A1	9/2004	Berrekouw
7,261,732 B2	8/2007	Justino	2004/0206363 A1	10/2004	McCarthy et al.
7,300,463 B2	11/2007	Liddicoat	2004/0210304 A1	10/2004	Seguin et al.
7,393,360 B2	7/2008	Spenser et al.	2004/0210305 A1	10/2004	Shu et al.
7,422,603 B2	9/2008	Lane	2004/0210307 A1	10/2004	Khairkahan
7,429,269 B2	9/2008	Schwammenthal et al.	2004/0225355 A1	11/2004	Stevens
7,442,204 B2	10/2008	Schwammenthal et al.	2004/0236411 A1	11/2004	Sarac et al.
			2004/0260389 A1	12/2004	Case et al.
			2004/0260390 A1	12/2004	Sarac et al.
			2005/0010285 A1	1/2005	Lambrecht et al.
			2005/0027348 A1	2/2005	Case et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0033398 A1 2/2005 Seguin  
 2005/0043760 A1 2/2005 Fogarty et al.  
 2005/0043790 A1 2/2005 Seguin  
 2005/0060029 A1 3/2005 Le et al.  
 2005/0065594 A1 3/2005 DiMatteo et al.  
 2005/0065614 A1 3/2005 Stinson  
 2005/0075584 A1 4/2005 Cali  
 2005/0075713 A1 4/2005 Biancucci et al.  
 2005/0075717 A1 4/2005 Nguyen et al.  
 2005/0075718 A1 4/2005 Nguyen et al.  
 2005/0075719 A1 4/2005 Bergheim  
 2005/0075720 A1 4/2005 Nguyen et al.  
 2005/0075724 A1 4/2005 Svanidze et al.  
 2005/0075728 A1 4/2005 Nguyen et al.  
 2005/0080454 A1 4/2005 Drews et al.  
 2005/0096738 A1 5/2005 Cali et al.  
 2005/0137682 A1 6/2005 Justino  
 2005/0137686 A1 6/2005 Salahieh et al.  
 2005/0137687 A1 6/2005 Salahieh et al.  
 2005/0137688 A1 6/2005 Salahieh et al.  
 2005/0137689 A1 6/2005 Salahieh et al.  
 2005/0137690 A1 6/2005 Salahieh et al.  
 2005/0137691 A1 6/2005 Salahieh et al.  
 2005/0137692 A1 6/2005 Haug et al.  
 2005/0137694 A1 6/2005 Haug et al.  
 2005/0137695 A1 6/2005 Salahieh et al.  
 2005/0137702 A1 6/2005 Haug et al.  
 2005/0159811 A1 7/2005 Lane  
 2005/0165477 A1 7/2005 Anduiza et al.  
 2005/0165479 A1 7/2005 Drews et al.  
 2005/0182483 A1 8/2005 Osborne et al.  
 2005/0182486 A1 8/2005 Gabbay  
 2005/0192665 A1 9/2005 Spenser et al.  
 2005/0203616 A1 9/2005 Cribier  
 2005/0203617 A1 9/2005 Forster et al.  
 2005/0203618 A1 9/2005 Sharkawy et al.  
 2005/0216079 A1 9/2005 MaCoviak  
 2005/0222674 A1 10/2005 Paine  
 2005/0234546 A1 10/2005 Nugent et al.  
 2005/0240259 A1 10/2005 Sisken et al.  
 2005/0251252 A1 11/2005 Stobie  
 2005/0261765 A1 11/2005 Liddicoat  
 2005/0283231 A1 12/2005 Haug et al.  
 2006/0025857 A1 2/2006 Bergheim et al.  
 2006/0052867 A1 3/2006 Revuelta et al.  
 2006/0058871 A1 3/2006 Zakay et al.  
 2006/0058872 A1 3/2006 Salahieh et al.  
 2006/0074484 A1 4/2006 Huber  
 2006/0085060 A1 4/2006 Campbell  
 2006/0095125 A1 5/2006 Chinn et al.  
 2006/0122634 A1 6/2006 Ino et al.  
 2006/0122692 A1 6/2006 Gilad et al.  
 2006/0136054 A1 6/2006 Berg et al.  
 2006/0149360 A1 7/2006 Schwammenthal et al.  
 2006/0154230 A1 7/2006 Cunanan et al.  
 2006/0161249 A1 7/2006 Realyvasquez et al.  
 2006/0167543 A1 7/2006 Bailey et al.  
 2006/0195183 A1 8/2006 Navia et al.  
 2006/0195184 A1 8/2006 Lane et al.  
 2006/0195185 A1 8/2006 Lane et al.  
 2006/0195186 A1 8/2006 Drews et al.  
 2006/0207031 A1 9/2006 Cunanan et al.  
 2006/0229708 A1 10/2006 Powell et al.  
 2006/0235508 A1 10/2006 Lane et al.  
 2006/0241745 A1 10/2006 Solem  
 2006/0246888 A1 11/2006 Bender et al.  
 2006/0253191 A1 11/2006 Salahieh et al.  
 2006/0259134 A1 11/2006 Schwammenthal et al.  
 2006/0259135 A1 11/2006 Navia et al.  
 2006/0259136 A1 11/2006 Nguyen et al.  
 2006/0265056 A1 11/2006 Nguyen et al.  
 2006/0271172 A1 11/2006 Tehrani  
 2006/0271175 A1 11/2006 Woolfson et al.  
 2006/0287717 A1 12/2006 Rowe et al.  
 2006/0287719 A1 12/2006 Rowe et al.

2006/0293745 A1 12/2006 Carpentier et al.  
 2007/0005129 A1 1/2007 Damm et al.  
 2007/0010876 A1 1/2007 Salahieh et al.  
 2007/0010877 A1 1/2007 Salahieh et al.  
 2007/0016285 A1 1/2007 Lane et al.  
 2007/0016286 A1 1/2007 Herrmann et al.  
 2007/0016288 A1 1/2007 Gurskis et al.  
 2007/0043435 A1 2/2007 Seguin et al.  
 2007/0078509 A1 4/2007 Lotfy  
 2007/0078510 A1 4/2007 Ryan  
 2007/0100440 A1 5/2007 Figulla et al.  
 2007/0129794 A1 6/2007 Realyvasquez  
 2007/0142906 A1 6/2007 Figulla et al.  
 2007/0142907 A1 6/2007 Moaddeb et al.  
 2007/0150053 A1 6/2007 Gurskis et al.  
 2007/0156233 A1 7/2007 Kapadia et al.  
 2007/0162103 A1 7/2007 Case et al.  
 2007/0162107 A1 7/2007 Haug et al.  
 2007/0162111 A1 7/2007 Fukamachi et al.  
 2007/0179604 A1 8/2007 Lane  
 2007/0185565 A1 8/2007 Schwammenthal et al.  
 2007/0198097 A1 8/2007 Zegdi  
 2007/0203575 A1 8/2007 Forster et al.  
 2007/0203576 A1 8/2007 Lee et al.  
 2007/0213813 A1 9/2007 Von Segesser et al.  
 2007/0225801 A1 9/2007 Drews et al.  
 2007/0233237 A1 10/2007 Krivoruchko  
 2007/0239266 A1 10/2007 Birdsall  
 2007/0239269 A1 10/2007 Dolan et al.  
 2007/0239273 A1 10/2007 Allen  
 2007/0244546 A1 10/2007 Francis  
 2007/0244558 A1 10/2007 Machiraju  
 2007/0255398 A1 11/2007 Yang et al.  
 2007/0260305 A1 11/2007 Drews et al.  
 2007/0265701 A1 11/2007 Gurskis et al.  
 2007/0270944 A1 11/2007 Bergheim et al.  
 2007/0282436 A1 12/2007 Pinchuk  
 2007/0288089 A1 12/2007 Gurskis et al.  
 2008/0021546 A1 1/2008 Patz et al.  
 2008/0033543 A1 2/2008 Gurskis et al.  
 2008/0065198 A1 3/2008 Quintessenza  
 2008/0119875 A1 5/2008 Ino et al.  
 2008/0154356 A1 6/2008 Obermiller et al.  
 2008/0281411 A1 11/2008 Berreklouw  
 2008/0319543 A1 12/2008 Lane  
 2009/0036903 A1 2/2009 Ino et al.  
 2009/0192599 A1 7/2009 Lane et al.  
 2009/0192602 A1 7/2009 Kuehn  
 2009/0192603 A1 7/2009 Ryan  
 2009/0192604 A1 7/2009 Gloss  
 2009/0192605 A1 7/2009 Gloss et al.  
 2009/0192606 A1 7/2009 Gloss et al.  
 2010/0161036 A1 6/2010 Pintor et al.  
 2010/0249894 A1 9/2010 Oba et al.  
 2010/0249908 A1 9/2010 Chau et al.  
 2010/0331972 A1 12/2010 Pintor et al.  
 2011/0022165 A1 1/2011 Oba et al.  
 2011/0147251 A1 6/2011 Hodshon et al.  
 2012/0065729 A1 3/2012 Pintor et al.  
 2012/0150288 A1 6/2012 Hodshon et al.  
 2013/0053949 A1 2/2013 Pintor et al.  
 2013/0116777 A1 5/2013 Pintor et al.

FOREIGN PATENT DOCUMENTS

EP 0143246 A2 6/1985  
 EP 2537487 A1 12/2012  
 SU 1116573 A1 7/1985  
 SU 1697790 A1 12/1991  
 WO 9213502 A1 8/1992  
 WO 9742871 A1 11/1997  
 WO 2006029062 A1 3/2006

OTHER PUBLICATIONS

Sadowski, Jerzy; Kapelak, Boguslaw; Bartus, Krzysztof, "Sutureless Heart Valve Implantation—A Case Study," Touch Briefings, 2005, pp. 48-50.




Fig. 2





Fig. 3









Fig. 5A




Fig. 5




Fig. 6A




Fig. 6




Fig. 7




Fig. 8




Fig. 9A




Fig. 9B







Fig. 10




Fig. 11






Fig. 12A




10 R

Fig. 12B



10 R



10 R



Fig. 12C




Fig. 12D





Fig. 13A



*Fig. 13B*





Fig. 14A



*Fig. 14B*




Fig. 15A






Fig. 15B



10 L

Fig. 16A









Fig. 17A



*Fig. 17B*




Fig. 18




Fig. 19






Fig. 20








Fig. 22B





Fig. 22C



## RAPID DEPLOYMENT PROSTHETIC HEART VALVE

### RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 13/954,822, filed Jul. 30, 2013, now U.S. Pat. No. 8,911,493, which is a continuation of U.S. patent application Ser. No. 11/441,406, filed May 24, 2006, now U.S. Pat. No. 8,500,798, which claims the benefit of U.S. Patent Application No. 60/684,443, filed on May 24, 2005, entitled "Prosthetic Valve for Implantation in a Body Channel", all the disclosures which are incorporated by reference herein in their entireties.

### FIELD OF THE INVENTION

The present invention generally relates to prosthetic valves for implantation in body channels. More particularly, the present invention relates to prosthetic heart valves configured to be surgically implanted in less time than current valves.

### BACKGROUND OF THE INVENTION

Due to aortic stenosis and other heart valve diseases, thousands of patients undergo surgery each year wherein the defective native heart valve is replaced by a prosthetic valve, either bioprosthetic or mechanical. When the valve is replaced, surgical implantation of the prosthetic valve typically requires an open-chest surgery during which the heart is stopped and patient placed on cardiopulmonary bypass (a so-called "heart-lung machine"). In one common surgical procedure, the diseased native valve leaflets are excised and a prosthetic valve is sutured to the surrounding tissue at the valve annulus. Because of the trauma associated with the procedure and the attendant duration of extracorporeal blood circulation, some patients do not survive the surgical procedure or die shortly thereafter. It is well known that the risk to the patient increases with the amount of time required on extracorporeal circulation. Due to these risks, a substantial number of patients with defective valves are deemed inoperable because their condition is too frail to withstand the procedure. By some estimates, about 30 to 50% of the subjects suffering from aortic stenosis who are older than 80 years cannot be operated on for aortic valve replacement.

Because of the drawbacks associated with conventional open-heart surgery, percutaneous and minimally-invasive surgical approaches are garnering intense attention. In one technique, a prosthetic valve is configured to be implanted in a much less invasive procedure by way of catheterization. For instance, U.S. Pat. No. 5,411,552 to Andersen et al. describes a collapsible valve percutaneously introduced in a compressed state through a catheter and expanded in the desired position by balloon inflation. Although these remote implantation techniques have shown great promise for treating certain patients, replacing a valve via surgical intervention is still the preferred treatment procedure. One hurdle to the acceptance of remote implantation is resistance from doctors who are understandably anxious about converting from an effective, if imperfect, regimen to a novel approach that promises great outcomes but is relatively foreign. In conjunction with the understandable caution exercised by surgeons in switching to new regimens of heart valve replacement, regulatory bodies around the world are moving slowly as well. Numerous successful clinical trials and follow-up studies are in process, but much more experience

with these new technologies will be required before they are completely accepted. One question that remains unanswered is whether the new expandable valves will have the same durability as conventional prosthetic heart valves.

Accordingly, there is a need for an improved device and associated method of use wherein a prosthetic valve can be surgically implanted in a body channel in a more efficient procedure that reduces the time required on extracorporeal circulation. It is desirable that such a device and method be capable of helping patients with defective valves that are deemed inoperable because their condition is too frail to withstand a lengthy conventional surgical procedure. The present invention addresses this need.

### SUMMARY OF THE INVENTION

Various embodiments of the present invention provide prosthetic valves and methods of use for replacing a defective native valve in a human heart. Certain embodiments are particularly well adapted for use in a surgical procedure for quickly and easily replacing a heart valve while minimizing time using extracorporeal circulation (i.e., bypass pump).

In one embodiment, a method for treating a native aortic valve in a human heart, comprises: 1) accessing a native valve through an opening in a chest; 2) advancing an expandable support structure to the site of a native aortic valve, the support structure being radially compressed during the advancement; 3) radially expanding the support structure at the site of the native aortic valve; and 4) mechanically coupling a valve member to the expanded support structure, wherein the valve member replaces the function of the native aortic valve. A further understanding of the nature and advantages of the present invention are set forth in the following description and claims, particularly when considered in conjunction with the accompanying drawings in which like parts bear like reference numerals.

In one variation, the support structure is a stent, which may comprise a metallic frame. In one embodiment, at least a portion of the metallic frame is made of stainless steel. In another embodiment, at least a portion of the metallic frame is made of a shape memory material. The valve member may take a variety of forms. In one preferred embodiment, the valve member comprises biological tissue. The valve member further comprises a coupling portion configured to be connected to the support structure in a quick and efficient manner. In another variation of this method, the metallic frame is viewed under fluoroscopy during advancement of the prosthetic valve toward the native aortic valve.

The native valve leaflets may be removed before delivering the prosthetic valve. Alternatively, the native leaflets may be left in place to reduce surgery time and to provide a stable base for fixing the support structure within the native valve. In one advantage of this method, the native leaflets recoil inward to enhance the fixation of the metallic frame in the body channel. When the native leaflets are left in place, a balloon or other expansion member may be used to push the valve leaflets out of the way and thereby dilate the native valve before implantation of the support structure.

In another preferred embodiment, a method for treating a native aortic valve in a human heart, comprises accessing a native valve through an opening in a chest; advancing an expandable member to a position within the native aortic valve, the native aortic valve having at least two valvular leaflets; dilating the native aortic valve by expanding the expandable member to push aside the valvular leaflets of the native aortic valve; collapsing the expandable member and withdrawing the expandable member from the native aortic

3

valve; advancing an expandable support structure to a position within the dilated native aortic valve, the support structure being radially compressed during the advancement; radially expanding the support structure within the dilated aortic valve, wherein the expanded support structure maintains the native aortic valve in the dilated condition; and coupling a valve member to the expanded support structure, wherein the valve member replaces the function of the native aortic valve.

In another aspect, an improved prosthetic valve comprises an expandable stent sized for implantation at the site of a native aortic valve, the stent having a coupling means (e.g., a plurality of tines extending from a first end thereof); and a valve member comprising three leaflets mounted on a base portion. The coupling means is configured for attachment to the valve member. Alternatively, the coupling means may be provided on the valve member or on both the stent and valve member.

A particularly useful configuration of the present invention is a two-stage prosthetic heart valve, comprising an expandable anchoring member sized to contact a heart valve annulus in an expanded state and a substantially non-expandable valve member configured for connection to the anchoring member. Desirably, the valve member includes a base ring surrounding an inflow end thereof, and the anchoring member comprises a tubular structure having connectors adapted to engage the base ring. The connectors may comprise prongs that change shape and engage the base ring. For example, the base ring may be made of a suture-permeable material, and the prongs are configured to pierce the base ring, or the prongs are shaped to wrap around the base ring.

In an exemplary embodiment, the valve member includes a plurality of discrete connectors spaced around a peripheral inflow end thereof, and the anchoring member comprises a tubular structure having a plurality of mating connectors spaced around a peripheral outflow end thereof. The connectors on the valve member and anchoring member engage one another by displacing the valve member toward the anchoring member. For instance, the connectors on either the valve member or anchoring member comprise latches, and the connectors on the other of the valve member or anchoring member comprise brackets, the latches configured to engage and lock to the brackets upon axial movement of the latches and brackets toward one another. Additionally, a plurality of guide filaments may be provided, at least one for each of the connectors on the anchoring member and slidably received by the associated connector on the valve member. The guide filaments guide the valve member in proper orientation with respect to the anchoring member to ensure engagement of the mating connectors.

Desirably, the anchoring member comprises a stent having a wider outflow end than an inflow end thereof, wherein the valve member comprises a base ring surrounding an inflow end thereof that fits within the outflow end of the stent. In one embodiment, the valve member includes a suture-permeable base ring surrounding an inflow end thereof, and the anchoring member comprises a tubular structure having a suture-permeable fixation ring attached thereto, wherein the valve member connects to the anchoring member via sutures looped between the base ring and the fixation ring.

Another embodiment of the present invention comprises a two-stage prosthetic heart valve, having an expandable anchoring member sized to contact a heart valve annulus in an expanded state, a valve member, and an adapter sized to surround the valve member and engage the anchoring member, to connect the valve member and anchoring member.

4

The adapter may be an annular ring or a wireform-shaped member that closely surrounds and conforms to cusps and commissures of a flexible leaflet valve member.

Whatever its shape, the adapter desirably includes a plurality of discrete connectors, and the anchoring member comprises a tubular structure having a plurality of mating connectors spaced around a peripheral outflow end thereof. The connectors on the adapter and anchoring member are configured to engage one another by displacing the adapter toward the anchoring member. For example, the connectors on either the adapter or anchoring member comprise latches, and the connectors on the other of the adapter or anchoring member comprise brackets, the latches being configured to engage and lock to the brackets upon axial movement of the latches and brackets toward one another. In addition, the valve member preferably has a base ring surrounding an inflow end thereof, and the adapter further includes a plurality of connectors adapted to engage and couple the adapter directly to the base ring.

Another aspect of the present invention is a system for retrofitting a conventional prosthetic heart valve, comprising an off-the-shelf, non-expandable prosthetic heart valve having a sewing ring capable of being implanted using sutures through the sewing ring in an open-heart procedure. An expandable anchoring member contacts and anchors to a heart valve annulus in an expanded state. Coupling means connects the prosthetic heart valve to the anchoring member, the prosthetic heart valve thus being attached to the heart valve annulus via the anchoring member.

In the system for retrofitting a conventional prosthetic heart valve, the anchoring member may comprise a tubular structure having a suture-permeable fixation ring attached thereto, wherein the coupling means comprises sutures looped between the base ring and the fixation ring. An adapter sized to surround the heart valve engages the anchoring member, to connect the heart valve and anchoring member. The adapter may be annular or wireform-shaped. Desirably, the adapter includes a plurality of discrete connectors, and the anchoring member comprises a tubular structure having a plurality of mating connectors spaced around a peripheral outflow end thereof, the connectors on the adapter and anchoring member being configured to engage one another by displacing the adapter toward the anchoring member.

A surgical method of implanting a prosthetic heart valve of the present invention in a patient involves providing a two-stage prosthetic heart valve comprising an expandable anchoring member and a valve member, the anchoring member being sized to contact a heart valve annulus in an expanded state and the valve member being configured to connect to the anchoring member. The patient is prepared for surgery by placing him/her on cardiopulmonary bypass. The surgeon creates a direct access pathway to the heart valve annulus that preferably permits direct (i.e., naked eye) visualization of the heart valve annulus. The anchoring member is delivered and expanded to contact the valve annulus, and the valve member is delivered and connected to the anchoring member. Preferably, the direct access pathway is created by performing open-heart surgery. The method may include balloon-expanding the anchoring member. Further, the valve member may be expandable and the method includes delivering the valve member in a compressed state and expanding it prior to connecting it to the anchoring member.

In one embodiment, the valve member and the anchoring member are provided with mating connectors, and the step of delivering and connecting the valve member to the



5

anchoring member comprises axially displacing the valve member toward the anchoring member so that the mating connectors engage. In another embodiment, the anchoring member comprises a stent having an outflow end larger than an inflow end thereof, and the valve member comprises a non-expandable valve member having a base ring on an inflow end thereof sized to fit within the outflow end of the stent. The anchoring member may be provided with bendable connectors on an outflow end thereof, and the method includes causing the connectors to bend inward and engage a peripheral base ring of the valve member. For example, a bending tool may be used to bend connectors inward.

Another surgical method of implanting a two-stage prosthetic heart valve in a patient of the present invention includes providing an expandable anchoring member sized to contact a heart valve annulus in an expanded state, delivering and attaching the anchoring member to the heart valve annulus, providing a non-expandable valve member, and delivering and connecting the valve member to the anchoring member. The valve member and the anchoring member may be provided with mating connectors, and the step of delivering and connecting the valve member to the anchoring member comprises axially displacing the valve member toward the anchoring member so that the mating connectors engage. Desirably, the anchoring member comprises a stent having an outflow end larger than an inflow end thereof, and wherein the valve member comprises a base ring on an inflow end thereof sized to fit within the outflow end of the stent. The anchoring member may be provided with bendable connectors on an outflow end thereof, and the method includes causing the connectors to bend inward and engage a peripheral base ring of the valve member, such as by using a bending tool.

In an exemplary embodiment, the valve member includes a base ring on an inflow end thereof, and the method further includes providing an adapter sized to surround the valve member and seat on the base ring. The method therefore includes the step of delivering and connecting the valve member and coupling the adapter to the anchoring member. For instance, the adapter includes a plurality of discrete connectors, and the anchoring member comprises a tubular structure having a plurality of mating connectors spaced around a peripheral outflow end thereof. The step of coupling the adapter to the anchoring member comprises displacing the adapter toward the anchoring member to engage the mating connectors thereon. Additionally, the adapter may further have a plurality of connectors adapted to engage and couple the adapter directly to the base ring, and the method includes causing the connectors to engage the base ring.

In a still further surgical method of implanting a prosthetic heart valve in a patient, a prosthetic heart valve and a separate expandable anchoring member are provided. The prosthetic heart valve and anchoring member are positioned within a valve dilator/delivery tube having an exterior diameter sized to dilate a heart valve annulus. The valve dilator/delivery tube advances to the heart valve annulus, and the annulus is dilated using the valve dilator/delivery tube. The anchoring member is expelled from the tube and expanded to contact the heart valve annulus. The prosthetic heart valve is then expelled from the valve dilator/delivery tube, and connected to the anchoring member.

Another method of the present invention comprises retrofitting and rapidly implanting a conventional prosthetic heart valve in a patient. The method includes providing an off-the-shelf non-expandable prosthetic heart valve having a sewing ring capable of being implanted using sutures

6

through the sewing ring in an open-heart procedure. An expandable tissue anchoring member sized to contact a heart valve annulus in an expanded state is delivered and expanded into contact with the heart valve annulus. Finally, the prosthetic heart valve is delivered and connected to the tissue anchoring member.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The invention will now be explained and other advantages and features will appear with reference to the accompanying schematical drawings wherein:

FIG. 1 is an exploded perspective view illustrating a preferred embodiment of a two-stage prosthetic valve comprising a stent portion and a valve member, wherein the valve member may be quickly and easily connected to the stent portion.

FIG. 2 illustrates the valve embodiment of FIG. 1 after the valve member has been attached to the stent portion by crimping portions of the stent over the commissural points of the valve member.

FIG. 3 is an exploded perspective view of an alternative embodiment wherein the stent is provided with a plurality of tines configured to be crimped to a ring along the base of the valve member.

FIG. 4 illustrates the valve embodiment of FIG. 3 after the valve member has been attached to the stent portion by crimping the tines on to the valve member.

FIG. 4A is a sectional view through one side of the prosthetic heart valve of FIG. 4 taken along line 4A-4A and showing one configuration of tines connecting through a sewing ring portion of the valve member.

FIG. 5 is an exploded perspective view of an alternative embodiment wherein slotted posts are provided on the stent for coupling to protruding members on the valve member.

FIG. 5A is an enlarged view of one of the slotted posts provided on the stent of FIG. 5.

FIGS. 6 and 6A illustrate another alternative embodiment similar to FIGS. 5 and 5A wherein the posts are configured with L-shaped slots for locking the valve member to the stent.

FIG. 7 is a sectional view through a body channel that illustrates an alternative embodiment of prosthetic heart valves wherein first and second stents are provided for anchoring a valve member within the body channel.

FIG. 8 is an exploded perspective view of an alternative embodiment wherein the stent has a small diameter and a large diameter and wherein an expandable valve member is deployed within the large diameter.

FIG. 9A is an exploded perspective view of another alternative embodiment of a two part prosthetic valve wherein a ring portion along the base of the valve member snaps into a groove formed in the stent.

FIG. 9B illustrates the embodiment of FIG. 9A with the valve member connected to the stent.

FIG. 10 is an exploded perspective view of another alternative embodiment wherein the valve member and the stent are provided with corresponding threaded portions for threadably engaging the valve member to the stent.

FIG. 11 is an exploded perspective view of an alternative prosthetic heart valve of the present invention having a valve member, stent, and a threaded locking ring for coupling the two together.

FIGS. 12A and 12B are exploded and assembled perspective views of an alternative two-stage prosthetic heart valve having a valve member and tubular, expandable stent with tabs on an outflow end for coupling to the valve member.

FIGS. 12C and 12D are sectional views through one side of the prosthetic heart valve of FIG. 12B schematically illustrating an exemplary tool that may be used to bend the tabs on the outflow end of the stent around a sewing ring of the valve member.

FIGS. 13A and 13B are exploded and assembled perspective views of an alternative prosthetic heart valve of the present invention wherein a valve member and stent with tabs are coupled together in conjunction with a locking ring.

FIGS. 14A and 14B are exploded and assembled perspective views of a still further prosthetic heart valve wherein a valve member and tubular, expandable stent are coupled together using a wireform-shaped adapter having tabs.

FIGS. 15A and 15B are exploded and assembled perspective views of a prosthetic heart valve having a valve member and stent with locking bands on an outflow end.

FIGS. 16A and 16B are exploded and assembled perspective views of an alternative prosthetic heart valve wherein a stent exhibits locking clips on an outflow end that are guided through mating slits on a locking ring to join the stent to a valve member.

FIGS. 17A and 17B are exploded and assembled perspective views of an alternative prosthetic heart valve wherein a stent has brackets on an outflow end that receive guided locking clips on a locking ring to join the stent to a valve member.

FIG. 18 is a perspective view of an alternative stent for use in a prosthetic heart valve of the present invention.

FIG. 19 is a detailed sectional view through an inflow side of a prosthetic heart valve utilizing the stent of FIG. 18 and showing a valve member base ring captured between two sets of prongs.

FIG. 20 is a perspective exploded view of a prosthetic heart valve having a tubular stent with upstanding tines and a valve member with an additional adapter ring arranged around a base ring.

FIG. 21 is an exploded perspective view of an exemplary prosthetic heart valve having an expandable stent and non-expandable valve member connected by an array of parachute sutures being removed from a storage jar.

FIGS. 22A-22C are several views of the implantation of the prosthetic heart valve of FIG. 21 assisted by a tubular valve dilator/delivery tube.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention attempts to overcome drawbacks associated with conventional, open-heart surgery, while also adopting some of the techniques of newer technologies which decrease the duration of the treatment procedure. The prosthetic heart valves of the present invention are primarily intended to be delivered and implanted using conventional surgical techniques, including the aforementioned open-heart surgery. There are a number of approaches in such surgeries, all of which result in the formation of a direct access pathway to the particular heart valve annulus. For clarification, a direct access pathway is one that permits direct (i.e., naked eye) visualization of the heart valve annulus. In addition, it will be recognized that embodiments of the two-stage prosthetic heart valves described herein may also be configured for delivery using percutaneous approaches, and those minimally-invasive surgical approaches that require remote implantation of the valve using indirect visualization.

One primary aspect of the present invention is a two-stage prosthetic heart valve wherein the tasks of implanting a

tissue anchor and a valve member are somewhat separated and certain advantages result. For example, a two-stage prosthetic heart valve of the present invention may have an expandable tissue anchoring member that is secured in the appropriate location using a balloon or other expansion technique. A valve member is then coupled to the tissue anchoring member in a separate or sequential operation. By utilizing an expandable anchoring member, the duration of the initial anchoring operation is greatly reduced as compared with a conventional sewing procedure utilizing an array of sutures. The expandable anchoring member may simply be radially expanded outward into contact with the implantation site, or may be provided with additional anchoring means, such as barbs. The operation may be carried out using a conventional open-heart approach and cardiopulmonary bypass. In one advantageous feature, the time on bypass is greatly reduced due to the relative speed of implanting the expandable anchoring member.

For definitional purposes, the term “tissue anchoring member,” or simply “anchoring member” refers to a structural component of a heart valve that is capable of attaching to tissue of a heart valve annulus. The anchoring members described herein are most typically tubular stents, or stents having varying diameters. A stent is normally formed of a biocompatible metal wire frame, such as stainless steel or Nitinol. Other anchoring members that could be used with valves of the present invention include rigid rings, spirally-wound tubes, and other such tubes that fit tightly within a valve annulus and define an orifice therethrough for the passage of blood, or within which a valve member is mounted. It is entirely conceivable, however, that the anchoring member could be separate clamps or hooks that do not define a continuous periphery. Although such devices sacrifice some dynamic stability, these devices can be configured to work well in conjunction with a particular valve member.

The term “valve member” refers to that component of a heart valve that possesses the fluid occluding surfaces to prevent blood flow in one direction while permitting it in another. As mentioned above, various constructions of valve numbers are available, including those with flexible leaflets and those with rigid leaflets or a ball and cage arrangement. The leaflets may be bioprosthetic, synthetic, or metallic.

A primary focus of the present invention is the two-stage prosthetic heart valve having a first stage in which an anchoring member secures to a valve annulus, and a subsequent second stage in which a valve member connects to the anchoring member. It should be noted that these stages can be done almost simultaneously, such as if the two components were mounted on the same delivery device, or can be done in two separate clinical steps, with the anchoring member deployed using a first delivery device, and then the valve member using another delivery device. It should also be noted that the term “two-stage” does not necessarily limit the valve to just two parts, as will be seen below.

Another potential benefit of a two-stage prosthetic heart valve, including an anchoring member and a valve member, is that the valve member may be replaced after implantation without replacing the anchoring member. That is, an easily detachable means for coupling the valve member and anchoring member may be used that permits a new valve member to be implanted with relative ease. Various configurations for coupling the valve member and anchoring member are described herein.

It should be understood, therefore, that certain benefits of the invention are independent of whether the anchoring member or valve member are expandable or not. That is,

various embodiments illustrate an expandable anchoring member coupled to a conventional valve member. However, the same coupling structure may be utilized for a non-expandable anchoring member and conventional valve member. Additionally, although a primary embodiment of the present invention is an expandable anchoring member coupled with a conventional valve member, both could be expandable and introduced percutaneously or through a minimally-invasive approach. Therefore, the invention should not be construed as being limited in these regards, but instead should be interpreted via the appended claims.

As a point of further definition, the term “expandable” is used herein to refer to a component of the heart valve capable of expanding from a first, delivery diameter to a second, implantation diameter. An expandable structure, therefore, does not mean one that might undergo slight expansion from a rise in temperature, or other such incidental cause. Conversely, “non-expandable” should not be interpreted to mean completely rigid or a dimensionally stable, as some slight expansion of conventional “non-expandable” heart valves, for example, may be observed.

In the description that follows, the term “body channel” is used to define a blood conduit or vessel within the body. Of course, the particular application of the prosthetic heart valve determines the body channel at issue. An aortic valve replacement, for example, would be implanted in, or adjacent to, the aortic annulus. Likewise, a mitral valve replacement will be implanted at the mitral annulus. Certain features of the present invention are particularly advantageous for one implantation site or the other. However, unless the combination is structurally impossible, or excluded by claim language, any of the heart valve embodiments described herein could be implanted in any body channel.

With reference now to FIG. 1, one preferred embodiment of an improved prosthetic valve 10 generally includes an expandable anchoring member or stent 20 and a valve member 30. The stent provides a support structure for anchoring the valve member within a body lumen. Although a stent is described for purposes of illustration, any support structure capable of anchoring the valve member to the body lumen may be used. As will be described in more detail below, the prosthetic valve is configured such that the valve member may be quickly and easily connected to the stent. It should be noted here, that the anchoring members or stents described herein can be a variety of designs, including having the diamond-shaped openings shown or other configurations detailed below. The material depends on the mode of delivery (i.e., balloon- or self-expanding), and the stent can be bare strut material or covered to promote in-growth and/or to reduce paravalvular leakage. For example, a suitable cover that is often used is a sleeve of fabric such as Dacron.

The stent may be securely deployed in the body channel using an expandable member, such as, for example, a balloon. Because the stent is expanded before the valve member is attached, the valve member will not be damaged or otherwise adversely affected during the stent deployment. After the stent has been deployed in the body channel, the valve member may be connected to the stent. In one preferred application, the two-stage prosthetic valve is well-suited for use in heart valve replacement. In this application, the stent may be advantageously used to push the native leaflets aside such that the valve member can replace the function of the native valve. The anchoring members or stents described herein could include barbs or other such tissue anchors to further secure the stent to the tissue. In one

preferred embodiment, the barbs are deployable (e.g., configured to extend or be pushed radially outward) by the expansion of a balloon.

In another advantageous feature, the two-stage prosthetic valve illustrated in FIG. 1 provides a device and method for substantially reducing the time of the surgical procedure. This reduces the time required on extracorporeal circulation and thereby substantially reduces the risk to the patient. The surgical time is reduced because the stent may be deployed quickly and the valve member may be attached to the stent quickly. This simplifies and reduces the surgical time as compared with replacement valves that are sutured to the tissue after removing the native leaflets.

When used for aortic valve replacement, the valve member 30 preferably has three leaflets 36 which provide the valvular function for replacing the function of the native valve. In various preferred embodiments, the valve leaflets may be taken from another human heart (cadaver), a cow (bovine), a pig (porcine valve) or a horse (equine). In other preferred variations, the valve member may comprise mechanical components rather than biological tissue. In one preferred embodiment, the valve is compressible in diameter. Accordingly, the valve may be reduced in diameter for delivery into the stent and then expanded. The three leaflets are supported by three commissural posts 34. A ring 32 is provided along the base portion of the valve member.

With continued reference to FIG. 1, the stent 20 is provided with two diameters. A lower portion 22 has a small diameter and an upper portion 24 has a large diameter. The lower portion 22 is preferably sized to be deployed at the location of the native valve (e.g., along the aortic annulus). The upper portion 24 expands outwardly into the perspective cavity adjacent the native valve. For example, in an aortic valve replacement, the upper portion 24 expands into the area of the sinus cavities just downstream from the aortic annulus. Of course, care should be taken to orient the stent 20 so as not to block the coronary openings. The stent body is preferably configured with sufficient radial strength for pushing aside the native leaflets and holding the native leaflets open in a dilated condition. The native leaflets provide a stable base for holding the stent, thereby helping to securely anchor the stent in the body. To further secure the stent to the surrounding tissue, the lower portion may be configured with anchoring members, such as, for example, hooks or barbs (not shown).

The upper portion 24 of the stent 20 has a larger diameter sized for receiving the valve member 30. A transition region 28 between the upper and lower portions of the stent body may be advantageously used to provide a seat for the bottom end of the valve member. The stent may further comprise a ridge (not shown) along an inner wall for providing a more definite seat portion within the stent.

With continued reference to FIG. 1, the prosthetic valve 10 is provided with a coupling mechanism for securing the valve member 30 to the stent 20. The coupling mechanism may take a variety of different forms. However, in the illustrated embodiment, the stent body comprises three posts 26 which correspond to the three commissural points 34 on the valve member. The three posts 26 are preferably formed of a malleable material such that the posts 26 may be crimped over the commissural points on the valve member. A bending tool (not shown) may be provided for crimping the posts 26 over the commissures of the valve member, or the posts 26 may be hinged or made of the shape memory material so as to curl once implanted in the body. With reference to FIG. 2, the prosthetic valve 10 is illustrated in the assembled condition with the posts 26 crimped over the

commissural points **34** of the valve member. In one variation, the three posts on the stent are formed with a recess for receiving the commissural points, such as in a snap-fit relationship.

In a preferred embodiment, the stent **20** is expandable, but the valve member **30** is a conventional, non-expandable prosthetic heart valve, such as the Carpentier-Edwards PERIMOUNT Magna® Aortic Heart Valve available from Edwards Lifesciences of Irvine, Calif. In this sense, a “conventional” prosthetic heart valve is an off-the-shelf (i.e., suitable for stand-alone sale and use) non-expandable prosthetic heart valve having a sewing ring capable of being implanted using sutures through the sewing ring in an open-heart procedure. An implant procedure therefore involves first delivering and expanding the stent **20** and the aortic annulus, and then coupling the valve member **30** thereto. Because the valve member **30** is non-expandable, the entire procedure is typically done using the conventional open-heart technique. However, because the stent **20** is delivered and implanted by simple expansion, the entire operation takes less time. This hybrid approach will also be much more comfortable to surgeons familiar with the open-heart procedures and conventional heart valves. Moreover, the relatively small change in procedure coupled with the use of proven heart valves should create a much easier regulatory path than strictly expandable, remote procedures.

A variation of the embodiment described in FIGS. **1** and **2** may incorporate an expandable stent **20** and an expandable valve member **30**. Although not shown, the valve member **30** may be capable of expansion within the body, such as the Cribier-Edwards Aortic Percutaneous Heart Valve, also available from Edwards Lifesciences. Therefore, the valve **10** may be implanted without an open-heart procedure, and even without stopping heart. In such a remote procedure, the three posts **26** on the stent **20** may be made of a shape memory material having a temperature-induced shape change once implanted. Alternatively, a tool for bending the posts **26** may be delivered along with the valve **10** and utilized when the valve member **30** seats within the stent **20**.

With reference now to FIG. **3**, an alternative prosthetic valve **10A** comprises a stent **40** provided with a bottom portion **42** and an upper flared portion **44**. A plurality of prongs or tines **46** is disposed along a top end of the flared portion **44**. The tines **46** are preferably bendable members configured to engage the ring portion **32** along the base of the valve member **30**. In one preferred embodiment, the tines **46** are crimped over the ring as shown in FIG. **4**. If desired, the tines **46** may have pointed tips for passing through a fabric or other similar material along the ring portion of the valve member, such as seen in FIG. **4A**.

Once again, the stent **40** is desirably an expandable member that can be easily delivered and implanted at the body channel. The valve member **30** may be conventional, or may also be expandable. The illustrated embodiment shows a conventional valve **30** having the sewing ring portion **32** surrounding an inflow end. Sewing rings are typically made of suture-permeable material covered with cloth. The tines **46** may be sharp enough to pierce the material of the sewing ring portion **32** (FIG. **4A**). In this regard, a conventional valve member **30** may be utilized without modification. In the alternative, the sewing ring portion **30** may be replaced with a more rigid peripheral band or ring, and the tines **46** are simply bent inward so as to fold over the ring and capture the valve member **31** on the top of the stent **40**. Desirably, a seat or rim of some sort is provided within the interior of the stent **40** so that the valve member **30** can easily be positioned therein. The tines **46**

may be mechanically bent using a deployment tool (not shown), or they may be hinged or made of a shape memory material so as to curl inward upon reaching a certain temperature.

With reference now to FIG. **5**, another alternative prosthetic valve **10B** comprises an anchoring member or stent **50** provided with a cylindrical portion **52** and three posts **54** extending upward from the cylindrical portion. Each post **54** may be slotted, as illustrated in the enlarged view of FIG. **5B**, or formed with an orifice. Radially protruding members **38** are provided along the ring portion **32** of the valve member **30** for mating with the posts on the stent. The exemplary slot has a thin neck portion **58** wherein engagement members, such as angled teeth, are provided. The teeth are angled such that the slot widens as the protruding member **38** is pushed downward into the slot. After passing through the teeth into the capture portion **59**, the protruding member **38** is securely captured. Because the teeth are angled in only one direction, an upward force will not cause the slot to widen, thereby capturing the protruding member.

With reference now to FIG. **6**, yet another alternative embodiment of a component prosthetic valve **10C** is illustrated. The embodiment of FIG. **6** is similar to the embodiment illustrated and described above with respect to FIG. **5**. However, in this variation, the posts or connecting members **55** are provided with L-shaped slots **57** for receiving the protruding member disposed along the valve member. With reference to FIG. **6A**, an enlarged view of one preferred connecting member **55** is shown. The slot **57** of the connecting member **55** is shaped such that the protruding member **38** moves longitudinally into the slot and then rotationally to enter the capture portion. One or more teeth **58** may be provided for holding the protruding member in the capture portion. Alternatively, the protruding member **38** may be held in the slot **57** using friction or a mechanical locking member. In another alternative, a key lock system or “bayonet” attachment mechanism may be provided for coupling the valve member to the stent.

With reference now to FIG. **7**, another alternative prosthetic valve **10D** is illustrated wherein the valve member **30** is captured and held between first and second stents **60**, **62**. In use, the first stent **60** is expanded within a body channel such that the outer surface of the stent is in contact with the vessel wall **64**. The valve member **30** is then advanced through the body channel and into contact with the first stent. A ring **32** is preferably provided along the base portion of the valve member for contacting the outflow end of the first stent. The second stent is then advanced through the body channel and is deployed such that an inflow end of the second stent contacts a top surface of the ring **32** of the valve member for anchoring the valve member between the first and second stents.

The embodiment of FIG. **7** employs a slightly different means for connecting the valve member **30** the anchoring member. Primarily, stents **60**, **62** capture the ring **32** of the valve member **30** therebetween simply by providing upper and lower barriers to movement. The valve member **30** is desirably a non-expandable type, therefore the ring **32** is not overly susceptible to compression. By providing sufficient of the thickness of the stents **60**, **62**, the valve member **30** remains sandwiched therebetween. In this regard, the outflow end of the first stent **60** and the inflow end of the upper stent **62** are preferably flat or blunt so as not to dig into the ring **32**. Because of the anchoring function of the stents **60**, **62**, there is no need to suture the valve member **30**, and thus the ring **32** may be made relatively firm or rigid. Alternatively, the facing edges of the stents **60**, **62** may be provided

with barbs or other such piercing devices, and the ring **32** provided as a conventional suture-permeable sewing ring.

As noted above, the anchoring members or stents described herein could include barbs or other anchors to further secure the stent to the tissue. Further, the barbs could be deployable (e.g., configured to extend or be pushed radially outward) by the expansion of a balloon. Likewise, the stent can be covered to promote in-growth and/or to reduce paravalvular leakage. The cover would be similar to those on other valves, e.g., a Dacron tube or the like.

Alternatively, the valve member may be constructed with a tubular frame or cage for engaging one or both stents **60**, **62**. In various preferred embodiments, the stents may be self-expanding or balloon-expandable. In one advantageous feature, the valve member **30** of this embodiment is not required to be mounted within a cylindrical frame or stent. Accordingly, the flow through area of the valve member may be maximized to improve valve function. In another variation, the first and second stents may be integrated as a single unit forming a chamber therebetween. In this variation, the valve member may be expanded within the chamber for securely deploying the valve member in the body channel.

With reference now to FIG. **8**, another alternative embodiment of a two-stage prosthetic valve **10E** is illustrated wherein the anchoring member or stent **70** is provided with a varying diameter. More particularly, a lower portion **72** of the stent has a small diameter sized for implantation at a native valve annulus. In one preferred configuration, the small diameter is about 23 mm. The stent also has an upper portion **74** with a larger diameter for receiving an expandable valve member **30A**. In one preferred configuration, the larger diameter is about 29 mm. In this embodiment, the valve member **30A** is provided as a tubular body that is radially expandable. The valve leaflets are disposed along the interior of the valve member.

The stent **70** preferably includes a circular ridge **76** formed along the transition region between the large and small diameters. The ridge provides a seat for the base of the valve member **30A**. In one preferred embodiment, the ridge **76** incorporates a support wire **78** that extends at least partially through the ridge for strength and may be used to provide a radiopaque marker. The remaining portion of the ridge may be formed of Dacron or any other suitable material. The stent **70** may be comprised of a screen or mesh. A cover **75**, such as a polymer sheet, may be provided along at least a portion of the stent to help prevent leakage and enhance sealing. In addition, a sponge or cloth may be provided along the exterior portion of the stent for further enhancing sealing.

The stent **70** of FIG. **8** may be self-expanding or balloon-expandable. When provided as a balloon-expandable stent, an expandable tapered (i.e., two diameter) balloon may be provided for deploying the stent. When configured for use with a stent having diameters of 23 mm and 29 mm, the balloon may have diameters of 22 mm and 28 mm, respectively.

With reference now to FIGS. **9A** and **9B**, another alternative embodiment of a component prosthetic valve **10F** is provided wherein a valve member **30** is configured for connection with an anchoring member or stent **90**. In this embodiment, the stent **90** is provided with a groove **94** formed in an inwardly-directed circumferential member **92**. The groove extends at least partially around the inner portion of the stent and is sized to receive the ring portion **32** of the valve member **30**. In one preferred embodiment, the ring is configured to snap fit into the groove, as seen in FIG. **9B**. In another variation, the ring is made of a shape

memory material configured to expand after deployment in the body. In this variation, the ring is configured to radially expand for securely anchoring itself within the groove.

With reference now to FIG. **10**, yet another alternative embodiment of a component prosthetic valve **10G** is illustrated wherein the valve member **30** is configured for threadable engagement with an anchoring member or stent **100**. In this embodiment, the stent is provided on one end with a threaded region **102** along an inner wall configured for receiving a threaded flange portion **33** on the valve member **30**. The threaded flange portion is preferably provided along the ring **32** at the base of the valve member. During use, the stent is first deployed in the body channel. The stent may be deployed in a manner wherein the diameter of the threaded region remains substantially constant so as to not affect the threads. In one embodiment, the stent is substantially non-expandable and is delivered into the lumen in its fully expanded condition. This can be achieved by first stretching or dilating the delivery site for receiving the stent. In another embodiment, only the lower portion of the stent is expanded for engaging the tissue. In either embodiment, the valve member is threadably attached to the threaded flange on the stent after the stent has been firmly anchored in the body channel. This attachment means is configured such that the valve member advantageously connects to the stent through rotational movement. Accordingly, longitudinal forces applied to the valve member after implantation will have little or no effect on the integrity of the connection between the stent and valve.

With reference now to FIG. **11**, an alternative prosthetic heart valve **10H** comprises a valve member **30**, an anchoring member or stent **110**, and a locking ring **112**. As before, the stent **110** desirably expands first at the implantation site, after which a conventional valve member **30** couples to the stent through the use of the locking ring **112**. However, the valve member **30** may also be expandable, and the stent **110** can take a variety of forms. In a preferred embodiment, the stent **110** comprises a latticework of balloon-expandable members adapted to be delivered to the implantation site in a collapsed or compressed state, and then expanded from within using a balloon. Of course, a self-expanding stent **110** could also be used, and additional anchoring means of such as exterior barbs may be provided to help prevent the stent from migrating after implantation.

A series of tabs or flanges **114** project slightly inwardly from an outflow end of the stent **110**. The flanges **114** are configured to mate with exterior threading **116** on a downwardly-projecting shoulder of the locking ring **112**. The number and configuration of the flanges **114** is selected to avoid interfering with radial expansion of the stent **110**, and also to mate with the threads **116** of the locking ring **112**. Desirably, a series of space-apart flanges **114**, for example eight, evenly spaced around the outflow rim of the stent **110** project inward therefrom a distance of between 1-3 mm.

An inner bore **118** of the locking ring **112** possesses a diameter large enough to pass over the entire valve member **30** except for the base ring **32**, which could be a sewing ring of a conventional heart valve. When coupled together, the locking ring **112** surrounds the valve member **30** and desirably includes an inner ledge that rests on the base ring **32** thereof. The inner diameter of the shoulder having the exterior threading **116** is sized larger than the base ring **32** and extends downwardly into engagement with the flanges **114**. By screwing down the locking ring **112**, the components can be easily and rapidly assembled. After implantation, removal and replacement of the valve member **30** merely requires releasing the locking ring **112** from any

tissue ingrowth, unscrewing and removing it, and releasing the valve member 30 from the stent 110 by cutting away any tissue ingrowth therebetween.

FIGS. 12A and 12B illustrate another prosthetic heart valve 10I of the present invention having an expandable anchoring member or stent 120 coupled to a valve member 30. Much like the valve 10A of FIGS. 3 and 4, the outflow end of the stent 120 exhibits a series of spaced-apart tabs 122 that curl around the base ring 32 of the valve member 30. In this embodiment, the stent 120 is a straight tube, and there are fewer tabs 122 (e.g., eight) than there are tines 46 in the valve 10A. The tabs 122 may be bent using an auxiliary tool (not shown), or may possess a property permitting autonomous bending, such as temperature-induced movement.

FIGS. 12C and 12D are sectional views through one side of the prosthetic heart valve 10I of FIG. 12B schematically illustrating an exemplary tool that may be used to bend the tabs 122 on the outflow end of the stent 120 around the base ring 32 of the valve member 30. It should be noted that the section is taken radially through one side of the system, and the tool will typically be annular or at least peripherally arranged to bend each one of the tabs 122. The tool comprises a forming member 124 having a forming surface 125. The forming member 124 slides within and relative to an outer anvil 126 having an inwardly angled portion 128 that directly surrounds and engages each of the tabs 122. The forming surface 125 is curved such that axial displacement of the forming member 124 in the direction shown in FIG. 12C curls each of the tabs 122 inward to the shape of FIG. 12D. In this embodiment, the tabs 122 wrap over the top of and restrain the base ring 32. In other embodiments, the tool may be used to bend prongs so that they pierce the base ring 32. It should be noted that the outer anvil 126 is primarily used for centering purposes to guide the forming member 124 toward the tabs 122.

FIGS. 13A and 13B illustrate another embodiment of a prosthetic valve 10J having multiple components joined together. An anchoring member or stent 130 includes a plurality of tangs or flanges 132 on an outflow end. A valve member 30 seats adjacent the outflow end of the stent 130, and a fixation ring 134 extends therearound. Additionally, a plurality of tabs 136 project downward from the fixation ring 34. Although not shown, the tabs 136 enable the fixation ring 34 to be coupled to the base ring 32 of the valve member 30 by mechanically bending the tabs, or configuring the tabs to curl upon reaching a certain temperature. As seen in FIG. 13B, the flanges 132 extend around the outside of the fixation ring 134 and bend around the upper or outflow end thereof. Again, this can be accomplished using an auxiliary tool or through temperature-induced movement. Alternatively, the flanges 132 may be formed of a resilient polymer or metal having the shape seen in FIG. 13B such that they can be flexed outward around the fixation ring 134 and then snapped back into place to secure the ring around the valve member 30. Although not shown, the interior of the fixation ring 134 is desirably contoured to mate with the base ring 32 of the valve member 30. The fixation ring 134 can be made of any number of materials, including rigid, flexible, metallic, polymer, bioabsorbable, etc. One preferred configuration is a Teflon ring coated with anti-thrombogenic or anti-microbial compositions.

FIG. 14A illustrates a still further prosthetic heart valve 10K having an expandable anchoring member or stent 140, a valve member 30, and a wireform-shaped adapter 142. The stent 140 and valve member 30 have been previously described. The adapter 142 has a shape similar to a so-called “wireform” used in the internal construction of many prior

art bioprosthetic tissue valves. Indeed, the valve member 30 is desirably a Carpentier-Edwards PERIMOUNT Magna® Aortic Heart Valve made by Edwards Lifesciences, and including therewithin an Elgiloy wireform. The adapter 142 may be formed of biocompatible polymers or metals, preferably an alloy such as Nitinol.

The adapter 142 carries a plurality of securing tabs 144, 146. In the illustrated embodiment, three lower securing tabs 144 are located at the apex of the three cusps of the wireform-shape, and two upper securing tabs 146 are located at each of the upstanding commissures of the wireform-shape, for a total of six at the commissures. FIG. 14B is a detailed illustration of the assembly of the stent 140, valve member 30, and adapter 142. The base ring 32 of the valve member 30 seats on or just within the outflow end of the stent 140, and the adapter 142 fits over the valve member and couples to it, as well as to the stent. In this regard, the cusps of the adapter 142 seat on or slightly outside the base ring 32 with the commissures surrounding and conforming to the commissures of the valve member 30. The cusp securing tabs 144 bend up over the base ring 32 and down into engagement with the stent 140. The two securing tabs 146 at each commissure of the adapter 142 bend or wrap around the corresponding valve member commissure.

Again, a supplemental tool may be used to accomplish the bending of the securing members 144, 146, or they may exhibit temperature-changing properties. In the illustrated embodiment, the securing tabs 144, 146 are malleable, though other configurations are within the scope of the invention. For example, the lower securing tabs 144 may be barbs or tangs which pierce the base ring 32 and hook around the stent 140, while the upper securing tabs 146 may be resilient straps that wrap around each one of the commissures of the valve member 30.

To further secure the valve member 30 to the stent 140, the stent includes a plurality of upstanding barbs 147 comprising spaced apart posts having teeth 140. The adapter 142 possesses a plurality of outwardly projecting brackets 149 defining slots therethrough. As seen in FIG. 14B, the barbs 147 pass through the base ring 32 and through the slots of the brackets 149 in the adapter 142. The teeth 148 prevent removal of the barbs 147 from the slots. In this way, the stent 140 and adapter 142 are securely connected together, sandwiching the valve member 30 therebetween.

Another possibility is that the securing tabs 144, 146 are not initially carried by the adapter 142, but instead are added after the assembly of the three components. For instance, staples or even sutures may be used after the valve member 30 seats on the stent 140, and the adapter 142 is lowered around the valve member. Even if sutures are used, the time required relative to a conventional sewing operation is greatly reduced. Moreover, the structural support and anchoring properties of the wireform-shaped adapter 142 greatly enhances the overall integrity of the assembly. In this regard, securing tabs such as those shown may be placed more continuously around the adapter 142 so as to provide more uniform contact with the valve member 30. One possible configuration is a series of small hooks or brackets extending along the undulating adapter 142 that loop over the corresponding undulating shape on the valve member 30. The valve member 30 is therefore restrained from upward movement relative to the adapter simply by lowering the adapter 142 over the valve member. In such an arrangement, only the lower securing members need be actively attached, such as by causing their shape to change and bend into engagement with the stent 140, as seen in FIG. 14B.

A further prosthetic valve embodiment 10L seen in FIG. 15A includes an expandable anchoring member or stent 150 and a valve member 30. A plurality of fixation straps 152 ring the outflow end of the stent 150. Four such straps 152 are shown, but more or less may be utilized. For example, three straps extending farther around the periphery of the outflow end of the stent 150 may be substituted. Conversely, four or more straps that overlap one another may be used.

FIG. 15B illustrates the valve member 30 seated on top of the stent 150 with one of the straps 152 securing the two components together. Straps 152 may be attached at both of their ends to the stent 150, and may comprise a resilient biocompatible material that stretches over the base ring 32 of the valve member 30. Alternatively, the straps may be bent or folded over the base ring. In one variation, one end of each strap 152 may be initially free, and after the strap is looped over the base ring 32 is then attached to the stent 150, somewhat like a belt configuration. The straps 152 may be formed of a variety of materials, typically cloth-covered so as to permit tissue ingrowth over a cloth-covered base ring 32 for enhanced long-term anchorage. One possible variation is to incorporate small barbs or Velcro-style hooks in each of the straps 152 so as to gain better purchase on the base ring 32.

FIGS. 16A and 16B illustrate a still further embodiment, wherein the prosthetic heart valve 10M comprises a valve member 30, expandable anchoring member or stent 160, and coupling ring 162. The coupling ring 162 defines a series of circumferentially-spaced apertures or slots 164 that receive upstanding hooks or latches 166 on the stent 160. As seen in FIG. 16B, the coupling ring 162 surrounds the commissures of the valve member 30 and seats on the base ring 32, and the latches 166 extend through the slots 164 and are secured therein by outwardly directed teeth 168. In the illustrated embodiment, the latches 166 each comprise a pair of parallel, spaced apart upstanding members, each with an outwardly directed tooth 168, which may be cammed inward toward one another as they pass through the slots 164. As the teeth 168 clear the slot 164, the parallel members resiliently spring outward thus latching the stent 160 to the coupling ring 162. The coupling ring 162 may further include a plurality of outwardly projecting tabs 172 that are bent or curl around the base ring 32.

To aid in guiding the latches 166 through the slots 164, one or more guide members may be used to direct the coupling ring toward the stent such that the slots are aligned with the latch members. For example, in the illustrated embodiment, a plurality of guide filaments 170 are attached to each one of the upstanding latch members and passed through the corresponding slots. FIG. 16A illustrates the pre-assembled valve 10M with the guide filaments 170 extending up through each of the slots 164. The implantation procedure comprises first delivering and expanding the stent 160, and then advancing the valve member 30 to the position shown in FIG. 16B. The coupling ring 162 is then parachuted down the array of guide filaments 170, ultimately facilitating passage of the latches 166 through the slots 164. The final assembly is seen in FIG. 16B. In a preferred embodiment, each two guide filaments 170 comprises a strand of a single looped passing through small holes in each of the latch members. Removal of the guide filaments 170 is thus a simple matter of just pulling one of the strands, or severing the loop in between the latch members. Note that guide filaments could be used on any of the embodiments described herein to facilitate coupling of the separate components of the prosthetic heart valves. For example, in

another variation, a wireform similar to the embodiment illustrated in FIG. 14A may also be used with a guiding filament.

The exemplary embodiment shows the latches 166 extending around the outside of the base ring 32 of the valve member 30. It is entirely feasible, on the other hand, to design the latches 166 to pierce through the base ring 32. Inclusion of the coupling ring 162 is suggested, because of its washer-like function in holding the assembly together. However, the latches 166 may be designed to pierce through and securely fasten to stent 160 to the base ring 32 without the use of the coupling ring 162. In this regard, the latches 166 may be configured differently, or more than the number shown may be provided. For example, 4, 6, 8, or more single latch members having a configuration such as shown with a leading sharp point and rearwardly directed barb (much like a fish hook) could fight adequate anchorage through a conventional base ring 32 made of a silicone sponge covered with cloth. Those of skill in the art will understand that there are numerous alternatives available.

The stent 160 in FIGS. 16A and 16B has an outflow end that is preferably sized larger than its inflow end. More particularly, the outflow end is flared so as to receive therein the base ring 32 of the valve member 30. In this way, a larger orifice valve member can be utilized than with a straight tubular stent. The reader is also reminded that at least the flared portion of the stent 160 is desirably provided with a sleeve of Dacron or other such fabric to help prevent paravalvular leaking between the base ring 32 and the surrounding native valve annulus.

With reference to FIGS. 17A and 17B, yet another two part prosthetic valve 10N is configured for rapid deployment in a heart for replacing a defective native valve. In this version, an expandable anchoring member or stent 180 couples to a valve member 30 through the use of a coupling ring 182 in a manner similar to the last-described embodiment. The coupling ring 182 carries a plurality of latches 184 which mate with brackets 186 provided on the stent 180. In the illustrated embodiment, the latches 184 again comprise a pair of spaced-apart latch members having outwardly directed teeth 188, and the brackets 186 are simply apertures or slots in material loops that extend outward from the stent 180 adjacent its outflow end. Bringing the three components together, the latches 184 extend through the brackets 186 as seen in FIG. 17B. To facilitate proper and rapid passage of the latches 184 through the brackets 186, a plurality of guide filaments 190 loop through the brackets 186 and through holes provided in the latches 184. Simply parachuting the coupling ring 182 down the filaments 190 aims the latches 184 through the brackets 186.

At this stage, it is important to note that any of the fixation rings (i.e., locking ring 112, fixation ring 134, adapter 142, coupling ring 162, or coupling ring 182) described above could be designed to engage the surrounding tissue (annulus) and provide additional protection against paravalvular leakage. For example, a tissue growth factor or fibrin glue or the like may be coated on the exterior of any of these fixation rings for a better seal. Alternatively, the fixation rings might have an outer rim of fabric for encouraging tissue ingrowth. Moreover, the various fixation rings described and the base ring 32 of the valve member 30 may be constructed as a single component. For example, the base ring 32 could be configured to have slots (or any coupling member) in lieu of a separate fixation ring.

With reference now to FIG. 18, an alternative expandable anchoring member or stent 200 is illustrated wherein the anchoring member is configured to receive a valve member

19

30 to form a prosthetic heart valve. As illustrated in FIG. 19, a portion of the valve member is gripped between inwardly extending members located within the stent. More particularly, the stent 200 comprises a plurality of axial struts 202 connected by a number of rows of circumferential crown-shaped struts 204 to form a generally tubular structure. A lower or inflow end of the stent 200 includes a circumferential row of crown-shaped struts 206 that is larger than the others such that the inflow end of the stent flares outward. The upper rows 204 of circumferential struts define valleys (pointing downward) at the axial struts 202 and peaks (pointing upward) midway between each two adjacent axial struts. As seen from FIG. 18, therefore, the spaces defined between adjacent axial struts 202 and adjacent rows of circumferential struts 204 are preferably chevron-shaped, pointed upward. Conversely, the lower circumferential row of struts 206 has upper peaks at the axial struts 202 and lower valleys therebetween, resulting in elongated hexagon-shaped spaces between the lower two circumferential rows of struts.

The stent 200 possesses a plurality of prongs that extend inward therefrom to capture the valve member 30. As seen in FIG. 19, the base ring 32 of the valve member 30 seats on a plurality of lower prongs 208. FIG. 18 shows the lower prongs 208 extending inward from the lower row of struts 206 at the valleys between adjacent axial struts 202. The lower prongs 208 terminate in enlarged heads 210 to prevent damage to the base ring 32. As seen in FIG. 19, the lower prongs 208 project inward farther than the expanded to defined by the upper portion of the stent 200. Additionally, a plurality of upper prongs 212 extend inward from one of the upper rows of circumferential struts 204. In the illustrated embodiment, there are four rows of circumferential struts 204, and the upper prongs 212 project inward from the second lowest row. As seen in FIG. 19, the upper prongs 212 contact the base ring 32 of the valve member 30. In this manner, the valve member 30 is captured between the lower prongs 208 and upper prongs 212.

In the illustrated embodiment, the stent 200 includes twelve axial struts 202, and one of each of the prongs 208, 212 between each adjacent pair of axial struts, resulting in twelve each of the lower and upper prongs. Of course, the number of prongs could be more or less depending on the configuration of the stent 200. Further, there may be more than one prong between adjacent pairs of axial struts 202, or the prongs may be provided only between every other pair. The prongs 208, 212 may be initially flat within the profile of the surrounding struts to prevent interference with an expansion-balloon. After stent deployment they may be bent inward into the angles shown using a tool (not shown). Alternatively, the balloon wall could be relatively thick and able to withstand puncture by the round heads of the prongs 208, 212 such that they are at all times biased inward and automatically assume the angles shown after balloon removal.

To deploy the prosthetic heart valve of FIGS. 18 and 19, the user advances the stent 200 in a collapsed state through the vasculature or a chest port into the target implantation site. Through self-expansion or balloon-expansion, the stent 200 expands into contact with the surrounding valve annulus. The valve member 30 then advances into position adjacent the outflow or upper end of the stent 200. Desirably, the valve member 30 is a conventional non-expandable design, but could also be expandable, in which case it is then expanded prior to assembly with the stent 200.

The outer diameter of the base ring 32 of the valve member 30 is sized approximately the same as the inner

20

diameter of the tubular upper portion of the stent 200. The valve member 30 advances from the outflow end of the stent 200 toward the inflow end until the base ring 32 contacts the circular row of upper prongs 212. The upper prongs 212 are flexible, hinged, or otherwise capable of being displaced outward by the base ring 32 as the valve member 30 passes. Ultimately, the base ring 32 seats on the circular row of relatively non-flexible lower prongs 28 and the valve member 30 cannot be advanced farther. The spacing between the lower prongs 208 and the upper prongs 212 is such that the upper prongs 212 spring inward at the point that the base ring 32 seats on the lower prongs 208. The upper prongs 212 may be formed with blunt heads like the lower prongs 208, or may be straight or even sharp-pointed to pierce the base ring 32 and provided enhanced anchorage. In a preferred embodiment, both the lower prongs 208 and upper prongs 212 possess enlarged, blunt heads such that the base ring 32 is merely trapped between the two sets of prongs.

The design of the stent 200 of FIG. 18 thus enables rapid deployment of a valve member therewithin, as well as positive tactile feedback to the user with valve member 30 is completely installed. Because the base ring 32 is sized closely within the stent 200, good peripheral sealing is provided. To better enhance sealing, a peripheral skirt or layer of graft material may be added on the interior or exterior of the stent 200.

With reference to FIG. 20, another embodiment of a prosthetic heart valve 220 comprises a tubular, expandable anchoring member or stent 222, a valve member 30, and an adapter ring 224 for coupling the two components together. The stent 222 and manner of connecting the stent to the valve member 30 is similar to embodiment of FIGS. 3 and 4, and also the embodiment of FIG. 12, in that a plurality of tines 226 project upward from the stent 222. However, instead of the tines 226 piercing or curling around the base ring 32 of the valve member 30, the tines interact with the adapter ring 224. In particular, the adapter ring 224 attaches around the lower periphery of the base ring 32, preferably via a secure stitch line formed during assembly of the valve member 30. The tines 226 pierce or otherwise engage the adapter ring 224 instead of the base ring 32 to couple the valve member 30 to the stent 222. The supplemental adapter ring 224 provides an added margin of safety that helps prevent damage to the valve member 30 by the tines 226. For instance, if the tines 226 are configured to pierce and curl inward, they are farther away from the inner flexible leaflets 36 of the valve member which are susceptible to puncture or tearing.

With reference to FIG. 21, yet another embodiment of a prosthetic heart valve 230 comprises an anchoring member or stent 232 coupled to a valve member 30 via a plurality of sutures 234. The components of the valve 230 are shown exploded above a container or jar 236 used to store the components. In this regard, the entire assembly, including the attachment sutures 234, may be stored together in the jar 236 so as to be ready for deployment. Alternatively, only the stent 232 and valve member 30 may be stored in the jar 236, and the sutures 234 added just prior to deployment but before the actual operation. Still further, the stent 232 can be stored dry in a sterile container, while the valve member 30 having bioprosthetic leaflets may be stored separately in a suitable preservative fluid such as glutaraldehyde. In any event, details of the prosthetic heart valve 230 will be described below with reference to FIGS. 22A through 22C.

FIGS. 22A through 22C show the components of the prosthetic heart valve 230 in conjunction with a valve dilator/delivery tube 240. The usage of the delivery tube 240



will be described below. The stent **232** comprises an expandable, tubular structure formed of a plurality of axial struts **242** joined by a plurality of angled circumferential struts **244**. In this embodiment, there are four rows of circumferential struts **244**, the upper two pointing upward, and the lower two pointing downward. The result is a series of both diamond-shaped and chevron-shaped openings. Three axial bars **246** substitute for the more narrow struts **242** at three evenly-spaced positions around the stent **232**. As seen in the view of FIG. **22B**, the commissures **34** of the valve member **30** align with the axial bars **246**.

With reference now to the sectional view of FIG. **22C**, the stent **232** additionally comprises an inner fixation ring **250** and an outer sealing ring **252**. Both these rings **250**, **252** attach to the struts of the stent **232** independently, or to each other through the struts. For example, a series of sutures (not shown) can be used to join the inner ring **250** and outer ring **252** in a relatively continuous circumferential line around the stent **232**. These rings are desirably made of suture-permeable, typically compressible material such as silicone rubber, or may be rolled up fabric cuffs. In any event, the inner fixation ring **250** couples to the valve member **30**, while the outer sealing ring **252** help prevent leakage around the stent **232**.

As seen in FIG. **22A**, the attachment sutures **234** extend upward within the stent **232** from the inner fixation ring **250**. In this regard, each two strands of the attachment sutures **234** may be defined by looping a single length of suture downward and back upward through the fixation ring **250**. The circular array of sutures **234** then passes through corresponding sectors of the base ring **32** of the valve member **30**. Again, this can be done at the time of valve assembly, just prior to the valve replacement procedure, or after the stent **232** has been implanted. Those of skill in the art will understand the process of lining up the circular array of attachment sutures **234** into the appropriate locations around the base ring **32** to permit the valve member **32** to parachute down the sutures until it contacts the fixation ring **250**.

The entire procedure will now be described in conjunction with use of the valve dilator/delivery tube **240**. As mentioned above, the valve replacement procedures described herein are sometimes done without removing the existing native valve. The annulus and valve leaflets are often heavily calcified, and sometimes provide a serious impediment to passage and implant of a replacement valve, even a valve that is initially quite small and balloon expanded. To help widened the orifice in which the prosthetic valve **230** will be implanted, the delivery tube **240** receives all of the valve components therein and acts as a protective sleeve and dilator. In a preferred embodiment, just the sealing ring **252** extends out of the delivery tube **240** at an inflow or leading end thereof.

First, the attachment sutures **234** are preinstalled within the fixation ring **250** and, while maintaining a non-crossing circular array, are passed through the delivery tube **240** to be accessible out the upper end. The sutures **234** are then passed through the appropriate locations within the base ring **32** of the valve member **30**. Of course, this can be done during fabrication of the prosthetic heart valve **230**, though some structure for maintaining the relative position and orientation of two components is required. In any event, a holder (not shown) attached to the valve member **30** is used to advance the valve member along the array of sutures **234** and within the delivery tube **240**, into the approximate position seen in FIG. **22A**.

When the patient has been prepared, and an access opening to the target implantation site created, the assembly of the prosthetic heart valve **230** within the delivery tube **240** advances into the body. The leading end comprises the sealing ring **252** and an outwardly bulged portion **254** in the delivery tube **240**. For installation in the aortic annulus, the delivery tube **240** advances down the ascending aorta until the stent **232** lines up with the annulus (with the help of radiopaque markers or the like). The outwardly bulged portion **254** in the delivery tube **240** helps open up the calcified annulus. Even if the native valve is resected, sometimes the annulus will shrink a little prior to implant of the valve. The valve dilator/delivery tube **240** thus helps open up the annulus to permit implant of a desired diameter valve. The contour of the bulged portion **254** is relatively smooth, and the material may be Teflon or other such highly lubricated surface so that the tube easily slips through the annulus. A slight back-and-forth movement may be required to fully open the annulus.

At this stage, the delivery tube **240** retracts relative to the stent **232**, through the use of a pusher (not shown) for example, such that the stent **232** may fully expand into the annulus. The stent **232** may be self-expanding and thus be only partially expanded within the delivery tube **240**. When the delivery tube **240** is removed, the stent **232** springs outward into firm engagement with the annulus. Alternatively, a balloon (not shown) may be used to accomplish the final expansion of the stent **232**, which configuration would require a catheter passing through the center of the valve leaflets **34**. If the stent **232** is balloon expandable, consideration must be taken of the continual attachment of the valve to the guide sutures **234**. On the other hand, if the stent **232** is self-expanding, then typically an auxiliary sheath would be provided to hold the stent in the contracted condition.

When the user is satisfied that the stent **232** is properly positioned, the valve member **30** is advanced using the aforementioned holder (not shown). As the valve member **30** advances, care is taken to ensure that the attachment sutures **234** remain untangled and taut. Ultimately, the valve member **30** seats on the fixation ring **250** as seen in FIGS. **22B** and **22C**. At this point, the user ties off and severs the attachment sutures **234** in a conventional manner. The provision of the sealing ring **252** directly adjacent and surrounding the fixation ring **250** greatly enhances the ability of the prosthetic valve **230** to resist paravalvular leaking.

In one advantageous feature, preferred embodiments of the component based prosthetic valves described herein may be used with existing technology. For example, certain stent embodiments may be configured for attachment to sewing rings provided on existing prosthetic valves. In other cases, valve member require only small variations in order to be used with the component based system. Not only will this contribute to a lower price for the final valve, but also learned familiarity to the system for surgeons who might be hesitant to adopt a completely new system.

It will be appreciated by those skilled in the art that embodiments of the present invention provide important new devices and methods wherein a valve may be securely anchored to a body lumen in a quick and efficient manner. Embodiments of the present invention provide a means for implanting a prosthetic valve in a surgical procedure without requiring the surgeon to suture the valve to the tissue. Accordingly, the surgical procedure time is substantially decreased. Furthermore, in addition to providing an anchoring member for the valve, the stent may be used to maintain

the native valve in a dilated condition. As a result, it is not necessary for the surgeon to remove the native leaflets, thereby further reducing the procedure time.

It will also be appreciated that the present invention provides an improved system wherein a valve member may be replaced in a more quick and efficient manner. More particularly, it is not necessary to cut any sutures in order to remove the valve. Rather, the valve member may be disconnected from the stent (or other support structure) and a new valve member may be connected in its place. This is an important advantage when using biological tissue valves or other valves having limited design lives. Still further, it will be appreciated that the devices and methods of the present invention may be configured for use in a minimally invasive approach (e.g., through a small incision between the ribs) or in a percutaneous procedure while still remaining within the scope of the invention.

While the invention has been described in its preferred embodiments, it is to be understood that the words which have been used are words of description and not of limitation. Therefore, changes may be made within the appended claims without departing from the true scope of the invention.

What is claimed is:

1. A prosthetic heart valve comprising:

a non-expandable valve member comprising a base ring surrounding an inflow end thereof;

an expandable anchoring member sized to contact and anchor to a heart valve annulus in an expanded state, the expandable anchoring member comprising an expandable, tubular structure formed of a plurality of axial struts joined by a plurality of angled circumferential struts; and

means for coupling the non-expandable valve member to the anchoring member.

2. The prosthetic heart valve of claim 1, wherein the means for coupling comprises a plurality of sutures.

3. The prosthetic heart valve of claim 1, wherein the anchoring member comprises a suture-permeable fixation ring attached thereto, wherein the means for coupling comprises sutures looped between the base ring and the fixation ring.

4. The prosthetic heart valve of claim 3, further comprising an outer sealing ring.

5. The prosthetic heart valve of claim 1, further including an adapter sized to surround the non-expandable valve member and to engage the anchoring member, to connect the non-expandable valve member and anchoring member.

6. The prosthetic heart valve of claim 5, wherein the adapter is selected from the group consisting of:  
an annular ring; and  
a wireform-shaped member.

7. The prosthetic heart valve of claim 5, wherein the adapter includes a plurality of discrete connectors, and the anchoring member comprises a plurality of mating connectors spaced around a peripheral outflow end thereof, the connectors on the adapter and anchoring member being configured to engage one another by displacing the adapter toward the anchoring member.

8. The prosthetic heart valve of claim 5, wherein the adapter further includes a plurality of connectors adapted to engage and couple the adapter directly to the base ring.

9. The prosthetic heart valve of claim 1, wherein the expandable, tubular structure comprises a series of both diamond-shaped and chevron-shaped openings.

\* \* \* \* \*