

US009566582B2

(12) **United States Patent**
Buse et al.

(10) **Patent No.:** **US 9,566,582 B2**
(45) **Date of Patent:** **Feb. 14, 2017**

(54) **MULTI-WELL TRAY**

2200/02 (2013.01); *B01L 2200/025* (2013.01);
B01L 2200/026 (2013.01);

(71) Applicant: **GEN-PROBE INCORPORATED**, San Diego, CA (US)

(Continued)

(72) Inventors: **David Buse**, San Diego, CA (US);
Byron J. Knight, San Diego, CA (US)

(58) **Field of Classification Search**

CPC G01N 35/026; G01N 2035/0444;
G01N 35/1065; B01L 3/523; B01L
3/50825; B01L 3/527; B01L 3/502; B01L
3/50853; Y10T 436/113332; Y10T
436/11; B65D 2539/003; B01F 9/0021
See application file for complete search history.

(73) Assignee: **GEN-PROBE INCORPORATED**, San Diego, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(56) **References Cited**

U.S. PATENT DOCUMENTS

(21) Appl. No.: **14/837,647**

5,356,525 A * 10/1994 Goodale G01N 27/44743
204/602
5,622,675 A * 4/1997 Glenday B01L 3/5085
422/552

(22) Filed: **Aug. 27, 2015**

(Continued)

(65) **Prior Publication Data**

US 2015/0362515 A1 Dec. 17, 2015

FOREIGN PATENT DOCUMENTS

Related U.S. Application Data

CA 2724106 A 6/2011
WO 2010/140680 A1 9/2010

(63) Continuation of application No. 14/210,105, filed on Mar. 13, 2014.

(Continued)

OTHER PUBLICATIONS

CIPO Office Action, Canadian Application No. 2,945,126, Nov. 17, 2016.

(51) **Int. Cl.**

B01L 3/00 (2006.01)
B65B 69/00 (2006.01)

(Continued)

Primary Examiner — Lyle Alexander

Assistant Examiner — Bryan Kilpatrick

(74) *Attorney, Agent, or Firm* — Rothwell, Figg, Ernst & Manbeck PC; Charles B. Cappellari, Esq.


(52) **U.S. Cl.**

CPC **B01L 3/5082** (2013.01); **B01L 3/502** (2013.01); **B01L 3/50825** (2013.01); **B01L 3/50853** (2013.01); **B01L 3/50855** (2013.01); **B01L 3/523** (2013.01); **B01L 3/527** (2013.01); **B65B 69/00** (2013.01); **B65D 1/0207** (2013.01); **B65D 1/34** (2013.01); **B65D 39/0017** (2013.01); **B65D 39/0029** (2013.01); **C12Q 1/686** (2013.01); **G01N 35/026** (2013.01); **G01N 35/1079** (2013.01); **B01L**

(57) **ABSTRACT**

System, apparatuses, and methods for performing automated reagent-based analysis are provided. Also provided are methods for automated attachment of a cap to a reaction receptacle, and automated removal of a cap from a capped reaction receptacle.

15 Claims, 28 Drawing Sheets



Related U.S. Application Data	(56)	References Cited
(60) Provisional application No. 61/782,320, filed on Mar. 14, 2013.		U.S. PATENT DOCUMENTS
(51) Int. Cl. <i>B65D 39/00</i> (2006.01) <i>G01N 35/02</i> (2006.01) <i>C12Q 1/68</i> (2006.01) <i>G01N 35/10</i> (2006.01) <i>B65D 1/02</i> (2006.01) <i>B65D 1/34</i> (2006.01) <i>G01N 30/60</i> (2006.01)		5,753,186 A 5/1998 Hanley et al. 6,063,341 A 5/2000 Fassbind et al. 6,086,827 A * 7/2000 Horner B01L 9/06 206/438 6,337,053 B1 1/2002 Tajima 6,602,474 B1 8/2003 Tajima 7,187,286 B2 3/2007 Morris et al. D618,820 S 6/2010 Wilson et al. D637,737 S 5/2011 Wilson et al. 2004/0005714 A1 1/2004 Safar et al. 2005/0244972 A1 11/2005 Hilsen et al. 2006/0258010 A1 11/2006 Safar et al. 2007/0148052 A1 6/2007 Hiramatsu et al. 2007/0259348 A1 11/2007 Phadke et al. 2008/0195326 A1 8/2008 Munzer et al. 2008/0268529 A1 10/2008 Furusato et al. 2009/0074624 A1 * 3/2009 Liang 422/100 2009/0088336 A1 4/2009 Burd et al. 2009/0129978 A1 5/2009 Wilson et al. 2009/0221059 A1 9/2009 Williams et al. 2010/0075426 A1 3/2010 Kubo et al. 2010/0180980 A1 7/2010 Lee et al. 2011/0022331 A1 1/2011 Clinton et al. 2012/0122231 A1 5/2012 Tajima 2012/0149035 A1 6/2012 Burd et al.
(52) U.S. Cl. CPC . <i>B01L 2200/0668</i> (2013.01); <i>B01L 2200/0689</i> (2013.01); <i>B01L 2200/16</i> (2013.01); <i>B01L</i> <i>2300/042</i> (2013.01); <i>B01L 2300/044</i> (2013.01); <i>B01L 2300/046</i> (2013.01); <i>B01L</i> <i>2300/0609</i> (2013.01); <i>B01L 2300/0829</i> (2013.01); <i>B01L 2300/0832</i> (2013.01); <i>B01L</i> <i>2300/0838</i> (2013.01); <i>B01L 2300/0851</i> (2013.01); <i>B01L 2300/0858</i> (2013.01); <i>B01L</i> <i>2400/0406</i> (2013.01); <i>B65D 2539/003</i> (2013.01); <i>G01N 30/6091</i> (2013.01); <i>Y10T</i> <i>436/11</i> (2015.01)		
		* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 2E




FIG. 2F




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B






FIG. 5A






FIG. 5D




FIG. 5E




FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B




FIG. 8





FIG. 9A






FIG. 9D




FIG. 9E




FIG. 10A




FIG. 10B




FIG. 11A




FIG. 11B




FIG. 11C




FIG. 11D

MULTI-WELL TRAY

CROSS REFERENCE TO RELATED APPLICATION

This application claims the benefit under 35 U.S.C. §120 of the filing date of non-provisional patent application Ser. No. 14/210,105 filed Mar. 13, 2014, which claims the benefit under 35 U.S.C. §119(e) of the filing date of U.S. Provisional Application No. 61/782,320, filed Mar. 14, 2013, which is incorporated herein by reference.

BACKGROUND

Field

The present disclosure relates to systems and apparatuses for performing automated reagent-based biochemical assays.

Background Information

Automated molecular assay instrumentation offers numerous advantages, however most automated instruments suffer from a limited set of assay capabilities. These limited capabilities complicate or inhibit parallel processing of multiple assays and, as a result, reduce sample throughput and flexibility in assay choices. This is particularly true for sensitive assays such as those involving nucleic acid detection and/or an amplification procedure. There are many procedures in use for amplifying nucleic acids, including the polymerase chain reaction (PCR), (see, e.g., Mullis, "Process for Amplifying, Detecting, and/or Cloning Nucleic Acid Sequences," U.S. Pat. No. 4,683,195), transcription-mediated amplification (TMA), (see, e.g., Kacian et al., "Nucleic Acid Sequence Amplification Methods," U.S. Pat. No. 5,399,491), ligase chain reaction (LCR), (see, e.g., Birkenmeyer, "Amplification of Target Nucleic Acids Using Gap Filling Ligase Chain Reaction," U.S. Pat. No. 5,427,930), strand displacement amplification (SDA), (see, e.g., Walker, "Strand Displacement Amplification," U.S. Pat. No. 5,455,166), and loop-mediated isothermal amplification (see, e.g., Notomi et al., "Process for Synthesizing Nucleic Acid," U.S. Pat. No. 6,410,278). A review of several amplification procedures currently in use, including PCR and TMA, is provided in HELEN H. LEE ET AL., NUCLEIC ACID AMPLIFICATION TECHNOLOGIES (1997).

Automated molecular assays incorporate the use of consumable components, which may or may not hold reagents utilized in the molecular assay to be performed, which can be manually loaded onto automated instrumentation. Providing such consumable components that are configured to limit contamination, enhance target detection, simplify loading into and transport within the system, enhance the operability of mechanical components within the automated system while lowering cost, and providing high performance in connection with the assay to be performed is desirable.

The present disclosure addresses these and other needs in the art.

All documents referred to herein, or the indicated portions, are hereby incorporated by reference herein. No document, however, is admitted to be prior art to the claimed subject matter.

SUMMARY

The present disclosure relates to systems, methods, and apparatuses for performing automated reagent-based biochemical assays.

Accordingly, in an aspect of the present disclosure, there is provided a single-piece receptacle. The receptacle includes a body having a generally cylindrical upper portion and a tapered lower portion, the upper portion having an open end and the lower portion being closed-ended, an annular ring formed on an outer surface of the body, the annular ring separating the upper and lower portions of the body, a lip circumscribing the open end of the upper portion, the lip being adapted for inter-locking engagement with a mated cap, and a plurality of longitudinally oriented grooves formed in an inner surface of the upper portion of the body and situated between the open end and the annular ring. In various embodiments, the closed end of the lower portion may be flat or curved. The number of grooves disposed on the inner surface of the upper portion is selected from the group consisting of 2, 3, 4, 5, 6, 7, and 8. The lip may radially-extend from an exterior surface of the upper portion and tapers towards the open end thereof.

In another aspect, the disclosure provides a cap securable to the single-piece receptacle. The cap includes a lower portion having an outer surface for sealing engagement of an inner surface of the open upper end of the body, the outer surface including one or more annular ring(s), an upper portion having a length, an inner surface, an outer surface, and an open end configured for engagement with an automated pipettor, and further including one or more recess(es), which can be concave in shape, disposed on the outer surface thereof extending along at least part of the length of the upper portion, and one or more linear rib(s) disposed on the inner surface of the upper portion, each linear rib having a length corresponding to the length of at least one of the recesses, and wherein each of the one or more linear ribs is positioned on the inner surface of the cap in a manner that corresponds to at least one of the recesses such that at least one linear rib lies on an inner surface of the cap that directly opposes the position of at least one recess on the outer surface of the cap, and a lip positioned between, and extending radially away from, the upper and lower portions, the lip including a plurality of locking arms extending toward the lower portion of the cap for securely engaging the lip of the receptacle. In various embodiments, the number of linear ribs corresponds to the number of recesses in a one-to-one relationship, and the number of recesses disposed on the outer surface of the cap is selected from the group consisting of 2, 3, 4, 5, 6, 7, and 8. The lower portion of the cap may include 1, 2, or 3 annular rings for sealing engagement of the inner surface of the body of the receptacle.

In certain embodiments, the locking arms comprise a snap fit attachment for securely engaging the lip of the receptacle. The number of locking arms may be selected from the group consisting of 1, 2, 3, 4, 5, 6, 7, and 8. In addition, the number of linear ribs disposed on the inner surface of the upper portion of the cap may be selected from the group consisting of 2, 3, 4, 5, 6, 7, and 8. The distal portion of the cap may further include a bottom separating the upper portion of the cap from the proximal lower portion of the cap. In certain embodiments, the bottom is scored for piercing. The at least one of the linear rib includes a portion that gradually tapers radially inward toward the center of the upper portion, or increases in size (e.g., an increase in thickness or radial geometry) as the at least one of the linear ribs approaches the bottom separating the upper portion of the cap from the proximal lower of the cap.

In another aspect, the disclosure provides a method for the automated removal of a cap from a capped reaction receptacle. The method includes providing a single-piece recep-

3

tacle comprising a body having a generally cylindrical upper portion and a tapered lower portion, the upper portion having an open end and the lower portion being closed-ended; an annular ring formed on an outer surface of the body, the annular ring separating the upper and lower portions of the body; a lip circumscribing the open end of the upper portion, the lip being adapted for inter-locking engagement with a mated cap; and a plurality of longitudinally oriented grooves formed in an inner surface of the upper portion of the body and situated between the open end and the annular ring; and a cap securable to the single-piece receptacle, comprising: a lower portion having an outer surface for sealing engagement of an inner surface of the open upper end of the body, the outer surface including one or more annular ring(s); an upper portion having a length, an inner surface, an outer surface, and an open end configured for engagement with an automated pipettor, and further including one or more recess(es) disposed on the outer surface thereof extending along at least part of the length of the upper portion, and one or more linear rib(s) disposed on the inner surface of the upper portion, each linear rib having a length corresponding to the length of at least one of the recesses, and wherein each of the one or more linear ribs is positioned on the inner surface of the cap in a manner that corresponds to at least one of the recesses such that at least one linear rib lies on an inner surface of the cap that directly opposes the position of at least one recess on the outer surface of the cap; and a lip positioned between, and extending radially away from, the upper and lower portions, the lip including a plurality of locking arms extending toward the lower portion of the cap for securely engaging the lip of the receptacle. The cap is securely engaged to the single piece receptacle. The method further includes performing an automated motion of contacting an inner portion of at least one of the plurality of locking arms with a raised annular ridge defined around a receptacle slot, wherein said contacting urges the locking arms away from the lip of the receptacle thereby disengaging the cap from the receptacle, and while the cap is disengaged from the receptacle, performing an automated motion of lifting the cap away from the receptacle, thereby removing the cap from the capped reaction receptacle.

In another aspect, the disclosure provides a multi-well tray for use in an automated process. The multi-well tray includes a base having a top surface, a card insert having a first surface, the card insert configured for removable attachment to the base, wherein when attached to the base, the first surface of the card insert is substantially parallel to and flush with the top surface of the base, and a plurality of sets of wells. Each set of wells includes a first well disposed in an opening of the top surface of the base, the first well being configured to receive a receptacle cap, second well disposed in an opening of the top surface of the base, the second well being configured to receive a receptacle, wherein the receptacle cap and the receptacle are configured for secure engagement with each other, and a third well disposed in an opening of the first surface of the card insert, the third well containing a lyophilized reagent. The wells of each set of wells are disposed in alignment with each other, and the third well is sealed with a frangible seal. In certain embodiments the third well may include one or more retention features for retaining a lyophilized reagent at the bottom thereof.

In another aspect, the disclosure provides a reagent-containing multi-well tray for use in an automated process. The multi-well tray includes a base having a top surface and a plurality of wells disposed therein. Each of the wells may

4

be defined by a cylindrical or conical wall, an open upper end, and a bottom. The wells may be disposed in alignment with each other, and sealed with a frangible seal. In certain embodiments each of the wells may include at least one retention feature to retain a lyophilized reagent therein. The multi-well tray may further include a lyophilized reagent disposed within each well, positioned at, or adjacent to, the bottom. Exemplary retention features include, but are not limited to, an annular ridge formed on the well wall and positioned above the lyophilized reagent, a spiral channel formed along a length of the well wall and positioned above the lyophilized reagent, a tapered ring attached to the well wall and positioned above the lyophilized reagent, a capillary insert attached to the well wall, and a collar attached to the well wall at or proximal to the open upper end. The collar may further include one or more fingers formed on a bottom surface thereof that protrude along a radius of curvature toward an axial center of the well. The capillary insert may include an open upper end that tapers toward the bottom of the well, and a capillary channel formed between the open upper end and the bottom of the well. In certain embodiments, the lyophilized reagent is held in position at, or adjacent to, the bottom through the use of electrostatic force.

In various aspects, any of the multi-well trays may also include machine readable indicia positioned on the base or card insert containing identifying information regarding the multi-well tray or card insert, including reagents contained therein. The machine readable indicia may be a barcode, 2D barcode, or a radio frequency identification (RFID). In addition, the multi-well tray may include one or more locking arms disposed on the card insert for locking engagement with the base. The first well may be defined by a first side wall and a bottom surface, and include a protrusion extending from a center of the bottom surface of the well toward the top surface of the base for frictional engagement with a hollow portion in the lower portion of the receptacle cap. The first well may also include a plurality of tabs protruding from the first side wall for securely engaging the receptacle cap. The second well may be defined by a second side wall and a second bottom, the second bottom including a through-hole extending from an inner surface of the second well to an outer surface of the base. An annular ledge may then be formed within the second well at the circumference of the through-hole. The second well may also include a plurality of legs protruding from the second side wall for securely engaging the distal portion of the cap. The third well may be defined by a third side wall and a third bottom, and include one or more features selected from the group consisting of a convex groove, a concave groove, and a set of grooves comprising a criss-cross pattern disposed in the third bottom. The third side wall may be conical, tapering toward the bottom thereof. The third well may also include a plurality of rigid guides radially protruding from the third wall toward a center thereof. The base may be spatially indexed such that an automated pipettor can accurately identify and/or access any of the plurality of wells when the multi-well tray is placed in an automated system.

In another aspect, the disclosure provides a cartridge with communicating wells for use in an automated process. The cartridge includes a casing having a top surface, a fluid chamber disposed within the casing, and wherein a first opening is provided in the top surface of the casing having at least one side wall surface extending to, or optionally forming at least a portion of, the fluid chamber, and a fluid reservoir disposed within the casing adjacent to and in fluid communication with the fluid chamber. In certain embodiments, the cartridge also includes an oil reservoir disposed

5

within the casing and adjacent to the fluid chamber. The fluid communication between the fluid chamber and the fluid reservoir may be both liquid and gaseous communication, and may be provided by the same or different means. The cartridge may also include a second opening that is provided in the top surface of the casing having at least one side wall surface extending to, or optionally forming at least a portion of, the fluid reservoir. Each of the first and second openings may be sealed from exposure to the ambient atmosphere with a frangible seal.

In another aspect, the disclosure provides a cartridge rack for use in an automated process. The cartridge rack includes a chassis having a top surface and a first and a second opposing end, the chassis being configured for releasable attachment to one or more multi-well trays(s) as set forth herein, a plurality of machine readable indicia including data disposed on the chassis, and a handle disposed on the first end surface of the chassis. The chassis is configured for releasable attachment to a plurality (e.g., two or more, or up to five) multi-well trays. In various embodiments, the chassis is configured for releasable attachment to a cartridge with communicating wells. As discussed above, the cartridge includes a casing having a top surface; a fluid chamber disposed within the casing, and wherein a first opening is provided in the top surface of the casing having at least one side wall surface extending to, or optionally forming at least a portion of, the fluid chamber; and a fluid reservoir disposed within the casing adjacent to and in fluid communication with the fluid chamber. The machine readable indicia may include identifying information regarding the multi-well tray attached thereto, and may be in the form of a barcode, 2D barcode, QR code, or an RFID. The machine readable indicia may be readable through a direct contact connection, a wired connection, or wirelessly.

In another aspect, the disclosure provides a system for conducting an automated reagent-based assay. The system includes a multi-well tray, a cartridge with communicating wells, and an automated pipettor positioned on a robot arm. The multi-well tray may include a plurality of wells, each of the wells containing a lyophilized reagent, wherein the plurality of wells are disposed in alignment with each other and sealed with a frangible seal, wherein the lyophilized reagent includes a target-specific reagent. The cartridge with communicating wells includes a casing having a top surface; a fluid chamber disposed within the casing, and wherein a first opening is provided in the top surface of the casing having at least one side wall surface extending to, or optionally forming at least a portion of, the fluid chamber; a fluid reservoir disposed within the casing in fluid communication with the fluid chamber; and a diluent contained within the fluid chamber. The automated pipettor is adapted to execute a retrieval and dispense protocol that includes a retrieval of a portion of the reagent from the cartridge and a dispense of the portion of the reagent in one of the plurality of wells, and wherein the retrieval and dispense protocol is repeated for each of the plurality of wells. In various embodiments, the multi-well tray, the cartridge with communicating wells, and the automated pipettor are contained within a housing, such as an automated biochemical analyzer.

In another aspect, the disclosure provides a method for providing a stabilized reagent for a molecular assay. The method includes introducing a fluid molecular assay reagent to a well, the well including a tapered opening and a capillary insert having a capillary channel, wherein the tapered opening and capillary channel are in fluid communication. Thereafter, subjecting the well containing the

6

reagent to conditions suitable for lyophilizing the fluid molecular assay reagent to prepare a lyophilized reagent. Thereafter, reconstituting the lyophilized reagent by introducing a reconstitution solution to the tapered opening of the well to prepare a reconstituted reagent. Then withdrawing the reconstituted reagent using a fluid transfer device that is introduced into the tapered opening of the well. In various embodiments, the fluid transfer device is a pipettor. The molecular assay may be a polymerase chain reaction (PCR) assay.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1A-1D are pictorial diagrams showing a receptacle of the present disclosure. FIG. 1A is a side view of the receptacle. FIG. 1B is a cross-sectional view of the receptacle taken along the line 1B-1B in FIG. 1A. FIG. 1C top view of the receptacle. FIG. 1D is a perspective view of the receptacle.

FIGS. 2A-2F are pictorial diagrams showing a cap of the present disclosure. FIG. 2A is a side view of the cap. FIG. 2B is a cross-sectional view of the cap taken along the line 2B-2B in FIG. 2A. FIG. 2C top view of the cap. FIG. 2D is a bottom view of the cap. FIGS. 2E and 2F are top and bottom perspective views of the cap.

FIG. 3A is an exploded perspective view of the receptacle, the cap, and a portion of a receptacle transport mechanism configured to be inserted into the cap.

FIG. 3B is a side cross-sectional view of the cap installed in the receptacle.

FIG. 4A is a perspective view of a multi-well tray for use in an automated reagent-based analyzer.

FIG. 4B is a perspective view of the multi-well tray with a card insert exploded from the multi-well tray.

FIGS. 5A-5E are pictorial diagrams showing details of a card insert. FIGS. 5B-5E show various views of inner surfaces of the wells of the card insert.

FIGS. 6A and 6B are pictorial diagrams showing attachment of the card insert to the base of the multi-well tray.

FIGS. 7A and 7B are cross-sectional views showing a cap and receptacle contained within the wells of the multi-well tray.

FIG. 8 is a pictorial diagram showing a cross-sectional view of an automated pipettor reconstituting a lyophilized reagent contained in a well of a multi-well tray.

FIGS. 9A-9E are pictorial diagrams showing alternative configurations of a multi-well tray and various exemplary embodiments of inner surfaces of the wells therein.

FIGS. 10A and 10B are pictorial diagrams showing perspective views of two cartridges with communicating wells.

FIGS. 11A-11D are pictorial diagrams showing a cartridge rack.

DETAILED DESCRIPTION

The present disclosure relates to a system, apparatus, and method for automated processing of a sample receptacle holder that is adapted for use in an automated instrument capable of performing nucleic acid-based amplification assays. Also provided are methods for conducting automated, random-access temperature cycling processes using the same.

Before the present systems, methods, and apparatuses are described, it is to be understood that this disclosure is not limited to particular methods and experimental conditions described, as such methods and conditions may vary. It is also to be understood that the terminology used herein is for

purposes of describing particular embodiments only, and is not intended to be limiting, since the scope of the present disclosure will be limited only in the appended claims.

As used in this specification and the appended claims, the singular forms “a,” “an,” and “the” include plural references unless the context clearly dictates otherwise. Thus, for example, references to “the method” includes one or more methods, and/or steps of the type described herein which will become apparent to those persons skilled in the art upon reading this disclosure and so forth.

The term “comprising,” which is used interchangeably with “including,” “containing,” “having,” or “characterized by,” is inclusive or open-ended language and does not exclude additional, unrecited elements or method steps. The phrase “consisting of” excludes any element, step, or ingredient not specified in the claim. The phrase “consisting essentially of” limits the scope of a claim to the specified materials or steps and those that do not materially affect the basic and novel characteristics of the disclosed subject matter. The present disclosure contemplates exemplary embodiments of an apparatus and methods of use thereof corresponding to the scope of each of these phrases. Thus, an apparatus or method comprising recited elements or steps contemplates particular embodiments in which the apparatus or method consists essentially of or consists of those elements or steps.

Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this disclosure belongs. Although any methods and materials similar or equivalent to those described herein can be used in the practice or testing disclosed herein, the preferred methods and materials are now described.

As used herein, a “reaction mixture” refers to a volume of fluid comprising one or more of a target-specific reagent, diluent for reconstituting a lyophilized reagent, one or more nucleotides, an enzyme, and a sample containing or suspected of containing a nucleic acid.

As used herein, a “sample” or a “test sample” refers to any substance suspected of containing a target organism or biological molecule, such as nucleic acid. The substance may be, for example, an unprocessed clinical specimen, a buffered medium containing the specimen, a medium containing the specimen and lytic agents for releasing nucleic acid belonging to the target organism, or a medium containing nucleic acid derived from a target organism which has been isolated and/or purified in a reaction receptacle or on a reaction material or device. In some instances, a sample or test sample may comprise a product of a biological specimen, such as an amplified nucleic acid to be detected.

As used herein, the term “biochemical assay” refers to a scientific investigative procedure for qualitatively assessing or quantitatively measuring the presence or amount or the functional activity of a target entity, such as, but not limited to, a biochemical substance, a cell, organic sample, or target nucleic acid sequence. Included in the term “biochemical assay” are nucleic acid amplification and heat denaturation (i.e., melting). Nucleic acid melting typically involves precise warming of a double stranded nucleic acid molecule to a temperature at which the two strands separate or “melt” apart. The melting process typically occurs at a temperature of about 50° C. to about 95° C.

As used herein, the term “lyophilization” refers to a dehydration process that is typically used to preserve a perishable material and/or facilitate transport thereof. Thus, “conditions for lyophilization” refer to subjecting a liquid material and/or a vessel containing the liquid material to

freezing conditions while reducing the surrounding pressure to allow the frozen water within the material to sublime directly from the solid phase to the gas phase. Such freezing conditions may include cooling the material below the lowest temperature at which the solid and liquid phases thereof can coexist (known in the art as the “triple point”). Usually, the freezing temperatures are between –50° C. and –80° C., however, one of skill in the art can determine the appropriate freezing temperature to lyophilize the reagent for use in the automated biochemical assay.

As used herein, the term “reconstituting” refers to the act of returning a lyophilized material to its liquid form. Thus, the term encompasses contacting a fluid, e.g., water or other suitable diluent, with a lyophilized reagent for sufficient time to allow the lyophilized reagent to absorb water, thereby forming a stabilized liquid reagent.

Receptacle & Cap

Accordingly, in an exemplary aspect, there is provided a receptacle **100** to receive and store fluid test samples for subsequent analysis, including analysis with nucleic acid-based assays or immunoassays diagnostic for a particular pathogenic organism. As shown in FIGS. 1A-1D, the receptacle **100** is a single-piece receptacle that includes a body **105** having a generally cylindrical upper portion **110** and a tapered lower portion **120**. Formed on an outer surface of the body **105** is a laterally-extending flange, which, in the illustrated embodiment, comprises an annular ring **125**, which separates the upper and lower portions of the body. The upper portion **110** of the body **105** has an open end **145** through which fluid samples are deposited or removed from the receptacle **100**. The tapered lower portion **120** has a closed end **150** that may either be flat or rounded to provide optical communication with an optical system, for example, one or more optical fibers (not shown) of a biochemical analyzer. In various embodiments, the bottom surface of the closed-ended lower portion may be flat or curved.

The receptacle **100** optionally containing a sample or reaction mixture is configured for insertion into a receptacle holder of an automated biochemical analyzer (not shown). As used herein, a receptacle that is “configured for insertion” refers to the exterior surface of the body **105** of the receptacle **100** being sized and shaped to maximize contact between the receptacle and a receptacle well of a receptacle holder. In certain embodiments, this maximal contact refers to physical contact of the receptacle well with at least a portion of the receptacle **100**. Also in certain embodiments, this maximal contact refers to physical contact of the receptacle well with the tapered lower portion **120** of the receptacle **100**, or at least a portion the tapered lower portion **120** of the receptacle **100**.

Formed in the inner surface **140** of the upper portion **110** of the body **105** is one or more longitudinally oriented grooves **135** to facilitate the venting of air displaced from the interior upon deposit of the test sample or attachment of a cap **200** to the receptacle **100**. In various embodiments, a plurality (i.e., 2, 3, 4, 5, 6, 7, or 8) of longitudinally oriented grooves may be formed in the inner surface **140** of the upper portion **110**, and the grooves **135** may be equally spaced apart from one another around the entire circumference of the body **105**.

Circumscribing the open end **145** of the upper portion **110** of the body **105** is a lip **155** extending radially outward from a central axis thereof. In various embodiments, the lip **155** tapers from the outer-most portion of the radially-extended lip towards the open end of the body, and is configured for securable attachment to a cap **200** (FIGS. 2A-2D).

With reference now to FIGS. 2A-2D, the securable cap 200 includes a lower portion 220 having an outer surface for sealing engagement of the inner surface 140 of the upper portion 110 of the receptacle 100 and an upper portion 210. To ensure an essentially leak-proof seal when the cap 200 is

5 securely attached to the open end 145 of the upper portion 110 of the receptacle 100, the outer surface of the lower portion 220 of the cap 200 is formed with one or more annular ribs 230 for contacting the inner surface 140 of the upper portion 110 thereof. In various embodiments, the

10 lower portion 220 of the cap 200 is formed with 1, 2, or 3 annular ribs 230 for contacting the inner surface 140 of the upper portion 110 of the receptacle 100.

The upper portion 210 of the cap 200 includes an open end 215 for frictional attachment to a portion of a receptacle transport mechanism 300 (FIG. 3A), such as a tubular probe of a pipettor or pick-and-place robot. Guiding insertion of the receptacle transport mechanism 300 into the open end 215 of the upper portion 210 of the cap 200 are one or more linear ribs 260 formed in the inner surface 270 of the upper

20 portion 210. The linear ribs 260 protrude towards an axial center of the cap 200, thereby decreasing the inner fitment diameter of the upper portion 210 of the cap 200. Each linear rib 260 may be beveled (as at 262) at an upper, or proximal, end thereof. These linear ribs 260 can, among other things,

25 enhance the frictional attachment to the receptacle transport mechanism 300. In various embodiments, 1, 2, 3, 4, 5, 6, 7, or 8 linear ribs 260 are formed in the inner surface 270 of the cap 200 and extend at least a portion of the way down the length of the upper portion 210 thereof.

At least one of the linear ribs 260 may be formed with a portion 265 thereof, e.g., at a lower, or distal, end, that gradually tapers radially inward toward a central axis of the upper portion 210 of the cap. In other words, the amount of protrusion of the linear rib 260 may gradually increase in

35 size as the linear rib 260 approaches the bottom 245 of the upper portion 210 of the cap 200. Alternatively, or in addition thereto, in certain embodiments, the linear rib 260 may gradually increase in overall thickness as it approaches

40 the bottom 245 of the upper portion 210 of the cap 200. Thus, gradual increase in thickness or radial geometry is contemplated for the gradual tapering of the one or more linear ribs 260, which serves to stabilize and center the receptacle transport mechanism 300 as it is lowered into the cap 200 for transport.

Corresponding with each linear rib 260 and disposed on the exterior surface of the upper portion 210 of the cap 200 are one or more indentations, or recesses, 234 that extend along at least part of the length thereof. The recesses may be formed in any shape such as, for example, concave, notched,

50 squared, etc. Thus, at least one recess 234 is formed in the exterior surface of the upper portion 210 of the cap 200. In various embodiments, the length of the recess 234 is the same as the length of the corresponding linear rib 260, and each linear rib 260 is positioned such that it lies on the inner

55 surface 270 of the cap 200 in a location that directly opposes the position of the at least one recess 234 formed on the outer surface of the cap 200 in a one-to-one relationship. The coupling of a linear rib 260 with an recess 234 in this manner enhances the predictability of the frictional attachment of the cap 200 to a receptacle transport mechanism 300. In certain

60 embodiments, as the receptacle transport mechanism 300 is lowered into the open end 215 of the cap 200, it contacts the one or more linear ribs 260, thereby pressing against the one or more linear ribs 260. Such pressing against the linear ribs

65 260 causes the cap 200, and recesses 234 to flex and/or expand radially outward with respect to the axial center

thereof to accommodate the receptacle transport mechanism 300 and thus enhance frictional attachment of the cap 300 to the receptacle transport mechanism 300. Accordingly, 1, 2, 3, 4, 5, 6, 7, or 8 recesses 234 may be formed on the exterior surface of the upper portion 210 of the cap 200.

Circumscribing the open end 215 of the upper portion 210 of the cap 200 is a lip 225 extending radially outward from a central axis thereof. In various embodiments, the lip 225 tapers from the open end 215 towards the lower portion 220. Protruding from the taper of the lip 225 are a plurality of protrusions 235. The protrusions 235 may be equally spaced apart from one another and facilitate stacking and/or docking within a well of a multi-well tray 400 (FIG. 4A) for use in an automated biochemical analyzer. In various embodi-

15 ments, 1, 2, 3, 4, 5, 6, 7, or 8 protrusions 235 are formed in the taper of the lip 225.

In various embodiments, the cap 200 is removed from the receptacle transport mechanism 300 by means of a sleeve 306 coaxially disposed over a tip of the receptacle transport mechanism 300 and axially movable with respect to thereto. The sleeve 306 moves axially with respect to the tip toward a distal end of the tip and contacts the lip 225 of the cap, thereby pushing the cap off the tip of the receptacle transport mechanism 300.

Separating the upper portion 210 from the lower portion 220 of the cap 200 is a flange 240 that extends radially away from an axial center thereof. The flange 240 includes a plurality of locking arms 250 that extend from the flange 240 toward the lower portion 220 of the cap 200. The locking

30 arms 250 are shaped for securely engaging the lip 155 of the receptacle 100, and may be disposed to allow for removable attachment of the cap 200 to the receptacle 100, while maintaining a leak-proof seal of the contents thereof. In various embodiments, 1, 2, 3, 4, 5, 6, 7, or 8 locking arms

35 250 are formed in the cap 200.

The flange 240 of the cap 200 additionally serves to form a bottom 245 to separate the upper portion 210 from the lower portion 220, thereby closing the interior of the receptacle 100 from the environment. However, in certain

40 embodiments, the bottom 245 is scored 255 for piercing by a mechanism for collecting and/or adding reagents to the test sample within the receptacle 100. Such piercing avoids the need to remove the secured cap 200 from engagement with the receptacle 100, while providing access to the contents

45 therein.

The receptacle 100 and cap 200 of the present disclosure may be prepared from a number of different polymer and heteropolymer resins, including, but not limited to, polyolefins (e.g., high density polyethylene ("HDPE"), low density polyethylene ("LDPE"), a mixture of HDPE and LDPE, or polypropylene), polystyrene, high impact polystyrene and polycarbonate. An example of an HDPE is sold under the trade name Alathon M5370 and is available from Polymerland of Huntsville, N.C.; an example of an LDPE is sold under the trade name 722 and is available from The Dow Chemical Company of Midland, Mich.; and an example of a polypropylene is sold under the trade name Rexene 13T10ACS279 and is available from the Huntsman Corporation of Salt Lake City, Utah. Although LDPE is a softer, more malleable material than HDPE, the softness of LDPE provides flexibility in the locking arms 250 of the cap 200 to securably engage the lip 155 of the receptacle 100. And, while a cap made of HDPE is more rigid than one made of LDPE, this rigidity tends to make an HDPE cap more difficult to penetrate than one made of LDPE. It should be understood that the receptacle 100 and cap 200 may be comprised of a combination of resins, including, for

example, a mixture of LDPE and HDPE, preferably in a mixture range of about 20% LDPE:80% HDPE to about 50% LDPE:50% HDPE by volume. In addition, the amounts of LDPE and HDPE used to form each of the receptacle **100** and cap **200** may be the same or different. In various embodiments, at least a portion of the cap **200** is formed from an opaque material having low to no autofluorescence characteristics. Also, in certain embodiments, the portion of the cap **200** formed from an opaque material having low to no autofluorescence characteristics is at least the lower portion **220** thereof, including the inner surface **232** of the lower portion **220** of the cap **200**.

Regardless of the type or mixture of resins chosen, the receptacle **100** and cap **200** are preferably injection molded as unitary pieces using procedures well-known to those skilled in the art of injection molding, including a multi-gate process for facilitating uniform resin flow into the receptacle and cap cavities used to form the shapes thereof. Uniform resin flow is desirable for achieving consistency in thickness, which is important for a variety of reasons, including for the penetrable bottom **245** of the cap **200**; to ensure a secure, such as an air-tight, engagement of the cap **200** and receptacle **100**; to ensure a predictable engagement of the cap **200** with the receptacle transport mechanism **300**; and to ensure maximal contact of the receptacle **100** with a receptacle well of a receptacle holder.

Method for Automated Removal of a Cap

In another aspect, disclosed herein is a method for automated removal of a cap from a capped reaction receptacle. The method includes providing a receptacle **100** securably engaging the lip **155** of a receptacle **100**, as shown in FIG. 3B. Thereafter, performing an automated motion of contacting an inner portion **280** of at least one of the plurality of locking arms **250** of the cap **200** with a raised annular ridge defined around a receptacle slot. The receptacle slot may be provided in a receptacle holder of an automated biochemical analyzer, alternatively the receptacle slot may be provided in a card or cartridge intended to be removed from an automated biochemical analyzer. The contacting urges the locking arms **250** away from the lip **155** of the receptacle **100**, thereby disengaging the cap **200** from the receptacle **100**. While the cap **200** is being disengaged from the receptacle **100**, an automated motion is performed to lift the cap **200** away from the receptacle **100**, thereby removing the cap **200** from the receptacle **100**. In various embodiments, the automated motion is performed by a receptacle transport mechanism **300** (FIG. 3A), such as, for example, a pipettor or pick-and-place robot.

Multi-Well Tray

In another aspect, disclosed herein is a multi-well tray for use in an automated process. Referring now to FIGS. 4A and 4B, a multi-well tray **400**, as shown, includes a base **410** having disposed in a top surface **417** thereof, a plurality of wells **415**, **416**. A card insert **420** (see also FIG. 5A) configured for removable attachment to the base **410**, is attached thereto. When the card insert **420** is attached to the base **410**, a top surface **425** of the card insert **420** is substantially parallel to and flush with the top surface **417** of the base **410**.

Disposed in the top surface **425** of the card insert **420**, is a plurality of wells **430**, each configured for containing one or more reagents used for performing a biochemical analysis. Each well **430** of the card insert **420** corresponds to at least one of the wells **415** disposed in the base **410**. Thus, in certain embodiments, after attachment of the card insert **420** to the base **410**, the multi-well tray **400** takes on the uniform appearance of, for example, a multi-well plate. The wells

415, **416** disposed in the base **410** may be arranged in pairs, where each pair corresponds to a single well **430** of the card insert **420**. As such, the multi-well tray **400** may include a plurality of sets **435** of wells, where each set **435** includes a first well **415** and a second well **416**, which are disposed in the top surface **417** of the base **410**, and a third well **430** disposed in the top surface **425** of the card insert **420**. The wells of each set **435** of wells may be in alignment with each other, thereby resulting in a multi-well tray **400** that is spatially indexed such that an automated receptacle transport mechanism **300** can accurately identify and/or access any of the plurality of wells when the multi-well tray **400** is placed or inserted into an automated system. In certain embodiments, the multi-well tray **400** includes ten sets **435** of wells. As such, the base **410** is formed with ten pairs of first and second wells **415**, **416** and the card insert **420** is formed with ten third wells **430**, where each of the first, second, and third wells of the set **435** are arranged in alignment with each other. Thus, the multi-well tray **400** may include ten receptacles **100** and ten caps **200** provided therein for used in an automated biochemical analyzer.

The first and second wells **415**, **416** of the set **435** are configured to receive a cap **200** and a receptacle **100**, respectively. While it should be understood that the terms “first” and “second” as used to distinguish the wells formed in the base **410**, for descriptive purposes, the “first well”, or cap well, **415** will refer to a well configured to receive a receptacle cap **200**.

With reference now to FIGS. 7A and 7B, the first well **415** of the base **410** is defined by a cylindrical wall **470** and a bottom wall **472**. Formed in the center of the bottom surface **472** is a protrusion **475** extending upwardly toward the top surface **417** of the base **410**. The protrusion **475** is sized and shaped for engagement, optionally frictional engagement, with a hollow portion **232** of the lower portion **220** of the cap **200**. Alternatively, or in addition thereto, the cylindrical wall **470** may be formed with a plurality of tabs **477** protruding towards the axial center of the first well **415**. Such tabs **477** are configured for securely engaging at least a portion of the cap **200** to prevent the cap **200** from dislodging from the multi-well tray if, for example, the multi-well tray is inverted or shaken. In certain embodiments, 2, 3, 4, 5, 6, 7, or 8 tabs **477** are formed in the cylindrical wall **470** of the first well. Each of tabs **477** may securely engage the top surface of the flange **240** of the cap **200**.

Similarly, the “second well”, or receptacle well, **416** will refer to a well configured to receive a receptacle **100**. As shown in FIGS. 7A and 7B, the second well **416** is defined by a cylindrical wall **480** and a bottom wall **482**. Formed in the center of the bottom wall **482** is a through-hole **485** base. The through-hole **485** is sized and shaped in conformance with the outer surface of the lower portion **120** of the receptacle **100**. As such, the through-hole may be tapered at an angle corresponding to the angle of the lower portion **120**. As shown in FIG. 7A, the bottom wall **482** of the second well **416** forms an annular ledge at the perimeter of the through-hole for engaging the ring **125** of the receptacle **100**. Alternatively, or in addition thereto, the cylindrical wall **480** may be formed with a plurality of legs **487** protruding towards the axial center of the second well **416**. Such legs **487** are configured for securely engaging at least a portion of the receptacle **100** to prevent the receptacle **100** from dislodging from the multi-well tray if, for example, the multi-well tray is inverted or shaken. In certain embodiments, 2, 3, 4, 5, 6, 7, or 8 legs **487** are formed in the

cylindrical wall **480** of the second well **416**. Each of the legs **487** may securely engage the top surface of the ring **125** of the receptacle **100**.

As discussed above, the third well, or reagent well, **430** of each set **435** contains one or more reagents for performing a biochemical analysis. In certain embodiments, the third well **430** of the set **435** contains a lyophilized reagent **495** (FIGS. **8** and **9C**), and may be sealed with a frangible seal **440** (FIG. **8**). For example, each well **430** of the card insert **420** may be sealed with a metallic foil (or foil laminate) using, for example, a pressure sensitive adhesive which is applied to the top surface **425** thereof. The frangible seal **440** may further include a plastic liner, such as a thin veneer of HDPE applied to one or both surfaces thereof, which promotes attachment of the frangible seal **440** to the top surface **425** when a heat sealer is used. Heat sealing is a well-known process and involves the generation of heat and the application of pressure to the surface being sealed, which, in this case, is the top surface **425** or a raised lip **427** (see FIGS. **4A**, **5A**) surrounding the well **430** of the card insert **420**. Alternatively, any known ultrasonic welding procedure using either high frequency or high amplitude sound waves may also be used to affix the frangible seal **440** to the card insert **420**. The card insert **420** may include a plurality of frangible seals **440**, each of which sealing a single well **430**, or may include a single sheet that seals all wells **430** disposed therein.

A single lyophilized reagent **495** may be provided in each well **430** of the card insert **420**. However, in certain embodiments, one or more wells **430** of the card insert **420** may contain a different lyophilized reagent **495**, such as a different target-specific reagent. Thus, each well **430** of the card insert **420** may contain a distinct lyophilized reagent **495** compared with the lyophilized reagent **495** contained in at least one other of the plurality of wells **430** therein. In various embodiments, the card insert **420** does not contain non-reagent consumables. As used herein, a "reagent" refers to a substance or mixture for use in a chemical or biochemical reaction. Thus, a "non-reagent consumable" refers to a component that is used by an automated biochemical assay, but is not a reagent. Exemplary non-reagent consumables include, but are not limited to, contamination limiting elements, receptacles **100**, and caps **200**.

Referring now to FIGS. **5A-5E**, each well **430** of the card insert **420** is defined by a side wall, or well wall, **450** and a bottom, or bottom wall or bottom wall portion, **455**. In various embodiments, the side wall **450** tapers from an upper end thereof to the bottom **455**, and may therefore be referred to as a conical wall. As shown in FIGS. **5B-5E**, the bottom **455** of each well may be formed with one or more features to facilitate deposit of and collection of fluid from the well. Such features include, but are not limited to a concave groove **457**, **460** (FIGS. **5C**, **5D**, **5E**), convex ridge (not shown), or a set of grooves positioned in a crisscross pattern (not shown). The features may be located at the axial center of the well **430**, as shown in FIG. **5C**, or may be off-set to a side thereof, as shown in FIG. **5B**. Alternatively, or in addition thereto, the side wall **450** may be formed with a plurality of bumps **462** on the surface thereof for additional facilitation of depositing and/or collecting fluids contained therein. The side wall **450** of each well **430** of the card insert **420** may further be formed with a plurality of rigid guides **465** that protrude radially from the side wall **450** towards the axial center of the well **430**. Such rigid guides **465** guide a pipette tip **310** (FIGS. **8** and **9C**) mounted on an automated pipettor toward the axial center of the well **430** as the tip is lowered therein, and may further serve to retain the

lyophilized reagent at, or adjacent to, the bottom **455** of the well **430**. In various embodiments, each well **430** may be independently formed with 2, 3, 4, 5, 6, 7, or 8 rigid guides **465** protruding from the respective tapered side wall **450**.

The features formed at the bottom **455** of the well **430**, such as grooves, ridges, and/or bumps, interfere with the end of a pipette tip inserted into the well **430** and thus prevent the end of the pipette tip from making sealing contact with the bottom **455** so as to prevent a negative pressure build up within the pipette tip during a fluid aspiration. For example, as shown in FIG. **5E**, a feature formed on the bottom **455** of well **430**, such as groove **457**, provides a clearance that prevents a pipette tip **310** from making sealing contact with the bottom **455** of the well **430**.

Additionally, in certain embodiments, the side wall **450** of each well **430** of the card insert **420** may include one or more retention features (FIGS. **8**, and **9C-9D**) that can be used to retain the lyophilized reagent **495** at, or adjacent to, the bottom **455** of the well **430** when, for example a diluent is deposited into the well **430** for reconstitution of a lyophilized reagent. In FIGS. **9C** and **9D**, the retention features are shown within a well **715** of an alternative embodiment of a multi-well tray **700** described below. In various embodiments, the retention feature may include one or more protrusions or an annular ridge **800** formed above the area to be occupied by the lyophilized reagent **495**, and extending toward the axial center of the well **430**. Such protrusions or annular ridge **800** narrow the opening of the side wall **450** such that the opening is smaller than the diameter of the lyophilized reagent **495**.

As shown in FIG. **9E**, the annular ridge **800** may be formed by inserting one or more heat stakes **880** into the wells **430**, such that the side wall **450** is deformed, thereby forming an annular ridge **800** therein. The one or more heat stakes **880** may be attached to an apparatus **890**, which may heat the one or more heat stakes **880**, thereby providing sufficient heat to deform the side wall **450** at a point along the taper where the diameter thereof equals that of the diameter of the heat stake.

In various embodiments, the retention feature may also take the form of one or more solid extensions **810** formed over the area to be occupied by the lyophilized reagent **495**. Such extensions **810** connect opposing areas of the side wall **450**, thereby retaining the lyophilized reagent **495** at, or adjacent to, the bottom **455** of the well **430**. In various embodiments, the side wall **450** may be formed to mimic the thread of a coarse screw as shown at **820**. Such a threaded feature **820** may be formed during injection molding of the well **430**, or may be formed by applying a heated screw portion to the well wall, thereby forming a spiral channel along a length thereof, through which fluid may run to the bottom **455** using gravitational force. In various embodiments, the retention feature may be provided in the form of a tapered ring insert **830** that is fixedly attached to the side wall **450** either before or after deposit of the lyophilized reagent **495**. The tapered ring **830** may be formed of plastic and include an exterior surface that tapers in accordance with the taper of the side wall **450**. When present, the tapered ring **830** narrows the opening of the well **430** such that the lyophilized reagent **495** is retained at, or adjacent to, the bottom **455** of the well **430**.

As shown in FIG. **9D**, the inner surface of a well wall may be substantially vertical as at **840**, while an exterior surface of the well retains its tapered shape. In certain embodiments, the inner surface of the well wall may be substantially vertical as at **840**, while the exterior surface of the well is also substantially vertical (not shown). When present, the

vertical wall **840** allows the entirety of a liquid reagent to be lyophilized to settle at the bottom **455** of the well, thereby ensuring reagent uniformity upon lyophilization.

In various embodiments, as also shown in FIG. **9D**, the retention feature may be in the form of a capillary insert **850** that is fixedly attached to the well wall. The capillary insert **850** may be formed of plastic and include an exterior surface that tapers in accordance with the taper of the well wall. In an exemplary embodiment, the well and capillary insert **850** may be formed as a single unit. The capillary insert **850** may not extend completely to the bottom of the well, thereby defining a chamber **856** below a bottom end of the capillary insert **850**. The inner surface of the capillary insert **850** may include substantially vertical walls forming a capillary channel **852** extending from an upper end of the insert to a lower end of the insert through which fluid will flow via capillary attraction, and within which the fluid will be retained as a result of the combination of surface tension and adhesive forces between the fluid and the walls of the capillary channel. The capillary insert **850** may further include an open upper end **854** that tapers from a top surface of the insert **850** to the channel **852**. Thus, when a capillary insert **850** is present in a well and a liquid reagent to be lyophilized is deposit therein, the reagent remains held within the capillary channel thereof, and is prevented from flowing into the bottom of the well. After lyophilizing the liquid reagent, the lyophilized reagent **495** remains lodged within the channel **852** of the capillary insert **850**. Deposit of a diluent for reconstitution of the lyophilized reagent **495** is accomplished by addition of the diluent to the tapered open upper end **854** of the capillary insert **850**. The diluent then flows within the capillary channel **852** via capillary attraction, and is retained therein as a result of the combination of surface tension and adhesive forces between the diluent and the walls of the capillary channel **852**. Once reconstituted, the reagent may be collected by insertion of the pipette tip **310** into the tapered open upper end **854** of the capillary insert **850** and withdrawing the liquid reagent therefrom. The entirety of the liquid reagent may therefore be collected at the tapered open upper end **854** of the capillary insert **850** since the liquid will travel upwards due to capillary attraction within the channel **852** of the capillary insert **850**.

Alternatively, or in addition thereto, the bottom **455** of the well can be formed to include a roughened surface, thereby providing sufficient surface area to which the lyophilized reagent **495** will adhere upon formation thereof. Alternatively, or in addition thereto, the lyophilized reagent **495** will adhere to, or adjacent to, the bottom **455** of the well **430** through a static electrical attractive force created on the well wall **450** and/or bottom **455** of the well **430**. In such embodiments, the inner surface of the well **430** is provided with an electrical charge such that the lyophilized reagent **495** adheres thereto.

In various embodiments, the retention feature may take the form of an insert through which the pipette tip **310** may be inserted. For example, as shown in FIG. **9D** the retention feature may be a fingered collar **860** that is fixedly attached to a top portion of the well. The fingered collar **860** may be formed of plastic and include an exterior surface that tapers in accordance with the taper of the well wall. The fingered collar **860** may include one or more (i.e., 1, 2, 3, 4, 5, 6, 7, or 8) fingers extending from a bottom surface thereof, and protruding along a radius of curvature toward the axial center of the well. The one or more fingers may be flexible such that contact with a pipette tip **310** inserted therein causes the fingers to flex toward the well wall, thereby allowing the pipette tip **310** to pass there through. Upon

withdrawal of the pipette tip **310**, the fingers return to a rest position such that the fingers protrude along the radius of curvature toward the axial center of the well.

In an alternative embodiment, the retention feature may take the form of a collar **870** that resembles the fingered collar **860**, but does not include the one or more fingers protruding therefrom. Such a collar **870** may be fixedly attached to a top or center portion of the well wall, and may be formed of plastic and include an exterior surface that tapers in conformance with the taper of the well wall. When present, the collar **870** narrows the well wall to retain the lyophilized reagent **495** at, or adjacent to, the bottom **455** of the well, while allowing the pipette tip **310** to pass there through.

Each of the base **410** and card insert **420** may be independently constructed of an injection molded plastic, such as the plastics described above. The plastic used to form the base **410** may be the same or different from the plastic used to form the card insert **420**. For example, the card insert **420** may be formed from a plastic having lower permeability to air and/or moisture than the plastic forming the base **410**. Such plastics may be more expensive than their conventional counterparts but, due to the decreased air and moisture permeability, provide for enhanced stability of reagents, such as lyophilized reagents contained in the wells thereof. Any exterior surface of the base **410** or card insert **420** may further include one or more identifying labels **490**, such as a barcode, 2D barcode, quick response (QR) code, radio frequency identification (RFID), or other human or machine readable indicia, disposed thereon. The information carried on such label may include identifying information regarding the multi-well tray **400** and/or card insert **420**, including information regarding the reagents contained therein, such as lot number, serial number, assay type, expiration date, etc. In various embodiments, the base **410** may include one or more barcodes and/or QR codes on a side surface thereof for identifying assays to be performed by the automated biochemical analyzer.

As shown in FIG. **4B**, the base **410** may be formed with one or more locking arms **445** positioned for locking engagement with the card insert **420**. Additionally, the card insert **420** may be formed with one or more corresponding lock-holes **447** for receiving the locking arms **445** of the base **410**. Once secured into the base **410** by the locking arms **445** and/or the lock-holes **447**, the card insert **420** is prevented from detachment therefrom. However, in certain embodiments, locking arms **445** may be moved out of locking engagement with the card insert **420** to release the card insert **420** from the base **410**. Such releasable engagement provides for reuse of the base **410**, if necessary, and/or replacement of a card insert **420** should the need arise.

As shown in FIG. **6A**, base **410** may be further formed with one or more locking fingers **422** disposed on a side surface thereof. The locking fingers **422** are configured for releasably engaging a rack to secure the base **410** to the rack for use in automated processing. In various embodiments, the base **410** may further include a release **437** for urging the locking fingers **422** away from the engaging surface of the rack to facilitate removal therefrom.

As shown in FIG. **6B**, the card insert **420** may be secured to the base **410** by means of locking features **424** disposed along opposed sides of the card insert **420** that are configured for locking engagement with cooperating ledges **412** formed in the base **410**.

FIGS. **9A-9E** show an alternative embodiment of a multi-well tray **700**. Referring now to FIGS. **9A** and **9B**, the multi-well tray **700** includes a base **710** having disposed in

a top surface 717 thereof, a plurality of wells 715. The base 710 also includes an arm 720 for engagement by a transport mechanism, such as a rotary distributor (not shown) for transport within an automated biochemical analyzer. As shown in FIG. 9B, the bottom surface 730 of the base 710 is formed with one or more snap fingers 735, which define a slot 740 into which an element (not shown) of the biochemical analyzer is inserted. Thus, snap fingers 735 grasp the element (not shown) of the biochemical analyzer, thereby forming a secure attachment thereto.

The base 710 of the multi-well tray 700 is defined by a first end 701 and a second end 702 with the length of the base 710 defined by a longitudinal extent between the first end 701 and the second end 702 being longer than the width of the base. The base further includes opposed generally parallel side walls 703, 704 extending from the first end 701 to the second end 702 between the top surface 717 and the bottom surface 730.

A plurality of wells 721 depend from the top surface 717, as shown in FIG. 9B, and include openings 715 at the top surface 717. In the illustrated embodiment, the wells are arranged in parallel rows 716, 718 extending longitudinally of the base 710. As shown in FIG. 9B, ribs 723 may extend from a portion of an outer surface of well 721, for example between the well 721 and an inner surface of a sidewall 703 or 704.

The arm 720 is defined by a bridge section 706 extending the top surface 717 beyond a first end wall 705. A post 707 projects from the end of the bridge 706 in a direction generally transverse to the plane of the top surface 717, downward in the illustrated embodiment, with a gap 713 between the post 707 and the first end wall 705.

Referring to FIG. 9B, the snap fingers 735 are defined by opposed tabs 736, 737 oriented in a direction extending from the second end 702 toward the first end 701 of the base 710. The slot 740 is defined between the opposed tabs 736, 737. In the illustrated embodiment, each opposed tab 736, 737 includes a flared end 738, 739, respectively.

As shown in FIG. 9B, the outer periphery of the base 710 is defined by a perimeter wall 712 that defines the side walls 703, 704, the first end wall 705, and the opposed tab 736, 737 extending inwardly from a second end wall 711.

In this alternative embodiment, all of the wells 715 are configured to contain one or more reagents used for performing automated biochemical analysis. Similar to the wells 430 of the multi-well tray insert 420, each well 715 is defined by an inner side wall 750 and a bottom 755. In various embodiments, the side wall 750 tapers from a top portion of the well 715 to the bottom 755, as shown in FIG. 9C.

As discussed above, the bottom 755 of each well 715 may be formed with one or more features to facilitate deposit of and collection of fluid from the well. Such features include, but not limited to a concave groove 457, 460 (FIGS. 5B-5D), a convex ridge (not shown), or a set of grooves positioned in a crisscross pattern (not shown). The features may be located at the axial center of the well 715, as shown in FIG. 5C, or may be off-set to a side thereof, as shown in FIG. 5B. Alternatively, or in addition thereto, the inner wall 750 may be formed with a plurality of bumps 462 (FIGS. 5B-5D) on the surface thereof for additional facilitation of depositing and/or collecting fluids contained therein. The inner wall 750 of each well 715 of the card 700 may further be formed with a plurality of rigid guides 465 (FIG. 5B) that protrude radially from the inner wall 750 towards the axial center of the well 715. Such rigid guides 465 guide the tip 310 (FIGS. 8 and 9C) mounted on an automated pipettor toward the

axial center of the well 715 as the tip is lowered therein, and may further serve to retain the lyophilized reagent 495 at, or adjacent to, the bottom 755 of the well 715. In various embodiments, each well 715 may be independently formed with 2, 3, 4, 5, 6, 7, or 8 rigid guides protruding from the respective tapered well wall 750.

Additionally, in certain embodiments, the inner well walls 750 of each well 715 of the card 700 may include one or more retention features 800, 810, 820, 830, 840, 850, 860, 870 (FIGS. 8 and 9C-9D), as described above, configured to retain the lyophilized reagent 495 at, or adjacent to, the bottom 755 of the well 715 when, for example a diluent is deposited into the well 715 for reconstitution. In various embodiments, the retention features may include an annular ridge 800 formed above the area to be occupied by the lyophilized reagent 495, and extending toward the axial center of the well 715. In various embodiments, the retention features may also take the form of one or more solid extensions 810 formed over the area to be occupied by the lyophilized reagent 495. Such extensions 810 connect opposing areas of the well wall 750, thereby retaining the lyophilized reagent 495 at, or adjacent to, the bottom 755 of the well 715. In various embodiments, the well 715 may include any of the various inserts 830, 850, 860, or 870, as discussed above. Alternatively, or in addition thereto, the well wall 750 may be a vertical wall 840 or may be formed to include a screw thread (i.e., a spiral channel) 820. Alternatively, or in addition thereto, the bottom 755 of the well can be formed to include a rough surface, thereby providing sufficient surface area to which the lyophilized reagent 495 will adhere upon formation thereof. Alternatively, or in addition thereto, the lyophilized reagent 495 will adhere to the bottom 755 of the well 715 through a static electrical attractive force created on the well wall 750 and/or bottom 755 of the well 715.

Cartridge with Communicating Wells

In another aspect of the disclosure, a cartridge 500 with communicating wells for use in an automated process is shown in FIGS. 10A and 10B, which depict different alternative cartridge embodiments. The cartridge 500 includes a casing 510 having a top surface 517, a fluid chamber 520, and a fluid reservoir 515. In various embodiment, the fluid chamber 520 and the fluid reservoir 515 comprise wells open at the top surface 517. In various embodiments, as reflected in the drawings, the fluid chamber 520 has a smaller volumetric capacity than the fluid reservoir 515. As further reflected in the drawings, the perimeter of the open end of the fluid chamber 520 may be smaller than the perimeter of the open end of the fluid reservoir 515, and thus the exposed surface of a fluid in the fluid chamber 520 would be smaller than the exposed surface of a fluid in the fluid reservoir 515.

The fluid chamber 520 and the fluid reservoir 515 may contain the same liquid, such as a diluent or a reconstitution solution for reconstituting the lyophilized reagent (e.g., lyophilized reagent 495).

The cartridge 500 may be provided with one or more fluid connections between the fluid chamber 520 and the fluid reservoir 515. Thus, in various embodiments, one or more openings 525 and/or 527 between the fluid chamber 520 and the fluid reservoir 515 may include one or more channels between the fluid reservoir 515 and the fluid chamber 520 to provide a path through which a liquid or gas may flow between the fluid chamber 520 and the fluid reservoir 515. An opening, such as opening 527, between the fluid chamber

520 and the fluid reservoir **515** may be provided by a slot or hole formed in a wall separating the fluid chamber **520** and the fluid reservoir **515**.

In various embodiments, a first opening **525** is provided proximate a lower portion of the fluid chamber **520** and the fluid reservoir **515** (e.g., at a base of the casing **510**) for fluid communication between the fluid chamber **520** and the fluid reservoir **515**, and a second opening **527** is provided proximate an upper end (i.e., near the open ends) of the fluid chamber **520** and the fluid reservoir **515** for fluid communication between the fluid chamber **520** and the fluid reservoir **515**.

As shown in FIG. 10A, the cartridge **500** may also include a second fluid reservoir **530** disposed within the casing and adjacent to the fluid chamber **520**. The second reservoir **530** can be utilized to store the same or a different liquid than is stored in reservoir **515**. In certain embodiments the second reservoir **530** is not in fluid communication with the fluid reservoir **515** or the fluid chamber **520**. In certain embodiments the fluid reservoir **515** and the fluid chamber **520** contain a reconstitution solution, and the second reservoir **530** contains oil.

In various embodiments, each of the fluid chamber **520**, fluid reservoir **515**, and second reservoir **530** may be sealed with a seal (not shown), such as a metallic foil (or foil laminate). A seal over the fluid reservoir **515**, the fluid chamber **520**, and/or the second reservoir **530** may be provided to prevent spillage of fluid contents in case cartridge **500** is tipped, dropped, shaken, or inverted. The seal also prevents or retards evaporation of the fluid contents of the sealed reservoir or chamber by preventing or limiting exposure to ambient atmosphere. The seal may further include a plastic liner, such as a thin veneer of HDPE applied to one or both surfaces thereof. The seal may be secured using, for example, a pressure sensitive adhesive or heat seal securing the foil to the top surface **517** securing the seal about the perimeter of the opening of each reservoir or chamber. A plastic liner, such as a thin veneer of HDPE applied to one or both surfaces of the seal, promotes attachment of the frangible seal to the top surface **517** when a heat sealer is used. The one or more openings (**525**, **527**) may also be sealed with a frangible seal to prevent exposure to the ambient atmosphere.

The fluid reservoir **515** and the fluid chamber **520** and any connecting opening(s) are configured so that as fluid is removed from the fluid chamber **520**, replacement fluid flows into the fluid chamber **520** from the fluid reservoir **515** (e.g., through an opening **525** provided proximate a lower portion of the fluid chamber **520** and fluid reservoir **515**). Moreover, if the fluid reservoir is sealed, one or more conduits may be provided to permit air to flow into the fluid reservoir **515** (e.g., through an opening **527** provided proximate an upper portion of the fluid chamber **520** and fluid reservoir **515**) as fluid is drawn out of the fluid reservoir **515** to thereby allow the pressure in the reservoir to equilibrate.

The chamber **520** is may be sealed with a frangible seal that is puncturable by a pipette tip. The entire volume of fluid in the fluid chamber **520** and the fluid reservoir **515** is accessible to a fluid transfer apparatus, but a relatively small surface area of that fluid—e.g., corresponding to the width of the chamber **520** or to the size of a puncture hole formed in a seal over the chamber **520**—is exposed to air. Thus, the configuration of the cartridge **500** retards evaporation of fluids contained therein.

An amount of liquid, such as reconstitution solution, may be removed from the fluid chamber **520** within an automated

pipettor and transferred to a well (e.g., well **430** or **715**) to reconstitute a lyophilized reagent (e.g., lyophilized reagent **495**), as described below.

The cartridge **500** may be constructed of an injection molded plastic, such as the plastics described above. As discussed above, the plastic used to form the cartridge **500** may be one having low permeability to air and/or moisture.

Any exterior surface of the cartridge **500** may further include one or more identifying labels, such as a barcode, 2D barcode, quick response (QR) code, radio frequency identification (RFID), or other human or machine readable indicia, disposed thereon. The information carried on such label may include identifying information regarding the cartridge **500**, including information regarding the liquids/reagents contained therein, such as lot number, serial number, assay type, expiration date, etc.

Cartridge Rack

In another aspect, disclosed herein is a cartridge rack for use in an automated process. With reference now to FIGS. 11A-11D, the cartridge rack **600** includes a chassis **610** and a handle **620**. A top surface **615** of the chassis **610** is configured for releasable attachment of one or more multi-well trays **400** thereto, and therefore may include a plurality of locking members **625** for releasably engaging the locking fingers **422** of the multi-well tray **400** (see FIG. 6A). While the FIG. 11B shows that two locking members **625** are provided for each multi-well tray **400**, it should be understood that the number of locking members **625** provided for each multi-well tray **400** will correspond with the number of locking fingers **422** provided on the multi-well tray **400** to be attached thereto.

Disposed on a surface of the chassis **610** is a plurality of identifying labels such as machine readable indicia **630**, such as a barcode, 2D barcode, quick response (QR) code, radio frequency identification (RFID), or other human or machine readable indicia, disposed thereon. The information carried on such label may include identifying information regarding the cartridge rack **600**, multi-well tray(s) **400** attached thereto, and/or the card insert(s) **420** attached to the multi-well tray(s) **400**, and/or the multi-well tray **400** position on the rack. The machine readable indicia **630** may be readable through a direct contact connection, a wired connection, or a wireless connection between the cartridge rack **600** on the automated biochemical analyzer.

In various embodiments, the chassis **610** is configured for releasable attachment of two or more multi-well trays **400** thereto, and may further be configured for releasable attachment to a cartridge with communicating wells **500**. Thus, in an exemplary embodiment, five multi-well receptacles **400** and one cartridge **500** may be releasably attached to the chassis **610** for use in an automated biochemical analyzer. However, 2, 3, 4, 5, 6, 7, or 8 multi-well trays **400**, and/or 1, 2, 3, or 4 cartridges **500** may be attached to the chassis **610**.

System for Automated Reagent-Based Assay

In another aspect, the present disclosure provides a system for an automated reagent-based assay. The system includes a multi-well tray **400** that includes a plurality of wells **430**, a cartridge with communicating wells **500**, and an automated pipettor positioned on a robot arm (not shown). The system includes a housing within which each of the components are located. Each well **430** of the multi-well tray **400** shown and discussed above contains a lyophilized reagent **495** and is arranged in alignment with each other. The wells **430** of the multi-well tray **400** may be sealed with a frangible seal. The multi-well tray **400** may further include a plurality of additional wells **415**, **416** provided for receiv-

ing a receptacle **100** and a cap **200**. When present, the additional wells are positioned in aligned pairs, and the pairs are positioned in alignment with at least one well **430** containing a reagent, such as a lyophilized reagent **495**. Thus, the multi-well tray **400** may contain a plurality of sets **435** of wells, where a first well **415** contains a cap **200**, a second well **416** contains a receptacle **100**, and a third well contains a reagent such as a lyophilized reagent **495**.

The cartridge with communicating wells **500** includes a casing **510** having a top surface **517**, a fluid chamber **520**. A first opening **527** is provided in the top surface of the casing having at least one side wall surface extending to, or optionally forming at least a portion of, the fluid chamber. A fluid reservoir **515** is disposed within the casing and in fluid communication with the fluid chamber. In certain embodiments, the cartridge **500** will also include a second reservoir **530** that is disposed within the casing **510** and adjacent to the fluid chamber **520**.

The automated pipettor is positioned on a robot arm contained in an automated biochemical analyzer. The automated pipettor is adapted to execute a retrieval and dispense protocol for conducting biochemical reactions. The retrieval and dispense protocol may be performed by a controller (not shown) electrically connected to the robot arm and/or the automated pipettor to retrieve a portion of the reagent from the cartridge **500** and dispense the portion of the reagent into one or more wells of the multi-well tray **400**, **700** or into one or more receptacles. The retrieval and dispense protocol may then be repeated for automated dispensing of the reagent into each of remaining wells of the multi-well tray **400**.

In one exemplary embodiment, the automated pipettor will receive a command to perform automated actions required for performing an automated reagent-based assay. The automated pipettor is then moved by the robot arm to a position over an unused pipette tip **310** and is lowered to enable frictional attachment thereto. Once the automated pipettor, having the pipette tip **310** attached thereto, is raised such that the pipette tip **310** is not obstructed by additional unused tips and/or other components within the automated biochemical analyzer, the robot arm moves the automated pipettor into a designated position over a cartridge **500**. The automated pipettor is thereafter lowered into the fluid chamber of the cartridge **500**. If present, a frangible seal covering the fluid chamber is punctured by the pipette tip **310**. The automated pipettor then withdraws a predetermined amount of diluent and is raised such that the pipette tip **310** is unobstructed by the cartridge **500** and/or other components within the automated biochemical analyzer.

The robot arm then moves the automated pipettor into a designated position over a spatially indexed multi-well tray **400** and then lowers the pipettor such that the pipette tip **310** punctures a frangible seal **440** (if present) covering a well **430** disposed in the card insert **420** attached to the base **410** of the multi-well tray **400**. The diluent is then deposited into the well **430** containing a lyophilized reagent **495** used in the reagent-based assay. Optionally, the automated pipettor will repeatedly aspirate and then dispense the liquid contained in the well **430** to allow sufficient time and fluidic pressure required to reconstitute the lyophilized reagent **495**. The automated pipettor thereafter collects the reconstituted reagent and withdraws the pipette tip **310** from the well **430** of the multi-well tray **400** such that the pipette tip **310** is unobstructed by the well **430** and/or other components within the automated biochemical analyzer. The robot arm then moves the automated pipettor into a second designated position over the spatially indexed multi-well tray **400**. The second position is selected in accordance with the set **435** of

wells to which the well **430** of the card insert belongs. The automated pipettor is then lowered into a well **416** containing a receptacle **100**, which may or may not contain a sample undergoing analysis. Optionally, when a sample undergoing analysis is present in the receptacle **100**, the automated pipettor will repeatedly aspirate and then dispense the liquid contained in the receptacle **100** to allow sufficient time and fluidic pressure required to mix the contents of the receptacle **100** within the well **416**, thereby creating a reaction mixture.

After optional mixing, the automated pipettor withdraws the pipette tip **310** from the well **416**, but leaves the reaction mixture within the receptacle **100**. The robot arm then moves the automated pipettor to a location over a waste receptacle and ejects the pipette tip **310**. After ejection, the robot arm moves the automated pipettor to a third designated position over the spatially indexed multi-well tray **400**. The third position is selected in accordance with the set **435** of wells to which the first and second wells belong. The automated pipettor is then lowered into the third well **415** containing a cap **200** to enable frictional attachment thereto. Once the automated pipettor having the cap **200** attached thereto is raised such that the cap **200** is not obstructed the well **415** and/or other components within the automated biochemical analyzer, the robot arm moves the automated pipettor into the second designated position over the well **416** containing the receptacle **100** containing the reaction mixture. The automated pipettor is then lowered such that the cap **200** is securably attached to the receptacle **100** as described above. As the automated pipettor withdraws from the well **416**, the capped receptacle attached thereto is withdrawn from the well **416** of the multi-well tray **400** for transport to, for example, a thermocycler for automated incubation.

In another exemplary embodiment, the automated pipettor will receive a command to perform automated actions required for performing an automated reagent-based assay. The automated pipettor is then moved by the robot arm to a position over an unused pipette tip **310**, and is lowered to enable frictional attachment thereto. Simultaneously, prior to, or after such movement, a transport mechanism, such as a rotary distributor (not shown) within the biochemical analyzer attaches to an arm **720** of a multi-well tray **700** and transports the multi-well tray **700** to a predetermined position for use in the analysis.

Once the automated pipettor, having the pipette tip **310** attached thereto, is raised such that the pipette tip **310** is not obstructed by additional unused tips and/or other components within the automated biochemical analyzer, the robot arm moves the automated pipettor into a designated position over a cartridge **500**. The automated pipettor is thereafter lowered into the oil chamber **530** of the cartridge **500**. If present, a frangible seal covering the oil chamber **530** is punctured by the pipette tip **310**. The automated pipettor then withdraws a predetermined amount of oil and is raised such that the pipette tip **310** is unobstructed by the cartridge **500** and/or other components within the automated biochemical analyzer.

The robot arm then moves the automated pipettor into a designated position over a spatially indexed multi-well tray **400** and/or over a receptacle **100**, and the pipettor is lowered such that the pipette tip **310** enters the open end **145** thereof. The oil is then dispensed into the receptacle **100**. Optionally, the procedure of withdrawing oil from the oil chamber **530** of the cartridge **500** is repeated one or more times, depending on the number of reactions to be performed.

Thereafter, the automated pipettor withdraws the pipette tip **310** from the receptacle **100**, and the robot arm moves the automated pipettor to a location over a waste receptacle and ejects the pipette tip **310**. After ejection, the robot arm moves the automated pipettor to a position over a second unused pipette tip **310** and lowers the pipettor to enable frictional attachment thereto. Once the automated pipettor, having the second pipette tip **310** attached thereto, is raised such that the pipette tip **310** is not obstructed by additional unused tips and/or other components within the automated biochemical analyzer, the robot arm moves the automated pipettor into a designated position over a second receptacle **100** having therein a sample for analysis, and is lowered such that the pipette tip **310** enters the open end **145** thereof. The sample is then collected from the second receptacle and transferred to the first receptacle **100**. It should be understood that in certain embodiments, the sample will have been previously dispensed into the receptacle prior to deposit of the oil and/or the sample for analysis may be transferred from a material transfer unit (not shown) within the biochemical analyzer. After depositing the sample into the first receptacle, the automated pipettor withdraws the pipette tip **310** from the receptacle **100**, and the robot arm moves the automated pipettor to a location over a waste receptacle and ejects the pipette tip **310**. After ejection, the robot arm moves the automated pipettor to a position over a third unused pipette tip **310** and lowers the pipettor to enable frictional attachment thereto.

Once the automated pipettor having the third pipette tip **310** attached thereto is raised such that the pipette tip **310** is not obstructed by additional unused tips, and/or other components within the automated biochemical analyzer, the robot arm moves the automated pipettor into the second designated position over the cartridge **500** and lowers the pipettor into the fluid chamber **520** of the cartridge **500**. If present, a frangible seal covering the fluid chamber **520** is punctured by the pipette tip **310**. The automated pipettor then withdraws a predetermined amount of diluent and is raised such that the pipette tip **310** is unobstructed by the cartridge **500** and/or other components within the automated biochemical analyzer.

The robot arm then moves the automated pipettor into a designated position over a spatially indexed multi-well tray **700** and lowers the pipettor such that the pipette tip **310** punctures a frangible seal (if present) covering a well **715** disposed in the multi-well tray **700**. The diluent is then deposited into the well **715** containing a lyophilized reagent **495** used in the reagent-based assay. Optionally, the automated pipettor will repeatedly aspirate and dispense the liquid contained in the well **715** to allow sufficient time and fluidic pressure required to reconstitute the lyophilized reagent **495**.

The automated pipettor thereafter collects the reconstituted reagent and withdraws the pipette tip **310** from the well **715** of the multi-well tray **700** such that the pipette tip **310** is unobstructed by the well **715** and/or other components within the automated biochemical analyzer. The robot arm then moves the automated pipettor into the designated position over the first receptacle **100** containing the dispensed oil and sample for analysis. The automated pipettor is then lowered into the open end **145** of the receptacle **100** to dispense the reconstituted reagent. Optionally, the automated pipettor will repeatedly aspirate and dispense the liquid contained in the receptacle **100** to allow sufficient time and fluidic pressure required to mix the contents of the receptacle **100**, thereby creating a reaction mixture.

After optional mixing, the automated pipettor withdraws the pipette tip **310** from the receptacle **100**, but leaves the reaction mixture within the receptacle **100**. The robot arm then moves the automated pipettor to a location over the waste receptacle and ejects the pipette tip **310**. After ejection, the robot arm moves the automated pipettor to a designated position over a well **415** containing a cap **200** to enable frictional attachment thereto. Once the automated pipettor having the cap **200** attached thereto is raised such that the cap **200** is not obstructed the well **415** and/or other components within the automated biochemical analyzer, the robot arm moves the automated pipettor into the designated position over the receptacle **100** containing the reaction mixture. The automated pipettor is then lowered such that the cap **200** is securably attached to the receptacle **100**. As the automated pipettor is raised, the capped receptacle is lifted from a receptacle holder or well of a multi-well tray **400** for transport to, for example, a centrifuge and/or thermocycler for automated incubation.

In certain embodiments, it is desirable to expedite the process of reconstitution of the lyophilized reagent **495**, mixing of the reagent with the test sample, and subsequent capping of the receptacle **100** containing the reagent mixture. In such embodiments, more than one robot arm and automated pipettor may be provided within the automated biochemical analyzer, and may be independently controlled to expand the capabilities thereof. Alternatively, or in addition thereto, the automated biochemical analyzer may include one or more pick and place robots, which may be used to perform functions not related to collection and/or deposit of liquids, such as capping of a receptacle **100** containing a reaction mixture and/or transport of the capped receptacle to a centrifuge and/or thermocycler for automated incubation.

Although the present disclosure has been described with reference to the above example, it will be understood that modifications and variations are encompassed within the spirit and scope of the disclosed subject matter. Accordingly, the present disclosure is limited only by the following claims.

What is claimed is:

1. A single piece multi-well tray for use in an automated instrument and comprising:
 - a an elongated base having a first end and a second end, said base comprising a top surface and opposed side walls extending from the top surface to a bottom surface, a first end wall extending between said side walls, and an arm extending outwardly from the first end of the base and configured to be engaged by a transport mechanism for transporting the tray within the instrument, wherein the arm comprises a bridge extending outwardly from the first end wall and a post having one end attached to the bridge and an opposite end that is not attached to the bridge and wherein the post extends from the bridge so as to define a gap between the opposite end of the post and the first end wall;
 - a plurality of wells depending from the top surface and disposed between the opposed side walls, each having an opening at the top surface, wherein the wells are arranged in at least one row extending between the first end and the second end of the base, and wherein the wells do not extend below the bottom surface of the side walls; and
 - a snap fingers disposed at the second end of the base and configured to grasp an element of the instrument for securing the tray to the element, wherein the snap

25

fingers comprise opposed spaced-apart tabs defining a slot therebetween configured to receive the element of the instrument.

2. The multi-well tray of claim 1, wherein the post extends in an orientation substantially perpendicular to a plane of the top surface.

3. The multi-well tray of claim 1, further comprising at least one frangible seal secured to the top surface and covering the opening of a corresponding well.

4. The multi-well tray of claim 1, wherein each well comprises a side wall and a bottom wall, and at least one of the wells further comprises one or more features selected from the group consisting of a plurality of bumps, a concave groove, a convex ridge, and a set of grooves and/or ridges comprising a crisscross pattern formed on an inner surface of the bottom wall.

5. The multi-well tray of claim 1, wherein at least one of the wells comprises one or more retention features selected from the group consisting of a tapered ring insert, a collar, and a fingered collar, wherein the one or more retention features are disposed within the well and are sized to retain a lyophilized reagent within the well.

6. The multi-well tray of claim 1, wherein a perimeter wall of the base defines the opposed side walls and a front end wall.

7. The multi-well tray of claim 1, wherein the wells are arranged in two parallel rows of wells.

8. The multi-well tray of claim 1, wherein the snap fingers comprise a portion of the bottom surface.

9. The multi-well tray of claim 1, wherein the opposed tabs are oriented in a direction extending from the second end of the base toward the first end of the base.

26

10. The multi-well tray of claim 1, wherein the opposed tabs flare away from each other at their ends.

11. The multi-well tray of claim 9, wherein the opposed tabs flare away from each other at their ends.

12. The multi-well tray of claim 1, wherein the base is defined by a perimeter wall that defines the opposed side walls, a first end wall, and a second end wall with the opposed tabs extending inwardly from the second end wall, wherein the first end of the base comprises the first end wall, and wherein the second end of the base comprises the second end wall.

13. The multi-well tray of claim 9, wherein the base is defined by a perimeter wall that defines the opposed side walls, a first end wall, and a second end wall with the opposed tabs extending inwardly from the second wall, wherein the first end of the base comprises the first end wall, and wherein the second end of the base comprises the second end wall.

14. The multi-well tray of claim 10, wherein the base is defined by a perimeter wall that defines the opposed side walls, a first end wall, and a second end wall with the opposed tabs extending inwardly from the second wall, wherein the first end of the base comprises the first end wall, and wherein the second end of the base comprises the second end wall.

15. The multi-well tray of claim 11, wherein the base is defined by a perimeter wall that defines the opposed side walls, a first end wall, and a second end wall with the opposed tabs extending inwardly from the second wall, wherein the first end of the base comprises the first end wall, and wherein the second end of the base comprises the second end wall.

* * * * *