



US009579217B2

(12) **United States Patent**
Chervitz et al.

(10) **Patent No.:** **US 9,579,217 B2**
(45) **Date of Patent:** **Feb. 28, 2017**

(54) **SPINAL FACET IMPLANTS WITH MATING
ARTICULATING BEARING SURFACE AND
METHODS OF USE**

(2013.01); *A61F 2/4405* (2013.01); *A61F*
2002/3085 (2013.01); *A61F 2002/30125*
(2013.01); *A61F 2002/30154* (2013.01); *A61F*
2002/30156 (2013.01);

(71) Applicant: **GLOBUS MEDICAL, INC.**, Audubon,
PA (US)

(Continued)

(72) Inventors: **Alan Chervitz**, Palm Harbor, FL (US);
Daniel J. Triplett, Providence, UT
(US); **T. Wade Fallin**, Hyde Park, UT
(US); **Robert W. Hoy**, Paradise, UT
(US)

(58) **Field of Classification Search**

CPC *A61B 17/7064*; *A61B 17/1757*; *A61B*
17/1671; *A61B 17/7067*; *A61B 17/8695*
USPC 606/246–249, 280–299; 623/17.11,
623/17.14–17.15

See application file for complete search history.

(73) Assignee: **GLOBUS MEDICAL, INC.**, Audubon,
PA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

4,408,927 A * 10/1983 Fraiberg 403/320
5,735,853 A * 4/1998 Olerud 606/71

(Continued)

(21) Appl. No.: **13/846,034**

Primary Examiner — Mary Hoffman

Assistant Examiner — Tara R Carter

(22) Filed: **Mar. 18, 2013**

(65) **Prior Publication Data**

US 2014/0058447 A1 Feb. 27, 2014

Related U.S. Application Data

(63) Continuation of application No. 10/860,543, filed on
Jun. 2, 2004, now Pat. No. 8,419,770.

(Continued)

(51) **Int. Cl.**

A61B 17/88 (2006.01)

A61F 2/46 (2006.01)

(Continued)


(52) **U.S. Cl.**

CPC *A61F 2/4611* (2013.01); *A61B 17/7067*
(2013.01); *A61B 17/7049* (2013.01); *A61B*
17/8625 (2013.01); *A61B 17/8695* (2013.01);
A61B 2017/8655 (2013.01); *A61F 2/30771*

(57) **ABSTRACT**

Superior and/or inferior facets of one or more facet joints
may be replaced by superior and/or inferior facet joint
protheses. In one embodiment, a kit of superior or inferior
protheses is provided, in which the protheses have at least
two dimensions that vary among members of the kit inde-
pendently of each other. Each prothesis may have a bone
engaging surface having a surface that is polyaxially rotat-
able against a corresponding resection of a vertebra. Each
prothesis may also have an articulating surface shaped such
that, after attachment to the spine, the replaced or partially
replaced facet joints provide a larger medial-lateral range of
motion when the spine is flexed than when the spine is
extended. Crosslinks may be used to connect left and right
prothesis together in such a manner that they are stabilized
in a position in which they are seated directly against the
vertebra.

17 Claims, 74 Drawing Sheets



Related U.S. Application Data

(60) Provisional application No. 60/528,726, filed on Dec. 10, 2003, provisional application No. 60/545,094, filed on Feb. 17, 2004, provisional application No. 60/545,101, filed on Feb. 17, 2004.

(51) **Int. Cl.**

A61B 17/70 (2006.01)
A61B 17/86 (2006.01)
A61F 2/30 (2006.01)
A61F 2/44 (2006.01)

(52) **U.S. Cl.**

CPC *A61F 2002/30171* (2013.01); *A61F 2002/30426* (2013.01); *A61F 2002/30433* (2013.01); *A61F 2002/30448* (2013.01); *A61F 2002/30514* (2013.01); *A61F 2002/30576* (2013.01); *A61F 2002/30578* (2013.01); *A61F 2002/30579* (2013.01); *A61F 2002/30616* (2013.01); *A61F 2002/30841* (2013.01); *A61F 2220/005* (2013.01); *A61F 2220/0025*

(2013.01); *A61F 2220/0041* (2013.01); *A61F 2230/005* (2013.01); *A61F 2230/0008* (2013.01); *A61F 2230/0021* (2013.01); *A61F 2230/0023* (2013.01); *A61F 2310/00017* (2013.01); *A61F 2310/00023* (2013.01); *A61F 2310/00203* (2013.01); *A61F 2310/00239* (2013.01); *A61F 2310/00796* (2013.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

6,132,464	A *	10/2000	Martin	623/17.15
7,717,959	B2 *	5/2010	William	A61F 2/4425 623/17.15
2002/0065557	A1 *	5/2002	Goble et al.	623/17.11
2002/0123806	A1 *	9/2002	Reiley	623/17.11
2002/0151895	A1 *	10/2002	Soboleski et al.	606/61
2002/0177851	A1 *	11/2002	Happonen et al.	606/73
2006/0079892	A1 *	4/2006	Roychowdhury et al.	606/61

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 23




Fig. 24




Fig. 25




Fig. 26




Fig. 27




Fig. 28




Fig. 28A




Fig. 29




Fig. 30




Fig. 31




Fig. 32




Fig. 33




Fig. 34




Fig. 35




Fig. 36




Fig. 37




Fig. 38




Fig. 39




Fig. 40




Fig. 41




Fig. 42




Fig. 43




Fig. 44




Fig. 45




Fig. 46




Fig. 47




Fig. 48




Fig. 49




Fig. 50




Fig. 51




Fig. 52




Fig. 53A




Fig. 53B




Fig. 53C




Fig. 53D




Fig. 53E




Fig. 53F




Fig. 53G




Fig. 53H




Fig. 53I




Fig. 54




Fig. 55




Fig. 56




Fig. 57




Fig. 58




Fig. 59




Fig. 60




Fig. 61




Fig. 62




Fig. 63




Fig. 64




Fig. 65

**SPINAL FACET IMPLANTS WITH MATING
ARTICULATING BEARING SURFACE AND
METHODS OF USE**

CROSS REFERENCE TO RELATED
APPLICATIONS

This application is a continuation application of U.S. Ser. No. 10/860,543, filed Jun. 2, 2004, which claims priority to U.S. Provisional Application 60/528,726, filed Dec. 10, 2003, U.S. Provisional Application 60/545,094, filed Feb. 17, 2004, and U.S. Provisional Application 60/545,101, filed Feb. 17, 2004, all of which are incorporated by reference in their entireties.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to surgical devices and methods to guide instruments that prepare the surface of bones and other tissues for implants that replace a damaged, diseased, or otherwise painful spinal facet joint.

2. Description of Related Art

Traumatic, inflammatory, metabolic, and degenerative disorders of the spine can produce debilitating pain that can have severe socioeconomic and psychological effects. One of the most common surgical interventions today is arthrodesis, or spine fusion, of one or more motion segments, with approximately 300,000 procedures performed annually in the United States. Clinical success varies considerably, depending upon technique and indications, and consideration must be given to the concomitant risks and complications. For example, Tsantrizos and Nibu have shown that spine fusion decreases function by limiting the range of motion for patients in flexion, extension, rotation, and lateral bending. Furthermore, Khoo and Nagata have shown that spine fusion creates increased stresses and, therefore, accelerated degeneration of adjacent non-fused motion segments. Additionally, pseudoarthrosis, as a result of an incomplete or ineffective fusion, may reduce or even eliminate the desired pain relief for the patient. Finally, the fusion device, whether artificial or biological, may migrate out of the fusion site.

Recently, several attempts have been made to recreate the natural biomechanics of the spine by use of an artificial disc. Artificial discs provide for articulation between vertebral bodies to recreate the full range of motion allowed by the elastic properties of the natural intervertebral disc that directly connects two opposed vertebral bodies.

However, the artificial discs proposed to date do not fully address the mechanics of motion of the spinal column. In addition to the intervertebral disc, posterior elements called the facet joints help to support axial, torsional and shear loads that act on the spinal column. Furthermore, the facet joints are diarthroidal joints that provide both sliding articulation and load transmission features. The effects of their absence as a result of facetectomy was observed by Goh to produce significant decreases in the stiffness of the spinal column in all planes of motion: flexion and extension, lateral bending, and rotation. Furthermore, contraindications for artificial discs include arthritic facet joints, absent facet joints, severe facet joint tropism or otherwise deformed facet joints, as noted by Lemaire.

U.S. Pat. No. Re. 36,758 to Fitz discloses an artificial facet joint where the inferior facet, the mating superior facet, or both, are resurfaced.

U.S. Pat. No. 6,132,464 to Martin discloses a spinal facet joint prosthesis that is supported on the posterior arch of the

vertebra. Extending from this support structure are inferior and/or superior blades that replace the cartilage at the facet joint. The Martin prosthesis generally preserves existing bony structures and therefore does not address pathologies that affect the bone of the facets in addition to affecting the associated cartilage. Furthermore, the Martin invention requires a mating condition between the prosthesis and the posterior arch (also known as the lamina) that is a thin base of curved bone that carries all four facets and the spinous process. Since the posterior arch is a very complex and highly variable anatomic surface, it would be very difficult to design a prosthesis that provides reproducible positioning to correctly locate the cartilage-replacing blades for the facet joints.

Another approach to surgical intervention for spinal facets is provided in WO9848717A1 to Villaret. While Villaret teaches the replacement of spine facets, the replacement is interlocked in a manner to immobilize the joint.

It would therefore be an improvement in the art to provide a vertebral facet replacement device and method that provides a relatively high degree of mobility in the joint, while effectively removing the source of arthritic, traumatic, or other disease mediated pain with a minimum of patient discomfort.

SUMMARY OF THE INVENTION

In order to overcome the shortcomings of the prior art, the present invention provides a vertebral facet replacement device and method that replaces a bony portion of the facets so as to remove the source of arthritic, traumatic, or other disease mediated pain. Facet joint replacement in conjunction with artificial disc replacements represent a holistic solution to recreating a fully functional motion segment that is compromised due to disease or trauma. Together, facet joint and disc replacement can eliminate all sources of pain, return full function and range of motion, and completely restore the natural biomechanics of the spinal column. Additionally, degenerative or traumatized facet joints may be replaced in the absence of disc replacement when the natural intervertebral disc is unaffected by the disease or trauma.

Accordingly, in certain embodiments, the present invention provides an artificial vertebral facet that replaces the cartilage and a portion of the bone of a facet. Furthermore, the invention may provide a method for preparing a vertebra for the installation of an artificial vertebral facet, a method for replacing a spinal facet, and possibly, a total vertebral facet joint replacement.

The present invention may provide numerous advantages over the prior art. One advantage may be that the quality of attachment of the prosthesis is improved. The present invention may provide a precise press fit into bones, as opposed to relying on prosthetic surfaces mating with highly complex and variable external surfaces of the vertebra, such as the posterior arch or facet. Another advantage may be that the optional porous coating is placed into interior bone spaces where porous coatings have proven to achieve bone ingrowth for excellent long term fixation strength. This ability to achieve bone ingrowth is uncertain for the prior art devices that engage the external bone surfaces of the vertebra. Yet another advantage may lie in the removal of the facet bone structure; where the facet bone is involved in the disease pathology or the trauma that compromised the articular or cartilaginous surface of the facet, resection provides a means for ensuring that all pain associated with the disease or trauma is removed.

The above, and other features and advantages of the present invention, will become apparent from the following description, which is to be read in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a portion of the spine;
 FIG. 2 is a lateral view of a facet joint reconstructed in accordance with the present invention;
 FIG. 3 is a dorsal view of the facet joint shown in FIG. 2;
 FIG. 4 is a perspective view of the implanted left inferior facet prosthesis shown in FIGS. 2 and 3;
 FIG. 5 is a perspective view of the left inferior facet prosthesis shown in FIGS. 2 and 3;
 FIG. 6 is a cranial view of the implanted left superior facet prosthesis shown in FIGS. 2 and 3;
 FIG. 7 is a perspective view of the left superior facet prosthesis shown in FIGS. 2 and 3;
 FIG. 8 is a perspective view of an alternative implanted left inferior facet prosthesis;
 FIG. 9 is a perspective view of an alternative left inferior facet prosthesis;
 FIG. 10 is a lateral view of an alternative reconstructed facet joint;
 FIG. 11 is a dorsal view of an alternative reconstructed facet joint;
 FIG. 12 is a perspective view of the implanted left inferior facet prosthesis shown in FIGS. 10 and 11;
 FIG. 13 is a perspective view of the alternative left inferior facet prosthesis shown in FIGS. 10 and 11;
 FIG. 14 is a cranial view of the alternative implanted left superior facet prosthesis shown in FIGS. 10 and 11;
 FIG. 15 is a perspective view of the alternative left superior facet prosthesis shown in FIGS. 10 and 11;
 FIG. 16 is a perspective view of an alternative bearing surface for the superior facet prosthesis shown in FIG. 15;
 FIG. 17 is a dorsal view of a single intact vertebra;
 FIG. 18 is a lateral view of the same intact vertebra shown in FIG. 17;
 FIG. 19 is a dorsal view of the same vertebra of FIG. 17 and FIG. 18, with a portion of the superior facet resected and a portion of the inferior facet resected;
 FIG. 20 is a lateral view of the resected vertebra shown in FIG. 19;
 FIG. 21 is a dorsal view of the same resected vertebra shown in FIG. 18 and FIG. 19 with a fixation element placed through the first superior resection surface and into the pedicle bone;
 FIG. 22 is a dorsal view showing the resected vertebra, the fixation element, and a superior facet prosthesis;
 FIG. 23 is a dorsal view of the vertebra and the implant of FIG. 23 and also showing the addition of an inferior facet prosthesis;
 FIG. 24 is a dorsal view of the implant and vertebra of FIG. 23 and also showing the addition of an enlarged head that has the shape of a locking nut;
 FIG. 25 is a perspective view of a vertebra with an assembled implant comprising a fixation element, superior facet prosthesis, and a locking nut;
 FIG. 26 is a perspective, cross-sectioned view of the same vertebra and implant of FIG. 25 with a cross section aligned with the axis of the fixation element;
 FIG. 27 is a cranial, cross-sectioned view of the vertebra and implant of FIG. 25, with the section plane positioned as in FIG. 26;

FIG. 28 is a side view of embodiments A, B, C, D, E, and F of the fixation element, a cross-sectional view of each of embodiments A, B, C, D, E, and F, and a side view of the enlarged head in the shape of a locking nut;
 FIG. 28A is a side view of embodiments G, H, I, J, K, and L of the fixation element with attached enlarged heads, and a cross-sectional view of each of embodiments G, H, I, J, K, and L;
 FIG. 29 is a perspective view of a radially expanding fixation element in its unexpanded state;
 FIG. 30 is a side view and a bottom view of (i) an expanded radially expanding fixation element and (ii) an unexpanded radially expanding fixation element;
 FIG. 31 is a perspective cross-sectional view of a vertebra and a facet implant showing a cross-pin torsionally and axially securing the fixation element;
 FIG. 32 is a dorsal view of a spinal section showing a top, middle, and bottom vertebra with unilateral facet replacements on the right side of the spine section, both between the top and middle vertebra, and between the middle and bottom vertebra;
 FIG. 33 is a dorsal view of a spine section showing a superior hemiarthroplasty facet replacement between the top and the middle vertebra and unilateral replacement between the middle and the bottom vertebra;
 FIG. 34 is a dorsal view of a spinal section showing an inferior facet hemiarthroplasty replacement between the top and the middle vertebra and a unilateral replacement on the right side between the middle and the bottom vertebra;
 FIG. 35 is a dorsal view of a spinal section showing a unilateral replacement between the top and middle vertebrae on the right side, and an inferior facet hemiarthroplasty replacement between the middle and bottom vertebrae on the same side;
 FIG. 36 is a dorsal view of a spinal section showing a unilateral replacement between the top and middle vertebrae on the right side and a superior facet hemiarthroplasty replacement on the right side between the middle and bottom vertebrae on the same side;
 FIG. 37 is a spinal section of two vertebrae showing one inferior facet of the top vertebra and the adjoining superior facet of the bottom vertebra replaced by an articulating facet implant;
 FIG. 38 is a perspective view of a curved superior facet prosthesis;
 FIG. 39 is a perspective view of a superior facet prosthesis with a bone ingrowth surface;
 FIG. 40 is a perspective view of an inferior facet prosthesis;
 FIG. 41 is a perspective view of an inferior facet prosthesis with a bone ingrowth surface;
 FIG. 42 is an exploded, perspective view illustrating the addition of a locking washer to the construction of the implant shown in FIG. 25;
 FIG. 43 is a perspective view illustrating the implant of FIG. 25 with a locking washer fully installed;
 FIG. 44 is a perspective view of the locking washer shown in FIG. 42;
 FIG. 45 is a perspective view of superior and inferior facet prostheses held against a vertebra by flexible fixation elements;
 FIG. 46 is a dorsal view of a bilateral inferior implant;
 FIG. 47 is perspective view of a vertebra with an alternative embodiment of a superior facet prosthesis fixed to the bone by one embodiment of a fixation element;
 FIG. 48 is a perspective, cross-sectional view of the embodiment of the superior facet prosthesis and fixation

5

element of FIG. 47 showing the semispherical shape of the resection and the approximately similarly semispherical shape of the apposition side of the superior facet prosthesis, as well as an angled resection and corresponding angled flat on the apposition side of the superior facet prosthesis in combination with the semispherical resection;

FIG. 49 is a perspective view of the resected vertebra without the superior facet prosthesis attached to the vertebra, in which the fixation element is installed in the vertebra;

FIG. 50 is a perspective view of the resected vertebra with the superior facet prosthesis attached to the vertebra, with the fixation element installed in the vertebra, but without the locking fastener shown in FIG. 47;

FIG. 51 is a top view of the superior facet prosthesis showing the semispherical shape of the bone apposition side in combination with the angled flat on the bone apposition side;

FIG. 52 is a rear view of the superior facet prosthesis showing the semispherical nut engaging surface on the top of the area that is design to connect to the fixation element and the locking nut, or the inferior prosthesis and the fixation element;

FIG. 53A is a rear view and a perspective view of a plurality of superior facet prostheses of a kit;

FIG. 53B is a top view of an inferior facet prosthesis according to one embodiment of the invention;

FIG. 53C is a side view of the inferior facet prosthesis of FIG. 53B;

FIG. 53D is a perspective view of a plurality of inferior facet prostheses of a kit;

FIG. 53E is a perspective view showing how a superior facet prosthesis and an inferior facet prosthesis may fit together;

FIG. 53F is a dorsal view of an L5 superior facet prosthesis and an inferior facet prosthesis fit on adjacent vertebrae to articulate against each other;

FIG. 53G is a posteriolateral view of the implants and vertebrae shown in FIG. 53F;

FIG. 53H is a posteriolateral view showing a cross-section along a first plane cut through the articulation of the implants of FIG. 53F;

FIG. 53I is a cephalad view showing a cross-section along a second plane cut through the articulation of the implants shown in FIG. 53F;

FIG. 54 is a dorsal view of a bilateral inferior facet prosthesis system and a superior facet prosthesis in situ;

FIG. 55 is a perspective view of the bilateral inferior facet prosthesis system and the superior facet prosthesis of FIG. 54;

FIG. 56 is a lateral view of the bilateral inferior facet prosthesis system and superior facet prosthesis in situ;

FIG. 57 is a cranial view of the bilateral inferior implant system in situ;

FIG. 58 is a bottom view of the bilateral inferior facet prosthesis system in situ;

FIG. 59 is rear view of the bilateral inferior facet prosthesis system in isolation;

FIG. 60 is a top view of the bilateral inferior facet prosthesis system in isolation;

FIG. 61 is a bottom view of the bilateral inferior facet prosthesis system in isolation;

FIG. 62 is a perspective view of the right inferior prosthesis;

FIG. 63 is a perspective view of various ball-shaped members of inferior prostheses, the ball-shaped members having differing surface features, particularly circumferential grooves, longitudinal grooves, and knurling;

6

FIG. 64 is an end view of the ball-shaped members of FIG. 63; and

FIG. 65 is a dorsal view of the bilateral inferior facet prosthesis system, in which castle nuts are attached to the left and right fixation elements.

DETAILED DESCRIPTION OF THE DRAWINGS

Referring now to FIG. 1, there is shown a perspective view of a superior vertebra 1 and an inferior vertebra 3, with an intervertebral disc 2 located in between. The superior vertebra 1 has superior facets 43, inferior facets 6, a posterior arch (or lamina) 35 and a spinous process 46. The inferior vertebra 3 has superior facets 7, inferior facets 44, a posterior arch (or lamina) 36 and a spinous process 45. Each of the vertebrae 1, 3 also has a pair of pedicles 11.

Referring now to FIG. 2, in a lateral view, the left inferior facet 6 of the superior vertebra 1 shown in FIG. 1 has been resected and an inferior facet prosthesis 4 has been attached to the superior vertebra 1. Similarly, the left superior facet 7 of the inferior vertebra 3 has been resected and a superior facet prosthesis 5 has been attached to the inferior vertebra 3.

FIG. 3 illustrates a dorsal view of the elements shown in FIG. 2. It can be appreciated that inferior facet prosthesis 4 replicates the natural anatomy when compared to the contralateral inferior facet 6 of vertebra 1. Similarly, it can be appreciated that superior facet prosthesis 5 replicates the natural anatomy when compared to the contralateral superior facet 7 of vertebra 3. Neither the inferior facet prosthesis 4 nor the superior facet prosthesis 5 rests on the lamina 35.

Turning now to FIG. 4, a perspective view of the superior vertebra 1 with implanted inferior facet prosthesis 4 is provided. A bone resection on the left side of the superior vertebra 1, shown as a resection 31, has removed the natural inferior facet 6 at the bony junction between the inferior facet 6 and the lamina 35. In this manner, any bone pain associated with a disease, such as osteoarthritis, or trauma of the left inferior facet 6 will be eliminated as the involved bony tissue has been osteotomized.

FIG. 5 illustrates a perspective view of the inferior facet prosthesis 4. A surface 8 replicates the natural articular surface of the replaced inferior facet 6. A post 9 provides a mechanism that can be used to affix the inferior facet prosthesis 4 to the superior vertebra 1. The post 9 is implanted into the interior bone space of the left pedicle 11 on the superior vertebra 1 and may or may not extend into the vertebral body of superior vertebra 1 to provide additional stability.

FIG. 6 illustrates a cranial view of the inferior vertebra 3 with the implanted superior facet prosthesis 5. A resection surface 32 represents the bony junction between the natural superior facet 7 and the lamina 36.

FIG. 7 illustrates a perspective view of the superior facet prosthesis 5. A surface 38 replicates the natural articular surface of the replaced superior facet 7. The post 37 provides a mechanism usable to affix the superior facet prosthesis 5 to the inferior vertebra 3. The post 37 is implanted into the interior bone space of the left pedicle 11 (FIG. 6) on the inferior vertebra 3 and may or may not extend into the vertebral body of the inferior vertebra 3 to provide additional stability.

When the total facet joint is replaced, as shown in FIGS. 2 and 3, then the surface 8 (FIG. 5) articulates against the surface 38 (FIG. 7) to recreate the natural biomechanics of the spine motion segment made up of the superior vertebra 1, the inferior vertebra 3, and the intervertebral disc 2.

Neither the inferior facet prosthesis **4** nor the superior facet prosthesis **5** rests on the lamina **35** or the lamina **36**, respectively.

FIG. **8** illustrates a perspective view of an alternative inferior facet prosthesis **10** that may be implanted into the interior bone space of the lamina **35** of the superior vertebra **1**. The interior bone space is accessed from the resection **31**.

FIG. **9** shows a perspective view of the alternative inferior facet prosthesis **10**, including a fin **13** that extends into the interior bone space of the **35**. A surface **12** replicates the natural articular surface of the replaced facet.

The surfaces of the post **9** (FIG. **5**), the post **37** (FIG. **7**), and the fin **13** (FIG. **9**) may or may not include porous coatings to facilitate bone ingrowth to enhance the long-term fixation of the implant. Furthermore, such porous coatings may or may not include osteoinductive or osteoconductive substances to further enhance bone remodeling into the porous coating. In this application, the term "implant" refers to any natural or man-made, fabricated or unfabricated device or group of devices that may be added to a human spine. An implant may include one or more prostheses, one or more fixation devices, and/or other components.

Referring now to FIG. **10**, there is shown a lateral view of a superior vertebra **14** and an inferior vertebra **16**, with an intervertebral disc **15** located in between. The left inferior facet of the superior vertebra **14** has been resected and an inferior facet prosthesis **18** has been attached to superior vertebra **14** via a screw fastener **17**. Similarly, the left superior facet of the inferior vertebra **16** has been resected and a superior facet prosthesis **19** has been attached to vertebra **16** via a screw fastener **17**.

FIG. **11** illustrates a dorsal view of the elements of FIG. **10**. It can be appreciated that inferior facet prosthesis **18** replicates the natural anatomy when compared to the contralateral inferior facet **22** of the superior vertebra **14**. Similarly, it can be appreciated that superior facet prosthesis **19** replicates the natural anatomy when compared to the contralateral superior facet **21** of the inferior vertebra **16**. Neither the inferior facet prosthesis **18** nor the superior facet prosthesis **19** rests on the lamina of the corresponding vertebra **14** or **16**.

Turning now to FIG. **12**, there is provided a perspective view of the superior vertebra **14** with the implanted inferior facet prosthesis **18**. A resection **34** has removed the natural inferior facet at the bony junction between the inferior facet and the adjoining lamina. In this manner, any bone pain associated with a disease, such as osteoarthritis, or trauma of the natural inferior facet **22** will be eliminated inasmuch as the involved bony tissue has been osteotomized.

FIG. **13** illustrates a perspective view of the inferior facet prosthesis **18**. A surface **23** replicates the natural articular surface of the replaced facet. A flange **25** contacts the pedicle **11** (FIG. **12**) and a hole **24** receives the screw fastener **17** to attach the inferior facet prosthesis **18** to the superior vertebra **14**.

FIG. **14** illustrates a cranial view of the inferior vertebra **16** with the implanted superior facet prosthesis **19**. A resection surface **33** represents the bony junction between the natural superior facet **21** (FIG. **11**) and the corresponding lamina.

FIG. **15** illustrates a perspective view of the superior facet prosthesis **19**. A surface **27** replicates the natural articular surface of the replaced facet. A flange **39** contacts the pedicle **11** (FIG. **14**) and hole **26** receives a screw fastener **17** to attach the superior facet prosthesis **19** to the inferior vertebra **16**.

FIG. **16** provides a perspective view of an alternative superior facet prosthesis **40** with a bearing surface **41** that mounts to substrate **42**. The bearing surface **41** is a biocompatible polymeric material, such as ultra high molecular weight polyethylene. Alternatively, the bearing surface can be ceramic, such as zirconia or alumina. The substrate is a biocompatible metal alloy, such as an alloy of titanium, cobalt, and/or iron.

The bearing surface **41** may be formed separately from the remainder of the superior facet prosthesis **40**, so that the bearing surface **41** and the remainder form components that can be assembled as needed. A kit of differently-sized prostheses may include multiple bearing surfaces like the bearing surface **41** that may have different thicknesses, articulating surface shapes, material selections, and the like. Such a kit may also include other differently-sized components designed such that some subset of the components can be selected and assembled together to provide a prosthesis having the desired dimensions. Prosthesis kits will be shown and described in greater detail subsequently.

Referring to FIG. **17** and FIG. **18**, a single intact vertebra **100** is shown. FIG. **17** is a dorsal view of the vertebra **100**. FIG. **18** is a lateral view of the same vertebra **100**. Similar to the two vertebrae **1**, **3** shown in the portion of the spine illustrated in FIGS. **1** through **3**, the vertebra **100** has posterior anatomy comprising left and right superior facets **43** on the superior, or top side in this view of the dorsal vertebra **100**, left and right inferior facets **6** on the inferior or bottom side of the posterior vertebra **100**, left and right transverse processes **105** extending laterally from the posterior portion of vertebra **100**, and left and right pedicles **11**. Each of the superior facets **43** has a superior articulating surface **145**. The posterior portion of vertebra **100** also has a posterior arch (or lamina) **35**, and a spinous process **46** that protrudes from the lamina **35** posteriorly, out of the page in FIG. **17** and to the left in FIG. **18**. In FIG. **17**, the bony structure of the superior facets **43** and the inferior facets **6** are intact, as it would be presented in a vertebra without significant tissue degeneration or remodeling resulting from facet joint disease. Although the vertebra **100** is shown in FIG. **17** as a generally structurally healthy and intact vertebra, if the vertebra **100** were a diseased vertebra, the vertebra could exhibit signs of facet joint disease.

Consequently, structural pathology related to facet joint disease would likely be visible. For example, the left superior facet **43** and the right superior facet **43** of the vertebra **100** are symmetrical in FIG. **17** and FIG. **18**. But in the case of a vertebra **100** with only one diseased joint, the facet on the diseased side would likely be showing pathological signs of disease such as tissue degeneration or inflammation resulting in an asymmetrical structural comparison between the two facets.

Also, in more extreme cases the facet disease could progress to a state in which the articular process of the facet is eroded or inflamed resulting in anatomic morphology that is unique to the pathology of a particular facet joint of an individual patient. This could present unusual facet morphology that could be different from what is shown in FIGS. **17** and **18**.

Furthermore, the facet disease could eventually disable the biomechanics of a patient such that the facet joint is essentially non-articulating and immobile. In this case, one superior facet of a first vertebra could essentially be fused to one inferior facet of a second vertebra. Since the structural pathology of the diseased facet is variable, a surgeon may determine that the best bone apposition surface or foundation for securing a facet implant is a resected bone surface.

Referring to FIG. 19 and FIG. 20 which are dorsal and lateral views of the same vertebra shown in FIG. 17 and FIG. 18 after a portion of the right superior facet 43 and a portion of the right inferior facet 6 have been resected. The removal of a portion of the superior facet 43 by resection results in a superior facet resection 111. In the resection shown in FIG. 19 and FIG. 20, the superior resection 111 has two resulting faces, a first resection surface 112 and a second resection surface 113. Likewise, the inferior facet resection results in an inferior facet resection surface 121.

Tissue removal tools (not shown) such as a bone burr, rasp, reamer, mill, saw, rongeur, osteotome or similar tools designed to cut and remove bone tissue can be used to create these resection surfaces. The surgeon uses anatomic landmarks such as the pedicle 11 or transverse process 105 to align the tissue removal tools in such a way as to remove the portion of the facet necessary to provide a superior resection 111 that serves as a bone apposition surface or foundation to eventually support a superior facet prosthesis 300, as shown in FIG. 22. The left superior facet 43 is shown intact in both FIG. 19 and FIG. 20, but a portion of the right superior facet 43 is resected resulting in the first resection surface 112 and the adjacent second resection surface 113 (FIG. 19). The shape of the superior resection 111 will vary in accordance with the structure of the tissue removal tool. In the embodiment shown in FIG. 19 and FIG. 20, the first resection surface 112 and the second resection surface 113 are on approximately perpendicular planes. However, the geometry of the resection surfaces is a function of the patient anatomy, the pathology of the diseased tissue, the technique of the surgeon, and other factors such as the type of tissue removal tools used to prepare the resection. In general, the first resection surface 112 will be formed in such a way that it will serve as a foundation to support the superior facet prosthesis 300 (FIG. 22). The second resection surface 113 or other additional resection surfaces may or may not be present.

FIG. 19 and FIG. 20 also show that a portion of the inferior facet 6 is resected by tissue removal instruments resulting in an inferior resection surface 121. Such resection is preferably effected so that resection is confined to the tissue of the inferior facet 6 and does not extend into the tissue of the posterior arch (or lamina) 35. In FIGS. 19 and 20, the left inferior facet 6 is intact, while a portion of the right inferior facet 6 is resected resulting in the inferior resection surface 121 on the right side. The bone surrounding the inferior resection surface 121 is contoured by tissue removal tools in a shape designed to cradle and support an inferior facet prosthesis 400 (FIG. 23) on the medial side such that when the inferior facet prosthesis 400 is loaded on the lateral side it compresses against and is supported by the inferior resection surface 121.

Alternatively, the inferior facet 6 can be resected, and inferior facet prosthesis 400 sized and shaped, so that inferior facet prosthesis 400 does not engage the inferior resection surface 121.

FIG. 21 is a dorsal view of the vertebra 100 with a fixation element 200 placed through the superior resection 111 and into the bone of the pedicle 11 to receive the superior facet prosthesis 300 (FIG. 22). The fixation element 200 is aligned and placed into the pedicle 11, similar to how other pedicle screws for posterior stabilization involved with vertebrae fusion are placed in the pedicle 11. In one method, a long guide wire (not shown), with a diameter sized to fit freely into a cannulation 211 (as also shown in FIG. 26 and FIG. 27) in the fixation element 200, is placed through the first resection surface 112 and into the bone of the pedicle 11. The

alignment of the long guide wire can be confirmed by x-ray. The fixation element 200 is then guided over the guide wire and driven into the vertebra 100 by a driver (not shown) engaged with a drive feature 212 (FIG. 21) on a proximal post 230 of the fixation element 200. The fixation element 200 is driven into the vertebra 100 until a connection feature 213 (e.g., a screw thread) is just above the first resection surface 112. This connection feature 213 is eventually used to secure the superior facet prosthesis 300 to the vertebra 100.

In a second method for guiding the fixation element 200 into the pedicle 11, a long guide wire (not shown), with a diameter sized to fit freely into a cannulation in a bone preparation instrument (not shown) such as a tap, drill, broach or reamer, is placed through the first resection surface 112 and into the bone of the pedicle 11. The alignment of the long guide wire can be confirmed by x-ray. The bone preparation instrument is then guided over the guide wire and driven into the bone of the pedicle 11 to prepare a cavity for the fixation element 200. The guide wire and bone preparation instrument are then removed and the fixation element 200 is guided into the prepared cavity in the pedicle 11 by a driver (not shown) engaged with the drive feature 212 on the proximal post 230 of the fixation element 200. Like in the first method, the fixation element 200 is driven into the vertebra until a connection feature 213 (e.g., a screw thread) is just above the first resection surface 112. This connection feature 213 is eventually used to secure the superior facet prosthesis 300 to the vertebra 100.

In yet a third method of placing the fixation element 200 in the pedicle, the surgeon aligns the fixation element 200 with anatomic landmarks and simply drives the fixation element 200 through the first resected surface 112 and into the pedicle 11. As with the first and second methods, the fixation element 200 is driven into the vertebra 100 until a connection feature 213 (e.g., a screw thread) is just above the first superior resection surface 112.

In FIG. 22, a dorsal view illustrates a superior facet prosthesis 300 placed around the fixation element 200. The superior facet prosthesis 300 has a facet articulating component 320 that articulates against the inferior facet articulating surface of the vertebra above it. The facet articulating component 320 is preferably formed in the general shape of a blade or wing ear. The superior facet prosthesis 300 also has a bone apposition surface 322 that has been placed on the first resection surface 112 and an opening 324 in a flange 323 that surrounds the fixation element 200. The superior facet articulating component 320 has an articulating surface 321 generally adjacent to the flange 323 that is oriented in a direction that faces approximately the same direction that the original anatomic superior articulating surface 145 faced prior to resection.

This orientation of the articulating surface 321 allows the superior facet prosthesis 300 to function as either a hemiarthroplasty implant and articulate against a natural anatomic inferior facet 6 or act as a portion of a unilateral prosthesis and articulate against an inferior facet prosthesis 400 on the vertebra superior (cephalad) to it. No portion of superior facet prosthesis 300 rests on the lamina of the vertebra 100. In this application, a "unilateral prosthesis" is a prosthesis in which both facets of only one of the facet joints between adjacent vertebrae are replaced by prostheses. A "hemiarthroplasty" is a type of arthroplasty in which one side of an articulating joint surface is replaced with an artificial implant.

FIG. 23 is a dorsal view showing the addition of the inferior facet prosthesis 400 to the construct described in

11

FIG. 22. The inferior facet prosthesis 400 generally has a shape similar to a longitudinal rod that is curved to match the contour of the inferior resection 121 (FIGS. 19 and 20). The inferior facet prosthesis 400 has an opening 410 through its superior end 420 that is shaped to surround the portion of the fixation element 200 that protrudes from the first resection surface 112. In FIG. 23, the inferior facet prosthesis 400 is placed over the superior facet prosthesis 300. However, the order of the placement of the prostheses 300, 400 can be reversed such that the inferior prosthesis 400 is placed on the fixation element 200 first, followed by the superior prosthesis 300. When only the inferior facet 6 or the superior facet 43 is being replaced, only the appropriate (superior or inferior) facet prosthesis 300 or 400 is placed on the fixation element 200 without the other (inferior or superior) facet prosthesis 300 or 400.

Because the various components of the implant are modular, many combinations of configurations and implant size, structure and shapes are feasible. For example, in a patient with unusual anatomy, the inferior facet prosthesis 400 may need to be larger than expected to conform to a particularly unusual or exceptionally large morphology of the inferior resection surface 121, and the superior facet prosthesis 300 may need to have an unusual angle to its articulating surface 321 to conform to particular anatomic constraints. If this is the case, the modularity of the system allows for the surgeon to assemble an implant specifically designed to match the patient's anatomic structures during the surgery. This flexibility of a modular implant design allows the implant manufacturer to accommodate a large variation in anatomic structures with a limited selection of implant component sizes, shapes, and material types.

The modularity of the implant design also allows different components of the implant to be fabricated from different materials. Traditionally, bone fixation implants such as the fixation element 200 are fabricated from biocompatible metals or alloys that provide sufficient strength and fatigue properties, such as cobalt chrome alloys, titanium and titanium alloys, and stainless steels. However, the fixation element 200 may be fabricated from ceramics, polymers, or biological materials such as allograft bone, composites, or other biocompatible structural materials. Likewise the superior facet prosthesis 300 and the inferior facet prosthesis 400 may be fabricated from metals, alloys, ceramics, polymers, biological materials, composites, or other biocompatible structural materials.

In FIG. 24, a dorsal view illustrates the addition of an enlarged head 500 to the fixation element 200. The enlarged head 500 is tightened down to force the prostheses 300, 400 against the bone to stabilize them. The enlarged head 500 shown in FIG. 24 has a hexagonal geometry on its external surface that is shaped to accept a driver (not shown) that is used to force an internal connection feature 520 (e.g., a screw thread) of the enlarged head 500 onto the connection feature 213 of the fixation element 200. In the case of the threaded embodiment of the connection feature 213, the enlarged head 500 is provided with a threaded connection feature 520 and is driven onto the fixation element 200 by turning the enlarged head 500 and allowing the threads to drive all components of the implant between the enlarged head 500 and the first resection surface 112 against the bone at or near the resection surface 112.

FIG. 25 is a perspective posterior view of the assembly of the fixation element 200, the superior facet prosthesis 300, and the enlarged head 500. The enlarged head 500 has been placed on the first resection surface 112.

12

FIG. 26 is a perspective, cross-sectioned view of the same construct shown in FIG. 25. The superior facet prosthesis 300, the enlarged head 500, the fixation element 200, and the vertebra 100 have been cut by a cross-sectioning plane 150 placed along an axis that passes through the center of the fixation element 200. The cross-section plane 150 is shown for visualization purposes to illustrate, using a cross-sectioned view, how the vertebra 100, fixation element 200, superior facet prosthesis 300 and the enlarged head 500 engage each other. In actual surgery, it is highly unlikely that a surgeon would make a cut as illustrated by the cross-section 150 shown in FIG. 26.

FIG. 27 is a cranial, section view of the vertebra 100 and the implant, wherein the cross-section plane 150 is oriented to face the viewer. In FIG. 27, the fixation element 200 is in the vertebra 100. The embodiment of the fixation element 200 in FIG. 27 comprises a distal end 220 that is shaped to guide the fixation element 200 into bone tissue, a bone stabilizing portion 210 adjacent to the distal end, a shaft portion 240 adjacent to the bone stabilizing portion 210, a connection feature 213 adjacent to the shaft portion 240, and a drive feature 212.

The distal end 220 shown in FIG. 27 has a frusto-conical shape that allows the fixation element 200 to be driven or guided into the vertebra 100. The distal end 220 could be shaped in the form of a spade tip, trochar tip, or twist drill tip to assist in the guidance of the fixation element 200 in the vertebra 100. The fixation element 200 may also have a cutting flute (not shown) formed in the distal end 220 to help remove bone tissue and accommodate the guidance of the fixation element 200 in the vertebra 100. The bone stabilizing portion 210 helps to secure the fixation element 200 to the vertebra 100. The bone stabilizing portion 210 can include various features designed to anchor into bone such as threads, ribs, grooves, slots, fins, barbs, splines, bone ingrowth surfaces, roughened surfaces, or any geometric feature that helps to engage the fixation element 200 with the bone tissue to help stabilize the fixation element 200. In FIG. 27, the bone stabilizing portion 210 has a unitary continuous bone thread 231. However, other types of threads such as multiple lead threads, variable pitched thread, non-uniform pitch thread, buttress thread, or other thread forms used on bone screws may be used. Because FIG. 27 is a cross-sectional view, the full length of the cannulation 211 is seen passing from the distal end 220 of the fixation element 200 to the proximal post 230 of the fixation element 200.

The drive feature 212 in the embodiment shown in FIG. 27 is an internal hex. However, any shape of drive feature 212 that transmits the loads necessary to drive the fixation element 200 into the vertebra 100 can be formed on the proximal post 230 of the fixation element 200. The depth of the drive feature 212 formed in the proximal post 230 of the fixation element 200 is seen in the cross-sectional view of FIG. 27. The drive feature 212 may be an internal drive feature such as the hex socket shown in this embodiment, or an external drive feature with geometry on the periphery of the proximal post 230 of the fixation element 200 that engages with a corresponding internal drive feature on a driver tool (not shown). In this embodiment the depth of the drive feature 212 is slightly longer than its cross-section is wide. This depth can be adjusted based on the material properties of the fixation element 200 and the drive tool (not shown).

The fixation element 200 is fabricated from biocompatible base materials that provide the necessary structural rigidity and strength. Examples of base materials that may be used in the construction of the fixation element 200 include

titanium, titanium alloys, cobalt-chrome alloys, stainless steel alloys, zirconium alloys, other biocompatible metal materials, biocompatible ceramics, biocompatible composites, and biocompatible polymers. The fixation element **200** may also have surface materials formed on the base material that provide material properties specific to a particular portion of the fixation element **200**. For example, the bone stabilization portion **210** could be coated with materials that allow for improved bone ingrowth into the implant surface such as a hydroxylapatite, bioceramic, Bioglass®, or other calcium phosphate derived material. The tribological bearing properties of the material in the areas that the fixation element **200** interfaces with other artificial elements may be improved by applying surface hardening techniques to the material of the fixation element **200** in these areas. Surface hardening techniques known in the materials science and materials engineering arts such as anodizing, ion implantation, and other techniques could be applied to these isolated areas.

As mentioned previously, the connection feature **213** is formed on the portion of the fixation element **200** that protrudes from the first resection surface **112**. This connection feature **213** is designed to connect the enlarged head **500** to the fixation element **200**. In the embodiment of the connection feature **213** shown in FIG. **21**, threads **260** are on the external surface of this proximal section of the fixation element **200**. These threads **260** engage with the threads of the internal connection feature **520** (FIG. **27**) of the enlarged head **500**. Although the connection feature **213** in this embodiment is threaded, other mechanical locking features (not shown) capable of locking the fixation element **200** and the enlarged head **500** together, such as press fit, taper fit, bonding fit by cement or glue, interference fit, expansion fit and mechanical interlocking fit such as a bayonet connection, can be used as the connection feature **213**. A corresponding construction may then be used as connection feature **520** of the enlarged head **500**.

Also shown in FIG. **27** is a cross-sectional view of the superior facet prosthesis **300**. This embodiment of the superior facet prosthesis **300** has a flange **323** that has an opening **324** that receives the fixation element **200**. In the assembled and implanted configuration of this embodiment, the flange **323** is positioned such that its bone apposition surface **322** makes contact with the first resection surface **112**. Although not shown in this embodiment, other embodiments of the superior facet prosthesis **300** have structures (e.g., spikes) that protrude into the first resection surface **112** to help resist torsion and other anatomic loads. Protruding from the flange **323** at a given angle α , and a given distance X from the opening **324**, is the articulating component **320**. The articulating surface **321** of the facet articulating component **320** replicates the natural articular surface of the replaced facet. Once the surgeon assesses the anatomy of the superior facet **43** that is being replaced, a particular superior facet prosthesis **300** is selected that has the angle α and the distance X that best fits the anatomy of the level of vertebra, the left or right side, and the size of the patient's anatomy being replaced. Thus a kit containing various sizes and shapes of superior facet prostheses **300** is provided to the surgeon and the surgeon selects the superior facet prosthesis **300** that best suits the situation.

After the fixation element **200** and the superior facet prosthesis **300** are selected and placed, they are locked to the vertebra **100** by the enlarged head **500**. As shown in FIG. **24**, the enlarged head **500** in this embodiment has an internal connection feature **520** and a hexagonal shaped external drive feature **510** that is used to drive the enlarged head **500**

over the fixation element **200** and against the superior facet prosthesis **300**. The specific shape of the external drive feature **510** is dependent on the mating shape of the driver (not shown).

Referring to FIG. **28**, side and cross-sectional views illustrate six different embodiments of fixation elements, which are labeled A, B, C, D, E, and F. The figure shows a side view of each fixation element embodiment and a cross-sectional view of each embodiment to the right of the respective side view. To the left of the six embodiments is a representative enlarged head **500**. Embodiment A is the threaded fixation element **200** embodiment shown in FIGS. **26** and **27** and described above. Embodiments B through E are various designs of fixation elements with non-circular cross-sections. Embodiment B is a four rib cruciate design with four longitudinal fins **285** configured to resist torsion when the fixation element **200** is in the vertebra **100**. Embodiment C is an oval shaped cross-section design that is wider in the first direction **286** than the second direction **287** to resist torsion. If the width in the first direction **286** is equal to the width in the second direction **287**, the cross-section shape becomes more of a circle and bone stabilization portion **210** becomes more of a press-fit peg. Embodiment D is a square cross-section design with four approximately perpendicular sides **288**. The corners **289** of the sides **288** help to resist torsion. Embodiment E is a triangular cross-section design with three sides **291** to resist torsion. Embodiment F is an anchor-like design that is driven into the vertebra, with the wire arches or barbs **290** being compressed against the host bone and applying a radial expansion force so as to lock the structure to the bone.

Referring to FIG. **28A**, side and cross-sectional views illustrate six more different embodiments of fixation elements, which are labeled G, H, I, J, K, and L. FIG. **28A** shows a side view of each fixation element embodiment and a cross-sectional view of each embodiment to the right of the respective side view. Each embodiment has an attached or integrally formed enlarged head **500'**. Embodiment G is similar to the threaded fixation element **200** embodiment shown in FIGS. **10**, **11**, **12** and **24** and described above. Embodiments H through K are various designs of fixation elements with non-circular cross-sections. Embodiment H is a four rib cruciate design with four longitudinal fins **285** configured to resist torsion when the fixation element is in the vertebra **100**. Embodiment I is an oval shaped cross-section design that is wider in a first direction **286** than in a second direction **287** to resist torsion. If the width in the first direction **286** is equal to the width in the second direction **287**, the cross-section shape becomes more of a circle and the bone stabilization portion **210** becomes more of a press-fit peg. Embodiment J is a square cross-section design with four approximately perpendicular sides **288**. The corners **289** of the sides **288** help to resist torsion. Embodiment K is a triangular cross-section design with three sides **291** to resist torsion.

Embodiment L is an anchor-like design that is similar to Embodiment F in FIG. **28**, but with an attached or integrally formed enlarged head **500'**. As embodiment L is driven into the vertebra, wire arches or barbs **290** are compressed and apply radial expansion force against the wall of the prepared bone and into the pedicle **11**, resulting in a locking anchor.

FIG. **29** is a perspective view of a radially expanding fixation element **600**. The radially expanding fixation element **600** comprises two main elements, an expansion sleeve **620** and a central element **610** that is inside of the expansion sleeve **620**. The radially expanding fixation element **600** is placed into the vertebra **100** and then the central element **610**

is drawn outward relative to the expansion sleeve 620 resulting in radial expansion of the fixation element 600. This is shown in FIG. 30.

Referring to FIG. 30, side and bottom views illustrate the fixation element 600 of FIG. 29. As a proximal post 630 of the central element 610 is pulled axially along its longitudinal axis, and the expansion sleeve is held axially in the bone by compression fit, talons 621 on the expansion sleeve 620 are radially expanded outward by a mandrel 660 on the central element 610. The talons or fingers 621 provide both torsional and axial stability to the radially expanding fixation element 600. This provides a secure fixation element for fixation of the remaining implant components. Furthermore, expansion of the fixation element 600 may cause the fixation element 600 to center itself within the pedicle 11.

FIG. 31 is a perspective, cross-sectional view of a cross-pin element 700 engaged with the fixation element 200 to help secure the fixation element 200 both torsionally and axially. The cross-pin element 700 is columnar in shape having a distal end 710, a midsection 730 (with a length along its longitudinal axis that is longer than its transverse cross-sectional width), and a proximal post 720. The distal end 710 is shaped to penetrate through bone tissue and into a cross hole 280 formed in the fixation element 200. Instrumentation (not shown) is used to align the cross-pin element 700 with the cross-hole 280 via fixation of the instrumentation to the drive feature 212 or the cannulation 211 on the fixation element 200 and alignment of the direction of insertion of the cross-pin element 700 with the cross-hole 280. Once the cross-pin element 700 is in place in the bone and through the fixation element 200, the torsional and axial stability of the fixation element 200 is improved.

The various embodiments of the fixation element 200 described above and shown in FIG. 28 through FIG. 31 function in conjunction with the enlarged head 500 to hold the inferior facet prosthesis 400 and/or the superior facet prosthesis 300 to their respective resection surfaces 112, 113, and/or 121. Various combinations of this modular implant will be described below and shown in FIGS. 32 through 37. Although these figures illustrate the use of the fixation element 200 and the enlarged head 500 as the mechanism for securing the prostheses 300, 400 to the vertebra 100, other clamping devices such as the screw fastener 17 (FIG. 10) may be used to mount the prostheses 300, 400 to the bone. For example, the screw prostheses 17 shown in FIGS. 10 through 12 may pass through either the opening 324 (FIG. 22) in the superior facet prosthesis 300 or the opening 410 (FIG. 23) in the inferior facet prosthesis 400 or through both of these openings 324, 410. The head of the screw fastener 17 acts as the securing mechanism by pressing the inferior facet prosthesis 400 and the superior facet prosthesis 300 against their respective resection surfaces 112, 113, and/or 121.

FIGS. 32 through 37 demonstrate different combinations of assemblies of facet replacement prostheses. The basic components of the prosthesis are the fixation element 200, the superior facet prosthesis 300, the inferior facet prosthesis 400, and the enlarged head 500. However, as described above, a screw fastener 17 can replace the fixation element 200 and the enlarged head 500.

Referring to FIG. 32, a dorsal view illustrates three sequential layers of vertebrae. A top vertebra 101 is above a middle vertebra 102, and the middle vertebra 102 is above a bottom vertebra 103. Portions of some of the facets on the right side of the vertebrae are replaced by prostheses. With regard to the facet joint between the top vertebra 101 and the middle vertebra 102, an inferior facet prosthesis 401 is

articulating against a superior facet prosthesis 302 to form an artificial unilateral joint. The inferior facet of the middle vertebra 102 is replaced by an inferior facet prosthesis 402 and the superior facet of the bottom vertebra 103 is replaced by superior facet prosthesis 303. Thus, a second unilateral prosthetic joint is formed that is also on the right side and is located at the level between the middle vertebra 102 and the bottom vertebra 103. FIG. 32 demonstrates the difference in shape of the inferior facet prosthesis 401 that is implanted around the fixation element 201 without a superior facet prosthesis 300 and an inferior facet prosthesis 402 that is implanted around a fixation element 202 and over a superior facet prosthesis 302. The opening 410 (not visible) of the inferior facet prosthesis 401 on the top vertebra 101 in this assembly is offset more laterally than the opening 410 (not visible) in the inferior facet prosthesis 402 for the middle vertebra 102. This is because the fixation element 201 is implanted more laterally on the top vertebra 101 to preserve more of the superior facet since it is not replaced by a prosthesis at this level.

Referring to FIG. 33, a dorsal view illustrates the top vertebra 101 in intact form, without resection of the facets. Portions of both the superior and inferior facets on the right side of the middle vertebra 102 are replaced by a superior facet prosthesis 302 and an inferior facet prosthesis 402. Only the right superior facet of the bottom vertebra 103 is replaced (i.e., by a superior facet prosthesis 303) in FIG. 33. Thus, a hemiarthroplasty replacement has been performed on the right facet joint between the top vertebra 101 and the middle vertebra 102 and a unilateral replacement has been performed between the middle vertebra 102 and the bottom vertebra 103. The assembly shown in FIG. 33 demonstrates how the superior facet prosthesis 302 can articulate against the natural inferior facet 6 and the superior facet prosthesis 303 can articulate against the inferior facet prosthesis 402.

FIG. 34 is a dorsal view illustrating how the inferior facet prosthesis 401 can articulate against the natural superior facet 43, or the inferior facet prosthesis 402 can articulate against the superior facet prosthesis 303. The right facet joint between the top vertebra 101 and the middle vertebra 102 is a hemiarthroplasty replacement with the inferior facet replaced by the inferior facet prosthesis 401. The right facet joint between the middle vertebra 102 and the bottom vertebra 103 is a unilateral replacement with the inferior facet replaced by the inferior facet prosthesis 402 and the superior facet of the bottom vertebra 103 replaced by the superior facet prosthesis 303.

Referring to FIG. 35, a dorsal view shows another example of how the superior facet prosthesis 303 can articulate against the natural inferior facet 6 or the superior facet prosthesis 302 can articulate against the inferior facet prosthesis 401. In this assembly of the implant, the right side between the top vertebra 101 and the middle vertebra 102 is a unilateral replacement and the right side between the middle vertebra 102 and the bottom vertebra 103 is a hemiarthroplasty replacement.

Referring to FIG. 36, a dorsal view shows another example of how the inferior facet prosthesis 402 can articulate against the natural superior facet 43, or the inferior facet prosthesis 401 can articulate against the superior facet prosthesis 302. The right facet joint between the top vertebra 101 and the middle vertebra 102 is a unilateral replacement with the inferior facet of the top vertebra 101 replaced by the inferior facet prosthesis 401 and the superior facet of the middle vertebra 102 replaced by the superior facet prosthesis 302. The right facet joint between the middle vertebra 102

and the bottom vertebra **103** is a hemiarthroplasty replacement with the inferior facet replaced by the inferior facet prosthesis **402**.

Referring to FIG. **37**, a dorsal view illustrates only one level, that between the middle vertebra **102** and the bottom vertebra **103**, being replaced on the right side. The right facet joint between the middle vertebra **102** and the bottom vertebra **103** is a unilateral replacement with the inferior facet of the middle vertebra **102** replaced by the inferior facet prosthesis **402** and the superior facet of the bottom vertebra **103** replaced by the superior facet prosthesis **303**.

FIG. **38** and FIG. **39** show two embodiments of the superior facet prosthesis. In FIG. **38**, a perspective view illustrates an embodiment in which a curved superior facet prosthesis **305** with a curved articulating component **330** has a curved articulating surface **331**. This curved articulating surface **331** allows for a more distributed contact load between an inferior facet prosthesis, such as the inferior facet prosthesis **400** of FIG. **23**, and the curved articulating surface **331**. This allows slightly more flexibility in the position that the surgeon places the curved superior facet prosthesis **305** than the superior facet prosthesis **300** previously described. The articulating surface **321** of the superior facet prosthesis **300** previously described is relatively flat. The articulating surface **331** of the curved superior facet prosthesis **305** is curved. Since the bearing portion of the inferior facet prosthesis **400** is columnar, the two prostheses can be aligned on a slight mismatch and make more of an anatomic contact if the articulated surface is curved as in FIG. **38**.

Referring to FIG. **39** a perspective view illustrates a bone ingrowth feature **390** on a superior facet prosthesis **306**. The bone ingrowth feature **390** can be any surface that allows bone to grow into the implant between the first resection surface **112** of the vertebra **100** and the apposition surface **322** of the implant. Examples of bone ingrowth features **390** include porous coating of beads or meshes, electrochemically etched shapes and porous pads pressed onto the implant surface made from tantalum, titanium, cobalt chrome alloys and/or other biocompatible material such as hydroxylapatite or calcium phosphate ceramics.

Referring to FIG. **40**, a perspective view shows the inferior facet prosthesis **400**, which is formed in the general shape of a finger or talon. More particularly, the inferior facet prosthesis **400** is formed with a flange **420** on its superior side shaped to fit between the enlarged head **500** and either the superior facet prosthesis **300** or the first resection surface **112**. The flange **420** has an opening **410** that is dimensioned to allow the inferior facet prosthesis **400** to fit over the proximal post **230** of the fixation element **200** and around the shaft portion **240** of the fixation element **200**. The inferior facet prosthesis **400** also has an inferior portion **450** on the opposite side of the flange **420** that has a bone apposition side **440** that is shaped to contact the surface of the inferior facet resection surface **121** (FIG. **19**) and a joint articulation side **430** that is shaped to articulate against a natural or prosthetic superior facet.

Referring to FIG. **41**, a perspective view shows an inferior facet prosthesis **460** also formed in the general shape of a finger or talon. The inferior facet prosthesis **460** is formed with a superior end **420** having an opening **410** that is dimensioned and shaped to accept the fixation element **200**. The inferior facet prosthesis **460** is generally columnar in shape, having a curved length designed to conform to the prepared anatomy of the vertebra **100**. The inferior facet prosthesis **460** of FIG. **41** has an inferior portion **470**, which is shown opposite the superior end **420**, and slightly medi-

ally offset from the superior end **420**. This medial offset of the opening **410** relative to the inferior portion **470** allows the inferior facet prosthesis **400** to be anchored to the bone by the fixation element **200** and secured to the bone by the enlarged head **500**, or the superior facet prosthesis **300** in combination with the enlarged head **500**, at an anatomical position that allows optimal bone fixation. The inferior facet prosthesis **460** of FIG. **41** has a bone ingrowth surface **441** and a joint articulating side **430** on its inferior end **470**. In this embodiment, the bone ingrowth surface **441** is a textured structure that permits bone cells to grow into the implant surface. The shape of the bone ingrowth surface **441** can be a uniform textured surface as shown in FIG. **41**, or can be a non-uniform randomized structure such as an open cell foam structure, a porous beaded structure, a wire mesh structure, an electrochemical etched structure, or other bone ingrowth structures known in the design of orthopedic implants. The bone ingrowth surface **441** is shaped to mate with the inferior resected bone surface **121** shown in FIG. **19** and FIG. **20**.

FIG. **42** shows an exploded, perspective view of the vertebra **100** with the superior facet prosthesis **300** installed. An additional locking washer **800** is used to assist in stabilizing the attachment of the superior facet prosthesis **300** to the first resection surface **112**. The construction of the implant assembly shown in FIG. **42** is similar to that of the assembly shown in FIG. **25** with the addition of the locking washer **800** that is placed over and around the proximal post **230** of the fixation element **200**.

Referring to FIG. **43**, a perspective view shows the same implant of FIG. **42** with the enlarged head **500** locked onto the fixation element **200** and pushing the locking washer **800** against the superior facet prosthesis **300** and into the bone tissue. This added bone penetration of the locking washer **800** helps to fix the superior prosthesis **300** such that the entire assembly is more mechanically stable with respect to the vertebra **100**.

FIG. **43** shows a further step in, the assembly of the implant construct described in FIG. **42**. In FIG. **43**, the locking washer **800** is secured over the fixation element **200** and into the bone tissue by the enlarged head **500**. Although this embodiment of the locking washer **800** is only shown with the superior facet prosthesis **300**, the locking washer **800** can alternatively be used to mechanically secure the inferior facet prosthesis **400**, or the combination of the inferior facet prosthesis **400** and the superior facet prosthesis **300**. In the embodiment of the locking washer **800** shown in FIG. **42** and FIG. **43**, the locking washer **800** is placed over the superior facet prosthesis **300**. However, the locking washer **800** may be placed under the superior facet prosthesis **300**, under the inferior facet prosthesis **400** and the superior facet prosthesis **300**, or between the superior facet prosthesis **300** and the inferior facet prosthesis **400** to stabilize the implant construct.

FIG. **44** shows a perspective view of the locking washer **800**. The locking washer **800** has a body **805** with an opening **810** that is dimensioned to fit over the proximal post **230** of the fixation element **200**. The locking washer **800** also has an anti-rotation feature **820** that mates with either the superior facet prosthesis **300** or the inferior facet prosthesis **400** or a combination of both the inferior facet prosthesis **400** and the superior facet prosthesis **400**. The anti-rotation feature **820** shown in this embodiment is a flat surface, however, any feature that would rotationally constrain the locking washer **800** to the other components of the implant (such as a tab, groove, taper or other geometric shape) can be formed on the locking washer **800** as an anti-rotation

feature. The locking washer **800** also has prongs **830** that pass into the bone tissue of the vertebra **100** to help stabilize the implant construct. The prongs **830** in this embodiment of the locking washer **800** are elongated protrusions that taper to a tissue penetration tip **840**. The prongs have sidewalls **850** that provide a surface to resist torsion once the locking washer **800** penetrates the bone tissue. The prongs **830** may also be simple spikes that are either symmetrical or asymmetrical in cross-section that protrude from the locking washer body **805**. The shape and length of the locking washer prongs **830** are dependent on how the locking washer **800** is used. The prongs **830** of the locking washer **800** that holds only one of the inferior facet prosthesis **400** or the superior facet prosthesis **300** to the vertebra **100** may be shorter than prongs of a locking washer that holds both the inferior facet prosthesis **400** and the superior facet prosthesis **300** to the vertebra **100**.

FIG. **45** shows a perspective view of the superior facet prosthesis **300** and inferior facet prosthesis **400** held to the vertebra **100** by an adjunctive flexible fixation element **900** and a secondary flexible fixation element **910**. These flexible fixation elements **900** and/or **910** may be made from such constructs as suture, braided cable, wire, ribbon, and/or other constructs that have longer lengths than cross-sections and withstand larger loads in tension than in compression. The flexible fixation elements **900** and/or **910** may be manufactured from biocompatible metals, alloys such as cobalt chrome alloys, titanium alloys, stainless steel alloys, polymers, bioabsorbable materials, composites, or other materials that are biocompatible and can be formed into a flexible element structure **900** and/or **910** such as those shown in FIG. **45**. The adjunctive flexible element **900** shown in FIG. **45** is shown attached to and securing the elongated head **500**. A flexible element attachment portion **580** (e.g., including an opening) mates the flexible element **900** to the elongated head. However, the adjunctive flexible fixation element **900** may alternatively or additionally be attached to the fixation element **200**, the superior facet prosthesis **300**, the inferior facet prosthesis **400** or any combination of the above listed elements. A flexible fixation attachment portion **480** (e.g., including an opening) in the inferior facet prosthesis **400** allows the secondary flexible fixation element **910** to secure the inferior facet prostheses **400** to the vertebra **100**. The flexible fixation elements **900** and/or **910** may be secured to the vertebra **100** by physically wrapping them around anatomic features such as the posterior arch **35**, the spinous process **46**, transverse process **105**, or a combination of these anatomic features. The flexible element **900** and the secondary flexible element **910** may also be secured to the vertebra **100** by bone anchors such as anchors designed to anchor flexible fixation elements (such as suture, not shown) to bone. Suture anchors such as threaded suture anchors, barbed suture anchors, toggle suture anchors or any other means of anchoring a flexible fixation element to bone may be used to anchor the flexible fixation element **900** and/or the secondary flexible fixation element **910** to the vertebra **100**.

FIG. **46** is a dorsal view of a bilateral inferior facet prosthesis **1000**. The bilateral inferior facet prosthesis **1000** is a one-piece inferior facet prosthesis that has both a right inferior side **1040** and a left inferior side **1020** connected by a stabilizing bar **1010**. Both the right inferior side **1040** and the left inferior side **1020** are designed to fix to the top vertebra **101** at the respective inferior resection surface **121** (FIG. **19**) and at the first resection surface **112**. The bilateral inferior facet prosthesis **1000** allows replacement of both the left and the right inferior facets. In this embodiment, the

bilateral inferior facet prosthesis **1000** is placed over the left and right fixation elements **200** which extend into the bone of the top vertebra **101**. In the embodiment shown in FIG. **46**, the right inferior side **1040** is articulating against the right superior facet prosthesis **300** attached to the bottom vertebra **102**. Also in this embodiment, the left inferior side **1020** is articulating against the left natural superior facet **43** of the bottom vertebra **102**. The stabilizing bar **1010** of the bilateral inferior prosthesis **1000** is designed to stabilize the left side **1020** and the right side **1040** so that they are secure.

FIG. **47** illustrates a perspective view of a superior facet prosthesis **1100** coupled to the vertebra **3**. The superior facet prosthesis **1100** has a bone apposition surface (not shown) that has been placed on a first resection surface **1112** and an opening (not shown) in a flange **1116** that surrounds a fixation element **1110**, and coupled thereto by a locking fastener such as a castle nut **1114** or the like. The superior facet prosthesis **1100** has a superior facet articulating component **1120** with an articulating surface **1122** generally adjacent to the flange **1116**. The articulating surface **1122** is oriented in a direction that faces approximately the same direction that the original anatomic superior articulating surface faced prior to resection. This orientation of the articulating surface **1122** allows the superior facet prosthesis **1100** to function as either a hemiarthroplasty implant by articulating against a natural anatomic inferior facet **6** or as a unilateral prosthesis by articulating against an inferior facet prosthesis on the vertebra superior (cephalad) to it, such as the inferior facet prosthesis **4** shown in FIG. **5**, the inferior facet prostheses **10** shown in FIGS. **8** and **9**, and the inferior facet prosthesis **400** shown in FIG. **40**, as well as those described below.

The facet articulating component **1120** is preferably formed in the general shape of a blade or wing ear, wherein the articulating surface **1122** has a concave shape. In the embodiment shown, the articulating surface **1122** curves from an orientation generally perpendicular to the flange **1116** towards an orientation generally parallel to the flange **1116** from a distal end **1124** thereof to a proximal end **1126** thereof.

The concave shape of the articulating surface **1122** provides more tolerance for a miss-match with the natural anatomic inferior facet **6** or with the inferior facet prosthesis **4** on the vertebra superior to it. Functionally, the clearance between the concave shape of the articulating surface **1122** and the adjacent inferior facet **6** or inferior facet prosthesis **4** increases as the patient bends forward (flexion) and decreases as the patient bends backward (extension). Thus in flexion the patient has more facet movement allowing for more torsion (twisting) and lateral bending (side to side movement) than in a neutral stance. As the patient extends, the articulating members are more constrained in torsion and lateral bending. This mimics the natural anatomic constraints of the spinal facets.

FIG. **48** is a perspective view of the same construct shown in FIG. **47**, but with the implants and the vertebra **3** cut by a cross-sectioning plane **1130** placed along an axis that passes through the center of the fixation element **1110**. The cross-section plane **1130** shown cutting through the vertebra **3** and the implant of FIG. **47** is shown for visualization purposes to illustrate, using a cross-sectioned view, how the vertebra **3**, fixation element **1110**, and superior facet prosthesis **1100** engage each other.

The fixation element **1110** provides a mechanism that affixes the superior facet prosthesis **1100** to vertebra **3**. Fixation element **1110** is implanted into the interior bone space of the left pedicle **11** (FIG. **6**) on the vertebra **3** and

may or may not extend into the vertebral body of vertebra **3** to provide additional stability. The fixation element **1110** can take the form of a screw (as shown), or any of the devices shown in FIGS. **28-30**. The fixation element **1110** has a drive feature **1140**, which is an internal hex in the embodiment shown in FIG. **48**. However, any shape of drive feature that transmits the loads necessary to drive the fixation element **1110** into the vertebra **3** can be formed on a proximal post **1142** of the fixation element **1110**.

The depth of the drive feature **1140** formed in the proximal post **1142** of the fixation element **1110** is seen in the cross-sectional view of FIG. **48**. The drive feature **1140** may be an internal drive feature such as the hex socket shown in this embodiment, or an external drive feature with geometry on the periphery of the proximal post **1142** of the fixation element **1110** that engages with a corresponding internal drive feature on a driver tool (not shown). The flange **1116** of the superior facet prosthesis **1100** is secured to the fixation element **1110** by the castle nut **1114** or the like.

The flange **1116** of the superior facet prosthesis **1100** includes a coupling portion **1144** having a generally semispherical bone engaging surface **1150** on the apposition side of the superior facet prosthesis **1100** that engages a corresponding semispherical resection **1146** in the bone bed of the pedicle of vertebra **3**. The term “semispherical” relates to a surface that includes some sectorial portion of a sphere, which may be less than a hemisphere. A semispherical surface may be concave or convex. A surface that is semispherical or generally semispherical may have some deviations from a precise semispherical shape.

The semispherical resection **1146** may be said to be “inversely shaped” with respect to the coupling portion because the semispherical resection **1146** has a generally concave surface that matches the generally convex surface of the coupling portion **1144**. Although the coupling portion **1144** and the semispherical resection **1146** are semispherical in the embodiment of FIGS. **47** and **48**, in alternative embodiments, they may have a variety of other matched shapes, including three-dimensional parabolas, ellipsoids, and other regularly or irregularly curved or flat-sided shapes. Furthermore, although the coupling portion **1144** is convex and the semispherical resection **1146** is concave in the embodiment of FIGS. **47** and **48**, in alternative embodiments, the shapes may be reversed so that a coupling portion is concave and a resection is convex.

In the embodiment of FIGS. **47** and **48**, the coupling portion **1144** is integrally formed with the articulating surface **1122** of the superior facet articulating component **1120**. The coupling portion **1144** may be said to be “attached to” the articulating surface **1122** because in this application, the term “attached” is used broadly to include parts that are integrally formed with each other as well as parts that are formed separately and subsequently coupled together.

The semispherical resection **1146** in the bone bed allows for less transverse process to be resected (vs. a flat bone bed resection). The semispherical resection **1146** in the bone bed also allows for more stable support of the superior facet prosthesis **1100**, than does a flat bone bed resection, as the superior facet prosthesis **1100** is polyaxially supported in such a way as to resist any shear forces applied between the semispherical resection **1146** and the coupling portion **1144**. In this application, “polyaxial” refers to a linear or angular force or motion acting with respect to at least two perpendicular axes. The coupling portion **1144** may seat directly against the semispherical resection **1146**. In this application,

an item that “seats directly against” another is positioned to abut the other item so that surfaces of the two items are in contact with each other.

The coupling portion **1144** has a fixation element receiving aperture **1148** that can be made slightly larger than a circumferential diameter of the fixation element **1110** taken in a direction perpendicular to a longitudinal axis thereof to provide accurate polyaxial seating of the implant **1100** in relation to the resected bone bed and fixation element **1110**, as well as to provide increased tolerance for miss-match. An implant engaging end **1154** of the castle nut **1114** (or other fastener) also has a semispherical shape for engaging a semispherical nut engaging side of the coupling portion **1144** of the superior facet prosthesis **1100** at the final position of the superior facet prosthesis **1100**.

The semispherical shape of the coupling portion **1144** enables the coupling portion **1144** to move polyaxially against the semispherical resection **1146**. Movement “against” the semispherical resection refers to movement in which the coupling portion **1144** remains substantially continuously in contact with the semispherical resection **1146** so as to slide against the semispherical resection **1146**. Accordingly, during installation, a surgeon can position the coupling portion **1144** against the semispherical resection **1146** and then pivot the coupling portion **1144** along three perpendicular axes, without removing the coupling portion **1144** from the semispherical resection **1146**. The coupling portion **1144** simply rotates against the semispherical resection **1146**.

The phrase “polyaxial motion” refers to any combination of translation and/or rotation along at least two perpendicular axes. Since the coupling portion **1144** is pivotable with respect to the semispherical resection **1146** along three perpendicular axes, the coupling portion **1144** is “tri-axially pivotable” with respect to the semispherical resection **1146**.

When the superior facet prosthesis **1100** has been rotated to the proper orientation, the articulating surface **1122** is positioned for proper articulation against the corresponding inferior facet or inferior facet prosthesis. The orientation of the coupling portion **1144** may then be fixed with respect to the semispherical resection **1146** by tightening the castle nut **1114** (or another fastener) on the fixation element **1110**, thereby firmly gripping the coupling portion **1144** against the semispherical resection **1146**. Accordingly, the coupling portion **1144** is “selectively polyaxially movable” with respect to the semispherical resection **1146** because the coupling portion **1144** is movable with respect to the semispherical resection **1146** along multiple perpendicular axes until the surgeon decides to fix its disposition.

In alternative embodiments (not shown) of the invention, tri-axial pivotal movement need not be provided. Rather, a coupling portion and a corresponding resection surface may have a cylindrical, flat-sided, splined, or other shape designed to enable relative translation in addition to or in place of rotation. In place of the fixation element receiving aperture **1148**, an elongated fixation element receiving aperture may be used to accommodate relative translation between the coupling portion and a fixation element. Alternatively, a coupling portion and a resection surface may be shaped to provide relative pivotal motion along only one or two axes.

In an alternative embodiment the implant engaging end **1154** of the castle nut **1114** (or other fastener) can be deformable such that the implant engaging end **1154** conforms under pressure to the adjacent surface of the coupling portion **1144** regardless of the angle of the surface with respect to the axis of the castle nut **1114**. The deformable end

can be formed of a plastic such as polyethylene attached to the metal body of the castle nut **1114**, but is preferably formed of a substance that hardens over time, such as a fast-curing and biocompatible resin or a material that is heated prior to insertion into the patient and hardens upon cooling to the patient's body temperature. The material that hardens over time provides more stability than the deformable material, though both provide acceptable results.

FIG. **48** also shows an angled resection **1112** and corresponding angled flat **1156** on the apposition side of the superior facet prosthesis **1100** in combination with the semispherical resection **1148**.

The surfaces of the apposition side of the coupling portion **1144** and flat **1156**, as well as fixation element **1110**, may or may not include porous coatings to facilitate bone ingrowth to enhance the long-term fixation of the implant. Furthermore, such porous coatings may or may not include osteoinductive or osteoconductive substances to further enhance the bone remodeling into the porous coating.

FIG. **49** shows a perspective view of the vertebra **3** with a fixation element **1110** portion implant placed through the semispherical resection **1146** in the resection surface **1112** and into the bone of the pedicle **11**. The fixation element **1110** is aligned and placed into the pedicle **11** in a manner similar to that of other pedicle screws for posterior stabilization vertebrae fusion procedures.

In FIG. **50**, a perspective view illustrates the superior facet prosthesis **1100** in place around the fixation element **1110**. The castle nut **1114** has not yet been installed. As shown, the coupling portion **1144** has a semispherical nut engaging surface **1152**.

FIG. **51** is a top view of the superior facet prosthesis **1100**, particularly showing the curved shape of the articulating surface **1122** and the semispherical bone engaging surface **1150** of the coupling portion **1144**. Additionally, FIG. **51** more clearly illustrates the angled flat **1156** on the apposition side of the superior facet prosthesis **1100**.

FIG. **52** is an illustration of a rear view of the superior facet prosthesis **1100**. In this context, "rear" means as viewed from along the axis of the fixation element receiving aperture **1148**. FIG. **52** particularly shows the curved shape of the articulating surface **1122** and the semispherical nut engaging surface **1152** of the coupling portion **1144**.

FIG. **53A** shows a kit including a plurality of differently configured superior facet prostheses **1100**, **1162**, **1164**, **1166**, **1168**. View A is a rear view of the superior facet prostheses **1100**, **1162**, **1164**, **1166**, **1168**, while View B illustrates a perspective view of the laterally adjacent prosthesis **1100**, **1162**, **1164**, **1166**, **1168** rotated 90°. As shown, the superior facet prostheses **1100**, **1162**, **1164**, **1166**, **1168** have differing physical dimensions.

Referring again to FIG. **51**, which shows a single superior facet prosthesis **1100**, some of the physical dimensions that change between the differently sized superior facet prostheses **1100**, **1162**, **1164**, **1166**, **1168** in the kit (FIG. **53A**) are a resection angle (α), an x offset (X_1), a y offset (Y_1), a facet angle (β), and a facet articulation radius (R). Exemplary values for the foregoing will be provided below. Although the exemplary values relate primarily to L5 superior and L4 inferior, they may apply to other combinations of vertebrae in the lower back and/or the sacrum. One or more of these variables can change between the different superior facet prosthesis sizes.

P1 is the most medial and anterior point on the articulating surface **1122**. The superior pedicle axis **1170** is the axis that is colinear with the longitudinal axis of the fixation element **1110** that is positioned through the pedicle **11** nearest to the

resected superior facet (not shown). The superior pedicle axis **1170** extends through a saddle point S1, which is offset as shown, by an offset **1176**, which may be about 2 mm, from the fixation element receiving aperture **1148**. The superior pedicle axis **1170** is parallel with the direction of the y offset (Y_1). The direction of the x offset (X_1) is perpendicular to the direction of the y offset (Y_1). The direction of the x offset (X_1) is generally, but not precisely, lateral to medial with respect to the central axis of the patient's spine.

P4 is the most posterior point on the articulating surface **1122**. As shown, P4 is displaced from the saddle point S1 by an x offset (X_4) and a y offset (Y_4). The direction of the X_4 offset is parallel to that of the X_1 offset, and the direction of the Y_4 offset is parallel to that of the Y_1 offset.

The resection angle (α) for the superior facet prostheses **1100** can range from 5° to 85°. However, the optimal range of the resection angle (α) for the majority of patients will range from 30° to 70°. Thus, by way of example, a family containing nine sets of superior facet prostheses **1100** can be provided with the resection angles (α) varying in increments of 5°. Sets of superior facet prostheses **1100** would be provided with resection angles (α) at 30°, 35°, 40°, 45°, 50°, 55°, 60°, 65° and 70°.

The x offset (X_1) for the superior facet prosthesis **1100** can range from 5 mm to 30 mm. However, for the majority of patients, the x offset (X_1) will range from 10 mm to 20 mm. Therefore a family of superior facet prostheses **1100** can be provided with the x offset (X_1) varying in increments of 5 mm. Thus, sets of superior facet prostheses **1100** would be provided with x offset (X_1) at 10 mm, 12 mm, 14 mm, 16 mm, 18 mm, and 20 mm to provide superior facet prostheses **1100** that cover the statistical range for the majority of the population of patients needing superior facet prostheses **1100**.

The y offset (Y_1) for the superior facet prosthesis **1100** can range from 2 mm to 20 mm. However, for the majority of patients, the y offset (Y_1) will range from 5 mm to 15 mm. Therefore a family of superior facet prostheses **1100** can be provided with the y offset (Y_1) varying in increments of 2 mm. Thus, sets of superior facet prostheses **1100** would be provided with y offset (Y_1) at 5 mm, 7 mm, 9 mm, 11 mm, 13 mm, and 15 mm to provide superior facet prostheses **1100** that cover the statistical range for the majority of the population of patients needing superior facet prostheses **1100**.

The x offset (X_4) for the superior facet prosthesis **1100** can range from about 5 mm to about 25 mm. However, for the majority of patients, X_4 will range from about 8 mm to about 20 mm. A family of superior facet prostheses may be provided with X_4 values varying in increments of 2 mm. Thus, sets of superior facet prostheses **1100** would be provided with X_4 values of 8 mm, 10 mm, 12 mm, 14 mm, 16 mm, 18 mm, and 20 mm to provide superior facet prostheses **1100** that cover the statistical range for the majority of the population of patients needing superior facet prostheses **1100**.

The y offset (Y_4) for the superior facet prosthesis **1100** can range from about -5 to about 15 mm. However, for the majority of patients, Y_4 will range from about -2 mm to about 10 mm. A family of superior facet prostheses may be provided with Y_4 values varying in increments of 2 mm. Thus, sets of superior facet prostheses **1100** would be provided with Y_4 values of -2 mm, 0 mm, 2 mm, 4 mm, 6 mm, 8 mm, and 10 mm to provide superior facet prostheses **1100** that cover the statistical range for the majority of the population of patients needing superior facet prostheses **1100**.

The facet angle (β) for the superior facet prosthesis **1100** can range from 50° to 120° . However, for the majority of patients, the facet angle (β) will range from 60° to 100° . Therefore a family of superior facet prostheses **1100** can be provided with the facet angle (β) varying in increments of 5° . Thus, sets of superior facet prostheses **1100** would be provided with the angle (β) at 60° , 65° , 70° , 75° , 80° , 85° , 90° , 95° , and 100° to provide superior facet prostheses **1100** that cover the statistical range for the majority of the population of patients needing superior facet prostheses **1100**.

Once the surgeon assesses the anatomy of the superior facet that is being replaced, a particular superior facet prosthesis **1100** is selected that has the curvature and overall angle of the articulating surface **1122**, with respect to the flange **1116** that best fits the anatomy of the level of vertebra, the left or right side, and the size of the patient's anatomy being replaced. Thus a kit containing various sizes and shapes of superior facet prostheses **1100** is provided to the surgeon and the surgeon selects the superior facet prosthesis **1100** that best suits the situation.

According to one example, such a kit may contain nine prostheses, which may be dimensioned to provide a variety of combinations of values for α , X_1 , Y_1 , β , X_4 , Y_4 , and R , within the ranges listed above. If desired, one or more of the above-listed variables may remain constant over the entire kit. For example, R may have a constant value, such as 11.5 mm, for all members of the kit.

The prostheses **1100**, **1162**, **1164**, **1166**, **1168** of the kit of FIG. **53A** are not simply scaled up or down, but are varied according to a number of carefully selected parameters to cover the vast majority of morphologies occurring in the L5 vertebra. In a similar manner, a plurality of inferior facet prostheses adapted to replace inferior facets can be provided either as a separate kit, or in combination with the kit of FIG. **53A**. Such a kit will be shown and described in connection with FIG. **53D**.

FIGS. **53B** and **53C** illustrate top and side views, respectively, of an exemplary inferior facet prosthesis **1172**. The inferior facet prosthesis **1172** has an x offset (X), a y offset (Y), and a z offset (Z), which are illustrated in FIGS. **53B** and **53C**. As shown, the offsets X , Y , and Z run between a saddle point **S1** of the inferior facet prosthesis **1172** and a center point **C1** of the articulation surface **1174**. The saddle point **S1** of FIGS. **53B** and **53C** is defined in a manner similar to that of the superior facet prosthesis **1100** of FIG. **51**.

As shown in FIGS. **53B** and **53C**, the inferior facet prosthesis **1172** has a semispherical coupling portion similar to the coupling portion **1144** of the superior facet prosthesis **1100** introduced in the description of FIG. **47**. Accordingly, the inferior facet prosthesis **1172** provides the same type of tri-axial pivotal motion during installation as the coupling portion **1144**, as described previously. The coupling portion of the inferior facet prosthesis **1172** may also be nested in the coupling portion **1144** of the superior facet prosthesis **1100**, or vice versa, to enable independent polyaxial adjustment of the prostheses **1100**, **1170** when positioned in engagement with a single semispherical resection **1146**.

Referring to FIG. **53D**, a perspective view illustrates a kit of inferior facet prostheses **1180**, **1182**, **1184**, **1186**, **1188**, **1190**. Again, the physical dimensions can vary between the various inferior facet prostheses **1180** in the kit of FIG. **53D**. These dimensions may include an inferior resection angle ($I\alpha$), an inferior x offset (X), an inferior y offset (Y), an inferior facet angle ($I\beta$), an inferior facet articulation radius

(IR), and an inferior z offset (Z), from the center of fixation to the center of the articulation radius).

The inferior resection angle $I\alpha$ is the angle of the flat resection to be made in the vertebra, for example, the vertebra **101** illustrated in some of the preceding drawings, to serve as a backing for the articulating surface of the selected inferior facet prosthesis **1180**, **1182**, **1184**, **1186**, **1188**, or **1190**. When measured according to the coordinate system established for the superior facet prosthesis **1100**, as illustrated in FIG. **51**, the inferior resection angle $I\alpha$ may be approximately the same as the facet angle β for the superior prosthesis **1100** because the articulation surfaces **1122**, **1174** are to be positioned generally parallel to each other. Due to the clearance between the articulating surfaces **1122**, **1174** and the generally concave and convex shapes thereof, as long as the selected inferior facet prosthesis **1180**, **1182**, **1184**, **1186**, **1188**, or **1190** is placed so that the articulating surfaces **1122**, **1174** are generally parallel to each other, proper articulation may be expected to occur.

Thus, the inferior facet prosthesis **1180**, **1182**, **1184**, **1186**, **1188**, or **1190** may be dimensioned such that $I\alpha$ is nearly the same as β , and the orientation of the articulating surface **1174** may be adjusted as needed to permit the inferior facet prosthesis **1180**, **1182**, **1184**, **1186**, **1188**, or **1190** to be attached to the corresponding vertebra **101**. Accordingly, $I\alpha$ need not be determined based on measurement of the vertebra **101**, but may instead be inferred based on the selection of the superior facet prosthesis **1100**, **1162**, **1164**, **1166**, or **1168** and adjusted during installation.

The inferior facet angle $I\beta$ may be defined as the angle of the surface to which the articulating surface **1174** is most nearly parallel. Due to the shape of the inferior facet prostheses **1180**, **1182**, **1184**, **1186**, **1188**, or **1190**, this angle is the same as the inferior resection angle $I\alpha$, when measured according to the coordinate system of the superior facet prosthesis **1100** of FIG. **51**.

The inferior pedicle axis **1170** is the axis that is collinear with the longitudinal axis of the fixation element **1110** that is positioned through the pedicle **11** nearest to the resected inferior facet (not shown). This axis is parallel with the direction of the inferior y offset (Y). The direction of the inferior x offset (X) is perpendicular to the direction of the inferior y offset (Y). The direction of the inferior x offset (X) is generally lateral to medial with respect to the central axis of the patient's spine. The direction of the inferior y offset (Y) is generally anterior to posterior. The direction of the inferior z offset (Z) is generally cephalad to caudal.

The inferior x offset (X) for the inferior facet prosthesis **1180** can range from 0 mm to 20 mm. However, for the majority of patients, the inferior x offset (X) will range from 2 mm to 16 mm. Therefore a family of inferior facet prostheses **1180** can be provided with the inferior x offset (X) varying in increments of 2 mm. Thus, sets of inferior facet prostheses **1180** would be provided with inferior x offset (X) at 2 mm, 4 mm, 6 mm, 8 mm, 10 mm, 12 mm, 14 mm, and 16 mm to provide inferior facet prostheses **1180** that cover the statistical range for the majority of the population of patients needing inferior facet prostheses **1180**.

The inferior y offset (Y) for the inferior facet prosthesis **1180** can range from -15 mm to 5 mm. However, for the majority of patients, the inferior y offset (Y) will range from -12 mm to 4 mm. Therefore a family of inferior facet prostheses **1180** can be provided with the inferior y offset (Y) varying in increments of 2 mm. Thus, sets of inferior facet prostheses **1180** would be provided with inferior y offset (Y) at -12 mm, -10 mm, -8 mm, -6 mm, -4 mm, -2

mm, 0 mm, 2 mm, and 4 mm to provide inferior facet prostheses **1180** that cover the statistical range for the majority of the population of patients needing inferior facet prostheses **1180**.

The inferior facet articulation radius (IR) for the inferior facet prosthesis **1180** can range from 5 mm to 30 mm. However, for the majority of patients, the inferior facet articulation radius (IR) will range from 10 mm to 15 mm. A family of incremented inferior prostheses may be provided to cover the aforementioned range. Alternatively, the inferior facet articulation radius (IR) may be set at a given value, for example, 12 mm, and such a value may be used in substantially all cases.

The inferior z offset (Z) for the inferior facet prosthesis **1180** can range from 20 mm to 40 mm. However, for the majority of patients, the inferior z offset (Z) will range from 25 mm to 31 mm. Therefore a family of inferior facet prostheses **1180** can be provided with the inferior z offset (Z) varying in increments of 1 mm. Thus, sets of inferior facet prostheses **1180** would be provided with inferior z offset (Z) at 25 mm, 26 mm, 27 mm, 28 mm, 29 mm, 30 mm, and 31 mm to provide inferior facet prostheses **1180** that cover the statistical range for the majority of the population of patients needing inferior facet prostheses **1180**.

If desired, a kit having ten inferior facet prostheses may be assembled. Like the prostheses **1100**, **1162**, **1164**, **1166**, **1168** of the kit of FIG. **53A**, the prostheses **1180**, **1182**, **1184**, **1186**, **1188**, **1190** of FIG. **53D** are not simply scaled up or down, but are varied according to a number of carefully selected parameters to cover the vast majority of morphologies occurring in the L4 vertebra and/or other vertebrae.

The parameters of the prostheses **1100**, **1162**, **1164**, **1166**, **1168** of FIG. **53A** and/or the prostheses **1180**, **1182**, **1184**, **1186**, **1188**, **1190** of FIG. **53D** may include at least two dimensions that vary among the members of the kit independently of each other. Dimensions that vary independently of each other need not change according to any established relationship between the dimensions, but instead, one may change while the other remains the same between any two prostheses of the kit.

FIG. **53E** is a perspective view illustrating how a superior facet prosthesis **1100** and an inferior facet prosthesis **1180** fit together. The surgeon selects an inferior facet prosthesis that, in addition to most adequately meeting the anatomy of the patient, has an articulating surface adapted for articulating with the articulating surface of the superior facet prosthesis selected.

FIG. **53F** is a dorsal view of a superior facet prosthesis **1100** and an inferior facet prosthesis **1204** attached to the L5 and L4 lumbar vertebrae **102**, **101**. In FIG. **53F**, the superior facet prosthesis **1100** is attached to the left side of the L5 vertebra **102** and the inferior facet prosthesis **1204** is attached to the left L4 vertebra **101**. The two prostheses **1100**, **1204** are positioned on respective bone resections and oriented such that they articulate together through the range of motion naturally exhibited between the L4 and L5 vertebrae **1100**, **1204**. This range of motion includes flexion-extension, lateral left and right bending, torsion along a sagittal axis and combinations and coupling of all these ranges of motion.

FIG. **53F** shows the prostheses **1100**, **1204** and vertebrae **101**, **102** in a natural position. The articulation surface **1174** of the inferior prosthesis **1204** and the articulation surface **1122** of the superior prosthesis **1100** are in contact in the neutral position. However, the prostheses **1100**, **1204** are shaped to allow anatomic contact and articulation between

the inferior facet articulation surface **1174** and the superior facet articulation surface **1122** throughout various anatomic ranges of motion.

Also shown in FIG. **53F** are two planes labeled "Plane 1" and "Plane 2" that intersect along an axis (not shown) that passes through the contact areas of the superior facet articulation surface **1122** and the inferior facet articulation surface **1174**. Plane 1 is parallel to the page of FIG. **53F**, and Plane 2 is perpendicular to the page.

FIG. **53G** is a posteriolateral view of the same inferior and superior facet prostheses **1100**, **1204** with the planes shown in FIG. **53F**. In FIG. **53G**, Plane 2 is oriented parallel to the page and plane 1 is oriented perpendicular to the page. FIG. **53G** illustrates the saddle point (S1) of the vertebra **102** to which the superior facet prosthesis **1100** is coupled, and the saddle point (S2) of the vertebra **101** to which the inferior facet prosthesis **1204** is coupled. The saddle points S1, S2 are displaced from each other along an x offset (IX) parallel to the axis at which Plane 1 and Plane 2 intersect, a y offset (IY) extending perpendicular to Plane 2, or out of the page with respect to FIG. **53G**, and a z offset (IZ) extending perpendicular to Plane 1. The offsets IX, IY, and IZ may be used for implant sizing and/or selection, as will be discussed subsequently.

FIG. **53H** is a posteriolateral view showing a cross-section along Plane 2. This cross-section view cuts through the articulation surfaces **1122**, **1174** of the prostheses **1100**, **1204**, thereby showing the convex shape of the inferior articulation surface **1174** against the concave shape of the superior articulation surface **1122**.

FIG. **53H** also illustrates the cephalad and caudal ends **1250**, **1252** of the articulation surface **1122** of the superior facet prosthesis **1100**. The articulation surface **1122** has a radius of curvature **1254** generally about an axis **1256**. However, since the radius of curvature **1254** changes along the articulating surface **1122**, the axis **1256** may be the center of curvature for only a portion of the articulation surface **1122**. The radius of curvature **1254** is shown extending from the axis **1256** to the articulation surface **1122** in FIG. **53H**. Furthermore, FIG. **53H** illustrates a longitudinal axis **1258** of the spine in general. The axis **1256** is angled from the axis **1258** by an offset angle **1259**. Since the axis **1256** and the axis **1258** may not both be precisely parallel to Plane 2, the offset angle **1259** may have a component that extends out of the page with respect to the view of FIG. **53H**.

FIG. **53I** is a cephalad view showing a cross-section along Plane 1. This cross-section cuts through the articulation surfaces **1122**, **1174** of the prostheses showing the convex shape of the inferior articulation surface **1174** against the concave shape of the superior articulation surface **1122**. Each of the articulating surfaces **1122**, **1174** has a curved shape. The articulating surfaces **1122**, **1174** of the superior and inferior prostheses **1100**, **1204**, respectively, are shaped and relatively positioned to articulate against each other such that a medial-lateral range of relative motion between the first and second vertebrae **101**, **102** increases significantly with flexion (i.e., forward bending) of the spine.

A "significant" increase in the medial-lateral range of motion refers to a difference in the range of motion that approximates the natural motion of the spine to a degree sufficient to be noticeable by the patient. More precisely, a "significant" increase may refer to the existence of at least one additional millimeter of clearance between articulating surfaces of a facet joint under flexion, as compared to the same facet joint under extension. Furthermore, a "significant" increase in the medial-lateral range of motion may

refer to the existence of two additional millimeters of clearance between the articulating surfaces.

As shown in FIG. 53H, one of the articulating surfaces **1122**, **1174**, for example, the articulating surface **1122** of the superior facet prosthesis **1100**, has a cephalad end **1250** and a caudal end **1252**. The articulating surface **1122** also has a radius of curvature **1254** about an axis **1256** extending generally from the cephalad end **1250** end to the caudal end **1252**. The radius of curvature **1254** changes along the axis **1256** to provide greater clearance between the articulating surfaces **1122**, **1174** when the spine is under flexion. Similarly, the changing radius of curvature **1254** provides less clearance between the articulating surfaces **1122**, **1174** when the spine is extended.

In this embodiment, the articulating surface **1122** is shaped such that, when the superior facet prosthesis **1100** is coupled to the vertebra, the axis **1256** is significantly anteriorly inclined at the cephalad end **1250** to provide greater clearance between the articulating surfaces **1122**, **1174** when the spine is under flexion. In addition to or in the alternative to variation of the radius of curvature **1254** from the cephalad end **1250** to the caudal end **1252**, the radius of curvature **1254** could vary along a medial-lateral direction of the articulating surface.

More precisely, with brief reference to FIG. 51 again, the radius of curvature may be larger toward a medial end **1260** and a lateral end **1262** of the articulating surface **1122** than at a central portion **1264** thereof. The radius of curvature could also be substantially infinite toward the medial and lateral ends, such that the articulating surface of the superior prosthesis has a curved region **1268** proximate the central portion **1264**, a first tangent flat **1270** disposed medially of and tangent to the curved region **1268**, and a second tangent flat **1272** disposed laterally of and tangent to the curved region **1268**.

If desired, the inferior facet prosthesis may have an articulating surface with a three-dimensionally curved, generally elliptical shape. A three-dimensionally dimensionally curved, generally elliptical shape may have the appearance of a stretched spheroid or the like. Accordingly, a three-dimensionally curved, generally elliptical shape has a first cross section having a generally elliptical shape and a second cross section perpendicular to the first cross section, having a semicircular shape. Alternatively, an inferior facet prosthesis may have an articulating surface with a generally cylindrical or semispherical shape, as illustrated in connection with FIGS. 40, 53B, and 53C, for example.

According to one alternative embodiment, the articulating surface of the superior facet prosthesis may have a uniform, substantially unchanging radius of curvature. The relative medial-lateral motion between the vertebra and the adjacent vertebra may still increase significantly with flexion of the spine due to the curvature of the inferior facet prosthesis. The radius of curvature of the articulating surface of the inferior facet prosthesis may change along an axis thereof, either along the cephalad-caudal direction or along the medial-lateral direction, to provide greater clearance between the articulating surfaces when the spine is under flexion. According to yet another alternative, the variation in motion in the medial-lateral direction may be obtained, not through a variable radius of curvature, but rather, through the relative positioning of the superior and inferior facet prostheses.

Returning to FIGS. 53F, 53G, 53H, and 53I, the materials used to construct the articulating surfaces of the prostheses **1100**, **1174** may be selected from a group consisting of a polymeric material, a polymeric bearing material attached to

a metal substrate, a ceramic bearing material, a metal bearing material, and combinations thereof. A variety of surface coatings, treatments, and the like may be used to enhance the performance and/or longevity of the prostheses **1100**, **1174**.

The superior facet prosthesis **1100** may be shaped such that, when the superior facet prosthesis **1100** is coupled to the vertebra **102**, the axis **1256** is significantly anteriorly inclined from a longitudinal axis (not shown) of the spine to provide greater clearance between the articulating surfaces **1122**, **1174** when the spine is under flexion. In this application, “significantly anteriorly inclined” refers to the presence of a deliberate offset, from the longitudinal axis of the spine, that has a meaningful effect on the facet joint of which the corresponding prosthesis is a part. The offset angle **1259** between the axis **1256** and the longitudinal axis **1258** of the spine may range from about -2.5° to about 14.5° . More precisely, the offset angle **1259** may range from about 5° to about 10° . Yet more precisely, the offset angle **1259** may be about 7.25° .

Referring briefly again to FIG. 51 and FIG. 53G, one method of selecting inferior and superior facet prosthesis will be described. The appropriate prosthesis of the kit of superior facet prostheses may be selected by, for example, forming a semicircular resection centered at a position along the pedicle axis **1170** of the vertebra **102**, at a known displacement from the saddle point **S1**. Certain offsets, such as X_1 , and X_2 as shown in FIG. 51, may be measured with between the saddle point **S1** and the most medial and anterior point **P1**.

Based on X_1 and X_2 , values of the resection angle α and the facet angle β may be obtained. The values of α and β may be used to select the appropriate superior facet prosthesis of the kit by, for example, looking up the values of α and β on a lookup table or the like. The remaining dimensions of the selected superior facet prosthesis may thus be determined based on the combination of α and β .

The appropriate prosthesis of the kit of inferior facet prostheses may also be selected by making a limited number of measurements. More precisely, a semicircular resection may be formed at a position centered along the pedicle axis of the vertebra **101**, at a known displacement from the saddle point **S2**. One or more of the offsets **IX**, **IY**, and **IZ** may be measured between the resections of the saddle points **S1** and **S2**.

Based on the values of **IX**, **IY**, and/or **IZ** obtained, the values of $I\alpha$ and Z (as illustrated in FIG. 53C) are determined. The values of $I\alpha$ and Z may be used to select the appropriate inferior facet prosthesis of the kit by, for example, looking up the values of $I\alpha$ and Z on a lookup table or the like. The remaining dimensions of the selected inferior facet prosthesis may thus be determined based on the combination of $I\alpha$ and Z .

The above-described selection method is beneficial because a relatively small number of linear measurements may be made to determine which set of prostheses is most appropriate for a given patient. Ease of measurement is important because the measurements must generally be performed during surgery. Accordingly, easier, more rapid measurements enable surgery to be more rapidly and safely carried out. In alternative embodiments, different measurement schemes may be carried out, and may include different linear measurements, angular measurements, and the like. In this application, measuring the “relative positions” of bony landmarks may include measurement of linear displacements, angular displacements, or any combination thereof.

In alternative embodiments, a kit of superior and/or inferior prosthesis need not have multiple one-piece prostheses, but may instead have multiple components designed to be assembled together to provide a prosthesis having the necessary parameters. For example, each of a plurality of semispherical bone contacting portions may be connectable to any of a plurality of articulating surfaces, via a plurality of connecting members. Selecting a prosthesis may then entail selecting a bone contacting portion, an articulating surface, and a connecting member. The bone contacting portion, articulating surface, and connecting member may then be coupled together via set screws, adhesives, interference fits, or the like.

If desired, the manner in which the various components are attached together may also be adjustable to enable further adjustability of the dimensions of a selected prosthesis. Such a kit of components may also include additional components such as bearing surfaces, as described in connection with FIG. 16. As yet another alternative, a single prosthesis may be adjustably deformed, for example, through the use of a lever-operated manual press, a hydraulic press, or the like, to provide the desired dimensions prior to attachment to a patient's vertebra.

After a semispherical resection 1146 has been formed in a vertebra and the corresponding prosthesis has been selected, a flat resection, such as the first resection surface 1112 of FIG. 48, may be formed. The flat resection may be contiguous with the semispherical resection 1146, or may be separated from the semispherical resection 1146 by an expanse of unresected bone. The determination of which prosthesis to use may also indicate to the surgeon the proper placement of the flat resection to properly receive the selected prosthesis. After the flat resection has been formed, the selected prosthesis may be attached to the vertebra. The procedure may be the same as or similar to that described above for installation of the inferior and superior facet prostheses.

FIG. 54 is a dorsal view of a bilateral inferior facet prosthesis system 1200 in situ. The bilateral inferior facet prosthesis system 1200 is a multi-piece inferior and superior facet prosthesis that has both a right inferior facet prosthesis 1202 and a left inferior facet prosthesis 1204 connected by a crosslink, which may take the form of a stabilizing bar 1210. Both the right inferior facet prosthesis 1202 and the left inferior facet prosthesis 1204 are designed to be affixed to the top vertebra 101 at the respective inferior facet resection surfaces 121 (FIG. 19).

The bilateral inferior facet prostheses 1202, 1204 allow replacement of both the left and the right inferior facets. In this embodiment, the inferior prostheses are placed over left and right fixation elements 1232, 1234 that extend into the top vertebra 101. In the embodiment shown in FIG. 54, the right inferior side is articulating against a right superior facet prosthesis 1100 attached to the first resection surface 1112 (FIG. 49) of the bottom vertebra 102. Also in this embodiment, the left inferior facet prosthesis 1204 is articulating against the left natural superior facet of the bottom vertebra 102.

The stabilizing bar 1210 of the bilateral inferior prosthesis system 1200 is designed to stabilize the left inferior facet prosthesis 1204 and the right inferior facet prosthesis 1202 so that they are secure. The stabilizing bar 1210 also allows the left and right inferior facet prostheses 1204, 1202 to support each other rather than requiring stabilizing members to be coupled to the spine lamina or the resected inferior facet tissue. Further, the stabilizing bar 1210 can compress

the left and right inferior facet prostheses 1202, 1204 against the resected bone to improve bony ingrowth and apposition.

As also shown in FIG. 54, the stabilizing bar 1210 is coupled to the left and right inferior prostheses 1202, 1204 by a gripping mechanism. The gripping mechanism may include any of a variety of structures, including clips, clamps, adhesive-bonds, threaded fasteners, and the like. In the embodiment of FIG. 54, the gripping mechanism includes fore and aft flanges 1212, 1214 that engage the stabilizing bar 1210 to form a groove-and-rod joint. The fore and aft flanges 1212, 1214 are compressed together with threaded turnbuckles 1216, 1218 to pinch the stabilizing bar 1210 there between.

The pinching action of the flanges 1212, 1214 allows the distance between the left and right inferior prostheses 1202, 1204 to be adjusted to best suit the anatomy of the patient. During surgery, the surgeon would use a tool (not shown) to compress the left and right inferior prostheses 1202, 1204 to the desired positions and then tighten the turnbuckles 1216, 1218 to secure the stabilizing bar 1210.

FIG. 55 is a perspective view of the bilateral inferior facet prosthesis system 1200. The right inferior facet prosthesis 1202 includes a convex articulating surface 1220 that engages an articulating surface 1122 of the superior facet prosthesis 1100. In one embodiment, the articulating surface 1122 of the superior facet prosthesis 1100 has a concave shape (FIGS. 47, 51).

In this application, the term "convex" relates to a surface that bulges outward with a three-dimensional curvature. Accordingly, a convex surface is not just a sectorial portion of a cylinder, but rather, has some outward curvature along two perpendicular directions. A convex surface may be "semispherical," or in other words, may include some sectorial portion of a sphere, which may be less than a hemisphere. However, a convex surface need not be semispherical, but may instead have contouring that provides a portion of an oval, elliptical, parabolic, and/or irregular cross sectional shape. A convex surface also need not be curved in whole or in part, but may instead have one or more planar portions.

In this application, "concave" refers to a surface with a central portion that is recessed with respect to at least two peripheral portions positioned on either side of the central portion. A concave surface may be formed by planar regions, curves, or combinations thereof. The central portion may be recessed along only one dimension, as with a surface defined by an interior section of a cylindrical wall. Alternatively, the central portion may be recessed along two perpendicular dimensions, so that the central portion is recessed with respect to at least four peripheral portions arranged around the central portion. Accordingly, the surface may include a semispherical section, a three-dimensional parabolic or ellipsoidal section, or any other three-dimensionally curved shape.

As another alternative, the central portion of a concave surface may be recessed along one direction and distended with respect to a perpendicular direction, so that the concave surface takes on a shape similar to that of the rounded groove of a pulley that is designed to receive a rope. Like a convex surface, a concave surface need not be curved in whole or in part, but may instead have one or more planar portions.

FIG. 56 is a lateral view of the bilateral inferior facet prosthesis system 1200 and superior facet prosthesis 1100. The right inferior prosthesis 1202 includes a member 1230 upon which the flanges 1212, 1214 clamp. In the embodiment shown, the member 1230 is a ball-shaped member

1230 upon which the flanges 1212, 1214 clamp to form a ball-and-socket joint. The ball-and-socket joint and groove-and-rod joint provide multiple degrees of freedom for variable positioning of the left and right inferior prostheses 1202, 1204. More precisely, the ball-and socket joint enables tri-axial rotation, i.e., rotation about three perpendicular axes, until the flanges 1212, 1214 are pressed about the member 1230 to resist further relative rotation.

The ball-and-socket joint enables relative motion between the inferior prostheses 1202, 1204 along the anterior/posterior directions and along the cephalad/caudal directions. The groove-and-rod joint enables relative motion between the inferior prostheses 1202, 1204 along the lateral/medial directions. However, when the turnbuckles 1216, 1218 are tightened, the displacement between the ball-shaped members 1230 of the inferior prostheses 1202, 1204 becomes fixed, and the ball-shaped members 1230 are no longer freely pivotable with respect to the flanges 1212, 1214. Thus, the relative positions and orientations of the inferior prostheses 1202, 1204 may be fixed by tightening the turnbuckles 1216, 1218.

An alternative embodiment replaces the ball shaped member 1230 with a member (not shown) of differing shape and flanges adapted to engage the alternative member. Other potential shapes that allow a range of adjustability and movement between the left and right inferior prostheses 1202, 1204 and the flanges 1212, 1214 prior to clamping include, but are not limited to, columnar and annular shapes.

The ball-shaped member 1230 shown in FIG. 56 has several divots formed thereon. Upon compression of the flanges 1212, 1214, the flanges deform into the divots to provide enhanced coupling and resistance to slippage therebetween. An alternative embodiment of the ball-shaped member 1230 has circumferential or axial splines (FIG. 63) formed thereon, which “bite” into the flanges 1212, 1214. Other alternative surface features of the ball-shaped member 1230 include knurling, nubs, grooves, facets, and combinations of any of the above.

Similarly, the stabilizing bar 1210 can have surface features to enhance coupling to the flanges 1212, 1214. Exemplary surface features include longitudinal splines, knurling, divots, nubs, and grooves. Splines prevent rotation of the stabilizing bar 1210 with respect to the flanges 1212, 1214. Knurling advantageously prevents both rotation and translation of the stabilizing bar 1210 with respect to the flanges 1212, 1214.

The flanges 1212, 1214 can be formed of a material softer than that of the stabilizing bar 1210 and the ball-shaped members 1230 to further enhance coupling. Illustrative materials for the stabilizing bar 1210 and ball-shaped members 1230 are Cobalt-Chrome (Co—Cr) alloys, Titanium (Ti) and stainless steel alloys. However, other biocompatible materials such as rigid polymers including PEEK and PEAK can be formed into the shapes of the stabilization bar 1210, and/or the ball-shaped members 1230. In one alternative embodiment, the flanges 1212, 1214 are formed integrally with or rigidly attached to the left and right inferior prostheses 1202, 1204.

Referring again to FIG. 54, ends of the flanges 1212, 1214 that engage the stabilizing bar 1210 are angled towards each other. This angling avoids interference with surrounding bone and avoids interference with the superior facet or the superior facet prosthesis 1100.

With continued reference to FIG. 54, it is seen that the heads of the turnbuckles 1216, 1218 can vary in size. As shown, the turnbuckle 1216 is larger than the turnbuckle 1218. The larger head of the turnbuckle 1216 allows the

surgeon to exert more torque on the turnbuckle 1216, thereby allowing a more secure coupling of the flanges 1212, 1214 to the stabilizing bar 1210. The smaller head of the turnbuckle 1218 requires less space at the surgical site of the patient than the larger head of the turnbuckle 1216. Therefore, the surgeon can select a turnbuckle head having the desired size, weighing the benefits of more applied torque of the larger head with the reduced spatial requirements of the smaller head.

An alternative embodiment replaces the stabilizing bar 1210 with a flexible link, such as a cable of a biocompatible material. Yet another alternative embodiment includes a stabilizing bar having threaded ends. Instead of pinching flanges, the threaded ends of the stabilizing bar extend through flanges of the left and right inferior prostheses 1202, 1204. Threaded fasteners engage the threaded ends of the stabilizing bar. The threaded fasteners are then tightened to provide the desired positioning of the left and right inferior prostheses 1202, 1204. In another variation, the stabilizing bar is rotated such that the threads of the stabilizing bar engage fixed threaded portions of the flanges.

FIG. 57 is a cranial view of the bilateral inferior facet prosthesis system 1200.

FIG. 58 is a bottom in situ view of the bilateral inferior facet prosthesis system 1200 in situ.

FIG. 59 is rear view of the bilateral inferior facet prosthesis system 1200 in isolation.

FIG. 60 is a top view of the bilateral inferior facet prosthesis system 1200.

FIG. 61 is a bottom view of the bilateral inferior facet prosthesis system 1200.

FIG. 62 is a perspective view of the right inferior prosthesis 1204.

FIGS. 63 and 64 are perspective and end views, respectively, of various ball-shaped members 1240, 1242, 1244 that may be included in the inferior prostheses 1202, 1204 in place of the members 1230, the ball-shaped members 1240, 1242, 1244 having differing surface features, particularly circumferential grooves 1302, longitudinal grooves 1304, and knurling 1306.

FIG. 65 is a dorsal view of the bilateral inferior facet prosthesis system 1200, in which castle nuts 1320 are attached to the left and right fixation elements 1232, 1234 and to the fixation member 1110.

While various embodiments have been described above, it should be understood that they have been presented by way of example only, and not by way of limitation. Thus, the breadth and scope of the invention should not be limited by any of the above-described exemplary embodiments, but should be defined only in accordance with the following claims and their equivalents.

What is claimed is:

1. A surgical method comprising:

providing a first prosthesis, wherein the first prosthesis comprises an articulating component, wherein the articulating component comprises an articulating surface;

providing a second prosthesis, wherein the second prosthesis comprises an articulating component, wherein the articulating component comprises an articulating surface;

providing one or more fixation elements; and

attaching the first and second prosthesis via the one or more fixation elements into one or more vertebrae;

wherein the articulating surface of the first prosthesis articulates with respect to a superior vertebra and

35

wherein the articulating surface of the second prosthesis articulates with respect to an inferior vertebra, wherein the first prosthesis is independent from the second prosthesis, wherein the articulating surface of the first prosthesis is positioned adjacent the articulating surface of the second prosthesis, 5
 wherein the articulating surface of the first or second prosthesis having a concrete shape with a variable radius of curvature, and
 wherein a proximal end of the one or more fixation elements includes a drive feature. 10

2. The method of claim **1**, wherein the first prosthesis further comprises a flange between the fixation element and the articulating component.

3. The method of claim **2**, wherein the flange comprises an opening that surrounds the fixation element. 15

4. The method of claim **2**, wherein the flange is attached to the fixation element via a castle nut.

5. The method of claim **1**, wherein the articulating component of the first prosthesis is in the shape of a blade or wing ear. 20

6. The method of claim **1**, wherein the second prosthesis further comprises a flange between the fixation element and the articulating component.

7. The method of claim **6**, wherein the flange comprises an opening that surrounds the fixation element.

8. The method of claim **1**, wherein a proximal portion of the fixation element includes the drive feature. 25

9. The method of claim **8**, wherein the drive feature comprises an internal hex.

10. A surgical method comprising: 30
 resecting a portion of a bone member;
 providing a first prosthesis, wherein the first prosthesis comprises an articulating component, wherein the articulating component comprises an articulating surface;
 providing a second prosthesis, wherein the second prosthesis comprises an articulating component, wherein the articulating component comprises an articulating surface; 35

36

providing one or more fixation elements; and
 attaching the first and second prosthesis via the one or more fixation elements into one or more bone members;

wherein the articulating surface of the first prosthesis articulates with respect to a superior vertebra and wherein the articulating surface of the second prosthesis articulates with respect to an inferior vertebra, 5
 wherein the first prosthesis is independent from the second prosthesis, wherein the articulating surface of the first prosthesis is positioned adjacent the articulating surface of the second prosthesis, 10
 wherein the articulating surface of the first or second prosthesis having a concave shape with a variable radius of curvature, and
 wherein a proximal end of the one or more fixation elements comprises a drive feature.

11. The method of claim **10**, wherein the bone member 20 comprises a pedicle.

12. The method of claim **10**, wherein the first prosthesis further comprises a coupling portion attached to the articulating component.

13. The method of claim **12**, wherein the coupling portion comprises a bone engaging surface that engages the resected portion of the bone member. 25

14. The method of claim **10**, wherein the second prosthesis further comprises a coupling portion attached to the articulating component.

15. The method of claim **10**, wherein the first prosthesis further comprises a flange with an opening that surrounds the fixation element. 30

16. The method of claim **10**, wherein the drive feature is a hex socket.

17. The method of claim **10**, wherein at least a portion of the articulating surface of the second prosthesis is concave. 35

* * * * *