

US009597123B2

(12) **United States Patent**  
**Suh et al.**

(10) **Patent No.:** **US 9,597,123 B2**  
(45) **Date of Patent:** **\*Mar. 21, 2017**

(54) **CLIVUS PLATE**

(71) Applicant: **GLOBUS MEDICAL, INC.**, Audubon, PA (US)

(72) Inventors: **Sean Suh**, Jamesburg, NJ (US); **Roy T. Daniel**, Epalinges (CH)

(73) Assignee: **Globus Medical, Inc.**, Audubon, PA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/661,154**

(22) Filed: **Mar. 18, 2015**

(65) **Prior Publication Data**

US 2015/0190180 A1 Jul. 9, 2015

**Related U.S. Application Data**

(63) Continuation of application No. 12/511,733, filed on Jul. 29, 2009, now Pat. No. 9,011,500.

(51) **Int. Cl.**  
**A61B 17/70** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **A61B 17/7055** (2013.01); **A61B 17/7059** (2013.01)

(58) **Field of Classification Search**  
CPC ..... A61B 17/7055; A61B 17/7059  
USPC ..... 606/280-299; 623/17.16  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,127,912 A *	7/1992	Ray .....	A61B 17/7041
			606/250
5,167,664 A *	12/1992	Hodorek .....	A61B 17/8685
			606/306
6,001,130 A *	12/1999	Bryan .....	A61B 17/686
			606/247
6,328,738 B1 *	12/2001	Suddaby .....	A61B 17/1757
			606/282
6,355,036 B1 *	3/2002	Nakajima .....	A61B 17/66
			606/54
6,902,565 B2 *	6/2005	Berger .....	A61B 17/7055
			606/250
2006/0004363 A1 *	1/2006	Brockmeyer .....	A61B 17/7055
			606/281
2006/0089648 A1 *	4/2006	Masini .....	A61B 17/1615
			606/71
2006/0111782 A1 *	5/2006	Petersen .....	A61B 17/1604
			623/17.11
2007/0118129 A1 *	5/2007	Fraser .....	A61F 2/0811
			606/71
2007/0123989 A1 *	5/2007	Gfeller .....	A61B 17/562
			623/17.16
2008/0177263 A1 *	7/2008	Freedman .....	A61B 17/7059
			606/71
2009/0036894 A1 *	2/2009	Henderson, Sr. ..	A61B 17/7055
			606/60
2009/0210062 A1 *	8/2009	Thalgott .....	A61F 2/4465
			623/17.16


(Continued)

Primary Examiner — Zade Coley

(57) **ABSTRACT**

The present disclosure generally relates to a fixation device for positioning and immobilizing at least two adjacent vertebrae. In particular, in one or more embodiments, the present disclosure relates to an anterior clivus plate that immobilizes at least two adjacent vertebrae.

**9 Claims, 3 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

2009/0287258 A1 \* 11/2009 Vannemreddy .... A61B 17/7059  
606/298

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4

FIG. 5





FIG. 6




FIG. 7

**1****CLIVUS PLATE****CROSS REFERENCE TO RELATED APPLICATIONS**

This patent application is a continuation of U.S. patent application Ser. No. 12/511,733 filed on Jul. 29, 2009, which is incorporated in its entirety herein.

**FIELD OF THE INVENTION**

The present disclosure generally relates to a fixation device for positioning and immobilizing at least two adjacent vertebrae. In particular, in one or more embodiments, the present disclosure relates to an anterior clivus plate that immobilizes at least two adjacent vertebrae.

**BACKGROUND**

Bones and bony structures are susceptible to a variety of weaknesses that can affect their ability to provide support and structure. Weaknesses in bony structures may have many causes, including degenerative diseases, tumors, fractures, and dislocations. By way of example, rheumatoid arthritis may lead to weakness in the C1-C2 articulation, resulting, for example, in basilar invagination. Advances in medicine and engineering have provided doctors with a plurality of devices and techniques for alleviating or curing these weaknesses.

Typically, weaknesses in the spine are corrected by using devices that fuse one or more vertebrae together. Common devices involve plate systems that align and maintain adjacent cervical vertebrae in a desired position, with desired spacing. These devices, commonly referred to as bone fixation plating systems, typically include one or more plates and screws for aligning and holding vertebrae in a fixed position with respect to one another. In the treatment of basilar invagination, devices that fix one or more adjacent vertebrae may be used either alone or in combination with decompression. By way of example, occipitocervical fusion may be used for a rheumatoid arthritis patient with basilar invagination.

Thus, there is a need for a plate system that provides structural stability to adjacent vertebrae, for example, a plate system that provides structural stability to the C1-C2 articulation.

**SUMMARY**

An embodiment of the present invention provides an implantable device. The implantable device may comprise a bone plate having a lower surface configured to contact bone. The bone plate may comprise a base portion that comprises a body and an extended portion. The bone plate further may comprise an opening in the base portion that extends from an upper surface of the bone plate to the lower surface of the base plate. The bone plate further may comprise an angled portion located on an opposite end of the base portion from the extended portion. The angled portion may be at an angle with respect to the base portion.

The features and advantages of the present invention will be readily apparent to those skilled in the art. While numerous changes may be made by those skilled in the art, such changes are within the spirit of the invention.

**BRIEF DESCRIPTION OF THE DRAWINGS**

FIG. 1 is a front view of one embodiment of a bone plate of the present invention.

**2**

FIG. 2 is a lateral view of the embodiment of the bone plate of FIG. 1.

FIG. 3 is a front view of another embodiment of a bone plate of the present invention.

FIG. 4 is a lateral view of the embodiment of the bone plate of FIG. 3.

FIG. 5 is an isometric view of one embodiment of a bone plate of the present invention installed in a patient.

FIG. 6 is a lateral view of one embodiment of a bone plate of the present invention installed in a patient.

FIG. 7 is a perspective view one embodiment of a spacer of the present invention installed in a patient.

**DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS**

The present disclosure generally relates to a fixation device for positioning and immobilizing at least two adjacent vertebra. In particular, in one or more embodiments, the present disclosure relates to an anterior clivus plate that immobilizes at least two adjacent vertebrae.

FIGS. 1-2 illustrate a bone plate **10** in accordance with embodiments of the present invention. The bone plate **10** may be used, for example, in an anterior approach to realign and immobilize the clivus-C1-C2 for a rheumatoid arthritis patient with basilar invagination. Realignment and immobilization of the clivus-C1-C2 may be desirable, for example, for a rheumatoid arthritis patient with basilar invagination of the C2 odontoid into the foramen magnum of the occiput. As will be appreciated by those of ordinary skill in the art, with the benefit of this disclosure, the bone plate **10** may be a standalone device or may be used in conjunction with one or more additional devices and/or techniques. By way of example, the bone plate **10** may be used in combination with other decompression techniques, such as removal of the anterior C1 arch and/or C2 odontoid.

As illustrated in FIGS. 1-2, the bone plate **10** may include an upper surface **12** and a lower surface **14**, with the lower surface **14** configured to contact the bone. The bone plate **10** also may include a base portion **16** and an angled portion **18**. The bone plate **10** further may include at least one opening **20** formed in the base portion **16** that extends from the upper surface **12** to the lower surface **14**. The bone plate **10** further may include a number of holes **22** configured and adapted to receive fasteners, such as, for example, screws that will affix the bone plate **10** to the bone.

As illustrated in FIGS. 1-2, the base portion **16** may include body **24** and extended portion **26** having a width narrower than the width of the body **24**. The width of the extended portion **26** may be, for example, sufficient to accommodate at least one screw, while the width of the base portion **16** may be, for example, sufficient to accommodate at least two screws. The base portion **16** may be configured, for example, to attach to two vertebrae in the cervical region of the spine. For example, the base portion **16** may be configured to attach to the C1 and C2 vertebrae with the body **24** disposed over the C1 vertebrae and the extended portion **26** disposed over the C2 vertebrae.

The base portion **16** further may include at least one opening **20** formed in the base portion **16** that extends from the upper surface **12** to the lower surface **14** of the bone plate **10**. The surface area of the opening **20** relative to the surface area of the body **24** of the base portion **16** may be, for example, from about 25% to about 75%. The opening **20** may or may not be centered in the body **24**. In addition, the opening **20** may be symmetrical or asymmetrical. The opening **20** may be formed in the base portion **16** to allow

access, for example, to the space between adjacent bones. By way of example, the opening **20** may be formed in the base portion **16** to allow access to the space between the C1 and C2 vertebrae. By way of example, fusion of the C1 and C2 vertebrae may be observed by way of the opening **20**. In certain embodiments, graft materials and/or synthetic proteins may be placed through the opening **20** to accelerate bone growth between adjacent bones, such as between the clivus and the C1 vertebrae. While the opening **20** is illustrated as generally oval, a wide variety of other shapes may be suitable for the particular purpose, including, for example, circular, oblong, rectangular, square, and the like.

The angled portion **18** may be located on the opposite end of the base portion **16** from the extended portion **26**. In general, the angled portion **18** may be at an angle with respect to base portion **16**, for example, to allow alignment of the angled portion **18** with the clivus **28** and alignment of the base portion **16** with vertebrae in the cervical region of the spine. As illustrated in FIGS. 1-2, the angled portion **18** may be at an angle of about 90° with respect to the base portion **18**. However, other angles may also be suitable in embodiments of the present invention. By way of example, the angle of the angled portion **18** with respect to the base portion **16** may be in the range of from about 90° to about 145°. As further illustrated in FIGS. 1-2, the base portion **16** and the angled portion **18** may be rigidly connected. For example, the base portion **16** and the angled portion **18** may be formed as unitary body. In other embodiments, the base portion **16** and the angled portion **18** may be not be formed as a unitary body.

Holes **22** may be formed in the bone plate **10** that extend from the upper surface **12** to the lower surface **14**. In general, the holes **22** may be configured and adapted to receive fasteners, such as, for example, screws that will affix the bone plate **10** to the bone. As illustrated in FIGS. 1-2, two or more of the holes **22** may be formed in the angled portion **18** of the bone plate **10**. By way of example, the two or more holes **22** formed in the angled portion **18** may be configured and adapted for alignment with the clivus. In addition, two or more of the holes **22** may be formed in the body **24** of the base portion **16** and at least one of the holes **22** may be formed in the extended portion **26** of the base portion **16**. By way of example, the two or more of holes **22** formed in the body **24** may be configured and adapted for alignment with the C1 vertebra, and the hole(s) formed in the extended portion **26** may be configured and adapted for alignment with the C2 vertebra. In certain embodiments, the holes **22** formed in the base portion **16** may be configured and adapted at the C1-C2 transarticular trajectory starting from the lateral mass of the C2 vertebra to the C1 vertebra. While not illustrated, an additional hole may be formed in the bottom edge of the extended portion **26**. By way of example, this additional hole could be configured and adapted in the direction of the odontoid from the bottom edge of the extended portion **26**.

The screws that may be used to connect the bone plate **10** to the bone may be provided with a spherical head that is selectively engageable with the spherical curvature of the hole, in certain embodiments. An elongate shaft may be connected to the spherical head to allow it to penetrate the bone. Preferably, the elongate shaft may include threads that aid in fixing the bone plate **10** to the bone. It is also preferable to have a hexagonal projection to aid in gripping the screw. The length of the elongate shaft may be varied as desired. The elongate shaft of the screws for use in the holes **22** in the angled portion **18** may have a length, for example, within a range of about 4 millimeters to about 26 millime-

ters. In one embodiment, the elongate shaft of these screws may have a length of about 20 millimeters. The elongate shaft of the screws for use in the holes **22** in the base portion **16** may have a length, for example, within a range of about 40 millimeters to about 65 millimeters. However, it should be understood that lengths outside the examples disclosed herein are encompassed by embodiments of the present invention.

Embodiments of the bone plate **10** also may include at least one tool engagement feature on the sides and/or top of the plate. While not illustrated, the sides of the bone plate **10** may include, for example, depressions positioned for engaging with an instrument. By way of example, the engaging instrument may contact the bone plate **10** in the depressions thereby enabling the surgeon or user to control the bone plate **10** so that it may be placed in the proper position in the bony elements of the spine. The shape of the depressions should generally allow for the ability to have the screws positioned through a fixed or variable angle connection.

The size of the bone plate **10** may be of any appropriate size required to perform its function. By way of example, the bone plate **10** may be of sufficient length to extend across the clivus, C1 vertebra, and C2 vertebra. In certain embodiments, the length of the bone plate **10** may be within a range of about 26 millimeters to about 69 millimeters. The extended portion **26** may extend, for example, for a length of about 10 millimeters to about 26 millimeters beyond an end of the body **24** that is opposite the angled portion **19**. The width of the bone plate **10** may be, for example, within a range of about 30 millimeters to about 60 millimeters. The width of the angled portion **18** of the bone plate **10** may be, for example, within a range of about 10 millimeters to about 30 millimeters. The width of the body **24** of the base portion **16** of the bone plate **10** may be, for example, within a range of about 30 millimeters to about 60 millimeters. The width of the extended portion **26** of the base portion **16** may be, for example, within a range of about 10 millimeters to about 20 millimeters. However, it should be understood that lengths and widths outside the example ranges disclosed herein are encompassed by embodiments of the present invention.

The bone plate **10** may comprise, for example, any of a variety of biocompatible materials, including metals, ceramic materials, and polymers. Examples of biocompatible materials include titanium, aluminum, cobalt-chromium, alloys, and polyethylene. Moreover, the lower surface **14** of the bone plate **10** may include, for example, a plurality of teeth or a porous or macrotecture surface to assist in attaching the bone plate **10** to the bone.

Referring now to FIGS. 3-4, another embodiment of the base plate **10** is illustrated in accordance with embodiments of the present invention. As illustrated in FIGS. 3-4, the angled portion **18** may be pivotably connected to the base portion **16** in certain embodiments of the present invention. In the illustrated embodiment, the base plate **10** further may include a hinge **30** connecting the base portion **16** and the angled portion **18**. It should be understood that the pivoted connection (e.g., hinge **30**) between the angled portion **18** and the base portion **16** generally should allow for a variety of different angles of the angled portion **18** with respect to the base portion. By way of example, the angle of the angled portion **18** with respect to the base portion **16** may be in the range of from about 90° to about 145°. Moreover, the pivoted connection between the angled portion **18** and the base portion **16**, in certain embodiments, generally may be lockable at a predetermined angle when implanted in a

## 5

patient. For example, it may be desired to lock the angled portion 16 at angle of 90° when the base plate 10 is installed in a patient.

FIGS. 5-6 illustrate positioning of the bone plate 10 in a patient in accordance with one embodiment of the present invention. In the illustrated embodiment, a pair of vertebrae spacers 32 is shown between the C1 vertebra 34 and the C2 vertebrae 36. The vertebrae spacers 32 will be described in more detail below with respect to the embodiment of FIG. 7.

As illustrated in FIGS. 5-6, the bone plate 10 may be attached to the clivus 28, the C1 vertebra 34, and the C2 vertebra 36. The plate may be introduced superiorly at a latero-medial side of a mandible. Partial mandible removal may be required prior to positioning of the plate. In addition, a soft retractor blade may be used for retraction of the trachea and larynx. In the illustrated embodiment, the bone plate 10 may be positioned over the clivus 28, the C1 vertebra 34, and the C2 vertebra 36 with the opening 20 being positioned so that the disc space between the clivus 28 and the C1 vertebra 34 is accessible through the opening 20. In the pivotably connected embodiments, the angled portion 18 may be locked at the desired angled, for example. Clivus screws 38 may be screwed into the clivus through the holes 22 in the angled portion 18 of the bone plate 10. C1 screws 40 may be screwed into the C1 vertebra 34 through the holes in body 24 of the base portion 16 of the bone plate 10. C2 screws 42 may be screwed in the C2 vertebra 36 through the holes in the extended portion 26 of the base portion 16 of the bone plate 10. The bone plate 10 may be attached to the clivus 28, C1 vertebra 34, and C2 vertebra 36 in any suitable order. By way of example, in certain embodiments, the angled portion 18 of the bone plate may be attached to the clivus 28 prior to attachment of the base portion 16 to the C1 vertebra 34 and the C2 vertebra 36. In other embodiments, the base portion 16 of the bone plate 10 may be attached to the C1 vertebra 34 and the C2 vertebra 36 prior to attachment of the angled portion 18 to the clivus 28.

FIG. 7 illustrates a vertebrae spacer 32 in accordance with embodiments of the present invention. The vertebrae spacer 32 may be used, for example, in a posterior approach to restore space between the C1 vertebra 34 and the C2 vertebra 36. Use of the vertebrae spacer 32, for example, to realign and fuse the C1-C2 vertebrae may be desirable for a rheumatoid arthritis patient with basilar invagination of the C2 odontoid into the foramen magnum of the occiput.

As illustrated in FIG. 7, a pair of vertebrae spacers 32 may be disposed between the C1 and C2 vertebrae. In the illustrated embodiment, the vertebrae spacers 32 are shaped to fit between the superior and inferior lateral masses of the cervical spine. In another embodiment, the vertebrae spacers 32 may be u-shaped, thereby allowing for a lateral approach to restoring space between the C1 vertebra 34 and the C2 vertebra 36. In addition, each of the vertebrae spacers 32 may include one or more holes that are configured and adapted to receive fasteners, such as, for example, screws 44 that will affix the spacers 32 to the bone. The screws 32 may be a fully or partially threaded long screw. In other embodiments, the vertebrae spacers 32 may not include a hole for the fastener, but instead, the vertebrae spacers 32 may be made from a material into which a fastener can be drilled without any pre-defined trajectory. By way of example, vertebrae spacers 32 may be made from a polymeric material similar to MicroFuse™ granules, which are available from Globus Medical, Inc.

While the vertebrae spacers 32 are illustrated in FIG. 7 as a standalone device, the vertebrae spacers 32 may also be

## 6

used in combination with one or more additional devices and/or techniques. By way of example, the vertebrae spacers 32 may be used in combination with an anterior plate that bridges the C1 and C2 vertebrae, such the bone plate 10. By way of further example, the vertebrae spacers 32 may be used in combination with wiring of the C1 and C2 vertebrae with a bone graft. By way of further example, the vertebrae spacers 32 may be used in combination with a post rod and wiring of the C1 and C2 vertebrae. By way of further example, the vertebrae spacers 32 may be used in combination with a cable through the occiput. In yet another embodiment, a screw may be used to secure the C1 vertebra and the occiput.

The vertebrae spacers 32 may comprise, for example, any of a variety of biocompatible materials, including metals, ceramic materials, and polymers. Examples of biocompatible materials include titanium, stainless steel, aluminum, cobalt-chromium, alloys, and polyethylene. Moreover, surfaces of the vertebrae spacers 32 may include, for example, a plurality of teeth or a porous or macrotecture surface to assist in attaching the vertebrae spacer to the bone.

While it is apparent that the invention disclosed herein is well calculated to fulfill the objects stated above, it will be appreciated that numerous modifications and embodiments may be devised by those skilled in the art.

What is claimed is:

1. A method of stabilizing vertebrae comprising: providing an implantable system comprising:

a bone plate having a lower surface configured to contact bone, wherein the bone plate comprises:  
a base portion comprising a plate including a body and an extended portion, the body and the extended portion each including at least one hole for receiving a screw, wherein a number of holes in the body is greater than a number of holes in the extended portion, wherein the plate extends a length such that the body is attachable to a first vertebra and the extended portion is attachable to a second vertebra; an opening in the base portion that extends from an upper surface of the bone plate to the lower surface of the bone plate; and

an angled portion located on an opposite end of the base portion from the extended portion, wherein the angled portion is at an angle with respect to the base portion,  
a spacer; and

a fastener;  
wherein the base portion and the angled portion are formed as a unitary body,

wherein base portion and the angled portion are configured to be positioned to extend across a clivus, the first vertebra and the second vertebra,  
wherein the spacer includes a through hole for receiving the fastener,

positioning the spacer between a patient's C1 and C2 vertebrae; and  
fastening the fastener to affix the spacer to bone

wherein the base portion is attached to a patient's C1 and C2 vertebrae with the body disposed over the C1 vertebra and the extended portion disposed over the C2 vertebra, and wherein the angled portion is attached to the patient's clivus.

2. The method of claim 1, wherein the bone plate has a length of about 26 millimeters to about 69 millimeters.

3. The method of claim 1, wherein the opening is configured to allow access to space between the C1 vertebra and C2 vertebra.



7

4. The method of claim 1, wherein the opening has an area that is about 25% to about 75% of the body's surface area.

5. The method of claim 1, wherein the angled portion is at an angle of from about 90° to about 145° with respect to the base portion.

6. The method of claim 1, wherein the extended portion extends for a length of about 10 millimeters to about 26 millimeters beyond an end of the body that is opposite the angled portion, and wherein the extended portion has a width of about 10 millimeters to about 20 millimeters.

7. The method of claim 1, wherein the bone plate further comprise holes for receiving fasteners for affixing the bone plate to bone.

8. A method of stabilizing vertebrae, the method comprising:

positioning a bone plate having a lower surface configured to contact bone, wherein the bone plate comprises:

a base portion comprising a plate including a body and an extended portion, wherein the extended portion has a width less than the body, the body and the extended portion each including at least one hole for receiving a screw, wherein a number of holes in the body is greater than a number of holes in the extended portion, wherein the plate extends a length such that the body is attachable to a first vertebra and the extended portion is attachable to a second vertebra;

an opening in the base portion that extends from an upper surface of the bone plate to the lower surface of the bone plate;

8

an angled portion located on an opposite end of the base portion from the extended portion, wherein the angled portion is at an angle with respect to the base portion; and

positioning a spacer between a patient's C1 and C2 vertebrae,

providing a fastener through the spacer to affix the spacer to bone; and

attaching the base portion to a patient's C1 and C2 vertebrae with the body disposed over the C1 vertebra and the extended portion disposed over the C2 vertebra,

attaching the angled portion to the patient's clivus, and wherein the opening is configured to allow access to space between the patient's clivus and C1 vertebra.

9. A method of stabilizing vertebrae, the method comprising:

positioning a bone plate such that the bone plate is positioned over a patient's clivus, C1 vertebra, and C2 vertebra, wherein the bone plate comprises:

a base portion positioned over the C1 vertebra and the C2 vertebra; and

an angled portion positioned over the clivus, wherein the angled portion is at an angle with respect to the base portion;

attaching the angled portion of the bone plate to the clivus;

attaching the base portion of bone plate to the C1 vertebra; and

attaching the base portion of the bone plate to the C2 vertebra.

\* \* \* \* \*