

US009603754B2

(12) **United States Patent**  
**Tsang et al.**

(10) **Patent No.:** **US 9,603,754 B2**  
(45) **Date of Patent:** **\*Mar. 28, 2017**

(54) **DISPOSABLE ABSORBENT ARTICLE WITH  
PROFIED ABSORBENT CORE**

(71) Applicant: **DSG TECHNOLOGY HOLDINGS  
LTD**, Road Town, Tortola (VG)

(72) Inventors: **Patrick King Yu Tsang**, Derbyshire  
(GB); **Anne Smid**, Wolvega (NL);  
**Andrew C. Wright**, Derbyshire (GB);  
**Eugenio G. Varona**, Marietta, GA (US)

(73) Assignee: **DSG Technology Holdings Ltd.**, Kwai  
Chung, N.T. (HK)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 106 days.

This patent is subject to a terminal dis-  
claimer.

(21) Appl. No.: **14/163,763**

(22) Filed: **Jan. 24, 2014**

(65) **Prior Publication Data**  
US 2014/0213997 A1 Jul. 31, 2014

**Related U.S. Application Data**  
(63) Continuation of application No. 12/925,765, filed on  
Oct. 28, 2010, now Pat. No. 8,702,671.  
(Continued)

(51) **Int. Cl.**  
**A61F 13/49** (2006.01)  
**A61F 13/53** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC .. **A61F 13/49017** (2013.01); **A61F 13/49426**  
(2013.01); **A61F 13/533** (2013.01);  
(Continued)

(58) **Field of Classification Search**  
CPC ..... A61F 13/49017; A61F 13/49025; A61F  
13/49026; A61F 13/49028; A61F  
13/53436; A61F 13/535  
See application file for complete search history.

(56) **References Cited**  
**U.S. PATENT DOCUMENTS**  
4,216,773 A 8/1980 Ryan  
4,323,070 A \* 4/1982 Ternstrom ..... A61F 13/49019  
604/385.25  
(Continued)


**FOREIGN PATENT DOCUMENTS**  
EP 0238334 9/1987  
EP 0321980 9/1995  
(Continued)

**OTHER PUBLICATIONS**  
International Search Report and Written Opinion mailed Jan. 10,  
2011 (issued in PCT Application No. PCT/US2010/002858).  
(Continued)

*Primary Examiner* — Kathryn E Ditmer  
(74) *Attorney, Agent, or Firm* — Alberto Q. Amatong, Jr.;  
Amatong McCoy LLC

(57) **ABSTRACT**  
A disposable absorbent article has a central body defining a  
first waist end region including a first end edge, a second  
waist end region spaced longitudinally from the first waist  
end region and including a second end edge, and a crotch  
region positioned therebetween. An absorbent core is situ-  
ated between the end edges, and includes a plurality of  
elastics incorporated therewith such that the core is substan-  
tially laterally contracted in a narrowed region about the  
elastics. The absorbent core includes at least one end region  
that is substantially non-elasticized and has a lateral width  
substantially wider than that of the narrowed region.

**33 Claims, 19 Drawing Sheets**



**Related U.S. Application Data**

(60) Provisional application No. 61/279,923, filed on Oct. 28, 2009.

**(51) Int. Cl.**

*A61F 13/532* (2006.01)

*A61F 13/535* (2006.01)

*A61F 13/494* (2006.01)

*A61F 13/533* (2006.01)

**(52) U.S. Cl.**

CPC ..... *A61F 13/535* (2013.01); *A61F 13/5323* (2013.01); *A61F 2013/5355* (2013.01)

**(56) References Cited**

## U.S. PATENT DOCUMENTS

4,606,964 A \* 8/1986 Wideman ..... A41D 31/02  
15/229.11

4,760,764 A 8/1988 De Jonckheere et al.

4,762,521 A 8/1988 Roessler et al.

4,775,375 A \* 10/1988 Aledo ..... A61F 13/49007  
604/378

4,886,511 A \* 12/1989 Korpman ..... A61F 13/49009  
604/365

4,891,258 A 1/1990 Fahrenkrug

4,897,084 A 1/1990 Ternstrom et al.

4,911,701 A \* 3/1990 Mavinkurve ..... A61F 13/476  
604/385.25

5,295,987 A \* 3/1994 Widlund ..... A61F 13/49019  
604/358

5,527,300 A \* 6/1996 Sauer ..... A61F 13/49  
604/373

5,562,793 A 10/1996 Menard

5,597,437 A 1/1997 Lange et al.

5,681,302 A 10/1997 Melbye et al.

5,695,846 A 12/1997 Lange et al.

5,906,602 A 5/1999 Weber et al.

6,090,090 A 7/2000 Roe et al.

6,258,196 B1 7/2001 Suzuki et al.

6,437,214 B1 8/2002 Everett et al.

6,520,945 B1 \* 2/2003 Hansson ..... A61F 13/4702  
604/385.24

6,569,137 B2 5/2003 Suzuki et al.

6,736,923 B1 5/2004 Franzmann et al.

6,794,557 B1 9/2004 Klemp et al.

6,840,929 B2 1/2005 Kurata

6,913,718 B2 7/2005 Ducker et al.

7,037,299 B2 5/2006 Turi et al.

7,087,044 B2 \* 8/2006 Ohnishi ..... A61F 13/49019  
604/378

7,090,667 B2 8/2006 Fell et al.

7,780,643 B2 8/2010 Persson

8,235,961 B2 8/2012 Nakaoka et al.

2001/0014797 A1 8/2001 Suzuki et al.

2001/0039700 A1 11/2001 Krueger

2001/0047159 A1 \* 11/2001 Mizutani ..... A61F 13/47218  
604/385.23

2002/0169428 A1 11/2002 Fell et al.

2003/0083630 A1 5/2003 Fell et al.

2003/0087056 A1 5/2003 Ducker et al.

2004/0030313 A1 2/2004 Watanabe et al.

2004/0033750 A1 2/2004 Everett et al.

2004/0127871 A1 7/2004 Odorzynski et al.

2004/0193128 A1 9/2004 Klemp et al.

2004/0253892 A1 12/2004 Baker et al.

2005/0015068 A1 1/2005 Bean et al.

2005/0033254 A1 2/2005 Fell et al.

2005/0113791 A1 5/2005 Neubauer et al.

2005/0137552 A1 6/2005 Hansson et al.

2005/0143703 A1 6/2005 Persson

2006/0047257 A1 3/2006 Raidel et al.

2007/0078424 A1 4/2007 Wu et al.

2007/0135787 A1 6/2007 Raidel et al.

2007/0233029 A1 10/2007 Jansson et al.

2009/0062760 A1 3/2009 Wright et al.

2011/0130736 A1 6/2011 Tsang et al.

2013/0011601 A1 1/2013 Fenske

## FOREIGN PATENT DOCUMENTS

EP 0670153 9/1995

EP 0801551 10/1997

EP 0904755 3/1999

EP 0969786 1/2000

EP 1011579 6/2000

EP 1018981 7/2000

EP 1019002 7/2000

EP 1019003 7/2000

EP 1021152 7/2000

EP 1062929 12/2000

EP 1116479 7/2001

EP 1621168 2/2006

WO 95-34264 12/1995

WO 96-21411 7/1996

WO 98-25999 6/1998

WO 98-43575 10/1998

WO 99-08639 2/1999

WO 00-71068 11/2000

WO 01-00123 1/2001

WO 01-05440 1/2001

WO 02-45637 6/2002

WO 02-092898 11/2002

WO 03-039850 5/2003

WO 2004-060227 7/2004

WO 2005-004764 1/2005

WO 2005-055895 6/2005

WO 2005-060892 7/2005

WO 2005-063160 7/2005

WO 2006-025934 3/2006

WO 2006-059922 6/2006

WO 2007-069966 6/2007

WO 2007-070183 6/2007

WO 2009-008788 1/2009

## OTHER PUBLICATIONS

Supplementary European Search Report mailed Oct. 22, 2013  
(issued in EP Application No. 10828653.5); 9 pages.

\* cited by examiner






FIG. 1C  
(Prior Art)

FIG. 1A  
(Prior Art)






FIG. 1B  
(Prior Art)



**FIG. 2B**



**FIG. 2A**




FIG. 2C




FIG. 2D




FIG. 2E




FIG. 3A




FIG. 3B




FIG. 4B




FIG. 4A




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B






FIG. 6C




FIG. 6E




FIG. 6D






FIG. 6F




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 8A







FIG. 9A




FIG. 10A






FIG. 10B










FIG. 10F




FIG. 10D




FIG. 10G




FIG. 11A




FIG. 11D




FIG. 12




FIG. 11B




FIG. 11C




FIG. 11E




FIG. 11F






FIG. 13A




FIG. 13B




FIG. 13C




FIG. 13D




FIG. 13F




FIG. 13E




FIG. 14A

FIG. 14B

FIG. 14C




FIG. 15A




FIG. 15B




FIG. 15C






FIG. 16A




FIG. 16B

## DISPOSABLE ABSORBENT ARTICLE WITH PROFILED ABSORBENT CORE

The present application is a Continuation of U.S. patent application Ser. No. 12/925,765, filed Oct. 28, 2010 (pending), which claims the benefit of the filing date of U.S. Provisional Application Ser. No. 61/279,923 filed on Oct. 28, 2009 (which is hereby incorporated by reference for all purposes and made a part of the present disclosure).

### BACKGROUND OF THE INVENTION

The present invention relates generally to disposable absorbent articles, such as baby diapers, training pants, adult incontinence products, feminine hygiene articles, and the like. More particularly, the present invention relates to improved absorbent core components, disposable absorbent articles utilizing such absorbent core components, and a method of making or manufacturing same.

An advantageous application of the various concepts and embodiments of the present invention is one directed to baby diapers. For this reason, much of the exemplary descriptions provided herein are directed to diapers. The invention extends, of course, to applications beyond diapers.

Most absorbent articles used today as baby diapers have a configuration similar to the absorbent article **10** depicted in FIGS. **1A** and **1B**. The conventional absorbent article **10** is shown in a laid out flat position in FIG. **1A**, and in cross sectional view in FIG. **1B**. This absorbent article **10** includes an outer-side fluid impermeable backsheet **101**, a bodyside, fluid permeable nonwoven coverstock or topsheet **102**, and an absorbent construction **110** positioned between the backsheet **101** and topsheet **102**. An absorbent core **103** provides the primary component of the absorbent construction **110** and is designed and positioned to receive and retain bodily fluids. The absorbent construction **110** may also include at least one fluid management, fluid distribution and/or surge layer **104a**.

As shown in FIG. **1A**, the backsheet **101** and topsheet **102** together form or define a chassis or central body **105** of the absorbent article **10**. The central body **105** may be described as having a first longitudinal end edge **112a**, a second longitudinal end edge **112b**, and a longitudinal centerline **YY** that extends through the central body **105**, bisecting both the first and second end edges **112a**, **112b**. Left and side margins **106a**, **106b** extend from one end edge **112a** to the other end edge **112b**. Each end edge **112a**, **112b** partly defines waist regions **113a**, **113b** of the central body **105** which are generally characterized as having a lateral width significantly greater than a lateral width of a central region or crotch region **114** of the central body **105**. The waist regions **113a**, **113b** are designed to allow the absorbent article **10** to be placed about the waist of the user. In this respect, the first and second waist regions **113a**, **113b** may be described as front and rear waist regions **113a**, **113b**, respectively. The conventional absorbent article **10** further includes a fastening means **104** attached to each side of the rear waist region **113a**. The fastening means **104** are extendible and thereby, fastenable to a corresponding side of the front waist region **113b**. The fastening means **104** helps to retain the article **10** around and on the body of the user. The absorbent article **10** also includes a means for elasticizing **107** the article **10** to maintain closure and sealing around the user's legs. The elasticizing means **107** (e.g., leg cuffs and/or leg cutters) are necessarily positioned outboard of and along longitudinal side margins **106a**, **106b** of the absorbent construction **110**. Referring to FIG. **1A**, the conventional

absorbent core **110** is centrally positioned in and about the crotch region **114** of the absorbent article **10**.

Currently, most diaper cores are made from mixtures of fibers and superabsorbent particles, specifically cellulose based fibers derived from wood pulp and superabsorbent particles (SAP) derived from polyacrylic acid derivatives. An absorbent composite that is particularly suited for application in or with the disposable absorbent articles introduced herein is described in U.S. Pat. No. 6,540,853. SAP-non-woven absorbent composites of the type disclosed in this patent reference are available to the diaper manufacturing process in roll form and allow much greater freedom for the design of absorbent cores. Nevertheless, because fluff pulp-superabsorbent cores are generally provided as a continuous stream or web of absorbent material, the simpler and most cost efficient processes require the absorbent core to be maintained in a generally rectangular shape.

These cores are typically formed into rectangular shapes that are designed for incorporation into an absorbent article. The core shape, particularly its width, is maintained at dimensions that accommodate placement within a diaper corresponding with the crotch area of the user. Moreover, it is preferred in many applications for the absorbent core to take on a nearly hourglass shape. Such diaper cores are known in the art as providing a narrower crotch region that presents a better fit and comfort for the user. The hourglass shape also provides wider regions at the longitudinal ends of the core, which enhances the absorbency and leakage control capability of the diaper at those regions above the central crotch region.

FIG. **1C** illustrates another prior art disposable absorbent article **10'**. The absorbent article **10'** employs a design in which an absorbent core **110'** is reduced in width in the crotch region **114'**, but is wider at the front and rear waist regions **113a'**, **113b'**. The result is an absorbent core **110'** having a more hourglass shape. To achieve this desired hourglass shaped core, a rectangular absorbent core section is cut from a continuous web of absorbent material and shaped further, particularly in forming the narrow central region.

As known in the art, the preferred diaper assembly process is a substantially linear and efficient machine directed process that produces a high volume of packaged products. Because of the nature of the consumer product as a disposable, high frequency of use item and the abundance of competing products and alternative products (e.g., reusable cloth diapers), it is imperative to maintain the low cost of the final product. Accordingly, it is also imperative to control the complexity of the manufacturing process and to minimize steps and material waste. This presents a technical challenge to one attempting to create alternative shapes and functionalities in the conventional disposable absorbent article. For example, although an hourglass shaped diaper core is generally desirable or, in some applications, a core having distinct areas of absorbency, additional cutting or forming steps or increased material cost may make the alternative design less effective.

In any event, absorbent core configurations achieving further functionalities and/or improved fit and comfort for the sure are desirable. Caution must be exercised, however, to minimize material cost and manufacturing complexity.

### SUMMARY OF THE INVENTION

The present invention is particularly directed to achieving absorbent core configurations that easily accommodate the conventional disposable absorbent article and maintains



comfort and fit for the user. Such absorbent core configurations, and disposable absorbent articles employing same, are readily made at high volume without overburdening the manufacturing process with additional steps and material waste. In this respect, the invention provides improved hourglass or nearly hourglass shaped core constructions by providing and presenting more usable and flexible core components or core elements and incorporating these components into highly effective diapers, training pants and the like.

In one aspect, a disposable absorbent article is provided having a central body defining a first waist end region including a first longitudinal end edge, a second waist end region spaced longitudinally from the first waist end region and including a second longitudinal end edge, and a crotch region positioned therebetween. An absorbent core is situated between the end edges, and includes a first core element formed by materials imparting absorbent properties and a second core element formed by materials imparting absorbent properties. The second core element partially superimposes the first core element to form a multi-layer primary absorbent region of the absorbent core.

In another aspect, a disposable absorbent article is provided having a central body defining a first waist end region including a first end edge, a second waist end region spaced longitudinally from the first waist end region and including a second end edge, and a crotch region positioned therebetween. The absorbent core is situated between the end edges, and includes a plurality of elastics incorporated therewith such that the core is substantially laterally contracted in a narrowed region about the elastics. The absorbent core includes at least one end region that is substantially non-elasticized, and the at least one end region has a lateral width substantially wider than a lateral width of the narrowed region.

These exemplary aspects and other aspects of the invention are illustrated through FIGS. 1-14 and/or the Detailed Description provided below.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a simplified plan view illustration of a prior art disposable absorbent article having an absorbent core;

FIG. 1B is a simplified cross-sectional view illustration of a prior art disposable absorbent article of the type depicted in FIG. 1A;

FIG. 1C is simplified plan view illustration of another prior art disposable absorbent article;

FIG. 2A is a simplified plan view illustration of a disposable absorbent article, with a partial cut-out revealing an absorbent core, according to the present invention;

FIG. 2B is a perspective view illustration of the disposable absorbent article in FIG. 2A;

FIG. 2C is an isolated plan view of the absorbent core in the disposable absorbent article in FIG. 2A;

FIG. 2D is a cross sectional view illustrating a longitudinal absorbent profile of the absorbent article in FIG. 2A;

FIG. 2E is a cross sectional view illustrating a lateral absorbent profile of the absorbent article in FIG. 2A, across lines 2E-2E;

FIG. 3A is a simplified plan illustration of yet another embodiment of a disposable absorbent article according to the present invention;

FIG. 3B is an isolated perspective view of the absorbent core in the disposable absorbent article in FIG. 3A;

FIG. 4A is a simplified plan illustration of an absorbent core according to yet another embodiment of the present invention;

FIG. 4B is a perspective view of the absorbent core in FIG. 4A;

FIG. 5A is a simplified plan illustration of an absorbent core according to yet another embodiment of the present invention;

FIG. 5B is a simplified plan illustration of a disposable absorbent article employing an absorbent core, according to yet another embodiment of the present invention;

FIG. 6A is a simplified illustration of an absorbent core according to yet another embodiment of the present invention, in a pre-tensioned state;

FIG. 6B is a simplified illustration of the absorbent core in FIG. 6A in a relaxed or contracted state;

FIG. 6C is a simplified plan illustration of a disposable absorbent article, including a pair of the absorbent cores in FIG. 6A, according to the present invention;

FIG. 6D is a simplified cross-sectional view of the disposable absorbent article in FIG. 6C across line 6D--6D;

FIG. 6E is a simplified plan illustration of one variation of the absorbent core in FIG. 6A;

FIG. 6F is an isolated perspective view of an absorbent core utilizing a pair of the absorbent core elements in FIG. 6E;

FIG. 7A is a simplified plan illustration of an alternate absorbent core according to the present invention, shown in a tensioned state;

FIG. 7B is a further illustration of the absorbent core in FIG. 7A in a relaxed or contracted state;

FIG. 7C is a simplified illustration of a variation of the absorbent core in FIG. 7A, in a tensioned state, according to the present invention;

FIG. 7D is an illustration of the absorbent core in FIG. 7C in a relaxed or contracted state;

FIG. 8A is a simplified perspective view of an elasticated absorbent core, shown in a tensioned state, according to the present invention;

FIG. 8B is an exploded view of the absorbent core in FIG. 8A;

FIG. 8C is a simplified, perspective view illustration of the absorbent core in FIG. 8A, shown in a relaxed or contracted state, according to the present invention;

FIG. 8D is a simplified, perspective view of an alternative elasticated absorbent core, according to the present invention;

FIG. 8E is an exploded view of yet another variation of an elasticated absorbent core, according to the present invention;

FIG. 9A is a perspective illustration of an elasticated absorbent core, according to yet another embodiment of the present invention;

FIG. 9B is a cross-sectional view of a disposable absorbent article utilizing the absorbent core in FIG. 9A;

FIG. 10A is a simplified illustration of an absorbent core element according to yet another embodiment of the present invention;

FIG. 10B is a further illustration of the absorbent core element in FIG. 10A, shown in an applied state;

FIG. 10C is a simplified illustration of an absorbent core utilizing the absorbent core elements in FIG. 10A, as shown in an applied state;

FIG. 10D is a perspective view of an alternate absorbent core utilizing the absorbent core elements in FIG. 10A;



## 5

FIG. 10E is a simplified plan illustration of a pair of absorbent core elements utilized in an alternative absorbent core, according to the present invention;

FIG. 10F is a simplified plan perspective illustration of an absorbent core utilizing the core elements in FIG. 10E;

FIG. 10G is a simplified plan illustration of yet another alternate absorbent core, according to the present invention;

FIG. 11A is a simplified perspective illustration of an alternative absorbent core, according to the present invention;

FIG. 11B is a simplified plan illustration of a source of elasticated absorbent core element shown in a tensioned state, according to yet another embodiment of the present invention;

FIG. 11C is a simplified plan illustration of the source of absorbent core element in FIG. 11B, shown in a relaxed or contracted state;

FIG. 11D is a simplified perspective illustration of a web or source of dual absorbent core elements of the type shown in FIG. 11C;

FIG. 11E is a simplified plan illustration of a web or source of alternative absorbent core elements according to yet another embodiment of the present invention, shown in a tensioned state;

FIG. 11F is a simplified plan illustration of the web or source of absorbent core in FIG. 11E, as shown in a relaxed or contracted state;

FIG. 12 is a simplified plan illustration of yet another alternate absorbent core according to the present invention

FIG. 13A is a simplified plan illustration of an absorbent core in FIG. 12, in a pre-applied state, according to the present invention;

FIG. 13B is a simplified plan illustration of an absorbent core element according to yet another embodiment of the present invention;

FIG. 13C is a perspective, exploded view of a dual layered absorbent core utilizing the absorbent core element in FIG. 13B, according to the present invention;

FIG. 13D is a plan illustration of the absorbent core in FIG. 13C;

FIG. 13E is a plan illustration highlighting the varying absorbency in the pair of absorbent elements utilized in the absorbent core of FIG. 13D;

FIG. 13F is a plan illustration highlighting the varying absorbency in the absorbent core in FIG. 13E, according to the present invention;

FIG. 14A is a simplified plan illustration of an absorbent core element according to yet another embodiment of the present invention;

FIG. 14B is a plan illustration of the absorbent core element of FIG. 14A in a post-folding stage;

FIG. 14C is a simplified plan illustration of an alternative resultant absorbent core according to the present invention;

FIGS. 15A-C are simplified illustrations of stages in the manufacture of a core construction from a web of core elements, according to the invention; and

FIGS. 16A-B are simplified illustrations of a method of laterally elasticize a core construction of the invention.

#### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS OF THE INVENTION

The present invention is directed, in one respect, to developing and utilizing alternate absorbent core designs that maintain or improve the comfort and fit of the absorbent article while also maintaining or improving the absorbency and sealing capability of the core and the absorbent article.

## 6

Various embodiments of the invention place particular emphasis on selective placement and shaping of commercially available absorbent materials, while maintaining the cost efficiency and manufacturability of the resultant disposable absorbent article. In one aspect, emphasis is directed to selective placement and varying of absorbent materials along the longitudinal and/or lateral direction (i.e., absorbent profile) to achieve a certain functionality and efficiency. Selected absorbent profiles provide regions or expanse within the resultant core construction exhibiting advantageous or optimal absorbent or absorption capacity per unit area (sometimes referred to herein as “absorbent density” or “absorption density”). As mentioned briefly above, various aspects of the invention are particularly applicable to baby diapers (and also, training pants). For this reason, much of the description and illustrations herein are provided in the context of diapers. It will become apparent to one skilled in the art provided with the present disclosure, however, that the invention, and its various aspects, are also applicable to other disposable absorbent articles and absorbent core constructions. The detailed descriptions and illustrations of inventive embodiments should not, therefore, be construed as limiting the invention.

FIGS. 2A and 2B depict a disposable absorbent article 20, in the form of a diaper, embodying various aspects of the present invention, including an improved absorbent core construction 210 (see also FIG. 2C). The absorbent article 20 has a backsheet 201 and a topsheet that is removed in FIG. 2A to reveal the absorbent core construction 210. Together, the combination of the backsheet 201 and topsheet helps to define a chassis or central body 205 of the absorbent article 20. The central body 205 also provides a first waist end region 213a, including a first longitudinal end edge 212a (or simply, first end edge 212a), a second waist end region 213b, including a second longitudinal end edge 212b (or second end edge), and a longitudinal centerline YY extending the length of the central body 205 to bisect the first and second end edges 212a, 212b. Referring to FIG. 2A, the waist regions 213a, 213b may be identified with the portions of the absorbent article 20 and the central body 205 that are generally positioned vertically, and above and about the thighs of the user when the absorbent article 20 is worn.

The central body 205 also helps define a crotch region 214 located generally centrally between the first and second waist regions 213a, 213b and about a lateral centerline XX. As is readily known to consumers and manufacturers alike, much of the crotch region 214 is positioned generally horizontally and/or is curved upwards when the article 20 is in use. The absorbent core construction 210 is preferably centered and supported about the crotch region 214 between the backsheet 201 and topsheet 202. In such an arrangement, the absorbent construction 210 is placed in a nearly optimal position to receive bodily exudates when the absorbent article 20 is in use. The absorbent construction 210 is also described herein as having a first longitudinal end 207a (or simply, first end 207a) and a second longitudinal end 207b (or second end 207b) spaced longitudinally from the first end 212a and second end 212b of the central body 205, respectively. In some embodiments, the first and second ends 207a, 207b of the absorbent construction 210 may not be clearly defined, e.g., as an edge, line, or point. In such embodiments, the terms first and second ends are used to identify generally the margins of the absorbent construction or absorbent core spaced furthest along the longitudinal direction from the lateral centerline XX. In other embodi-



ments, the first and second ends may not be defined by one core component or element, but by multiple components or elements.

To facilitate description and illustration, the absorbent core construction **210** is often illustrated and described as consisting only of layers of absorbent materials, as illustrated in FIGS. 2A-2C. The absorbent construction **210** is, therefore, simply referred to herein as an absorbent core **210**. As will also become apparent with the descriptions of various embodiment of the invention, the absorbent core **210** may be composed of more than one independently applied core component or absorbent core element having significantly enhanced absorbent properties. In the embodiment of FIGS. 2A-2C, for example, the absorbent core **210** includes a first absorbent core element **211a** and a second absorbent core element **211b** that are applied separately during assembly. The absorbent core elements **211a**, **211b** may be constructed from any combination of nonwoven material, absorbent fibers and/or superabsorbent particles, as briefly discussed above. In this embodiment, the form of the absorbent core element **211a**, **211b** deviates from the conventional rectangular shape and takes on an irregular, non-rectangular shape that Applicants have discovered provides certain benefits or helps to achieve specific core functionalities and shapes.

As shown further in FIGS. 2B and 2C, the first and second absorbent core elements **211a**, **211b** are preferably provided in a generally trapezoidal shape. Among other things, the irregular shape of the core element **211** is conducive to forming an hourglass shaped absorbent core. In this embodiment, the first and second trapezoidal core elements **211a**, **211b** are preferably made of the same or substantially similar absorbent materials and, more preferably, originate from the same source or web of absorbent core composite to facilitate and ease manufacturing. In one aspect of the invention, the absorbent core elements **211a**, **211b** are also of the same shape, and thus, one core element may be substantially indistinguishable from another except for the position or orientation taken by the core element in the final assembly of the resultant absorbent core. This commonality and consistency facilitates manufacturing and, ultimately, helps to control product cost. For convenience, the core elements **211a**, **211b** may be referred to simply using the same reference numeral (i.e., **211**). It should be noted, however, that other applications and further embodiments may require absorbent core elements having different properties or characteristics (e.g., absorbent properties) so as to achieve a particular overall absorbent core design or capability. The absorbent core elements may also take on very different shapes and configurations, as will be illustrated in other embodiments described in this Detailed Description.

The trapezoid shaped core elements **211** may be formed and applied by any number of suitable means including vacuum forming techniques, cutting with the aid of rotary dies, and cutting using waterjet devices. Referring to the top core element **211a** in FIG. 2C, the width of each trapezoidal shaped absorbent core element **211** is tapered from a wide first end **217a** or wide section to a narrow second end **217b** or narrow section. As applied on the absorbent article **20**, each trapezoidal shaped absorbent core element **211** is preferably positioned in alignment (co-incident) with the longitudinal centerline YY of the absorbent article **20** with the wide end **217a** located proximate one of the waist regions **213** of the central body **205** and the narrow end **217b** located more inwardly. The two core elements **211** are partially, mutually overlaid or superimposed near the center of the crotch region **214** such that the overlaid narrower

sections form a dual layered section **250** (distinguished through use of cross-hatching in FIG. 2C) of the absorbent core **210**. Moreover, the two core elements **211** are positioned as substantially mirror images of one another such that the resultant absorbent core **210** is generally symmetric about the longitudinal centerline YY and about the lateral centerline XX. In this configuration, the wider ends **217a** of the core elements **211** provide, or coincide with, the longitudinal ends **217** of the resultant absorbent core **210**.

It should be noted that because the two core elements **211** are identical in shape and in substance, application and positioning of the core elements **211** within the article **20** may be simplified. The core elements **211** may be applied separately or via separate sub-processes. The core elements **211** may also come from the same source or web of absorbent material and may be applied generally together via the same sub-processes with one core element being flipped, rotated, or otherwise further manipulated to reach its ultimate position adjacent the other core element **211**.

Referring specifically to FIG. 2C, the resultant, two-element, absorbent core **210** features, therefore, a narrow mid-section or central region **M0** that is positioned proximate the lateral centerline XX in the crotch region **214**. This narrowing of the central region **M0** translates to improved user comfort as well as compatibility with the leg sealing components of the absorbent article **20**. The greater amount of absorbent material per unit of area in the narrower central region **M0** and more specifically, in the multi-layered section **250**, provides greater or increased absorbency in the portion of the absorbent article **210** that has the greatest need for it. Accordingly, the multi-layered section **250** may be referred to as the primary absorbent region **250**. Also, the resultant absorbent core **210** is wider upward from the crotch region **214** toward the front and rear longitudinal ends **207a**, **207b** (i.e., the upper absorbent regions). This increased expanse of core material increases the absorbent coverage in these upper regions of the absorbent article **210**. The extra core material also helps to seal and prevent leakage in and from the waist regions **213** of the article **210**.

To facilitate the present description, the absorbent core **20** may be described as having a narrow central region or midsection **M0**, and a pair of end regions **E1**, **E2** on opposite sides of the central region **M0**. The locations or bordering of these regions are only generally defined (for purposes of the present description). In various embodiments, the primary absorbent region **250** is situated substantially in the central region **M0**, but may extend longitudinally into the end regions **E1**, **E2**. The end regions **E1**, **E2** may also be referred to as upper absorbent regions as these regions are generally positioned above the central region **M0** when the absorbent article is in use.

The graphical illustration of FIG. 2D illustrates the increase and decrease in the concentration of absorbent material in the absorbent article **20** along the longitudinal centerline YY from one waist end region **213a** to the other waist end region **213b**. This graphical illustration represents, therefore, the longitudinal absorbency profile of the article **20** from one end **212a** to the other end **212b**. The illustration also helps describe profiled cores according to the present invention as an absorbent construction having marked variations in absorbency (absorbent capacity per unit area (e.g., square inch) or absorbent densities) along specified directions or at specified locations on the central body **205**. As explained above, the greater concentration of absorbent material provided by the two layers of core elements **211a**, **211b** provide high absorbency at the crotch region **214** of the absorbent article **20**. The absorbent article **210** also exhibits



absorbency per unit area near the waist regions **213a**, **213b** as imparted by the end regions **E1**, **E2** of the core **210**, although it is significantly decreased from that which characterizes the primary absorbent region **250**. Nevertheless, the core elements **211** extend sufficiently upward into the waist regions **213a**, **213b** to expand and extend the absorbent coverage of the article **210**. Beyond the absorbent core **210**, the absorbency (and absorbency per unit area) of the disposable absorbent article **20** drops off significantly as expected. FIG. 2E illustrates the lateral absorbency profile of the core **210** along a lateral direction demarcated by the line LL-LL in FIG. 2A. This line LL-LL is actually located below the lateral centerline XX. The lateral absorbent profile illustrates a relatively narrow absorbent region with relatively high absorbency and/or absorbent density.

In the descriptions provided herein, the inventive core may be described as a profiled core. In the present context, this description relates to the varying absorbency imparted upon the absorbent article along specific directions or at specified locations on the central body. It also refers to the varying physical contour of the resultant absorbent core—which is illustrated by the absorbent profiles in FIGS. 2D and 2E. It should be noted that in some applications, variation in absorbent densities may be achieved by using core materials of different absorbent properties in lieu of, or in addition to core materials of substantially similar absorbent properties.

In developing the various configurations provided herein, optimal use of absorbent materials is an important design consideration. A balance is often struck between achieving high absorbency in the article and maintaining low material cost. This also requires controlling over use and over concentration of absorbent material so as to prevent lumps from forming or cause components to impinge upon the user's skin, thereby compromising the comfort of the user. Without care, an irregular core profile may also negatively impact the shape of the absorbent core when worn and lead to stressing the leakage prevention mechanisms of the article (e.g., elasticized leg cuffs and leg gathers). Thus, aside from cost considerations, the absorbent profiles proposed are not simply the result of laying out as much absorbent material as possible.

As discussed above, the design considerations accounted for also include manufacturability and ease of assembly. Very often these attributes translates to cost efficiency in the resultant product, as well as increased quality of construction. In this respect, the present invention achieves improved product designs, including configurations that achieve specific absorbent properties and/or specific shapes without sacrificing or burdening manufacturability. One feature of the invention that helps achieve these objectives is the use of substantially identical core elements to create various core shapes, including irregular shapes (e.g., non-rectangular), and absorbent profiles. The selection of core elements also provides design and manufacturing flexibility as FIG. 2C helps to illustrate.

As an example, the inventive configuration and selection of core elements **211** allow the manufacturer of the absorbent article **20** to readily vary or fine tune the shape of the absorbent core **210** and disposable absorbent article **20** by adjusting the distance X between the longitudinal end **217a** of the first core element **211a** and the longitudinal end **217b** of the second core element **211b**. In this way, the overall length L of the absorbent core **210** may be adjusted to accommodate different size absorbent articles. Such a linear adjustment may be easily made in a substantially linear assembly process of the absorbent core. This adjustment also

allows desired lateral or longitudinal absorbent profiles to be achieved, including enlarging or reducing the primary absorbent region. The manufacturer can also make further modifications to the absorbent profile and the overall dimensions of the core by adjusting the length C and widths A and B of the individual absorbent core elements.

FIGS. 3A and 3B illustrates an alternately profiled absorbent core **310** utilized in an absorbent article **30** and composed of identical absorbent core elements **311a**, **311b** having an alternate shape (wherein like elements are referred to using like elements). In this embodiment, a first, rectangular shaped absorbent core element **311a** is partially overlaid or superimposed over at least a second rectangular shaped absorbent core element **311b** to produce an absorbent core **310** of a different shape and absorbent profile. Key features of this embodiment again include a lateral narrowing of a mid section M0 of the absorbent core **310** to achieve a near hourglass shape. The longitudinal position of this narrow mid section M0 can be varied by displacing one of the rectangular shaped core elements **311** laterally relative to the second rectangular shaped core element **311**. The inventive absorbent core **310** also provides laterally wider upper or end regions **E1**, **E2** that saddle the mid section M0.

The overlay of two core elements **311** also forms a dual layered primary absorbent region **350** in the central region M0, which displays a relatively greater concentration of absorbent material. In this embodiment, the primary absorbent region **350** extends all the way through the length of the end regions **E1**, **E2**.

FIGS. 4A and 4B depict an alternative absorbent core **410** that is a further variation of the absorbent cores **210**, **310** described above. The absorbent core **410** is produced from two non-rectangular, irregularly shaped absorbent core elements **411a**, **411b** but, in this embodiment, each core element **411** has a parallelogram shape. These core elements **411a**, **411b** are superimposed to produce a longitudinally and laterally symmetric absorbent core **410** (symmetric about the longitudinal and lateral centerlines YY, XX). With this configuration, the longitudinal ends **407a**, **407b** of the absorbent core **410** are defined by a single straight edge (spaced in parallel relation with the end edge of the absorbent article (not shown)). Thus, the end or upper absorbent regions **E1**, **E2** of the core **410** are fairly uniform, and less likely to lump, impinge, pinch, or provide discomfort to the user. As with the absorbent core of FIGS. 3A, 3B, the absorbent core **410** features a primary absorbent region **450** that can extend from the central region M0 into the upper absorbent regions **E1**, **E2**.

In yet another aspect of the present invention, an absorbent core **510** is achieved utilizing a pair of non-symmetrical absorbent core elements **511a**, **511b** as shown in FIGS. 5A and 5B. The core elements **511a**, **511b** are provided in either rectangular or parallelogram shape and together form an absorbent core **510**. In this embodiment, the two core elements **511a**, **511b** are superimposed proximate mutually adjacent ends **517a** rather than centrally. This overlay produces a generally kite shaped primary absorbent region **550** suitable for incorporation into a disposable absorbent article **50** such as that shown in FIG. 5B. Thus, the resultant absorbent core **510** is characterized as having greater concentration of absorbent material at one end region **E1** (also greater absorbent density), and a lower concentration but wider expanse of absorbent material at an opposite end region **E2**, and a longitudinal absorbent profile reflecting same. In between, the absorbent core **510** still exhibits a narrow central region M0.



## 11

It is anticipated that an absorbent core of this type may be utilized in a baby diaper construction with the end region including the primary absorbent region being presented to the front of the wearer, thereby positioning a region of high absorbency to receive liquid exudates, and a wider absorbent region presented to the back of the wearer to provide better containment of solid exudates. In addition, the two absorbent core elements **511a**, **511b** may be arranged to present a v-shaped recess in the back of the diaper, thereby providing a containment pocket for feces collection.

In alternative embodiments, the core elements may be modified with angled edges (as longitudinal ends). The edges of adjacent core elements can cooperate to present a straight edge at the front or rear ends of the core, in a manner similar to that provided in the parallelogram shaped core elements **411** of FIGS. **4A**, **4B**.

FIGS. **6** through **9** illustrate alternative absorbent articles embodying various aspects of the invention, including absorbent cores of advantageous designs. More particularly, these alternative embodiments illustrate another mode of achieving advantageously shaped and advantageously profiled absorbent cores, and disposable absorbent articles with distinct absorbent profiles. In one aspect of the present invention, elastic materials are attached to, or otherwise incorporated into, the absorbent core element(s) to generate inventive absorbent core constructions.

Referring first to FIG. **6A**, an absorbent core element **611** is initially provided having a generally rectangular shape and a pair of longitudinally spaced apart ends **617a**, **617b**. A suitable, tensioned elastomeric material **619** is selectively applied on or within the absorbent core element **611** at various points or locations near the first end **617a**. The elastomeric material **619** is oriented lengthwise in the lateral direction. Suitable elastomeric materials include, but are not limited to, elastic strands, elastic films or elastomeric adhesives. As shown in FIG. **6A**, the elastomeric material **619** is preferably an elongated elastic element, such as an elastic strand. The applied elastomeric materials are referred to simply as elastic elements or elastics. The selected attachment points preferably make for a predetermined pattern that describes multiple, laterally-oriented rows of elastics **619** at even pitch, as shown in FIG. **6A**. Accordingly, the applied pre-tensioned elastics impart an elastic force in the generally lateral direction across the absorbent core element **611**.

Preferably, the rows of elastics **619** are concentrated in a region **670** proximate one longitudinal end **617a** of the core element **611** (i.e., a substantially elasticated end region **670**). While this longitudinal end region **670** of the core element **611** is substantially incorporated with elastics **619**, the opposite end region **672** is substantially clear of elastomeric elements (i.e., non-elasticated). FIG. **6B** depicts the absorbent core element **611** in a relaxed state. Releasing the elastics **619** from tension allows the elasticated region **670** to substantially contract and narrow (relative to other regions), and the rectangular shaped core element **611** to deform to near trapezoidal shape.

FIG. **6C** depicts an absorbent article **60** employing a pair of the absorbent core elements **611** and a resultant absorbent core **610** having an advantageously hourglass shape and unique absorbent profile. The absorbent profile of the core element **611** reveals higher concentration of absorbent material in the area of the elasticated core region **670** due to the contracted core material. A first absorbent core element **611a** is positioned over a second, substantially similar absorbent core element **611b** to define a narrow, substantially elasticated central region **M0** and wider generally non-elasticated end regions **E1**, **E2**. As previous embodiments have dem-

## 12

onstrated, the inventive configuration also provides a greater concentration of absorbent material (greater absorbent density) in the central region **M0** of the absorbent core **60** than in the end regions **E1**, **E2**. The elasticated core region **670** defined in this embodiment substantially corresponds with the primary absorbent region **650** described in previous embodiments. The primary absorbent region **650** is therefore, defined by both higher absorbent capacity per unit area as imparted by the multiple layers of absorbent material and high contraction due to the high concentration of elastics **619**.

The cross-sectional view of FIG. **6D** reveals a central region **M0** not only composed of multiple core layers, but of layers of core material that are more highly concentrated. The contraction of the core elements **611a**, **611b** creates undulations in each core element **611a**, **611b**, producing yet another unique physical profile and unique absorbent profile. Generally, the contraction of the core material produces a core element of greater average thickness. Further, the stacking of one core element over another core element with undulations produces a thicker and larger (in volume) absorbent core. The core includes voids or spaces **S0** between the core elements **611a**, **611b** and between the top core element **611a** and the topsheet **602** (or A/D layer). The contracted core material also provides channels **C1** that function as acquisition and distribution channels for the absorbent core **610** and ridges **P** alongside the channels **C1**. The channels **C1** help capture liquid exudates, for example, and disperse the liquids over a greater area of core material. FIG. **6D** also shows an additional, supplemental layer **639** of a non-woven or core material below each of the core elements **611a**, **611b**. The supplemental layer **634** is provided to promote and provide adhesion between the core material and the elastics **619**. In the cross-sectional view of FIG. **6D**, the supplemental layer **639** resides below the elastics **619**.

FIGS. **6E** and **6F** illustrate a variation of the inventive absorbent core elements in FIGS. **6A** to **6D** (wherein like elements are identified using like reference numerals). In one embodiment, the tension placed on the elastics **619'** during attachment to the absorbent core element **611'** is increased. When the elastics **619'** are released, the core material contracts even more to produce an elasticated region **670'** having an overall area that is reduced relative to that in the embodiment shown in FIGS. **6A** to **6D**. A differently shaped elasticated region **670'** may be produced by selecting a different type of elastic or an elastic of different shape and length. A different shape, particularly the curvature, may also be created by changing the tension denier of the elastic strand, changing the number of or the pitch between elastics, and/or by altering the position of the elastic(s) (e.g., varying the distance between successive elastics). In this embodiment, the resulting absorbent core **610'** has a narrower and more pronounced central region **M0**. The central region **M0** takes on a more curved or concave shape at the transition between the elasticated region **670'** and the end regions **E1**, **E2**.

FIGS. **7A** and **7B** depict yet a further embodiment of the present invention, wherein an absorbent core is provided with a single core element **711**. An alternatively shaped absorbent core or core element **711** is produced via the selective placement and attachment of elastic elements **719** within the core material, beneath the core element, or on top of the core element. By selective placement of elastic strand or other elastomeric materials, the relative width of the core element **711** in these areas is reduced, as discussed above. FIG. **7A** shows one such embodiment of this core, with pre-tensioned, extended elastic strands **719** secured to the



absorbent core element **711** in a central elasticated region **770**. When tension is released, the width of the absorbent core element **711** is substantially reduced as shown in FIG. 7B, creating a narrow elasticated material region **M0**.

FIGS. 7C and 7D depict yet another embodiment in which an absorbent core element **711** provides an absorbent core with an elasticated central region **M0**. Elastics **719** are applied to the core element **711** in the same laterally extended fashion. The elastics in this embodiment are arranged in rows of varying pitch, however, to achieve a specific shape. Preferably, the elastics **719** near the lateral centerline **XX** are spaced closer together, while the elastics **719** farther away from center are spaced further apart. The area near the lateral centerline **XX** is, therefore, more elasticated than areas beyond. This results in an absorbent core **711** having a more gradually narrowed or curved central region **M0**. By varying the pitch in this manner, the curved shaped of the narrowed central region may be adjusted further.

FIGS. 8A through 8E illustrates yet another aspect of the invention, in which elastic elements **819** are introduced between, above, within or below multiple layers of absorbent core elements. FIG. 8A provides a simplified illustration of an absorbent core construction **810**. Pre-tensioned elastic elements **819** are first disposed beneath a first elongated absorbent core element **811a** and attached thereto. The elastics **819** in this exemplary embodiment are centrally located respective of the first core element **811a**, and are spaced at a consistent pitch. The Figures show elastic strands employed as the elastics **819**; however, elastic materials such as elastic film, elastic adhesive or elastic nonwovens may be used to achieve similar effects.

Referring also to the view in FIG. 8B, a second absorbent core element **811b** is provided and then deployed on top of the first absorbent core element **811a**. The generally rectangular second absorbent element **811b** is cut appropriately shorter (and perhaps, reduced in width also) to correspond with the dimensions of the desired primary absorbent region and/or desired absorbent profile. The elastics **819** and the dual layer of absorbent core elements **811a**, **811b** are bonded using any suitable bonding means, such as hot melt adhesives, ultrasonic bonding or through the fusing of thermoplastic fibers by heat. It is a desirable, but not necessary, feature of this invention that at least one of the absorbent core elements **811** (i.e., the top absorbent core element **811b** in FIGS. 8A, 8B) is slit or cut at multiple locations (producing slits **873**). As shown in the Figures, the top absorbent core element **811b** preferably contains multiple slits **873**. The slits **873** are generally aligned in the lateral direction and, in this embodiment, staggered in rows of two and three slits. The slits **873** preferably penetrate entirely through each layer of absorbent material, and in some embodiments may have a length of between 1-50 mm. It is envisaged that the invention also allows for further layers of slit or unslit absorbent material (core elements), elastic materials, fluid handling materials such as acquisition layers or surge layers, tissue layers, nonwoven layers or film.

Both FIGS. 8A and 8B depict the shape of the absorbent core **810** prior to release of the elastics **819** from tension. FIG. 8C depicts the absorbent core **810** after the elastics **819** are released. The width of the absorbent core **810** in an elasticated central region **M0** is substantially reduced, particularly more so around the lateral centerline **XX** where the elastics **819** are gathered. Further, the laterally aligned slits **873** disposed on the top core element **811b** are caused to open up and create voids **875** within the core element **811b**. These voids **875** provide passages that facilitate flow of fluid

into lower levels of the core construction (e.g., the first core element **811a**) of the absorbent core **810**.

FIG. 8D depicts an alternative absorbent core **810'** that achieves a slightly different shape by arranging the rows of elastics **819** by arranging the elastics **819** at a higher pitch (than in FIGS. 8A, 8B). This arrangement produces a smoother curved central region **M0**. FIG. 8E illustrates a variation of the core construction described in FIGS. 8A-8C. In this alternative absorbent core **810''**, the pre-tensioned elastic elements **819** are disposed between the two absorbent core layers **811a**, **811b** (rather than below the bottom core element **811a**). As previously discussed, it is possible for the elastics to be distributed, above, below, within or between any of the layers of the absorbent core. In some embodiments, the elastics are preferably positioned within or between layers to promote adhesion.

FIG. 9A illustrates yet a further aspect of the present invention. The elasticized, accordion-shaped absorbent core construction **910** is produced using two absorbent core elements **911a**, **911b** and elastic elements **919**. Notably, the longitudinal centerline **YY** or longitudinal direction of the absorbent article is identified as being perpendicular to the elastics **919**. FIG. 9B is a lateral cross-sectional view of disposable absorbent article **90** utilizing the absorbent core **910** with the cross-section aligned along a single laterally extending elastic **919**. A series (or layer) of pre-tensioned elastic elements **919** is disposed between a first or bottom absorbent core element **911a** and a second or top absorbent core element **911b**. The two layers of core elements **911a**, **911b** and the pre-tensioned elastic elements **919** are bonded at predetermined locations along the lateral extent of the tensioned elastic **919**. The bonding locations are preferably equally spaced apart. In this specific embodiment, the bonding locations actually make longitudinally extending bonding strips **930** that run generally, continuously across the rows of laterally oriented elastics **919**. Thus, between two elastics **919**, the core elements **911a**, **911b** may be bonded directly to one another. Between the bonding strips **930**, the core elements **911a**, **911b** remain un-bonded. Bonding may be achieved using hotmelt adhesives, ultrasonic bonding, through the fusing of thermoplastic materials by heat, or by any other suitable means.

The clearly defined bonding strips **930** are generally perpendicular to the direction of elasticity (lateral direction in this embodiment). Accordingly, when tension on the elastics **919** is released, the core elements **911a**, **911b** contract with the elastics **919** on both sides of the bonding strips **930**. In the un-bonded areas between the bonding strips, the un-restrained portions of the core element rise to create peaks or ridges **P1**. As shown in FIGS. 9A and 9B, troughs **Ti** are also produced between the ridges **P1** and along or about the extent of the bonding strips **930**. The resultant absorbent core **910** provides, therefore, an accordion like structure defined by a regular series of peaks **P1** and troughs **Ti**. As further shown in FIG. 9B, the accordion-shaped core **910** features an abundance of laterally extending voids or spaces **S0** between the core elements **911a**, **911b** and between top core element **911b** and the topsheet **902**.

An important benefit of the resultant structure is that the inventive core construction achieves loftiness (i.e., which promotes comfort and softer regions) and void space out of an otherwise flat core and without significant void volume. The added void volume serves to provide a temporary fluid holding and fluid transporting space. This space provides the fluid a place within the confines of the diaper to temporarily reside during the few seconds it takes for the superabsorbent to activate and permanently lock up the fluid. The troughs **Ti**



## 15

and the voids or spaces **S0** above the troughs **Ti** channels, and facilitate dispersal of fluid exudates.

FIGS. **10A-10H** depict absorbent core constructions embodying further aspects of the present invention. These absorbent core constructions provide ergonomically-shaped cores that enhance the fit and sealing capabilities of the resultant disposable absorbent article. In particular, the design of the absorbent core constructions target an absorbent core having a nearly hourglass shape and an advantageous absorbent profile. Regarding the absorbent profile, the inventive absorbent core constructions in these Figures illustrate means for distributing absorbent core material in an optimized, non-uniform manner in and along the central body of the disposable absorbent article.

Referring first to FIGS. **10A** and **10B**, a single layered core element **1011** is provided in a generally rectangular, elongated shape, which can be described as having longitudinal and lateral centerlines **YY**, **XX**, first and second longitudinal ends **1017a**, **1017b**, and right and left side margins **1006a**, **1006b**, respectively. In accordance with the invention, the core element **1011** is marked by a pair of generally lateral cuts or slits **1008** that originate at and extend from, the right margin **1006a**. The slits **1008** preferably terminate proximate the left margin **1006b** but are spaced sufficiently therefrom to prevent compromising the structural soundness of the core element **1011**. Each of the slits **1008** is preferably spaced the same distance from the proximate longitudinal ends **1017a**, **1017b**. The slits **1008** help define the three sections of the core element **1011**: a top section or flap **1003**; a middle or mid section **1004**; and a bottom section or flap **1005**.

In one aspect, each of the slits **1008** is sufficiently long to allow the adjacent flap **1003**, **1005** to bend and pivot away from the mid section **1004**, as illustrated in FIG. **10B**. The top and bottom flaps **1003**, **1005** are preferably displaced in this manner and, at an acute angle from the midsection **1004**. As necessary, the width and shape of the slits **1008** may be enlarged and/or the left side margin **1006b** provided with cut-outs proximate the slit **1008** to accommodate the rotation of the flaps **1003**, **1005** and compression of the area along the side margin **1006b**.

Now turning to FIGS. **10C** and **10D**, an advantageous absorbent core construction **1010** is created through cooperation of two substantially similar core elements **1011** of the type depicted in FIGS. **10A-10B**. For purposes of the description, one core element **1011** may be referred to as a first or right core element **1011a**, and the other core element **1011b** as a second or left core element **1011b**. The two core elements **1011** are substantially similar and the components of the two core elements **1011** are referred to using like reference numerals. The two core elements **1011a**, **1011b** are placed adjacent one another in a manner whereby the slits **1008** are laterally aligned and substantially co-incident. The core elements **1011a**, **1011b** are preferably spaced the same distance from a longitudinal centerline **YY**. With this placement, each of flaps **1003** or **1005** oppose a corresponding flap **1003** or **1005** and is displaced and rotated away from the longitudinal centerline **YY**. This creates an open section or recess **1026** above the slits **1008**. There is some overlap between each opposing pair of flaps **1003**, **1005**, however, and, in the context of the resultant absorbent core **1010**, each pair of opposing flaps **1003**, **1005** cooperate to form one of two flared and widened end region **E1**, **E2**.

As also shown in FIG. **10C**, midsections **1004** substantially overlap and mutually cooperate to create a highly absorbent central region **M0** of the resultant absorbent core **1010**. Preferably, the central region **M0** is aligned symmetri-

## 16

cally about both the longitudinal centerline **YY**. As also shown in FIG. **10C**, the central region **M0** is substantially narrower than the end regions **E1**, **E2**. It is an advantageous feature of this embodiment that the transversely displaced pairs of flaps **1003**, **1005** are displaced outwardly, and slightly rotated, to help form the generally hour glass shape of the absorbent core **1010**. In yet another advantageous aspect, the flaps **1003**, **1005**, and the slits **1008** that help to define these sections, can readily interrelate and interlock to facilitate cooperation between the core elements **1011**. This interlocking feature helps to stabilize the resultant absorbent core **1010** and to positively place and shape the end regions **E1**, **E2** according to the desired design. In specific applications, this interlocking relationship helps to guard against any bias in the end regions **E1**, **E2** to return toward the longitudinal centerline **YY**.

FIG. **10D** illustrates an optional and further configuration utilizing the core elements **1011** in FIGS. **10A-10C**, wherein like elements are again referred to using like reference numerals (as previously used in respect to FIGS. **10A-10C**). This further configuration addresses possible shortfalls in the configuration previously described. Referring to FIG. **10D**, a resultant absorbent construction **1010a** utilizes a third core element **1011c**. Generally, the third core element **1011c** provides a substantially rectangular layer of absorbent material to add to the central region **M0**. The third core element **1011c** in this embodiment is made longer than the mid-sections **1004**, so as to cover any undesirable areas of low or substantially nil absorbency. In particular, the third core element **1011c** is shaped and positioned to extend over the previously open recess **1026** in FIG. **10C** (see FIG. **10C**), thereby covering the recess **1026**.

The third core element **1011c** also enlarges the primary absorbent region **1050** of the absorbent core, increasing its absorbent capacity. It is noted, however, that in other embodiments, it may not be desirable to increase the thickness or absorbency of the primary absorbent region (to minimize cost and manufacturing complexity, for example). In such cases, the thicknesses of the third core element and the other core elements may be adjusted to minimize the overall thickness of the central region. In the illustration of FIG. **10D**, this third core element **1011c** is shown positioned between the other two core elements **1011a**, **1011b**. In further embodiments, the third core element **1011c** may be positioned above or below both core elements **1011** (as the top-most or the bottom-most layer of absorbent material).

FIGS. **10E** and **10F** illustrate yet a further configuration and variation of the invention, wherein first and second absorbent core elements **1011a**, **1011b** provide the components of yet another resultant absorbent core **1010b** (see FIG. **10F**). This resultant absorbent core **1010b** features an alternative means for increasing the absorbency in regions of nil and substantially nil absorbency. Each of the core elements **1011a**, **1011b** is again provided with a pair of lateral slits **1008** that help define a top flap **1003**, a midsection **1004**, and a bottom flap **1005**. In this embodiment, the top and bottom flaps **1003**, **1005** are not substantially identical. For the first core element **1011a**, the top flap **1005** is shorter than the bottom flap **1003**. Thus, the top flap **1005** also provides a smaller area than the bottom flap **1003**. In contrast, the second core element **1011b** is provided with a top flap **1005** that is longer and thus larger, than the bottom flap **1003**. Now referring to FIG. **10F**, core elements **1011a**, **1011b** are placed in a mutually cooperative relationship to form the desired absorbent core **1010b**. As in other embodiments, this cooperative relationship provides a substantially dual-layered, narrow central region **M0**. The combination of core



17

elements **1011a**, **1011b** also forms end regions E1, E2. As best illustrated in FIG. 10F, the overlapping of the various regions of the two core elements **1011**, **1011b** tend to cover the voids or regions of previously low or nil absorbency (see, e.g., recesses **1026** in FIGS. 10A, 10B). These regions of previously low or nil absorbency are reduced or eliminated by extending the longer flaps closer to center and overlapping the longer flap with the shorter opposing flap.

FIG. 10G illustrates yet another alternative configuration for an absorbent core **1010c** in accordance with this embodiment of the present invention. FIG. 10G illustrates an alternative cooperation of two core elements **1011a**, **1011b** that achieves a particularly desirable interlocking relationship. The lateral slits **1008** of the core elements **1011a**, **1011b**, as well as the top and bottom flaps **1005**, **1003**, positively interlock the core elements **1011a**, **1011b**. As shown in FIG. 10G, the two flaps **1003**, **1005** of the first core element **1011a** are placed beneath the corresponding flaps **1003**, **1005** of the second core element **1011b**, while the mid section **1004** of the first core element **1011a** is placed above or atop the corresponding mid section **1004** of the second core element **1011b**. This positive interlocking relationship between the two core elements **1011a**, **1011b** aids stabilization of the resultant absorbent core **1010**, and also, reduces or eliminates the use of adhesive to secure the core elements **1011a**, **1011b** together.

FIG. 11A illustrates yet another embodiment of the present invention. In particular, FIG. 11A depicts an absorbent core **1110** that utilizes a pair of core elements **1111a**, **1111b** and exhibits a generally hourglass shape. The absorbent core **1110** features a narrow central region M0 that features a multi-layered primary absorbent region **1150** formed by mutual overlapping of the two core elements **1111a**, **1111b**. For purposes of description, the core elements **1111a** are referred to as having longitudinal ends **1117a**, **1117b**, respectively and right and left side margins **1106a**, **1106b**, respectively. The absorbent core **1110** also provides substantially identical end regions E1, E2, both spaced longitudinally from the central region M0. The end regions E1, E2 have a lateral width that is greater than that of the narrower central region M0 of the absorbent core **1110**. As with previous embodiments, the primary absorbent region **1150** is positioned about and extends from this narrow central region M0 of the absorbent core **1110**. The resultant absorbent core **1110** exhibits, therefore, a nearly hour glass shape, having wider upper or end regions E1, E2 and a narrow central region M0. As explained in respect to previous embodiments, this nearly hour glass shape improves the fit and comfort of the disposable absorbent article, while enhancing the sealing capabilities of the article. It is noted that the core elements **1111a**, **1111b** utilized in this absorbent core **1110** have a more curved or S-shaped form. The core elements **1111a**, **1111b** are also slender than core elements of previously described embodiments. The resultant absorbent core **1110** has, therefore, a more aesthetically pleasing appearance and conforms well with the shape and configuration of the disposable absorbent article, before use and while in use.

In yet another aspect, the core elements **1111a**, **1111b** utilizes elastics **1119** which are situated at select locations. Selective and strategic placement of the elastics **1119** achieves the curved and S-shape form of each core element **1111a**, **1111b**. Notably, the elastics **1119** are oriented along a generally longitudinal direction at application, and are provided at a length generally short relative to the length of each core element **1111a**, **1111b**. As will be explained in more detail below, the longitudinally oriented elastic **1119** serves to contract and curve (concave) the surrounding

18

areas, which coincides with a localized portion of the near side margins **1106** of the core element **1111**. As a result, each elastic strand **1119** tends to make the longitudinal side margin **1106** of the core element **1111** concave about a point at or near the middle of the elastic **1119**. To better illustrate how the curved shape of the core element **1119** is achieved, further reference is made to FIGS. 11B-11D, each of which illustrates a stage in the manufacture or assembly of the absorbent core **1110**.

The source of the absorbent material is presented as an elongated continuous web **1180** of absorbent material (or core elements). A stretched elastic **1119** (i.e., in tension) is applied near the side margin **1106a** or **1106b** of the web and is preferably laminated thereabout to the absorbent material. Depending on the specific application, the length of the stretched elastic **1119** is typically a significant proportion of the length of the core. Each elastic **1119** is oriented along the longitudinal direction and spaced a short lateral distance from the near side margin **1106**. For the illustrated embodiment, this lateral spacing is only about  $\frac{1}{10}^{th}$  the width of the web **1180**. Furthermore, the elastics **1119** are preferably intermittently applied along each side margin **1106a**, **1106b**. The longitudinal spacing elastics **1119** is preferably slightly larger than the stretched width of the individual elastics **1119**, although it will be apparent to one skilled in the relevant art that the longitudinal spacing and the length of the elastics chosen will depend primarily on the size and degree of curvature targeted for the resultant absorbent core and absorbent article.

In the manner described, a series of elastics **1119** is applied near each side margin **1106** of the web **1180** of absorbent material. To achieve the configuration illustrated in FIG. 11A, the series of elastics **1119** along one side margin **1106a** is preferably substantially identical to the other series or set along the other side margin **1106b**. The intermittent period of the two series are, however, offset at one-half period intervals or 180 degrees. As shown in FIG. 11B, this means that along each lateral line across the web **1180** whereon an elastic **1119** is applied along one side margin **1106**, that elastic **1119** is the only elastic applied. The area along the opposite side margin **1106** is clear and non-elasticized. Along the longitudinal direction of the web **1180**, elastics **1119** are therefore applied alternately between one side margin **1106a** and the other side margin **1106b**. Accordingly, along the longitudinal direction, the web **1180** of absorbent material may be described as being alternately elasticized between one side margin **1106a** and then the other side margin **1106b**.

After tension is removed from the elastics **1119**, the regions around each elastic **1119** contract and the elastics **1119** draw the absorbent material into a gathered material as shown in FIG. 11C. Due to the contraction of the tensioned elastics **1119** and the distribution pattern of the elastics **1119** in alternate side regions, the absorbent web **1180** takes on a continuous S-shaped configuration. This S-shaped configuration provides alternate concave and convex curves. In this configuration, the elastics **1119** are present on the short sides or concave portions and the non-elasticized regions are found on the longer side or convex portions.

FIG. 11D depicts a continuous, dual web **1180'** of absorbent core element consisting of two of the absorbent core webs **1180'** described in FIGS. 11B and 11C. The web **1180'** of absorbent core element is formed by overlapping a first web **1180a** of continuous sinuosoidal-shaped (or "S-shaped") absorbent material with a second web **1180b** of continuous S-shaped absorbent material. The two absorbent webs **1180a**, **1180b** are arranged in a non-parallel, opposed



configuration such that the elastics **1119** are laterally aligned. The result is that the elastics **1119** on the two webs **1180a**, **1180b** alternate between being both on the inside side margins **1106** of the two absorbent webs **1180** and being both on the outside side margin **1106** of the two absorbent webs **1180**. The resultant web **1180** also has alternating wide and narrow regions. This resultant web **1180** is then divided into individual absorbent cores **1110** by cutting through the transverse width of the core as indicated by lateral line **1130**. The cuts are preferably made at the widest lateral portions which coincide where the elastics **1119** are both located along adjacent side margins **1106**. These wide lateral portions, wherein the elastics **1119** are on adjacent margins **1106**, provide the end regions **E1**, **E2** of the resultant absorbent core **1110** (see FIG. **11A**). The narrow lateral portions between these lateral wide portions, which overlap, become the narrow central region **M0** of the resultant absorbent core **1110**. This substantial overlap of webs **1180** in this narrow lateral portion also provides the primary absorbent region **1150** of the resultant advantageous absorbent core **1110**.

FIG. **11E** illustrates an alternate elongated web **1180c** of absorbent core element. In this embodiment, slits **1133** are introduced to the web **1180** of absorbent core material to facilitate bending and flexibility of the individual core elements. The slits **1133** are preferably applied as groups of elastic, each group disposed primarily in the non-elasticized region of the core web **1180** (where the side margin **1106** extend and curve inward upon release of the elastics **1119**). FIGS. **11E** and **11F** illustrate the web **1180** with multiple slits **1133** oriented in the generally lateral or transverse direction. The slits **1133** sever the non-elasticized portion of the near side margin **1106** of the web **1180**. FIG. **11E** depicts the web **1180** of absorbent material with the elastic elements **1119** under tension. When tension is released, the contraction of the elastic elements **1119** causes the surrounding region near the side margins **1106** to also contract. Meanwhile, the slits **1133** in the non-elasticized regions allow these regions near the side margin **1106** to extend more readily and provides a smoother curve. In certain embodiments, the length of the slits **1133** are less than  $\frac{1}{2}$  or  $\frac{1}{3}$  the lateral width of the web **1180**. As a result, the web **1180** of absorbent material adopts a continuous S-shaped configuration, which is then used as a source web for a generally hourglass-shaped, elasticized core (see e.g., FIG. **11A**).

FIG. **12A** illustrates yet another absorbent core **1220** in accordance with a further embodiment of the present invention. The inventive absorbent core **1220** features a narrow central region **M0** and broader end regions **E1**, **E2** and thus, provides yet another generally hourglass shaped absorbent core **1220**. Notably, this configuration of an hourglass shaped core may be achieved with a single core element. In one of the simpler forms, the inventive absorbent core **1220** is formed by “twisting” a core element having the typical, generally rectangular, trapezoidal or parallelogram shape. More specifically, one end **1217a** of the core element is turned or twisted clockwise (e.g., the bottom end **1217a** in FIG. **12**) and the other end **1217b** is turned or “twisted” counter-clockwise. A twisted, narrow region of the core element is produced and provides the central region **M0** of the absorbent core **1220**. The wider, open ends of the twist are disposed as the end regions **E1**, **E2** of the absorbent core **1220**.

FIGS. **13A-13B** illustrates a method of making another “twisted” absorbent core **1310** or absorbent core element according to the present invention. Referring to FIG. **13A**, an absorbent core element **1311** is first provided in a

preferably generally parallelogram shape. The core element **1311** may be described as having a bottom end **1317a**, a top end **1317b**, a left side margin **1306a**, a right side margin **1306b**, and four corners **V1**, **V2**, **V3**, **V4** each defined by the intersection of one of the ends **1317** and one of the side margins **1306**. For purposes of this description, the core element **1311** is further described as having a pair of spaced apart twist axes **ZZ** and a longitudinal centerline **YY** preferably positioned generally parallel with and equidistantly between the twist axes **ZZ**. Each of twist axes **ZZ** is, therefore, laterally offset from the longitudinal centerline **YY** of the core element **1311**. The twist axes **ZZ** are also preferably spaced laterally from opposing corners of the parallelogram shaped core element **1211**.

As shown in FIG. **13A**, the bottom left corner **V1** is twisted in the counter clockwise direction about its twist axes **ZZ** while top right corner **V3** is twisted in the clockwise direction about its twist axis **ZZ**. Referring to FIG. **13B**, the resultant twisted absorbent core element **1311** has a somewhat distorted hourglass shape. Nevertheless, the resultant core element **1311** or resultant absorbent core construction provides certain features targeted by the invention. The absorbent core element **1311** has a narrow central region **M0**, wider end regions **E1**, **E2**, and a multi-layered primary absorbent region **1350** that imparts higher absorbency at specific target locations. The core element may be described further as having top and bottom V-shaped flaps **W1**, **W2** (respectively) that extend laterally from the rest of the absorbent core element **1311**.

Alternatively, the core element **1311** of FIG. **13B** may be combined with another core element **1311** having substantially similar structure to produce an advanced embodiment of the present invention. FIGS. **13C** and **13D** illustrate the making of an improved absorbent core construction **1310** by combining two such absorbent core elements **1311**. A top core element **1311b** is positioned above a bottom core element **1311a**, such that one is turned over relative to the other. Essentially, the core element **1311** in FIG. **13C** is rotated  $180^\circ$  to the right and is presented as bottom core element **1311a** in FIG. **13C**. The flaps **W1**, **W2** (of the core elements **1311**) that are directly one atop the other extends, therefore, in opposite lateral directions, as shown in FIG. **13C**. The first core element **1311b** is then set upon (overlaid) the second core element **1311a**. FIG. **13D** depicts a resultant absorbent core **1310** that exhibits a more pronounced hourglass shape. The absorbent core also provides a more defined, and wider, top and bottom end regions **E1**, **E2**.

FIG. **13E** illustrates the relative distribution of absorbent material in the core elements **13a**, **13b** utilized in the absorbent core **1310**, prior to joining the two core elements **1311a**, **1311b**. The lighter areas represent regions provided by one layer of absorbent material while the darker areas represent regions with two layers of absorbent material, and thus, relatively higher absorbency. FIG. **13F** illustrates the relative distribution of absorbent material in the resultant absorbent core **1310**, which is comprised of the two core elements **1311a**, **1311b**. The illustration reflects an absorbent core **1310** with a multi-faceted absorbent profile along various directions (including along the longitudinal centerline). This resultant absorbent core **1310** features regions with single (**A1**), double (**A2**), triple (**A3**) and quadruple (**A4**) stacked layers of absorbent core material. The resultant absorbent profile reflects a highly absorbent region that is centered about the intersection of the longitudinal and lateral centerlines (**YY**, **XX** respectively), which provides the mid section **M0**. This highly absorbent region will correspond with, and provide sufficient coverage for, the crotch region



of the absorbent article. The resultant absorbent core **1310** further provides broadened end regions **E1**, **E2** that also feature varying absorbency, including broad regions extending from the mid section **M0** with triple layers (**A3**) of absorbent material. One unique benefit of this multi-faceted design is the creation of channels with lesser amounts of absorbent material (fewer layers of core). For example, FIG. **13F** shows an X-shaped channel **C1** between the four regions **A4**. These channels **C1** help to distribute fluid to other regions of the core **1310**, thereby utilizing absorbent materials in other areas of the core **1310**.

The resultant absorbent core **1310** provides certain targeted advantages and benefits. Firstly, the resultant absorbent core **1310** provides a better, more form fitting, fit for the wearer of the absorbent article as well as improved leakage prevention performance by providing absorbent material over a greater area of the article in the waist regions. Secondly the resultant absorbent structure provides a profiled, distribution of absorbent material throughout the article. A greater amount of absorbent material is provided in the crotch region of the article where receipt of fluids is expected. Concentrations of absorbent material, albeit lesser amounts, are also provided around the waist regions and side margins of the absorbent article. These absorbent regions perform an enhanced leak prevention function.

FIGS. **14A-14C** provide a further embodiment of the present invention, featuring an enhanced absorbent core construction and absorbency profile. FIG. **14C** depicts, more specifically, a dual layered core construction **1410**. Initially, an absorbent element **1411a** is presented having a generally rectangular configuration. The core element **1411a** of this embodiment is provided with at least two laterally extending slits **1421** preferably positioned near or about the lateral centerline **XX** of the core element **1411a** (and ultimately of the resultant absorbent core construction **1410**). The laterally extending slits **1411** are directed inwardly from opposite side margins **1413** of the generally rectangular core element **1411a**. In this embodiment, each of the lateral slits **1421** extends inwardly about  $\frac{1}{5}^{th}$  the lateral width of the core element **1411a**. Four imaginary folding lines **1422** are also presented in the generally rectangular core element **1411a**. The folding lines **1422** also run inwardly from the side margins **1413** and downwardly toward the lateral centerline **XX**, thereby intersecting the end of the lateral slits **1421**, as shown in FIG. **14A**.

The imaginary folding lines **1422** may be created by a number of suitable means or methods, including initially pre-stressing the absorbent core element **1411a** or stamping the absorbent core element **1411a** prior to the folding steps. In a subprocess of making the absorbent core construction **1410**, an urging force is applied to the side margins **1413** of the core element **1411a** above and below the location of the lateral slits **1421**. This force dislodges and/or urges a pair of resultant flaps **1423** inwardly about the imaginary folding lines **1422**, as shown in FIG. **14B**. The urging force may be provided by air jet mechanisms that blow or apply pressure on the side margins **1413** proximate the imaginary folding lines **1422**. In alternative processes, a mechanical means, such as a piston, may be employed.

In any event, a pair of inwardly folding flaps **1423** is provided along each side margin **1413** above and below the former location of the lateral slit **1421**. Turning to FIG. **14C**, a second core element **1411b** may be provided centrally atop the first core element **1411a**, and underneath and inwardly from the four flaps **1423**. The second core element **1411b** may be applied on the first core element **1411a** prior to the urging or folding steps (applied to the flaps **1423**). Alterna-

tively, the second core element **1411b** may be inserted under the flaps **1423** after the folding operation. The second core element may also be applied over the top of the first or bottom core element and its folded side flaps, such that the folded flaps is placed between upper and lower core elements.

The result of either case is a generally hourglass-shaped absorbent core construction **1410**, as shown by FIG. **14C**. The absorbent core construction **1410** features an enhanced central absorbent region **1450**, as provided by the second core element **1411b**. The flaps **1423** also provide enhanced absorbency to the core construction **1410** (as the flaps **1423** are also made of highly absorbent material). Moreover, the absorbent flaps **1423** provide an enhanced absorbent region that functions as a leakage dam or sealant along the edges or side margins of the central region **1450**. Additionally, as illustrated by FIG. **14C**, the absorbent flaps **1423** help to secure the second core element **1411b** centrally and atop the first core element **1411a**. Specifically, the absorbent flaps **1423** wrap around the longitudinal edges of the second core element **1411b**. In further embodiments, the second core element **1411b** may be provided on top of the flaps **1423** of the first absorbent core element **1411a**, or beneath the first core element **1411a**. In either further embodiment, the second core element **1411b** still provides enhanced absorbency in a central region **1450** of the hourglass-shaped absorbent core construction **1410**.

FIGS. **15A** and **15B** illustrate how a superimposed core construction **1510** such as that provided in FIG. **2A** may be generated in an efficient and advantageous manner. As described previously, the core consists of two core elements **A**, **B** having a trapezoidal shape. The selection of a trapezoidal shape allows the core elements **A**, **B** to be derived from the same material source. Preferably, a web **1580** of core material, as shown in FIG. **15A**, is presented as the core material source. Alternating trapezoidal core elements **A** and **B** are stamped on or cut from the web **1580**. The two trapezoid shapes or blanks **A**, **B** are identical except that one is oriented 180 degrees from the other. Alternating inclined cuts **1581** may be made across the web **1580** (edge to edge) to produce and shape the two adjacent core elements **A**, **B** without waste of the web material. Each inclined cut **1581** is common to both blanks **A**, **B** and simultaneously defines a side of both trapezoid core elements **A**, **B**.

As shown in FIGS. **15B-C**, the two trapezoid blanks **A**, **B** are then overlaid to form the desired core construction. In further embodiments, a third core element **C**, which, in this case, has a rectangular shape, is disposed about the center of the core construction **1510** and overlays both trapezoid core elements **A**, **B**. The overlay of core elements **A**, **B**, **C** defines an even more highly absorbent central region.

It will be appreciated by those skilled in the art that other core elements shapes may be selected which allow adjacent blanks to be cut without waste material. The adjacent blanks will preferably be of an irregular shape (as required by various embodiments of the invention) and provided as mirror images of one another. With many irregular shapes, the blanks on the web will be oriented 180 degrees apart. In one application, instead of inclined sides or cuts, the cuts are curved and the core elements have curved outlines. In one particular embodiment, the core elements are preferably S-shaped and the blanks on the web may either be symmetrical along the longitudinal centerline or the blanks are oriented 180 degrees apart. Again, each cut or side is common to both blanks and defines corresponding sides of the adjacent blanks or core elements.



23

FIGS. 16A and 16B illustrate an exemplary method of laterally elasticizing a core construction **1610** similar to that of FIG. 6B. This particular method utilizes a rectangular, laterally elasticized composite **1619** such as that described in U.S. Pat. Nos. 7,361,246 and 7,462,172 (both of which are hereby incorporated by reference for all purposes, including being made a part of the present disclosure) (which patents have one or more inventors common to the present invention (s)). As described in these patent documents, the elastic composite **1619** may comprise at least one nonwoven sheet or other substrate and a plurality of lateral elastics thereon. In some embodiments, the elastic composite consists of elastics sandwiched between two nonwoven layers, but it is further contemplated that, for present purposes, only one substrate layer may be required. The elastic composite **1619** is applied, in tension, on a core element **1611** preferably centrally using suitable adhesives or the like. Once released from tension, the elastic composite **1619** contracts laterally, thereby also contracting the core element **1611** attached beneath the elastic composite **1619**. This contraction creates a narrowed central region **M0** of the resulting core construction **1610**, as desired.

In respect to the embodiments of FIGS. 11A-11F, it is further contemplated that the longitudinally-directed elastics **1119** may be applied to the web **1180** of core element as one continuous strand. Sections of the continuous strand may be selectively severed to leave the intermittent series of elastics **1119** on the web **1180**. Alternatively, the continuous strand may be adhered to the core material in the tensioned state (e.g., using glue or other suitable adhesive), then select portions of the continuous elastic strand are de-activated. Released from tension, the once-continuous elastic strand generates the intermittent series of contracted elastics **1119** and thus, the desired curved side margins (of the web **1180** and the resultant core elements **1111a**, **1111b**). In respect to the embodiments of FIGS. 11E and 11F, the slits **1133** may be made immediately after application of the continuous strand onto the web **1180**.

The foregoing descriptions of various embodiments and aspects of the present invention have been presented for purposes of illustration and description. These descriptions are not intended to limit the invention to the various absorbent cores or articles, and processes disclosed. Various aspects of the invention are intended for applications other than diapers and training pants. The core constructions described may also be incorporated into or with other garments, textiles, fabrics, and the like, or combinations thereof. The core constructions described may also incorporate different components. These and other variations of the invention will become apparent to one generally skilled in the relevant consumer product art provided with the present disclosure. Consequently, variations and modifications commensurate with the above teachings, and the skill and knowledge of the relevant art, are within the scope of the present invention. The embodiments described and illustrated herein are further intended to explain the best modes for practicing the invention, and to enable others skilled in the art to utilize the invention and other embodiments and with various modifications required by the particular applications or uses of the present invention.

What is claimed is:

1. A disposable absorbent article comprising:  
a central body defining a first waist end region including a first end edge, a second waist end region spaced longitudinally from the first waist end region and including a second end edge, and a crotch region positioned therebetween; and

24

an absorbent core situated between the end edges, the absorbent core including a first absorbent core element including superabsorbent particles and extending laterally across the crotch region and a plurality of elastics that are generally laterally extended, mutually longitudinally spaced apart and attached to the first absorbent core element such that the first absorbent core element is laterally contracted in a narrowed region of the first core element about the plurality of elastics; and  
wherein the absorbent core has a shape that includes a pair of end regions that are non-elasticized and have a lateral width wider than a lateral width of the narrowed region;  
wherein each of said plurality of elastics extends laterally from a location proximate one side margin of the first core element in the narrowed region to a location proximate an opposite side margin of the first core element in the narrowed region; and  
wherein the plurality of elastics are disposed together in one concentration of elastics in a central region of the first core element between the end regions and within the side margins of the first core element, and wherein the elastics are arranged in longitudinally spaced apart rows; and  
wherein the absorbent core further includes a second core element, said plurality of elastics being disposed between said first core element and said second core element.

2. The disposable absorbent article of claim 1, wherein the plurality of elastics are longitudinally spaced apart and extend laterally between longitudinally extending side margins of the absorbent core at the crotch region.

3. The disposable absorbent article of claim 2, wherein ends of the plurality of elastics are positioned proximate the side margins to provide a concavity in each said side margin proximate the plurality of elastics.

4. The disposable absorbent article of claim 1, wherein the absorbent core includes the first core element formed from materials imparting absorbent properties and the second core element formed from materials imparting absorbent properties, the second core element superimposing the first core element to form a multi-layer primary absorbent region of the absorbent core having an absorption capacity per unit area increased from an absorption capacity per unit area in the end regions of the absorbent core; and

wherein the multi-layer absorbent region substantially coincides with the narrowed region; and

wherein each of the first and second core elements includes a plurality of elastics incorporated therewith to form a narrowed region of the respective core element; and

wherein the narrowed regions of the core elements are positioned adjacent one another to substantially form the narrowed region of the absorbent core.

5. The disposable absorbent article of claim 1, wherein the plurality of elastics are placed within said absorbent core.

6. The disposable absorbent article of claim 1, wherein the plurality of elastics are placed, pre-tensioned, on a planar absorbent surface of the absorbent core.

7. The disposable absorbent article of claim 1, wherein the rows of said elastics are arranged in the narrowed region in rows of varying pitch to define a curved shape to said narrowed region of the first core element.

8. The disposable absorbent article of claim 1, wherein the rows of said elastics are arranged in the narrowed region in rows of varying tension to provide a curved shape to said narrowed region.



25

9. The disposable absorbent article of claim 1, wherein rows of said elastics are arranged in the narrowed region in rows of varying shape to achieve the shape of the absorbent core.

10. The disposable absorbent article of claim 1, wherein the rows of said elastics are arranged in the narrowed region in rows of varying type to achieve the shape of the absorbent core.

11. The disposable absorbent article of claim 1, wherein the rows of said elastics are arranged in rows of varying length to achieve the shape of the absorbent core.

12. A disposable absorbent article comprising:

a central body defining a first waist end region including a first end edge, a second waist end region spaced longitudinally from the first waist end region and including a second end edge, and a crotch region positioned therebetween; and

an absorbent core situated between the end edges, the absorbent core including a first absorbent core element including superabsorbent particles and extending laterally across the crotch region and a plurality of elastics that are generally laterally extended, mutually longitudinally spaced apart and attached to the first absorbent core element such that the first absorbent core element is laterally contracted in a narrowed region of the first core element about the plurality of elastics; and

wherein the absorbent core has a shape that includes a pair of end regions that are non-elasticized and have a lateral width wider than a lateral width of the narrowed region; and

wherein the absorbent core includes the first core element formed from materials imparting absorbent properties and a second core element formed from materials imparting absorbent properties, the second core element superimposing the first core element to form a multi-layer primary absorbent region of the absorbent core having an absorption capacity per unit area increased from an absorption capacity per unit area in the end regions of the absorbent core; and

wherein the multi-layer absorbent region substantially coincides with the narrowed region of the absorbent core; and

wherein each of the first and second core elements includes a plurality of elastics incorporated therewith to form a narrowed region of the respective core element; and

wherein the narrowed regions of the core elements are positioned adjacent one another to substantially form the narrowed region of the absorbent core

wherein each of said plurality of elastics extends laterally from a location proximate one side margin of the respective core element in the narrowed region thereof to a location proximate an opposite side margin of the respective core element in the narrowed region thereof; and

wherein each of said plurality of elastics are disposed together in one concentration of elastics in a central region of the respective core element between the end regions and within the side margins of the respective core element, and wherein the elastics are arranged in longitudinally spaced apart rows; and

wherein the narrowed regions of the core elements are situated to provide a laterally contracted primary absorbent region; and

26

wherein the second core element includes slits that provide voids penetrating through the second core element in the substantially laterally contracted primary absorbent region.

13. A disposable absorbent article comprising:

a central body defining a first waist end region including a first end edge, a second waist end region spaced longitudinally from the first waist end region and including a second end edge, and a crotch region positioned therebetween; and

an absorbent core situated between the end edges, the absorbent core including a first absorbent core element including superabsorbent particles and extending laterally across the crotch region and a plurality of elastics that are generally laterally extended, mutually longitudinally spaced apart and attached to the first absorbent core element such that the first absorbent core element is laterally contracted in a narrowed region of the first core element about the plurality of elastics; and

wherein the absorbent core has a shape that includes a pair of end regions that are non-elasticized and have a lateral width wider than a lateral width of the narrowed region;

wherein each of said plurality of elastics extends laterally from a location proximate one side margin of the first core element in the narrowed region to a location proximate an opposite side margin of the first core element in the narrowed region; and

wherein the plurality of elastics are disposed together in one concentration of elastics in a central region of the first core element between the end regions and within the side margins of the first core element, and wherein the elastics are arranged in longitudinally spaced apart rows; and

wherein said plurality of elastics are adhered to the first absorbent core element at a plurality of adhesion locations positioned and spaced apart along the length of each elastic of said plurality of said elastics adhered to the first absorbent core element to form a plurality of laterally spaced apart ridges in the first core element in between adhesion locations.

14. The disposable absorbent article of claim 13, wherein the adhesion locations associated with each elastic are longitudinally aligned with adhesion locations on others of the plurality of elastics to form a plurality of longitudinally aligned and laterally spaced apart sets of adhesion locations that form ridges that are longitudinally extended and spaced laterally between sets of adhesion locations.

15. The disposable absorbent article of claim 14, wherein the ridges are spaced apart to form a plurality of longitudinally extending void spaces below said ridges and a plurality of channels between laterally spaced apart ridges.

16. The disposable absorbent article of claim 14, wherein the absorbent core further includes a second absorbent core element placed below the first absorbent core element and the plurality of elastics.

17. A disposable absorbent article comprising:

a central body defining a first waist end region including a first end edge, a second waist end region spaced longitudinally from the first waist end region and including a second end edge, and a crotch region positioned therebetween; and

an absorbent core situated between the end edges, the absorbent core including a first absorbent core element including superabsorbent particles and imparting absorbent properties, and extending laterally across the



27

crotch region, and a plurality of spaced apart elastics incorporated with the first core element; and wherein said plurality of elastics are adhered to the first core element at a plurality of adhesion locations positioned and spaced apart along the length of each elastic of said plurality of said elastics adhered to the first core element to form a plurality of spaced apart ridges in the first core element in between adhesion locations; and wherein the adhesion locations associated with each elastic are aligned with adhesion locations on other elastics of said plurality of said elastics adhered to the first core element to form a plurality of spaced apart sets of adhesion locations that form ridges that are extended and spaced between sets of adhesion locations; and wherein the absorbent core further includes a second absorbent core element placed below the first absorbent core element and the plurality of elastics incorporated therewith, the second absorbent core element including a plurality of elastics incorporated therewith, each of the plurality of elastics forming a narrowed region of the respective absorbent core element, wherein narrowed regions of the core elements are positioned adjacent one another to substantially form a narrowed region of the absorbent core.

18. The disposable absorbent article of claim 17, wherein the absorbent core further includes a material layer positioned below the first core element and the plurality of elastics incorporated therewith and a second material layer positioned below the second core element and the plurality of elastics incorporated therewith.

19. The disposable absorbent article of claim 17, wherein the elastics of each of the plurality of elastics are longitudinally spaced apart and include adhesion locations that are longitudinally aligned to form longitudinally extending, laterally spaced apart ridges.

20. The disposable absorbent article of claim 17, wherein the ridges are spaced apart to form a plurality of longitudinally extending void spaces below said ridges and a plurality of channels between laterally spaced apart ridges.

21. The disposable absorbent article of claim 17, wherein said plurality of elastics of said second core element includes elastics adhered thereto at a plurality of adhesion locations, and wherein the adhesion locations of the second core element associated with each said elastic are longitudinally aligned with adhesion locations of the second core element on others of said elastics in the plurality of elastics of the second core element to form a plurality of longitudinally aligned and laterally spaced apart sets of adhesion locations of the second core element that form ridges that are longitudinally extended and spaced laterally between sets of adhesion locations of the second core element.

22. The disposable absorbent article of claim 17, wherein said plurality of elastics incorporated with the first core element and said plurality of elastics incorporated with the second core element are respectively adhered to said first and second core elements at said adhesion locations.

23. The disposable absorbent article of claim 22, wherein a plurality of ridges are formed in the second core element such that a plurality of mutually spaced apart and extended void spaces are formed between the core elements.

24. The disposable absorbent article of claim 23, wherein each of said void spaces is formed between a ridge on the first core element and a corresponding ridge on the second core element that protrudes in a direction away from the first core element.

28

25. A disposable absorbent article comprising:  
a central body defining a first waist end region including a first end edge, a second waist end region spaced longitudinally from the first waist end region and including a second end edge, and a crotch region positioned therebetween; and  
an absorbent core situated between the end edges, the absorbent core including a first absorbent core element and a plurality of elastics attached to the first core element; and  
a second absorbent core element and a plurality of elastics attached to the second core element, the first and second core elements being superimposed to provide a narrowed region of the absorbent core in the crotch region;  
wherein for each core element, one elastic of said plurality of elastics of the core element extends longitudinally along a side margin of the core element and is disposed in a central region of the core element to form a concavity in the core element,  
wherein the central regions of the first and second core elements and the concavities thereof provide, at least partially, the narrowed region,  
wherein the concavities and the longitudinally extending elastics are situated on portions of the narrowed region outside a portion provided by superimposed portions of the first and second core elements; and  
wherein each of said plurality of elastics of each core element is disposed incorporated with the respective core element and within opposite side margins of the respective core element.

26. A disposable absorbent article comprising:  
a central body defining a first waist end region including a first end edge, a second waist end region spaced longitudinally from the first waist end region and including a second end edge, and a crotch region positioned therebetween; and  
an absorbent core situated between the end edges, the absorbent core including at least one absorbent core element including superabsorbent particles and imparting absorbent properties, and extending laterally across the crotch region, and a plurality of spaced apart elastics incorporated with the core element and attached to the absorbent core element such that the absorbent core element is laterally contracted in a narrowed region of the core element about the plurality of elastics; and  
wherein said plurality of elastics are adhered to the core element at a plurality of adhesion locations positioned and spaced apart along the length of each elastic of said plurality of elastics adhered to the core element to form a plurality of spaced apart ridges in the core element in between adhesion locations; and  
wherein the adhesion locations associated with each elastic are aligned with adhesion locations on other elastics of said plurality of elastics adhered to the core element to form a plurality of spaced apart sets of adhesion locations that form ridges that are extended and spaced between sets of adhesion locations; and  
a topsheet disposed over the absorbent core such that mutually-spaced apart and extended void spaces are formed between the topsheet and the absorbent core.

27. A disposable absorbent article comprising:  
a central body defining a first waist end region including a first end edge, a second waist end region spaced longitudinally from the first waist end region and



29

including a second end edge, and a crotch region positioned therebetween; and  
 an absorbent core situated between the end edges, the absorbent core including a first absorbent core element including superabsorbent particles and extending laterally across the crotch region and a plurality of elastics that are generally laterally extended, mutually longitudinally spaced apart and attached to the first absorbent core element such that the first absorbent core element is laterally contracted in a narrowed region of the first core element about the plurality of elastics; and  
 wherein the absorbent core has a shape that includes a pair of end regions that are non-elasticized and have a lateral width wider than a lateral width of the narrowed region;  
 wherein each of said plurality of elastics extends laterally from a location proximate one side margin of the first core element in the narrowed region to a location proximate an opposite side margin of the first core element in the narrowed region; and  
 wherein the plurality of elastics are disposed together in one concentration of elastics in a central region of the first core element between the end regions and within the side margins of the first core element, and wherein the elastics are arranged in longitudinally spaced apart rows; and  
 wherein the rows of said elastics are arranged in the narrowed region in rows of varying pitch to define a curved shape to said narrowed region of the first core element.

**28.** The disposable absorbent article of claim **27**, wherein the absorbent core further includes a second core element, said plurality of elastics being disposed between said first core element and said second core element.

**29.** The disposable absorbent article of claim **27**, wherein the absorbent core includes the first core element formed from materials imparting absorbent properties and a second core element formed from materials imparting absorbent properties, the second core element superimposing the first core element to form a multi-layer primary absorbent region of the absorbent core having an absorption capacity per unit area increased from an absorption capacity per unit area in the end regions of the absorbent core; and  
 wherein the multi-layer absorbent region substantially coincides with the narrowed region; and  
 wherein each of the first and second core elements includes a plurality of elastics incorporated therewith to form a narrowed region of the respective core element; and  
 wherein the narrowed regions of the core elements are positioned adjacent one another to substantially form the narrowed region of the absorbent core.

**30.** The disposable absorbent article of claim **27**, wherein ends of the plurality of elastics are positioned proximate the

30

side margins to provide a concavity in each said side margin proximate the plurality of elastics.

**31.** A disposable absorbent article comprising:

a central body defining a first waist end region including a first end edge, a second waist end region spaced longitudinally from the first waist end region and including a second end edge, and a crotch region positioned therebetween; and

an absorbent core situated between the end edges, the absorbent core including a first absorbent core element including superabsorbent particles and extending laterally across the crotch region and a plurality of elastics that are generally laterally extended, mutually longitudinally spaced apart and attached to the first absorbent core element such that the first absorbent core element is laterally contracted in a narrowed region of the first core element about the plurality of elastics; and

wherein the absorbent core has a shape that includes a pair of end regions that are non-elasticized and have a lateral width wider than a lateral width of the narrowed region;

wherein each of said plurality of elastics extends laterally from a location proximate one side margin of the first core element in the narrowed region to a location proximate an opposite side margin of the first core element in the narrowed region; and

wherein the plurality of elastics are disposed together in one concentration of elastics in a central region of the first core element between the end regions and within the side margins of the first core element, and

wherein the plurality of elastics are arranged in longitudinally spaced apart rows; and wherein the plurality of elastics are placed within said absorbent core.

**32.** The disposable absorbent article of claim **31**, wherein the absorbent core includes the first core element formed from materials imparting absorbent properties and a second core element formed from materials imparting absorbent properties, the second core element superimposing the first core element to form a multi-layer primary absorbent region of the absorbent core having an absorption capacity per unit area increased from an absorption capacity per unit area in the end regions of the absorbent core; and

wherein the multi-layer absorbent region substantially coincides with the narrowed region; and

wherein each of the first and second core elements includes a plurality of elastics incorporated therewith to form a narrowed region of the respective core element; and wherein the narrowed regions of the core elements are positioned adjacent one another to substantially form the narrowed region of the absorbent core.

**33.** The disposable absorbent article of claim **32**, wherein ends of the plurality of elastics are positioned proximate the side margins to provide a concavity in each said side margin proximate the plurality of elastics.

\* \* \* \* \*