

US009604641B2

(12) **United States Patent**
Al-Stouhi

(10) **Patent No.:** **US 9,604,641 B2**
(45) **Date of Patent:** **Mar. 28, 2017**

(54) **SYSTEM AND METHOD FOR PROVIDING VEHICLE COLLISION AVOIDANCE AT AN INTERSECTION**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **Honda Motor Co., Ltd.**, Tokyo (JP)

6,049,295 A 4/2000 Sato

6,720,920 B2 4/2004 Breed et al.

7,081,833 B2 7/2006 Jo

7,317,406 B2 1/2008 Wolterman

(72) Inventor: **Samir K. Al-Stouhi**, Dearborn, MI (US)

(Continued)

(73) Assignee: **Honda Motor Co., Ltd.**, Tokyo (JP)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

JP 2010102529 5/2010

OTHER PUBLICATIONS

(21) Appl. No.: **14/740,420**

Maile, M., et al.: "Cooperative Intersection Collision Avoidance System for Violations (CICAS-V) for Avoidance of Violation-Based Intersection Crashes", Mercedes-Benz Research & Development North America, Inc., USA Paper No. 09-0118.

(22) Filed: **Jun. 16, 2015**

(65) **Prior Publication Data**

US 2016/0368492 A1 Dec. 22, 2016

Primary Examiner — Yonel Beaulieu

Assistant Examiner — Martin Weeks

(74) *Attorney, Agent, or Firm* — Rankin, Hill & Clark LLP

(51) **Int. Cl.**

B60W 10/18 (2012.01)

B60W 10/20 (2006.01)

B60W 30/09 (2012.01)

B60W 10/04 (2006.01)

B60W 30/095 (2012.01)

(57) **ABSTRACT**

A system and method for providing vehicle collision avoidance at an intersection include receiving vehicle parameters from a reference vehicle and environmental parameters from roadside equipment. The system and method also include processing a vehicle behavioral map based on the vehicle parameters and the environmental parameters and transmitting the vehicle behavioral map to a target vehicle. The system and method additionally include processing a confidence table based on the vehicle behavioral map and vehicle parameters provided by the target vehicle. The system and method further include providing a collision avoidance response based on the confidence table, wherein the collision avoidance response is provided to the target vehicle to avoid a possible collision with the reference vehicle at the intersection.

(52) **U.S. Cl.**


CPC **B60W 30/0953** (2013.01); **B60W 10/04** (2013.01); **B60W 10/18** (2013.01); **B60W 10/20** (2013.01); **B60W 30/09** (2013.01); **B60W 2550/12** (2013.01); **B60W 2550/302** (2013.01); **B60W 2550/308** (2013.01); **B60W 2710/18** (2013.01); **B60W 2710/20** (2013.01); **B60W 2720/10** (2013.01)

(58) **Field of Classification Search**

CPC G01C 21/00; G08G 1/16; B60W 10/18; B60W 10/20; B60W 30/09

See application file for complete search history.

20 Claims, 7 Drawing Sheets




(56)

References Cited

U.S. PATENT DOCUMENTS

7,430,218 B2 9/2008 Lee et al.
7,873,474 B2 1/2011 Yamamoto et al.
8,027,762 B2* 9/2011 Otake B60T 7/22
701/117
8,103,449 B2 1/2012 Mudalige
8,340,894 B2 12/2012 Yester
8,386,156 B2 2/2013 Miller
8,594,919 B2 11/2013 Munakata
8,639,437 B2 1/2014 Caminiti et al.
2005/0107954 A1* 5/2005 Nahla B61L 25/021
701/301
2011/0298603 A1 12/2011 King et al.
2012/0029798 A1 2/2012 Miller
2012/0235947 A1* 9/2012 Yano G01C 21/3664
345/173
2014/0372016 A1* 12/2014 Buchholz G08G 1/161
701/117
2015/0256624 A1* 9/2015 Buckel H04L 67/025
709/202
2015/0314780 A1* 11/2015 Stenneth B60W 30/00
701/23

* cited by examiner






FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

1

SYSTEM AND METHOD FOR PROVIDING VEHICLE COLLISION AVOIDANCE AT AN INTERSECTION

BACKGROUND

Generally, intersections increase the collision risk for vehicles, particularly as relates to vehicle to vehicle collisions. This is due to the fact that drivers of vehicles may not be aware of the existence of other vehicles that are approaching the intersection from other directions. Additionally, drivers may have to account for other vehicles that may not abide by speed limits and/or traffic light/stop signs that are provided at the intersection. For example, certain vehicles may be approaching the intersection when another vehicle is bypassing a red light at a high rate of speed. Intersections also pose a higher risk for various types of collisions including head-on and side impact collisions caused by one vehicle crossing an opposing lane of traffic to turn at an intersection.

BRIEF DESCRIPTION

According to one aspect, a computer-implemented method for providing vehicle collision avoidance at an intersection includes receiving vehicle parameters from a reference vehicle and environmental parameters from roadside equipment. The method also includes processing a vehicle behavioral map based on the vehicle parameters and the environmental parameters and transmitting the vehicle behavioral map to a target vehicle. The method additionally includes processing a confidence table based on the vehicle behavioral map and vehicle parameters provided by the target vehicle. The method further includes providing a collision avoidance response based on the confidence table. The collision avoidance response is provided to the target vehicle to avoid a possible collision with the reference vehicle at the intersection.

According to a further aspect, a system for providing vehicle collision avoidance at an intersection is provided. The system includes an intersection collision avoidance (ICA) application that is executed on at least one of: a reference vehicle, a target vehicle, roadside equipment, and externally hosted computing infrastructure. The system also includes a reference vehicle data collection module that is included as a module of the ICA application that receives vehicle parameters from the reference vehicle and environmental parameters from the roadside equipment. The system additionally includes a behavioral map processing module that is included as a module of the ICA application that processes a vehicle behavioral map based on the vehicle parameters and the environmental parameters and a behavioral map data transmission module that is included as a module of the ICA application that transmits the vehicle behavioral map to the target vehicle. Additionally, the system includes a confidence table processing module that is included as a module of the ICA application that processes a confidence table based on the vehicle behavioral map and vehicle parameters provided by the target vehicle. The system further includes a collision avoidance determinant module that is included as a module of the ICA application that provides a collision avoidance response based on the confidence table, wherein the collision avoidance response is provided to the target vehicle to avoid a possible collision with the reference vehicle at the intersection.

According to still another aspect, a computer readable storage medium storing instructions that, when executed by

2

a processor, perform actions, including receiving vehicle parameters from a reference vehicle and environmental parameters from roadside equipment. The instructions also include processing a vehicle behavioral map based on the vehicle parameters and the environmental parameters and transmitting the vehicle behavioral map to a target vehicle. The instructions additionally include processing a confidence table based on the vehicle behavioral map and vehicle parameters provided by the target vehicle. The instructions further include providing a collision avoidance response based on the confidence table. The collision avoidance response is provided to the target vehicle to avoid a possible collision with the reference vehicle at the intersection.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic view of an operating environment for implementing systems and methods for vehicle collision avoidance at an intersection according to an exemplary embodiment;

FIG. 2 is a process flow diagram of a method for providing vehicle collision avoidance executed by an intersection collision avoidance (ICA) application from the operating environment of FIG. 1 according to an exemplary embodiment;

FIG. 3 is a process flow diagram of a method for processing an vehicle behavioral map from the operating environment of FIG. 1 according to an exemplary embodiment;

FIG. 4 is an illustration of the vehicle behavioral map processed by behavioral map processing module of the ICA application according to an exemplary embodiment;

FIG. 5 is a process flow diagram of a method for processing a confidence table based on the vehicle behavioral map and vehicle parameters provided by a target vehicle(s) from the operating environment of FIG. 1 according to an embodiment;

FIG. 6 is a process flow diagram of a method for estimating a path of travel of reference vehicle(s) and target vehicle(s) for providing a collision avoidance response from the operating environment of FIG. 1 according to an exemplary embodiment; and

FIG. 7 is an illustrative example of estimating an overlap between the expected path of the reference vehicle(s) and the expected path of the target vehicle(s) approaching or traveling through the intersection according to an exemplary embodiment.

DETAILED DESCRIPTION

The following includes definitions of selected terms employed herein. The definitions include various examples and/or forms of components that fall within the scope of a term and that can be used for implementation. The examples are not intended to be limiting.

A “bus”, as used herein, refers to an interconnected architecture that is operably connected to other computer components inside a computer or between computers. The bus can transfer data between the computer components. The bus can be a memory bus, a memory controller, a peripheral bus, an external bus, a crossbar switch, and/or a local bus, among others. The bus can also be a vehicle bus that interconnects components inside a vehicle using protocols such as Media Oriented Systems Transport (MOST), Controller Area network (CAN), Local Interconnect Network (LIN), among others.

“Computer communication”, as used herein, refers to a communication between two or more computing devices

(e.g., computer, personal digital assistant, cellular telephone, network device) and can be, for example, a network transfer, a file transfer, an applet transfer, an email, a hypertext transfer protocol (HTTP) transfer, and so on. A computer communication can occur across, for example, a wireless system (e.g., IEEE 802.11), an Ethernet system (e.g., IEEE 802.3), a token ring system (e.g., IEEE 802.5), a local area network (LAN), a wide area network (WAN), a point-to-point system, a circuit switching system, a packet switching system, among others.

A “disk”, as used herein can be, for example, a magnetic disk drive, a solid state disk drive, a floppy disk drive, a tape drive, a Zip drive, a flash memory card, and/or a memory stick. Furthermore, the disk can be a CD-ROM (compact disk ROM), a CD recordable drive (CD-R drive), a CD rewritable drive (CD-RW drive), and/or a digital video ROM drive (DVD ROM). The disk can store an operating system that controls or allocates resources of a computing device.

A “database”, as used herein can refer to table, a set of tables, a set of data stores and/or methods for accessing and/or manipulating those data stores. Some databases can be incorporated with a disk as defined above.

A “memory”, as used herein can include volatile memory and/or non-volatile memory. Non-volatile memory can include, for example, ROM (read only memory), PROM (programmable read only memory), EPROM (erasable PROM), and EEPROM (electrically erasable PROM). Volatile memory can include, for example, RAM (random access memory), synchronous RAM (SRAM), dynamic RAM (DRAM), synchronous DRAM (SDRAM), double data rate SDRAM (DDR SDRAM), and direct RAM bus RAM (DRRAM). The memory can store an operating system that controls or allocates resources of a computing device.

A “module”, as used herein, includes, but is not limited to, non-transitory computer readable medium that stores instructions, instructions in execution on a machine, hardware, firmware, software in execution on a machine, and/or combinations of each to perform a function(s) or an action(s), and/or to cause a function or action from another module, method, and/or system. A module may also include logic, a software controlled microprocessor, a discrete logic circuit, an analog circuit, a digital circuit, a programmed logic device, a memory device containing executing instructions, logic gates, a combination of gates, and/or other circuit components. Multiple modules may be combined into one module and single modules may be distributed among multiple modules.

An “operable connection”, or a connection by which entities are “operably connected”, is one in which signals, physical communications, and/or logical communications can be sent and/or received. An operable connection can include a wireless interface, a physical interface, a data interface and/or an electrical interface.

A “processor”, as used herein, processes signals and performs general computing and arithmetic functions. Signals processed by the processor can include digital signals, data signals, computer instructions, processor instructions, messages, a bit, a bit stream, or other means that can be received, transmitted and/or detected. Generally, the processor can be a variety of various processors including multiple single and multicore processors and co-processors and other multiple single and multicore processor and co-processor architectures. The processor can include various modules to execute various functions.

A “portable device”, as used herein, is a computing device typically having a display screen with user input (e.g., touch, keyboard) and a processor for computing. Portable devices

include, but are not limited to, handheld devices, mobile devices, smart phones, laptops, tablets and e-readers. In some embodiments, a “portable device” could refer to a remote device that includes a processor for computing and/or a communication interface for receiving and transmitting data remotely.

A “vehicle”, as used herein, refers to any moving vehicle that is capable of carrying one or more human occupants and is powered by any form of energy. The term “vehicle” includes, but is not limited to: cars, trucks, vans, minivans, SUVs, motorcycles, scooters, boats, go-karts, amusement ride cars, rail transport, personal watercraft, and aircraft. In some cases, a motor vehicle includes one or more engines. Further, the term “vehicle” can refer to an electric vehicle (EV) that is capable of carrying one or more human occupants and is powered entirely or partially by one or more electric motors powered by an electric battery. The EV can include battery electric vehicles (BEV) and plug-in hybrid electric vehicles (PHEV). The term “vehicle” can also refer to an autonomous vehicle and/or self-driving vehicle powered by any form of energy. The autonomous vehicle may or may not carry one or more human occupants. Further, the term “vehicle” can include vehicles that are automated or non-automated with pre-determined paths or free-moving vehicles.

A “wearable computing device”, as used herein can include, but is not limited to, a computing device component (e.g., a processor) with circuitry that can be worn by and/or in possession of a user. In other words, a wearable computing device is a computer that is subsumed into the personal space of a user. Wearable computing devices can include a display and can include various sensors for sensing and determining various parameters associated with a user. For example, location, motion, and biosignal (physiological) parameters, among others. Some wearable computing devices have user input and output functionality. Exemplary wearable computing devices can include, but are not limited to, watches, glasses, clothing, gloves, hats, shirts, jewelry, rings, earrings necklaces, armbands, shoes, earbuds, headphones and personal wellness devices.

A “value” and “level”, as used herein can include, but is not limited to, a numerical or other kind of value or level such as a percentage, a non-numerical value, a discrete state, a discrete value, a continuous value, among others. The term “value of X” or “level of X” as used throughout this detailed description and in the claims refers to any numerical or other kind of value for distinguishing between two or more states of X. For example, in some cases, the value or level of X may be given as a percentage between 0% and 100%. In other cases, the value or level of X could be a value in the range between 1 and 10. In still other cases, the value or level of X may not be a numerical value, but could be associated with a given discrete state, such as “not X”, “slightly x”, “x”, “very x” and “extremely x”.

I. System Overview

Referring now to the drawings, wherein the showings are for purposes of illustrating one or more exemplary embodiments and not for purposes of limiting same, FIG. 1 is a schematic view of an operating environment 100 for implementing systems and methods for vehicle collision avoidance at an intersection according to an exemplary embodiment. The components of the environment 100, as well as the components of other systems, hardware architectures, and software architectures discussed herein, can be combined, omitted, or organized into different architectures for various embodiments.

Generally, the environment **100** includes an intersection collision avoidance (ICA) application **102** that is utilized to predict behaviors (e.g., path of travel, rate of travel, direction of travel, overlap between travel paths, etc.) of a plurality of vehicles at an intersection. It is to be appreciated that for purposes of simplicity one or more of the plurality of vehicles located near or at the intersection will be classified by the ICA application **102** as one or more reference vehicles **104** and another one or more of the plurality of vehicles located near or at the intersection will be classified as one or more target vehicles **106**. As discussed in more detail below, data can be transmitted from one or more reference vehicles **104** to one or more roadside equipment (units) **108** (RSE) to provide a collision avoidance response at one or more of the target vehicles **106** that receive the data in a processed format from the RSE **108**. As described in more detail below, the ICA application **102** can be executed on a head unit **110** of the reference vehicle(s) **104**, a head unit **112** of the target vehicle(s) **106**, a control unit(s) **114** of the RSE **108**, and/or on an externally hosted computing infrastructure **154** that is accessed by the head units **110**, **112** and/or the control unit(s) **114**. Additionally, the ICA application **102** can utilize additional components of the reference vehicle(s) **104**, the target vehicle(s) **106**, and the RSE **108**.

In the illustrated embodiment of FIG. 1, the reference vehicle(s) **104** and target vehicle(s) **106** can both include a respective vehicle computing device **116**, **118** (VCD) with provisions for processing, communicating and interacting with various components of the vehicles **104**, **106** and other components of the environment **100**. In one embodiment, the VCDs **116**, **118** can be implemented on the head units **110**, **112** and respective electronic control units (not shown), among other components of the reference vehicle(s) **104** and target vehicle(s) **106**. Generally, the VCDs **116**, **118** includes a respective processor (not shown), a respective memory (not shown), a respective disk (not shown), and a respective input/output (I/O) interface (not shown), which are each operably connected for computer communication via a respective bus (not shown). The I/O interfaces provide software and hardware to facilitate data input and output between the components of the VCDs **116**, **118** and other components, networks, and data sources, of the environment **100**.

As will be described in more detail below, in one or more embodiments, the ICA application **102** can communicate one or more data commands to the VCD **118** to provide the collision avoidance response. Specifically, one or more components of the ICA application **102** can communicate one or more data commands to the VCD **118** to provide collision prevention warnings and/or autonomous vehicle collision controls. In an exemplary embodiment, the collision avoidance response can be provided by the ICA application **102** based on an estimated probability of collision between the target vehicle(s) **106** and the reference vehicle(s) **104** approaching and/or traveling through the intersection. As discussed below, the VCD **118** can provide the collision prevention warnings in the form of audio, visual, and/or tactile warnings to the driver(s) of the target vehicle(s) **106** to warn of the estimated probability of collision between the target vehicle(s) **106** and the reference vehicle(s) **104**. Additionally, the VCD **118** can control one or more vehicle functions (e.g., steering, accelerating, braking, etc.) to provide the autonomous vehicle collision controls to control the target vehicle(s) **106** to avoid a collision with the reference vehicle(s) **104** based on the estimated probability of collision between the target vehicle(s) **106** and the reference vehicle(s) **104**.

The VCDs **116**, **118** are also operably connected for computer communication (e.g., via the bus and/or the I/O interface) to the head units **110**, **112**. The head units **110**, **112** can be connected to one or more respective display devices (not shown) (e.g., display screens), respective audio devices (not shown) (e.g., audio system, speakers), respective haptic devices (not shown) (e.g., haptic steering wheel), etc. that are utilized to provide a human machine interface (HMI) (not shown) to provide a driver(s) of the target vehicle(s) **106** and/or the reference vehicle(s) **104** with various types of information.

In some embodiments, the head units **110**, **112** can include respective storage units **120**, **122**. In alternate embodiments, the storage units **120**, **122** can be included as stand alone components of the reference vehicle(s) **104** and/or the target vehicle(s) **106**. The storage units **120**, **122** can store one or more operating systems, applications, associated operating system data, application data, vehicle system and subsystem user interface data, and the like that are executed by the VCDs **116**, **118** and/or the head units **110**, **112**. As will be discussed in more detail below, in an exemplary embodiment, the storage unit(s) **120** of the reference vehicle(s) **104** can be utilized by the ICA application **102** to store one or more vehicle parameters that are associated with the reference vehicle(s) **104**. Additionally, the storage unit(s) **122** of the target vehicle(s) can be utilized by the ICA application **102** to store one or more vehicle parameters that are associated with the target vehicle(s) **106**.

The reference vehicle(s) **104** and the target vehicle(s) **106** can additionally include respective on-board equipment (OBE) **124**, **126**. In one embodiment, the OBEs **124**, **126** can include a respective processor (not shown), a respective memory (not shown), a respective disk (not shown), and a respective input/output (I/O) interface (not shown), which are each operably connected for computer communication via a respective bus (not shown). In an alternate embodiment, the OBE **124**, **126** are operably controlled by the respective VCDs **116**, **118** of the reference vehicle(s) **104** and the target vehicle(s) **106**.

The OBE **124**, **126** can include a respective communications device (not shown) that can communicate with one or more components of the operating environment **100** and/or additional systems and components outside of the operating environment **100**. The respective communication device of each OBE **124**, **126** can include, but is not limited to, one or more transceivers (not shown), one or more receivers (not shown), one or more transmitters (not shown), one or more antennas (not shown), and additional components (not shown) that can be utilized for wired and wireless computer connections and communications via various protocols. For example, the respective communication device can use a dedicated short range communication protocol (DSRC network) that can be used to provide data transfer to send/receive electronic signals with one or more RSE **108** to be utilized by the ICA application **102** over a respective RSE to OBE communication network. For example, the DSRC network can be configured to operate in a 5.9 GHz band that includes an approximate bandwidth of ~75 MHz and an approximate range of ~1610 m in order for the reference vehicle(s) **104** and the target vehicle(s) **106** to communicate with the RSE **108** over the RSE to OBE communication network. It is to be appreciated that in some embodiments, the OBE **124** of the reference vehicle(s) **104** and the OBE **126** of the target vehicle(s) **106** can directly communicate via the DSRC communication protocol via a vehicle to vehicle (V2V) network.

The reference vehicle(s) **104** and the target vehicle(s) **106** can additionally include respective vehicle sensors **128, 130** that can sense and provide the one or more vehicle parameters that are associated with the reference vehicle(s) **104** and the target vehicle(s) **106** to be used by the ICA application **102**. It is understood that the vehicle sensors **128, 130** can include, but are not limited to, sensors associated with respective vehicle systems **132, 134** and other sensors associated with the reference vehicle(s) **104** and target vehicle(s) **106**. Specific vehicle sensors **128, 130** can include, but are not limited to, vehicle speed sensors, vehicle acceleration sensors, vehicle angular velocity sensors, accelerator pedal sensors, brake sensors, steering wheel angle sensors, vehicle locational sensors (e.g., GNSS coordinates), vehicle directional sensors (e.g., vehicle compass), throttle position sensors, respective wheel sensors, anti-lock brake sensors, camshaft sensors, among other sensors. Other vehicle sensors **128, 130** can include, but are not limited to, cameras (not shown) mounted to the interior or exterior of the reference vehicle(s) **104** and target vehicle(s) **108**, radar and laser sensors mounted to the exterior of the of the reference vehicle(s) **104** and target vehicle(s), etc. Additionally, vehicle sensors **128, 130** can include specific types of sensors that provide data pertaining to road conditions and the surrounding environment of the vehicle(s) **104, 106**, such as, but not limited to, antilock brake sensors, daylight sensors, temperature sensors, wheel slip sensors, traction control sensors, etc. It is understood that the vehicle sensors **128, 130** can be any type of sensor, for example, acoustic, electric, environmental, optical, imaging, light, pressure, force, thermal, temperature, proximity, among others.

The reference vehicle(s) **104** and the target vehicle(s) **106** can additionally include respective vehicle systems **132, 134** that can sense and provide the one or vehicle parameters that are associated with the reference vehicle(s) **104** and the target vehicle(s) **106** to be used by the ICA application **102**. It is understood that the vehicle systems **132, 134** can include, but are not limited to, systems associated with respective vehicle sensors **128, 130** and other subsystems associated with the reference vehicle(s) **104** and target vehicle(s) **106**. Specific vehicle systems **132, 134** can include, but are not limited to, an electronic stability control system, an anti-lock brake system, a brake assist system, an automatic brake prefill system, a low speed follow system, a cruise control system, a collision warning system, a collision mitigation braking system, an auto cruise control system, a lane departure warning system, a blind spot indicator system, a lane keep assist system, a navigation system, a transmission system, brake pedal systems, an electronic power steering system, visual devices (e.g., camera systems, proximity sensor systems), a climate control system, an electronic pretensioning system, among others.

In an exemplary embodiment, the vehicle sensors **128, 130** and/or the vehicle systems **132, 134** are operable to output one or more data signals associated with reference vehicle(s) **104** and target vehicle(s) **106** to the storage units **120, 122**, the head units **110, 112**, the VCDs **116, 118**, and/or the OBE **124, 126**. As will be described in more detail below, these data signals can be converted by one or more components of the ICA application **102** into one or more vehicle parameters associated with the reference vehicle(s) **104** and target vehicle(s) **106**. The one or more vehicle parameters associated with vehicles **104, 106** can be indicative of at least one of, positional parameters, directional parameters, and/or dynamic parameters. Positional parameters can include data that pertains to the position (e.g., GNSS coordinates at or near the intersection) of the reference vehicle(s)

104 and the target vehicle(s) **106**. Directional parameters can include data that pertains to the directional orientation (e.g., heading at or near the intersection) of the reference vehicle(s) **104** and the target vehicle(s) **106**. Dynamic parameters can include data that pertains to vehicle dynamics that include but are not limited to angular velocity and acceleration (hereinafter referred to as velocity) (e.g., real-time speed), braking, signal usage, steering angle, roll, pitch, yaw, etc. of the reference vehicle(s) **104** and the target vehicle(s) **106**. Additionally, the dynamic parameters can include data that pertains to road conditions of the roadway (e.g., based on antilock break sensors, wheel slip sensors, etc.) on which the reference vehicle(s) **104** and the target vehicle(s) **106** are traveling.

In one or more exemplary embodiments, specific vehicle sensors **128, 130** including but not limited to GPS sensors can be utilized to provide the positional parameters that can include data that pertains to the position (e.g., GNSS coordinates) of the reference vehicle(s) **104** and/or the target vehicle(s) **106** that are approaching and/or traveling through the intersection. In additional embodiments, specific vehicle systems **132, 134** including, but not limited to the navigation system can be utilized to provide the positional parameters that can include data that pertains to the position of the reference vehicle(s) **104** and/or the target vehicle(s) **106**.

In some embodiments, one or more magnetometers of the vehicle sensors **128, 130** can provide the directional parameters that can include data that pertains to the directional orientation (e.g., heading at or near the intersection) of the reference vehicle(s) **104** and/or the target vehicle(s) **106**. In one or more embodiments, various vehicle sensors **128, 130** including speed sensors, acceleration sensors, brake sensors, signal sensors, wheel sensors, can output data signals pertaining to the dynamic performance of the reference vehicle(s) **104** and/or the target vehicle(s) **106**. Additionally, in some embodiments, cameras mounted to the interior or exterior of the reference vehicle(s) **104** and/or target vehicle(s) **106**, radar and laser sensors mounted to the exterior of the reference vehicle(s) **104** and/or target vehicle(s) **106** that are included as part of the vehicle systems **132, 134** can be utilized to provide one or more dynamic parameters.

As mentioned above, the operating environment **100** also includes one or more RSE **108** that can be included at the intersection. The one or more RSE **108** can include devices that are located at various locations within and surrounding the intersection. For example, the one or more RSE **108** can be included as devices that are attached to one or more street lights, traffic lights, road signs, and the like that are located at or near the intersection. Additionally, one or more RSE **108** can be included as devices that are included within the roadway. For example, one or more RSE **108** can be included as in-road devices that are positioned on one or more lane markers of the roadways that make up the intersection.

The control unit(s) **114** (e.g., a processor) of the one or more RSE **108** can process and compute functions associated with the components of the RSE **108**. The RSE **108** can additionally include a communication device(s) **136** that can communicate with one or more components of the operating environment **100** and/or additional systems and components outside of the operating environment **100**. The communication device(s) **136** of the RSE **108** can include, but is not limited to, one or more transceivers (not shown), one or more receivers (not shown), one or more transmitters (not shown), one or more antennas (not shown), and additional components (not shown) that can be used for wired and

wireless computer connections and communications via various protocols, as discussed in detail above.

The communications device(s) **136** can be additionally used by one or more components of the RSE **108** to communicate with components that are residing externally from the RSE **108**. For example, the control unit(s) **114** can utilize the communication device(s) **136** to access the head units **110**, **112**, and/or the external computing infrastructure to execute one or more externally hosted applications, including the ICA application **102**.

The RSE **108** can additionally include a storage unit(s) **138**. The storage unit(s) **138** can store one or more operating systems, applications, associated operating system data, application data, and the like that are executed by the control unit(s) **114**. As will be discussed in more detail below, the storage unit(s) **138** can be accessed by the ICA application **102** to store the one or more vehicle behavioral maps that are processed by the ICA application **102**.

The RSE **108** can additionally include environmental sensors **140**. The environmental sensors **140** can include, but are not limited to, cameras, proximity sensors, motion sensors, temperature sensors, precipitation sensors, etc. The environmental sensors **140** can include control logic that is designed to determine environmental conditions that are present within the vicinity of the intersection and are output as one or more data signals (by sensing and/or downloading data) in the form of one or more environmental parameters. The one or more environmental parameters can reflect natural and man-made conditions that persist within a vicinity of the intersection (a predetermined area surrounding the intersection). In one embodiment, the environmental parameter(s) can be indicative of at least one of, infrastructure data, traffic data, and/or weather data. Infrastructure data can include, but is not limited to, data pertaining to the characteristics of infrastructure (e.g., width, length, number of lanes, number of intersection roadways, curbs, objects, speed limits, traffic lights/stop signs, etc.) of the intersection. Traffic data can include, but is not limited to, data pertaining to traffic patterns within the vicinity of the intersection. For example, traffic data can include metrics regarding traffic slowdown/stoppage based on various traffic issues including, but not limited to, vehicle accidents, road construction, and the like. Weather data can include, but is not limited to, data pertaining to natural weather conditions within the vicinity of the intersection. The weather data can include information regarding time of day, daylight, temperature, precipitation, etc. that can influence roadway conditions at the intersection. For example, the weather data can indicate snow and sleet that can cause icy roadway conditions at the intersection.

In one embodiment, the communications device(s) **136** can be utilized to connect to an externally hosted traffic control center (not shown) in order for the RSE **108** to upload and/or download environmental parameters that are indicative of traffic data and/or infrastructure data. In another embodiment, the communications device(s) **136** can also be utilized to connect to an externally hosted weather monitoring center (not shown) in order for the RSE **108** to upload/download environmental parameters that are indicative of weather data. In some embodiments, the RSE **108** can determine traffic and weather data at the intersection by utilizing data provided by the environmental sensors **140** in conjunction with data provided by the externally hosted traffic control center and/or the externally hosted weather monitoring center.

In one or more embodiments, the RSE **108** can also include a map database(s) **142** that is hosted on the storage

unit(s) **138**. In another embodiment, the RSE **108** can utilize the communication device(s) **136** to access the map database(s) **142** that is hosted on the externally hosted computing infrastructure **154**. In an exemplary embodiment, the map database(s) **142** can include data that pertains to geographical maps and satellite/aerial imagery of the intersection in the form of road network data, landmark data, aerial view data, street view data, political boundary data, centralized traffic data, centralized infrastructure data, etc. As discussed below, the ICA application **102** can query the map database(s) **142** to obtain an intersection map and associated data.

II. The ICA Application and Related Methods

The components of the ICA application **102** will now be described according to an exemplary embodiment and with reference to FIG. **1**. In an exemplary embodiment, the ICA application **102** can be stored on one or more of the storage units **120**, **122**, **138** and executed by one or more of the head unit(s) **110** of the reference vehicle(s) **104**, the head unit(s) **112** of the target vehicle(s) **106**, and/or the control unit(s) **114** of the RSE **108**. In another embodiment, the ICA application **102** can be stored on the externally hosted computing infrastructure **154** and can be accessed by the OBE **124**, **126** of the vehicles **104**, **106** and/or the communication device(s) **136** of the RSE **108** to be executed by the head unit(s) **110** of the reference vehicle(s) **104**, the head unit(s) **112** of the target vehicle(s) **106**, and/or the control unit(s) **114** of the RSE **108**.

The general functionality of the ICA application **102** will now be discussed. In an exemplary embodiment, the ICA application **102** can include a reference vehicle data collection module **144**, a behavioral map processing module **146**, a behavioral map data transmission module **148**, a confidence table processing module **150**, and a collision avoidance determinant module **152**. In an exemplary embodiment, the ICA application **102** executes a training phase of the application **102** that is initiated to evaluate one or more vehicle parameters associated with the one or more reference vehicles **104** that are approaching and/or traveling through the intersection. During the training phase of the application **102**, the RSE **108** can communicate with the OBE **124** of the reference vehicle(s) **104** to gather vehicle parameters to build one or more vehicle behavioral maps that indicate one or more vehicle parameters associated with the reference vehicle(s) **104**. Additionally, the vehicle behavioral map(s) can include environmental parameters provided by the RSE **108** and/or the externally hosted traffic center/weather center. Upon building the one or more vehicle behavioral maps, the application **102** can execute a collision avoidance phase of the ICA application **102**. During the collision avoidance phase, the RSE **108** can communicate with the OBE **126** of the target vehicle(s) **106** to transmit the one or more vehicle behavioral maps to the OBE **126** to provide a collision avoidance response at the target vehicle(s) **106**. For example, the communication device(s) **136** can utilize the DSRC network to send/receive electronic signals with the reference vehicle(s) **104** and/or the target vehicle(s) **106** over the respective RSE to OBE communication network. As described in more detail below, the one or more behavioral maps can be processed by the ICA application **102** to build a confidence table of the predicted path of one or more reference vehicles **104** along with environmental conditions to estimate a probability of collision between the reference vehicle(s) **104** and the target vehicle(s) **106**.

FIG. **2** is a process flow diagram of a method **200** for providing vehicle collision avoidance executed by the ICA application **102** from the operating environment of FIG. **1**

according to an exemplary embodiment. FIG. 2 will be described with reference to the components of FIG. 1, though it is to be appreciated that the method of FIG. 2 can be used with other systems/components. At block 202, the method includes receiving vehicle parameters from a reference vehicle(s) 104 and environmental parameters from roadside equipment.

In an exemplary embodiment, the reference vehicle data collection module 144 of ICA application 102 can utilize the environmental sensors 140 of one or more RSE 108 located at the intersection to determine the existence of one or more vehicles that are approaching or traveling through the intersection. Upon determining the existence of one or more vehicles that are approaching or traveling through the intersection, the vehicle data collection module 144 can classify the vehicle(s) as the reference vehicle(s) 104. Upon classifying the reference vehicle(s) 104, the data collection module 144 can utilize the communication device(s) 136 of the RSE 108 to establish computer communication with the OBE 124 of the reference vehicle(s) 104.

As discussed above, the vehicle sensors 128 of the reference vehicle(s) 128 are operable to output one or more data signals that include vehicle parameters associated with reference vehicle(s) 104. In an exemplary embodiment, upon establishing computer communication between the RSE 108 and the OBE 124, the reference vehicle data collection module 144 receives the vehicle parameters in the form of one or more data signals that are provided by the vehicle sensors 128. As discussed above, the vehicle parameters associated with reference vehicle 104 are indicative of at least one of: the positional parameters, the directional parameters, and/or the dynamic parameters.

Upon the vehicle sensors 128 outputting the one or more data signals that pertain to the vehicle parameters, the reference vehicle data collection module 144 utilizes the OBE 124 of the reference vehicle(s) 104 to communicate (e.g., transmit) respective data signals to the communication device(s) 136 of the RSE 108. In an exemplary embodiment, upon receiving the one or more data signals that pertain to the vehicle parameters, the reference vehicle data collection module 144, can store the vehicle parameters sent from the OBE 124 within the storage unit(s) 138 of the RSE 108.

Also as discussed above, the environmental sensors 140 of the RSE 108 are operable to output one or more data signals that include the environmental parameters associated with vicinity of the intersection. In some embodiments, the environmental parameters associated with the vicinity of the intersection can be downloaded from the externally hosted computing infrastructure 154. In an exemplary embodiment, upon receiving the one or more data signals that pertain to the environmental parameters, the reference vehicle data collection module 144, can store the one or more environmental parameters within the storage unit(s) 138 of the RSE 108.

At block 204, the method includes processing a vehicle behavioral map based on the vehicle parameters and the environmental parameters. Specifically, the behavioral map processing module 146 can utilize the control unit(s) 114 of the RSE 108 to access the vehicle parameters and the environmental parameters (stored on the storage unit(s) 138) provided by the reference vehicle data collection module 144 to process the vehicle behavioral map.

Referring now to FIG. 3, a process flow diagram of a method 300 for processing the vehicle behavioral map from the operating environment of FIG. 1 according to an exemplary embodiment. FIG. 3 will be described with reference

to the components of FIG. 1, though it is to be appreciated that the method of FIG. 3 can be used with other systems/components.

At block 302, the method includes evaluating the vehicle parameters. In one embodiment, upon receiving the vehicle parameters provided by the reference vehicle data collection module 144, the behavioral map processing module 146 can evaluate the vehicle parameters to determine one or more attributes related the manner in which the reference vehicle(s) 104 will approach and/or travel through the intersection. Specifically, the behavioral map processing module 146 can evaluate the positional parameters, directional parameters, and/or dynamic parameters associated with the reference vehicle(s) 104 to determine the one or more attributes related to the manner in which the reference vehicle(s) 104 will approach and/or travel through the intersection. As an illustrative example, the behavioral map processing module 146 can evaluate the vehicle parameters to determine the position of the reference vehicle(s) 104 with respect to the intersection, the heading of the reference vehicle(s) 104 with respect to the intersection, the speed of the reference vehicle(s) 104 when approaching and passing through the intersection, the (driver's) intent to turn (based on signaling, braking), and additional factors such as road conditions that can impact the one or more possible directions in which the reference vehicle(s) 104 will approach and/or travel through the intersection.

At block 304, the method includes evaluating the environmental parameters. In one embodiment, the behavioral map processing module 146 can communicate with the environmental sensors 140 of the RSE 108 to determine further environmental conditions that are present within the vicinity of the intersection. As discussed, the environmental parameters can include natural and man-made conditions that can impact the one or more attributes related the manner in which the reference vehicle(s) 104 will approach and/or travel through the intersection. In some embodiments, the behavioral map processing module 146 can aggregate the infrastructure data, traffic data, and the weather data provided by the environmental sensors 140 and the infrastructure data, traffic data, and weather data received from the externally hosted traffic control center and/or the externally hosted weather monitoring center to more clearly determine environmental factors such as traffic and/or road conditions that can impact the one or more possible directions in which the reference vehicle(s) 104 will approach and/or travel through the intersection.

At block 306, the method includes determining if a requisite amount of vehicle parameters and environmental parameters have been evaluated. In an exemplary embodiment, the vehicle parameters and environmental parameters can continue to be evaluated by the behavioral map processing module 146 until a requisite amount of data is received to process the vehicle behavioral map that is reliable (i.e., completely includes one or more attributes related the manner in which the reference vehicle(s) 104 will approach and pass through the intersection). In one embodiment, based on the evaluation of the vehicle parameters and the environmental parameters, the behavioral map processing module 146 can determine intersection metrics that include, but are not limited to, traffic density, weather conditions, and/or the number of roadways that make up the intersection to determine if a requisite amount of vehicle parameter data and environmental parameter data have been evaluated. For example, if the intersection includes a large number of reference vehicles 104 and/or large number of possible routes that the reference vehicles 104 can travel

after passing through the intersection, the behavioral map processing module **146** may require a larger subset of vehicle parameter data to process the vehicle behavioral map. Similarly, if high traffic density, inclement weather, and/or low daylight visibility persists within the vicinity of the intersection, the behavioral map processing module **146** may require a larger subset of environmental parameter data to process the vehicle behavioral map.

If it is determined that the requisite amount of vehicle parameter data and environmental parameter data have not been evaluated (at block **306**), the method returns to block **302**, wherein the behavioral map processing module **146** continues to evaluate the vehicle parameters. However, if it is determined that the requisite amount of vehicle parameter data and environmental parameter data have been evaluated (at block **306**), at block **308** the method includes receiving an intersection map and associated data. In an exemplary embodiment, the behavioral map processing module **146** can access the map database(s) **142** of the RSE **108** to obtain the geographical map of the intersection. Specifically, the map database(s) **142** can be queried to obtain the geographical map of the intersection that can include, but is not limited to, road network data, landmark data, aerial view data, street view data, political boundary data, centralized traffic data, etc.

At block **310**, the method includes processing the vehicle behavioral map. In an exemplary embodiment, upon obtaining the geographical map of the intersection from the map database(s) **142** of the RSE **108**, the behavioral map processing module **146** can augment the geographical map with the location of one or more reference vehicles **104** that are approaching and/or traveling through the intersection. The behavioral map processing module **146** can additionally augment the geographical map with data that is indicative of expected vehicle maneuvers based on the evaluation of the vehicle parameters and the environmental parameters. In other words, the behavioral map processing module **146** can augment one or more possible route directions for each of the reference vehicles **104** approaching and/or traveling through the intersection based on the evaluated positional parameters, directional parameters, and/or dynamical parameters, captured by the vehicle sensors **128**, along with evaluated infrastructure data, traffic data, and/or weather data captured by the environmental sensors **140**, and/or provided by the externally hosted traffic control center and/or the externally hosted weather monitoring center.

In an exemplary embodiment, upon augmenting the geographical map, the behavioral map determinant module **136** can process the vehicle behavioral map by aggregating and packaging the augmented geographical map with additional vehicle parameter and environmental parameter data (e.g., vehicle speed, vehicle signal usage, vehicle break usage, directional orientation, weather conditions, traffic conditions, etc.). In some embodiments, the vehicle behavioral map can be processed as an overhead geographical map (as shown in FIG. **4**). However, it is to be appreciated that the vehicle behavioral map can be processed into various types of formats, including, but not limited to, a multi-dimensional table, a data matrix, a three-dimensional/street view geographical map, etc.

FIG. **4** is an illustration of the vehicle behavioral map **402** processed by behavioral map processing module **146** of the ICA application **102**. The vehicle behavioral map **402** shown in the illustration of FIG. **4** is presented as an over-head augmented geographical map that includes one or more

attributes related to the manner in which the reference vehicle(s) **104** will approach and pass through the intersection **404**.

In one or more embodiments, the vehicle behavioral map **402** can present one or more possible vehicle maneuvers **406** that the one or more reference vehicle(s) **104** can take as the reference vehicle(s) **104** approach and/or travel through the intersection **104**. Specifically, as discussed above, based on the evaluation of the vehicle parameters and the environmental parameters, the behavioral map processing module **146** can determine one or more possible vehicle maneuvers that can be represented by directional arrows **406** on the vehicle behavioral map **402**. The vehicle behavioral map **402** can also include a representation of the position of the one or more reference vehicles **104** that are located within the vicinity of the intersection **404**. As shown, the one or more reference vehicles **104** can additionally be presented in accordance with a respective directional orientation such as the reference vehicle **410** that is presented as heading in a north east position.

In some embodiments, the vehicle behavioral map **402** can include additional vehicle parameter data and environmental parameter data in the form of one or more data stamps **408** that are augmented near one or more reference vehicles **104**. In other embodiments, the data stamp(s) **408** can be provided as a data package that is not shown but is packaged into the vehicle behavioral map **402** to be evaluated by the confidence table processing module **150** of the ICA application **102** (as discussed below). The data stamp(s) **408** can include, but is not limited to, time of day, vehicle positional coordinates (e.g., GNSS coordinates), the directional orientation of the reference vehicle **104** (e.g., west), the speed of the reference vehicle **104**, traffic and weather conditions within the vicinity of the intersection, etc.) In one or more embodiments, upon processing the vehicle behavioral map, the behavioral map processing module **146** can utilize the storage unit(s) **138** of the RSE(s) **108** to store the behavioral map to be used for various purposes, including, but not limited to, transmission to one or more target vehicles **106** (as discussed below), historical data collection, transmission to the externally hosted traffic control center, etc. In an alternate embodiment, upon processing the vehicle behavioral map, the behavioral map processing module **146** can utilize the communication device(s) **136** of the RSE(s) **108** to transmit the vehicle behavioral map in the form of one or more data signals to the externally hosted computing environment to be used for the various purposes discussed above.

With reference back to FIG. **1**, in some embodiments, the ICA application **102** accounts for abnormal route activity that persists for a predetermined period of time that can negatively affect the training phase of the ICA application **102**. More specifically, such abnormal route activity can include, but is not limited to, traffic accidents, road construction, power outages affecting traffic lights, etc. that can adversely affect the processing of the vehicle behavioral map by the behavioral map processing module **146**. In other words, such abnormal route activity can adversely affect the ICA application **102** to provide a reliable collision avoidance response based on the evaluation of the vehicle behavioral map. In one embodiment, when the environmental parameters provided by the environmental sensors **140** and/or the environmental parameters communicated by externally hosted traffic control center (via the communication device(s) **136**) are indicative of an abnormal route activity based on an abnormal flow of traffic through the intersection, the control unit(s) **114** can communicate the presence of the

abnormal route activity to the behavioral map processing module 146 to temporarily stop the processing of the vehicle behavioral map. By stopping the processing of the vehicle behavioral map, the ICA application 102 can ensure that the abnormal route activity does not adversely affect the vehicle behavioral map with skewed and/or incorrect data that is based on the vehicle parameters and/or environmental parameters that are evaluated during the abnormal route activity.

In one or more embodiments, the behavioral map processing module 146 can restart the processing of the vehicle behavioral map upon the control unit(s) 114 communicating the presence of normal route activity that persists for a predetermined period of time to the behavioral map processing module 146. In an exemplary embodiment of the ICA application 102, upon processing the vehicle behavioral map, the ICA application 102 completes the training phase and commences the collision avoidance phase of the application 102 to provide the collision avoidance response at one or more target vehicles 106.

Referring again to FIG. 2, upon processing the vehicle behavioral map based on the vehicle parameters (at block 204), at block 206, the method includes transmitting the vehicle behavioral map to the target vehicle 106. In an exemplary embodiment, the behavioral map data transmission module 148 of the ICA application 102 can utilize the environmental sensors 140 of one or more RSE 108 located at the intersection to determine the existence of one or more vehicles that are approaching or traveling through the intersection. Upon determining the existence of one or more vehicles that are approaching or traveling through the intersection, the behavioral map data transmission module 148 can classify the vehicle(s) as the target vehicle(s) 106. Upon classifying the target vehicle(s) 106, the behavioral map data transmission module 148 can utilize the communication device(s) 136 of the RSE(s) 108 to establish computer communication with the OBE 126 of the target vehicle(s) 106. In an exemplary embodiment, upon establishing computer communication between the RSE(s) 108 and the OBE 126, the behavioral map data transmission module 148 transmits the vehicle behavioral map that was processed by the behavioral map processing module 146 at each RSE 108 in the form of one or more data signals to the OBE 126.

At block 208, the method includes processing a confidence table based on the vehicle behavioral map and vehicle parameters provided by the target vehicle 104. In an exemplary embodiment, the confidence table can be created for each target vehicle 106 approaching or traveling through the intersection. The confidence table can include a set of data elements that pertain to the vehicle parameters that are associated with one or more reference vehicles 104, each respective target vehicle 106, and environmental parameters that are associated with the intersection. It is to be appreciated that the confidence table can be processed into various types of formats, including, but not limited to, a multi-dimensional table, a data matrix, etc. As described in more detail below, the confidence table can be populated with data extracted from one or more vehicle behavioral maps and vehicle sensors 130 of the target vehicle(s) 106. As also will be described, the ICA application 102 can utilize the confidence table to provide a collision avoidance response at each target vehicle 106 approaching and/or traveling through the intersection. It is to be appreciated that the confidence table can also be utilized by various vehicle systems 134 including, but not limited to, vehicle safety systems to provide one or more safety features to the driver(s) of the target vehicle(s) 106.

FIG. 5 is a process flow diagram of a method 500 for processing a confidence table based on the vehicle behavioral map and vehicle parameters provided by the target vehicle(s) 106 from the operating environment of FIG. 1 according to an embodiment. FIG. 5 will be described with reference to the components of FIG. 1, though it is to be appreciated that the method of FIG. 5 can be used with other systems/components. At block 502, the method includes obtaining one or more behavioral maps. In an exemplary embodiment, upon the transmission of the vehicle behavioral map(s) from one or more RSE 108 located at the intersection to the OBE 126 of the target vehicle(s) 106, the confidence table processing module 150 can obtain the vehicle behavioral map(s) from the OBE 126. Upon obtaining the one or more vehicle behavioral maps from the OBE 126, the confidence table processing module 150 can store the one or more vehicle behavioral maps on the storage unit(s) 122 of the target vehicle(s) 106.

At block 504, the method includes processing the one or more behavioral maps into a confidence table(s). In one embodiment, when two or more RSE 108 transmit vehicle behavioral maps to the OBE 126 of the target vehicle(s) 106, upon obtaining the two or more vehicle behavioral maps, the confidence table processing module 150 can further evaluate the vehicle behavioral maps. Specifically, in one embodiment, the confidence table processing module 150 can evaluate the vehicle behavioral maps to extract data included within the vehicle behavioral maps. Upon extracting data from the vehicle behavioral maps, the confidence table processing module 150 can further evaluate the data to determine data consistencies and data inconsistencies between two or more vehicle behavioral maps. For example, the confidence table processing module 150 can determine data consistencies and/or data inconsistencies between the vehicle behavioral maps with respect to vehicle parameters that pertain to one or more reference vehicles 104 that are approaching or traveling through the intersection and/or environmental parameters that are associated with the vicinity of the intersection. Upon determining the data consistencies and data inconsistencies between the two or more vehicle behavioral maps, the confidence table processing module 150 can aggregate the consistencies between the two or more vehicle behavioral maps and can further populate the aggregated data into the confidence table(s).

In an alternate embodiment, if the intersection only includes a single RSE 108 that transmits a (single) vehicle behavioral map to the OBE 126 of the target vehicle(s) 106, upon receiving the behavioral map, the confidence table processing module 150 can further evaluate the vehicle behavioral map to extract data included within the vehicle behavioral map. Upon extracting the data, the behavioral map data transmission module 148 can convert the data into a format that can be populated into the confidence table.

At block 506, the method includes processing vehicle parameters of the target vehicle(s) 106 into the confidence table(s). In one embodiment, the confidence table processing module 150 can communicate with the vehicle sensors 130 of the target vehicle(s) 106 to receive vehicle parameters of the target vehicle(s) 106. Specifically, the confidence table processing module 150 can receive the positional parameters, directional parameters, and/or dynamic parameters associated with the target vehicle(s) 106. Upon receiving the vehicle parameters, the confidence table processing module 150 can convert the data into a format that can be populated into the confidence table. It is to be appreciated that the ICA application 102 can continually process the confidence table(s) with one or more behavioral maps and vehicle

parameters of the target vehicle(s) **106** to provide up to date real time data to provide the collision avoidance response at the target vehicle(s) **106** approaching and/or traveling through the intersection.

At block **508**, the method includes storing the confidence table(s) to be utilized to provide a collision avoidance response(s). In one embodiment, upon processing the confidence table(s) (at blocks **504** and **506**), the confidence table processing module **150** can utilize the storage unit(s) **122** of the target vehicle(s) **106** to store the confidence table(s) to be further utilized by the ICA application **102** to provide the collision avoidance response at the target vehicle(s) **106** approaching and/or traveling through the intersection. In another embodiment, upon processing the confidence table(s), the confidence table processing module **150** can communicate with the externally hosted computing infrastructure **154** to store the confidence table(s) to be further accessed and utilized by the ICA application **102**.

Referring again to FIG. 2, at block **210**, the method includes providing a collision avoidance response based on the confidence table. In an exemplary embodiment, the collision avoidance determinant module **152** of the ICA application **102** can access the confidence table(s) stored on the storage unit(s) **122** of the target vehicle(s) or the externally hosted computing infrastructure **154** to evaluate data contained within the confidence table(s). As will be described in more detail below, the data can be analyzed to estimate a probability of collision between the one or more reference vehicles **104** and the one or more target vehicles **106** approaching and/or traveling through the intersection. The collision avoidance determinant module **152** can utilize the estimation of the probability of collision to provide the collision avoidance response at the one or more target vehicles **106** approaching and/or traveling through the intersection to avoid a possible collision with one or more reference vehicles **104** that are also approaching and/or traveling through the intersection.

FIG. 6 is a process flow diagram of the method **600** for estimating a path of travel of the reference vehicle(s) **104** and the target vehicle(s) **106** to provide a collision avoidance response from the operating environment of FIG. 1 according to an embodiment. FIG. 6 will be described with reference to the components of FIG. 1, though it is to be appreciated that the method of FIG. 6 can be used with other systems/components. At block **602**, the method includes evaluating environmental parameters associated with the vicinity of the intersection. Specifically, the collision avoidance determinant module **152** can access the confidence table(s) stored on the storage unit **122** or the externally hosted computing infrastructure **154**. Upon accessing the confidence table(s), the collision avoidance determinant module **152** can evaluate the confidence table(s) to determine environmental parameters that include the infrastructure data, traffic data, and/or weather data that pertains to the infrastructure of the intersection, the real time traffic pattern within the vicinity of the intersection, and the real time weather within the vicinity of the intersection. Specifically, the collision avoidance determinant module **152** can determine infrastructure characteristics (e.g., width, length, number of lanes, number of intersection roadways, curbs, objects, speed limits, traffic lights/stop signs, etc.) of the intersection. The collision avoidance determinant module **152** can also determine the real time traffic pattern that can influence the flow of traffic that travels through the intersection. Additionally, the collision avoidance determinant module **152** can also determine the real time weather that can influence the road visibility and the flow of traffic that

travels through the intersection. As will be discussed in detail, the collision avoidance determinant module **152** can utilize the environmental parameters when estimating the future position of the reference vehicle(s) **104** and the target vehicle(s) **106** approaching or traveling through the intersection. Additionally, the environmental parameters can be further evaluated when determining if an overlap exists between the reference vehicle(s) **104** and the target vehicle(s) **106** approaching or traveling through the intersection.

At block **604**, the method includes evaluating the positional location of the reference vehicle(s) **104**. Specifically, the collision avoidance determinant module **152** can access the confidence table(s) to evaluate the positional parameters of the reference vehicle(s) **104** to determine a real time positional location of the reference vehicle(s) **104** which is indicative of the exact location of the reference vehicle(s) **104** with respect to the intersection (e.g., GNSS coordinates).

At block **606**, the method includes evaluating the directional location of the reference vehicle(s) **104**. Specifically, the collision avoidance determinant module **152** can access the confidence table(s) to evaluate the directional parameters of the reference vehicle(s) **104** to determine a real time directional orientation of the reference vehicle(s) **104** which is indicative of the heading of the reference vehicle(s) **104** as the reference vehicle(s) **104** is approaching and/or traveling through the intersection.

At block **608**, the method includes evaluating the vehicle dynamics the reference vehicle(s) **104**. Specifically, the collision avoidance determinant module **152** can access the confidence table(s) to evaluate the dynamic parameters of the reference vehicle(s) **104** to determine real time data pertaining to speed, braking, signal usage, steering angle, roll, pitch, yaw, etc. of the reference vehicle(s) **104** which can be utilized to estimate a rate of travel of the reference vehicle(s) **104** as the reference vehicle(s) **104** is approaching and/or is traveling through the intersection.

At block **610**, the method includes estimating a path of travel of the reference vehicle(s) **104**. In an exemplary embodiment, the collision avoidance determinant module **152** can aggregate the evaluated environmental parameters, positional location of the reference vehicle(s) **104**, directional location of the reference vehicle(s) **104** and the vehicle dynamics of the reference vehicle(s) **104** to estimate the path of travel of the reference vehicle(s) **104** as the reference vehicle(s) **104** is approaching and/or is traveling through the intersection.

FIG. 7 is an illustrative example of estimating an overlap between the expected path of the reference vehicle(s) **104** and the expected path of the target vehicle(s) **106** approaching and/or traveling through the intersection according to an exemplary embodiment. In an exemplary embodiment, the collision avoidance determinant module **152** can evaluate the positional location of the reference vehicle **104** (shown as y_0) and the directional orientation of the reference vehicle **104** (as represented by the arrow from y_0) to determine the direction in which the reference vehicle **104** will travel (left turn, right turn, straight, etc.) once the reference vehicle **104** passes through the intersection **702**. In some embodiments, the collision avoidance determinant module **152** can also evaluate the environmental data (based on the evaluation at block **602**) to determine that the intersection **702** is located a certain distance ahead of the reference vehicle **104**. Additionally, the collision avoidance determinant module **152** can evaluate the vehicle dynamics of the reference vehicle **104** to estimate the rate of travel of the reference vehicle **104** (based on the speed, acceleration, braking, signaling, etc.).

The rate of travel of the reference vehicle **104** can be utilized to predict a timeframe in which the reference vehicle **104** will arrive at the intersection **702**. As discussed above, the collision avoidance determinant module **152** can aggregate the evaluated data (at blocks **602**, **604**, **606**, and/or **608** of the method **600**) to estimate the path of travel of the reference vehicle **104** (shown as estimated positions y_1 , y_2 , y_3).

Referring again to FIG. **6**, at block **612**, the method includes evaluating the positional location of the target vehicle(s) **106**. Specifically, the collision avoidance determinant module **152** can utilize the vehicle sensors **130** to provide one or more real time vehicle parameters associated with the target vehicle(s) **106**. In one embodiment, the collision avoidance determinant module **152** can communicate with the GPS sensors to determine the positional parameters pertaining to the exact location of the target vehicle(s) **106** with respect to the intersection (e.g., GNSS coordinates).

At block **614**, the method includes evaluating the directional location of the target vehicle(s) **106**. In one embodiment, the collision avoidance determinant module **152** can communicate with one or more magnetometers of the vehicle sensors **130** that can be utilized to provide directional parameters pertaining to the heading of the target vehicle(s) **106** approaching or traveling through the intersection.

At block **616**, the method includes evaluating the vehicle dynamics of the target vehicle **106**. In one embodiment, the collision avoidance determinant module **152** can communicate with one or more sensors, including, but not limited to vehicle speed sensors, vehicle acceleration sensors, vehicle angular velocity sensors, accelerator pedal sensors, brake sensors, steering wheel angle sensors, signal sensors, throttle position sensors, etc. to determine real time data pertaining to speed, braking, signal usage, steering angle, roll, pitch, yaw, etc. of the target vehicle(s) **106** that can be utilized to estimate a rate of travel of the target vehicle(s) **106** as the target vehicle(s) **106** is approaching and/or is traveling through the intersection.

At block **618**, the method includes estimating a path of travel of the target vehicle(s) **106**. In an exemplary embodiment, the collision avoidance determinant module **152** can aggregate the evaluated environmental parameters, positional location of the target vehicle(s) **106**, directional location of the target vehicle(s) **106** and the vehicle dynamics of the target vehicle(s) **106** to estimate the path of travel of the target vehicle(s) **106** as the target vehicle(s) **106** is approaching and/or is traveling through the intersection.

Referring again to the illustrative example of FIG. **7**, the collision avoidance determinant module **152** can evaluate the positional location of the target vehicle **106** (shown as X_0) and the directional orientation of the target vehicle **106** (as represented by the arrow from x_0) to determine the direction in which the reference vehicle **104** will travel (left turn, right turn, straight, etc.) once the target vehicle **106** passes through the intersection **702**. In some embodiments, the collision avoidance determinant module **152** can also evaluate the environmental data (based on the evaluation at block **602**) to determine that the intersection **702** is located a certain distance ahead of the target vehicle **106**. Additionally, the collision avoidance determinant module **152** can evaluate the vehicle dynamics of the target vehicle **106** to estimate the rate of travel of the target vehicle **106** (based on the speed, acceleration, braking, signaling, etc.). The rate of travel of the target vehicle **106** can be utilized to predict a timeframe in which the target vehicle **106** will arrive at the intersection **702**. The collision avoidance determinant mod-

ule **152** can aggregate the evaluated data (at blocks **602**, **612**, **614**, and/or **616** of the method **600**) to estimate the path of travel of the target vehicle(s) **106** (shown as estimated positions x_1 , x_2 , x_3).

Referring again to FIG. **6**, at block **620**, the method includes determining if the estimated path of travel of the reference vehicle(s) **104** overlap with the estimated path of travel of the target vehicle(s) **106**. In an exemplary embodiment, the collision avoidance determinant module **152** can evaluate the estimated path of the reference vehicle(s) **104** (determined at block **610**) and the estimated path of the target vehicle(s) **106** (determined at block **618**) to determine one or more estimated points of overlap. As illustrated in FIG. **7**, the estimated path of the reference vehicle **104** will be compared to the estimated path of the target vehicle **106** to estimate an overlap of the estimated future position of the target vehicle **106** at x_3 and the estimate future position of the reference vehicle **104** at y_3 .

In an alternate embodiment, the collision avoidance determinant module **152** can access one or more vehicle behavioral maps from the storage unit **122** and/or the externally hosted computing infrastructure **154** to determine one or more points of overlap of the directional arrows (as shown in FIG. **4** as **406**) that represent the one or more possible vehicle maneuvers on the vehicle behavioral map(s).

At block **622**, the method includes estimating a probability of collision between the reference vehicle(s) **104** and the target vehicle(s) **106**. In an exemplary embodiment, the collision avoidance determinant module **152** can further evaluate the vehicle parameters of the reference vehicle(s) **104** and/or target vehicle(s) **106**, the environmental parameters associated with the vicinity of the intersection, additional data provided by the vehicle sensors **128**, **130**, and/or additional data provided by the vehicle systems **132**, **134** to estimate a probability of collision. In one or more embodiments, the probability of collision can include one or more values that can be indicative of an intensity and propensity of collision between the reference vehicle(s) **104** and the target vehicle(s) **106**. Some non-limiting exemplary embodiments of utilizing vehicle parameters, environmental parameters, and/or additional vehicle sensor/system data will now be discussed that can be utilized to determine the probability of collision between the reference vehicle(s) **104** and the target vehicle(s) **106**.

In one embodiment, collision avoidance determinant module **152** can utilize the vehicle parameters and environmental parameters to estimate a higher probability of collision when the reference vehicle(s) **104** and/or the target vehicle(s) **106** are traveling at a high rate of speed during heavy traffic conditions since drivers of the reference vehicle(s) **104** and/or target vehicle(s) **106** may have less reaction time to avoid the collision. Alternatively, the collision avoidance determinant module **152** can estimate a lower probability when the reference vehicle(s) **104** and/or the target vehicle(s) **106** are traveling at a low rate of speed during lighter traffic conditions.

In another embodiment, the collision avoidance determinant module **152** can communicate with the vehicle system(s) **134** of the target vehicle(s) **106** to evaluate vehicle safety system data to determine if the driver(s) has been warned of the potential collision with the reference vehicle(s) **104**. Vehicle systems **134**, including, but not limited to, a blind spot sensing system, a collision avoidance system, a lane keep assist system, and the like can be used to warn the driver(s) of the target vehicle(s) **106** of one or more potential safety hazards. The collision avoidance determinant module **152** can evaluate the safety system data to

determine if the reference vehicle(s) **104** is detected by the safety system data (i.e., the driver(s) of the target vehicle(s) **106** is provided a warning or notification of the presence or location of the reference vehicle(s) **104** at the intersection). Based on this evaluation, the collision avoidance determinant module **152** can increase or decrease the probability of collision since the driver(s) that have been warned of the presence of the reference vehicle(s) **104** may adjust for such a condition to avoid a collision.

In an additional embodiment, the collision avoidance determinant module **152** can communicate with the vehicle system(s) **134** of the target vehicle(s) **106** to evaluate navigation system data to determine if the driver(s) has inputted a destination and is following predetermined navigation directions. Specifically, the collision avoidance determinant module **152** can evaluate the navigation data to determine if driver of target vehicle(s) **106** is following a path (based on the predetermined navigation directions) that will directly intersect with the path of the reference vehicle(s) **104** approaching or traveling through the intersection. Based on this evaluation, the collision avoidance determinant module **152** can further evaluate additional vehicle parameters and/or environmental parameters to increase or decrease the probability of collision since the predetermined path of target vehicle(s) **106** can intersect with the path of reference vehicle(s) **104**. Therefore, the vehicle safety system data can be utilized by the collision avoidance determinant module **152** to estimate the probability of collision between the reference vehicle(s) **104** and the target vehicle(s) **106**. It is appreciated that various additional data supplied by the vehicle sensors **128**, **130**, the VCDs **116**, **118**, and/or additional vehicle systems **132**, **134** not discussed herein will be apparent to determine the probability of collision between the reference vehicle(s) **104** and the target vehicle(s) **106**. It is also to be appreciated that as the reference vehicle(s) **104** and the target vehicle(s) **106** are approaching and/or traveling through the intersection, the probability of collision between the reference vehicle(s) **104** and the target vehicle(s) **106** can be continuously updated.

At block **624**, the method includes providing a collision avoidance response. In an exemplary embodiment, the collision avoidance determinant module **152** can communicate with the VCD **118** to provide the collision avoidance response. The collision avoidance determinant module **152** can communicate with the VCD **118** to provide one or more collision prevention warnings to the driver(s) of the target vehicle(s) **106** via the vehicle systems **134** via audio, visual, or tactile feedback. Additionally, the collision avoidance determinant module **152** can also communicate with the VCD **118** to provide one or more autonomous vehicle collision controls in order decelerate the speed of the target vehicle(s) **106**, stop the target vehicle(s) **106** and/or alter the course of the target vehicle(s) **106**.

In one embodiment, the collision avoidance determinant module **152** can determine a collision probability range that is representative of the probability of collision between the reference vehicle(s) **104** and the target vehicle(s) **106**. For instance, the collision probability range can be divided into ten subunits, wherein a lower probability of collision can be represented as a value of 1 and an extremely high probability of collision can be represented as a value of 10. However, it is to be appreciated that the collision avoidance determinant module **152** can provide the estimation of the probability of collision in various types of formats such as different ranges, metrics, and values. In one or more embodiments, the collision avoidance determinant module **152** can provide the one or more collision prevention warnings and/or autonomous

vehicle collision controls at a level that corresponds to the collision probability range value. For example, a low intensity warning (indicative of a low collision probability range value such as 1-3 values) can include a simple audio buzzing warning that is presented to the driver of the target vehicle(s) **106**. A medium intensity warning (indicative of a medium collision probability range value such as 4-6 values) can include tactile feedback via a steering wheel of the vehicle followed by a gradual slowing down of the target vehicle(s) **106**. A high intensity warning (indicative of a high collision probability range value such as 7-10 values) can include tactile, audio, and visual feedback corresponding to autonomously changing the course of the target vehicle(s) **106** and/or stopping the target vehicle(s) **106**. It is appreciated that other embodiments are apparent to provide a collision avoidance response to one or more target vehicles **106**.

The embodiments discussed herein may also be described and implemented in the context of non-transitory computer-readable storage medium storing computer-executable instructions. Non-transitory computer-readable storage media includes computer storage media and communication media. For example, flash memory drives, digital versatile discs (DVDs), compact discs (CDs), floppy disks, and tape cassettes. Non-transitory computer-readable storage media may include volatile and nonvolatile, removable and non-removable media implemented in any method or technology for storage of information such as computer readable instructions, data structures, modules or other data. Non-transitory computer readable storage media excludes transitory and propagated data signals.

It will be appreciated that various implementations of the above-disclosed and other features and functions, or alternatives or varieties thereof, may be desirably combined into many other different systems or applications. Also that various presently unforeseen or unanticipated alternatives, modifications, variations or improvements therein may be subsequently made by those skilled in the art which are also intended to be encompassed by the following claims.

The invention claimed is:

1. A computer-implemented method for providing vehicle collision avoidance at an intersection, comprising:
 - receiving vehicle parameters from a reference vehicle and environmental parameters from roadside equipment (RSE), wherein the environmental parameters are indicative of infrastructure data, traffic data, and weather data associated with the vicinity of the intersection;
 - processing a vehicle behavioral map, wherein processing the vehicle behavioral map includes evaluating the vehicle parameters and the environmental parameters and augmenting a geographical map with a location of the reference vehicle and data that is indicative of expected vehicle maneuvers based on the vehicle parameters and the environmental parameters;
 - transmitting the vehicle behavioral map to a target vehicle;
 - processing a confidence table based on the vehicle behavioral map and the vehicle parameters provided by the target vehicle, wherein the confidence table is populated with data extracted from the vehicle behavioral map and the vehicle parameters provided by the target vehicle; and
 - providing a collision avoidance response based on the confidence table, wherein the collision avoidance response is provided to the target vehicle to avoid a possible collision with the reference vehicle at the intersection.

2. The computer-implemented method of claim 1, wherein receiving vehicle parameters from the reference vehicle includes receiving a data signal that is transmitted by on-board equipment (OBE) of the reference vehicle, wherein the vehicle parameters are indicative of at least one of: positional parameters, directional parameters, and dynamic parameters associated with the reference vehicle.

3. The computer-implemented method of claim 2, wherein receiving environmental parameters from roadside equipment includes receiving a data signal from environmental sensors of the RSE to the OBE of the reference vehicle.

4. The computer-implemented method of claim 3, wherein processing the vehicle behavioral map includes evaluating the vehicle parameters and the environmental parameters and augmenting the geographical map of the intersection with a positional location of the reference vehicle based on the positional parameters, a directional orientation of the reference vehicle based on the directional parameters, data that reflects the dynamic parameters of the reference vehicle, the environmental parameters associated with the vicinity of the intersection, and expected vehicle maneuvers of the reference vehicle.

5. The computer-implemented method of claim 1, further including stopping the processing of the vehicle behavioral map when abnormal intersection activity is determined based on the environmental parameters, wherein abnormal intersection activity is based on an abnormal flow of traffic through the intersection.

6. The computer-implemented method of claim 1, wherein transmitting the vehicle behavioral map to the target vehicle includes determining the existence of the target vehicle that is approaching or traveling through the intersection, establishing computer communication with OBE of the target vehicle, and transmitting a data signal to the OBE of the target vehicle.

7. The computer-implemented method of claim 1, wherein providing the collision avoidance response based on the confidence table includes evaluating the confidence table to estimate a path of travel of the reference vehicle approaching the intersection, wherein the estimated path of travel of the reference vehicle is based on the evaluation of environmental parameters associated with the vicinity of the intersection, a positional location of the reference vehicle, a directional location of the reference vehicle, and vehicle dynamics of the reference vehicle.

8. The computer-implemented method of claim 7, wherein providing the collision avoidance response based on the confidence table includes evaluating the confidence table to estimate a path of travel of the target vehicle approaching or traveling through the intersection, wherein the estimated path of travel of the target vehicle is based on the evaluation of environmental parameters associated with the vicinity of the intersection, a positional location of the target vehicle, a directional location of the target vehicle, and the vehicle dynamics of the target vehicle.

9. The computer-implemented method of claim 8, wherein providing the collision avoidance response based on the confidence table includes determining that the estimated path of travel of the reference vehicle overlaps with the estimated path of travel of the target vehicle and estimating a probability of collision between the reference vehicle and the target vehicle, wherein the collision avoidance response can be based on the probability of collision between the reference vehicle and the target vehicle.

10. A system for providing vehicle collision avoidance at an intersection, comprising:

a memory storing instructions that when executed by a processor cause the processor to:

receive vehicle parameters from a reference vehicle and environmental parameters from roadside equipment (RSE), wherein the environmental parameters are indicative of infrastructure data, traffic data, and weather data associated with the vicinity of the intersection;

process a vehicle behavioral map based on the vehicle parameters and the environmental parameters, wherein processing the vehicle behavioral map includes evaluating the vehicle parameters and the environmental parameters and augmenting a geographical map with a location of the reference vehicle and data that is indicative of expected vehicle maneuvers based on the vehicle parameters and the environmental parameters;

transmit the vehicle behavioral map to a target vehicle; process a confidence table based on the vehicle behavioral map and vehicle parameters provided by the target vehicle, wherein the confidence table is populated with data extracted from the vehicle behavioral map and vehicle parameters provided by the target vehicle; and provide a collision avoidance response based on the confidence table, wherein the collision avoidance response is provided to the target vehicle to avoid a possible collision with the reference vehicle at the intersection.

11. The system of claim 10, wherein a data signal that is transmitted by on-board equipment (OBE) of the reference vehicle that includes the vehicle parameters of the reference vehicle, wherein the vehicle parameters are indicative of at least one of: positional parameters, directional parameters, and dynamic parameters associated with the reference vehicle.

12. The system of claim 11, wherein a data signal from environmental sensors of the RSE is transmitted by the RSE to the OBE of the reference vehicle.

13. The system of claim 12, wherein the vehicle parameters and the environmental parameters are evaluated and the processor augments a geographical map of the intersection with a positional location of the reference vehicle based on the positional parameters, a directional orientation of the reference vehicle based on the directional parameters, data that reflects the dynamic parameters of the reference vehicle, the environmental parameters associated with the vicinity of the intersection, and expected vehicle maneuvers of the reference vehicle.

14. The system of claim 10, wherein the processor stops processing of the vehicle behavioral map when abnormal intersection activity is determined based on the environmental parameters, wherein abnormal intersection activity is based on an abnormal flow of traffic through the intersection.

15. The system of claim 10, wherein the processor determines the existence of the target vehicle that is approaching or traveling through the intersection, establishes computer communication with OBE of the target vehicle, and transmits a data signal to the OBE of the target vehicle.

16. The system of claim 10, wherein the confidence table is evaluated to estimate a path of travel of the reference vehicle approaching the intersection, wherein the estimated path of travel of the reference vehicle is based on the evaluation of environmental parameters associated with the vicinity of the intersection, a positional location of the reference vehicle, a directional location of the reference vehicle, and vehicle dynamics of the reference vehicle.

17. The system of claim 16, wherein the confidence table is evaluated to estimate a path of travel of the target vehicle

25

approaching or traveling through the intersection, wherein the estimated path of travel of the target vehicle is based on the evaluation of environmental parameters associated with the vicinity of the intersection, a positional location of the target vehicle, a directional location of the target vehicle, and the vehicle dynamics of the target vehicle.

18. The system of claim 17, wherein the processor determines that the estimated path of travel of the reference vehicle overlaps with the estimated path of travel of the target vehicle and estimates a probability of collision between the reference vehicle and the target vehicle, wherein the collision avoidance response can be based on the probability of collision between the reference vehicle and the target vehicle.

19. A non-transitory computer-readable storage medium storing instructions that when executed by a processor perform actions, comprising:

receiving vehicle parameters from a reference vehicle and environmental parameters from roadside equipment (RSE), wherein the environmental parameters are indicative of infrastructure data, traffic data, and weather data associated with the vicinity of the intersection;

processing a vehicle behavioral map, wherein processing the vehicle behavioral map includes evaluating the vehicle parameters and the environmental parameters

26

and augmenting a geographical map with a location of the reference vehicle and data that is indicative of expected vehicle maneuvers based on the vehicle parameters and the environmental parameters;

transmitting the vehicle behavioral map to a target vehicle;

processing a confidence table based on the vehicle behavioral map and vehicle parameters provided by the target vehicle, wherein the confidence table is populated with data extracted from the vehicle behavioral map and vehicle parameters provided by the target vehicle; and providing a collision avoidance response based on the confidence table, wherein the collision avoidance response is provided to the target vehicle to avoid a possible collision with the reference vehicle at the intersection.

20. The computer readable storage medium of claim 19, wherein providing the collision avoidance response based on the confidence table includes determining that an estimated path of travel of the reference vehicle overlaps with an estimated path of travel of the target vehicle and estimating a probability of collision between the reference vehicle and the target vehicle, wherein the collision avoidance response can be based on the probability of collision between the reference vehicle and the target vehicle.

* * * * *