

US009606336B2

(12) **United States Patent**
Komatsu et al.

(10) **Patent No.:** **US 9,606,336 B2**
(45) **Date of Patent:** **Mar. 28, 2017**

(54) **ZOOM LENS AND IMAGING APPARATUS**

(71) Applicant: **FUJIFILM Corporation**, Tokyo (JP)

(72) Inventors: **Daiki Komatsu**, Saitama-ken (JP);
Nobuaki Toyama, Saitama-ken (JP)

(73) Assignee: **FUJIFILM Corporation**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 219 days.

6,545,818 B2 * 4/2003 Usui G02B 15/173
359/683
7,505,213 B2 * 3/2009 Tsutsumi G02B 15/173
359/684
8,300,320 B2 10/2012 Kodaira
8,570,662 B2 * 10/2013 Eguchi G02B 15/17
348/340
8,879,164 B2 * 11/2014 Hori G02B 15/173
359/683
8,988,786 B2 * 3/2015 Shimomura G02B 15/173
359/683
9,001,433 B2 * 4/2015 Toyama G02B 13/18
359/686

(Continued)

(21) Appl. No.: **14/328,782**

(22) Filed: **Jul. 11, 2014**

(65) **Prior Publication Data**

US 2015/0015969 A1 Jan. 15, 2015

(30) **Foreign Application Priority Data**

Jul. 12, 2013 (JP) 2013-146209

(51) **Int. Cl.**
G02B 15/17 (2006.01)
G02B 15/173 (2006.01)
G02B 15/167 (2006.01)

(52) **U.S. Cl.**
CPC **G02B 15/17** (2013.01); **G02B 15/167**
(2013.01); **G02B 15/173** (2013.01)

(58) **Field of Classification Search**
CPC G02B 15/14; G02B 15/163; G02B 15/167;
G02B 15/17
USPC 359/687-688, 684
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,757,554 A 5/1998 Fukami
5,808,809 A 9/1998 Yahagi

FOREIGN PATENT DOCUMENTS

JP 09-15501 1/1997
JP 10-31157 2/1998

(Continued)

OTHER PUBLICATIONS

Geary, Joseph M. Introduction to Lens Design: With Practical ZEMAX Examples. Richmond, VA: Willmann-Bell, 2002. 23. Print.*
Japanese Official Action—2013-146209—Aug. 16, 2016.


Primary Examiner — Zachary Wilkes
(74) *Attorney, Agent, or Firm* — Young & Thompson

(57) **ABSTRACT**

A zoom lens includes: a first lens group having a positive refractive power which is fixed while changing magnification; two or more movable lens groups that move independently from each other while changing magnification; and a final lens group having a positive refractive power which is fixed while changing magnification, provided in this order from an object side. The zoom lens satisfying Conditional Formula (1) below:

$$1.30 < h / (Y \sin \theta) < 2.37 \quad (1).$$

19 Claims, 16 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

9,025,255 B2 * 5/2015 Toyama G02B 15/177
359/688
9,170,406 B2 * 10/2015 Toyama G02B 15/14
2012/0002300 A1 1/2012 Kodaira
2014/0320977 A1 10/2014 Yakita

FOREIGN PATENT DOCUMENTS

JP 2004-341238 12/2004
JP 2012-013817 1/2012
JP 2013-7898 1/2013
JP 2013-73196 4/2013
JP 2014-232313 12/2014
WO 2013/065299 5/2013

* cited by examiner

FIG. 1

EXAMPLE 1




FIG. 2




FIG. 3

EXAMPLE 2




FIG. 4

EXAMPLE 3




FIG. 5

EXAMPLE 4




FIG. 6




FIG. 7

EXAMPLE 6




FIG. 8

EXAMPLE 7






FIG. 9

EXAMPLE 1

WIDE ANGLE END



INTERMEDIATE



TELEPHOTO END






FIG. 10

EXAMPLE 2

WIDE ANGLE END



INTERMEDIATE



TELEPHOTO END






FIG. 11

EXAMPLE 3

WIDE ANGLE END



INTERMEDIATE



TELEPHOTO END






FIG.12

EXAMPLE 4

WIDE ANGLE END



INTERMEDIATE



TELEPHOTO END






FIG.13

EXAMPLE 5

WIDE ANGLE END



INTERMEDIATE



TELEPHOTO END






FIG. 14

EXAMPLE 6

WIDE ANGLE END



INTERMEDIATE



TELEPHOTO END






FIG. 15

EXAMPLE 7

WIDE ANGLE END



INTERMEDIATE



TELEPHOTO END





FIG. 16



ZOOM LENS AND IMAGING APPARATUS

CROSS REFERENCE TO RELATED APPLICATIONS

The present application claims priority under 35 USC §119 to Japanese Patent Application No. 2013-146209, filed on Jul. 12, 2013. The above application is hereby expressly incorporated by reference in its entirety, into the present application.

TECHNICAL FIELD

The present invention is related to a zoom lens for use in electronic cameras such as a digital camera, a video camera, a broadcast camera, a cinematic camera, and a surveillance camera. The present invention is also related to an imaging apparatus equipped with the zoom lens.

BACKGROUND ART

Wide angle zoom lenses for use in electronic cameras, and particularly, wide angle zoom lenses for use in broadcast cameras, are disclosed in Japanese Unexamined Patent Publication Nos. 9(1997)-015501 and 2012-013817. However, there are not many known wide angle zoom lenses for use in cinematic cameras, which have larger imaging elements than those of broadcast cameras.

In addition, the number of pixels in imaging elements for cinematic cameras is increasing. However, there are not many known high performance zoom lenses which are compatible with such imaging elements. Japanese Unexamined Patent Publication No. 10 (1998)-031157 discloses a high performance zoom lens having a five group configuration for use in broadcast cameras.

DISCLOSURE OF THE INVENTION

However, it cannot be said that the first lens group of the zoom lenses disclosed in Japanese Unexamined Patent Publication Nos. 9(1997)-015501, 2012-013817, and 10(1998)-031157 are sufficiently miniaturized, although the image sizes thereof are not overly large. Particularly in recent years, imaging styles have become varied, demand for portable zoom lenses is increasing, and lenses which are compact and lightweight in view of large image sizes are desired. Particularly, wide angle zoom lenses, which have not yet been proposed, are desired.

The present invention has been developed in view of the foregoing circumstances. It is an object of the present invention is to provide a compact, light weight, and high performance zoom lens that has a wide angle of view. It is another object of the present invention to provide an imaging apparatus equipped with such a zoom lens.

A first zoom lens of the present invention comprises:

a first lens group having a positive refractive power which is fixed while changing magnification;

two or more movable lens groups that move independently from each other while changing magnification; and

a final lens group having a positive refractive power which is fixed while changing magnification, provided in this order from an object side;

the zoom lens satisfying Conditional Formula (1) below.

$$1.30 < h / (Y_{img} \cdot \tan \theta) < 2.37 \quad (1)$$

wherein h is the height at which a chief ray of light having a maximum image height enters a first surface at a wide

angle end, Y_{img} is the maximum image height, and θ is the half angle of view at the wide angle end.

Here, it is preferable for the first lens group to comprise a 11 lens group having a negative refractive power, a 12 lens group having a positive refractive power, and a 13 lens group having a positive refractive power; and for the 12 lens group to move to perform focusing operations.

A second zoom lens of the present invention comprises: a first lens group having a positive refractive power which is fixed while changing magnification;

two or more movable lens groups that move independently from each other while changing magnification; and

a final lens group having a positive refractive power which is fixed while changing magnification, provided in this order from an object side;

the first lens group comprising a 11 lens group having a negative refractive power, a 12 lens group having a positive refractive power, and a 13 lens group having a positive refractive power;

the 12 lens group moving to perform focusing operations; and

the zoom lens satisfying Conditional Formula (2) below.

$$1.530 < n_{1a} < 1.670 \quad (2)$$

wherein n_{1a} is the average refractive index of the 11 lens group with respect to the d line.

In the first and second zoom lenses, the movable lens groups may be a second lens group having a negative refractive power and a third lens group having a negative refractive power, provided in this order from the object side.

Alternatively, the movable lens groups may be a second lens group having a negative refractive power, a third lens group having a positive refractive power, and a fourth lens group having a negative refractive power, provided in this order from the object side.

In addition, it is preferable for Conditional Formula (3) below to be satisfied.

$$1.95 < f_{13} / f_1 < 3.00 \quad (3)$$

wherein f₁ is the focal length of the first lens group, and f₁₃ is the focal length of the 13 lens group.

In addition, it is preferable for Conditional Formula (4) below to be satisfied.

$$-2.20 < f_{11} / Y_{img} < -1.50 \quad (4)$$

wherein f₁₁ is the focal length of the 11 lens group, and Y_{img} is a maximum image height.

In addition, it is preferable for the 12 lens group to comprise two pairs of cemented lenses.

In addition, it is preferable for the two pairs of cemented lenses of the 12 lens group to be a cemented lens formed by a positive lens and a negative lens, and a cemented lens formed by a negative lens and a positive lens, provided in this order from the object side.

In addition, it is preferable for the surface most toward the object side within the first lens group and the surface toward the object side of the lens second from the object side to be aspherical.

In addition, it is preferable for Conditional Formula (1-1) below to be satisfied.

$$1.70 < h / (Y_{img} \cdot \tan \theta) < 2.37 \quad (1-1)$$

In addition, it is preferable for Conditional Formula (2-1) below to be satisfied.

$$1.530 < n_{1a} < 1.665 \quad (2-1)$$

3

In addition, it is preferable for Conditional Formula (3-1) to be satisfied, and more preferable for Conditional Formula (3-2) to be satisfied.

$$2.10 < f_{13}/f_1 < 2.90 \quad (3-1)$$

$$2.20 < f_{13}/f_1 < 2.80 \quad (3-2)$$

In addition, it is preferable for Conditional Formula (4-1) to be satisfied, and more preferable for Conditional Formula (4-2) to be satisfied.

$$-2.10 < f_{11}/Y_{img} < -1.60 \quad (4-1)$$

$$-2.00 < f_{11}/Y_{img} < -1.65 \quad (4-2)$$

An imaging apparatus of the present invention is characterized by being equipped with the zoom lens of the present invention.

Note that the expression "comprises" means that the zoom lens of the present invention may also include lenses that practically have no power, optical elements other than lenses such as an aperture stop, a mask, a cover glass, and filters, and mechanical components such as lens flanges, a lens barrel, an imaging element, a camera shake correcting mechanism, etc., in addition to the lens groups which have been listed as constituent elements.

In addition, the surface shapes of lenses as well as the signs of the refractive powers of lenses are considered in the paraxial region for lenses that include aspherical surfaces.

The first zoom lens of the present invention comprises the first lens group having a positive refractive power which is fixed while changing magnification; two or more movable lens groups that move independently from each other while changing magnification; and the final lens group having a positive refractive power which is fixed while changing magnification, provided in this order from an object side. In addition, the first zoom lens of the present invention satisfies Conditional Formula (1) below. Therefore, it becomes possible to realize a compact, lightweight, and high performance zoom lens having a wide angle of view.

$$1.30 < h/(Y_{img} \cdot \tan \theta) < 2.37 \quad (1)$$

The second zoom lens of the present invention comprises: the first lens group having a positive refractive power which is fixed while changing magnification; two or more movable lens groups that move independently from each other while changing magnification; and the final lens group having a positive refractive power which is fixed while changing magnification, provided in this order from an object side. The first lens group comprises a 11 lens group having a negative refractive power, a 12 lens group having a positive refractive power, and a 13 lens group having a positive refractive power, and the 12 lens group moves to perform focusing operations. In addition, the zoom lens satisfies Conditional Formula (2) below. Therefore, it becomes possible to realize a compact, lightweight, and high performance zoom lens having a wide angle of view.

$$1.530 < n_{1a} < 1.670 \quad (2)$$

The imaging apparatus of the present invention is equipped with the zoom lens of the present invention. Therefore, the imaging apparatus can be designed to be compact and lightweight, is capable of imaging with a wide angle of view, and can obtain video having high image quality.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a collection of sectional diagrams that illustrate a first example of the configuration of a zoom lens according to an embodiment of the present invention (which is common with Example 1).

4

FIG. 2 is a diagram that illustrates the paths of light rays that pass through the zoom lens according to the embodiment of the present invention (which is common with Example 1).

FIG. 3 is a collection of sectional diagrams that illustrate the configuration of a zoom lens according to Example 2.

FIG. 4 is a collection of sectional diagrams that illustrate the configuration of a zoom lens according to Example 3.

FIG. 5 is a collection of sectional diagrams that illustrate the configuration of a zoom lens according to Example 4.

FIG. 6 is a collection of sectional diagrams that illustrate the configuration of a zoom lens according to Example 5.

FIG. 7 is a collection of sectional diagrams that illustrate the configuration of a zoom lens according to Example 6.

FIG. 8 is a collection of sectional diagrams that illustrate the configuration of a zoom lens according to Example 7.

FIG. 9 is a collection of diagrams (A through L) that illustrate aberrations of the zoom lens of Example 1.

FIG. 10 is a collection of diagrams (A through L) that illustrate aberrations of the zoom lens of Example 2.

FIG. 11 is a collection of diagrams (A through L) that illustrate aberrations of the zoom lens of Example 3.

FIG. 12 is a collection of diagrams (A through L) that illustrate aberrations of the zoom lens of Example 4.

FIG. 13 is a collection of diagrams (A through L) that illustrate aberrations of the zoom lens of Example 5.

FIG. 14 is a collection of diagrams (A through L) that illustrate aberrations of the zoom lens of Example 6.

FIG. 15 is a collection of diagrams (A through L) that illustrate aberrations of the zoom lens of Example 7.

FIG. 16 is a schematic diagram that illustrates the configuration of an imaging apparatus according to an embodiment of the present invention.

BEST MODE FOR CARRYING OUT THE INVENTION

Hereinafter, embodiments of the present invention will be described in detail with reference to the attached drawings. FIG. 1 is a collection of sectional diagrams that illustrate the configuration of a zoom lens according to an embodiment of the present invention. FIG. 2 is a diagram that illustrates the paths of light rays that pass through the lens of FIG. 1. The example of the configuration illustrated in FIG. 1 and FIG. 2 is the same as the configuration of a zoom lens of Example 1 to be described later. In FIG. 1 and FIG. 2, the left side is the object side and the right side is the image side. In addition, FIG. 2 illustrates an axial light beam w_a and a light beam w_b at a maximum angle of view.

As illustrated in FIG. 1 and FIG. 2, this zoom lens is constituted by a first lens group G1 having a positive refractive power which is fixed while changing magnification, two or more movable lens groups (a second lens group G2 and a third lens group G3 in the present embodiment) that move independently from each other while changing magnification, an aperture stop St, and a final lens group (a fourth lens group G4 in the present embodiment) having a positive refractive power which is fixed while changing magnification, provided in this order along an optical axis Z from the object side. Note that the aperture stop St does not necessarily represent the size or the shape thereof, but the position thereof along the optical axis Z.

When this zoom lens is applied to an imaging apparatus, it is preferable for a cover glass, a prism, and various filters, such as an infrared cutoff filter and a low pass filter, to be provided between the optical system and an imaging surface Sim, depending on the configuration of the camera to which

5

the lens is mounted. Therefore, FIG. 1 and FIG. 2 illustrate an example in which a plane parallel plate shaped optical member PP that presumes such filters is provided between the lens system and the imaging surface Sim.

The first lens group G1 comprises a 11 lens group G11 5 having a negative refractive power, a 12 lens group G12 having a positive refractive power, and a 13 lens group G13, provided in this order from the object side. The 12 lens group G12 is configured to move to perform focusing operations. By adopting such a configuration, variations in the angle of view due to focusing operations can be suppressed. 10

In addition, the zoom lens is configured to satisfy Conditional Formula (1) below. By the value of $h/(Y_{img} \cdot \tan \theta)$ not exceeding the upper limit defined in Conditional Formula (1), the diameter of the 11 lens group G11 can be prevented from becoming excessively large, which contributes to miniaturization and a reduction in weight. In addition, a configuration in which the value of $h/(Y_{img} \cdot \tan \theta)$ is not less than the lower limit defined in Conditional Formula (1) is advantageous from the viewpoint of correcting field curvature and distortion. Note that more favorable properties can be achieved if the zoom lens satisfies Conditional Formula (1-1) below. 15

$$1.30 < h/(Y_{img} \cdot \tan \theta) < 2.37 \quad (1)$$

$$1.70 < h/(Y_{img} \cdot \tan \theta) < 2.37 \quad (1-1)$$

wherein h is the height at which a chief ray of light having a maximum image height enters a first surface at a wide angle end, Y_{img} is the maximum image height, and θ is the half angle of view at the wide angle end. 20

In addition, the zoom lens is configured to satisfy Conditional Formula (2) below. By the value of n_{1a} not exceeding the upper limit defined in Conditional Formula (2), the specific weight of glass materials can be prevented from becoming excessively large, which contributes to a reduction in weight. In addition, a configuration in which the value of n_{1a} is not less than the lower limit defined in Conditional Formula (2) is not only advantageous from the viewpoint of correcting field curvature and lateral chromatic aberration, but also can prevent the outer diameter and the thickness of the 11 lens group G11 from becoming excessively large, which contributes to miniaturization and a reduction in weight. Note that more favorable properties can be achieved if the zoom lens satisfies Conditional Formula (2-1) below. 25

$$1.530 < n_{1a} < 1.670 \quad (2)$$

$$1.530 < n_{1a} < 1.665 \quad (2-1)$$

wherein n_{1a} is the average refractive index of the 11 lens group with respect to the d line.

In the zoom lens of the present embodiment, an example is being described in which the second lens group G2 having a negative refractive power and the third lens group G3 having a negative refractive power, provided in this order from the object side, are the movable lens groups. Alternatively, the zoom lens having a five group configuration as a whole, in which the movable lens groups are a second lens group having a negative refractive power, a third lens group having a positive refractive power, and a fourth lens group having a negative refractive power, provided in this order from the object side. 30

In addition, it is preferable for Conditional Formula (3) below to be satisfied. A configuration in which the value of f_{13}/f_1 does not exceed the upper limit defined in Conditional 35

6

Formula (3) is not only advantageous from the viewpoint of correcting spherical aberration and field curvature, but also advantageous from the viewpoint of correcting spherical aberration and field curvature during focusing operations, and further can suppress variations in the angle of view during focusing operations. In addition, by the value of f_{13}/f_1 is not less than the lower limit defined in Conditional Formula (3), variations in the angle of view during focusing operations can be decreased, and the amount of movement necessary to perform focusing operations can be prevented from becoming excessively large, which contributes to miniaturization and a reduction in weight. Note that more favorable properties can be achieved if the zoom lens satisfies Conditional Formula (3-1) below, and more preferably Conditional Formula (3-2) below. 40

$$1.95 < f_{13}/f_1 < 3.00 \quad (3)$$

$$2.10 < f_{13}/f_1 < 2.90 \quad (3-1)$$

$$2.20 < f_{13}/f_1 < 2.80 \quad (3-2)$$

wherein f_1 is the focal length of the first lens group, and f_{13} is the focal length of the 13 lens group. 45

In addition, it is preferable for Conditional Formula (4) below to be satisfied. A configuration in which the value of f_{11}/Y_{img} does not exceed the upper limit defined in Conditional Formula (4) is not only advantageous from the viewpoint of correcting astigmatism, field curvature, and distortion, but also can prevent the diameters of the 12 lens group G12 and the 13 lens group G13 from becoming excessively large, which contributes to miniaturization and a reduction in weight. In addition, a configuration in which the value of f_{11}/Y_{img} is not less than the lower limit defined in Conditional Formula (4) is advantageous from the viewpoint of correcting spherical aberration and field curvature. Note that more favorable properties can be achieved if the zoom lens satisfies Conditional Formula (4-1) below, and more preferably Conditional Formula (4-2) below. 50

$$-2.20 < f_{11}/Y_{img} < -1.50 \quad (4)$$

$$-2.10 < f_{11}/Y_{img} < -1.60 \quad (4-1)$$

$$-2.00 < f_{11}/Y_{img} < -1.65 \quad (4-2)$$

wherein f_{11} is the focal length of the 11 lens group, and Y_{img} is a maximum image height.

In addition, it is preferable for the 12 lens group to comprise two pairs of cemented lenses. By adopting such a configuration, variations in spherical aberration, longitudinal chromatic aberration, and lateral chromatic aberration during focusing operations can be suppressed. 55

In this case, it is preferable for the two pairs of cemented lenses of the 12 lens group to be a cemented lens formed by a positive lens and a negative lens, and a cemented lens formed by a negative lens and a positive lens, provided in this order from the object side. Such a configuration is advantageous from the viewpoint of correcting longitudinal chromatic aberration and lateral chromatic aberration. 60

In addition, it is preferable for the surface most toward the object side within the first lens group and the surface toward the object side of the lens second from the object side to be aspherical. By adopting such a configuration, correction of astigmatism, field curvature, and distortion is facilitated, and such a configuration is also advantageous from the viewpoint of miniaturization. 65

In the present zoom lens, a specific preferred material of the component provided most toward the object side is glass. Alternatively, a transparent ceramic material may be employed.

In the case that the present zoom lens is to be utilized in an environment in which the zoom lens is likely to be damaged, it is preferable for a protective multiple layer film coating to be administered. Further, a reflection preventing coating may be administered in order to reduce the amount of ghost light during use, in addition to the protective coating.

In addition, FIG. 1 illustrates an example in which the optical member PP is provided between the lens system and the imaging surface Sim. Alternatively, various filters such as low pass filters and filters that cut off specific wavelength bands may be provided among each of the lenses instead of being provided between the lens system and the imaging surface Sim. As a further alternative, coatings that have the same functions as the various filters may be administered on the surfaces of the lenses.

Next, examples of numerical values of the zoom lens of the present invention will be described.

First, the zoom lens of Example 1 will be described. FIG. 1 is a collection of sectional diagrams that illustrate the lens configuration of the zoom lens of Example 1. Note that the optical member PP is also illustrated, the left side is the object side, the right side is the image side, and the aperture stop St in the drawings do not necessarily represent the size or the shape thereof, but the position thereof along the optical axis Z, in FIG. 1 and FIGS. 3 through 8 that correspond to Examples 2 through 7 to be described later.

The zoom lens of Example 1 is constituted by the first lens group G1 having a positive refractive power which is fixed while changing magnification, two the second lens group G2 that moves while changing magnification, the third lens group G3 that moves while changing magnification, and the fourth lens group G4 (final lens group) having a positive refractive power which is fixed while changing magnification.

Basic lens data are shown in Table 1, data related to various items are shown in Table 2, data related to the distances among movable surfaces are shown in Table 3, and aspherical surface coefficients are shown in Table 4, for the zoom lens of Example 1. In the following description, the meanings of the symbols in the tables will be described for Example 1. The meanings of the symbols are basically the same for Examples 2 through 7.

In the lens data of Table 1, i th ($i=1, 2, 3, \dots$) lens surface numbers that sequentially increase from the object side to the image side, with the lens surface at the most object side designated as first, are shown in the column Si. The radii of curvature of i th surfaces are shown in the column Ri, the distances between an i th surface and an $i+1$ st surface along the optical axis Z are shown in the column Di. The refractive indices of j th ($j=1, 2, 3, \dots$) optical elements that sequentially increase from the object side to the image side, with the optical element at the most object side designated as first, with respect to the d line (wavelength: 587.6 nm) are shown in the column Ndj. The Abbe's numbers of the j th optical element with respect to the d line are shown in the column v_{dj}. The partial dispersion ratios of j th optical elements ($j=1, 2, 3, \dots$) that sequentially increase from the object side to the image side, with the optical element at the most object side designated as first, are shown in the column θ_{gFj} .

Note that the partial dispersion ratio θ_{gF} is represented by the following formula.

$$\theta_{gF} = (N_g - N_F) / (N_F - N_C)$$

wherein N_g is the refractive index with respect to the g line, N_F is the refractive index with respect to the F line, and N_C is the refractive index with respect to the C line.

Here, the signs of the radii of curvature are positive in cases that the surface shape is convex toward the object side, and negative in cases that the surface shape is convex toward the image side. The aperture stop St and the optical member PP are also included in the basic lens data. Text reading "(aperture stop)" is indicated along with a surface number in the column of the surface numbers at the surface corresponding to the aperture stop. In addition, DD [i] is indicated in the column of the distances for distances that change while changing magnification. In addition, the lowermost value in the column Di is the distance between the surface of the optical member PP toward the image side and the imaging surface Sim.

Table 2 shows the values of the zoom magnification rates of the entire system, the focal lengths f (mm), the back focus Bf, F values (F No.), the angles of view (2ω), at the wide angle end, at an intermediate position, and at the telephoto end, respectively, as well as the maximum image height at the wide angle end, as the data related to various items.

In the basic lens data, the data related to various items, and the data related to the movable surfaces, am are used as the units for lengths and degrees are used as the units for angles. However, it is possible for optical systems to be proportionately enlarged or proportionately reduced and utilized. Therefore, other appropriate units may be used.

In the lens data of Table 1, the symbol "*" is appended to the surface numbers of aspherical surfaces, and numerical values that represent the paraxial radii of curvature are shown as the radii of curvature of the aspherical surfaces. The data of Table 4 related to aspherical surface coefficients show the surface numbers of the aspherical surfaces and aspherical surface coefficients related to the aspherical surfaces. The aspherical coefficients are the values of coefficients KA and Am ($m=3, 4, 5, \dots, 20$) in formula (A) below.

$$Zd = C \cdot h^2 / \{1 + (1 - KA \cdot C^2 \cdot h^2)^{1/2}\} + \sum Am \cdot h^m \quad (A)$$

wherein: Zd is the depth of the aspherical surface (the length of a normal line from a point on the aspherical surface at a height h to a plane perpendicular to the optical axis in contact with the peak of the aspherical surface), h is height (the distance from the optical axis), C is the inverse of the paraxial radius of curvature, and KA and Am ($m=3, 4, 5, \dots, 20$) are aspherical surface coefficients.

TABLE 1

Example 1: Lens Data					
Si (Surface No.)	Ri (Radius of Curvature)	Di (Distance)	Ndi (Re- fractive Index)	v _{dj} (Abbe's Number)	$\theta_{g, Fj}$ (Partial Dispersion Ratio)
*1	409.9270	4.5006	1.58313	59.38	0.5435
2	31.9478	17.0179			
*3	106.6254	2.9991	1.74400	44.78	0.5656
4	30.0422	14.4978			
5	-52.2008	2.2991	1.65160	58.55	0.5427
6	67.6585	6.1233	1.53172	48.84	0.5631
7	198.7908	4.9704			
8	139.4689	10.3618	1.80400	46.58	0.5573
9	-96.4727	DD [9]			
10	299.2196	8.9693	1.51742	52.43	0.5565

TABLE 1-continued

Example 1: Lens Data					
Si (Surface No.)	Ri (Radius of Curvature)	Di (Distance)	Ndi (Re- fractive Index)	vdj (Abbe's Number)	θ_g, F_j (Partial Dispersion Ratio)
11	-66.0762	3.9994	1.84661	23.78	0.6207
12	-106.4066	0.1491			
13	107.8632	2.5000	1.88100	40.14	0.5701
14	48.5554	10.7557	1.49700	81.54	0.5375
15	-310.8769	DD [15]			
16	-11732.3504	6.5205	1.49700	81.54	0.5375
17	-67.8512	0.1490			
18	193.0989	2.6893	1.43875	94.93	0.5343
19	30544.0697	DD [19]			
20	62.4444	3.0001	1.58913	61.14	0.5407
21	43.1799	6.0889			
22	-176.8246	1.1993	1.68893	31.07	0.6004
23	46.0137	3.3263			
24	55.5904	3.6577	1.78470	26.29	0.6136
25	-556.6621	DD [25]			
26	-69.9641	1.1991	1.60300	65.44	0.5402
27	44.5306	2.3725	1.80000	29.84	0.6018
28	106.1842	DD [28]			
29 (aperture stop)	∞	1.2990			
30	61.1821	2.9929	1.80100	34.97	0.5864
31	-479.0028	0.1492			
32	67.4770	19.7929	1.61800	63.33	0.5441
33	-30.4084	1.2003	1.90366	31.32	0.5948
34	98.6984	9.2684			
35	72.3486	4.3177	1.85002	32.40	0.5986
36	-51.8177	2.0606			
37	35.2035	6.3115	1.49700	81.54	0.5875
38	-31.6712	1.2010	1.88100	40.14	0.5701
39	26.8368	2.0274			
40	47.8031	7.3291	1.48749	70.23	0.5301
41	-18.9526	1.1991	1.91082	35.25	0.5822
42	8343.9540	0.1502			
43	90.6666	7.3503	1.48749	70.23	0.5301
44	-23.7246	0.0000			
45	∞	2.3000	1.51633	64.14	0.5353
46	∞	29.9940			

TABLE 2

Example 1: Items (related to d line)			
	Wide Angle End	Intermediate	Telephoto End
Zoom Ratio	1.00	1.49	1.95
f'	14.203	21.162	27.695
Bf	31.510	31.510	31.510
F No.	2.71	2.71	2.71
2ω [°]	98.2	72.4	58.0
h	38.470		
Yimg	15.75		

TABLE 3

Example 1: Zoom Distances			
	Wide Angle End	Intermediate	Telephoto End
DD [9]	8.921	8.921	8.921
DD [15]	3.935	3.935	3.935
DD [19]	1.500	29.121	41.635
DD [25]	14.635	3.103	5.194
DD [28]	33.513	17.425	2.819

TABLE 4

Example 1: Aspherical Surface Coefficients			
Surface No.	1	Surface No.	3
5 KA	1.00000000E+00	KA	1.00000000E+00
A3	-4.62278307E-06	A4	-4.86286556E-06
A4	6.14778261E-06	A6	-8.77554561E-10
A5	-1.92932204E-08	A8	1.34711999E-11
A6	-3.67925408E-09	A10	-4.96075731E-14
10 A7	3.35087759E-11	A12	1.15033129E-16
A8	1.57495428E-12	A14	-1.60626594E-19
A9	1.17528821E-15	A16	1.22990998E-22
A10	-4.54994700E-16	A18	-4.17694414E-26
A11	-5.04502281E-18	A20	2.65204259E-30
A12	-1.45086775E-20		
15 A13	8.02307748E-22		
A14	4.58656163E-23		
A15	1.06535667E-24		
A16	1.09653575E-26		
A17	-2.54537928E-28		
A18	-1.34715266E-29		
A19	-1.70590216E-31		
20 A20	8.57519103E-33		

A through L of FIG. 9 are diagrams that illustrate various aberrations of the zoom lens of Example 1. The spherical aberration, the astigmatic aberration, the distortion, and the lateral chromatic aberration of the zoom lens of Example 1 at the wide angle end are illustrated in A through D of FIG. 9, respectively. The spherical aberration, the astigmatic aberration, the distortion, and the lateral chromatic aberration of the zoom lens of Example 1 at an intermediate focal distance are illustrated in E through H of FIG. 9, respectively. The spherical aberration, the astigmatic aberration, the distortion, and the lateral chromatic aberration of the zoom lens of Example 1 at the telephoto end are illustrated in I through L of FIG. 9, respectively.

The diagrams that illustrate spherical aberration, astigmatic aberration, and distortion show aberrations related to the d line (wavelength: 587.6 nm). The diagrams that illustrate spherical aberration show aberrations related to the d line (wavelength: 587.6 nm), aberrations related to the C line (wavelength: 656.3 nm), and aberrations related to the F line (wavelength: 486.1 nm), as solid lines, broken lines, and dotted lines, respectively. In the diagrams that illustrate astigmatic aberrations, aberrations in the sagittal direction are indicated by solid lines, while aberrations in the tangential direction are indicated by dotted lines. In the diagrams that illustrate lateral chromatic aberration, aberrations related to the C: line (wavelength: 656.3 nm) and aberrations related to the F line (wavelength: 486.1 nm) are shown as broken lines and dotted lines, respectively. In the diagrams that illustrate spherical aberrations, "Fno." denotes F values. In the other diagrams that illustrate the aberrations, " ω " denotes half angles of view.

Next, a zoom lens according to Example 2 will be described. FIG. 3 is a collection of sectional diagrams that illustrate the lens configuration of the zoom lens of Example 2.

The zoom lens of Example 2 is constituted by a first lens group G1 having a positive refractive power which is fixed while changing magnification, a second lens group G2 having a negative refractive power which moves while changing magnification, a third lens group G3 having a negative refractive power which moves while changing magnification, and a fourth lens group G4 (final lens group) having a positive refractive power which is fixed while changing magnification.

11

In addition, basic lens data of the zoom lens of Example 2 are shown in Table 5, data related to various items of the zoom lens of Example 2 are shown in Table 6, data related to the distances among movable surfaces of the zoom lens of Example 2 are shown in Table 7, data related to aspherical surface coefficients of the zoom lens of Example 2 are shown in Table 8, and various aberrations of the zoom lens of Example 2 are shown in A through L of FIG. 10.

TABLE 5

Example 2: Lens Data					
Si (Surface No.)	Ri (Radius of Curvature)	Di (Distance)	Ndi (Re- fractive Index)	vdj (Abbe's Number)	θ_g, F_j (Partial Dispersion Ratio)
*1	821.5018	4.5033	1.58313	59.38	0.5435
2	31.5717	17.1046			
*3	112.8237	3.0008	1.74400	44.78	0.5656
4	29.3852	14.3024			
5	-52.2372	2.3299	1.65160	58.55	0.5427
6	61.3517	6.2842	1.53172	48.84	0.5631
7	213.8560	5.1100			
8	136.3532	11.2833	1.80400	46.58	0.5573
9	-94.7857	DD [9]			
10	328.4968	8.8107	1.51742	52.43	0.5565
11	-66.0762	4.0007	1.84661	23.78	0.6207
12	-106.9894	0.1495			
13	108.8604	2.4995	1.88100	40.14	0.5701
14	47.7436	11.0535	1.49700	81.54	0.5375
15	-274.5647	DD [15]			
16	-15632.8276	6.6588	1.49700	81.54	0.5375
17	-66.4006	0.1491			
18	211.2845	2.4734	1.43875	94.93	0.5343
19	4209.3691	DD [19]			
20	61.1845	2.9992	1.58913	61.14	0.5407
21	43.1398	6.6406			
22	-164.5955	1.1991	1.68893	31.07	0.6004
23	46.0859	3.3263			
24	54.8700	3.7000	1.78470	26.29	0.6136
25	-534.4627	DD [25]			
26	-77.3276	1.1991	1.60300	65.44	0.5402
27	46.9962	2.2700	1.80000	29.84	0.6018
28	106.8527	DD [28]			
29 (aperture stop)	∞	1.2990			
30	63.5411	2.4660	1.80518	25.42	0.6162
31	443.3579	0.1491			
32	48.6249	8.0301	1.56384	60.83	0.5408
33	-172.1528	0.4530			
34	718.9845	6.5372	1.55332	71.68	0.5403
35	-30.8697	1.1991	1.90366	31.32	0.5948
36	97.5055	9.7747			
37	107.0521	4.1214	1.85002	32.40	0.5986
38	-45.7197	3.0316			
39	35.1380	6.3252	1.49700	81.54	0.5375
40	-30.5251	1.1991	1.88100	40.14	0.5701
41	26.0385	1.6118			
42	35.9154	7.8882	1.48749	70.23	0.5301
43	-18.4695	1.1999	1.91082	35.25	0.5822
44	931.2713	1.2785			
45	112.2373	7.2528	1.48749	70.23	0.5301
46	-23.2427	0.0000			
47	∞	2.3000	1.51633	64.14	0.5353
48	∞	30.8700			

TABLE 6

Example 2: Items (related to d line)			
	Wide Angle End	Intermediate	Telephoto End
Zoom Ratio	1.00	1.49	1.95
f'	13.801	20.563	26.911
Bf	32.386	32.386	32.386
F No.	2.71	2.71	2.71

12

TABLE 6-continued

Example 2: Items (related to d line)			
	Wide Angle End	Intermediate	Telephoto End
2 ω [°]	99.8	74.0	59.4
h	38.550		
Yimg	15.75		

TABLE 7

Example 2: Zoom Distances			
	Wide Angle End	Intermediate	Telephoto End
DD [9]	7.582	7.582	7.582
DD [15]	3.695	3.695	3.695
DD [19]	1.499	29.452	41.907
DD [25]	13.483	2.994	6.258
DD [28]	36.009	18.545	2.826

TABLE 8

Example 2: Aspherical Surface Coefficients			
Surface No.	1	Surface No.	3
KA	1.00000000E+00	KA	1.00000000E+00
A3	-6.19960130E-06	A4	-5.32872676E-06
A4	7.10169757E-06	A6	-4.14123998E-10
A5	-3.94902024E-08	A8	1.36128219E-11
A6	-3.95088610E-09	A10	-4.94110009E-14
A7	3.96583237E-11	A12	1.14406960E-16
A8	1.69064292E-12	A14	-1.61231505E-19
A9	1.91914204E-15	A16	1.23793133E-22
A10	-4.79410275E-16	A18	-3.98065907E-26
A11	-6.04038966E-18	A20	6.85445131E-31
A12	-3.33911800E-20		
A13	6.15155323E-22		
A14	4.72501812E-23		
A15	1.23554996E-24		
A16	1.65224208E-26		
A17	-1.51203736E-28		
A18	-1.25849261E-29		
A19	-1.85915802E-31		
A20	5.94365475E-33		

Next, a zoom lens according to Example 3 will be described. FIG. 4 is a collection of sectional diagrams that illustrate the lens configuration of the zoom lens of Example 3.

The zoom lens of Example 3 is constituted by a first lens group G1 having a positive refractive power which is fixed while changing magnification, a second lens group G2 having a negative refractive power which moves while changing magnification, a third lens group G3 having a positive refractive power which moves while changing magnification, a fourth lens group G4 having a negative refractive power which moves while changing magnification, and a fifth lens group G5 (final lens group) having a positive refractive power which is fixed while changing magnification.

In addition, basic lens data of the zoom lens of Example 3 are shown in Table 9, data related to various items of the zoom lens of Example 3 are shown in Table 10, data related to the distances among movable surfaces of the zoom lens of Example 3 are shown in Table 11, data related to aspherical surface coefficients of the zoom lens of Example 3 are shown in Table 12, and various aberrations of the zoom lens of Example 3 are shown in A through L of FIG. 11.

13

TABLE 9

Example 3: Lens Data					
Si (Surface No.)	Ri (Radius of Curvature)	Di (Distance)	Ndi (Re- fractive Index)	vdj (Abbe's Number)	θ_g, F_j (Partial Dispersion Ratio)
*1	10000.0000	4.1998	1.58313	59.38	0.5435
2	32.2211	15.8119			
*3	74.8507	2.9994	1.72916	54.68	0.5445
4	33.9087	15.9374			
5	-60.8937	2.0004	1.62230	53.17	0.5542
6	52.2565	7.0614	1.64769	33.79	0.5939
7	268.1345	0.3004			
8	80.2515	13.1581	1.51742	52.43	0.5565
9	-263.2128	DD [9]			
10	400.3201	12.7251	1.51742	52.43	0.5565
11	-45.5823	3.0010	1.80518	25.42	0.6162
12	-73.2623	0.1509			
13	92.2770	2.4002	1.88300	40.80	0.5656
14	47.3282	13.4005	1.49700	81.54	0.5375
15	-131.3566	DD [15]			
16	440.5038	6.2316	1.49700	81.54	0.5375
17	-84.6784	0.1490			
18	113.8967	1.8709	1.67790	55.34	0.5473
19	162.6816	DD [19]			
20	49.9400	1.9993	1.78472	25.68	0.6162
21	32.6069	5.5028			
22	-172.4815	1.2010	1.60311	60.64	0.5415
23	37.4416	DD [23]			
24	46.7805	3.0176	1.78472	25.68	0.6162
25	148.9296	DD [25]			
26	-38.6766	1.2008	1.60300	65.44	0.5402
27	53.0088	3.4169	1.80000	29.84	0.6018
28	-227.4770	DD [28]			
29 (aperture stop)	∞	1.7011			
30	128.5387	2.9391	1.80518	25.43	0.6103
31	-102.8542	1.2149	1.80610	33.27	0.5885
32	-123.8381	4.0718			
33	41.9640	6.9852	1.59282	68.63	0.5441
34	-33.8072	1.2008	1.90366	31.32	0.5948
35	118.9395	10.4118			
36	230.1445	3.6022	1.84139	24.56	0.6127
37	-48.2639	0.2996			
38	33.9414	4.9201	1.49700	81.54	0.5375
39	-79.9336	1.2007	1.90366	31.32	0.5948
40	28.3339	1.9573			
41	47.1420	6.4878	1.56883	56.36	0.5489
42	-25.7955	1.2008	1.91082	35.25	0.5822
43	133.4236	0.1509			
44	66.4493	4.8070	1.51633	64.14	0.5353
45	-42.5558	42.1624			
46	∞	2.3000	1.51633	64.14	0.5353
47	∞	6.8700			

TABLE 10

Example 3: Items (related to d line)			
	Wide Angle End	Intermediate	Telephoto End
Zoom Ratio	1.00	1.69	2.40
f'	14.502	24.508	34.805
Bf'	50.551	50.551	50.551
F No.	2.76	2.76	2.76
2 ω [°]	97.2	64.2	47.6
h	39.752		
Yimg	15.75		

14

TABLE 11

Example 3: Zoom Distances			
	Wide Angle End	Intermediate	Telephoto End
5	DD [9]	1.999	1.999
	DD [15]	3.194	3.194
	DD [19]	1.500	30.612
	DD [23]	2.918	3.870
	DD [25]	32.001	9.398
10	DD [28]	18.948	11.487

TABLE 12

Example 3: Aspherical Surface Coefficients			
Surface No.	1	Surface No.	3
KA	1.00000000E+00	KA	1.00000000E+00
A3	0.00000000E+00	A4	-4.48998467E-06
A4	6.99592748E-06	A6	-1.63755377E-09
A5	-9.31615918E-08	A8	1.65105078E-11
A6	-1.82380523E-09	A10	-5.56597762E-14
A7	2.16562421E-11	A12	1.16319351E-16
A8	1.18566591E-12	A14	-1.53007740E-19
A9	-9.20263760E-16	A16	1.22395091E-22
A10	-3.67463235E-16	A18	-5.24386986E-26
20	A11	A20	8.75856166E-30
	A12		
	A13		
	A14		
	A15		
	A16		
25	A17		
	A18		
	A19		
	A20		

35 Next, a zoom lens according to Example 4 will be described. FIG. 5 is a collection of sectional diagrams that illustrate the lens configuration of the zoom lens of Example 4.

40 The zoom lens of Example 4 is constituted by a first lens group G1 having a positive refractive power which is fixed while changing magnification, a second lens group G2 having a negative refractive power which moves while changing magnification, a third lens group G3 having a positive refractive power which moves while changing magnification, a fourth lens group G4 having a negative refractive power which moves while changing magnification, and a fifth lens group G5 (final lens group) having a positive refractive power which is fixed while changing magnification.

50 In addition, basic lens data of the zoom lens of Example 4 are shown in Table 13, data related to various items of the zoom lens of Example 4 are shown in Table 14, data related to the distances among movable surfaces of the zoom lens of Example 4 are shown in Table 15, data related to aspherical surface coefficients of the zoom lens of Example 4 are shown in Table 16, and various aberrations of the zoom lens of Example 4 are shown in A through L of FIG. 12.

TABLE 13

Example 4: Lens Data					
Si (Surface No.)	Ri (Radius of Curvature)	Di (Distance)	Ndi (Re- fractive Index)	vdj (Abbe's Number)	θ_g, F_j (Partial Dispersion Ratio)
60					
65	*1	10000.0000	4.0006	1.58313	59.38
	2	32.9933	17.2882		

15

TABLE 13-continued

Example 4: Lens Data					
Si (Surface No.)	Ri (Radius of Curvature)	Di (Distance)	Ndi (Re- fractive Index)	v _{dj} (Abbe's Number)	θ _g , F _j (Partial Dispersion Ratio)
*3	87.0979	3.0002	1.58913	61.14	0.5407
4	33.2350	16.5350			
5	-58.3333	2.0003	1.58913	61.14	0.5407
6	45.1187	6.9705	1.59551	39.24	0.5804
7	131.6367	1.8871			
8	81.5665	11.9999	1.51742	52.43	0.5565
9	-160.9692	DD [9]			
10	940.4868	12.8191	1.51742	52.43	0.5565
11	-42.4380	2.4010	1.80518	25.42	0.6162
12	-66.0091	0.1495			
13	86.9718	2.9994	1.88300	40.80	0.5656
14	45.5306	12.8459	1.49700	81.54	0.5375
15	-157.5820	DD [15]			
16	153.1852	7.1314	1.49700	81.54	0.5375
17	-88.9356	DD [17]			
18	43.2939	2.0008	1.62041	60.29	0.5427
19	29.9643	5.8258			
20	-194.0683	1.1993	1.62041	60.29	0.5427
21	33.9926	DD [21]			
22	39.1631	3.6463	1.60342	38.03	0.5836
23	151.6252	DD [23]			
24	-44.3515	1.2010	1.60300	65.44	0.5402
25	53.7225	3.1924	1.80000	29.84	0.6018
26	-452.7386	DD [26]			
27 (aperture stop)	∞	1.3177			
28	87.3983	3.4625	1.80518	25.43	0.6103
29	-97.7067	1.2008	1.80610	33.27	0.5885
30	-112.2153	0.1498			
31	47.7318	6.8015	1.59282	68.63	0.5441
32	-33.0684	1.2010	1.90366	31.32	0.5948
33	100.3029	11.8604			
34	712.8535	3.5246	1.84139	24.56	0.6127
35	-43.7794	0.2990			
36	33.0831	5.4367	1.49700	81.54	0.5375
37	-58.3870	1.2003	1.90366	31.32	0.5948
38	29.1855	2.3905			
39	70.9544	5.7982	1.56883	56.36	0.5489
40	-24.3753	1.2004	1.91082	35.25	0.5822
41	250.8216	0.1510			
42	63.3138	5.4349	1.51633	64.14	0.5353
43	-37.5309	42.1624			
44	∞	2.3000	1.51633	64.14	0.5353
45	∞	7.2740			

TABLE 14

Example 4: Items (related to d line)			
	Wide Angle End	Intermediate	Telephoto End
Zoom Ratio	1.00	1.69	2.40
f'	14.502	24.509	34.805
Bf'	50.954	50.954	50.954
F No.	2.76	2.76	2.76
2ω [°]	97.0	64.2	47.6
h	40.475		
Yimg	15.75		

TABLE 15

Example 4: Zoom Distances			
	Wide Angle End	Intermediate	Telephoto End
DD [9]	2.001	2.001	2.001
DD [15]	4.351	4.351	4.351
DD [17]	1.648	30.144	45.142

16

TABLE 15-continued

Example 4: Zoom Distances			
	Wide Angle End	Intermediate	Telephoto End
DD [21]	2.708	3.660	2.538
DD [23]	28.703	7.715	4.698
DD [26]	21.115	12.655	1.796

TABLE 16

Example 4: Aspherical Surface Coefficients			
Surface No.	1	Surface No.	3
15 KA	1.00000000E+00	KA	1.00000000E+00
A3	0.00000000E+00	A4	-5.29504060E-06
A4	6.75059893E-06	A6	-5.71449059E-10
A5	-8.28752745E-08	A8	1.57517676E-11
A6	-1.96498556E-09	A10	-5.54412820E-14
A7	2.02284701E-11	A12	1.16432393E-16
A8	1.18830034E-12	A14	-1.53241444E-19
A9	-5.05719925E-16	A16	1.22413439E-22
A10	-3.57264124E-16	A18	-5.26028411E-26
A11	-2.39742061E-18	A20	8.89038276E-30
A12	4.34277976E-21		
A13	1.09559279E-22		
A14	1.67422397E-23		
A15	5.24037655E-25		
A16	6.31296722E-27		
A17	-2.61711042E-29		
A18	-2.31751638E-30		
A19	-1.27029101E-31		
30 A20	1.16955006E-33		

Next, a zoom lens according to Example 5 will be described. FIG. 6 is a collection of sectional diagrams that illustrate the lens configuration of the zoom lens of Example 5.

The zoom lens of Example 5 is constituted by a first lens group G1 having a positive refractive power which is fixed while changing magnification, a second lens group G2 having a negative refractive power which moves while changing magnification, a third lens group G3 having a positive refractive power which moves while changing magnification, a fourth lens group G4 having a negative refractive power which moves while changing magnification, and a fifth lens group G5 (final lens group) having a positive refractive power which is fixed while changing magnification.

In addition, basic lens data of the zoom lens of Example 5 are shown in Table 17, data related to various items of the zoom lens of Example 5 are shown in Table 18, data related to the distances among movable surfaces of the zoom lens of Example 5 are shown in Table 19, data related to aspherical surface coefficients of the zoom lens of Example 5 are shown in Table 20, and various aberrations of the zoom lens of Example 5 are shown in A through L of FIG. 13.

TABLE 17

Example 5: Lens Data					
Si (Surface No.)	Ri (Radius of Curvature)	Di (Distance)	Ndi (Refractive Index)	v _{dj} (Abbe's Number)	θ _g , F _j (Partial Dispersion Ratio)
*1	9996.1662	3.9990	1.58313	59.38	0.5435
2	33.0268	17.6736			
*3	92.7441	3.0004	1.56384	60.67	0.5403

17

TABLE 17-continued

Example 5: Lens Data					
Si (Surface No.)	Ri (Radius of Curvature)	Di (Distance)	Ndi (Refractive Index)	v _{dj} (Abbe's Number)	θ _g , F _j (Partial Dispersion Ratio)
4	32.9830	16.7002			
5	-57.7257	2.0009	1.56384	60.67	0.5403
6	44.4273	6.9894	1.59551	39.24	0.5804
7	123.4868	2.2107			
8	81.8371	11.0878	1.51742	52.43	0.5565
9	-175.4565	DD [9]			
10	908.4134	12.8193	1.51742	52.43	0.5565
11	-42.4326	2.4005	1.80518	25.42	0.6162
12	-65.6231	0.1510			
13	86.6019	2.4000	1.88300	40.80	0.5656
14	45.0903	12.7416	1.49700	81.54	0.5375
15	-168.5297	DD [15]			
16	144.0425	7.2491	1.49700	81.54	0.5375
17	-89.5821	DD [17]			
18	43.5673	2.0001	1.62041	60.29	0.5427
19	29.8335	5.8291			
20	-200.5387	1.2005	1.62041	60.29	0.5427
21	34.0496	DD [21]			
22	39.1990	3.6683	1.60342	38.03	0.5836
23	156.1540	DD [23]			
24	-43.9071	1.2006	1.60300	65.44	0.5402
25	54.0052	3.1865	1.80000	23.84	0.6018
26	-430.7076	DD [26]			
27	∞	1.3026			
(aperture stop)					
28	85.9546	3.4471	1.80518	25.43	0.6103
29	-100.1930	1.1997	1.80610	33.27	0.5885
30	-110.4660	0.1505			
31	48.3759	6.7674	1.53282	68.63	0.5441
32	-32.8141	1.1999	1.90366	31.32	0.5948
33	100.3206	11.8554			
34	718.3071	3.5385	1.84139	24.56	0.6127
35	-43.5209	0.2992			
36	33.2408	5.4687	1.49700	81.54	0.5375
37	-56.8048	1.2002	1.90366	31.32	0.5948
38	29.1867	2.3596			
39	68.8322	6.2059	1.56883	56.36	0.5489
40	-24.2121	1.2004	1.91082	35.25	0.5822
41	224.8661	0.1499			
42	62.5064	5.5209	1.51633	64.14	0.5353
43	-36.7534	42.1624			
44	∞	2.3000	1.51633	64.14	0.5353
45	∞	6.7840			

TABLE 18

Example 5: Items (related to d line)			
	Wide Angle End	Intermediate	Telephoto End
Zoom Ratio	1.00	1.69	2.40
f'	14.502	24.508	34.805
Bf'	50.465	50.465	50.465
F No.	2.76	2.76	2.76
2ω [°]	97.0	64.2	47.6
h	40.585		
Yimg	15.75		

TABLE 19

Example 5: Zoom Distances			
	Wide Angle End	Intermediate	Telephoto End
DD [9]	2.001	2.001	2.001
DD [15]	4.134	4.134	4.134
DD [17]	1.650	30.084	45.030

18

TABLE 19-continued

Example 5: Zoom Distances			
	Wide Angle End	Intermediate	Telephoto End
DD [21]	2.704	3.656	2.535
DD [23]	28.332	7.585	4.692
DD [26]	21.359	12.719	1.787

TABLE 20

Example 5: Aspherical Surface Coefficients			
Surface No.	1	Surface No.	3
KA	1.00000000E+00	KA	1.00000000E+00
A3	0.00000000E+00	A4	-5.34557685E-06
A4	6.62012404E-06	A6	-4.77918366E-10
A5	-8.00989016E-08	A8	1.56978908E-11
A6	-1.97332847E-09	A10	-5.54192293E-14
A7	2.00322887E-11	A12	1.16440250E-16
A8	1.18543694E-12	A14	-1.53260905E-19
A9	-5.62931037E-16	A16	1.22421216E-22
A10	-3.58303992E-16	A18	-5.25557609E-26
A11	-2.40915082E-18	A20	8.84678479E-30
A12	4.42425152E-21		
A13	1.18549232E-22		
A14	1.69519099E-23		
A15	5.26851207E-25		
A16	6.24066577E-27		
A17	-2.83311374E-29		
A18	-2.36817680E-30		
A19	-1.28243816E-31		
A20	1.23191223E-33		

Next, a zoom lens according to Example 6 will be described. FIG. 7 is a collection of sectional diagrams that illustrate the lens configuration of the zoom lens of Example 6.

The zoom lens of Example 6 is constituted by a first lens group G1 having a positive refractive power which is fixed while changing magnification, a second lens group G2 having a negative refractive power which moves while changing magnification, a third lens group G3 having a positive refractive power which moves while changing magnification, a fourth lens group G4 having a negative refractive power which moves while changing magnification, and a fifth lens group G5 (final lens group) having a positive refractive power which is fixed while changing magnification.

In addition, basic lens data of the zoom lens of Example 6 are shown in Table 21, data related to various items of the zoom lens of Example 6 are shown in Table 22, data related to the distances among movable surfaces of the zoom lens of Example 6 are shown in Table 23, data related to aspherical surface coefficients of the zoom lens of Example 6 are shown in Table 24, and various aberrations of the zoom lens of Example 6 are shown in A through L of FIG. 14.

TABLE 21

Example 6: Lens Data					
Si (Surface No.)	Ri (Radius of Curvature)	Di (Distance)	Ndi (Refractive Index)	v _{dj} (Abbe's Number)	θ _g , F _j (Partial Dispersion Ratio)
*1	833.2049	4.2000	1.58313	59.38	0.5435
2	31.7636	17.9002			
*3	127.6910	3.0000	1.72916	54.68	0.5445

TABLE 21-continued

Example 6: Lens Data					
Si (Surface No.)	Ri (Radius of Curvature)	Di (Distance)	Ndi (Refractive Index)	vdj (Abbe's Number)	θ_g, F_j (Partial Dispersion Ratio)
4	34.3126	14.6813			
5	-69.9234	2.0609	1.65100	56.16	0.5482
6	45.5660	9.2669	1.80610	40.92	0.5702
7	578.7597	2.3162			
8	93.6917	7.8281	1.51742	52.43	0.5565
9	-256.4813	DD [9]			
10	∞	11.3461	1.51742	52.43	0.5565
11	-44.7600	3.0000	1.80518	25.42	0.6162
12	-73.1209	0.1503			
13	96.2962	2.4200	1.88300	40.80	0.5656
14	46.8100	12.4094	1.49700	81.54	0.5375
15	-180.2152	DD [15]			
16	951.6580	6.3106	1.49700	81.54	0.5375
17	-77.2853	0.1509			
18	163.9945	3.0654	1.51633	64.14	0.5353
19	∞	DD [19]			
20	57.6292	2.0006	1.80519	25.40	0.6157
21	37.7564	5.0473			
22	-146.0915	1.2000	1.62041	60.29	0.5427
23	41.6554	DD [23]			
24	54.8186	3.0165	1.78472	25.68	0.6162
25	265.6294	DD [25]			
26	-43.8649	1.2000	1.60300	65.44	0.5402
27	56.3300	3.0813	1.80000	29.84	0.6018
28	-477.8065	DD [28]			
29	∞	1.3000			
(aperture stop)					
30	83.3692	2.1698	1.80518	25.42	0.6162
31	633.2100	2.1715	1.80400	46.58	0.5573
32	-187.0891	6.3158			
33	36.6370	6.9118	1.61800	63.33	0.5441
34	-36.6370	1.2000	1.90366	31.32	0.5948
35	63.4913	12.4536			
36	218.6049	3.7518	1.84139	24.56	0.6127
37	-45.5768	0.3017			
38	31.9703	5.6143	1.49700	81.54	0.5375
39	-61.6770	1.2000	1.91082	35.25	0.5822
40	26.9714	1.6352			
41	33.2963	7.2686	1.51633	64.14	0.5353
42	-26.3200	1.2000	1.91082	35.25	0.5822
43	122.8536	0.2203			
44	59.1966	4.9714	1.51633	64.14	0.5353
45	-46.6277	37.6430			
46	∞	2.3000	1.51633	64.14	0.5353
47	∞	5.7960			

TABLE 22

Example 6: Items (related to d line)			
	Wide Angle End	Intermediate	Telephoto End
Zoom Ratio	1.00	1.69	2.40
f'	14.503	24.510	34.808
Bf	44.956	44.956	44.956
F No.	2.75	2.75	2.75
2 ω [°]	97.2	64.2	47.6
h	39.391		
Yimg	15.75		

TABLE 23

Example 6: Zoom Distances			
	Wide Angle End	Intermediate	Telephoto End
5	DD [9]	1.999	1.999
	DD [15]	3.720	3.720
	DD [19]	1.500	31.951
	DD [23]	3.097	3.968
	DD [25]	31.053	8.441
10	DD [28]	21.337	12.628
			1.999
			3.720
			47.943
			2.812
			4.417
			1.816

TABLE 24

Example 6: Aspherical Surface Coefficients				
Surface No.	1	Surface No.	3	
KA	1.00000000E+00	KA	1.00000000E+00	
A3	-7.36624463E-06	A4	-4.10988571E-06	
A4	6.48233272E-06	A6	-1.21995779E-09	
A5	-7.39213084E-08	A8	1.59589857E-11	
A6	-1.96775959E-09	A10	-5.49266080E-14	
A7	1.87763145E-11	A12	1.16559890E-16	
A8	1.19443930E-12	A14	-1.54783593E-19	
A9	1.64603963E-16	A16	1.23414774E-22	
A10	-3.50236069E-16	A18	-5.23355121E-26	
20	A11	-2.53695199E-18	A20	8.61685265E-30
	A12	-4.38860761E-21		
	A13	-1.40947481E-22		
	A14	1.29050477E-23		
	A15	5.05727148E-25		
	A16	8.41600054E-27		
	A17	1.65092551E-28		
25	A18	-8.29887329E-31		
	A19	-8.12713794E-32		
	A20	-1.81223806E-33		

Next, a zoom lens according to Example 7 will be described. FIG. 8 is a collection of sectional diagrams that illustrate the lens configuration of the zoom lens of Example 7.

The zoom lens of Example 7 is constituted by a first lens group G1 having a positive refractive power which is fixed while changing magnification, a second lens group G2 having a negative refractive power which moves while changing magnification, a third lens group G3 having a positive refractive power which moves while changing magnification, a fourth lens group G4 having a negative refractive power which moves while changing magnification, and a fifth lens group G5 (final lens group) having a positive refractive power which is fixed while changing magnification.

In addition, basic lens data of the zoom lens of Example 7 are shown in Table 25, data related to various items of the zoom lens of Example 7 are shown in Table 26, data related to the distances among movable surfaces of the zoom lens of Example 7 are shown in Table 27, data related to aspherical surface coefficients of the zoom lens of Example 7 are shown in Table 28, and various aberrations of the zoom lens of Example 7 are shown in A through L of FIG. 15.

TABLE 25

Example 7: Lens Data				
Si (Surface No.)	Ri (Radius of Curvature)	Di (Distance)	Ndi (Refractive Index)	θ_g, F_j (Abbe's Number)
60				
65	*1	474.1079	4.0745	1.88000
	2	38.1537	15.3232	36.02

TABLE 25-continued

Example 7: Lens Data				
Si (Surface No.)	Ri (Radius of Curvature)	Di (Distance)	Ndi (Refractive Index)	θg, Fj (Abbe's Number)
*3	57.6675	3.0000	1.88000	40.00
4	32.3563	15.9448		
5	-111.1467	1.2000	1.88300	40.76
6	140.5909	1.2000	1.88300	40.76
7	101.7368	8.0019		
8	-77.3379	1.2000	1.43500	82.06
9	-615.4996	6.6907		
10	301.7285	9.6136	1.87999	34.48
11	-83.3740	1.1964		
12	87.3406	15.9509	1.43956	87.94
13	-86.3341	2.9828		
14	-69.4525	1.7988	1.88000	24.68
15	-82.1391	1.5524		
16	205.8050	6.9859	1.88001	33.30
17	47.9172	14.8863	1.43501	86.05
18	-188.9332	5.4496		
19	275.6761	11.0517	1.56570	69.89
20	-76.4781	0.3443		
21	123.8611	2.7878	1.44152	89.00
22	240.6510	DD [22]		
*23	67.8102	1.2534	1.88000	40.00
24	31.7225	4.2411		
25	-484.3459	1.2000	1.68126	57.44
26	63.9111	DD [26]		
27	56.2453	2.3229	1.79506	25.25
28	158.3898	DD [28]		
29	-47.7543	1.2000	1.56867	65.78
30	64.6989	2.9294	1.88000	28.37
31	-552.2441	DD [31]		
32 (aperture stop)	∞	0.2993		
33	459.5820	2.4215	1.43501	89.63
34	-127.7905	0.2970		
35	90.0800	2.8112	1.74142	27.93
36	-14886.6570	7.8174		
37	95.5653	10.1929	1.55514	71.35
38	-39.6539	1.6944	1.85632	34.30
39	-251.4526	19.7231		
40	90.7134	4.4685	1.46016	62.61
41	-50.6603	8.2083		
42	44.6260	6.1506	1.63441	34.69
43	-26.8777	1.1999	1.87980	25.58
44	26.3581	1.0758		
45	39.0893	7.7742	1.52585	50.15
46	-21.5664	1.2000	1.87768	40.23
47	-470.8190	3.6661		
48	70.5057	8.5184	1.46393	85.55
49	-28.0438	0.0000		

TABLE 25-continued

Example 7: Lens Data				
Si (Surface No.)	Ri (Radius of Curvature)	Di (Distance)	Ndi (Refractive Index)	θg, Fj (Abbe's Number)
50	∞	3.7000	1.51633	64.14
51	∞	29.5110		

TABLE 26

Example 7: Items (related to d line)			
	Wide Angle End	Intermediate	Telephoto End
20 Zoom Ratio	1.00	1.50	2.40
f	10.348	15.522	24.834
Bf	31.950	31.950	31.950
F No.	2.67	2.67	2.67
2ω [°]	115.8	89.4	63.4
h	45.011		
25 Yimg	15.75		

TABLE 27

Example 7: Zoom Distances			
	Wide Angle End	Intermediate	Telephoto End
35 DD [22]	1.500	24.832	46.278
DD [26]	7.494	8.700	6.716
DD [28]	31.917	11.571	4.959
DD [31]	18.568	14.375	1.526

TABLE 28

Example 7: Aspherical Surface Coefficients			
	Surface No.		
	1	3	23
45 KA	1.00000000E+00	1.00000000E+00	1.00000000E+00
A3	0.00000000E+00	0.00000000E+00	0.00000000E+00
A4	5.18882505E-06	-5.14249825E-06	-5.25532447E-07
A5	0.00000000E+00	0.00000000E+00	0.00000000E+00
A6	-3.23450934E-09	5.12834157E-11	8.34301502E-10
50 A7	0.00000000E+00	0.00000000E+00	0.00000000E+00
A8	1.98740330E-12	1.14153099E-12	-4.93172362E-12
A9	0.00000000E+00	0.00000000E+00	0.00000000E+00
A10	-6.83584428E-16	-3.42331893E-16	1.06735795E-14
A11	0.00000000E+00	0.00000000E+00	0.00000000E+00
A12	1.14552162E-19	-1.12891019E-21	-7.89012953E-18
A13	0.00000000E+00	0.00000000E+00	0.00000000E+00
55 A14	0.00000000E+00	0.00000000E+00	0.00000000E+00
A15	0.00000000E+00	0.00000000E+00	0.00000000E+00
A16	0.00000000E+00	0.00000000E+00	0.00000000E+00
A17	0.00000000E+00	0.00000000E+00	0.00000000E+00
A18	0.00000000E+00	0.00000000E+00	0.00000000E+00
A19	0.00000000E+00	0.00000000E+00	0.00000000E+00
60 A20	0.00000000E+00	0.00000000E+00	0.00000000E+00

In addition, Table 29 shows values corresponding to Conditional Formulae (1) through (4) for Examples 1 through 7. Note that all of the Examples use the d line as a reference wavelength, and the values shown in Table 29 are those with respect to the reference wavelength.

TABLE 29

Formula	Conditional Formula	Example 1	Example 2	Example 3	Example 4	Example 5	Example 6	Example 7
(1)	$h/(Y_{img} \times \tan\theta)$	2.12	2.06	2.23	2.27	2.28	2.21	1.79
(2)	n_{1a}	1.663	1.663	1.620	1.575	1.565	1.657	1.807
(3)	f_{13}/f_1	2.59	2.66	2.64	2.78	2.73	2.28	2.85
(4)	f_{11}/Y_{img}	-1.89	-1.85	-1.68	-1.68	-1.69	-1.84	1.79

Based on the data above, all of the zoom lenses of Examples 1 through 6 satisfy Conditional Formulae (1) through (4), and the zoom lens of Example 7 satisfies Conditional Formulae (1), (3), and (4). Therefore, it can be understood that these zoom lenses are high performance zoom lenses having wide angles of view, while being compact and lightweight.

Next, an imaging apparatus according to an embodiment of the present invention will be described. FIG. 16 is a schematic diagram that illustrates the configuration of an imaging apparatus equipped with a zoom lens according to an embodiment of the present invention as an example of an imaging apparatus according to the embodiment of the present invention. Note that FIG. 16 schematically illustrates each of the lens groups. Examples of this imaging apparatus include a video camera and an electronic still camera having a solid state imaging element such as a CCD and a CMOS as a recording medium.

The imaging apparatus 10 illustrated in FIG. 16 is equipped with an imaging lens 1, a filter 6 that functions as a low pass filter or the like, provided toward the image side of the imaging lens 1, an imaging element 7 provided toward the image side of the filter 6, and a signal processing circuit 8. The imaging element 7 converts optical images formed by the imaging lens 1 into electrical signals. A CCD (Charge Coupled Device) or a CMOS (Complementary Metal Oxide Semiconductor) may be employed as the imaging element 7, for example. The imaging element 7 is provided such that the imaging surface thereof is positioned at the image formation plane of the imaging lens 1.

Images obtained by the imaging lens 1 are formed on the imaging surface of the imaging element 7. Output signals from the imaging element 7 related to the images undergo calculation processes at the signal processing circuit 8, and the images are displayed by a display device 9.

The present invention has been described in connection with the embodiments and the Examples. However, the zoom lens of the present invention is not limited to the embodiments and Examples described above, and various modifications are possible. For example, the values of the radii of curvature, the distances among surfaces, and the refractive indices, etc., of each lens component are not limited to the numerical values indicated in connection with the Examples, and may be other values.

What is claimed is:

1. A zoom lens, comprising:

a first lens group having a positive refractive power which is fixed while changing magnification;

two or more movable lens groups that move independently from each other while changing magnification; and

a final lens group having a positive refractive power which is fixed while changing magnification, provided in this order from an object side;

the zoom lens satisfying Conditional Formula (1) below:

$$1.30 < h/(Y_{img} \times \tan \theta) < 2.37 \quad (1)$$

wherein h is the height at which a chief ray of light having a maximum image height enters a first surface at a wide angle end, Y_{img} is the maximum image height, and θ is the half angle of view at the wide angle end.

2. A zoom lens as defined in claim 1, wherein:

the first lens group comprises an eleven lens group having a negative refractive power, a twelve lens group having a positive refractive power, and a thirteen lens group having a positive refractive power; and
the twelve lens group moves to perform focusing operations.

3. A zoom lens as defined in claim 2 that satisfies Conditional Formula (3) below:

$$1.95 < f_{13}/f_1 < 3.00 \quad (3)$$

wherein f_1 is the focal length of the first lens group, and f_{13} is the focal length of the thirteen lens group.

4. A zoom lens as defined in claim 2 that satisfies Conditional Formula (4) below:

$$-2.20 < f_{11}/Y_{img} < -1.50 \quad (4)$$

wherein f_{11} is the focal length of the eleven lens group, and Y_{img} is a maximum image height.

5. A zoom lens as defined in claim 2, wherein:

the twelve lens group comprises two pairs of cemented lenses.

6. A zoom lens as defined in claim 5, wherein:

the two pairs of cemented lenses are a cemented lens formed by a positive lens and a negative lens, and a cemented lens formed by a negative lens and a positive lens, provided in this order from the object side.

7. A zoom lens as defined in claim 2 that satisfies Conditional Formula (2-1) below:

$$1.530 < n_{1a} < 1.665 \quad (2-1)$$

wherein n_{1a} is the average refractive index of the eleven lens group with respect to the d line.

8. A zoom lens as defined in claim 2 that satisfies Conditional Formula (3-1) below:

$$2.10 < f_{13}/f_1 < 2.90 \quad (3-1)$$

wherein f_1 is the focal length of the first lens group, and f_{13} is the focal length of the thirteen lens group.

9. A zoom lens as defined in claim 2 that satisfies Conditional Formula (3-2) below:

$$2.20 < f_{13}/f_1 < 2.80 \quad (3-2)$$

wherein f_1 is the focal length of the first lens group, and f_{13} is the focal length of the thirteen lens group.

10. A zoom lens as defined in claim 2 that satisfies Conditional Formula (4-1) below:

$$-2.10 < f_{11}/Y_{img} < -1.60 \quad (4-1)$$

wherein f_{11} is the focal length of the eleven lens group, and Y_{img} is a maximum image height.

11. A zoom lens as defined in claim 2 that satisfies Conditional Formula (4-2) below:

$$-2.00 < f_{11}/Y_{img} < -1.65 \quad (4-2)$$

25

wherein f_{11} is the focal length of the eleven lens group, and Y_{img} is a maximum image height.

12. A zoom lens as defined in claim 1, wherein:

a second lens group having a negative refractive power and a third lens group having a negative refractive power are provided in this order from the object side as the movable lens groups.

13. A zoom lens as defined in claim 1, wherein:

a second lens group having a negative refractive power, a third lens group having a positive refractive power, and a fourth lens group having a negative refractive power are provided in this order from the object side as the movable lens groups.

14. A zoom lens as defined in claim 1 that satisfies Conditional Formula (1-1) below:

$$1.70 < h / (Y_{img} \cdot \tan \theta) < 2.37 \quad (1-1)$$

wherein h is the height at which a chief ray of light having a maximum image height enters a first surface at a wide angle end, Y_{img} is the maximum image height, and θ is the half angle of view at the wide angle end.

15. An imaging apparatus equipped with the zoom lens defined in claim 1.

16. A zoom lens, comprising:

a first lens group having a positive refractive power which is fixed while changing magnification;
two or more movable lens groups that move independently from each other while changing magnification;
and

a final lens group having a positive refractive power which is fixed while changing magnification, provided in this order from an object side;

26

the first lens group comprising an eleven lens group having a negative refractive power, a twelve lens group having a positive refractive power, and a thirteen lens group having a positive refractive power;

the twelve lens group moving to perform focusing operations; and

the zoom lens satisfying Conditional Formula (2) below:

$$1.530 < n_{1a} < 1.670 \quad (2)$$

wherein n_{1a} is the average refractive index of the eleven lens group with respect to the d line, wherein,

a second lens group having a negative refractive power and a third lens group having a negative refractive power are provided in this order from the object side as the movable lens groups.

17. A zoom lens as defined in claim 16 that satisfies Conditional Formula (3) below:

$$1.95 < f_{13} / f_1 < 3.00 \quad (3)$$

wherein f_1 is the focal length of the first lens group, and f_{13} is the focal length of the thirteen lens group.

18. A zoom lens as defined in claim 16 that satisfies Conditional Formula (4) below:

$$-2.20 < f_{11} / Y_{img} < -1.50 \quad (4)$$

wherein f_{11} is the focal length of the eleven lens group, and Y_{img} is a maximum image height.

19. An imaging apparatus equipped with the zoom lens defined in claim 16.

* * * * *