



US009615349B2

(12) **United States Patent**
Fix et al.

(10) **Patent No.:** **US 9,615,349 B2**
(45) **Date of Patent:** ***Apr. 4, 2017**

(54) **GEOGRAPHIC REDUNDANCY DETERMINATION FOR TIME BASED LOCATION INFORMATION IN A WIRELESS RADIO NETWORK**

(58) **Field of Classification Search**
CPC H04W 64/00; H04W 4/025; G01S 5/02; G01S 5/0226

(Continued)

(71) Applicants: **AT&T Mobility II LLC**, Atlanta, GA (US); **AT&T INTELLECTUAL PROPERTY I, L.P.**, Atlanta, GA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(72) Inventors: **Jeremy Fix**, Acworth, GA (US); **Jie Chen**, Watchung, NJ (US); **Sheldon Kent Meredith**, Marietta, GA (US)

4,718,081 A 1/1988 Brenig
5,515,062 A 5/1996 Maine et al.

(Continued)

(73) Assignees: **AT&T INTELLECTUAL PROPERTY I, L.P.**, Atlanta, GA (US); **AT&T MOBILITY II LLC**, Atlanta, GA (US)

FOREIGN PATENT DOCUMENTS

EP 0856746 A2 8/1998
EP 1145526 10/2001

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

OTHER PUBLICATIONS

This patent is subject to a terminal disclaimer.

Notice of Allowance dated Aug. 21, 2014 for U.S. Appl. No. 13/447,069, 78 pages.

(Continued)

(21) Appl. No.: **15/186,410**

Primary Examiner — Sharad Rampuria

(22) Filed: **Jun. 17, 2016**

(74) *Attorney, Agent, or Firm* — Amin, Turocy & Watson, LLP

(65) **Prior Publication Data**

(57) **ABSTRACT**

US 2016/0302169 A1 Oct. 13, 2016

Determining levels of geographic redundancy among radios of a wireless radio network is disclosed. The level of geographic redundancy for a radio can affect the determination of location information for a user equipment (UE) on the wireless radio network. The disclosed subject matter can be employed in conjunction with timed fingerprint location (TFL) technologies to facilitate selection of radios employed in determining time values for TFL location determination. Levels of geographic redundancy can be employed to rank or order radios of a wireless radio network so as to reduce the likelihood of using geographically redundant radios in location determination. Further, rules can be selected to adjust threshold values and equations employed in determining the levels of geographic redundancy. Moreover,

(Continued)

Related U.S. Application Data

(63) Continuation of application No. 14/520,287, filed on Oct. 21, 2014, now Pat. No. 9,398,556, which is a (Continued)


(51) **Int. Cl.**

H04W 64/00 (2009.01)
G01S 5/02 (2010.01)
H04W 4/02 (2009.01)

(52) **U.S. Cl.**

CPC **H04W 64/00** (2013.01); **G01S 5/02** (2013.01); **G01S 5/0226** (2013.01); **H04W 4/025** (2013.01)

100



rules can be selected to apply boundary conditions to reduce the number of determinations formed for a set of radios of the wireless radio network.

20 Claims, 10 Drawing Sheets

Related U.S. Application Data

continuation of application No. 13/525,065, filed on Jun. 15, 2012, now Pat. No. 8,897,805.

(58) **Field of Classification Search**

USPC 455/456.1-457
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,724,660	A	3/1998	Kauser et al.	7,065,349	B2	6/2006	Nath et al.
5,732,354	A	3/1998	MacDonald	7,098,805	B2	8/2006	Meadows et al.
5,732,383	A	3/1998	Foladare et al.	7,113,793	B2	9/2006	Veerasingam et al.
5,831,545	A	11/1998	Murray et al.	7,149,534	B2	12/2006	Bloebaum et al.
5,844,521	A	12/1998	Stephens et al.	7,181,218	B2	2/2007	Ovesjo et al.
5,982,324	A	11/1999	Watters et al.	7,203,752	B2	4/2007	Rice et al.
6,018,312	A	1/2000	Haworth et al.	7,277,049	B2	10/2007	Korneluk et al.
6,026,301	A	2/2000	Satarasinghe	7,289,039	B2	10/2007	Kato et al.
6,058,260	A	5/2000	Brockel et al.	7,346,359	B2	3/2008	Damarla et al.
6,108,532	A	8/2000	Matsuda et al.	7,359,719	B1	4/2008	Duffett-Smith et al.
6,108,556	A	8/2000	Ito	7,366,492	B1	4/2008	Ganesh
6,125,125	A	9/2000	Narasimha et al.	7,375,649	B2	5/2008	Guezic
6,148,219	A	11/2000	Engelbrecht et al.	7,420,464	B2	9/2008	Fitzgerald et al.
6,216,002	B1	4/2001	Holmring	7,432,829	B2	10/2008	Poltorak
6,230,018	B1	5/2001	Watters et al.	7,436,794	B2	10/2008	Takahashi et al.
6,256,577	B1	7/2001	Graunke	7,463,143	B2	12/2008	Forr et al.
6,263,190	B1	7/2001	Mamori et al.	7,508,321	B2	3/2009	Guezic
6,292,665	B1	9/2001	Hildebrand et al.	7,664,492	B1	2/2010	Lee et al.
6,298,233	B1	10/2001	Souissi et al.	7,696,922	B2	4/2010	Nicholson et al.
6,307,503	B1	10/2001	Liu et al.	7,697,917	B2	4/2010	Camp et al.
6,311,078	B1	10/2001	Hardouin et al.	7,706,964	B2	4/2010	Horvitz et al.
6,317,686	B1	11/2001	Ran	7,744,740	B2	6/2010	Diehl
6,321,092	B1	11/2001	Fitch et al.	7,747,258	B2	6/2010	Farmer et al.
6,330,459	B1	12/2001	Crichton et al.	7,761,225	B2	7/2010	Vaughn
6,351,235	B1	2/2002	Stilp	7,831,380	B2	11/2010	Chapman et al.
6,353,778	B1	3/2002	Brown et al.	7,848,880	B2	12/2010	Cheung
6,397,074	B1	5/2002	Pihl et al.	7,890,299	B2	2/2011	Fok et al.
6,405,047	B1	6/2002	Moon	7,917,156	B2	3/2011	Sheynblat et al.
6,407,703	B1	6/2002	Minter et al.	7,945,271	B1	5/2011	Barnes et al.
6,429,815	B1	8/2002	Soliman	7,958,001	B2	6/2011	Abbadessa et al.
6,434,396	B1	8/2002	Rune	7,962,162	B2	6/2011	McNair
6,449,486	B1	9/2002	Rao	7,962,280	B2	6/2011	Kindo et al.
6,453,168	B1	9/2002	McCrary et al.	7,994,981	B1	8/2011	Farrokhi et al.
6,493,539	B1	12/2002	Falco et al.	7,996,020	B1	8/2011	Chhabra
6,515,623	B2	2/2003	Johnson	8,000,726	B2	8/2011	Altman et al.
6,522,296	B2	2/2003	Holt	8,005,050	B2	8/2011	Scheinert et al.
6,526,335	B1	2/2003	Treyz et al.	8,010,164	B1	8/2011	Sennett et al.
6,552,682	B1	4/2003	Fan	8,036,822	B2	10/2011	Ho et al.
6,560,532	B2	5/2003	Cayford	8,050,690	B2	11/2011	Neeraj
6,560,567	B1	5/2003	Yechuri et al.	8,054,802	B2	11/2011	Burgess et al.
6,594,576	B2	7/2003	Fan et al.	8,065,185	B2	11/2011	Foladare et al.
6,604,083	B1	8/2003	Bailey et al.	8,098,152	B2	1/2012	Zhang et al.
6,668,226	B2	12/2003	Sutanto et al.	8,121,604	B1	2/2012	Schwinghammer
6,690,292	B1	2/2004	Meadows et al.	8,126,479	B2	2/2012	Morrison
6,744,383	B1	6/2004	Alfred et al.	8,140,079	B2	3/2012	Olson
6,744,740	B2	6/2004	Chen	8,193,984	B2	6/2012	Ward et al.
6,757,545	B2	6/2004	Nowak et al.	8,194,589	B2	6/2012	Wynn et al.
6,801,782	B2	10/2004	McCrary et al.	8,195,175	B2	6/2012	Govindan et al.
6,801,855	B1	10/2004	Walters et al.	8,224,349	B2	7/2012	Meredith et al.
6,816,782	B1	11/2004	Walters et al.	8,253,559	B2	8/2012	Howard et al.
6,850,761	B2	2/2005	Pallonen	8,254,959	B2	8/2012	Fix et al.
6,892,054	B2	5/2005	Belcher et al.	8,264,956	B2	9/2012	Ramankutty et al.
6,915,123	B1	7/2005	Daudelin et al.	8,270,933	B2	9/2012	Riemer et al.
6,933,100	B2	8/2005	Igawa et al.	8,280,438	B2	10/2012	Barbera et al.
6,933,860	B1	8/2005	Gehman et al.	8,295,854	B2	10/2012	Osann et al.
7,058,710	B2	6/2006	McCall et al.	8,300,663	B2	10/2012	Chion et al.
				8,307,030	B1	11/2012	Hu
				8,326,682	B2	12/2012	Redford et al.
				8,355,364	B1	1/2013	Vargantwar et al.
				8,355,865	B2	1/2013	Wagner et al.
				8,417,264	B1	4/2013	Whitney et al.
				8,469,274	B2	6/2013	Tseng et al.
				8,548,494	B2	10/2013	Agarwal et al.
				8,572,198	B2	10/2013	Jhanji
				8,594,700	B2	11/2013	Nabbefeld
				8,611,919	B2	12/2013	Barnes
				8,612,410	B2	12/2013	Meredith et al.
				8,666,388	B2	3/2014	Catovic et al.
				8,666,390	B2*	3/2014	Meredith H04W 24/08 455/404.2
				8,761,799	B2	6/2014	Meredith et al.
				8,897,805	B2	11/2014	Fix et al.
				8,909,247	B2	12/2014	Tipton et al.
				8,923,134	B2*	12/2014	Meredith H04W 16/18 370/241
				9,008,684	B2	4/2015	Tipton et al.
				9,008,698	B2	4/2015	Meredith et al.
				9,232,399	B2	1/2016	Tipton et al.
				2001/0047242	A1	11/2001	Ohta

(56)

References Cited

U.S. PATENT DOCUMENTS

2002/0059266	A1	5/2002	I'anson et al.	2009/0079622	A1	3/2009	Seshadri et al.
2002/0069312	A1	6/2002	Jones	2009/0104917	A1	4/2009	Rached et al.
2002/0077116	A1	6/2002	Havinis et al.	2009/0117907	A1	5/2009	Wigren et al.
2002/0172223	A1	11/2002	Stilp et al.	2009/0125380	A1	5/2009	Otto et al.
2003/0040323	A1	2/2003	Pihl et al.	2009/0131073	A1	5/2009	Carlson et al.
2003/0092448	A1	5/2003	Forstrom et al.	2009/0181695	A1	7/2009	Wirola et al.
2003/0095065	A1	5/2003	Ericson et al.	2009/0227265	A1	9/2009	Kang et al.
2003/0097330	A1	5/2003	Hillmer et al.	2009/0234876	A1	9/2009	Schigel et al.
2003/0115228	A1	6/2003	Horvitz et al.	2009/0260055	A1	10/2009	Parmar
2003/0115260	A1	6/2003	Edge	2009/0280828	A1	11/2009	Wang et al.
2003/0125046	A1	7/2003	Riley et al.	2009/0286510	A1	11/2009	Huber et al.
2003/0158924	A1	8/2003	DeLegge	2009/0287922	A1	11/2009	Herwono et al.
2003/0222819	A1	12/2003	Karr et al.	2009/0299788	A1	12/2009	Huber et al.
2003/0225508	A9	12/2003	Petzold et al.	2009/0310501	A1	12/2009	Catovic et al.
2004/0024639	A1	2/2004	Goldman et al.	2009/0312005	A1	12/2009	Mukundan et al.
2004/0067759	A1	4/2004	Spirito et al.	2009/0327134	A1	12/2009	Carlson et al.
2004/0082338	A1	4/2004	Norrgard et al.	2010/0004997	A1	1/2010	Mehta et al.
2004/0127191	A1	7/2004	Matsunaga	2010/0020776	A1	1/2010	Youssef et al.
2004/0131036	A1	7/2004	Walsh	2010/0054237	A1	3/2010	Han et al.
2004/0155814	A1	8/2004	Bascobert	2010/0056179	A1	3/2010	Gaenger et al.
2004/0172190	A1	9/2004	Tsunehara et al.	2010/0058442	A1	3/2010	Costa et al.
2004/0219930	A1	11/2004	Lin	2010/0081389	A1	4/2010	Lawrow et al.
2004/0224698	A1	11/2004	Yi et al.	2010/0094758	A1	4/2010	Chamberlain et al.
2004/0267410	A1	12/2004	Duri et al.	2010/0100732	A1	4/2010	Hatakeyama et al.
2004/0267561	A1	12/2004	Meshkin et al.	2010/0100732	A1	4/2010	Hatakeyama et al.
2005/0007993	A1	1/2005	Chambers et al.	2010/0113035	A1	5/2010	Eskicioglu et al.
2005/0039056	A1	2/2005	Bagga et al.	2010/0120447	A1	5/2010	Anderson et al.
2005/0053099	A1	3/2005	Spear et al.	2010/0122314	A1	5/2010	Zhang et al.
2005/0136911	A1	6/2005	Csapo et al.	2010/0124886	A1	5/2010	Fordham et al.
2005/0239410	A1	10/2005	Rochester	2010/0124931	A1	5/2010	Eskicioglu et al.
2005/0272445	A1	12/2005	Zellner	2010/0135178	A1	6/2010	Aggarwal et al.
2005/0276385	A1	12/2005	McCormick et al.	2010/0144368	A1	6/2010	Sullivan
2006/0030333	A1	2/2006	Ward et al.	2010/0159951	A1	6/2010	Shkedi et al.
2006/0046744	A1	3/2006	Dublish et al.	2010/0163632	A1*	7/2010	Tseng G06K 9/3233
2006/0075131	A1	4/2006	Douglas et al.				235/494
2006/0089153	A1	4/2006	Sheynblat	2010/0172259	A1	7/2010	Aggarwal et al.
2006/0200303	A1	9/2006	Fuentes et al.	2010/0180039	A1	7/2010	Oh et al.
2006/0240839	A1	10/2006	Chen et al.	2010/0189236	A1	7/2010	MacDonald et al.
2006/0240841	A1	10/2006	Bhattacharya	2010/0190509	A1	7/2010	Davis et al.
2006/0267841	A1	11/2006	Lee et al.	2010/0195566	A1	8/2010	Krishnamurthy et al.
2006/0270419	A1	11/2006	Crowley et al.	2010/0203903	A1	8/2010	Dingler et al.
2006/0282660	A1	12/2006	Varghese et al.	2010/0207470	A1	8/2010	Kim et al.
2007/0001873	A1	1/2007	Ishikawa et al.	2010/0220665	A1	9/2010	Govindan et al.
2007/0049286	A1	3/2007	Kim et al.	2010/0222075	A1	9/2010	Miura
2007/0060130	A1	3/2007	Gogic et al.	2010/0227589	A1	9/2010	Cook et al.
2007/0088818	A1	4/2007	Roberts et al.	2010/0250542	A1	9/2010	Fujimaki
2007/0121560	A1	5/2007	Edge	2010/0262449	A1	10/2010	Monteforte et al.
2007/0149214	A1	6/2007	Walsh et al.	2010/0273504	A1	10/2010	Bull et al.
2007/0176749	A1	8/2007	Boyd	2010/0291907	A1	11/2010	MacNaughtan et al.
2007/0213074	A1	9/2007	Fitch et al.	2010/0296467	A1	11/2010	Pelletier et al.
2007/0217375	A1	9/2007	Zampiello et al.	2010/0299060	A1	11/2010	Snavelly et al.
2007/0217379	A1	9/2007	Fujiwara et al.	2010/0311437	A1	12/2010	Palanki et al.
2007/0293157	A1	12/2007	Haartsen et al.	2010/0313157	A1	12/2010	Carlsson et al.
2007/0298807	A1	12/2007	Yarkosky	2010/0323723	A1	12/2010	Gerstenberger et al.
2008/0004789	A1	1/2008	Horvitz et al.	2010/0331013	A1	12/2010	Zhang
2008/0010365	A1	1/2008	Schneider	2011/0009068	A1	1/2011	Miura
2008/0032705	A1	2/2008	Patel et al.	2011/0010085	A1	1/2011	Tanaka et al.
2008/0039114	A1	2/2008	Phatak et al.	2011/0023129	A1	1/2011	Vernal
2008/0056193	A1	3/2008	Bourlas et al.	2011/0026475	A1	2/2011	Lee et al.
2008/0070593	A1	3/2008	Altman et al.	2011/0026495	A1	2/2011	Lee et al.
2008/0071466	A1	3/2008	Downs et al.	2011/0039593	A1	2/2011	Lee et al.
2008/0076450	A1	3/2008	Nanda et al.	2011/0053609	A1	3/2011	Grogan et al.
2008/0096566	A1	4/2008	Brunner et al.	2011/0060808	A1	3/2011	Martin et al.
2008/0127354	A1	5/2008	Carpenter et al.	2011/0065450	A1	3/2011	Kazmi
2008/0133730	A1	6/2008	Park et al.	2011/0069668	A1	3/2011	Chion et al.
2008/0186234	A1	8/2008	Alles et al.	2011/0072034	A1	3/2011	Sly
2008/0192682	A1	8/2008	Matsumoto et al.	2011/0076975	A1	3/2011	Kim et al.
2008/0274750	A1	11/2008	Carlson et al.	2011/0077030	A1	3/2011	Wigren et al.
2008/0299995	A1	12/2008	Spain	2011/0077032	A1	3/2011	Correale et al.
2008/0305832	A1	12/2008	Greenberg	2011/0099047	A1	4/2011	Weiss et al.
2008/0311923	A1	12/2008	Petrovic et al.	2011/0106416	A1	5/2011	Scofield et al.
2009/0017823	A1	1/2009	Sachs et al.	2011/0130135	A1	6/2011	Trigui
2009/0024546	A1	1/2009	Ficcaglia et al.	2011/0151839	A1	6/2011	Bolon et al.
2009/0028082	A1	1/2009	Wynn et al.	2011/0161261	A1	6/2011	Wu et al.
2009/0052330	A1	2/2009	Matsunaga et al.	2011/0164596	A1	7/2011	Montemurro et al.
				2011/0171912	A1	7/2011	Beck et al.
				2011/0172905	A1	7/2011	Schroder et al.
				2011/0205964	A1	8/2011	Fix et al.
				2011/0207470	A1	8/2011	Meredith et al.
				2011/0210843	A1	9/2011	Kummetz et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2011/0210849 A1 9/2011 Howard et al.
 2011/0244879 A1 10/2011 Siomina et al.
 2011/0256874 A1 10/2011 Hayama et al.
 2011/0271331 A1 11/2011 Adams
 2011/0287801 A1 11/2011 Levin et al.
 2011/0296169 A1 12/2011 Palmer
 2011/0319098 A1 12/2011 Potorny et al.
 2012/0016902 A1 1/2012 Ranjan et al.
 2012/0025976 A1 2/2012 Richey et al.
 2012/0028650 A1 2/2012 Cooper et al.
 2012/0030083 A1 2/2012 Newman et al.
 2012/0032855 A1 2/2012 Reede et al.
 2012/0052883 A1 3/2012 Austin et al.
 2012/0052884 A1 3/2012 Bogatin
 2012/0062415 A1 3/2012 Hwang et al.
 2012/0087338 A1 4/2012 Brandt et al.
 2012/0099621 A1 4/2012 Karlsson et al.
 2012/0139782 A1 6/2012 Gutt et al.
 2012/0144452 A1 6/2012 Dyor et al.
 2012/0144457 A1 6/2012 Counterman
 2012/0158289 A1 6/2012 Brush et al.
 2012/0182180 A1 7/2012 Wolf et al.
 2012/0182874 A1 7/2012 Siomina et al.
 2012/0185309 A1 7/2012 Kakarla et al.
 2012/0214509 A1 8/2012 Levin et al.
 2012/0287911 A1 11/2012 Takano et al.
 2012/0302254 A1 11/2012 Charbit et al.
 2012/0317500 A1 12/2012 Kosseifi et al.
 2012/0323703 A1 12/2012 Hillier et al.
 2012/0327869 A1 12/2012 Wang et al.
 2013/0007058 A1 1/2013 Meredith et al.
 2013/0023237 A1 1/2013 Meredith et al.
 2013/0023247 A1 1/2013 Bolon et al.
 2013/0023274 A1 1/2013 Meredith et al.
 2013/0023281 A1 1/2013 Meredith et al.
 2013/0053057 A1 2/2013 Cansino et al.
 2013/0066748 A1 3/2013 Long
 2013/0095861 A1 4/2013 Li et al.
 2013/0096966 A1 4/2013 Barnes
 2013/0109407 A1 5/2013 Tipton et al.
 2013/0114464 A1 5/2013 Tarraf et al.
 2013/0137464 A1 5/2013 Kramer et al.
 2013/0226451 A1 8/2013 O'Neill et al.
 2013/0281111 A1 10/2013 Syrjarinne et al.
 2013/0324149 A1 12/2013 Fix et al.
 2013/0337824 A1 12/2013 Meredith et al.
 2014/0062782 A1 3/2014 Abraham
 2014/0106779 A1 4/2014 Arslan et al.
 2014/0122220 A1 5/2014 Bradley et al.
 2014/0171060 A1 6/2014 Cook et al.
 2014/0278744 A1 9/2014 Lo Faro et al.

FOREIGN PATENT DOCUMENTS

JP 2004069609 A 3/2004
 JP 2005091303 A 4/2005
 JP 2007328050 A 12/2007
 WO WO2006031035 A1 3/2006

OTHER PUBLICATIONS

Office Action dated Aug. 28, 2014 for U.S. Appl. No. 13/526,988, 83 pages.
 Office Action dated Sep. 22, 2014 for U.S. Appl. No. 13/175,199, 62 pages.
 Office Action dated Oct. 17, 2014 for U.S. Appl. No. 13/204,535, 47 pages.
 Office Action dated Oct. 20, 2014 for U.S. Appl. No. 13/494,959, 64 pages.
 Office Action dated Oct. 22, 2014 for U.S. Appl. No. 13/557,425, 59 pages.
 Office Action dated Aug. 11, 2014 for U.S. Appl. No. 14/279,176, 22 pages.

Office Action dated Nov. 14, 2014 for U.S. Appl. No. 13/277,595, 74 pages.
 Notice of Allowance dated Nov. 20, 2014 for U.S. Appl. No. 13/866,909, 27 pages.
 Notice of Allowance dated Dec. 9, 2014 for U.S. Appl. No. 12/958,146, 48 pages.
 Office Action dated Dec. 11, 2014 for U.S. Appl. No. 13/447,072, 28 pages.
 Office Action dated Dec. 1, 2014 for U.S. Appl. No. 13/495,756, 76 pages.
 Office Action dated Jan. 7, 2015 for U.S. Appl. No. 13/557,425, 30 pages.
 Notice of Allowance mailed Jan. 21, 2015 for U.S. Appl. No. 13/495,391, 98 pages.
 Notice of Allowance mailed Feb. 6, 2015 for U.S. Appl. No. 13/204,535, 20 pages.
 Office Action dated Feb. 13, 2015 for U.S. Appl. No. 14/516,286, 62 pages.
 Girardin, et al., "Digital footprinting: Uncovering tourists with user generated content." *Pervasive Computing*, IEEE 7.4, Oct.-Nov. 2008. 8 pages.
 Steinfield, "The development of location based services in mobile commerce." *ELife after the Dot Com Bust*. PhysicaVerlagHD, 2004. 15 pages.
 Sevtsuk, et al., "Does urban mobility have a daily routine? Learning from the aggregate data of mobile networks." *Journal of Urban Technology*, vol. 17, No. 1, Apr. 2010: 20 pages.
 Buhalis, et al., "Information communication technology revolutionizing tourism." *Tourism Recreation Research*, vol. 30, No. 3, 2005. 10 pages.
 Ratti, et al. "Mobile Landscapes: using location data from cell phones for urban analysis." *Environment and Planning B: Planning and Design*, vol. 33, 2006, 23 pages.
 Office Action dated Sep. 14, 2015 for U.S. Appl. No. 13/557,425, 32 pages.
 Office Action dated Apr. 16, 2015 for U.S. Appl. No. 14/521,431, 82 Pages.
 Notice of Allowance dated Mar. 19, 2015 for U.S. Appl. No. 13/494,959, 41 Pages.
 Notice of Allowance dated Mar. 26, 2015 for U.S. Appl. No. 14/276,688, 75 pages.
 Office Action dated May 1, 2015 for U.S. Appl. No. 13/557,425, 33 pages.
 Office Action dated May 14, 2015 for U.S. Appl. No. 14/530,605, 72 pages.
 Office Action dated Jun. 1, 2015 for U.S. Appl. No. 13/447,072, 38 pages.
 Office Action dated Jun. 2, 2015 for U.S. Appl. No. 14/516,286, 20 pages.
 Office Action dated May 20, 2015 for U.S. Appl. No. 13/526,988, 52 pages.
 Office Action dated Jun. 9, 2015 for U.S. Appl. No. 13/495,756, 35 pages.
 Notice of Allowance dated Jul. 8, 2015 for U.S. Appl. No. 14/548,901, 125 pages.
 Buford, et al, "Location Privacy Enforcement in a Location-Based Services Platform," *IEEE*, 2009, 5 pages.
 Phillips, Jr., et al., "Information Sharing and Security in Dynamic Coalitions," *ACM*, 2002, pp. 87-96, 10 pages.
 Moniruzzaman, et al., "A Study of Privacy Policy Enforcement in Access Control Models", *Proceedings of 13th International Conference on Computer and Information Technology IEEE*, 2010, pp. 352-357, 6 pages.
 Office Action dated Jul. 22, 2015 for U.S. Appl. No. 13/188,136, 31 Pages.
 "Cell_DCH", in *INACON Glossary*, published online at [http://www.inacon.de/glossary/CELL_DCH.php] retrieved on Jul. 22, 2015, 1 page.
 Office Action dated Sep. 17, 2015 for U.S. Appl. No. 13/495,756, 23 Pages.
 Office Action dated Sep. 18, 2015 for U.S. Appl. No. 14/641,247, 69 Pages.

(56)

References Cited

OTHER PUBLICATIONS

Notice of Allowance dated Aug. 27, 2015 for U.S. Appl. No. 14/521,431, 39 Pages.

Office Action dated Nov. 16, 2015 for U.S. Appl. No. 13/188,136, 31 pages.

“Error”, The American Heritage(R) Dictionary of the English Language, 2011, Houghton Mifflin Company, Boston, MA, 2 pages. Retrieved from [<http://search.credreference.com/contententry/hmdictenglang/error/O>] on Nov. 16, 2015.

Office Action dated Nov. 23, 2015 for U.S. Appl. No. 14/520,287, 80 pages.

Office Action dated Nov. 16, 2015 for U.S. Appl. No. 14/566,657, 87 pages.

Office Action dated Dec. 18, 2015 for U.S. Appl. No. 14/548,901, 35 pages.

Office Action dated Dec. 31, 2015 for U.S. Appl. No. 14/952,609, 32 pages.

Office Action dated Dec. 1, 2015 for U.S. Appl. No. 13/526,988, 43 pages.

Office Action dated Nov. 30, 2015 for U.S. Appl. No. 13/447,072, 45 pages.

Office Action dated Jan. 11, 2016 for U.S. Appl. No. 13/175,199, 29 pages.

Notice of Allowance mailed Aug. 12, 2013, for U.S. Appl. No. 13/174,541, 40 pages.

Office Action dated Aug. 2, 2013 for U.S. Appl. No. 13/188,295, 26 pages.

Office Action dated Aug. 2, 2013, for U.S. Appl. No. 13/188,300, 38 pages.

Office Action dated Jun. 20, 2013, for U.S. Appl. No. 13/219,911, 61 pages.

Office Action dated Jul. 17, 2013, for U.S. Appl. No. 13/188,345, 27 pages.

Office Action dated Jun. 20, 2013, for U.S. Appl. No. 13/291,917, 52 pages.

Office Action dated May 31, 2013, for U.S. Appl. No. 13/523,770, 40 pages.

Office Action dated Sep. 19, 2013, for U.S. Appl. No. 13/927,020, 30 pages.

Office Action dated Oct. 2, 2013 for U.S. Appl. No. 12/958,146, 31 pages.

Office Action dated Sep. 26, 2013 for U.S. Appl. No. 13/284,456, 58 pages.

RouteFinder 3.00 for ArGIS Documentation, 2007, Routeware and Higher Mapping Solutions, 71 pages, downloaded from http://www.routeware.dk/download/routefinder_arcgis.pdf.

mySociety (Web page), “More travel-time maps and their uses”, 2007, downloaded from <http://www.mySociety.org/2007/more-travel-maps/>, 10 pages total (including a single page Examiner’s attachment showing the operation of the interactive travel-time map).

Wayback machine archive from Jan. 21, 2009 of the mySociety Web page, “More travel-time maps and their uses”, downloaded from <http://web.archive.org/web/20090121193615/http://www.mysociety.org/2007/more-travel-maps/>, 11 pages.

Street, Nicholas, “TimeContours: Using isochrone visualisation to describe transport network travel cost”, Final Report, Jun. 14, 2006, Department of Computing Imperial College London, 97 pages. Downloaded from <http://www.doc.ic.ac.uk/teaching/projects/Distinguished06/nicholasstreet.pdf>.

Office Action dated Nov. 5, 2013 for U.S. Appl. No. 13/188,136, 47 pages.

Office Action dated Sep. 18, 2013, for U.S. Appl. No. 13/284,497, 30 pages.

Office Action dated Aug. 22, 2013, for U.S. Appl. No. 13/277,595, 36 pages.

Office Action dated Oct. 21, 2013, for U.S. Appl. No. 13/523,770, 24 pages.

Office Action dated Nov. 5, 2013 for U.S. Appl. No. 13/188,345, 30 pages.

Office Action dated Dec. 11, 2013, for U.S. Appl. No. 13/188,295, 52 pages.

Office Action dated Dec. 24, 2013, for U.S. Appl. No. 13/188,300, 44 pages.

Office Action dated Dec. 11, 2013, for U.S. Appl. No. 13/291,917, 34 pages.

Office Action dated Jan. 15, 2014 for U.S. Appl. No. 13/219,911, 38 pages.

Office Action dated Jan. 28, 2014, for U.S. Appl. No. 12/958,146, 24 pages.

Notice of Allowance dated Feb. 14, 2014 for U.S. Appl. No. 13/284,456, 30 pages.

Office Action dated Feb. 24, 2014, for U.S. Appl. No. 13/927,020, 18 pages.

Office Action dated May 21, 2013 for U.S. Appl. No. 13/305,276, 28 pages.

Office Action dated Oct. 24, 2012 for U.S. Appl. No. 13/305,276, 37 pages.

“Locate your friends in real time with Google Latitude.” <http://googlemobile.blogspot.com/2009/02/locate-your-friends-in-real-time-with.html>. Last accessed Mar. 8, 2012, 23 pages.

“Location sharing and updating.” <http://support.google.com/mobile/bin/answer.py?hl=en&answer=136647>. Last accessed Mar. 8, 2012, 3 pages.

“Privacy Settings.” <http://support.google.com/mobile/bin/answer.py?hl=en&answer=136650>, Last accessed Mar. 8, 2012, 1 page.

Office Action dated Nov. 25, 2013 for U.S. Appl. No. 13/447,069, 40 pages.

Office Action dated May 9, 2013 for U.S. Appl. No. 13/447,069, 33 pages.

Tsai, et al, “Location-Sharing Technologies: Privacy Risks and Controls.” Feb. 2010. Retrieved on May 10, 2013, 26 pages.

Li et al, “Sharing Location in Online Social Networks”. IEEE Network, Sep./Oct. 2010; 0890-8044/10/\$25.00(c)2010 IEEE. Retrieved on May 10, 2013, 6 pages.

Tsai, et al, “Who’s Viewed You? The Impact of Feedback in a Mobile Location-Sharing Application”. CHI 2009—Security and Privacy, Apr. 9th, 2009—Boston, MA, USA. Retrieved on May 10, 2013, 10 pages.

Petterson, et al., “Automatic antenna tilt control for capacity enhancement in UMTS FDD.” Retrieved on Mar. 25, 2012, 5 pages.

Islam, et al., “Self-Optimization of Antenna Tilt and Pilot Power for Dedicated Channels.” Retrieved on Mar. 25, 2012, 8 pages.

Bigham, et al., “Tilting and Beam-shaping for Traffic Load Balancing in WCDMA Network.” Retrieved on Mar. 25, 2012, 4 pages.

3GPP TS 25.215 V6.4.0 (Sep. 2005) Physical Layer Measurements, Sep. 2005.

3GPP TS 25.331 V6.9.0 (Mar. 2006) RRC protocol for the UE-UTRAN radio interface, Mar. 2006.

3GPP TS 25.413 V6.9.0 (Mar. 2006) UTRAN lu interface RANAP signalling, Mar. 2006.

Calabrese, et al., “Real-Time Urban Monitoring Using Cell Phones: A Case Study in Rome”. IEEE Transactions on Intelligent Transportation Systems, 12 pages. (http://senseable.mit.edu/papers/pdf/2010_Calabrese_et_al_Rome_TITS.pdf). Retrieved on Sep. 29, 2012, 11 pages.

Smith, et al., “Airsage Overview”, (<http://mikeontraffic.typepad.com/files/raleigh-winter-2011-presentation-v11-final.pdf>) Retrieved on Sep. 29, 2012, 39 pages.

Office Action dated Feb. 5, 2014 for U.S. Appl. No. 13/526,988, 56 pages.

Marko Silventoinen, Timo Rantalainen, “Mobile Station Locating in GSM” Helsinki, Finland, Last accessed on Nov. 15, 2011, 7 pages.

Office Action dated Dec. 30, 2013 for U.S. Appl. No. 13/305,267, 10 pages.

Office Action dated Mar. 25, 2014 for U.S. Appl. No. 13/488,144, 60 Pages.

Interview Summary dated Feb. 3, 2014 for U.S. Appl. No. 13/188,136, 10 pages.

(56)

References Cited

OTHER PUBLICATIONS

Rabinowitz, et al., A new positioning system using television synchronization signals, IEEE Transactions on Broadcasting, vol. 51(1), p. 51-61, Mar. 2005.

Office Action dated Apr. 8, 2014 for U.S. Appl. No. 13/175,199, 52 Pages.

Office Action dated Apr. 23, 2014 for U.S. Appl. No. 13/291,917, 29 Pages.

Office Action dated Apr. 22, 2014 for U.S. Appl. No. 13/447,069, 51 Pages.

Office Action dated Sep. 20, 2012 for U.S. Appl. No. 12/870,254, 29 pages.

Office Action dated May 14, 2014 for U.S. Appl. No. 13/660,689, 62 pages.

Office Action dated May 9, 2014 for U.S. Appl. No. 13/188,136, 33 pages.

Squires, "Practical Physics", Cambridge University Press, p. 12, 1986, 3 pages.

Represent (2000). In Collins English dictionary. Retrieved on May 9, 2014 from <http://search.credoreference.com/content/entry/hcengdict/represent/0>, 2 pages.

Represent. (2001). In Chambers 21 st century dictionary. Retrieved on May 9, 2014 from <http://search.credoreference.com/content/entry/chambdict/represent/O>.

Represent. (2011). In The American heritage dictionary of the English language. Retrieved on May 9, 2014 from <http://search.credoreference.com/content/entry/hmdictenglang/represent/0>.

Office Action dated May 20, 2014 for U.S. Appl. No. 13/551,369, 29 pages.

Office Action dated May 30, 2014 for U.S. Appl. No. 13/277,595, 49 pages.

Office Action dated Jun. 3, 2014 for U.S. Appl. No. 13/523,770, 53 pages.

Office Action dated Jun. 6, 2014 for U.S. Appl. No. 13/447,072, 25 pages.

Office Action dated Apr. 3, 2014 for U.S. Appl. No. 13/188,295, 37 pages.

Office Action dated Jun. 18, 2014 for U.S. Appl. No. 13/305,276, 26 Pages.

Office Action dated Jun. 26, 2014 for U.S. Appl. No. 13/557,425, 24 Pages.

Office Action dated Jun. 30, 2014 for U.S. Appl. No. 13/305,267, 44 Pages.

Office Action dated Jul. 22, 2014 for U.S. Appl. No. 12/958,146, 38 Pages.

Notice of Allowance dated Jul. 22, 2014 for U.S. Appl. No. 13/525,065, 82 Pages.

Notice of Allowance dated Jul. 7, 2014 for U.S. Appl. No. 13/188,295, 51 pages.

Notice of Allowance dated Jul. 22, 2014 for U.S. Appl. No. 13/188,300, 49 Pages.

Office Action dated Aug. 8, 2014 for U.S. Appl. No. 13/284,497, 48 pages.

Office Action mailed Mar. 11, 2016 for U.S. Appl. No. 14/743,076, 86 pages.

Notice of Allowance mailed Mar. 16, 2016 for U.S. Appl. No. 14/520,287, 23 pages.

Office Action mailed Mar. 18, 2016 for U.S. Appl. No. 13/447,072, 37 pages.

Office Action dated Apr. 5, 2016 for U.S. Appl. No. 13/188,136, 33 pages.

Office Action dated Apr. 13, 2016 for U.S. Appl. No. 14/877,915, 76 pages.

Office Action dated May 17, 2016 for U.S. Appl. No. 15/074,622, 18 pages.

Office Action mailed Jun. 10, 2016 for U.S. Appl. No. 14/548,901, 33 pages.

Office Action mailed Jun. 22, 2016 for U.S. Appl. No. 14/970,533, 84 pages.

Office Action mailed Jun. 28, 2016 for U.S. Appl. No. 15/132,220, 17 pages.

Notice of Allowance dated Jul. 19, 2016 for U.S. Appl. No. 14/952,609, 99 pages.

Office Action dated Aug. 24, 2016 for U.S. Appl. No. 14/676,066, 107 pages.

Office Action dated Aug. 25, 2016 for U.S. Appl. No. 13/447,072, 38 pages.

3rd Generation Partnership Project, Technical Specification, "Group GSM/EDGE Radio Access Network, Radio subsystem synchronization (Release 8)", 3GPP TS 45.010 V8.0.0 (May 2008), last viewed Jul. 1, 2009, 30 pages.

3rd Generation Partnership Project, Technical Specification, "Group Radio Access Network, UTRAN Iuh interface Home Node B Application Part (HNBAP) signalling (Release 8)", 3GPP TS 25.469 V8.0.0 (Dec. 2008), last viewed Jul. 1, 2009, 56 pages.

Sullivan, Mark. "Signs and Wonders: Is AT&T Stepping Up Its Game?" PC World, Dec. 10, 2009, 1 page.

ETSI TS 125 215 V6.4.0 (Sep. 2005). Universal Mobile Telecommunications System (UMTS), Physical layer, Measurements (FDD), 3GPP TS 25.215 version 6.4.0 Release 6). Last accessed Jun. 18, 2010, 20 pages.

ETSI TS 125 331 V6.9.0 (Mar. 2006). Universal Mobile Telecommunications System (UMTS), Radio Resource Control (RRC) protocol specification, (3GPP TS 25.331 version 6.9.0 Release 6). Last accessed Jun. 18, 2010, 1211 pages.

New Devices Aim to Disable Cell Phones While Driving. FOXNews.com, Jan. 18, 2009. http://www.foxnews.com/printer_friendly_story/0,3566,480585,00.html. Last accessed Nov. 24, 2010, 2 pages.

Cortes, et al. "Support-Vector Networks", Machine Learning, 20, 1995. <http://www.springerlink.com/content/k238jx04hm87j80g/fulltext.pdf>. Last accessed Dec. 24, 2010, 25 pages.

ACM Website, Press release of Mar. 17, 2009. <http://www.acm.org/press-room/news-releases/pdfs/awards-08-groupa1.pdf>. Last accessed Dec. 24, 2010, 3 pages.

Boser, et al. A training algorithm for optimal margin classifiers. In D. Haussler, editor, 5th Annual ACM Workshop on COLT, pp. 144-152, Pittsburgh, PA, 1992. ACM Press. <http://citeseerx.ist.psu.edu/viewdoc/summary?doi=10.1.1.21.3818>. Last accessed Dec. 24, 2010, 9 pages.

Hsu, et al. A Practical Guide to Support Vector Classification. Department of Computer Science National Taiwan University, Last updated: Apr. 15, 2010. <http://www.csie.ntu.edu.tw/~cjlin/papers/guide/guide.pdf>. Last accessed Dec. 24, 2010, 16 pages.

Drucker, et al. Support Vector Regression Machines. <http://scholar.google.com/scholar?q=%22Support+Vector+Regression+Machines.%22>. Last accessed Dec. 24, 2010, 7 pages.

Suykens, et al., "Least squares support vector machine classifiers", Neural Processing Letters, vol. 9, No. 3, Jun. 1999, pp. 293-300.

Ferris, et al (2002). "Interior-point methods for massive support vector machines". SIAM Journal on Optimization 13: 783-804. doi:10.1137/S1052623400374379.

Meyer, et al "The support vector machine under test." Neurocomputing 55(1-2): 169-186, 2003.

International Search Report for PCT Application No. US2011/026122, dated Sep. 10, 2011, 11 pages.

International Search Report for PCT Application No. US2011/026120, dated Sep. 9, 2011, 13 pages.

Charitanetra et al. "Mobile positioning location using E-OTD method for GSM network" Research and Development, 2003. Proceedings Student Conference on Putrajaya, Malaysia Aug. 25-26, 2003, pp. 319-324.

"Location Labs Powers Location-based Fraud Detection", All Points Blog, http://webcache.googleusercontent.com/search?hl=en&rlz=1R2GFRE_enUS398&q=cache:trsMn9Sin6wJ:http://apb.directionsmag.com/entry/location-labs-powers-location-based-fraud-detection/162802+http%3A//apb.directionsmag.com/entry/location-labs-powers-location-based-...1&ct=clnk, Oct. 12, 2010.

"Location Based Fraud Detection", Finsphere Corporation, 2008-2010.

(56)

References Cited

OTHER PUBLICATIONS

Fleishman. Using the Personal Hotspot on your AT & T iPhone. Published online Mar. 15, 2011. http://www.macworld.com/article/158556/2011/03/personal_hotspot_att..., 4 pages.

Fleischfresser. Never Stop at a Red-Light Again. Published online Aug. 30, 2011. <http://www.smartplanet.com/blog/...>, 2 pages.

Cellphone Networks and the Future of Traffic. Published online Mar. 2, 2011. <http://m.wired.com/autopia/2011/03/cell-phone-networks-and-the-future-...> 15 pages.

Intelligent Transportation System. Published online http://en.wikipedia.org/wiki/Intelligent_transportation_system, retrieved on Aug. 15, 2011, 7 pages.

Koukoumidis Emmanouil, Peh Li-Shiuan, Martonosi Margaret, SignalGuru: Leveraging Mobile Phones for Collaborative Traffic Signal Schedule Advisory, MobiSys'11, Jun. 28-Jul. 1, 2011, Bethesda, Maryland, USA. 14 pages.

Bitcarrier Technology. Published online at <http://www.bitcarrier.com/technology>, retrieved on Aug. 15, 2011, 1 page.

Hao Peng, Ban Xuegang(Jeff). Estimating Vehicle Position in a Queue at Signalized Intersections Using Simple Travel Times from Mobile Sensors, retrieved Nov. 18, 2011. 6 pages.

Ban Xuegang(Jeff), Gruteser Marco. Mobile Sensor as Traffic Probes: Addressing Transportation Modeling and Privacy Protection in an Integrated Framework, dated Jan. 10, 2010, 17 pages.

Office Action for U.S. Appl. No. 12/836,471 dated Dec. 28, 2011, 34 pages.

Office Action dated Feb. 23, 2012 for U.S. Appl. No. 12/967,747, 31 pages.

Office Action dated Dec. 15, 2011 for U.S. Appl. No. 12/712,424, 34 pages.

Office Action dated Apr. 13, 2012 for U.S. Appl. No. 12/416,853, 36 pages.

Office Action dated Oct. 2, 2012 for U.S. Appl. No. 13/554,285, 19 pages.

Office Action dated Aug. 30, 2012 for U.S. Appl. No. 12/958,146, 40 pages.

MobileLutions Introduces MobiLoc-A Breakthrough Technology to Control Texting in the Mobile Workplace. Press release Oct. 10, 2010 by MobileLutions. 2 pages.

DriveAssist Frequently Ask question by Aegis Mobility, Wayback archive Jul. 12, 2010, 2 pages.

Office Action dated Jul. 30, 2012 for U.S. Appl. No. 12/967,747, 28 pages.

Office Action dated Jul. 17, 2012 for U.S. Appl. No. 13/220,083, 57 pages.

Office Action dated Sep. 11, 2012 for U.S. Appl. No. 13/188,345, 44 pages.

Office Action dated Oct. 15, 2012 for U.S. Appl. No. 13/523,778, 21 pages.

Office Action dated Dec. 20, 2012 for U.S. Appl. No. 12/958,146, 23 pages.

Office Action dated Dec. 28, 2012 for U.S. Appl. No. 13/188,295, 37 pages.

Office Action dated Jan. 3, 2013 for U.S. Appl. No. 13/188,300, 36 pages.

Office Action dated Nov. 8, 2012 for U.S. Appl. No. 13/204,535, 30 pages.

Office Action dated Jan. 25, 2013, for U.S. Appl. No. 13/554,285, 20 pgs.

Office Action dated Mar. 19, 2013, for U.S. Appl. No. 13/174,541, 46 pgs.

Office Action dated Feb. 13, 2013, for U.S. Appl. No. 13/220,083, 48 pgs.

Office Action dated Feb. 22, 2013, for U.S. Appl. No. 13/188,345, 45 pgs.

Office Action dated Mar. 15, 2013, for U.S. Appl. No. 13/204,535, 18 pgs.

Office Action dated Mar. 19, 2013, for U.S. Appl. No. 13/284,497, 46 pgs.

Office Action dated Apr. 19, 2013, for U.S. Appl. No. 13/277,595, 58 pages.

Office Action dated Sep. 30, 2016 for U.S. Appl. No. 14/957,525, 72 pages.

Notice of Allowance mailed Oct. 7, 2016 for U.S. Appl. No. 14/548,901, 45 pages.

Office Action dated Oct. 12, 2016 for U.S. Appl. No. 14/877,915, 34 pages.

Office Action dated Dec. 28, 2016 for U.S. Appl. No. 13/447,072, 34 pages.

Office Action dated Feb. 14, 2017 for U.S. Appl. No. 14/641,242, 120 pages.

Office Action dated Jan. 13, 2017 for U.S. Appl. No. 14/601,800, 95 pages.

Office Action dated Jan. 26, 2017 for U.S. Appl. No. 14/877,915, 30 pages.

Office Action dated Feb. 15, 2017 for U.S. Appl. No. 15/191,877, 104 pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10

1

**GEOGRAPHIC REDUNDANCY
DETERMINATION FOR TIME BASED
LOCATION INFORMATION IN A WIRELESS
RADIO NETWORK**

CROSS-REFERENCE TO RELATED
APPLICATIONS

This application is a continuation of, and claims priority to each of, U.S. patent application Ser. No. 14/520,287, filed on 21 Oct. 2014, and entitled "GEOGRAPHIC REDUNDANCY DETERMINATION FOR TIME BASED LOCATION INFORMATION IN A WIRELESS RADIO NETWORK," which is a continuation of U.S. patent application Ser. No. 13/525,065, filed on 15 Jun. 2012, and entitled "GEOGRAPHIC REDUNDANCY DETERMINATION FOR TIME BASED LOCATION INFORMATION IN A WIRELESS RADIO NETWORK," now issued as U.S. Pat. No. 8,897,805, the entireties of which applications are hereby incorporated herein by reference.

TECHNICAL FIELD

The disclosed subject matter relates to a determining geographic redundancy in a wireless radio network, e.g., determination of geographically redundant radios employed in determining time based location information in a wireless radio network.

BACKGROUND

In mobile equipment networks, locating user equipments (UEs) can provide valuable additional benefits to users and opportunities for additional or improved services. Locating UEs in a wireless network can facilitate providing location-centric services or information in relation to the UE, such as E911 services, mapping services, or traffic information services, among many others. Additionally, UE location information can be employed to improve network performance, to troubleshoot networks, by law enforcement, to aggregate valuable demographic information, or nearly a limitless number of other uses. Network timing delays include site timing delay in the wireless signal path among radio component(s) at the wireless base station and a sector antenna. Network timing delays further include delays that can arise from various mismatches (e.g., impedance mismatch) among electronic elements and components, stray capacitances and inductances, length of the antenna(s) cable(s) in base station(s); tower height of base station, signal path scattering, or "signal bounces," such as multipath or strong reflections, and the like. Propagation delay between a UE and a NodeB is conventionally assumed to be negligible with respect to timing delay. However, depending on the architecture of the serving base station and covered sector antenna(s), signal propagation delay can be non-negligible, particularly in distributed antenna systems and low-power wireless radio cells and cause error in UE location determinations for traditional methods.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is an illustration of a system that facilitates determining a level of geographic redundancy in accordance with aspects of the subject disclosure.

FIG. 2 is a depiction of a system that facilitates determining a level of geographic redundancy in accordance with aspects of the subject disclosure.

2

FIG. 3 illustrates a system that facilitates determining a level of geographic redundancy for a timed fingerprint locating enabled system in accordance with the disclosed subject matter.

FIG. 4 is an illustration of an exemplary system having a level of geographic redundancy in accordance with aspects of the subject disclosure.

FIG. 5 is an illustration of an exemplary system having a level of geographic redundancy in accordance with aspects of the subject disclosure.

FIG. 6 illustrates a method facilitating determining a level of geographic redundancy in accordance with aspects of the subject disclosure.

FIG. 7 illustrates a method for facilitating determining a level of geographic redundancy in accordance with aspects of the subject disclosure.

FIG. 8 illustrates an exemplary flowchart for a method facilitating determining a level of geographic redundancy in accordance with aspects of the subject disclosure.

FIG. 9 is a block diagram of an exemplary embodiment of a mobile network platform to implement and exploit various features or aspects of the subject disclosure.

FIG. 10 illustrates a block diagram of a computing system operable to execute the disclosed systems and methods in accordance with an embodiment.

DETAILED DESCRIPTION

The subject disclosure is now described with reference to the drawings, wherein like reference numerals are used to refer to like elements throughout. In the following description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the subject disclosure. It may be evident, however, that the subject disclosure may be practiced without these specific details. In other instances, well-known structures and devices are shown in block diagram form in order to facilitate describing the subject disclosure.

By way of brief background, a network locating system (NELOS) can employ timed fingerprint location (TFL). TFL, as disclosed in U.S. patent application Ser. No. 12/712,424, can facilitate determining location information based, in part, on receiving timing measurements between at least a pair of wireless network radios and a device. In an aspect, determining location information in a NELOS-enabled system, e.g., a system employing TFL, benefits from employing one or more timing measurements for a non-redundant radio link with a device, e.g., timing measurements associated with radio links between a NodeB site pair (NBSP) and a mobile device. Non-redundant radio links can generally employ non-redundant radios. A radio can be associated with a level of redundancy where, geographically, two or more radios are close enough to each other that they result in highly similar timing measurements for use in location information determination. In an aspect, while radios that are close together can be employed in determining location information, they generally will have greater error in a location determination information than radios that are not geographically redundant. As an example, radio pairs, e.g., NBSPs, with geographically redundant radios in a TFL-enabled system can yield results from a query that are highly similar and thus, determining an intersection of those query results can have a lower level of confidence than would be associated with query results from NBSPs with non-redundant radios.

A NELOS can employ TFL technologies that can include location information or timing information as disclosed

herein and as further disclosed in more detail in U.S. Ser. No. 12/712,424 filed Feb. 25, 2010, which application is hereby incorporated by reference in its entirety. TFL information can facilitate access to location information for a mobile device, e.g., a UE. TFL information can be information from systems in a timed fingerprint location wireless environment, such as a TFL component of a wireless telecommunications carrier. As a non-limiting example, UEs, including mobile devices not equipped with a GPS-type system, can be associated with TFL information, which can facilitate determining a location for a UE based on the timing information associated with the UE.

In an aspect, TFL information can include information to determine a differential value for a radio, e.g., a NodeB site pair, and a bin grid frame, as disclosed in more detail in incorporated U.S. Ser. No. 12/712,424. A centroid region (possible locations between any site pair) for an observed time value associated with any NodeB site pair (NBSP) can be calculated and can be related to the determined value (in units of chip) from any pair of NodeBs. When UE time data is accessed, a value look-up can be initiated (e.g., a lookup for “DV(?,X)” as disclosed in more detail in the application incorporated herein by reference). Relevant NBSPs can be prioritized as part of the look-up. Further, the relevant pairs can be employed as an index to lookup a first primary set. As an example, time data for a UE can be accessed in relation to a locating event in a TFL wireless carrier environment. In this example, it can be determined that a NBSP, with a first reference frame, be used for primary set lookup with the computed DV(?,X) value as the index. This can return, for example, a set of bin grid frame locations forming a hyperbola correlating to the radios of the NBSP. A second lookup can then be performed for an additional relevant NBSP, using the same value DV(?,X), as an index into the data set. Continuing the example, the returned set for the look up with second NBSP can return a second set of bin grid frames. Thus, the UE is likely located in both sets of bin grid frames. Therefore, where the UE is likely in both sets, it is probable that the location for the UE is at an intersection of the two sets. Additional NBSPs can be included to further narrow the possible locations of the UE by providing additional intersections among relevant bin grid sets. As such, employing TFL information for location determination is demonstrably different from conventional location determination techniques or systems such as GPS, AGPS, triangulation or multilateration in wireless carrier environments, near field techniques, or proximity sensors.

In an embodiment, a system can include a processor and memory. The processor can facilitate the execution of computer-executable instructions stored on the memory. The processor can facilitate execution of the computer-executable instructions to determine a level of geographic redundancy for a first radio of a wireless network. The determined level of geographic redundancy can be based on geographic information relating to a set of radios, of the wireless network, including the first radio.

In another embodiment, a method can include determining, by a system including at least one processor, a level of geographic redundancy for a first radio of a wireless network. The determining of the level of geographic redundancy can be based on geographic information relating to a set of radios, of the wireless network, including the first radio.

In a further embodiment, a method can include receiving, by a system including at least one processor, predetermined information relating to levels of geographic redundancy for a set of radios of a wireless network. The method can further

include determining, by the system, location information based on information relating to a selected radio. The selection of the radio can be based on the predetermined information relating to the levels of geographic redundancy for the set of radios of the wireless network.

To the accomplishment of the foregoing and related ends, the disclosed subject matter, then, comprises one or more of the features hereinafter more fully described. The following description and the annexed drawings set forth in detail certain illustrative aspects of the subject matter. However, these aspects are indicative of but a few of the various ways in which the principles of the subject matter can be employed. Other aspects, advantages and novel features of the disclosed subject matter will become apparent from the following detailed description when considered in conjunction with the drawings.

FIG. 1 is an illustration of a system **100**, which facilitates adaptive calibration in accordance with aspects of the subject disclosure. System **100** can include radio geographic information (RGI) component **110** that can facilitate access to geographic information related to radios of a wireless network. In an aspect, wireless network carriers know the location at which the radios of the wireless network are placed as part of deploying the physical resources of a wireless network. In certain embodiments, geographic information for wireless network radios can be in the form of geographic information system (GIS) information. A geographic information system can be a system designed to handle types of geographical data. At a very basic level, GIS can be a mélange of cartography, statistical analysis, and database technology. RGI component **110** can enable, in some embodiments, interaction with GIS information. As a non-limiting example, RGI component **110** can facilitate receiving geographic position information for radio resources of a wireless network carrier by way of a coupling with the carrier’s GIS system.

System **100** can further include rule component **120** that can facilitate access to one or more rules associated with determining a level of geographic redundancy. In an aspect, rules can relate to definition of, or characterization of geographic information as it relates to geographic redundancy. As an example, a rule can include one or more predetermined threshold values that correspond to different levels of redundancy. In a further aspect, rules can relate to boundary conditions related to determinations of geographic redundancy. As an example, in large sets of radios, a boundary condition can limit determining redundancy to radios within a predetermined distance, selected region, selected status, etc. Rule component **120** can also receive rule updates to facilitate changes to rule sets that affect the determination of levels of geographic redundancy.

System **100** can further include geographic redundancy component **130** to facilitate determination of a level of geographic redundancy. Geographic redundancy component **130** can be communicatively coupled to RGI component **110** to facilitate receiving geographic information for a set of radios associated with a wireless network. Geographic redundancy component **130** can also be communicatively coupled to rule component **120** to facilitate receiving at least a rule associated with determining a level of geographic redundancy for the set of radios associated with the wireless network.

In an aspect, geographic redundancy component **130** can determine a level of geographic redundancy. A level of geographic redundancy can be binary, e.g., redundant or not redundant, or can relate to a plurality of levels of redundancy, e.g., highly redundant, moderately redundant,

slightly redundant, not redundant, etc. As an example, a determination of ‘highly redundant’ can be associated with not using the radio in location determination, while a determination of ‘slightly redundant’ can be associated with using the radio for location determination only when it is also a well calibrated radio. Additionally, a level of geographic redundancy can be employed to rank or order radios, or as a factor in other ranking or ordering techniques, etc. As an example, the higher the level of geographic redundancy, the lower the radio can be ranked for selection in determining location information. Continuing the example, other factors, such as calibration confidence, etc., can be associated with increasing the ranking of the radio for use in determining location information.

In a further aspect, the determined level of geographic redundancy can be employed to update radio information. Wherein the geometry of wireless network radios is known, the geographically redundant radios can be determined and the information can then be associated with the radios such that the information is predetermined with respect to determining location information based on timing information relating to the radios of the wireless network. This can facilitate selection of radios that meet predetermined ranking criteria associated with a predetermined level of geographic redundancy. As an example, a UE can be associated with a set of radio pairs facilitating a TFL information determination, the set including at least a pair of radios with a predetermined level of geometrically redundancy. In light of the predetermined level of redundancy, the exemplary TFL information determination can be based on radio pairs of the set of radios with lower levels of geometric redundancy to increase an overall level of confidence in the determined location information.

In a further aspect, geographic redundancy component **130** can determine levels of geometric redundancy for some, all, or no radios in a set of radios associated with RGI received by way of RGI component **110**. In an embodiment, the selection of a subset of radios from a set of radios for which RGI is available can be a form of bounding. Bounding can allow, for example, predetermination of a level of geometric redundancy for radios within a predetermined distance from each other, etc. This can significantly reduce the number of determinations that are made in large sets of radios, e.g., determinations of radio sets for regions of a wireless network, etc.

FIG. 2 is a depiction of a system **200** that can facilitate determining a level of geographic redundancy in accordance with aspects of the subject disclosure. System **200** can include RGI component **210** that can facilitate access to geographic information related to radios of a wireless network. RGI component **210** can enable, in some embodiments, interaction with GIS information.

RGI component **210** can be communicatively coupled to radio information store **212**. Radio information store **212** can be a store of information relating to a radio of a wireless network of radios. In some embodiments, radio information store **212** can comprise part of a carrier’s GIS. Radio information store **212** can warehouse information about radios including geographic information, levels of geographic redundancy, radio identification, radio timing values, radio calibration information, or nearly any other type of information relative to a radio of a wireless network. Radio information store **212** can receive updates to the radio information as a radio update, e.g., information relating to a new radio, removal of a radio, updating a radio information, etc.

System **200** can further include rule component **220** that can facilitate access to one or more rules associated with determining a level of geographic redundancy. Rule component **220** can include rule criteria component **222**. In an aspect, rules can relate to definition of, or characterization of geographic information as it relates to geographic redundancy. As an example, a rule can include one or more predetermined threshold values that correspond to different levels of redundancy. Criteria for rules can be received by way of rule criteria component **222**. As an example, an equation for determining a level of geographic redundancy can be received by way of rule criteria component **222**. As another example, a rule for determining a level of geographic redundancy can be based on predetermined threshold values that can be received by way of rule criteria component **222**.

Rule component **220** can further comprise boundary condition component **224**. Boundary condition component **224** can receive information relating to a bounding condition. Rules can include boundary conditions related to determinations of geographic redundancy. As an example, in large sets of radios, a boundary condition can limit determining redundancy to radios within a predetermined distance, selected region, selected status, etc. Rule component **220** can also receive rule updates to facilitate changes to rule sets that affect the determination of levels of geographic redundancy.

System **200** can further include geographic redundancy component **230** to facilitate determination of a level of geographic redundancy. Geographic redundancy component **230** can be communicatively coupled to RGI component **210** to facilitate receiving geographic information for a set of radios associated with a wireless network. Geographic redundancy component **230** can also be communicatively coupled to rule component **220** to facilitate receiving at least a rule associated with determining a level of geographic redundancy for the set of radios associated with the wireless network.

In an aspect, geographic redundancy component **230** can determine a level of geographic redundancy. Determinations of a level of geometric redundancy can be made by determination component **232** and can be based on a rule received by way of rule component **220** and RGI by way of RGI component **210**. A level of geographic redundancy can be employed to rank or order radios, or as a factor in other ranking or ordering techniques, etc.

In a further aspect, a determined level of geographic redundancy can be employed to update radio information. Designation component **234** can facilitate designation a level of geometric redundancy by facilitating access to information relating to the determined level of redundancy. Wherein the geometry of wireless network radios is known, geographically redundant radios can be determined and the information can then be associated with the radios such that the information is predetermined with respect to determining location information based on timing information relating to the radios of the wireless network. Thus, predetermined levels of geometric redundancy can be determined, at determination component **232**, and information about said levels can be received, by way of designation component **234**, for storage at radio information store **212** by way of RGI component **210**. This can facilitate selection of radios that meet predetermined ranking criteria associated with a predetermined level of geographic redundancy.

In another aspect, geographic redundancy component **230** can determine levels of geometric redundancy for some, all, or no radios in a set of radios associated with RGI received

by way of RGI component **210**. In an embodiment, the selection of a subset of radios from a set of radios for which RGI is available can be a form of bounding. Bounding can allow, for example, predetermination of a level of geometric redundancy for radios within a predetermined distance from each other, etc. This can reduce the number of determinations that are made in large sets of radios.

Moreover, detection component **236** can determine if there have been changes to information relating to a set of radios, e.g., by communicative coupling with radio information store **212** by way of RGI component **210**. Changes can include addition of a new radio, e.g., a new radio being installed in a wireless network, etc., deletion of a radio, or updates to an existing radio. Where changes in radios occur, the RGI and geometric redundancy can also be impacted. As such, a detected change can allow for an automatic redetermination of geometric redundancy information. Further, the automatic redetermination can be for part, all, or none of a radio set based on which radios are detected as having changed. As an example, where a single radio is added, this can influence a relative few determined levels of geometric redundancy. As another example, where a new region of wireless network is added, e.g., by way of acquiring another wireless carrier, etc., it can be more prudent to re-determine all or most of the geometric redundancy determinations.

FIG. **3** illustrates a system **300** that facilitates determining a level of geographic redundancy for a timed fingerprint locating enabled system in accordance with aspects of the subject disclosure. System **300** can include RGI component **310** that can facilitate access to geographic information related to radios of a wireless network. In certain embodiments, geographic information for wireless network radios can be in the form of GIS information. RGI component **310** can enable, in some embodiments, interaction with GIS information. In an aspect, RGI component **310** can be communicatively coupled to radio information store **312**. Radio information store **312** can be a store of information relating to a radio of a wireless network of radios. In some embodiments, radio information store **312** can comprise part of a carrier's GIS. Radio information store **312** can warehouse information about radios including geographic information, levels of geographic redundancy, or nearly any other type of information relative to a radio of a wireless network. Radio information store **312** can receive updates to the radio information as a radio update.

System **300** can further include rule component **320** that can facilitate access to one or more rules associated with determining a level of geographic redundancy. In an aspect, rules can relate to definition of, or characterization of geographic information as it relates to geographic redundancy. In a further aspect, rules can relate to boundary conditions related to determinations of geographic redundancy. Rule component **320** can also receive rule updates to facilitate changes to rule sets that affect the determination of levels of geographic redundancy.

System **300** can further include geographic redundancy component **330** to facilitate determination of a level of geographic redundancy. Geographic redundancy component **330** can be communicatively coupled to RGI component **310** to facilitate receiving geographic information for a set of radios associated with a wireless network. Geographic redundancy component **330** can also be communicatively coupled to rule component **320** to facilitate receiving at least a rule associated with determining a level of geographic redundancy for the set of radios associated with the wireless network.

In an aspect, geographic redundancy component **330** can determine a level of geographic redundancy. A level of geographic redundancy can be employed to rank or order radios, or as a factor in other ranking or ordering techniques, etc. In an aspect, the determined level of geographic redundancy can be employed to update radio information. This can facilitate selection of radios that meet predetermined ranking criteria associated with a predetermined level of geographic redundancy.

In another aspect, geographic redundancy component **330** can determine levels of geometric redundancy for some, all, or no radios in a set of radios associated with RGI received by way of RGI component **310**. In an embodiment, the selection of a subset of radios from a set of radios for which RGI is available can be a form of bounding. Bounding can allow, for example, predetermination of a level of geometric redundancy for radios within a predetermined distance from each other, etc. This can significantly reduce the number of determinations that are made in large sets of radios, e.g., determinations of radio sets for regions of a wireless network, etc.

System **300** can further comprise timed fingerprint location (TFL) component **340**. TFL component **340** can be communicatively coupled to radio information store **312** to receive predetermined geographic redundancy information stored thereon by way of geographic redundancy component **330**. As such, geographic redundancy information can be employed in selection of radio pairs employed in determining location information by way of a TFL system, e.g., NELOS. As an example, a UE can be associated with a set of radio pairs facilitating a TFL information determination, the set including at least a pair of radios with a predetermined level of geometrically redundancy. In light of the predetermined level of redundancy, the exemplary TFL information determination can be based on radio pairs of the set of radios with lower levels of geometric redundancy to increase an overall level of confidence in the determined location information.

FIG. **4** is an illustration of an exemplary system **400** having a level of geographic redundancy in accordance with aspects of the subject disclosure. System **400** can include a set of radios, the set including radios **410**, **420**, **430**, and **440**. The set of radios can comprise part of a wireless network. Timing signals associated with radio links between the radios of the set and UEs can facilitate determination of location information, e.g., a NELOS or TFL-enabled wireless network. The distance between radio **410** and radio **420** can be distance **460**. Similarly, the distance between radio **410** and radio **430** can be distance **450**. Likewise, the distance between radio **420** and radio **430** can be distance **470**.

In an aspect, UEs can employ radio pairs, such as the pair **410/420** and the pair **410/430**, for determination of location information, such as by way of TFL techniques. However, use of radio pairs **410/420** and **410/430** can result in a degree of error where radios **420** and **430** can have a level of geometric redundancy. As an example, where radio **420** and radio **430** are close geometrically with respect to radio **410**, the resulting TFL lookups in a TFL-enabled system, can return similar sets of bins that can result in an inaccurate union between the returned sets of bins and a widening effect on the probable location of a UE. By predetermining that radio **420** and radio **430** have a level of geometric redundancy with regard to radio **410**, the selection of radio pairs for TFL lookup using both of the redundant radios can be deprioritized, for example, in favor of using just one of the geometrically redundant radios.

In an exemplary embodiment, the level of geometric redundancy can be binary. The exemplary embodiment can further be based on distance **450** and **460** being within, for example, 10% of each other. Then, where distances **450** and **460** are within 10% of each other, the distance **470** can be further evaluated to determine redundancy. As an example, where distance **470** is less than 10% of the average of distances **450** and **460**, then radios **420** and **430** can be determined to be geometrically redundant with regard to radio **410**.

In another exemplary embodiment, the same exemplary threshold values and rules can be employed and be applied with regard to radios **440**, **420**, and **430**. As such, where distances **490** and **480** are within 10% of each other, then distance **470** can be evaluated to determine geometric redundancy. Thus, where distance **470** is less than 10% of the average of distances **480** and **490**, radios **420** and **430** can be geometrically redundant with regard to radio **440**. As can be observed, where radio **410** is much further away from radios **420** and **430** than radio **440**, for the exemplary criteria, radios **420** and **430** are more likely to be geometrically redundant with regard to radio **410** than for radio **440**.

The level of geometric redundancy information can be stored for the several radios, e.g., by way of radio information store, **212** or **312**, etc. This predetermined geometric redundancy information can then facilitate selection of radio pairs that can be less affected by geometric redundancy when determining location information based on radio timing information.

It will be noted that the exemplary 10% value is arbitrarily selected to illustrate an example of the disclosed subject matter and that the disclosure is not so limited to that value or those near it. As further examples, the first determination of the difference between the long legs of the radio pair triangle, e.g., distances **460** and **450**, etc., can be subject to any threshold value, such as, but not limited to, 1%, 10%, 50%, 90%, 100 meters, 2 chip, 5 msec, etc. Similarly, the determination of a level of geometric redundancy with regard to the short leg of the radio pair triangle, e.g., distance **470**, etc., can be subject to any equation and/or threshold value, such as, but not limited to, distance **470** is greater than 1 meter but less than 100 meters; distance **470** is less than 2% of the sum of distances **460** and **450**; distance **470** is less than 22% of the average of distances **490** and **480**, etc.

FIG. **5** is an illustration of an exemplary system **500** having a level of geographic redundancy in accordance with aspects of the subject disclosure. System **500** can include a set of radios, the set including radios **510**, **520**, **530**, and **570**. The set of radios can comprise part of a wireless network. Timing signals associated with radio links between the radios of the set and a UE **502** can facilitate determination of location information, e.g., a NELOS or TFL-enabled wireless network.

Determination of a level of geometric redundancy can occur as disclosed herein. This predetermined level of redundancy can be stored and received to facilitate selection of radio pairs for determination of location information. Determination of location information can be by way of TFL-enabled techniques, e.g., NELOS. As an example, radios **520** and **530** can be predetermined to be geometrically redundant with regard to radio **510** and not geometrically redundant with regard to radio **570**. As such, selection of radio pairs for location determination can be considerate of the predetermined geometric redundancy.

Continuing the example, if radio pair **510/520** and radio pair **510/530** are selected for determining location information by way of a TFL technique, lookup of the timing values

of the pairs can result in exemplary probable bin locations defined by curved lines **540** and **550** respectively. As will be noted in the illustration of system **500**, bin locations for **540** and **550** are highly similar and a union of the two sets of bin locations could result in a probable location between area **560** and **562** along curves **540** or **550**. This result can be less accurate, due to employing geometrically redundant radio pairs, than a TFL lookups with non-redundant radio pairs.

As an example of selecting non-redundant radio pairs, curved line **580** can represent the set of returned bin grid locations for an exemplary TFL lookup for radio pair **570/530**. As such, for determining location information for UE **502**, it can be determined that employing radio pair **510/520** in conjunction with radio pair **510/530** is lower priority because of a predetermined geometric redundancy. Therefore, either radio pair **510/520** or radio pair **510/530** can be employed with another non-redundant radio pair, such as radio pair **570/530**. This can result in determining the probable location to be at the union of either curve **540** or **550** with curve **580**. Given that the curves are much less similar, the union can be more distinct and can have less ambiguity as to the probable location of UE **502** at **582**, rather than between **560** and **562** as discussed earlier in the example.

In a further aspect, treatment of radio pairs demonstrating a level of geometric redundancy can include exclusion of one of the redundant radio pairs as disclosed in the above example. Another treatment option can include exclusion of both pairs in favor of purely non-redundant radios. A further treatment can include 'averaging' the redundant radio pairs, e.g., an 'average' of radio **520** and radio **530** with regard to radio **510** can return an average of the curves **540** and **550**. Yet another treatment can include selecting one or more of the redundant radios based on another criteria in light of the radios being redundant, for example, where the radios are redundant but have the most recent calibration they can still be selected over other non-redundant but poorly calibrated radios, though the selection techniques are beyond the scope of the present disclosure.

In view of the example system(s) described above, example method(s) that can be implemented in accordance with the disclosed subject matter can be better appreciated with reference to flowcharts in FIG. **6**-FIG. **8**. For purposes of simplicity of explanation, example methods disclosed herein are presented and described as a series of acts; however, it is to be understood and appreciated that the claimed subject matter is not limited by the order of acts, as some acts may occur in different orders and/or concurrently with other acts from that shown and described herein. For example, one or more example methods disclosed herein could alternatively be represented as a series of interrelated states or events, such as in a state diagram. Moreover, interaction diagram(s) may represent methods in accordance with the disclosed subject matter when disparate entities enact disparate portions of the methods. Furthermore, not all illustrated acts may be required to implement a described example method in accordance with the subject specification. Further yet, two or more of the disclosed example methods can be implemented in combination with each other, to accomplish one or more aspects herein described. It should be further appreciated that the example methods disclosed throughout the subject specification are capable of being stored on an article of manufacture (e.g., a computer-readable medium) to allow transporting and transferring such methods to computers for execution, and thus implementation, by a processor or for storage in a memory.

11

FIG. 6 illustrates aspects of a method 600 facilitating determining a level of geographic redundancy in accordance with aspects of the subject disclosure. At 610, radio geographic information (RGI) can be received. RGI can be related to radios of a wireless network. Whereas wireless network carriers know the location at which radios of a wireless network are placed as part of deploying the physical resources of a wireless network, RGI can include the geographic information of radios in the wireless network. In certain embodiments, geographic information for wireless network radios can be in the form of geographic information system (GIS) information. A geographic information system can be a system designed to handle types of geographical data.

At 620, a level of geographic redundancy can be determined based on the RGI received at 610. The determination of the level of geographic redundancy can be based on a rule. In an aspect, rules can relate to definition of, or characterization of geographic information as it relates to geographic redundancy. As an example, a rule can include a predetermined threshold value that corresponds to different levels of redundancy. In a further aspect, rules can relate to boundary conditions related to determinations of geographic redundancy. As an example, in large sets of radios, a boundary condition can limit determining redundancy to radios within a predetermined distance, selected region, selected status, etc.

A level of geographic redundancy can be binary or can relate to a plurality of levels of redundancy. Additionally, a level of geographic redundancy can be employed to rank or order radios, or as a factor in other ranking or ordering techniques, etc. In a further aspect, levels of geometric redundancy can be determined for some, all, or no radios in a set of radios associated with received RGI. In an aspect, the selection of a subset of radios from a set of radios for which RGI is available can be a form of bounding. Bounding can allow, for example, predetermination of a level of geometric redundancy for radios within a predetermined distance from each other, etc. This can significantly reduce the number of determinations that are made in large sets of radios, e.g., determinations of radio sets for regions of a wireless network, etc.

At 630, radio information can be updated based on the determined level of geographic redundancy. At this point, method 600 can end. A determined level of geographic redundancy can be employed to update radio information. This can facilitate selection of radios that meet predetermined ranking criteria associated with a predetermined level of geographic redundancy. As an example, a UE can be associated with a set of radio pairs facilitating a TFL information determination, the set including at least a pair of radios with a predetermined level of geometric redundancy. In light of the predetermined level of redundancy, the exemplary TFL information determination can be based on radio pairs of the set of radios with lower levels of geometric redundancy to increase an overall level of confidence in the determined location information.

FIG. 7 illustrates a method 700 that facilitates determining a level of geographic redundancy in accordance with aspects of the subject disclosure. At 710, radio information can be received. Radio information can be for a set of radios (RS) including a first radio (RA) a second radio (RB) and a third radio (RC) of a wireless network. At 720, RGI can be determined from the radio information received at 710. RGI can be related to radios of a wireless network. RGI can include the geographic information of radios in the wireless network.

12

At 730, the difference between the distance from the first to the third radio and the distance from the second to the third radio can be determined, e.g., the difference between RA to RC (AC) and RB to RC (BC). In an aspect, this can be written in equation form as $|AC-BC|$. At 740, a distance between the first and second radio can be determined, e.g., the distance RA to RB (AB).

At 750, a level of geographic redundancy can be determined based on the distances determined at 730 and 740, e.g., AC, BC, and AB, etc. The determination of the level of geographic redundancy can be based on a rule. In an aspect, rules can relate to definition of, or characterization of geographic information as it relates to geographic redundancy. As an example, a rule can include a predetermined threshold value that corresponds to different levels of redundancy. In a further aspect, rules can relate to boundary conditions related to determinations of geographic redundancy. As an example, in large sets of radios, a boundary condition can limit determining redundancy to radios within a predetermined distance, selected region, selected status, etc.

A level of geographic redundancy can be binary or can relate to a plurality of levels of redundancy. Additionally, a level of geographic redundancy can be employed to rank or order radios, or as a factor in other ranking or ordering techniques, etc. In a further aspect, levels of geometric redundancy can be determined for some, all, or no radios in a set of radios associated with received RGI. In an aspect, the selection of a subset of radios from a set of radios for which RGI is available can be a form of bounding. Bounding can allow, for example, predetermination of a level of geometric redundancy for radios within a predetermined distance from each other, etc. This can significantly reduce the number of determinations that are made in large sets of radios, e.g., determinations of radio sets for regions of a wireless network, etc.

In an embodiment, the determination of a level of geographic redundancy can be based on a two-part determination. The first part of the determination can be based on the distance difference determined at 730. As a non-limiting example, a rule for the first part of the determination can be that to proceed to the second part of the determination the difference between the distance from the first to the third radio and the distance from the second to the third radio must be within 10%. The first part of the exemplary determination, in equation form, can be

$$\begin{cases} |AC - BC| \leq 0.1(AC) \\ |AC - BC| \leq 0.1(BC) \end{cases}$$

The second part of the determination for the particular embodiment can be based on a comparison of the distance between the first and second radios and the determined distance from the first part of the determination. As a non-limiting example of the second part of the determination, inclusive of the results of the first part of the determination, in equation form, can be that geometric redundancy is present if,

$$[2(AB)/((AC) + (BC))] \leq 0.1.$$

It will be noted that the exemplary threshold values and exemplary equations are merely for illustration and are

non-limiting. It will further be noted that other equations and threshold values can be employed without departing from the scope of the present subject matter. Moreover, the particular example of a two-part determination is non-limiting and other examples are not presented simply for clarity and brevity, though all such other techniques for determining a level of geographic redundancy are to be considered within the scope of the presently disclosed subject matter.

At **760**, radio information can be updated based on the determined level of geographic redundancy. At this point, method **700** can end. A determined level of geographic redundancy can be employed to update radio information. This can facilitate selection of radios that meet predetermined ranking criteria associated with a predetermined level of geographic redundancy. As an example, a UE can be associated with a set of radio pairs facilitating a TFL information determination, the set including at least a pair of radios with a predetermined level of geometrically redundancy. In light of the predetermined level of redundancy, the exemplary TFL information determination can be based on radio pairs of the set of radios with lower levels of geometric redundancy to increase an overall level of confidence in the determined location information.

FIG. **8** illustrates a method **800** that facilitates determining a level of geographic redundancy in accordance with aspects of the subject disclosure. At **810**, radio information can be received. Radio information can be for a set of radios (RS) including a first radio (RA) a second radio (RB) and a third radio (RC) of a wireless network. At **820**, RGI can be determined from the radio information received at **810**. RGI can be related to radios of a wireless network, e.g., RS. RGI can include the geographic information of radios in the wireless network.

At **830**, it can be determined if the difference between the distance from the first to the third radio and the distance from the second to the third radio is within a predetermined range of values, e.g., the difference between distance AC can be less than a predetermined percentage of the distance BC. If the determination at **830** is affirmative, at **840**, it can be determined if a distance between the first and second radio, e.g., distance AB, is less than a weighted average of the distance from the first to the third radio and the distance from the second to the third radio, e.g.,

$$AB < \frac{(AC + BC)}{20}.$$

Where **840** is determined in the affirmative, a level of geographic redundancy is indicated and method **800** proceeds to **850**.

At **850**, radio information can be updated based on the determined level of geographic redundancy. At this point, method **800** can end. A determined level of geographic redundancy can be employed to update radio information. This can facilitate selection of radios that meet predetermined ranking criteria associated with a predetermined level of geographic redundancy.

It will be noted that the exemplary threshold values and exemplary equations are merely for illustration and are non-limiting. It will further be noted that other equations and threshold values can be employed without departing from the scope of the present subject matter.

FIG. **9** presents an example embodiment **900** of a mobile network platform **910** that can implement and exploit one or

more aspects of the disclosed subject matter described herein. Generally, wireless network platform **910** can include components, e.g., nodes, gateways, interfaces, servers, or disparate platforms, that facilitate both packet-switched (PS) (e.g., internet protocol (IP), frame relay, asynchronous transfer mode (ATM)) and circuit-switched (CS) traffic (e.g., voice and data), as well as control generation for networked wireless telecommunication. As a non-limiting example, wireless network platform **910** can be included in telecommunications carrier networks, and can be considered carrier-side components as discussed elsewhere herein. Mobile network platform **910** includes CS gateway node(s) **912** which can interface CS traffic received from legacy networks like telephony network(s) **940** (e.g., public switched telephone network (PSTN), or public land mobile network (PLMN)) or a signaling system #7 (SS7) network **970**. Circuit switched gateway node(s) **912** can authorize and authenticate traffic (e.g., voice) arising from such networks. Additionally, CS gateway node(s) **912** can access mobility, or roaming, data generated through SS7 network **970**; for instance, mobility data stored in a visited location register (VLR), which can reside in memory **930**. Moreover, CS gateway node(s) **912** interfaces CS-based traffic and signaling and PS gateway node(s) **918**. As an example, in a 3GPP UMTS network, CS gateway node(s) **912** can be realized at least in part in gateway GPRS support node(s) (GGSN). It should be appreciated that functionality and specific operation of CS gateway node(s) **912**, PS gateway node(s) **918**, and serving node(s) **916**, is provided and dictated by radio technology(ies) utilized by mobile network platform **910** for telecommunication.

In addition to receiving and processing CS-switched traffic and signaling, PS gateway node(s) **918** can authorize and authenticate PS-based data sessions with served mobile devices. Data sessions can include traffic, or content(s), exchanged with networks external to the wireless network platform **910**, like wide area network(s) (WANs) **950**, enterprise network(s) **970**, and service network(s) **980**, which can be embodied in local area network(s) (LANs), can also be interfaced with mobile network platform **910** through PS gateway node(s) **918**. It is to be noted that WANs **950** and enterprise network(s) **960** can embody, at least in part, a service network(s) like IP multimedia subsystem (IMS). Based on radio technology layer(s) available in technology resource(s) **917**, packet-switched gateway node(s) **918** can generate packet data protocol contexts when a data session is established; other data structures that facilitate routing of packetized data also can be generated. To that end, in an aspect, PS gateway node(s) **918** can include a tunnel interface (e.g., tunnel termination gateway (TTG) in 3GPP UMTS network(s) (not shown)) which can facilitate packetized communication with disparate wireless network(s), such as Wi-Fi networks.

In embodiment **900**, wireless network platform **910** also includes serving node(s) **916** that, based upon available radio technology layer(s) within technology resource(s) **917**, convey the various packetized flows of data streams received through PS gateway node(s) **918**. It is to be noted that for technology resource(s) **917** that rely primarily on CS communication, server node(s) can deliver traffic without reliance on PS gateway node(s) **918**; for example, server node(s) can embody at least in part a mobile switching center. As an example, in a 3GPP UMTS network, serving node(s) **916** can be embodied in serving GPRS support node(s) (SGSN).

For radio technologies that exploit packetized communication, server(s) **914** in wireless network platform **910** can

execute numerous applications that can generate multiple disparate packetized data streams or flows, and manage (e.g., schedule, queue, format . . .) such flows. Such application(s) can include add-on features to standard services (for example, provisioning, billing, customer support . . .) provided by wireless network platform **910**. Data streams (e.g., content(s) that are part of a voice call or data session) can be conveyed to PS gateway node(s) **918** for authorization/authentication and initiation of a data session, and to serving node(s) **916** for communication thereafter. In addition to application server, server(s) **914** can include utility server(s), a utility server can include a provisioning server, an operations and maintenance server, a security server that can implement at least in part a certificate authority and firewalls as well as other security mechanisms, and the like. In an aspect, security server(s) secure communication served through wireless network platform **910** to ensure network's operation and data integrity in addition to authorization and authentication procedures that CS gateway node(s) **912** and PS gateway node(s) **918** can enact. Moreover, provisioning server(s) can provision services from external network(s) like networks operated by a disparate service provider; for instance, WAN **950** or Global Positioning System (GPS) network(s) (not shown). Provisioning server(s) can also provision coverage through networks associated to wireless network platform **910** (e.g., deployed and operated by the same service provider), such as femto-cell network(s) (not shown) that enhance wireless service coverage within indoor confined spaces and offload RAN resources in order to enhance subscriber service experience within a home or business environment by way of UE **975**.

It is to be noted that server(s) **914** can include one or more processors configured to confer at least in part the functionality of macro network platform **910**. To that end, the one or more processor can execute code instructions stored in memory **930**, for example. It is should be appreciated that server(s) **914** can include a content manager **915**, which operates in substantially the same manner as described hereinbefore.

In example embodiment **900**, memory **930** can store information related to operation of wireless network platform **910**. Other operational information can include provisioning information of mobile devices served through wireless platform network **910**, subscriber databases; application intelligence, pricing schemes, e.g., promotional rates, flat-rate programs, couponing campaigns; technical specification(s) consistent with telecommunication protocols for operation of disparate radio, or wireless, technology layers; and so forth. Memory **930** can also store information from at least one of telephony network(s) **940**, WAN **950**, enterprise network(s) **960**, or SS7 network **970**. In an aspect, memory **930** can be, for example, accessed as part of a data store component or as a remotely connected memory store.

In order to provide a context for the various aspects of the disclosed subject matter, FIG. **10**, and the following discussion, are intended to provide a brief, general description of a suitable environment in which the various aspects of the disclosed subject matter can be implemented. While the subject matter has been described above in the general context of computer-executable instructions of a computer program that runs on a computer and/or computers, those skilled in the art will recognize that the disclosed subject matter also can be implemented in combination with other program modules. Generally, program modules include rou-

tines, programs, components, data structures, etc., that perform particular tasks and/or implement particular abstract data types.

In the subject specification, terms such as “store,” “storage,” “data store,” data storage,” “database,” and substantially any other information storage component relevant to operation and functionality of a component, refer to “memory components,” or entities embodied in a “memory” or components comprising the memory. It will be appreciated that the memory components described herein can be either volatile memory or nonvolatile memory, or can include both volatile and nonvolatile memory, by way of illustration, and not limitation, volatile memory **1020** (see below), non-volatile memory **1022** (see below), disk storage **1024** (see below), and memory storage **1046** (see below). Further, nonvolatile memory can be included in read only memory (ROM), programmable ROM (PROM), electrically programmable ROM (EPROM), electrically erasable ROM (EEPROM), or flash memory. Volatile memory can include random access memory (RAM), which acts as external cache memory. By way of illustration and not limitation, RAM is available in many forms such as synchronous RAM (SRAM), dynamic RAM (DRAM), synchronous DRAM (SDRAM), double data rate SDRAM (DDR SDRAM), enhanced SDRAM (ESDRAM), Synchlink DRAM (SLDRAM), and direct Rambus RAM (DRRAM). Additionally, the disclosed memory components of systems or methods herein are intended to comprise, without being limited to comprising, these and any other suitable types of memory.

Moreover, it will be noted that the disclosed subject matter can be practiced with other computer system configurations, including single-processor or multiprocessor computer systems, mini-computing devices, mainframe computers, as well as personal computers, hand-held computing devices (e.g., PDA, phone, watch, tablet computers, netbook computers, . . .), microprocessor-based or programmable consumer or industrial electronics, and the like. The illustrated aspects can also be practiced in distributed computing environments where tasks are performed by remote processing devices that are linked through a communications network; however, some if not all aspects of the subject disclosure can be practiced on stand-alone computers. In a distributed computing environment, program modules can be located in both local and remote memory storage devices.

FIG. **10** illustrates a block diagram of a computing system **1000** operable to execute the disclosed systems and methods in accordance with an embodiment. Computer **1012**, which can be, for example, part of the hardware of a geographical redundancy component e.g., component **130**, **23**, **330**, etc., TFL component, e.g., **340**, etc., a user equipment, e.g., UE **502**, etc., includes a processing unit **1014**, a system memory **1016**, and a system bus **1018**. System bus **1018** couples system components including, but not limited to, system memory **1016** to processing unit **1014**. Processing unit **1014** can be any of various available processors. Dual microprocessors and other multiprocessor architectures also can be employed as processing unit **1014**.

System bus **1018** can be any of several types of bus structure(s) including a memory bus or a memory controller, a peripheral bus or an external bus, and/or a local bus using any variety of available bus architectures including, but not limited to, Industrial Standard Architecture (ISA), Micro-Channel Architecture (MSA), Extended ISA (EISA), Intelligent Drive Electronics, VESA Local Bus (VLB), Peripheral Component Interconnect (PCI), Card Bus, Universal Serial Bus (USB), Advanced Graphics Port (AGP), Personal

Computer Memory Card International Association bus (PC-MCIA), Firewire (IEEE 1194), and Small Computer Systems Interface (SCSI).

System memory **1016** can include volatile memory **1020** and nonvolatile memory **1022**. A basic input/output system (BIOS), containing routines to transfer information between elements within computer **1012**, such as during start-up, can be stored in nonvolatile memory **1022**. By way of illustration, and not limitation, nonvolatile memory **1022** can include ROM, PROM, EPROM, EEPROM, or flash memory. Volatile memory **1020** includes RAM, which acts as external cache memory. By way of illustration and not limitation, RAM is available in many forms such as SRAM, dynamic RAM (DRAM), synchronous DRAM (SDRAM), double data rate SDRAM (DDR SDRAM), enhanced SDRAM (ESDRAM), Synchlink DRAM (SLDRAM), Rambus direct RAM (RDRAM), direct Rambus dynamic RAM (DRDRAM), and Rambus dynamic RAM (RDRAM).

Computer **1012** can also include removable/non-removable, volatile/non-volatile computer storage media. FIG. **10** illustrates, for example, disk storage **1024**. Disk storage **1024** includes, but is not limited to, devices like a magnetic disk drive, floppy disk drive, tape drive, flash memory card, or memory stick. In addition, disk storage **1024** can include storage media separately or in combination with other storage media including, but not limited to, an optical disk drive such as a compact disk ROM device (CD-ROM), CD recordable drive (CD-R Drive), CD rewritable drive (CD-RW Drive) or a digital versatile disk ROM drive (DVD-ROM). To facilitate connection of the disk storage devices **1024** to system bus **1018**, a removable or non-removable interface is typically used, such as interface **1026**.

Computing devices typically include a variety of media, which can include computer-readable storage media or communications media, which two terms are used herein differently from one another as follows.

Computer-readable storage media can be any available storage media that can be accessed by the computer and includes both volatile and nonvolatile media, removable and non-removable media. By way of example, and not limitation, computer-readable storage media can be implemented in connection with any method or technology for storage of information such as computer-readable instructions, program modules, structured data, or unstructured data. Computer-readable storage media can include, but are not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disk (DVD) or other optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or other tangible and/or non-transitory media which can be used to store desired information. Computer-readable storage media can be accessed by one or more local or remote computing devices, e.g., via access requests, queries or other data retrieval protocols, for a variety of operations with respect to the information stored by the medium.

Communications media typically embody computer-readable instructions, data structures, program modules or other structured or unstructured data in a data signal such as a modulated data signal, e.g., a carrier wave or other transport mechanism, and includes any information delivery or transport media. The term “modulated data signal” or signals refers to a signal that has one or more of its characteristics set or changed in such a manner as to encode information in one or more signals. By way of example, and not limitation, communication media include wired media, such as a wired network or direct-wired connection, and wireless media such as acoustic, RF, infrared and other wireless media.

It can be noted that FIG. **10** describes software that acts as an intermediary between users and computer resources described in suitable operating environment **1000**. Such software includes an operating system **1028**. Operating system **1028**, which can be stored on disk storage **1024**, acts to control and allocate resources of computer system **1012**. System applications **1030** take advantage of the management of resources by operating system **1028** through program modules **1032** and program data **1034** stored either in system memory **1016** or on disk storage **1024**. It is to be noted that the disclosed subject matter can be implemented with various operating systems or combinations of operating systems.

A user can enter commands or information into computer **1012** through input device(s) **1036**. Input devices **1036** include, but are not limited to, a pointing device such as a mouse, trackball, stylus, touch pad, keyboard, microphone, joystick, game pad, satellite dish, scanner, TV tuner card, digital camera, digital video camera, web camera, cell phone, smartphone, tablet computer, etc. These and other input devices connect to processing unit **1014** through system bus **1018** by way of interface port(s) **1038**. Interface port(s) **1038** include, for example, a serial port, a parallel port, a game port, a universal serial bus (USB), an infrared port, a Bluetooth port, an IP port, or a logical port associated with a wireless service, etc. Output device(s) **1040** use some of the same type of ports as input device(s) **1036**.

Thus, for example, a USB port can be used to provide input to computer **1012** and to output information from computer **1012** to an output device **1040**. Output adapter **1042** is provided to illustrate that there are some output devices **1040** like monitors, speakers, and printers, among other output devices **1040**, which use special adapters. Output adapters **1042** include, by way of illustration and not limitation, video and sound cards that provide means of connection between output device **1040** and system bus **1018**. It should be noted that other devices and/or systems of devices provide both input and output capabilities such as remote computer(s) **1044**.

Computer **1012** can operate in a networked environment using logical connections to one or more remote computers, such as remote computer(s) **1044**. Remote computer(s) **1044** can be a personal computer, a server, a router, a network PC, cloud storage, cloud service, a workstation, a microprocessor based appliance, a peer device, or other common network node and the like, and typically includes many or all of the elements described relative to computer **1012**.

For purposes of brevity, only a memory storage device **1046** is illustrated with remote computer(s) **1044**. Remote computer(s) **1044** is logically connected to computer **1012** through a network interface **1048** and then physically connected by way of communication connection **1050**. Network interface **1048** encompasses wire and/or wireless communication networks such as local-area networks (LAN) and wide-area networks (WAN). LAN technologies include Fiber Distributed Data Interface (FDDI), Copper Distributed Data Interface (CDDI), Ethernet, Token Ring and the like. WAN technologies include, but are not limited to, point-to-point links, circuit-switching networks like Integrated Services Digital Networks (ISDN) and variations thereon, packet switching networks, and Digital Subscriber Lines (DSL). As noted below, wireless technologies may be used in addition to or in place of the foregoing.

Communication connection(s) **1050** refer(s) to hardware/software employed to connect network interface **1048** to bus **1018**. While communication connection **1050** is shown for illustrative clarity inside computer **1012**, it can also be

external to computer 1012. The hardware/software for connection to network interface 1048 can include, for example, internal and external technologies such as modems, including regular telephone grade modems, cable modems and DSL modems, ISDN adapters, and Ethernet cards.

The above description of illustrated embodiments of the subject disclosure, including what is described in the Abstract, is not intended to be exhaustive or to limit the disclosed embodiments to the precise forms disclosed. While specific embodiments and examples are described herein for illustrative purposes, various modifications are possible that are considered within the scope of such embodiments and examples, as those skilled in the relevant art can recognize.

In this regard, while the disclosed subject matter has been described in connection with various embodiments and corresponding Figures, where applicable, it is to be understood that other similar embodiments can be used or modifications and additions can be made to the described embodiments for performing the same, similar, alternative, or substitute function of the disclosed subject matter without deviating therefrom. Therefore, the disclosed subject matter should not be limited to any single embodiment described herein, but rather should be construed in breadth and scope in accordance with the appended claims below.

As it employed in the subject specification, the term “processor” can refer to substantially any computing processing unit or device comprising, but not limited to comprising, single-core processors; single-processors with software multithread execution capability; multi-core processors; multi-core processors with software multithread execution capability; multi-core processors with hardware multithread technology; parallel platforms; and parallel platforms with distributed shared memory. Additionally, a processor can refer to an integrated circuit, an application specific integrated circuit (ASIC), a digital signal processor (DSP), a field programmable gate array (FPGA), a programmable logic controller (PLC), a complex programmable logic device (CPLD), a discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. Processors can exploit nano-scale architectures such as, but not limited to, molecular and quantum-dot based transistors, switches and gates, in order to optimize space usage or enhance performance of user equipment. A processor may also be implemented as a combination of computing processing units.

In the subject specification, terms such as “store,” “storage,” “data store,” “data storage,” “database,” and substantially any other information storage component relevant to operation and functionality of a component, refer to “memory components,” or entities embodied in a “memory” or components comprising the memory. It will be appreciated that the memory components described herein can be either volatile memory or nonvolatile memory, or can include both volatile and nonvolatile memory.

As used in this application, the terms “component,” “system,” “platform,” “layer,” “selector,” “interface,” and the like are intended to refer to a computer-related entity or an entity related to an operational apparatus with one or more specific functionalities, wherein the entity can be either hardware, a combination of hardware and software, software, or software in execution. As an example, a component may be, but is not limited to being, a process running on a processor, a processor, an object, an executable, a thread of execution, computer-executable instructions, a program, and/or a computer. By way of illustration and not limitation, both an application running on a server and the server can be a component. One or more components may reside within a process and/or thread of execution and a component may be

localized on one computer and/or distributed between two or more computers. In addition, these components can execute from various computer readable media having various data structures stored thereon. The components may communicate via local and/or remote processes such as in accordance with a signal having one or more data packets (e.g., data from one component interacting with another component in a local system, distributed system, and/or across a network such as the Internet with other systems via the signal). As another example, a component can be an apparatus with specific functionality provided by mechanical parts operated by electric or electronic circuitry, which is operated by a software or firmware application executed by a processor, wherein the processor can be internal or external to the apparatus and executes at least a part of the software or firmware application. As yet another example, a component can be an apparatus that provides specific functionality through electronic components without mechanical parts, the electronic components can include a processor therein to execute software or firmware that confers at least in part the functionality of the electronic components. While various components have been illustrated as separate components, it will be appreciated that multiple components can be implemented as a single component, or a single component can be implemented as multiple components, without departing from example embodiments.

In addition, the term “or” is intended to mean an inclusive “or” rather than an exclusive “or.” That is, unless specified otherwise, or clear from context, “X employs A or B” is intended to mean any of the natural inclusive permutations. That is, if X employs A; X employs B; or X employs both A and B, then “X employs A or B” is satisfied under any of the foregoing instances. Moreover, articles “a” and “an” as used in the subject specification and annexed drawings should generally be construed to mean “one or more” unless specified otherwise or clear from context to be directed to a singular form.

Moreover, terms like “user equipment (UE),” “mobile station,” “mobile,” “subscriber station,” “subscriber equipment,” “access terminal,” “terminal,” “handset,” and similar terminology, refer to a wireless device utilized by a subscriber or user of a wireless communication service to receive or convey data, control, voice, video, sound, gaming, or substantially any data-stream or signaling-stream. The foregoing terms are utilized interchangeably in the subject specification and related drawings. Likewise, the terms “radio,” “access point (AP),” “base station,” “Node B,” “evolved Node B (eNode B),” “home Node B (HNB),” “home access point (HAP),” and the like, are utilized interchangeably in the subject application, and refer to a wireless network component or appliance that serves and receives data, control, voice, video, sound, gaming, or substantially any data-stream or signaling-stream to and from a set of subscriber stations or provider enabled devices. Data and signaling streams can include packetized or frame-based flows.

Additionally, the terms “core-network,” “core,” “core carrier network,” “carrier-side,” “carrier network,” or similar terms can refer to components of a telecommunications network that typically provides some or all of aggregation, authentication, call control and switching, charging, service invocation, or gateways. Aggregation can refer to the highest level of aggregation in a service provider network wherein the next level in the hierarchy under the core nodes is the distribution networks and then the edge networks. UEs do not normally connect directly to the core networks of a large service provider but can be routed to the core by way of a switch or radio area network. Authentication can refer to determinations regarding whether the user requesting a service from the telecom network is authorized to do so

within this network or not. Call control and switching can refer determinations related to the future course of a call stream across carrier equipment based on the call signal processing. Charging can be related to the collation and processing of charging data generated by various network nodes. Two common types of charging mechanisms found in present day networks can be prepaid charging and postpaid charging. Service invocation can occur based on some explicit action (e.g. call transfer) or implicitly (e.g., call waiting). It is to be noted that service “execution” may or may not be a core network functionality as third party network/nodes may take part in actual service execution. A gateway can be present in the core network to access other networks. Gateway functionality can be dependent on the type of the interface with another network.

Furthermore, the terms “user,” “subscriber,” “customer,” “consumer,” “prosumer,” “agent,” and the like are employed interchangeably throughout the subject specification, unless context warrants particular distinction(s) among the terms. It should be appreciated that such terms can refer to human entities or automated components (e.g., supported through artificial intelligence, as through a capacity to make inferences based on complex mathematical formalisms), that can provide simulated vision, sound recognition and so forth.

Aspects, features, or advantages of the subject matter can be exploited in substantially any, or any, wired, broadcast, wireless telecommunication, radio technology or network, or combinations thereof. Non-limiting examples of such technologies or networks include Geocast technology; broadcast technologies (e.g., sub-Hz, ELF, VLF, LF, MF, HF, VHF, UHF, SHF, THz broadcasts, etc.); Ethernet; X.25; powerline-type networking (e.g., PowerLine AV Ethernet, etc.); femto-cell technology; Wi-Fi; Worldwide Interoperability for Microwave Access (WiMAX); Enhanced General Packet Radio Service (Enhanced GPRS); Third Generation Partnership Project (3GPP or 3G) Long Term Evolution (LTE); 3GPP Universal Mobile Telecommunications System (UMTS) or 3GPP UMTS; Third Generation Partnership Project 2 (3GPP2) Ultra Mobile Broadband (UMB); High Speed Packet Access (HSPA); High Speed Downlink Packet Access (HSDPA); High Speed Uplink Packet Access (HSUPA); GSM Enhanced Data Rates for GSM Evolution (EDGE) Radio Access Network (RAN) or GERAN; UMTS Terrestrial Radio Access Network (UTRAN); or LTE Advanced.

What has been described above includes examples of systems and methods illustrative of the disclosed subject matter. It is, of course, not possible to describe every combination of components or methods herein. One of ordinary skill in the art may recognize that many further combinations and permutations of the claimed subject matter are possible. Furthermore, to the extent that the terms “includes,” “has,” “possesses,” and the like are used in the detailed description, claims, appendices and drawings such terms are intended to be inclusive in a manner similar to the term “comprising” as “comprising” is interpreted when employed as a transitional word in a claim.

What is claimed is:

1. A system, comprising:
 - a processor; and
 - a memory that stores executable instructions that, when executed by the processor, facilitate performance of operations, comprising:
 - in response to receiving geographic information relating to a first radio and a second radio of a wireless

network, determining a level of geographic redundancy associated with the first radio and second radio;

selecting the first radio based on the level of geographic redundancy being determined to have satisfied a first rule related to a threshold redundancy level; and enabling, for a device associated with a request for time fingerprint location information, access to first timed fingerprint location information corresponding to the first radio.

2. The system of claim 1, wherein the determining the level of geographic redundancy comprises determining an error in location accuracy associated with determining a location based on the first timed fingerprint location information corresponding to the first radio and second timed fingerprint location information corresponding to the second radio.

3. The system of claim 1, wherein access to second timed fingerprint location information corresponding to the second radio is deprioritized relative to the first timed fingerprint location information.

4. The system of claim 1, wherein access to first timed fingerprint location information corresponding to the first radio is prioritized relative to the second timed fingerprint location information.

5. The system of claim 1, wherein the level of geographic redundancy is a first level of geographic redundancy, and wherein the selecting the first radio is based on the first level of geographic redundancy being determined to have satisfied the first rule related to the threshold redundancy level and a second level of geographic redundancy associated with the first radio and a third radio being determined to have satisfied the first rule related to the threshold redundancy level.

6. The system of claim 5, wherein the selecting the first radio is further based on the first radio and the second radio being determined to satisfy a second rule related to a bounding condition.

7. The system of claim 5, wherein the selecting the first radio is further based on the first radio and the third radio being determined to satisfy a second rule related to a bounding condition.

8. A method, comprising:

determining, by a system comprising a processor, a level of geographic redundancy for a first radio in relation to a second radio based on first geographic information of the first radio and second geographic information of the second radio; and

enabling, by the system in response to a request for timed fingerprint location information, access to first timed fingerprint location information corresponding to the first radio based on the level of geographic redundancy for a first radio.

9. The method of claim 8, wherein the determining the level of geographic redundancy comprises determining an error in location accuracy associated with determining a location based on the first timed fingerprint location information corresponding to the first radio and second timed fingerprint location information corresponding to the second radio.

10. The method of claim 8, wherein access to second timed fingerprint location information corresponding to the second radio is restricted for a device enabled to access the first timed fingerprint location information and the second timed fingerprint location information.

11. The method of claim 8, wherein access to first timed fingerprint location information corresponding to the first

23

radio is promoted for a device enabled to access the first timed fingerprint location information and the second timed fingerprint location information.

12. The method of claim 8, wherein the enabling the access to the first timed fingerprint location information is based on the level of geographic redundancy being determined to have satisfied a rule related to a threshold redundancy level.

13. The method of claim 12, wherein the level of geographic redundancy is a first level of geographic redundancy, and wherein the enabling the access to the first timed fingerprint location information is based on the first level of geographic redundancy being determined to have satisfied the rule related to the threshold redundancy level and determining a second level of geographic redundancy associated with the first radio and a third radio is determined to have satisfied the rule related to the threshold redundancy level.

14. The method of claim 13, wherein the rule is a first rule, and wherein the enabling the access to the first timed fingerprint location information is further based on the first radio and the second radio being determined to satisfy a second rule related to a proximity between the first radio and the second radio.

15. The method of claim 13, wherein the rule is a first rule, and wherein the enabling the access to the first timed fingerprint location information is further based on the first radio and the third radio being determined to satisfy a second rule related to a proximity between the first radio and the second radio.

16. A non-transitory computer-readable storage medium, comprising executable instructions that, when executed by a processor, facilitate performance of operations, comprising:
determining a level of geographic redundancy for a first radio in relation to a second radio based on first

24

geographic information of the first radio and second geographic information of the second radio;
setting an indicator related to excluding the second radio from a determination of first timed fingerprint location information; and

enabling access to the first timed fingerprint location information in response to receiving a timed fingerprint location information request from a device.

17. The non-transitory computer-readable storage medium of claim 16, wherein the determining the level of geographic redundancy comprises determining an error in location accuracy associated with determining a location based on the first timed fingerprint location information corresponding to the first radio and second timed fingerprint location information corresponding to the second radio.

18. The non-transitory computer-readable storage medium of claim 16, wherein the enabling the access to the first timed fingerprint location information is based on the level of geographic redundancy being determined to have satisfied a rule related to a threshold redundancy level.

19. The non-transitory computer-readable storage medium of claim 18, wherein the level of geographic redundancy is a first level of geographic redundancy, and wherein the enabling the access to the first timed fingerprint location information is further based on a second level of geographic redundancy associated with the first radio and a third radio being determined to have satisfied the rule related to the threshold redundancy level.

20. The non-transitory computer-readable storage medium of claim 19, wherein the rule is a first rule, and wherein the operations further comprise:

determining that the first radio, the second radio, and the third radio satisfy a second rule related to a threshold distance between radios.

* * * * *