



US009615563B2

(12) **United States Patent**  
**Fontaine**

(10) **Patent No.:** **US 9,615,563 B2**  
(45) **Date of Patent:** **Apr. 11, 2017**

(54) **DOUBLE ENDED FISHING WORM CANISTER**

2,507,319 A	5/1950	Peters	
3,423,869 A	1/1969	Duerst	
5,118,021 A *	6/1992	Fiocchi	225/103
5,481,823 A	1/1996	Hoover et al.	
6,442,887 B2	9/2002	Sanquist	
2001/0045050 A1 *	11/2001	Sanquist	43/55
2003/0005617 A1 *	1/2003	Holverson	43/41

(71) Applicant: **Sylvain Fontaine**, La Baie (CA)

(72) Inventor: **Sylvain Fontaine**, La Baie (CA)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 782 days.

**FOREIGN PATENT DOCUMENTS**

FR	1106118	7/1955
GB	2391863	2/2004

\* cited by examiner

(21) Appl. No.: **13/900,580**

(22) Filed: **May 23, 2013**

(65) **Prior Publication Data**

US 2014/0345187 A1 Nov. 27, 2014

*Primary Examiner* — Kristen C Hayes

(51) **Int. Cl.**

**A01K 97/00** (2006.01)

**A01K 97/04** (2006.01)

(52) **U.S. Cl.**

CPC ..... **A01K 97/04** (2013.01)

(58) **Field of Classification Search**

CPC ..... A01K 97/04; A01K 97/05

USPC ..... 43/54.1, 55; 225/39, 43

See application file for complete search history.

(57) **ABSTRACT**


A double ended fishing worm canister in a double ended canister for storing and using worms as bait for fishing. The canister has a cylindrical body having a top end and a bottom end, a first lid removably attached to the top end, and a second lid removably attached to the bottom end. The first lid includes a container therein having a pivoting cover attached thereto, the pivoting cover includes at least one side wall adapted to cut worms into separate pieces, such that the canister is adapted to store worms and dirt therein, be opened and closed from either end, and cut worms into separate pieces for use as bait for fishing.

(56) **References Cited**


**U.S. PATENT DOCUMENTS**

1,150,778 A	8/1915	Lamb
2,326,414 A	8/1943	Thompson

**11 Claims, 6 Drawing Sheets**



**FIG. 1**








FIG. 2



**FIG. 4**




FIG. 5b






FIG. 5a





1

## DOUBLE ENDED FISHING WORM CANISTER

This application claims priority based on request  
GB1209900.8 filed Jun. 2, 2012

### FIELD OF THE INVENTION

The present invention relates generally to fishing equip-  
ment but more particularly to a double ended fishing worm  
canister.

### BACKGROUND OF THE INVENTION

Worms are still popular as bait for fish. Canisters filled  
with dirt are generally used for keeping worms over an  
extended period of time. The problem with canisters is that  
worms tend to dig deep into the container and one has.

### SUMMARY OF THE INVENTION

In view of the foregoing disadvantages inherent in the  
known devices now present in the prior art, the present  
invention, which will be described subsequently in greater  
detail, is to provide objects and advantages which are:

To provide for a double ended canister that has a lid at  
each end of the container so that if worms can't be easily  
found on one end, there is always the other end of the  
container which can be reached by opening the other lid.  
Other features include a worm cutter with its own smaller  
container to store the remaining worm part as well as an  
integrated belt clip to conveniently carry the canister.

In order to do so, the invention consists in a double ended  
canister for storing and using worms as bait for fishing. The  
canister has a cylindrical body having a top end and a bottom  
end, a first lid removably attached to the top end, and a  
second lid removably attached to the bottom end. The first  
lid includes a container therein having a pivoting cover  
attached thereto, the pivoting cover includes at least one side  
wall adapted to cut worms into separate pieces, such that the  
canister is adapted to store worms and dirt therein, be  
opened and closed from either end, and cut worms into  
separate pieces for use as bait for fishing.

The double ended canister has the pivoting cover, and the  
at least one side wall form a worm cutter assembly and the  
pivoting cover is formed as a flip cover, and the at least one  
side wall is formed as a blade.

The lid further includes a container therein having a  
pivoting cover attached thereto, the pivoting cover including  
at least one side wall adapted to cut worms into separate  
pieces.

The pivoting cover, and the at least one side wall form a  
worm cutter assembly, and the pivoting cover is formed as  
a flip cover, and the at least one side wall is formed as a  
blade.

The pivoting cover includes two side walls formed as  
blades and are both adapted to cut worms into separate  
pieces.

The pivoting cover of the second lid container includes  
two side walls formed as blades and are both adapted to cut  
worms into separate pieces.

The lids are removably attached to the ends via matching  
threads between the lid and the end of the canister body.

The side wall of the cylindrical body has a plurality of  
holes therethrough adapted to allow air to pass through for  
the worms to breathe and stay alive for a long duration of  
time.

2

The double ended canister has a clip member removably  
attached to an exterior side wall portion of the cylindrical  
body and adapted to clip onto a portion of a fisherman's belt.

The double ended canister is further comprised of a clip  
attachment member adapted to be connected to a portion of  
a boat, such that the clip member can clip to the clip  
attachment member and thereby be attached to the boat.

The double ended canister can be formed from a material  
chosen from a list of materials comprising steel, aluminum,  
plastic, and polycarbonate.

There has thus been outlined, rather broadly, the more  
important features of the invention in order that the detailed  
description thereof that follows may be better understood,  
and in order that the present contribution to the art may be  
better appreciated. There are additional features of the  
invention that will be described hereinafter and which will  
form the subject matter of the claims appended hereto.

In this respect, before explaining at least one embodiment  
of the invention in detail, it is to be understood that the  
invention is not limited in its application to the details of  
construction and to the arrangements of the components set  
forth in the following description or illustrated in the draw-  
ings. The invention is capable of other embodiments and of  
being practiced and carried out in various ways. Also, it is  
to be understood that the phraseology and terminology  
employed herein are for the purpose of description and  
should not be regarded as limiting.

As such, those skilled in the art will appreciate that the  
conception, upon which this disclosure is based, may readily  
be utilized as a basis for the designing of other structures,  
methods and systems for carrying out the several purposes  
of the present invention. It is important, therefore, that the  
claims be regarded as including such equivalent construc-  
tions insofar as they do not depart from the spirit and scope  
of the present invention.

Further, the purpose of the foregoing abstract is to enable  
the U.S. Patent and Trademark Office and the public gener-  
ally, and especially the scientists, engineers and practitio-  
ners in the art who are not familiar with patent or legal terms  
or phraseology, to determine quickly from a cursory inspec-  
tion the nature and essence of the technical disclosure of the  
application. The abstract is neither intended to define the  
invention of the application, which is measured by the  
claims, nor is it intended to be limiting as to the scope of the  
invention in any way.

These together with other objects of the invention, along  
with the various features of novelty which characterize the  
invention, are pointed out with particularity in the claims  
annexed to and forming a part of this disclosure. For a better  
understanding of the invention, its operating advantages and  
the specific objects attained by its uses, reference should be  
made to the accompanying drawings and descriptive matter  
which contains illustrated preferred embodiments of the  
invention.

### BRIEF DESCRIPTION OF THE DRAWINGS

- FIG. 1 Isometric view of the invention.  
FIG. 2 Exploded view of the invention.  
FIGS. 3a-b top and side views, respectively, of the  
invention.  
FIG. 4 Cutaway side view of the invention.  
FIGS. 5a-b Side views of a belt and a boat clip.  
FIG. 6 Isometric view of the invention and how it attaches  
to a boat clip.



DETAILED DESCRIPTION OF THE  
PREFERRED EMBODIMENT

A double ended canister (10) that has a first and a second lid (12, 12') at each end (14, 14') of a container body (16) so that if worms can't be easily found on one end (14) when opening the first lid (12), there is always the opposite end (14') of the container body (16) which can be reached by opening the second lid (12'). In a preferred embodiment, the lids (12, 12') are threadably attached to the body (16) but they could alternatively be snap off lids.

Other features include a worm cutter assembly (18) located on each lid (12, 12') with its own small container (20) embedded inside the lid (12, 12') to store the remaining worm part. The worm cutter assembly (18) is further comprised of a flip cover (19) and a blade (21).

The container body (16) can also have an integrated clip (22) to conveniently carry the canister (10) either on a belt or the clip (22) can connect to a clip attachment (24) on a boat.

Also, as is known in the art of worm canisters, the canister body (16) has a plurality of through holes (26) spread across its surface for the worms to breathe.

As to a further discussion of the manner of usage and operation of the present invention, the same should be apparent from the above description. Accordingly, no further discussion relating to the manner of usage and operation will be provided.

With respect to the above description then, it is to be realized that the optimum dimensional relationships for the parts of the invention, to include variations in size, materials, shape, form, function and manner of operation, assembly and use, are deemed readily apparent and obvious to one skilled in the art, and all equivalent relationships to those illustrated in the drawings and described in the specification are intended to be encompassed by the present invention.

Therefore, the foregoing is considered as illustrative only of the principles of the invention. Further, since numerous modifications and changes will readily occur to those skilled in the art, it is not desired to limit the invention to the exact construction and operation shown and described, and accordingly, all suitable modifications and equivalents may be resorted to, falling within the scope of the invention.

The invention claimed is:

1. A double ended canister for storing and using worms as bait for fishing, said canister comprising a cylindrical body having a top end and a bottom end; a first lid removably attached to said top end, and a second lid removably attached to said bottom end, thereby defining an interior storage volume; said first lid including a container therein having a pivoting cover attached thereto, said pivoting cover

includes two parallel side walls each adapted to cut worms into separate pieces, such that said bait can be cut into a predefined length defined by the distance between said two parallel side walls, such that said canister is adapted to store worms and dirt therein, be opened and closed from either end, and cut worms into separate pieces of predefined length for use as bait for fishing.

2. The double ended canister of claim 1, wherein said pivoting cover, and said two parallel side walls are formed as a worm cutter assembly; and wherein said pivoting cover is formed as a flip cover, and said two parallel side walls are formed as blades.

3. The double ended canister of claim 1, wherein said second lid further includes a container therein having a pivoting cover attached thereto, said pivoting cover including at least one side wall adapted to cut worms into separate pieces.

4. The double ended canister of claim 3, wherein said pivoting cover of said second lid, and said at least one side wall form a worm cutter assembly; and wherein said pivoting cover is formed as a flip cover, and said at least one side wall is formed as a blade.

5. The double ended canister of claim 3, wherein said pivoting cover of said second lid container includes two side walls formed as blades and are both adapted to cut worms into separate pieces.

6. The double ended canister of claim 1, wherein said first lid is removably attached to said top end via matching threads between said first lid and said top end.

7. The double ended canister of claim 1, wherein said second lid is removably attached to said bottom end via matching threads between said second lid and said bottom end.

8. The double ended canister of claim 1, wherein the side wall of said cylindrical body has a plurality of holes there-through adapted to allow air to pass through for the worms to breathe and stay alive for a long duration of time.

9. The double ended canister of claim 1, further comprising a clip member removably attached to an exterior side wall portion of said cylindrical body and adapted to clip onto a portion of a fisherman's belt.

10. The double ended canister of claim 9, further comprising a clip attachment member adapted to be connected to a portion of a boat, such that said clip member can clip to said clip attachment member and thereby be attached to said boat.

11. The double ended canister of claim 1, wherein said canister is formed from a material chosen from a list of materials consisting of steel, aluminum, plastic, and polycarbonate.

\* \* \* \* \*