



US009618620B2

(12) **United States Patent**
Zweigle et al.

(10) **Patent No.:** **US 9,618,620 B2**
(45) **Date of Patent:** **Apr. 11, 2017**

(54) **USING DEPTH-CAMERA IMAGES TO SPEED REGISTRATION OF THREE-DIMENSIONAL SCANS**

(58) **Field of Classification Search**
CPC G01B 11/002; G01B 11/24; G01C 11/00;
G01C 15/002; G01S 17/89; G01S 7/4817;
G01S 7/4818

(71) Applicant: **FARO Technologies, Inc.**, Lake Mary, FL (US)

See application file for complete search history.

(72) Inventors: **Oliver Zweigle**, Stuttgart (DE);
Bernd-Dietmar Becker, Ludwigsburg (DE); **Reinhard Becker**, Ludwigsburg (DE)

(56) **References Cited**

U.S. PATENT DOCUMENTS

698,890 A 4/1902 Austin
1,535,312 A 4/1925 Hosking
(Continued)

(73) Assignee: **FARO TECHNOLOGIES, INC.**, Lake Mary, FL (US)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 310 days.

AT 506110 A1 6/2009
AT 508635 A1 3/2011
(Continued)

(21) Appl. No.: **14/559,367**

OTHER PUBLICATIONS

(22) Filed: **Dec. 3, 2014**

May S et al: "Robust 3D-mapping with time-of-flight cameras", Intelligent Robots and Systems, 2009. IROS 2009. IEEE/RSJ International Conference on, IEEE, Piscataway, NJ, USA, Oct. 10, 2009, pp. 1673-1678, XP031581042, ISBN: 978-1-4244-3803-7.*

(65) **Prior Publication Data**

US 2015/0160343 A1 Jun. 11, 2015

(Continued)

Related U.S. Application Data

(63) Continuation of application No. PCT/IB2013/003082, filed on Sep. 27, 2013.
(Continued)

Primary Examiner — Luke Ratcliffe

(74) *Attorney, Agent, or Firm* — Cantor Colburn LLP

(30) **Foreign Application Priority Data**

Oct. 5, 2012 (DE) 10 2012 109 481

(57) **ABSTRACT**


(51) **Int. Cl.**
G01S 17/42 (2006.01)
B25J 13/08 (2006.01)

(Continued)

A method for measuring and registering 3D coordinates has a 3D scanner measure a first collection of 3D coordinates of points from a first registration position and a second collection of 3D coordinates of points from a second registration position. In between these positions, the 3D measuring device collects depth-camera images. A processor determines first and second translation values and a first rotation value based on the depth-camera images. The processor identifies a correspondence among registration targets in the first and second collection of 3D coordinates based at least in part on the first and second translation values and the first rotation value. The processor uses this correspondence and

(Continued)

(52) **U.S. Cl.**
CPC **G01S 17/42** (2013.01); **B25J 13/08** (2013.01); **G01B 11/002** (2013.01);
(Continued)



the first and second collection of 3D coordinates to determine 3D coordinates of a registered 3D collection of points.

16 Claims, 16 Drawing Sheets

Related U.S. Application Data

(60) Provisional application No. 61/716,845, filed on Oct. 22, 2012.

(51) **Int. Cl.**

G01S 17/88 (2006.01)
G01S 17/89 (2006.01)
G01S 7/00 (2006.01)
G01S 7/481 (2006.01)
G05D 1/02 (2006.01)
G09B 29/00 (2006.01)
G01B 11/00 (2006.01)
G01B 11/27 (2006.01)
G01S 17/36 (2006.01)
G01C 15/00 (2006.01)
G01S 7/48 (2006.01)
G01C 7/04 (2006.01)
G01S 17/02 (2006.01)
G01S 17/87 (2006.01)

(52) **U.S. Cl.**

CPC **G01B 11/272** (2013.01); **G01C 15/002** (2013.01); **G01S 7/003** (2013.01); **G01S 7/4808** (2013.01); **G01S 7/4813** (2013.01); **G01S 7/4817** (2013.01); **G01S 17/36** (2013.01); **G01S 17/88** (2013.01); **G01S 17/89** (2013.01); **G05D 1/024** (2013.01); **G05D 1/0274** (2013.01); **G09B 29/004** (2013.01); **G01C 7/04** (2013.01); **G01S 17/023** (2013.01); **G01S 17/87** (2013.01); **G05D 2201/0207** (2013.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

1,538,758 A 5/1925 Taylor
 1,918,813 A 7/1933 Kinzy
 2,316,573 A 4/1943 Egy
 2,333,243 A 11/1943 Glab
 2,702,683 A 2/1955 Green et al.
 2,748,926 A 6/1956 Leahy
 2,983,367 A 6/1958 Paramater et al.
 2,924,495 A 9/1958 Haines
 2,966,257 A 12/1960 Littlejohn
 3,066,790 A 12/1962 Armbruster
 3,447,852 A 6/1969 Barlow
 3,458,167 A 7/1969 Cooley, Jr.
 3,830,567 A 8/1974 Riegl
 3,899,145 A 8/1975 Stephenson
 3,945,729 A 3/1976 Rosen
 4,138,045 A 2/1979 Baker
 4,178,515 A 12/1979 Tarasevich
 4,340,008 A 7/1982 Mendelson
 4,379,461 A 4/1983 Nilsson et al.
 4,413,907 A 11/1983 Lane
 4,424,899 A 1/1984 Rosenberg
 4,430,796 A 2/1984 Nakagawa
 4,457,625 A 7/1984 Greenleaf et al.
 4,506,448 A 3/1985 Topping et al.
 4,537,233 A 8/1985 Vroonland et al.
 4,544,236 A 10/1985 Endo
 4,561,776 A 12/1985 Pryor
 4,606,696 A 8/1986 Slocum

4,659,280 A 4/1987 Akeel
 4,663,852 A 5/1987 Guarini
 4,664,588 A 5/1987 Newell et al.
 4,667,231 A 5/1987 Pryor
 4,676,002 A 6/1987 Slocum
 4,714,339 A 12/1987 Lau et al.
 4,733,961 A 3/1988 Mooney
 4,736,218 A 4/1988 Kutman
 4,751,950 A 6/1988 Bock
 4,767,257 A 8/1988 Kato
 4,790,651 A 12/1988 Brown et al.
 4,816,822 A 3/1989 Vache et al.
 4,870,274 A 9/1989 Hebert et al.
 4,882,806 A 11/1989 Davis
 4,891,509 A 1/1990 Jones et al.
 4,954,952 A 9/1990 Ubhayakar et al.
 4,982,841 A 1/1991 Goedecke
 4,984,881 A 1/1991 Osada et al.
 4,996,909 A 3/1991 Vache et al.
 4,999,491 A 3/1991 Semler et al.
 5,021,641 A 6/1991 Swartz et al.
 5,025,966 A 6/1991 Potter
 5,027,951 A 7/1991 Johnson
 5,068,971 A 12/1991 Simon
 5,069,524 A 12/1991 Watanabe et al.
 5,155,684 A 10/1992 Burke et al.
 5,168,532 A 12/1992 Seppi et al.
 5,189,797 A 3/1993 Granger
 5,205,111 A 4/1993 Johnson
 5,211,476 A 5/1993 Coudroy
 5,212,738 A 5/1993 Chande et al.
 5,213,240 A 5/1993 Dietz et al.
 5,216,479 A 6/1993 Dotan et al.
 5,218,427 A 6/1993 Koch
 5,219,423 A 6/1993 Kamaya
 5,239,855 A 8/1993 Schleifer et al.
 5,289,264 A 2/1994 Steinbichler
 5,289,265 A 2/1994 Inoue et al.
 5,289,855 A 3/1994 Baker et al.
 5,313,261 A 5/1994 Leatham et al.
 5,319,445 A 6/1994 Fitts
 5,329,347 A 7/1994 Wallace et al.
 5,329,467 A 7/1994 Nagamune et al.
 5,332,315 A 7/1994 Baker et al.
 5,337,149 A 8/1994 Kozah et al.
 5,371,347 A 12/1994 Plesko
 5,372,250 A 12/1994 Johnson
 5,373,346 A 12/1994 Hocker
 5,402,365 A 3/1995 Kozikaro et al.
 5,402,582 A 4/1995 Raab
 5,412,880 A 5/1995 Raab
 5,416,505 A 5/1995 Eguchi et al.
 5,430,384 A 7/1995 Hocker
 5,446,846 A 8/1995 Lennartsson
 5,455,670 A 10/1995 Payne et al.
 5,455,993 A 10/1995 Link et al.
 5,510,977 A 4/1996 Raab
 5,517,297 A 5/1996 Stenton
 5,528,354 A 6/1996 Uwira
 5,528,505 A 6/1996 Granger et al.
 5,535,524 A 7/1996 Carrier et al.
 5,563,655 A 10/1996 Lathrop
 5,577,130 A 11/1996 Wu
 5,611,147 A 3/1997 Raab
 5,615,489 A 4/1997 Breyer et al.
 5,623,416 A 4/1997 Hocker, III
 5,629,756 A 5/1997 Kitajima
 5,668,631 A 9/1997 Norita et al.
 5,675,326 A 10/1997 Juds et al.
 5,677,760 A 10/1997 Mikami et al.
 5,682,508 A 10/1997 Hocker, III
 5,716,036 A 2/1998 Isobe et al.
 5,724,264 A 3/1998 Rosenberg et al.
 5,734,417 A 3/1998 Yamamoto et al.
 5,745,050 A 4/1998 Nakagawa
 5,745,225 A 4/1998 Watanabe et al.
 5,752,112 A 5/1998 Paddock et al.
 5,754,449 A 5/1998 Hoshal et al.
 5,768,792 A 6/1998 Raab

(56)

References Cited

U.S. PATENT DOCUMENTS

5,793,993 A	8/1998	Broedner et al.	6,512,575 B1	1/2003	Marchi
5,804,805 A	9/1998	Koenck et al.	6,519,860 B1	2/2003	Bieg et al.
5,825,666 A	10/1998	Freifeld	D472,824 S	4/2003	Raab et al.
5,829,148 A	11/1998	Eaton	6,542,249 B1	4/2003	Kofman et al.
5,831,719 A	11/1998	Berg et al.	6,547,397 B1	4/2003	Kaufman et al.
5,832,416 A	11/1998	Anderson	6,598,306 B2	7/2003	Eaton
5,844,591 A	12/1998	Takamatsu et al.	6,611,346 B2	8/2003	Granger
5,856,874 A	1/1999	Tachibana et al.	6,611,617 B1	8/2003	Crampton
5,887,122 A	3/1999	Terawaki et al.	D479,544 S	9/2003	Raab et al.
5,894,123 A	4/1999	Ohtomo et al.	6,612,044 B2	9/2003	Raab et al.
5,898,490 A	4/1999	Ohtomo et al.	6,621,065 B1	9/2003	Fukumoto et al.
5,909,939 A	6/1999	Fugmann	6,626,339 B2	9/2003	Gates et al.
5,926,782 A	7/1999	Raab	6,633,051 B1	10/2003	Holloway et al.
5,933,267 A	8/1999	Ishizuka	6,649,208 B2	11/2003	Rodgers
5,936,721 A	8/1999	Ohtomo et al.	6,650,402 B2	11/2003	Sullivan et al.
5,940,170 A	8/1999	Berg et al.	6,668,466 B1	12/2003	Bieg et al.
5,940,181 A	8/1999	Tsubono et al.	6,675,122 B1	1/2004	Markendorf et al.
5,949,530 A	9/1999	Wetteborn	6,681,495 B2	1/2004	Masayuki et al.
5,956,661 A	9/1999	Lefebvre et al.	6,710,859 B2	3/2004	Shirai et al.
5,956,857 A	9/1999	Raab	D490,831 S	6/2004	Raab et al.
5,969,321 A	10/1999	Danielson et al.	D491,210 S	6/2004	Raab et al.
5,973,788 A	10/1999	Pettersen et al.	6,750,873 B1	6/2004	Bernardini et al.
5,978,748 A	11/1999	Raab	6,753,876 B2	6/2004	Brooksby et al.
5,983,936 A	11/1999	Schwieterman et al.	6,759,649 B2	7/2004	Hipp
5,988,862 A	11/1999	Kacyra et al.	6,759,979 B2	7/2004	Vashisth et al.
5,991,011 A	11/1999	Damm	6,764,185 B1	7/2004	Beardsley et al.
5,996,790 A	12/1999	Yamada et al.	6,789,327 B2	9/2004	Roth et al.
5,997,779 A	12/1999	Potter	6,820,346 B2	11/2004	Raab et al.
6,040,898 A	3/2000	Mrosik et al.	6,822,749 B1	11/2004	Christoph
D423,534 S	4/2000	Raab et al.	6,825,923 B2	11/2004	Hamar et al.
6,050,615 A	4/2000	Weinhold	6,826,664 B2	11/2004	Hocker, III et al.
6,057,915 A	5/2000	Squire et al.	6,847,436 B2	1/2005	Bridges
6,060,889 A	5/2000	Hocker	6,856,381 B2	2/2005	Christoph
6,067,116 A	5/2000	Yamano et al.	6,858,836 B1	2/2005	Hartrumpf
6,069,700 A	5/2000	Rudnick et al.	6,862,097 B2	3/2005	Yanagisawa et al.
6,077,306 A	6/2000	Metzger et al.	6,868,359 B2	3/2005	Raab
6,112,423 A	9/2000	Sheehan	6,879,933 B2	4/2005	Steffey et al.
6,115,511 A	9/2000	Sakai et al.	6,889,903 B1	5/2005	Koenck
6,125,337 A	9/2000	Rosenberg et al.	6,892,465 B2	5/2005	Raab et al.
6,131,299 A	10/2000	Raab et al.	6,894,767 B2	5/2005	Ishinabe et al.
6,134,507 A	10/2000	Markey, Jr. et al.	6,895,347 B2	5/2005	Dorny et al.
6,138,915 A	10/2000	Danielson et al.	6,901,673 B1	6/2005	Cobb et al.
6,149,112 A	11/2000	Thieltges	6,904,691 B2	6/2005	Raab et al.
6,151,789 A	11/2000	Raab et al.	6,914,678 B1	7/2005	Ulrichsen et al.
6,163,294 A	12/2000	Talbot	6,917,415 B2	7/2005	Gogolla et al.
6,166,504 A	12/2000	Iida et al.	6,920,697 B2	7/2005	Raab et al.
6,166,809 A	12/2000	Pettersen et al.	6,922,234 B2	7/2005	Hoffman et al.
6,166,811 A	12/2000	Long et al.	6,922,252 B2	7/2005	Harvill et al.
6,204,651 B1	3/2001	Marcus et al.	6,925,722 B2	8/2005	Raab et al.
6,204,961 B1	3/2001	Anderson et al.	6,931,745 B2	8/2005	Granger
6,219,928 B1	4/2001	Raab et al.	6,935,036 B2	8/2005	Raab et al.
D441,632 S	5/2001	Raab et al.	6,935,748 B2	8/2005	Kaufman et al.
6,240,651 B1	6/2001	Schroeder et al.	6,948,255 B2	9/2005	Russell
6,246,468 B1 *	6/2001	Dimsdale G01B 11/002 356/4.02	6,957,496 B2	10/2005	Raab et al.
6,253,458 B1	7/2001	Raab et al.	6,965,843 B2	11/2005	Raab et al.
6,282,195 B1	8/2001	Miller et al.	6,973,734 B2	12/2005	Raab et al.
6,285,390 B1	9/2001	Blake	6,988,322 B2	1/2006	Raab et al.
6,298,569 B1	10/2001	Raab et al.	6,989,890 B2	1/2006	Riegl et al.
6,339,410 B1	1/2002	Milner et al.	7,003,892 B2	2/2006	Eaton et al.
6,349,249 B1	2/2002	Cunningham	7,006,084 B1	2/2006	Buss et al.
6,366,831 B1	4/2002	Raab	7,024,032 B2	4/2006	Kidd et al.
6,408,252 B1	6/2002	De Smet	7,029,126 B2	4/2006	Tang
6,418,774 B1	7/2002	Brogaardh et al.	7,032,321 B2	4/2006	Raab et al.
6,438,507 B1	8/2002	Imai	7,040,136 B2	5/2006	Forss et al.
6,438,856 B1	8/2002	Kaczynski	7,051,447 B2	5/2006	Kikuchi et al.
6,442,419 B1	8/2002	Chu et al.	7,069,124 B1	6/2006	Whittaker et al.
6,445,446 B1	9/2002	Kumagai et al.	7,069,875 B2	7/2006	Warecki
6,460,004 B2	10/2002	Greer et al.	7,076,420 B1	7/2006	Snyder et al.
6,470,584 B1	10/2002	Stoodley	7,106,421 B2	9/2006	Matsuura et al.
6,477,784 B2	11/2002	Schroeder et al.	7,117,107 B2	10/2006	Dorny et al.
6,480,270 B1	11/2002	Studnicka et al.	7,120,092 B2	10/2006	Del Prado Pavon et al.
6,483,106 B1	11/2002	Ohtomo et al.	7,127,822 B2	10/2006	Kumagai et al.
6,497,394 B1	12/2002	Dunchock	7,136,153 B2	11/2006	Mori et al.
6,504,602 B1	1/2003	Hinderling	7,140,213 B2	11/2006	Feucht et al.
			7,142,289 B2	11/2006	Ando et al.
			7,145,926 B2	12/2006	Vitruk et al.
			7,152,456 B2	12/2006	Eaton
			7,174,651 B2	2/2007	Raab et al.
			7,180,072 B2	2/2007	Persi et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,184,047	B1	2/2007	Crampton	7,599,106	B2	10/2009	Matsumoto et al.
7,190,465	B2	3/2007	Froehlich et al.	7,600,061	B2	10/2009	Honda
7,191,541	B1	3/2007	Weekers et al.	7,602,873	B2	10/2009	Eidson
7,193,690	B2	3/2007	Ossig et al.	7,604,207	B2	10/2009	Hasloecheer et al.
7,196,509	B2	3/2007	Teng	7,610,175	B2	10/2009	Eidson
7,199,872	B2	4/2007	Van Cranenbroeck	7,614,157	B2	11/2009	Granger
7,200,246	B2	4/2007	Cofer et al.	7,624,510	B2	12/2009	Ferrari
7,202,941	B2	4/2007	Munro	7,625,335	B2	12/2009	Deichmann et al.
7,230,689	B2	6/2007	Lau	7,626,690	B2	12/2009	Kumagai et al.
7,242,590	B1	7/2007	Yeap et al.	D607,350	S	1/2010	Cooduvalli et al.
7,246,030	B2	7/2007	Raab et al.	7,656,751	B2	2/2010	Rischar et al.
7,249,421	B2	7/2007	MacManus et al.	7,659,995	B2	2/2010	Knighton et al.
7,256,899	B1	8/2007	Faul et al.	D610,926	S	3/2010	Gerent et al.
7,269,910	B2	9/2007	Raab et al.	7,693,325	B2	4/2010	Pulla et al.
D551,943	S	10/2007	Hodjat et al.	7,697,748	B2	4/2010	Dimsdale et al.
7,285,793	B2	10/2007	Husted	7,701,592	B2	4/2010	Saint Clair et al.
7,296,364	B2	11/2007	Seitz et al.	7,712,224	B2	5/2010	Hicks
7,296,955	B2	11/2007	Dreier	7,721,396	B2	5/2010	Fleischman
7,296,979	B2	11/2007	Raab et al.	7,728,833	B2	6/2010	Verma et al.
7,306,339	B2	12/2007	Kaufman et al.	7,728,963	B2	6/2010	Kirschner
7,307,701	B2	12/2007	Hoffman, II	7,733,544	B2	6/2010	Becker et al.
7,312,862	B2	12/2007	Zumbrunn et al.	7,735,234	B2	6/2010	Briggs et al.
7,313,264	B2	12/2007	Crampton	7,743,524	B2	6/2010	Eaton et al.
D559,657	S	1/2008	Wohlford et al.	7,752,003	B2	7/2010	MacManus
7,319,512	B2	1/2008	Ohtomo et al.	7,756,615	B2	7/2010	Barfoot et al.
7,330,242	B2	2/2008	Reichert et al.	7,765,707	B2	8/2010	Tomelleri
7,337,344	B2	2/2008	Barman et al.	7,769,559	B2	8/2010	Reichert
7,342,650	B2	3/2008	Kern et al.	7,774,949	B2	8/2010	Ferrari
7,348,822	B2	3/2008	Baer	7,777,761	B2	8/2010	England et al.
7,352,446	B2	4/2008	Bridges et al.	7,779,548	B2	8/2010	Ferrari
7,360,648	B1	4/2008	Blaschke	7,779,553	B2	8/2010	Jordil et al.
7,372,558	B2	5/2008	Kaufman et al.	7,784,194	B2	8/2010	Raab et al.
7,372,581	B2	5/2008	Raab et al.	7,787,670	B2	8/2010	Urushiya
7,383,638	B2	6/2008	Granger	7,793,425	B2	9/2010	Bailey
7,388,654	B2	6/2008	Raab et al.	7,798,453	B2	9/2010	Maningo et al.
7,389,870	B2	6/2008	Slappay	7,800,758	B1	9/2010	Bridges et al.
7,395,606	B2	7/2008	Crampton	7,804,602	B2	9/2010	Raab
7,400,384	B1	7/2008	Evans et al.	7,805,851	B2	10/2010	Pettersson
7,403,268	B2	7/2008	England et al.	7,805,854	B2	10/2010	Eaton
7,403,269	B2	7/2008	Yamashita et al.	7,809,518	B2	10/2010	Zhu et al.
7,430,068	B2	9/2008	Becker et al.	7,834,985	B2	11/2010	Morcom
7,430,070	B2	9/2008	Soreide et al.	7,847,922	B2	12/2010	Gittinger et al.
7,432,686	B2	10/2008	Erdman et al.	RE42,055	E	1/2011	Raab
7,441,341	B2	10/2008	Eaton	7,869,005	B2	1/2011	Ossig et al.
7,443,555	B2	10/2008	Blug et al.	RE42,082	E	2/2011	Raab et al.
7,447,359	B2	11/2008	Tu et al.	7,881,896	B2	2/2011	Atwell et al.
7,447,360	B2	11/2008	Li et al.	7,889,324	B2	2/2011	Yamamoto
7,447,931	B1	11/2008	Rischar et al.	7,891,248	B2	2/2011	Hough et al.
7,449,876	B2	11/2008	Pleasant et al.	7,900,714	B2	3/2011	Milbourne et al.
7,454,265	B2	11/2008	Marsh	7,903,245	B2	3/2011	Miousset et al.
7,463,368	B2	12/2008	Morden et al.	7,903,261	B2	3/2011	Saint Clair et al.
7,477,359	B2	1/2009	England et al.	7,908,757	B2	3/2011	Ferrari
7,477,360	B2	1/2009	England et al.	7,933,055	B2	4/2011	Jensen et al.
7,480,037	B2	1/2009	Palmateer et al.	7,935,928	B2	5/2011	Seger et al.
7,508,496	B2	3/2009	Mettenleiter et al.	7,965,747	B2	6/2011	Kumano
7,508,971	B2	3/2009	Vaccaro et al.	7,974,461	B2	7/2011	England et al.
7,515,256	B2	4/2009	Ohtomo et al.	7,982,866	B2	7/2011	Vogel
7,525,276	B2	4/2009	Eaton	D643,319	S	8/2011	Ferrari et al.
7,527,205	B2	5/2009	Zhu et al.	7,990,397	B2	8/2011	Bukowski et al.
7,528,768	B2	5/2009	Wakayama et al.	7,994,465	B1	8/2011	Bamji et al.
7,541,830	B2	6/2009	Fahrbach et al.	7,995,834	B1	8/2011	Knighton et al.
7,545,517	B2	6/2009	Rueb et al.	8,001,697	B2	8/2011	Danielson et al.
7,546,689	B2	6/2009	Ferrari et al.	8,020,657	B2	9/2011	Allard et al.
7,551,771	B2	6/2009	England, III	8,022,812	B2	9/2011	Beniyama et al.
7,552,644	B2	6/2009	Haase et al.	8,028,432	B2	10/2011	Bailey et al.
7,557,824	B2	7/2009	Holliman	8,036,775	B2	10/2011	Matsumoto et al.
7,561,598	B2	7/2009	Stratton et al.	8,045,762	B2	10/2011	Otani et al.
7,564,250	B2	7/2009	Hocker	8,051,710	B2	11/2011	Van Dam et al.
7,568,293	B2	8/2009	Ferrari	8,052,857	B2	11/2011	Townsend
7,578,069	B2	8/2009	Eaton	8,064,046	B2	11/2011	Ossig et al.
D599,226	S	9/2009	Gerent et al.	8,065,861	B2	11/2011	Caputo
7,589,595	B2	9/2009	Cutler	8,082,673	B2	12/2011	Desforges et al.
7,589,825	B2	9/2009	Orchard et al.	8,099,877	B2	1/2012	Champ
7,591,077	B2	9/2009	Pettersson	8,117,668	B2	2/2012	Crampton et al.
7,591,078	B2	9/2009	Crampton	8,123,350	B2	2/2012	Cannell et al.
				8,152,071	B2	4/2012	Doherty et al.
				D659,035	S	5/2012	Ferrari et al.
				8,171,650	B2	5/2012	York et al.
				8,179,936	B2	5/2012	Bueche et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

D662,427 S	6/2012	Bailey et al.	2004/0111908 A1	6/2004	Raab et al.
8,218,131 B2	7/2012	Otani et al.	2004/0119020 A1	6/2004	Bodkin
8,224,032 B2	7/2012	Fuchs et al.	2004/0135990 A1	7/2004	Ohtomo et al.
8,260,483 B2	9/2012	Barfoot et al.	2004/0139265 A1	7/2004	Hocker, III et al.
8,269,984 B2	9/2012	Hinderling et al.	2004/0158355 A1	8/2004	Holmqvist et al.
8,276,286 B2	10/2012	Bailey et al.	2004/0162700 A1	8/2004	Rosenberg et al.
8,284,407 B2	10/2012	Briggs et al.	2004/0179570 A1	9/2004	Vitruk et al.
8,310,653 B2	11/2012	Ogawa et al.	2004/0221790 A1	11/2004	Sinclair et al.
8,321,612 B2	11/2012	Hartwich et al.	2004/0246462 A1	12/2004	Kaneko et al.
8,346,392 B2	1/2013	Walser et al.	2004/0246589 A1	12/2004	Kim et al.
8,346,480 B2	1/2013	Trepagnier et al.	2004/0259533 A1	12/2004	Nixon et al.
8,352,212 B2	1/2013	Fetter et al.	2005/0016008 A1	1/2005	Raab et al.
8,353,059 B2	1/2013	Crampton et al.	2005/0024625 A1	2/2005	Mori et al.
D676,341 S	2/2013	Bailey et al.	2005/0028393 A1	2/2005	Raab et al.
8,379,191 B2	2/2013	Braunecker et al.	2005/0046823 A1	3/2005	Ando et al.
8,381,704 B2	2/2013	Debelak et al.	2005/0058332 A1	3/2005	Kaufman et al.
8,384,914 B2	2/2013	Becker et al.	2005/0082262 A1	4/2005	Rueb et al.
D678,085 S	3/2013	Bailey et al.	2005/0085940 A1	4/2005	Griggs et al.
8,391,565 B2	3/2013	Purcell et al.	2005/0111514 A1	4/2005	Griggs et al.
8,402,669 B2	3/2013	Ferrari et al.	2005/0141052 A1	5/2005	Matsumoto et al.
8,422,035 B2	4/2013	Hinderling et al.	2005/0144799 A1	6/2005	Becker et al.
8,497,901 B2	7/2013	Pettersson	2005/0150123 A1	7/2005	Raab et al.
8,533,967 B2	9/2013	Bailey et al.	2005/0151963 A1	7/2005	Eaton
8,537,374 B2	9/2013	Briggs et al.	2005/0151963 A1	7/2005	Pulla et al.
8,619,265 B2	12/2013	Steffey et al.	2005/0166413 A1	8/2005	Crampton
8,645,022 B2	2/2014	Yoshimura et al.	2005/0172503 A1	8/2005	Kumagai et al.
8,659,748 B2	2/2014	Dakin et al.	2005/0188557 A1	9/2005	Raab et al.
8,659,752 B2	2/2014	Cramer et al.	2005/0190384 A1	9/2005	Persi et al.
8,661,700 B2	3/2014	Briggs et al.	2005/0259271 A1	11/2005	Christoph
8,677,643 B2	3/2014	Bridges et al.	2005/0276466 A1	12/2005	Vaccaro et al.
8,683,709 B2	4/2014	York	2005/0283989 A1	12/2005	Pettersson
8,699,007 B2	4/2014	Becker et al.	2006/0016086 A1	1/2006	Raab et al.
8,705,012 B2	4/2014	Greiner et al.	2006/0017720 A1	1/2006	Li
8,705,016 B2	4/2014	Schumann et al.	2006/0026851 A1	2/2006	Raab et al.
8,718,837 B2	5/2014	Wang et al.	2006/0028203 A1	2/2006	Kawashima et al.
8,784,425 B2	7/2014	Ritchey et al.	2006/0053647 A1	3/2006	Raab et al.
8,797,552 B2	8/2014	Suzuki et al.	2006/0056459 A1	3/2006	Stratton et al.
8,811,767 B2*	8/2014	Veeraraghavan	2006/0056559 A1	3/2006	Pleasant et al.
		G06T 7/0057	2006/0059270 A1	3/2006	Pleasant et al.
		356/521	2006/0061566 A1	3/2006	Verma et al.
			2006/0066836 A1	3/2006	Bridges et al.
			2006/0088044 A1	3/2006	Bridges et al.
			2006/0096108 A1	4/2006	Hammerl et al.
			2006/0103853 A1	4/2006	Hammerl et al.
			2006/0109536 A1	5/2006	Raab et al.
			2006/0123649 A1	5/2006	Palmateer
			2006/0129349 A1	5/2006	Mettenleiter et al.
			2006/0132803 A1	6/2006	Muller
			2006/0145703 A1	6/2006	Raab et al.
			2006/0169050 A1	6/2006	Clair et al.
			2006/0169608 A1	6/2006	Clair et al.
			2006/0170870 A1	7/2006	Steinbichler et al.
			2006/0182314 A1	7/2006	Steinbichler et al.
			2006/0186301 A1	8/2006	Kobayashi et al.
			2006/0193521 A1	8/2006	Kobayashi et al.
			2006/0241791 A1	8/2006	Carnevali et al.
			2006/0244746 A1	8/2006	Carnevali et al.
			2006/0245717 A1	8/2006	Kaufman et al.
			2006/0279246 A1	8/2006	Kaufman et al.
			2006/0282574 A1	8/2006	England et al.
			2006/0287769 A1	8/2006	England et al.
			2006/0291970 A1	8/2006	Dozier et al.
			2007/0019212 A1	8/2006	Dozier et al.
			2007/0030841 A1	8/2006	England, III et al.
			2007/0043526 A1	10/2006	England, III et al.
			2007/0050774 A1	10/2006	Pokorny et al.
			2007/0055806 A1	11/2006	Pokorny et al.
			2007/0058154 A1	11/2006	England et al.
			2007/0058162 A1	11/2006	England et al.
			2007/0064976 A1	11/2006	Ossig et al.
			2007/0097381 A1	12/2006	Ossig et al.
			2007/0097382 A1	12/2006	Hashimoto et al.
			2007/0100498 A1	12/2006	Hashimoto et al.
			2007/0105238 A1	12/2006	Zotov et al.
			2007/0118269 A1	12/2006	Zotov et al.
			2007/0122250 A1	12/2006	Yanagita et al.
			2007/0142970 A1	12/2006	Yanagita et al.
			2007/0147265 A1	12/2006	Granger
			2007/0147435 A1	1/2007	Gatsios et al.
			2007/0147562 A1	2/2007	Gatsios et al.
				2/2007	Lee et al.
				2/2007	Lee et al.
				2/2007	De Jonge et al.
				3/2007	De Jonge et al.
				3/2007	Eldson et al.
				3/2007	Eldson et al.
				3/2007	Stratton et al.
				3/2007	Stratton et al.
				3/2007	Reichert et al.
				3/2007	Reichert et al.
				3/2007	Granger
				3/2007	Granger
				3/2007	England, III
				5/2007	England, III
				5/2007	Tobiason et al.
				5/2007	Tobiason et al.
				5/2007	Granger
				5/2007	Granger
				5/2007	Matsumoto et al.
				5/2007	Matsumoto et al.
				5/2007	Mandl et al.
				5/2007	Mandl et al.
				5/2007	Gibson et al.
				5/2007	Gibson et al.
				5/2007	Mullner
				5/2007	Mullner
				6/2007	Burbank et al.
				6/2007	Burbank et al.
				6/2007	Eidson et al.
				6/2007	Eidson et al.
				6/2007	Hamilton et al.
				6/2007	Hamilton et al.
				6/2007	Eidson
				6/2007	Eidson

(56)

References Cited

U.S. PATENT DOCUMENTS

2007/0150111	A1	6/2007	Wu et al.	2009/0089004	A1	4/2009	Vook et al.
2007/0151390	A1	7/2007	Blumenkranz et al.	2009/0089078	A1	4/2009	Burse
2007/0153297	A1	7/2007	Lau	2009/0089233	A1	4/2009	Gach et al.
2007/0163134	A1	7/2007	Eaton	2009/0089623	A1	4/2009	Neering et al.
2007/0163136	A1	7/2007	Eaton et al.	2009/0095047	A1	4/2009	Patel et al.
2007/0171220	A1	7/2007	Kriveshko	2009/0100949	A1	4/2009	Shirai et al.
2007/0171394	A1	7/2007	Steiner et al.	2009/0109797	A1	4/2009	Eidson
2007/0172112	A1	7/2007	Paley et al.	2009/0113183	A1	4/2009	Barford et al.
2007/0176648	A1	8/2007	Baer	2009/0113229	A1	4/2009	Cataldo et al.
2007/0177016	A1	8/2007	Wu	2009/0122805	A1	5/2009	Epps et al.
2007/0181685	A1	8/2007	Zhu et al.	2009/0125196	A1	5/2009	Velazquez et al.
2007/0183459	A1	8/2007	Eidson	2009/0133276	A1	5/2009	Bailey
2007/0185682	A1	8/2007	Eidson	2009/0133494	A1	5/2009	Van Dam et al.
2007/0217169	A1	9/2007	Yeap et al.	2009/0139105	A1	6/2009	Granger
2007/0217170	A1	9/2007	Yeap et al.	2009/0157419	A1	6/2009	Burse
2007/0221522	A1	9/2007	Yamada et al.	2009/0161091	A1	6/2009	Yamamoto
2007/0223477	A1	9/2007	Eidson	2009/0165317	A1	7/2009	Little
2007/0229801	A1	10/2007	Tearney et al.	2009/0177435	A1	7/2009	Heininen
2007/0229929	A1	10/2007	Soreide et al.	2009/0177438	A1	7/2009	Raab
2007/0247615	A1	10/2007	Bridges et al.	2009/0185741	A1	7/2009	Nahari et al.
2007/0248122	A1	10/2007	Hamilton	2009/0187373	A1	7/2009	Atwell
2007/0256311	A1	11/2007	Ferrari	2009/0241360	A1	10/2009	Tait et al.
2007/0257660	A1	11/2007	Pleasant et al.	2009/0249634	A1	10/2009	Pettersson
2007/0258378	A1	11/2007	Hamilton	2009/0265946	A1	10/2009	Jordil et al.
2007/0282564	A1	12/2007	Sprague et al.	2009/0273771	A1	11/2009	Gittinger
2007/0294045	A1	12/2007	Atwell et al.	2009/0299689	A1	12/2009	Stubben et al.
2008/0046221	A1	2/2008	Stathis	2009/0322859	A1	12/2009	Shelton et al.
2008/0052808	A1	3/2008	Leick et al.	2009/0323121	A1	12/2009	Valkenburg et al.
2008/0052936	A1	3/2008	Briggs et al.	2009/0323742	A1	12/2009	Kumano
2008/0066583	A1	3/2008	Lott et al.	2010/0030421	A1	2/2010	Yoshimura et al.
2008/0068103	A1	3/2008	Cutler	2010/0040742	A1	2/2010	Dijkhuis et al.
2008/0075325	A1	3/2008	Otani et al.	2010/0049891	A1	2/2010	Hartwich et al.
2008/0075326	A1	3/2008	Otani et al.	2010/0057392	A1	3/2010	York
2008/0080562	A1	4/2008	Burch et al.	2010/0078866	A1	4/2010	Pettersson
2008/0096108	A1	4/2008	Sumiyama et al.	2010/0095542	A1	4/2010	Ferrari
2008/0098272	A1	4/2008	Fairbanks et al.	2010/0122920	A1	5/2010	Butter et al.
2008/0148585	A1	6/2008	Raab et al.	2010/0123892	A1	5/2010	Miller et al.
2008/0154538	A1	6/2008	Stathis	2010/0134596	A1	6/2010	Becker
2008/0179206	A1	7/2008	Feinstein et al.	2010/0134598	A1	6/2010	St-Pierre et al.
2008/0183065	A1	7/2008	Goldbach	2010/0134599	A1	6/2010	Billert et al.
2008/0196260	A1	8/2008	Pettersson	2010/0135534	A1	6/2010	Weston et al.
2008/0204699	A1	8/2008	Benz et al.	2010/0148013	A1	6/2010	Bhotika et al.
2008/0216552	A1	9/2008	Ibach et al.	2010/0195086	A1	8/2010	Ossig et al.
2008/0218728	A1	9/2008	Kirschner	2010/0207938	A1	8/2010	Yau et al.
2008/0228331	A1	9/2008	McNerney et al.	2010/0208062	A1	8/2010	Pettersson
2008/0232269	A1	9/2008	Tatman et al.	2010/0208318	A1	8/2010	Jensen et al.
2008/0235969	A1	10/2008	Jordil et al.	2010/0245851	A1	9/2010	Teodorescu
2008/0235970	A1	10/2008	Crampton	2010/0277747	A1	11/2010	Rueb et al.
2008/0240321	A1	10/2008	Narus et al.	2010/0281705	A1	11/2010	Verdi et al.
2008/0245452	A1	10/2008	Law et al.	2010/0286941	A1	11/2010	Merlot
2008/0246943	A1	10/2008	Kaufman et al.	2010/0312524	A1	12/2010	Siercks et al.
2008/0252671	A1	10/2008	Cannell et al.	2010/0318319	A1	12/2010	Maierhofer
2008/0256814	A1	10/2008	Pettersson	2010/0321152	A1	12/2010	Argudyaev et al.
2008/0257023	A1	10/2008	Jordil et al.	2010/0325907	A1	12/2010	Tait
2008/0263411	A1	10/2008	Baney et al.	2011/0000095	A1	1/2011	Carlson
2008/0271332	A1	11/2008	Jordil et al.	2011/0001958	A1	1/2011	Bridges et al.
2008/0273758	A1	11/2008	Fuchs et al.	2011/0007305	A1	1/2011	Bridges et al.
2008/0282564	A1	11/2008	Pettersson	2011/0007326	A1	1/2011	Daxauer et al.
2008/0295349	A1	12/2008	Uhl et al.	2011/0013199	A1	1/2011	Siercks et al.
2008/0298254	A1	12/2008	Eidson	2011/0019155	A1	1/2011	Daniel et al.
2008/0302200	A1	12/2008	Tobey	2011/0023578	A1	2/2011	Grasser
2008/0309460	A1	12/2008	Jefferson et al.	2011/0025905	A1	2/2011	Tanaka
2008/0309546	A1	12/2008	Wakayama et al.	2011/0043515	A1	2/2011	Stathis
2009/0000136	A1	1/2009	Crampton	2011/0066781	A1	3/2011	Debelak et al.
2009/0010740	A1	1/2009	Ferrari et al.	2011/0094908	A1	4/2011	Trieu
2009/0013548	A1	1/2009	Ferrari	2011/0107611	A1	5/2011	Desforges et al.
2009/0016475	A1	1/2009	Rischar et al.	2011/0107612	A1	5/2011	Ferrari et al.
2009/0021351	A1	1/2009	Beniyama et al.	2011/0107614	A1	5/2011	Champ
2009/0031575	A1	2/2009	Tomelleri	2011/0111849	A1	5/2011	Sprague et al.
2009/0046140	A1	2/2009	Lashmet et al.	2011/0112786	A1	5/2011	Desforges et al.
2009/0046752	A1	2/2009	Bueche et al.	2011/0119025	A1	5/2011	Fetter et al.
2009/0046895	A1	2/2009	Pettersson et al.	2011/0123097	A1	5/2011	Van Coppenolle et al.
2009/0049704	A1	2/2009	Styles et al.	2011/0164114	A1	7/2011	Kobayashi et al.
2009/0051938	A1	2/2009	Miousset et al.	2011/0166824	A1	7/2011	Haisty et al.
2009/0083985	A1	4/2009	Ferrari	2011/0169924	A1	7/2011	Haisty et al.
				2011/0173823	A1	7/2011	Bailey et al.
				2011/0173827	A1	7/2011	Bailey et al.
				2011/0173828	A1	7/2011	York
				2011/0178755	A1	7/2011	York

(56)

References Cited

U.S. PATENT DOCUMENTS

2011/0178758 A1 7/2011 Atwell et al.
 2011/0178762 A1 7/2011 York
 2011/0178764 A1 7/2011 York
 2011/0178765 A1 7/2011 Atwell et al.
 2011/0188739 A1 8/2011 Lee et al.
 2011/0192043 A1 8/2011 Ferrari et al.
 2011/0273568 A1 11/2011 Lagassey et al.
 2011/0282622 A1 11/2011 Canter et al.
 2011/0288684 A1 11/2011 Farlow et al.
 2012/0019806 A1 1/2012 Becker et al.
 2012/0033069 A1 2/2012 Becker et al.
 2012/0035788 A1 2/2012 Trepagnier et al.
 2012/0035798 A1 2/2012 Barfoot et al.
 2012/0044476 A1 2/2012 Earhart et al.
 2012/0046820 A1 2/2012 Allard et al.
 2012/0069325 A1 3/2012 Schumann et al.
 2012/0069352 A1 3/2012 Ossig et al.
 2012/0070077 A1 3/2012 Ossig et al.
 2012/0113913 A1 5/2012 Tirola et al.
 2012/0133953 A1 5/2012 Ossig et al.
 2012/0140083 A1 6/2012 Schultz et al.
 2012/0140244 A1 6/2012 Gittinger et al.
 2012/0154786 A1 6/2012 Gosch et al.
 2012/0155744 A1 6/2012 Kennedy et al.
 2012/0169876 A1 7/2012 Reichert et al.
 2012/0181194 A1 7/2012 McEwan et al.
 2012/0197439 A1 8/2012 Wang et al.
 2012/0210678 A1 8/2012 Alcouloumre et al.
 2012/0217357 A1 8/2012 Franke
 2012/0229788 A1 9/2012 Schumann et al.
 2012/0260512 A1 10/2012 Kretschmer et al.
 2012/0260611 A1 10/2012 Jones
 2012/0262700 A1 10/2012 Schumann et al.
 2012/0287265 A1 11/2012 Schumann et al.
 2013/0010307 A1 1/2013 Greiner et al.
 2013/0025143 A1 1/2013 Bailey et al.
 2013/0025144 A1 1/2013 Briggs et al.
 2013/0027515 A1 1/2013 Vinther et al.
 2013/0062243 A1 3/2013 Chang et al.
 2013/0070250 A1 3/2013 Ditte et al.
 2013/0094024 A1 4/2013 Ruhland et al.
 2013/0097882 A1 4/2013 Bridges et al.
 2013/0125408 A1 5/2013 Atwell et al.
 2013/0162472 A1 6/2013 Najim et al.
 2013/0176453 A1 7/2013 Mate et al.
 2013/0201487 A1 8/2013 Ossig et al.
 2013/0205606 A1 8/2013 Briggs et al.
 2013/0212889 A9 8/2013 Bridges et al.
 2013/0218024 A1 8/2013 Boctor et al.
 2013/0222816 A1 8/2013 Briggs et al.
 2013/0300740 A1 11/2013 Snyder et al.
 2014/0002608 A1 1/2014 Atwell et al.
 2014/0015963 A1 1/2014 Klaas
 2014/0028805 A1 1/2014 Tohme
 2014/0049784 A1 2/2014 Woloschyn et al.
 2014/0063489 A1 3/2014 Steffey et al.
 2014/0078519 A1 3/2014 Steffey et al.
 2014/0120493 A1 5/2014 Levin
 2014/0226190 A1 8/2014 Bridges et al.
 2014/0240690 A1 8/2014 Newman et al.
 2014/0267623 A1 9/2014 Bridges et al.
 2014/0268108 A1 9/2014 Grau
 2014/0300906 A1 10/2014 Becker et al.
 2014/0362424 A1 12/2014 Bridges et al.
 2015/0015701 A1 1/2015 Yu
 2015/0029516 A1 1/2015 Neundorf
 2015/0085068 A1 3/2015 Becker et al.
 2015/0085301 A1 3/2015 Becker et al.
 2015/0109419 A1 4/2015 Vollrath et al.
 2015/0160342 A1 6/2015 Zweigle et al.
 2015/0160347 A1 6/2015 Zweigle et al.
 2015/0160348 A1 6/2015 Zweigle et al.
 2015/0229907 A1 8/2015 Bridges
 2015/0241204 A1 8/2015 Steffey et al.
 2015/0369917 A1 12/2015 Bridges et al.

2015/0373321 A1 12/2015 Bridges
 2015/0378023 A1 12/2015 Royo Royo et al.
 2016/0033643 A1 2/2016 Zweigle et al.
 2016/0047914 A1 2/2016 Zweigle et al.
 2016/0069670 A1 3/2016 Ruhland et al.
 2016/0073085 A1 3/2016 Hillebrand et al.
 2016/0073091 A1 3/2016 Hillebrand et al.
 2016/0073104 A1 3/2016 Hillebrand et al.

FOREIGN PATENT DOCUMENTS

AU 2005200937 A1 9/2006
 CN 2236119 Y 9/1996
 CN 1133969 A 10/1996
 CN 1307241 A 8/2001
 CN 2508896 Y 9/2002
 CN 2665668 Y 12/2004
 CN 1630804 A 6/2005
 CN 1630805 A 6/2005
 CN 1735789 A 2/2006
 CN 1812868 A 8/2006
 CN 1818537 A 8/2006
 CN 1838102 A 9/2006
 CN 1839293 A 9/2006
 CN 1853084 A 10/2006
 CN 1926400 A 3/2007
 CN 101024286 A 8/2007
 CN 101156043 A 4/2008
 CN 101163939 A 4/2008
 CN 101371099 A 2/2009
 CN 101416024 A 4/2009
 CN 101484828 A 7/2009
 CN 201266071 Y 7/2009
 CN 101506684 A 8/2009
 CN 101511529 A 8/2009
 DE 2216765 A1 4/1972
 DE 2950138 A1 6/1981
 DE 3227980 A1 5/1983
 DE 3245060 A1 7/1983
 DE 3340317 A1 8/1984
 DE 4027990 C1 2/1992
 DE 4222642 A1 1/1994
 DE 4340756 A1 6/1994
 DE 4303804 A1 8/1994
 DE 4445464 A1 7/1995
 DE 4410775 A1 10/1995
 DE 4412044 A1 10/1995
 DE 29622033 2/1997
 DE 19543763 A1 5/1997
 DE 19601875 A1 7/1997
 DE 19607345 A1 8/1997
 DE 19720049 A1 11/1998
 DE 19811550 A1 9/1999
 DE 19820307 A1 11/1999
 DE 19850118 A1 5/2000
 DE 19928958 A1 11/2000
 DE 10026357 A1 1/2002
 DE 20208077 U1 5/2002
 DE 10137241 A1 9/2002
 DE 10149750 A1 9/2002
 DE 10155488 A1 5/2003
 DE 10219054 A1 11/2003
 DE 10232028 A1 2/2004
 DE 10336458 A1 2/2004
 DE 10244643 A1 4/2004
 DE 20320216 U1 4/2004
 DE 10304188 A1 8/2004
 DE 10313223 A1 10/2004
 DE 10326848 A1 1/2005
 DE 202005000983 U1 3/2005
 DE 10361870 A1 7/2005
 DE 102004015668 B3 9/2005
 DE 102004028090 A1 12/2005
 DE 10114126 B4 8/2006
 DE 202006005643 U1 8/2006
 DE 102004010083 B4 11/2006
 DE 102005043931 A1 3/2007
 DE 102005056265 A1 5/2007
 DE 102006053611 A1 5/2007

(56)

References Cited

FOREIGN PATENT DOCUMENTS			JP	5827264	2/1983
DE	102005060967	A1 6/2007	JP	S58171291	A 10/1983
DE	102006023902	A1 11/2007	JP	59133890	A 8/1984
DE	102006024534	A1 11/2007	JP	61062885	A 3/1986
DE	102006035292	A1 1/2008	JP	S61157095	A 7/1986
DE	202006020299	U1 5/2008	JP	63135814	A 6/1988
DE	102007037162	A1 2/2009	JP	0357911	A 3/1991
DE	102008014274	A1 8/2009	JP	04115108	A 4/1992
DE	102008039838	A1 3/2010	JP	04225188	A1 8/1992
DE	102005036929	B4 6/2010	JP	04267214	A 9/1992
DE	102008062763	B3 7/2010	JP	0572477	A 3/1993
DE	102009001894	A1 9/2010	JP	06313710	A 11/1994
DE	102009035336	B3 11/2010	JP	1994313710	A 11/1994
DE	102009055988	B3 3/2011	JP	06331733	A 12/1994
DE	202010005042	U1 8/2011	JP	06341838	A 12/1994
DE	102010032723	B3 11/2011	JP	074950	A 1/1995
DE	102010032726	B3 11/2011	JP	07128051	A 5/1995
DE	102010033561	B3 12/2011	JP	7210586	A 8/1995
DE	102010032725	A1 1/2012	JP	07229963	A 8/1995
DE	202011051975	U1 2/2013	JP	0815413	A 1/1996
DE	102012107544	B3 5/2013	JP	0821714	A 1/1996
DE	102012109481	A1 4/2014	JP	08129145	A 5/1996
DE	102012112322	A1 6/2014	JP	08136849	A 5/1996
EP	0546784	A2 6/1993	JP	08262140	A 10/1996
EP	0667549	A2 8/1995	JP	0921868	A 1/1997
EP	0727642	A1 8/1996	JP	10213661	A 8/1998
EP	0730210	A1 9/1996	JP	1123993	A 1/1999
EP	0614517	A1 3/1997	JP	2001056275	A 8/1999
EP	0838696	A1 4/1998	JP	2000121724	A 4/2000
EP	0949524	A1 10/1999	JP	2000249546	A 9/2000
EP	1160539	A1 12/2001	JP	2000339468	A 12/2000
EP	1189124	A1 3/2002	JP	2001013001	A 1/2001
EP	0767357	B1 5/2002	JP	2001021303	A 1/2001
EP	1310764	A2 5/2003	JP	2011066211	A 3/2001
EP	1342989	A2 9/2003	JP	2001337278	A 12/2001
EP	1347267	A1 9/2003	JP	2003050128	A 2/2003
EP	1361414	A1 11/2003	JP	2003156330	A 5/2003
EP	1452279	A1 9/2004	JP	2003156562	A 5/2003
EP	1468791	A1 10/2004	JP	2003194526	A 7/2003
EP	1056987	B1 4/2005	JP	2003202215	A 7/2003
EP	1528410	A1 5/2005	JP	2003216255	A 7/2003
EP	1669713	A1 6/2006	JP	2003308205	A 10/2003
EP	1734425	A2 12/2006	JP	2004109106	A 4/2004
EP	1429109	A2 4/2007	JP	2004245832	A 9/2004
EP	1764579	B1 12/2007	JP	2004257927	A 9/2004
EP	1878543	A2 1/2008	JP	2004333398	A 11/2004
EP	1882895	A1 1/2008	JP	2004348575	A 12/2004
EP	1967930	A2 9/2008	JP	2005030937	A 2/2005
EP	2003419	A1 12/2008	JP	2005055226	A 3/2005
EP	2023077	A1 2/2009	JP	2005069700	A 3/2005
EP	2042905	A1 4/2009	JP	2005174887	A 6/2005
EP	2060530	A1 5/2009	JP	2005517908	A1 6/2005
EP	2068067	A1 6/2009	JP	2005215917	A 8/2005
EP	2068114	6/2009	JP	2005221336	A 8/2005
EP	2108917	A1 10/2009	JP	2005257510	A 9/2005
EP	2177868	A2 4/2010	JP	2006038683	A 2/2006
EP	2259013	A1 12/2010	JP	2006102176	A 4/2006
EP	2400261	A1 12/2011	JP	2006203404	A 8/2006
EP	2428764	A1 3/2012	JP	2006226948	A 8/2006
EP	2693300	A2 2/2014	JP	2006241833	A 9/2006
EP	2728306	A1 5/2014	JP	2006266821	A 10/2006
FR	2603228	A1 3/1988	JP	2006301991	A 11/2006
FR	2935043	A1 2/2010	JP	2007514943	A 6/2007
GB	894320	4/1962	JP	2007178943	A 7/2007
GB	1112941	5/1968	JP	2008076303	A 4/2008
GB	2222695	A 3/1990	JP	2008082707	A 4/2008
GB	2255648	A 11/1992	JP	2008096123	A 4/2008
GB	2336493	A 10/1999	JP	2008107286	A 5/2008
GB	2341203	A 3/2000	JP	2008304220	A 12/2008
GB	2388661	A 11/2003	JP	2009063339	A 3/2009
GB	2420241	A 5/2006	JP	2009524057	6/2009
GB	2447258	A 9/2008	JP	2009531674	A 9/2009
GB	2452033	A 2/2009	JP	2009229255	A 10/2009
JP	5581525	6/1955	JP	2009541758	A 11/2009
JP	575584	A 1/1982	JP	2010169405	A 8/2010
JP	58171291	A 1/1983	JP	2013516928	A 5/2013
			JP	2013517508	A 5/2013
			JP	2013117417	A 6/2013
			JP	2013543970	A 12/2013

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO 8801924 A1 3/1988
 WO 8905512 A1 6/1989
 WO 9208568 A1 5/1992
 WO 9711399 3/1997
 WO 9808050 A1 2/1998
 WO 9910706 A1 3/1999
 WO 0014474 A1 3/2000
 WO 0020880 A2 4/2000
 WO 0026612 A1 5/2000
 WO 0033149 A1 6/2000
 WO 0034733 A1 6/2000
 WO 0063645 A1 10/2000
 WO 0063681 A2 10/2000
 WO 0177613 A1 10/2001
 WO 02084327 A2 10/2002
 WO 02088855 A1 11/2002
 WO 02101323 A2 12/2002
 WO 2004096502 A1 11/2004
 WO 2005008271 A2 1/2005
 WO 2005059473 A2 6/2005
 WO 2005072917 A1 8/2005
 WO 2005075875 8/2005
 WO 2005100908 A1 10/2005
 WO 2005103863 US 11/2005
 WO 2006000552 A1 1/2006
 WO 2006014445 A1 2/2006
 WO 2006051264 A1 5/2006
 WO 2006053837 A1 5/2006
 WO 2007002319 A1 1/2007
 WO 2007012198 A1 2/2007
 WO 2007028941 3/2007
 WO 2007051972 A1 5/2007
 WO 2007087198 A1 8/2007
 WO 2007118478 A1 10/2007
 WO 2007125081 A1 11/2007
 WO 2007144906 A1 12/2007
 WO 2008019856 A1 2/2008
 WO 2008027588 A2 3/2008
 WO 2008047171 A1 4/2008
 WO 2008048424 A2 4/2008
 WO 2008052348 A1 5/2008
 WO 2008064276 A3 5/2008
 WO 2008066896 6/2008
 WO 2008068791 A1 6/2008
 WO 2008075170 A1 6/2008
 WO 2008121073 A1 10/2008
 WO 2008157061 A1 12/2008
 WO 2009001165 A1 12/2008
 WO 2009003225 A1 1/2009
 WO 2009016185 A1 2/2009
 WO 2009053085 A1 4/2009
 WO 2009083452 A1 7/2009
 WO 2009095384 A2 8/2009
 WO 2009123278 A1 10/2009
 WO 2009127526 A1 10/2009
 WO 2009130169 A1 10/2009
 WO 2009149740 A1 12/2009
 WO 2010015086 A1 2/2010
 WO 2010040742 A1 4/2010
 WO 2010092131 A1 8/2010
 WO 2010108089 A2 9/2010
 WO 2010108644 A1 9/2010
 WO 2010148525 A1 12/2010
 WO 2011000435 A1 1/2011
 WO 2011000955 A1 1/2011
 WO 2011021103 A1 2/2011
 WO 2011029140 A1 3/2011
 WO 2011057130 A2 5/2011
 WO 2011060899 A1 5/2011
 WO 2011002908 A1 6/2011
 WO 2011090829 A2 7/2011
 WO 2011090895 A1 7/2011
 WO 2012037157 A2 3/2012
 WO 2012038446 A1 3/2012
 WO 2012061122 A1 5/2012

WO 2012013525 A2 8/2012
 WO 2012103525 A2 8/2012
 WO 2012112683 A2 8/2012
 WO 2012125671 A1 9/2012
 WO 2012168322 A2 12/2012
 WO 2013112455 A1 8/2013
 WO 2013184340 A1 12/2013
 WO 2013186160 A1 12/2013
 WO 2013188026 A1 12/2013
 WO 2013190031 A1 12/2013
 WO 2014128498 A2 8/2014

OTHER PUBLICATIONS

Davidson, A. et al., "MonoSLAM: Real-Time Single Camera SLAM", IEEE Transactions on Pattern Analysis and Machine Intelligence, vol. 29, No. 6, Jun. 1, 2007, pp. 1052-1067, XP011179664.
 Gebre, Biruk A., et al., "Remotely Operated and Autonomous Mapping System (ROAMS)", Technologies for Practical Robot Applications, TEPA 2009, IEEE International Conference on Nov. 9, 2009, pp. 173-178, XP031570394.
 Harrison A. et al., "High Quality 3D Laser Ranging Under General Vehicle Motion", 2008 IEEE International Conference on Robotics and Automation, May 19-23, 2008, pp. 7-12, XP031340123.
 International Search Report and Written Opinion for Application No. PCT/US2014/069185 dated Jul. 14, 2015.
 May, S. et al., "Robust 3D-Mapping with Time-of-Flight Cameras", Intelligent Robots and Systems, IROS 2009, IEEE/RSJ International Conference on Oct. 10, 2009, pp. 1673-1678, XP031581042.
 Ohno, K. et al., "Real-Time Robot Trajectory Estimation and 3D Map Construction Using 3D Camera", Intelligent Robots and Systems, 2006 IEEE/RSJ International Conference on Oct. 1, 2006, pp. 5279-5285, XP031006974.
 Surmann, H. et al., "An Autonomous Mobile Robot with a 3D Laser Range Finder for 3D Exploration and Digitalization of Indoor Environments", Robotics and Autonomous Systems, Elsevier Science Publishers, vol. 45, No. 3-4, Dec. 31, 2003, pp. 181-198.
 Yan, R., et al., "3D Point Cloud Map Construction Based on Line Segments with Two Mutually Perpendicular Laser Sensors", 2013 13th International Conference on Control, Automation and Systems (ICCAS 2013), IEEE, Oct. 20, 2013, pp. 1114-1116.
 Ye, C. et al., "Characterization of a 2-D Laser Scanner for Mobile Robot Obstacle Negotiation" Proceedings / 2002 IEEE International Conference on Robotics and Automation, May 11-15, 2002, Washington, D.C., May 1, 2002, pp. 2512-2518, XP009169742.
 Dylan, Craig R., High Precision Makes the Massive Bay Bridge Project Work. Suspended in MidAir—Cover Story—Point of Beginning, Jan. 1, 2010, [online] http://www.pobonline.com/Articles/Cover_Story/BNP_GUID_9-5-2006_A_10000000000... [Retrieved 1/25/2].
 Electro-Optical Information Systems, "The Handy Handheld Digitizer" [online], [retrieved on Nov. 29, 2011], <http://vidibotics.com/htm/handy.htm>, 2 pages.
 Elstrom, M.D., et al., Stereo-Based Registration of LADAR and Color Imagery, Intelligent Robots and Computer Vision XVII: Algorithms, Techniques, and Active Vision, Boston, MA, USA, vol. 3522, Nov. 2, 1998, Nov. 3, 1998 (p. 343-354).
 14th International Forensic Science Symposium, Interpol—Lyon, France, Oct. 19-22, 2004, Review Papers, Edited by Dr. Niamh Nic Daeid, Forensic Science Unit, Univeristy of Strathclyde, Glasgow, UK; 585 pages.
 Bouvet, D., et al., "Precise 3-D Localization by Automatic Laser Theodolite and Odometer for Civil-Engineering Machines", Proceedings of the 2001 IEEE International Conference on Robotics and Automation. ICRA 2001. Seoul, Korea, May 21-26, 2001; IEEE, US.
 Cho, et al., Implementation of a Precision Time Protocol over Low Rate Wireless Personal Area Networks, IEEE, 2008. 8 pages.
 Cooklev, et al., An Implementation of IEEE 1588 Over IEEE 802.11b for Synchronization of Wireless Local Area Network Nodes, IEEE Transactions on Instrumentation and Measurement, vol. 56, No. 5, Oct. 2007, 8 pages.

(56)

References Cited

OTHER PUBLICATIONS

- FARO Laserscanner LS, Presentation Forensic Package, Policeschool of Hessen, Wiesbaden, Germany, Dec. 14, 2005; FARO Technologies, Copyright 2008, 17 pages.
- FARO Product Catalog; Faro Arm; 68 pages; Faro Technologies Inc. 2009; printed Aug. 3, 2009.
- Franklin, Paul F., What IEEE 1588 Means for Your Next T&M System Design, Keithley Instruments, Inc., [on-line] Oct. 19, 2010, <http://www.eetimes.com/General/DisplayPrintViewContent?contentItemId=4209746>, [Retrieved Oct. 21, 2010], 6 pages.
- Gebre, et al. "Remotely Operated and Autonomous Mapping System (ROAMS)." Technologies for Practical Robot Applications, 2009. Tepra 2009. IEEE International Conference on IEEE, Piscataway, NJ, USA. Nov. 9, 2009, pp. 173-178.
- Ghost 3D Systems, Authorized MicroScribe Solutions, FAQs—MicroScribe 3D Laser, MicroScan Tools, & related info, [online], [retrieved Nov. 29, 2011], http://microscribe.ghost3d.com/gt_microscan-3d_faqs.htm, 4 pages.
- Godin, G., et al., A Method for the Registration of Attributed Range Images, Copyright 2001, [Retrieved on Jan. 18, 2010 at 03:29 from IEEE Xplore]. p. 178-186.
- GoMeasure3D—Your source for all things measurement, Baces 3D 100 Series Portable CMM from GoMeasure3D, [online], [retrieved Nov. 29, 2011], <http://www.gomeasure3d.com/baces100.html>, 3 pages.
- Haag, et al., "Technical Overview and Application of 3D Laser Scanning for Shooting Reconstruction and Crime Scene Investigations", Presented at the American Academy of Forensic Sciences Scientific Meeting, Washington, D.C., Feb. 21, 2008; 71 pages.
- Horn, B.K.P., Closed-Form Solution of Absolute Orientation Using Unit Quaternions, J. Opt. Soc. Am. A., vol. 4., No. 4, Apr. 1987, pp. 629-642, ISSN 0740-3232.
- Ingensand, H., Dr., "Introduction to Geodetic Metrology", "Einführung in die Geodatische Messtechnik", Federal Institute of Technology Zurich, 2004, with English translation, 6 pages.
- Leica Geosystems, TruStory Forensic Analysis by Albuquerque Police Department, 2006, 2 pages.
- Spada, et al., IEEE 1588 Lowers Integration Costs in Continuous Flow Automated Production Lines, XP-002498255, ARC Insights, Insight # 2003-33MD&H, Aug. 20, 2003.
- Trimble—Trimble SPS630, SPS730 and SPS930 Universal Total Stations, [on-line] http://www.trimble.com/sps630_730_930.shtml (1 of 4), [Retrieved Jan. 26, 2010 8:50:29AM].
- "Scanner Basis Configuration for Riegl VQ-250", Riegl Company Webpage, Feb. 16, 2011 [retrieved on Apr. 19, 2013]. Retrieved from the internet; 3 pages.
- A. Hart; "Kinematic Coupling Interchangeability" Precision Engineering; vol. 28, No. 1; Jan. 1, 2004 pp. 1-15.
- ABB Flexible Automation AB: "Product Manual IRB 6400R M99, On-line Manual"; Sep. 13, 2006; XP00002657684; [Retrieved on Sep. 28, 2011]. Retrieved from the Internet: (See URL Below).
- Akca, Devrim, "Full Automated Registration of Laser Scanner Point Clouds", Institute of Geodesy and Photogrammetry, Swiss Federal Institute of Technology, Zuerich, Switzerland; Published Dec. 2003, 8 pages.
- Anonymous : So wird's gemacht: Mit T-DSL and Windows XP Home Edition gemeinsam ins Internet (Teil 3) Internet Citation, Jul. 2003, XP002364586, Retrieved from Internet: URL:<http://support.microsoft.com/kb/814538/DE/> [retrieved on Jan. 26, 2006].
- Bornaz, L., et al., "Multiple Scan Registration in Lidar Close-Range Applications," The International Archives of the Photogrammetry, Remote Sensing and Spatial Information Sciences, vol. XXXIV, Part 5/W12, Jul. 2003, pp. 72-77, XP002590306.
- Brenneke et al: "Using 3D laser range data for slam in outdoor environments." Proceedings of the 2003 IEEE/RSJ International Conference on Intelligent Robots and Systems. Las Vegas, NV Oct. 27-31, 2003; IEEE US, vol. 1, Oct. 27 2003, pp. 188-193.
- Brenneke, C., et al., "Using 3D Laser Range Data for Slam in Outdoor Environments", Proceedings of the 2003 IEEE/RSJ International Conference on Intelligent Robots and Systems. (IROS 2003); Las Vegas, NV, Oct. 27-31, 2003; [IEEE/RSJ International Confer.
- Decision Revoking the European Patent (Art. 101(3)(b) EPC) dated Aug. 14, 2013, filed in Opposition re Application No. 07 785 873.6/U.S. Pat. No. 2 062 069, Proprietor: Faro Technologies, Inc., filed by Leica Geosystem AG on Feb. 5, 2013, 12 pages.
- EO Edmund Optics "Silicon Detectors" (5 pages) 2013 Edmund Optics, Inc. <http://www.edmundoptics.com/electrooptics/detector-components/silicon-detectors/1305>[Oct. 15, 2013 10:14:53 AM].
- FARO Laser Scanner LS, Recording Reality's Digital Fingerprint, The Measure of Success, Rev. Aug 22, 2005, 16 pages.
- Hart, A., "Kinematic Coupling Interchangeability", Precision Engineering, vol. 28, No. 1, Jan. 1, 2004, pp. 1-15, XP55005507, ISSN: 0141-6359, DOI: 10.1016/S0141-6359(03)00071-0.
- Howard, et al., "Virtual Environments for Scene of Crime Reconstruction and Analysis", Advanced Interfaces Group, Department of Computer Science, University of Manchester, Manchester, UK, Feb. 28, 2000.
- Huebner, S.F., "Sniper Shooting Technique", "Scharfschützen Schiebtechnik", Copyright by C.A. Civil Arms Verlag GmbH, Lichtenwald 1989, Alle Rechte vorbehalten, pp. 11-17.
- HYDROpro Navigation, Hydrographic Survey Software, Trimble, www.trimble.com, Copyright 1997-2003.
- Information on Electro-Optical Information Systems; EOIS 3D Mini-Moire C.M.M. Sensor for Non-Contact Measuring & Surface Mapping; Direct Dimensions, Jun. 1995.
- iQsun Laserscanner Brochure, 2 Pages, Apr. 2005.
- It is Alive in the Lab, Autodesk University, Fun with the Immersion MicroScribe Laser Scanner, [online], [retrieved Nov. 29, 2011], http://labs.blogs.com/its_alive_in_the_lab/2007/11/fun-with-the-im.html; 3 pages.
- J.Geng "Structured-Light 3D Surface Imaging: A Tutorial," Advances in Optics and Photonics 3; Mar. 31, 2011, pp. 128-160; IEEE Intelligent Transportation System Society; 2011 Optical Society of America.
- Jasiobedzki, Piotr, "Laser Eye—A New 3D Sensor for Active Vision", SPIE—Sensor Fusion VI, vol. 2059, Sep. 7, 1993, pp. 316-321, XP00262856, Boston, U.S.A., Retrieved from the Internet: URL:<http://scitation.aip.org/getpdf/servlet/Ge>.
- Jasperneite, et al., Enhancements to the Time Synchronization Standard IEEE-1588 for a System of Cascaded Bridges, IEEE, 2004.
- Jgeng "DLP-Based Structured Light 3D Imaging Technologies and Applications" (15 pages) Emerging Digital Micromirror Device Based Systems and Application III; edited by Michael R. Douglass, Patrick I. Oden, Proc. of SPIE, vol. 7932, 79320B; (2011) SPIE.
- Kreon Laser Scanners, Getting the Best in Cutting Edge 3D Digitizing Technology, B3-D MCAD Consulting/Sales [online], [retrieved Nov. 29, 2011], <http://www.b3-d.com/Kreon.html>.
- Langford, et al., "Practical Skills in Forensic Science", Pearson Education Limited, Essex, England, First Published 2005, Forensic Chemistry.
- Laser Reverse Engineering with Microscribe, [online], [retrieved Nov. 29, 2011], http://www.youtube.com/watch?v=8VRz_2aEJ4E&feature=Playlist&p=F63ABF74F3ODC81B&playnext=1&playnext_from=PL&index=1.
- Leica Geosystems TruStory Forensic Analysis by Albuquerque Police Department, 2006.
- Leica Geosystems, FBI Crime Scene Case Study, Tony Grissim, Feb. 2006; 11 pages.
- Leica Geosystems: "Leica Rugby 55 Designed for Interior Built for Construction", Jan. 1, 2009, XP002660558, Retrieved from the Internet: URL:http://www.leica-geosystems.com/downloads123/zz/lasers/Rugby%2055/brochures/Leica_Rugby_55_brochure_en.pdf [re.
- Leica TPS800 Performance Series—Equipment List, 2004.
- Merriam-Webster (m-w.com), "Interface". 2012. <http://www.merriam-webster.com/dictionary/interface>.
- Merriam-Webster (m-w.com), "Parts". 2012. <http://www.merriam-webster.com/dictionary/parts>.
- Merriam-Webster (m-w.com), "Traverse". 2012. <http://www.merriam-webster.com/dictionary/traverse>.

(56)

References Cited

OTHER PUBLICATIONS

Mg Lee; "Compact 3D LIDAR based on optically coupled horizontal and vertical Scanning mechanism for the autonomous navigation of robots" (13 pages) vol. 8037; downloaded from <http://proceedings.spiedigitallibrary.org/> on Jul. 2, 2013.

MicroScan 3D User Guide, RSI GmbH, 3D Systems & Software, Oberursel, Germany, email: info@rsi-gmbh.de, Copyright RSI Roland Seifert Imaging GmbH 2008.

Moog Components Group "Technical Brief; Fiber Optic Rotary Joints" Document No. 303 (6 pages) Mar. 2008; MOOG, Inc. 2008 Canada; Focal Technologies.

MOOG Components Group; "Fiber Optic Rotary Joints; Product Guide" (4 pages) Dec. 2010; MOOG, Inc. 2010.

P Ben-Tzvi, et al "Extraction of 3D Images Using Pitch-Actuated 2D Laser Range Finder for Robotic Vision" (6 pages) BNSDOCID <XP 31840390A_1_>, Oct. 15, 2010.

Provision of the minutes in accordance with Rule 124(4) EPC dated Aug. 14, 2013, filed in Opposition re Application No. 07 785 873.6/U.S. Pat. No. 2 062 069, Proprietor: Faro Technologies, Inc., filed by Leica Geosystem AG on Feb. 5, 2013.

Romer "Romer Absolute Arm Maximum Performance Portable Measurement" (Printed Oct. 2010); Hexagon Metrology, Inc. <http://us.ROMER.com>; Hexagon Metrology, Inc. 2010.

Romer Measuring Arms; Portable CMMs for the shop floor; 20 pages; Hexagon Metrology, Inc. (2009) <http://us.ROMER.com>.

RW Boyd "Radiometry and the Detection of Optical Radiation" (pp. 20-23) 1983 Jon Wiley & Sons, Inc.

Sauter, et al., Towards New Hybrid Networks for Industrial Automation, IEEE, 2009.

Se, et al., "Instant Scene Modeler for Crime Scene Reconstruction", MDA, Space Missions, Ontario, Canada, Copyright 2005, IEEE; 8 pages.

Surman et al. "An autonomous mobile robot with a 3D laser range finder for 3D exploration and digitalization of indoor environments." Robotics and Autonomous Systems vol. 45 No. 3-4, Dec. 31, 2003, pp. 181-198. Amsterdam, Netherlands.

The Scene, Journal of the Association for Crime Scene Reconstruction, Apr.-Jun. 2006, vol. 12, Issue 2; 31 pages.

Umeda, K., et al., Registration of Range and Color Images Using Gradient Constraints and Range Intensity Images, Proceedings of the 17th International Conference on Pattern Recognition (ICPR'04), Copyright 2010 IEEE. [Retrieved online Jan. 28, 2010—IEEE.

Williams, J.A., et al., Evaluation of a Novel Multiple Point Set Registration Algorithm, Copyright 2000, [Retrieved on Jan. 18, 2010 at 04:10 from IEEE Xplore], pp. 1006-1010.

Willoughby, P., "Elastically Averaged Precision Alignment", In: "Doctoral Thesis", Jun. 1, 2005, Massachusetts Institute of Technology, XP55005620, abstract 1.1 Motivation, Chapter 3, Chapter 6.

Yk Cho, et al. "Light-weight 3D LADAR System for Construction Robotic Operations" (pp. 237-244); 26th International Symposium on Automation and Robotics in Construction (ISARC 2009), Jun. 24, 2009.

Creaform Metrology Solutions, "Handy Scan 3D—The Truly Portable Metrology-Grade 3D Scanners" brochure, 7 pages.

Creaform, "Creaform Releases Completely Re-Engineered Handyscan 3D Portable Scanners", May 5, 2014, 1 page.

Mandy, Yousef B., et al; "Projector Calibration Using Passive Stereo and Triangulation"; International Journal of Future Computer and Communication; vol. 2; No. 5; 385-390; Oct. 2013; 6 pgs.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6A

FIG. 6B

FIG. 6C

800




FIG. 7




FIG. 8A




FIG. 8B




FIG. 8C






FIG. 9






FIG. 12




FIG. 13






FIG. 14A



SCANNER
FRAME OF REFERENCE

FIG. 14B



OBJECT
FRAME OF REFERENCE

FIG. 14C




FIG. 15

**USING DEPTH-CAMERA IMAGES TO
SPEED REGISTRATION OF
THREE-DIMENSIONAL SCANS**

CROSS-REFERENCE TO RELATED
APPLICATIONS

The present application claims the benefit of International Patent Application No. PCT/IB2013/003082, filed Sep. 27, 2013, which claims the benefit of German Patent Application No. 10 2012 109 481.0, filed Oct. 5, 2012 and of U.S. Patent Application No. 61/716,845, filed Oct. 22, 2012, the contents of all of which are incorporated by reference herein.

BACKGROUND OF THE INVENTION

U.S. Pat. No. 8,705,016 ('016) describes a laser scanner which, through use of a rotatable mirror, emits a light beam into its environment to generate a three-dimensional (3D) scan. The contents of this patent are incorporated herein by reference.

The subject matter disclosed herein relates to use of a 3D laser scanner time-of-flight (TOF) coordinate measurement device. A 3D laser scanner of this type steers a beam of light to a non-cooperative target such as a diffusely scattering surface of an object. A distance meter in the device measures a distance to the object, and angular encoders measure the angles of rotation of two axles in the device. The measured distance and two angles enable a processor in the device to determine the 3D coordinates of the target.

A TOF laser scanner is a scanner in which the distance to a target point is determined based on the speed of light in air between the scanner and a target point. Laser scanners are typically used for scanning closed or open spaces such as interior areas of buildings, industrial installations and tunnels. They may be used, for example, in industrial applications and accident reconstruction applications. A laser scanner optically scans and measures objects in a volume around the scanner through the acquisition of data points representing object surfaces within the volume. Such data points are obtained by transmitting a beam of light onto the objects and collecting the reflected or scattered light to determine the distance, two-angles (i.e., an azimuth and a zenith angle), and optionally a gray-scale value. This raw scan data is collected, stored and sent to a processor or processors to generate a 3D image representing the scanned area or object.

Generating an image requires at least three values for each data point. These three values may include the distance and two angles, or may be transformed values, such as the x, y, z coordinates. In an embodiment, an image is also based on a fourth gray-scale value, which is a value related to irradiance of scattered light returning to the scanner.

Most TOF scanners direct the beam of light within the measurement volume by steering the light with a beam steering mechanism. The beam steering mechanism includes a first motor that steers the beam of light about a first axis by a first angle that is measured by a first angular encoder (or other angle transducer). The beam steering mechanism also includes a second motor that steers the beam of light about a second axis by a second angle that is measured by a second angular encoder (or other angle transducer).

Many contemporary laser scanners include a camera mounted on the laser scanner for gathering camera digital images of the environment and for presenting the camera digital images to an operator of the laser scanner. By viewing the camera images, the operator of the scanner can determine the field of view of the measured volume and

adjust settings on the laser scanner to measure over a larger or smaller region of space. In addition, the camera digital images may be transmitted to a processor to add color to the scanner image. To generate a color scanner image, at least three positional coordinates (such as x, y, z) and three color values (such as red, green, blue "RGB") are collected for each data point.

A 3D image of a scene may require multiple scans from different registration positions. The overlapping scans are registered in a joint coordinate system, for example, as described in U.S. Published Patent Application No. 2012/0069352 ('352), the contents of which are incorporated herein by reference. Such registration is performed by matching targets in overlapping regions of the multiple scans. The targets may be artificial targets such as spheres or checkerboards or they may be natural features such as corners or edges of walls. Some registration procedures involve relatively time-consuming manual procedures such as identifying by a user each target and matching the targets obtained by the scanner in each of the different registration positions. Some registration procedures also require establishing an external "control network" of registration targets measured by an external device such as a total station. The registration method disclosed in '352 eliminates the need for user matching of registration targets and establishing of a control network.

However, even with the simplifications provided by the methods of '352, it is today still difficult to remove the need for a user to carry out the manual registration steps as described above. In a typical case, only 30% of 3D scans can be automatically registered to scans taken from other registration positions. Today such registration is seldom carried out at the site of the 3D measurement but instead in an office following the scanning procedure. In a typical case, a project requiring a week of scanning requires two to five days to manually register the multiple scans. This adds to the cost of the scanning project. Furthermore, the manual registration process sometimes reveals that the overlap between adjacent scans was insufficient to provide proper registration. In other cases, the manual registration process may reveal that certain sections of the scanning environment have been omitted. When such problems occur, the operator must return to the site to obtain additional scans. In some cases, it is not possible to return to a site. A building that was available for scanning at one time may be impossible to access at a later time. A forensics scene of an automobile accident or a homicide is often not available for taking of scans for more than a short time after the incident.

Accordingly, while existing 3D scanners are suitable for their intended purposes, what is needed is a 3D scanner having certain features of embodiments of the present invention.

BRIEF DESCRIPTION OF THE INVENTION

According to one aspect of the invention, a three-dimensional (3D) measuring device is provided including: a processor system including at least one of a 3D scanner controller, an external computer, and a cloud computer configured for remote network access; a 3D scanner having a first light source, a first beam steering unit, a first angle measuring device, a second angle measuring device, and a first light receiver, the first light source configured to emit a first beam of light, the first beam steering unit configured to steer the first beam of light to a first direction onto a first object point, the first direction determined by a first angle of rotation about a first axis and a second angle of rotation

about a second axis, the first angle measuring device configured to measure the first angle of rotation and the second angle measuring device configured to measure the second angle of rotation, the first light receiver configured to receive first reflected light, the first reflected light being a portion of the first beam of light reflected by the first object point, the first light receiver configured to produce a first electrical signal in response to the first reflected light, the first light receiver configured to cooperate with the processor system to determine a first distance to the first object point based at least in part on the first electrical signal, the 3D scanner configured to cooperate with the processor system to determine 3D coordinates of the first object point based at least in part on the first distance, the first angle of rotation and the second angle of rotation; a moveable platform configured to carry the 3D scanner; a depth camera configured to move in conjunction with the 3D scanner; wherein the processor system is responsive to executable instructions which when executed by the processor system is operable to: cause the 3D scanner, while fixedly located at a first registration position, to cooperate with the processor system to determine 3D coordinates of a first collection of points on an object surface; cause the 3D measuring device, while moving from the first registration position to a second registration position, to cooperate with the processor system to obtain a plurality of depth-camera image sets, each of the plurality of depth-camera image sets being a set of 3D coordinates of points on the object surface, each of the plurality of depth-camera image sets being collected by the 3D measuring device at a different position relative to the first registration position; determine a first translation value corresponding to a first translation direction, a second translation value corresponding to a second translation direction, and a first rotation value corresponding to a first orientational axis, wherein the first translation value, the second translation value, and the first rotation value are determined based at least in part on a fitting of the plurality of depth-camera image sets according to a first mathematical criterion; cause the 3D scanner, while fixedly located at the second registration position, to cooperate with the processor system to determine 3D coordinates of a second collection of points on the object surface; identify a correspondence among registration targets present in both the first collection of points and the second collection of points, the correspondence based at least in part on the first translation value, the second translation value, and the first rotation value; and determine 3D coordinates of a registered 3D collection of points based at least in part on a second mathematical criterion, the determined correspondence among the registration targets, the 3D coordinates of the first collection of points, and the 3D coordinates of the second collection of points.

In a further aspect of the invention, a method for measuring and registering three-dimensional (3D) coordinates is provided including: providing a 3D measuring device that includes a processor system, a 3D scanner, a depth camera, and a moveable platform, the processor system having at least one of a 3D scanner controller, an external computer, and a cloud computer configured for remote network access, the 3D scanner having a first light source, a first beam steering unit, a first angle measuring device, a second angle measuring device, and a first light receiver, the first light source configured to emit a first beam of light, the first beam steering unit configured to steer the first beam of light to a first direction onto a first object point, the first direction determined by a first angle of rotation about a first axis and a second angle of rotation about a second axis, the first angle

measuring device configured to measure the first angle of rotation and the second angle measuring device configured to measure the second angle of rotation, the first light receiver configured to receive first reflected light, the first reflected light being a portion of the first beam of light reflected by the first object point, the first light receiver configured to produce a first electrical signal in response to the first reflected light, the first light receiver configured to cooperate with the processor system to determine a first distance to the first object point based at least in part on the first electrical signal, the 3D scanner configured to cooperate with the processor system to determine 3D coordinates of the first object point based at least in part on the first distance, the first angle of rotation and the second angle of rotation, a depth camera configured to move in conjunction with the 3D scanner; the moveable platform configured to carry the 3D scanner and the depth camera; determining with the processor system, in cooperation with the 3D scanner, 3D coordinates of a first collection of points on an object surface while the 3D scanner is fixedly located at a first registration position; obtaining by the 3D measuring device in cooperation with the processor system a plurality of depth-camera image sets, each of the plurality of depth-camera image sets being collected as the 3D measuring device moves from the first registration position to a second registration position, each of the plurality of depth-camera image sets being collected by the 3D measuring device at a different position relative to the first registration position; determining by the processor system a first translation value corresponding to a first translation direction, a second translation value corresponding to a second translation direction, and a first rotation value corresponding to a first orientational axis, wherein the first translation value, the second translation value, and the first rotation value are determined based at least in part on a fitting of the plurality of depth-camera image sets according to a first mathematical criterion; determining with the processor system, in cooperation with the 3D scanner, 3D coordinates of a second collection of points on the object surface while the 3D scanner is fixedly located at the second registration position; identifying by the processor system a correspondence among registration targets present in both the first collection of points and the second collection of points, the correspondence based at least in part on the first translation value, the second translation value, and the first rotation value; determining 3D coordinates of a registered 3D collection of points based at least in part on a second mathematical criterion, the correspondence among registration targets, the 3D coordinates of the first collection of points, and the 3D coordinates of the second collection of points; and storing the 3D coordinates of the registered 3D collection of points.

These and other advantages and features will become more apparent from the following description taken in conjunction with the drawings.

BRIEF DESCRIPTION OF THE DRAWING

The subject matter, which is regarded as the invention, is particularly pointed out and distinctly claimed in the claims at the conclusion of the specification. The foregoing and other features, and advantages of the invention are apparent from the following detailed description taken in conjunction with the accompanying drawings in which:

FIG. 1 is a perspective view of a laser scanner in accordance with an embodiment of the invention;

FIG. 2 is a side view of the laser scanner illustrating a method of measurement according to an embodiment;

5

FIG. 3 is a schematic illustration of the optical, mechanical, and electrical components of the laser scanner according to an embodiment;

FIG. 4 depicts a planar view of a 3D scanned image according to an embodiment;

FIG. 5 depicts an embodiment of a panoramic view of a 3D scanned image generated by mapping a planar view onto a sphere according to an embodiment;

FIGS. 6A, 6B and 6C depict embodiments of a 3D view of a 3D scanned image according to an embodiment;

FIG. 7 depicts an embodiment of a 3D view made up of an image of the object of FIG. 6B but viewed from a different perspective and shown only partially, according to an embodiment;

FIG. 8A is a perspective view of a 3D measuring device according to an embodiment;

FIG. 8B is a front view of a camera used to collect depth-camera image data while the 3D measuring device moves along a horizontal plane according to an embodiment;

FIG. 8C is a perspective view of a 3D measuring device according to an embodiment;

FIG. 9 is a block diagram depicting a processor system according to an embodiment;

FIG. 10 is a schematic representation of a 3D scanner measuring an object from two registration positions according to an embodiment;

FIG. 11 is a schematic representation of a depth camera capturing depth-camera images at a plurality of intermediate positions as the 3D measuring device is moved along a horizontal plane, according to an embodiment;

FIG. 12 shows the depth camera capturing depth-camera images at a plurality of intermediate positions as the 3D measuring device is moved along a horizontal plane, according to an embodiment;

FIG. 13 shows the depth camera capturing depth-camera images at a plurality of intermediate positions as the 3D measuring device is moved along a horizontal plane, according to an embodiment;

FIGS. 14A, 14B and 14C illustrate a method for finding changes in the position and orientation of the 3D scanner over time according to an embodiment; and

FIG. 15 includes steps in a method for measuring and registering 3D coordinates with a 3D measuring device according to an embodiment.

The detailed description explains embodiments of the invention, together with advantages and features, by way of example with reference to the drawings.

DETAILED DESCRIPTION OF THE INVENTION

The present invention relates to a 3D measuring device having a 3D scanner and a depth camera. The depth camera may be an integral part of the 3D scanner or a separate camera unit. The 3D measuring device is used in two modes, a first mode in which the 3D scanner obtains 3D coordinates of an object surface over a 3D region of space and a second mode in which depth-camera images are obtained as the camera is moved between positions at which 3D scans are taken. The depth-camera images are used together with the 3D scan data from the 3D scanner to provide automatic registration of the 3D scans.

Referring now to FIGS. 1-3, a laser scanner 20 is shown for optically scanning and measuring the environment surrounding the laser scanner 20. The laser scanner 20 has a measuring head 22 and a base 24. The measuring head 22 is

6

mounted on the base 24 such that the laser scanner 20 may be rotated about a vertical axis 23. In one embodiment, the measuring head 22 includes a gimbal point 27 that is a center of rotation about the vertical axis 23 and a horizontal axis 25.

The measuring head 22 has a rotary mirror 26, which may be rotated about the horizontal axis 25. The rotation about the vertical axis may be about the center of the base 24. The terms vertical axis and horizontal axis refer to the scanner in its normal upright position. It is possible to operate a 3D coordinate measurement device on its side or upside down, and so to avoid confusion, the terms azimuth axis and zenith axis may be substituted for the terms vertical axis and horizontal axis, respectively. The term pan axis or standing axis may also be used as an alternative to vertical axis.

The measuring head 22 is further provided with an electromagnetic radiation emitter, such as light emitter 28, for example, that emits an emitted light beam 30. In one embodiment, the emitted light beam 30 is a coherent light beam such as a laser beam. The laser beam may have a wavelength range of approximately 300 to 1600 nanometers, for example 790 nanometers, 905 nanometers, 1550 nm, or less than 400 nanometers. It should be appreciated that other electromagnetic radiation beams having greater or smaller wavelengths may also be used. The emitted light beam 30 is amplitude or intensity modulated, for example, with a sinusoidal waveform or with a rectangular waveform. The emitted light beam 30 is emitted by the light emitter 28 onto the rotary mirror 26, where it is deflected to the environment. A reflected light beam 32 is reflected from the environment by an object 34. The reflected or scattered light is intercepted by the rotary mirror 26 and directed into a light receiver 36. The directions of the emitted light beam 30 and the reflected light beam 32 result from the angular positions of the rotary mirror 26 and the measuring head 22 about the axes 25 and 23, respectively. These angular positions in turn depend on the corresponding rotary drives or motors.

Coupled to the light emitter 28 and the light receiver 36 is a controller 38. The controller 38 determines, for a multitude of measuring points X, a corresponding number of distances d between the laser scanner 20 and the points X on object 34. The distance to a particular point X is determined based at least in part on the speed of light in air through which electromagnetic radiation propagates from the device to the object point X. In one embodiment the phase shift of modulation in light emitted by the laser scanner 20 and the point X is determined and evaluated to obtain a measured distance d.

The speed of light in air depends on the properties of the air such as the air temperature, barometric pressure, relative humidity, and concentration of carbon dioxide. Such air properties influence the index of refraction n of the air. The speed of light in air is equal to the speed of light in vacuum c divided by the index of refraction. In other words, $c_{air} = c/n$. A laser scanner of the type discussed herein is based on the time-of-flight (TOF) of the light in the air (the round-trip time for the light to travel from the device to the object and back to the device). Examples of TOF scanners include scanners that measure round trip time using the time interval between emitted and returning pulses (pulsed TOF scanners), scanners that modulate light sinusoidally and measure phase shift of the returning light (phase-based scanners), as well as many other types. A method of measuring distance based on the time-of-flight of light depends on the speed of light in air and is therefore easily distinguished from methods of measuring distance based on triangulation. Triangulation-based methods involve projecting light from a light source along a particular direction and then intercepting the

light on a camera pixel along a particular direction. By knowing the distance between the camera and the projector and by matching a projected angle with a received angle, the method of triangulation enables the distance to the object to be determined based on one known length and two known angles of a triangle. The method of triangulation, therefore, does not directly depend on the speed of light in air.

In one mode of operation, the scanning of the volume around the laser scanner **20** takes place by rotating the rotary mirror **26** relatively quickly about axis **25** while rotating the measuring head **22** relatively slowly about axis **23**, thereby moving the assembly in a spiral pattern. In an exemplary embodiment, the rotary mirror rotates at a maximum speed of 5820 revolutions per minute. For such a scan, the gimbal point **27** defines the origin of the local stationary reference system. The base **24** rests in this local stationary reference system.

In addition to measuring a distance *d* from the gimbal point **27** to an object point *X*, the scanner **20** may also collect gray-scale information related to the received optical power (equivalent to the term "brightness.") The gray-scale value may be determined at least in part, for example, by integration of the bandpass-filtered and amplified signal in the light receiver **36** over a measuring period attributed to the object point *X*.

The measuring head **22** may include a display device **40** integrated into the laser scanner **20**. The display device **40** may include a graphical touch screen **41**, as shown in FIG. **1**, which allows the operator to set the parameters or initiate the operation of the laser scanner **20**. For example, the screen **41** may have a user interface that allows the operator to provide measurement instructions to the device, and the screen may also display measurement results.

The laser scanner **20** includes a carrying structure **42** that provides a frame for the measuring head **22** and a platform for attaching the components of the laser scanner **20**. In one embodiment, the carrying structure **42** is made from a metal such as aluminum. The carrying structure **42** includes a traverse member **44** having a pair of walls **46**, **48** on opposing ends. The walls **46**, **48** are parallel to each other and extend in a direction opposite the base **24**. Shells **50**, **52** are coupled to the walls **46**, **48** and cover the components of the laser scanner **20**. In the exemplary embodiment, the shells **50**, **52** are made from a plastic material, such as polycarbonate or polyethylene for example. The shells **50**, **52** cooperate with the walls **46**, **48** to form a housing for the laser scanner **20**.

On an end of the shells **50**, **52** opposite the walls **46**, **48** a pair of yokes **54**, **56** are arranged to partially cover the respective shells **50**, **52**. In the exemplary embodiment, the yokes **54**, **56** are made from a suitably durable material, such as aluminum for example, that assists in protecting the shells **50**, **52** during transport and operation. The yokes **54**, **56** each includes a first arm portion **58** that is coupled, such as with a fastener for example, to the traverse **44** adjacent the base **24**. The arm portion **58** for each yoke **54**, **56** extends from the traverse **44** obliquely to an outer corner of the respective shell **50**, **54**. From the outer corner of the shell, the yokes **54**, **56** extend along the side edge of the shell to an opposite outer corner of the shell. Each yoke **54**, **56** further includes a second arm portion that extends obliquely to the walls **46**, **48**. It should be appreciated that the yokes **54**, **56** may be coupled to the traverse **42**, the walls **46**, **48** and the shells **50**, **54** at multiple locations.

The pair of yokes **54**, **56** cooperate to circumscribe a convex space within which the two shells **50**, **52** are arranged. In the exemplary embodiment, the yokes **54**, **56**

cooperate to cover all of the outer edges of the shells **50**, **54**, while the top and bottom arm portions project over at least a portion of the top and bottom edges of the shells **50**, **52**. This provides advantages in protecting the shells **50**, **52** and the measuring head **22** from damage during transportation and operation. In other embodiments, the yokes **54**, **56** may include additional features, such as handles to facilitate the carrying of the laser scanner **20** or attachment points for accessories for example.

On top of the traverse **44**, a prism **60** is provided. The prism extends parallel to the walls **46**, **48**. In the exemplary embodiment, the prism **60** is integrally formed as part of the carrying structure **42**. In other embodiments, the prism **60** is a separate component that is coupled to the traverse **44**. When the mirror **26** rotates, during each rotation the mirror **26** directs the emitted light beam **30** onto the traverse **44** and the prism **60**. Due to non-linearities in the electronic components, for example in the light receiver **36**, the measured distances *d* may depend on signal strength, which may be measured in optical power entering the scanner or optical power entering optical detectors within the light receiver **36**, for example. In an embodiment, a distance correction is stored in the scanner as a function (possibly a nonlinear function) of distance to a measured point and optical power (generally unscaled quantity of light power sometimes referred to as "brightness") returned from the measured point and sent to an optical detector in the light receiver **36**. Since the prism **60** is at a known distance from the gimbal point **27**, the measured optical power level of light reflected by the prism **60** may be used to correct distance measurements for other measured points, thereby allowing for compensation to correct for the effects of environmental variables such as temperature. In the exemplary embodiment, the resulting correction of distance is performed by the controller **38**.

In an embodiment, the base **24** is coupled to a swivel assembly (not shown) such as that described in commonly owned U.S. Pat. No. 8,705,012 ('012), which is incorporated by reference herein. The swivel assembly is housed within the carrying structure **42** and includes a motor that is configured to rotate the measuring head **22** about the axis **23**.

An auxiliary image acquisition device **66** may be a device that captures and measures a parameter associated with the scanned volume or the scanned object and provides a signal representing the measured quantities over an image acquisition area. The auxiliary image acquisition device **66** may be, but is not limited to, a pyrometer, a thermal imager, an ionizing radiation detector, or a millimeter-wave detector. In an embodiment, the auxiliary image acquisition device **66** is a color camera.

In an embodiment, a central color camera (first image acquisition device) **112** is located internally to the scanner and may have the same optical axis as the 3D scanner device. In this embodiment, the first image acquisition device **112** is integrated into the measuring head **22** and arranged to acquire images along the same optical pathway as emitted light beam **30** and reflected light beam **32**. In this embodiment, the light from the light emitter **28** reflects off a fixed mirror **116** and travels to dichroic beam-splitter **118** that reflects the light **117** from the light emitter **28** onto the rotary mirror **26**. The dichroic beam-splitter **118** allows light to pass through at wavelengths different than the wavelength of light **117**. For example, the light emitter **28** may be a near infrared laser light (for example, light at wavelengths of 780 nm or 1150 nm), with the dichroic beam-splitter **118** configured to reflect the infrared laser light while allowing visible light (e.g., wavelengths of 400 to 700 nm) to transmit

through. In other embodiments, the determination of whether the light passes through the beam-splitter **118** or is reflected depends on the polarization of the light. The digital camera **112** obtains 2D images of the scanned area to capture color data to add to the scanned image. In the case of a built-in color camera having an optical axis coincident with that of the 3D scanning device, the direction of the camera view may be easily obtained by simply adjusting the steering mechanisms of the scanner—for example, by adjusting the azimuth angle about the axis **23** and by steering the mirror **26** about the axis **25**.

FIG. **4** depicts an example of a planar view of a 3D scanned image **400**. The planar view depicted in FIG. **4** maps an image based on direct mapping of data collected by the scanner. The scanner collects data in a spherical pattern but with data points collected near the poles more tightly compressed than those collected nearer the horizon. In other words, each point collected near a pole represents a smaller solid angle than does each point collected nearer the horizon. Since data from the scanner may be directly represented in rows and column, data in a planar image is conveniently presented in a rectilinear format, as shown in FIG. **4**. With planar mapping described above, straight lines appear to be curved, as for example the straight fence railings **420** that appear curved in the planar view of the 3D image. The planar view may be a 3D unprocessed scanned image displaying just the gray-scale values received from the distance sensor arranged in columns and rows as they were recorded. In addition, the 3D unprocessed scanned image of the planar view may be in full resolution or reduced resolution depending on system characteristics (e.g., display device, storage, processor). The planar view may be a 3D processed scanned image that depicts either gray-scale values (resulting from the light irradiance measured by the distance sensor for each pixel) or color values (resulting from camera images which have been mapped onto the scan). Although the planar view extracted from the 3D scanner is ordinarily a gray-scale or color image, FIG. **4** is shown as a line drawing for clarity in document reproduction. The user interface associated with the display unit, which may be integral to the laser scanner, may provide a point selection mechanism, which in FIG. **4** is the cursor **410**. The point selection mechanism may be used to reveal dimensional information about the volume of space being measured by the laser scanner. In FIG. **4**, the row and column at the location of the cursor are indicated on the display at **430**. The two measured angles and one measured distance (the 3D coordinates in a spherical coordinate system) at the cursor location are indicated on the display at **440**. Cartesian XYZ coordinate representations of the cursor location are indicated on the display at **450**.

FIG. **5** depicts an example of a panoramic view of a 3D scanned image **600** generated by mapping a planar view onto a sphere, or in some cases a cylinder. A panoramic view can be a 3D processed scanned image (such as that shown in FIG. **5**) in which 3D information (e.g., 3D coordinates) is available. The panoramic view may be in full resolution or reduced resolution depending on system characteristics. It should be pointed out that an image such as FIG. **5** is a 2D image that represents a 3D scene when viewed from a particular perspective. In this sense, the image of FIG. **5** is much like an image that might be captured by a 2D camera or a human eye. Although the panoramic view extracted from the 3D scanner is ordinarily a gray-scale or color image, FIG. **5** is shown as a line drawing for clarity in document reproduction.

The term panoramic view refers to a display in which angular movement is generally possible about a point in space, but translational movement is not possible (for a single panoramic image). In contrast, the term 3D view as used herein refers to generally refers to a display in which provision is made (through user controls) to enable not only rotation about a fixed point but also translational movement from point to point in space.

FIGS. **6A**, **6B** and **6C** depict an example of a 3D view of a 3D scanned image. In the 3D view a user can leave the origin of the scan and see the scan points from different viewpoints and angles. The 3D view is an example of a 3D processed scanned image. The 3D view may be in full resolution or reduced resolution depending on system characteristics. In addition, the 3D view allows multiple registered scans to be displayed in one view. FIG. **6A** is a 3D view **710** over which a selection mask **730** has been placed by a user. FIG. **6B** is a 3D view **740** in which only that part of the 3D view **710** covered by the selection mask **730** has been retained. FIG. **6C** shows the same 3D measurement data as in FIG. **6B** except as rotated to obtain a different view. FIG. **7** shows a different view of FIG. **6B**, the view in this instance being obtained from a translation and rotation of the observer viewpoint, as well as a reduction in observed area. Although the 3D views extracted from the 3D scanner are ordinarily a gray-scale or color image, FIGS. **6A-C** and **7** are shown as line drawings for clarity in document reproduction.

FIGS. **8A**, **8B**, **8C** and **9** show an embodiment of a 3D measuring device **800** that includes a 3D scanner **20**, a processor system **950**, an optional moveable platform **820**, and a depth camera at locations discussed further below. The 3D measuring device **800** may be a 3D TOF scanner **20** as described in reference to FIG. **1**.

The processor system **950** includes one or more processing elements that may include a 3D scanner processor (controller) **38**, an external computer **970**, and a cloud computer **980**. The processors may be microprocessors, field programmable gate arrays (FPGAs), digital signal processors (DSPs), and generally any device capable of performing computing functions. The one or more processors have access to memory for storing information. In an embodiment illustrated in FIG. **9**, the controller **38** represents one or more processors distributed throughout the 3D scanner. Also included in the embodiment of FIG. **9** are an external computer **970** and one or more cloud computers **980** for remote computing capability. In an alternative embodiment, only one or two of the processors **38**, **970**, and **980** is provided in the processor system. Communication among the processors may be through wired links, wireless links, or a combination of wired and wireless links. In an embodiment, scan results are uploaded after each scanning session to the cloud (remote network) for storage and future use. For the case in which a depth camera **840** is attached to the moveable platform **820**, the depth-camera data may be sent to the processor system through wired or wireless communication channels.

The depth cameras may be either of two types: a central-element depth camera and a triangulation-based depth camera. A central-element depth camera uses a single integrated sensor element combined with an illumination element to determine distance (“depth”) and angles from the camera to points on an object. One type of central-element depth camera uses a lens combined with a semiconductor chip to measure round-trip time of light travelling from the camera to the object and back. For example, the Microsoft Xbox One includes a Kinect depth camera that uses an infrared

(IR) light source to illuminate a 640×480 pixel photosensitive array. This depth camera is used in parallel with a 640×480 pixel RGB camera that measures red, blue, and green colors. Infrared illumination is provided in the IR illuminators adjacent to the lens and IR array. Another example of a central-element depth camera includes a lens and a PMD Technologies PhotonICs 19k-S3 3D chip used in conjunction with an IR light source. The measurement distance range of this 160×120 pixel chip is scalable based on the camera layout. Many other central-element depth cameras and associated IR sources are available today. Most central-element depth cameras include a modulated light source. The light source may use pulse modulation for direct determination of round-trip travel time. Alternatively, the light source may use continuous wave (CW) modulation with sinusoidal or rectangular waveforms to obtain round-trip travel time based on measured phase shift.

FIG. 8A shows two possible locations for a central-element depth camera. In an embodiment, the central-element depth camera **66** is located on the 3D scanner **20**. The depth camera **66** includes an integrated light source. In an alternative embodiment, the central-element depth camera **840** is located on the optional moveable platform **820**. It may be located on a base of the platform **820** or attached to one or more tripod legs, for example. In another embodiment, a central-element depth camera takes the place of central-color camera **112**. In this case, the light source may be integrated into the central-depth camera package or placed near to it so that the illumination light passes through the dichroic beam splitter **118**. Alternatively, the beam splitter **118** may not be a dichroic beam splitter but instead transmit and reflect wavelengths used by the central-element depth camera **112**. In this case, the wavelengths used by the depth camera **112** may be sent from the launch **28**, reflected off the beam splitter **118** onto the object, and reflected back from the object onto the depth camera.

The second type of depth camera is a triangulation-based depth camera. An example of such a camera is the Kinect of the Microsoft Xbox 360, which is a different Kinect than the Kinect of the Microsoft Xbox One described herein above. An IR light source on the Kinect of the Xbox 360 projects a pattern of light onto an object, which is imaged by an IR camera that includes a photosensitive array. The Kinect determines a correspondence between the projected pattern and the image received by the photosensitive array. It uses this information in a triangulation calculation to determine the distance to object points in the measurement volume. This calculation is based partly on the baseline between the projector and the IR camera and partly on the camera pattern received and projector pattern sent out. Unlike the central-element depth camera, a triangulation camera cannot be brought arbitrarily close to the light source (pattern projector) as accuracy is reduced with decreasing baseline distance. Many types of triangulation-based depth cameras are available.

FIG. 8C shows two possible locations for a triangulation-based depth camera. In an embodiment, the triangulation-based depth camera **66** is located on the 3D scanner **20**. The depth camera **66** includes a camera **882** and a pattern projector **884**. It may also include an optional color camera **886**. In an alternative embodiment, the triangulation-based depth camera **870** is located on the optional moveable platform **820**. The depth camera **870** includes a camera **872** and a pattern projector **874**. It may also include a color camera **876**. The triangulation-based depth camera **870** may be located on a base of the platform **820** or attached to one or more tripod legs, for example. It is not generally possible

to replace the central-color camera **112** with a triangulation-based depth camera because of the need for a baseline separation between the projector and the camera.

In one mode of operation of the 3D measuring device **800**, the depth camera (**112**, **70** or **840**) captures overlapping depth-camera images as the 3D measuring device is moved between positions at which 3D scans are taken. For the case in which the depth camera is an internal camera (for example, in place of the central color camera **112**) or a camera **66** mounted on the measuring head **22**, the camera may be optionally steered about the vertical axis **23** to increase the effective FOV of the depth camera. In an embodiment, the laser power from the 3D scanner is turned off as the depth-camera images are collected. In an alternative embodiment, the laser power is left on so that the 3D scanner **20** may make 2D scans in a horizontal plane while the depth-camera images are collected. For the case in which the depth camera **840** is mounted on the moveable platform **820**, the direction at which the depth camera is pointed is unaffected by rotation of horizontal axis **25** or vertical axis **23**.

The optional position/orientation sensor **920** in the 3D scanner **20** may include inclinometers (accelerometers), gyroscopes, magnetometers, and altimeters. Usually devices that include one or more of an inclinometer and gyroscope are referred to as an inertial measurement unit (IMU). In some cases, the term IMU is used in a broader sense to include a variety of additional devices that indicate position and/or orientation—for example, magnetometers that indicate heading based on changes in magnetic field direction relative to the earth's magnetic north and altimeters that indicate altitude (height). An example of a widely used altimeter is a pressure sensor. By combining readings from a combination of position/orientation sensors with a fusion algorithm that may include a Kalman filter, relatively accurate position and orientation measurements can be obtained using relatively low-cost sensor devices.

The optional moveable platform **820** enables the 3D measuring device **20** to be moved from place to place, typically along a floor that is approximately horizontal. In an embodiment, the optional moveable platform **820** is a tripod that includes wheels **822**. In an embodiment, the wheels **822** may be locked in place using wheel brakes **824**. In another embodiment, the wheels **822** are retractable, enabling the tripod to sit stably on three feet attached to the tripod. In another embodiment, the tripod has no wheels but is simply pushed or pulled along a surface that is approximately horizontal, for example, a floor. In another embodiment, the optional moveable platform **820** is a wheeled cart that may be hand pushed/pulled or motorized.

FIG. 10 shows the 3D measuring device **800** moved to a first registration position **1112** in front of an object **1102** that is to be measured. The object **1102** might for example be a wall in a room. In an embodiment, the 3D measuring device **800** is brought to a stop and is held in place with brakes, which in an embodiment are brakes **824** on wheels **822**. The 3D scanner **20** in the 3D measuring device **800** takes a first 3D scan of the object **1102**. In an embodiment, the 3D scanner **20** may if desired obtain 3D measurements in all directions except in downward directions blocked by the structure of the 3D measuring device **800**. However, in the example of FIG. 10, in which 3D scanner **20** measures a long, mostly flat structure **1102**, a smaller effective FOV **1130** may be selected to provide a more face-on view of features on the structure.

When the first 3D scan is completed, the processor system **950** causes the 3D measuring device **800** to change from 3D

scanning mode to a depth-camera imaging mode. The depth-camera imaging data is sent from the camera (112, 70 or 840) to the processor system 950 for mathematical analysis. In an embodiment, the scanner begins collecting depth-camera imaging data as the 3D scanning stops. In another embodiment, the collection of depth-camera imaging data starts when the processor system 950 receives a signal such as a signal from the position/orientation sensor 920, a signal from a brake release sensor, or a signal sent in response to a command from an operator. The processor system 950 may cause depth-camera imaging data to be collected when the 3D measuring device 800 starts to move, or it may cause depth-camera imaging data to be continually collected, even when the 3D measuring device 800 is stationary.

In an embodiment, the depth-camera imaging data is collected as the 3D measuring device 800 is moved toward the second registration position 1114. In an embodiment, the depth-camera imaging data is collected and processed as the 3D scanner 20 passes through a plurality of 2D measuring positions 1120. At each measuring position 1120, the depth camera collects depth-camera imaging data over an effective FOV 1140. Using methods described in more detail below, the processor system 950 uses the depth-camera imaging data from a plurality of depth-camera images at positions 1120 to determine a position and orientation of the 3D scanner 20 at the second registration position 1114 relative to the first registration position 1112, where the first registration position and the second registration position are known in a 3D coordinate system common to both. In an embodiment, the common coordinate system is represented by 2D Cartesian coordinates x , y and by an angle of rotation θ relative to the x or y axis. In an embodiment, the x and y axes lie in the horizontal x - y plane of the 3D scanner 20 and may be further based on a direction of a "front" of the 3D scanner 20. An example of such an (x, y, θ) coordinate system is the coordinate system 1410 of FIG. 14A.

On the object 1102, there is a region of overlap 1150 between the first 3D scan (collected at the first registration position 1112) and the second 3D scan (collected at the second registration position 1114). In the overlap region 1150 there are registration targets (which may be natural features of the object 1102) that are seen in both the first 3D scan and the second 3D scan. A problem that often occurs in practice is that, in moving the 3D scanner 20 from the first registration position 1112 to the second registration position 1114, the processor system 950 loses track of the position and orientation of the 3D scanner 20 and hence is unable to correctly associate the registration targets in the overlap regions to enable the registration procedure to be performed reliably. By using the succession of depth-camera images, the processor system 950 is able to determine the position and orientation of the 3D scanner 20 at the second registration position 1114 relative to the first registration position 1112. This information enables the processor system 950 to correctly match registration targets in the region of overlap 1150, thereby enabling the registration procedure to be properly completed.

FIG. 12 shows the 3D measuring device 800 collecting depth-camera imaging data at selected positions 1120 over an effective FOV 1140. At different positions 1120, the depth camera captures a portion of the object 1102 marked A, B, C, D, and E. FIG. 12 shows depth camera moving in time relative to a fixed frame of reference of the object 1102.

FIG. 13 includes the same information as FIG. 12 but shows it from the frame of reference of the 3D scanner 20 while collecting depth-camera images rather than the frame of reference of the object 1102. This figure makes clear that

in the scanner frame of reference, the position of features on the object change over time. Hence it is clear that the distance traveled by the 3D scanner 20 between registration position 1 and registration position 2 can be determined from the depth-camera imaging data sent from the camera to the processor system 950.

FIG. 14A shows a coordinate system that may be used in FIGS. 14B and 14C. In an embodiment, the 2D coordinates x and y are selected to lie on a plane parallel to the horizontal plane of movement of the moveable platform. The angle θ is selected as a rotation angle in the plane, the rotation angle relative to an axis such as x or y . FIGS. 14B, 14C represent a realistic case in which the 3D scanner 20 is moved not exactly on a straight line, for example, nominally parallel to the object 1102, but also to the side. Furthermore, the 3D scanner 20 may be rotated as it is moved.

FIG. 14B shows the movement of the object 1102 as seen from the frame of reference of the 3D scanner 20 in traveling from the first registration position to the second registration position. In the scanner frame of reference (that is, as seen from the scanner's point of view), the object 1102 is moving while the depth camera is fixed in place. In this frame of reference, the portions of the object 1102 seen by the depth camera appear to translate and rotate in time. The depth camera provides a succession of such translated and rotated depth-camera images to the processor system 950. In the example shown in FIGS. 14A, B, the scanner translates in the $+y$ direction by a distance 1420 shown in FIG. 14B and rotates by an angle 1430, which in this example is $+5$ degrees. Of course, the scanner could equally well have moved in the $+x$ or $-x$ direction by a small amount. To determine the movement of the depth camera in the x , y , θ directions, the processor system 950 uses the data recorded in successive depth-camera images as seen in the frame of reference of the scanner 20, as shown in FIG. 14B.

As the 3D scanner 20 collects successive depth-camera images and performs best-fit calculations of successive depth-camera images, the processor system 950 keeps track of the translation and rotation of the 3D scanner 20. In this way, the processor system 950 is able to accurately determine the change in the values of x , y , θ as the measuring device 800 moves from the first registration position 1112 to the second registration position 1114.

It is important to understand that the processor system 950 determines the position and orientation of the 3D measuring device 800 based on a comparison of the succession of depth-camera images and not on fusion of the depth-camera imaging data with 3D scan data provided by the 3D scanner 20 at the first registration position 1112 or the second registration position 1114.

Instead, the processor system 950 is configured to determine a first translation value, a second translation value, and a first rotation value that, when applied to a combination of the first depth-camera image data and second depth-camera image data, results in transformed first depth-camera data that matches transformed second depth-camera data as closely as possible according to an objective mathematical criterion. In general, the translation and rotation may be applied to the first scan data from the 3D scanner, the second scan data from the 3D scanner, or to a combination of the two. For example, a translation applied to the first scan data set is equivalent to a negative of the translation applied to the second scan data set in the sense that both actions produce the same match in the transformed data sets. An example of an "objective mathematical criterion" is that of minimizing the sum of squared residual errors for those portions of the scan data judged to overlap. Another type of objective

mathematical criterion may involve a matching of multiple features identified on the object. For example, such features might be the edge transitions **1103**, **1104**, and **1105** shown in FIG. **11B**.

In an embodiment, the processor system **950** extracts a horizontal slice from the depth-camera image. The resulting 2D coordinates on the horizontal plane provides information of the sort shown in FIGS. **12-14**. As explained herein above, such information may be used to provide first and second translation values and a first rotation value to provide a good starting point for 3D registration.

For the case in which the depth camera is internal to the camera, for example, taking the place of central color camera **112**, the light from depth-camera light source is sent off the mirror **26** and the scattered light is reflected off the object onto the mirror **26** and then onto the depth camera. In an embodiment, the mirror **26** is kept fixed about the horizontal axis **25** as shown in FIG. **8B**.

In most cases, a single horizontal slice is sufficient to provide accurate first and second translation values and first rotation value. However, in the event that the scanned area is nearly featureless over the horizontal slice, other methods may be used. One method is to take multiple horizontal slices, each at a different height. A scanned region that is nearly featureless at one height may include several features at a different height.

Another mathematical method that may be used to determine the first and second translation values and the first rotation value is an enhanced version of "optical flow." The mathematical method known in the art as "optical flow" is used extract information to evaluate sequentially overlapping camera images. This method is adapted from the studies of American psychologist James Gibson in the 1940s. A tutorial on optical flow estimation as used today is given in "Mathematical Models in Computer Vision: The Handbook" by N. Paragios, Y. Chen, and O. Faugeras (editors), Chapter 15, Springer 2005, pp. 239-258, the contents of which are incorporated by reference herein. For the case considered here, in which the camera is a depth camera rather than an ordinary 2D camera, depth information is further available for application to the optical-flow algorithm to further improve determination of the first and second translation values and the first rotation value. Additional mathematical methods known in the art may also be used to extract information on movement from the sequential depth-camera images.

The mathematical criterion may involve processing of the raw camera image data provided by the camera to the processor system **950**, or it may involve a first intermediate level of processing in which features are represented as a collection of line segments using methods that are known in the art, for example, methods based on the Iterative Closest Point (ICP). Such a method based on ICP is described in Censi, A., "An ICP variant using a point-to-line metric," IEEE International Conference on Robotics and Automation (ICRA) 2008.

In an embodiment, the first translation value is dx , the second translation value is dy , and the first rotation value $d\theta$. If first depth-camera image data has translational and rotational coordinates (in a reference coordinate system) of (x_1, y_1, θ_1) , then the second depth-camera image data collected at a second location has coordinates given by $(x_2, y_2, \theta_2) = (x_1 + dx, y_1 + dy, \theta_1 + d\theta)$. In an embodiment, the processor system **950** is further configured to determine a third translation value (for example, dz) and a second and third rotation values (for example, pitch and roll). The third translation value, second rotation value, and third rotation value may be

determined based at least in part on readings from the position/orientation sensor **920**.

The 3D scanner **20** collects depth-camera image data at the first registration position **1112** and more depth-camera image data at the second registration position **1114**. In some cases, these may suffice to determine the position and orientation of the 3D measuring device at the second registration position **1114** relative to the first registration position **1112**. In other cases, the two sets of depth-camera image data are not sufficient to enable the processor system **950** to accurately determine the first translation value, the second translation value, and the first rotation value. This problem may be avoided by collecting depth-camera image data at intermediate locations **1120**. In an embodiment, the depth-camera image data is collected and processed at regular intervals, for example, once per second. In this way, features are easily identified in successive depth-camera images **1120**. If more than two depth-camera images are obtained, the processor system **950** may choose to use the information from all the successive depth-camera images in determining the translation and rotation values in moving from the first registration position **1112** to the second registration position **1114**. Alternatively, the processor may choose to use only the first and last depth-camera images in the final calculation, simply using the intermediate depth-camera images to ensure proper correspondence of matching features. In most cases, accuracy of matching is improved by incorporating information from multiple successive depth-camera images.

The 3D measuring device **800** is moved to the second registration position **1114**. In an embodiment, the 3D measuring device **800** is brought to a stop and brakes are locked to hold the 3D scanner stationary. In an alternative embodiment, the processor system **950** starts the 3D scan automatically when the moveable platform is brought to a stop, for example, by the position/orientation sensor **920** noting the lack of movement. The 3D scanner **20** in the 3D measuring device **800** takes a 3D scan of the object **1102**. This 3D scan is referred to as the second 3D scan to distinguish it from the first 3D scan taken at the first registration position.

The processor system **950** applies the already calculated first translation value, the second translation value, and the first rotation value to adjust the position and orientation of the second 3D scan relative to the first 3D scan. This adjustment, which may be considered to provide a "first alignment," brings the registration targets (which may be natural features in the overlap region **1150**) into close proximity. The processor system **950** performs a fine registration in which it makes fine adjustments to the six degrees of freedom of the second 3D scan relative to the first 3D scan. It makes the fine adjustment based on an objective mathematical criterion, which may be the same as or different than the mathematical criterion applied to the depth-camera image data. For example, the objective mathematical criterion may be that of minimizing the sum of squared residual errors for those portions of the scan data judged to overlap. Alternatively, the objective mathematical criterion may be applied to a plurality of features in the overlap region. The mathematical calculations in the registration may be applied to raw 3D scan data or to geometrical representations of the 3D scan data, for example, by a collection of line segments.

Outside the overlap region **1150**, the aligned values of the first 3D scan and the second 3D scan are combined in a registered 3D data set. Inside the overlap region, the 3D scan values included in the registered 3D data set are based on some combination of 3D scanner data from the aligned values of the first 3D scan and the second 3D scan.

FIG. 15 shows elements of a method 1500 for measuring and registering 3D coordinates.

An element 1505 includes providing a 3D measuring device that includes a processor system, a 3D scanner, a depth camera, and a moveable platform. The processor system has at least one of a 3D scanner controller, an external computer, and a cloud computer configured for remote network access. Any of these processing elements within the processor system may include a single processor or multiple distributed processing elements, the processing elements being a microprocessor, digital signal processor, FPGA, or any other type of computing device. The processing elements have access to computer memory. The 3D scanner has a first light source, a first beam steering unit, a first angle measuring device, a second angle measuring device, and a first light receiver. The first light source is configured to emit a first beam of light, which in an embodiment is a beam of laser light. The first beam steering unit is provided to steer the first beam of light to a first direction onto a first object point. The beam steering unit may be a rotating mirror such as the mirror 26 or it may be another type of beam steering mechanism. For example, the 3D scanner may contain a base onto which is placed a first structure that rotates about a vertical axis, and onto this structure may be placed a second structure that rotates about a horizontal axis. With this type of mechanical assembly, the beam of light may be emitted directly from the second structure and point in a desired direction. Many other types of beam steering mechanisms are possible. In most cases, a beam steering mechanism includes one or two motors. The first direction is determined by a first angle of rotation about a first axis and a second angle of rotation about a second axis. The first angle measuring device is configured to measure the first angle of rotation and the second angle measuring device configured to measure the second angle of rotation. The first light receiver is configured to receive first reflected light, the first reflected light being a portion of the first beam of light reflected by the first object point. The first light receiver is further configured to produce a first electrical signal in response to the first reflected light. The first light receiver is further configured to cooperate with the processor system to determine a first distance to the first object point based at least in part on the first electrical signal, and the 3D scanner is configured to cooperate with the processor system to determine 3D coordinates of the first object point based at least in part on the first distance, the first angle of rotation and the second angle of rotation. The moveable platform is configured to carry the 3D scanner. The depth camera is configured to obtain depth-camera images and to send the depth-camera image data to the processor system 950. The depth camera may be located internal to the 3D scanner, mounted on the 3D scanner, or attached to the moveable platform.

An element 1510 includes determining with the processor system 950, in cooperation with the 3D scanner 20, 3D coordinates of a first collection of points on an object surface while the 3D scanner is fixedly located at a first registration position.

An element 1515 includes obtaining by the 3D measuring device in cooperation with the processor system a plurality of depth-camera image sets. Each of the plurality of depth-camera image sets is a set of 3D coordinates of points on the object surface collected as the 3D scanner moves from the first registration position to a second registration position. Each of the plurality of depth-camera image sets is collected by the depth camera at a different position relative to the first registration position.

An element 1520 includes determining by the processor system a first translation value corresponding to a first translation direction, a second translation value corresponding to a second translation direction, and a first rotation value corresponding to a first orientational axis, wherein the first translation value, the second translation value, and the first rotation value are determined based at least in part on a fitting of the plurality of depth-camera image sets according to a first mathematical criterion. In an embodiment, the first orientation axis is a vertical axis perpendicular to the planes in which the depth-camera image sets are collected.

An element 1525 includes determining with the processor system, in cooperation with the 3D scanner, 3D coordinates of a second collection of points on the object surface while the 3D scanner is fixedly located at the second registration position.

An element 1535 includes identifying by the processor system a correspondence among registration targets present in both the first collection of points and the second collection of points, the correspondence based at least in part on the first translation value, the second translation value, and the first rotation value. This is a step that aligns to a relatively high accuracy level the 3D scan data collected at the first and second registration positions.

An element 1545 includes determining 3D coordinates of a registered 3D collection of points based at least in part on a second mathematical criterion, the correspondence among registration targets, the 3D coordinates of the first collection of points, and the 3D coordinates of the second collection of points. This step performs a fine registration and merges the first and second collections of points into a single registered 3D collection of points. An element 1550 includes storing the 3D coordinates of the registered 3D collection of points.

Terms such as processor, controller, computer, DSP, FPGA are understood in this document to mean a computing device that may be located within an instrument, distributed in multiple elements throughout an instrument, or placed external to an instrument.

While the invention has been described in detail in connection with only a limited number of embodiments, it should be readily understood that the invention is not limited to such disclosed embodiments. Rather, the invention can be modified to incorporate any number of variations, alterations, substitutions or equivalent arrangements not heretofore described, but which are commensurate with the spirit and scope of the invention. Additionally, while various embodiments of the invention have been described, it is to be understood that aspects of the invention may include only some of the described embodiments. Accordingly, the invention is not to be seen as limited by the foregoing description, but is only limited by the scope of the appended claims.

What is claimed is:

1. A three-dimensional (3D) measuring device comprising:
 - a processor system including at least one of a 3D scanner controller, an external computer, and a cloud computer configured for remote network access;
 - a 3D scanner having a first light source, a first beam steering unit, a first angle measuring device, a second angle measuring device, and a first light receiver, the first light source configured to emit a first beam of light, the first beam steering unit configured to steer the first beam of light to a first direction onto a first object point, the first direction determined by a first angle of rotation about a first axis and a second angle of rotation about a second axis, the first angle measuring device configured to measure the first angle of rotation and the

second angle measuring device configured to measure the second angle of rotation, the first light receiver configured to receive first reflected light, the first reflected light being a portion of the first beam of light reflected by the first object point, the first light receiver configured to produce a first electrical signal in response to the first reflected light, the first light receiver configured to cooperate with the processor system to determine a first distance to the first object point based at least in part on the first electrical signal, the 3D scanner configured to cooperate with the processor system to determine 3D coordinates of the first object point based at least in part on the first distance, the first angle of rotation and the second angle of rotation;

a moveable platform configured to carry the 3D scanner;

a depth camera configured to move in conjunction with the 3D scanner;

wherein the processor system is responsive to executable instructions which when executed by the processor system is operable to:

- cause the 3D scanner, while fixedly located at a first registration position, to cooperate with the processor system to determine 3D coordinates of a first collection of points on an object surface;
- cause the 3D measuring device, while moving from the first registration position to a second registration position, to cooperate with the processor system to obtain a plurality of depth-camera image sets, each of the plurality of depth-camera image sets being a set of 3D coordinates of points on the object surface, each of the plurality of depth-camera image sets being collected by the 3D measuring device at a different position relative to the first registration position;
- determine a first translation value corresponding to a first translation direction, a second translation value corresponding to a second translation direction, and a first rotation value corresponding to a first orientational axis, wherein the first translation value, the second translation value, and the first rotation value are determined based at least in part on a fitting of the plurality of depth-camera image sets according to a first mathematical criterion;
- cause the 3D scanner, while fixedly located at the second registration position, to cooperate with the processor system to determine 3D coordinates of a second collection of points on the object surface;
- identify a correspondence among registration targets present in both the first collection of points and the second collection of points, the correspondence based at least in part on the first translation value, the second translation value, and the first rotation value; and
- determine 3D coordinates of a registered 3D collection of points based at least in part on a second mathematical criterion, the determined correspondence among the registration targets, the 3D coordinates of the first collection of points, and the 3D coordinates of the second collection of points.

2. The 3D measuring device of claim 1 wherein the 3D measuring device further includes a position/orientation sensor, the position orientation sensor including at least one sensor selected from the group consisting of an inclinometer, a gyroscope, a magnetometer, and an altimeter.
3. The 3D measuring device of claim 1 wherein the moveable platform is a tripod having wheels and a brake.

4. The 3D measuring device of claim 1 wherein the first beam steering unit includes a first mirror configured to rotate about a horizontal axis and a carriage that holds the first mirror configured to rotate about a vertical axis, the rotation about the horizontal axis being driven by a first motor and the rotation about the vertical axis being driven by a second motor.
5. The 3D measuring device of claim 1 wherein the processor is further configured to respond to a stopping signal to cause the 3D scanner, while fixedly located at the second registration position, to automatically begin cooperating with the processor system to determine 3D coordinates of a second collection of points on the object surface.
6. The 3D measuring device of claim 5 wherein the stopping signal is generated in response to a signal received by the processor system from the position/orientation sensor.
7. The 3D measuring device of claim 1, wherein the registration targets are natural features of the object surface.
8. The 3D measuring device of claim 1, wherein the depth camera is selected from the group consisting of a depth camera internal to the 3D scanner, a depth camera mounted on the 3D scanner, and a depth camera mounted on the moveable platform.
9. A method for measuring and registering three-dimensional (3D) coordinates comprising:
 - providing a 3D measuring device that includes a processor system, a 3D scanner, a depth camera, and a moveable platform,
 - the processor system having at least one of a 3D scanner controller, an external computer, and a cloud computer configured for remote network access,
 - the 3D scanner having a first light source, a first beam steering unit, a first angle measuring device, a second angle measuring device, and a first light receiver, the first light source configured to emit a first beam of light, the first beam steering unit configured to steer the first beam of light to a first direction onto a first object point, the first direction determined by a first angle of rotation about a first axis and a second angle of rotation about a second axis, the first angle measuring device configured to measure the first angle of rotation and the second angle measuring device configured to measure the second angle of rotation, the first light receiver configured to receive first reflected light, the first reflected light being a portion of the first beam of light reflected by the first object point, the first light receiver configured to produce a first electrical signal in response to the first reflected light, the first light receiver configured to cooperate with the processor system to determine a first distance to the first object point based at least in part on the first electrical signal, the 3D scanner configured to cooperate with the processor system to determine 3D coordinates of the first object point based at least in part on the first distance, the first angle of rotation and the second angle of rotation,
 - a depth camera configured to move in conjunction with the 3D scanner;
 - the moveable platform configured to carry the 3D scanner and the depth camera;
 - determining with the processor system, in cooperation with the 3D scanner, 3D coordinates of a first collection of points on an object surface while the 3D scanner is fixedly located at a first registration position;
 - obtaining by the 3D measuring device in cooperation with the processor system a plurality of depth-camera image sets, each of the plurality of depth-camera image sets

21

being collected as the 3D measuring device moves from the first registration position to a second registration position, each of the plurality of depth-camera image sets being collected by the 3D measuring device at a different position relative to the first registration position;

determining by the processor system a first translation value corresponding to a first translation direction, a second translation value corresponding to a second translation direction, and a first rotation value corresponding to a first orientational axis, wherein the first translation value, the second translation value, and the first rotation value are determined based at least in part on a fitting of the plurality of depth-camera image sets according to a first mathematical criterion;

determining with the processor system, in cooperation with the 3D scanner, 3D coordinates of a second collection of points on the object surface while the 3D scanner is fixedly located at the second registration position;

identifying by the processor system a correspondence among registration targets present in both the first collection of points and the second collection of points, the correspondence based at least in part on the first translation value, the second translation value, and the first rotation value;

determining 3D coordinates of a registered 3D collection of points based at least in part on a second mathematical criterion, the correspondence among registration targets, the 3D coordinates of the first collection of points, and the 3D coordinates of the second collection of points; and

storing the 3D coordinates of the registered 3D collection of points.

10. The method of claim **9** wherein, in the element of providing a 3D measuring device that includes a processor system, a 3D scanner, a depth camera, and a moveable platform, the 3D measuring device further includes a position/orientation sensor, the position orientation sensor

22

including at least one sensor selected from the group consisting of an inclinometer, a gyroscope, a magnetometer, and an altimeter.

11. The method of claim **9** wherein, in the element of providing a 3D measuring device that includes a processor system, a 3D scanner, a depth camera, and a moveable platform, the moveable platform is a tripod having wheels and a brake.

12. The method of claim **9** wherein, in the element of providing a 3D measuring device that includes a processor system, a 3D scanner, a depth camera, and a moveable platform, the first beam steering unit includes a first mirror configured to rotate about a horizontal axis and a carriage that holds the first mirror, the carriage configured to rotate about a vertical axis, the rotation about the horizontal axis being driven by a first motor and the rotation about the vertical axis being driven by a second motor.

13. The method of claim **12** wherein, in the element of obtaining by the 3D measuring device in cooperation with the processor system a plurality of depth-camera image sets, the first mirror is held fixed and the second mirror is held fixed.

14. The method of claim **12** wherein, in the element of obtaining by the 3D measuring device in cooperation with the processor system a plurality of range camera image sets, the first mirror rotates about the vertical axis while the horizontal axis is held fixed.

15. The method of claim **9** wherein in the element of determining with the processor system, in cooperation with the 3D scanner, 3D coordinates of a second collection of points on the object, the processor is further configured to respond to a stopping signal to cause the 3D scanner to automatically start measurement of the second collection of points.

16. The method of claim **15** wherein in the element of determining with the processor system, in cooperation with the 3D scanner, 3D coordinates of a second collection of points on the object, the stopping signal is generated in response to a signal received by the processor system from the position/orientation sensor.

* * * * *