



US009630087B2

(12) **United States Patent**  
**Shigeta**

(10) **Patent No.:** **US 9,630,087 B2**  
(45) **Date of Patent:** **\*Apr. 25, 2017**

(54) **CARD READER**

(71) Applicant: **Angel Playing Cards Co., Ltd.**, Osaka (JP)

(72) Inventor: **Yasushi Shigeta**, Kyoto (JP)

(73) Assignee: **Angel Playing Cards Co., Ltd.**, Shiga (JP)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/844,375**

(22) Filed: **Sep. 3, 2015**

(65) **Prior Publication Data**

US 2015/0375097 A1 Dec. 31, 2015

**Related U.S. Application Data**

(63) Continuation of application No. 14/022,109, filed on Sep. 9, 2013, now Pat. No. 9,126,104, which is a (Continued)

(30) **Foreign Application Priority Data**

Mar. 19, 2004 (JP) ..... 2004-079519

(51) **Int. Cl.**

**A63F 1/14** (2006.01)

**A63F 1/18** (2006.01)

**A63F 9/24** (2006.01)

(52) **U.S. Cl.**

CPC ..... **A63F 1/14** (2013.01); **A63F 1/18** (2013.01); **A63F 2009/2419** (2013.01); **A63F 2250/58** (2013.01)

(58) **Field of Classification Search**

CPC ..... **A63F 1/12**; **A63F 1/14**; **A63F 2250/58**; **A63F 1/06**

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,513,696 A 4/1985 Fujii et al.

4,513,969 A 4/1985 Samsel, Jr.

(Continued)

FOREIGN PATENT DOCUMENTS

JP H5-398 1/1993

JP H5-20512 1/1993

(Continued)

OTHER PUBLICATIONS

Australian Patent Application No. 2008200596, Examiner's First Report mailed Nov. 6, 2009.

(Continued)


*Primary Examiner* — Tramar Harper

(74) *Attorney, Agent, or Firm* — Chadbourne & Parke LLP

(57) **ABSTRACT**

A card shooter apparatus including a card shooter unit including a card housing which contains a plurality of cards and an opening, a card reading unit that reads the number of the card pulled out from the card shooter, a control unit having a processing function to determine win or lose of the card game based on information about the number of the cards sequentially read by the card reading unit, and a display unit which indicates a result determined by the control unit, wherein the card shooter unit, the card reading unit and the control unit are integrated and are able to be set on the game table, and the display unit includes a first display unit which is provided on an upper part of the housing and a second display unit which is provided on a side part of the housing.

**13 Claims, 13 Drawing Sheets**



**Related U.S. Application Data**

continuation of application No. 11/884,021, filed as application No. PCT/JP2005/003789 on Mar. 4, 2005, now Pat. No. 8,561,989.

- (58) **Field of Classification Search**  
 USPC ..... 273/149 R  
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,534,562	A	8/1985	Cuff et al.	
4,586,712	A	5/1986	Lorber et al.	
4,794,239	A	12/1988	Allais	
5,067,713	A	11/1991	Soules et al.	
5,166,502	A	11/1992	Rendleman et al.	
5,169,155	A	12/1992	Soules et al.	
5,259,907	A	11/1993	Soules et al.	
5,331,141	A	7/1994	Kaneko	
5,374,061	A	12/1994	Albrecht	
5,669,813	A	9/1997	Jairazbhoy et al.	
5,669,816	A	9/1997	Garczynski et al.	
5,707,287	A	1/1998	McCrea, Jr.	
5,722,893	A *	3/1998	Hill ..... A63F 1/14	
			273/149 R	
5,779,546	A	7/1998	Meissner et al.	
5,814,804	A	9/1998	Kostizak	
5,911,626	A	6/1999	McCrea, Jr.	
5,941,769	A	8/1999	Order	
6,039,650	A	3/2000	Hill	
6,042,150	A	3/2000	Daley	
6,066,857	A	5/2000	Fantone et al.	
6,093,103	A	7/2000	McCrea, Jr.	
6,098,892	A	8/2000	Peoples, Jr.	
6,126,166	A	10/2000	Lorson et al.	
6,217,447	B1	4/2001	Lofink et al.	
6,270,406	B1	8/2001	Sultan	
6,460,848	B1	10/2002	Soltys et al.	
6,527,191	B1	3/2003	Jannersten	
6,582,301	B2	6/2003	Hill	
6,588,751	B1	7/2003	Grauzer et al.	
6,629,894	B1	10/2003	Purton	
6,638,161	B2	10/2003	Soltys et al.	
7,029,009	B2	4/2006	Grauzer et al.	
7,093,130	B1	8/2006	Kobayashi et al.	
7,172,507	B2	2/2007	Fujimoto et al.	
7,222,852	B2	5/2007	Soltys et al.	
7,422,522	B2	9/2008	Fujimoto et al.	
7,699,694	B2 *	4/2010	Hill ..... A63F 1/18	
			463/11	
7,762,889	B2	7/2010	Shigeta	
7,946,586	B2	5/2011	Krenn et al.	
8,221,244	B2	7/2012	French	
8,309,163	B2	11/2012	Van Duren et al.	
8,556,262	B2	10/2013	Shigeta	
8,590,896	B2	11/2013	Krenn et al.	
2002/0068635	A1 *	6/2002	Hill ..... A63F 1/14	
			463/47	
2002/0155869	A1	10/2002	Soltys et al.	
2002/0163125	A1 *	11/2002	Grauzer ..... G10L 19/07	
			273/149 R	
2002/0165029	A1	11/2002	Soltys et al.	

2003/0003997	A1	1/2003	Vuong et al.	
2003/0171142	A1	9/2003	Kaji et al.	
2003/0176209	A1	9/2003	Soltys et al.	
2004/0026636	A1	2/2004	Shigeta	
2004/0100026	A1	5/2004	Haggard	
2005/0062227	A1	3/2005	Grauzer et al.	
2005/0121852	A1 *	6/2005	Soltys ..... A63F 1/18	
			273/149 P	
2005/0137005	A1	6/2005	Soltys et al.	
2007/0018389	A1	1/2007	Downs, III	
2012/0306152	A1	12/2012	Krishnamurty et al.	
2014/0042697	A1	2/2014	Berube et al.	
2015/0014925	A1	1/2015	Miller et al.	

FOREIGN PATENT DOCUMENTS

JP	H9-215812	3/1997		
JP	H9-144353	6/1997		
JP	H10508236	8/1998		
JP	2000327255	11/2000		
JP	2001222687	8/2001		
JP	2002165916	6/2002		
JP	2002224443	8/2002		
JP	WO 02/064225	A1 * 8/2002	..... A63F 9/24	
JP	2002282413	10/2002		
JP	2003052902	2/2003		
JP	2003070956	3/2003		
JP	2003144742	5/2003		
JP	2003250950	9/2003		
JP	2005198668	7/2005		
JP	2005267625	9/2005		
JP	2005296634	10/2005		
JP	2007236995	9/2007		
JP	2008188471	8/2008		
WO	9614115	5/1996		
WO	9943404	9/1999		
WO	0156670	8/2001		
WO	02064225	8/2002		
WO	03026763	4/2003		

OTHER PUBLICATIONS

Australian Patent Application No. 2010235931, Examiner's Report No. 2 mailed Jul. 11, 2011.  
 International Application No. PCT/JP2005/003789, International Preliminary Report on Patentability mailed Feb. 2, 2006.  
 International Application No. PCT/JP2005/003789, International Search Report mailed Apr. 26, 2005.  
 U.S. Appl. No. 10/542,073, Final Office Action mailed Apr. 14, 2010.  
 U.S. Appl. No. 11/884,021, Non-Final Office Action mailed Dec. 8, 2010.  
 U.S. Appl. No. 11/929,727, Non-Final Office Action mailed Oct. 1, 2010.  
 U.S. Appl. No. 11/929,727, Non-Final Office Action mailed Mar. 7, 2011.  
 U.S. Appl. No. 12/231,657, Non-Final Office Action mailed Mar. 19, 2010.  
 U.S. Appl. No. 12/231,657, Final Office Action mailed Dec. 8, 2010.  
 U.S. Appl. No. 12/825,261, Non-Final Office Action mailed Nov. 23, 2010.

\* cited by examiner

FIG. 1






FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6





FIG. 7








FIG. 8

PATTERN	OBJECT DETECTING SENSOR	MEASUREMENT VALIDITY DETERMINING SENSOR	PROCESSING
MEASUREMENT (NORMAL)	ON OFF	ON OFF	VALID MEASUREMENT (APPROVED) CARD IS NORMAL/ABNORMAL
SLIP BACK 1	ON OFF		INVALID MEASUREMENT (CANCELLED)
SLIP BACK 2	ON OFF	ON OFF	INVALID MEASUREMENT (CANCELLED)
CUT CARD	ON OFF	NO REACTION	INVALID MEASUREMENT (CANCELLED)

SAME

FIG. 9













	AT THE TIME OF VALID MEASUREMENT	INVALID MEASUREMENT
OBJECT DETECTING SENSOR	ON 	ON 
UV SENSOR	REPEITION OF ON/OFF 	REPEITION OF ON/OFF 
MEASUREMENT VALIDITY DETERMINING SENSOR	ON 	OFF ON POINT 
	AT THE TIME OF PASSAGE OF CUT CARD	AT THE TIME OF NO UV PRINTING
OBJECT DETECTING SENSOR	ON 	ON 
UV SENSOR	OFF 	OFF 
MEASUREMENT VALIDITY DETERMINING SENSOR	OFF ON POINT 	ON 

FIG. 10






FIG. 11







FIG. 12

FIG. 13






FIG. 14



# 1

## CARD READER

### CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 14/022,109, filed Sep. 9, 2013, entitled, "CARD READER," which is a continuation of U.S. patent application Ser. No. 11/884,021, filed Aug. 9, 2007, now U.S. Pat. No. 8,561,989, entitled, "CARD READER," which is a U.S. National Stage Application under 35 U.S.C. §371 of International Application No. PCT/JP2005/003789, filed Mar. 4, 2005, entitled "CARD READING DEVICE," which claims priority to Japanese Patent Application No. 2004-079519, filed Mar. 19, 2004, the contents of which are incorporated herein by reference.

### FIELD OF THE INVENTION

The present invention relates to a card reader that reads playing cards (trump cards; hereinafter simply referred to as cards), and particularly, an apparatus that is used suitably for a card game in which a card shooter is to be used.

### BACKGROUND OF THE INVENTION

Conventionally, a card reader that is used suitably for a card game in a casino, etc. is suggested. For example, PCT Japanese Translation Patent Publication No. 10-508236 (Page 12, FIG. 1) discloses a card reader equipped with a card shooter. In the apparatus of this literature, a CCD image sensor and related optical system components are built in the card shooter. Further, an outlet of the card shooter is provided with a card reading window. Also, when a card passes through the shooter outlet, the card is read through the reading window.

However, in the conventional apparatus, reading precision is restricted by the CCD image sensor and related optical system components. The reading precision is desired to improve as much as possible. This point is also important in reducing the influence on a game progress caused by generation of a read error.

Further, in the conventional apparatus, in order to secure reading capability, the speed of a card when a card is pulled out of the card shooter needs to be comparatively low, for example, the maximum speed is about 1 m/s. On the other hand, even if the card speed is larger, a card needs to be read accurately. This point is also important in the game progress of a casino, etc.

The invention has been made in view of the above problems. It is therefore an object of the invention to provide a card reader that is capable of utilizing an existing card shooter, is high in reading precision, and is high in the threshold value of the card speed at the time of reading.

### SUMMARY OF THE INVENTION

One aspect of the present invention is a card reader comprising: a platform; a card shooter mounted on the platform; a card guide unit that guides cards, which are pulled out one by one from the card shooter; and one or more black light sensors provided in the card guide unit to read an ultraviolet-ray reaction code from a card guided by the card guide unit, the ultraviolet-ray reaction code indicating at least the number the card.

Another aspect of the present invention is a card shooter apparatus having a card reading function, the apparatus

# 2

comprising: one or more black light sensors that reads an ultraviolet-ray reaction code from cards pulled one by one from a card shooter unit, the ultraviolet-ray reaction code indicating at least the number of each card.

Another aspect of the present invention is a card reader including: a platform; a card shooter mounted on the platform; a card guide unit that guides cards, which are pulled out one by one from the card shooter; and one or more black light sensors provided in the card guide unit to read an ultraviolet-ray reaction code from a card guided by the card guide unit, the ultraviolet-ray reaction code indicating card information of the card.

As described hereafter, other aspects of the invention exist. Thus, this summary of the invention is intended to provide a few aspects of the invention and is not intended to limit the scope of the invention described and claimed herein.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a view showing the overall configuration of a card reader of the present embodiment.

FIG. 2 is a view showing a platform along with a game table and a card shooter.

FIG. 3 is a plan view of the platform and the card shooter.

FIG. 4 is a plan view in a state where a sensor cover is detached.

FIG. 5 is a sectional view of the platform.

FIG. 6 is a view showing a sensor arrangement.

FIG. 7 is a view showing the back surface of the platform.

FIG. 8 is a block diagram showing a control configuration including a control box.

FIG. 9 is a view showing sensor output according to situations.

FIG. 10 is a view showing an example of the output waves of sensors.

FIG. 11 is a flow chart showing the operation of the card reader when a normal mode is set.

FIG. 12 is a flow chart showing the operation of the card reader when a special mode is set.

FIG. 13 is a view showing an example of a card.

FIG. 14 is a view showing a configuration in which the card reader and the card shooter are integrated.

### DETAILED DESCRIPTION OF THE EXEMPLARY EMBODIMENTS

The following detailed description refers to the accompanying drawings. The following detailed description and the accompanying drawings do not limit the invention. Instead, the scope of the invention is defined by the appended claims.

A card reader includes: a platform that is set on a game table and has a card shooter mounted thereon; a card guide unit that is provided in the platform to guide cards, which are pulled out one by one from the card shooter, onto the game table; and black light sensors that are provided in the card guide unit to read an ultraviolet-ray reaction code including the number of a card from the card.

According to this card reader, the platform is provided between the game table and the card shooter, and the platform is provided with a card reading function. Thus, reading of a card is enabled while the existing card shooter is utilized. Moreover, since the black light sensors are used, reading precision is high, and the threshold value of the card speed at the time of reading can also be set to a large value,



for example, about 3.6 m/s. Also, the reading result of a card is suitably helpful to prevention of an illegal act.

Preferably, the card guide unit has a card guide surface, card guide rails are provided at edges of the card guide surface, a card passage gap is formed between the card guide surface and the card guide rails, and the black light sensors are provided so as to read a card from the card guide surface within the card passage gap. Accordingly, the influence of outside light in a card reading part can be reduced, and reading precision can be improved.

Preferably, the card reader further includes a win/lose determining means that determines the win or lose of a card game on the basis of the numbers of the cards that are sequentially read by the black light sensors, and an output means that outputs a game result determined by the win/lose determining means. Accordingly, the progress of a game can be supported, and an illegal act can be prevented.

Preferably, the card reader further includes an invalid mode setting means that sets a first card invalid mode that invalidates a card that is first pulled out in each game. Accordingly, even when a rule that invalidates a first card is adopted, the card reader can perform game result determination processing adapted to a card game, and can smoothly process a card game.

Preferably, the card reader further includes first and second card detecting sensors that are arranged along a guiding direction of the card guide unit to detect the existence or nonexistence of a card, and a measurement validity/invalidity determining means that determines whether or not a card has normally passed along the card guide unit, on the basis of detection signals of the first and second card detecting sensors.

Preferably, the measurement validity/invalidity determining means validates reading of a card when the first card detecting sensor and the second card detecting sensor detect the card in order, and then the first card detecting sensor and the second card detecting sensor stop detecting the card in order.

Preferably, the measurement validity/invalidity determining means invalidates reading of a card when the first card detecting sensor and the second card detecting sensor detect the card in order, and then the second card detecting sensor and the first card detecting sensor stop detecting the card in order. Accordingly, when a card slips back, it is possible to suitably cope with this.

Preferably, in the card reader, the sensitivity of the second card detecting sensor is set so as to detect a card for game and so as not to detect a cut card. Accordingly, when a cut card is used, the card reader can suitably cope with this.

Further, in the card reader, the black light sensors are adapted to detect code elements including a given number from a card which the code elements are arrayed in a card pulling direction as an ultraviolet-ray reaction code, and to output a detection signal. Also, the card reader includes a number specifying means, and the number specifying means specifies a card associated with the numbers of the code elements on the basis of the detection signals of the black light sensors. The code elements are typically marks printed with ultraviolet-ray reaction ink.

The numbers of the code elements are associated with at least the number of a card. The numbers of the code elements may be associated with the type (spade, heart, etc.) of a card, in addition to the number of the card. The numbers of the code elements may be associated with other information.

Further, the ultraviolet-ray reaction code may have plural rows of the code elements. A card may be specified by a

combination of the numbers of the plural rows of code elements. In this case, a card is specified from the plural rows of code elements including given numbers. Accordingly, even in this case, the code elements including given numbers are read. Also, the number specifying unit specifies the number of a card associated with the numbers of the code elements.

Since the black light sensors are provided, the code elements is detected by the black light sensors, and a card is specified from the numbers of the code elements, the card can be detected with high precision.

A card shooter apparatus has a card reading function to read the number of a card. This card shooter apparatus includes black light sensors that read an ultraviolet-ray reaction code including the number of each of cards that are pulled one by one from a card shooter, from the card. In this aspect, the card shooter and the card reader may be provided separately or integrally. Even in this aspect, an advantage that reading precision can be improved is obtained, and an advantage that the threshold value of the card speed at the time of reading is raised is obtained.

The card shooter apparatus may further include a housing, a card shooter unit that is provided in the housing, and a card guide unit that is provided in the housing to guide cards pulled out one by one from the card shooter unit onto a game table. Here, the black light sensors are provided in the housing. The black light sensors may be provided in the housing. The housing may include a processing unit that processes the read data of the black light sensors, and a display unit that displays a processing result of the processing unit.

Hereinafter, embodiments of the invention will be described with reference to the drawings.

FIG. 1 shows a card reader 10 of the present embodiment. The card reader 10 includes a platform 12, a control box 14 is connected to the platform 12, and a monitor 16, and a win/lose display box 18 are connected to the control box 14. The control box 14 is a computer apparatus that controls the whole apparatus.

Referring to FIG. 2, the platform 12 is set on a game table 20, and a card shooter 22 (card shoe) is mounted on the platform 12.

The card shooter 22 may be a general type of existing shooter. The card shooter 22 includes a card housing 24, and a fore leg 26 and a hind leg 27 under the card housing. A floor 28 and a front wall 30 of the card housing 24 incline as shown. Within the card housing 24, a deck of cards is forward pushed against the front wall 30 by a card push member 32 with a roller. The front wall 30, as shown in FIG. 3, has a U-shaped opening 34 in a lower part. A dealer slides the cards to take them out of the opening 34.

In addition, black cloth 36 (omitted in the other drawings) is hung on the front wall 30 so as to block the opening 34. Further, though not shown, a cover is attached to an upper part of the card housing 24. The card shooter 22 is black as a whole, and is made of resin.

Next, the configuration of the platform 12 will be described. The platform 12 is black and is made of resin, similarly to the card shooter 22. The platform 12 has a thin box shape as a whole. The platform 12 has a table mounting surface 40 at the bottom thereof, and a shooter setting surface 42 at the top thereof, and both the surfaces are flat.

The shooter setting surface 42 is provided with shooter positioning blocks 44 and 46. The card shooter 22 is put on the shooter setting surface 42 so that the fore leg 26 and the hind leg 27 of the card shooter 22 may contact the shooter



## 5

positioning blocks **44** and **46**, and thereby, the card shooter **22** is positioned with respect to the platform **12**.

Further, shooter hold-down blocks **48** are attached to a front end of the shooter setting surface **42**. The shooter hold-down blocks **48** holds down the front end of the card shooter **22** from upside, and thereby, the card shooter **22** is held on the platform **12**.

The platform **12** has a card guide unit **50** in a front part thereof. The card guide unit **50** guides cards, which are pulled out one by one from the card shooter **22**, onto the game table **20**, as described below.

As shown in FIGS. **2** and **3**, the card guide unit **50** has a card guide surface **52** that is an inclined plane. One end of the card guide surface **52** is connected with an opening **34** of a card outlet of the platform **12**. The card guide surface **52** extends forward and downward from the front the card outlet, and the other end of the card guide surface is connected with the game table **20**. The card guide surface **52** becomes a measurement surface for card reading.

Card guide rails **54** are attached to edges on both sides of the card guide surface **52**. As shown in FIG. **2**, a card passage gap **56** is formed between the card guide rails **54** and the card guide surface **52**. The size of the card passage gap **56** is set to be slightly larger than the thickness of a card. After a card is pulled out of the card shooter **22**, it passes along the card guide surface **52**. At this time, both ends of the card pass through the card passage gap **56**.

Further, the inclination of the card guide surface **50** is changed on the way as shown. The card guide rails **54** are provided in a region before the inclination changes, and the card guide rails **54** is slightly longer than the short sides of a card.

Further, a sensor cover **58** is attached to each of the two card guide rails **54** with screws. As shown in FIG. **4**, when the sensor covers **58** are detached, four sensors are exposed. The four sensors are two black light sensors **60**, an object detecting sensor **62**, and a measurement validity determining sensor **64**, and these sensors are provided in the card guide surface **52** of the card guide unit **50**. In the drawing, the black light sensors **60** and the measurement validity determining sensor **64** can be seen from sensor cleaning holes **66** and **67** that pass through the card guide rails **54**.

As shown in FIG. **4**, the black light sensors **60** (hereinafter referred to as UV sensors **60**) are located on the relatively upstream side in the direction of flow of a card, on the card guide surface **52**. Further, as shown in FIGS. **2** and **5**, the UV sensors **60** are arranged in the inner space of the platform **12**, are fixed to the ceiling (the other side of the card guide surface **52**) of the platform with stays, and are exposed through the opening of the card guide surface **52**.

Each of the UV sensors **60** includes an LED (ultraviolet LED) that emits ultraviolet rays, and a detector. A card is irradiated with ultraviolet rays (black light, and a code of the card is detected by the detectors. The code of the number (rank: A, **1** to **10**, J, Q, and K) a card is printed on the card with ultraviolet ray emission ink that produces a color when ultraviolet rays strike the card.

The above UV sensors **60** are connected to the control box **14** through cables. In the control box **14**, the number of a card is determined from output signals of the detectors of the UV sensors **60**.

Here, as the code the number of a card, for example, a plurality of quadrangular marks are arrayed on edges of the card. The number of the card is expressed by the numbers of the marks. The UV sensors **60** output ON signals when the marks are detected. Accordingly, the UV sensors **60** on both edges output ON signals of the numbers of the marks. In the

## 6

control box **14**, the ON signals input from the two UV sensors **60** are counted. Thereby, the two mark numbers detected by the two UV sensors **60** are obtained. Also, the control box **14** specifies the number of a card from the numbers of the marks.

In addition, although the numbers of marks and the number of a card may be the same as each other, they may not be the same as each other. The numbers of the marks and the number of a card only need to match each other one-on-one. In the control box **14**, a detected mark number is compared with a mark number that is registered in advance, and thereby, the number of a card may be specified.

Further, in the baccarat game, "J", "Q", and "K" are treated as equal to "10." Thus, the same code as "10" may be attached to "J", "Q", and "K." Further, in addition to the number of a card, a code representing a suit (spades, hearts, diamonds, and blacks) may be attached to a card, and this may be read. In this way, the type of codes is not limited if the numbers of cards required for a game are expressed.

As described above, in the present embodiment, the card reader **10** includes the UV sensors **60** that detects marks from a card and outputs signals. The above UV sensors **60** output ON signals during passage of marks. Marks including a given number are provided on a card, and the marks are provided on the edges of the card, and thereby arrayed in a card pulling direction so that they may pass through the UV sensors **60**. Then, the number of the marks is associated with the number of the card, and the control box **14** specifies the card from detection signals of the UV sensors **60**.

Further, as described above, in the card reader **10** of the present embodiment, the two UV sensors **60** are provided as shown in FIGS. **4** and **5**. Then, as shown in the example of FIG. **13**, marks are arrayed on both edges of a card in correspondence with both the UV sensors **60**, and the marks are read by both the UV sensors **60**. The marks are suitably provided in a region where a picture is not provided as shown. However, actual marks are not usually visible.

As described above, in the present embodiment, marks including a given number are suitably arrayed on each edge of a card. As for the association between a mark number and a card, the sum of mark numbers may simply be associated with the number of a card. Further, a combination of two rows of mark numbers may be associated with the number of a card. In the latter form, it is possible to identify more cards by few marks. In addition, FIG. **13** is just illustrative, and the number of mark rows is not limited to two, but the number of rows may be one or three or more. Also, two mark rows are suitably provided on each of both edges of a card. In this case, the arrangement of the UV sensors is also properly adjusted.

Further, additionally describing the configuration of the control box **14**, the control box **14** of the card reader **10** includes a counter, a memory (storage means), and a number specifying unit. The counter counts detection signals from the UV sensors **60**, and finds out a mark number. Also, the memory stores information that associates the mark number with a card. The associated information is typically a table. The number specifying unit specifies the number of a card from the numbers of marks with reference to the information of the memory.

In the present embodiment, the counter is able to find out two mark numbers corresponding to the two UV sensors **60**. As described above, in the present embodiment, a combination of a plurality of rows of mark numbers may be associated with a card. In this case, a memory stores information that associates the combination of the mark



numbers with a card. Also, the number specifying unit specifies a card corresponding to the combination of the card numbers.

Next, the object detecting sensor **62** and the measurement validity determining sensor **64** are fiber sensors that detect the existence or non-existence of a card. The object detecting sensor **62** is located on the most upstream side along the flow direction of a card on the card guide surface **52**, and the measurement validity determining sensor **64** is located on the downstream side of the object detecting sensor **62**. Also, as shown in FIG. **6**, the object detecting sensor **62** and the measurement validity determining sensor **64** are provided on the upstream and downstream sides of reading points of the UV sensors **60**. The object detecting sensor **62** and the measurement validity determining sensor **64** correspond to a first card detecting sensor and a second card detecting sensor, respectively.

Further, similarly to the UV sensors **60**, the object detecting sensor **62** and the measurement validity determining sensor **64** are arranged in the inner surface of the platform **12**, are fixed to the ceiling of the platform, and are exposed through the opening of the card guide surface **52**.

The object detecting sensor **62** and the measurement validity determining sensor **64**, as shown in FIG. **2**, are connected to the control box **14** by cables via a sensor amplifier **68**. The sensor amplifier **68** is of a two channel type, and is able to independently control the object detecting sensor **62** and the measurement validity determining sensor **64**. On the basis of detection signals of the object detecting sensor **62** and the measurement validity determining sensor **64**, the control box **14**, as will be described below, controls the start and end of reading of the UV sensors **60**, and determines whether or not a card has normally passed along the card guide surface **52**.

Further, as shown in FIG. **2**, a side surface of the platform **12** is further provided with a buzzer **70**, a push button **72** with a lamp, a reset switch **74**, an error lamp **76** (red), a monitor changeover switch **78**, and a normal lamp **80** (green). In the push button **72** with a lamp, the lamp is turned on or turned off whenever the button is pushed. The reset switch **74** is a switch of a type in which a key inserted into a keyhole is turned, and the monitor changeover switch **78** is a lever switch. Further, the upper surface of the platform **12** is provided with a standard/special mode changeover switch **82**. This switch **82** is also a switch of a type in which a key inserted into a keyhole is turned. Further, as shown in FIG. **7**, the back surface of the platform **12** is provided with a power switch **84** and a cable connector **86**. The above various switches, lamps, buzzer, etc. are connected to the control box **14** through cables, and are used for various kinds of processing of the control box **14**.

The configuration of the platform **12** has been described hitherto. As shown in FIG. **1**, the card reader **10** is further provided with the monitor **16** and the win/lose display box **18**.

The monitor **16** is controlled by the control box **14** to display the information on reading of a card, and a game. The win/lose display box **18** is provided with three lamps, i.e., a player-win lamp **90** (red), a draw lamp **92** (yellow), and a banker-win lamp **94** (green). These lamps are controlled by the control box **14**, and they are turned on or off in order to display the win or lose of a game. As shown in this description, the card reader **10** of the present embodiment is applied to a baccarat game.

Further, the monitor **16** and the win/lose display box **18** are set in a proper location on the game table **20**. On the

other hand, the control box **14** is arranged in a proper location, such as the underside of the game table **20**.

FIG. **8** is a functional block diagram of various components relevant to the control box **14**. The control box **14** is a computer apparatus as earlier mentioned. The control box **14** is connected to the UV sensors **60**, object detecting sensor **62**, and measurement validity determining sensor **64** of the platform **12**. Moreover, the control box **14** is connected to the various switches and lamps of the platform **12** to control them. Further, the control box **14** is connected to the monitor **16** and three lamps of the win/lose display box **18** to controls the display of them.

A computer serving as the control box **14** has a processing function to automatically determine win or lose of a game. This function is realized by incorporating a program for win/lose determination into the computer, and this program is executed by a processor of the computer.

As determination processing, the computer acquires the numbers of cards, which are sequentially taken out of the card shooter **22** to the game table **20**, using the UV sensors **60**. The acquired numbers of the cards are sequentially stored in the memory. At this time, the information on to which player each card has been distributed is also stored. That is, the numbers of cards are stored in association with distribution destinations.

From this point, the card reader **10** of the present embodiment is used in a baccarat game as earlier mentioned. In the baccarat game, two persons including a player and a banker exist (here, both are called players). Also, to which player the next card is to be distributed is uniquely determined from the number of cards distributed by then, and the number of each of the cards. The computer determines to which player a card read by the UV sensors **60** is to be distributed with reference to the numbers of the cards stored in the memory. Also, the number of the distributed card is stored in the memory in association with each player.

Moreover, the computer reads the numbers of the cards, which have been distributed to both players, from the memory, compares the numbers of the both players, and determines a win or lose. The numbers of the cards are summed, both sums are compared, and which player has won is determined. A draw is also determined.

As such, concerning the baccarat game, win or lose can be automatically determined only from the numbers of the cards sequentially taken out of the card reader **10**. To which player a card has been distributed may not be detected using other sensors, for example, sensors separately embedded in the table.

The control box **14** causes a game result to be output to the monitor **16** and the win/lose display box **18**. Read numbers, a game result, etc. are displayed on the monitor **16**. Further, in the win/lose display box **18**, a banker-win lamp **90**, a draw lamp **92**, or a player-win lamp **94** are turned on according to the game result.

Next, the functions of the object detecting sensor **62** and measurement validity determining sensor **64** will be described. As already described, the object detecting sensor **62** and the measurement validity determining sensor **64** detect the existence or non-existence of a card, and output detection signals to the control box **14**. In the present embodiment, if a card exists, a signal is turned on, and if a card disappears, a signal is turned off.

First, the detection signal of the object detecting sensor **62** is used to control the start and end of reading of the UV sensors **60**. That is, when the object detecting sensor **62** detects a card (from OFF to ON), the control box **14** instructs the UV sensors **60** to start reading. In the UV sensors **60**, an



LED is turned on, and a detector reads code. When the object detecting sensor 62 stops detecting a card (from ON to OFF, the control box 14 instructs the UV sensors 60 to end reading. In the UV sensors 60, an LED is turned off.

The object detecting sensor 62 and the measurement validity determining sensor 64 are further used to determine whether or not a card has normally passed along the card guide surface 52.

The first step of FIG. 9 shows a sensor output when (when a card has normally passed along the card guide surface) measurement is normal. In this case, a signal is turned on in order of the object detecting sensor 62 and the measurement validity determining sensor 64, and then, the signal is turned off in order of the object detecting sensor 62 and the measurement validity determining sensor 64. The reading result (measurement result) of the UV sensors 60 is valid (reading is approved).

However, if passage of a card is normal, but a mark number read by the UV sensors 60 read is abnormal, the control box 14 determines that the card itself is abnormal. For example, a card is abnormal when there is no mark at both edges of the card. The numbers of marks may be registered, and be compared with a detected mark number.

The second step of FIG. 9 shows a sensor output when a card slightly comes out onto a card guide, and slips back. The object detecting sensor 62 is turned on, and then, the object detecting sensor 62 is turned off. Since a card has not reached the measurement validity determining sensor 64, the measurement validity determining sensor 64 is not turned on. In this case, the reading result of the UV sensors 60 is invalidated.

The third step of FIG. 9 shows a sensor output when a card slips back after the card has reached the measurement validity determining sensor 64. A signal is turned on in order of the object detecting sensor 62 and the measurement validity determining sensor 64, and then, the signal is turned off in order of the measurement validity determining sensor 64 and the object detecting sensor 62. Even in this case, the reading result of the UV sensors 60 is invalidated.

The fourth step of FIG. 9 shows a sensor output when a cut card is taken out. Here, the cut card is a card used in a casino, etc., and is inserted into a deck of cards. Cards following the cut card are not used for a game. If this cut card is not disregarded, a read error is generated. Then, in order to disregard the cut card, the present embodiment is configured as follows.

Blue is given to the cut card. The sensitivity of the object detecting sensor 62 is adjusted so as to detect white and a mark color (a color when ultraviolet-ray reaction ink produces a color) as well as a blue object. On the other hand, the sensitivity of the object detecting sensor 64 is adjusted so as not to detect a blue object but to detect a white object and an object with a mark color. This is realized by lowering the sensitivity of the measurement validity determining sensor 64.

Since such sensitivity setting has been performed, when a cut card passes by as shown in the fourth step of FIG. 9, the object detecting sensor 62 is turned on, and then turned off. The measurement validity determining sensor 64 does not react. Accordingly, the same sensor output as the second step of FIG. 9 is obtained, and accordingly, reading of the UV sensors 60 is invalidated. In this way, passage of a cut card can be suitably disregarded.

In addition, although a cut card is blue in the above example, the invention is not limited thereto. A separate color may be given as long as it can adjust sensor sensitivity so that only a cut card may not be detected.

FIG. 10 shows examples of the above-mentioned sensor output waves. When measurement is valid, the object detecting sensor 62 and the measurement validity determining sensor 64 are normally turned on and off as described above. Also, the UV sensors 60 are turned on and off during the measurement (during "ON" of the object detecting sensor 62), and the number of a card is found out from ON/OFF signals of the UV sensors 60.

Since the card slips back in the following pattern, the object detecting sensor 62 is turned off before the measurement validity determining sensor 64 is turned on. Therefore, the reading result of the UV sensors 60 during the measurement is invalidated.

Since the cut card has passed along the card guide surface in the following pattern, only the object detecting sensor 62 is turned on and off, similarly to the above pattern. The UV sensors 60 do not output any ON signal. Even in this case, the reading result is invalidated.

Since a card on which a code is not printed has passed along the card guide surface in the following pattern, the object detecting sensor 62 and the measurement validity determining sensor 64 are normally turned on and off, but the UV sensors 60 are kept turned off during the measurement. In this case, the control box 14 determines that an abnormal card has passed along the card guide surface.

The functions of sensors have been described hitherto in detail. Next, the operation of the card reader 10 of the present embodiment will be described.

FIG. 11 shows the operation of the card reader 10 when one game is performed. The power switch 84 is turned on as a precondition of the operation of FIG. 11. Further, the lever of the monitor changeover switch 78 is tilted to a position "before a game," and the "before a game" is displayed on the monitor 16. Moreover, the key of the reset switch 74 is turned to the left that is a normal position. Further, the standard/special mode setting switch 82 is turned to the standard side.

A first card is read in this state (S10). It is determined whether or not reading (measurement) has been valid (S12) on the basis of the output of the object detecting sensor 62 and the measurement validity determining sensor 64. If the answer is NO (invalid) in S12, the process returns to S10. For example, when a card has slipped back or a cut card has passed along the card guide surface, the process returns to S10 from S12.

If the answer is YES (valid) in S12, it is determined whether or not the code of the card is normal (S14). For example, if there is no code, the answer is set to NO in S14. In this case, the error lamp 76 is turned on, and an alarm sound is emitted from the buzzer 70 (S16). An alarm sound is, for example, a large volume of continuous sound. If a reset switch 74 is operated, the alarm sound will stop. The reset switch 74 is turned to the right from the left, and slips back to the left.

If the answer is YES (normal) in S14, the normal lamp 80 is turned on, and a sound indicating normality from the buzzer 70 is emitted (S18). For example, a short small sound is output.

Next, game processing is performed (S20). Here, as earlier mentioned, the read number of the card is stored for a player or a banker. Then, the number of the card that is stored in advance is compared, it is determined whether or not the game is ended, and the win or lose of the game is determined. If the game is not ended (S22, NO), the process returns to S10 where the next card is read. If the game is ended (S22, YES), the process will wait for the operation of the monitor changeover switch 78 (S24).



## 11

Also, if the lever of the monitor changeover switch **78** is tilted to a position “after a game” (**S24**, YES), the display of the monitor **16** is switched to “after a game,” and a win or lose is displayed (**S26**). Further, even in the win/lose display box **18**, a lamp corresponding to a game result is turned on (**S28**).

If the lever of the monitor changeover switch **78** is tilted to a position “before a game” (**S30**, YES), the display of the monitor **16** is changed to “before a game,” and the processing is completed. Then, the process proceeds to the next game, and the processing of FIG. **11** is performed again.

FIG. **12** shows the operation of the card reader **10** when a special mode is set. The special mode is set by the control box **14** when the standard/special mode changeover switch **82** is turned to “Special.” The special mode is a first card invalid mode in which a card that is first pulled out in each game is invalidated.

FIG. **12** is different from FIG. **11** in that it is first determined whether or not any card is first just before **S10** (**S40**). Here, for example, the object detecting sensor **62** and the measurement validity determining sensor **64** are turned on in this order, and turned off in this order. As a result, when a card has passed along the card guide surface, it is determined whether or not this card is first. If a card is first, the process does not proceed to **S10** but returns to **S40**. If a card is not first, the process proceeds to **S10**. Accordingly, the second and succeeding cards are read.

Whether or not a card is first is determined, for example, using a flag. That is, when the flag is not raised in the processing of **S40**, it is determined that the card is first, and the flag is raised. Also, if the flag is raised, it will be determined that the card is not first. The flag is reset after the game is ended.

In addition, in the push button **72** with a lamp in the platform **12**, a lamp is turned on or turned off whenever the button is pushed. When the button **72** is turned off, the card reader **10** reads a card as described above. On the other hand, when the button **72** is turned on, the card reader **10** does not read a card. The button **72** is used, for example, when reading of the card reader **10** is temporarily suppressed.

The preferred embodiment has been described hitherto. According to the present embodiment, the platform **12** is provided between the game table **20** and the card shooter **22**, and the platform **12** is provided with a card reading function. Thus, reading of a card is enabled while the existing card shooter **22** is utilized. Moreover, since the black light sensors **60** are used, reading precision is high, and the threshold value of the card speed at the time of reading can also be set to a large value, for example, about 3.6 m/s. In this way, a card reader that is capable of utilizing an existing card shooter, is high in reading precision, and is high in the threshold value of the card speed at the time of reading can be provided. Also, the reading result of a card is suitably helpful to prevention of an illegal act.

Further, in the present embodiment, the card guide **50** has the card guide surface **52**, the edge of the card guide surface **52** is provided with the card guide rails **54**, and the card passage gap **56** is formed between the card guide surface **52** and the card guide rails **54**. Also, the black light sensors **60** are provided so as to read a card from the card guide surface **52** within the card passage gap **56**. Accordingly, the influence of outside light in a card reading part can be reduced, and reading precision can be improved.

Further, in the present embodiment, the computer of the control box **14** functions as a win/lose determining means, the win or lose of a card game is automatically determined on the basis of the numbers of cards that are sequentially

## 12

read by the black light sensors, and the determined game result is output from the monitor **16** and the win/lose display box **18**. Thus, an illegal act can be prevented while the progress of a game can be supported.

Further, in the present embodiment, the computer of the control box **14** functions as an invalid mode setting means, and a first card invalid mode can be set as described above. Accordingly, even when a rule that invalidates the first card is adopted, the card reader **10** can perform game result determination processing adapted to a card game, and can progress a card game smoothly.

Further, in the present embodiment, first and second card detecting sensors (the object detecting sensor **62** and the measurement validity determining sensor **64**) are arranged along the guiding direction of the card guide unit **50**, and the computer of the control box **14** functions as a measurement validity/invalidity determining means. Accordingly, the computer of the control box **14** can determine whether or not a card has normally passed along the card guide unit **50**.

Further, in the present embodiment, the computer of the control box **14** suitably determines that a card normally passed along the card guide unit, when the first card detecting sensor and the second card detecting sensor detect the card in order, and then, the first card detecting sensor and the second card detecting sensor stop detecting a card in order.

Further, in the present embodiment, the computer of the control box **14** invalidates reading of a card, when the card is detected in order of the first card detecting sensor and the second card detecting sensor, and then, detecting a card is stopped in order of the first card detecting sensor and the second card detecting sensor. Accordingly, when a card slips back, it is possible to suitably cope with this.

Further, in the present embodiment, the sensitivity of a second card detecting sensor is set low so as to detect a card for a game and so as not to detect a cut card. Accordingly, when a cut card is used, it is possible to suitably cope with this.

Further, in the card reader **10** of the above-described present embodiment, the black light sensors (UV sensors) detect code elements including a given number from a card which the code elements are arrayed in a card pulling direction as an ultraviolet-ray reaction code, and outputs a detection signal. Also, the card reader **10** includes a number specifying means, and the number specifying means specifies a card associated with the numbers of the code elements on the basis of the detection signals of the black light sensors. In the above embodiment, the code elements are marks printed with ultraviolet-ray reaction ink. Further, the number specifying means is the computer of the control box.

Further, an ultraviolet-ray reaction code may have plural rows of the code elements like the above example. A card may be specified by a combination of the numbers of the plural rows of code elements. In this case, a card is specified from the plural rows of code elements including given numbers. Accordingly, even in this case, the code elements including given numbers are read. Also, the number specifying unit specifies the number of a card associated with the numbers of the code elements.

In the present embodiment, as described above, the numbers of the code elements are associated with at least the number of a card. The numbers of the code elements may be associated with the type (spade, heart, etc.) of a card, in addition to the number of the card. Moreover, the numbers of the code elements may be associated with other information.

According to the present embodiment, since the black light sensors are provided, the code elements are detected by



## 13

the black light sensors, and a card is specified from the numbers of the code elements, the card can be detected with high precision.

Here, the advantages of the present embodiment will be described in more detail by contrast with a conventional technique.

The conventional technique uses a visible light camera. When the visible light camera is used, an existing conventional picture must be used for a card. The code elements like the present embodiment cannot be used for the following reason. That is, since only a photographic subject of visible light can be read when a camera is used, the code elements should also be printed with visible light ink. However, adding code elements onto a card separately from the conventional existing picture is not allowed in appearance. Accordingly, when the visible light camera is used, the code elements like the present embodiment cannot be used. On the other hand, the black light sensors are used in the present embodiment. Accordingly, the code elements just need to react to ultraviolet rays. That is, the code elements may not ordinarily be a photographic subject of visible light. As such, in the present embodiment, the black light sensors are provided so that the code elements can be utilized as objects to be read other than a conventional picture of a card.

Further, since the visible light camera is conventionally used, the conventional card picture must be used as described above. Therefore, the precision of reading is low, and the threshold value of the card speed at the time of reading is also low. On the other hand, in the present embodiment, the black light sensors detect code elements. Also, a card is specified from the numbers of the code elements. The code elements are, for example, marks. The numbers of the marks just needs to be counted, not the image processing of a picture. Such counting can be performed with high precision. Also, even if the card speed is increased, the counting of the mark numbers can be performed with high precision.

Further, the present embodiment is also different from a bar code reader. In the bar code reader, the thickness of a line is an object to be read. On the other hand, in the present embodiment, the thickness of a line is not detected, but marks are simply detected, and a card is specified from the numbers of the marks. Accordingly, even if the present embodiment is compared with the bar code reader, reading is precise, and the threshold value of the card speed at the time of reading increases.

As such, in the present embodiment, (1) black light sensors are provided, whereby objects to be read become code elements other than the conventional picture, and (2) unlike the conventional image processing of a picture, code elements are detected, and a card is specified from the numbers of the code elements. By virtue of these factors, precision of reading can be improved compared with the conventional technique, and the threshold value of the card speed at the time of reading can also be made high.

As an additional advantage, according to the present embodiment, code elements are suitably given to all the cards. Accordingly, it can be understood that, when any code elements are not detected, a card is abnormal. This is suitably helpful to prevention of an illegal act.

Further, as an additional advantage, according to the present embodiment, the black light sensors can be used to miniaturize an apparatus compared with a configuration provided with the conventional visible light camera.

Further, in the card reader **10** of the present embodiment, the platform **12**, the control box **14**, the monitor **16**, and the win/lose display box **18** are separately provided. As a

## 14

modified example, some or all of them may be integrated. For example, the control box **14** may be built in the platform **12**.

Further, since the card reader **10** of the present embodiment can be used for checking of a card for illegal act prevention, etc., it can be called a card checking apparatus. Also, since the card reader is used along with a shoe (shooter), it can also be called a shoe-type checking apparatus. Also, reading of a code in the above embodiment can also be called measurement for checking. Accordingly, the UV sensors **60** may be called code reading sensors, and may be called measuring sensors.

In another modified example, the card reader **10** of the present embodiment is integrated with a card shooter. In this case, an advantage that an existing card shooter can be utilized is no longer obtained. However, an advantage that reading precision can be improved is obtained, and an advantage that the threshold value of the card speed at the time of reading is raised is obtained.

FIG. **14** shows an integrated configuration. A card shooter apparatus **200** includes a housing **202**. The housing **202** corresponds to the configuration in which the housing of the shooter and the housing of the platform in the above-described embodiment are integrated together. The housing **202** is provided with a card shooter unit **204**. The card shooter unit **204** includes various components of the above-described card shooter.

The housing **202** is further provided with a card reading unit **206**, a control unit **208**, a first display unit **210**, and a second display unit **212**. The card reading unit **206** is composed of a card guide unit **214** and a sensor unit **216**.

The card guide unit **214** has the same function as the card guide unit in the above-described embodiment. In the above-described embodiment, the card guide unit is provided in the platform. In this configuration, the card guide unit **214** is provided in the housing **202**. The card guide unit **214** may be connected with a card outlet of the card shooter unit **204**, and may be integrated with the outlet.

The sensor unit **216** is composed of the sensors of the above-described embodiment. That is, the sensor unit **216** has two black light sensors **2161**, an object detecting sensor **2162**, a measurement validity determining sensor **2163**, and related components. In the above-described embodiment, the sensors are built in the platform. In this configuration, the sensor unit **216** is built in the housing **202**. Also, the sensor unit **216** is located in the place where the card guide unit **206** exists.

The control unit **208** is a control device corresponding to the control box of the above-described embodiment. In the above-described embodiment, the control box is arranged separately from the platform. In this configuration, the control unit **208** is built in the housing **202**.

The first display unit **210** is the monitor of the above-described embodiment. The second display unit **212** corresponds to the three lamps of the win/lose display box in the above-described embodiment. In the above-described embodiment, the monitor and the lamps are disposed on the table apart from the platform. In this configuration, the monitor of the first display unit **210** is provided on a side surface of the housing **202**. Further, the second display unit **212** is provided at a rear end of an upper surface of the housing **202**.

Similarly to the above-described embodiment, in the card shooter apparatus **200**, a card is read, read data is processed, and a processing result is displayed.

The preferred embodiment of the invention has been described hitherto. However, it is natural that the invention



is not limited to the above-described embodiment, but persons skilled in the art can alter the above-described embodiment within the scope of the invention.

#### INDUSTRIAL APPLICABILITY

The invention can improve the reading precision of the code of a card, and is useful in prevention of an illegal act. The invention claimed is:

1. A card shooter apparatus comprising:
  - a card shooter unit including a card housing which contains a plurality of cards and an opening, the plurality of cards used in playing a card game;
  - a card reading unit which is provided with a card guide unit which guides the cards along a card guide surface pulled out one by one from the opening onto a game table, the card reading unit reads a rank of the cards pulled out from the card shooter;
  - a control unit having a processing function to determine the result of the card game based on information about the cards, including the rank, sequentially read by the card reading unit;
  - one or more card detecting sensors configured to detect the existence or non-existence of the cards and to output one or more signals;
  - wherein the control unit further determines whether one or more of the cards has moved in an opposite direction along the card guide surface based on the one or more signals output from the one or more card detecting sensors;
  - an output means configured to output the result determined by the control unit; and
  - a display unit which indicates the result determined by the control unit;
- the card shooter unit, the card reading unit and the control unit integrated and able to be set on the game table, and the display unit includes a first display unit and a second display unit, wherein the first display unit is provided on a portion which is not adjacent to the second display unit and able to be seen only by the dealer and not by the player while the card shooter apparatus is set on the game table, and the second display unit is provided on the upper surface of the card shooter unit, the first display unit indicating at least the rank of the cards sequentially read by the card reading unit and the second display unit indicating the result of the card game
- wherein the determining of whether one or more of the cards has moved in an opposite direction along the card guide surface is based on the one or more signals output from the one or more card detecting sensors indicating whether one or more of the cards has moved in an opposite direction as compared to a direction in which the one or more of the cards are guided along the card guide surface pulled out one by one from the opening onto a game table.
2. The card shooter apparatus of claim 1, wherein the output means is further configured to emit a visual output indicating the result determined by the control unit.

3. The card shooter apparatus of claim 1, wherein the card reading unit is further configured to read the cards by reading invisible codes on the cards.

4. The card shooter apparatus of claim 1, wherein the control unit further determines whether the readings of the cards are valid based on the one or more signals output from the one or more card detecting sensors.

5. The card shooter apparatus of claim 4, wherein the output means is further configured to emit a sound indicating the result determined by the control unit when the readings of the cards are determined to be valid by the control unit.

6. The card shooter apparatus of claim 1, wherein the determining of whether one or more of the cards has moved in an opposite direction along the card guide surface is based on the one or more signals output from the one or more card detecting sensors and further comprises determining whether one or more of the cards has reversed direction after traveling in a direction in which the one or more of the cards are guided along the card guide surface pulled out one by one from the opening onto a game table.

7. The card shooter apparatus of claim 1, wherein the one or more card detecting sensors are positioned on the card guide surface.

8. The card shooter apparatus of claim 1, wherein the one or more card detecting sensors are fiber sensors.

9. The card shooter apparatus of claim 1, wherein the one or more card detecting sensors comprise a first card detecting sensor and a second card detecting sensor.

10. The card shooter apparatus of claim 9, wherein the first card detecting sensor comprises an object detecting sensor and the second card detecting sensor comprises a measurement validity determining sensor.

11. The card shooter apparatus of claim 10, wherein the object detecting sensor is positioned upstream of the measurement validity determining sensor with respect to a direction in which the one or more cards the cards are guided along the card guide surface pulled out one by one from the opening onto a game table.

12. The card shooter apparatus of claim 9, wherein the first card detecting sensor is arranged before the second card detecting sensor in a card dealing direction, and wherein the control unit determines whether one or more of the cards has moved in an opposite direction along the card guide surface when the first sensor is turned off indicating non-existence of a card after the first sensor is turned on indicating existence of a card and before the second sensor is turned on indicating existence of a card.

13. The card shooter apparatus of claim 1, wherein the first card detecting sensor is arranged before the second card detecting sensor in a card dealing direction, and wherein the control unit determines whether one or more of the cards has moved in an opposite direction along the card guide surface when the second sensor is turned off indicating non-existence of a card after the second sensor is turned on indicating existence of a card and before the first sensor is turned off indicating non-existence of a card.