



US009633577B2

(12) **United States Patent**  
**Constantine, III**

(10) **Patent No.:** **US 9,633,577 B2**  
(45) **Date of Patent:** **Apr. 25, 2017**

(54) **CPR TRAINING SYSTEM AND METHODS**

(56) **References Cited**

(71) Applicant: **ZOLL MEDICAL CORPORATION**,  
Chelmsford, MA (US)

U.S. PATENT DOCUMENTS

(72) Inventor: **Henry C. Constantine, III**, Rochester,  
NY (US)

4,683,890	A	8/1987	Hewson	
6,351,671	B1 *	2/2002	Myklebust et al.	607/5
6,356,785	B1	3/2002	Snyder et al.	
6,749,567	B2	6/2004	Davis et al.	
7,308,304	B2	12/2007	Hampton et al.	
2001/0047140	A1	11/2001	Freeman	
2004/0143298	A1	7/2004	Nova et al.	
2004/0210170	A1	10/2004	Palazzolo et al.	
2006/0015044	A1	1/2006	Stavland et al.	
2007/0010764	A1 *	1/2007	Palazzolo et al.	601/41
2007/0135739	A1 *	6/2007	Halperin et al.	601/41
2007/0197926	A1	8/2007	Danehorn et al.	
2007/0299473	A1	12/2007	Matos	

(73) Assignee: **ZOLL MEDICAL CORPORATION**,  
Chelmsford, MA (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

(Continued)

(21) Appl. No.: **13/633,391**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Oct. 2, 2012**

DE	3110915	A1	12/1982
WO	2006006871	A2	1/2006

(65) **Prior Publication Data**

US 2014/0093853 A1 Apr. 3, 2014

OTHER PUBLICATIONS

(51) **Int. Cl.**

<b>G09B 23/28</b>	(2006.01)
<b>A61B 5/02</b>	(2006.01)
<b>A61B 5/0205</b>	(2006.01)
<b>A61H 31/00</b>	(2006.01)

Aramendi et al. "A Simple Effective Filtering Method for Removing  
CPR Caused Artefacts from Surface ECG Signals". Computers in  
Cardiology. Sep. 25, 2005.

(Continued)

(52) **U.S. Cl.**

CPC ..... **G09B 23/28** (2013.01); **A61B 5/02**  
(2013.01); **A61B 5/0205** (2013.01); **A61B**  
**5/02055** (2013.01); **A61H 31/00** (2013.01)

*Primary Examiner* — Eddy Saint-Vil

(74) *Attorney, Agent, or Firm* — ZOLL Medical  
Corporation

(58) **Field of Classification Search**


CPC . A61B 2562/0219; A61B 5/11; A61B 5/6892;  
A61B 5/7242; A61B 5/02; A61B 5/0205;  
A61B 5/02055; A61H 2201/5061; A61H  
2201/5084; A61H 31/005; A61H 31/00;  
G09B 23/288

(57) **ABSTRACT**

A system including a chest compression sensor configured to  
detect at least one parameter corresponding to chest com-  
pressions of a subject and an electrocardiogram signal  
simulator configured to generate a simulated electrocardio-  
gram signal and combine and/or modify the simulated  
electrocardiogram signal with an output of the chest com-  
pression sensor to produce a simulated electrocardiogram  
signal with a CPR artifact.

USPC ..... 434/262, 265, 267; 600/300, 301  
See application file for complete search history.

**31 Claims, 8 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

2008/0208082 A1\* 8/2008 Nysaether et al. .... 600/595  
2010/0164612 A1 7/2010 Koyrakh  
2010/0292748 A9 11/2010 Stickney et al.  
2011/0034836 A1 2/2011 Halperin et al.  
2011/0066054 A1 3/2011 Yazicioglu et al.  
2011/0105930 A1 5/2011 Thiagarajan et al.  
2012/0150169 A1 6/2012 Zielinski et al.  
2012/0191024 A1\* 7/2012 Halperin et al. .... 601/41  
2013/0184600 A1 7/2013 Tan et al.

OTHER PUBLICATIONS

Romero et al. "Motion Artifact Reduction in Ambulatory ECG Monitoring: An Integrated System Approach". Wireless Health. Oct. 10, 2011.

\* cited by examiner

Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6






Fig. 7





Fig. 8



## CPR TRAINING SYSTEM AND METHODS

## TECHNICAL FIELD

The invention relates generally to methods and associated equipment for training users of medical devices.

## BACKGROUND

Automated External Defibrillators (AEDs) have been shown to be very effective in saving lives, when used quickly and properly. Depending on the condition of the subject, an effective treatment often combines the delivery of appropriately timed defibrillation therapy with continuous cardio-pulmonary resuscitation (CPR).

Advanced AED devices have been developed that can accommodate this simultaneous emergency treatment protocol. A key to expanding this life saving procedure has been the development of AED devices that can be used by non-medical personnel with limited training.

## SUMMARY

Various aspects of examples of the invention are set out in the claims. A system comprises a chest compression sensor configured to detect at least one parameter corresponding to chest compressions of a subject and an electrocardiogram signal simulator configured to generate a simulated electrocardiogram signal and combine the simulated electrocardiogram signal with an output of the chest compression sensor to produce a simulated electrocardiogram signal with a CPR artifact.

According to a second aspect of the present invention, a method comprises generating a simulated electrocardiogram signal and receiving an output of a chest compression sensor. The chest compression sensor is configured to detect at least one parameter corresponding to chest compressions of a subject. The method further comprises combining the simulated electrocardiogram signal with an output of the chest compression sensor to produce a simulated electrocardiogram signal with a CPR artifact and displaying at least one of the simulated electrocardiogram signal, the CPR artifact, the output of the chest compression sensor and the simulated electrocardiogram signal with the CPR artifact.

According to a third aspect of the present invention, a system comprises at least one processor and at least one memory including computer program code. The at least one memory and the computer program code is configured with the at least one processor to cause the system to generate a simulated electrocardiogram signal and receive an output of a chest compression sensor. The chest compression sensor is configured to detect at least one parameter corresponding to chest compressions of a subject. The system is further configured to combine the simulated electrocardiogram signal with an output of the chest compression sensor to produce a simulated electrocardiogram signal with a CPR artifact and display at least one of the simulated electrocardiogram signal, CPR artifact, output of the chest compression sensor and simulated electrocardiogram signal with the CPR artifact.

## BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings are not intended to be drawn to scale. In the drawings, each identical or nearly identical component that is illustrated in various figures is represented

by a like numeral. For purposes of clarity, not every component may be labeled in every drawing. In the drawings:

FIG. 1 is a diagram showing a simulated emergency response scene and a CPR training system including a device and external ECG signal simulator according to an example embodiment of the invention;

FIG. 2 is a diagram showing a chest compression sensor system according to an embodiment of the invention;

FIG. 3 is an exploded view of an assembly comprising a sensor/electrode connector of a chest compression sensor, a connector plug intercept of an ECG signal simulator, and a device connector according to an example embodiment of the invention;

FIG. 4 is a diagram showing a simulated emergency response scene and a CPR training system including a device and an internal ECG signal simulator according to an example embodiment of the invention;

FIG. 5 is a diagram of an ECG signal simulator and a chest compression sensor according to an example embodiment of the invention;

FIG. 6 is a schematic representation of various time-dependent, related waveforms associated with CPR;

FIG. 7 is a block diagram of a system comprising a chest compression sensor and an ECG signal simulator, the ECG signal simulator disposed within a medical monitoring device according to an example embodiment of the invention; and

FIG. 8 is a flow diagram depicting a method according to an example embodiment of the invention.

## DETAILED DESCRIPTION

FIG. 1 is a diagram showing a simulated emergency response scene **100a** and a CPR training system **101a** including a device **125a** and external ECG signal simulator **115a** according to an example embodiment of the invention. In the embodiment, a CPR training system comprises an ECG signal simulator such as ECG signal simulator **115a** that communicates with a chest compression sensor such as chest compression sensor **120**. ECG signal simulator **115a** modifies a simulated ECG output signal in real time based on the actual chest compressions being performed by trainee **105** on subject **110**. In an embodiment, ECG signal simulator **115a** combines an internally generated ECG signal with an output of the chest compression sensor to produce an ECG signal with a CPR artifact in real time.

In an embodiment, ECG signal simulator **115a** is configurable by a user to provide various simulated ECG waveforms such as but not limited to ventricular fibrillation (fine and coarse), ventricular tachycardia, atrial fibrillation, atrial ventricular block (third degree), absolute arrhythmia, pulseless electrical activity, asystole, and normal sinus rhythm. For training purposes, ECG signal simulator **115a** may be further configurable to provide various sequential combinations of simulated ECG waveforms such as but not limited to ventricular fibrillation and then normal sinus rhythm, ventricular tachycardia and then asystole, and so on. ECG signal simulator **115a** may be configurable to provide any number or combination of sequential ECG waveforms useful for providing instruction to a trainee.

Further, ECG signal simulator **115a** may include a user interface such as user interface **116** to enable a user to select particular waveforms or combinations of waveforms. In an embodiment, ECG signal simulator **115a** comprises a touch screen display **116**, however, ECG signal simulator **115a** may comprise any number of input and/or output elements

as part of the user interface such as but not limited to buttons, knobs, switches and/or the like.

In an embodiment, ECG signal simulator **115a** comprises at least one communication interface, such as communication interface **117**. A communication interface is a wired or wireless interface, which is capable of transmitting and/or receiving signals. In the embodiment, the communication interface is capable of receiving signals from CPR sensor **120**. The communication interface is capable of transmitting signals related to at least one of an ECG simulated signal and CPR artifact signal. Signals from ECG simulator **115a** may be transmitted through interface **135** to a display, medical monitoring device, AED or other device capable of displaying data related to the signals such as device **125a**.

An ECG signal simulator may be disposed as a standalone unit such as ECG signal simulator **115a**. However, the ECG simulator need not be a physically separate device that is required to be plugged into device **125a**. As further described in FIG. 4, the ECG signal simulator may be disposed within a medical monitoring device such as device **125b** of FIG. 4. In another embodiment, ECG signal simulator may be disposed in a mannequin such as mannequin **110**. The mannequin can be instrumented with an ECG signal simulator so that the ECG signal may be read directly by an applied electrode system.

The chest compression sensor **120** may be any chest compression sensor system, such as a CPR-D•padz® accelerometer-based sensor system available from Zoll Medical Corporation as shown in FIG. 2 and described more fully below. Signals from a CPR sensor may comprise data from at least one accelerometer, which may be disposed within the CPR sensor. Accelerometer data may include but are not limited to data related to least one of acceleration, velocity, displacement, amplitude, rate of CPR compressions and the like.

A device **125a** comprising display **130a** may be used to display at least one of the ECG simulated signal, the CPR artifact signal and the ECG signal complicated by the CPR artifact. Device **125a** may be any device comprising a display, which is capable of displaying ECG waveforms. For example, device **125a** may be any type of AED, medical monitoring device, display and/or the like such as but not limited to an AED E-Series Monitor Defibrillator manufactured by the Zoll Medical Corporation of Chelmsford, Mass.

According to FIG. 1, trainee **105** performs chest compressions on a mannequin **110** in an effort to improve her knowledge and performance in the delivery of CPR. A trainee may be a lay person with little or no experience in CPR, emergency medical technician (EMT), a police officer, firefighter, or a medical professional such as a physician or nurse, and/or the like. Further, trainee **105** may receive instruction and feedback with respect to her performance of CPR and on how to use certain medical devices, such as ECG signal simulator **115a** and device **125a**. The instructions and/or trainee feedback may be provided by device **125a**, for example, when display device **125a** is an AED such as an AED Plus manufactured by the Zoll Medical Corporation. In this way, the device can be used for training a rescuer in a simulated emergency situation with accommodation for ECG signal input complicated by an actual CPR artifact.

When device **125a** is a medical monitoring device such as an AED, device **125a** can react in a similar manner as it would in the event of a real-life emergency on a subject, including providing a defibrillation therapy shock when conditions warrant. A trainee such as trainee **105** can learn how the medical monitoring device responds to a subject's

condition and how the trainee's actions during CPR affect the course of events. By replicating a real-life emergency, the trainee is placed in the best position to react quickly and effectively in the event of an actual real-life emergency.

In an embodiment, when ECG signal simulator **115a** generates a simulated true ECG signal (ventricular fibrillation (fine and coarse), ventricular tachycardia, atrial fibrillation, atrial ventricular block (third degree), absolute arrhythmia, pulseless electrical activity, asystole, and normal sinus rhythm, etc.), device **125a** prompts the trainee **105** to begin CPR. As chest compressions are initiated by trainee **105** and sensed by the CPR sensor, the output of the CPR sensor is input to each of device **125a** and the ECG signal generator **115a**. Device **125a** monitors both the rate and the magnitude of compressions and directs the trainee accordingly. For example, if device is an AED manufactured by Zoll Medical Corporation, Zoll's Real CPR Help® functionality guides the trainee to ensure optimal CPR protocol, in accordance with AHA guidelines. Device **125a** monitors compression data from the CPR sensor in real time and provides an adaptive metronome to help the trainee with the proper rate and depth, saying "Push harder" or "Good compressions," as needed. CPR compression rate and/or depth can also be displayed on display **130a**. In this manner, the trainee rapidly achieves and maintains the correct rate and depth of chest compressions during CPR.

If the trainee **105** pauses CPR, since device **125a** is directly connected to the CPR sensor, the device **125a** may recognize that CPR is not being performed and directs the trainee to "Start CPR." The onset of CPR compressions may cause the output of the ECG signal simulator to change in real time, consistent with the rate and depth of CPR compressions being performed.

Device **125a** may monitor the changing ECG signal complicated by chest compressions and, consistent with the teachings of U.S. Pat. No. 6,865,413 ("413 patent"), which is incorporated herein by reference in its entirety, applies a correction to the changing ECG signal to separate the CPR-induced artifact in the signal from the underlying simulated true ECG signal.

When the device **125a** determines that the subject's condition is appropriate for defibrillation therapy, device **125a** may direct the trainee to stop CPR and deliver a shock to the mannequin. To avoid actual delivery of the shock to the electrodes attached to the mannequin, the connector plug intercept may include a suitably sized resistor, to dissipate safely the electromagnetic energy, or shunt the shock energy to the simulator where it is dissipated.

In this manner, a fully operational, field usable device **125a** can be employed in a training setting with a mannequin to replicate as realistically as possible the operation and functioning of an advanced AED system. Neither the AED device nor the trainee is deceived as to the effect of the CPR compression data on the ECG signal. The generated baseline simulated true ECG signal is modified in real time to include a CPR compression artifact consistent with the CPR compressions being performed by the trainee. Device **125a**, with the benefit of its integrated internal CPR artifact functionality, effectively subtracts out the CPR artifact from its received signal, to monitor the underlying true ECG signal.

Device **125a** in accordance with embodiments of the invention accurately presents to a trainee, in a convincing fashion, the effects of CPR compressions being performed by the trainee. Various signals, including the CPR sensor output (e.g., acceleration, velocity, and displacement), the CPR artifact, and the ECG signal with and without the CPR artifact can be displayed individually or in various combi-

nations to the trainee, to provide additional understanding of the electrophysiological effects of CPR on the victim and operation of the AED device. A trainer selectable mode switch may be provided on the ECG generator for this purpose. Accordingly, the trainee can appreciate that the AED device is able to analyze the underlying heart rhythm, despite the CPR artifact.

Device **125a** can be configured by user for “training mode” to permit training and demonstration functionality, as well as emergency treatment capability, in a single device. Alternatively, control software or hardware in device **125a** could be adapted to recognize the insertion of the connector plug intercept and not deliver a high energy shock to the electrodes, but otherwise perform in a real life manner to simulate a real rescue. Further, the device **125a** may be used in a “normal operating mode” which effectively turns off the ECG simulation capability for normal operation.

Device **125a** may be configured with a mode switch, that can be selected by the trainer or the trainee to display the CPR artifact laden ECG signal or the underlying ECG signal with the CPR artifact filtered out. The CPR artifact laden ECG signal depicts an artifact synchronized with the actions of the rescuer on the subject, correlated to CPR sensor compression depth and rate.

FIG. 2 is a diagram showing a chest compression sensor system **171** according to an embodiment of the invention. A chest compression sensor system **171** may be any chest compression sensor, such as a CPR-D•padz® accelerometer-based sensor system available from Zoll Medical Corporation. In an embodiment, chest compressor sensor **120** of FIG. 1 is chest compression sensor system **171**.

The CPR-D•padz® system comprises a pair of ECG signal pickup electrodes **172** configured to attach adhesively to a subject’s chest to acquire data indicative of the subject’s heart rhythm and to convey a defibrillating shock, if appropriate. The electrode pair **172** is integrated with a chest compression sensor pad **180** in a one-piece, pre-connected apparatus. For example, see U.S. Pat. No. 7,245,974, the disclosure of which is incorporated herein by reference in its entirety. Conventional AED systems require that the rescuer use and place two separate electrodes. By using CPR hand placement as a landmark, the combined system can be positioned and adhered to the mannequin’s chest quickly and in the appropriate location and orientation.

The chest compression sensor system **171** further comprises a communication interface **178** comprising sensor wires **174** and electrode wires **176**. In an embodiment, the communication interface **178** couples with a device such as device **125a** of FIG. 1. In another embodiment, the communication interface **178** couples with an intercept plug such as intercept plug **135** of FIG. 1 and/or intercept plug **165** of FIG. 3. In an embodiment, the communication interface couples with a ECG signal simulator such as ECG signal simulator **115a**.

FIG. 3 is an exploded view of an assembly **150** comprising a sensor/electrode connector **160** of a chest compression sensor, a connector plug intercept **165** of an ECG signal simulator, and a device connector **169** according to an example embodiment of the invention. Assembly **150** is configured to carry signals from a chest compression sensor such as chest compression sensor system **171** of FIG. 2 through sensor/electrode connector **160** and connection plug intercept **165** to at least one of an ECG signal simulator and a device such as device **125a** of FIG. 1. In an embodiment, leads **155** are configured to electrically couple assembly **150** with a chest compression sensor such as chest compression sensor system **171** of FIG. 2.

Assembly **150** is further configured to carry at least one of a simulated ECG signal, chest compression artifact signal, and a modified simulated ECG signal from an ECG signal simulator such as ECG signal simulator **115a** of FIG. 1 to a device such as device **125a** of FIG. 1. In an embodiment, leads **167** are configured to electrically couple assembly **150** with an ECG signal simulator such as ECG signal simulator **115a**. In an embodiment, leads **170** are configured to electrically couple assembly **150** with a device such as device **125a**. In an embodiment, assembly **150** is interface **135** of FIG. 1.

In an embodiment, assembly **150** may further couple defibrillator electrodes such as electrodes **172** of FIG. 2 with a device such as an AED. In an embodiment, to avoid actual delivery of a shock from an AED to the electrodes, which may be attached to a mannequin, connector plug intercept **165** can include a suitably sized resistor, to safely dissipate the electric shock energy or shunt the shock energy to the ECG signal simulator where it is dissipated. The ECG signal simulator optionally can include circuitry for delivering a simulated subject impedance signal to the AED device. In another embodiment, the ECG signal simulator can include circuitry for shunting a defibrillation therapy output signal of an AED device.

FIG. 4 is a diagram showing a simulated emergency response scene **100b** and a CPR training system **101b** including a device **125b** and an internal ECG signal simulator **115b** according to an example embodiment of the invention. In an embodiment, a CPR training system such as CPR training system **101b** comprises an ECG signal simulator **115b** disposed within a device such as device **125b** and a chest compression sensor such as chest compression sensor **120**. ECG signal simulator **115b** modifies a simulated ECG output signal based on actual chest compressions being performed by a trainee such as trainee **105**. In an embodiment, ECG signal simulator **115b** is an internal version of external ECG signal simulator **115a** of FIG. 1 and comprises substantially the same functionality as ECG signal simulator **115a** of FIG. 1. Device **125b** may be used to display at least one of the ECG simulated signal, the CPR artifact signal and the ECG signal complicated by the CPR artifact signal. In this way, the display device can be used for training a rescuer in a simulated emergency situation with accommodation for ECG signal input complicated by an actual CPR artifact.

The chest compression sensor **120** may be any chest compression sensor system, such as a CPR-D•padz® accelerometer-based sensor system available from Zoll Medical Corporation as shown in FIG. 2 and described more fully below.

A device such as device **125b** may be any device capable of displaying an ECG waveform, which includes embedded ECG signal simulator **115b**. For example, device **125b** may be any type of AED, medical monitoring device, display and/or the like such as but not limited to an AED E-Series Defibrillator manufactured by the Zoll Medical Corporation of Chelmsford, Mass.

When device **125b** is an AED used with CPR training system **101b** according to an embodiment, the AED can react in a similar manner as it would in the event of a real-life emergency on a subject, including providing a defibrillation therapy shock when conditions warrant. A trainee such as trainee **105** can learn how the AED responds to a subject’s condition and how the trainee’s actions during CPR affect the course of events as described above for trainee **105** of FIG. 1.

In FIG. 4, trainee **105** performs chest compressions on a mannequin **110** in an effort to improve her knowledge and

performance in the delivery of CPR. Further, trainee **105** may receive instruction and feedback with respect to her performance of CPR and/or on how to use certain medical devices, for example, medical monitors and defibrillators, ECG signal simulator **115b** and display device **125**. In an embodiment, the instructions and/or feedback may be provided by display device **125b**, for example, when display device **125b** is an AED such as an AED Plus manufactured by the Zoll Medical Corporation of Chelmsford, Mass.

In an embodiment, ECG signal simulator **115b** is configurable to provide various simulated ECG waveforms such as but not limited to ventricular fibrillation (fine and course), ventricular tachycardia, atrial fibrillation, atrial ventricular block (third degree), absolute arrhythmia, pulseless electrical activity, asystole, and normal sinus rhythm. For training purposes, ECG signal simulator **115b** may be configurable to provide various sequential combinations of simulated ECG waveforms such as but not limited to ventricular fibrillation and then normal sinus rhythm, ventricular tachycardia and then asystole, and so on. ECG signal simulator **115b** may be configurable to provide any number or combination of sequential ECG waveforms useful for providing instruction to a trainee.

Further, ECG signal simulator **115b** may include a user interface such as user interface **116b** to enable a user to select particular waveforms or combinations of waveforms. In an embodiment, ECG signal simulator **115b** comprises a touch screen display **116b**, however, ECG signal simulator **115b** may comprise any number of input and/or output elements as part of a user interface such as but not limited to buttons, knobs, switches and/or the like.

In an embodiment, ECG signal simulator **115b** comprises at least one communication interface, such as communication interface **117b**. A communication interface is a wired or wireless interface, which is capable of transmitting and/or receiving signals. In the embodiment, the communication interface is capable of receiving signals from a chest compression sensor, such as chest compression sensor **120**. Signals from a chest compression sensor may comprise CPR artifact data from at least one accelerometer, which may be disposed within the chest compression sensor. Accelerometer data may include but is not limited to data related to least one of acceleration, velocity, displacement, amplitude, rate of CPR compressions and the like. In the embodiment, the communication interface is capable of transmitting signals related to at least one of an ECG simulated signal and CPR artifact signal.

FIG. **5** is a diagram of an ECG signal simulator **300** and a chest compression sensor **315** according to an example embodiment of the invention. In an embodiment, ECG signal simulator **300** is ECG signal simulator **115a** of FIG. **1**. In another embodiment, ECG signal simulator **300** is ECG signal simulator **115b** of FIG. **4**.

In an embodiment, ECG signal simulator **300** comprises a signal generator **310**, which is configured to produce a simulated true ECG signal such as but not limited to ventricular fibrillation (fine and course), ventricular tachycardia, atrial fibrillation, atrial ventricular block (third degree), absolute arrhythmia, pulseless electrical activity, asystole, and normal sinus rhythm. In an embodiment, ECG signal generator is configurable by a user to provide any one simulated ECG signal or various configurable sequential combinations of simulated ECG waveforms such as but not limited to ventricular fibrillation and then normal sinus rhythm, ventricular tachycardia and then asystole, and so on. For example, waveform **705** of FIG. **6** may represent output **325** of ECG signal simulator.

A chest compression sensor **315**, which may utilize at least one accelerometer, provides chest compression data to the ECG signal simulator as input signal **340**. In the embodiment, when a user provides chest compressions using chest compression sensor **315** to a subject, the sensor produces chest compression signal **340**. An example waveform depicting a chest compression signal **340** is shown as signal **710** of FIG. **6**, wherein reference **725** represents a time when CPR begins. An example waveform depicting an actual accelerometer signal is shown as signal **720** of FIG. **6**. Chest compression sensor data may include but is not limited to data related to least one of acceleration, velocity, displacement, amplitude, rate of CPR compressions and the like. A chest compression sensor may be any type of chest compression sensor such as but not limited to chest compression sensor **171** of FIG. **2**, chest compression sensor **120** of FIGS. **1** and **4**.

In an embodiment, input signal **340** feeds ECG signal generator **310** and transfer function **360**. When ECG signal generator **310** is configured to produce a ventricular fibrillation waveform, ECG signal generator **310** may modify received input signal **340** to provide a ventricular fibrillation waveform with a higher amplitude and/or frequency relative to the amplitude and/or frequency of the corresponding chest compressions detected by chest compression sensor **315**. Simultaneously, the simulated ECG signal **325** is modified by signal modifier **312** to include a CPR artifact signal **345** correlated with the actual rate and depth of compressions being performed. The signal modification can be performed in accordance with the teaching of the '413 patent or similar technique. In an embodiment, the influence of the CPR compressions can be modeled as the output of a linear system perturbed by the actual chest compression sensor signal. For example, output **345** of transfer function **360** can be summed with the simulated true ECG signal **325** to produce a simulated ECG signal with true CPR artifact **350**, which tracks the influence of the actual CPR compressions being performed. For example, a simulated true ECG signal with true CPR artifact is depicted as waveform **715** of FIG. **6**. When CPR is not being performed, the CPR sensor input **345** to the summing junction **312** is zero and signals **350** and **330** represent an unmodified simulated ECG signal. The onset of chest compressions causes the output of the ECG signal generator to change in real time, consistent with the rate and depth of CPR compressions being performed.

In an embodiment, a signal modifier **327** may receive as inputs simulated ECG signal with true CPR artifact **330** and chest compression signal **345**. Signal modifier **327** may be configured to produce signal **335**, which represents the simulated ECG signal with a removed or substantially reduced CPR artifact component signal. For demonstration purposes, in this way, a trainee such as trainee **105** of FIG. **4** may observe CPR artifact reduction technology in a simulated environment.

FIG. **7** is a block diagram of a system **200** comprising a chest compression sensor **273** and an ECG signal simulator **255**, the ECG signal simulator **255** disposed within a medical monitoring device such as medical monitoring device **205** according to an example embodiment of the invention. In an embodiment, a medical monitoring device **205** is a defibrillator such as but not limited to the Zoll X-Series Monitor Defibrillator manufactured by Zoll Medical Corporation of Chelmsford, Mass. In an embodiment, ECG signal simulator **255** is ECG signal simulator **300** of FIG. **5**. In an embodiment, chest compression sensor **273** is chest com-

pression sensor **315** of FIG. **5**. In an embodiment, chest compression sensor **273** is chest compression sensor **120** of FIG. **4**.

Medical monitoring device **205** further comprises at least one memory such as volatile memory **225** and/or a non-volatile memory **230**. Volatile memory **225** may comprise a cache area for the temporary storage of data. Medical monitoring device **205** may further comprise non-volatile memory **230**, which may be embedded and/or removable. The non-volatile memory **230** may further comprise an electrically erasable programmable read only memory (EEPROM), flash memory, and/or the like. In an embodiment, medical monitoring device **205** may use memory to store any number of pieces of information and/or data to implement one or more features of medical monitoring device **205** such as the defibrillation unit **235** or ECG signal simulator **255**.

Medical monitoring device **205** may comprise at least one processor such as processor **210** and may comprise at least one other processing component. Processor **210** may comprise circuitry for implementing medical monitoring features such as but not limited to ECG signal simulation, signal modification, defibrillation as well as other medical monitor functionality. For example, the at least one processor **210** may comprise a digital signal processor device, a microprocessor device, a digital to analog converter, other support circuits, and/or the like. Further, the processor **210** may comprise features to operate one or more software programs. In an embodiment, the processor **210** may be capable of operating a software program to implement functionality of the ECG signal simulator, defibrillator signal modification, signal filtering, defibrillation, connectivity as well as other medical monitor functionality. Further, the connectivity program may allow the medical monitoring device **205** to transmit and receive Internet and/or cellular data, such as but not limited to voice, text, email messages, location-based content, web page content, fax content and/or the like. Further, in an embodiment, processor **220** is configured to execute a software program for configuring and/or operating the ECG signal simulator **255**. In an embodiment, processor **220** is configured to of execute a software program for configuring chest compression sensor **273**.

In an embodiment, the medical monitoring device **205** comprises at least one antenna **297** to communicate with a transmitter **213** and a receiver **212**. Transmitter **213** and/or receiver **212** are coupled with a network interface **214** for transmitting and receiving data with devices such as other medical equipment or emergency medical services centers. Processor **210** provides at least one signal to the transmitter **213** and receives at least one signal from receiver **212**. Further, transmitter **213** and/or receiver **212** coupled with network interface **214** may be configured to transmit and receive voice communications such as with emergency medical personnel.

Further, the medical monitoring device **205** may further comprise an identifier, such as international mobile equipment identification (IMEI) code, capable of uniquely identifying itself. For example, the processor **210**, using the stored instructions, may determine an identity, e.g., using cell identification information.

Medical monitoring device **205** further comprises a user interface **215**, which may include at least one input and/or output device coupled with processor **210** such as but not limited to a display, touch screen, keyboard, keypad, mouse and/or the like. In the embodiment, display **220** coupled with processor **210** and ECG signal simulator **255** is capable of displaying at least one of a simulated electrocardiogram

signal, CPR artifact signal and an output of a signal modifier. In an embodiment, a keypad or keyboard enables a user to configure an ECG simulator such as ECG simulator **255** to produce at least one waveform such as but not limited to ventricular fibrillation (fine and coarse), ventricular tachycardia, atrial fibrillation, atrial ventricular block (third degree), absolute arrhythmia, pulseless electrical activity, asystole, and normal sinus rhythm. Further, the keypad or keyboard may enable a user to compose text-based messages and communicate with other users such as emergency medical personnel. In an embodiment, medical monitoring device **205** further comprises a speaker **217** and/or a microphone **280**. Speaker **217**, for example, may enable the medical monitoring device to provide voice instructions to a user. Microphone **280**, for example, may enable a user to speak with emergency medical personnel via network interface **214** at an emergency response facility.

System **200** further comprises a chest compression sensor such as chest compression sensor **273** configured to detect at least one parameter corresponding to chest compressions of a subject. The at least one parameter may be at least one of acceleration, velocity, displacement amplitude and rate of chest compressions. In an embodiment, chest compression sensor **273** communicates the at least one parameter with processor **210** through chest compression sensor interface **270**. Further, processor **210** may display the at least one parameter to a user via user interface **215** and/or display **220**. In an embodiment, processor **210** may instruct ECG signal simulator to combine the at least one parameter from chest compression sensor **273** such as but not limited to acceleration or velocity with the output of the ECG signal simulator **255**. The resulting ECG simulated signal with CPR artifact may be displayed by display **220**, through user interface **215** or sent remotely through network interface **214**.

In an embodiment, medical monitoring device **205** further comprises at least one power supply such as battery **205** for providing power to medical monitoring device and/or for charging defibrillation unit **235**. Medical monitoring device **205** may further comprise a location determining unit **240**. Location determining unit **240** may comprise a global positioning system (GPS) receiver for receiving a geographic location of medical monitoring device **205**. Location determining unit **240** may use cell identification information to determine a geographic location for medical monitoring device **205**.

In an embodiment, system **200** further comprises electrodes **277** electrically coupled with medical monitoring device **205**. In an embodiment, electrodes **277** are electrodes **171** of FIG. **2**. In the embodiment, electrodes **277** are electrically and physically connected with electrode interface **275**. Processor **210** may monitor a subject's ECG signal through electrodes **277**. Defibrillation unit **235** may analyze a subject's ECG signal and determine whether or not to provide a defibrillation shock to the subject using electrodes **277**. In an embodiment, CPR artifact reduction unit **250** may monitor signals from chest compression sensor **273** through chest compression sensor interface **270** and filter at least some of the CPR artifact from an ECG waveform received through electrodes interface **275**.

In an embodiment, medical monitoring device **205** further comprises a carbon dioxide monitoring unit **260** coupled with processor **210** configured to monitor a subject's end tidal carbon dioxide (EtCO<sub>2</sub>). Medical monitoring device **205** may monitor a subject's other physiological parameters. For example, in an embodiment, medical monitoring device **205** comprises a pulse oximeter configured to measure a subject's oxygen saturation SpO<sub>2</sub>.

## 11

FIG. 8 is a flow diagram depicting a method 800 according to an example embodiment of the invention. In an embodiment, at 805 a simulated ECG signal is generated by an ECG signal simulator such as ECG signal simulator 115a of FIG. 1, ECG signal simulator 300 of FIG. 5 and ECG signal generator 255 of FIG. 7. The simulated ECG signal may be but is not limited to one of ventricular fibrillation (fine and coarse), ventricular tachycardia, atrial fibrillation, atrial ventricular block (third degree), absolute arrhythmia, pulseless electrical activity, asystole, and normal sinus rhythm.

At 810, an output of a chest compression sensor is received by the ECG signal simulator. The chest compression sensor is configured to detect at least one parameter corresponding to chest compressions of a subject. The chest compression sensor may be but is not limited to chest compression sensor 120 of FIGS. 1 and 4, chest compression sensor 180 of FIG. 2, chest compression sensor 315 of FIG. 5 or chest compression sensor 273 of FIG. 6. The at least one parameter may be but is not limited to acceleration, velocity, displacement, amplitude and rate of chest compressions.

At 815, the simulated ECG signal is modified or combined with an output of the chest compression sensor to produce a simulated electrocardiogram signal with a CPR artifact. The simulated ECG signal may be modified by signal modifier 312 of FIG. 5 to include a chest compression signal component correlated with the actual rate and depth of compressions being performed. As previously disclosed, the signal modification can be performed in accordance with the teaching of the '413 patent or any similar or appropriate technique. The influence of the CPR compressions can be modeled as the output of a linear system perturbed by the actual chest compression sensor signal. For example, output of a chest compression sensor can be summed with the simulated ECG signal to produce a simulated ECG signal with CPR artifact, which tracks the influence of the actual CPR compressions being performed.

At 820, at least one of the simulated ECG signal, CPR artifact, output of the chest compression sensor and the simulated ECG signal may be displayed. One or more of the signals may be displayed by any display capable of displaying an ECG signal, for example, a medical monitoring device or device 125a of FIG. 1.

At 825, a CPR artifact may be filtered from a simulated ECG signal and the filtered ECG signal may be displayed. The CPR artifact may be filtered in any manner such as but not limited to utilizing the See-Thru CPR filtering techniques and methods developed by Zoll Medical Corporation of Chelmsford, Mass.

Without in any way limiting the scope, interpretation, or application of the claims appearing below, a technical effect of one or more of the example embodiments disclosed herein is to provide system for CPR training. The CPR training system allows a user to perform chest compressions on a subject and view one or more simulated ECG waveforms complicated by a true ECG artifact signal, which tracks the influence of the actual CPR compressions being performed. Another technical effect of one or more of the example embodiments disclosed herein is to provide a method for training a user to perform CPR on a subject and observe a number of possible ECG waveforms complicated by CPR artifact. Another technical effect of one or more of the example embodiments disclosed herein is to provide a method for training a user to observe a number of possible ECG waveforms complicated by a CPR artifact and removal or substantial reduction thereof.

## 12

Embodiments of the present invention may be implemented in software, firmware, hardware, application logic or a combination of software, hardware and application logic. The software, firmware, application logic and/or hardware may reside on at least one of system such as system 115a of FIG. 1, system 125b of FIG. 4, system 300 of FIG. 5 and system 200 of FIG. 7. If desired, part of the software, application logic and/or hardware may reside on system such as system 205 of FIG. 7 and part of the software, application logic and/or hardware may reside on system such as system 255 of FIG. 7. In an embodiment, the application logic, software or an instruction set is maintained on any one of various conventional computer-readable media. In the context of this document, a "computer-readable medium" may be any media or means that can contain, store, communicate, propagate or transport the instructions for use by or in connection with an instruction execution system, apparatus, or device, such as a computer, with one example of a computer described and depicted in FIG. 7. A computer-readable medium may comprise a computer-readable storage medium that may be any media or means that can contain or store the instructions for use by or in connection with an instruction execution system, apparatus, or device, such as a computer.

If desired, the different functions discussed herein may be performed in a different order and/or concurrently with each other. Furthermore, if desired, one or more of the above-described functions may be optional or may be combined.

Although various aspects of the invention are set out in the independent claims, other aspects of the invention comprise other combinations of features from the described embodiments and/or the dependent claims with the features of the independent claims, and not solely the combinations explicitly set out in the claims. It is also noted herein that while the above describes example embodiments of the invention, these descriptions should not be viewed in a limiting sense. Rather, there are several variations and modifications which may be made without departing from the scope of the present invention as defined in the appended claims.

What is claimed is:

1. A cardio-pulmonary resuscitation (CPR) training system, comprising: a chest compression sensor configured to detect at least one parameter corresponding to chest compressions of a mannequin and generate a chest compression signal; and an electrocardiogram signal simulator comprising a transfer function with a single input to the transfer function, the electrocardiogram signal simulator configured to: receive the chest compression signal from the chest compression sensor as the single input to the transfer function; generate a first electrocardiogram signal representative of cardiac-induced electrical activity; and generate a modification signal that acts upon the first electrocardiogram signal to create a second, modified electrocardiogram signal that simulates an electrocardiogram signal of a patient undergoing chest compressions during cardiac arrest, the modification signal simulating a compression-induced artifact that would be present in a measured electrocardiogram signal in a non-simulated environment as a result of mechanical disturbances from the chest compressions, wherein the modification signal is based on the chest compression signal and is generated at least in part by applying the transfer function to the chest compression signal.

2. The CPR training system of claim 1, comprising a display coupled with the electrocardiogram signal simulator, the display configured to present at least one of the first electrocardiogram signal, the modification signal, the sec-



ond, modified electrocardiogram signal, the compression-induced artifact, and an output of the chest compression sensor.

3. The CPR training system of claim 2, wherein the second, modified electrocardiogram signal includes the compression-induced artifact, the compression-induced artifact being synchronized with the chest compressions of the mannequin and correlated to a depth and rate of the chest compressions of the mannequin.

4. The CPR training system of claim 1, wherein the electrocardiogram signal simulator is disposed within a medical monitoring device.

5. The CPR training system of claim 4, wherein the medical monitoring device comprises a defibrillator.

6. The CPR training system of claim 1, wherein the first electrocardiogram signal simulates at least one of ventricular fibrillation, ventricular tachycardia, atrial fibrillation, atrial ventricular block third degree, absolute arrhythmia, pulseless electrical activity, asystole and normal sinus rhythm.

7. The CPR training system of claim 1, wherein the at least one parameter is at least one of acceleration, velocity, displacement, amplitude and rate of chest compressions.

8. The CPR training system of claim 1, comprising an artifact reduction unit configured to remove the compression-induced artifact from the second, modified electrocardiogram signal.

9. The CPR training system of claim 1, wherein the CPR training system comprises a medical monitoring device.

10. The CPR training system of claim 9, wherein the medical monitoring device is configured to generate the first electrocardiogram signal when operating in a training mode and not generate the first electrocardiogram signal when operating in a normal mode.

11. The CPR training system of claim 1, comprising a display coupled with the electrocardiogram signal simulator, the display configured to present the first electrocardiogram signal and the second, modified electrocardiogram signal.

12. The CPR training system of claim 1, wherein the electrocardiogram signal simulator is configured to remove the compression-induced artifact from the second, modified electrocardiogram signal to generate a filtered electrocardiogram signal, and wherein the CPR training system comprises a display configured to present the first electrocardiogram signal, the modification signal, the second, modified electrocardiogram signal, the compression-induced artifact, and the filtered electrocardiogram signal.

13. The CPR training system of claim 1, wherein the modification signal simulates a compression-induced artifact caused by changes in half-cell potential of electrodes of a medical monitoring device used to measure the measured electrocardiogram signal in the non-simulated environment.

14. The CPR training system of claim 1, wherein the compression-induced artifact is consistent with characteristics of the chest compressions of the mannequin.

15. The CPR training system of claim 1, comprising a display coupled with the electrocardiogram signal simulator, the display configured to present the compression-induced artifact.

16. The CPR training system of claim 1, wherein the electrocardiogram signal simulator is configured to combine the first electrocardiogram signal and the modification signal to produce the second, modified electrocardiogram signal that includes the compression-induced artifact.

17. A method for training a rescuer to perform cardio-pulmonary resuscitation (CPR), comprising: generating a first electrocardiogram signal representative of cardiac-induced electrical activity; receiving a chest compression

signal from a chest compression sensor as a single input to a transfer function, the chest compression sensor configured to detect at least one parameter corresponding to chest compressions of a mannequin; generating a modification signal that acts upon the first electrocardiogram signal to create a second, modified electrocardiogram signal that simulates an electrocardiogram signal of a patient undergoing chest compressions during cardiac arrest, the modification signal simulating a compression-induced artifact that would be present in a measured electrocardiogram signal in a non-simulated environment as a result of mechanical disturbances from the chest compressions, wherein the modification signal is based on the chest compression signal and is generated at least in part by applying the transfer function to the chest compression signal; and presenting at least one of the first electrocardiogram signal, the modification signal, the second, modified electrocardiogram signal, the compression-induced artifact, and an output of the chest compression sensor.

18. The method of claim 17, wherein the presenting is performed by a medical monitoring device.

19. The method of claim 17, wherein the first electrocardiogram signal simulates at least one of ventricular fibrillation, ventricular tachycardia, atrial fibrillation, atrial ventricular block third degree, absolute arrhythmia, pulseless electrical activity, asystole, and normal sinus rhythm.

20. The method of claim 17, wherein the at least one parameter comprises an indication of at least one of acceleration, velocity, displacement, amplitude and rate of chest compressions.

21. The method of claim 17, comprising filtering the compression-induced artifact from the second, modified electrocardiogram signal.

22. The method of claim 21, comprising presenting a filtered electrocardiogram signal.

23. The method of claim 17, wherein at least one of the generating the first electrocardiogram signal and generating the modification signal is performed by an electrocardiogram signal simulator.

24. The method of claim 23, wherein the electrocardiogram signal simulator is disposed within a medical monitoring device configured to generate the first electrocardiogram signal when operating in a training mode and not generate the first electrocardiogram signal when operating in a normal mode.

25. The method of claim 24, wherein the medical monitoring device comprises a defibrillator.

26. A cardio-pulmonary resuscitation (CPR) training system, comprising: at least one processor; and at least one memory including computer program code; the at least one memory and the computer program code configured with the at least one processor to cause the system to: generate a first electrocardiogram signal representative of cardiac induced electrical activity; receive a chest compression signal from a chest compression sensor as a single input to a transfer function, the chest compression sensor configured to detect at least one parameter corresponding to chest compressions of a mannequin; generate a modification signal that acts upon the first electrocardiogram signal to create a second, modified electrocardiogram signal that simulates an electrocardiogram signal of a patient undergoing chest compressions during cardiac arrest, the modification signal simulating a compression-induced artifact that would be present in a measured electrocardiogram signal in a non-simulated environment as a result of mechanical disturbances from the chest compressions, wherein the modification signal is based on the chest compression signal and is generated at least in

part by applying the transfer function to the chest compression signal; and present at least one of the first electrocardiogram signal, the modification signal, the second, modified electrocardiogram signal, the compression-induced artifact, and an output of the chest compression sensor. 5

**27.** The CPR training system of claim **26**, wherein the at least one parameter is at least one of acceleration, velocity, displacement, amplitude and rate of chest compressions.

**28.** The CPR training system of claim **26**, wherein the at least one memory and the computer program code is configured with the at least one processor to cause the system to filter the compression-induced artifact from the second, modified electrocardiogram signal. 10

**29.** The CPR training system of claim **28**, wherein the at least one memory and the computer program code is configured with the at least one processor to cause the system present a filtered electrocardiogram signal. 15

**30.** The CPR training system of claim **26**, wherein the CPR training system is disposed within a medical monitoring device configured to generate the first electrocardiogram signal when operating in a training mode and not generate the first electrocardiogram signal when operating in a normal mode. 20

**31.** The CPR training system of claim **30**, wherein the medical monitoring device comprises a defibrillator. 25

\* \* \* \* \*