

US009640154B2

(12) **United States Patent**  
**Sikra**

(10) **Patent No.:** **US 9,640,154 B2**  
(45) **Date of Patent:** **May 2, 2017**

(54) **HI-HAT PEDAL ASSEMBLY**

- (71) Applicant: **Drum Workshop, Inc.**, Oxnard, CA (US)
- (72) Inventor: **Richard A Sikra**, Thousand Oaks, CA (US)
- (73) Assignee: **DRUM WORKSHOP, INC.**, Oxnard, CA (US)
- (\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/002,264**

(22) Filed: **Jan. 20, 2016**

(65) **Prior Publication Data**  
US 2016/0210946 A1 Jul. 21, 2016

**Related U.S. Application Data**

- (60) Provisional application No. 62/106,144, filed on Jan. 21, 2015, provisional application No. 62/106,661, filed on Jan. 22, 2015.
- (51) **Int. Cl.**  
*G10D 13/02* (2006.01)  
*G10D 13/06* (2006.01)  
*G10D 13/00* (2006.01)
- (52) **U.S. Cl.**  
CPC ..... *G10D 13/065* (2013.01); *G10D 13/006* (2013.01)
- (58) **Field of Classification Search**  
CPC ..... G10D 13/065; G10D 13/006  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,147,661 A *	9/1964	Padera .....	G10D 13/065 84/422.4
3,530,757 A *	9/1970	Osuga .....	G10D 13/065 84/422.3
4,145,951 A *	3/1979	Kobayashi .....	G10D 13/065 84/422.3
4,449,440 A *	5/1984	Hoshino .....	G10D 13/065 84/422.3
4,488,471 A *	12/1984	Youakim .....	G10D 13/065 248/158
4,517,876 A *	5/1985	Duhon .....	G10D 13/065 84/421
4,667,562 A *	5/1987	Lee .....	G10D 13/065 84/421

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 14/506,350, filed Oct. 3, 2014, Sikra.  
(Continued)


*Primary Examiner* — Robert W Horn

(74) *Attorney, Agent, or Firm* — Koppel, Patrick, Heybl & Philpott

(57) **ABSTRACT**

Drum pedal assemblies are disclosed which can include one or more adjustment features. Adjustment features which can be included in embodiments of the present disclosure can include components for adjusting pedal angle and/or height, and the resistance offered by the pedal (such as due to a spring connection). Pedal assemblies according to some embodiments of the present disclosure can include rotatable base plates for easy storage and travel. Pedal assemblies according to some embodiments the present disclosure can include securing means such as retractable spikes for stabilizing the pedal assembly.

**31 Claims, 5 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS

4,846,040 A \* 7/1989 Hoshino ..... G10D 13/065  
84/422.1  
4,976,181 A \* 12/1990 Hsieh ..... G10D 13/065  
84/422.3  
4,977,810 A \* 12/1990 Hsieh ..... G10D 13/065  
84/422.3  
5,090,289 A \* 2/1992 Holcomb ..... G10D 13/006  
84/422.1  
5,251,528 A \* 10/1993 Kurosaki ..... G10D 13/065  
84/422.3  
5,301,592 A 4/1994 Johnson  
5,789,688 A \* 8/1998 Schiano ..... G10D 13/065  
84/422.1  
5,945,616 A \* 8/1999 Hoshino ..... G10D 13/065  
84/422.3  
6,003,822 A \* 12/1999 Kurosaki ..... G10D 13/065  
248/161  
6,031,170 A \* 2/2000 Hoshino ..... G10D 13/065  
84/422.2  
6,271,450 B1 8/2001 Mackie  
6,278,046 B1 \* 8/2001 Sikra ..... G10D 13/065  
84/422.1  
6,329,584 B1 \* 12/2001 Liao ..... G10D 13/065  
84/422.1  
6,399,865 B1 \* 6/2002 Ishimatsu ..... G10D 13/065  
84/421  
6,590,147 B2 7/2003 Kassabian  
6,747,200 B2 \* 6/2004 Sato ..... G10D 13/065  
84/422.1  
6,762,354 B2 7/2004 Cocca  
6,930,232 B2 \* 8/2005 Shigenaga ..... G10D 13/065  
84/422.3  
7,301,088 B2 \* 11/2007 Chen ..... G10D 13/006  
84/422.1  
7,371,953 B2 \* 5/2008 Takegawa ..... F16M 11/36  
84/422.3

7,511,212 B1 \* 3/2009 Chang ..... G10D 13/065  
84/422.1  
7,633,000 B2 \* 12/2009 Dorfman ..... G10D 13/006  
464/136  
7,737,352 B2 \* 6/2010 Chang ..... G10D 13/065  
248/166  
7,968,781 B1 \* 6/2011 Luo ..... G10D 13/006  
84/422.1  
8,063,293 B1 11/2011 Kjellgren  
8,455,746 B2 6/2013 Johnson et al.  
8,859,870 B2 \* 10/2014 Yamane ..... G10D 13/024  
84/422.1  
8,946,531 B2 \* 2/2015 Nakata ..... G10D 13/065  
84/422.3  
8,993,865 B2 \* 3/2015 Liao ..... G10D 13/006  
84/422.1  
2003/0209128 A1 \* 11/2003 Hsieh ..... G10D 13/065  
84/422.3  
2006/0169124 A1 \* 8/2006 Tanaka ..... G10D 13/065  
84/422.3  
2008/0245210 A1 \* 10/2008 Chang ..... G10D 13/065  
84/421  
2015/0082968 A1 \* 3/2015 Sikra ..... G10D 13/006  
84/422.1  
2016/0210946 A1 \* 7/2016 Sikra ..... G10D 13/065

OTHER PUBLICATIONS

U.S. Appl. No. 14/495,718, filed Sep. 24, 2014, Sikra.  
U.S. Appl. No. 13/663,655, filed Oct. 30, 2012, Sikra.  
U.S. Appl. No. 61/882,538, filed Sep. 25, 2013, Sikra.  
U.S. Appl. No. 61/899,762, filed Nov. 4, 2013, Sikra.  
DWCP3500 "Hi-Hat Stand" from Drum Workshop, Inc., available  
online at [www.dwdrums.com](http://www.dwdrums.com), downloaded Feb. 3, 2016.  
International Search Report and Written Opinion from Appl. No.  
PCT/US14/57383, dated Dec. 17, 2014.

\* cited by examiner




FIG. 1





FIG. 2






FIG. 4




FIG. 5

## 1

## HI-HAT PEDAL ASSEMBLY

This application claims the benefit of U.S. Provisional Patent Application 62/106,144 to Sikra, filed on Jan. 21, 2015, and to U.S. Provisional Patent Application 62/106,661 to Sikra, filed on Jan. 22, 2015, each of which is fully incorporated by reference herein in its entirety.

## BACKGROUND OF THE INVENTION

## Field of the Invention

This invention relates generally to drum/cymbal pedal assemblies that can connect to drums and/or cymbals, such as hi-hat systems, and more particularly to pedal assemblies with features that can adjust the tension, resistance, and/or delay time that a user experiences upon actuating the pedal.

## Description of the Related Art

A hi-hat is a common component of a drum set that can include two cymbals facing one another and mounted on a vertical tube or pole. A hi-hat can be operated in many different ways, including by a foot pedal which can cause the cymbals to strike one another, or by actuation using a drum stick, among other operation methods. The top and/or bottom cymbal can be adjustable so as to be mounted at different heights; in many prior art systems, the height of the top cymbal is adjustable. Adjustable cymbals can be attached to the tube using a clutch, which can aid in adjusting the cymbal height. Some exemplary clutches are described, for example, in U.S. patent application Ser. No. 14/506,350 to Sikra, filed on Oct. 3, 2014, which is fully incorporated by reference herein in its entirety. Either cymbal can be adjusted so as to be, for example, separated from the other cymbal, to be in loose contact with the other cymbal, or to be in tight contact with the other cymbal.

Pedal assemblies are used as a mechanism with which a drummer can strike a drum and/or a cymbal, such as a hi-hat, with his or her feet, thus allowing the drummer's hands to be free for use with other instruments. Variations in drummer technique mean that it is very difficult to design a single pedal assembly to meet the needs of every drummer. Such variables can include desired drumming speed, foot force, and/or desired strike point, among other variables.

Adjustable pedals can provide the customization necessary to achieve some or all of a drummer's desired pedal characteristics. Some pedals with adjustable features are described in U.S. Pat. Nos. 5,301,592 and 8,455,746 to Johnston and U.S. Pat. No. 6,590,147 to Kassabian, each of which is fully incorporated by reference herein in its entirety. However, adjustment mechanisms provided in the prior art can be unwieldy, which can increase difficulty to the user, and/or can lack adjustability of a variable which is independent of other variables, thus reducing the amount of customization available via adjustments.

Accordingly, there is a present need for a novel and efficient design for a pedal assembly for use with percussion instruments such as hi-hats which specifically addresses the aforementioned problems.

## SUMMARY OF THE DISCLOSURE

The present disclosure relates to drum pedal assemblies for use with an instrument, such as a hi-hat. The pedal assembly can include various adjustable features such that a user can alter the operation of the pedal assembly to fit his or her needs and playing style.

One embodiment of a pedal assembly according to the present disclosure can include a pedal, and a spring operably

## 2

connected to the pedal. A first spring tensioning feature can be operable to adjust the length of the spring mechanism.

Another embodiment of a pedal assembly according to the present disclosure can include a base plate and a pedestal, and a pedal on the base plate. The base plate can be rotatable relative to the pedestal.

Yet another embodiment of a pedal assembly according to the present disclosure can include a pedestal assembly and a pedal connected to the pedestal assembly. Securing means can be attached to the pedestal assembly to interact with an object or surface thereunder.

Yet another embodiment of a pedal assembly according to the present disclosure can include a pedestal assembly, pedal, and spring mechanism operably linked to the pedal. A rigid link member can be between the pedal and spring mechanism. A bracket can be attached to the pedestal assembly, and can include a portion between the link member and the spring. The position of the bracket can be adjustable.

This has outlined, rather broadly, the features and technical advantages of the present disclosure in order that the detailed description that follows may be better understood. Additional features and advantages of the disclosure will be described below. It should be appreciated by those skilled in the art that this disclosure may be readily utilized as a basis for modifying or designing other structures for carrying out the same purposes of the present disclosure. It should also be realized by those skilled in the art that such equivalent constructions do not depart from the teachings of the disclosure as set forth in the appended claims. The novel features, which are believed to be characteristic of the disclosure, both as to its organization and method of operation, together with further features and advantages, will be better understood from the following description when considered in connection with the accompanying figures. It is to be expressly understood, however, that each of the figures is provided for the purpose of illustration and description only and is not intended as a definition of the limits of the present disclosure.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of one embodiment of pedal assembly **100** according to the present invention.

FIG. 2 is another perspective view of the pedal assembly **100** according to the present invention.

FIG. 3 is another perspective view of the pedal assembly **100** according to the present invention.

FIG. 4 is an exploded perspective view of another embodiment of a pedal assembly **200** according to the present invention.

FIG. 5 is another exploded perspective view of the pedal assembly **200** according to the present invention.

## DETAILED DESCRIPTION OF THE INVENTION

The present invention relates to a drum and/or cymbal beating devices and assemblies, such as a pedal device for use with a hi-hat. While pedal assemblies described herein may be described in certain cases as "hi-hat pedal assemblies," it is understood that these pedal assemblies can be modified to fit other uses such as with other percussion instruments, or that concepts described with regard to a hi-hat pedal assembly can be incorporated into other types of pedal assemblies. The hi-hat pedal assembly according to the present invention can include various adjustment fea-



tures and/or interlocking features. The adjustment features can adjust the tension and/or resistance a user experiences when actuating the pedal, the rebound characteristics of the pedal as it returns to its rest position after an actuation, and/or the inclination angle of the pedal. Moreover, the adjustment features can cause the pedal assembly to become collapsible. The hi-hat pedal assembly can also include a flexible heel plate attached to a base and/or pedal. Additionally, the hi-hat pedal assembly can include interconnection features such as tab/slot combinations for connecting two or more parts of the device. These tab/slot combinations can reduce or eliminate undesired movements. Such interconnection features are described in U.S. patent application Ser. No. 14/495,718 to Sikra, which is fully incorporated by reference herein.

Throughout this disclosure, the preferred embodiment and examples illustrated should be considered as exemplars, rather than as limitations on the present invention. As used herein, the terms “invention,” “device,” “apparatus,” “method,” “present invention,” “present device,” “present apparatus” or “present method” refers to any one of the embodiments of the invention described herein, and any equivalent and similar embodiments. Furthermore, reference to various feature(s) of the “invention,” “device,” “apparatus,” “method,” “present invention,” “present device,” “present apparatus” or “present method” throughout this document does not mean that all claimed embodiments or methods must include the referenced feature(s).

It is also understood that when an element or feature is referred to as being “on” or “adjacent” to another element or feature, it can be directly on or adjacent the other element or feature or intervening elements or features may also be present. In contrast, when an element is referred to as being “directly on” or extending “directly onto” another element, there are no intervening elements present. Additionally, it is understood that when an element is referred to as being “connected” or “coupled” to another element, it can be directly connected or coupled to the other element or intervening elements may be present. In contrast, when an element is referred to as being “directly connected” or “directly coupled” to another element, there are no intervening elements present.

Furthermore, relative terms such as “inner,” “outer,” “upper,” “top,” “above,” “lower,” “bottom,” “beneath,” “below,” and similar terms, may be used herein to describe a relationship of one element to another. Terms such as “higher,” “lower,” “wider,” “narrower,” and similar terms, may be used herein to describe angular relationships. It is understood that these terms are intended to encompass different orientations of the elements or system in addition to the orientation depicted in the figures.

Although the terms first, second, etc., may be used herein to describe various elements, components, regions and/or sections, these elements, components, regions, and/or sections should not be limited by these terms. These terms are only used to distinguish one element, component, region, or section from another. Thus, unless expressly stated otherwise, a first element, component, region, or section discussed below could be termed a second element, component, region, or section without departing from the teachings of the present invention. As used herein, the term “and/or” includes any and all combinations of one or more of the associated list items.

The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms “a,” “an,” and “the” are intended to include the plural forms

as well, unless the context clearly indicates otherwise. For example, when the present specification refers to “an” assembly, it is understood that this language encompasses a single assembly or a plurality or array of assemblies. It will be further understood that the terms “comprises,” “comprising,” “includes” and/or “including” when used herein, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

It is understood that while the present disclosure makes reference to pedal assemblies for use with percussion assemblies, such as hi-hats, and that pedal assemblies for drums and/or cymbal assemblies are the primary application concerned with the present disclosure, devices incorporating features of the present invention can be utilized with any application.

Embodiments of the invention are described herein with reference to view illustrations that are schematic illustrations. As such, the actual thickness of elements can be different, and variations from the shapes of the illustrations as a result, for example, of manufacturing techniques and/or tolerances are expected. Thus, the elements illustrated in the figures are schematic in nature and their shapes are not intended to illustrate the precise shape of a region and are not intended to limit the scope of the invention.

FIG. 1 is a perspective view of one embodiment of a pedal assembly 100 according to the present invention, which can be a hi-hat pedal assembly. The hi-hat pedal assembly 100 can comprise a base plate 102, hinge piece 104, heel plate 106, and pedal 108. The hi-hat pedal assembly 100 can also comprise several different drum key screws or rotatable members, including the drum key screws or rotatable members 110, spring tension screw or drum key screw 112, drum key screw or rotatable member 114, and/or drum key screw or rotatable member 116. It is understood that while the phrase “drum key screw” in places throughout this disclosure, any similar connecting/attachment/fastening mechanism including but not limited to rotatable members can be used in place of a drum key screw. Further, while the specific embodiments shown herein include base plates, such as the base plate 102, it is understood that embodiments of the present invention without base plates are possible. For example, instead of a base plate, embodiments of pedal assemblies according to the present invention can include a heel plate connected to a pedestal assembly via rods or similar structures. One example of an assembly not incorporating a base plate, for example, is the DWCP3500 Hi-Hat Stand, available from Drum Workshop, Inc. of Oxnard, Calif., U.S.A. Such assemblies not having a base plate can include the other components, features, and/or capabilities of embodiments of the present invention described herein.

The hi-hat pedal assembly 100 can comprise a spring assembly such as the spring assembly 118 shown in FIG. 1. The spring assembly 118 can be connected to a spring (not shown) and/or a spring bushing (not shown), such as a compression spring. The spring assembly 118 can be, for example, the same as or similar to the spring assembly 218 shown in FIGS. 4 and 5, including a spring bushing and a spring. The spring assembly 118 can include a substantially vertical portion, a substantially horizontal portion, a spring bushing on the substantially horizontal portion, and a spring on the spring bushing and/or substantially horizontal portion. The spring bushing and/or spring can be partially or fully within hi-hat piping 140. It is understood that in certain embodiments of the present invention, the spring may be

above and/or rest on the spring bushing, and in other embodiments the spring may be above and/or on the horizontal portion of the spring assembly. Embodiments without a spring bushing are also possible, and many different shapes of spring assemblies are possible.

The hi-hat pedal assembly **100** can also comprise a bracket **122**, rod **124**, and pedestal **126**, which can itself include a pedestal baseplate **126a**. The bracket **122** can be adjustable, such as but not limited to vertically adjustable, and/or can be slidable, or in other embodiments may or may not be capable of movements including but not limited to sliding. Additionally, the bracket **122** can take many different shapes, including but not limited to an "L" shape "C" shape. Additionally, the hi-hat pedal assembly **100** can comprise a clamp locking assembly **128**, pedal attachment mechanism **130**, link member **132**, and the hi-hat tubing **140**. It is understood that different combinations of these and other components, including combinations omitting some of the above components, are possible.

The hi-hat pedal assembly **100** can include the ability to rotate and/or collapse amongst itself for storing purposes. As shown in FIGS. 1-3, some embodiments of the present invention can include drum key screws **110**, clamp locking assemblies such as the clamp locking assembly **128**, and/or a clamp screw **138**, all of which can work together to allow the base plate **102** to incline and/or decline. The clamp screw **138** can be loosened or tightened to control whether the clamp locking assembly **128** is in an open or a locked position. When in a locked position, a forward portion **128a** of the clamping assembly **128** can be proximate the pedestal base plate **126a**, in contact with the pedestal base plate **126a**, and/or within an aperture of the pedestal base plate **126a**. This placement of the clamping assembly **128** and/or the forward portion **128a** can prevent rotation of the base plate **102** with respect to the pedestal **126**. When in an open position, the forward portion **128a** of the clamping assembly **128** can be raised further away from the pedestal base plate **126a**. Placement of the forward portion **128a** further away from the pedestal base plate **126a** can enable rotation of the footboard **102** about the drum key screws **110**.

Tightening of the drum key screws **110** can also prevent or make difficult movement of the base plate **102**, even if the clamping assembly **128** is in an open position. When the clamp locking assembly **128** is in an open position, the base plate **102** can incline. If the clamp locking assembly **128** is in a locked position, and/or, in some embodiments, if the drum key screws **110** are tightened, then the base plate **102** cannot be inclined, or can be more difficult to incline. As such, the clamp locking assembly **128** and/or the drum key screws **110** can be operable to control the incline and/or decline of the base plate **102** as desired by the user.

When the base plate **102** inclines or declines, such as inclines or declines in a rotational manner, the pedal **108** can move and/or rotate along with the base plate **102**. When the base plate **102** and pedal **108** are inclined, one or both of the base plate **102** and pedal **108** can align at angles of 45° or above, and/or in some embodiments at angles of 60° or above, and/or in some embodiments at angles of 75° or above, and/or in some embodiments at an angle of near 90° or 90°, such as at or near the same angle as the pedestal **126** and/or hi-hat tubing **140** so as to be approximately parallel with the pedestal **126** and/or hi-hat tubing **140**. Drum key screws such as the drum key screws **110** can then be re-tightened to lock the base plate **102** and pedal **108** into a compact position, and/or to make rotation or movement of the base plate **102** relative to the pedestal **126** more difficult. This can allow the hi-hat pedal assembly **100** to become

much easier to store and/or transport. To reverse the process, drum key screws **110** can be loosened so that the base plate **102** and/or pedal **108** can decline. Once the base plate **102** and/or the pedal **108** are declined, the clamp locking assembly **128** can be locked into position and/or the drum key screws **110** can be tightened, which can replicate the positioning shown in FIGS. 1-3.

While the above describes a locking/rotation system incorporating a single drum key screw **110** on each side of the pedal assembly **100**, it is understood that further such mechanisms can be used. For example, another drum key screw can be included below each of the drum key screws **110**, with these additional screws being placed within an aperture pathway of the base plate portions **102a** (it is understood that while the base plate portions **102a** are shown as portions of the base plate **102**, embodiments where these portions are separate elements is also possible). Thus, when not tightened, rotation could be enabled about the drum key screws **110**, and when tightened rotation could be prevented or made more difficult. It is understood that such mechanisms could be used with or without mechanisms previously described, such as, for example, the clamp locking assembly **128**.

The direct drive assembly **120** can comprise a link member **132**, bracket **122**, and/or rod **124**. While a direct drive assembly is shown in the specific embodiment of FIGS. 1-3, it is understood that other types of drive assemblies, such as chain drive assemblies, can be used in embodiments of the present invention. User movement of pedal **108** corresponds to movement of link member **132**, bracket **122**, and/or rod **124** in a generally downward direction. A cymbal can be mounted on the rod **124** and can form the top cymbal of a hi-hat assembly, such that actuation of the pedal **108** causes the rod **124** and cymbal to move downward such that the top cymbal impacts the bottom cymbal. As displayed in FIG. 1, the link member **132**, bracket **122**, and/or rod **124** can all be connected to one another. The rod **124** can extend up and into hi-hat tubing **140**.

The direct drive assembly **120** can be configured such that the hi-hat pedal assembly **100** can be played in a manner such that other components of the pedal assembly **100** immediately respond or nearly immediately responds to user movement of the pedal **108**, with little or no rebound after the pedal assembly has returned to its resting position. One factor in one such configuration is that the linking member **132** is rigid, such as metal. In hi-hat pedals known in the art, a chain is often used to pull the hi-hat cymbals together. However, a chain has "flop" or "give," which can result in a delay or lag time once the user moves a pedal (and/or in the resulting return of the pedal to its resting position). As such, the direct drive assembly **120** of the present invention can allow a user to play with no, little, and/or reduced flop or give. While in some embodiments, the link member **132**, bracket **122**, and/or rod **124** are all rigid components that work in conjunction to allow the present invention to be played with no, little, and/or reduced delay or lag time, it is understood that embodiments of the present invention can also utilize chains, ropes, straps, and/or similar components in addition to or in place of those described above.

In some embodiments, the positioning of the bracket **122** can affect the playing experience of the user. In embodiments of the present invention, the position of the bracket **122** can be adjustable, such as vertically adjustable. In the specific embodiment shown, the bracket **122** is movable upward and downward, such as being slidable upward and downward. As shown in FIG. 3, the drum key screw **142** (or in other embodiments another type of device) can control the

movement of the bracket **122**. When the drum key screw **142** is loosened, the bracket **122** can be moved up or down. If the bracket **122** is in a lowered position, the pedal stop **123** may impact the bracket **122**, such as the lower portion of the “L” or “C” in an L-shaped or C-shaped bracket upon a user releasing the pedal **108**, causing the pedal **108** to immediately or nearly immediately stop its upward motion upon impact. A pedal in such a configuration does not have much, if any, rebound upon the pedal assembly **100** returning to its resting position. Such a configuration can also result in the pedal **108** being at a relatively lower angle when the pedal assembly **100** is in its resting position.

If, however, the bracket **122** is in a raised position as shown in FIG. **3**, the bracket **122** is further from the pedal stop **123**. This can result in more rebound or bounce of the pedal **108**, such as after the pedal has reached its maximum angle and/or the pedal stop **123** has impacted the bracket **122** (such as the lower portion of the “L” in the L-bracket shown). In some such embodiments, the pedal stop **123** may not even be in contact with the bracket **122** when the system is at rest, allowing even more rebound and/or bounce for the pedal **108**. For example, in some embodiments the bracket **122** can be adjusted such that the pedal **108** may actually rebound downward after reaching its maximum angle, such as due to spring action, instead of or in addition to contacting the bracket **122**. Such a configuration can also result in the pedal **108** being at a relatively higher angle when the pedal assembly **100** is in its resting position, compared to the configuration described above with the bracket in a lowered position. It is understood that while a pedal stop **123** is described herein as a separate element, a portion of the link member or another element may serve the same purpose and be substituted for the pedal stop.

In one specific embodiment, when the bracket **122** is lowered, the hi-hat pedal assembly **100** is in a configuration such that there is less rebound and/or bounce, and/or when the bracket **122** is raised, the pedal assembly **100** is in a configuration allowing more rebound and/or bounce. In other embodiments it is understood that this can be reversed.

Additionally, positioning of the bracket **122** can have an impact upon the tension/resistance felt by a user when actuating the pedal **108**. For instance, when the bracket **122** is in a higher position, the pedal **108** can be at a higher angle, and/or a compression spring within the system can be less compacted (and be longer) due to the top of the spring being moved higher, and thus the spring may offer less resistance when a user actuates the pedal **108**. When the bracket **122** is in a lower position, the pedal **108** can be at a lower angle, and/or the compression spring within the system can be more compacted (and be shorter), and thus the spring may offer more resistance when a user actuates the pedal **108**. It is also understood that similar concepts can be applied to a tension spring, where the raised or lowered position may result in more or less tension within the spring and, thus, the pedal offering more or less resistance. Further, while the above describes the bracket impacting the position of the top of the spring, other embodiments where it impacts the position of the bottom of the spring are also possible, as well as embodiments where it impacts the position of both the top and bottom of the spring.

The tension/resistance in the pedal **108** can also be adjusted by the raising or lowering of spring assembly **118**. The spring assembly can include a substantially vertical portion and a substantially horizontal portion. A spring tension screw **112** and/or adjustment screw **136** can be loosened to allow for the raising or lowering of the spring assembly **118**. Alternatively, the use of an adjustment screw

can automatically raise or lower the spring assembly **118** based upon the screwing motion. Similar systems are described in U.S. patent application Ser. No. 14/495,718 to Sikra, entitled “Drum Pedal with Adjustment Features and Interlocking Features” and filed on Sep. 24, 2014, which is fully incorporated by reference herein in its entirety.

In one embodiment, raising the spring assembly **118** can result in increased pedal resistance and/or tension, and lowering the spring assembly **118** can decrease this resistance and/or tension. For example, in one embodiment, when the spring assembly **118** is raised to its highest position, the spring assembly **118** is configured so as to maximize resistance and/or tension in the pedal **108** (keeping all other variables constant), and the lowest position of the spring assembly **118** corresponds to the lowest resistance and/or tension in the pedal **108** (keeping all other variables constant). This can be due to the fact that, in one embodiment, raising the spring assembly **118**, related spring bushing, and/or bottom of a compression spring (such as the spring bushing **262** and/or compression spring **260** in FIGS. **4** and **5** and previously described herein) can shorten the length of the compression spring when the pedal assembly is at rest, meaning that the compression spring provides more resistance upon pedal actuation (which shortens the compression spring even further, such as by lowering the top of the compression spring). This can be because as the spring assembly **118** is raised, the spring bushing or lower end of the spring can also be raised while the top of the spring remains stationary.

Similarly, lowering the spring assembly **118**, bottom of a spring bushing, and/or bottom of a compression spring can increase the length of the compression spring when the pedal assembly is at rest, meaning the compression spring provides less resistance to compression upon pedal actuation. It is understood, however, that the relationship of position height and the corresponding tension levels may be inverted.

In one such example wherein the relationship of position height and pedal tension/resistance levels are inverted in relation to the specific embodiment described above, a tension spring is used instead of a compression spring, such that lowering of the spring assembly and corresponding lengthening of the tension spring results in more spring resistance upon actuation of the pedal, and/or raising of the bottom of the spring assembly and corresponding shortening of the tension spring results in less spring resistance upon pedal actuation.

Once a user has achieved the desired resistance level in the pedal **108**, the spring tension screw **112** and/or adjustment screw **136** can be tightened to lock the spring assembly **118** in place. Alternatively, if the screwing motion itself raises and/or lowers the spring assembly **118**, the spring assembly **118** may already be locked into place. Similar features are described in U.S. patent application Ser. No. 14/495,718 to Sikra, entitled “Drum Pedal with Adjustment Features and Interlocking Features” and filed on Sep. 24, 2014, which is fully incorporated by reference herein in its entirety.

In some embodiments, a heel plate **106** can be attached to the base plate **102** and/or a hinge piece **104**. The hinge piece **104** can also be attached to base plate **102**, or can be suspended over the base plate **102**, such as between the heel plate **106** and the pedal **108**. The heel plate **106** can also be flexible, such that it is referred to as a flexible heel plate. The heel plate **106** can be made of several different types of materials, such as metal. In some embodiments, the top of the heel plate **106** is separated from the bottom of the heel

plate. The heel plate **106** can be several different shapes, such as a J-shape or a U-shape. In J-shape embodiments, the shorter end of the heel plate can be attached to base plate **102**, while the longer end is attached to hinge piece **104**. In these embodiments, the shorter end can be the bottom of the heel plate, while the longer end can be the top of the heel plate. The top of the heel plate **106** can flex in a downward manner when force is applied by a user. Further, suspension of the hinge piece **104** over the base plate **102** can add further flexibility to the heel plate **106**. It is understood that in other embodiments, the heel plate **106** may not be flexible, and that the heel plate **106** can take various shapes.

The hi-hat pedal assembly **100** can also comprise interlocking features, such as interlocking features that can connect the base **102** to heel plate **106**, heel plate **106** to hinge piece **104**, and/or hinge piece **104** to pedal **108**. Many pedal assemblies known in the art using conventional screw connections or other connections, such that some elements can begin to experience undesirable movement, which can be due to wear and tear. Moreover, undesired motion can also cause other problems, such as hinge lock-up based on bending of parts. The present invention can include interlocking features which can reduce or eliminate these problems. Some flexible heel plates and interlocking features which can be incorporated into embodiments of the present invention are discussed in commonly assigned U.S. application Ser. No. 14/495,718 to Sikra, which is fully incorporated by reference herein in its entirety.

In some embodiments, the hi-hat pedal assembly **100** can include a pedal incline adjustment feature. In these embodiments, the pedal **108** can be attached to a pedal attachment mechanism **130**, which in turn can connect to the link member **132**. As shown in FIG. 2, a connecting member **134** can connect the link member **132** to the pedal attachment mechanism **130**. The connecting member **134** can be, for example, a pin, rod, screw, or other similar type of device; many different types of connecting members are possible. In one embodiment, the connecting member **134** can be a drum key screw or similar device placed through apertures in both the linking member **132** and the pedal attachment mechanism **130**; when the drum key screw is loosened, its positioning within the pedal attachment mechanism **130** can be altered, whereas when the drum key screw is tightened, it is locked into position. In other embodiments, the connecting member **134** can be held in place by a drum key screw such as the drum key screw **116** (shown in FIGS. 1 and 3) or other similar device. It is understood that other screw or connections mechanisms besides such screws can be used, and it is understood that many different connection mechanisms are possible.

In some embodiments, the height of the connecting member **134** relative to the pedal attachment mechanism **130** can adjust the incline angle of pedal **108**. In these embodiments, when the drum key **116** or similar is loosened, the height of the pedal attachment mechanism **130** can be adjusted such that the connecting member **134** is lower or higher within an aperture of the pedal attachment mechanism **130**. When the drum key **116** is tightened, the connecting member **134** can be locked into place within the pedal attachment mechanism **134**, which can set the incline angle of pedal **108**. For example, when the connecting member **134** is in a lower position in relation to pedal attachment mechanism **130**, pedal **108** can be at a higher incline angle. When the connecting member **134** is in a higher position in relation to pedal attachment mechanism **130**, the pedal **108** can be at a lower incline angle. Other embodiments including the inverse of that described above are possible. The incline angle of pedal **108** can be adjusted to fit a user's needs and preferences. Further, this incline angle adjustment can be

made independent of other features or characteristics in hi-hat pedal assembly **100**, such as independent of the resistance offered by the pedal **108**. Accordingly, the pedal incline adjustment feature of the present invention allows the pedal assembly **100** to be highly customizable.

According to some embodiments of the present invention, the pedal incline adjustment feature can be used in combination with a bracket such as the bracket **122** so that the pedal can be at the same angle whether the bracket **122** is at its maximum height or at its minimum height. Similarly, a tension adjustment feature such as the spring assembly **118** can be used in coordination with the bracket **122** such that a user can experience the same pedal resistance when the bracket **122** is at its maximum height or at its minimum height. Similarly, pedal angle and pedal resistance can be adjusted using, for example, the incline adjustment feature and the spring assembly **118** such that angle and resistance are the same when the bracket **122** is at its maximum height and at its minimum height. Pedal assemblies incorporating combinations of the features described herein can be highly customizable.

In some embodiments, the pedal assembly **100** can be held in place by securing means **150**, such as spikes (although many different types of securing means including pillars, objects including roughened bottom surfaces, etc. are possible). The securing means **150** can be retractable within the rest of the pedal assembly, such as within the pedestal base plate **126a** and/or the remainder of the pedestal **126**. In one such embodiment, the securing means **150** are fully retractable within the remainder of the pedal assembly **100**, although in other embodiments the securing means can be only partially retractable or not retractable. In some embodiments, the movement of another pedal assembly element, such as a drum key screw **152**, can result in movement of the spikes **150**. For example, when a drum key screw or similar device is loosened or tightened, a corresponding securing means **150** can move downward or move upward and retract, and vice versa. In other embodiments, the securing means **150** can be revealed or retracted without the use of drum key screws **152**.

The securing means **150** can allow the hi-hat pedal assembly **100** to remain in place by engaging a surface or object under the pedal assembly **100**. The use of spikes as a securing means, for example, can be particularly applicable to carpet surfaces. When the securing means **150** are lowered, they can engage the surface/object and hold the hi-hat pedal assembly **100** in place. Similarly, when the securing means **150** are raised, this can allow the pedal assembly **100** to be moved. It is understood that some embodiments of the pedal assembly **100** do not include the securing means **150** and/or drum key screws **152**.

FIGS. 4 and 5 are exploded perspective views of another embodiment of a pedal assembly **200** according to the present invention. The pedal assembly **200** can include components and/or features similar to or the same as those described above with regard to the pedal assembly **100**. The hi-hat pedal assembly **200** can comprise a base plate **202**, hinge piece **204**, heel plate **206**, pedal **208**, drum key screws **210**, spring tension screw **212**, drum key screws **214**, drum key screws **216**, a spring assembly **218**, a direct drive assembly **220**, a bracket **222**, a rod **224**, a pedestal **226**, a clamp locking assembly **228**, a pedal attachment mechanism **230**, a link member **232**, a pin **234**, an adjustment screw **236**, a clamp screw **238**, a drum key screw **242**, securing means **250**, drum key screws **252**, a compression spring **260**, and/or a spring bushing **262**. These elements can be the same as or similar to corresponding elements described above with regard to FIGS. 1-3, or can be different and have different characteristics.

## 11

The compression spring 260 and/or spring bushing 262 can work separately and/or together with the spring assembly 218 to adjust the tension of the hi-hat pedal assembly 200. As described above with regard to the pedal assembly 100 shown in FIGS. 1-3, when the spring assembly 218 is raised or lowered, the length of the compression spring 260 and/or spring bushing 262 can be altered. In one embodiment, when the spring assembly 218 is raised, the height of the spring bushing 262 and/or the lower edge of the compression spring 260 is increased, which can increase the resistance felt by a user when actuating the pedal 208. In another embodiment, when the spring assembly 218 is lowered, the height of the spring bushing 262 and/or lower edge of the compression spring 260 is decreased, which can result in lengthening of the compression spring 260 and/or in the pedal 208 requiring more force to actuate. In some embodiments, the spring bushing 262 can be adjusted to increase and/or decrease the force in the compression spring 260. It is understood that the raising and/or lowering of the spring assembly 218 can correspond to either an increase and/or decrease in the force in the compression spring 260. It is further understood that a tension spring could replace the compression spring 260, with other components appropriately altered for operation with a tension spring. Such a system may operate in a manner different than that described above with regard to the FIGS. 4 and 5 embodiment incorporating a compression spring, and may operate in a manner similar to or the same as the tension spring embodiment described above with regard to FIGS. 1-3.

As mentioned previously, the adjustment of the spring assembly 218 can increase and/or decrease the resistance in the pedal 208. Moreover, such adjustments can increase and/or decrease the velocity with which the pedal 208 and/or other components return to resting position after an actuation. For example, embodiments where the pedal 208 offers more resistance to actuation may also have a relatively higher return velocity of the pedal 208, and embodiments where the pedal 208 offers less resistance to actuation may have a relatively lower return velocity of the pedal 208 (although it is understood that other embodiments are possible). Accordingly, the spring assembly 218, the compression spring 260 and/or the spring bushing 262, as well as any other component described herein, can work together and/or separately to adjust to a user's preferred pedal assembly characteristics.

It is understood that embodiments presented herein are meant to be exemplary. Embodiments of the present invention can comprise any combination of compatible features shown in the various figures, and these embodiments should not be limited to those expressly illustrated and discussed.

Although the present invention has been described in detail with reference to certain configurations thereof, other versions are possible. Therefore, the spirit and scope of the invention should not be limited to the versions described above.

The foregoing is intended to cover all modifications and alternative constructions falling within the spirit and scope of the invention as expressed in the appended claims, wherein no portion of the disclosure is intended, expressly or implicitly, to be dedicated to the public domain if not set forth in the claims.

I claim:

1. A pedal assembly for use with percussion instrument, said pedal assembly comprising:  
 a pedal;  
 a spring mechanism operably connected to said pedal such that said pedal is configured to provide resistance to a user actuation; and  
 a first spring tensioning feature operable to adjust the length of said spring mechanism when said pedal

## 12

assembly is at rest, said first spring tensioning feature comprising a spring assembly having an adjustable position, wherein at least a portion of said spring assembly is offset from said spring mechanism so as to not be vertically aligned with said spring mechanism.

2. The pedal assembly of claim 1, further comprising a base plate and a pedestal on said base plate;  
 wherein said pedal is on said base plate and rotatable relative to said base plate; and  
 wherein said portion of said spring assembly has a position that is adjustable within an aperture of said pedestal.

3. The pedal assembly of claim 1, wherein said spring assembly is vertically adjustable.

4. The pedal assembly of claim 3, further comprising a screw mechanism operably connected to said spring assembly.

5. The pedal assembly of claim 1, wherein said spring assembly comprises a spring bushing; and  
 wherein a bottom of said spring mechanism is on said spring bushing.

6. The pedal assembly of claim 1, further comprising:  
 a link member between said pedal and said spring mechanism; and  
 a second spring tensioning feature operable to adjust the length of said spring mechanism when said pedal assembly is at rest, said second spring tensioning feature comprising an adjustable bracket with a position that is adjustable;  
 wherein at least a portion of said adjustable bracket is between said link member and said spring bushing.

7. The pedal assembly of claim 6, further comprising a pedal stop between said link member and said portion of said adjustable bracket;  
 wherein said position of said adjustable bracket is adjustable to a position where said pedal stop is in contact with a bottom of said portion of said adjustable bracket when said pedal assembly is at rest.

8. The pedal assembly of claim 6, wherein said link member is rigid.

9. The pedal assembly of claim 6, wherein said adjustable bracket is vertically adjustable.

10. The pedal assembly of claim 6, wherein downward adjustment of said adjustable bracket is configured to decrease the length of said spring mechanism when said pedal assembly is at rest; and  
 wherein upward adjustment of said adjustable bracket is configured to increase the length of said spring mechanism when said pedal assembly is at rest.

11. The pedal assembly of claim 6, further comprising a base plate;  
 wherein said pedal is on said base plate and rotatable relative to said base plate; and  
 wherein vertical adjustment of said adjustable bracket changes the angle of said pedal to said base plate.

12. A pedal assembly for use with a percussion instrument, said pedal assembly comprising:  
 a base plate;  
 a pedestal assembly on said base plate;  
 a pedal on said base plate; and  
 a clamp locking assembly on said base plate, said clamp locking assembly comprising a forward portion;  
 wherein said clamp locking assembly is adjustable such that said forward portion is movable downward toward said base plate from an unlocked position to a locked position; and

## 13

wherein said base plate is rotatable relative to said pedestal assembly when said forward portion is in said unlocked position, and wherein said base plate is not rotatable relative to said pedestal assembly when said forward portion is in said locked position.

13. The pedal assembly of claim 12, wherein said pedal is rotatable with said base plate when said forward portion is in said unlocked position.

14. The pedal assembly of claim 12, wherein said base plate is rotatable to an angle of 45° or more when said forward portion is in said unlocked position.

15. A pedal assembly for use with a percussion instrument, said pedal assembly comprising:

a pedestal assembly at least partially on a base plate;  
a pedal connected to said pedestal assembly; and  
a securing means connected to at least one of said pedestal assembly and said base plate, said securing means configured to interact with an object or surface under said base plate.

16. The pedal assembly of claim 15, wherein said securing means comprises a spike.

17. The pedal assembly of claim 15, wherein said securing means is at least partially retractable within said pedestal assembly.

18. The pedal assembly of claim 15, further comprising a screw operably connected to said securing means such that rotation of said screw causes movement of said securing means.

19. The pedal assembly of claim 15, wherein said securing means is a first securing means and further comprising a second securing means and first and second screws;

wherein said first screw is operably connected to said first securing means such that rotation of said first screw causes movement of said first securing means; and

wherein said second screw is operably connected to said second securing means such that rotation of said second screw causes movement of said second securing means.

20. The pedal assembly of claim 15, wherein said securing means is at least partially retractable through said base plate and into said pedestal assembly.

21. The pedal assembly of claim 20, wherein said securing means is retractable such that no portion of said securing means is below a bottom of said base plate.

22. The pedal assembly of claim 15, wherein said securing means comprises at least one of a spike, a pillar, and a roughened bottom surface.

23. A pedal assembly for use with a hi-hat, comprising:  
a pedestal assembly;

a pedal;

a spring mechanism operably linked to said pedal such that user actuation of said pedal is configured to change the length of said spring mechanism;

## 14

a link member between said pedal and said spring mechanism; and

a bracket attached to said pedestal assembly, said bracket comprising a portion between said link member and said spring mechanism;

wherein the position of said bracket is adjustable relative to a top of said link member.

24. The pedal assembly of claim 23, wherein said bracket is vertically adjustable between a minimum height and a maximum height.

25. The pedal assembly of claim 24, further comprising a pedal stop between said link member and said portion of said bracket.

26. The pedal assembly of claim 25, wherein when said pedal assembly is in a resting position and said bracket is at said minimum height, said pedal stop is in contact with said bracket.

27. The pedal assembly of claim 26, wherein when said pedal assembly is in a resting position and said bracket is at said maximum height, a space remains between the top of said pedal stop and the bottom of said bracket.

28. The pedal assembly of claim 23, wherein said link member is rigid.

29. The pedal assembly of claim 23, wherein adjustment of the position of said bracket is configured to adjust the length of said spring mechanism.

30. A pedal assembly for use with a percussion instrument, said pedal assembly comprising:

a pedal;

a spring mechanism operably connected to said pedal such that said pedal is configured to provide resistance to a user actuation; and

a spring assembly having an adjustable position and operable to adjust the length of said spring mechanism when said pedal assembly is at rest, said spring assembly comprising a spring bushing;

wherein a bottom of said spring mechanism is on said spring bushing.

31. A pedal assembly for use with a percussion instrument, said pedal assembly comprising:

a pedestal assembly;

a pedal connected to said pedestal assembly; and

a securing means connected to said pedestal assembly, said securing means configured to interact with an object or surface under said pedestal assembly;

wherein said securing means is at least partially retractable within said pedestal assembly.

\* \* \* \* \*