



US009668533B2

(12) **United States Patent**
Dua et al.

(10) **Patent No.:** **US 9,668,533 B2**
(45) **Date of Patent:** **Jun. 6, 2017**

(54) **ARTICLE OF FOOTWEAR HAVING AN UPPER INCORPORATING A KNITTED COMPONENT**

(71) Applicant: **NIKE, Inc.**, Beaverton, OR (US)

(72) Inventors: **Bhupesh Dua**, Portland, OR (US);
Bruce Huffa, Encino, CA (US);
Benjamin A. Shaffer, Saratoga, CA (US)

(73) Assignee: **NIKE, Inc.**, Beaverton, OR (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 611 days.

(21) Appl. No.: **14/198,620**

(22) Filed: **Mar. 6, 2014**

(65) **Prior Publication Data**

US 2014/0245639 A1 Sep. 4, 2014

Related U.S. Application Data

(60) Continuation of application No. 13/591,942, filed on Aug. 22, 2012, now Pat. No. 9,468,250, which is a (Continued)

(51) **Int. Cl.**

D04B 1/10 (2006.01)

A43B 1/04 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **A43B 1/04** (2013.01); **A43B 7/20** (2013.01); **A43B 23/0205** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC D04B 1/106; D04B 1/123; D04B 1/16; D04B 1/225; D04B 7/14; D04B 7/30; A43B 1/04; A43B 23/027; A43B 23/0245

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

601,192 A 3/1898 Woodside

1,215,198 A 2/1917 Rothstein

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1925763 3/2007

CN 102271548 12/2011

(Continued)

OTHER PUBLICATIONS

Letter from Bruce Huffa dated Dec. 23, 2013 (71 Pages).

(Continued)


Primary Examiner — Danny Worrell

(74) *Attorney, Agent, or Firm* — Andrew A. Hufford; Brinks Gilson & Lione

(57) **ABSTRACT**

An article of footwear has an upper that includes a knitted component and a sole structure secured to the upper. The knitted component may define a tube formed of unitary knit construction, and a strand may extend through a length of the tube. As another example, the knitted component may have a pair of at least partially coextensive knitted layers formed of unitary knit construction, and a plurality of floating yarns may extend between the knitted layers. In some configurations, the knit type or yarn type may vary in different regions of the knitted component to impart different properties. Additionally, the knitted component may incorporate a thermoplastic yarn that is fused in different regions of the knitted component to impart different properties. A flat knitting process or a variety of other knitting processes may be utilized to form the knitted component.

20 Claims, 15 Drawing Sheets



Related U.S. Application Data

division of application No. 12/338,726, filed on Dec. 18, 2008, now Pat. No. 8,490,299.

(51) **Int. Cl.**

D04B 1/24 (2006.01)
A43B 7/20 (2006.01)
A43C 1/04 (2006.01)
A43B 23/02 (2006.01)
D04B 1/12 (2006.01)
D04B 1/16 (2006.01)

(52) **U.S. Cl.**

CPC *A43B 23/0215* (2013.01); *A43B 23/0245* (2013.01); *A43C 1/04* (2013.01); *D04B 1/106* (2013.01); *D04B 1/123* (2013.01); *D04B 1/16* (2013.01); *D04B 1/24* (2013.01); *D10B 2403/0113* (2013.01); *D10B 2403/022* (2013.01); *D10B 2501/043* (2013.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

1,597,934 A 8/1926 Stimpson
 1,888,172 A 11/1932 Joha
 1,902,780 A 3/1933 Holden et al.
 1,910,251 A 5/1933 Joha
 2,001,293 A 5/1935 Wilson
 2,047,724 A 7/1936 Zuckerman
 2,147,197 A 2/1939 Glidden
 2,314,098 A 3/1943 McDonald
 2,330,199 A 9/1943 Basch
 2,343,390 A 3/1944 Ushakoff
 2,400,692 A 5/1946 Herbert
 2,440,393 A 4/1948 Clark
 2,569,764 A 10/1951 Jonas
 2,586,045 A 2/1952 Hoza
 2,608,078 A 8/1952 Anderson
 2,641,004 A 6/1953 Whiting et al.
 2,675,631 A 4/1954 Doughty
 2,994,322 A 8/1961 Cullen et al.
 3,063,074 A 11/1962 Scholl
 3,583,081 A 6/1971 Hayashi
 3,694,940 A 10/1972 Stohr
 3,704,474 A 12/1972 Winkler
 3,766,566 A 10/1973 Tadokoro
 3,778,856 A 12/1973 Christie et al.
 3,952,427 A 4/1976 Von den Benken et al.
 3,972,086 A 8/1976 Belli et al.
 4,027,402 A 6/1977 Liu et al.
 4,031,586 A 6/1977 Von den Benken et al.
 4,211,806 A 7/1980 Civardi et al.
 4,232,458 A 11/1980 Bartels
 4,255,949 A 3/1981 Thorneburg
 4,258,480 A 3/1981 Famolare, Jr.
 4,317,292 A 3/1982 Melton
 4,373,361 A 2/1983 Thorneburg
 4,447,967 A 5/1984 Zaino
 4,465,448 A 8/1984 Aldridge
 4,607,439 A 8/1986 Sogabe et al.
 4,737,396 A 4/1988 Kamat
 4,750,339 A 6/1988 Simpson et al.
 4,756,098 A 7/1988 Boggia
 4,785,558 A 11/1988 Shiomura
 4,813,158 A 3/1989 Brown
 5,031,423 A 7/1991 Ikenaga
 5,067,260 A 11/1991 Jenkins
 5,095,720 A 3/1992 Tibbals, Jr.
 5,117,567 A 6/1992 Berger
 5,152,025 A 10/1992 Hirmas
 5,177,882 A 1/1993 Berger
 5,192,601 A 3/1993 Neisler
 5,345,638 A 9/1994 Nishida
 5,353,524 A 10/1994 Brier

5,371,957 A 12/1994 Gaudio
 5,461,884 A 10/1995 McCartney et al.
 5,511,323 A 4/1996 Dahlgren
 5,572,860 A 11/1996 Mitsumoto et al.
 5,575,090 A 11/1996 Condini
 5,623,840 A 4/1997 Roell
 5,729,918 A 3/1998 Smets
 5,735,145 A 4/1998 Pernick
 5,746,013 A 5/1998 Fay, Sr.
 5,765,296 A 6/1998 Ludemann et al.
 5,884,419 A 3/1999 Davidowitz et al.
 5,996,189 A 12/1999 Wang
 6,029,376 A 2/2000 Cass
 6,032,387 A 3/2000 Johnson
 6,052,921 A 4/2000 Oreck
 6,088,936 A 7/2000 Bahl
 6,151,802 A 11/2000 Reynolds
 6,170,175 B1 1/2001 Funk
 6,308,438 B1 10/2001 Throneburg et al.
 6,333,105 B1 12/2001 Tanaka et al.
 6,401,364 B1 6/2002 Burt
 6,558,784 B1 5/2003 Norton et al.
 6,588,237 B2 7/2003 Cole et al.
 6,754,983 B2 6/2004 Hatfield et al.
 6,910,288 B2 6/2005 Dua
 6,922,917 B2 8/2005 Kerns et al.
 6,931,762 B1 8/2005 Dua
 D517,297 S 3/2006 Jones et al.
 7,051,460 B2 5/2006 Orei et al.
 7,056,402 B2 6/2006 Koerwien et al.
 7,347,011 B2 3/2008 Dua et al.
 7,441,348 B1 10/2008 Dawson
 7,543,397 B2 6/2009 Kilgore et al.
 7,568,298 B2 8/2009 Kerns
 7,682,219 B2 3/2010 Falla
 8,490,299 B2 7/2013 Dua et al.
 8,839,532 B2* 9/2014 Huffa A43B 1/04
 36/25 R
 8,997,530 B1* 4/2015 Podhajny A43B 1/04
 36/47
 2002/0078599 A1 6/2002 Delgorgue et al.
 2002/0148258 A1 10/2002 Cole et al.
 2003/0126762 A1 7/2003 Tseng
 2003/0191427 A1 10/2003 Jay et al.
 2004/0118018 A1 6/2004 Dua
 2004/0181972 A1 9/2004 Csorba
 2005/0115284 A1 6/2005 Dua
 2005/0193592 A1 9/2005 Dua et al.
 2005/0273988 A1 12/2005 Christy
 2005/0284000 A1 12/2005 Kerns
 2006/0048413 A1 3/2006 Sokolowski et al.
 2006/0059715 A1 3/2006 Aveni
 2006/0162187 A1 7/2006 Byrnes et al.
 2007/0022627 A1 2/2007 Sokolowski et al.
 2007/0180730 A1 8/2007 Greene et al.
 2008/0017294 A1 1/2008 Bailey et al.
 2008/0078102 A1 4/2008 Kilgore et al.
 2008/0110048 A1 5/2008 Dua et al.
 2008/0189830 A1 8/2008 Egglesfield
 2008/0313939 A1 12/2008 Ardill
 2009/0068908 A1 3/2009 Hinchcliff
 2010/0051132 A1 3/2010 Glenn
 2010/0154256 A1 6/2010 Dua
 2010/0170651 A1 7/2010 Scherb et al.
 2011/0030244 A1 2/2011 Motawi et al.
 2011/0078921 A1 4/2011 Greene et al.
 2012/0255201 A1 10/2012 Little
 2012/0318026 A1 12/2012 Dua et al.
 2015/0059210 A1* 3/2015 Droege A43B 23/0235
 36/84
 2016/0058099 A1* 3/2016 Panian A43B 23/0265
 36/84
 2016/0208421 A1* 7/2016 Baines A43B 1/04

FOREIGN PATENT DOCUMENTS

DE 870963 C 3/1953
 DE 1084173 6/1960

(56)

References Cited

FOREIGN PATENT DOCUMENTS

DE	19738433	4/1998
DE	19728848	1/1999
EP	0448714	10/1991
EP	0728860	8/1996
EP	0758693	2/1997
EP	0279950 A2	8/1998
EP	0898002 A2	2/1999
EP	1233091	8/2002
EP	1437057 A1	7/2004
EP	1563752 A1	8/2005
EP	1602762 A1	12/2005
EP	1972706 A1	9/2008
EP	2378910	3/2014
FR	2171172	9/1973
GB	538865	8/1941
GB	2018837 A	10/1979
GB	1603487	11/1981
JP	H06113905	4/1994
JP	H08109553	4/1996
JP	H11302943	11/1999
JP	2001054409	2/2001
JP	5391493	6/2012
NL	7304678	10/1974
WO	9003744	4/1990
WO	0032861	6/2000
WO	0231247	4/2002
WO	2010080182	7/2010

OTHER PUBLICATIONS

Notice of Allowance for U.S. Appl. No. 13/591,942, dated Aug. 2, 2016, 2016 (5 pages).
 Chinese Office Action dated Dec. 1, 2015 with summary.

Declaration of Dr. Edward C. Frederick from the US Patent and Trademark Office Inter Partes Review of U.S. Pat. No. 7,347,011 (178 pp).
 David J. Spencer, Knitting Technology: A Comprehensive Handbook and Practical Guide (Third ed., Woodhead Publishing Ltd. 2001) (413 pp).
 Excerpt of Hannelore Eberle et al., Clothing Technology (Third English ed., Beuth-Verlag GmnH 2002) (book cover and back; pp. 2-3, 83).
 International Search Report and Written Opinion in connection with PCT/US2009/056795 mailed on Apr. 20, 2010.
 International Search Report and Written Opinion in connection with PCT/US2012/028576 mailed on Oct. 1, 2012.
 International Search Report and Written Opinion in connection with PCT/US2012/028559 mailed on Oct. 19, 2012.
 International Search Report and Written Opinion in connection with PCT/US2012/028534 mailed on Oct. 17, 2012.
 International Preliminary Report on Patentability in connection with PCT/US2012/028534 mailed Sep. 17, 2013.
 International Preliminary Report on Patentability in connection with PCT/US2012/028576 mailed Sep. 17, 2013.
 Chinese Office Action dated Oct. 8, 2013 cited in Chinese Application No. 200980150405.0, 9 pp.
 European Partial Search Report dated Mar. 5, 2014 in European Patent Application No. 13198800.8.
 European Partial Search Report dated Mar. 5, 2014 in European Patent Application No. 13198822.2.
 International Preliminary Report on Patentability in connection with PCT/US2009/056795 mailed Jun. 30, 2011.
 Chinese Notice of Allowance dated Jun. 5, 2014 cited in Chinese Application No. 200980150405.0.
 Extended European Search Report dated Jun. 16, 2014 in European Patent Application 13198800.8.
 Extended European Search Report dated Jun. 16, 2014 in European Patent Application 13198822.2.

* cited by examiner




Figure 2




Figure 3




Figure 4




Figure 5A




Figure 5B




Figure 5C





Figure 5D






Figure 7A




Figure 7B




Figure 7C




Figure 7E




Figure 8B

Figure 8A

ARTICLE OF FOOTWEAR HAVING AN UPPER INCORPORATING A KNITTED COMPONENT

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 13/591,942, entitled "Article of Footwear Having An Upper Incorporating A Knitted Component", filed on Aug. 22, 2012, which application is a division of U.S. patent application Ser. No. 12/338,726, entitled "Article Of Footwear Having An Upper Incorporating A Knitted Component", which was filed in the U.S. Patent and Trademark Office on Dec. 18, 2008 and issued as U.S. Pat. No. 8,490,299 on Jul. 23, 2013, the disclosures of which applications are hereby incorporated by reference in their entirety.

BACKGROUND

Conventional articles of footwear generally include two primary elements, an upper and a sole structure. The upper is secured to the sole structure and forms a void on the interior of the footwear for comfortably and securely receiving a foot. The sole structure is secured to a lower surface of the upper so as to be positioned between the upper and the ground. In some articles of athletic footwear, for example, the sole structure may include a midsole and an outsole. The midsole may be formed from a polymer foam material that attenuates ground reaction forces to lessen stresses upon the foot and leg during walking, running, and other ambulatory activities. The outsole is secured to a lower surface of the midsole and forms a ground-engaging portion of the sole structure that is formed from a durable and wear-resistant material. The sole structure may also include a sockliner positioned within the void and proximal a lower surface of the foot to enhance footwear comfort.

The upper generally extends over the instep and toe areas of the foot, along the medial and lateral sides of the foot, and around the heel area of the foot. In some articles of footwear, such as basketball footwear and boots, the upper may extend upward and around the ankle to provide support or protection for the ankle. Access to the void on the interior of the upper is generally provided by an ankle opening in a heel region of the footwear. A lacing system is often incorporated into the upper to adjust the fit of the upper, thereby permitting entry and removal of the foot from the void within the upper. The lacing system also permits the wearer to modify certain dimensions of the upper, particularly girth, to accommodate feet with varying dimensions. In addition, the upper may include a tongue that extends under the lacing system to enhance adjustability of the footwear, and the upper may incorporate a heel counter to limit movement of the heel.

Various materials are conventionally utilized in manufacturing the upper. The upper of athletic footwear, for example, may be formed from multiple material elements. The materials may be selected based upon various properties, including stretch-resistance, wear-resistance, flexibility, air-permeability, compressibility, and moisture-wicking, for example. With regard to an exterior of the upper, the toe area and the heel area may be formed of leather, synthetic leather, or a rubber material to impart a relatively high degree of wear-resistance. Leather, synthetic leather, and rubber materials may not exhibit the desired degree of flexibility and air-permeability for various other areas of the exterior. Accordingly, the other areas of the exterior may be formed

from a synthetic textile, for example. The exterior of the upper may be formed, therefore, from numerous material elements that each impart different properties to the upper. An intermediate or central layer of the upper may be formed from a lightweight polymer foam material that provides cushioning and enhances comfort. Similarly, an interior of the upper may be formed of a comfortable and moisture-wicking textile that removes perspiration from the area immediately surrounding the foot. The various material elements and other components may be joined with an adhesive or stitching. Accordingly, the conventional upper is formed from various material elements that each impart different properties to various areas of the footwear.

SUMMARY

A flat knitting process or a variety of other knitting processes may be utilized to form a knitted component for an upper of an article of footwear. Various features may be incorporated into the knitted component. For example, the knitted component may define a tube formed of unitary knit construction, and a strand may extend through a length of the tube. As another example, the knitted component may have a pair of at least partially coextensive knitted layers formed of unitary knit construction, and a plurality of floating yarns may extend between the knitted layers. In some configurations, the knit type or yarn type may vary in different regions of the knitted component to impart different properties. Additionally, the knitted component may incorporate a thermoplastic yarn that is fused in different regions of the knitted component to impart different properties.

The advantages and features of novelty characterizing aspects of the invention are pointed out with particularity in the appended claims. To gain an improved understanding of the advantages and features of novelty, however, reference may be made to the following descriptive matter and accompanying figures that describe and illustrate various configurations and concepts related to the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing Summary and the following Detailed Description will be better understood when read in conjunction with the accompanying figures.

FIG. 1 is a perspective view of an article of footwear.

FIG. 2 is a lateral side elevational view of an article of footwear.

FIG. 3 is a medial side elevational view of the article of footwear.

FIG. 4 is a top plan view of the article of footwear.

FIGS. 5A-5D are cross-sectional views of the article of footwear, as respectively defined by section lines 5A-5D in FIG. 2.

FIG. 6 is a top plan view of a knitted component that forms a portion of an upper of the article of footwear.

FIGS. 7A-7G are side elevational views corresponding with FIG. 2 and depicting further configurations of the article of footwear.

FIGS. 8A and 8B are cross-sectional views corresponding with FIG. 5D and depicting further configurations of the article of footwear.

DETAILED DESCRIPTION

The following discussion and accompanying figures disclose an article of footwear having an upper that includes a knitted component. The article of footwear is disclosed as

having a general configuration suitable for walking or running. Concepts associated with the footwear, including the upper, may also be applied to a variety of other athletic footwear types, including baseball shoes, basketball shoes, cross-training shoes, cycling shoes, football shoes, tennis shoes, soccer shoes, and hiking boots, for example. The concepts may also be applied to footwear types that are generally considered to be non-athletic, including dress shoes, loafers, sandals, and work boots. The concepts disclosed herein apply, therefore, to a wide variety of footwear types.

General Footwear Structure

An article of footwear **10** is depicted in FIGS. 1-5D as including a sole structure **20** and an upper **30**. For reference purposes, footwear **10** may be divided into three general regions: a forefoot region **11**, a midfoot region **12**, and a heel region **13**, as shown in FIGS. 2 and 3. Footwear **10** also includes a lateral side **14** and a medial side **15**. Forefoot region **11** generally includes portions of footwear **10** corresponding with the toes and the joints connecting the metatarsals with the phalanges. Midfoot region **12** generally includes portions of footwear **10** corresponding with the arch area of the foot, and heel region **13** corresponds with rear portions of the foot, including the calcaneus bone. Lateral side **14** and medial side **15** extend through each of regions **11-13** and correspond with opposite sides of footwear **10**. Regions **11-13** and sides **14-15** are not intended to demarcate precise areas of footwear **10**. Rather, regions **11-13** and sides **14-15** are intended to represent general areas of footwear **10** to aid in the following discussion. In addition to footwear **10**, regions **11-13** and sides **14-15** may also be applied to sole structure **20**, upper **30**, and individual elements thereof.

Sole structure **20** is secured to upper **30** and extends between the foot and the ground when footwear **10** is worn. The primary elements of sole structure **20** are a midsole **21**, an outsole **22**, and an sockliner **23**. Midsole **21** is secured to a lower surface of upper **30** and may be formed from a compressible polymer foam element (e.g., a polyurethane or ethylvinylacetate foam) that attenuates ground reaction forces (i.e., provides cushioning) when compressed between the foot and the ground during walking, running, or other ambulatory activities. In further configurations, midsole **21** may incorporate a fluid-filled bladder that supplements the ground reaction force attenuation properties, or midsole **21** may be primarily formed from the fluid-filled bladder. Outsole **22** is secured to a lower surface of midsole **21** and may be formed from a wear-resistant rubber material that is textured to impart traction. Sockliner **23** is located within upper **30** and is positioned to extend under a lower surface of the foot. Although this configuration for sole structure **20** provides an example of a sole structure that may be used in connection with upper **30**, a variety of other conventional or nonconventional configurations for sole structure **20** may also be utilized. Accordingly, the structure and features of sole structure **20** or any sole structure utilized with upper **30** may vary considerably.

Upper **30** defines a void within footwear **10** for receiving and securing a foot relative to sole structure **20**. The void is shaped to accommodate the foot and extends along the lateral side of the foot, along the medial side of the foot, over the foot, around the heel, and under the foot. Access to the void is provided by an ankle opening **31** located in at least heel region **13**. A lace **32** extends through portions of upper **30**, as described in greater detail below, and permits the wearer to modify dimensions of upper **30** to accommodate the proportions of the foot. More particularly, lace **32**

permits the wearer to tighten upper **30** around the foot, and lace **32** permits the wearer to loosen upper **30** to facilitate entry and removal of the foot from the void (i.e., through ankle opening **31**). In addition, upper **30** includes a tongue **33** that extends under lace **32**.

A majority of upper **30** is formed from a knitted component **40** that may, for example, be manufactured through a flat knitting process. Knitted component **40** extends through each of regions **11-13**, along both lateral side **14** and medial side **15**, over forefoot region **11**, and around heel region **13**. In addition, knitted component **40** forms both an interior surface and an opposite exterior surface of upper **30**. As such, knitted component **40** defines at least a portion of the void within upper **30**, and knitted component **40** also defines ankle opening **31** to provide access to the void. In some configurations, knitted component **40** may also extend under the foot. For purposes of example in the various figures, however, a strobel sock **34** is secured to knitted component **40** and forms a majority of the portion of upper **30** that extends under the foot. In this configuration, sockliner **23** extends over strobel sock **34** and forms a surface upon which the foot rests.

Knitted Component Configuration

Knitted component **40** incorporates various knit types that impart different properties to separate areas of upper **30**. As an example that is depicted in FIGS. 1, 4, and 5A, knitted component **40** forms various apertures **41** that extend through upper **30** in forefoot region **11**, whereas many other areas of upper **30** have a more continuous or less-apertured configuration. In addition to imparting greater permeability, which allows air to circulate within upper **30**, apertures **41** may increase both the flexibility and stretch of upper **30** in forefoot region **11**. As further examples, other properties that may be varied through selecting particular knit types for a particular area of knitted component **40** include permeability to liquids, the directions in which knitted component **40** stretches or resists stretch, the stiffness of knitted component **40**, and the compressibility of knitted component **40**. Additional examples of knitted components for footwear uppers that have areas with different knit types to impart different properties may be found in U.S. Pat. No. 6,931,762 to Dua and U.S. Pat. No. 7,347,011 to Dua et al., both of which are entirely incorporated herein by reference. As a related matter, the density of the knit within knitted component **40** may vary among separate areas of upper **30** to, for example, make less-permeable or stiffer portions. Accordingly, knitted component **40** may exhibit various properties in separate areas depending upon the particular knit type that is selected for the areas.

Knitted component **40** may also incorporate various yarn types that impart different properties to separate areas of upper **30**. Moreover, by combining various yarn types with various stitch types, knitted component **40** may impart a range of different properties to separate areas of upper **30**. The properties that a particular type of yarn will impart to an area of knitted component **40** partially depend upon the materials that form the various filaments and fibers within the yarn. Cotton, for example, provides a soft hand, natural aesthetics, and biodegradability. Elastane and stretch polyester each provide substantial stretch and recoverability, with stretch polyester also providing recycleability. Rayon provides high luster and moisture absorption. Wool also provides high moisture absorption, in addition to insulating properties. Nylon is a durable and abrasion-resistant material with high strength. Polyester is a hydrophobic material that also provides relatively high durability. In addition to materials, other aspects relating to the yarn may affect the

properties of upper 30. For example, the yarn may be a monofilament yarn or a multifilament yarn. The yarn may also include separate filaments that are each formed of different materials. The yarn may also include filaments that are each formed of two or more different materials, such as a bicomponent yarn with filaments having a sheath-core configuration or two halves formed of different materials. Different degrees of twist and crimping, as well as different deniers, may affect the properties of upper 30 where the yarn is located. Accordingly, both the materials forming the yarn and other aspects of the yarn may be selected to impart a variety of properties to separate areas of upper 30.

In addition to knit types and yarn types, knitted component 40 may incorporate various knitted structures. Referring to FIGS. 2 and 3, for example, knitted component 40 includes various tubes 42 in which strands 43 are located. Tubes 42 are generally hollow structures formed by two overlapping and at least partially coextensive layers of knitted material, as depicted in FIGS. 5B and 5C. Although the sides or edges of one layer of the knitted material forming tubes 42 may be secured to the other layer, a central area is generally unsecured such that another element (e.g., strands 43) may be located between the two layers of knitted material and pass through tubes 42. An additional example of knitted components for footwear uppers that have overlapping or at least partially coextensive layers may be found in U.S. Patent Application Publication 2008/0110048 to Dua et al., which is incorporated herein by reference.

Tubes 42 extend upward along lateral side 14 and medial side 15. Each tube 42 is adjacent to at least one other tube 42 to form a tube pair. In general, one of strands 43 passes through a first tube 42 of a tube pair, extends outward from an upper end of the first tube 42, forms a loop 44 on the exterior of upper 30, extends into an upper end of a second tube 42 of the tube pair, and passes through the second tube 42. That is, each strand 43 passes through at least two tubes 42, and an exposed portion of the strand 43 forms a loop 44.

An individual strand 43 may only pass through two adjacent tubes 42 (i.e., a single tube pair) such that the strand 43 forms a single loop 44. In this configuration, end portions of the strand 43 exit lower ends of the two adjacent tubes 42 and may be secured to sole structure 20 under strobil sock 34, for example, to prevent the end portions from being pulled through one of tubes 42. In another configuration, an individual strand 43 may pass through each of tubes 42, thereby passing through multiple tube pairs and forming multiple loops 44. In yet another configuration, one strand 43 may pass through each of tubes 42 located on lateral side 14, and another strand 43 may pass through each of tubes 42 located on medial side 15. In general, therefore, an individual strand 43 passes through at least one tube pair to form at least one loop 44, but may pass through multiple tube pairs to form multiple loops 44.

Referring to FIGS. 1-4, lace 32 extends through each of loops 44 and also passes through various apertures 41 that are formed in knitted component 40 adjacent to each of loops 44. The combination of lace 32, the apertures 41 through which lace 32 extends, the various tubes 42 on both lateral side 14 and medial side 15, strands 43, and loops 44 provide an effective lacing system for upper 30. When lace 32 is placed in tension (i.e., when the wearer is tying lace 32), tension may also be induced in strands 43. In the absence of strands 43, other portions of knitted component 40 would bear the tension and resulting stresses from tying lace 32. The presence of strands 43, however, provides a separate element to bear the tension and stresses. Moreover, a majority of knitted component 40 may be generally formed

through selection of knit type and yarn type to stretch when placed in tension, thereby allowing upper 30 to conform with the contours of the foot. Strands 43, however, may be generally non-stretch in comparison with upper 30.

Strands 43 may be formed from a variety of materials and may have the configurations of a rope, thread, webbing, cable, yarn, filament, or chain, for example. In some configurations, strands are located within tubes 42 during the knitting process that forms knitted component 40. As such, strands 43 may be formed from any generally one-dimensional material that may be utilized in a knitting machine or other device that forms knitted component 40. As utilized with respect to the present invention, the term "one-dimensional material" or variants thereof is intended to encompass generally elongate materials exhibiting a length that is substantially greater than a width and a thickness. Accordingly, suitable materials for strands 43 include various filaments, fibers, and yarns, that are formed from rayon, nylon, polyester, polyacrylic, silk, cotton, carbon, glass, aramids (e.g., para-aramid fibers and meta-aramid fibers), ultra high molecular weight polyethylene, and liquid crystal polymer. In addition to filaments and yarns, other one-dimensional materials may be utilized for strands 43. Although one-dimensional materials will often have a cross-section where width and thickness are substantially equal (e.g., a round or square cross-section), some one-dimensional materials may have a width that is somewhat greater than a thickness (e.g., a rectangular, oval, or otherwise elongate cross-section). Despite the greater width, a material may be considered one-dimensional if a length of the material is substantially greater than a width and a thickness of the material.

Another structure formed by knitted component 40 is a padded collar 45 that extends at least partially around ankle opening 31. Referring to FIGS. 1-3, collar 45 exhibits a greater thickness than many other portions of knitted component 40. In general, collar 45 is formed by two overlapping and at least partially coextensive layers of knitted material (i.e., a tubular structure) and a plurality of floating yarns 46 extending between the layers, as depicted in FIG. 5D. Although the sides or edges of one layer of knitted material forming collar 45 may be secured to the other layer of knitted material, a central area is generally unsecured. As such, the layers of knitted material effectively form a tube or tubular structure similar to tubes 42, and floating yarns 46 may be located or laid-in between the two layers of knitted material to pass through the tubes. That is, floating yarns 46 extend between the layers of knitted material, are generally parallel to surfaces of the knitted material, and also pass through and fill an interior volume between the layers. Whereas a majority of knitted component 40 is formed from yarns that are mechanically-manipulated to form a knitted component, floating yarns 46 are generally free or otherwise laid-in within the interior volume between the layers of knitted material forming the exterior of collar 45.

Whereas tubes 42 include a single strand 43, collar 45 includes a plurality of floating yarns 46 that extend through the area between the layers of knitted material. Accordingly, knitted component 40 may form generally tubular structures having one or multiple yarns within the tubular structures. Moreover, floating yarns 46 may be formed from a variety of materials and may be located within collar 45 during the knitting process that forms knitted component 40. As such, floating yarns 46 may be formed from any generally one-dimensional material that may be utilized in a knitting machine or other device that forms knitted component 40.

The presence of floating yarns **46** imparts a compressible aspect to collar **45**, thereby enhancing the comfort of footwear **10** in the area of ankle opening **31**. Many conventional articles of footwear incorporate polymer foam elements or other compressible materials into a collar area. In contrast with the conventional articles of footwear, collar **45** utilizes floating yarns **46** to provide a compressible structure.

The combination of tubes **42** and strands **43** provides upper **30** with a structural element that, for example, resists stretch in a lacing system. Similarly, the combination of collar **45** and floating yarns **46** provides upper **30** with a structural element that, for example, compresses to impart greater comfort around ankle opening **31**. Although these knitted structures provide different benefits to upper **30**, these knitted structures are similar in that each includes (a) a tubular structure formed from two overlapping and at least partially coextensive layers of knitted material formed of unitary knit construction and (b) at least one yarn, strand, or other one-dimensional material that is laid-in or otherwise located within the tubular structure and extends through at least a portion of a length of the tubular structure.

Flat Knitting Process

A flat knitting process may be utilized to manufacture knitted component **40**. Flat knitting is a method for producing a knitted material that is turned periodically (i.e., the material is knitted from alternating sides). The two sides (otherwise referred to as faces) of the material are conventionally designated as the right side (i.e., the side that faces outwards, towards the viewer) and the wrong side (i.e., the side that faces inwards, away from the viewer). Although flat knitting provides a suitable manner for forming knitted component **40**, other knitting processes may also be utilized, depending upon the features that are incorporated into knitted component **40**. Examples of other knitting processes that may be utilized include wide tube circular knitting, narrow tube circular knit jacquard, single knit circular knit jacquard, double knit circular knit jacquard, warp knit tricot, warp knit raschel, and double needle bar raschel.

An advantage to utilizing a flat knitting process to manufacture knitted component **40** is that each of the features discussed above may be imparted to knitted component **40** through the flat knitting process. That is, a flat knitting process may form knitted component **40** to have, for example, (a) various knit types that impart different properties to separate areas of upper **30**, (b) various yarn types that impart different properties to separate areas of upper **30**, (c) knitted components with the configuration of overlapping knitted layers in tubes **42**, (d) a material such as strand **43** that is laid into tubes **42**, (e) knitted components with the configuration of overlapping knitted layers in collar **45**, and (f) floating yarns between layers of knitted material in collar **45**. Moreover, each of these features, as well as other features, may be incorporated into knitted component **40** through a single flat knitting process. As such, a flat knitting process may be utilized to substantially form upper **30** to have various properties and structural features that are advantageous to footwear **10**.

Although one or more yarns may be mechanically-manipulated by an individual to form knitted component **40** (i.e., knitted component **40** may be formed by hand), flat-knitting machines may provide an efficient manner of forming relatively large numbers of knitted component **40**. The flat-knitting machines may also be utilized to vary the dimensions of knitted component **40** to form uppers **30** that are suitable for footwear with different sizes based on one or both of the length and width of a foot. Additionally, the flat-knitting machines may be utilized to vary the configu-

ration of knitted component **40** to form uppers **30** that are suitable for both left and right feet. Various aspects of knitted component **40** may also be varied to provide a custom fit for individuals. Accordingly, the use of mechanical flat-knitting machines may provide an efficient manner of forming multiple knitted components **40** having different sizes and configurations.

Knitted component **40** incorporates various features and structures formed of unitary knit construction. In general, the features and structures are formed of unitary knit construction when incorporated into knitted component **40** through the flat knitting process, rather than other processes (e.g., stitching, bonding, shaping) that are performed after the flat knitting process. As an example, tubes **42** and portions of collar **45** are formed from overlapping and at least partially coextensive layers of knitted material, and sides or edges of one layer may be secured to the other layer. The two layers of knitted material are generally formed during the flat knitting process and do not involve supplemental stitching, bonding, or shaping processes. The overlapping layers are, therefore, formed of unitary knit construction through the flat knitting process. As another example, the regions of knitted component **40** formed from knit types that define apertures **41** are formed of unitary knit construction through the flat knitting process. As yet another example, floating yarns **46** are formed of unitary knit construction.

A further advantage of utilizing a flat knitting process to form knitted component **40** is that three-dimensional aspects may be incorporated into upper **30**. Upper **30** has a curved or otherwise three-dimensional structure that extends around the foot and conforms with a shape of the foot. The flat knitting process may, for example, form areas of knitted component **40** with some curvature in order to complement the shape of the foot. Examples of knitted components for footwear uppers that have three-dimensional aspects may be found in U.S. Patent Application Publication 2008/0110048 to Dua, et al., which is incorporated herein by reference.

Knitted component **40** is depicted separate from footwear **10** and following the flat knitting process in FIG. 6. Whereas edges of many textile materials are cut to expose ends of the yarns forming the textile materials, knitted component **40** may be formed to have a finished configuration. That is, flat-knitting or other knitting techniques may be utilized to form knitted component **40** such that ends of the yarns within knitted component **40** are substantially absent from the edges of knitted component **40**. An advantage of the finished configuration formed through flat-knitting is that the yarns forming the edges of knitted component **40** are less likely to unravel, which is an inherent issue with weft knit materials. By forming finished edges, the integrity of knitted component **40** is strengthened and fewer or no post-processing steps are required to prevent unraveling. In addition, loose yarns are also less likely to inhibit the aesthetic appearance of upper **30**. In other words, the finished configuration of knitted component **40** may enhance the durability and aesthetic qualities of upper **30**, while increasing manufacturing efficiency.

Knitted component **40** provides one example of a configuration that is suitable for upper **30** of footwear **10**. Depending upon the intended use of an article of footwear, the desired properties of the article of footwear, and advantageous structural attributes of the article of footwear, for example, a knitted component similar to knitted component **40** may be formed through flat knitting to have the desired features. That is, flat knitting may be utilized to (a) locate specific knit types in desired areas of the knitted component,

(b) locate specific yarn types in desired areas of the knitted component, (c) form overlapping knitted layers similar to tubes **42** and collar **45** in desired areas of the knitted component, (d) place strands or floating yarns similar to strands **43** and floating yarns **46** between the knitted layers, (e) form three-dimensional aspects in the knitted component, and (f) impart finished edges. More particularly, any of the features discussed above, for example, may be mixed and matched within a knitted component to form specific properties or structural attributes for a footwear upper.

Further Configurations

The features of upper **30** discussed above provides one example of a suitable configuration for footwear **10**. A variety of other configurations may also be utilized. As an example, some of the features discussed above may be absent from knitted component **40** in some configurations of footwear **10**. Referring to FIG. 7A, collar **45** is absent from knitted component **40** such that a single layer of knitted material forms the area extending around ankle opening **31**. Similarly, tubes **42** and strands **43** are absent in FIG. 7B. By utilizing only the structures or features that are beneficial for a particular athletic activity, for example, footwear **10** may have a minimal configuration with only necessary or advantageous elements.

As discussed above, separate areas of upper **30** may have different properties due to utilizing different knit types or yarn types in those areas. Another manner of modifying the properties of particular areas relates to fusing thermoplastic materials from the yarns in those areas. That is, particular areas may be formed from yarns that incorporate thermoplastic polymer materials. By heating the thermoplastic polymer materials, adjacent yarns, filaments, or fibers may fuse to each other in those areas to lock the knit loops together, thereby increasing stiffness or wear-resistance. In some configurations, individual layers of knitted component **40** (e.g., the exterior layer or the interior layer of tubes **42** or collar **45**) or laid-in yarns within knitted component **40** (i.e., strands **43** or floating yarns **46**) may be formed from yarns that incorporate thermoplastic polymer materials. As an alternative, the entirety of knitted component **40** may also be formed from yarns that incorporate thermoplastic polymer materials, and only portions corresponding with fused areas **47** may be heated to modify the properties. Referring to FIG. 7C, knitted component **40** includes two fused areas **47**. One of fused areas **47** is in heel region **13** and may impart greater stiffness in order to effectively provide a heel counter to footwear **10**. Examples of footwear uppers having fused regions may be found in U.S. Pat. No. 6,910,288 to Dua, which is incorporated herein by reference. Another of fused area **47** is in forefoot region **11** and may impart greater wear-resistance to the forefoot area. Fusing may also be utilized to reinforce apertures **41**, provide areas of decreased flex, or decrease permeability.

While fusing areas of knitted component **40** may impart greater stiffness and wear-resistance to those areas, another method may be to increase the knit density in specific areas. Referring to FIG. 7D, knitted component **40** includes two dense areas **48**. One of dense areas **48** is in heel region **13** and may impart greater stiffness in order to effectively provide a heel counter to footwear **10**. Another of dense areas **48** is in forefoot region **11** and may impart greater wear-resistance to the forefoot area. As with forming fused areas **47**, forming a denser knit may also be utilized to reinforce apertures **41**, provide areas of decreased flex, or decrease permeability.

Knitted component **40** forms both an interior surface and an opposite exterior surface of upper **30**. In some configura-

tions of footwear **10**, other elements may be utilized in combination with knitted component **40**, and the other elements may form a portion or all of one of the interior or exterior surfaces. Referring to FIG. 7E, a heel counter **35** is secured to knitted component **40** in heel region **13** and may be formed from a relatively stiff polymer material. An adhesive bonding process may be utilized to join heel counter **35** to knitted component **40**. In other configurations, a lining may extend over the interior surface, thereby forming a portion of the void within upper **30**. Other materials may be welded, adhered, or bonded onto the exterior surface to protect the knit structure of knitted component **40** or provide other benefits to footwear **10**.

Tubes **42** are depicted in FIGS. 2 and 3 as being immediately adjacent to at least one other tube **42**. The relative positions of tubes **42** may, however, vary significantly. Referring to FIG. 7F, tubes **42** are separated from each other and form V-shaped structures. Whereas tubes **42** may be utilized as part of a lacing system, tubes **42** or similar structures may also be utilized to impart longitudinal stretch-resistance. Referring to FIG. 7G, tubes **42** extend longitudinally, and strands **43** within tubes **42** may resist stretch through each of regions **11-13**.

The manner in which yarns **46** are incorporated into collar **45** may vary significantly. In the configuration discussed above, floating yarns **46** are generally parallel to the layers of knitted material forming collar **45** when passing the tubular structure. Referring to FIG. 8A, yarns **46** extend from one layer of knitted material to another layer of knitted material and are generally perpendicular to the layers, thereby imparting a structure similar to a spacer-knit material that is formed through the flat knitting process. As depicted in an enlarged area of FIG. 8A, yarns **46** may extend around yarns forming the knitted layers. In one configuration, yarns **46** may be the same yarns that form the knitted layers. That is, yarns **46** may be unknitted portions of the yarns that form the knitted layers. In another configuration, yarns **46** may be unsecured or otherwise separate (i.e., do not extend around) the yarns forming the knitted layers. Accordingly, yarns **46** may be incorporated into knitted component **40** in a variety of ways. As a further matter, some configurations of upper **30** may include a polymer foam material that is placed between the layers of knitted material following the manufacture of knitted component **40**.

As noted above, collar **45** may have a structure similar to a spacer-knit material, wherein yarns **46** extend from one layer of knitted material to another layer of knitted material and in a direction that is generally perpendicular to the layers. Although collar **45** is a suitable area for having this structure, the flat-knitting process may be utilized to impart the structure of a spacer-knit material to any area of knitted component **40**. For example, the spacer-knit configuration may be positioned on either of sides **14** and **15** in forefoot region **11** or midfoot region **12** to impart a cushioning or compressible aspect to upper **30**. Portions of strobrel sock **34** or tongue **33** may also be formed through a flat knitting process to have a spacer-knit configuration. Moreover, a variety of yarns types may be utilized for areas of knitted component **40** having the spacer-knit configuration, including mono-filament yarns or textured yarns.

In the various configurations discussed above, sockliner **23** is a separate element that is located within the void in upper **30** and strobrel sock **34** is a separate element that is joined with edges of knitted component **40**. The flat knitting process may also be utilized to form sockliner **23** and strobrel sock **34** of unitary knit construction, as depicted in FIG. 8B.

11

As with collar **45**, a sockliner **23** of unitary knit construction may be formed to include floating yarns that impart a compressible configuration. The flat knitting process may also be utilized to form other elements, such as tongue **33**, of unitary knit construction.

Manufacturing Efficiency

As discussed in the Background section above, the upper of athletic footwear, for example, may be formed from multiple material elements that each impart different properties to various areas of the footwear. In order to manufacture a conventional upper, the material elements are cut to desired shapes and then joined together, usually with stitching or adhesive bonding. As the number and types of material elements incorporated into an upper increases, the time and expense associated with transporting, stocking, cutting, and joining the material elements may also increase. Waste material from cutting and stitching processes also accumulates to a greater degree as the number and types of material elements incorporated into the upper increases. Moreover, footwear with a greater number of materials, material elements, and other components may be more difficult to recycle than uppers formed from few elements and materials. By decreasing the number of elements and materials utilized in an upper, therefore, waste may be decreased while increasing the efficiency of manufacture and recycleability.

Whereas conventional uppers require a variety of manufacturing steps involving a plurality of material elements, knitted component **40** may be formed through a single flat knitting process. Following the flat knitting process, a relatively small number of steps are required to incorporate knitted component **40** into footwear **10**. More particularly, strobol sock **34** is joined to edges of knitted component **40**, two edges in heel region **13** are joined, lace **32** is incorporated, and the substantially completed upper **30** is secured with sole structure **20**. In comparison with conventional manufacturing processes, the use of knitted component **40** may reduce the overall number of manufacturing steps. Additionally, waste may be decreased while increasing recycleability.

The invention is disclosed above and in the accompanying figures with reference to a variety of configurations. The purpose served by the disclosure, however, is to provide an example of the various features and concepts related to the invention, not to limit the scope of the invention. One skilled in the relevant art will recognize that numerous variations and modifications may be made to the configurations described above without departing from the scope of the present invention, as defined by the appended claims.

What is claimed is:

1. An article of footwear having an upper and a sole structure secured to the upper, the upper comprising:

a knitted component formed of unitary knit construction, the knitted component including at least one tubular structure disposed on the upper;

the at least one tubular structure comprising a first knitted layer and a second knitted layer that are at least partially coextensive with each and are joined along edges of the first knitted layer and the second knitted layer to form a tube defining an unsecured central area of the tubular structure;

a strand having a configuration of a one-dimensional material, the strand extending through the unsecured central area of the tube between the first knitted layer and the second knitted layer;

12

wherein the tube formed by the first knitted layer and the second knitted layer has a unitary knit construction so as to be a one-piece element with the upper; and the knitted component including at least one yarn formed from a thermoplastic polymer material and incorporated into one of the first knitted layer and the second knitted layer, wherein the thermoplastic polymer material is fused to at least a portion of the strand extending through the tube.

2. The article of footwear according to claim **1**, wherein the at least one yarn formed from the thermoplastic polymer material is incorporated into the first knitted layer and the second knitted layer.

3. The article of footwear according to claim **1**, wherein the thermoplastic polymer material is fused to lock loops of the knitted component incorporating the at least one yarn formed from the thermoplastic polymer material together.

4. The article of footwear according to claim **1**, wherein the strand is made of the thermoplastic polymer material.

5. The article of footwear according to claim **4**, wherein the thermoplastic polymer material of the strand is fused to yarns forming at least one of the first knitted layer and the second knitted layer of the tubular structure.

6. The article of footwear according to claim **5**, wherein the strand is fused to at least one of the first knitted layer and the second knitted layer to lock the position of the strand within the tube.

7. An article of footwear having an upper and a sole structure secured to the upper, the upper comprising:

a first yarn forming a first knitted layer that comprises at least a portion of an exterior surface of the upper;

a second yarn forming a second knitted layer that comprises at least a portion of an interior surface of the upper, the second knitted layer formed of unitary knit construction with the first knitted layer, the second knitted layer being positioned adjacent to the first knitted layer and at least partially coextensive with the first knitted layer;

at least one tubular structure comprising the first knitted layer and the second knitted layer, the first knitted layer and the second knitted layer overlapping and joined to each other along opposite edges to define sides of a tube between the first knitted layer and the second knitted layer; and

a strand having a configuration of a one-dimensional material, the strand extending through the tube and between the first knitted layer and the second knitted layer;

wherein the tube formed by the first knitted layer and the second knitted layer has a unitary knit construction so as to be a one-piece element with the upper; and

wherein at least one of the first yarn and the second yarn includes a thermoplastic polymer material fused to at least a portion of the strand extending through the tube.

8. The article of footwear according to claim **7**, wherein the first knitted layer extends along a lateral side of the upper, along a medial side of the upper, over a forefoot region of the upper, and around a heel region of the upper; and

wherein the at least one tubular structure extends along at least one of the medial side and the lateral side of the upper.

9. The article of footwear according to claim **8**, wherein the at least one tubular structure is oriented to extend upward from an area proximal the sole structure; and

a portion of the strand extends outward from an end of the tubular structure and forms a loop that receives a lace.

13

10. The article of footwear according to claim 7, wherein the strand is fused to at least one of the first knitted layer and the second knitted layer to lock the position of the strand within the tube.

11. The article of footwear according to claim 7, wherein the upper includes at least one fused area, the at least one fused area including the at least one of the first yarn and the second yarn that includes the thermoplastic polymer material fused to lock loops of the first knitted layer and the second knitted layer together.

12. The article of footwear according to claim 11, wherein the at least one fused area is disposed in a heel region of the upper.

13. The article of footwear according to claim 11, wherein the at least one fused area is disposed in a forefoot region of the upper.

14. The article of footwear according to claim 7, wherein the strand is made of the thermoplastic polymer material.

15. An article of footwear having an upper and a sole structure secured to the upper, the upper comprising:

a knitted component formed of unitary knit construction, the knitted component comprising a first knitted layer and a second knitted layer that are at least partially coextensive with each other;

the knitted component including a plurality of tubular structures, the plurality of tubular structures comprising the first knitted layer and the second knitted layer that are overlapping and joined to each other along opposite edges to define sides of a first tube and a second tube, the first tube and the second tube being formed by the first knitted layer and the second knitted layer to have unitary knit construction so as to be a one-piece element with the remaining portion of the knitted com-

14

ponent, the first tube disposed at a first location on the knitted component, the second tube disposed at a second location on the knitted component, the first tube and the second tube extending in an upward direction from an area proximal the sole structure, and first ends of the first tube and the second tube being located in an upper area of the upper and second ends of the first tube and the second tube being located in the area proximal the sole structure;

a strand extending through the first tube and the second tube, a portion of the strand extending between the first ends of the first tube and the second tube to form a loop, wherein at least one of the first knitted layer and the second knitted layer are formed by a yarn made of a thermoplastic polymer material that is fused to at least a portion of the strand extending through the first tube and the second tube.

16. The article of footwear according to claim 15, wherein the strand is fused to at least one of the first knitted layer and the second knitted layer to lock the position of the strand within the tube.

17. The article of footwear of claim 1, wherein the cross-sectional width of the strand is substantially equal to its cross-sectional thickness.

18. The article of footwear of claim 7, wherein the cross-sectional width of the strand is substantially equal to its cross-sectional thickness.

19. The article of footwear of claim 15, wherein the strand has a configuration of a one-dimensional material.

20. The article of footwear of claim 19, wherein the cross-sectional width of the strand is substantially equal to its cross-sectional thickness.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 9,668,533 B2
APPLICATION NO. : 14/198620
DATED : June 6, 2017
INVENTOR(S) : Bhupesh Dua et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims

In Column 11, Claim 1, Line 60, after “coextensive with each” insert --other--.

Signed and Sealed this
Third Day of October, 2017



Joseph Matal
*Performing the Functions and Duties of the
Under Secretary of Commerce for Intellectual Property and
Director of the United States Patent and Trademark Office*