



US009681253B2

(12) **United States Patent**
Lyman et al.

(10) **Patent No.:** **US 9,681,253 B2**
(45) **Date of Patent:** **Jun. 13, 2017**

(54) **SYSTEMS AND METHOD FOR CONFIGURING MOBILE DEVICE APPLICATIONS BASED ON LOCATION**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **eBay Inc.**, San Jose, CA (US)
(72) Inventors: **Nate L Lyman**, Livermore, CA (US);
Frank Russo, Sunnyvale, CA (US)
(73) Assignee: **eBay Inc.**, San Jose, CA (US)

6,259,381 B1 7/2001 Small
8,326,315 B2 12/2012 Phillips et al.
8,750,895 B2 6/2014 Grosman et al.
8,755,824 B1 6/2014 Wang et al.
9,451,403 B2 9/2016 Lyman et al.
2004/0235464 A1 11/2004 Korkalo et al.
2007/0038761 A1 2/2007 Tebeka
(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **15/240,375**

CN 1650649 A 8/2005
CN 104584508 A 4/2015
WO WO-2014036296 A1 3/2014

(22) Filed: **Aug. 18, 2016**

OTHER PUBLICATIONS

(65) **Prior Publication Data**
US 2016/0360338 A1 Dec. 8, 2016

“U.S. Appl. No. 13/958,340, Final Office Action mailed May 8, 2015”, 8 pgs.
(Continued)

Related U.S. Application Data

(63) Continuation of application No. 13/958,340, filed on Aug. 2, 2013, now Pat. No. 9,451,403.
(60) Provisional application No. 61/695,196, filed on Aug. 30, 2012.

Primary Examiner — Temica M Beamer
(74) *Attorney, Agent, or Firm* — Schwegman, Lundberg & Woessner, P.A.

(51) **Int. Cl.**
H04W 24/00 (2009.01)
H04W 4/00 (2009.01)
H04L 29/08 (2006.01)
H04W 4/02 (2009.01)

(57) **ABSTRACT**


Methods and systems for automatically configuring mobile device applications based on location are described. In an example, methods and systems for enabling contextual in-store experience modification on a mobile device can include capabilities for altering the functionality of a mobile application based at least in part on the location of the mobile device. For example, a mobile shopping application can be configured to perform different functions depending upon the type of retail location the mobile device is currently in. Additionally, the mobile application can be configured to enable different functions between a retail location and a user’s residence, among other locations.

(52) **U.S. Cl.**
CPC **H04W 4/001** (2013.01); **H04L 67/18** (2013.01); **H04L 67/34** (2013.01); **H04W 4/021** (2013.01)

(58) **Field of Classification Search**
CPC H04W 64/00; H04W 4/02; H04W 4/021–4/027
USPC 455/456.1, 456.2, 456.3, 422.1, 414.1, 455/414.2, 414.3

See application file for complete search history.

20 Claims, 9 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2010/0262554	A1	10/2010	Elliott
2010/0291950	A1	11/2010	Lin et al.
2011/0208797	A1	8/2011	Kim
2011/0256881	A1	10/2011	Huang et al.
2013/0203445	A1	8/2013	Grainger et al.
2013/0231137	A1	9/2013	Hugie
2013/0295970	A1	11/2013	Sheshadri et al.
2013/0331128	A1	12/2013	Qiu
2014/0057648	A1	2/2014	Lyman et al.
2014/0066101	A1	3/2014	Lyman et al.
2014/0135039	A1	5/2014	Sartipi et al.

OTHER PUBLICATIONS

“U.S. Appl. No. 13/958,340, Non Final Office Action mailed Sep. 11, 2015”, 8 pgs.
 “U.S. Appl. No. 13/958,340, Non Final Office Action mailed Oct. 8, 2014”, 8 pgs.
 “U.S. Appl. No. 13/958,340, Notice of Allowance mailed Jan. 29, 2016”, 5 pgs.
 “U.S. Appl. No. 13/958,340, Notice of Allowance mailed May 11, 2016”, 5 pgs.
 “U.S. Appl. No. 13/958,340, Response filed Jan. 8, 2015 to Non Final Office Action mailed Oct. 8, 2014”, 12 pgs.
 “U.S. Appl. No. 13/958,340, Response filed Jan. 11, 2016 to Non Final Office Action mailed Sep. 11, 2015”, 13 pgs.
 “U.S. Appl. No. 13/958,340, Supplemental Notice of Allowability mailed Feb. 19, 2016”, 2 pgs.
 “U.S. Appl. No. 13/958,340, Response filed Aug. 10, 2015 to Final Office Action mailed May 8, 2015”, 11 pgs.
 “Australian Application Serial No. 2013308666, First Examiner Report mailed Sep. 23, 2015”, 4 pgs.

“Australian Application Serial No. 2013308666, Response filed Feb. 12, 2016 to First Examiner Report mailed Sep. 23, 2015”, 21 pgs.
 “Canadian Application Serial No. 2,881,660, Office Action mailed Jun. 21, 2016”, 3 pgs.
 “European Application Serial No. 13762948.1, Communication pursuant to Rules 161(1) and 162 EPC mailed Apr. 9, 2015”, 2 pgs.
 “European Application Serial No. 13762948.1, Response filed Oct. 19, 2015 to Communication pursuant to Rules 161(1) and 162 EPC mailed Apr. 9, 2015”, 20 pgs.
 “International Application Serial No. PCT/US2013/057349, International Preliminary Report on Patentability mailed Mar. 12, 2015”, 6 pgs.
 “International Application Serial No. PCT/US2013/057349, International Search Report mailed Oct. 17, 2013”, 4 pgs.
 “International Application Serial No. PCT/US2013/057349, Written Opinion mailed Oct. 17, 2013”, 4 pgs.
 “Korean Application Serial No. 2015-7007973, Office Action mailed Mar. 28, 2016”, w/ English Translation, 8 pgs.
 “Korean Application Serial No. 2015-7007973, Response filed May 27, 2016 to Office Action mailed Mar. 28, 2016”, W/ English Translation of Claims, 42 pgs.
 “Chinese Application Serial No. 201380045296.2, Office Action mailed Nov. 2, 2016”, With English Translation, 14 pgs.
 “Korean Application Serial No. 2016-7026344, Office Action mailed Oct. 12, 2016”, W/English Translation, 4 pgs.
 “Korean Application Serial No. 2016-7026344, Response filed Dec. 9, 2016 to Office Action mailed Oct. 12, 2016”, w/ English Claims, 13 pgs.
 U.S. Appl. No. 13/958,340, filed Aug. 2, 2013, Systems and Method for Configuring Mobile Device Applications Based on Location.
 “Canadian Application Serial No. 2,881,660, Resposns filed Dec. 19, 2016 to Office Action mailed Jun. 21, 2016”, 18 pgs.
 “Chinese Application Serial No. 201380045296.2, Response filed Mar. 15, 2017 to Office Action mailed Nov. 2, 2016”, w/ English Claims, 9 pgs.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

700 ↗




FIG. 7




FIG. 8




FIG. 9

1

SYSTEMS AND METHOD FOR CONFIGURING MOBILE DEVICE APPLICATIONS BASED ON LOCATION

CLAIM OF PRIORITY

This application is a continuation of U.S. patent application Ser. No. 13/958,340, filed on Aug. 2, 2013, which application claims the benefit of priority to U.S. Provisional Application Ser. No. 61/695,196, filed on Aug. 30, 2012, which applications are incorporated herein by reference in their entirety.

COPYRIGHT NOTICE

A portion of the disclosure of this patent document contains material that is subject to copyright protection. The copyright owner has no objection to the facsimile reproduction by anyone of the patent document or the patent disclosure, as it appears in the Patent and Trademark Office patent files or records, but otherwise reserves all copyright rights whatsoever. The following notice applies to the software and data as described below and in the drawings that form a part of this document: Copyright 2012, eBay, Inc. All Rights Reserved.

TECHNICAL FIELD

This application relates generally to data processing within a network-based system operating over a distributed network or data processing on a mobile device, and more specifically to systems and methods for implementing a contextual in-store experience for mobile devices.

BACKGROUND

The ever-increasing use of smart phones, such as the iPhone® (from Apple, Inc. of Cupertino Calif.), with data connections and location determination capabilities is slowly changing the way people interact, shop for products and services, and even manage accounts. Smart phones can provide users with nearly instant information regarding a wide range of information, such as product availability, friend locations, or pricing. For example, applications such as RedLaser™ (from eBay, Inc. of San Jose, Calif.) allow a smart phone user to scan a bar code and instantly check prices across online and local retail outlets. Smart phones also commonly include mechanisms, such as global positioning system (GPS) receivers, that allow the devices to constantly update location information. These technology changes are also driving changes in the way people wish to interact with mobile devices within different contextual locations (e.g., retail stores, at home, or at school).

BRIEF DESCRIPTION OF THE DRAWINGS

Some embodiments are illustrated by way of example and not limitation in the figures of the accompanying drawings in which:

FIG. 1 is a block diagram depicting a system for enabling contextual in-store experience modifications on a mobile device, according to an example embodiment.

FIG. 2 is a block diagram illustrating an environment for operating a mobile device, according to an example embodiment.

FIG. 3 is a block diagram illustrating the mobile device, according to an example embodiment.

2

FIG. 4 is a block diagram illustrating a network-based system within which contextual in-store experience modifications can operate, according to an example embodiment.

FIG. 5 is a block diagram illustrating geo-location modules, according to an example embodiment.

FIG. 6 is a block diagram illustrating example geofences and a mobile device trajectory associated with a particular geofence, according to an example embodiment.

FIG. 7 is a flowchart illustrating a method for using contextual in-store experience modification on a mobile device, according to an example embodiment.

FIG. 8 is a flowchart illustrating a method of enabling contextual in-store experience modification on a mobile device, according to an example embodiment.

FIG. 9 is a diagrammatic representation of a machine in the example form of a computer system within which a set of instructions for causing the machine to perform any one or more of the methodologies discussed herein may be executed.

DEFINITIONS

Location—For the purposes of this specification and the associated claims, the term “location” is used to refer to a geographic location, such as a longitude/latitude combination or a street address. The term “location” is also used within this specification in reference to a physical location associated with an event, such as a vacation destination.

Real-time—For the purposes of this specification and the associated claims, the term “real-time” is used to refer to calculations or operations performed on-the-fly as events occur or input is received by the operable system. However, the use of the term “real-time” is not intended to preclude operations that cause some latency between input and response, so long as the latency is an unintended consequence induced by the performance characteristics of the machine.

Context—For the purposes of this specification and the associated claims, the term “context” is used to refer to environmental inputs, such as location, time, and weather conditions, among others. The context generally refers to conditions describing an individual’s (e.g., user’s) environment and/or activities. For example, context information can include a user’s location, direction of movement, current activity (e.g., working, driving, playing golf, shopping, etc.), current weather conditions, time of day, and time of year (e.g., season), among other things. In certain examples, context information about a user can also include past events, purchase history, or other historical data about the user. In the following examples, context can alter how a particular mobile device (e.g., smart phone) application operates on a particular mobile device. For example, a mobile shopping application may enter different modes depending upon location. In this example, if the user of the mobile device is at home the mobile shopping application may default to creation of a shopping list. In contrast, if the user of the mobile device is in a grocery store, the mobile shopping application can enter a grocery shopping mode displaying a repetitive grocery list. In yet another retail location, such as an electronics store, the mobile shopping application can enter a price comparison mode or access a wish list.

DETAILED DESCRIPTION

Example systems and methods for using contextual in-store experience modifications on a mobile device are

described, among other things. Also described are systems and methods for generating and utilizing geofence enabled mobile application configurations on a mobile device. In some example embodiments, the systems and methods for enabling contextual in-store experience modifications on a mobile device allow a mobile device to seamlessly alter the functionality of a mobile application based on location context, among other things. In the following description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of example embodiments. It will be evident, however, to one skilled in the art, that the present invention may be practiced without these specific details. It will also be evident that contextual in-store experience on a mobile device is not limited to the examples provided and may include other scenarios not specifically discussed.

Geofences can be used on a location-aware mobile device to detect when a user of the mobile device enters a specific location, such as a specific retail store. Geofences can be defined in terms of Global Positioning System (GPS) coordinates (e.g., latitude and longitude) combined with a radius measured in meters or feet, for example. Alternatively, geofences can also be defined according a series of GPS coordinates defining a bounding box. In yet other examples, a geofence can be any geometric shape defined by a mathematical formula and anchored by a GPS coordinate. In certain examples, location data points can also be used to detect movement trajectories, which can be used to refine detection of presence within geofences representing a physical location (e.g., retail store, user's residence, etc. . . .).

Using the concept of geofences or another means of location monitoring, a mobile device can monitor location and signal a mobile application to change configuration based at least in part upon the current location of the device. For example, RedLaser (from eBay, Inc. of San Jose, Calif.) is a mobile shopping application that allows users to scan products and obtain pricing and other product information. The functionality that automatically occurs when a user scans a product (e.g., a bar code, Quick Response (QR) code, or similar 2D matrix codes) can be modified based on the current location of the mobile device. If the mobile device is located within a retail location, the product scan can result in price comparison between the current location and online options, for example. Alternatively, if the mobile device is located within the user's residence, scanning a product may bring up promotional materials or a user guide for the product. In yet other examples, scanning a product may result in adding that product to a shopping list or online wish list. In some examples, the mobile application can include user configurable options for default responses within various locations, such as home, work, or individual retail stores (e.g., electronics store versus grocery store), among others. For example, scanning a QR or bar code while in a grocery store can result in checking the product off on a shopping list as purchased. The mobile application can also provide information on a current location, such as store hours, address, phone number, return policies, price match policy, or top selling products, among others.

Mobile applications, such as RedLaser, can also be configured to send notifications customized to a particular location. The notifications can be triggered when the mobile device (or a central monitoring service) detects that the mobile device has entered a particular location. For example, upon entering a particular electronics retailer location, the mobile application can provide offers, deals, inventory information, or store layout maps tailored to that particular location. This information may allow the mobile

device user quicker access to the desired product or incentive purchase of desired items. In some examples, the mobile application can interact with a network-based publishing system that can be configured to send personalized notifications and offers customized for the individual user and the current location. For example, a mobile device user may maintain some sort of online wish list (or similar user profile information on desired products and services), the online wish list can be matched against a retail location's current inventory and offers to produce a customized notification regarding opportunities for the mobile device user to make a purchase of an item on the wish list.

Mobile devices, such as an iPhone® (from Apple, Inc. of Cupertino, Calif.) or a device running Android™ (from Google, Inc. of Mountain View, Calif.), can often only monitor a limited number of geofences at a given time. Additionally, applications running on a mobile device commonly can only update monitored geofences when the application is opened by a user (or at least active in memory on the mobile device).

In order to overcome the limitation of only being able to monitor a limited number of geofences, a concept of geofence paging has been developed. Geofence paging can also provide a benefit of limiting the amount of memory required within a mobile device for monitoring and maintaining geofences. For example, a mobile device operating according to an embodiment can monitor 10 geofences at any given time (please note, 10 is an arbitrary number and is not intended to limit the systems and methods disclosed herein). Nine of the monitored geofences are assigned to specific geographical locations of interest (e.g., a retail store), while the 10th geofence geographically encircles the other nine. In some examples, the nine smaller geofences are referred to as child geofences with the large encompassing geofence referred to as a parent geofence. In yet other examples, the 10 geofences may be referred to as a page of geofences, with the large geofence describing the boundaries of the page and the smaller geofences located within the page. The concept of geofence paging (or parent/child geofence groups) is further discussed in a co-pending application titled "Passive Dynamic Geofencing for Mobile Devices," by inventors Nate Lyman and Frank Russo, filed on Aug. 22, 2012, Application Ser. No. 61/692,173. The Passive Dynamic Geofencing for Mobile Devices application is hereby incorporated by reference in its entirety.

Example System

FIG. 1 is a block diagram depicting a system 100 for enabling contextual in-store experience modifications on a mobile device, according to an example embodiment. In an example, system 100 can include users 110A-110N (collectively referred to as either user 110 or users 110 depending upon context) and a network-based publication system 120. In an example, the users 110A-110N can connect to the network-based publication system 120 via mobile devices 115A-115N (collectively referred to as mobile device 115). Users 110A-110N can also connect to the network-based publication system 120 via clients 140A-140N (collectively referred to as client 140 or clients 140).

In an example, the users 110 can configure an account on the network-based publication system 120. The account can be accessed by each user, such as user 110A, using mobile device 115A or client 140A, if user 110A meets the specified access criteria or rules. In an example, the access rules can include user identification and location identification rules (e.g., user must be located within a location supported by the network-based publication system 120). A user account on the network-based publication system 120 can allow the user

to define specific locations of interest for monitoring via geofences. In some examples, the network-based publication system **120** can monitor user behavior and create geofences based on past and predicted user behaviors. In certain examples, the network-based publication system **120** can be used by merchants as a location-based advertising platform, where users, such as users **110**, opt-in to location-based advertisements. For example, a national electronics retailer may use the network-based publication system **120** to provide location-based advertising to users **110** via mobile devices **115**. In this example, a series of parent geofences may be generated, each encompassing a manageable number of geographically related retail locations. Each of the electronics store locations would be covered by a much smaller child geofence that enables the network-based publication system **120** to serve location-based advertising relevant to the specific electronic retailer store location only when one of the users **110** is in geographic proximity to the store (based on the mobile device **115** detecting a location within one of the monitored child geofences).

In other examples, either the mobile device, such as mobile device **115**, or the network-based publication network **120** can re-configure a mobile application based on entry into a child geofence (or via other location-based determination and triggering mechanism).

Example Operating Environment

FIG. **2** is a block diagram illustrating an environment **200** for operating a mobile device **115**, according to an example embodiment. The environment **200** is an example environment within which methods for implementing contextual in-store experience modifications can operate. The environment **200** can include a mobile device **115**, a communication connection **210**, a network **220**, servers **230**, a wireless communication connection **260**, a communication satellite **270**, a merchant server **280**, and a database **290**. The servers **230** can optionally include location based service application **232**, location determination application **234**, publication application **236**, and location configurable application **238**. The database **290** can optionally include geofence pages **292**, user profiles **294**, and/or location history **296**. The mobile device **115** represents one example device that can be utilized by a user to monitor current location and alter mobile device application behavior, such as location configurable application **238**. The mobile device **115** may be any of a variety of types of devices (for example, a cellular telephone, a Personal Digital Assistant (PDA), a Personal Navigation Device (PND), a handheld computer, a tablet computer, a notebook computer, or other type of movable device). The mobile device **115** may interface via a connection **210** with a communication network **220**. Depending on the form of the mobile device **115**, any of a variety of types of connections **210** and communication networks **220** may be used.

For example, the connection **210** may be Code Division Multiple Access (CDMA) connection, a Global System for Mobile communications (GSM) connection, or other type of cellular connection. Such connection **210** may implement any of a variety of types of data transfer technology, such as Single Carrier Radio Transmission Technology (1xRTT), Evolution-Data Optimized (EVDO) technology, General Packet Radio Service (GPRS) technology, Enhanced Data rates for GSM Evolution (EDGE) technology, or other data transfer technology (e.g., fourth generation wireless, 4G networks). When such technology is employed, the communication network **220** may include a cellular network that has a plurality of cell sites of overlapping geographic coverage, interconnected by cellular telephone exchanges.

These cellular telephone exchanges may be coupled to a network backbone (for example, the public switched telephone network (PSTN), a packet-switched data network, or other types of networks).

In another example, the connection **210** may be Wireless Fidelity (Wi-Fi, IEEE 802.11x type) connection, a Worldwide Interoperability for Microwave Access (WiMAX) connection, or another type of wireless data connection. In such an embodiment, the communication network **220** may include one or more wireless access points coupled to a local area network (LAN), a wide area network (WAN), the Internet, or other packet-switched data network.

In yet another example, the connection **210** may be a wired connection, for example an Ethernet link, and the communication network may be a LAN, a WAN, the Internet, or other packet-switched data network. Accordingly, a variety of different configurations are expressly contemplated.

A plurality of servers **230** may be coupled via interfaces to the communication network **220**, for example, via wired or wireless interfaces. These servers **230** may be configured to provide various types of services to the mobile device **115**. For example, one or more servers **230** may execute location based service (LBS) applications **232**, which interoperate with software executing on the mobile device **115**, to provide LBSs to a user. LBSs can use knowledge of the device's location, and/or the location of other devices, to provide location-specific information, recommendations, notifications, interactive capabilities, and/or other functionality to a user. For example, an LBS application **232** can provide location data to a network-based publication system **120**, which can then be used to provide access to a group account on the network-based publication system **120**. Knowledge of the device's location, and/or the location of other devices, may be obtained through interoperation of the mobile device **115** with a location determination application **234** executing on one or more of the servers **230**. Location information may also be provided by the mobile device **115**, without use of a location determination application, such as application **234**. In certain examples, the mobile device **115** may have some limited location determination capabilities that are augmented by the location determination application **234**. In some examples, the servers **230** can also include publication application **236** for providing location-aware publication of data such as advertisements or offers. In certain examples, location data can be provided to the publication application **236** by the location determination application **234**. In some examples, the location data provided by the location determination application **234** can include merchant information (e.g., identification of a retail location). In certain examples, the location determination application **234** can receive signals via the network **220** to further identify a location. For example, a merchant may broadcast a specific IEEE 802.11 service set identifier (SSID) that can be interpreted by the location determination application **234** to identify a particular retail location. In another example, the merchant may broadcast an identification signal via radio-frequency identification (RFID), near-field communication (NFC), or a similar protocol that can be used by the location determination application **234**. In addition to examples using these various mechanisms to identify a particular location, these mechanisms (e.g., SSIDs, RFIDs, NFC, and so forth) can be used as secondary authentication factors, which are discussed in more detail below.

In certain examples, the location configurable application **238** can leverage the LBS application **232** or the location

determination application **234** to assist in determining device location and proper location-based configuration to apply.

Example Mobile Device

FIG. **3** is a block diagram illustrating the mobile device **115**, according to an example embodiment. The mobile device **115** may include a processor **310**. The processor **310** may be any of a variety of different types of commercially available processors suitable for mobile devices (for example, an XScale architecture microprocessor, a Micro-processor without Interlocked Pipeline Stages (MIPS) architecture processor, or another type of processor). A memory **320**, such as a Random Access Memory (RAM), a Flash memory, or other type of memory, is typically accessible to the processor **310**. The memory **320** may be adapted to store an operating system (OS) **330**, as well as application programs **340**, such as a mobile location enabled application that may provide LBSs to a user. In certain examples, the application programs **340** can include instructions to alter functional behavior based on location information. The processor **310** may be coupled, either directly or via appropriate intermediary hardware, to a display **350** and to one or more input/output (I/O) devices **360**, such as a keypad, a touch panel sensor, a microphone, and the like. Similarly, in some embodiments, the processor **310** may be coupled to a transceiver **370** that interfaces with an antenna **390**. The transceiver **370** may be configured to both transmit and receive cellular network signals, wireless data signals, or other types of signals via the antenna **390**, depending on the nature of the mobile device **115**. In this manner, the connection **210** with the communication network **220** may be established. Further, in some configurations, a GPS receiver **380** may also make use of the antenna **390** to receive GPS signals.

Additional detail regarding providing and receiving location-based services can be found in U.S. Pat. No. 7,848,765, titled "Location-Based Services," granted to Phillips et al. and assigned to eBay, Inc. of San Jose, Calif., which is hereby incorporated by reference.

An example geo-location concept discussed within U.S. Pat. No. 7,848,765 is a geofence. A geofence can be defined as a perimeter or boundary around a physical location or mobile object (e.g., a user). A geofence can be as simple as a radius around a physical location defining a circular region around the location. However, a geofence can be any geometric shape or an arbitrary boundary drawn on a map. A geofence can be used to determine a geographical area of interest for the calculation of demographics, advertising, or similar purposes. Geofences can be used in conjunction with the offer generation and delivery concepts discussed herein. For example, a geofence can be used to assist in determining whether a user (or mobile device associated with the user) is within a geographic area of interest (e.g., target location) to providing access to a group account. If the user is within a geofence established by provisioning of a group account, the systems discussed herein can use that information to authorize the user to access the group account, such as authorizing the user to process a payment against a group payment account.

Example Platform Architecture

FIG. **4** is a block diagram illustrating a network-based system **400** within which contextual in-store experience modifications can operate, according to an example embodiment. The block diagram depicts a network-based system **400** (in the exemplary form of a client-server system), within which an example embodiment can be deployed. A networked system **402** is shown, in the example form of a

network-based location-aware publication or payment system, that provides server-side functionality, via a network **404** (e.g., the Internet or WAN) to one or more client machines **410**, **412**. FIG. **4** illustrates, for example, a web client **406** (e.g., a browser, such as the Internet Explorer browser developed by Microsoft Corporation of Redmond, Wash. State) and a programmatic client **408** (e.g., PAYPAL payments smart phone application from PayPal, Inc. of San Jose Calif.) executing on respective client machines **410** and **412**. In an example, the client machines **410** and **412** can be in the form of a mobile device, such as mobile device **115**. In yet another example, the programmatic client **408** can be the RedLaser mobile shopping application from eBay, Inc. of San Jose, Calif.

An Application Programming Interface (API) server **414** and a web server **416** are coupled to, and provide programmatic and web interfaces respectively to, one or more application servers **418**. The application servers **418** host one or more publication modules **420** (in certain examples, these can also include commerce modules, advertising modules, and marketplace modules, to name a few), payment modules **422**, and geo-location modules **432**. The application servers **418** are, in turn, shown to be coupled to one or more database servers **424** that facilitate access to one or more databases **426**. In some examples, the application server **418** can access the databases **426** directly without the need for a database server **424**.

The publication modules **420** may provide a number of publication functions and services to users that access the networked system **402**. The payment modules **422** may likewise provide a number of payment services and functions to users. The payment modules **422** may allow users to accumulate value (e.g., in a commercial currency, such as the U.S. dollar, or a proprietary currency, such as "points") in accounts, and then later to redeem the accumulated value for products (e.g., goods or services) that are advertised or made available via the various publication modules **420**, within retail locations, or within external online retail venues. The payment modules **422** can also be configured to facilitate payment processing based on geofence detection and work in conjunction with the geo-location modules **432**. The geo-location modules **432** may provide determination of current location, among other things. While the publication modules **420**, payment modules **422**, and geo-location modules **432** are shown in FIG. **4** to all form part of the networked system **402**, it will be appreciated that, in alternative embodiments, the payment modules **422** may form part of a payment service that is separate and distinct from the networked system **402**.

Further, while the system **400** shown in FIG. **4** employs a client-server architecture, the present invention is of course not limited to such an architecture, and could equally well find application in a distributed, or peer-to-peer, architecture system, for example. The various publication modules **420**, payment modules **422**, and authorization modules **432** could also be implemented as standalone systems or software programs, which do not necessarily have networking capabilities.

The web client **406** accesses the various publication modules **420**, payment modules **422**, and geo-location modules **432** via the web interface supported by the web server **416**. Similarly, the programmatic client **408** accesses the various services and functions provided by the publication modules **420**, payment modules **422**, and geo-location modules **432** via the programmatic interface provided by the API server **414**. The programmatic client **408** may, for example, be a smart phone application (e.g., the PAYPAL payments

application) that enables users to process payments directly from their smart phones leveraging user profile data and current location information provided by the smart phone or accessed over the network **404**.

FIG. **4** also illustrates a third party application **428**, executing on a third party server machine **440**, as having programmatic access to the networked system **402** via the programmatic interface provided by the API server **414**. For example, the third party application **428** may, utilizing information retrieved from the networked system **402**, support one or more features or functions on a web site hosted by the third party. The third party website may, for example, provide one or more promotional, marketplace or payment functions that are supported by the relevant applications of the networked system **402**. Additionally, the third party website may provide merchants with access to the geo-location modules **432** for advertising or marketing purposes.

Example Geo-Location Modules

FIG. **5** is a block diagram illustrating geo-location modules **432**, according to an example embodiment. In this example, the geo-location modules **432** can include a rules engine **505**, a communication module **510**, a generation module **520**, an account module **530**, and a location module **540**. In an example, the geo-location modules **432** can access database **426** to store and/or retrieve generation rules, user profile data, location data, and geofences (parent and child), as well as other information, to enable contextual in-store experience modifications to a mobile application running on a mobile device.

In an example, the rules engine **505** can be configured to manage and evaluate rules controlling how one or more mobile applications can be configured in various locations or other contextual situations (e.g., weather, time of day, time of the year, etc. . . .).

The communication module **510** can be configured to manage all communications involving the geo-location module **432**. In an example, the communication module **510** can be configured to manage communications between the geo-location modules **432** and a user, where the user is communicating via the mobile device **115** or the client **140**.

In an example, the generation module **520** is configured to generate mobile application configuration packages (e.g., files) according to information provided by modules, such as the account module **530**, the location module **540** and the rules engine **505**.

In an example, the account module **530** is configured to provision (setup) and manage a user account on the networked system **402**. In certain examples, the account module **530** can provision a user account according to configuration data received by the communication module **510**. The account module **530** can also work in conjunction with the rules engine **505** in provisioning or decommissioning user accounts.

In an example, the location module **540** is configured to receive location data from a mobile device, such as mobile device **115**, and determine from the location data a current physical location, which may include reference to landmarks or other sites of interest. In some examples, the location module **540** can receive GPS-type coordinates (e.g., longitude and latitude), which can be used to establish a current location associated with a mobile device (and, thus, a user of the mobile device). Using the longitude and latitude coordinates, the location module **540** can determine if the current location is within a current parent geofence, for example. In certain examples, the location module **540** can receive other location determining information from a mobile device, such as a photograph or scan of data only readily available

at a certain physical location (generally referred to as secondary location authentication factor). In another example, some merchants may broadcast specific wireless network signals that can be received by a mobile device, such as mobile device **115**. Once received, the mobile device **115** can include programming or circuitry to translate the signal into a specific location, or the mobile device **115** can simply retransmit the unique signal to the location module **540**. In an example, a merchant location can transmit a unique SSID, which the location module can be programmed to interpret as identifying a specific merchant location. In another example, the merchant may broadcast a unique SSID within all of its locations and the location module **540** can be programmed to use a combination of the unique SSID and other location data (e.g., GPS coordinates or cell tower locations) to identify a specific location. Further functionality that can be provided by the location module **540** is discussed in reference to FIG. **6** below.

Additional details regarding the functionality provided by the geo-location modules **432** are detailed in reference to FIGS. **6-8** below.

Example Geo-Location Trajectory Tracking

FIG. **6** is a block diagram illustrating example geofences and a mobile device trajectory associated with a particular geofence, according to an example embodiment. In this example, geofences **610A** through **610N** (collectively referred to as geofence **610** or geofences **610** depending upon context) represent a series of monitored geofences. In certain examples, geofences **610** can represent a series of monitored physical locations, such as a chain of coffee shops or retail stores. Locations **630A** through **630N** (collectively referred to as locations **630**) represent chronologically captured location data from a mobile device, such as mobile device **115**. In an example, locations **630** can be analyzed to determine a trajectory **620** of mobile device **115**, which can in turn be utilized to more accurately determine when the mobile device **115** actually enters a geofence, such as geofence **610C**. Tracking a mobile device, such as mobile device **115**, over time can provide more accurate location information than merely receiving a single location indicator from the mobile device **115**. Additionally, using trajectories **620** can improve the ability to accurately determine when a mobile device actually enters a physical location, such as a retail store.

In some examples, location determination mechanisms can also use location averaging to improve the accuracy of location determination. For example, in addition to using trajectory tracking, the networked system **402** can also obtain multiple location data points from the mobile device **115** to further refine the location data used in subsequent processing. Similarly, the mobile device **115** itself can also use location averaging to refine the position reported out or used by mobile applications for other location-based services and processing.

Example Methods

FIG. **7** is a flowchart illustrating a method **700** for using contextual in-store experience modification on a mobile device, according to an example embodiment. In an example, the method **700** can include operations for: monitoring mobile device location at **710**, monitoring one or more geofences on a mobile device at **720**, detecting entry into a monitored geofence at **730**, configuring a mobile application based at least in part on entry into the monitored geofence at **740**, and optionally altering functionality of a particular mobile application function based on presence within a geofence at **750**.

11

In an example, the method 700 can begin at 710 with the mobile device 115 monitoring its current location. At 720, the method 700 can continue with the mobile device 115 monitoring one or more geofences in reference to the current location of the mobile device 115. At 730, the method 700 can continue with the mobile device 115 detecting entry into a monitored geofence. In an example, the mobile device 115 can detect entry into the monitored geofence including calculating a trajectory associated with the mobile device 115.

At 740, the method 700 can continue with the mobile device 115 configuring a mobile application based at least in part on entry into the monitored geofence. In an example, the mobile device 115 can select a mobile application configuration based on the entered geofence (e.g., physical location). In this example, each geofence (or type of geofence) can have a mobile application configuration associated with it. Finally, at 750, the method 700 can optionally include the mobile device 115 altering a specific individual function of a mobile application based on presence within a geofence (or physical location if determined through means other than geofencing).

FIG. 8 is a flowchart illustrating a method 800 of enabling contextual in-store experience modification on a mobile device, according to an example embodiment. In an example, the method 800 can include operations for: monitoring geofences associated with physical locations at 810, receiving mobile device location data at 820, determining whether the mobile device is within a location at 830, selecting a mobile application configuration at 840, and transmitting a mobile application configuration at 850. Optionally, the method 800 can also include operations such as: receiving a mobile application function request at 860 and processing the mobile application request at 870.

The method 800 can begin at operation 810 with the networked system 402 monitoring one or more geofences associated with physical locations. In an example, the networked system 402 can be configured to monitor geofences associated with various retail locations and other locations of interest to subscribing users (e.g., users of a particular mobile application or users registered with the networked system 402). The networked system 402 can also monitor multiple mobile devices, such as mobile devices 115, in reference to the geofences. At 820, the method 800 can continue with networked system 402 receiving, from a mobile device, such as mobile device 115, location data indicating a current location associated with the mobile device 115.

At 830, the method 800 can continue with the networked system 402 determining, based on the location data received from the mobile device 115, whether the mobile device 115 is within a monitored geofence (e.g., within a physical location of interest). If the networked system 402 determines that the mobile device 115 is within a physical location of interest (e.g., a geofence), then the method 800 can continue at 840, with the networked system 402 selecting a mobile application configuration corresponding to the physical location (e.g., geofence). At 850, the method 800 can continue with the networked system 402 transmitting the mobile application configuration to the mobile device 115.

Optionally, the method 800 can also include operation 860 that includes the networked system 402 receiving a mobile application function request from the mobile device 115. In an example, the method 800 can continue at 870 with the networked system 402 processing the mobile application function request based at least in part on the current location of the mobile device 115. For example, if the networked

12

system 402 determines (at operation 830) that the mobile device 115 is located within an electronics retail store, the mobile application function request can be processed in light of this information. In this example, if the mobile application function request includes a product identifier, the networked system 402 can interpret the function request as a price comparison request, and process it accordingly.

Modules, Components and Logic

Certain embodiments are described herein as including logic or a number of components, modules, or mechanisms. Modules may constitute either software modules (e.g., code embodied on a machine-readable medium or in a transmission signal) or hardware modules. A hardware module is a tangible unit capable of performing certain operations and may be configured or arranged in a certain manner. In example embodiments, one or more computer systems (e.g., a standalone, client, or server computer system) or one or more hardware modules of a computer system (e.g., a processor or a group of processors) may be configured by software (e.g., an application or application portion) as a hardware module that operates to perform certain operations as described herein.

In various embodiments, a hardware module may be implemented mechanically or electronically. For example, a hardware module may comprise dedicated circuitry or logic that is permanently configured (e.g., as a special-purpose processor, such as a field programmable gate array (FPGA) or an application-specific integrated circuit (ASIC)) to perform certain operations. A hardware module may also comprise programmable logic or circuitry (e.g., as encompassed within a general-purpose processor or other programmable processor) that is temporarily configured by software to perform certain operations. It will be appreciated that the decision to implement a hardware module mechanically, in dedicated and permanently configured circuitry, or in temporarily configured circuitry (e.g., configured by software) may be driven by cost and time considerations.

Accordingly, the term “hardware module” should be understood to encompass a tangible entity, be that an entity that is physically constructed, permanently configured (e.g., hardwired) or temporarily configured (e.g., programmed) to operate in a certain manner and/or to perform certain operations described herein. Considering embodiments in which hardware modules are temporarily configured (e.g., programmed), each of the hardware modules need not be configured or instantiated at any one instance in time. For example, where the hardware modules comprise a general-purpose processor configured using software, the general-purpose processor may be configured as respective different hardware modules at different times. Software may accordingly configure a processor, for example, to constitute a particular hardware module at one instance of time and to constitute a different hardware module at a different instance of time.

Hardware modules can provide information to, and receive information from, other hardware modules. Accordingly, the described hardware modules may be regarded as being communicatively coupled. Where multiple of such hardware modules exist contemporaneously, communications may be achieved through signal transmission (e.g., over appropriate circuits and buses) that connects the hardware modules. In embodiments in which multiple hardware modules are configured or instantiated at different times, communications between such hardware modules may be achieved, for example, through the storage and retrieval of information in memory structures to which the multiple hardware modules have access. For example, one hardware

module may perform an operation and store the output of that operation in a memory device to which it is communicatively coupled. A further hardware module may then, at a later time, access the memory device to retrieve and process the stored output. Hardware modules may also initiate communications with input or output devices and can operate on a resource (e.g., a collection of information).

The various operations of example methods described herein may be performed, at least partially, by one or more processors that are temporarily configured (e.g., by software) or permanently configured to perform the relevant operations. Whether temporarily or permanently configured, such processors may constitute processor-implemented modules that operate to perform one or more operations or functions. The modules referred to herein may, in some example embodiments, comprise processor-implemented modules.

Similarly, the methods described herein may be at least partially processor-implemented. For example, at least some of the operations of a method may be performed by one or more processors or processor-implemented modules. The performance of certain of the operations may be distributed among the one or more processors, not only residing within a single machine, but deployed across a number of machines. In some example embodiments, the processor or processors may be located in a single location (e.g., within a home environment, an office environment or as a server farm), while in other embodiments the processors may be distributed across a number of locations.

The one or more processors may also operate to support performance of the relevant operations in a “cloud computing” environment or as a “software as a service” (SaaS). For example, at least some of the operations may be performed by a group of computers (as examples of machines including processors), with these operations being accessible via a network (e.g., the Internet) and via one or more appropriate interfaces (e.g., APIs).

Electronic Apparatus and System

Example embodiments may be implemented in digital electronic circuitry, or in computer hardware, firmware, software, or in combinations of these. Example embodiments may be implemented using a computer program product, for example, a computer program tangibly embodied in an information carrier, for example, in a machine-readable medium for execution by, or to control the operation of, data processing apparatus, for example, a programmable processor, a computer, or multiple computers.

A computer program can be written in any form of programming language, including compiled or interpreted languages, and it can be deployed in any form, including as a stand-alone program or as a module, subroutine, or other unit suitable for use in a computing environment. A computer program can be deployed to be executed on one computer or on multiple computers at one site or distributed across multiple sites and interconnected by a communication network.

In example embodiments, operations may be performed by one or more programmable processors executing a computer program to perform functions by operating on input data and generating output. Method operations can also be performed by, and apparatus of example embodiments may be implemented as, special purpose logic circuitry (e.g., a FPGA or an ASIC).

The computing system can include clients and servers. A client and server are generally remote from each other and typically interact through a communication network. The

relationship of client and server arises by virtue of computer programs running on the respective computers and having a client-server relationship to each other. In embodiments deploying a programmable computing system, it will be appreciated that both hardware and software architectures require consideration. Specifically, it will be appreciated that the choice of whether to implement certain functionality in permanently configured hardware (e.g., an ASIC), in temporarily configured hardware (e.g., a combination of software and a programmable processor), or a combination of permanently and temporarily configured hardware may be a design choice. Below are set out hardware (e.g., machine) and software architectures that may be deployed, in various example embodiments.

Example Machine Architecture and Machine-Readable Medium

FIG. 9 is a block diagram of a machine in the example form of a computer system 900 within which instructions, for causing the machine to perform any one or more of the methodologies discussed herein, may be executed. In alternative embodiments, the machine operates as a standalone device or may be connected (e.g., networked) to other machines. In a networked deployment, the machine may operate in the capacity of a server or a client machine in a server-client network environment, or as a peer machine in a peer-to-peer (or distributed) network environment. The machine may be a personal computer (PC), a tablet PC, a set-top box (STB), a PDA, a cellular telephone, a web appliance, a network router, switch or bridge, or any machine capable of executing instructions (sequential or otherwise) that specify actions to be taken by that machine. Further, while only a single machine is illustrated, the term “machine” shall also be taken to include any collection of machines that individually or jointly execute a set (or multiple sets) of instructions to perform any one or more of the methodologies discussed herein.

The example computer system 900 includes a processor 902 (e.g., a central processing unit (CPU), a graphics processing unit (GPU) or both), a main memory 904 and a static memory 906, which communicate with each other via a bus 908. The computer system 900 may further include a video display unit 910 (e.g., a liquid crystal displays (LCD) or a cathode ray tube (CRT)). The computer system 900 also includes an alphanumeric input device 912 (e.g., a keyboard), a cursor control (user interface (UI) navigation) device 914 (e.g., a mouse), a disk drive unit 916, a signal generation device 918 (e.g., a speaker) and a network interface device 920.

Machine-Readable Medium

The disk drive unit 916 includes a machine-readable medium 922 on which is stored one or more sets of instructions and data structures (e.g., software) 924 embodying or used by any one or more of the methodologies or functions described herein. The instructions 924 may also reside, completely or at least partially, within the main memory 904, static memory 906, and/or within the processor 902 during execution thereof by the computer system 900, with the main memory 904 and the processor 902 also constituting machine-readable media.

While the machine-readable medium 922 is shown in an example embodiment to be a single medium, the term “machine-readable medium” may include a single medium or multiple media (e.g., a centralized or distributed database, and/or associated caches and servers) that store the one or more instructions or data structures. The term “machine-readable medium” shall also be taken to include any tangible medium that is capable of storing, encoding or carrying

instructions for execution by the machine and that cause the machine to perform any one or more of the methodologies of the present invention, or that is capable of storing, encoding or carrying data structures used by or associated with such instructions. The term “machine-readable medium” shall accordingly be taken to include, but not be limited to, solid-state memories and optical and magnetic media. Specific examples of machine-readable media include non-volatile memory, including by way of example, semiconductor memory devices (e.g., Erasable Programmable Read-Only Memory (EPROM), Electrically Erasable Programmable Read-Only Memory (EEPROM)) and flash memory devices; magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM and DVD-ROM disks.

Transmission Medium

The instructions 924 may further be transmitted or received over a communications network 926 using a transmission medium. The instructions 924 may be transmitted using the network interface device 920 and any one of a number of well-known transfer protocols (e.g., HTTP). Examples of communication networks include a LAN, a WAN, the Internet, mobile telephone networks, Plain Old Telephone (POTS) networks, and wireless data networks (e.g., WiFi and WiMAX networks). The term “transmission medium” shall be taken to include any intangible medium that is capable of storing, encoding or carrying instructions for execution by the machine, and includes digital or analog communications signals or other intangible media to facilitate communication of such software.

Thus, a method and system for contextual in-store experience modification on a mobile device has been described. Although the present invention has been described with reference to specific example embodiments, it will be evident that various modifications and changes may be made to these embodiments without departing from the broader spirit and scope of the invention. Accordingly, the specification and drawings are to be regarded in an illustrative rather than a restrictive sense.

Although an embodiment has been described with reference to specific example embodiments, it will be evident that various modifications and changes may be made to these embodiments without departing from the broader spirit and scope of the invention. Accordingly, the specification and drawings are to be regarded in an illustrative rather than a restrictive sense. The accompanying drawings that form a part hereof, show by way of illustration, and not of limitation, specific embodiments in which the subject matter may be practiced. The embodiments illustrated are described in sufficient detail to enable those skilled in the art to practice the teachings disclosed herein. Other embodiments may be used and derived therefrom, such that structural and logical substitutions and changes may be made without departing from the scope of this disclosure. This Detailed Description, therefore, is not to be taken in a limiting sense, and the scope of various embodiments is defined only by the appended claims, along with the full range of equivalents to which such claims are entitled.

Such embodiments of the inventive subject matter may be referred to herein, individually and/or collectively, by the term “invention” merely for convenience and without intending to voluntarily limit the scope of this application to any single invention or inventive concept if more than one is in fact disclosed. Thus, although specific embodiments have been illustrated and described herein, it should be appreciated that any arrangement calculated to achieve the same purpose may be substituted for the specific embodi-

ments shown. This disclosure is intended to cover any and all adaptations or variations of various embodiments. Combinations of the above embodiments, and other embodiments not specifically described herein, will be apparent to those of skill in the art upon reviewing the above description.

All publications, patents, and patent documents referred to in this document are incorporated by reference herein in their entirety, as though individually incorporated by reference. In the event of inconsistent usages between this document and those documents so incorporated by reference, the usage in the incorporated reference(s) should be considered supplementary to that of this document; for irreconcilable inconsistencies, the usage in this document controls.

In this document, the terms “a” or “an” are used, as is common in patent documents, to include one or more than one, independent of any other instances or usages of “at least one” or “one or more.” In this document, the term “or” is used to refer to a nonexclusive or, such that “A or B” includes “A but not B,” “B but not A,” and “A and B,” unless otherwise indicated. In the appended claims, the terms “including” and “in which” are used as the plain-English equivalents of the respective terms “comprising” and “wherein.” Also, in the following claims, the terms “including” and “comprising” are open-ended; that is, a system, device, article, or process that includes elements in addition to those listed after such a term in a claim are still deemed to fall within the scope of that claim. Moreover, in the following claims, the terms “first,” “second,” and “third,” and so forth are used merely as labels, and are not intended to impose numerical requirements on their objects.

The Abstract of the Disclosure is provided to comply with 37 C.F.R. §1.72(b), requiring an abstract that will allow the reader to quickly ascertain the nature of the technical disclosure. It is submitted with the understanding that it will not be used to interpret or limit the scope or meaning of the claims. In addition, in the foregoing Detailed Description, it can be seen that various features are grouped together in a single embodiment for the purpose of streamlining the disclosure. This method of disclosure is not to be interpreted as reflecting an intention that the claimed embodiments require more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive subject matter lies in less than all features of a single disclosed embodiment. Thus the following claims are hereby incorporated into the Detailed Description, with each claim standing on its own as a separate embodiment.

The claimed invention includes:

1. A method of improving location determination accuracy of a mobile device comprising:
 - monitoring, on the mobile device, a parent geofence that geographically encompasses a plurality of child geofences, each of the child geofences representing a physical location within the parent geofence;
 - detecting, based at least in part on a first location of the mobile device, entry into a first child geofence of the plurality of child geofences within the parent geofence;
 - detecting, based at least in part on a second location of the mobile device, entry into a second child geofence of the plurality of child geofences within the parent geofence;
 - tracking a chronology of the plurality of child geofences entered by the mobile device, the chronology indicating a chronological sorting of location data indicative of locations of the mobile device within the parent geofence, the location data including at least first location data corresponding to the first location of the

17

mobile device and second location data corresponding to the second location of the mobile device; and calculating a trajectory of the mobile device based on the chronology of child geofences.

2. The method of claim 1, wherein each of the plurality of child geofences include a corresponding mobile application configuration, the mobile application configuration altering a function performed by an application executed on the mobile device.

3. The method of claim 1, wherein the monitoring the plurality of child geofences includes monitoring a plurality of types of geofences.

4. The method of claim 3, further comprising: associating a type of geofence from the plurality of types of geofences with each geofence of the plurality of child geofences; and assigning a mobile application configuration to each type of geofence of the plurality of types of geofences.

5. The method of claim 1, further comprising: detecting entry into a first child geofence from among the plurality of child geofences based on the trajectory.

6. The method of claim 1, further comprising: accessing a wish list associated with a user of the mobile device, the wish list comprising a list of desired items; and causing display of a notification at the mobile device based on the trajectory, wherein the notification includes an offer based on the list of desired items of the wish list.

7. The method of claim 1, further comprising: generating a geofence that encompasses a location based on the trajectory.

8. A system to improve location determination accuracy of a mobile device comprising: one or more processors; a memory including instructions that, when executed by the one or more processors, cause the system to perform operations comprising: monitoring, on the mobile device, a parent geofence that geographically encompasses a plurality of child geofences, each of the child geofences representing a physical location within the parent geofence; detecting, based at least in part on a first location of the mobile device, entry into a first child geofence of the plurality of child geofences within the parent geofence; detecting, based at least in part on a second location of the mobile device, entry into a second child geofence of the plurality of child geofences within the parent geofence; tracking a chronology of the plurality of child geofences entered by the mobile device, the chronology indicating a chronological sorting of location data indicative of locations of the mobile device within the parent geofence, the location data including at least first location data corresponding to the first location of the mobile device and second location data corresponding to the second location of the mobile device; and calculating a trajectory of the mobile device based on the chronology of child geofences.

9. The system of claim 8, wherein each of the plurality of child geofences include a corresponding mobile application configuration, the mobile application configuration altering a function performed by an application executed on the mobile device.

10. The system of claim 8, wherein the monitoring the plurality of child geofences includes monitoring a plurality of types of geofences.

18

11. The system of claim 10, wherein the instructions cause the system to perform operations further comprising: associating a type of geofence from the plurality of types of geofences with each geofence of the plurality of child geofences; and assigning a mobile application configuration to each type of geofence of the plurality of types of geofences.

12. The system of claim 8, wherein the instructions cause the system to perform operations further comprising: detecting entry into a first child geofence from among the plurality of child geofences based on the trajectory.

13. The system of claim 8, wherein the instructions cause the system to perform operations further comprising: accessing a wish list associated with a user of the mobile device, the wish list comprising a list of desired items; and causing display of a notification at the mobile device based on the trajectory, wherein the notification includes an offer based on the list of desired items of the wish list.

14. The system of claim 8, wherein the instructions cause the system to perform operations further comprising: generating a geofence that encompasses a location based on the trajectory.

15. A non-transitory machine-readable storage medium including instructions that, when executed by one or more processors of a mobile device, cause the mobile device to perform operations to improve location determination accuracy of a mobile device, the operations comprising: monitoring, on the mobile device, a parent geofence that geographically encompasses a plurality of child geofences, each of the child geofences representing a physical location within the parent geofence; detecting, based at least in part on a first location of the mobile device, entry into a first child geofence of the plurality of child geofences within the parent geofence; detecting, based at least in part on a second location of the mobile device, entry into a second child geofence of the plurality of child geofences within the parent geofence; tracking a chronology of the child geofences entered by the mobile device, the chronology indicating a chronological sorting of location data indicative of locations of the mobile device within the parent geofence, the location data including at least first location data corresponding to the first location of the mobile device and second location data corresponding to the second location of the mobile device; and calculating a trajectory of the mobile device based on the chronology of child geofences.

16. The non-transitory machine-readable storage medium of claim 15, wherein each of the plurality of child geofences include a corresponding mobile application configuration, the mobile application configuration altering a function performed by an application executed on the mobile device.

17. The non-transitory machine-readable storage medium of claim 15, wherein the monitoring the plurality of child geofences includes monitoring a plurality of types of geofences.

18. The non-transitory machine-readable storage medium of claim 17, wherein the instructions cause the mobile device to perform operations further comprising: associating a type of geofence from the plurality of types of geofences with each geofence of the plurality of child geofences; and assigning a mobile application configuration to each type of geofence of the plurality of types of geofences.

19. The non-transitory machine-readable storage medium of claim 15, wherein the instructions cause the mobile device to perform operations further comprising:

detecting entry into a first child geofence from among the plurality of child geofences based on the trajectory. 5

20. The non-transitory machine-readable storage medium of claim 15, wherein the instructions cause the mobile device to perform operations further comprising:

accessing a wish list associated with a user of the mobile device, the wish list comprising a list of desired items; 10
and

causing display of a notification at the mobile device based on the trajectory, wherein the notification includes an offer based on the list of desired items of the wish list. 15

* * * * *