



US009690061B2

(12) **United States Patent**
Hurley et al.

(10) **Patent No.:** **US 9,690,061 B2**
(45) **Date of Patent:** ***Jun. 27, 2017**

(54) **MULTIFIBER SUBUNIT CABLE**

(71) Applicant: **Corning Optical Communications LLC**, Hickory, NC (US)

(72) Inventors: **William Carl Hurley**, Hickory, NC (US); **Samuel Don Navé**, Newton, NC (US)

(73) Assignee: **Corning Digital Communications LLC**, Hickory, NC (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/750,150**

(22) Filed: **Jun. 25, 2015**

(65) **Prior Publication Data**

US 2015/0293320 A1 Oct. 15, 2015

Related U.S. Application Data

(60) Division of application No. 14/217,952, filed on Mar. 18, 2014, now Pat. No. 9,097,869, which is a continuation of application No. 13/491,122, filed on Jun. 7, 2012, now Pat. No. 8,718,428, which is a continuation of application No. PCT/US2010/058717, filed on Dec. 2, 2010.

(Continued)

(51) **Int. Cl.**
G02B 6/44 (2006.01)
B29C 47/02 (2006.01)

(52) **U.S. Cl.**
CPC **G02B 6/4411** (2013.01); **G02B 6/4401** (2013.01); **G02B 6/443** (2013.01); **G02B 6/4434** (2013.01); **B29C 47/02** (2013.01)

(58) **Field of Classification Search**

CPC G02B 6/441; G02B 6/443; G02B 6/4411; G02B 6/4429; G02B 6/4434; G02B 6/4479; G02B 6/4401

USPC 385/100–114; 264/1.24, 1.28, 1.29; 427/163.2

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,696,541 A 9/1987 Haag et al. 350/96.23
4,906,067 A 3/1990 Mayr et al. 350/96.23
(Continued)

FOREIGN PATENT DOCUMENTS

DE 4408548 A1 12/1995 G02B 6/44
JP 07270651 A 10/1995 G02B 6/44

OTHER PUBLICATIONS

Patent Cooperation Treaty International Search Report, Application No. PCT/US2010/058717, Apr. 18, 2011, 4 pages.

(Continued)

Primary Examiner — Akm Enayet Ullah


Assistant Examiner — Michael Mooney

(74) *Attorney, Agent, or Firm* — William D. Doyle

(57) **ABSTRACT**

A method of making a subunit cable includes providing at least two subunits along a process direction, each subunit comprising a plurality of optical fibers, compressing the subunits so that at least one of the subunits has a cross-section with a minor outside dimension and a major outside dimension, and the ratio of the minor dimension to the major dimension is less than 0.9, and extruding a subunit cable jacket around the subunits, wherein the subunits are compressed within the subunit cable jacket.

5 Claims, 2 Drawing Sheets



Related U.S. Application Data

(60) Provisional application No. 61/286,212, filed on Dec. 14, 2009.

References Cited

U.S. PATENT DOCUMENTS

5,039,195	A *	8/1991	Jenkins	G02B 6/4416 174/70 R
5,982,965	A	11/1999	Cheron et al.	385/100
6,205,277	B1	3/2001	Mathis et al.	385/106
6,389,204	B1	5/2002	Hurley	385/102
6,434,307	B1	8/2002	Church	385/114
7,266,273	B2	9/2007	Bonicelet et al.	385/100
8,290,321	B2	10/2012	Rhyne et al.	
8,559,778	B2	10/2013	Hurley et al.	385/110
8,718,428	B2	5/2014	Hurley et al.	
2002/0126967	A1	9/2002	Panak et al.	385/101
2002/0197030	A1	12/2002	McAlpine et al.	385/103
2003/0156805	A1	8/2003	Shi	385/100
2004/0120665	A1	6/2004	Hurley et al.	385/106
2011/0243514	A1	10/2011	Nave	385/110

OTHER PUBLICATIONS

Patent Cooperation Treaty International Preliminary Report on Patentability, Application No. PCT/US2010/058717, Jun. 19, 2012, 5 pages.
Chinese First Office Action and Search Report CN201080056817.0 Dated May 21, 2014, Chinese Patent Office.
Chinese Second Office Action CN201080056817.0 Dated Jan. 13, 2015, Chinese Patent Office.
Chinese Third Office Action CN201080056817.0 Dated Aug. 3, 2015, Chinese Patent Office.

* cited by examiner




FIG. 1




FIG. 2

1

MULTIFIBER SUBUNIT CABLE

PRIORITY APPLICATION

This Application is a divisional of U.S. application Ser. No. 14/217,952, filed Mar. 18, 2014, which is a continuation of U.S. application Ser. No. 13/491,122, filed Jun. 7, 2012, which is a continuation of International Application No. PCT/US10/58717, filed Dec. 2, 2010, which claims the benefit of priority to U.S. application Ser. No. 61/286,212, filed Dec. 14, 2009, each of which is incorporated by reference herein in its entirety.

TECHNICAL FIELD

The present disclosure relates to optical cables with features that provide easy access to and/or segregation between optical fibers in different groups of optical fibers.

BACKGROUND

Data centers require high density for optical components to compensate for limited space. MTP connectors are used in data centers because they allow for high density, as well as high efficiency. 24 fiber MTP connectors, for example, provide for high density optical connectivity. Typical MTP connectors are designed for a cable of circular profile and an outer diameter of 3.3 mm or less.

During cable access and connectorization of 24 fiber cables, the installer must be able to distinguish fibers **1-12** in the first group of fibers from fibers **13-24** in the second group. There are, however, only twelve colors used in the industry standard color coding scheme. One method to distinguish the two groups fibers is to provide fibers **13-24** with marking indicia, such as dashed lines, to distinguish them from fibers **1-12**. Fiber coloring inks are applied and cured at extremely high speeds, however, and applying dashes or other indicia slows production line speed as well as increasing costs of manufacture.

Another method of distinguishing between fiber groups is to bundle fibers **13-24** in the second group with a thread binder that is wrapped around the bundle of fibers. The binder can untwist, however, when the installer removes the outer jacket of the cable. When the binder untwists, the installer loses traceability between the two groups of 12 colored fibers.

Conventional cables may also be difficult to connect to MTP connectors, or have bend characteristics that render the cables difficult to route through data center space.

SUMMARY

According to one aspect of the present embodiments, a subunit cable comprises a subunit cable jacket and at least two subunits located within the cable jacket. Each subunit comprises a buffer tube and a plurality of optical fibers disposed within the buffer tube, wherein the subunits are compressed in the subunit cable jacket so that at least one of the subunits has a cross-section with a minor outside dimension and a major dimension, and the ratio of the minor outside dimension to the major outside dimension is less than 0.9. In an uncompressed state, the subunits can have a generally circular cross-section, and while in a compressed state, the subunits can have a generally oval cross-section.

According to another aspect of the present embodiments, a method of making a subunit cable comprises providing at least two subunits located within the cable jacket, each

2

subunit comprising a buffer tube and a plurality of optical fibers disposed within the buffer tube, compressing the subunits so that at least one of the subunits has a cross-section with a minor outside dimension and a major outside dimension, and the ratio of the minor dimension to the major dimension is less than 0.9, and extruding a subunit cable jacket around the subunits, wherein the subunits are compressed within the subunit cable jacket. In an uncompressed state, the subunits can have a generally circular cross-section, and while in a compressed state, the subunits can have a generally oval cross-section.

The accompanying drawings are included to provide a further understanding, and are incorporated in and constitute a part of this specification. The drawings illustrate one or more embodiment(s), and together with the description serve to explain principles and operation of the embodiments.

BRIEF DESCRIPTION OF THE FIGURES

The present embodiments are explained in more detail below with reference to figures which show the exemplary embodiments.

FIG. 1 is a cross section of a micromodule cable according to a first embodiment.

FIG. 2 is a cross section of one of the micromodule subunit cables used in the cable of FIG. 1.

DETAILED DESCRIPTION

FIG. 1 is a cross section of a micromodule cable **10** according to a first embodiment. The optical cable **10** comprises a plurality of micromodule subunit cables **20** disposed in an interior **30** of the micromodule cable **10**. The interior **30** of the cable **10** is defined by the cable's outer jacket **50**. The outer jacket **50** can be formed from, for example, a flame-retardant polymer material, and has a thickness **52**. A strength element **56** may be disposed in the interior **30** and contacting the micromodule cable subunits **20**. Each micromodule subunit cable **20** includes a plurality of optical fiber waveguides **60**.

In the illustrated embodiment, the micromodule cable **10** has six micromodule subunit cables **20**, with each micromodule subunit cable **20** including **24** optical fiber waveguides **60**. Other numbers of subunit cables **20** and optical fibers **60** can be employed for various applications, however. The micromodule cable **10** and the micromodule subunit cables **20** have generally circular cross-sections, although other cross-sections may be used. The diameters of the certain circular cross-sections are described to in this specification. It is understood that the illustrated cables and subunit cables will not have perfectly circular cross sections, and that any citations of outside diameters may represent an average diameter of a generally circular cross section.

FIG. 2 is a cross section of one of the exemplary micromodule subunit cables **20** illustrated in FIG. 1 having an outside diameter **22**. Each micromodule subunit cable **20** has a subunit cable jacket **70** of thickness **72** that encloses two subunits **100**. A strain-relief component **104** may be disposed within an interior **106** of the cable jacket **70** and surrounding the subunits **100**. The strain-relief component **104** may be, for example, a layer of longitudinally-extending tensile yarn strands **108** that extend along the length of the micromodule subunit cable **20** for absorbing a tensile loads on the cable.

According to one aspect of the first embodiment, the optical fibers **60** are arranged in two subunits **100** within the

3

subunit cable jacket 70. The subunits 100 each have a subunit cable jacket or buffer tube 114 that encloses a group of optical fibers 60 in the subunit interior 116. The subunits 100 segregate the optical fibers 60 so that they can be easily identified. For example, each of the optical fibers 60 in one subunit 100 may have a corresponding optical fiber 60 in the other subunit 100 that is identical in appearance and/or color. There is no need to provide identifying indicia (e.g. stripes) on the optical fibers 60 of either of the subunits 100. Also according to the disclosed embodiment, there is no need to enclose one fiber group in a thread binder. In one embodiment, each subunit 100 includes twelve optical fibers 60 in a 12 color sequence of blue, orange, green, brown, slate, white, red, black, yellow, violet, rose, and aqua.

According to one aspect of the first embodiment, the subunits 100 can be compressed against each other and against the interior of the subunit cable jacket 70. Under these compressive loads, the cross-sections of the subunits 100 are deformed from what might otherwise be a generally circular cross-section. Compressing the subunits 100 so that they have the generally oval cross-section shown in FIG. 2 allows for a smaller diameter subunit cable 20. The degree of deformation of the subunits 100 can be measured by comparing the largest, or major outside width dimension D1 of a subunit with its smallest, or minor outside width dimension D2. According to one aspect of the present embodiment, the ratio of minor dimension D1 to major dimension D2 (i.e., D1/D2) can be 0.9 or less. According to another aspect, the ratio of minor dimension to major dimension can be 0.8 or less, or even 0.7 or less under higher compressive loads.

The subunits 100 in the subunit cable 20 can be, for example, standard 1.6 mm nominal (before compression) outside diameter modules used in current EDGE™ data center cables available from Corning Cable Systems, Inc. Smaller subunits 100 could be used; it is possible to make subunits 100 with buffer tube 114 wall thicknesses of about 0.12 mm, resulting in subunit nominal (before compression) outside diameter of about 1.45 mm. When incorporating two standard 1.6 mm subunits 100 in a cable 20 with a nominal cable diameter 22 of less than 3.5 mm, the subunits 100 are compressed going through the extrusion tip. To achieve an outside diameter 22 of 3.1 mm, the subunits 100 are each compressed by about 0.3 mm along the axis of the minor dimension D1, resulting in the generally oval shape with a minor dimension D1 of about 1.3 mm and a major dimension D2 of about 1.9 mm, with the subunit cable jacket thickness 72 of 0.25 mm. The subunits 100 and strength members 104 are processed longitudinally without stranding. However, it is possible to strand the subunits 100 and strength members 104.

A 24 fiber subunit cable 20 can have a nominal diameter 22 of about, for example, 3.3 mm or less, and can be less than or equal to 3.1 mm. Smaller cable diameters are desirable because they reduce congestion on equipment racks in data center applications. Typical MTP connectors are designed for a cable of circular profile and an outer diameter of 3.3 mm or less, so the small cross-sections possible with the present embodiments are suitable for conventional connectorization. The dual subunit 100 design segregates the fibers 60 which makes it faster and easier for installers to identify the separate groups of 12 fibers and to keep them segregated during cable access and connectorization. With this design there is no entanglement between the fibers and the strain-relief component strands 108.

Subunit cables 20 according to the present embodiments can also have exceptional skew performance. The fibers 60

4

in each subunit 100 can meet the 3.75 ps/m requirement for high data rate applications. Also since the subunit 100 are compressed together in the tip during cabling, they act together as one unit so the skew between the 12 optical fibers 60 in each subunit, as well as between all 24 fibers, is exceptionally low.

EXAMPLE 1

A micromodule subunit cable 20 as shown in FIG. 2 includes two subunits 100 of twelve optical fiber waveguides 60. Each subunit 100 includes fibers in the 12-color sequence: blue, orange, green, brown, slate, white, red, black, yellow, violet, rose, and aqua. For each fiber 60 in one subunit 100, there is a corresponding fiber 60 in the other subunit 100 of identical appearance, including color or external pattern or identifying indicia, if any. In this example, the fibers 60 are of solid color with no identifying indicia. The cable diameter 22 is about 3.1 mm, and the thickness 72 of the jacket 70 is about 0.25 mm. Before integration into the subunit cable 20, the outside diameter of the buffer tube 114 is about 1.6 mm, and the thickness of the buffer tube 114 is about 0.20 mm. The fibers 60 are bare, non-tight buffered fibers of about 0.250 mm diameter and are sold as ClearCurve® multimode fiber available from Corning Incorporated. The jacket 70 and the buffer tube 114 are made from a flame-retardant PVC available from AlphaGary Corporation. The strain-relief component 104 comprises KEVLAR® aramid tensile yarns disposed around the subunits 100. From 2-8 strands of tensile yarn are used. The subunit cable 20 is connectorized to MTP connectors.

The present cable embodiments may utilize tensile yarns as tension relief elements that provide tensile strength to the cables. A preferred material for the tensile yarns is aramid (e.g., KEVLAR®), but other tensile strength materials could be used. For example, high molecular weight polyethylenes such as SPECTRA® fiber and DYNEEMA® fiber, Teijin Twaron® aramids, fiberglass, etc. may also be used. The yarns may be stranded to improve cable performance.

The components of the cable 10, such as the micromodule cables 20, can be constructed of selected materials of selected thicknesses such that the cable 10 achieves plenum burn ratings according to desired specifications. The micromodule subunit cables 20 can also be constructed so that they are relatively robust, such that they are suitable for field use, while also providing a desired degree of accessibility. For example, the micromodule cables 20 according to the present embodiment can be constructed with thicker cable jackets 70 which provide sufficient protection for the fibers such that the subunit cables 20 may be used as furcation legs.

The outer jacket 50, the subunit cable jackets 70, and the buffer tubes 114 can be formed from fire-retardant materials to obtain a desired plenum burn rating. For example, highly-filled PVCs of a specified thicknesses can be used to form these components. Other suitable materials include PVDF, CPE, and low smoke zero halogen (LSZH) materials such as flame retardant polyethylene (FRPE). One plenum burn standard is the National Fire Protection Standards (NFPA) 262 burn test. NFPA 262 prescribes the methodology to measure flame travel distance and optical density of smoke for insulated, jacketed, or both, electrical wires and cables and optical fiber cables that are to be installed in plenums and other spaces used to transport environmental air without being enclosed in raceways. Other materials include nylons, polyesters, PE, PP, and fluoropolymers such as FEP, PTFE, ETFE, etc. could be used dependent on burn requirements.

5

In one particular set of parameters, cables according to the present embodiments may contain from four to twelve optical fibers within each subunit **20**. The dimensions of the subunits **20** may be adjusted based on the number of fibers within the module. The fibers **60** may be loosely disposed within the subunits **20** in an essentially parallel array. The fibers **60** may be coated with a thin film of powder, such as chalk or talc, which forms a separation layer that prevents the fibers from sticking to the molten sheath material during extrusion. The cable **10** may be further encased in an interlocking armor for enhanced crush resistance.

The subunit cable **20** can be manufactured by first producing subunits **100**. The subunits **100** can be manufactured by providing optical fibers **60** and extruding the buffer tubes **114** around the fibers **60**. The subunits **100** are then provided along a process direction, and the cable jacket **70** is extruded over subunits **100**. The subunits **100** are compressed as the jacket **70** is extruded. If present, the aramid fibers **108** of the strength component **104** are also provided within the cable jacket **70** during extrusion of the cable jacket.

The subunit cables **20** could be made in higher fiber counts by compressing more subunits **100** together. For example, a 48-fiber subunit cable could be made by compressing four subunits **100** together and adding aramid and jacket over the modules. The 48f cable could have an OD of about 5 mm or less.

The number of fibers in the subunits **100** can be adjusted to meet specific transmission schemes. For example, a 40 Gb/s parallel optics transmission system could use four fibers operating a 10 Gb/s for transmission and another four fibers for receiving. Thus subunits **100** can include four fibers each.

According to one aspect of the present embodiments, the cables may have nonpreferential bend characteristics, of relatively small diameter, and utilize non-tight buffered fiber groupings. These features allow the cables to be easily attached to MTP connectors, and also allow for easy routing of the fibers once in the MTP body.

Many modifications and other embodiments of the present invention, within the scope of the claims will be apparent to those skilled in the art. For instance, the concepts of the

6

present invention can be used with any suitable fiber optic cable design and/or method of manufacture. For instance, the embodiments shown can include other suitable cable components such as an armor layer, coupling elements, different cross-sectional shapes, or the like.

What is claimed is:

1. A method of making a subunit cable, comprising:
 - providing at least two subunits along a process direction, each subunit comprising a plurality of optical fibers;
 - compressing the subunits so that at least one of the subunits has a cross-section with a minor outside dimension and a major outside dimension, and the ratio of the minor dimension to the major dimension is less than 0.9; and
 - extruding a subunit cable jacket around the subunits, wherein the subunits are compressed within the subunit cable jacket,
- wherein the at least two subunits comprises a first subunit and a second subunit, wherein for each optical fiber in the first subunit, there is a corresponding optical fiber in the second subunit of identical color and appearance, wherein the first subunit comprises twelve optical fibers and the second subunit comprises twelve optical fibers.
2. The method of claim 1, wherein the ratio of minor outside dimension to major outside dimension is less than 0.8.
3. The method of claim 1, further comprising paying off a tensile yarn strain-relief component, wherein the subunit cable jacket is extruded around the strain-relief component, and wherein the tensile yarns contact the subunits and the subunit cable jacket.
4. The method of claim 1, wherein the first subunit comprises twelve optical fibers and the second subunit comprises twelve optical fibers, and wherein a nominal outside diameter of the cable is about 3.5 mm or less.
5. The method of claim 1, wherein the compressed subunits have a generally oval cross section.

* * * * *