



US009691424B2

(12) **United States Patent**
Duda et al.

(10) **Patent No.:** **US 9,691,424 B2**
(45) **Date of Patent:** **Jun. 27, 2017**

(54) **BOLOMETER FOR INTERNAL LASER POWER MONITORING IN HEAT-ASSISTED MAGNETIC RECORDING DEVICE**

(71) Applicant: **Seagate Technology LLC**, Cupertino, CA (US)

(72) Inventors: **John Charles Duda**, Bloomington, MN (US); **Ruoxi Yang**, St. Louis Park, MN (US); **James Gary Wessel**, Savage, MN (US)

(73) Assignee: **SEAGATE TECHNOLOGY LLC**, Cupertino, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/051,053**

(22) Filed: **Feb. 23, 2016**

(65) **Prior Publication Data**

US 2016/0284372 A1 Sep. 29, 2016

Related U.S. Application Data

(60) Provisional application No. 62/137,396, filed on Mar. 24, 2015.

(51) **Int. Cl.**

G11B 11/00 (2006.01)

G11B 5/60 (2006.01)

G11B 5/31 (2006.01)

G11B 5/00 (2006.01)

G11B 11/105 (2006.01)

G11B 11/12 (2006.01)

G11B 11/14 (2006.01)

(52) **U.S. Cl.**

CPC **G11B 5/6088** (2013.01); **G11B 5/314** (2013.01); **G11B 11/10532** (2013.01); **G11B 11/10543** (2013.01); **G11B 11/10547**

(2013.01); **G11B 11/12** (2013.01); **G11B 11/14** (2013.01); **G11B 2005/0021** (2013.01)

(58) **Field of Classification Search**

CPC **G11B 2005/0021**; **G11B 5/6088**; **G11B 11/10543**; **G11B 11/10545**; **G11B 11/10547**; **G11B 11/12**; **G11B 11/14**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

8,824,085 B2 9/2014 Wilson et al.
8,879,189 B2 11/2014 Miyamoto et al.
9,042,210 B2 5/2015 Macken et al.

(Continued)

OTHER PUBLICATIONS

File History for U.S. Appl. No. 15/007,772.


Primary Examiner — Tan X Dinh

(74) *Attorney, Agent, or Firm* — Hollingsworth Davis, LLC

(57) **ABSTRACT**

An apparatus comprises a slider having an air-bearing surface (ABS), a write pole at or near the ABS, and a reader at or near the ABS and connected to a pair of reader bond pads of the slider. A near-field transducer (NFT) is formed on the slider at or near the ABS, and an optical waveguide is formed in the slider and configured to receive light from a laser source. A sensor is situated proximal of the write pole at a location within the slider that receives at least some of the light communicated along the waveguide. The sensor may be electrically coupled to the reader bond pads in parallel with the reader, and configured to generate a signal indicative of output optical power of the laser source.

23 Claims, 10 Drawing Sheets





(56) **References Cited**

U.S. PATENT DOCUMENTS

9,153,272	B1 *	10/2015	Rausch	G11B 7/1267 369/13.33
9,536,555	B1 *	1/2017	Duda	G11B 5/6076 369/13.33
9,558,774	B1 *	1/2017	Macken	G11B 5/607 369/13.33
2011/0299367	A1	12/2011	Naniwa et al.	
2012/0051196	A1	3/2012	Grobis et al.	
2014/0119164	A1 *	5/2014	Wilson	G11B 5/314 369/13.32
2014/0269238	A1	9/2014	Kautzky et al.	
2015/0109892	A1	4/2015	Contreras et al.	
2015/0279430	A1 *	10/2015	Trantham	G11B 5/314 369/13.26
2015/0332725	A1 *	11/2015	Rausch	G11B 5/012 369/13.26
2016/0104514	A1 *	4/2016	Burnett	G11B 5/6088 369/13.33
2017/0032810	A1 *	2/2017	Macken	G11B 5/6005 369/13.33

* cited by examiner








FIGURE 3




FIGURE 4




FIGURE 5




FIGURE 6

FIGURE 7




FIGURE 8





FIGURE 9






FIGURE 10





FIGURE 11

FIGURE 12



BOLOMETER FOR INTERNAL LASER POWER MONITORING IN HEAT-ASSISTED MAGNETIC RECORDING DEVICE

RELATED PATENT DOCUMENTS

This application claims the benefit of Provisional Patent Application Ser. No. 62/137,396 filed on Mar. 24, 2015, to which priority is claimed pursuant to 35 U.S.C. §119(e), and which is incorporated herein by reference in its entirety.

SUMMARY

Embodiments are directed to an apparatus comprising a slider having an upper surface, a lower air-bearing surface (ABS), and an internal body extending between the upper and lower surfaces. A write pole is situated at or near the ABS, and a reader is situated at or near the ABS and connected to a pair of reader bond pads of the slider. The reader bond pads are configured to electrically bias the reader during read operations. A near-field transducer (NFT) is formed on the slider at or near the ABS, and an optical waveguide is formed in the slider and extends from the upper surface of the slider through the internal body of the slider and to the NFT. The waveguide is configured to receive light from a laser source. A bolometer is situated proximal of the write pole at a location within the internal body of the slider that receives at least some of the light communicated along the waveguide. The bolometer is electrically coupled to bond pads, such as the reader bond pads, for biasing the bolometer, and configured to generate a signal indicative of output optical power of the laser source during write operations.

Other embodiments are directed to an apparatus comprising a slider having an air-bearing surface (ABS), a write pole at or near the ABS, and a reader at or near the ABS and connected to a pair of reader bond pads of the slider. A near-field transducer (NFT) is formed on the slider at or near the ABS, and an optical waveguide is formed in the slider and configured to receive light from a laser source. A sensor is situated proximal of the write pole at a location within the slider that receives at least some of the light communicated along the waveguide. The sensor is electrically coupled to the reader bond pads in parallel with the reader, and configured to generate a signal indicative of output optical power of the laser source.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a slider in which the various embodiments disclosed herein may be implemented;

FIG. 2 is a detailed partial cross-sectional view of a slider which incorporates an internal bolometric sensor in accordance with various embodiments;

FIG. 3 is a detailed partial cross-sectional view of a slider which incorporates an internal bolometric sensor in accordance with some embodiments;

FIG. 4 is a detailed partial cross-sectional view of a slider which incorporates an internal bolometric sensor in accordance with other embodiments;

FIG. 5 is a detailed partial cross-sectional view of a slider which incorporates an internal bolometric sensor in accordance with further embodiments;

FIG. 6 shows various details of a bolometric sensor incorporated within the internal body of a slider in accordance with embodiments of the disclosure;

FIG. 7 is a graph showing the temperature response of a bolometric sensor as a function of core-to-sensor spacing, CSS, in accordance with embodiments of the disclosure;

FIG. 8 is a graph showing the response of a bolometric sensor in terms of output sensor signal as a function of core-to-sensor spacing, CSS, in accordance with embodiments of the disclosure;

FIG. 9 is a graph that shows the effect presence of the bolometric sensor has on waveguide mode profile in accordance with embodiments of the disclosure;

FIG. 10 is a circuit that includes a reader and a bias shunt coupled in parallel to a pair of electrical bond pads of a slider in accordance with embodiments of the disclosure;

FIG. 11 is a circuit that includes a reader and a bolometer coupled in parallel to a pair of electrical bond pads of a slider in accordance with embodiments of the disclosure; and

FIG. 12 is a diagram of an output optical power monitor for a heat-assisted magnetic recording slider in accordance with various embodiments.

The figures are not necessarily to scale. Like numbers used in the figures refer to like components. However, it will be understood that the use of a number to refer to a component in a given figure is not intended to limit the component in another figure labeled with the same number.

DETAILED DESCRIPTION

The present disclosure generally relates to laser power monitoring in data storage devices that employ heat-assisted magnetic recording (HAMR), also referred to as energy-assisted magnetic recording (EAMR), thermally-assisted magnetic recording (TAMR), and thermally-assisted recording (TAR). This technology uses a laser source and a near-field transducer (NFT) to heat a small spot on a magnetic disk during recording. The heat lowers magnetic coercivity at the spot, allowing a write transducer to change the orientation of a magnetic domain at the spot. Due to the relatively high coercivity of the medium after cooling, the data is less susceptible to paramagnetic effects that can lead to data errors.

A HAMR drive generally uses a laser diode to heat the recording medium to aid in the recording process. The laser diode generates heat and is also heated by other components (writer, reader, heater elements) in the magnetic slider. During write operation, for example, laser diode heating can vary the junction temperature of the laser diode, causing a shift in laser emission wavelength, leading to a change of optical feedback from optical path in slider to the cavity of the laser diode, a phenomenon that is known to lead to mode hopping and/or power instability of the laser diode. Mode hopping is particularly problematic in the context of single-frequency lasers. Under some external influences, a single-frequency laser may operate on one resonator mode (e.g., produce energy with a first wavelength) for some time, but then suddenly switch to another mode (produce energy, often with different magnitude, with a second wavelength) performing “mode hopping.” Temperature variation is known to cause mode hopping in laser diodes. Mode hopping is problematic for HAMR applications, as mode hopping leads to laser output power jumping and magnetic transition shifting from one block of data to another. Large transition shifts in a block of data may not be recoverable by channel decoding, resulting in error bits.

Monitoring of laser power is important to ensure proper operation of the laser diode and to avoid instabilities such as mode hopping. Conventional laser power monitoring involves use of an external photodiode situated on a sub-

mount that also supports the laser diode. The photodiode senses optical power output of the laser diode, and can be used to determine if the laser performance is sufficiently stable to ensure adequate writing performance. However, future integrated HAMR recording transducers will not be able to include an external photodiode due to reduced submount dimensions. For HAMR hard drives, it is critical to detect small fluctuations in laser output optical power delivered to the NFT while minimizing any light delivery losses. Typically, an electrical element such as an internal laser power monitor (e.g., photodiode) would require extra, dedicated electrical bond pads. Since additional bond pads add cost and complexity to the head gimbal assembly, it is desirable to provide for sensing of laser output optical power without the need for additional bond pads.

Embodiments of the disclosure are directed to a sensor arrangement internal to the slider that can be used to facilitate monitoring of output optical power of the laser diode. Embodiments of the disclosure are directed to a sensor that can be situated in the vicinity of the light path of the slider yet have substantially no or only negligible impact on waveguide efficiency and/or performance of the NFT. Embodiments are directed to a sensor that shares electrical bond pads of an existing slider component, thereby obviating the need for additional bond pads to bias the sensor.

According to various embodiments, a bolometric sensor can be situated adjacent the core of an optical waveguide formed in the slider so that light produced by the laser diode impinges on or is harvested by the bolometric sensor. The bolometric sensor can be situated in or near the optical light path of the slider so that it absorbs or harvests light communicated along the waveguide, while minimally or negligibly impacting light transmission (e.g., minimal or negligible effect on waveguide efficiency and/or the mode profile along the light delivery path). For example, the bolometric sensor can be situated within the internal body of the slider proximate the core of the waveguide, such as within the cladding of the waveguide. In various embodiments, the bolometric sensor comprises a thin metallic element, such as a wire, with a high thermal coefficient of resistance (TCR).

When a small bias current is applied across the bolometric sensor, any change in bolometric sensor temperature will create a corresponding change in measured voltage. As a result, the bolometric sensor can be used to monitor fluctuations in laser output optical power that cause fluctuations in absorption and temperature in the bolometric sensor. In general, a bolometer-based internal power monitor according to embodiments of the disclosure does not appreciably decrease light path efficiency yet still absorbs enough light to create a sufficiently large signal for detection. Moreover, embodiments of a bolometric sensor do not require any additional bond pads and would ideally be wired in series or parallel with an existing sensor of the recording transducer.

An embodiment of a HAMR slider **100** is illustrated in FIG. **1**. As shown, the HAMR slider **100** includes a light source (e.g., a laser diode) **102** located proximate a trailing edge surface **104** of the slider **100**. An optical wave (e.g., a laser beam) generated by the light source **102** is delivered to a mode converter **106**, such as a higher order mode converter (HOMC), and from the mode converter **106** to an NFT **112** (see FIG. **2**) via an optical waveguide **110**. Generally, the mode converter **106** may be utilized with an external phase-shifter (not shown) that receives the mode converted light and shifts phase appropriate for exciting the NFT **112**. In this configuration, the mode converter **106** can be made compact and introduce negligible optical losses. The optical wave exiting the mode converter **106** is directed onto the NFT **112**

located proximate a read/write head **113**. The NFT **112** is aligned with a plane of an air bearing surface (ABS) **114** of the slider **100**, and one edge of the read/write head **113** is on the ABS **114**. The air bearing surface **114** faces, and is held proximate to, a surface **116** of a magnetic medium **118** (see FIG. **2**) during device operation. In the following, the ABS **114** is also referred to as a media-facing surface **114**.

The light source **102** in this representative example may be an integral, edge firing device, although it will be appreciated that any source of electromagnetic energy may be used. For example, a surface emitting laser (SEL), instead of an edge firing laser, may be used as the source **102**. A light source may also be mounted alternatively to other surfaces of the slider **100**, such as the trailing edge surface **104**. While the representative embodiment of FIG. **1** shows the waveguide **110** integrated with the slider **100**, any type of light delivery configuration may be used. For example, in a free-space light delivery configuration, the light source **102** may be external to the slider **100**, and coupled to the mode converter **106** by way of optic fibers and/or waveguides. For instance, the slider **100** in one such arrangement may include a grating coupler into which the light source **102** is coupled and the electromagnetic energy may be delivered to the mode converter **106** using the slider-integrated waveguide **110**.

A HAMR device utilizes the types of optical devices described above to heat a magnetic recording media (e.g., hard disk) in order to overcome superparamagnetic effects that limit the areal data density of typical magnetic media. When writing with a HAMR device, the electromagnetic energy (e.g., laser or light) is concentrated onto a small hotspot over the track of the magnetic medium **118** where writing takes place, as shown in FIG. **2**. The light from the source **102** propagates to the NFT **112**, e.g., either directly from the source **102** or through the mode converter **106** or by way of a focusing element. Other optical elements, such as couplers, mirrors, prisms, etc., may also be formed integral to the slider. FIG. **2**, for example, shows a coupler **107** adjacent the light source **102**, which is configured to couple light produced from the light source **102** to the waveguide **110**. The optical elements used in HAMR recording heads are generally referred to as integrated optics devices.

The field of integrated optics relates to the construction of optics devices on substrates, sometimes in combination with electronic components, to produce functional systems or subsystems. For example, an integrated optics device may transfer light between components via rectangular dielectric slab or channel waveguides that are built up on a substrate using layer deposition techniques. These waveguides may be formed as a layer of materials with appropriate relative refractive indices so that light propagates through the waveguide in a similar fashion as through an optic fiber.

As a result of what is known as the diffraction limit, optical components cannot be used to focus light to a dimension that is less than about half the wavelength of the light. The lasers used in some HAMR designs produce light with wavelengths on the order of 700-1550 nm, yet the desired hot spot is on the order of 50 nm or less. Thus the desired hot spot size is well below half the wavelength of the light. Optical focusers cannot be used to obtain the desired hot spot size, being diffraction limited at this scale. As a result, the NFT **112** is employed to create a hotspot on the media.

The NFT **112** is a near-field optics device configured to generate local surface plasmon resonance at a designated (e.g., design) wavelength. The NFT **112** is generally formed

5

from a thin film of plasmonic material (e.g., gold, silver, copper) on a substrate. In a HAMR slider **100**, the NFT **112** is positioned proximate the write pole **126** of the read/write head **113**. The NFT **112** is aligned with the plane of the ABS **114** parallel to the read/write surface **116** of the magnetic medium **118**. A waveguide **110** and/or the mode converter **106** and/or other optical element directs electromagnetic energy (e.g., light) onto the NFT **112**.

The NFT **112** achieves surface plasmon resonance in response to the incident electromagnetic energy. The plasmons generated by this resonance are emitted from the NFT **112** towards the magnetic medium **118** where they are absorbed to create a hotspot. At resonance, a high electric field surrounds the NFT **112** due to the collective oscillations of electrons at the metal surface (e.g., substrate) of the magnetic medium **118**. At least a portion of the electric field surrounding the NFT **112** tunnels into, and gets absorbed by, the magnetic medium **118**, thereby raising the temperature of a spot on the medium **118** as data is being recorded.

FIG. 2 shows a detailed partial cross-sectional view of an embodiment of the HAMR slider **100** in accordance with various embodiments. As illustrated, the NFT **112** is positioned proximate the ABS (or media-facing surface) **114** and a magnetic write pole **126**. The ABS **114** is shown positioned proximate the surface **116** of the magnetic recording medium **118** during device operation. In the orientation illustrated in FIG. 2, the media-facing surface (or ABS) **114** is arranged parallel to the x-z plane. Electromagnetic energy (e.g., laser) **120** from the light source (e.g., laser diode) **102** is delivered to the mode converter **106** via the coupler **107** and propagates along the waveguide **110** in the y-direction. Optical wave **122** exits the mode converter **106** and is delivered to the NFT **112** along waveguide **124** in the y-direction. The NFT **112** generates surface plasmon enhanced near-field electromagnetic energy proximate the surface **116** of the medium **118**, and exits the NFT **112** in the y-direction. This may result in a highly localized hot spot (not shown) on the media surface **116** when in close proximity to ABS **114** of the slider **100**. The write pole **126** generates a magnetic field (e.g., in a y- or perpendicular direction) used for changing the magnetic orientation of the hotspot on the surface **116** during writing.

The slider **100** shown in FIG. 2 incorporates a sensor **202** situated in the vicinity of the light path (e.g., the waveguide **110**) and proximal of the NFT **112** in accordance with various embodiments. According to some embodiments, the sensor **202** comprises an optical-to-thermal transducer configured to respond to fluctuations in output optical power of the laser **102**. The sensor **202** may be implemented in the form of a bolometer or bolometric sensor **202**, for example. In some embodiments, the sensor **202** comprises a thin metallic wire placed across the light path (e.g., the waveguide **110**) within the internal body of the slider at a location between the coupler **107** and the NFT **112**. A small fraction of the output optical power of the laser **102** transmitted via the light path is absorbed by the wire and converted into thermal power, thereby increasing wire temperature. Fluctuations in output optical power of the laser **102** correlate to fluctuations in thermal power and temperature of the sensor **202**. These fluctuations in temperature can be detected by circuitry configured to monitor the resistance fluctuations in the wire by using a small bias current and a high thermal coefficient of resistance material. Heating by direct absorption of light greatly decreases the response time and increases bandwidth of the output optical power monitor. The wire can be placed in light path or adjacent to optics to harvest scattered light.

6

According to the embodiment shown in FIG. 2, a bolometric sensor **202** is situated in the vicinity of the light path (e.g., the waveguide **110**) and positioned between the mode converter **106** and the NFT **112**. In the embodiment shown in FIG. 2, the bolometric sensor **202** can be positioned away from the NFT **112** or the mode converter **106** in the y-direction by a distance as small as about 2 μm according to some embodiments. In other embodiments this separation distance can range between about 2 μm and 10 μm . In further embodiments, this separation can be a distance of about 10 μm or greater. For example, the bolometric sensor **202** can be situated between the NFT **112** and the mode converter **106**, such that the bolometric sensor **202** is spaced away from the NFT **112** by a distance between about 2 μm and 50 μm (e.g., between about 2 μm and 30 μm). In general, the data in FIG. 9 suggests that the presence of the bolometer sensor **202** does not disturb the mode profile in the waveguide **110** at distances further than about 2 μm from the bolometer sensor **202**. Thus, the minimum separation between the bolometer sensor **202** and any other component of the light deliver system (i.e., input coupler **107**, mode converter **106**, or NFT **112**) is about 2 μm .

As shown in FIG. 2, the bolometric sensor **202** has a longitudinal axis that is oriented transverse to the longitudinal axis of the waveguide **110**. More particularly, the bolometric sensor **202** shown in FIG. 2 has a longitudinal axis that is oriented substantially normal to the longitudinal axis of the waveguide **110**. In some embodiments, the bolometric sensor **202** is spaced away from a core of the waveguide **110** and positioned above the waveguide **110** in the x-direction. In other embodiments, the bolometric sensor **202** is spaced away from a core of the waveguide **110** and positioned below the waveguide **110** in the x-direction. The bolometric sensor **202** may also be positioned to scavenge otherwise wasted optical energy, although the sensor response may be more limited than when in positions adjacent to the waveguide.

FIG. 3 shows a variation of the embodiment shown in FIG. 2. As in the case of the embodiment of FIG. 2, the bolometric sensor **202** of FIG. 3 is situated in the vicinity of the light path (e.g., the waveguide **110**) and positioned between the mode converter **106** and the NFT **112**. Rather than being oriented normal to the waveguide **110**, the longitudinal axis of the bolometric sensor **202** of FIG. 3 is oriented diagonally with respect to the longitudinal axis of the waveguide **110**. Orienting the bolometric sensor **202** diagonally with respect to the waveguide **110** serves to expose more surface area of the sensor **202** to optical energy transmitted along the waveguide **110** than a perpendicular orientation of the sensor **202**. In the embodiment shown in FIG. 3, the bolometric sensor **202** can be spaced away from the NFT **112** by a distance between about 2 μm and 50 μm (e.g., between about 2 μm and 30 μm).

According to the embodiment shown in FIG. 4, a bolometric sensor **202** is situated in the vicinity of the light path (e.g., the waveguide **110**) and positioned between the coupler **107** and the mode converter **106**. In the embodiment shown in FIG. 4, the separation distance in the y-direction between the bolometric sensor **202** and either the mode converter **106** or the input coupler **107** can be as small as 2 μm , a distance between about 2 μm and 10 μm , or a distance of about 10 μm or greater. It is noted that the mode converter **106** can be spaced away from the NFT **112** by a distance between about 30 μm and 50 μm , and the coupler **107** can be spaced away from the NFT **112** by a distance between about 60 μm and 80 μm . As such, the bolometric sensor **202** can be situated between the mode converter **106** and the

coupler **107** and spaced away from the NFT **112** in the y-direction by a distance of between about 30 μm and 80 μm (e.g., between about 50 and 70 μm).

The bolometric sensor **202** shown in FIG. 4 has a longitudinal axis oriented transverse to the longitudinal axis of the waveguide **110**. In particular, the bolometric sensor **202** shown in FIG. 4 has a longitudinal axis oriented substantially normal to the longitudinal axis of the waveguide **110**. In some embodiments, the bolometric sensor **202** can be spaced away from a core of the waveguide **110** and positioned above the waveguide **110** in the x-direction. In other embodiments, the bolometric sensor **202** can be spaced away from a core of the waveguide **110** and positioned below the waveguide **110** in the x-direction. FIG. 5 shows a variation of the embodiment shown in FIG. 4. The bolometric sensor **202** of FIG. 5 is situated in the vicinity of the light path (e.g., the waveguide **110**) and positioned between the coupler **107** and the mode convertor **106**. The longitudinal axis of the bolometric sensor **202** of FIG. 5 is oriented diagonally with respect to the longitudinal axis of the waveguide **110**.

FIG. 6 shows various details of a bolometric sensor **202** incorporated within the internal body of a slider in accordance with embodiments of the disclosure. FIG. 6 shows the bolometric sensor **202** spaced apart from the waveguide **110** (e.g., a channel waveguide) by a core-to-sensor spacing, CSS. The bolometric sensor **202** is positioned at a distance CSS away from a core of the waveguide **110** so as to absorb enough optical power to generate sufficient bolometric response yet otherwise minimally (e.g., negligibly) disturb the transmission of optical energy along the waveguide **110**. In some embodiments, the bolometric sensor **202** can be formed in the cladding of the waveguide **110**, for example. Modeling of one efficacious embodiment included a waveguide core having an index of refraction, n , of 2.06, waveguide cladding having an index of refraction, n , of 1.46, and a sensor wire **202** having an index of refraction, n , of 3.47. The core and cladding had an extinction coefficient, k , of 0, and the wire had an extinction coefficient, k , of 2.8. It is understood that these and other parameter values are provided for non-limiting illustrative purposes.

According to various embodiments, the bolometric sensor **202** can be spaced apart from the waveguide **110** by a core-to-sensor spacing, CSS, of between about 50 nm to 300 nm. In some embodiments, the bolometric sensor **202** can be spaced apart from the waveguide **110** by a core-to-sensor spacing, CSS, of between about 75 nm to 150 nm. In other embodiments, the bolometric sensor **202** can be spaced apart from the waveguide **110** by a core-to-sensor spacing, CSS, of about 100 nm. Experimentation has demonstrated that waveguide efficiency (P_{out}/P_{in}) drops as CSS approaches zero and, for channel waveguides, degrades with increasing stripe width. The bolometric sensor **202** can be implemented to include a wire having a width, w_{wire} , of between about 50 and 300 nm, a height, h_{wire} , of between about 25 and 100 nm, and a length, l_{wire} , of between about 1 and 5 μm . Generally, a TCR value of $1.5 \times 10^{-3} \text{ } ^\circ\text{C}^{-1}$ or higher is suitable, though operating conditions can be changed to accommodate a lower TCR value. That is, the measurable signal is proportional to the bias current times the TCR times the change in temperature times the intrinsic resistance of the sensor (i.e., $I \cdot \text{TCR} \cdot dT \cdot R_0$), such that a slightly higher bias current can be applied or a higher intrinsic resistance can be designed to compensate for a lower TCR.

FIG. 7 is a graph showing the temperature response of a bolometric sensor **202** as a function of core-to-sensor spacing, CSS. The x-axis of the graph shows CSS values

between 0 and about 350 nm. The y-axis of the graph shows sensor temperature ($\Delta T_{avg}/P_{in}$ (K/mW)) values between 0 and 80. The data for three different wire configurations (1:1, 2:1, and 1:2) are plotted. One wire configuration (plotted as circles) represents a wire having a ratio of width to height of 1:1 (e.g., 50 nm $\times$ 50 nm). A second wire configuration (plotted as squares) represents a wire having a ratio of width to height of 2:1 (e.g., 100 nm $\times$ 50 nm). A third wire configuration (plotted as diamonds) represents a wire having a ratio of width to height of 1:2 (e.g., 50 nm $\times$ 100 nm). FIG. 8 is a graph showing the response of a bolometric sensor **202** in terms of output sensor signal as a function of core-to-sensor spacing, CSS. The x-axis of the graph shows CSS values between 0 and about 350 nm. The y-axis of the graph shows sensor signal magnitude ($\Delta V/P_{in}$ (mV/mW/mA)) values between 0 and 0.12. The data for the three different wire configurations (1:1, 2:1, and 1:2) described above are plotted in FIG. 7.

It can be seen from the data of FIG. 7 that the temperature response of the sensor drops with increasing CSS. It is noted that ΔT changes approximately linearly with output optical power fluctuation. It can be seen from the data of FIG. 8 that the output signal magnitude of the sensor also drops with increasing CSS. The data reflected in FIGS. 7 and 8 was generated from computer modeling using a 1 mA bias current through the sensor wire and 20 mW of laser light transmitted along the waveguide, which yielded a signal of between 0.5 to 2 mV when the CSS ranged between 0 and 100 nm.

FIG. 9 is a graph that shows the effect presence of the bolometric sensor has on the waveguide mode profile. The y-axis shows values of normalized mode intensity between 0 and 1. Although a fundamental TE mode is represented in FIG. 9, embodiments of the disclosure are extendable to a higher order mode. The x-axis shows values of position upstream (i.e., -2 μm) and downstream (i.e., +2 μm) of the bolometric sensor within the waveguide in the y-direction (represented in terms of the y-coordinate (μm)). The data plotted in FIG. 9 demonstrates that the waveguide mode is somewhat disturbed by the presence of the bolometric sensor positioned above the waveguide, but recovers downstream within about 2 microns from the sensor. Recovery of the waveguide mode also occurs within about 2 microns from the sensor for a channel waveguide mode of TE(0,0). The degree of mode profile disturbance indicated in FIG. 9 does not have an appreciable impact (i.e. only a negligible effect) on waveguide efficiency (P_{out}/P_{in}).

Generally, incorporating an electrical element such as a bolometer into a slider would require extra, dedicated electrical pads to bias the element. Since additional bond pads add significant cost and complexity to a head gimbal assembly, embodiments of the disclosure are directed to a bolometric sensor that is electrically connected in series or parallel with another electrical component of the slider. FIG. 10 is a circuit **1000** that includes a reader **1002** coupled to a pair of electrical bond pads (R+ and R-) of the slider. The reader **1002** is also coupled to ground via resistances R1 and R2, typically for purposes of electrostatic discharge (ESD) protection. In some slider implementations, a bias shunt **1004** is coupled in parallel with the reader **1002** as shown in FIG. 10 and typically has a resistance on the order of 1 K Ω .

According to various embodiments of a bolometric sensor incorporated within the interior body of a slider, the bias shunt **1004** is replaced by a bolometer **1102**, as shown in FIG. 11. In the circuit **1100** of FIG. 11, the bolometer **1102** serves as both an optical-to-thermal transducer and a bias shunt during read operations. Because reading and writing

9

data are operations that do not occur concurrently in a disk drive, the bolometer 1102 and the reader 1002 can share the same bond pads without interfering with the normal operation of either component. Since the laser is operated only during write operations, the bolometer 1102 need only operate during write operations and need not be operative during read operations. It is noted that the preamp and disk drive firmware need to be modified in order to accommodate time multiplexing of bolometer and reader signals. It is also noted that the bolometer 1102 need not replace an existing component of the slider, such as the bias shunt 1004 shown in FIG. 10, but can be incorporated as an additional slider component coupled in parallel with the reader 1002 as shown in FIG. 11. It is understood that, in some embodiments, the bolometer 1102 can be biased by dedicated bond pads.

FIG. 12 is a diagram of an output optical power monitor for a HAMR slider in accordance with various embodiments. The apparatus 1200 shown in FIG. 12 includes the circuit 1100 shown in FIG. 11, with a bolometer 1102 coupled in parallel and sharing bond pads with a reader 1002. The bolometer 1102 is coupled to an optical power monitor controller system 1202 configured to detect fluctuations in the sensor signal produced by the bolometer 1102, such fluctuations corresponding to fluctuations in output optical power of the laser. The optical power monitor controller system 1202 is coupled to a power supply 1204 which supplies power to a laser diode 102. The power supply 1204 is configured to adjust the power supplied to the laser diode 102 in response to signals received from the optical power monitor controller system 1202. Monitoring for fluctuations in output optical power of the laser diode 102 using an internal bolometer 1102 provides for high precision control of output optical power stability of the laser diode 102 and a reduced risk of mode hopping.

Systems, devices or methods disclosed herein may include one or more of the features structures, methods, or combination thereof described herein. For example, a device or method may be implemented to include one or more of the features and/or processes above. It is intended that such device or method need not include all of the features and/or processes described herein, but may be implemented to include selected features and/or processes that provide useful structures and/or functionality. Various modifications and additions can be made to the disclosed embodiments discussed above. Accordingly, the scope of the present disclosure should not be limited by the particular embodiments described above, but should be defined only by the claims set forth below and equivalents thereof.

What is claimed is:

1. An apparatus, comprising:

- a slider having an upper surface, a lower air-bearing surface (ABS), and an internal body extending between the upper and lower surfaces;
- a write pole at or near the ABS;
- a reader at or near the ABS and connected to a pair of reader bond pads of the slider, the reader bond pads configured to electrically bias the reader during read operations;
- a near-field transducer (NFT) formed on the slider at or near the ABS;
- an optical waveguide formed in the slider and extending from the upper surface of the slider through the internal body of the slider and to the NFT, the waveguide configured to receive light from a laser source; and
- a bolometer:

10

situated proximal of the write pole at a location within the internal body of the slider that receives at least some of the light communicated along the waveguide;

electrically coupled to the reader bond pads for biasing the bolometer; and

configured to generate a signal indicative of output optical power of the laser source during write operations.

2. The apparatus of claim 1, wherein the bolometer is connected to the pair of reader bond pads in parallel with the reader.

3. The apparatus of claim 2, wherein the bolometer serves as a bias shunt during read operations.

4. The apparatus of claim 1, wherein the bolometer is configured for operation during write operations and non-operation during read operations.

5. The apparatus of claim 1, wherein the bolometer is situated proximal but spaced apart from a core of the waveguide.

6. The apparatus of claim 1, wherein the bolometer is spaced apart from a core of the waveguide by about 50 to 300 nm.

7. The apparatus of claim 1, wherein the bolometer is situated proximal of the NFT by a separation distance of about 2 μm to 80 μm .

8. The apparatus of claim 1, wherein the bolometer is spaced apart from a core of the waveguide and oriented normal to the core.

9. The apparatus of claim 1, wherein the bolometer is spaced apart from a core of the waveguide and oriented diagonally with respect to the core.

10. The apparatus of claim 1, wherein the bolometer comprises a material having a high thermal coefficient of resistance of about $1.5\text{e-}3^\circ\text{C}^{-1}$ or higher.

11. The apparatus of claim 1, wherein:

the waveguide comprises a coupler at a proximal end of the waveguide and a mode converter distal of the coupler; and

the bolometer is situated between the coupler and the mode converter.

12. The apparatus of claim 1, wherein:

the waveguide comprises a coupler at a proximal end of the waveguide and a mode converter distal of the coupler; and

the bolometer is situated between the mode converter and the write pole.

13. An apparatus, comprising:

a slider having an air-bearing surface (ABS);

a write pole at or near the ABS;

a reader at or near the ABS and connected to a pair of reader bond pads of the slider;

a near-field transducer (NFT) formed on the slider at or near the ABS;

an optical waveguide formed in the slider and configured to receive light from a laser source; and

a sensor:

situated proximal of the write pole at a location within the slider that receives at least some of the light communicated along the waveguide;

electrically coupled to the reader bond pads in parallel with the reader; and

configured to generate a signal indicative of output optical power of the laser source.

14. The apparatus of claim 13, wherein the sensor is configured to generate the signal only during write operations.

15. The apparatus of claim 13, wherein the sensor is spaced apart from a core of the waveguide by about 50 to 300 nm.
16. The apparatus of claim 13, wherein the bolometer is situated proximal of the NFT by a separation distance of 5 about 2 μm to 80 μm .
17. The apparatus of claim 13, wherein the sensor is spaced apart from a core of the waveguide and oriented normal to the core.
18. The apparatus of claim 13, wherein the sensor is 10 spaced apart from a core of the waveguide and oriented diagonally with respect to the core.
19. The apparatus of claim 13, wherein the sensor comprises a material having a high thermal coefficient of resistance of about $1.5\text{e-}3^\circ\text{C}^{-1}$ or higher. 15
20. The apparatus of claim 13, wherein:
the waveguide comprises a coupler at a proximal end of the waveguide and a mode converter distal of the coupler; and
the sensor is situated between the coupler and the mode 20 converter.
21. The apparatus of claim 13, wherein:
the waveguide comprises a coupler at a proximal end of the waveguide and a mode converter distal of the coupler; and 25
the sensor is situated between the mode converter and the write pole.
22. The apparatus of claim 1, wherein at least a portion of the bolometer crosses the waveguide.
23. The apparatus of claim 13, wherein at least a portion 30 of the sensor crosses the waveguide.

* * * * *