

(12) **United States Patent**
Bhushan et al.

(10) **Patent No.:** **US 9,713,035 B2**
(45) **Date of Patent:** **Jul. 18, 2017**

(54) **BEACON TRANSMISSION OVER UNLICENSED SPECTRUM**

(71) Applicant: **QUALCOMM Incorporated**, San Diego, CA (US)

(72) Inventors: **Naga Bhushan**, San Diego, CA (US); **Durga Prasad Malladi**, San Diego, CA (US); **Yongbin Wei**, San Diego, CA (US); **Peter Gaal**, San Diego, CA (US); **Tao Luo**, San Diego, CA (US); **Tingfang Ji**, San Diego, CA (US); **Gavin Bernard Horn**, La Jolla, CA (US); **Wanshi Chen**, San Diego, CA (US); **Aleksandar Damnjanovic**, Del Mar, CA (US)

(73) Assignee: **QUALCOMM Incorporated**, San Diego, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 86 days.

(21) Appl. No.: **14/281,641**

(22) Filed: **May 19, 2014**

(65) **Prior Publication Data**
US 2014/0341035 A1 Nov. 20, 2014

Related U.S. Application Data

(60) Provisional application No. 61/825,459, filed on May 20, 2013.

(51) **Int. Cl.**
H04L 5/00 (2006.01)
H04W 28/02 (2009.01)
(Continued)

(52) **U.S. Cl.**
CPC **H04W 28/08** (2013.01); **H04L 1/00** (2013.01); **H04L 5/001** (2013.01); **H04L 5/0044** (2013.01);
(Continued)

(58) **Field of Classification Search**
None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,870,673 A * 2/1999 Haartsen H04W 68/00 455/426.1
6,424,936 B1 7/2002 Shen et al.
(Continued)

FOREIGN PATENT DOCUMENTS

EP 1441468 A1 7/2004
EP 1763147 A1 3/2007
(Continued)

OTHER PUBLICATIONS


NTT DOCOMO, "Views on Load Balancing and Enhanced Interference Coordination for SCE," 3GPP TSG RAN WG1 Meeting #72bis, R1-131670, Chicago, US, Apr. 15-19, 2013, pp. 1-6, downloaded from http://www.3gpp.org/ftp/tsg_ran/wg1_r11/TSGR1_72b/Docs/, 3rd Generation Partnership Project.

(Continued)

Primary Examiner — Chi H Pham
Assistant Examiner — Soon-Dong D Hyun
(74) *Attorney, Agent, or Firm* — Larry J. Moskowitz

(57) **ABSTRACT**
Methods and apparatuses are described in which an unlicensed spectrum is used for Long Term Evolution (LTE) communications. A first method includes broadcasting beacon signals in an unlicensed spectrum at predetermined times from an evolved Node B (eNB). A second method includes receiving beacon signals broadcast in an unlicensed spectrum at predetermined times from an eNB. The beacon signals may include downlink signals identifying the eNB and at least one associated attribute of the eNB.

58 Claims, 46 Drawing Sheets



(51) Int. Cl.					
<i>H04W 74/08</i>	(2009.01)	2013/0107856	A1	5/2013	Naden et al.
<i>H04W 28/08</i>	(2009.01)	2013/0165134	A1	6/2013	Touag et al.
<i>H04W 24/02</i>	(2009.01)	2013/0272263	A1	10/2013	Pi et al.
<i>H04W 28/16</i>	(2009.01)	2013/0294356	A1	11/2013	Bala et al.
<i>H04W 72/04</i>	(2009.01)	2013/0315152	A1	11/2013	Ratasuk et al.
<i>H04W 56/00</i>	(2009.01)	2014/0029539	A1	1/2014	Choi et al.
<i>H04W 74/04</i>	(2009.01)	2014/0140314	A1*	5/2014	Wei H04W 48/12 370/329
<i>H04W 16/14</i>	(2009.01)	2014/0169487	A1	6/2014	Liu et al.
<i>H04W 76/02</i>	(2009.01)	2014/0302856	A1*	10/2014	Nory H04W 48/10 455/437
<i>H04L 1/00</i>	(2006.01)	2014/0335876	A1	11/2014	Ratasuk et al.
<i>H04L 27/26</i>	(2006.01)	2014/0341018	A1	11/2014	Bhushan et al.
<i>H04L 27/00</i>	(2006.01)	2014/0341024	A1	11/2014	Bhushan et al.
<i>H04W 48/10</i>	(2009.01)	2014/0341053	A1	11/2014	Bhushan et al.
<i>H04W 72/08</i>	(2009.01)	2014/0341135	A1	11/2014	Bhushan et al.
<i>H04W 74/00</i>	(2009.01)	2014/0341207	A1	11/2014	Bhushan et al.
<i>H04L 5/14</i>	(2006.01)	2014/0342745	A1	11/2014	Bhushan et al.
<i>H04W 84/12</i>	(2009.01)	2014/0378157	A1	12/2014	Wei et al.
<i>H04W 88/06</i>	(2009.01)	2015/0029952	A1	1/2015	Huang
<i>H04W 88/08</i>	(2009.01)	2015/0036556	A1	2/2015	Imamura et al.
<i>H04J 11/00</i>	(2006.01)	2015/0057011	A1	2/2015	Di et al.
<i>H04W 88/02</i>	(2009.01)	2015/0131536	A1	5/2015	Kaur et al.
		2015/0131544	A1	5/2015	Behravan et al.
		2015/0188675	A1	7/2015	Abeysekera et al.
		2016/0381567	A1	12/2016	Bhushan et al.
		2017/0111802	A1	4/2017	Bhushan et al.

(52) **U.S. Cl.**
 CPC *H04L 5/0053* (2013.01); *H04L 5/14* (2013.01); *H04L 5/1469* (2013.01); *H04L 27/0006* (2013.01); *H04L 27/2602* (2013.01); *H04W 16/14* (2013.01); *H04W 24/02* (2013.01); *H04W 28/0252* (2013.01); *H04W 28/0289* (2013.01); *H04W 28/16* (2013.01); *H04W 48/10* (2013.01); *H04W 56/002* (2013.01); *H04W 72/04* (2013.01); *H04W 72/082* (2013.01); *H04W 74/006* (2013.01); *H04W 74/04* (2013.01); *H04W 74/0816* (2013.01); *H04W 74/0833* (2013.01); *H04W 76/025* (2013.01); *H04J 11/00* (2013.01); *H04L 5/005* (2013.01); *H04W 56/001* (2013.01); *H04W 84/12* (2013.01); *H04W 88/02* (2013.01); *H04W 88/06* (2013.01); *H04W 88/08* (2013.01)

FOREIGN PATENT DOCUMENTS

EP	2056529	A1	5/2009
WO	WO-2012037236	A2	3/2012
WO	WO-2012040520	A1	3/2012
WO	WO-2012074343	A2	6/2012
WO	WO-2012075343	A2	6/2012
WO	WO-2012078565	A1	6/2012
WO	WO-2012095038	A1	7/2012
WO	WO-2012101481	A1	8/2012
WO	WO-2012109195	A2	8/2012
WO	WO-2012134567	A1	10/2012
WO	WO-2013006988	A1	1/2013
WO	WO-2013059999	A1	5/2013
WO	WO-2013185835	A1	12/2013

OTHER PUBLICATIONS

Samsung, "Performance Considerations for Standalone NCT," 3GPP TSG RAN WG1 #73, R1-131957, Fukuoka, JP, May 20-24, 2013, pp. 1-4, downloaded from http://www.3gpp.org/ftp/tsg_ran/wg1_rl1/TSGR1_73/Docs/, 3rd Generation Partnership Project.

Huawei, "Analysis and Evaluation of UL DM RS Design for LTE-A Scenarios," 3GPP TSG RAN WG1 Meeting #59bis, Valencia, Spain, Jan. 18-22, 2010, 8 pgs., R1-100262, URL: http://www.3gpp.org/ftp/tsg_ran/wg1_rl1/TSGR1_59b/Docs/, 3rd Generation Partnership Project.

Intel Corporation, "UL CoMP DM-RS Enhancements for Homogenous Networks," 3GPP TSG-RAN WG1 Meeting #67, San Francisco, U.S.A., Nov. 14-18, 2011, 6 pgs., R1-113664, URL: http://www.3gpp.org/ftp/tsg_ran/wg1_rl1/TSGR1_67/Docs/, 3rd Generation Partnership Project.

Motorola, "Uplink Multiple Access for EUTRA," 3GPP TSG RAN1 #40bis Meeting, Beijing, China, Apr. 4-8, 2005, 11 pgs., R1-050245, URL: http://www.3gpp.org/ftp/tsg_ran/wg1_rl1/TSGR1_40bis/Docs/, 3rd Generation Partnership Project.

QUALCOMM Europe, "Considerations on OFDMA and SC-FDMA Based Uplink for E-UTRA Evaluation (PAR Aspects)," 3GPP TSG-RAN WG1 #42-bis, San Diego, CA, Oct. 10-14, 2005, 4 pgs., R1-051120, URL: http://www.3gpp.org/ftp/tsg_ran/wg1_rl1/TSGR1_42bis/Docs/, 3rd Generation Partnership Project.

3GPP Standard, "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Resource Control (RRC); Protocol Specification (Release 11)," 3GPP TS 36.331 v11.2.0 (Dec. 2012), Dec. 2012, XP-002729254, 26 pgs.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,218,623	B1*	5/2007	Proctor, Jr.	H04B 7/2618 370/335
8,503,343	B2	8/2013	Kawakami et al.	
2003/0007473	A1	1/2003	Strong et al.	
2003/0016647	A1	1/2003	Margon	
2004/0142696	A1	7/2004	Saunders et al.	
2004/0194142	A1	9/2004	Jiang et al.	
2009/0116430	A1	5/2009	Bonta et al.	
2009/0180451	A1	7/2009	Alpert et al.	
2010/0014502	A1	1/2010	Singh et al.	
2010/0046657	A1	2/2010	Karlsson	
2010/0195601	A1	8/2010	Zhang et al.	
2011/0090855	A1	4/2011	Kim	
2011/0142019	A1	6/2011	Bharghavan et al.	
2011/0149918	A1	6/2011	Gong et al.	
2011/0261708	A1	10/2011	Grandhi	
2012/0039252	A1	2/2012	Damnjanovic et al.	
2012/0063373	A1*	3/2012	Chincholi	H04L 5/001 370/281
2012/0113831	A1	5/2012	Pelletier et al.	
2012/0281573	A1*	11/2012	Kazmi	H04W 8/26 370/252
2012/0281593	A1	11/2012	Stewart et al.	
2013/0023286	A1*	1/2013	Soma	H04W 4/02 455/456.1
2013/0094375	A1	4/2013	Liu et al.	

(56)

References Cited

OTHER PUBLICATIONS

Beluri et al, "Mechanisms for LTE Coexistence in TV White Space," 2012 IEEE International Symposium on Dynamic Spectrum Access Networks (DYSPAN), Oct. 16-19, 2012, Bellevue, WA, pp. 317-326, ISBN 978-1-4673-4447-0, IEEE.

Cisco Public Information, "802.11ac: the Fifth Generation of WiFi," Technical White Paper, Aug. 2012, pp. 1-25, downloaded from http://www.cisco.com/c/en/us/products/collateral/wireless/aironet-3600-series/white_paper_c11-713103.pdf, Cisco Systems, Inc., San Jose, CA.

ISA/EPO, International Search Report and Written Opinion of the International Searching Authority, Int'l. App. No. PCT/US2014/038768, Sep. 19, 2014, European Patent Office, Rijswijk, NL, 12 pgs.

Ratasuk et al., "License-exempt LTE Deployment in Heterogeneous Network," 2012 International Symposium on Wireless Communication Systems (ISWCS), Aug. 28, 2012, pp. 246-250, ISBN 978-1-4673-0761-1, IEEE.

Yang et al., "Performance Analysis on a New MAC DT-CSMA," IECON 2011 37th Annual Conference on IEEE Industrial Electronics Society, Nov. 7, 2011, pp. 3522-3527, ISBN 978-1-61284-969-0, IEEE.

U.S. Appl. No. 15/460,538, filed Mar. 16, 2017.

* cited by examiner




FIG. 1

200




FIG. 2A

200-a




FIG. 2B

300




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 7A

705




FIG. 7B




FIG. 8




FIG. 9A




FIG. 9B




FIG. 9C




FIG. 9D




FIG. 10A




FIG. 10B




FIG. 10C

1000-c




FIG. 10D




FIG. 10E




FIG. 10F




FIG. 10G




FIG. 11




FIG. 12A




FIG. 12B




FIG. 13A




FIG. 13B




FIG. 14A




FIG. 14B




FIG. 14C

1500




FIG. 15

1600




FIG. 16




FIG. 17A




FIG. 17B




FIG. 18A




FIG. 18B




FIG. 19A




FIG. 19B




FIG. 20


2100


FIG. 21

2200




FIG. 22A

2200-a




FIG. 22B

2300




FIG. 23




FIG. 24

2500




FIG. 25




FIG. 26

2700




FIG. 27




FIG. 28




FIG. 29

3000




FIG. 30




FIG. 31




FIG. 32

BEACON TRANSMISSION OVER UNLICENSED SPECTRUM

CROSS REFERENCES

The present application for patent claims priority to U.S. Provisional Patent Application No. 61/825,459 by Bhushan et al., entitled "LTE-Unlicensed," filed May 20, 2013, assigned to the assignee hereof, and expressly incorporated by reference herein.

BACKGROUND

Wireless communication networks are widely deployed to provide various communication services such as voice, video, packet data, messaging, broadcast, and the like. These wireless networks may be multiple-access networks capable of supporting multiple users by sharing the available network resources.

A wireless communication network may include a number of base stations or Node-Bs that can support communication for a number of user equipments (UEs). A UE may communicate with a base station via downlink and uplink. The downlink (or forward link) refers to the communication link from the base station to the UE, and the uplink (or reverse link) refers to the communication link from the UE to the base station.

As wireless communications networks become more congested, operators are beginning to look at ways to increase capacity. One approach may be to use Wireless Local Area Networks (WLANs) to offload some of the traffic and/or signaling. WLANs (or WiFi networks) are attractive because, unlike cellular networks that operate in a licensed spectrum, they generally operate in unlicensed spectrum. Moreover, a growing amount spectrum is being allocated for access without a license, making the option of offloading traffic and/or signaling to WLANs more attractive. This approach, however, may provide a partial solution to the congestion problem since WLANs tend to use spectrum less efficiently than cellular networks. Moreover, the regulations and protocols involved in WLANs are different from those for cellular networks. Therefore, unlicensed spectrum may remain a reasonable option to alleviate congestion if it can be used more efficiently and in accordance with regulatory requirements.

SUMMARY

Methods and apparatuses are described in which an unlicensed spectrum may be used for 3GPP Long Term Evolution (LTE) communications. Various deployment scenarios may be supported including a supplemental downlink mode in which LTE downlink capacity in a licensed spectrum may be offloaded to an unlicensed spectrum. A carrier aggregation mode may be used to offload both LTE downlink and uplink capacity from a licensed spectrum to an unlicensed spectrum. In a standalone mode, LTE downlink and uplink communications between a base station (e.g., an evolved Node B (eNB)) and a UE may take place in an unlicensed spectrum. Base stations as well as UEs may support one or more of these or similar modes. Orthogonal Frequency-Division Multiple Access (OFDMA) communications signals may be used for LTE downlink communications in an unlicensed spectrum, while Single-Carrier Frequency-Division Multiple Access (SC-FDMA) communications signals may be used for LTE uplink communi-

tions in an unlicensed spectrum. The use of LTE configured for an unlicensed spectrum may be referred to as LTE-Unlicensed or LTE-U.

In a first set of illustrative examples, a method for wireless communications is described. In one example, the method includes broadcasting beacon signals in an unlicensed spectrum at predetermined times from an eNB, where the beacon signals include downlink signals identifying the eNB and at least one associated attribute of the eNB. In some embodiments, the at least one associated attribute of the eNB includes at least one attribute of the eNB. In some embodiments, the at least one associated attribute of the eNB includes an eNB deployment configuration for an eNB deployment with which the eNB is associated. In some embodiments, the at least one associated attribute of the eNB includes an eNB deployment configuration for an eNB deployment with which the eNB is associated, wherein downlink signals from eNBs in the eNB deployment are synchronized and concurrently transmitted by the eNBs of the eNB deployment in the unlicensed spectrum and in a licensed spectrum. In some embodiments, the at least one associated attribute of the eNB includes a Random Access Channel (RACH) configuration associated with the eNB, and the beacon signals also include a paging message for at least one user equipment (UE). In some embodiments, the eNBs in the eNB deployment are each deployed by a same operator. In some embodiments, broadcasting the beacon signals includes broadcasting the beacon signals at a duty cycle below 5%, with a maximum broadcasting interval of approximately once every 50 milliseconds. In some embodiments, the beacon signals include one or more of a Primary Synchronization Signal (PSS), a Secondary Synchronization Signal (SSS), a Cell-Specific Reference Signal (CRS), a Physical Broadcast Channel (PBCH), a Global Cell Identifier (GCI), a CSG-ID, a Public Land Mobile Network (PLMN) ID, a deployment identifier, a periodic gating structure configuration, a Clear Channel Assessment randomization seed (CCA-RS), a RACH configuration, a System Information Block (SIB), and a lite version of an SIB (SIB-lite). In some embodiments, the beacon signals include information that identifies the eNB as being active or dormant.

In a second set of illustrative examples, an apparatus for wireless communications is described. In one example, the apparatus includes means for broadcasting beacon signals in an unlicensed spectrum at predetermined times from an eNB, where the beacon signals include downlink signals identifying the eNB and at least one associated attribute of the eNB. In some embodiments, the at least one associated attribute of the eNB includes at least one attribute of the eNB. In some embodiments, the at least one associated attribute of the eNB includes an eNB deployment configuration for an eNB deployment with which the eNB is associated. In some embodiments, the at least one associated attribute of the eNB includes an eNB deployment configuration for an eNB deployment with which the eNB is associated, wherein downlink signals from eNBs in the eNB deployment are synchronized and concurrently transmitted by the eNBs of the eNB deployment in the unlicensed spectrum and in a licensed spectrum. In some embodiments, the at least one associated attribute of the eNB includes a RACH configuration associated with the eNB, and the beacon signals also include a paging message for at least one UE. In some embodiments, the eNBs in the eNB deployment are each deployed by a same operator. In some embodiments, broadcasting the beacon signals comprises broadcasting the beacon signals at a duty cycle below 5%, with a

maximum broadcasting interval of approximately once every 50 milliseconds. In some embodiments, the beacon signals include one or more of a PSS, an SSS, a CRS, a PBCH, a GCI, a CSG-ID, a PLMN ID, a deployment identifier, a periodic gating structure configuration, a CCA-RS, a RACH configuration, an SIB, and an SIB-lite. In some embodiments, the beacon signals include information that identifies the eNB as being active or dormant.

In a third set of illustrative examples, another apparatus for wireless communications is described. In one example, the apparatus includes a processor, memory in electronic communication with the processor, and instructions stored in the memory. The instructions may be executable by the processor to broadcast beacon signals in an unlicensed spectrum at predetermined times from an eNB, where the beacon signals include downlink signals identifying the eNB and at least one associated attribute of the eNB. In some embodiments, the at least one associated attribute of the eNB includes at least one attribute of the eNB. In some embodiments, the at least one associated attribute of the eNB includes an eNB deployment configuration for an eNB deployment with which the eNB is associated. In some embodiments, the at least one associated attribute of the eNB includes an eNB deployment configuration for an eNB deployment with which the eNB is associated, wherein downlink signals from eNBs in the eNB deployment are synchronized and concurrently transmitted by the eNBs of the eNB deployment in the unlicensed spectrum and in a licensed spectrum. In some embodiments, the at least one associated attribute of the eNB includes a RACH configuration associated with the eNB, and the beacon signals also include a paging message for at least one UE. In some embodiments, the eNBs in the eNB deployment are each deployed by a same operator. In some embodiments, broadcasting the beacon signals comprises broadcasting the beacon signals at a duty cycle below 5%, with a maximum broadcasting interval of approximately once every 50 milliseconds. In some embodiments, the beacon signals include one or more of a PSS, an SSS, a CRS, a PBCH, a GCI, a CSG-ID, a PLMN ID, a deployment identifier, a periodic gating structure configuration, a CCA-RS, a RACH configuration, an SIB, and an SIB-lite. In some embodiments, the beacon signals include information that identifies the eNB as being active or dormant.

In a fourth set of illustrative examples, a computer program product for communications by a wireless communications apparatus in a wireless communications system is described. In one example, the computer program product includes a non-transitory computer-readable medium storing instructions executable by a processor to cause the wireless communications apparatus to broadcast beacon signals in an unlicensed spectrum at predetermined times from an eNB, where the beacon signals include downlink signals identifying the eNB and at least one associated attribute of the eNB. In some embodiments, the at least one associated attribute of the eNB includes at least one attribute of the eNB. In some embodiments, the at least one associated attribute of the eNB includes an eNB deployment configuration for an eNB deployment with which the eNB is associated. In some embodiments, the at least one associated attribute of the eNB includes an eNB deployment configuration for an eNB deployment with which the eNB is associated, wherein downlink signals from eNBs in the eNB deployment are synchronized and concurrently transmitted by the eNBs of the eNB deployment in the unlicensed spectrum and in a licensed spectrum. In some embodiments, the at least one associated attribute of the eNB includes a

RACH configuration associated with the eNB, and the beacon signals also include a paging message for at least one UE. In some embodiments, the eNBs in the eNB deployment are each deployed by a same operator. In some embodiments, broadcasting the beacon signals comprises broadcasting the beacon signals at a duty cycle below 5%, with a maximum broadcasting interval of approximately once every 50 milliseconds. In some embodiments, the beacon signals include one or more of a PSS, an SSS, a CRS, a PBCH, a GCI, a CSG-ID, a PLMN ID, a deployment identifier, a periodic gating structure configuration, a CCA-RS, a RACH configuration, an SIB, and an SIB-lite. In some embodiments, the beacon signals include information that identifies the eNB as being active or dormant.

In a fifth set of illustrative examples, another method for wireless communications is described. In one example, the method includes receiving beacon signals broadcast in an unlicensed spectrum at predetermined times from an eNB, where the beacon signals include downlink signals identifying the eNB and at least one associated attribute of the eNB. In some embodiments, the at least one associated attribute of the eNB includes at least one attribute of the eNB. In some embodiments, the at least one associated attribute of the eNB includes an eNB deployment configuration for an eNB deployment with which the eNB is associated. In some embodiments, the at least one associated attribute of the eNB includes an eNB deployment configuration for an eNB deployment with which the eNB is associated, wherein downlink signals from eNBs in the eNB deployment are synchronized and concurrently transmitted by the eNBs of the eNB deployment in the unlicensed spectrum and in a licensed spectrum. In some embodiments, the at least one associated attribute of the eNB includes a RACH configuration associated with the eNB, and the beacon signals also include a paging message for at least one UE. In some embodiments, the method includes responding to the paging message using the RACH configuration. In some embodiments, the method includes using the beacon signals to make a coarse timing adjustment at a UE.

In some embodiments, the eNBs in the eNB deployment are each deployed by a same operator. In some embodiments, broadcasting the beacon signals includes broadcasting the beacon signals at a duty cycle below 5%, with a maximum broadcasting interval of approximately once every 50 milliseconds. In some embodiments, the beacon signals include one or more of a PSS, an SSS, a CRS, a PBCH, a GCI, a CSG-ID, a PLMN ID, a deployment identifier, a periodic gating structure configuration, a CCA-RS, a RACH configuration, a SIB, and a SIB-lite. In some embodiments, the beacon signals include information that identifies the eNB as being active or dormant.

In a sixth set of illustrative examples, another apparatus for wireless communications is described. In one example, the apparatus includes means for receiving beacon signals broadcast in an unlicensed spectrum at predetermined times from an eNB, where the beacon signals include downlink signals identifying the eNB and at least one associated attribute of the eNB. In some embodiments, the at least one associated attribute of the eNB includes at least one attribute of the eNB. In some embodiments, the at least one associated attribute of the eNB includes an eNB deployment configuration for an eNB deployment with which the eNB is associated. In some embodiments, the at least one associated attribute of the eNB includes an eNB deployment configuration for an eNB deployment with which the eNB is associated, wherein downlink signals from eNBs in the eNB deployment are synchronized and concurrently transmitted

by the eNBs of the eNB deployment in the unlicensed spectrum and in a licensed spectrum. In some embodiments, the at least one associated attribute of the eNB includes a RACH configuration associated with the eNB, and the beacon signals also include a paging message for at least one UE. In some embodiments, the apparatus includes means for responding to the paging message using the RACH configuration. In some embodiments, the apparatus includes means for using the beacon signals to make a coarse timing adjustment at a UE.

In some embodiments, the eNBs in the eNB deployment are each deployed by a same operator. In some embodiments, broadcasting the beacon signals includes broadcasting the beacon signals at a duty cycle below 5%, with a maximum broadcasting interval of approximately once every 50 milliseconds. In some embodiments, the beacon signals include one or more of a PSS, an SSS, a CRS, a PBCH, a GCI, a CSG-ID, a PLMN ID, a deployment identifier, a periodic gating structure configuration, a CCA-RS, a RACH configuration, a SIB, and a SIB-lite. In some embodiments, the beacon signals include information that identifies the eNB as being active or dormant.

In a seventh set of illustrative examples, another apparatus for wireless communications is described. In one example, the apparatus includes a processor, memory in electronic communication with the processor, and instructions stored in the memory. The instructions may be executable by the processor to receive beacon signals broadcast in an unlicensed spectrum at predetermined times from an eNB, where the beacon signals include downlink signals identifying the eNB and at least one associated attribute of the eNB. In some embodiments, the at least one associated attribute of the eNB includes at least one attribute of the eNB. In some embodiments, the at least one associated attribute of the eNB includes an eNB deployment configuration for an eNB deployment with which the eNB is associated. In some embodiments, the at least one associated attribute of the eNB includes an eNB deployment configuration for an eNB deployment with which the eNB is associated, wherein downlink signals from eNBs in the eNB deployment are synchronized and concurrently transmitted by the eNBs of the eNB deployment in the unlicensed spectrum and in a licensed spectrum. In some embodiments, the at least one associated attribute of the eNB includes a RACH configuration associated with the eNB, and the beacon signals also include a paging message for at least one UE. In some embodiments, the instructions are executable by the processor to respond to the paging message using the RACH configuration. In some embodiments, the instructions are executable by the processor to use the beacon signals to make a coarse timing adjustment at a UE.

In some embodiments, the eNBs in the eNB deployment are each deployed by a same operator. In some embodiments, broadcasting the beacon signals includes broadcasting the beacon signals at a duty cycle below 5%, with a maximum broadcasting interval of approximately once every 50 milliseconds. In some embodiments, the beacon signals include one or more of a PSS, an SSS, a CRS, a PBCH, a GCI, a CSG-ID, a PLMN ID, a deployment identifier, a periodic gating structure configuration, a CCA-RS, a RACH configuration, a SIB, and a SIB-lite. In some embodiments, the beacon signals include information that identifies the eNB as being active or dormant.

In an eighth set of illustrative examples, another computer program product for communications by a wireless communications apparatus in a wireless communications system is described. In one example, the computer program product

includes a non-transitory computer-readable medium storing instructions executable by a processor to cause the wireless communications apparatus to receive beacon signals broadcast in an unlicensed spectrum at predetermined times from an eNB, where the beacon signals include downlink signals identifying the eNB and at least one associated attribute of the eNB. In some embodiments, the at least one associated attribute of the eNB includes at least one attribute of the eNB. In some embodiments, the at least one associated attribute of the eNB includes an eNB deployment configuration for an eNB deployment with which the eNB is associated. In some embodiments, the at least one associated attribute of the eNB includes an eNB deployment configuration for an eNB deployment with which the eNB is associated, wherein downlink signals from eNBs in the eNB deployment are synchronized and concurrently transmitted by the eNBs of the eNB deployment in the unlicensed spectrum and in a licensed spectrum. In some embodiments, the at least one associated attribute of the eNB includes a RACH configuration associated with the eNB, and the beacon signals also include a paging message for at least one UE. In some embodiments, the instructions are executable by the processor to cause the wireless communications apparatus to respond to the paging message using the RACH configuration. In some embodiments, the instructions are executable by the processor to cause the wireless communications apparatus to use the beacon signals to make a coarse timing adjustment at a UE.

In some embodiments, the eNBs in the eNB deployment are each deployed by a same operator. In some embodiments, broadcasting the beacon signals includes broadcasting the beacon signals at a duty cycle below 5%, with a maximum broadcasting interval of approximately once every 50 milliseconds. In some embodiments, the beacon signals include one or more of a PSS, an SSS, a CRS, a PBCH, a GCI, a CSG-ID, a PLMN ID, a deployment identifier, a periodic gating structure configuration, a CCA-RS, a RACH configuration, a SIB, and a SIB-lite. In some embodiments, the beacon signals include information that identifies the eNB as being active or dormant.

The foregoing has outlined rather broadly the features and technical advantages of examples according to the disclosure in order that the detailed description that follows may be better understood. Additional features and advantages will be described hereinafter. The conception and specific examples disclosed may be readily utilized as a basis for modifying or designing other structures for carrying out the same purposes of the present disclosure. Such equivalent constructions do not depart from the spirit and scope of the appended claims. Features which are believed to be characteristic of the concepts disclosed herein, both as to their organization and method of operation, together with associated advantages will be better understood from the following description when considered in connection with the accompanying figures. Each of the figures is provided for the purpose of illustration and description only, and not as a definition of the limits of the claims.

BRIEF DESCRIPTION OF THE DRAWINGS

A further understanding of the nature and advantages of the present disclosure may be realized by reference to the following drawings. In the appended figures, similar components or features may have the same reference label. Further, various components of the same type may be distinguished by following the reference label by a dash and a second label that distinguishes among the similar compo-

nents. If only the first reference label is used in the specification, the description is applicable to any one of the similar components having the same first reference label irrespective of the second reference label.

FIG. 1 shows a diagram that illustrates an example of a wireless communications system according to various embodiments;

FIG. 2A shows a diagram that illustrates examples of deployment scenarios for using LTE in an unlicensed spectrum according to various embodiments;

FIG. 2B shows a diagram that illustrates another example of a deployment scenario for using LTE in an unlicensed spectrum according to various embodiments;

FIG. 3 shows a diagram that illustrates an example of carrier aggregation when using LTE concurrently in licensed and unlicensed spectrum according to various embodiments;

FIG. 4A is a flowchart of an example of a method for concurrent use of LTE in licensed and unlicensed spectrum in a base station according to various embodiments;

FIG. 4B is a flowchart of another example of a method for concurrent use of LTE in licensed and unlicensed spectrum in a base station according to various embodiments;

FIG. 5A is a flowchart of an example of a method for concurrent use of LTE in licensed and unlicensed spectrum in a UE according to various embodiments;

FIG. 5B is a flowchart of yet another example of a method for concurrent use of LTE in licensed and unlicensed spectrum in a UE according to various embodiments;

FIG. 6A shows a diagram that illustrates an example of a periodic gating structure aligned to a periodic frame structure according to various embodiments;

FIG. 6B shows a diagram that illustrates an example of a periodic gating structure that is half a periodic frame structure according to various embodiments;

FIG. 6C shows a diagram that illustrates an example of a periodic gating structure that is twice a periodic frame structure according to various embodiments;

FIG. 6D shows a diagram that illustrates an example of a periodic gating structure that is smaller than a periodic frame structure according to various embodiments;

FIG. 7A shows a diagram that illustrates an example of a periodic gating structure waveform according to various embodiments;

FIG. 7B shows a diagram that illustrates another example of a periodic gating structure waveform according to various embodiments;

FIG. 8 is a flowchart of an example of a method for synchronizing a periodic gating structure with a periodic frame structure according to various embodiments;

FIG. 9A shows a diagram that illustrates an example of an S' subframe in a periodic gating structure according to various embodiments;

FIG. 9B shows a diagram that illustrates an example of placement options for clear channel assessment (CCA) slots in an S' subframe according to various embodiments;

FIG. 9C shows a diagram that illustrates another example of an S' subframe in a periodic gating structure according to various embodiments;

FIG. 9D shows a diagram that illustrates another example of an S' subframe in a periodic gating structure according to various embodiments;

FIG. 10A shows a diagram that illustrates an example of gating when the channel usage assessment occurs at the end of a previous gating interval according to various embodiments;

FIG. 10B shows a diagram that illustrates an example of gating when the channel usage assessment occurs at the beginning of a previous gating interval according to various embodiments;

FIG. 10C shows a diagram that illustrates an example of gating in response to WiFi transmission activity according to various embodiments;

FIG. 10D shows a diagram that illustrates an example of a periodic gating structure waveform with 14 Orthogonal Frequency-Division Multiplexing (OFDM) symbols according to various embodiments;

FIG. 10E shows a diagram that illustrates another example of a periodic gating structure waveform with 14 OFDM symbols according to various embodiments;

FIG. 10F shows a diagram that illustrates an example of a periodic gating structure waveform with two subframes according to various embodiments;

FIG. 10G shows a diagram that illustrates another example of a periodic gating structure waveform with two subframes according to various embodiments;

FIG. 11 is a flowchart of an example of a method for gating a periodic structure according to various embodiments;

FIG. 12A is a flowchart of an example of a method for synchronizing CAA slots across multiple base stations according to various embodiments;

FIG. 12B is a flowchart of another example of a method for synchronizing CAA slots across multiple base stations according to various embodiments;

FIG. 13A is a flowchart of an example of a method for performing CAA when the CCA slots are synchronized across multiple base stations according to various embodiments;

FIG. 13B is a flowchart of another example of a method for performing CAA when the CCA slots are synchronized across multiple base stations according to various embodiments;

FIG. 14A shows a diagram that illustrates an example of the use of Channel Usage Beacon Signals (CUBS) to reserve a channel in an unlicensed spectrum according to various embodiments;

FIG. 14B shows a diagram that illustrates another example of the use of CUBS to reserve a channel in an unlicensed spectrum according to various embodiments;

FIG. 14C shows a diagram that illustrates yet another example of the use of CUBS to reserve a channel in an unlicensed spectrum according to various embodiments;

FIG. 15 is a flowchart of an example of a method for transmitting signals to reserve an unlicensed spectrum according to various embodiments;

FIG. 16 shows a diagram that illustrates an example of feedback information being sent in a licensed spectrum to address signals transmitted in an unlicensed spectrum according to various embodiments;

FIG. 17A is a flowchart of an example of a method for receiving feedback information via a Primary Component Carrier (PCC) uplink in a licensed spectrum according to various embodiments;

FIG. 17B is a flowchart of an example of a method for transmitting feedback information via a PCC uplink in a licensed spectrum according to various embodiments;

FIG. 18A shows a diagram that illustrates an example of LTE-U beacon signal broadcasting in an unlicensed spectrum according to various embodiments;

FIG. 18B shows a diagram that illustrates an example of a payload in an LTE-U beacon signal according to various embodiments;

FIG. 19A is a flowchart of an example of a method for broadcasting LTE-U beacon signals in an unlicensed spectrum according to various embodiments;

FIG. 19B is a flowchart of another example of a method for broadcasting LTE-U beacon signals in an unlicensed spectrum according to various embodiments;

FIG. 20 shows a diagram that illustrates an example of request-to-send (RTS) and clear-to-send (CTS) signals in an unlicensed spectrum according to various embodiments;

FIG. 21 is a flowchart of an example of a method for transmitting RTS signals and receiving CTS signals in an unlicensed spectrum according to various embodiments;

FIG. 22A shows a diagram that illustrates an example of virtual CTS (V-CTS) signals in a licensed spectrum according to various embodiments;

FIG. 22B shows a diagram that illustrates an example of a virtual RTS (V-RTS) signal and virtual V-CTS signals in a licensed spectrum according to various embodiments;

FIG. 23 is a flowchart of an example of a method for transmitting an RTS signal or a V-RTS signal according to various embodiments;

FIG. 24 is a flowchart of an example of a method for receiving V-CTS signals in response to an RTS signal or a V-RTS signal according to various embodiments;

FIG. 25 shows a diagram that illustrates an example of normal and robust subframes in an unlicensed spectrum according to various embodiments;

FIG. 26 is a flowchart of an example of a method for transmitting normal or robust subframes in an unlicensed spectrum based on past transmission activity according to various embodiments;

FIG. 27 shows a diagram that illustrates an example of Physical Uplink Control Channel (PUCCH) signals and Physical Uplink Shared Channel (PUSCH) signals for an unlicensed spectrum according to various embodiments;

FIG. 28 is a flowchart of an example of a method for generating PUCCH and/or PUSCH signals for an unlicensed spectrum according to various embodiments;

FIG. 29 shows a diagram that illustrates an example of load-based gating in an unlicensed spectrum according to various embodiments;

FIG. 30 shows a block diagram that illustrates an example of a UE architecture according to various embodiments;

FIG. 31 shows a block diagram that illustrates an example of a base station architecture according to various embodiments; and

FIG. 32 shows a block diagram that illustrates an example of a multiple-input multiple-output (MIMO) communications system according to various embodiments.

DETAILED DESCRIPTION

Various systems, methods, and apparatuses are described in which unlicensed spectrum is used for LTE communications. Various deployment scenarios may be supported including a supplemental downlink mode in which LTE downlink traffic may be offloaded to an unlicensed spectrum. A carrier aggregation mode may be used to offload both LTE downlink and uplink traffic from a licensed spectrum to an unlicensed spectrum. In a standalone mode, LTE downlink and uplink communications between a base station (e.g., an eNB) and a UE may occur in an unlicensed spectrum. LTE and other base stations and UEs may support one or more of these or similar modes of operation. OFDMA communications signals may be used for LTE downlink communications in an unlicensed spectrum, while SC-FDMA commu-

nications signals may be used for LTE uplink communications in an unlicensed spectrum.

Operators have so far looked at WiFi as the primary mechanism to use unlicensed spectrum to relieve ever increasing levels of congestion in cellular networks. However, a new carrier type (NCT) based on LTE in an unlicensed spectrum (LTE-U) may be compatible with carrier-grade WiFi, making LTE-U an alternative to WiFi. LTE-U may leverage LTE concepts and may introduce some modifications to physical layer (PHY) and media access control (MAC) aspects of the network or network devices to provide efficient operation in the unlicensed spectrum and to meet regulatory requirements. The unlicensed spectrum may range from 600 Megahertz (MHz) to 6 Gigahertz (GHz), for example. In some scenarios, LTE-U may perform significantly better than WiFi. For example, in an all LTE-U deployment (for single or multiple operators), or when there are dense small cell LTE-U deployments, LTE-U may perform significantly better than WiFi. LTE-U may also perform better than WiFi in other scenarios, such as when LTE-U is mixed with WiFi (for single or multiple operators).

For a single service provider (SP), an LTE-U network on an unlicensed spectrum may be configured to be synchronous with an LTE network on a licensed spectrum. In some embodiments, some or all of the LTE-U networks deployed on a given channel by multiple SPs may also be configured to be synchronous across the multiple SPs. One approach to incorporate both the above features may involve using a constant timing offset between LTE and LTE-U for a given SP. In some embodiments, some or all of the LTE-U networks deployed on a given channel by multiple SPs may be configured to be asynchronous across the multiple SPs. An LTE-U network may provide unicast and/or multicast services according to the needs of the SP. Moreover, an LTE-U network may operate in a bootstrapped mode in which LTE cells act as anchor and provide relevant LTE-U cell information (e.g., radio frame timing, common channel configuration, system frame number or SFN, etc.). In this mode, there may be close interworking between LTE and LTE-U. For example, the bootstrapped mode may support the supplemental downlink and the carrier aggregation modes described above. The PHY-MAC layers of the LTE-U network may operate in a standalone mode in which the LTE-U network operates independently from an LTE network. In this case, there may be a loose interworking between LTE and LTE-U based on RLC-level aggregation with colocated LTE/LTE-U cells, or multiframe across multiple cells and/or base stations, for example.

The techniques described herein are not limited to LTE, and may also be used for various wireless communications systems such as CDMA, TDMA, FDMA, OFDMA, SC-FDMA, and other systems. The terms “system” and “network” are often used interchangeably. A CDMA system may implement a radio technology such as CDMA2000, Universal Terrestrial Radio Access (UTRA), etc. CDMA2000 covers IS-2000, IS-95, and IS-856 standards. IS-2000 Releases 0 and A are commonly referred to as CDMA2000 1x, 1x, etc. IS-856 (TIA-856) is commonly referred to as CDMA2000 1xEV-DO, High Rate Packet Data (HRPD), etc. UTRA includes Wideband CDMA (WCDMA) and other variants of CDMA. A TDMA system may implement a radio technology such as Global System for Mobile Communications (GSM). An OFDMA system may implement a radio technology such as Ultra Mobile Broadband (UMB), Evolved UTRA (E-UTRA), IEEE 802.11 (Wi-Fi), IEEE 802.16 (WiMAX), IEEE 802.20, Flash-OFDM, etc. UTRA and E-UTRA are part of Universal Mobile Telecommuni-

cation System (UMTS). LTE and LTE-Advanced (LTE-A) are new releases of UMTS that use E-UTRA. UTRA, E-UTRA, UMTS, LTE, LTE-A, and GSM are described in documents from an organization named “3rd Generation Partnership Project” (3GPP). CDMA2000 and UMB are described in documents from an organization named “3rd Generation Partnership Project 2” (3GPP2). The techniques described herein may be used for the systems and radio technologies mentioned above as well as other systems and radio technologies. The description below, however, describes an LTE system for purposes of example, and LTE terminology is used in much of the description below, although the techniques are applicable beyond LTE applications. In this description, LTE-Advanced (LTE-A) communications are considered to be a subset of LTE communications, and therefore, references to LTE communications encompass LTE-A communications.

The following description provides examples, and is not limiting of the scope, applicability, or configuration set forth in the claims. Changes may be made in the function and arrangement of elements discussed without departing from the spirit and scope of the disclosure. Various embodiments may omit, substitute, or add various procedures or components as appropriate. For instance, the methods described may be performed in an order different from that described, and various steps may be added, omitted, or combined. Also, features described with respect to certain embodiments may be combined in other embodiments.

Referring first to FIG. 1, a diagram illustrates an example of a wireless communications system or network **100**. The system **100** includes base stations (or cells) **105**, communication devices **115**, and a core network **130**. The base stations **105** may communicate with the communication devices **115** under the control of a base station controller (not shown), which may be part of the core network **130** or the base stations **105** in various embodiments. Base stations **105** may communicate control information and/or user data with the core network **130** through backhaul links **132**. In embodiments, the base stations **105** may communicate, either directly or indirectly, with each other over backhaul links **134**, which may be wired or wireless communication links. The system **100** may support operation on multiple carriers (waveform signals of different frequencies). Multi-carrier transmitters can transmit modulated signals simultaneously on the multiple carriers. For example, each communication link **125** may be a multi-carrier signal modulated according to the various radio technologies described above. Each modulated signal may be sent on a different carrier and may carry control information (e.g., reference signals, control channels, etc.), overhead information, data, etc.

The base stations **105** may wirelessly communicate with the devices **115** via one or more base station antennas. Each of the base station **105** sites may provide communication coverage for a respective geographic area **110**. In some embodiments, base stations **105** may be referred to as a base transceiver station, a radio base station, an access point, a radio transceiver, a basic service set (BSS), an extended service set (ESS), a NodeB, eNodeB (eNB), Home NodeB, a Home eNodeB, or some other suitable terminology. The coverage area **110** for a base station may be divided into sectors making up only a portion of the coverage area (not shown). The system **100** may include base stations **105** of different types (e.g., macro, micro, and/or pico base stations). There may be overlapping coverage areas for different technologies.

In some embodiments, the system **100** may be an LTE/LTE-A network that supports one or more LTE-U modes of

operation or deployment scenarios. In other embodiments, the system **100** may support wireless communications using an unlicensed spectrum and an access technology different from LTE-U, or a licensed spectrum and an access technology different from LTE/LTE-A. The terms evolved Node B (eNB) and user equipment (UE) may be generally used to describe the base stations **105** and devices **115**, respectively. The system **100** may be a Heterogeneous LTE/LTE-A/LTE-U network in which different types of eNBs provide coverage for various geographical regions. For example, each eNB **105** may provide communication coverage for a macro cell, a pico cell, a femto cell, and/or other types of cell. Small cells such as pico cells, femto cells, and/or other types of cells may include low power nodes or LPNs. A macro cell generally covers a relatively large geographic area (e.g., several kilometers in radius) and may allow unrestricted access by UEs with service subscriptions with the network provider. A pico cell would generally cover a relatively smaller geographic area and may allow unrestricted access by UEs with service subscriptions with the network provider. A femto cell would also generally cover a relatively small geographic area (e.g., a home) and, in addition to unrestricted access, may also provide restricted access by UEs having an association with the femto cell (e.g., UEs in a closed subscriber group (CSG), UEs for users in the home, and the like). An eNB for a macro cell may be referred to as a macro eNB. An eNB for a pico cell may be referred to as a pico eNB. And, an eNB for a femto cell may be referred to as a femto eNB or a home eNB. An eNB may support one or multiple (e.g., two, three, four, and the like) cells.

The core network **130** may communicate with the eNBs **105** via a backhaul **132** (e.g., S1, etc.). The eNBs **105** may also communicate with one another, e.g., directly or indirectly via backhaul links **134** (e.g., X2, etc.) and/or via backhaul links **132** (e.g., through core network **130**). The system **100** may support synchronous or asynchronous operation. For synchronous operation, the eNBs may have similar frame and/or gating timing, and transmissions from different eNBs may be approximately aligned in time. For asynchronous operation, the eNBs may have different frame and/or gating timing, and transmissions from different eNBs may not be aligned in time. The techniques described herein may be used for either synchronous or asynchronous operations.

The UEs **115** may be dispersed throughout the system **100**, and each UE may be stationary or mobile. A UE **115** may also be referred to by those skilled in the art as a mobile station, a subscriber station, a mobile unit, a subscriber unit, a wireless unit, a remote unit, a mobile device, a wireless device, a wireless communications device, a remote device, a mobile subscriber station, an access terminal, a mobile terminal, a wireless terminal, a remote terminal, a handset, a user agent, a mobile client, a client, or some other suitable terminology. A UE **115** may be a cellular phone, a personal digital assistant (PDA), a wireless modem, a wireless communication device, a handheld device, a tablet computer, a laptop computer, a cordless phone, a wireless local loop (WLL) station, or the like. A UE may be able to communicate with macro eNBs, pico eNBs, femto eNBs, relays, and the like.

The communications links **125** shown in system **100** may include uplink (UL) transmissions from a mobile device **115** to a base station **105**, and/or downlink (DL) transmissions, from a base station **105** to a mobile device **115**. The downlink transmissions may also be called forward link transmissions while the uplink transmissions may also be

called reverse link transmissions. The downlink transmissions may be made using a licensed spectrum (e.g., LTE), an unlicensed spectrum (e.g., LTE-U), or both (LTE/LTE-U). Similarly, the uplink transmissions may be made using a licensed spectrum (e.g., LTE), an unlicensed spectrum (e.g., LTE-U), or both (LTE/LTE-U).

In some embodiments of the system **100**, various deployment scenarios for LTE-U may be supported including a supplemental downlink mode in which LTE downlink capacity in a licensed spectrum may be offloaded to an unlicensed spectrum, a carrier aggregation mode in which both LTE downlink and uplink capacity may be offloaded from a licensed spectrum to an unlicensed spectrum, and a standalone mode in which LTE downlink and uplink communications between a base station (e.g., eNB) and a UE may take place in an unlicensed spectrum. Base stations **105** as well as UEs **115** may support one or more of these or similar modes of operation. OFDMA communications signals may be used in the communications links **125** for LTE downlink transmissions in an unlicensed spectrum, while SC-FDMA communications signals may be used in the communications links **125** for LTE uplink transmissions in an unlicensed spectrum. Additional details regarding the implementation of LTE-U deployment scenarios or modes of operation in a system such as the system **100**, as well as other features and functions related to the operation of LTE-U, are provided below with reference to FIGS. **2A-32**.

Turning next to FIG. **2A**, a diagram **200** shows examples of a supplemental downlink mode and a carrier aggregation mode for an LTE network that supports LTE-U. The diagram **200** may be an example of portions of the system **100** of FIG. **1**. Moreover, the base station **105-a** may be an example of the base stations **105** of FIG. **1**, while the UEs **115-a** may be examples of the UEs **115** of FIG. **1**.

In the example of a supplemental downlink mode shown in diagram **200**, the base station **105-a** may transmit OFDMA communications signals to a UE **115-a** using a downlink **205**. The downlink **205** may be associated with a frequency F1 in an unlicensed spectrum. The base station **105-a** may transmit OFDMA communications signals to the same UE **115-a** using a bidirectional link **210** and may receive SC-FDMA communications signals from that UE **115-a** using the bidirectional link **210**. The bidirectional link **210** may be associated with a frequency F4 in a licensed spectrum. The downlink **205** in the unlicensed spectrum and the bidirectional link **210** in the licensed spectrum may operate concurrently. The downlink **205** may provide a downlink capacity offload for the base station **105-a**. In some embodiments, the downlink **205** may be used for unicast services (e.g., addressed to one UE) or multicast services (e.g., addressed to several UEs). This scenario may occur with any service provider (e.g., a traditional mobile network operator or MNO) that uses a licensed spectrum and needs to relieve some of the traffic and/or signaling congestion in the licensed spectrum.

In one example of a carrier aggregation mode shown in diagram **200**, the base station **105-a** may transmit OFDMA communications signals to a UE **115-a** using a bidirectional link **215** and may receive SC-FDMA communications signals from the same UE **115-a** using the bidirectional link **215**. The bidirectional link **215** may be associated with the frequency F1 in the unlicensed spectrum. The base station **105-a** may also transmit OFDMA communications signals to the same UE **115-a** using a bidirectional link **220** and may receive SC-FDMA communications signals from the same UE **115-a** using the bidirectional link **220**. The bidirectional link **220** may be associated with a frequency F2 in a licensed

spectrum. The bidirectional link **215** may provide a downlink and uplink capacity offload for the base station **105-a**. Like the supplemental downlink described above, this scenario may occur with any service provider (e.g., MNO) that uses a licensed spectrum and needs to relieve some of the traffic and/or signaling congestion.

In another example of a carrier aggregation mode shown in diagram **200**, the base station **105-a** may transmit OFDMA communications signals to a UE **115-a** using a bidirectional link **225** and may receive SC-FDMA communications signals from the same UE **115-a** using the bidirectional link **225**. The bidirectional link **215** may be associated with the frequency F3 in an unlicensed spectrum. The base station **105-a** may also transmit OFDMA communications signals to the same UE **115-a** using a bidirectional link **230** and may receive SC-FDMA communications signals from the same UE **115-a** using the bidirectional link **230**. The bidirectional link **230** may be associated with the frequency F2 in the licensed spectrum. The bidirectional link **225** may provide a downlink and uplink capacity offload for the base station **105-a**. This example, and those provided above, are presented for illustrative purposes and there may be other similar modes of operation or deployment scenarios that combine LTE and LTE-U for capacity offload.

As described above, the typical service provider that may benefit from the capacity offload offered by using LTE-U (LTE in an unlicensed spectrum) is a traditional MNO with LTE licensed spectrum. For these service providers, an operational configuration may include a bootstrapped mode (e.g., supplemental downlink, carrier aggregation) that uses the LTE primary component carrier (PCC) on the licensed spectrum and the LTE-U secondary component carrier (SCC) on the unlicensed spectrum.

In the supplemental downlink mode, control for LTE-U may be transported over the LTE uplink (e.g., uplink portion of the bidirectional link **210**). One of the reasons to provide downlink capacity offload is because data demand is largely driven by downlink consumption. Moreover, in this mode, there may not be a regulatory impact since the UE is not transmitting in the unlicensed spectrum. In some embodiments, there may be no need to implement listen-before-talk (LBT) or carrier sense multiple access (CSMA) requirements on the UE. However, LBT may be implemented on the base station (e.g., eNB) by, for example, using a periodic (e.g., every 10 milliseconds) clear channel assessment (CCA) and/or a grab-and-relinquish mechanism aligned to a radio frame boundary.

In the carrier aggregation mode, data and control may be communicated in LTE (e.g., bidirectional links **210**, **220**, and **230**) while data may be communicated in LTE-U (e.g., bidirectional links **215** and **225**). The carrier aggregation mechanisms supported when using LTE-U may fall under a hybrid frequency division duplexing-time division duplexing (FDD-TDD) carrier aggregation or a TDD-TDD carrier aggregation with different symmetry across component carriers.

FIG. **2B** shows a diagram **200-a** that illustrates an example of a standalone mode for LTE-U. The diagram **200-a** may be an example of portions of the system **100** of FIG. **1**. Moreover, the base station **105-b** may be an example of the base stations **105** of FIG. **1** and the base station **105-a** of FIG. **2A**, while the UE **115-b** may be an example of the UEs **115** of FIG. **1** and/or the UEs **115-a** of FIG. **2A**.

In the example of a standalone mode shown in diagram **200-a**, the base station **105-b** may transmit OFDMA communications signals to the UE **115-b** using a bidirectional link **240** and may receive SC-FDMA communications sig-

nals from the UE **115-b** using the bidirectional link **240**. The bidirectional link **240** may be associated with the frequency F3 in an unlicensed spectrum described above with reference to FIG. 2A. The standalone mode may be used in non-traditional wireless access scenarios, such as in-stadium access scenarios (e.g., unicast, multicast). The typical service provider for this mode of operation may be a stadium owner, cable company, event host, hotel, enterprise, and/or large corporation that does not have licensed spectrum. For these service providers, an operational configuration for the standalone mode may use the LTE-U PCC on the unlicensed spectrum. Moreover, LBT may be implemented on both the base station and the UE.

Turning next to FIG. 3, a diagram **300** illustrates an example of carrier aggregation when using LTE concurrently in licensed and unlicensed spectrum according to various embodiments. The carrier aggregation scheme in diagram **300** may correspond to the hybrid FDD-TDD carrier aggregation described above with reference to FIG. 2A. This type of carrier aggregation may be used in at least portions of the system **100** of FIG. 1. Moreover, this type of carrier aggregation may be used in the base stations **105** and **105-a** of FIG. 1 and FIG. 2A, respectively, and/or in the UEs **115** and **115-a** of FIG. 1 and FIG. 2A, respectively.

In this example, an FDD (FDD-LTE) may be performed in connection with LTE in the downlink, a first TDD (TDD1) may be performed in connection with LTE-U, a second TDD (TDD2) may be performed in connection with LTE, and another FDD (FDD-LTE) may be performed in connection with LTE in the uplink. TDD1 results in a DL:UL ratio of 6:4, while the ratio for TDD2 is 7:3. On the time scale, the different effective DL:UL ratios are 3:1, 1:3, 2:2, 3:1, 2:2, and 3:1. This example is presented for illustrative purposes and there may be other carrier aggregation schemes that combine the operations of LTE and LTE-U.

FIG. 4A shows a flowchart of a method **400** for concurrent use of LTE in licensed and unlicensed spectrum by a first wireless node (e.g., a base station or eNB) according to various embodiments. The method **400** may be implemented using, for example, the base stations or eNBs **105**, **105-a**, and **105-b** of FIG. 1, FIG. 2A, and FIG. 2B, respectively; and/or the system **100** of FIG. 1 and the portions of the system **200** and/or **200-a** of FIG. 2A and FIG. 2B. In one implementation, one of the base stations or eNBs **105** may execute one or more sets of codes to control the functional elements of the base stations or eNB **105** to perform the functions described below.

At block **405**, a first OFDMA communications signal may be transmitted to a second wireless node (e.g., UE **115**) in a licensed spectrum. At block **410**, a second OFDMA communications signal may be transmitted to the second wireless node in an unlicensed spectrum concurrently with the transmission of the first OFDMA communications signal. In some embodiments, the first and second OFDMA communications signals may be transmitted from at least one base station or eNB.

In some embodiments of the method **400**, the transmission of the second OFDMA communications signal in the unlicensed spectrum may be time-synchronized with the transmission of the first OFDMA communications signal in the licensed spectrum, with a fixed offset between a frame structure of the first OFDMA communications signal and a frame structure of the second OFDMA communications signal. In some embodiments, the fixed offset may be zero or substantially zero.

In some embodiments of the method **400**, a first SC-FDMA communications signal may be received

from the second wireless node in a licensed spectrum concurrently with the transmission of the first and second OFDMA communications signals. The first SC-FDMA communications signal received from the second wireless node in the licensed spectrum may carry signaling or other control information related to the second OFDMA communications signal transmitted in the unlicensed spectrum. The method may include receiving, concurrently with the transmission of the first and second OFDMA communications signals, a second SC-FDMA communications signal from the second wireless node in an unlicensed spectrum. The method may include receiving, concurrently with the transmission of the first and second OFDMA communications signals, a first SC-FDMA communications signal from the in a licensed spectrum and a second SC-FDMA communications signal from the UE in an unlicensed spectrum. In some embodiments, each of the first and second OFDMA communications signals may include an LTE signal.

FIG. 4B shows a flowchart of a method **400-a** for concurrent use of LTE in licensed and unlicensed spectrum by a first wireless node (e.g., a base station or eNB) according to various embodiments. The method **400-a**, like the method **400** above, may be implemented using, for example, the base stations or eNBs **105**, **105-a**, and **105-b** of FIG. 1, FIG. 2A, and FIG. 2B, respectively; and/or the system **100** of FIG. 1 and the portions of the system **200** and/or **200-a** of FIG. 2A and FIG. 2B. In one implementation, one of the base stations or eNBs **105** may execute one or more sets of codes to control the functional elements of the base station or eNB **105** to perform the functions described below.

At block **415**, a first SC-FDMA communications signal may be received from a second wireless node (e.g., UE **115**) in a licensed spectrum.

At block **420**, a second SC-FDMA communications signal may be received from the second wireless node in an unlicensed spectrum concurrently with the reception of the first OFDMA communications signal. In some embodiments, the first and second SC-FDMA communications signals may be received from at least one UE. In some embodiments, each of the first and second SC-FDMA communications signals may include an LTE signal.

FIG. 5A shows a flowchart of a method **500** for concurrent use of LTE in licensed and unlicensed spectrum by a first wireless node (e.g., a UE) according to various embodiments. The method **500** may be implemented using, for example, the UEs **115**, **115-a**, and **115-b** of FIG. 1, FIG. 2A, and FIG. 2B, respectively; and/or the system **100** of FIG. 1 and the portions of the system **200** and/or **200-a** of FIG. 2A and FIG. 2B. In one implementation, one of the UEs **115** may execute one or more sets of codes to control the functional elements of the UE **115** to perform the functions described below.

At block **505**, a first OFDMA communications signal may be received from a second wireless node (e.g., a base station or eNB **105**) in a licensed spectrum.

At block **510**, a second OFDMA communications signal may be received from the second wireless node in an unlicensed spectrum concurrently with the reception of the first OFDMA communications signal. In some embodiments, the first and second OFDMA communications signals may be received at a UE.

In some embodiments of the method **500**, a first SC-FDMA communications signal may be transmitted to the second wireless node in a licensed spectrum concurrently with the reception of the first and second OFDMA communications signals. The first SC-FDMA communications signal received transmitted to the second wireless node in the

licensed spectrum may carry signaling or other control information related to the second OFDMA signal received on the unlicensed spectrum. The method may include transmitting, concurrently with the reception of the first and second OFDMA communications signals, a second SC-FDMA communications signal to the second wireless node in an unlicensed spectrum. The method may include transmitting, concurrently with the reception of the first and second OFDMA communications signals, a first SC-FDMA communications signal to the second wireless node in a licensed spectrum and a second SC-FDMA communications signal to the second wireless node in an unlicensed spectrum. Each of the first and second OFDMA communications signals may include an LTE signal.

FIG. 5B shows a flowchart of a method 500-*a* for concurrent use of LTE in licensed and unlicensed spectrum by a first wireless node (e.g., a UE) according to various embodiments. The method 500-*a*, like the method 500 above, may be implemented using, for example, the UEs 115, 115-*a*, and 115-*b* of FIG. 1, FIG. 2A, and FIG. 2B, respectively; and/or the system 100 of FIG. 1 and the portions of the system 200 and/or 200-*a* of FIG. 2A and FIG. 2B. In one implementation, one of the UEs 115 may execute one or more sets of codes to control the functional elements of the UE 115 to perform the functions described below.

At block 515, a first SC-FDMA communications signal may be transmitted to a second wireless node (e.g., a base station or eNB 105) in a licensed spectrum.

At block 520, a second SC-FDMA communications signal may be transmitted to the second wireless node in an unlicensed spectrum concurrently with the transmission of the first SC-FDMA communications signal. In some embodiments, the first and second SC-FDMA communications signals may be transmitted from a UE. In some embodiments, each of the first and second SC-FDMA communications signals may include an LTE signal.

In some embodiments, a transmitting device such as a base station, eNB 105, UE 115 (or a transmitter of a transmitting device) may use a gating interval to gain access to a channel of the unlicensed spectrum. The gating interval may define the application of a contention-based protocol, such as a Listen Before Talk (LBT) protocol based on the LBT protocol specified in ETSI (EN 301 893). When using a gating interval that defines the application of an LBT protocol, the gating interval may indicate when a transmitting device needs to perform a Clear Channel Assessment (CCA). The outcome of the CCA indicates to the transmitting device whether a channel of the unlicensed spectrum is available or in use. When the CCA indicates that the channel is available (e.g., “clear” for use), the gating interval may allow the transmitting device to use the channel—typically for a predefined period of time. When the CCA indicates that the channel is not available (e.g., in use or reserved), the gating interval may prevent the transmitting device from using the channel for a period of time.

In some cases, it may be useful for a transmitting device to generate a gating interval on a periodic basis and synchronize at least one boundary of the gating interval with at least one boundary of a periodic frame structure. For example, it may be useful to generate a periodic gating interval for a downlink in an unlicensed spectrum, and to synchronize at least one boundary of the periodic gating interval with at least one boundary of a periodic frame structure associated with the downlink. Examples of such synchronization are illustrated in FIGS. 6A, 6B, 6C, and 6D.

FIG. 6A illustrates a first example 600 of a periodic gating interval 605 for transmissions (uplink and/or downlink) in

an unlicensed spectrum. The periodic gating interval 605 may be used by an eNB that supports LTE-U (LTE-U eNB). Examples of such an eNB may be the base stations 105, 105-*a*, and 105-*b* of FIG. 1, FIG. 2A, and FIG. 2B, respectively. The gating interval 605 may be used with the system 100 of FIG. 1 and with portions of the system 200 and/or 200-*a* shown in FIG. 2A and FIG. 2B.

By way of example, the duration of the periodic gating interval 605 is shown to be equal to (or approximately equal to) the duration of the periodic frame structure 610. In some embodiments, the periodic frame structure 610 may be associated with a primary component carrier (PCC) of a downlink. In some embodiments, “approximately equal” means the duration of the periodic gating interval 605 is within a cyclic prefix (CP) duration of the duration of the periodic frame structure 610.

At least one boundary of the periodic gating interval 605 may be synchronized with at least one boundary of the periodic frame structure 610. In some cases, the periodic gating interval 605 may have boundaries that are aligned with the frame boundaries of the periodic frame structure 610. In other cases, the periodic gating interval 605 may have boundaries that are synchronized with, but offset from, the frame boundaries of the periodic frame structure 610. For example, the boundaries of the periodic gating interval 605 may be aligned with subframe boundaries of the periodic frame structure 610, or with subframe midpoint boundaries (e.g., the midpoints of particular subframes) of the periodic frame structure 610.

In some cases, each periodic frame structure 610 may include an LTE radio frame (e.g., an LTE radio frame (N-1), an LTE radio frame (N), or an LTE radio frame (N+1)). Each LTE radio frame may have a duration of ten milliseconds, and the periodic gating interval 605 may also have a duration of ten milliseconds. In these cases, the boundaries of the periodic gating interval 605 may be synchronized with the boundaries (e.g., frame boundaries, subframe boundaries, or subframe midpoint boundaries) of one of the LTE radio frames (e.g., the LTE radio frame (N)).

FIG. 6B illustrates a second example 600-*a* of a periodic gating interval 605-*a* for transmissions (uplink and/or downlink) in an unlicensed spectrum. The periodic gating interval 605-*a* may be used by an eNB that supports LTE-U (LTE-U eNB). Examples of such an eNB may be the base stations 105, 105-*a*, and 105-*b* of FIG. 1, FIG. 2A, and FIG. 2B, respectively. The gating interval 605 may be used with the system 100 of FIG. 1 and with portions of the system 200 and/or 200-*a* shown in FIG. 2A and FIG. 2B.

By way of example, the duration of the periodic gating interval 605-*a* is shown to be a sub-multiple of (or an approximate sub-multiple of) the duration of the periodic frame structure 610. In some embodiments, an “approximate sub-multiple of” means the duration of the periodic gating interval 605-*a* is within a cyclic prefix (CP) duration of the duration of a sub-multiple of (e.g., half) the periodic frame structure 610.

At least one boundary of the periodic gating interval 605-*a* may be synchronized with at least one boundary of the periodic frame structure 610. In some cases, the periodic gating interval 605-*a* may have a leading or trailing boundary that is aligned with a leading or trailing frame boundary of the periodic frame structure 610. In other cases, the periodic gating interval 605-*a* may have boundaries that are synchronized with, but offset from, each of the frame boundaries of the periodic frame structure 610. For example, the boundaries of the periodic gating interval 605-*a* may be aligned with subframe boundaries of the periodic frame

structure **610**, or with subframe midpoint boundaries (e.g., the midpoints of particular subframes) of the periodic frame structure **610**.

In some cases, each periodic frame structure **610** may include an LTE radio frame (e.g., an LTE radio frame (N-1), an LTE radio frame (N), or an LTE radio frame (N+1)). Each LTE radio frame may have a duration of ten milliseconds, and the periodic gating interval **605-a** may have a duration of five milliseconds. In these cases, the boundaries of the periodic gating interval **605-a** may be synchronized with the boundaries (e.g., frame boundaries, subframe boundaries, or subframe midpoint boundaries) of one of the LTE radio frames (e.g., LTE radio frame (N)). The periodic gating interval **605-a** may then be repeated, for example, every periodic frame structure **610**, more than once every periodic frame structure **610** (e.g., twice), or once every Nth periodic frame structure **610** (e.g., for N=2, 3, . . .).

FIG. 6C illustrates a third example **600-b** of a periodic gating interval **605-b** for transmissions (uplink and/or downlink) in an unlicensed spectrum. The periodic gating interval **605-b** may be used by an eNB that supports LTE-U (LTE-U eNB). Examples of such an eNB may be the base stations **105**, **105-a**, and **105-b** of FIG. 1, FIG. 2A, and FIG. 2B, respectively. The gating interval **605** may be used with the system **100** of FIG. 1 and with portions of the system **200** and/or **200-a** shown in FIG. 2A and FIG. 2B.

By way of example, the duration of the periodic gating interval **605-b** is shown to be an integer multiple of (or an approximate integer multiple of) the duration of the periodic frame structure **610**. In some embodiments, an "approximate integer multiple of" means the duration of the periodic gating interval **605-b** is within a cyclic prefix (CP) duration of an integer multiple of (e.g., double) the duration of the periodic frame structure **610**.

At least one boundary of the periodic gating interval **605-b** may be synchronized with at least one boundary of the periodic frame structure **610**. In some cases, the periodic gating interval **605-b** may have a leading boundary and a trailing boundary that are aligned with respective leading or trailing frame boundaries of the periodic frame structure **610**. In other cases, the periodic gating interval **605-b** may have boundaries that are synchronized with, but offset from, the frame boundaries of the periodic frame structure **610**. For example, the boundaries of the periodic gating interval **605-b** may be aligned with subframe boundaries of the periodic frame structure **610**, or with subframe midpoint boundaries (e.g., the midpoints of particular subframes) of the periodic frame structure **610**.

In some cases, each periodic frame structure **610** may include an LTE radio frame (e.g., an LTE radio frame (N-1), an LTE radio frame (N), or an LTE radio frame (N+1)). Each LTE radio frame may have a duration of ten milliseconds, and the periodic gating interval **605-b** may have a duration of twenty milliseconds. In these cases, the boundaries of the periodic gating interval **605-b** may be synchronized with the boundaries (e.g., frame boundaries, subframe boundaries, or subframe midpoint boundaries) of one or two of the LTE radio frames (e.g., LTE radio frame (N) and LTE radio frame (N+1)).

FIG. 6D illustrates a fourth example **600-c** of a periodic gating interval **605-c** for transmissions (uplink and/or downlink) in an unlicensed spectrum. The periodic gating interval **605-c** may be used by an eNB that supports LTE-U (LTE-U eNB). Examples of such an eNB may be the base stations **105**, **105-a**, and **105-b** of FIG. 1, FIG. 2A, and FIG. 2B, respectively. The gating interval **605** may be used with the

system **100** of FIG. 1 and with portions of the system **200** and/or **200-a** shown in FIG. 2A and FIG. 2B.

By way of example, the duration of the periodic gating interval **605-c** is shown to be a sub-multiple of (or an approximate sub-multiple of) the duration of the periodic frame structure **610**. The sub-multiple may be one-tenth of the duration of the periodic frame structure **610**.

At least one boundary of the periodic gating interval **605-c** may be synchronized with at least one boundary of the periodic frame structure **610**. In some cases, the periodic gating interval **605-c** may have a leading or trailing boundary that is aligned with a leading or trailing frame boundary of the periodic frame structure **610**. In other cases, the periodic gating interval **605-c** may have boundaries that are synchronized with, but offset from, each of the frame boundaries of the periodic frame structure **610**. For example, the boundaries of the periodic gating interval **605-c** may be aligned with subframe boundaries of the periodic frame structure **610**, or with subframe midpoint boundaries (e.g., the midpoints of particular subframes) of the periodic frame structure **610**.

In some cases, each periodic frame structure **610** may include an LTE radio frame (e.g., an LTE radio frame (N-1), an LTE radio frame (N), or an LTE radio frame (N+1)). Each LTE radio frame may have a duration of ten milliseconds, and the periodic gating interval **605-c** may have a duration of one millisecond (e.g., the duration of one subframe). In these cases, the boundaries of the periodic gating interval **605-c** may be synchronized with the boundaries (e.g., frame boundaries, subframe boundaries, or subframe midpoint boundaries) of one of the LTE radio frames (e.g., LTE radio frame (N)). The periodic gating interval **605-c** may then be repeated, for example, every periodic frame structure **610**, more than once every periodic frame structure **610**, or once every Nth periodic frame structure **610** (e.g., for N=2, 3, . . .).

FIG. 7A illustrates a fifth example **700** of a periodic gating interval **605-d-1** for transmissions (uplink and/or downlink) in an unlicensed spectrum. The periodic gating interval **605-d-1** may be used by an eNB that supports LTE-U (LTE-U eNB). Examples of such an eNB may be the base stations **105**, **105-a**, and **105-b** of FIG. 1, FIG. 2A, and FIG. 2B, respectively. The gating interval **605-d-1** may be used with the system **100** of FIG. 1 and with portions of the system **200** and/or **200-a** shown in FIG. 2A and FIG. 2B.

By way of example, the duration of the periodic gating interval **605-d-1** is shown to be equal to (or approximately equal to) the duration of a periodic frame structure **610-a**. In some embodiments, the periodic frame structure **610-a** may be associated with a primary component carrier (PCC) of a downlink. The boundaries of the periodic gating interval **605-d-1** may be synchronized with (e.g., aligned with) the boundaries of the periodic frame structure **610-a**.

The periodic frame structure **610-a** may include an LTE radio frame having ten subframes (e.g., SF0, SF1, . . . , SF9). Subframes SF0 through SF8 may be downlink (D) subframes **710**, and subframe SF9 may be a special (S') subframe **715**. The D and/or S' subframes **710** and/or **715** may collectively define a channel occupancy time of the LTE radio frame, and at least part of the S' subframe **715** may define a channel idle time. Under the current LTE standard, an LTE radio frame may have a maximum channel occupancy time (ON time) between one and 9.5 milliseconds, and a minimum channel idle time (OFF time) of five percent of the channel occupancy time (e.g., a minimum of 50 microseconds). To ensure compliance with the LTE standard, the periodic gating interval **605-d** may abide by these

requirements of the LTE standard by providing a 0.5 millisecond guard period (i.e., OFF time) as part of the S' subframe **715**.

Because the S' subframe **715** has a duration of one millisecond, it may include one or more CCA slots **720** (e.g., time slots) in which the transmitting devices contending for a particular channel of an unlicensed spectrum may perform their CCAs. When a transmitting device's CCA indicates the channel is available, but the device's CCA is completed before the end of the periodic gating interval **605-d-1**, the device may transmit one or more signals to reserve the channel until the end of the periodic gating interval **605-d-1**. The one or more signals may in some cases include Channel Usage Pilot Signals (CUPS) or Channel Usage Beacon Signals (CUBS) **730**. CUBS **730** are described in detail later in this description, but may be used for both channel synchronization and channel reservation. That is, a device that performs a CCA for the channel after another device begins to transmit CUBS on the channel may detect the energy of the CUBS **730** and determine that the channel is currently unavailable.

Following a transmitting device's successful completion of a CCA for a channel and/or the transmission of CUBS **730** over a channel, the transmitting device may use the channel for up to a predetermined period of time (e.g., one gating interval or one LTE radio frame) to transmit a waveform (e.g., an LTE-based waveform **740**).

FIG. **7B** illustrates a sixth example **705** of a periodic gating interval **605-d-2** for transmissions (uplink and/or downlink) in an unlicensed spectrum. The periodic gating interval **605-d-2** may be used by an eNB or UE that supports LTE-U (LTE-U eNB or LTE-U UE). Examples of such an eNB may be the base stations **105**, **105-a**, and **105-b** of FIG. **1**, FIG. **2A**, and FIG. **2B**, respectively, and examples of such a UE may be the UEs **115**, **115-a**, and **115-b** of FIG. **1**. The gating interval **605-d-2** may be used with the system **100** of FIG. **1** and with portions of the system **200** and/or **200-a** shown in FIG. **2A** and FIG. **2B**.

By way of example, the duration of the periodic gating interval **605-d-2** is shown to be equal to (or approximately equal to) the duration of a periodic frame structure **610-a**. In some embodiments, the periodic frame structure **610-a** may be associated with a primary component carrier (PCC) of a downlink. The boundaries of the periodic gating interval **605-d-2** may be synchronized with (e.g., aligned with) the boundaries of the periodic frame structure **610-a**.

The periodic frame structure **610-b** may include an LTE radio frame having ten subframes (e.g., SF0, SF1, . . . , SF9). Subframes SF0 through SF4 may be downlink (D) subframes **710**; subframe SF5 may be a special (S) subframe **735**; subframes SF6 through SF8 may be uplink (U) subframes **745**; and subframe SF9 may be a special (S') subframe **715**. The D, S, U, and/or S' subframes **710**, **735**, **745**, and/or **715** may collectively define a channel occupancy time of the LTE radio frame, and at least part of the S subframe **735** and/or S' subframe **715** may define a channel idle time. Under the current LTE standard, an LTE radio frame may have a maximum channel occupancy time (ON time) between one and 9.5 milliseconds, and a minimum channel idle time (OFF time) of five percent of the channel occupancy time (e.g., a minimum of 50 microseconds). To ensure compliance with the LTE standard, the periodic gating interval **605-d-2** may abide by these requirements of the LTE standard by providing a 0.5 millisecond guard period or silence period (i.e., OFF time) as part of the S subframe **735** and/or S' subframe **715**.

Because the S' subframe **715** has a duration of one millisecond, it may include one or more CCA slots **720** (e.g., time slots) in which the transmitting devices contending for a particular channel of an unlicensed spectrum may perform their CCAs. When a transmitting device's CCA indicates the channel is available, but the device's CCA is completed before the end of the periodic gating interval **605-d-2**, the device may transmit one or more signals to reserve the channel until the end of the periodic gating interval **605-d-2**. The one or more signals may in some cases include CUPS or CUBS **730**. CUBS **730** are described in detail later in this description, but may be used for both channel synchronization and channel reservation. That is, a device that performs a CCA for the channel after another device begins to transmit CUBS on the channel may detect the energy of the CUBS **730** and determine that the channel is currently unavailable.

Following a transmitting device's successful completion of a CCA for a channel and/or the transmission of CUBS **730** over a channel, the transmitting device may use the channel for up to a predetermined period of time (e.g., one gating interval or one LTE radio frame) to transmit a waveform (e.g., an LTE-based waveform **740**).

When a channel of the unlicensed spectrum is reserved, for example, by a base station or eNB for a gating interval or LTE radio frame, the base station or eNB may in some cases reserve the channel for Time Domain Multiplexing (TDM) use. In these examples, the base station or eNB may transmit data in a number of D subframes (e.g., subframes SF0 through SF4) and then allow a UE with which it is communicating to perform a CCA **750** (e.g., an uplink CCA) in an S subframe (e.g., subframe SF5). When the CCA **750** is successful, the UE may transmit data to the base station or eNB in a number of U subframes (e.g., subframes SF6 through SF8).

When a gating interval defines an application of the LBT protocol specified in ETSI (EN 301 893), the gating interval may take the form of an LBT Fixed Based Equipment (LBT-FBE) gating interval or an LBT Load Based Equipment (LBT-LBE) gating interval. An LBT-FBE gating interval may have a fixed/periodic timing and may not be directly influenced by traffic demand (e.g., its timing can be changed through reconfiguration). In contrast, an LBT-LBE gating interval may not have a fixed timing (i.e., be asynchronous) and may be largely influenced by traffic demand. FIGS. **6A**, **6B**, **6C**, **6D**, and **7** each illustrate an example of a periodic gating interval **605**, which periodic gating interval **605** may be an LBT-FBE gating interval. A potential advantage of the periodic gating interval **605** described with reference to FIG. **6A** is that it may preserve the ten millisecond LTE radio frame structure defined in the current LTE specification. However, when the duration of a gating interval is less than the duration of an LTE radio frame (e.g., as described with reference to FIG. **6B** or **6D**), the advantages of preserving the LTE radio frame structure no longer exist and an LBT-LBE gating interval may be advantageous. A potential advantage of using an LBT-LBE gating interval is that it may retain the subframe structure of LTE PHY channels, without any symbol puncturing at the beginning or end of the gating interval. However, a potential disadvantage of using an LBT-LBE gating interval is not being able to synchronize the use of a gating interval between the different eNBs of an LTE-U operator (e.g., because each eNB uses a random back-off time for an extended CCA).

FIG. **8** is a flow chart illustrating an example of a method **800** for wireless communications. For clarity, the method **800** is described below with reference to one of the eNBs

105 or UEs 115 shown in FIGS. 1, 2A, and/or 2B. In one implementation, one of the eNBs 105 or UEs 115 may execute one or more sets of codes to control the functional elements of the eNB 105 or UE 115 to perform the functions described below.

At block 805, a periodic gating interval for a downlink in an unlicensed spectrum may be generated.

At block 810, at least one boundary of the periodic gating interval may be synchronized with at least one boundary of a periodic frame structure associated with a PCC of the downlink. In some embodiments, the PCC may include a carrier in a licensed spectrum.

In some embodiments, the periodic gating interval may include an LBT frame and/or the periodic frame structure may include an LTE radio frame.

In some embodiments, the duration of the periodic gating interval may be an integer multiple of the duration of the periodic frame structure. Examples of such an embodiment are described, supra, with reference to FIGS. 6A and 6C. In other embodiments, the duration of the periodic gating interval may be a sub-multiple of the duration of the periodic frame structure. Examples of such an embodiment are described, supra, with reference to FIGS. 6B and 6D.

Thus, the method 800 may provide for wireless communications. It should be noted that the method 800 is just one implementation and that the operations of the method 800 may be rearranged or otherwise modified such that other implementations are possible.

FIGS. 9A, 9B, 9C, and 9D illustrate examples 900, 900-a, 920, 950 of how a contention-based protocol such as LBT may be implemented within an S' subframe 725-a of a gating interval, such as an S' subframe of the ten millisecond gating interval 605-d-1 or 605-d-2 described with reference to FIG. 7A or 7B. The contention-based protocol may be used with, for example, the base stations 105, 105-a, and 105-b of FIG. 1, FIG. 2A, and FIG. 2B, respectively. The contention-based protocol may be used with the system 100 of FIG. 1 and with portions of the system 200 and/or 200-a shown in FIG. 2A and FIG. 2B.

Referring now to FIGS. 9A and 9B, there is shown an example 900/900-a of an S' subframe 725-a-1 having a guard period 905 and a CCA period 910. By way of example, each of the guard period 905 and the CCA period 910 may have a duration of 0.5 milliseconds and include seven OFDM symbol positions 915. As shown in FIG. 9B, each of the OFDM symbol positions 915 in the CCA period 910 may be transformed into a CCA slot 720-a upon an eNB selecting the OFDM symbol position 915 for performing CCA. In some cases, the same or different ones of the OFDM symbol positions 915 may be pseudo-randomly selected by ones of multiple eNBs, thereby providing a sort of CCA time dithering. The eNBs may be operated by a single LTE-U operator or different LTE-U operators. An OFDM symbol position 915 may be pseudo-randomly selected in that an eNB may be configured to select different ones of the OFDM symbol positions at different times, thereby giving each of the multiple eNBs an opportunity to select the OFDM symbol position 915 that occurs earliest in time. This may be advantageous in that the first eNB to perform a successful CCA has an opportunity to reserve a corresponding channel or channels of an unlicensed spectrum, and an eNB's pseudo-random selection of an OFDM symbol position 915 for performing CCA ensures that it has the same chance of performing a successful CCA as every other eNB. In the case of eNBs operated by a single LTE-U operator, the eNBs may in some cases be configured to select the same CCA slot 720-a.

FIG. 9C shows an example 920 of an S' subframe 725-a-2 having a guard period 905 and a CCA period 910. By way of example, each the guard period 905 may have a duration of 0.5 milliseconds and include seven OFDM symbol positions. The CCA period 910 may include one OFDM symbol position or a fraction of one OFDM symbol position, which may include one or more CCA slots, each having a duration less than or equal to an OFDM symbol position. The CCA period 910 may be followed by a CUBS period 930. The guard period 905 may be preceded by a shortened D subframe 925. In some examples, all of the wireless nodes (e.g., all base stations or eNBs) associated with an operator or public land mobile network (PLMN) may perform a CCA at the same time during the CCA period 910. The S' subframe 725-a-2 shown in FIG. 9C may be useful in scenarios where an operator operates asynchronously with respect to other operators with which it competes for access to an unlicensed spectrum.

FIG. 9D shows an example 950 of an S' subframe 725-a-3 having a shortened D subframe 925, a CCA period 910, and a CUBS period 930. The CCA period 910 may include one OFDM symbol position or a fraction of one OFDM symbol position, which may include one or more CCA slots, each having a duration less than or equal to an OFDM symbol position. The CCA period 910 may be followed by a CUBS period 930. In some examples, all of the wireless nodes (e.g., all base stations or eNBs) associated with an operator or public land mobile network (PLMN) may perform a CCA at the same time during the CCA period 910. The S' subframe 725-a-3 shown in FIG. 9D may be useful in scenarios where an operator operates asynchronously with respect to other operators with which it competes for access to an unlicensed spectrum, and where the S' subframe 725-a-3 is used in a TDM context, such as with the gating interval 605-d-2. When used in a TDM context, a silent period may provided in an S subframe of a frame of which the S' subframe 725-a-3 forms a part.

FIGS. 10A and 10B provide examples of how an S' subframe such as the S' subframe 725-a described with reference to FIGS. 9A and/or 9B may be used in conjunction with a current gating interval 605. By way of example, the current gating intervals 605-e, 605-g shown in FIGS. 10A and 10B may be examples of the ten millisecond gating interval 605-d described with reference to FIG. 7. The use of S' subframes in conjunction with a current gating interval may be handled by, for example, the base stations 105, 105-a, and 105-b of FIG. 1, FIG. 2A, and FIG. 2B, respectively. The use of S' subframes in conjunction with a current gating interval may be handled may be the system 100 of FIG. 1 and with portions of the system 200 and/or 200-a shown in FIG. 2A and/or FIG. 2B.

FIG. 10A provides an example 1000 in which an S' subframe is included as a last subframe of the current gating interval 605-e. Thus, the guard period 905-a and the CCA period 910-a of the S' subframe occur at the end of the current gating interval 605-e, just prior to a trailing boundary of the current gating interval 605-e and the start of a next transmission interval 605-f. The next transmission interval 605-f may be gated ON or gated OFF for a downlink transmission of each of a number of transmitting devices, depending on whether a CCA performed by the transmitting device indicates that unlicensed spectrum is available or unavailable during the next transmission interval 605-f. In some cases, the next transmission interval 605-f may also be a next gating interval.

FIG. 10B provides an example 1000-a in which an S' subframe is included as a first subframe of the current gating

interval **605-g**. Thus, the guard period **905-b** and the CCA period **910-b** of the S' subframe occur at the start of the current gating interval **605-g**, just after a leading boundary of the current gating interval **605-g**. The next transmission interval **605-h** may be gated ON or gated OFF for a downlink transmission of each of a number of transmitting devices, depending on whether a CCA performed by the transmitting device indicates that unlicensed spectrum is available or unavailable during the next transmission interval **605-f**. In some cases, the next transmission interval **605-h** may also be a next gating interval.

FIG. **10C** provides an example **1000-b** of how the performance of CCAs for an unlicensed spectrum (or a channel of the unlicensed spectrum) may be synchronized across multiple eNBs **105**. By way of example, the multiple eNBs **105** may include an LTE-U eNB1 and an LTE-U eNB2. The performance of CCAs may be provided by, for example, the base stations **105**, **105-a**, and **105-b** of FIG. **1**, FIG. **2A**, and FIG. **2B**, respectively. The performance of CCAs may be used in the system **100** of FIG. **1** and with portions of the system **200** and/or **200-a** shown in FIG. **2A** and/or FIG. **2B**.

Because of synchronization between the eNB1 and the eNB2, an S' subframe **725-b** within a current gating interval of the eNB1 may be synchronized with an S' subframe **725-c** within a current gating interval of the eNB2. Also, and because of a synchronized pseudo-random CCA slot selection processes implemented by each eNB, the eNB2 may select a CCA slot **720-c** that occurs at a different time (e.g., different OFDM symbol position) than the CCA slot **720-b** selected by eNB1. For example, the eNB1 may select a CCA slot **720-b** aligned with the fifth OFDM symbol position of the aligned CCA periods of the S' subframes **725-b** and **725-c**, and the eNB2 may select a CCA slot **720-c** aligned with the third OFDM symbol position of the aligned CCA periods.

A next transmission interval following the synchronized S' subframes **725-b** and **725-c** may begin after the CCA periods of the S' subframes **725-b** and **725-c** and start with a D subframe, as shown. Because the CCA slot **720-c** of the eNB2 is scheduled first in time, the eNB2 has a chance to reserve the next transmission interval before the eNB1 has a chance to reserve the next transmission interval. However, because of the pseudo-random CCA slot selection process implemented by each of eNB1 and eNB2, the eNB1 may be provided the first chance to reserve a later transmission interval (e.g., because its CCA slot may occur at an earlier time than the CCA slot of the eNB2 in a later gating interval).

By way of example, FIG. **10C** shows there is WiFi transmission (Tx) activity that coincides with a portion of the aligned CCA periods of the S' subframes **725-b** and **725-c**. Because of the timing of the CCA slot **720-c** selected by the eNB2, the eNB2 may determine as a result of performing its CCA that the unlicensed spectrum is unavailable, and may gate OFF a downlink transmission **1005-a** in the unlicensed spectrum for the next transmission interval. A downlink transmission of the eNB2 may therefore be blocked as a result of the WiFi Tx activity occurring during performance of the eNB2's CCA.

During the CCA slot **720-b**, the eNB1 may perform its CCA. Because of the timing of the CCA slot **720-b** selected by the eNB1, the eNB1 may determine as a result of performing its CCA that the unlicensed spectrum is available (e.g., because the WiFi Tx activity does not occur during the CCA slot **720-b**, and because the eNB2 was not able to reserve the next transmission interval at an earlier time). The eNB1 may therefore reserve the next transmission interval

and gate ON a downlink transmission **1005** in the unlicensed spectrum for the next transmission interval. Methods for reserving the unlicensed spectrum (or a channel of the unlicensed spectrum) are described in detail later in this description.

FIGS. **9A**, **9B**, **10A**, **10B**, and **10C** provide examples of how a CCA slot **720** may be selected in the context of a ten millisecond gating interval, such as the gating interval **605-d** described with reference to FIG. **7**. In contrast, FIGS. **10D**, **10E**, **10F**, and **10G** provide examples of how a CCA slot **720** may be selected in the context of a one or two millisecond gating interval. A gating interval of ten milliseconds may provide advantages such as a low gating interval overhead in the presence of low WiFi activity, and an ability to retain the subframe-based PHY channel design of existing LTE channels. However, it may have the disadvantage of a long channel idle time (e.g., 0.5+ milliseconds, depending on CCA delay induced by CCA dithering), which may provide a WiFi node with short contention window a transmit opportunity (e.g., a transmit opportunity during the guard period **905** described with reference to FIGS. **9A** and **9B**). It may also have the disadvantage of delaying a downlink transmission at least ten milliseconds when a CCA is not successful. A gating interval of, for example, one or two milliseconds may lead to a higher gating interval overhead, and may require more extensive changes to the LTE PHY channel design to support sub-millisecond transmit durations. However, a gating interval of perhaps one or two milliseconds may mitigate or eliminate the afore-mentioned disadvantages associated with a ten millisecond gating interval.

FIG. **10D** provides an example **1000-c** of a one millisecond gating interval **605-i**. A one millisecond gating interval may be used by the base stations **105**, **105-a**, and **105-b** of FIG. **1**, FIG. **2A**, and FIG. **2B**, respectively. The one millisecond gating interval may be used in the system **100** of FIG. **1** and with portions of the system **200** and/or **200-a** shown in FIG. **2A** and/or FIG. **2B**.

The current LTE specification requires a channel occupancy time (ON time) \geq one millisecond, and a channel idle time five percent of the channel occupancy time. Thus, the current LTE specification dictates a minimum gating interval duration of 1.05 milliseconds. However, if the LTE specification could be relaxed to require a minimum channel occupancy time of perhaps 0.95 milliseconds, then a one millisecond gating interval would be possible.

As shown in FIG. **10D**, a gating interval **605-i** of one millisecond may include 14 OFDM symbols (or symbol positions). When a successful CCA is performed during a CCA slot **720-d** preceding the gating interval **605-i**, a downlink transmission may occur during the first 13 OFDM symbols of the gating interval **605-i**. Such a downlink transmission may have a duration (or channel occupancy time) of 929 microseconds. In accord with the current LTE standard, a channel occupancy time of 929 microseconds would require a channel idle time **905-a** of 48 microseconds, which is less than the 71.4 microsecond duration of one OFDM symbol. As a result, the channel idle time **905-a** of 48 microseconds, as well as one or more CCA slots **720-d**, may be provided during the 14th OFDM symbol position. In some cases, two CCA slots **720-d** having a total duration of 20 microseconds may be provided during the 14th OFDM symbol position, thereby enabling some amount of CCA randomization (dithering). Of note, each CCA slot **720-d** in the example **1000-c** has a duration of less than one OFDM symbol.

Because the CCA slots **720-d** are positioned at the end of the one millisecond gating interval **605-i** or subframe shown in FIG. **10D**, the gating interval **605-i** is common reference signal (CRS) friendly. An example **1000-d** of a one millisecond gating interval **605-j** that is UE-specific reference signal (UERS) friendly is shown in FIG. **10E**. Similar to the gating interval **605-i**, the gating interval **605-j** includes 14 OFDM symbols. However, the channel idle time **905-b** and CCA slots **720-e** are provided in the first OFDM symbol position. A successful CCA performed during a CCA slot **720-e** of the current gating interval **605-j** thereby enables the unlicensed spectrum to be reserved, and enables a downlink transmission to be made, in the current gating interval. The next transmission interval is therefore included within the current gating interval.

FIG. **10F** provides an example **1000-e** of a two millisecond gating interval **605-k**. A two millisecond gating interval may be used by the base stations **105**, **105-a**, and **105-b** of FIG. **1**, FIG. **2A**, and FIG. **2B**, respectively. The two millisecond gating interval may be used in the system **100** of FIG. **1** and with portions of the system **200** and/or **200-a** shown in FIG. **2A** and/or FIG. **2B**.

In contrast to the one millisecond gating intervals **605-i** and **605-j**, the two millisecond gating interval **605-k** complies with the current LTE specification requirements for maximum channel occupancy time and minimum channel idle time.

As shown, the gating interval **605-k** may include a D subframe **710-a** and an S' subframe **725-d**. However, the S' subframe is configured somewhat differently than previously described S' subframes. More particularly, the first 12 OFDM symbol positions of the S' subframe, as well as the 14 OFDM symbol positions of the preceding D subframe, may be used for a downlink transmission upon performing a successful CCA during a CCA slot **720-f** preceding the gating interval **605-k**. The channel occupancy time may therefore be 1.857 milliseconds, requiring a channel idle time **905-c** of 96 microseconds. The channel idle time **905-c** may therefore occupy the 13th OFDM symbol position of the S' subframe and part of the 14th OFDM symbol position of the S' subframe. However, the remaining duration of the 14th OFDM symbol position may be filled, at least in part, by a number of CCA slots **720-f**. In some cases, the number of CCA slots **720-f** may be three CCA slots **720-f**, which provides a slightly greater amount of CCA randomization (dithering) than the one millisecond gating intervals described with reference to FIGS. **10D** and **10E**.

Because the CCA slots **720-f** are positioned at the end of the two millisecond gating interval **605-k** shown in FIG. **10F**, the gating interval **605-k** is CRS friendly. An example **1000-f** of a two millisecond gating interval **605-l** that is UERS friendly is shown in FIG. **10G**. Similar to the gating interval **605-k**, the gating interval **605-l** includes a D subframe **725-e** and an S' subframe **710-b**. However, the temporal order of the subframes is reversed, with the S' subframe **710-b** occurring first in time and the D subframe **725-e** occurring later in time. Furthermore, the channel idle time **905-d** and CCA slots **720-g** are provided in the first OFDM symbol position of the S' subframe **710-b**. A successful CCA performed during a CCA slot **720-g** of the current gating interval **605-l** thereby enables the unlicensed spectrum to be reserved, and enables a downlink transmission to be made, in the current gating interval. The next transmission interval is therefore included within the current gating interval.

FIG. **11** is a flow chart illustrating an example of a method **1100** for wireless communications. For clarity, the method **1100** is described below with reference to one of the eNBs

105 shown in FIGS. **1**, **2A**, and/or **2B**. In one implementation, one of the eNBs **105** may execute one or more sets of codes to control the functional elements of the eNB **105** to perform the functions described below.

At block **1105**, a CCA is performed for another unlicensed spectrum in a current gating interval to determine whether the unlicensed spectrum is available for a downlink transmission in a next transmission interval. Performing the CCA for the unlicensed spectrum may in some cases involve performing the CCA for one or more channels of the unlicensed spectrum. In some cases, the next transmission interval may be a next gating interval. In other cases, the next transmission interval may be included within the current gating interval. In still other cases, such as cases in which an asynchronous LBT-LBE gating interval is used, the next transmission interval may follow the current gating interval but not be part of a next gating interval.

At block **1110**, and when a determination is made that the unlicensed spectrum is unavailable, a downlink transmission in the unlicensed spectrum may be gated OFF for the next transmission interval. Otherwise, when a determination is made that the unlicensed spectrum is available, a downlink transmission in the unlicensed spectrum may be gated ON for the next transmission interval.

In some embodiments of the method **1100**, the CCA may be performed during a first subframe or first or second OFDM symbol position of the current gating interval. In other embodiments of the method **1100**, the CCA may be performed during a last subframe or last OFDM symbol position of the current gating interval.

In some embodiments of the method **1100**, performance of the CCA may be synchronized across multiple eNBs, including multiple eNBs operated by a single LTE-U operator or by different LTE-U operators.

Thus, the method **1100** may provide for wireless communications. It should be noted that the method **1100** is just one implementation and that the operations of the method **1100** may be rearranged or otherwise modified such that other implementations are possible.

FIG. **12A** is a flow chart illustrating yet another example of a method **1200** for wireless communications. For clarity, the method **1200** is described below with reference to one of the eNBs **105** shown in FIGS. **1**, **2A**, and/or **2B**. In one implementation, one of the eNBs **105** may execute one or more sets of codes to control the functional elements of the eNB **105** to perform the functions described below.

At block **1205**, CCA slots may be synchronized across multiple base stations (e.g., LTE-U eNBs **105**) to determine an availability of an unlicensed spectrum (or at least one channel of the unlicensed spectrum) for downlink transmissions in a next transmission interval.

In some embodiments, the CCA slots may be located in a first subframe or a first or second OFDM symbol position of a current gating interval. In other embodiments, the CCA slots may be located in a last subframe or last OFDM symbol position of a current gating interval.

In some embodiments, such as embodiments in which a gating interval has a duration of ten milliseconds, the interval between commencement of adjacent CCA slots may be approximately the duration of an OFDM symbol. For purposes of this description, "approximately the duration of the OFDM symbol" includes equal to the duration of an OFDM symbol. An example in which the interval between commencement of adjacent CCA slots may be approximately the duration of an OFDM symbol is shown in FIG. **9B**.

Thus, the method **1200** may provide for wireless communications. It should be noted that the method **1200** is just one implementation and that the operations of the method **1200** may be rearranged or otherwise modified such that other implementations are possible.

FIG. **12B** is a flow chart illustrating another example of a method **1200-a** for wireless communications. For clarity, the method **1200-a** is described below with reference to one of the eNBs **105** shown in FIGS. **1**, **2A**, and/or **2B**. In one implementation, one of the eNBs **105** may execute one or more sets of codes to control the functional elements of the eNB **105** to perform the functions described below.

At block **1215**, CCA slots may be synchronized across multiple base stations (e.g., LTE-U eNBs **105**) to determine an availability of an unlicensed spectrum (or at least one channel of the unlicensed spectrum) for downlink transmissions in a next transmission interval.

In some embodiments, the CCA slots may be located in a first subframe or a first or second OFDM symbol position of a current gating interval. In other embodiments, the CCA slots may be located in a last subframe or last OFDM symbol position of a current gating interval.

In some embodiments, such as embodiments in which a gating interval has a duration of ten milliseconds, the interval between commencement of adjacent CCA slots may be approximately the duration of an OFDM symbol. An example in which the interval between commencement of adjacent CCA slots may be approximately a duration of an OFDM symbol is shown in FIG. **9B**.

At block **1220**, one of the CCA slots is identified as a CCA slot in which to determine the availability of unlicensed spectrum. The one of the CCA slots may be identified based at least in part on a pseudo-random selection sequence driven by a randomization seed.

In some embodiments, at least a subset of the multiple base stations may use the same randomization seed for their pseudo-random sequence generation. The subset may be associated with a deployment of base stations by a single operator.

Thus, the method **1200-a** may provide for wireless communications. It should be noted that the method **1200-a** is just one implementation and that the operations of the method **1200-a** may be rearranged or otherwise modified such that other implementations are possible.

FIG. **13A** is a flow chart illustrating another example of a method **1300** for wireless communications. For clarity, the method **1300** is described below with reference to one of the eNBs **105** shown in FIGS. **1**, **2A**, and/or **2B**. In one implementation, one of the eNBs **105** may execute one or more sets of codes to control the functional elements of the eNB **105** to perform the functions described below.

At block **1305**, a CCA may be performed during one of multiple CCA slots synchronized across multiple eNBs **105** (e.g., LTE-U eNBs) to determine an availability of an unlicensed spectrum (or at least one channel of the unlicensed spectrum) for downlink transmissions in a next transmission interval.

In some embodiments, different eNBs may use different ones of the multiple CCA slots to perform CCA during a gating interval. In other embodiments, two or more eNBs may use the same CCA slot to perform CCA during a gating interval (e.g., when there exists coordination between a subset of eNBs, such as coordination between the eNBs deployed by a single operator).

Thus, the method **1300** may provide for wireless communications. It should be noted that the method **1300** is just one implementation and that the operations of the method

1300 may be rearranged or otherwise modified such that other implementations are possible.

FIG. **13B** is a flow chart illustrating yet another example of a method **1300-a** for wireless communications. For clarity, the method **1300-a** is described below with reference to one of the eNBs **105** shown in FIGS. **1**, **2A**, and/or **2B**. In one implementation, one of the eNBs **105** may execute one or more sets of codes to control the functional elements of the eNB **105** to perform the functions described below.

At block **1315**, a CCA slot may be identified (e.g., by an eNB) from among multiple CCA slots synchronized across multiple eNBs **105** (e.g., LTE-U eNBs). The slot may be identified based at least in part on a pseudo-random selection sequence generated from a randomization seed. In alternate embodiment, the slot may be identified based at least in part on coordination information exchanged between at least a subset of the eNBs over a backhaul, such as the backhaul **132** or **134** described with reference to FIG. **1**.

At block **1320**, a CCA may be performed during the identified CCA slot to determine an availability of an unlicensed spectrum (or at least one channel of the unlicensed spectrum) for downlink transmissions in a next transmission interval.

In some embodiments, different eNBs may identify different ones of multiple CCA slots to perform CCA during a gating interval. In other embodiments, two or more eNBs may identify the same CCA slot to perform CCA during a gating interval.

Thus, the method **1300-a** may provide for wireless communications. It should be noted that the method **1300-a** is just one implementation and that the operations of the method **1300-a** may be rearranged or otherwise modified such that other implementations are possible.

FIG. **14A** provides another example **1400** of how the performance of CCAs for an unlicensed spectrum (or a channel of the unlicensed spectrum) may be synchronized across multiple eNBs **105**. Examples of the eNBs **105** may be the base stations **105**, **105-a**, and **105-b** of FIG. **1**, FIG. **2A**, and FIG. **2B**, respectively. The performance of CCAs may in some examples be synchronized across the eNBs **105** used in the system **100** of FIG. **1**, or with portions of the system **100** shown in FIG. **2A** and FIG. **2B**.

FIG. **14A** also shows how the unlicensed spectrum may be reserved by one or more of the eNBs **105** following a successful CCA. By way of example, the multiple eNBs **105** may include an LTE-U eNB1, an LTE-U eNB2, and an LTE-U eNB3.

As shown, the boundaries of the current gating intervals of each eNB (e.g., eNB1, eNB2, and eNB3) may be synchronized, thereby providing synchronization of the S' subframes **725-f**, **725-g**, **725-h** of the eNBs. A CCA period of each S' subframe may include multiple CCA slots **720**. Because of a synchronized pseudo-random CCA slot selection processes implemented by each eNB, the eNB2 may select a CCA slot **720-i** that occurs at a different time (e.g., different OFDM symbol position) than the CCA slot **720-h** selected by eNB1. For example, the eNB1 may select a CCA slot **720-h** aligned with the fifth OFDM symbol position of the aligned CCA periods of the S' subframes **725-f** and **725-g**, and the eNB2 may select a CCA slot **720-i** aligned with the third OFDM symbol position of the aligned CCA periods. However, when the eNB3 is deployed by the same operator as the eNB1, the eNB3 may synchronize the timing of its CCA slot **720-j** with the timing of the CCA slot **720-h** selected for eNB1. The operator deploying both eNB1 and eNB3 may then determine which eNB is allowed access to the unlicensed spectrum or coordinate simultaneous access

to the unlicensed spectrum by virtue of orthogonal transmissions and/or other transmission mechanisms.

A next transmission interval following the synchronized S' subframes **725-f**, **725-g**, **725-h** may begin after the CCA periods of the S' subframes **725-f**, **725-g**, **725-h** and start with a D subframe, as shown. Because the CCA slot **720-i** of the eNB2 is scheduled first in time, the eNB2 has a chance to reserve the next transmission interval before the eNB1 and eNB3 have a chance to reserve the next transmission interval. However, because of the pseudo-random CCA slot selection process implemented by each of eNB1, eNB1, and eNB3, the eNB1 or eNB3 may be provided the first chance to reserve a later transmission interval.

By way of example, FIG. 14A shows there is WiFi transmission (Tx) activity that coincides with a portion of the aligned CCA periods of the S' subframes **725-f**, **725-g**, **725-h**. Because of the timing of the CCA slot **720-i** selected by the eNB2, the eNB2 may determine as a result of performing its CCA that the unlicensed spectrum is unavailable, and may gate OFF a downlink transmission **1005-c** in the unlicensed spectrum for the next transmission interval. A downlink transmission of the eNB2 may therefore be blocked as a result of the WiFi Tx activity occurring during performance of the eNB2's CCA.

During the CCA slots **720-h** and **720-j**, the eNB1 and the eNB3 may each perform their respective CCA. Because of the timing of the CCA slots **720-h**, **720-j** selected by the eNB1 and the eNB3, each of the eNB1 and the eNB3 may determine as a result of performing their CCA that the unlicensed spectrum is available (e.g., because the WiFi Tx activity does not occur during the CCA slots **720-h**, **720-i**, and because the eNB2 was not able to reserve the next transmission interval at an earlier time). The eNB1 and the eNB3 may therefore each reserve the next transmission interval and gate ON a downlink transmission **1005-b**, **1005-d** in the unlicensed spectrum for the next transmission interval.

An eNB may reserve the next transmission interval by transmitting one or more signals before the next transmission interval to reserve the unlicensed spectrum during the next transmission interval. For example, after determining that the unlicensed spectrum is available (e.g., by performing a successful CCA), the eNB1 may fill each of the CCA slots following its performance of a successful CCA with CUBS **1010-a**. The CUBS **1010-a** may include one or more signals that are detectable by other devices to let the other devices know the unlicensed spectrum (or at least a channel thereof) has been reserved for use by another device (e.g., by the eNB1). The CUBS **1010-a** may be detected by both LTE and WiFi devices. Unlike most LTE signals, which begin at a subframe boundary, the CUBS **1010-a** may begin at an OFDM symbol boundary.

In some cases, the CUBS **1010-a** may include a placeholder signal transmitted for the purpose of reserving the unlicensed spectrum. In other cases, the CUBS **1010-a** may include, for example, at least one pilot signal for one or both of time-frequency synchronization and channel quality estimation over the unlicensed spectrum. The pilot signal(s) may be used by one or more UEs **115** to make channel quality measurements on different resource elements, so that a channel quality may be reported to the eNB1. The eNB1 may then receive the report of channel quality from the UE **115** in response to the CUBS **1010-a**, and allocate resource elements for transmissions from the eNB1 to the UE **115** to provide fractional resource reuse among multiple UEs **115**, to avoid interference among the multiple UEs **115**.

In some embodiments, the CUBS **1010-a** may be transmitted repetitively, with the transmission of each signal starting at a boundary of one of the multiple CCA slots.

In some embodiments, it may be ensured that at least one OFDM symbol position worth of CUBS is transmitted following a successful CCA, to assist in time/frequency synchronization between a transmitting LTE-U eNB and a receiving UE.

In some embodiments, and when there is a duration of more than two OFDM symbols between a successful CCA and the start of a next transmission interval, the third and subsequent CUBS transmissions may be modified to carry downlink data and control information from the transmitting LTE-U eNB to a receiving UE.

In some embodiments, the CUBS **1010-a** may be modeled after the downlink pilot time slot (DwPTS) structure defined in the current LTE specification.

In some embodiments, the CUBS **1010-a** may include a wideband waveform that carries a signature sequence determined by the DeploymentID of the transmitting LTE-U eNB. The signature sequence may be a known sequence having low information content, and hence be IC-friendly for LTE-U receiver nodes. The wideband waveform may in some cases be transmitted at full transmit power, to overcome the transmit power spectral density (Tx-PSD) and minimum bandwidth (min-BW) constraints, as well as silence other nodes (e.g., WiFi nodes).

The eNB3 may likewise fill each of the CCA slots following its performance of a successful CCA with CUBS **1010-b**, and may receive a report of channel quality from a different one of the UEs **115**.

FIG. 14B provides yet another example **1400-a** of how the performance of CCAs for an unlicensed spectrum (or a channel of the unlicensed spectrum) may be synchronized across multiple eNBs **105**. Examples of the eNBs **105** may be the base stations **105**, **105-a**, and **105-b** of FIG. 1, FIG. 2A, and FIG. 2B, respectively. The performance of CCAs may in some examples be synchronized across the eNBs **105** used in the system **100** of FIG. 1, or with portions of the system **100** shown in FIG. 2A and FIG. 2B.

FIG. 14B also shows how the unlicensed spectrum may be reserved by one of the eNBs **105** following a successful CCA. By way of example, the multiple eNBs **105** may include an LTE-U eNB1, an LTE-U eNB2, and an LTE-U eNB4.

As shown, the boundaries of the current gating intervals of each eNB (e.g., eNB1, eNB2, and eNB4) may be synchronized, thereby providing synchronization of the S' subframes **725-f**, **725-g**, **725-i** of the eNBs. A CCA period of each S' subframe may include multiple CCA slots **720**. Because of a synchronized pseudo-random CCA slot selection processes implemented by each eNB, the eNB2 may select a CCA slot **720-i** that occurs at a different time (e.g., different OFDM symbol position) than the CCA slot **720-h** selected by eNB1. For example, the eNB1 may select a CCA slot **720-h** aligned with the fifth OFDM symbol position of the aligned CCA periods of the S' subframes **725-f** and **725-g**, and the eNB2 may select a CCA slot **720-i** aligned with the third OFDM symbol position of the aligned CCA periods. Likewise, the eNB4 may select a CCA slot **720-k** that occurs at a different time than the CCA slots **720-h**, **720-i** selected by each of the eNB1 and the eNB2 (e.g., because the eNB4 may not be deployed by the same operator as the eNB1, as was the case with the eNB3 described with reference to FIG. 14A). For example, the eNB4 may select a CCA slot **720-k** aligned with the sixth OFDM symbol position of the aligned CCA periods.

A next transmission interval following the synchronized S' subframes **725-f**, **725-g**, **725-i** may begin after the CCA periods of the S' subframes **725-f**, **725-g**, **725-i** and start with a D subframe, as shown. Because the CCA slot **720-i** of the eNB2 is scheduled first in time, the eNB2 has a chance to reserve the next transmission interval before the eNB1 and eNB4 have a chance to reserve the next transmission interval. However, because of the pseudo-random CCA slot selection process implemented by each of the eNB1, the eNB2, and the eNB4, the eNB1 or the eNB4 may be provided the first chance to reserve a later transmission interval.

By way of example, FIG. 14B shows there is WiFi transmission (Tx) activity that coincides with a portion of the aligned CCA periods of the S' subframes **725-f**, **725-g**, **725-i**. However, because the WiFi Tx activity does not coincide with the timing of the CCA slot **720-i** selected by the eNB2, the eNB2 may determine as a result of performing its CCA that the unlicensed spectrum is available, and may gate ON a downlink transmission **1005-c** in the unlicensed spectrum for the next transmission interval. Also, and following its successful CCA, the eNB2 may fill the subsequent CCA slots with CUBS **1010-c**, thereby reserving the next transmission interval for its own use.

During the CCA slots **720-h** and **720-k**, the eNB1 and the eNB4 may each perform their respective CCA. However, because the eNB2 has already begun to transmit CUBS **1010-c**, the eNB1 and the eNB4 determine that the unlicensed spectrum is unavailable. Stated another way, the eNB1 and the eNB4 are blocked from the unlicensed spectrum by virtue of the eNB2 already having reserved the unlicensed spectrum.

FIG. 14C provides yet another example **1400-b** of how the performance of CCAs for an unlicensed spectrum (or a channel of the unlicensed spectrum) may be synchronized across multiple eNBs **105**. Examples of the eNBs **105** may be the base stations **105**, **105-a**, and **105-b** of FIG. 1, FIG. 2A, and FIG. 2B, respectively. The performance of CCAs may in some examples be synchronized across the eNBs **506** used in the system **100** of FIG. 1, or with portions of the system **100** shown in FIG. 2A and FIG. 2B.

FIG. 14C also shows how the unlicensed spectrum may be reserved by one of the eNBs **105** following a successful CCA. By way of example, the multiple eNBs **105** may include an LTE-U eNB1, an LTE-U eNB2, and an LTE-U eNB4.

As shown, the boundaries of the current gating intervals of each eNB (e.g., eNB1, eNB2, and eNB4) may be synchronized, thereby providing synchronization of the S' subframes **725-f**, **725-g**, **725-i** of the eNBs. A CCA period of each S' subframe may include multiple CCA slots **720**. Because of a synchronized pseudo-random CCA slot selection processes implemented by each eNB, the eNB2 may select a CCA slot **720-i** that occurs at a different time (e.g., different OFDM symbol position) than the CCA slot **720-h** selected by eNB1. For example, the eNB1 may select a CCA slot **720-h** aligned with the fifth OFDM symbol position of the aligned CCA periods of the S' subframes **725-f** and **725-g**, and the eNB2 may select a CCA slot **720-i** aligned with the third OFDM symbol position of the aligned CCA periods. Likewise, the eNB4 may select a CCA slot **720-k** that occurs at a different time than the CCA slots **720-h**, **720-i** selected by each of the eNB1 and the eNB2 (e.g., because the eNB3 may not be deployed by the same operator as the eNB1, as was the case in the example described with reference to FIG. 14A). For example, the eNB4 may select

a CCA slot **720-k** aligned with the sixth OFDM symbol position of the aligned CCA periods.

A next transmission interval following the synchronized S' subframes **725-f**, **725-g**, **725-i** may begin after the CCA periods of the S' subframes **725-f**, **725-g**, **725-i** and start with a D subframe, as shown. Because the CCA slot **720-i** of the eNB2 is scheduled first in time, the eNB2 has a chance to reserve the next transmission interval before the eNB1 and eNB4 have a chance to reserve the next transmission interval. However, because of the pseudo-random CCA slot selection process implemented by each of the eNB1, the eNB2, and the eNB4, the eNB1 or the eNB4 may be provided the first chance to reserve a later transmission interval.

By way of example, FIG. 14C shows there is WiFi transmission (Tx) activity that coincides with a portion of the aligned CCA periods of the S' subframes **725-f**, **725-g**, **725-i**. Because of the timing of the CCA slot **720-i** selected by the eNB2, the eNB2 may determine as a result of performing its CCA that the unlicensed spectrum is unavailable, and may gate OFF a downlink transmission **1005-c** in the unlicensed spectrum for the next transmission interval. A downlink transmission of the eNB2 may therefore be blocked as a result of the WiFi Tx activity occurring during performance of the eNB2's CCA.

During the CCA slot **720-h**, the eNB1 may perform its CCA and determine that the unlicensed spectrum is available (e.g., because the WiFi Tx activity does not occur during the CCA slot **720-h**, and because the eNB2 was not able to reserve the next transmission interval at an earlier time). The eNB1 may therefore reserve the next transmission interval and gate ON a downlink transmission **1005-b** in the unlicensed spectrum for the next transmission interval. Also, and following its successful CCA, the eNB1 may fill the subsequent CCA slots with CUBS **1010-d**, thereby reserving the next transmission interval for its own use.

During the CCA slot **720-k**, the eNB4 may perform its CCA and detect the CUBS **1010-d**. As a result, the eNB4 may determine that the unlicensed spectrum is unavailable and gate OFF a downlink transmission **1005-d** in the unlicensed spectrum. Stated another way, the eNB4 is blocked from the unlicensed spectrum by virtue of the eNB1 already having reserved the unlicensed spectrum.

In FIGS. 14A, 14B, and 14C, CUBS **1010** are transmitted prior to a next transmission interval, to reserve unlicensed spectrum for an LTE-U eNB's use during the next transmission interval. However, in some embodiments, CUBS **1010** may be transmitted at the beginning of an active transmission interval to provide, for example, time/frequency synchronization for an LTE-U eNB and UE that are in communication during the active transmission interval.

In some embodiments, CUBS may be transmitted for less than the duration an OFDM symbol. Transmissions of CUBS for less than an OFDM symbol may be referred to as partial CUBS (PCUBS). By way of example, and in the context of the one or two millisecond gating intervals described with reference to FIGS. 10D, 10E, 10F, and 10G, PCUBS may be transmitted between the performance of a successful CCA and the start of a next OFDM symbol boundary. In some embodiments, PCUBS may be obtained from a full symbol CUBS by puncturing three out of every four tones and truncating the CUBS to a desired duration. Alternately, PCUBS may be formed by a physical layer convergence procedure (PLCP) preamble and header based on the IEEE 802.11g/n standard (which can silence at least standard compliant WiFi nodes).

FIG. 15 is a flow chart illustrating an example of a method 1500 for wireless communications. For clarity, the method 1500 is described below with reference to one of the eNBs 105 shown in FIGS. 1, 2A, and/or 2B. In one implementation, one of the eNBs 105 may execute one or more sets of codes to control the functional elements of the eNB 105 to perform the functions described below.

At block 1505, a CCA may be performed during one of multiple CCA slots synchronized across multiple eNBs 105 (e.g., LTE-U eNBs) to determine an availability of an unlicensed spectrum (or at least one channel of the unlicensed spectrum) for downlink transmissions in a next transmission interval.

In some embodiments, different eNBs may use different ones of the multiple CCA slots to perform CCA during a gating interval. In other embodiments, two or more eNBs may use the same CCA slot to perform CCA during a gating interval (e.g., when there exists coordination between a subset of eNBs, such as coordination between the eNBs deployed by a single operator).

At block 1510, and when the unlicensed spectrum is available (e.g., when it is determined by performing a successful CCA that the unlicensed spectrum is available), one or more signals may be transmitted before the next transmission interval to reserve the unlicensed spectrum during the next transmission level. In some cases, the one or more signals may include CUBS 1010, as described with reference to FIGS. 14A, 14B, and/or 14C.

In some embodiments, the one or more signals transmitted before the next transmission interval may include at least one pilot signal for one or both of time-frequency synchronization and channel quality estimation over the unlicensed spectrum. The pilot signal(s) may be used by one or more UEs 115 to make channel quality measurements on different resource elements, so that a channel quality may be reported to the eNB 105 that transmitted the one or more signals. The eNB 105 may then receive the report of channel quality from the UE 115 in response to the pilot signal(s) and allocate resource elements for transmissions from the eNB 105 to the UE 115 to provide fractional resource reuse among multiple UEs 115, to avoid interference among the multiple UEs 115.

Thus, the method 1500 may provide for wireless communications. It should be noted that the method 1500 is just one implementation and that the operations of the method 1500 may be rearranged or otherwise modified such that other implementations are possible.

When gating access to an unlicensed spectrum, gating intervals may force an LTE-U eNB to be silent for several LTE radio frames. Because of this, an LTE-U eNB that relies on conventional LTE reporting of feedback information (e.g., channel state information (CSI)) may not have up-to-date channel quality indicator (CQI) information before scheduling a downlink transmission. An LTE-U eNB that relies on conventional LTE reporting of feedback information may also fail to receive hybrid automatic repeat requests (HARQ) in a timely fashion. Mechanisms that take gating intervals of an unlicensed spectrum into account, and report CSI and HARQ over gated OFF transmission intervals of a downlink in the unlicensed spectrum, may therefore be used to improve the LTE-U eNB's CQI and HARQ processing. Examples of such mechanisms are described with reference to FIGS. 16, 17A, and 17B.

FIG. 16 is a diagram 1600 illustrating communications between an eNB 105-c and a UE 115-c. The eNB 105-c may be an example of the base stations 105, 105-a, and 105-b of FIG. 1, FIG. 2A, and FIG. 2B, respectively. The UE 115-c may be an example of the UEs 115, 115-a, and 115-b of FIG.

1, FIG. 2A, and FIG. 2B, respectively. The eNB 105-c and the UE 115-c may be used in the system 100 of FIG. 1 and with portions of the system 100 shown in FIG. 2A and FIG. 2B.

The eNB 105-c may communicate with the UE 115-c via a downlink 1610 in an unlicensed spectrum, and the UE 115-c may communicate with the eNB 105-c via a primary component carrier (PCC) uplink 1605 in a licensed spectrum. The UE 115-c may transmit feedback information to the eNB 105-c via the PCC uplink 1605, and the eNB 105-c may receive the feedback information from the UE 115-c via the PCC uplink 1605. In some cases, the feedback information may address (or pertain to) signals transmitted from the eNB 105-c to the UE 115-c via the downlink 1610. Transmitting feedback information for the unlicensed spectrum via the licensed spectrum may improve the reliability of feedback information for the unlicensed spectrum.

The feedback information may in some cases include feedback information for at least one transmission interval gated from the downlink 1610.

In some embodiments, the feedback information may include channel state information (CSI), such as CSI for the downlink 1610. For at least one transmission interval during which the eNB 105-c gated OFF transmissions for the downlink 1610, the CSI may include long-term CSI. However, for at least one transmission interval during which the eNB 105-c gated ON transmissions for the downlink, the CSI may include short-term CSI. The long-term CSI may include, for example, radio resource management (RRM) information that captures the details of the channel interference environment (e.g., information identifying each source of dominant interference, whether it be a WiFi, station (STA), and/or LTE-U eNB, for example; information identifying the average strength and/or spatial characteristics of each interfering signal; etc.). The short-term CSI may include, for example, a CQI, a rank indicator (RI), and/or a pre-coding matrix indicator. In some cases, the CSI may be sent from a UE 115 to an eNB 115, via the PCC uplink 1605, in a second subframe following the start of downlink transmissions in a current transmission interval in the unlicensed spectrum.

In some embodiments, the feedback information may include HARQ feedback information, such as HARQ feedback information for the downlink 1610. In one example of HARQ transmission, HARQ may ignore transmission intervals where downlink transmissions were gated OFF. In another example of HARQ transmission, HARQ may be used for transmission intervals where downlink transmissions are gated ON, and a simple automated repeat request (ARQ) may be used for transmission intervals where downlink transmissions are gated OFF. Both examples may retain almost full HARQ functionality in the context of a single LTE-U deployment with no WiFi interference. However, in the presence of WiFi interference or multiple LTE-U deployments (e.g., deployments by different operators), the second example may be forced to predominantly use ARQ, in which case CSI may become the main tool for link adaptation. Asynchronous HARQ may be transmitted in a manner that is unaffected by gating of the unlicensed spectrum.

When a downlink transmission is not acknowledged (NAK'd), a best effort HARQ retransmission may be made via the downlink 1610. However, after a timeout period, the NAK'd packet may be recovered through radio link control (RLC) retransmissions via the downlink 1610 or a PCC downlink.

The eNB 105-c may in some cases use both the long-term CSI and the short-term CSI to select a modulation and coding scheme (MCS) for the downlink 1610 in the unli-

censed spectrum. The HARQ may then be used to fine-tune the served spectral efficient of the downlink **1610** in real-time.

FIG. **17A** is a flow chart illustrating an example of another method **1700** for wireless communications. For clarity, the method **1700** is described below with reference to one of the eNBs **105** shown in FIGS. **1**, **2A**, and/or **2B**. In one implementation, one of the eNBs **105** may execute one or more sets of codes to control the functional elements of the eNB **105** to perform the functions described below.

At block **1705**, feedback information is received (e.g., by an eNB **105**) from a UE **115** via a PCC uplink in a licensed spectrum. The feedback information may include information that addresses (or pertains to) signals transmitted to the UE **115** via a downlink in an unlicensed spectrum.

The feedback information may in some cases include feedback information for at least one transmission interval gated from the downlink **1610**.

In some embodiments, the feedback information may include channel state information (CSI), such as CSI for the downlink **1610**. For at least one transmission interval during which the eNB **105-c** gated OFF transmissions for the downlink **1610**, the CSI may include long-term CSI. However, for at least one transmission interval during which the eNB **105-c** gated ON transmissions for the downlink, the CSI may include short-term CSI. The long-term CSI may include, for example, radio resource management (RRM) information that captures the details of the channel interference environment (e.g., information identifying each source of dominant interference, whether it be a WiFi, station (STA), and/or LTE-U eNB, for example; information identifying the average strength and/or spatial characteristics of each interfering signal; etc.). The short-term CSI may include, for example, a CQI, a rank indicator (RI), and/or a pre-coding matrix indicator. In some cases, the CSI may be sent from a UE **115** to an eNB **115**, via the PCC uplink **1605**, in a second subframe following the start of downlink transmissions in a current transmission interval in the unlicensed spectrum.

In some embodiments, the feedback information may include HARQ feedback information, such as HARQ feedback information for the downlink **1610**. In one example of HARQ transmission, HARQ may ignore transmission intervals where downlink transmissions were gated OFF. In another example of HARQ transmission, HARQ may be used for transmission intervals where downlink transmissions are gated ON, and a simple automated repeat request (ARQ) may be used for transmission intervals where downlink transmissions are gated OFF. Both examples may retain almost full HARQ functionality in the context of a single LTE-U deployment with no WiFi interference. However, in the presence of WiFi interference or multiple LTE-U deployments (e.g., deployments by different operators), the second example may be forced to predominantly use ARQ, in which case CSI may become the main tool for link adaptation. Asynchronous HARQ may be transmitted in a manner that is unaffected by gating of the unlicensed spectrum.

When a downlink transmission is not acknowledged (NAK'd), a best effort HARQ retransmission may be made via the downlink **1610**. However, after a timeout period, the NAK'd packet may be recovered through radio link control (RLC) retransmissions via the downlink **1610** or a PCC downlink.

The eNB **105-c** may in some cases use both the long-term CSI and the short-term CSI to select a modulation and coding scheme (MCS) for the downlink **1610** in the unli-

censed spectrum. The HARQ may then be used to fine-tune the served spectral efficient of the downlink **1610** in real-time.

Thus, the method **1700** may provide for wireless communications. It should be noted that the method **1700** is just one implementation and that the operations of the method **1700** may be rearranged or otherwise modified such that other implementations are possible.

FIG. **17B** is a flow chart illustrating an example of a method **1700-a** for wireless communications. For clarity, the method **1700-a** is described below with reference to one of the UEs **115** shown in FIGS. **1**, **2A**, and/or **2B**. In one implementation, one of the UEs **115** may execute one or more sets of codes to control the functional elements of the UE **115** to perform the functions described below.

At block **1715**, feedback information may be transmitted (e.g., from a UE **115**) to an eNB **105** via a PCC uplink in a licensed spectrum. The feedback information may include information that addresses (or pertains to) signals transmitted to the UE **115** via a downlink in an unlicensed spectrum.

The feedback information may in some cases include feedback information for at least one transmission interval gated from the downlink **1610**.

In some embodiments, the feedback information may include channel state information (CSI), such as CSI for the downlink **1610**. For at least one transmission interval during which the eNB **105-c** gated OFF transmissions for the downlink **1610**, the CSI may include long-term CSI. However, for at least one transmission interval during which the eNB **105-c** gated ON transmissions for the downlink, the CSI may include short-term CSI. The long-term CSI may include, for example, radio resource management (RRM) information that captures the details of the channel interference environment (e.g., information identifying each source of dominant interference, whether it be a WiFi, station (STA), and/or LTE-U eNB, for example; information identifying the average strength and/or spatial characteristics of each interfering signal; etc.). The short-term CSI may include, for example, a CQI, a rank indicator (RI), and/or a pre-coding matrix indicator. In some cases, the CSI may be sent from a UE **115** to an eNB **115**, via the PCC uplink **1605**, in a second subframe following the start of downlink transmissions in a current transmission interval in the unlicensed spectrum.

In some embodiments, the feedback information may include HARQ feedback information, such as HARQ feedback information for the downlink **1610**. In one example of HARQ transmission, HARQ may ignore transmission intervals where downlink transmissions were gated OFF. In another example of HARQ transmission, HARQ may be used for transmission intervals where downlink transmissions are gated ON, and a simple automated repeat request (ARQ) may be used for transmission intervals where downlink transmissions are gated OFF. Both examples may retain almost full HARQ functionality in the context of a single LTE-U deployment with no WiFi interference. However, in the presence of WiFi interference or multiple LTE-U deployments (e.g., deployments by different operators), the second example may be forced to predominantly use ARQ, in which case CSI may become the main tool for link adaptation. Asynchronous HARQ may be transmitted in a manner that is unaffected by gating of the unlicensed spectrum.

When a downlink transmission is not acknowledged (NAK'd), a best effort HARQ retransmission may be made via the downlink **1610**. However, after a timeout period, the

NAK'd packet may be recovered through radio link control (RLC) retransmissions via the downlink **1610** or a PCC downlink.

The eNB **105-c** may in some cases use both the long-term CSI and the short-term CSI to select a modulation and coding scheme (MCS) for the downlink **1610** in the unlicensed spectrum. The HARQ may then be used to fine-tune the served spectral efficient of the downlink **1610** in real-time.

Thus, the method **1700-a** may provide for wireless communications. It should be noted that the method **1700-a** is just one implementation and that the operations of the method **1700-a** may be rearranged or otherwise modified such that other implementations are possible.

Turning next to FIG. **18A**, a diagram **1800** illustrates an example of LTE-U beacon signal broadcasting in an unlicensed spectrum according to various embodiments. The LTE-U beacon signal (or discovery beacons) **1805** may be transmitted or broadcast by an eNB that supports LTE-U. Examples of such an eNB may be the base stations **105**, **105-a**, and **105-b** of FIG. **1**, FIG. **2A**, and FIG. **2B**, respectively. The broadcasting may be performed in connection with a system or network like the system **100** of FIG. **1** and the portions of the system **100** of FIG. **2A** and FIG. **2B**.

The transmissions may occur when the eNB is in an active state or when the eNB is in a dormant or inactive state. The beacon signals **1805** may be transmitted at a low duty cycle (e.g., 1 or 2 subframes every 100 milliseconds) and may span up to about 5 Megahertz (MHz) in bandwidth. Because of their low duty cycle, the beacon signals **1805** may be transmitted without the need for a listen-before-talk (LBT) scheme. Accordingly, the beacon signals **1805** may be transmitted (e.g., broadcast) at predetermined times. In the example shown in FIG. **18A**, beacon signals **1805** may be transmitted at least at times t_0 , t_1 , t_2 , and t_3 . The timing of these transmissions may be periodic. In some cases the transmissions may not need to be periodic as long as the times are scheduled (e.g., predetermined) and the schedule may be known to the devices or entities listening for the beacon signals **1805**. The beacon signals **1805** may be used by other eNBs and/or by UEs (e.g., UEs **115**) for dormant/active eNB discovery and for coarse time-frequency tracking.

FIG. **18B** shows a diagram **1800-a** that illustrates an example of a payload in an LTE beacon signal according to various embodiments. The beacon signal **1805-a** shown in FIG. **18B** may be an example of the beacon signals **1805** of FIG. **18A**. Accordingly, the beacon signal **1805-a** may be transmitted or broadcast by an eNB that supports LTE-U (LTE-U eNB). Examples of such an eNB may be the base stations **105**, **105-a**, and **105-b** of FIG. **1**, FIG. **2A**, and FIG. **2B**, respectively.

A payload of the beacon signal **1805-a** may include multiple fields of information or attributes associated with an eNB. For example, the beacon signal **1805-a** may include one or more of a primary synchronization signal (PSS) field **1810**, a secondary synchronization signal (SSS) field **1815**, a cell-specific reference signal (CRS) field **1820**, a physical broadcast channel (PBCH) field **1825**, a system information block (SIB) field **1830**, a closed subscriber group identity (CSG-ID) field **1835**, a public land mobile network identifier (PLMN ID) field **1840**, a global cell ID (GCI) field **1845**, a clear channel assessment randomization seed (CCA-RS) field **1850**, a random access channel (RACH) configuration field **1855**, a light- or lite-version of an SIB (SIB-lite) field **1860**, and a deployment ID field **1865**. In some embodiments, the SIB-lite field **1860** may include the GCI field

1845 and the CSG-ID field **1835**. The GCI field **1845** may include the PLMN ID field **1840**. The payload contents shown in FIG. **18B** need not be exhaustive. Other information or attributes associated with an eNB may be included to enable the use of LTE-based communications in an unlicensed spectrum. For example, the payload of the beacon signal **1805-a** may include a periodic gating structure configuration for use in gating ON/OFF a next gating or transmission interval. Moreover, some of the fields shown need not be transmitted in some cases and some of the fields may be combined.

The combination of information on the PLMN ID field **1840** and in the CSG-ID field **1835** may be used to identify an LTE-U deployment configuration (e.g., an eNB deployment configuration) for the LTE-U deployment (e.g., an eNB deployment) associated with a given eNB. For example, LTE-U eNBs deployed by different cellular operators may have different PLMN IDs. Some PLMN IDs may be reserved for non-operator deployment of LTE-U. For example, an LTE-U eNB deployed by a non-operator/enterprise may use a reserved PLMN ID together with a unique CSG-ID.

FIG. **19A** shows a flowchart of a method **1900** for broadcasting LTE beacon signals in an unlicensed spectrum according to various embodiments. The method **1900** may be implemented using, for example, the base stations or eNBs **105**, **105-a**, and **105-b** of FIG. **1**, FIG. **2A**, and FIG. **2B**, respectively; and/or the system **100** of FIG. **1** and the portions of the system **100** of FIG. **2A** and FIG. **2B**. In one implementation, one of the eNBs **105** may execute one or more sets of codes to control the functional elements of the eNB **105** to perform the functions described below.

At block **1905**, beacon signals (e.g., beacon signals **1805**) may be broadcast in an unlicensed spectrum at predetermined times from an eNB, where the beacon signals include downlink signals that identify the eNB and at least one associated attribute of the eNB. The beacon signals may in some cases be received at a UE (or at a plurality of UEs). In some embodiments, a UE may use the beacon signals to make a coarse timing adjustment to communicate in the unlicensed spectrum at the UE.

In some embodiments of the method **1900**, the at least one associated attribute of the eNB may include at least attribute of the eNB. In some embodiments, the at least one associated attribute of the eNB may include an eNB deployment configuration for an eNB deployment with which the eNB is associated. In some embodiments, the at least one associated attribute of the eNB may include an eNB deployment configuration for an eNB deployment with which the eNB is associated, wherein downlink signals from eNBs in the eNB deployment are synchronized and concurrently transmitted by the eNBs of the eNB deployment in the unlicensed spectrum and in a licensed spectrum. In some embodiments, the eNBs in the eNB deployment are each deployed by a same operator.

In some embodiments of the method **1900**, the at least one associated attribute of the eNB may include a RACH configuration associated with the eNB. In these embodiments, the beacon signals may also include a paging message for at least one UE. Upon receiving a beacon signal broadcast in the unlicensed spectrum, a UE may respond to the paging message using the RACH configuration.

In some embodiments of the method **1900**, broadcasting the beacon signals includes broadcasting the beacon signals at a duty cycle below 5% (e.g., 1-2%), with a maximum broadcasting interval of approximately once every 50 milliseconds. In some embodiments, the beacon signals include

one or more of a PSS, an SSS, a CRS, a PBCH, a GCI, a CSG-ID, a PLMN ID, a deployment ID, a periodic gating structure configuration, a CCA-RS, a RACH configuration, an SIB, and an SIB-lite. The beacon signals may include information that identifies the eNB as being active or dormant.

FIG. 19B shows a flowchart of a method **1900-a** for broadcasting LTE beacon signals in an unlicensed spectrum according to various embodiments. The method **1900-a**, like the method **1900** above, may be implemented using, for example, the base stations or eNBs **105**, **105-a**, and **105-b** of FIG. 1, FIG. 2A, and FIG. 2B, respectively; and/or the system **100** of FIG. 1 and the portions of the system **100** of FIG. 2A and FIG. 2B. In one implementation, one of the eNBs **105** may execute one or more sets of codes to control the functional elements of the eNB **105** to perform the functions described below.

At block **1915**, an eNB deployment is identified in which downlink signals from the deployed eNBs are synchronized and concurrently transmitted by the deployed eNBs in an unlicensed spectrum and in a licensed spectrum.

At block **1920**, beacon signals (e.g., beacon signals **1805**) may be broadcast in an unlicensed spectrum at predetermined times from one or more of the deployed eNBs, where the beacon signals include the identified eNB deployment.

Turning next to FIG. 20, a diagram **2000** is shown that illustrates an example of request-to-send (RTS) and clear-to-send (CTS) signals in an unlicensed spectrum according to various embodiments. The RTS signals may be transmitted by an eNB that supports LTE-U (LTE-U eNB). Examples of such an eNB may be the base stations **105**, **105-a**, and **105-b** of FIG. 1, FIG. 2A, and FIG. 2B, respectively. The CTS signals may be transmitted by a UE that supports LTE-U (LTE-U UE). Examples of such a UE may be the UES **115**, **115-a**, and **115-b** of FIG. 1, FIG. 2A, and FIG. 2B, respectively.

An RTS signal **2005** (or RTS **2005**) may be generated and transmitted after a CCA **720-1** during a subframe **725-j** in a current gating interval. The subframe **725-j** may be an example of the subframe 9 (S') **725** of FIG. 7. That is, the subframe **725-j** may be a last subframe in the current gating interval. The RTS **2005** may be transmitted when the CCA **720-1** is successful in the middle of the subframe interval. An LTE-U eNB may use the transmission of the RTS **2005** to hold the channel until the next subframe boundary (or beyond).

The RTS **2005** may be compatible with RTS as defined for IEEE 802.11 standards (e.g., WiFi). A transmitter address (TA) field of the RTS **2005** may include the MAC ID of the transmitting LTE-U eNB. From the MAC ID, other LTE-U nodes (e.g., LTE-U eNBs) of the same deployment may recognize this as a “friendly RTS” and not go silent (may follow LTE-U MAC/enhanced intercell interference coordination (eICIC) procedures instead). A network allocation vector (NAV) field may be used to reserve time slots, as defined in IEEE 802.11 standards. For example, a NAV field may reserve at least a next subframe (1 milliseconds period). However, more typically, a NAV field may reserve at least the next 5 subframes (up to a maximum consistent with listen-before-talk). A receiver address (RA) field of the RTS **2005** may contain multiple hashes of cell radio network temporary identifier (C-RNTI) for a set of UEs served by the LTE-U eNB.

An RTS signal such as the RTS **2005** may be used prior to an UL grant to protect the subsequent UL transmission. In a standalone deployment, such as the one described above

with respect to FIG. 2B, an RTS signal may also be sent prior to a physical downlink shared channel (PDSCH) transmission to protect the subsequent UL subframe where HARQ feedback (ACK/NACK) may be sent by a UE (on the same unlicensed spectrum channel). In response to an RTS signal, at least the UEs that are referred to in the RA field of the RTS signal may respond by sending a CTS signal if they are capable of receiving data/signaling from the eNB. Other UEs served by the LTE-U eNB that may wish to send a scheduling request (SR) or a pending CSI report may also respond with a CTS signal. Unlike WiFi, the CTS sent by the LTE-U UEs contain the MAC ID of the serving eNB in their TA field. A NAV field in the CTS may be determined from the corresponding RTS signal.

Returning to FIG. 20, the UEs named/served by the transmitting eNB may send a common CTS signal **2010** (or CTS **2010**) a short inter-frame space (SIFS) interval after the RTS **2005**. The common CTS **2010** allows the UEs to grab the channel as quickly as possible. In the remaining duration of subframe 9, before the next subframe boundary (with subframe 10), the UEs identified by the RTS **2005** may send individual CTS signals **2015** (or CTSs **2015**) staggered in time. The staggering may depend on the order in which the UEs are identified in the RA field of the RTS **2005**. A TA field in each of the individual CTSs **2015** may carry a hash of their full identity. The individual CTSs **2015** indicate to the eNB that the UEs are ready to receive data/grant. The use of individual CTSs **2015** enable better scheduling design, more efficient use of the channel by using FDMA among multiple UEs. After subframe 9, which includes the RTS **2005**, the common CTS **2010**, and the individual CTSs **2015**, a next subframe **710-a** (subframe 10) may include transmissions of PDSCH **2020**, **2020-a**, and **2020-b**.

FIG. 21 shows a flowchart of a method **2100** for transmitting RTS signals and receiving CTS signals in an unlicensed spectrum according to various embodiments. The method **2100** may be implemented using, for example, the base stations or eNBs **105**, **105-a**, and **105-b** of FIG. 1, FIG. 2A, and FIG. 2B, respectively; and/or the system **100** of FIG. 1 and the portions of the system **100** of FIG. 2A and FIG. 2B. In one implementation, one of the eNBs **105** may execute one or more sets of codes to control the functional elements of the eNB **105** to perform the functions described below.

At block **2105**, clear channel assessment (CCA) may be performed to determine the availability of unlicensed spectrum.

At block **2110**, an RTS signal (e.g., RTS **2005**) may be transmitted to a set of UEs using the unlicensed spectrum when a determination is made that the unlicensed spectrum is available (e.g., CCA is successful).

At block **2115**, a common CTS signal (e.g., CTS **2010**) and an individual CTS signal (e.g., CTS **2015**) may be received from one or more of the UEs in response to the RTS signal.

The RTS signal may be received at the UEs in the set of UEs over the unlicensed spectrum, and the common CTS signal and a respective individual CTS signal may be transmitted from each UE, over the unlicensed spectrum, in response to the RTS signal.

In some embodiments of the method **2100**, transmitting the RTS signal includes transmitting the RTS signal prior to an uplink grant to protect a subsequent uplink transmission over the unlicensed spectrum, from the set of UEs. The RTS signal may include a MAC ID of a source (e.g., eNB) of the RTS signal. The MAC ID of the source may include a 48-bit

MAC ID, for example. The RTS signal may include a hashed version of the MAC ID of the UEs in the set.

In some embodiments of the method **2100**, the common CTS signal may be received a SIFS after the transmission of the RTS signal and the common CTS signal may include a MAC ID of the source of the RTS signal. Each of the individual CTS signals received may include a MAC ID of the source of the RTS signal and a MAC ID of the UE transmitting the individual CTS signal. The individual CTS signals may be received at staggered times.

In some embodiments of the method **2100**, the CCA may be performed during a subframe of a current gating interval, the RTS signal may be transmitted after the CCA, and the common CTS and individual CTSs signals may be received before an end of the subframe. In some embodiments, a time associated with the CCA and a time associated with the subsequent transmission of the RTS signal may be randomly staggered among different eNBs to avoid collisions at devices receiving the RTS signal. Moreover, a time associated with the CCA and a time associated with the subsequent transmission of the RTS signal may be mutually staggered to avoid collisions at devices receiving the RTS signal, the staggering being based at least on coordinating signaling exchanged between eNBs.

Turning next to FIG. **22A**, a diagram **2200** is shown that illustrates an example of virtual CTS (V-CTS) signals in a licensed spectrum according to various embodiments. The V-CTS signals may be transmitted by UEs that support LTE-U (LTE-U UE). Examples of such UEs may be the UES **115**, **115-a**, **115-b**, and of FIG. **1**, FIG. **2A**, and FIG. **2B**, respectively.

After a DCF interframe space (DIFS) interval, which may include a CCA (e.g., 4 milliseconds) occurring whenever media frees up, an eNB (e.g., base station **105**) may send an RTS signal **2205** (or RTS **2205**) in an unlicensed spectrum addressing all UEs (e.g., UE_1, \dots, UE_n) of interest with NAV. After a SIFS interval, the eNB sends a CTS-to-self in the unlicensed spectrum. The eNB may immediately schedule downlink traffic based on current knowledge for the rest of the subframe and continue scheduling and ACK **2230**. The scheduling may be performed using the physical downlink control channel (PDCCH) and the PDSCH in signals **2220** and **2225**. The UEs addressed by the RTS **2205** may send back, in a licensed spectrum, V-CTS signals **2215** (or V-CTSs **2215**) with updated measurements (e.g., RTS/CTS measurements) for the eNB to improve future scheduling. In this scenario, the CTS signaling takes place virtually or out-of-band (out of the unlicensed spectrum) by concurrently using the licensed spectrum in LTE-U.

Turning next to FIG. **22B**, a diagram **2200-a** is shown that illustrates an example of virtual RTS (V-RTS) signals in a licensed spectrum according to various embodiments. The V-RTS signals may be transmitted by eNBs that support LTE-U (LTE-U eNB). Examples of such eNBs may be the base stations **105**, **105-a**, and **105-b** of FIG. **1**, FIG. **2A**, and FIG. **2B**, respectively.

After a DIFS interval, which may include a CCA (e.g., 4 milliseconds) occurring whenever media frees up, an eNB (e.g., base station **105**) may poll the UEs of interest (e.g., UE_1, \dots, UE_n) on a primary cell (PCell) when the media or channel is sensed to be free or available. The eNB need only send a CTS-to-self signal **2210** (or CTS-to-self **2210**) on an unlicensed spectrum to save overhead. The eNB sends a V-RTS signal **2235** (or V-RTS **2235**) using a licensed spectrum and the UEs addressed by the V-RTS **2235** may respond by each sending a V-CTS **2215-a** also in the licensed spectrum. In this scenario, all the signaling needed

for RTS and CTS takes place virtually or out-of-band (out of the unlicensed spectrum) by concurrently using the licensed spectrum in LTE-U. Like the scenario in FIG. **22A**, the eNB may proceed to send scheduling information using signals **2220** and **2225** (e.g., PDCCH and PDSCH).

FIG. **23** shows a flowchart of a method **2300** for transmitting an RTS signal or a V-RTS signal according to various embodiments. The method **2300** may be implemented using, for example, the base stations or eNBs **105**, **105-a**, and **105-b** of FIG. **1**, FIG. **2A**, and FIG. **2B**, respectively; and/or the system **100** of FIG. **1** and the portions of the system **100** of FIG. **2A** and FIG. **2B**. In one implementation, one of the eNBs **105** may execute one or more sets of codes to control the functional elements of the eNB **105** to perform the functions described below.

At block **2305**, an RTS signal (e.g., RTS **2205**) may be transmitted in an unlicensed spectrum or a V-RTS signal (e.g., RTS **2235**) may be transmitted in a licensed spectrum, addressed to a set of UEs (e.g., UE_1, \dots, UE_n).

At block **2310**, a CTS-to-self signal may be transmitted in an unlicensed spectrum along with the transmission of the V-RTS signal.

The RTS signal or the V-RTS signal may be received at the UEs in the set of UEs over the unlicensed spectrum.

In some embodiments of the method **2300**, a V-CTS signal may be received in the licensed spectrum for each of the UEs in the set in response to the RTS signal or the V-RTS signal. The V-CTS signal may include measurements made by the respective UE for use in future scheduling. In some embodiments, traffic may be scheduled after receiving the V-CTS signals based on current channel knowledge for a remainder of a subframe. The RTS signal may be transmitted in the downlink primary component carrier.

FIG. **24** shows a flowchart of a method **2400** for receiving V-CTS signals in response to an RTS signal or a V-RTS signal according to various embodiments. The method **2400** may be implemented using, for example, the base stations or eNBs **105**, **105-a**, and **105-b** of FIG. **1**, FIG. **2A**, and FIG. **2B**, respectively; and/or the system **100** of FIG. **1** and the portions of the system **100** of FIG. **2A** and FIG. **2B**. In one implementation, one of the eNBs **105** may execute one or more sets of codes to control the functional elements of the eNB **105** to perform the functions described below.

At block **2405**, an RTS signal (e.g., RTS **2205**) may be transmitted in an unlicensed spectrum or a V-RTS signal (e.g., RTS **2235**) may be transmitted in a licensed spectrum, addressed to a set of UEs (e.g., UE_1, \dots, UE_n).

At block **2410**, a CTS-to-self signal may be transmitted in an unlicensed spectrum along with the transmission of the V-RTS signal.

At block **2415**, a V-CTS signal may be received in the licensed spectrum from each of the UEs in the set in response to the RTS signal or the V-RTS signal.

At block **2420**, traffic may be scheduled after receiving the V-CTS signals based on current channel knowledge for a remainder of a subframe.

The RTS signal or the V-RTS signal may be received at the UEs in the set of UEs over the unlicensed spectrum, and the V-CTS signal may be transmitted from each UE, over the unlicensed spectrum, in response to the RTS signal or the V-RTS signal.

Turning next to FIG. **25**, a diagram **2500** is shown that illustrates examples of normal and robust subframes in an unlicensed spectrum according to various embodiments. The normal and robust subframes may be transmitted by eNBs that support LTE-U (LTE-U eNB). Examples of such eNBs may be the base stations **105**, **105-a**, and **105-b** of FIG. **1**,

FIG. 2A. and FIG. 2B, respectively. The normal and robust subframes may be used by UEs that support LTE-U (LTE-U UE). Examples of such UEs may be the UEs **115**, **115-a**, and **115-b** of FIG. 1, FIG. 2A. and FIG. 2B, respectively.

A normal legacy carrier type (LCT) subframe **2505** is shown. Normal LCT subframes **2505** may be used for LCT waveforms and may carry time-division multiplexed (TDM) PDCCH and CRS. Also shown is a normal new carrier type (NCT) subframe **2515**. Normal NCT subframes **2514** may be used for NCT waveforms but may not include TDM PDCCH and CRS. Instead, a UE may use channel state information-reference signals (CSI-RS) for feedback and UE-RS for demodulation. In addition to the normal LCT and NCT subframes, FIG. 25 shows a robust LCT subframe **2510** and a robust NCT subframe **2520**. Robust subframes may differ from the normal ones in that they may include additional pilots (e.g., common pilots, eCRS) in comparison to normal subframes, which may be used to facilitate time-frequency tracking and channel estimation at the UE after a long gated-OFF period of LTE DL transmissions.

For gated LCT waveforms, SYNC subframes (e.g., subframes carrying PSS, SSS, (possibly) PBCH, in addition to other LTE subchannels) may be transmitted in a subframe index=0 (mod 5). The robust LCT subframes **2510** may be transmitted for the first X subframes after a gated-OFF period that is greater than Y subframes. The parameters X and Y may vary based on the structure of the subframes and usage rules, for example. Normal LCT subframes **2505** may be transmitted in all other gated-ON periods.

For gated NCT waveforms, SYNC subframes may be transmitted in a subframe index=0 (mod 5). The robust NCT subframes **2520** may be transmitted for the first X subframes after a gated-OFF period that is greater than Y subframes. The parameters X and Y may vary based on the structure of the subframes and usage rules, for example. Normal NCT subframes **2515** may be transmitted in all other gated-ON periods.

FIG. 26 shows a flowchart of a method **2600** for transmitting normal or robust subframes in an unlicensed spectrum according to various embodiments. The method **2600** may be implemented using, for example, the base stations or eNBs **105**, **105-a**, and **105-b** of FIG. 1, FIG. 2A, and FIG. 2B, respectively; and/or the system **100** of FIG. 1 and the portions of the system **100** of FIG. 2A and FIG. 2B.

At block **2605**, past transmission activity on an unlicensed spectrum may be compared to an activity threshold (e.g., a number of gated-ON periods in the unlicensed spectrum over a time period, a duration of a number of gated-ON periods in the unlicensed spectrum over a time period, and/or a number of SYNC subframes transmitted in the unlicensed spectrum over a time period).

At block **2610**, a first subframe type (e.g., normal LCT/NCT subframes) may be transmitted in the unlicensed spectrum during a next active transmission when the past transmission activity is greater than the activity threshold.

At block **2615**, a second subframe type (e.g., robust LCT/NCT subframes) may be transmitted in the unlicensed spectrum during a next active transmission when the past transmission activity is lesser than the activity threshold. The second subframe type may include a more robust subframe type than the first subframe type.

In some embodiments of the method **2600**, the first subframe type may include an LCT subframe. In some embodiments, the first subframe type may include an NCT subframe. In some embodiments, the second subframe type may include an LCT subframe with additional common pilots for tracking and channel estimation. In some embodi-

ments, the second subframe type may include an NCT subframe with additional common pilots for tracking and channel estimation. The method may include transmitting the first subframe type in the unlicensed spectrum after a predetermined number of transmissions of the second subframe type is identified.

Turning next to FIG. 27, a diagram **2700** is shown that illustrates examples of Physical Uplink Control Channel (PUCCH) signals and Physical Uplink Shared Channel (PUSCH) signals for an unlicensed spectrum according to various embodiments. The PUCCH and PUSCH signals may be handled by eNBs that support LTE-U (LTE-U eNB). Examples of such eNBs may be the base stations **105**, **105-a**, and **105-b** of FIG. 1, FIG. 2A. and FIG. 2B, respectively. The PUCCH and PUSCH signals may be handled by UEs that support LTE-U (LTE-U UE). Examples of such UEs may be the UEs **115**, **115-a**, and **115-b** of FIG. 1, FIG. 2A. and FIG. 2B, respectively.

PUCCH and PUSCH signals are typically based on localized frequency division multiplexing (LFDM) waveforms that occupy a set of subcarriers where a different modulation symbol is sent for each subcarrier or some precoding is done before sending the frequency domain waveform. When using these waveforms, small amounts of data available to be sent result in a small portion of the spectrum being occupied. Because of limitations in transmit power spectral density (TX-PSD), when occupying a small part of the bandwidth a small amount of power is transmitted. To get away from that, there may be a need to occupy pretty much the entire waveform. But if most of the waveform is occupied and does not leave any subcarriers unused, it may not be possible to multiplex different users for a given amount of bandwidth. One approach to address this issue is to have each transmitter interleave its signals so they occupy every 1-out-of-every-Nth subcarrier (e.g., 1-out-of-10, 1-out-of-12), thereby leaving many subcarriers in the middle unoccupied. This approach may increase the nominal bandwidth occupancy to enable sending the waveform with a higher power (but still with low enough PSD to meet regulations). Interleaved frequency division multiplexing (IFDM) and interleaved orthogonal frequency division multiplexing (I-OFDM) signals may be used that occupy 1-out-of-Nth subcarrier in order to send signals confined to those subcarriers. In FIG. 25, IFDM waveforms are shown to generate PUCCH signals **2705** and PUSCH signals **2710** for transmission in an unlicensed spectrum. Similarly, I-OFDM waveforms are shown to generate PUCCH signals **2715** and PUSCH signals **2720** for transmission in an unlicensed spectrum.

FIG. 28 shows a flowchart of a method **2800** for generating PUCCH and/or PUSCH signals for an unlicensed spectrum according to various embodiments. The method **2800** may be implemented using, for example, the base stations or eNBs **105**, **105-a**, and **105-b** of FIG. 1, FIG. 2A, and FIG. 2B, respectively; the UEs **115**, **115-a**, and **115-b** of FIG. 1, FIG. 2A. and FIG. 2B, respectively; and/or the system **100** of FIG. 1 and the portions of the system **100** of FIG. 2A and FIG. 2B. In one implementation, one of the eNBs **105** or one of the UEs **115** may execute one or more sets of codes to control the functional elements of the eNB **105** or the UE **115** to perform the functions described below.

At block **2805**, one or both of PUCCH signals and PUSCH signals may be generated based on interleaved signals that increase nominal bandwidth occupancy in an unlicensed spectrum.

At block **2810**, the generated signals may be transmitted (e.g., by an eNB) in the unlicensed spectrum. In some

embodiments, the interleaved signals may include IFDM signals. In some embodiments, the interleaved signals may include I-OFDM signals.

One or both of the generated signals may be received in the unlicensed spectrum by, for example, a UE.

Turning next to FIG. 29, a diagram 2900 is shown that illustrates an example of load-based gating in an unlicensed spectrum according to various embodiments. The load-based gating may be performed by eNBs that support LTE-U (LTE-U eNB). Examples of such eNBs may be the base stations 105, 105-a, and 105-b of FIG. 1, FIG. 2A, and FIG. 2B, respectively.

The listen-before-talk (LBT) techniques described above may be used in frame-based equipment (FBE). However, other LBT techniques are also available that are based on load-based equipment (LBE). The LBT-FBE techniques rely in part on gating that preserves the 10 milliseconds radio frame structure of LTE. The use of shorter gating structures (1 milliseconds, 2 milliseconds), while allowing for periodic gating, tend not to preserve the LTE frame structure. Using LBT-LBE may provide the potential benefit of retaining the subframe structure of LTE PHY channels without the need for symbol puncturing at the beginning or end. However, time-reuse among different LTE-U nodes may no longer be assured on the same deployment because each eNB uses its own random back-off time for extended CCA. Therefore, for LBT-LBE, the CCA may be similar to the CCA for LBT-FBE, but extended CCA (which is not used in LBT-FBE), may be based on randomly selecting an integer N (e.g., $1 \leq N \leq q$), and waiting for N CCA durations where the channel is clear.

The transmission at different subframes (SFs) in a subframe sequence transmitted in an unlicensed spectrum channel may be based on results from extended CCAs and from CCA. Extended CCA may be based on a parameter $4 \leq q \leq 32$, whose value is advertised by the vendor. When the channel has had a long break, CCA may need to be performed. If CCA finds a clear channel, then it may be possible to start transmitting right away. If not, extended CCA may be performed before transmission. Once transmission begins, it may continue for at most $(13/32) \times q$ msc (referred to as the maximum channel occupancy time), before another extended CCA may need to be performed. Upon a successful reception (from another node), ACK/NACK transmission may begin immediately (without) CCA, provided that the last successful CCA/extended CCA was performed less than a maximum channel occupancy time before.

Returning to the example of FIG. 29, the CCA time may be set to 25 μ s and $q=24$, so that the maximum channel occupancy time is approximately 9.75 milliseconds. The minimum idle time for extended CCA is approximately between 25 μ s and 0.6 milliseconds. CUBS may be used to fill the gap as described above. In this example, extended CCA 720-m is performed at subframe (SF) 8 in a sequence 2905. The maximum channel occupancy time is such that a next extended CCA 720-m need not be performed until SF18. LTE downlink transmissions may take place during SFs 9-12 as a result of the channel being free after the first extended CCA 720-m. Since there is a transmission gap after SF 12, a CCA 720-n may be performed at SF 15 for additional transmissions within the maximum channel occupancy time. As a result of the CCA 720-n, LTE transmissions may take place at SFs 16 and 17. As noted above, a second extended CCA 720-m may occur after the maximum channel occupancy time, which in this example leads to additional LTE transmissions in SFs 22-25.

Turning to FIG. 30, a diagram 3000 is shown that illustrates a UE 115-d configured for LTE-U. The UE 115-d may have various other configurations and may be included or be part of a personal computer (e.g., laptop computer, netbook computer, tablet computer, etc.), a cellular telephone, a PDA, a digital video recorder (DVR), an internet appliance, a gaming console, an e-readers, etc. The UE 115-d may have an internal power supply (not shown), such as a small battery, to facilitate mobile operation. The station UE 115-d may be an example of the UEs 115, 115-a, 115-b, and 115-c of FIG. 1, FIG. 2A, FIG. 2B, and FIG. 16, respectively. The UE 115-d may be configured to implement at least some of the features and functions described above with respect to FIGS. 1-29.

The UE 115-d may include a processor module 3010, a memory module 3020, a transceiver module 3040, antennas 3050, and an UE modes module 3060. Each of these components may be in communication with each other, directly or indirectly, over one or more buses 3005.

The memory module 3020 may include random access memory (RAM) and read-only memory (ROM). The memory module 3020 may store computer-readable, computer-executable software (SW) code 3025 containing instructions that are configured to, when executed, cause the processor module 3010 to perform various functions described herein for using LTE-based communications in an unlicensed spectrum. Alternatively, the software code 3025 may not be directly executable by the processor module 3010 but be configured to cause the computer (e.g., when compiled and executed) to perform functions described herein.

The processor module 3010 may include an intelligent hardware device, e.g., a central processing unit (CPU), a microcontroller, an application-specific integrated circuit (ASIC), etc. The processor module 3010 may process information received through the transceiver module 3040 and/or to be sent to the transceiver module 3040 for transmission through the antennas 3050. The processor module 3010 may handle, alone or in connection with the UE modes module 3060, various aspects of using LTE-based communications in an unlicensed spectrum.

The transceiver module 3040 may be configured to communicate bi-directionally with base stations (e.g., base stations 105). The transceiver module 3040 may be implemented as one or more transmitter modules and one or more separate receiver modules. The transceiver module 3040 may support communications in a licensed spectrum (e.g., LTE) and in an unlicensed spectrum (e.g., LTE-U). The transceiver module 3040 may include a modem configured to modulate the packets and provide the modulated packets to the antennas 3050 for transmission, and to demodulate packets received from the antennas 3050. While the UE 115-d may include a single antenna, there may be embodiments in which the UE 115-d may include multiple antennas 3050.

According to the architecture of FIG. 30, the UE 115-d may further include a communications management module 3030. The communications management module 3030 may manage communications with various access points. The communications management module 3030 may be a component of the UE 115-d in communication with some or all of the other components of the UE 115-d over the one or more buses 3005. Alternatively, functionality of the communications management module 3030 may be implemented as a component of the transceiver module 3040, as a computer program product, and/or as one or more controller elements of the processor module 3010.

The UE modes module **3060** may be configured to perform and/or control some or all of the functions or aspects described in FIGS. 1-29 related to using LTE-based communications in an unlicensed spectrum. For example, the UE modes module **3060** may be configured to support a supplemental downlink mode, a carrier aggregation mode, and/or a standalone mode of operation in an unlicensed spectrum. The UE modes module **3060** may include an LTE module **3061** configured to handle LTE communications, an LTE unlicensed module **3062** configured to handle LTE-U communications, and an unlicensed module **3063** configured to handle communications other than LTE-U in an unlicensed spectrum. The UE modes module **3060**, or portions of it, may be a processor. Moreover, some or all of the functionality of the UE modes module **3060** may be performed by the processor module **3010** and/or in connection with the processor **3010**.

Turning to FIG. 31, a diagram **3100** is shown that illustrates a base station or eNB **105-d** configured for LTE-U. In some embodiments, the base station **105-d** may be an example of the base stations **105**, **105-a**, **105-b**, and **105-c** of FIG. 1, FIG. 2A, FIG. 2B, and FIG. 16, respectively. The base station **105-d** may be configured to implement at least some of the features and functions described above with respect to FIGS. 1-29. The base station **105-d** may include a processor module **3110**, a memory module **3120**, a transceiver module **3130**, antennas **3140**, and a base station modes module **3190**. The base station **105-d** may also include one or both of a base station communications module **3160** and a network communications module **3170**. Each of these components may be in communication with each other, directly or indirectly, over one or more buses **3105**.

The memory module **3120** may include RAM and ROM. The memory module **3120** may also store computer-readable, computer-executable software (SW) code **3125** containing instructions that are configured to, when executed, cause the processor module **3110** to perform various functions described herein for using LTE-based communications in an unlicensed spectrum. Alternatively, the software code **3125** may not be directly executable by the processor module **3110** but be configured to cause the computer, e.g., when compiled and executed, to perform functions described herein.

The processor module **3110** may include an intelligent hardware device, e.g., a CPU, a microcontroller, an ASIC, etc. The processor module **3110** may process information received through the transceiver module **3130**, the base station communications module **3160**, and/or the network communications module **3170**. The processor module **3110** may also process information to be sent to the transceiver module **3130** for transmission through the antennas **3140**, to the base station communications module **3160**, and/or to the network communications module **3170**. The processor module **3110** may handle, alone or in connection with the base station modes module **3190**, various aspects of using LTE-based communications in an unlicensed spectrum.

The transceiver module **3130** may include a modem configured to modulate the packets and provide the modulated packets to the antennas **3140** for transmission, and to demodulate packets received from the antennas **3140**. The transceiver module **3130** may be implemented as one or more transmitter modules and one or more separate receiver modules. The transceiver module **3130** may support communications in a licensed spectrum (e.g., LTE) and in an unlicensed spectrum (e.g., LTE-U). The transceiver module **3130** may be configured to communicate bi-directionally,

via the antennas **3140**, with one or more UEs **115** as illustrated in FIG. 1, FIG. 2A, FIG. 2B, and FIG. 16, for example. The base station **105-d** may typically include multiple antennas **3140** (e.g., an antenna array). The base station **105-d** may communicate with a core network **130-a** through the network communications module **3170**. The core network **130-a** may be an example of the core network **130** of FIG. 1. The base station **105-d** may communicate with other base stations, such as the base station **105-e** and the base station **105-f**, using the base station communications module **3160**.

According to the architecture of FIG. 31, the base station **105-d** may further include a communications management module **3150**. The communications management module **3150** may manage communications with stations and/or other devices. The communications management module **3150** may be in communication with some or all of the other components of the base station **105-d** via the bus or buses **3105**. Alternatively, functionality of the communications management module **3150** may be implemented as a component of the transceiver module **3130**, as a computer program product, and/or as one or more controller elements of the processor module **3110**.

The base station modes module **3190** may be configured to perform and/or control some or all of the functions or aspects described in FIGS. 1-29 related to using LTE-based communications in an unlicensed spectrum. For example, the base station modes module **3190** may be configured to support a supplemental downlink mode, a carrier aggregation mode, and/or a standalone mode of operation in an unlicensed spectrum. The base station modes module **3190** may include an LTE module **3191** configured to handle LTE communications, an LTE unlicensed module **3192** configured to handle LTE-U communications, and an unlicensed module **3193** configured to handle communications other than LTE-U in an unlicensed spectrum. The base station modes module **3190**, or portions of it, may be a processor. Moreover, some or all of the functionality of the base station modes module **3190** may be performed by the processor module **3110** and/or in connection with the processor **3110**.

Turning next to FIG. 32, a block diagram of a multiple-input multiple-output (MIMO) communication system **3200** is shown including a base station **105-g** and a user equipment or UE **115-e**. The base station **105-g** and the UE **115-e** may support LTE-based communications using an unlicensed spectrum (LTE-U). The base station **105-g** may be an example of the base stations **105**, **105-a**, **105-b**, and **105-c** of FIG. 1, FIG. 2A, FIG. 2B, and FIG. 16, while the UE **115-e** may be an example of the UE **115**, **115-a**, **115-b**, and **115-c** of FIG. 1, FIG. 2A, FIG. 2B, and FIG. 16. The system **3200** may illustrate aspects of the system **100** of FIG. 1 and aspects of the portions of the system **100** shown in FIG. 2A and FIG. 2B.

The base station **105-g** may be equipped with antennas **3234-a** through **3234-x**, and the UE **115-e** may be equipped with antennas **3252-a** through **3252-n**. In the system **3200**, the base station **105-g** may be able to send data over multiple communication links at the same time. Each communication link may be called a "layer" and the "rank" of the communication link may indicate the number of layers used for communication. For example, in a 2x2 MIMO system where base station **800** transmits two "layers," the rank of the communication link between the base station **105-g** and the UE **115-e** is two.

At the base station **105-g**, a transmit (Tx) processor **3220** may receive data from a data source. The transmit processor **3220** may process the data. The transmit processor **3220**

may also generate reference symbols, and a cell-specific reference signal. A transmit (Tx) MIMO processor **3230** may perform spatial processing (e.g., precoding) on data symbols, control symbols, and/or reference symbols, if applicable, and may provide output symbol streams to the transmit modulators **3232-a** through **3232-x**. Each modulator **3232** may process a respective output symbol stream (e.g., for OFDM, etc.) to obtain an output sample stream. Each modulator **3232** may further process (e.g., convert to analog, amplify, filter, and upconvert) the output sample stream to obtain a downlink (DL) signal. In one example, DL signals from modulators **3232-a** through **3232-x** may be transmitted via the antennas **3234-a** through **3234-x**, respectively.

At the UE **115-e**, the antennas **3252-a** through **3252-n** may receive the DL signals from the base station **105-g** and may provide the received signals to the demodulators **3254-a** through **3254-n**, respectively. Each demodulator **3254** may condition (e.g., filter, amplify, downconvert, and digitize) a respective received signal to obtain input samples. Each demodulator **3254** may further process the input samples (e.g., for OFDM, etc.) to obtain received symbols. A MIMO detector **3256** may obtain received symbols from all the demodulators **3254-a** through **3254-n**, perform MIMO detection on the received symbols if applicable, and provide detected symbols. A receive (Rx) processor **3258** may process (e.g., demodulate, deinterleave, and decode) the detected symbols, providing decoded data for the UE **115-e** to a data output, and provide decoded control information to a processor **3280**, or memory **3282**. The processor **3280** may include a module or function **3281** that may perform various functions related to using LTE-based communications in an unlicensed spectrum. For example, the module or function **3281** may perform some or all of the functions described above with reference to the FIGS. **1-29**.

On the uplink (UL), at the UE **115-e**, a transmit (Tx) processor **3264** may receive and process data from a data source. The transmit processor **3264** may also generate reference symbols for a reference signal. The symbols from the transmit processor **3264** may be precoded by a transmit (Tx) MIMO processor **3266** if applicable, further processed by the demodulators **3254-a** through **3254-n** (e.g., for SC-FDMA, etc.), and be transmitted to the base station **105-g** in accordance with the transmission parameters received from the base station **105-g**. At the base station **105-g**, the UL signals from the UE **115-e** may be received by the antennas **3234**, processed by the demodulators **3232**, detected by a MIMO detector **3236** if applicable, and further processed by a receive processor. The receive (Rx) processor **3238** may provide decoded data to a data output and to the processor **3240**. The processor **3240** may include a module or function **3241** that may perform various aspects related to using LTE-based communications in an unlicensed spectrum. For example, the module or function **3241** may perform some or all of the functions described above with reference to FIGS. **1-29**.

The components of the base station **105-g** may, individually or collectively, be implemented with one or more Application Specific Integrated Circuits (ASICs) adapted to perform some or all of the applicable functions in hardware. Each of the noted modules may be a means for performing one or more functions related to operation of the system **3200**. Similarly, the components of the UE **115-e** may, individually or collectively, be implemented with one or more Application Specific Integrated Circuits (ASICs) adapted to perform some or all of the applicable functions in

hardware. Each of the noted components may be a means for performing one or more functions related to operation of the system **3200**.

It should be noted that the various methods described in flowcharts are just one implementation and that the operations of those methods may be rearranged or otherwise modified such that other implementations are possible.

The detailed description set forth above in connection with the appended drawings describes exemplary embodiments and does not represent the only embodiments that may be implemented or that are within the scope of the claims. The term “exemplary” used throughout this description means “serving as an example, instance, or illustration,” and not “preferred” or “advantageous over other embodiments.” The detailed description includes specific details for the purpose of providing an understanding of the described techniques. These techniques, however, may be practiced without these specific details. In some instances, well-known structures and devices are shown in block diagram form in order to avoid obscuring the concepts of the described embodiments.

Information and signals may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the above description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof.

The various illustrative blocks and modules described in connection with the disclosure herein may be implemented or performed with a general-purpose processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general-purpose processor may be a microprocessor, but in the alternative, the processor may be any conventional processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices, e.g., a combination of a DSP and a microprocessor, multiple microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration.

The functions described herein may be implemented in hardware, software executed by a processor, firmware, or any combination thereof. If implemented in software executed by a processor, the functions may be stored on or transmitted over as one or more instructions or code on a computer-readable medium. Other examples and implementations are within the scope and spirit of the disclosure and appended claims. For example, due to the nature of software, functions described above can be implemented using software executed by a processor, hardware, firmware, hardwiring, or combinations of any of these. Features implementing functions may also be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations. Also, as used herein, including in the claims, “or” as used in a list of items prefaced by “at least one of” indicates a disjunctive list such that, for example, a list of “at least one of A, B, or C” means A or B or C or AB or AC or BC or ABC (i.e., A and B and C).

Computer-readable media includes both computer storage media and communication media including any medium that facilitates transfer of a computer program from one place to

another. A storage medium may be any available medium that can be accessed by a general purpose or special purpose computer. By way of example, and not limitation, computer-readable media can comprise RAM, ROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium that can be used to carry or store desired program code means in the form of instructions or data structures and that can be accessed by a general-purpose or special-purpose computer, or a general-purpose or special-purpose processor. Also, any connection is properly termed a computer-readable medium. For example, if the software is transmitted from a website, server, or other remote source using a coaxial cable, fiber optic cable, twisted pair, digital subscriber line (DSL), or wireless technologies such as infrared, radio, and microwave, then the coaxial cable, fiber optic cable, twisted pair, DSL, or wireless technologies such as infrared, radio, and microwave are included in the definition of medium. Disk and disc, as used herein, include compact disc (CD), laser disc, optical disc, digital versatile disc (DVD), floppy disk and blu-ray disc where disks usually reproduce data magnetically, while discs reproduce data optically with lasers. Combinations of the above are also included within the scope of computer-readable media.

The previous description of the disclosure is provided to enable a person skilled in the art to make or use the disclosure. Various modifications to the disclosure will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other variations without departing from the spirit or scope of the disclosure. Throughout this disclosure the term "example" or "exemplary" indicates an example or instance and does not imply or require any preference for the noted example. Thus, the disclosure is not to be limited to the examples and designs described herein but is to be accorded the widest scope consistent with the principles and novel features disclosed herein.

What is claimed is:

1. A method for wireless communications, comprising: broadcasting beacon signals in an unlicensed spectrum at predetermined times from an evolved Node B (eNB), the beacon signals identifying the eNB and at least one associated attribute of the eNB that comprises an eNB deployment configuration for an eNB deployment with which the eNB is associated, wherein downlink signals from eNBs in the eNB deployment are synchronized and concurrently transmitted by the eNBs of the eNB deployment in the unlicensed spectrum.
2. The method of claim 1, wherein the at least one associated attribute of the eNB comprises at least one attribute of the eNB.
3. The method of claim 1, wherein broadcasting of the beacon signals is independent of a listen before talk (LBT) scheme.
4. The method of claim 1, wherein the at least one associated attribute of the eNB comprises a Random Access Channel (RACH) configuration associated with the eNB, and wherein the beacon signals also comprise a paging message for at least one user equipment (UE).
5. The method of claim 1, wherein the eNBs in the eNB deployment are each deployed by a same operator.
6. The method of claim 1, wherein broadcasting the beacon signals comprises broadcasting the beacon signals at a duty cycle below 5%, with a maximum broadcasting interval of approximately once every 50 milliseconds.
7. The method of claim 1, wherein the beacon signals comprise one or more of:

- a Primary Synchronization Signal;
 - a Secondary Synchronization Signal;
 - a Cell-Specific Reference Signal;
 - a Physical Broadcast Channel;
 - a Global Cell Identifier;
 - a CSG-ID;
 - a PLMN ID;
 - a deployment identifier;
 - a periodic gating structure configuration;
 - a Clear Channel Assessment randomization seed (CCARS)
 - a Random Access Channel (RACH) configuration;
 - a System Information Block (SIB);
 - a lite version of an SIB (SIB-lite); or
 - any combination thereof.
8. The method of claim 1, wherein the beacon signals comprise information that identifies the eNB as being active or dormant.
 9. An apparatus for wireless communications, comprising:
 - means for generating beacon signals at an evolved Node B (eNB), the beacon signals identifying the eNB and at least one associated attribute of the eNB that comprises an eNB deployment configuration for an eNB deployment with which the eNB is associated, wherein downlink signals from eNBs in the eNB deployment are synchronized and concurrently transmitted by the eNBs of the eNB deployment in an unlicensed spectrum; and
 - means for broadcasting beacon signals in the unlicensed spectrum at predetermined times.
 10. The apparatus of claim 9, wherein the at least one associated attribute of the eNB comprises at least one attribute of the eNB.
 11. The apparatus of claim 9, wherein broadcasting of the beacon signals is independent of a listen before talk (LBT) scheme.
 12. The apparatus of claim 9, wherein the at least one associated attribute of the eNB comprises a Random Access Channel (RACH) configuration associated with the eNB, and wherein the beacon signals also comprise a paging message for at least one user equipment (UE).
 13. The apparatus of claim 9, wherein the eNBs in the eNB deployment are each deployed by a same operator.
 14. The apparatus of claim 9, wherein the means for broadcasting the beacon signals comprises means for broadcasting the beacon signals at a duty cycle below 5%, with a maximum broadcasting interval of approximately once every 50 milliseconds.
 15. The apparatus of claim 9, wherein the beacon signals comprise one or more of:
 - a Primary Synchronization Signal;
 - a Secondary Synchronization Signal;
 - a Cell-Specific Reference Signal;
 - a Physical Broadcast Channel;
 - a Global Cell Identifier;
 - a CSG-ID;
 - a PLMN ID;
 - a deployment identifier;
 - a periodic gating structure configuration;
 - a Clear Channel Assessment randomization seed (CCARS)
 - a Random Access Channel (RACH) configuration;
 - a System Information Block (SIB);
 - a lite version of an SIB (SIB-lite); or
 - any combination thereof.

16. The apparatus of claim 9, wherein the beacon signals comprise information that identifies the eNB as being active or dormant.

17. An apparatus for wireless communications, comprising:

a processor;
memory in electronic communication with the processor;
and
instructions stored in the memory, the instructions being executable by the processor to:

broadcast beacon signals in an unlicensed spectrum at predetermined times from an evolved Node B (eNB), the beacon signals identifying the eNB and at least one associated attribute of the eNB that comprises an eNB deployment configuration for an eNB deployment with which the eNB is associated, wherein downlink signals from eNBs in the eNB deployment are synchronized and concurrently transmitted by the eNBs of the eNB deployment in the unlicensed spectrum.

18. The apparatus of claim 17, wherein the at least one associated attribute of the eNB comprises at least one attribute of the eNB.

19. The apparatus of claim 17, wherein broadcasting of the beacon signals is independent of a listen before talk (LBT) scheme.

20. The apparatus of claim 17, wherein the at least one associated attribute of the eNB comprises a Random Access Channel (RACH) configuration associated with the eNB, and wherein the beacon signals also comprise a paging message for at least one user equipment (UE).

21. The apparatus of claim 17, wherein the eNBs in the eNB deployment are each deployed by a same operator.

22. The apparatus of claim 17, wherein the instructions executable by the processor to broadcast the beacon signals comprise instructions executable by the processor to broadcast the beacon signals at a duty cycle below 5%, with a maximum broadcasting interval of approximately once every 50 milliseconds.

23. The apparatus of claim 17, wherein the beacon signals comprise one or more of:

a Primary Synchronization Signal;
a Secondary Synchronization Signal;
a Cell-Specific Reference Signal;
a Physical Broadcast Channel;
a Global Cell Identifier;
a CSG-ID;
a PLMN ID;
a deployment identifier;
a periodic gating structure configuration;
a Clear Channel Assessment randomization seed (CCAR-
RS)
a Random Access Channel (RACH) configuration;
a System Information Block (SIB);
a lite version of an SIB (SIB-lite); or
any combination thereof.

24. The apparatus of claim 17, wherein the beacon signals comprise information that identifies the eNB as being active or dormant.

25. A computer program product for communications by a wireless communications apparatus in a wireless communications system, the computer program product comprising a non-transitory computer-readable medium storing instructions executable by a processor to cause the wireless communications apparatus to:

broadcast beacon signals in an unlicensed spectrum at predetermined times from an evolved Node B (eNB), the beacon signals identifying the eNB and at least one

associated attribute of the eNB that comprises an eNB deployment configuration for an eNB deployment with which the eNB is associated, wherein downlink signals from eNBs in the eNB deployment are synchronized and concurrently transmitted by the eNBs of the eNB deployment in the unlicensed spectrum.

26. The computer program product of claim 25, wherein the at least one associated attribute of the eNB comprises at least one attribute of the eNB.

27. The computer program product of claim 25, wherein broadcasting of the beacon signals is independent of a listen before talk (LBT) scheme.

28. A method for wireless communications, comprising: receiving beacon signals broadcast in an unlicensed spectrum at predetermined times from an evolved Node B (eNB), the beacon signals identifying the eNB and at least one associated attribute of the eNB that comprises an eNB deployment configuration with which the eNB is associated, wherein downlink signals from eNBs in the eNB deployment are synchronized and concurrently transmitted by the eNBs of the eNB deployment in the unlicensed spectrum.

29. The method of claim 28, wherein the at least one associated attribute of the eNB comprises at least one attribute of the eNB.

30. The method of claim 28, wherein the at least one associated attribute of the eNB comprises a Random Access Channel (RACH) configuration associated with the eNB, and wherein the beacon signals also comprise a paging message for at least one user equipment (UE).

31. The method of claim 30, further comprising: responding to the paging message using the RACH configuration.

32. The method of claim 28, further comprising: using the beacon signals to make a coarse timing adjustment to communicate in the unlicensed spectrum at a user equipment (UE).

33. The method of claim 28, wherein the eNBs in the eNB deployment are each deployed by a same operator.

34. The method of claim 28, wherein receiving the beacon signals comprises receiving the beacon signals at a duty cycle below 5%, with a maximum receiving interval of approximately once every 50 milliseconds.

35. The method of claim 28, wherein the beacon signals comprise one or more of:

a Primary Synchronization Signal;
a Secondary Synchronization Signal;
a Cell-Specific Reference Signal;
a Physical Broadcast Channel;
a Global Cell Identifier;
a CSG-ID;
a PLMN ID;
a deployment identifier;
a periodic gating structure configuration;
a Clear Channel Assessment randomization seed (CCAR-
RS)
a Random Access Channel (RACH) configuration;
a System Information Block (SIB);
a lite version of an SIB (SIB-lite); or
any combination thereof.

36. The method of claim 28, wherein the beacon signals comprise information that identifies the eNB as being active or dormant.

37. An apparatus for wireless communications, comprising: means for receiving beacon signals broadcast in an unlicensed spectrum at predetermined times from an

57

evolved Node B (eNB), the beacon signals identifying the eNB and at least one associated attribute of the eNB that comprises an eNB deployment configuration for an eNB deployment with which the eNB is associated, wherein downlink signals from eNBs in the eNB deployment are synchronized and concurrently transmitted by the eNBs of the eNB deployment in the unlicensed spectrum; and

means for determining the eNB deployment configuration based at least in part on the at least one associated attribute of the eNB.

38. The apparatus of claim **37**, wherein the at least one associated attribute of the eNB comprises at least one attribute of the eNB.

39. The apparatus of claim **37**, wherein the at least one associated attribute of the eNB comprises a Random Access Channel (RACH) configuration associated with the eNB, and wherein the beacon signals also comprise a paging message for at least one user equipment (UE).

40. The apparatus of claim **39**, further comprising: means for responding to the paging message using the RACH configuration.

41. The apparatus of claim **37**, further comprising: means for using the beacon signals to make a coarse timing adjustment to communicate in the unlicensed spectrum at a user equipment (UE).

42. The apparatus of claim **37**, wherein the eNBs in the eNB deployment are each deployed by a same operator.

43. The apparatus of claim **37**, wherein the means for receiving the beacon signals comprises means for receiving the beacon signals at a duty cycle below 5%, with a maximum receiving interval of approximately once every 50 milliseconds.

44. The apparatus of claim **37**, wherein the beacon signals comprise one or more of:

- a Primary Synchronization Signal;
- a Secondary Synchronization Signal;
- a Cell-Specific Reference Signal;
- a Physical Broadcast Channel;
- a Global Cell Identifier;
- a CSG-ID;
- a PLMN ID;
- a deployment identifier;
- a periodic gating structure configuration;
- a Clear Channel Assessment randomization seed (CCA-RS)
- a Random Access Channel (RACH) configuration;
- a System Information Block (SIB);
- a lite version of an SIB (SIB-lite); or
- any combination thereof.

45. The apparatus of claim **37**, wherein the beacon signals comprise information that identifies the eNB as being active or dormant.

46. An apparatus for wireless communications, comprising:

- a processor;
- memory in electronic communication with the processor; and
- instructions stored in the memory, the instructions being executable by the processor to:

receive beacon signals broadcast in an unlicensed spectrum at predetermined times from an evolved Node B (eNB), the beacon signals identifying the eNB and at least one associated attribute of the eNB that comprises an eNB deployment configuration for an eNB deployment with which the eNB is associated, wherein downlink signals from eNBs in the eNB deployment are

58

synchronized and concurrently transmitted by the eNBs of the eNB deployment in the unlicensed spectrum.

47. The apparatus of claim **46**, wherein the at least one associated attribute of the eNB comprises at least one attribute of the eNB.

48. The apparatus of claim **46**, wherein the at least one associated attribute of the eNB comprises a Random Access Channel (RACH) configuration associated with the eNB, and wherein the beacon signals also comprise a paging message for at least one user equipment (UE).

49. The apparatus of claim **48**, wherein the instructions are executable by the processor to: respond to the paging message using the RACH configuration.

50. The apparatus of claim **46**, wherein the instructions are executable by the processor to:

- use the beacon signals to make a coarse timing adjustment to communicate in the unlicensed spectrum at a user equipment (UE).

51. The apparatus of claim **46**, wherein the eNBs in the eNB deployment are each deployed by a same operator.

52. The apparatus of claim **46**, wherein receiving the beacon signals comprises receiving the beacon signals at a duty cycle below 5%, with a maximum receiving interval of approximately once every 50 milliseconds.

53. The apparatus of claim **46**, wherein the beacon signals comprise one or more of:

- a Primary Synchronization Signal;
- a Secondary Synchronization Signal;
- a Cell-Specific Reference Signal;
- a Physical Broadcast Channel;
- a Global Cell Identifier;
- a CSG-ID;
- a PLMN ID;
- a deployment identifier;
- a periodic gating structure configuration;
- a Clear Channel Assessment randomization seed (CCA-RS)
- a Random Access Channel (RACH) configuration;
- a System Information Block (SIB);
- a lite version of an SIB (SIB-lite); or
- any combination thereof.

54. The apparatus of claim **46**, wherein the beacon signals comprise information that identifies the eNB as being active or dormant.

55. A computer program product for communications by a wireless communications apparatus in a wireless communications system, the computer program product comprising a non-transitory computer-readable medium storing instructions executable by a processor to cause the wireless communications apparatus to:

- receive beacon signals broadcast in an unlicensed spectrum at predetermined times from an evolved Node B (eNB), the beacon signals identifying the eNB and at least one associated attribute of the eNB that comprises an eNB deployment configuration with which the eNB is associated, wherein downlink signals from eNBs in the eNB deployment are synchronized and concurrently transmitted by the eNBs of the eNB deployment in the unlicensed spectrum.

56. The computer program product of claim **55**, wherein the at least one associated attribute of the eNB comprises a random Access Channel (RACH) configuration associated with the eNB, and wherein the beacon signals also comprise a paging message for at least one user equipment (UE).

57. The computer program product of claim 56, wherein the instructions are executable by the processor to cause the wireless communications apparatus to:

respond to the paging message using the RACH configuration.

5

58. The computer program product of claim 55, wherein the instructions are executable by the processor to cause the wireless communications apparatus to:

use the beacon signals to make a coarse timing adjustment to communicate in the unlicensed spectrum at a user equipment (UE).

10

* * * * *