

US009732932B2

(12) **United States Patent**
Auyeung et al.

(10) **Patent No.:** **US 9,732,932 B2**
(45) **Date of Patent:** ***Aug. 15, 2017**

(54) **LIGHTING ASSEMBLY WITH MULTIPLE LIGHTING UNITS**

(71) Applicant: **Ultravision Technologies, LLC**, Dallas, TX (US)

(72) Inventors: **David Siucheong Auyeung**, Carrollton, TX (US); **William Y. Hall**, Dallas, TX (US); **Simon Magarill**, Mountain View, CA (US)

(73) Assignee: **Ultravision Technologies, LLC**, Dallas, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 29 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/413,306**

(22) Filed: **Jan. 23, 2017**

(65) **Prior Publication Data**

US 2017/0130931 A1 May 11, 2017

Related U.S. Application Data

(63) Continuation of application No. 15/162,278, filed on May 23, 2016, which is a continuation of application (Continued)

(51) **Int. Cl.**
F21V 1/00 (2006.01)
F21V 11/00 (2015.01)
(Continued)

(52) **U.S. Cl.**
CPC **F21V 5/007** (2013.01); **F21V 19/003** (2013.01); **F21V 21/26** (2013.01); **F21V 23/002** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC **F21V 5/007**; **F21V 29/745**; **F21V 29/83**; **F21V 21/26**; **F21V 23/002**; **F21V 31/005**;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,254,961 A 9/1941 Lawrence et al.
4,235,285 A 11/1980 Johnson et al.
(Continued)

FOREIGN PATENT DOCUMENTS

CA 2615706 A1 9/2006
CN 201925854 U 8/2011
(Continued)

OTHER PUBLICATIONS

Arik, M., "Thermal Management of LEDs: Package to System," Third International Conference on Solid State Lighting, Proc. of SPIE, vol. 5187, Jan. 21, 2012, pp. 64-75.

(Continued)


Primary Examiner — Alexander Garlen

(74) *Attorney, Agent, or Firm* — Slater Matsil, LLP

(57) **ABSTRACT**

A lighting assembly includes an assembly body. A first lighting unit is attached to the assembly body. The first lighting unit includes a number of light emitting diodes (LEDs) and optical elements arranged over the LEDs such that each optical element overlies only one associated LED. The first lighting unit is configured to illuminate a substantially rectangular region. A second lighting unit is attached to the assembly body and spaced from the first lighting unit. The second lighting unit includes a number of LEDs and optical elements arranged over the plurality of LEDs such that each optical element overlies only one associated LED. The lighting assembly is configured to illuminate the region so that the region can be illuminated without additional lighting and so that areas beyond edges of the region of the

(Continued)



substantially rectangular region receive minimum illumination.

29 Claims, 13 Drawing Sheets

Related U.S. Application Data

No. 14/992,680, filed on Jan. 11, 2016, now Pat. No. 9,349,307, which is a continuation of application No. 14/635,907, filed on Mar. 2, 2015, now Pat. No. 9,234,642, which is a continuation of application No. 13/836,517, filed on Mar. 15, 2013, now Pat. No. 8,974,077.

(60) Provisional application No. 61/677,346, filed on Jul. 30, 2012.

(51) **Int. Cl.**

F21V 5/00 (2015.01)
F21V 29/74 (2015.01)
F21V 29/83 (2015.01)
F21V 19/00 (2006.01)
F21V 31/00 (2006.01)
F21V 21/26 (2006.01)
F21V 23/00 (2015.01)
G09F 13/22 (2006.01)
G09F 13/02 (2006.01)
G09F 15/00 (2006.01)
F21W 131/10 (2006.01)
F21Y 115/10 (2016.01)

(52) **U.S. Cl.**

CPC *F21V 29/745* (2015.01); *F21V 29/83* (2015.01); *F21V 31/005* (2013.01); *G09F 13/02* (2013.01); *G09F 13/22* (2013.01); *G09F 15/005* (2013.01); *F21W 2131/10* (2013.01); *F21Y 2115/10* (2016.08); *G09F 2013/222* (2013.01)

(58) **Field of Classification Search**

CPC F21V 19/003; F21Y 2115/10; F21W 2131/10; G09F 13/02; G09F 13/22; G09F 15/005; G09F 2013/222

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,679,118 A 7/1987 Johnson et al.
 5,036,248 A 7/1991 McEwan et al.
 5,083,194 A 1/1992 Bartilson
 5,329,426 A 7/1994 Villani
 5,384,940 A 1/1995 Soule et al.
 5,803,579 A 9/1998 Turnbull et al.
 5,818,640 A 10/1998 Watanabe et al.
 5,857,767 A 1/1999 Hochstein
 5,896,093 A 4/1999 Sjobom
 5,924,788 A 7/1999 Parkyn, Jr.
 5,926,320 A 7/1999 Parkyn, Jr. et al.
 6,045,240 A 4/2000 Hochstein
 6,274,924 B1 8/2001 Carey et al.
 6,364,507 B1 4/2002 Yang
 6,428,189 B1 8/2002 Hochstein
 6,517,218 B2 2/2003 Hochstein
 6,536,923 B1 3/2003 Merz
 6,547,423 B2 4/2003 Marshall et al.
 6,582,103 B1 6/2003 Popovich
 6,607,286 B2 8/2003 West et al.
 6,674,096 B2 1/2004 Sommers
 6,741,351 B2 5/2004 Marshall et al.

6,783,269 B2 8/2004 Pashley et al.
 6,784,603 B2 8/2004 Pelka et al.
 6,799,864 B2 10/2004 Bohler et al.
 6,837,605 B2 1/2005 Reill
 6,864,513 B2 3/2005 Lin et al.
 6,896,381 B2 5/2005 Benitez et al.
 6,918,684 B2 7/2005 Harvey
 6,948,838 B2 9/2005 Kunstler
 7,006,306 B2 2/2006 Falicoff et al.
 7,009,213 B2 3/2006 Camras et al.
 7,048,400 B2 5/2006 Murasko et al.
 7,118,236 B2 10/2006 Hahm et al.
 7,144,135 B2 12/2006 Martin et al.
 7,153,002 B2 12/2006 Kim et al.
 7,159,997 B2 1/2007 Reo et al.
 7,246,931 B2 7/2007 Hsieh et al.
 7,336,195 B2 2/2008 van de Ven
 7,339,202 B2 3/2008 Chiu et al.
 7,374,306 B2 5/2008 Liu
 7,374,316 B2 5/2008 Kuo et al.
 7,375,381 B2 5/2008 Shimizu et al.
 7,390,117 B2 6/2008 Leatherdale et al.
 7,396,146 B2 7/2008 Wang
 7,410,275 B2 8/2008 Sommers et al.
 7,434,964 B1 10/2008 Zheng et al.
 7,458,706 B1 12/2008 Liu et al.
 7,478,915 B1 1/2009 Pedersen
 7,513,639 B2 4/2009 Wang
 7,513,653 B1 4/2009 Liu et al.
 7,549,777 B2 6/2009 Huang
 7,572,654 B2 8/2009 Chang
 7,618,162 B1 11/2009 Parkyn et al.
 7,618,163 B2 11/2009 Wilcox
 7,654,684 B1 2/2010 Wight et al.
 7,665,862 B2 2/2010 Villard
 7,674,019 B2 3/2010 Parkyn et al.
 7,686,469 B2 3/2010 Ruud et al.
 7,736,019 B2 6/2010 Shimada et al.
 7,748,863 B1 7/2010 Holman et al.
 7,753,561 B2 7/2010 Chaves et al.
 7,753,564 B2 7/2010 Cheng et al.
 7,841,750 B2 11/2010 Wilcox et al.
 7,857,483 B2 12/2010 Storch et al.
 7,866,851 B2 1/2011 Chang
 7,896,522 B2 3/2011 Heller et al.
 7,905,634 B2 3/2011 Agurok et al.
 7,942,559 B2 5/2011 Holder et al.
 7,952,262 B2 5/2011 Wilcox et al.
 7,959,326 B2 6/2011 Laporte
 7,980,733 B2 7/2011 Shih et al.
 7,997,761 B2 8/2011 Peck et al.
 8,002,435 B2 8/2011 Laporte
 8,035,119 B2 10/2011 Ng et al.
 8,052,303 B2 11/2011 Lo et al.
 8,056,614 B2 11/2011 Chen et al.
 8,092,049 B2 1/2012 Kinnune et al.
 8,101,434 B2 1/2012 Guillien et al.
 8,192,048 B2 6/2012 Kristoffersen et al.
 8,201,970 B2 6/2012 Wang et al.
 8,210,723 B2 7/2012 Peck et al.
 8,215,814 B2 7/2012 Marcoux
 8,235,553 B2 8/2012 Minami et al.
 8,246,219 B2 8/2012 Teng et al.
 8,262,252 B2 9/2012 Bergman et al.
 8,267,551 B2 9/2012 Lin
 8,273,158 B2 9/2012 Jarrier et al.
 8,308,331 B2 11/2012 Loh
 8,310,158 B2 11/2012 Coplin et al.
 8,330,387 B2 12/2012 York et al.
 8,338,841 B2 12/2012 Lerman et al.
 8,348,461 B2 1/2013 Wilcox et al.
 8,360,613 B2 1/2013 Little, Jr.
 8,376,585 B2 2/2013 Noeth
 8,408,737 B2 4/2013 Wright et al.
 8,454,194 B2 6/2013 Liu
 8,454,215 B2 6/2013 Bollmann
 8,465,178 B2 6/2013 Wilcox et al.
 8,469,552 B2 6/2013 Moeller
 8,476,650 B2 7/2013 Liao

(56)

References Cited

U.S. PATENT DOCUMENTS

8,547,023 B2	10/2013	Chang et al.
8,567,987 B2	10/2013	Wronski
8,573,815 B2	11/2013	Mallory et al.
8,577,434 B2	11/2013	Merchant et al.
8,585,253 B2	11/2013	Duong et al.
8,602,599 B2	12/2013	Zimmer et al.
8,610,357 B2	12/2013	Stoll et al.
8,622,574 B2	1/2014	Liu
8,628,217 B2	1/2014	Moshtagh
8,632,225 B2	1/2014	Koo et al.
8,651,693 B2	2/2014	Josefowicz et al.
8,662,704 B2	3/2014	Carraher et al.
8,733,981 B2	5/2014	Jiang et al.
8,789,967 B2	7/2014	Gordin et al.
8,801,221 B2	8/2014	Lin et al.
8,824,125 B1	9/2014	Cox et al.
8,835,958 B2	9/2014	Hsieh
8,858,024 B2	10/2014	Wu et al.
8,864,344 B2	10/2014	Jiang et al.
8,870,410 B2	10/2014	Auyeung
8,870,413 B2	10/2014	Auyeung
8,876,325 B2	11/2014	Lu et al.
8,922,734 B2	12/2014	Lin
8,931,934 B2	1/2015	Lin
9,046,293 B2	6/2015	Pelka et al.
9,182,101 B2	11/2015	Nakamura et al.
2003/0099105 A1	5/2003	Watson
2004/0004827 A1	1/2004	Guest
2005/0018428 A1	1/2005	Harvey
2005/0047170 A1	3/2005	Hilburger et al.
2005/0151141 A1	7/2005	Grotsch et al.
2006/0076568 A1	4/2006	Keller et al.
2006/0081863 A1	4/2006	Kim et al.
2006/0146531 A1	7/2006	Reo et al.
2006/0245083 A1	11/2006	Chou et al.
2007/0201225 A1	8/2007	Holder et al.
2007/0257270 A1	11/2007	Lu et al.
2007/0279904 A1	12/2007	Tasch et al.
2008/0073663 A1	3/2008	Chang
2008/0080179 A1	4/2008	Giorgi
2008/0084693 A1	4/2008	Shimada et al.
2008/0084701 A1	4/2008	Van De Ven et al.
2008/0180014 A1	7/2008	Tzeng et al.
2008/0212319 A1	9/2008	Klipstein
2008/0247173 A1	10/2008	Danek et al.
2008/0273327 A1	11/2008	Wilcox et al.
2009/0097265 A1	4/2009	Sun et al.
2009/0154158 A1	6/2009	Cheng et al.
2009/0180281 A1	7/2009	Ahland, III et al.
2009/0256459 A1	10/2009	Liu
2009/0262532 A1	10/2009	Wilcox et al.
2009/0267474 A1	10/2009	Zhou et al.
2009/0273933 A1	11/2009	Woodward et al.
2009/0290338 A1	11/2009	Heller et al.
2009/0296407 A1	12/2009	Bailey
2009/0303711 A1	12/2009	Remus et al.
2010/0008094 A1	1/2010	Shuai et al.
2010/0014289 A1	1/2010	Thomas et al.
2010/0014290 A1	1/2010	Wilcox
2010/0027271 A1	2/2010	Wilcox et al.
2010/0039810 A1	2/2010	Holder et al.
2010/0046225 A1	2/2010	Zheng
2010/0085774 A1	4/2010	Park
2010/0118531 A1	5/2010	Montagne
2010/0128488 A1	5/2010	Marcoux
2010/0149801 A1	6/2010	Lo et al.
2010/0172135 A1	7/2010	Holder et al.
2010/0195330 A1	8/2010	Schaefer et al.
2010/0232155 A1	9/2010	Wang
2010/0296267 A1	11/2010	Yu et al.
2010/0296283 A1	11/2010	Taskar et al.
2010/0302785 A1	12/2010	Zhou
2010/0302786 A1	12/2010	Wilcox et al.
2011/0002120 A1	1/2011	Song et al.
2011/0031887 A1	2/2011	Stoll et al.
2011/0038151 A1	2/2011	Carraher et al.
2011/0063857 A1	3/2011	Li et al.
2011/0068708 A1	3/2011	Coplin et al.
2011/0075409 A1	3/2011	Zheng
2011/0149548 A1	6/2011	Yang et al.
2011/0170283 A1	7/2011	Chan
2011/0205744 A1	8/2011	Kim
2011/0219650 A1	9/2011	Wright et al.
2011/0242807 A1	10/2011	Little, Jr. et al.
2011/0242816 A1	10/2011	Chowdhury et al.
2011/0278633 A1	11/2011	Clifford
2011/0280003 A1	11/2011	Hsu et al.
2012/0014115 A1	1/2012	Park et al.
2012/0043560 A1	2/2012	Wu et al.
2012/0080699 A1	4/2012	Chowdhury et al.
2012/0087125 A1	4/2012	Liu
2012/0163005 A1	6/2012	Liu
2012/0201022 A1	8/2012	van de Ven et al.
2012/0250321 A1	10/2012	Blincoe et al.
2012/0307495 A1	12/2012	Shih
2013/0010468 A1	1/2013	Stoll et al.
2013/0057861 A1	3/2013	Ishii et al.
2013/0063970 A1	3/2013	Oh
2013/0135861 A1	5/2013	Chen et al.
2013/0163005 A1	6/2013	Tsang
2013/0193850 A1	8/2013	Demuyne et al.
2013/0270585 A1	10/2013	Mei et al.
2013/0291414 A1	11/2013	Cegnar
2013/0335979 A1	12/2013	Lauret et al.
2014/0016326 A1	1/2014	Dieker et al.
2014/0029253 A1	1/2014	Auyeung
2014/0029259 A1	1/2014	Auyeung
2014/0029274 A1	1/2014	Auyeung
2014/0085905 A1	3/2014	Broughton
2014/0104851 A1	4/2014	Auyeung
2014/0112007 A1	4/2014	Auyeung
2014/0168963 A1	6/2014	Stone et al.
2014/0168998 A1	6/2014	Tang et al.
2014/0268761 A1	9/2014	Raleigh et al.
2014/0373348 A1	12/2014	Li

FOREIGN PATENT DOCUMENTS

CN	202629916 U	12/2012
CN	102889549 A	1/2013
DE	202005016441 U1	2/2007
EP	1078301 A1	2/2001
EP	1528603 A2	5/2005
EP	1988576 A1	11/2008
EP	2039985 A2	3/2009
EP	2092859 A1	8/2009
EP	2172696 A1	4/2010
EP	2378337 A2	10/2011
EP	2416062 A2	2/2012
EP	2448021 A2	5/2012
EP	2553331 A1	2/2013
EP	2622267 A1	8/2013
GB	2421584 A	6/2006
JP	2003195790 A	7/2003
JP	2005024706 A	1/2005
JP	2005217094 A	8/2005
JP	2005327820 A	11/2005
JP	2007035951 A	2/2007
JP	2007281260 A	10/2007
JP	2011060575 A	3/2011
JP	2012054115 A	3/2012
JP	2012113276 A	6/2012
WO	2004051223 A2	6/2004
WO	2006033770 A2	3/2006
WO	2006126123 A1	11/2006
WO	2008047335 A1	4/2008
WO	2008122941 A1	10/2008
WO	2009064607 A1	5/2009
WO	2010010494 A1	1/2010
WO	2010033545 A2	3/2010
WO	2010130732 A1	11/2010
WO	2011041813 A1	4/2011
WO	2011042837 A1	4/2011
WO	2011123267 A1	10/2011

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	2012021718	A1	2/2012
WO	2012095242	A1	7/2012
WO	2012121718	A1	9/2012

OTHER PUBLICATIONS

“General Catalog—2012,” Thorlux Lighting, Dec. 2012, 164 pages.
Tracepro, “LED Reflector and Lens Simulation Using TracePro Illumination Design and Analysis Software,” White Paper, Oct. 2013, 11 pages.

Tsai, J. et al., “LED Backlight Module by a Lightguide-Diffusive Component With Tetrahedron Reflector Array,” *J. Display Tech.*, vol. 8, No. 6, Jun. 2012, pp. 321-328.

Hubbell Lighting, “Universal Lighting Technologies Invention Disclosure,” Jun. 14, 2012, 15 pages.

Wang, K. et al., “Freeform LED Lens for Rectangularly Prescribed Illumination,” *J. Opt. A: Pure Appl. Opt.*, No. 11, Aug. 2009, 105501, 10 pages.

Wang, K. et al., “New reversing design method for LED uniform illumination,” *Optics Express*, vol. 19, Issue S4, Jul. 4, 2011, pp. A830-A840.

West, R.S. et al., “43.4: High Brightness Direct LED Backlight for LCD-TV,” *SID 03 Digest*, May 2003, 4 pages.

Wu, D. et al., “Freeform Lens Design for Uniform Illumination with Extended Source,” 2011 *Int'l Conf. Elecs. Packaging Tech. & High Density Packaging*, Aug. 2011, pp. 1085-1089.

Wu, R. et al., “Optimization Design of Irradiance Array for LED Uniform Rectangular Illumination,” *Applied Optics*, vol. 1, No. 13, May 2012, pp. 2257-2263.

Zhenrong, Z. et al., “Freeform Surface Lens for LED Uniform Illumination,” *Applied Optics*, vol. 48, No. 35, Dec. 2009, pp. 6627-6634.

Zhu, Z. et al., “Uniform Illumination Design by Configuration of LED Array and Diffuse Reflection Surface for Color Vision Application,” *J. Display tech*, vol. 7, No. 2, Feb. 2011, pp. 84-89.

P.R. 4-3 Joint Claim Construction and Prehearing Statement, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, filed Jan. 27, 2017, pp. 1-20.

Adaptive Micro Systems, LLC, “Signs—Sealed and Delivered! Adaptive’s Approach to Heat Management,” Mar. 2008, 2 pages.

“Advanced Lighting Guidelines,” 2001 Edition, New Buildings Institute, Inc., Jul. 20, 2001, 394 pages.

Dieker, et al., U.S. Appl. No. 61/659,828, filed Jun. 14, 2012, “Asymmetric Area Lighting Lens with Improved Uniformity,” 14 pages.

Barco, “DB-x20 Digital Billboard Out-of-Home Media LED Screen,” Apr. 2009, 6 pages.

Batinsey, J., “Outdoor Lighting Ordinance Guide,” Jun. 2006, 17 pages.

Chang, R. et al., “LED Backlight Module by Lightguide-Diffusive Component,” *Journal of Display Technology*, vol. 8, No. 2, Feb. 2012, pp. 79-86.

Chen, C. et al., “P-72: Inclined LED Array for Large-Sized Backlight System,” *Society for Information Display, International Symposium, Digest of Technical Papers, SID 05 Digest*, May 2005, pp. 558-561.

“Unified Development Code,” Chapter 10 of the Tyler Code of Ordinances, City of Tyler, Apr. 23, 2008, 378 pages.

Defendants Invalidation Contentions, Appendix A, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-19.

Defendants Invalidation Contentions, ExhibitA01, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-80.

Defendants Invalidation Contentions, ExhibitA02, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-74.

Defendants Invalidation Contentions, ExhibitA03, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-52.

Defendants Invalidation Contentions, ExhibitA04, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-53.

Defendants Invalidation Contentions, ExhibitB01, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-34.

Defendants Invalidation Contentions, ExhibitB02, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-36.

Defendants Invalidation Contentions, ExhibitB03, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-21.

Defendants Invalidation Contentions, ExhibitB04, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-27.

Defendants Invalidation Contentions, ExhibitC01, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-52.

Defendants Invalidation Contentions, ExhibitC02, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-67.

Defendants Invalidation Contentions, ExhibitC03, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-35.

Defendants Invalidation Contentions, ExhibitC04, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-87.

Defendants Invalidation Contentions, ExhibitC05, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-51.

Defendants Invalidation Contentions, ExhibitC06, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-79.

Defendants Invalidation Contentions, ExhibitD01, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-109.

Defendants Invalidation Contentions, ExhibitD02, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-186.

Defendants Invalidation Contentions, ExhibitD03, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-133.

Defendants Invalidation Contentions, ExhibitD04, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-111.

Defendants Invalidation Contentions, ExhibitD05, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-133.

Defendants Invalidation Contentions, ExhibitD06, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-135.

Defendants Invalidation Contentions, ExhibitE01, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-169.

Defendants Invalidation Contentions, ExhibitE02, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-192.

Defendants Invalidation Contentions, ExhibitE03, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-443.

Defendants Invalidation Contentions, ExhibitE04, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-171.

Defendants Invalidation Contentions, ExhibitF01, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-34.

Defendants Invalidation Contentions, ExhibitF02, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-13.

(56)

References Cited

OTHER PUBLICATIONS

- Defendants Invalidation Contentions, ExhibitF03, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-100.
- Defendants Invalidation Contentions, ExhibitG01, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-30.
- Defendants Invalidation Contentions, ExhibitG02, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-11.
- Defendants Invalidation Contentions, ExhibitG03, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-94.
- Defendants Invalidation Contentions, ExhibitH01 (redacted), *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-60.
- Defendants Invalidation Contentions, ExhibitH02 (redacted), *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-26.
- Defendants Invalidation Contentions, ExhibitH03 (redacted), *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-71.
- Defendants Invalidation Contentions, ExhibitH04 (redacted), *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-151.
- Defendants Invalidation Contentions, ExhibitH05 (redacted), *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-181.
- Defendants Invalidation Contentions, ExhibitI01 (redacted), *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-168.
- Deepa, R. et al., "Modeling and Simulation of Multielement LED Source," The Illuminating Engineering Institute of Japan, *Journal of Light & Visual Environment*, vol. 35, No. 1, Jun. 21, 2011, pp. 34-41.
- Deepa, R. et al., Optimization of multi-element LED source for uniform illumination of plane surface, *Optical Society of America, Optics Express*, vol. 19, No. S4, Jul. 4, 2011, pp. A639-A648.
- Design & Engineering Services, "Advanced Lighting Systems for Externally Lit Billboards," ET 08.12 Report, Southern California Edison, Jan. 4, 2010, 58 pages.
- Whang, et al., "Designing Uniform Illumination Systems by Surface-Tailored Lens and Configurations of LED Arrays," *IEEE 2009, Journal of Display Technology*, vol. 5, No. 3, Mar. 2009, pp. 94-103.
- Ding, Y., "Freeform LED lens for uniform illumination," *Optics Express*, vol. 16, No. 17, Aug. 18, 2008, 9 pages.
- Lee, S., "How to Select a Heat Sink," <http://www.electronics-cooling.com/1995/06/how-to-select-a-heat-sink/>, Jun. 1, 1995, pp. 1-10.
- Huang, K. et al., "Free-form lens design for LED indoor illumination," *Proc. of SPIE*, vol. 7852, Nov. 15, 2010, pp. 78521D-1-78521D-8.
- "The Lighting Handbook," 12-18, IES 10th Edition, Dec. 6, 2011, 1 page.
- "The Lighting Handbook," 8-17, IES 10th Edition, Dec. 6, 2011, 2 pages.
- Steigerwald, et al., "Illumination with Solid State Lighting Technology," *IEEE Journal on Selected Topics in Quantum Electronics*, vol. 8, No. 2, Mar./Apr. 2002, pp. 310-320.
- Defendant Irvin International, Inc.'s Answer, Affirmative Defenses, and Counterclaims to Plaintiff's Complaint, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, filed Jun. 6, 2016, pp. 1-41.
- Jeon, H. et al., Illuminance Distribution and Photosynthetic Photon Flux Density Characteristics of LED Lighting with Periodic Lattice Arrangements, *Transactions on Electrical and Electronic Materials*, vol. 13, No. 1, Feb. 25, 2012, pp. 16-18.
- Jiang, J., "Optical design of a freeform TIR lens for LED street-light," *Optik—International Journal for Light and Electron Optics*, vol. 121, Issue 19, Oct. 2010, pp. 1761-1765.
- Defendants Corrected Joint Invalidation Contentions, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-108.
- Keller, A., "Signs of the Times," *Floridatrend.com*, Dec. 2011, pp. 50-53.
- Kim, Yu-Sin, et al., "Development of a Numerical Model for the Luminous Intensity Distribution of a Planar Prism LED Luminaire for Applying an Optimization Algorithm," *Luekos*, vol. 9, No. 1, Jul. 2012, pp. 57-72.
- Lakkio, O., "Winning the Optical Challenges in LED Street Lighting," *Digi-Key*, May 27, 2011, 5 pages.
- Lamar's First Amended Answer and Counterclaims to Plaintiff's Complaint, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, filed Jun. 8, 2016, pp. 1-61.
- "BILLIE—The Bright Answer for Billboard Lighting," *Ledil Product Release*, Dec. 8, 2013, 2 pages.
- "LEDIL Standard Optics for Osram LEDs," *Ledil*, Jan. 2011, 60 pages.
- "Strada 6in1 Module for Streeting Lighting," *Ledil*, 2010, 1 page, <<http://ledil.fi/sites/default/files/Documents/Technical/Articles/Article_2.pdf>>.
- LEDIL, "Who is LEDIL?," www.ledil.com, Mar. 22, 2011, 17 pages.
- LEDIL, "Who is LEDIL?," www.ledil.com, May 22, 2011, 68 pages.
- Lee, S. et al., "Driving Performance and Digital Billboards Final Report," Virginia Tech Transportation Institute, Center for Automotive Safety Research, Mar. 22, 2007, 90 pages.
- Lee, Hsiao-Wen, et al., "Improvement of Illumination Uniformity for LED Flat Panel Light by Using Micro-Secondary Lens Array," *Optics Express*, vol. 20, No. S6, Nov. 5, 2012, 11 pages.
- Lighting Solutions Techzone Magazine, "Look Inside Today's Lighting Technology," *Digi-Key Corporation*, TZL112.US, Jun. 7, 2011, 76 pages.
- Liu, Peng, et al., "Optimized Design of LED Freeform Lens for Uniform Circular Illumination," *Journal of Zhejiang University—Science C (Computers & Electronics)*, 2012, pp. 929-936.
- Lo, Y. et al., "Optical Design of a Butterfly Lens for a Street Light Based on a Double-Cluster LED," *Microelectronics Reliability*, vol. 52, May 2011, pp. 889-893.
- LED Professional Review, Issue 17, Jan./Feb. 2010, 52 pages.
- LED Professional Review, Issue 18, Mar./Apr. 2010, 64 pages.
- LED Professional Review, Issue 19, May/Jun. 2010, 64 pages.
- LED Professional Review, Issue 20, Jul./Aug. 2010, 48 pages.
- LED Professional Review, Issue 21, Sep./Oct. 2010, 64 pages.
- LED Professional Review, Issue 22, Nov./Dec. 2010, 60 pages.
- Defendant American Lighting Technologies, Inc. D/B/A Lighting Technologies' Amended Answer, Affirmative Defenses and Counterclaims to Plaintiff's Complaint, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, filed Jun. 27, 2016, pp. 1-43.
- Defendant American Lighting Technologies, Inc. D/B/A Lighting Technologies' Answer and Affirmative Defenses to Plaintiff's Complaint, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, filed Jun. 6, 2016, pp. 1-37.
- Luminautics, "LED Display Primer," 2011, pp. 1-21.
- Luo, X. et al., "Automated Optimization of an Aspheric Light-Emitting Diode Lens for Uniform Illumination," *Applied Optics*, vol. 50, No. 20, Jul. 2011, pp. 3412-3418.
- Moreno, I., "Configuration of LED Arrays for Uniform Illumination," *Proc. of SPIE*, vol. 5622, Oct. 2004, pp. 713-718.
- "LED Ad-Poster Billboard Luminaire," *Neptun*, Jan. 2012, 1 page.
- "LED Ad-Poster Billboard Luminaire," *Neptun*, May 25, 2011, 1 page.
- Office Action Summary received in U.S. Appl. No. 14/630,500, mailed Dec. 31, 2015, 65 pages.
- "Street Lighting with LED Lights Sources Application Note," *OSRAM Opto Semiconductors*, Jan. 2009, pp. 1-10.
- Parkyn, William A., "Segmented Illumination Lenses for Steplighting and Wall-Washing," *SPIE Conference on Current Development in Optical Design and Optical Engineering VIII*, Denver, Colorado, Jul. 1999, *SPIE* vol. 3779, pp. 363-370.

(56)

References Cited

OTHER PUBLICATIONS

- Qin, Z. et al., "Analysis of Condition for Uniform Lighting Generated by Array of Light Emitting Diodes with Large View Angle," *Optics Express*, vol. 18, No. 16, Aug. 2010, pp. 17460-17476.
- Ramane, D. et al., "Automated Test Jig for Uniformity Evaluation of Luminaries," *IJAET*, vol. 3, No. 1, Mar. 2012, pp. 41-47.
- Ramane, D. et al., Optimization of multi-element LED source for uniform illumination of plane surface, *Optical Society of America, Optics Express*, vol. 19, No. S4, Jul. 4, 2011, pp. A639-A648.
- "Starbeam," Thorlux Lighting, Brochure, Aug. 2012, 8 pages.
- "Starbeam," Thorlux Lighting, Brochure, Jul. 2015, 4 pages.
- "Starbeam," Thorlux Lighting, Brochure, Mar. 2014, 16 pages.
- "Starbeam," Thorlux Lighting, Technical Information, Mar. 2014, 10 pages.
- "Starflood," Thorlux Lighting, Brochure, Mar. 2016, 16 pages.
- "Starflood; High performance mini LED floodlights," Thorlux Lighting, Retrieved Jul. 21, 2016, 16 pages, <<<http://www.thorlux.com/luminaires/starflood>>>.
- Cheng, et al., "The Research of LED Arrays for Uniform Illumination," *Advances in Information Sciences and Service Sciences (AISS)*, vol. 4, No. 10, Jun. 2012, pp. 174-182.




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 2




FIG. 3B




FIG. 3A




FIG. 3C




FIG. 4B




FIG. 4A




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 7A





FIG. 7B






FIG. 8B




FIG. 8C




FIG. 8D




FIG. 8E




FIG. 8F




FIG. 8G




FIG. 8H




FIG. 8I




FIG. 8J




FIG. 9

LIGHTING ASSEMBLY WITH MULTIPLE LIGHTING UNITS

This is a continuation of U.S. patent application Ser. No. 15/162,278, filed May 23, 2016, which is a continuation of U.S. patent application Ser. No. 14/992,680, filed Jan. 11, 2016, which is a continuation of U.S. patent application Ser. No. 14/635,907, filed Mar. 2, 2015, which is a continuation of U.S. patent application Ser. No. 13/836,517, filed Mar. 15, 2013, which claims the benefit of U.S. Provisional Application No. 61/677,346, filed on Jul. 30, 2012, which applications are hereby incorporated herein by reference.

The following patents and applications are related:

U.S. Pat. Appl. No. 61/677,340, filed Jul. 20, 2012
 U.S. Pat. Appl. No. 61/677,346, filed Jul. 30, 2012
 U.S. Pat. Appl. No. 61/677,352, filed Jul. 30, 2012
 U.S. patent application Ser. No. 13/836,517, filed Mar. 15, 2013 (now U.S. Pat. No. 8,974,077)
 U.S. patent application Ser. No. 13/836,612, filed Mar. 15, 2013 (now U.S. Pat. No. 8,870,410)
 U.S. patent application Ser. No. 13/836,710, filed Mar. 15, 2013 (now U.S. Pat. No. 9,062,873)
 U.S. patent application Ser. No. 14/137,306, filed Dec. 30, 2013 (now U.S. Pat. No. 8,985,806)
 U.S. patent application Ser. No. 14/137,343, filed Dec. 20, 2013 (now U.S. Pat. No. 8,870,413)
 U.S. patent application Ser. No. 14/137,380, filed Dec. 20, 2013 (now U.S. Pat. No. 9,068,738)
 U.S. patent application Ser. No. 14/630,500, filed Feb. 24, 2015 (co-pending)
 U.S. patent application Ser. No. 14/635,907, filed Mar. 2, 2015 (now U.S. Pat. No. 9,234,642)
 U.S. patent application Ser. No. 14/706,634, filed May 7, 2015 (now U.S. Pat. No. 9,212,803)
 U.S. patent application Ser. No. 14/968,520, filed Dec. 14, 2015 (co-pending)
 U.S. patent application Ser. No. 14/992,680, filed Jan. 11, 2016 (now U.S. Pat. No. 9,349,307)
 U.S. patent application Ser. No. 15/162,278, filed May 23, 2016 (co-pending)
 U.S. patent application Ser. No. 15/208,483, filed Jul. 12, 2016 (now U.S. Pat. No. 9,514,663)
 U.S. patent application Ser. No. 15/208,521, filed Jul. 12, 2016 (now U.S. Pat. No. 9,524,661)
 U.S. patent application Ser. No. 15/216,562, filed Jul. 21, 2016 (co-pending)
 U.S. patent application Ser. No. 15/216,595, filed Jul. 21, 2016 (now U.S. Pat. No. 9,542,870)

TECHNICAL FIELD

The following disclosure relates to lighting systems and, more particularly, to lighting systems using light emitting diodes to externally illuminate signs.

SUMMARY

The present invention, in one aspect thereof, comprises a back panel for use in a light emitting diode (LED) lighting assembly. An extruded substrate formed of a thermally conductive material is provided, the substrate having a plurality of fins extending from a first side of the substrate, each of the fins having a substantially rectangular shape oriented so that a longitudinal axis of the fin is substantially parallel to a longitudinal axis of the substrate. At least some of the fins include a hole formed through the fin to enable heated air to rise through the fins. A plurality of LEDs are

mounted on a second side of the substrate, and oriented in a longitudinal orientation with the fins oriented parallel to the bottom edge of a surface to be illuminated, such that heat rises perpendicular to the surface of the fin.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding, reference is now made to the following description taken in conjunction with the accompanying drawings in which:

FIG. 1A illustrates one embodiment of a billboard that may be externally lighted by one or more lighting assemblies;

FIGS. 1B-1D illustrate embodiments of angular positions of the lighting assembly of

FIG. 1 relative to the billboard;

FIG. 2 illustrates one embodiment of a lighting assembly that may be used to light the billboard of FIG. 1;

FIGS. 3A and 3B illustrate one embodiment of a back panel that may be used in the lighting assembly of FIG. 2;

FIG. 3C illustrates one embodiment of the back panel of FIGS. 3A and 3B with a light panel and an optics panel that may also be used in the lighting assembly of FIG. 2;

FIGS. 4A and 4B illustrate one embodiment of a light panel that may be used with the lighting assembly of FIG. 2;

FIGS. 5A, 5B, 5C and 5D illustrate one embodiment of an optics panel that may be used with the lighting assembly of FIG. 2;

FIGS. 6A-6C illustrate a more detailed embodiment of the lighting assembly of FIG. 2;

FIGS. 7A and 7B illustrate an embodiment of a back panel that may be used with the lighting assembly of FIGS. 6A-6C;

FIG. 8A illustrates an embodiment of an LED assembly and an optics panel that may be used with the lighting assembly of FIG. 6;

FIGS. 8B-8J illustrates embodiments of the optics panel of FIG. 8A and optical elements that may be used to form part of the optics panel; and

FIG. 9 illustrates a more detailed embodiment of the lighting assembly of FIG. 2.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

Billboards, such as those commonly used for advertising in cities and along roads, often have a picture and/or text that must be externally illuminated to be visible in low-light conditions. As technology has advanced and introduced new lighting devices such as the light emitting diode (LED), such advances have been applied to billboards. However, current lighting designs have limitations and improvements are needed. Although billboards are used herein for purposes of example, it is understood that the present disclosure may be applied to lighting for any type of sign that is externally illuminated.

Referring to FIG. 1A, one embodiment of a billboard **100** is illustrated. The billboard **100** includes a surface **102** onto which a picture and/or text may be painted, mounted, or otherwise affixed. The surface **102** may be any size, such as a commonly used size having a width of forty-eight feet wide and a height of fourteen feet. The surface **102** may be provided by placing a backing material on a frame **104** made of steel and/or other materials. The frame **104** may be mounted on one or more support poles **106**, which may be considered part of the frame **104** or separate from the frame

104. The billboard 100 may include a walkway or other support structure 108 that enables the surface 102 to be more easily accessed.

One or more lighting assemblies 110 may be coupled to the walkway 108 (e.g., to a safety rail or to the walkway itself) and/or to another structural member of the billboard 100 to illuminate some or all of the surface 102 in low light conditions. The lighting assembly 110 may be mounted at or near a top edge 112 of the billboard 100, a bottom edge 114 of the billboard 100, a right edge 116 of the billboard 100, and/or a bottom edge 118 of the billboard 100. The lighting assembly 110 may be centered (e.g., located in approximately the center of the billboard 100) or off center as illustrated in FIG. 1A.

With additional reference to FIGS. 1B-1D, a surface 120 of the lighting assembly 110 may be parallel with respect to the surface 102 of the billboard 100 (FIG. 1B), may be perpendicular with respect to the surface 102 (FIG. 1C), or may be angled with respect to the surface 102 (FIG. 1D). It is understood that the lighting assembly 110 may be placed in many different orientations and locations relative to the billboard 100 and to one another, and the illustrated positions are only for purposes of example. Furthermore, it is understood that references to “top,” “bottom,” “left,” and “right” are used in the present disclosure for purposes of description and do not necessarily denote a fixed position. For example, the billboard 100 may be turned on end, and the referenced “top,” “bottom,” “left,” and “right” edges may still be readily identifiable although the “top” edge would be the “left” edge or the “right” edge.

One problem with current lighting technology is that it can be difficult to direct light only onto the surface 102 and even more difficult to do so evenly. This may be due partly to the placement of the lighting assembly 110, as shown in FIGS. 1B-1D. As the lighting assembly 110 is off center relative to the surface 102, light emitted from the lighting assembly 110 may not evenly strike the surface 102. One problem with uneven illumination is that certain parts of the surface 102 may be more brightly illuminated than other parts. This creates “hot spots” that may be undesirable. Attempting to evenly illuminate the surface 102 may cause light to be directed past the edges 112, 114, 116, and 118 as attempts are made to balance out hot spots in particular areas. However, light that does not strike the surface 102 is wasted and may create problems (e.g., light pollution), as well as waste illumination that could be used for the surface 102.

In addition to the difficulties of evenly illuminating the surface 102, the use of LEDs in an exterior lighting environment involves issues such as heat dissipation and protecting the LEDs against environmental conditions such as moisture. The presence of moving mechanical features such as fans that may be used to provide increased airflow for cooling may create additional reliability problems. Due to the difficulty and expense of replacing and/or repairing the lighting assembly 110 in combination with the desire to provide consistent lighting while minimizing downtime, such issues should be addressed in a manner that enhances reliability and uptime.

Referring to FIG. 2, one embodiment of a lighting assembly 200 is illustrated. The lighting assembly 200 provides a more detailed embodiment of the lighting assembly 110 of FIG. 1. The lighting assembly 200 includes a back panel 202, a light panel 204 (e.g., a printed circuit board (PCB)) having a plurality of LEDs (not shown) mounted thereon, and an optics panel 206. As will be described below in more detailed examples, light from the LEDs of the light panel

204 may be directed by the optics panel 206 to illuminate the surface 102 of the billboard 100 of FIG. 1. The back panel 202 may be configured to serve as a supporting substrate for the light panel 204 and optics panel 206, as well as to dissipate heat produced by the LEDs.

It is understood that any of the back panel 202, light panel 204, and optics panel 206 may actually be two or more physical substrates rather than a single panel as illustrated in FIG. 2. Furthermore, it is understood that there may be additional panels positioned behind the back panel 202, in front of the optics panel 206, and/or between the back panel 202 and light panel 204 and/or between the light panel 204 and optics panel 206.

Referring to FIGS. 3A-3C, one embodiment of the back panel 202 is illustrated with a front surface 302 and a back surface 304. The back panel 202 includes a top edge 306, a bottom edge 308, a right edge 310, and a left edge 312. The panel 202 may be formed of one or more thermally conductive materials (e.g., aluminum) and/or other materials.

The front surface 302 provides a mounting surface for the light panel 204. In some embodiments, the front surface 302 of the panel 202 may include one or more protrusions 314a and 314b that are substantially parallel to the top edge 306. The protrusions 314a and 314b may be configured to protect the light panel 204 from moisture. Although only two protrusions 314a and 314b are illustrated, it is understood that a single protrusion may be provided or three or more protrusions may be provided. Furthermore, such protrusions may vary in length, shape (e.g., may have angled or curved surfaces), orientation, and/or location on the front surface 302.

Referring specifically to FIG. 3C, a light panel 204 and an optical panel 206 may be mounted under the protrusion 314a (FIG. 3C). Moisture running down the front surface 302 in the direction of arrow 316 may strike the protrusion 314a and be directed away from the light panel 204 and optical panel 206 as shown by arrow 318. Although not shown, moisture may also be directed length down the protrusion 314a. Accordingly, protrusion 314a may serve as a gutter and aid in directing moisture away from a joint 320 where the optical panel 206 abuts the front surface 302. This may be beneficial even when a moisture resistant compound is used to seal the joint 320. In embodiments where there are multiple light panels 204 arranged vertically on the front surface 302, there may be a protrusion positioned above each light panel 204. For example, the protrusion 314a may be positioned directly above one light panel 204 and the protrusion 314b may be positioned directly above another light panel 204.

Referring specifically to FIG. 3B, the back surface 304 may be configured to increase heat dissipation. For example, the back surface 304 may be configured with a heat sink provided by fins 322a-322N, where N denotes a total number of fins. The fins 322a-322N increase the surface area of the back surface 304, thereby providing for additional heat dissipation to the surrounding air. The fins 322a-322N may be formed as part of the panel 202 or may be otherwise coupled to the panel 202 (e.g., may be part of a discrete heat sink that is coupled to the back surface 304). Some or all of the fins 322a-322N may be angled, as shown by fins 322a and 322b. In some embodiments, holes (not shown) may be provided in some or all of the fins 322a-322N to aid in air circulation. In such embodiments, the holes may cause a chimney effect in which heated air rises through the holes and is replaced by cooler air. This may be particularly effective in environments where natural air movement is limited.

Referring to FIGS. 4A and 4B, one embodiment of a single PCB 402 of the light panel 204 is illustrated. In the present example, the light panel 204 may include multiple PCBs 402, although it is understood that any number of PCBs may be used based on design issues such as the amount of illumination needed, the amount of illumination provided by a single PCB 402, the size of the surface 102 of the billboard 100, and/or other factors. As shown in the present embodiment with a substantially rectangular cross-section, the PCB 402 includes a front surface 404, a back surface 406, a top edge 408, a bottom edge 410, a right edge 412, and a left edge 414.

The PCB 402 may include one or more strings of LEDs 416, with multiple LEDs 416 in a string. For example, a string may include eight LEDs 416 and each PCB 402 may include two strings for a total of sixteen LEDs 416. In this configuration, a light panel 204 having eight PCBs 402 would include ninety-six LEDs 416. It is understood that although the PCBs 402 are shown as being substantially identical, they may be different in terms of size, shape, and other factors for a single light panel 204.

In the present example, the LEDs 416 are surface mounted, but it is understood that the LEDs 416 may be coupled to the panel 204 using through hole or another coupling process. The surface mounted configuration may ensure that a maximum surface area of each LED 416 is in contact with the PCB 402, which is in turn in contact with the back panel 202 responsible for heat dissipation. Each string of LEDs may receive a constant current with the current divided evenly among the LEDs 416.

Referring to FIGS. 5A, 5B, 5C and 5D, one embodiment of a single lens panel 500 of the optics panel 206 is illustrated. In the present example, the optics panel 206 may include multiple lens panels 500, although it is understood that any number of lens panels may be used based on design issues such as the number, arrangement, and orientation of the LEDs 416, the size of the surface 102, and/or other factors. As shown in the present embodiment with a substantially rectangular cross-section that is configured for use with the PCB 402 of FIG. 4, a single lens panel 500 includes a front surface 502, a back surface 504, a top side 506, a bottom side 508, a right side 510, and a left side 512. The sides 506, 508, 510, and 512 may form a cavity into which the PCB 402 may fit, thereby providing protection for the PCB 402 from environmental conditions such as moisture.

The lens panel 500 may include a beveled or angled top side 506 and/or bottom side 508 as illustrated in FIG. 5B. The beveling/angling may aid in preventing moisture from reaching the PCB 402 under the lens panel 500, as water will more readily flow from the area of the joint 320 (FIG. 3C) due to the angled surface than if the top side 506 was relatively flat.

The lens panel 500 may include multiple optical elements 514. A single optical element 514 may be provided for each LED 416, a single optical element 514 may be provided for multiple LEDs 416, and/or multiple optical elements 514 may be provided for a single LED 416. In some embodiments, the optical elements 514 may be provided by a single multi-layer optical element system provided by the lens panel 500.

In the present example, the optical elements 514 are configured so that the light emitted from each LED 416 is projected onto the entire surface 102 of the billboard 100. In other words, if all other LEDs 416 were switched off except for a single LED 416, the entire surface 102 would be illuminated at the level of illumination provided by the single LED 416. In one embodiment, the rectangular target

area of the surface 102 would be evenly illuminated by the LED 416, while areas beyond the edges 112, 114, 116, and 118 would receive no illumination at all or at least a minimal amount of illumination from the LED 416. What is meant by “evenly” is that the illumination with a uniformity that achieves a 3:1 ratio of the average illumination to the minimum. Thus, by designing the lens in such a manner, when all LEDs are operating, the light from the collective thereof will illuminate the surface at the 3:1 ratio. When one or more LEDs fail, the overall illumination decreases, but the uniformity maintains the same uniformity. Also, as described hereinabove, the “surface” refers to the surface that is associated with a particular LED panel. It may be that an overall illuminated surface is segmented and multiple panels are provided, each associated with a particular segment.

FIG. 5C illustrates a detail of the lens assembly. Each of the diodes 416 is mounted on the board 408 at a minimum distance. Overlying the board and LEDs 416 is transparent lens substrate 520. This substrate 520 has a plurality of lens structures 522, each associated with one of the LEDs 416, such that each of the LEDs 416 has the light emitted therefrom directed outward towards the surface, each lens structure being substantially the same. The minimum distance is designed such that overlapping light from adjacent LEDs does not create interference patterns and result in dead spots on the surface. The lens structure 522 is designed to create the 3:1 uniformity and also, the lens structure is designed to “direct” the light from an edge of the surface to cover the entire surface. This is shown by the angle of the light rays in FIG. 5C. Also, the beveled edge 530 will basically surround the PCB 402, thus protecting it from moisture. The lens substrate 520 is secured with screws (not shown).

FIG. 5D illustrates a detail of the lens structure 522. This structure includes an interior surface 524 and an exterior surface 526 that shapes and directs the light in the correct pattern. This is an acrylic material. With such a design, the lighting assembly can be disposed at an edge of the surface to illuminate the entire surface.

In some embodiments, as shown in FIG. 1, two lighting assemblies 110 may be used. Each lighting assembly may be powered by a separate power supply (not shown), and may be configured to illuminate the entire surface 102. In such an embodiment, if one power supply fails, the remaining lighting assembly 110 will still illuminate the entire surface 102, although at a lesser intensity than when both lighting assemblies 110 are functioning. This provides evenly distributed illumination when both lighting assemblies 110 are functioning correctly, and continues to provide evenly distributed illumination when one lighting assembly 110 malfunctions. Accordingly, the entire surface 102 of the billboard 100 may be illuminated even when an entire lighting assembly 110 has malfunctioned and is providing no illumination at all due to the redundancy provided by configuration of the lighting assemblies 110.

Furthermore, in some embodiments as described above, each LED 416 of a single lighting assembly 110 may be configured via the optical elements 514 to illuminate the entire surface 102. In such embodiments, if one or more LEDs 416 or strings of LEDs fails, the remaining LEDs 416 will still illuminate the entire surface 102, although at a lesser intensity than when the failed LEDs 416 are functioning. This provides evenly distributed illumination when all LEDs 416 are functioning correctly, and continues to provide evenly distributed illumination when one or more LEDs are malfunctioning. Accordingly, the billboard 100

may be illuminated even when multiple LEDs **416** have malfunctioned and are providing no illumination at all due to the redundancy provided by configuration of the lighting assemblies **110**.

It is understood that some embodiments may direct substantially all illumination from a lighting assembly **110** evenly across the surface **102** while some illumination is not evenly distributed. For example, substantially all LEDs **416** may be directed to each evenly illuminate the surface **102** with the exception of a relatively small number of LEDs **416**. In such cases, the illumination provided by the remaining LED or LEDs **416** may be directed to one or more portions of the surface **102**. If done properly, this may be accomplished while minimizing any noticeable unevenness in the overall illumination, even if one of the remaining LEDs **416** malfunctions. For example, the lighting assembly **110** may be configured to direct the illumination provided by one LED **416** to only the left half of the surface **102**, while directing the illumination from another LED **416** to only the right half of the surface **102**. The loss of one of these two LEDs may not noticeably impact the illumination of the surface **102**. It is understood that such variations are within the scope of this disclosure.

In embodiments where the illumination is evenly distributed across the surface **102**, it is understood that the optics panel **206** may be configured specifically for the light panel **204** and the surface **102**. For example, assuming the surface **102** is forty-eight feet wide and sixteen feet high, the lens panel **500** of FIG. **5** may be specifically designed for use with the PCB **402** of FIG. **4**. This design may be based on the particular layout of the PCB **402** (e.g., the number and arrangement of the LEDs **416**), the amount of illumination provided by the LEDs **416**, the size of the surface **102**, the distance between the lens panel **500** and the surface **102**, the angle at which the lens panel **500** is mounted relative to the surface **102** (e.g., FIGS. **1B-1D**), and/or other factors. Accordingly, changes in any of these factors may entail a change in the design of the lens panel **500** in order to again evenly distribute the illumination provided by each LED **416** across the entire surface **102**. It is understood that various standard configurations of the lighting assembly **110** may be developed for various billboard and/or other externally illuminated signs so that a particular configuration may be provided based on the parameters associated with a particular billboard and/or externally illuminated sign.

Referring to FIGS. **6A-6C**, one embodiment of a lighting assembly **600** is illustrated that provides a more detailed embodiment of the lighting assembly **200** of FIG. **2**. The lighting assembly **600** includes a back panel **602**, a light panel formed by multiple LED assemblies (denoted by reference number **800** in FIG. **8A**), and an optics panel formed by multiple lens panels **604**. Accordingly, as described previously, the light panel **204** in the current example is represented by multiple LED assemblies **800** and the optics panel **206** is represented by multiple lens panels **604**. In the present embodiment, the lighting assembly **600** includes four LED assemblies **800** and four lens panels **604**.

Although various attachment mechanisms (e.g., threaded screws, bolts, and/or other fasteners) may be used to couple the lens panels and LED assemblies to the back panel **602**, the present embodiment uses multiple threaded fasteners **605** (e.g., screws) that extend through the lens panels and the LED assemblies and engage threaded holes in the back panel **602**.

The lighting assembly **600** is also illustrated with a mounting plate **606** that couples to the back panel **602** and to an adjustable mounting bracket **608**. The adjustable

mounting bracket **608** may be used to couple the lighting assembly **600** to a portion of the billboard **100** (FIG. **1**) and/or to another support member. A power supply enclosure **610** may be coupled to the mounting plate **606** and configured contain a power supply (not shown) capable of supplying power to LEDs of the LED assemblies **800**. It is noted that separating the power supply from the back panel **602** may aid in heat dissipation by the back panel **602** as it does not have to dissipate heat from the power supply to the same extent as if the power supply was mounted directly to the back panel **602**.

The location of the power supply may also be beneficial as snow not melted by the heat produced by the LED may be melted by heat produced by the power supply. This may aid in reducing snow buildup on the LEDs.

With additional reference to FIGS. **7A** and **7B**, one embodiment of the back panel of FIG. **602** is illustrated. A front surface **700** includes multiple protrusions **702** that may be configured to protect the light panels (not shown) against moisture as previously described. The front surface **700** may include additional protrusions **704**.

A back surface **706** includes multiple fins **708** that form a heat sink to aid in the dissipation of heat from the back panel **602**. In the present example, the fins **708** are substantially rectangular in shape. In the present example, the back panel **602** is extruded and the fins **708** run parallel to the top edge with a longitudinal axis of each fin **708** being substantially parallel to a longitudinal axis of the back panel **602**. Forming the fins **708** in a vertical manner is possible, but may increase the cost of the back panel **602** due to the extrusion process. As shown, the fins **708** may be substantially perpendicular to the back surface **706**, and/or may be angled. In the present example, the fins **708** are angled such that near the top of the back panel **702**, the fins **708** are angled towards the top.

Because the fins **708** are parallel to the top edge, heat may be trapped due to its inability to rise vertically. Accordingly, holes **710** may be present in some or all of the fins **708** (marked but not actually visible in the side view of FIG. **7B**) to provide paths for the heat to rise vertically in spite of the orientation of the fins **708**. The holes **710** may create a chimney effect that increases air flow across the fins **708** and aids in the cooling process. In some embodiments, some or all of the fins **708** may be angled such that heat is not trapped.

The back surface **706** may also include a groove **712** that is configured to receive a tongue of the mounting plate **606** in a tongue-in-groove manner.

With additional reference to FIGS. **8A-8J**, embodiments of a single LED assembly **800** and a single lens panel **604** that may be used with the lighting assembly **600** are illustrated. As shown, the single LED assembly **800** and the single optics panel **604** may be configured for use together.

Referring specifically to FIG. **8A**, the LED assembly **800** includes a substrate **802** (e.g., a PCB) onto which are mounted multiple LEDs **804**. In the present example, the LED assembly **800** includes two strings of eight LEDs **804** each for a total of sixteen LEDs **804**. It is understood that this is merely an example, and there may be more or fewer LEDs **804** on the light panel **800**, and the LEDs **804** may be arranged in many different ways on the substrate **802**.

Referring also to FIGS. **8B-8J**, the optics panel **604** may include optical elements **806** arranged on an upper surface **808** of the optics panel **604**. The optics panel **604** may further include sides **810**, **812**, **814**, and **816** that are configured to fit around the edge of the substrate **802** of the light panel **800**. The bottom edge of each side **810**, **812**, **814**, and

816 abuts the front surface **700** of the back panel **602** and may be sealed to the front surface **700** using a moisture resistant sealant.

As shown in FIGS. **8D-8H**, a single optical element **806** may include multiple lens elements designed to distribute the illumination provided by a single LED **804** across a surface such as the surface **102** of FIG. **1**. A first lens element **820** may be positioned proximate to the LED **804**, and additional lens elements **822**, **824**, and **826** may be positioned above the lens element **820**. Multiple optical elements **806** may be combined and formed as a single optics panel **604** that is configured to operate with the LED assembly **800**.

Referring to FIG. **9**, another embodiment of a lighting assembly **900** is illustrated that provides a more detailed embodiment of the lighting assembly **200** of FIG. **2**. The lighting assembly **900** is similar to the lighting assembly **600** of FIG. **6**, but includes six LED assemblies rather than the four six LED assemblies of the lighting assembly **600**. It is understood that the lighting assembly **900** may require a larger power supply than the lighting assembly **600** (e.g., a one hundred and fifty watt power supply instead of a one hundred and twenty watt power supply).

Although the preferred embodiment has been described in detail, it should be understood that various changes, substitutions and alterations can be made therein without departing from the spirit and scope of the invention as defined by the appended claims.

What is claimed is:

1. A lighting assembly comprising:

an assembly body;

a first lighting unit attached to the assembly body, the first lighting unit including a first plurality of light emitting diodes (LEDs) and a first plurality of optical elements arranged over the first plurality of LEDs such that each optical element overlies only one associated LED, wherein the first lighting unit is configured to illuminate a substantially rectangular region; and

a second lighting unit attached to the assembly body and spaced from the first lighting unit, the second lighting unit including a second plurality of LEDs and a second plurality of optical elements arranged over the plurality of LEDs such that each optical element overlies only one associated LED, wherein the second lighting unit is configured to illuminate the substantially rectangular region so that the lighting assembly can illuminate substantially all of the substantially rectangular region so that the region can be illuminated without additional lighting and so that areas beyond edges of the substantially rectangular region receive minimum illumination;

wherein the optical elements are configured so that light emitted from the first and second lighting units illuminates the substantially rectangular area in a manner that does not create hot spots or result in dead spots on the area regardless of whether all of the LEDs of the first and second pluralities of LEDs are functional or only some of the LEDs of the first and second pluralities of LEDs.

2. The lighting assembly of claim **1**, wherein the optical elements are configured so that failure of one or more of the LEDs will cause an illumination level of light emitted from the lighting assembly to decrease while a uniformity of the light emitted from the lighting assembly remains substantially the same.

3. The lighting assembly of claim **2**, wherein each optical element of the plurality of optical elements of the first and

the second lighting units comprises a first part, a second part, and a third part, wherein the first part comprises a first curved surface, wherein the second part comprises a second curved surface that intersects with the first curved surface at a region between the first part and the second part, wherein the first part and the second part each have a peak that is spaced from the region between the first part and the second part, and wherein the third part extends beyond the region between the first part and the second part in a direction away from the associated LED.

4. The lighting assembly of claim **3**, wherein the substantially rectangular region has a length of twenty-four feet.

5. The lighting assembly of claim **3**, wherein the LEDs of the first plurality of LEDs are arranged in rows on a substrate and extend along a longitudinal axis in a plane of a first surface of the substrate, the lighting assembly further comprising a heat sink thermally coupled to a second surface of the substrate, the second surface opposite the first surface, the heat sink comprising a first section substantially parallel to the first surface of the substrate so that each and every LED of the first plurality of LEDs is separated from the heat sink by the substrate, the heat sink further comprising a plurality of fins extending away from the first section and substantially perpendicular thereto, each fin extending along an axis in the plane of the first surface of the substrate, the axis for each fin being substantially perpendicular to the longitudinal axis of the first surface of the substrate, wherein the fins are substantially flat.

6. The lighting assembly of claim **5**, wherein the substantially rectangular region has a length of twenty-four feet.

7. The lighting assembly of claim **2**, wherein the substantially rectangular region has a length of twenty-four feet.

8. The lighting assembly of claim **7**, wherein the LEDs of the first plurality of LEDs are arranged in rows on a substrate and extend along a longitudinal axis in a plane of a first surface of the substrate, the lighting assembly further comprising a heat sink thermally coupled to a second surface of the substrate, the second surface opposite the first surface, the heat sink comprising a first section substantially parallel to the first surface of the substrate so that each and every LED of the first plurality of LEDs is separated from the heat sink by the substrate, the heat sink further comprising a plurality of fins extending away from the first section and substantially perpendicular thereto, each fin extending along an axis in the plane of the first surface of the substrate, the axis for each fin being substantially perpendicular to the longitudinal axis of the first surface of the substrate, wherein the fins are substantially flat.

9. The lighting assembly of claim **2**, wherein the LEDs of the first plurality of LEDs are arranged in rows on a substrate and extend along a longitudinal axis in a plane of a first surface of the substrate, the lighting assembly further comprising a heat sink thermally coupled to a second surface of the substrate, the second surface opposite the first surface, the heat sink comprising a first section substantially parallel to the first surface of the substrate so that each and every LED of the first plurality of LEDs is separated from the heat sink by the substrate, the heat sink further comprising a plurality of fins extending away from the first section and substantially perpendicular thereto, each fin extending along an axis in the plane of the first surface of the substrate, the axis for each fin being substantially perpendicular to the longitudinal axis of the first surface of the substrate, wherein the fins are substantially flat.

10. The lighting assembly of claim **1**, wherein each optical element of the plurality of optical elements of the first and the second lighting units comprises a first part, a second part,

11

and a third part, wherein the first part comprises a first curved surface, wherein the second part comprises a second curved surface that intersects with the first curved surface at a region between the first part and the second part, wherein the first part and the second part each have a peak that is spaced from the region between the first part and the second part, and wherein the third part extends beyond the region between the first part and the second part in a direction away from the associated LED.

11. The lighting assembly of claim 10, wherein the substantially rectangular region has a length of twenty-four feet.

12. The lighting assembly of claim 11, wherein the LEDs of the first plurality of LEDs are arranged in rows on a substrate and extend along a longitudinal axis in a plane of a first surface of the substrate, the lighting assembly further comprising a heat sink thermally coupled to a second surface of the substrate, the second surface opposite the first surface, the heat sink comprising a first section substantially parallel to the first surface of the substrate so that each and every LED of the first plurality of LEDs is separated from the heat sink by the substrate, the heat sink further comprising a plurality of fins extending away from the first section and substantially perpendicular thereto, each fin extending along an axis in the plane of the first surface of the substrate, the axis for each fin being substantially perpendicular to the longitudinal axis of the first surface of the substrate, wherein the fins are substantially flat.

13. The lighting assembly of claim 10, wherein the LEDs of the first plurality of LEDs are arranged in rows on a substrate and extend along a longitudinal axis in a plane of a first surface of the substrate, the lighting assembly further comprising a heat sink thermally coupled to a second surface of the substrate, the second surface opposite the first surface, the heat sink comprising a first section substantially parallel to the first surface of the substrate so that each and every LED of the first plurality of LEDs is separated from the heat sink by the substrate, the heat sink further comprising a plurality of fins extending away from the first section and substantially perpendicular thereto, each fin extending along an axis in the plane of the first surface of the substrate, the axis for each fin being substantially perpendicular to the longitudinal axis of the first surface of the substrate, wherein the fins are substantially flat.

14. The lighting assembly of claim 1, wherein the substantially rectangular region has a length of twenty-four feet.

15. The lighting assembly of claim 14, wherein the LEDs of the first plurality of LEDs are arranged in rows on a substrate and extend along a longitudinal axis in a plane of a first surface of the substrate, the lighting assembly further comprising a heat sink thermally coupled to a second surface of the substrate, the second surface opposite the first surface, the heat sink comprising a first section substantially parallel to the substrate so that each and every LED of the first plurality of LEDs is separated from the heat sink by the first surface of the substrate, the heat sink further comprising a plurality of fins extending away from the first section and substantially perpendicular thereto, each fin extending along an axis in the plane of the first surface of the substrate, the axis for each fin being substantially perpendicular to the longitudinal axis of the first surface of the substrate, wherein the fins are substantially flat.

16. The lighting assembly of claim 1, wherein each optical element of the plurality of optical elements of the first and the second lighting units comprises:

- a first side, a second side opposite the first side, and a third side perpendicular to the first side and the second side;

12

a first element comprising a first curved surface disposed at the first side;

a second element comprising a second curved surface disposed at the second side, wherein the second curved surface intersects with the first curved surface at an acute angle in a region between the first element and the second element; and

a third element disposed at the third side, wherein the third element extends beyond the region between the first element and the second element in a direction away from the associated LED.

17. The lighting assembly of claim 16, wherein the substantially rectangular region has a length of twenty-four feet.

18. The lighting assembly of claim 1, wherein each optical element of the plurality of optical elements of the first and the second lighting units comprises:

- a first side, a second side opposite the first side, and a third side perpendicular to the first side and the second side;

- a first element disposed at the first side;

- a second element disposed at the second side;

- a third element disposed at the third side;

wherein the third element extends beyond the first element and the second element in a direction away from the associated LED;

wherein the first element includes a first outer surface and a first inner surface facing the associated LED and the second element includes a second outer surface and a second inner surface facing the associated LED;

wherein the first inner surface is located at a first nearest distance from the associated LED and the second inner surface is located at a second nearest distance from the associated LED; and

wherein the first inner surface and the second inner surface connect at a connection region that is at a third nearest distance from the associated LED, wherein the third nearest distance is shorter than either the first nearest distance or the second nearest distance.

19. The lighting assembly of claim 1, further comprising a third lighting unit attached to the assembly body and spaced from the first lighting unit, the third lighting unit including a plurality of LEDs and a plurality of optical elements arranged over the plurality of LEDs such that each optical element overlies only one associated LED.

20. The lighting assembly of claim 1, wherein the LEDs of the first lighting unit are arranged in only a first row and a second row on a first substrate, and wherein the LEDs of the second lighting unit are arranged in only a first row and a second row on a second substrate.

21. A lighting assembly comprising:

- a first lighting unit that includes a first circuit board, a first plurality of LEDs arranged on the first circuit board, and a first plurality of optical elements; and

- a second lighting unit that includes a second circuit board, a second plurality of LEDs arranged on the second circuit board, and a second plurality of optical elements;

wherein each optical element of the first plurality of optical elements and the second plurality of optical elements overlies a respective one of the LEDs, each optical element being configured to redirect light from the respective one of the LEDs;

wherein the lighting assembly is configured to simultaneously direct light from the first lighting unit and the second lighting unit toward a substantially rectangular surface;

13

wherein the lighting assembly is configured so that the light is directed so that areas beyond edges of the substantially rectangular surface receive minimum illumination from the lighting assembly;

wherein the lighting assembly is configured to direct the light toward the substantially rectangular surface such that the light from the first lighting unit and from the second lighting unit illuminates substantially all of the substantially rectangular surface with an illumination level and a uniformity; and

wherein the optical elements are configured so that failure of one or more LEDs of the lighting assembly will cause the illumination level of light impinging the substantially rectangular surface to decrease while the uniformity of light impinging the substantially rectangular surface remains substantially the same.

22. The lighting assembly of claim **21**, wherein the lighting assembly further comprises a third lighting unit that includes a third circuit board, a third plurality of LEDs arranged on the third circuit board, and a third plurality of optical elements;

wherein each optical element of the third plurality of optical elements overlies a respective one of the LEDs of the third plurality of LEDs;

wherein the lighting assembly is configured to simultaneously direct light from the first lighting unit, the second lighting unit and the third lighting unit toward the substantially rectangular surface; and

wherein the lighting assembly is configured so that if one or more LEDs of the third plurality of LEDs fails, the uniformity of the light impinging the substantially rectangular surface remains substantially the same.

23. The lighting assembly of claim **21**, wherein a distance along a top boundary of the substantially rectangular surface from a left boundary to a right boundary is twenty-four feet.

24. The lighting assembly of claim **23**, wherein a distance along the right boundary of the substantially rectangular surface from the top boundary to a bottom boundary is fourteen feet.

25. The lighting assembly of claim **21**, wherein the first and the second lighting units are configured to avoid hot spots on the substantially rectangular surface.

26. The lighting assembly of claim **21**, wherein each optical element of the first plurality and the second plurality of optical elements comprises a first part, a second part, and a third part, wherein the first part comprises a first curved surface, wherein the second part comprises a second curved surface that intersects with the first curved surface at a region between the first part and the second part, wherein the first part and the second part each have a peak that is spaced from the region between the first part and the second part, and wherein the third part extends beyond the region between the first part and the second part in a direction away from the associated LED.

27. The lighting assembly of claim **21**, wherein each optical element of the first plurality and the second plurality of optical elements comprises:

a first outer boundary, a second outer boundary opposite the first outer boundary, a third outer boundary connecting the first outer boundary and the second outer boundary, a fourth outer boundary opposite the third outer boundary, and a central region halfway between the first outer boundary and the second outer boundary; a first element with a convex outer surface extending from the first outer boundary toward the central region and

14

having a peak located between the central region and the first outer boundary, the peak being spaced from the central region;

a second element with a convex outer surface extending from the second outer boundary toward the central region and having a peak located between the central region and the second outer boundary, the peak being spaced from the central region; and

a third element disposed between the third outer boundary and a region halfway between the third outer boundary and the fourth outer boundary.

28. The lighting assembly of claim **21**, wherein each optical element of the first plurality and the second plurality of optical elements comprises:

a first outer boundary, a second outer boundary opposite the first outer boundary, a third outer boundary connecting the first outer boundary and the second outer boundary, a fourth outer boundary opposite the third outer boundary, and a central region halfway between the first outer boundary and the second outer boundary;

a first element with a convex outer surface extending from the first outer boundary toward the central region and having a peak located between the central region and the first outer boundary, the peak being spaced from the central region;

a second element with a convex outer surface extending from the second outer boundary toward the central region and having a peak located between the central region and the second outer boundary, the peak being spaced from the central region;

a third element disposed between the third outer boundary and a region halfway between the third outer boundary and the fourth outer boundary; and

a fourth element disposed between the respective circuit board and the first, the second, and the third elements, wherein the first, the second, and the third elements join the fourth element at an interface, wherein the fourth element has a curved surface above the LED.

29. A lighting assembly designed to illuminate a substantially rectangular surface having visual media content located thereon, the substantially rectangular surface being at least a portion of a display surface of a billboard, the lighting assembly comprising:

a first lighting unit that includes a first circuit board, a first plurality of LEDs arranged on the first circuit board, and a first plurality of optical elements; and

a second lighting unit that includes a second circuit board, a second plurality of LEDs arranged on the second circuit board, and a second plurality of optical elements;

wherein each optical element of the first plurality of optical elements and the second plurality of optical elements overlies a respective one of the LEDs, each optical element being configured to redirect light from the respective one of the LEDs;

wherein the lighting assembly is configured to simultaneously direct light from the first lighting unit and the second lighting unit toward the substantially rectangular surface so that the light is directed so that areas beyond edges of the substantially rectangular surface receive minimum illumination from the lighting assembly;

wherein the lighting assembly is configured so that the light from the first lighting unit and the second lighting unit has a substantially rectangular wavefront and illuminates the visual media content of the substantially rectangular surface so that the visual media content on

15

the substantially rectangular surface is visible even without additional lighting;

wherein the lighting assembly is configured so that if one or more LEDs of the first plurality or the second plurality of LEDs fails, remaining LEDs of the first plurality or the second plurality of LEDs still illuminate the substantially rectangular surface so that the visual media content on the substantially rectangular surface remains visible even without additional lighting;

wherein the lighting assembly is configured to direct the light toward the substantially rectangular surface such that the light from the first lighting unit and the second lighting unit illuminates the visual media content on the substantially rectangular surface with an illumination level and a uniformity;

wherein the optical elements are configured so that failure of one or more LEDs of the lighting assembly will cause the illumination level of light impinging the substantially rectangular surface to decrease while the

16

uniformity of light impinging the substantially rectangular surface remains substantially the same;

wherein a distance along a top edge of the portion of the display surface from a left edge to a right edge is twenty-four feet and wherein a distance along the right edge of the display surface from the top edge to a bottom edge is fourteen feet; and

wherein each optical element of the first plurality and the second plurality of optical elements comprises a first part, a second part, and a third part, wherein the first part comprises a first curved surface, wherein the second part comprises a second curved surface that intersects with the first curved surface at a region between the first part and the second part, wherein the first part and the second part each have a peak that is spaced from the region between the first part and the second part, and wherein the third part extends beyond the region between the first part and the second part in a direction away from the associated LED.

* * * * *