

US009736706B2

(12) **United States Patent**  
**Salyers et al.**

(10) **Patent No.:** **US 9,736,706 B2**  
(45) **Date of Patent:** **Aug. 15, 2017**

(54) **MANAGED ACCESS SYSTEM WITH MONITORING DEVICE TO DETERMINE SYSTEM OPERABILITY**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **HARRIS CORPORATION**,  
Melbourne, FL (US)

3,983,492 A 9/1976 Fisher et al.  
4,527,281 A 7/1985 Imagawa et al.  
(Continued)

(72) Inventors: **Eric J. Salyers**, Grant, FL (US);  
**Shawn H. Gallagher**, Melbourne, FL  
(US); **Steven D. Halford**, Palm Bay,  
FL (US)

FOREIGN PATENT DOCUMENTS

EP 1 051 053 11/2000  
WO 03/019907 3/2003

(Continued)

(73) Assignee: **HARRIS CORPORATION**,  
Melbourne, FL (US)

OTHER PUBLICATIONS

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 26 days.

Salyers et al., U.S. Appl. No. 15/153,770, filed May 13, 2016.  
(Continued)

*Primary Examiner* — Kashif Siddiqui

(21) Appl. No.: **14/865,355**

(74) *Attorney, Agent, or Firm* — Allen, Dyer, Doppelt,  
Gilchrist, P.A.

(22) Filed: **Sep. 25, 2015**

(65) **Prior Publication Data**

(57) **ABSTRACT**

US 2017/0094534 A1 Mar. 30, 2017

A managed access system for mobile wireless devices (MWDs) in a facility that is geographically within a wireless communications network includes a plurality of antennas arranged at the facility and at least one MWD monitoring device. Radio equipment is coupled to the antennas. A management access controller cooperates with the radio equipment to communicate with a given MWD within the facility, block outside communications via the wireless communications network when the given MWD is an unauthorized MWD, and provide outside communications when the given MWD is an authorized MWD. The management access controller cooperates with at least one MWD monitoring device to determine whether the radio equipment and at least one MWD monitoring device both detect the given MWD.

(51) **Int. Cl.**

**H04W 24/02** (2009.01)  
**H04W 12/06** (2009.01)  
**H04W 12/08** (2009.01)  
**H04W 4/02** (2009.01)  
**H04W 84/04** (2009.01)

(52) **U.S. Cl.**


CPC ..... **H04W 24/02** (2013.01); **H04W 4/021**  
(2013.01); **H04W 12/06** (2013.01); **H04W**  
**12/08** (2013.01); **H04W 84/045** (2013.01)

(58) **Field of Classification Search**

CPC .... H04W 24/02; H04W 4/021; H04W 12/06;  
H04W 12/08; H04W 84/045

See application file for complete search history.

**34 Claims, 33 Drawing Sheets**





(56)

References Cited

U.S. PATENT DOCUMENTS

4,652,816 A 3/1987 Crookshanks  
 5,500,648 A 3/1996 Maine et al.  
 5,796,366 A 8/1998 Grebnev et al.  
 5,835,907 A 11/1998 Newman  
 5,870,029 A 2/1999 Otto et al.  
 5,977,913 A 11/1999 Christ  
 6,144,318 A 11/2000 Hayashi et al.  
 6,157,823 A 12/2000 Fougnyes et al.  
 6,202,026 B1 3/2001 Nimura et al.  
 6,288,640 B1 9/2001 Gagnon  
 D478,517 S 8/2003 Law  
 6,720,921 B2 4/2004 Ripingill, Jr. et al.  
 6,754,502 B2 6/2004 Hildebrand et al.  
 6,832,093 B1 12/2004 Ranta  
 6,845,240 B2 1/2005 Carlson et al.  
 6,853,687 B2 2/2005 Harrington et al.  
 6,912,230 B1 6/2005 Salkini et al.  
 6,912,388 B2 6/2005 Yang  
 6,970,183 B1 11/2005 Monroe  
 7,061,220 B1 6/2006 Nalbandian et al.  
 7,110,779 B2 9/2006 Billhartz et al.  
 7,132,961 B2 11/2006 Yannone et al.  
 7,187,326 B2 3/2007 Beadle et al.  
 7,218,090 B1 5/2007 Nalbandian et al.  
 7,259,694 B2 8/2007 Myllymaki et al.  
 7,321,777 B2 1/2008 Billhartz et al.  
 7,340,260 B2 3/2008 McAlexander  
 7,426,231 B1\* 9/2008 Dorfman ..... H01Q 21/24  
 375/130  
 7,578,448 B2 8/2009 Beenau et al.  
 7,592,956 B2 9/2009 McPherson et al.  
 7,616,155 B2 11/2009 Bull et al.  
 7,657,265 B2 2/2010 McAlexander  
 7,733,901 B2 6/2010 Salkini et al.  
 7,778,651 B2 8/2010 Billhartz  
 7,804,448 B2 9/2010 Bull et al.  
 7,864,047 B2 1/2011 Aninye et al.  
 7,911,385 B2 3/2011 Heuser  
 7,941,853 B2 5/2011 Rozenberg et al.  
 8,072,311 B2 12/2011 Sadr et al.  
 8,078,190 B2 12/2011 Noonan et al.  
 8,171,554 B2 5/2012 Elovici et al.  
 8,213,957 B2 7/2012 Bull et al.  
 8,224,233 B2 7/2012 Brisebois et al.  
 8,233,880 B2 7/2012 Johnson  
 8,238,936 B2 8/2012 Nadler et al.  
 8,254,886 B2 8/2012 Salkini et al.  
 8,346,281 B2 1/2013 Noonan et al.  
 8,350,675 B2 1/2013 Riechel  
 8,350,758 B1 1/2013 Parvizi et al.  
 8,437,741 B2 5/2013 Salkini et al.  
 8,461,973 B2 6/2013 Reed et al.  
 8,472,968 B1 6/2013 Kim  
 8,509,740 B2 8/2013 Salkini et al.  
 8,606,229 B2 12/2013 Johnson  
 8,624,727 B2 1/2014 Saigh et al.  
 8,626,195 B2 1/2014 Noonan et al.  
 8,629,762 B2 1/2014 Sadr et al.  
 8,711,033 B2 4/2014 Calmettes et al.  
 8,750,903 B1 6/2014 Fitzsimmons et al.  
 8,767,923 B1 7/2014 Edwards  
 8,825,011 B2 9/2014 Salkini et al.  
 8,838,812 B2 9/2014 Miller et al.  
 8,843,155 B2 9/2014 Burton et al.  
 8,866,607 B2 10/2014 Velusamy  
 8,878,725 B2 11/2014 Lu  
 8,893,224 B2 11/2014 Horvitz et al.  
 8,897,694 B2 11/2014 Brisebois et al.  
 8,923,824 B1 12/2014 Materman  
 8,929,206 B2 1/2015 Markwart et al.  
 8,983,446 B2 3/2015 Nadler et al.  
 9,237,422 B1\* 1/2016 Bhat ..... H04W 4/021  
 2001/0036821 A1 11/2001 Gainsboro et al.  
 2004/0121787 A1 6/2004 Day et al.  
 2004/0153553 A1 8/2004 Chotkowski et al.

2006/0046746 A1 3/2006 Ranford et al.  
 2008/0032666 A1 2/2008 Hughes et al.  
 2008/0032705 A1\* 2/2008 Patel ..... H04W 4/18  
 455/456.1  
 2008/0039089 A1\* 2/2008 Berkman ..... H04W 36/04  
 455/436  
 2008/0043993 A1 2/2008 Johnson  
 2008/0057976 A1 3/2008 Rae et al.  
 2008/0201158 A1 8/2008 Johnson et al.  
 2010/0079594 A1 4/2010 Voglewede et al.  
 2010/0159879 A1 6/2010 Salkini et al.  
 2010/0197324 A1 8/2010 Bolin et al.  
 2010/0304712 A1 12/2010 Sweeney et al.  
 2011/0045815 A1 2/2011 Schork et al.  
 2011/0059688 A1 3/2011 Noonan et al.  
 2012/0147834 A1 6/2012 Zisimopoulos et al.  
 2013/0316638 A1 11/2013 Jang et al.  
 2013/0316738 A1 11/2013 Noonan  
 2014/0018059 A1 1/2014 Noonan et al.  
 2014/0194084 A1 7/2014 Noonan et al.  
 2014/0199963 A1 7/2014 Mohebbi  
 2015/0312766 A1\* 10/2015 Teeni ..... H04W 4/043  
 455/411

FOREIGN PATENT DOCUMENTS

WO 2008/097506 8/2008  
 WO 2014/151249 9/2014

OTHER PUBLICATIONS

Salyers et al., U.S. Appl. No. 15/153,786, filed May 13, 2016.  
 Souppaya et al. "Guidelines for Managing the Security of Mobile Devices in the Enterprise—recommendations of the National Institute of Standards and Technology" Jun. 2013; NIST Special Publication 800-124 Revision 1; <http://csrc.nist.gov/>. pp. 20.  
 MMI Research Limited V. (1) Cellxion Limited et al. Neutral Citation No. [2009] EWHC 418 (Pat): Nov. 3, 2009; pp. 29.  
 "Operational Security Standard: Management of Information Technology Security (MITS)" <http://www.tbs-sct.gc.ca/pol/doc-eng.aspx?id=12328&section=HTML>; retrieved from internet Jun. 7, 2016; pp. 23.  
 Bisson et al. "Methods for Prevention of the Use of Mobile Phones in Correctional Institutions" 2012 IEEE International Carnahan Conference on Security Technology (ICCST), pp. 237-245. E-ISBN : 978-1-4673-2449-6. Date of Conference: Oct. 15-18, 2012.  
 Chen et al "Spectrum Occupancy Analysis Based on Radio Monitoring Network" 2012 1st IEEE International Conference on Communications in China (ICCC), pp. 739-744. E-ISBN : 978-1-4673-2813-5 Date of Conference: Aug. 15-17, 2012.  
 Divya et al. "Design of User Specific Intelligent Cell Phone Jammer" 2012 1st International Conference on Recent Advances in Information Technology (RAIT), pp. 312-316; Print ISBN: 978-1-4577-0694-3; Date of Conference: Mar. 15-17, 2012.  
 Gurr et al. "Wide-Band Radio Frequency (RF) Source Surveillance" International telemetering conference; 34th, ITC/USA '98; 1998; San Diego, CA: pp. 316 323; ISBN: 556176732.  
 Roxin et al. "Survey of Wireless Geolocation Techniques"IEEE Globecom Workshops, Nov. 2007, Washington, DC, United States. pp. 9 Pages, 2007, •DOI: 10.1109/GLOCOMW.2007.4437809.  
 Shah et al. "Cell Phone Jammer" INMIC 2008. IEEE International Multitopic Conference, 2008; pp. 579-580; E-ISBN : 978-1-4244-2824-3; Date of Conference: Dec. 23-24, 2008.  
 Wang et al. "An Agile Radio Framework for Unmanaged Wireless Environments" MobiHoc '09 Proceedings of the tenth ACM international symposium on Mobile ad hoc networking and computing: pp. 333-334; ISBN: 978-1-60558-624-3. May 18, 2009.  
 Wu et al. "Design of a Network Receiver for 20MHZ to 3GHZ Ultra-Short Wave Spectrum Monitoring" System Science, 2012 3rd International Conference on Engineering Design and Manufacturing Informatization (ICSEM), pp. 13-16; Print ISBN: 978-1-4673-0914-1; Date of Conference: Oct. 20-21, 2012 . Abstract Only.

(56)

**References Cited**

OTHER PUBLICATIONS

“Can New Cell Phone Blocking Technology Keep Prisoners Off the Line” *Wireless & Cybersecurity Watch*; Mar. 26, 2014; 5 Pgs; Retrieved From Internet May 6, 2015.

Devlin Barrett “CIA Aided Program to Spy on U.S. Cellphones” *The Wall Street Journal* Mar. 10, 2015; 5 Pgs. [www.wsj.com/articles/cia-gave-justice-department-secret-phone-scanning-technology-1426009924](http://www.wsj.com/articles/cia-gave-justice-department-secret-phone-scanning-technology-1426009924).

Jeff Stone “GPS Act Would Restrict Cops’ Use of ‘Stingrays’ and Other Phone Surveillance Tech” *International Business Times*; Jan. 23, 2015; <http://www.ibtimes.com/technology>; 5 Pgs. Retrieved From Internet on May 7, 2015.

“The Efficacy of Managed Access Systems to Intercept Calls From Contraband Cell Phones in California Prisons” *California Council on Science and Technology*; May 2012; pp. 72.

“Managed Access CC1500” [www.cellularintercept.com/emonprodshow/managed\\_access\\_cc1500.html](http://www.cellularintercept.com/emonprodshow/managed_access_cc1500.html); 3 Pgs. Retrieved From Internet Sep. 28, 2015.

U.S. Appl. No. 14/865,308, filed Sep. 25, 2015.

U.S. Appl. No. 14/865,277, filed Sep. 25, 2015.

U.S. Appl. No. 14/865,400, filed Sep. 25, 2015.

U.S. Appl. No. 14/865,466, filed Sep. 25, 2015.

Nicholas W. Scott “Study of Cellular Phone Detection Techniques” <http://digitalcommons.unl.edu/ceendiss>; Apr. 2011; pp. 54. <http://digitalcommons.unl.edu/cgi/viewcontent.cgi?article=1021&context=ceendiss>.

Caroline Gabriel “Small Cells Inside the Enterprise—The Who, What & Where” © Maravedis—Rethink 2013; pp. 23; [http://www.spidercloud.com/assets/pdfs/WP\\_Rethink\\_Enterprise\\_SmallCells\\_0613.pdf](http://www.spidercloud.com/assets/pdfs/WP_Rethink_Enterprise_SmallCells_0613.pdf).

Enabling Mobile Phone Services Anywhere by Globecom Systems, Inc. 2013; 2 Pgs. Retrieved From Internet Oct. 6, 2015; <http://www.globecommsystems.com/pdf/wp-gsm-softswitch-article.pdf>.

“Private Mobile Networks—Private GSM and IP Solutions” <http://www.mobilecomms-technology.com/contractors/fixed-mobile-convergence/teleware>; Aug. 13, 2013; pp. 3 Retrieved From Internet Oct. 6, 2015.

“Spectrum Analyzer Catches Cell Phone Cheats in Taiwan” <http://www.darkreading.com/vulnerabilities-and-threats/spectrum-analyzer-catches-cell-phone-cheats-in-taiwan/d/d-id/1095482?> : Jan. 14, 2011; pp. 2; Retrieved From Internet on Oct. 6, 2015.

\* cited by examiner






FIG. 1




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4






FIG. 5





FIG. 6




FIG. 7






FIG. 8




FIG. 9




FIG. 10








FIG. 11



CARRIER	PROPOSED RADIOS	BASE STATION COUNT
U.S. CELLULAR	0	2
CDMA 1xRTT	0	1
CDMA EVDO	0	1
VERIZON	9	37
LTE	2	3
CDMA 1xRTT	4	17
CDMA EVDO	3	17
SPRINT	5	21
LTE	2	5
CDMA 1xRTT	2	8
CDMA EVDO	1	8
AT&T	5	28
GSM	1	17
LTE	2	4
UMTS	2	7
T-MOBILE	2	14
GSM	1	10
LTE	1	4
FTC COMMUNICATIONS LLC	1	2
LTE	1	2
<b>GRAND TOTAL</b>	<b>22</b>	<b>104</b>

**FIG. 12**

**CELL Vs RADIOS  
COVERAGE BY TECHNOLOGY PER BAND**




	PROPOSED RADIOS	CARRIER BASE STATION COUNT
LTE	8	18
BAND II	2	5
BAND IV	1	1
BAND XIII	1	2
BAND XVII	2	5
BAND XXV	1	3
BAND XXVI	1	2
UMTS	2	7
BAND II	2	7
GSM	2	27
BAND II	2	27
CDMA 1xRTT	6	26
BAND II	1	4
BAND V	4	18
BAND XXVI	1	4
CDMA EVDO	4	26
BAND II	1	4
BAND V	3	18
BAND XXVI	0	4
<b>GRAND TOTAL</b>	<b>22</b>	<b>104</b>

**FIG. 13**



SOUTH CAROLINA														
CORE/BASE STATION	AT&T		SPRINT		T-MOBILE			VERIZON			FTC COMM		US CELLULAR	TOTAL
	700MHz BAND 17	1900MHz BAND 2	1900MHz BAND 2	1900MHz BAND 25	800MHz BAND 26	1900MHz BAND 2	2100MHz BAND 4	700MHz BAND 13	850MHz BAND 5	700MHz BAND 17	850 BAND 5			
CORE/BASE STATION	1													
		1		1										
					1									
							1	1		1				
LTE BASE STATION													8	
CDMA-a BASE STATION													4	
CDMA-b BASE STATION													2	
CDMA-c BASE STATION													4	
UMTS BASE STATION		2											2	
GSM BASE STATION		1											2	

FIG. 14



**FIG. 15**






FIG. 16





**FIG. 17**



**FIG. 18**




FIG. 19














FIG. 20

<b>AUTHORIZED DEVICES</b> ①  <b>REPORTS</b>	 12:32:04, 2015.51.23  12:31:42, 2015.51.23  14:33:20, 2015.51.23  12:33:02, 2015.51.23	1xRTT 1xRTT GSM 1xRTT	VOICE SMS SMS SMS	C6F03D29 C3FB03C7 310120841564781 C098AF34
---	--	--------------------------------	----------------------------	---

INDICATES SWAPPED SIM DETECTED

<b>AUTHORIZED DEVICES</b> ①  <b>REPORTS</b>	 12:32:04, 2015.51.23  12:31:42, 2015.51.23  14:33:20, 2015.51.23  12:33:02, 2015.51.23	1xRTT 1xRTT GSM 1xRTT	VOICE SMS SMS SMS	C6F03D29 C3FB03C7 310120841564781 C098AF34
---	--	--------------------------------	----------------------------	---





30


FIG. 21





**SYSTEM STATE OPERATING**


 SYSTEM

 DEVICE EVENTS 7

 AUTHORIZED DEVICES 1

 REPORTS

 ALARMS

 SETTINGS

FILTER

ALL

AUTHORIZED

UNAUTHORIZED

BLACK LISTED

DEACTIVATED

AUTH	TIME	TYPE	EVENT	IMEI/ESN	IMSI/MIN	NUMBER DIALED
<input type="checkbox"/>	12:32:33, 2015.51.23	LTE	DEREGISTRATION	310410224588714	875459582421155	<a href="#">VIEW</a> <a href="#">LOCATE</a>
<input type="checkbox"/>	12:33:31, 2015.51.23	EVDO	REGISTRATION	311480448795648	554562285476332	<a href="#">VIEW</a> <a href="#">LOCATE</a>
<input type="checkbox"/>	12:32:04, 2015.51.23	1xRTT	VOICE	C6F03D29	527451144243350	<a href="#">VIEW</a> <a href="#">LOCATE</a>
<input type="checkbox"/>	12:31:42, 2015.51.23	1xRTT	SMS	C3FB03C7	490115420323751	<a href="#">VIEW</a> <a href="#">LOCATE</a>
<input type="checkbox"/>	14:33:20, 2015.51.23	GSM	SMS	310120841564781	417586531245220	<a href="#">VIEW</a> <a href="#">LOCATE</a>
<input type="checkbox"/>	12:33:02, 2015.51.23	1xRTT	SMS	C098AF34	331251187485221	<a href="#">VIEW</a> <a href="#">LOCATE</a>
<input type="checkbox"/>	12:33:24, 2015.51.23	1xRTT	SMS	C098AF34	331251187485221	<a href="#">VIEW</a> <a href="#">LOCATE</a>

EMERGENCY SHUTDOWN

FIG. 22 ↖ 30




FIG. 23




FIG. 24




FIG. 25






FIG. 26




FIG. 27




FIG. 28





FIG. 29





**FIG. 30**





FIG. 31



**FIG. 32**




FIG. 33



1

**MANAGED ACCESS SYSTEM WITH  
MONITORING DEVICE TO DETERMINE  
SYSTEM OPERABILITY**

FIELD OF THE INVENTION

The present invention relates to communications systems, and more particularly, this invention relates to a managed access system for a mobile wireless device in a facility.

BACKGROUND

Over the last twenty years, the wireless telecommunications market has seen tremendous growth, including the use of contraband mobile wireless devices in correctional facilities or unauthorized use of such devices in other secure facilities, such as government offices. These devices are often smuggled into correctional facilities or other secure facilities and made available to unauthorized users, including inmates, which may use them to continue criminal enterprises outside the facility, threaten witnesses, and harass victims. Use of such devices may also pose a continued security risk in a correctional facility because the inmates may use them to coordinate inmate riots or direct retribution on guards, police or government officials.

It is difficult to prevent the smuggling of mobile wireless devices into correctional or other secure facilities because of commercial technology improvements and the variety of smuggling techniques available to unauthorized users and inmates. The improvements in commercial technology have reduced the size of mobile wireless devices and eased the challenges of smuggling or even accidentally carrying a mobile wireless device into a facility. Also, the accessibility of less expensive mobile wireless devices has placed these devices within the financial reach of most inmates or other unauthorized users. Though institutional security measurements are in place to attempt to prevent the smuggling of contraband into correctional facilities, the range of smuggling methods available to deliver contraband mobile wireless devices into the facility makes it difficult or even impossible to stop the flow. Inmates may coordinate smuggling efforts with visitors who move in and out of the facilities. Visiting friends and family are commonly involved in introducing contraband. Smugglers even employ methods such as throwing handsets over facility walls or fences, or concealing them in packages sent to the facility. Physical security measures alone may not be sufficient to prevent the introduction of mobile wireless devices into correction facilities or other secure facilities.

As smuggling cannot be reasonably prevented, alternative methods have been developed that focus on finding mobile wireless devices that are already inside the facilities. For example, some systems detect and locate contraband devices, which can then be confiscated. Often these systems include fixed, portable and handheld detection systems, but they can be expensive to acquire and require significant effort and personnel cost to use effectively. Their operational efficacy also is related to the effort that the facility invests in time, training, and technology. An increased effort from the facility may improve results, but it may also increase operational costs.

Because a cell phone's benefit to the user is its ability to access the commercial wireless network, denying the cell phone access to the wireless network may be a better approach to reduce the risks posed by contraband cell phones and other mobile wireless devices. The device is benign without access to the commercial wireless network.

2

A range of technology based approaches have been developed and are available to limit an unauthorized device's access to the commercial wireless network. These approaches include jammer technologies and access management approaches. There are several types of jammers, but they are typically designed to disrupt the communications of the device with the wireless communications network. One type of access management approach is a Managed Access System (MAS), which employs a private wireless network within a facility to provide wireless network access to authorized cell phones within the system's range. Authorized devices are provided access to voice and data services while unauthorized devices are denied access.

Another type of system, an Access Denial Service (ADS) works cooperatively with the commercial wireless network to deny access to unauthorized devices within a facility. An ADS system uses the interaction between cell phones and the network to determine if the cell phone is within a facility or not. When a cell phone is detected within the facility, the carrier is notified and if the device is not authorized for operation in the facility, it is prevented from future access to the wireless network by the carrier.

There are drawbacks to such systems. Geolocation devices alone will not provide sufficient detail on the device identification to enable action by the commercial service provider. Managed Access Systems may provide insufficient information to determine the location of a cellular device that has registered to their network. They can typically only identify that a device has attached, what has attached, and when it has attached. At best, it can identify which sector of a distributed antenna system the attachment has occurred. The system typically needs to operate on a persistent basis using fixed location, autonomous sensors.

SUMMARY OF THE INVENTION

A managed access system for mobile wireless devices (MWDs) in a facility that are geographically within a wireless communications network comprises a plurality of antennas arranged at the facility, radio equipment coupled to the plurality of antennas, and at least one MWD monitoring device for the wireless communications network. A management access controller cooperates with the radio equipment to communicate with a given MWD within the facility, block outside communications via the wireless communications network when the given MWD is an unauthorized MWD, and provide outside communications when the given MWD is an authorized MWD. The management access controller cooperates with the at least one MWD monitoring device to determine whether the radio equipment and at least one MWD monitoring device both detect the given MWD.

The managed access controller may be configured to generate an indication when one and not the other of the at least one MWD monitoring device and radio equipment detects the given MWD. The plurality of antennas may comprise a plurality of directional antennas arranged around a periphery of the facility. The at least one MWD monitoring device is operable for both cellular and non-cellular communications, and may comprise a plurality of external monitoring devices arranged around the periphery of the facility. The plurality of external monitoring devices may operate based on time-difference-of-arrival signals. The at least one MWD monitoring device may comprise a plurality of internal monitoring devices arranged within the periphery of the facility. The facility comprises a building and at least some of the plurality of internal monitoring devices are located within the building. The radio equipment may com-



prise a plurality of picocell radios, each coupled to a respective directional antenna. The management access controller may implement the corresponding change in the radio equipment as at least one of change in a power level of at least one of said picocell radios, a change in a communications protocol of at least one of said picocell radios, and a frequency range of at least one of said picocell radios.

The management access controller may provide outside communications when the given MWD is an authorized MWD via another network other than the commercial wireless network. The management access service may provide outside communications when the given MWD is an authorized MWD via at least one of the Public Switched Telephone Network (PSTN), and an Internet Protocol (IP) network. The radio equipment may be operable according to at least one of an LTE, CDMA, UMTS and GSM protocol.

A management access controller for a managed access system for mobile wireless devices (MWDs) in a facility, wherein the facility is geographically within a wireless communications network comprises a plurality of directional antennas arranged around a periphery of the facility, radio equipment coupled to the plurality of directional antennas, and at least one MWD monitoring device for the wireless communications network. The management access controller comprises a processor and a memory coupled thereto to cooperate with the radio equipment to communicate with a given MWD within the facility, block outside communications via the wireless communications network when the given MWD is an unauthorized MWD, and provide outside communications when the given MWD is an authorized MWD, and cooperate with the at least one MWD monitoring device to determine whether the radio equipment and at least one MWD monitoring device both detect the given MWD.

A method for operating a managed access system for mobile wireless devices (MWDs) in a facility that is geographically within a wireless communications network includes managed access system that comprises a plurality of directional antennas arranged around a periphery of the facility, radio equipment coupled to said plurality of directional antennas, and at least one MWD monitoring device for the wireless communications network. The method comprises operating a management access controller to cooperate with the radio equipment to communicate with a given MWD within the facility, block outside communications via the wireless communications network when the given MWD is an unauthorized MWD, and provide outside communications when the given MWD is an authorized MWD, and cooperate with the at least one MWD monitoring device to determine whether the radio equipment and at least one MWD monitoring device both detect the given MWD.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Other objects, features and advantages of the present invention will become apparent from the detailed description of the invention which follows, when considered in light of the accompanying drawings in which:

FIG. 1 is a block diagram showing functional components of the managed access system in accordance with a non-limiting example.

FIG. 2A is a more detailed block diagram of the managed access system in accordance with a non-limiting example.

FIG. 2B is another block diagram of the managed access system showing the facility and location of different devices in accordance with a non-limiting example.

FIG. 3 is a flow diagram showing a method of operation for the managed access system in accordance with a non-limiting example.

FIG. 4 is an environmental view of the managed access system for a facility showing directional antennas forming an area of blocked communications in accordance with a non-limiting example.

FIG. 5 is a plan view of the facility showing an area of uncertainty and location of directional antennas in accordance with a non-limiting example.

FIG. 6 is a block diagram showing a management access controller in communication with directional antennae in accordance with a non-limiting example.

FIG. 7 is another environmental view of the managed access system for a facility showing the wireless communications network formed by existing and new transceivers in accordance with a non-limiting example.

FIG. 8 is a fragmentary plan view of the managed access system similar to that shown in FIG. 7 and showing the effect of a changed RF signal from the wireless communications network in accordance with a non-limiting example.

FIG. 9 is a block diagram of a portion of the components forming the management access controller in accordance with a non-limiting example.

FIG. 10 is a block diagram of components that cooperate with a directional antenna in accordance with a non-limiting example.

FIG. 11 is a fragmentary block diagram of network security for the managed access system in accordance with a non-limiting example.

FIG. 12 is a bar chart of an example preliminary cellular design site study showing coverage by technology per carrier to implement a distributed antenna system in accordance with a non-limiting example.

FIG. 13 is a bar chart similar to that shown in FIG. 12, but showing the results of coverage by technology per band in accordance with a non-limiting example.

FIG. 14 is a table showing an example baseline cellular base station radio configuration in accordance with a non-limiting example.

FIG. 15 is a flowchart showing an example method for implementing the distributed antenna system in accordance with a non-limiting example.

FIG. 16 is a plan view of the facility showing positions of external geolocation devices in accordance with a non-limiting example.

FIG. 17 is an example of an external geolocation device in accordance with a non-limiting example.

FIG. 18 is an example of the spiral antennas used in the external geolocation device in accordance with a non-limiting example.

FIG. 19 is an example screen shot of the graphical user interface for the managed access system and showing a located mobile wireless device in accordance with a non-limiting example.

FIG. 20 is a plan view of the facility showing location of internal geolocation devices in accordance with a non-limiting example.

FIG. 21 is an example screenshot of the graphical user interface showing mobile wireless devices with swapped SIM cards in accordance with a non-limiting example.

FIG. 22 is an example screenshot of the graphical user interface showing located mobile wireless devices in accordance with a non-limiting example.



## 5

FIG. 23 is a fragmentary block diagram showing in-line monitoring for controlling communications with the management access controller in accordance with a non-limiting example.

FIG. 24 is a network diagram similar to that of FIG. 23 and showing the in-line monitoring using a managed access filter for use with the managed access system in accordance with a non-limiting example.

FIG. 25 is a network diagram showing a managed private cellular access system for use with the managed access system in accordance with a non-limiting example.

FIG. 26 is a network diagram showing a private Home Subscriber Server (HSS) for use with the managed access system in accordance with a non-limiting example.

FIG. 27 is a network diagram showing a coordinated access denial system for use with the managed access system in accordance with a non-limiting example.

FIG. 28 is a block diagram of Computer Software Configuration Items (CSCI) in accordance with a non-limiting example.

FIG. 29 is a block diagram showing managers and interfaces for the CSCI in accordance with a non-limiting example.

FIG. 30 is a block diagram showing interoperation of the message manager with the components in the CSCI in accordance with a non-limiting example.

FIG. 31 is a block diagram showing components of the SOH and network manager in accordance with a non-limiting example.

FIG. 32 is a block diagram showing the geolocation interface and interoperation among the internal and external geolocation devices in accordance with a non-limiting example.

FIG. 33 is a block diagram showing the Application Programming Interface (API) library and the management access controller in accordance with a non-limiting example.

## DETAILED DESCRIPTION

Different embodiments will now be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments are shown. Many different forms can be set forth and described embodiments should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope to those skilled in the art. Like numbers refer to like elements throughout.

The managed access system, in accordance with a non-limiting example, permits communications from authorized mobile wireless devices and detects and disrupts wireless communications from unauthorized or contraband mobile wireless devices within a protected facility, such as a correctional facility. The different embodiments will be described relative to a correctional facility, but it should be understood that the managed access system, in accordance with a non-limiting example, may be used in many different facilities, including non-secure and secure buildings such as government offices, military compounds, corporate workplaces, and other areas where managed access systems may be implemented to detect and disrupt wireless communications from contraband and unauthorized mobile wireless devices, but permit authorized users to communicate either internally within the facility or with an outside commercial communications network.

The managed access system as will be described can be scaled to address a wide variety of wireless communication

## 6

threats within a facility and mitigate the threat presented by contraband cellular and other unauthorized mobile wireless devices. The managed access system may be used to prohibit contraband and other unauthorized mobile wireless devices from accessing commercial voice and data networks. The system may provide a full-spectrum cellular service so that every mobile wireless device within the facility, regardless of commercial carrier or technology, e.g., as 4G LTE, 3G LTE, or other communication standards, is connected to the managed access system for both voice and data network communications rather than connected to any commercial networks.

Because local commercial cellular coverage varies from facility to facility, including a) the number of carriers, b) the technology mix of 2G, 3G and 4G standards, and c) the frequencies used by local carriers, the managed access system is built upon a modular system architecture and allows the communications technology mix to be optimized for any facility. For example, the managed access system may be reconfigured to address changes to the local communications environment and facilitate upgrades for future cellular and other communications technologies, such as 5G and beyond. The managed access system includes support for WiFi (802.11X) and other conventional radio technologies, including push-to-talk radios that can be added to the cellular core functionality to increase the diversity of the types of communications technology that can be detected and disrupted by the system. Drone detection capability may be implemented.

As will be explained in greater detail below, the managed access system is implemented after an initial site survey is performed where on-site data is collected to determine which commercial carriers are in the area and what cellular technologies and frequency bands cover the particular facility where the managed access system will be implemented. The collected data is used to determine the technology mix and frequency coverage necessary to provide effective cellular mitigation within the facility. To implement the managed access system, radio frequency (RF) propagation data for the facility is collected and provides empirical measurements to understand how signals propagate throughout the facility. This propagation data is used to design a Distributed Antenna System (DAS) using directional antennae and mitigate cellular access coverage from within the facility using a managed access system RF “bubble” over the facility. The empirical propagation data is used to predict signal levels in and around the facility. A cellular elevation survey is completed to determine the type and scope of infrastructure for improvements to support the managed access system RF “bubble.” Once installed, the system is maintained and monitored, including continuous system alarm monitoring.

Referring now to FIG. 1, there is illustrated a high-level block diagram of functional components in the managed access system 10 for use in a facility such as a correctional facility, which is geographically located within a wireless communications network, for example, a conventional commercial communications network. The system 10 includes a management access controller or server 12 that cooperates with a distributed antenna system 14 formed from a plurality of directional antennae as explained in detail below. The system 10 provides cellular monitoring 16 to detect managed access system cellular mode of operation and detect changes in cellular coverage, passive spectral monitoring 18 to sense non-cellular devices, and signal geolocation 20 using a series of internal and external sensors, as will also be explained in greater detail below. The system 10 provides



state of health monitoring **22** and system and configuration management **24** to manage the configuration of the managed access system RF “bubble.” A local coverage database **24** stores information regarding commercial carriers and devices. Changes in commercial coverage can be detected **28** using the cellular monitoring **16**, and changes may be made to the distributed antenna system **14** and other components as necessary. The system includes a graphical user interface **30** where an overlay of the facility can be viewed, data input and system changes made. Events are correlated **32** and logged, for example, an event corresponding to the determination of an unauthorized user. Reports are generated and events stored in an event log database **34** and records kept of different events, for example, when an unauthorized user is detected. The graphical user interface **30** provides a common interface for monitoring operation of the system **10**. Data is collected, fused and displayed on the graphical user interface **30** to show the operating environment within the facility. System state of health information can be viewed on the graphical user interface **30**.

Referring now to FIG. 2A, there is shown a more detailed, high-level block diagram of the managed access system **10**, which includes the management access controller **12** that is formed as a server and a segment of a radio or server rack **36**. The term “controller or server” may be used interchangeably when referring to the management access server, and the server includes a processor **12a** and a memory **12b** coupled thereto. The management access server **12** cooperates with radio equipment **40**, such as picocell radios to communicate with a given mobile wireless device **42** within the facility **44**, and blocks outside communications from a commercial wireless communications network **45** when the given MWD is an unauthorized MWD, and provides outside communications when the given MWD is an authorized MWD. The management access server **12** interoperates with the distributed antenna system **14** that includes a plurality of directional antennas **46** arranged around a periphery of the facility **44** and includes a distributed antenna system master “controller” or server **48**. Each directional antenna **46** interoperates with the radio equipment **40** via the distributed antenna system master **48** and remote cellular power amplifiers **50**. The radio equipment **40** may include different radios, including LTE radios, UMTS radios, IDEN radios, GSM radios, CDMA 2000 radios, and CDMA EVDO radios in this example. Other radios for communicating with mobile wireless devices **42** may be used depending on the type of coverage provided within and around the facility **44**.

The management access server **12** interoperates with an Ethernet switch **52** and includes a network firewall **54**, physical security **56**, e.g., locks for the rack **36**, a GPS time server **58**, GPS splitter **60**, power distribution circuits **62** and UPS (uninterrupted power supply) **64**. The management access server **12** interoperates through an electrical-to-optical (E/O) interface **66** to at least one external geolocation device that is formed as an external geolocation sensor array **70** and includes wideband remote sensors **72** as external geolocation devices, which are operable for both cellular and non-cellular communications to detect those signals in the facility **44**. These wideband sensors **72** are arranged around the periphery of the facility in a non-limiting example, and may communicate using an Ethernet connection via optical/electrical converters **74** and interconnect via an optical fiber bundle to the electrical/optical interface **66** and the management access server **12**.

An internal location sensor array **80** is arranged within the periphery of the facility **44**, and in an example, located within a building. Internal geolocation devices are sensors

**82** that may connect via wireless link to each other and via Ethernet to the management access server **12**.

The system **10** includes cellular environmental monitoring **86** of the wireless communications network and includes a remote cellular scanner **88** that connects via Ethernet connection to the management access server **12**. The monitoring device **86** determines a change in the wireless communications network as a commercial network, for example, and implements a corresponding change in the radio equipment **40** such as a change in the power level of one of the picocell radios, a change in communications protocol, and/or a frequency change. Such protocols could include data and address formats, address mapping changes, routing changes, change in acknowledgement systems, change in direction of data flow, and changes in sequence and flow control.

It is possible to change different communication standards, including TCP/IP models and protocol layering with different encapsulation data formats. Changes in software layering are possible. Different network protocols can be used. Power levels may be changed to increase or decrease the power in towers connected to radio equipment **40** and directional antennas **46**. Frequency changes may occur with changes in protocol or depending on what occurs at the wireless communications network **45** such as commercial networks. Frequencies can vary depending on what other outside communication networks are used or other transmitters and radio sources are monitored and determined near the facility to adjust HF, VHF, UHF, and other frequency ranges, including those in the cellular commercial band. Different carriers have different frequencies, including frequency bands such as 3G, 4G, GSM, IS-95 as CDMA, 3G, and 5G. Different bands include the 700, 800, 850, 1400, PCS, AWS, and BRS/EBS frequency bands. These are non-limiting examples only. Power may also depend on the type of cell such as use of a picocell that is a small cellular base station covering a small area such as a shopping mall or train station. The system allows an authorized user to connect into a commercial carrier network that provides roaming services so that even if an authorized user of a mobile wireless device is not able to connect directly to their carrier they use on their mobile wireless device, it is possible to connect into a commercial carrier network that could be the same as the wireless communications network around a facility or a different network that provides roaming services. The system is deployable on cruise ships, oil platforms, and in mines as non-limiting examples.

An example could be a change in the wireless communications network **45** such as the addition of a rogue base station. The management access server **12** would be changed and configured to block communications from any mobile wireless device (MWD) **42** with that rogue base station. The management access server **12** also may provide outside communications when the given mobile wireless device is an authorized mobile wireless device using a Session Initiation Protocol (SIP) and provide outside communication when the given mobile wireless device is an authorized mobile wireless device via another network other than the commercial wireless network, such as a land-line connection via the Public Switched Telephone Network (PSTN). Another network could be used, such as an Internet Protocol (IP) network.

The managed access system **10** provides both the signaling and services for all cellular devices within the facility **44** and uses strategic channel selection, parameter configuration, and signal dominance. For example, the management access server **12** strategically selects channels used to estab-



lish the voice and data network within the facility **44** and may configure key parameters of the system **10** to attract cellular and other mobile wireless devices **42** to the system while making the commercial cellular network **45** unavailable. This can be accomplished using a) signal dominance, such as delivering a higher power, b) delivering a better quality signal, and c) adjusting other parameters relative to the commercial carrier network **45** to help ensure that the managed access system **10** provides a cellular voice and data network that is the strongest and most attractive signal within the facility as seen by cellular or other mobile wireless devices **42** and block any device from connecting directly to the commercial communications network **45**. The system **10** is effective for use with smart phones, tablets, cell phones, modems and other types of wireless devices that use cellular technology and other radio frequency communications to access voice or data networks.

As noted before, because commercial cellular carrier coverage varies between different facilities, to optimize the system for a particular facility, a survey of the cellular network in and around a facility **44** is first completed. The collected data determines the technology mix and frequency coverage necessary to provide the effective cellular mitigation within the facility **44**. Using this data, the RF “bubble” is created around the facility using the distributed antenna system **14** and its individual directional antennas **46**. Inside the RF bubble, all cellular and other mobile wireless devices **42** connect to the management access server **12** while outside the RF “bubble,” cellular and other mobile wireless devices operate as normal by connecting to the available commercial communications network **45**. Use of the management access server **12** and radios **40** connected to the directional antennas **46** allow the size and shape of the RF bubble to be contoured and tailored to the facility **42** by selecting specific antenna locations and RF power levels for each unique signal.

As noted before, it is possible to have a roaming partnership with commercial carriers to give the flexibility to use authorized mobile wireless devices **42** in their fullest commercial capability. Nothing has to change with the billing involved with the commercial carrier. The management access server **12** may provide the device either all, some, or none of the services inside the “bubble” on a case-by-case basis. The system may push a mobile wireless device **42** to a SIP, a voice connection, or PSTN and move from the cellular network as noted before.

Also, the management access server **12** may cooperate with the at least one MWD monitoring device **88** to determine whether the radio equipment **40** and at least one MWD monitoring device **88** both detect the given mobile wireless device and may generate an indication or alarm when one and not the other of the at least one MWD monitoring device and radio equipment detects the given MWD. The system **10** is tiered so that the indication or alarm could indicate that the MWD is outside the facility and beyond the fence line, for example, when the monitoring device **88** detects the device, but not the radio equipment **40**.

FIG. 2B is a block diagram showing a general layout of the managed access system **10** for the mobile wireless devices **42** in a facility **44** that is geographically within the wireless communications network **45** such as a network of a commercial carrier. The network **45** includes a number of base stations **45a**. As illustrated, the managed access system **10** includes a plurality of directional antennas **46** with associated base stations that are arranged around a periphery of the facility **44**, such as defined by a fence line **156** as also shown in FIG. 4, with radio equipment **40** coupled to the

plurality of directional antennas **46**. The radio equipment **40** could be located in the central server and radio rack **36** located at or near the management access controller **12**. The radios **40** could be located at the individual directional antennas **46** formed as cell towers in this example. At least one MWD geolocation device for the wireless communications network interoperates with the management access controller **12** and cooperates with the radio equipment **40** to communicate with a given MWD **42** within the facility **44**, block outside communications via the wireless communications network **45** when the given MWD is an authorized MWD and provide outside communications when the given MWD is an authorized MWD. The management access controller **12** operates with the at least one MWD geolocation device to locate the given MWD within the facility **44**. As noted before, the management access controller **12** is also termed the management access server and includes a processor **12a** and memory **12b** as noted before.

The at least one MWD geolocation device is operable for both cellular and non-cellular communications whether it is internal or external, and in one embodiment, includes a plurality of external geolocation devices **72** forming an external sensor array and arranged around the periphery of the facility as the wideband remote sensors. These devices as the sensors **72** may operate based on the time-difference-of-arrival signals. Another series of MWD geolocation devices include a plurality of internal geolocation devices **82** as internal sensors and arranged within the periphery of the facility, and in an example, within a building (B) as described later. The radios **40** may be picocell radios each coupled to a respective directional antenna **46**.

The management access server **12** may implement a corresponding change in the radio equipment **40** in response to a change in the wireless communications network **45** of at least one of a change in the power level of at least one of the picocell radios, a change in a communications protocol of at least one of the picocell radios, and a frequency range of at least one of the picocell radios. This allows an RF “bubble” to form around the facility, and which the RF bubble can be maintained and adjusted as necessary. The management access server **12** may provide outside communications when the given MWD **42** is an authorized MWD via another network other than the wireless communications network **45** such as through the Public Switched Telephone Network (PSTN) **244** and/or an Internet Protocol (IP) network such as through an SIP server **242** (FIG. 11). The radio equipment **40** may be operable according to one of at least a LTE, CDMA, UMTS and GSM protocol as noted before.

As illustrated, the facility **44** includes at least one monitoring device **88** for the wireless communications network. The management access server **12** may cooperate with the monitoring device **88** to determine a change in the wireless communications network and implement a corresponding change in the radio equipment **40** to adjust the radio equipment and adjust the RF “bubble.” This is advantageous such as when a rogue base station **45b** is monitored and determined to be active in causing a change in the RF “bubble” such that the rogue base station communicates with a MWD within the facility. The management access server **12** may block communications with the rogue base station **45b**. The management access server **12** may also cooperate with at least one MWD monitoring device **88** to determine whether the radio equipment **40** and at least one MWD monitoring device both detect the given MWD and operate to determine if the system is operating.

The management access server **12** also cooperates with the at least one MWD geolocation device as external or



## 11

internal sensors **72**, **82** to determine that a given MWD is within the facility and compares an identification of the given MWD to a list of authorized MWDs and determine whether a given MWD is unauthorized or authorized. It may coordinate with the wireless communications network **45** to block outside communications when the given MWD is an authorized MWD, provide outside communications via the radio equipment **40** and the wireless communications network **45** when the given MWD is an authorized MWD. It may block the outside communications when the given MWD **42** is an authorized MWD based upon a coordinated access denial with the wireless communications network **45** by allowing the base stations **45a** and a service provider **45c** of the wireless communications network to prevent communications. As illustrated, a network interface device **280** operates as an in-line ID monitor or filter to the wireless communications network and configured to communicate with MWDs **42** via the radio equipment and compare an identification of a given MWD to a list of authorized MWDs to determine whether the given MWD is authorized or unauthorized. The management access server **12** will filter communications between an unauthorized MWD and the network interface device that is configured to provide communications with the communications carrier. Communications will pass between an authorized MWD and the network interface device. The identification of the given MWD may be an International Mobile Subscriber Identity (IMSI).

FIG. **3** is a high-level flow diagram **100** showing a basic sequence of operation for the managed access system **10**. The process starts (block **102**) and an RF signal is identified (block **104**). The signal is evaluated as to the type and its RSSI (received signal strength indication) measurements collected (block **106**). The management access server **12** makes a decision whether the signal is cellular (block **108**) or non-cellular (block **110**). If cellular (block **108**), the potential cellular or other contraband mobile wireless device is identified (block **112**) and a determination is made whether that potential cellular contraband as a potential unauthorized mobile wireless device is inside the facility (block **114**). If not, the action ends and is reported for system evaluation (block **116**). If the potential cellular or other mobile wireless device contraband is a potential unauthorized mobile wireless device inside the facility, then the basic device identifier is collected (block **118**). A determination is made whether the user is approved (block **120**), and if yes, the action ends and the user is white listed for permissible communications either inside the facility or to other devices outside the facility (block **121**). If the user is not approved, then the management access server **12** will lock-out that particular user's mobile wireless device from the system **10** and the user will not be able to communicate using their device since it is an unauthorized device (block **122**). The device may be held on a communications channel (block **124**), however. The unauthorized device as the contraband cell phone or other unauthorized mobile wireless device is geolocated using the various geolocation devices, including the internal and external sensor arrays **70**, **80** (block **126**). Once geolocated, the geolocation "event" is correlated and logged as log event data (block **128**) and can be stored in the event log database **34** (block **130**). Also, security may be dispatched to investigate after the device is geolocated (block **132**).

After the signal is evaluated for its type and the RSSI measurements collected and a determination has been made the device is non-cellular (block **110**), a determination is made whether the device is authorized (block **134**) and if

## 12

not, it is geolocated (block **126**). If the device is authorized, then the process ends (block **136**).

FIG. **4** illustrates an example RF "bubble" **150** formed by the managed access system **10** using the plurality of directional antennas **46** arranged around the periphery of the facility **44** and showing the areas of blocked communications and area of uninterrupted communications towards the property line **152**. A potential interruption area **154** is located near the fence line **156** where the directional antennas **46** are positioned. The managed access system **10** is able to detect and disrupt unauthorized cellular communications inside the outermost perimeter fence line **156** of the facility, including all indoor and outdoor areas. The coverage area extends to the perimeter fence line **156** with sufficient signal strength to ensure that cellular and other mobile wireless devices **42** connect to the managed access system **10**. Some signals may propagate beyond the perimeter fence line **156** and the coverage area for the RF bubble **150** can be customized so that signal propagation outside the perimeter fence line **156** is minimized to ensure emissions do not disrupt any commercial carrier service beyond the property line **152**. In one example, the signal target level from the directional antennae **46** may be 60 dB stronger than commercial carrier signals at the perimeter fence line **156**. At the property line **152**, the signals from the directional antenna **46** may be 3 dB weaker than commercial carrier signals or less than -105 dBm as absolute channel power.

FIG. **5** is another schematic plan view of the facility **44** similar to that shown in FIG. **4**, showing the directional antennas **46** positioned around the facility **44**, and illustrating a zone of uncertainty as the interruption area **154** and showing the property boundary line **152** with the antenna front lobe forming the desired 6 dB power signal level stronger than commercial carrier signals at the perimeter fence line **156**. This is created by having the front antenna lobe from the directional antenna stronger than its rear or back lobe with the resulting 3 dB signal weaker than the commercial carrier signals or less than -105 dBm as absolute channel power at the area of uncertainty **154** and extending into the property boundary line **152** so that commercial carrier signals are not impacted beyond the property boundary line **152**. A commercial cell tower as an example is illustrated at **158** and any of its communications signals extending beyond the property boundary line **152** should not be adversely affected.

The Distributed Antenna System (DAS) **14** includes the plurality of directional antennas **46**, which in this example are positioned at a height of about 10 meters for this example correctional facility. In one example, twelve (12) directional antennas **46** are used in the example shown in FIG. **4** and six are used in the example of FIG. **5**. Another directional antenna **46** may be located at the central portion of the facility **44**.

An example directional antenna **46** is an antenna manufactured and sold by Galtronics under the EXTENT™ trademark such as a model D5778I. These example antennas are designed as 60°/60° narrow beam directional antenna with an operating range of 698-960 MHz and 1695-2700 MHz and adapted as a broadband directional, single-sector MIMO antenna for high-capacity venues. Each directional antenna **46** is connected to a radio **40**, which in one example is a picocell commercial radio as noted before and shown diagrammatically in FIG. **2A** and via the DAS master server **48**.

The distributed antenna system **14** is controlled via the DAS master server **48** by the management access server **12** that includes its main server or radio rack **36** as illustrated in



FIG. 6. The management access server **12** provides a graphical user interface **30** as explained above that can be controlled at a network operations center (NOC) **160** from a remote operator station **162** as illustrated. Authorized and unauthorized mobile wireless devices are detected as illustrated in the representation of the graphical user interface **30** shown in FIG. 6. The management access server **12** may implement corresponding changes in the radio equipment **40** such as a) changing the power level in one of the picocell radios, b) changing communications protocol in at least one of the picocell radios, and/or c) changing a frequency range of at least one of the picocell radios. For example, if a new transceiver **164** is added to existing and known transceivers **166** forming the commercial network **45** as located near the property line **152** of the facility such as shown in FIG. 7, the external RF signal forces exerted against the facility **44** will change because of the changed RF signal. An example of this scenario is shown in FIG. 8. When the baseline RF signal changes, the DAS **14** will make corresponding changes to one or more directional antennas **46** to compensate for the external RF signal forces that had changed the internal RF signal forces to maintain the RF "bubble" **150**.

The management access server **12** with the corresponding DAS master server **48** are contained in a secure facility such as a communications closet on site at the facility **44** and in a cooled location and includes easy power access and a ready optical fiber connection. The directional antennae **46** connect by optical fiber to the DAS master server **48**, which includes the appropriate processor, RF interface modules, optical modules, power supply, and UPS as shown in FIG. 6. The DAS master server **48** connects via RF in one example to the management access server **12**. The server or radio rack **36** for the management access server **12** and rack for the DAS master server **48** in one example are 42 U and 19-inch trays. In one example, the management access server **12** includes an HPDL **380** GENS 64G RAM 2 TB hard drive and a 48 port GigE switch **52** and a GigE firewall **54** (FIG. 2A). The management access server **12** includes the UPS **64**, PDU **62**, and a GPS splitter **60** with the locks for physical security **56** (FIG. 2A), e.g., a locking 42 U 19-inch rack with an RF patch panel, radio trays, and a managed access carrier GEN (MACG). The main server and radio rack **36** includes enhanced physical security with door locks and door ajar sensors, and the additional security features of water, humidity, temperature and smoke sensors. A camera may be implemented to capture the area for breaches and use NETBOTZ physical security appliance and accessories. The GPS time circuit **58** provides GPS time to the rack equipment via Ethernet. The GPS splitter **60** splits and amplifies the GPS RF antenna signal to the rack equipment. The PDU **62** provides 220 VAC with power sockets for the racked equipment and provides remote power on/off, voltage, and amperage reading per plug and rack and provides alarms on faults.

A block diagram is shown in FIG. 9 of an example tray layout of the main server and radio rack **36** and picocell radio **40** and with a 19-inch rack and mountable trays as part of the management access server **12** and is shown in FIG. 9. As illustrated, the uninterrupted power supply (UPS) **64** connects to an input/output panel **170** and a fan bus **172** to operate various fans and maintain cooling for the server **12**. The power supply **64** also interconnects to a power amplifier **174** that powers the various radios **40**. Ethernet power **176** is also provided via the input/output panel **170** and to radios **40**. Each tray may also include power, fans, and status LED's and may also include RF duplexer, filters or amplifiers as necessary.

FIG. 10 is a block diagram of the distributed antenna system **14** connected to different radios **40** that operate at multiple bands illustrated generally as Bands X and Y, each connected to a splitter/combiner **180** and an intelligent point-of-interface **182** where one per band is provided per interface. This intelligent point-of-interface **182** provides RF leveling and is programmable. Each point-of-interface **182** is coupled to the optical transceiver **184** and by optical fiber into the remote unit **186**, and thus, to a respective directional antenna **46**.

A Managed Access Carrier Generator (MACG) may interoperate with the distributed antenna system **14** and is part of the management access server **12** and has multi-carrier transmitter functionality for wireless networks. It generates up to four independently tuned control channels in one of several wireless licensed bands. It is possible to modulate a PN sequence with multiple frequency bands with an RF power output of about 1 watt. It may include various interfaces, including four individual TNC connectors in one example on a back patch panel with a combined carrier single TNC preferred so long as it is individually power controlled. The network may be 10/100 Ethernet TCP/IP with a standard RJ45 on the back panel and use SNMP.

Generated messages may include bit, active channels, temperature, frequency tuning, output power adjustment per channel, channel on or off, soft reset and hard reset. The state of health reports and events may be generated via SNMP messaging with a time sensitive active, temperature, power, radio fault, and VSWR alarm. The distributed antenna system **14** shown in FIG. 2A provides the programmable interfaces for the radio signals and multiple remote units and directional antennas **46** that sculpt the RF coverage for the RF "bubble" **150**. As noted before, the goal is to set the RF power levels for each cellular downlink signal at the fence-line **156** (FIG. 5) to be  $\leq 6$  dB stronger inside the boundary and 3 dB or more weaker outside the boundary as illustrated. The zone of uncertainty **154** is generated due to the antenna pattern back lobes where the effect is amplified at higher antenna power towards the front lobes.

Referring now to FIG. 11, a network security diagram for the managed access system **10** shows various components that implement network security and operate to isolate equipment and prevent malicious intrusions and system degradation. The management access server **12** interoperates via a switch **202** to the uninterrupted power supply (UPS) **64** and its various PDU outlets **204**. A physical security device **206** interoperates with a camera **210**, smoke detector **212**, water sensor **214**, humidity sensor **216**, temperature sensor **218** and door sensor **220** as also described above. The switch **202** also interoperates with the DAS master server **48** and a DAS uninterrupted power supply (UPS) **210** and the remote units **186** and DAS directional antennas **46**. The radios **40** form a radio array in the main server and radio rack **36** and are interconnected via the switch **202** to other internal components of the management access server **12** and outward through the firewall **54** to the event database **34** where events are recorded with local status and control via the remote operator **162** also shown in FIG. 6. From the firewall **54**, a connection is made to an internet service provider point of presence **230** and then to the internet **232**. The internet connection can be made to a remote firewall **234** for remote status control with various gateways **236**, switches **238**, and controllers **240** to allow status and control from a remote location. The Internet connection can also be via a third party Session Initiation Protocol (SIP) server **242** and to the Public Switched Telephone Network (PSTN) **244**.



## 15

Using this network security design shown in FIG. 11, the graphical user interface 30 may be used to provide entry of user credentials, including a user name, password and operator role. This may include in a corrections facility example the correction officer's station, device authorizer, contract or maintenance user, and operations administrator. A display screen may be provided for each role based profile. A corrections officer operator station 162, such as at the network operating center 160 (FIG. 6), will have the appropriate screen and user interfaces operating 24/7 without a timeout. The graphical user interface 30 allows the corrections officer to monitor RF transmissions, view estimated device locations, and estimate the types of signal emissions. Because a corrections officer may not have an authorized access or clearance, and because of federal or state regulations, it is possible that no specific data on device identification may be provided in some examples. The corrections officer should be able to observe health monitoring alerts that would be stored and listed in the event log database 34 (FIG. 1) and allow the correctional staff to respond further. An administrator user role will allow a user to view all data available to the corrections officer stations, but also acknowledge and clear alarms, define and run reports, and authorize system users. A device authorizer user will perform the tasks of the operations administrator and authorize devices for use within the facility, including cellular and other mobile wireless devices and traditional RF radio frequency devices. These devices possibly may not report as unauthorized events for a corrections officer station. The contractor that built the system 10 will have access, and any contracts manager will have access.

As noted before with reference to FIGS. 1 and 2, the cellular monitoring 16 of the system 10 will monitor the cellular environment and notify the managed access server 12 of any significant change to the RF "bubble" 150. It also will aid in establishing a base station survey of the commercial carrier network 45 to implement the distributed antenna system 14.

An example monitoring device as a remote cellular scanner 88 is a fixed autonomous telecommunications measuring receiver such as manufactured and sold by Gladiator Forensics under the tradename Gladiator 6700. One or more devices may be positioned at the facility 44 in a central or other location at the fence line or other areas. This monitoring device 88 provides layer 3 data for primary bands and technologies except IDEN and WiMax, in an example, although it is possible to provide a monitoring device to also scan IDEN and WiMax. The device or scanner 88 operates at 0-55° C. and uses minimal power. It uses a 9-34 volt DC input and a control connection via USB or WiFi. It is a small package of about 3×6×9 inches in one example. It can be operated manually with single button operation and autonomously scans and measures 2G, 3G, and 4G wireless networks and supports GSM, UMTS, LTE (TDD and FDD), CDMA, and EVDO. Most bands are supported in the frequency range of about 447 MHz to 3.8 GHz with pre-selection up to 8 bands. It includes MIMO downlink characterization. It has a nominal operating power consumption of 40 watts and is small and lightweight at 7 kg and ruggedized to an environmental specification of class 2 vibration and shock. Downconverted RF to IF signals are pre-filtered and passed to a signal processor where the data is collected and processed and sent to the drive application for analysis. It should be understood that other types of monitoring devices may also be used.

Changes to the commercial cellular network 45 may have a significant impact on the performance of the managed

## 16

access system 10 and/or size and shape of the coverage area, i.e., the RF "bubble" 150. The cellular network monitoring device 88 will examine any commercial carrier cellular network environment, looking for changes in its environment that will impact the performance or coverage area of the managed access system 10. The monitoring system 16 supports most frequency bands and cellular technologies currently in use within the United States, including TD-LTE, LTE-FDD, UMTS, CDMA, 1×RTT, CDMA, EVDO, and GSN.

The monitoring system 16 also regularly surveys the cellular environment at the facility 44 and the results of these surveys are compared to the previously established baseline for that site. A comparison will detect configuration changes to any commercial carrier signals, including changes in transmitted power, alteration of configuration parameters, and changed or any new frequencies, channels or bands that are deployed in the area. Regular monitoring is important because changes to the commercial cellular network 45 will have an impact on the effectiveness of the managed access system's ability to prevent contraband or unauthorized mobile wireless devices from accessing the commercial voice and data networks. This task can be performed daily at the facility 44. Thus, the system 10 is able to mitigate changes in the commercial cellular footprint. The state of health monitoring 22 and system and configuration management 24 (FIG. 1) may operate 24/7 and the system 10 may generate weekly reports for status and activity updates and periodic updates for changes in cellular environmental changes that are discovered to the external network configurations in the commercial network 45. The table below illustrates non-limiting examples of different monitored features for the system 10.

Cellular Baseline System	Weekly Reports System Health Verification Blocked Call Detail Record User ID Report Audit Log Reports Authorized Number Alert Report Authorized Number Reports Authorized Number Expiration Reports Cellular Environment Current Status (Threat Assessment) State of Health Alerts Over-temperature Alert Tamper Alert - Rack Off-line System Components
Internal Localization Sensor Array	Weekly Reports System Health Verification Cellular/WiFi Event Localization Report

When a commercial carrier change in the commercial communications network 45 indicates a change is required to the software configuration for the managed access system 10, a file may be pushed electronically to the management access server 12 at the facility 44. Any software upgrades or updates can be coordinated with a designated facility officer or at the network operations center 160 to ensure any potential system operation disruption is coordinated and minimized. Once the update is applied, a repeat survey can be completed to ensure that the event risk has been mitigated and the issue resolved.

If a change in commercial carrier 45 dictates a hardware configuration change in the system 10, the system builder may coordinate with a designated facility office to schedule a site visit and make the prescribed changes. An example could be when the change in cellular coverage indicates an



alignment of one or more directional antennas **46** is required or an adjustment should be made to improve signal delivery and compensate for an increased commercial carrier signal level. If a change also indicates a new or additional hardware upgrade is necessary to maintain system performance effectiveness, such as when a new commercial carrier has added coverage to the area, the system builder may develop a proposal for necessary changes and add or upgrade equipment.

As noted before, the monitoring device **88** initially determines the existing commercial coverage site baseline using a cellular site survey. For example, FIGS. **12** and **13** are bar charts showing an example of the measurements in a local cellular environment in one non-limiting example that is assumed for a facility deployment. FIG. **12** compares the local coverage to an assumed base station radio selection by technology, per carrier, and FIG. **13** compares the local coverage to an assumed base station radio selection by frequency band, per technology. FIG. **14** is a table summarizing the base station technology mix that has been assumed at that facility.

FIG. **15** is a flowchart showing an example of the steps for designing and constructing the distributed antenna system **14**. The process starts (block **250**) and the existing commercial network **45** coverage site baseline is established (block **252**). This may encompass a drive survey around the facility **44** to determine the technologies, frequency bands, channels and predicted coverage for the facility **44**. The strongest serving cell plots for each carrier for each technology and frequency are established in the cell survey to form the coverage site baseline.

A preliminary distributed antenna system **14** design is implemented (block **254**) and the location, height and directional antenna **46** type are determined based upon the site baseline and the system **10** signal coverage zones established throughout the facility **44**. The signal coverage boundary at the facility **44** for the fence and property lines **152**, **156** are also calculated. A preliminary distributed antenna system **14** configuration is established.

The preliminary distributed antenna system **14** design is verified and finalized (block **256**), followed by an on-site installation with verification and tuning of directional antennas (block **258**) and on-site system coverage tuning (block **260**). The process ends (block **262**).

An example of an external geolocation device or sensor **72** that forms the external geolocation sensor array **70** around the periphery of the facility **44** is an array of sensor devices such as the RFeye array sensor manufactured and sold by CRFS as the RFeye series of sensor devices. These external geolocation devices **72** are arranged around the periphery of the facility such as shown in FIG. **16** and may provide a "heat map" with course granularity sensing of RF radiators, such as cellular or other mobile wireless devices, including non-cellular devices, that energize on the premises. This heat map may be generated from time difference of arrive (TDOA), power on arrival (POA), and angle of arrival (AOA) signals. This sensor array **70** may also locate rogue signals autonomously and report them to the management access server **12**. Each sensor **72** may include a dynamic and programmable RF filter mask with logging of signals and mapping of signals on the graphical user interface **30** to depict a floor plan at the facility and show the relative location of selected signals.

Referring to FIG. **16**, the facility **44** shows six directional antenna **46** locations indicated by the stars. The triangles depict four locations for external geolocation devices **72** forming the external sensor array **70** with devices **72** located

at the central sections of the rectangle formed at the fence line **156**. The poles supporting the directional antennae **46** at the mid-section could also support an external geolocation device **72** in a non-limiting example. FIG. **17** shows an example of the wideband remote sensor device **72** with a semi-hemispherical outer housing **72a** and support base **72b**. FIG. **18** shows the outer housing **72a** removed and showing spiral directional antenna modules **72c** that are arranged at an angle to each other, and in this example, about 60-90° from each other. This external geolocation sensor array **70** may be formed from remote sensor devices **72** that are available in different sizes and antenna configurations and have frequencies ranging from 20 MHz to 18 GHz. The sensor devices **72** use twin receiver channels to provide simultaneous monitoring, directional finding (DF), and geolocation capabilities. The spiral directional antenna modules **72c** may be optimized for different frequency bands and arranged in multiple orientations. These antennae are sensitive to incoming signal polarizations, including all linear polarizations. These sensor devices **72** allow an angle of arrival bearing based on the received power to each antenna and may be overlaid on a user interface **30** as maps, satellite images and 2D/3D GIS data sets to give a positional display and geolocation probabilities for a mobile wireless device **42** in the facility.

With angle of arrival sensing, the devices **72** rapidly switch between the directional antenna modules **72c** and respond directly to the received RF power. Thus, they are effective with most types of RF transmission. Using angle of arrival, three receiver points ensure geolocation to a small area, even when the target is colinear with two receivers. Results may be limited by the noise floor of the receiver.

With time difference of arrival, the devices **72** use synchronous time domain to determine the relative time of arrival of a signal at different receiver locations. Two monitoring receiver points provide geolocation probability in two dimensions along a hyperbolic curve, while three receiver points provide geolocation probability to a bounded area or point. An advantage is that the processing gain of correlations permits successful geolocation of signals close to or even below the receiver noise floor. Power on arrival uses synchronous frequency domain and is beneficial for those mobile wireless devices **46** that are close to or among different buildings where amplitude comparison will yield sufficient differences. It uses three or more monitoring receiver points.

An internal location sensor array **80** is formed from internal geolocation devices as internal sensors **82** and are arranged within the periphery of the facility. In addition to adding the ability to localize a cellular or other mobile wireless device **42** in and around the buildings on facility grounds, the internal sensor array **80** provides the added capability to detect and estimate the location of WiFi devices in and around the various buildings of the facility **44**.

An example internal geolocation sensor **82** is a location-based WiFi and cellular detection and monitoring device manufactured and sold by AirPatrol under the tradename ZoneAware, as a precision location-based services platform. These sensors **82** may interoperate with a ZoneEngine application programming interface, also manufactured and sold by AirPatrol. The sensor **82** location is accurate to within 6 to 50 feet depending on the type of device and their spacing. The sensors **82** may incorporate positioning capabilities using beacons and a Bluetooth standard known as "Bluetooth Low Energy" (BLE) to broadcast messages to other devices within a small tunable radius around the beacon. In one non-limiting example, sensors **82** may be



located approximately 65 feet apart with different sensors located on different floors and linked in a mesh network via WiFi or connected via wired Ethernet or Power over Ethernet. The sensors **82** are deployed throughout buildings in the facility, usually on the exterior of the buildings, and at a higher elevation for enhanced security to prevent tampering.

The detection of cellular signals using the managed access system **10** is a layered or tiered approach and focuses on determining which internal or external geolocation sensor **72**, **82** detected the signal and at what level the signal was detected. An indication or alert can be placed on the user interface **30** to indicate the sensor or sensors that identified the signal transmission and at what power level. This alert will provide a general location where the mobile wireless devices **42** are located, such as shown in the example of FIG. **19**, which illustrates the user interface **30**, for example, at an operator's screen at the network operations center **160**. This user interface **30** shows an example building **30a** at the facility and the alert **30b** on the floor for the mobile wireless device at an area near the stairwell **30c**.

Detection and accuracy of the localization functionality are dependent on the ability of the sensor **82** to: (1) receive a signal at a sufficient level (often  $-100$  dBm or greater); (2) the construction of the facility being protected; and (3) the placement separation of the sensors themselves. An example placement for sensors **82** is shown in the facility **44** of FIG. **20**. In this non-limiting example of a correctional facility, many sensors **82** are positioned on the exterior of buildings, indicated at **82a**, where they will not be reached easily and removed and can be readily observed by security. A few sensors indicated at **82b** are located inside some of the larger buildings, for example, which may have upper floors or internally secure areas.

In the example of FIG. **20**, the accuracy of a sensor **82** is equal to about twice the radius of a sensor separation distance. This will vary depending on the building type and the actual accuracy measurements would be determined based upon a completion of the site survey and design analysis. Usually mobile wireless devices **42** would be detected and marked with the resolution of about 50 meters. This is a layered approach to detection and disrupting unauthorized calls. If a facility desires a higher degree of accuracy, this can be accomplished by increasing the number of sensors **82**, resulting in enhanced accuracy to within five meters. This enhanced accuracy will increase the cost of any facility installation, however.

The managed access system **10** prohibits cellular and other mobile wireless devices within the protected facility **44** from accessing commercial voice and data networks by attracting and providing service to those devices within the facility. The system **10** interacts with each device using industry standard messaging traffic and these device interactions can be used to generate event records within the system **10** that identify specific information. The system **10** may process each event with a time/date stamp, the type of event (registration, voice call, text message and other details of the event), along with any electronic hardware identifier (IMEI/ESN/MEID) that is associated with the event, including carrier account identifiers (IMSI, MIN), and the dialed number if applicable. The system **10** may store each event record in the local database such as the event log database **34**. The system provides a flexible routing capability that allows the system **10** to route unauthorized device voice call and data access attempts. For example, voice calls could be routed to a standard or custom pre-recorded announcement or to a voice mailbox or even local dialed extension.

Further information could be verified as to the caller to allow the call to be connected or disabled. Data access attempts can be routed to a standard or customized website maintained locally within the facility **44** or can be configured to send traffic to a predefined address on the outside commercial communications network **45**. Authorized users are allowed to access outside voice and data networks so their devices can make outside voice calls, send texts, and access content on the Internet. This may be authorized by several techniques through the managed access system **10** such as redirecting authorized devices to the commercial communications network **45** and allow them to access the outside voice and data networks. This approach allows an authorized mobile wireless device **42** access to all services provided by their home commercial carrier. Another approach allows all authorized calls through the existing inmate telephone system (ITS), but this approach has privacy concerns for authorized device users.

A preferred technique is to provide voice conductivity through a third party SIP server **242** (FIG. **11**) and route text and data accesses directly to the Internet **232** through a gateway connection. This would allow the managed access server **12** to provide conductivity to any authorized devices and route the voice and data traffic to the Internet **232** and to the appropriate off-site service connection point. Up to forty authorized users may be used in an example and even more authorized users depending on the equipment and set-up. The managed access system **10** will permit 911 calls from any device whether authorized or not and calls can be directed to the appropriate local emergency services agency or facility security office using the voice-over-IP (VoIP) connection through the SIP server **242**, for example. Emergency 911 calls can result in an alert to the organization's security office that the call was initiated by a mobile wireless device **42** within the facility **44**. In the event of a 911 call by a mobile wireless device **42** connected to the managed access system **10**, a local emergency Public Safety Answer Point (PSAP) may be the answering location and the proposed baseline implementation routes the call through the locally hosted SIP server **242** for conductivity. This will result in a call appearing to be calling from a land-line phone within the facility.

As noted before, each call interaction with a mobile wireless device **42** connected to the managed access system **10** generates an event record within the system **10** that includes the time/date stamp, the type of event such as the registration, voice call, text message and other details along with the hardware identifier and any carrier account identifier that was associated with the event. The system **10** stores each event record in the event log database **34** such as shown in FIG. **1**. Because each of the attempted calls is stored as a unique event record, the system **10** may compare the data to search for the use of multiple SIM (Subscriber Identity Module) cards by a single hardware device or the occurrence of a single SIM in multiple hardware devices. This information may be automatically flagged and the device black-listed from use and placed on an investigative user interface screen for quick reference such as shown in the user interface **30** screen in FIG. **21**. In the indicia, the thumbs down corresponds to an unauthorized device and the thumbs up to an authorized device. The device with the swapped SIM card may be color coded differently. Other device details are included as illustrated, including device identifiers, type of calls such as voice or SMS, and other details.

As noted before, different reports may be generated with the aid of the user interface **30**, such as the example screen shots in FIG. **22** showing an authorized device with the



thumbs up designation and unauthorized devices with the thumbs down designation. Further details of those devices can be determined by clicking on appropriate tabs. The graphical user interface may include information such as the time of the event, e.g., call or SMS text, device identifier, and even number dialed.

The system **10** may also operate in a passive or active mode. In the passive mode, the system **10** allows a mobile wireless device **42** within the coverage area formed by the RF bubble **150** to interact with the system, but does not disrupt access to the commercial communications network **45**. It may be used during system verification prior to “going-live.” Once the system **10** is tuned and adjusted, it can be switched over to operate in the active mode where the system attracts and holds cellular and other mobile wireless devices **42** within the facility coverage area. The system **10** prevents those devices from obtaining service from the commercial networks. In this mode, authorized mobile wireless devices **42** are allowed access to voice and data services, while unauthorized devices are not. The active mode would be the normal mode of operation for the system **10**.

Because the system **10** has enterprise capability with connection to external communications of a commercial communications network **45**, the system **10** is provisioned to log and report event data in customizable ways that make use easy for the operator. In this case, reports, system alerts, emails, and even text messages can be sent and displayed on the graphical user interface **30** when specific events occur. This may include:

1) Health Monitoring: Provides the ability to monitor and view the system health, including status and performance of all major components, equipment alarms, software issues, performance of the servers and web portals.

2) Report Generation: The system also provides the ability to monitor and generate reports on the system performance and threat assessments, create alert logs, audit trails, and long-term activity records. Time and date information are synchronized to the facility logs. Some of the standard reports and alerts are listed below.

Blocked Call Detail Record: Identifies all blocked cellular wireless calls and includes information about the facility from which the call was placed, i.e., date and time, originator’s phone number, originator’s cellular device hardware ID, and destination phone number (dialed digits). If the optional sensor array is installed, a location estimate is also provided.

User ID Report: Reflects the activity of user ID accounts created/activated during a specific reporting period. This report indicates the name and User ID of the device user that created/activated the account with the date and time stamp, the user account(s) created/activated, the date the profile was deactivated, the last successful or attempted log-in, and all updates to the account.

User ID Alert: Notification of modifications to a device user account.

Audit Log: Provides the User ID, name, log-in date and time, activities (files accessed) for each session. The system also records and reports the user ID, name, time and date of failed attempts.

Authorized Number: Notifies the appropriate operator of the system **10** when a new mobile wireless device **42** has been added or devices have been deleted from the authorized cellular device list. Details the telephone numbers that have been identified as authorized to make calls within the facility. Includes the unique user identifier of the personnel that entered or modified the Authorized Number status as well as the dates of status changes to each number.

Authorized Number Expiration: Provides for authorized cellular wireless device or group of devices due to expire within 30 calendar days.

The system **10** is designed to self-monitor and report the system state of health in order to minimize the operational labor costs. Each functional component of the system **10** is monitored to ensure it is operating normally so the system operates at peak performance. The system **10** verifies communication links to provide a high reliability fault management approach. Any alarm or change in the operating conditions generates a system alert. All alerts are first acknowledged by the appropriate operator prior to the condition being either automatically or manually cleared.

As part of the state of health monitoring **22** (FIG. **1**), the system **10** may provide a physical security feature such as the network security shown in FIG. **11** that detects physical intrusions or hardware tampering attempts, such as an unauthorized opening of an equipment rack. The physical security also provides the ability to monitor humidity, temperature, and other environmental conditions remotely. Alerts are generated to protect the system integrity from physical intrusion and environmental threats. Cameras **210** (FIG. **11**), for example, are mounted to monitor the main system rack and are used to visually verify personnel prior to allowing physical access to hardware.

As noted before, the physical security includes the ability to control physical access to hardware and record and log physical access events. Built-in physical security includes an integrated camera **210** and environmental sensors, including temperature **218**, humidity **216**, airflow such as smoke **212**, door **220**, and audio and video recording (FIG. **11**). By monitoring these parameters, the system **10** is able to ensure that the system state of health is protected from accidental environmental faults and ensure any attempts to alter the system maliciously can be recorded for corrective action.

Automated Health Monitoring includes status of the physical (hardware) elements of the system, performance monitoring and metric collection, fault detection and alarms. The status of each line replaceable unit (LRU) is tracked and reported independently, including damaged cables, antennas and sensors.

The system includes an uninterruptable power supply (UPS) **64** (FIGS. **2**, **9** and **11**) with sufficient levels of stored power to support the management access server **12** and the associated DAS master **48** for 30 minutes during interruptions to primary power to the facility **44**. In the event that power is not promptly restored and the remaining power levels begin to reach a drained state, the system **10** may record an entry in the event log database **34** (FIG. **1**) and implement a graceful shutdown to avoid damage. When power is restored, manual reactivation may result in the system restarting and resuming full operation.

In order to control costs, any remote LRU’s may be connected to protected, back-up power, allowing their continued operation during temporary power outages. The system **10** is also designed to withstand the challenging environment of a correctional institution, if the system **10** is implemented in such a facility. As such, it is not anticipated to require frequent repair from routine damage of wear and tear. Should the system **10** be damaged from events such as lightning strikes, the system provider or installer may be automatically alerted to the event by the state of health monitoring **22** and the system **10** may generate an alert to notify an operator and system provider of the issue.

It is possible that the system **10** may identify and characterize rogue cellular towers using the various sensors and scanners **72**, **82**, **88**, in accordance with a non-limiting



example. An example is a rogue fempto cell tower, which is typically a small, low-power cellular base station and connects via broadband such as by DSL or cable to the network **45**. Rogue fempto cell towers create threats to the managed access system **10** and will be identified and managed. Other towers may be a newly provisioned commercial service or covertly placed near and network connected. A fempto cell could also be a voice over IP (VoIP) WiFi cell tower or rogue cell tower. The various devices and sensors **72, 82, 88** may use a cellular protocol layer-3 information to identify the existence and location of a rogue cellular tower in near real-time. The sensors **72, 82, 88** identify the operating characteristics of the new and/or rogue cellular towers in sufficient detail to allow the site to be mitigated by the managed access system **10** or they may be investigated by others. It is advantageous over those techniques that authenticate tokens and blacklist, or use a baseband “man-in-the-middle” approach for mitigating threats.

Referring now to FIG. **23**, it is also possible to provide a cellular in-line ID monitor **280** as a network interface device for access management. This in-line monitor **280** will provide device identification and filtering for controlled device access between a specific cellular base station and commercial networks. For example, the base station may be configured to induce a registration event as a localized LAC (Location Area Code) and the in-line ID monitor **280** may be installed on the S1-MME interface between the base station and the core network. The in-line ID monitor **280** will compare the IMSI (International Mobile Subscriber Identity) to a database **282** of approved IMSI ID’s, allowing only approved devices to register with the commercial network **284**. Any non-approved devices are connected to a local core network that is hosted within the system, allowing unauthorized devices to be managed within the system for assured security. FIG. **23** further shows the managed access system **10** and its management access server **12** and the monitoring function **16** with the monitoring device **88** and network operations control center **160**. The passive scanning and signal geolocation is operable by internal and external sensors **72, 82**. The in-line ID monitor **280** connects to an approved ID database **282** and approved devices **284** in the commercial communications network **35**.

As noted before, the management access server **12** may filter communications between an unauthorized MWD and the network interface device as the in-line IDS monitor and pass communications between an authorized MWD and the network interface device. As noted before, the system is a tiered approach. Unauthorized devices may be held within a “holding pen” where no communications are allowed, and it is possible to deny portions of services and allow the devices to communicate with other authorized or unauthorized devices only in the facility. It is possible to limit outside communications to the device. It is possible to allow the devices to text an SMS message. It is also possible to allow the devices to send alerts and other messages. Thus, the management access server **12** may be configured to permit an unauthorized MWD to communicate with other MWD’s

at the facility whether unauthorized or authorized depending on how the system is established.

FIG. **24** is another view similar to FIG. **23** and showing the commercial communications network **45** and further details of a MME server, HSS server, 3 GPPAAA server, and other components of the commercial communications network. The in-line monitor **280** forms the filter that is installed at the customer facility on the S1-MME interface between the local site eNodeB. It uses the database **282** of the approved IMSI ID’s to allow known approved devices to register with the commercial communications network **45**. Any non-approved mobile wireless devices **42** may be connected to a local core network that is hosted within the facility **44**, allowing unauthorized mobile wireless devices to be managed within the system **10** for security. Thus, it is possible to provide an automated in-line ID monitoring for private cellular installations and control and identify authorized users for service connection.

Referring now to FIG. **25**, a managed private cellular access system **286** operates similar to a commercial service provider’s offering service to all devices within the Customer Site Coverage area as the managed access system **10**. That system **286** interfaces the commercial communications network **45** using standards based interfaces for roaming partnerships. Once any devices are registered, the system uses an authorized access database **282** to manage which devices are allowed access outside the system.

FIG. **26** shows a private HSS **288** as a home subscriber server. Whenever a mobile wireless device **42** attempts to register on the site eNodeB installed at the customer site, the registration is routed to the private HSS **288** that is configured with the authorized set of devices as designated by the customer. Any unauthorized devices are not registered and the customer site coverage may induce a registration event, e.g., a localized LAC. The private HSS **288** may provide an ISMI and security credentials for the customer designated authorized devices.

FIG. **27** illustrates a coordinated access denial system **290** that provides passive monitoring and a geolocation system that locates mobile devices operating within the customer facility. When a device that is not on the approved list is detected and positively located as being within the facility, the system **290** communicates with the commercial carrier network **45** so that the carrier does not provide service to that device. This may raise some issues of how to re-allow service to a device once it has been identified by the system.

As noted before, the site survey will be used to form a baseline of the existing commercial cell coverage, design distributed antenna system, verify the distributed antenna system **14**, and finalize construction. As a non-limiting example, once the system is installed and operational and tuning of the distributed antenna system verified, a Site Acceptance Test (SAT) is completed, which ensures that operational coverage and functionality are acceptable for the facility **44**. Table 1 below is an example of the tests and verifications that may be completed for final installation as a non-limiting example.

TABLE 1

Example of High Level Tests and Verification					
Step	Capability	Key Performance Metrics	Success Criteria	Determination Methodology	Notes:
1	Operation	System Detects Faulted Hardware	100%	System running. Select any	A sample of random LRU’s will be tested

TABLE 1-continued

Example of High Level Tests and Verification					
Step	Capability	Key Performance Metrics	Success Criteria	Determination Methodology	Notes:
2	Operation	System Detects Physical Alarms and reports event	100%	LRU and pull power, disconnect Ethernet connection, or remove optical connector. Detect fault System running. Apply a heater to the rack temp sensor. Verify notification and log. Repeat for other sensors	Temp, Water, Smoke, Humidity, Video, Door Ajar
3	Operation	System Allows Remote Software Upgrades	100%	Remotely flash a new software load and verify new executable image loaded from a network login	
4	Operation	System Allows Remote Control and Status Monitoring	100%	Verify GUI works from outside firewall	
5	Operation	System Provides Tiered User Access levels via System Sign-on Credentials	100%	System Running, log in, determine access and lock outs	Repeat for each user class
6	Electronic Threats Detection	System Identifies contraband cellular phone in coverage area and reports	95%	System running. At selected locations, turn on Harris provided test contraband cellular phones. Verify registration and event logs	Multiply by All: local technologies × Providers × Bands. Locations will be determined by applying a 10 wide × 10 long grid across coverage area and selecting test points within each grid sector
7	Electronic Threats Detection	System Provides Logs of detected device events	100%	System running, invoke events, view logs	Multiply by All: local technologies × Providers × Bands. Locations will be determined by applying a 10 wide × 10 long grid across coverage area and selecting test points within each grid sector



TABLE 1-continued

Example of High Level Tests and Verification					
Step	Capability	Key Performance Metrics	Success Criteria	Determination Methodology	Notes:
8	Electronic Threats Detection	System Provides Localization of User Equipment in Covered Area to within (If option implemented)	TBD meters	System running, invoke contraband cellular phone, view GUI report	Each protected building will be tested at evenly distributed test points. 10-100 points/building
9	Interdictions	System Interdicts contraband cellular phone voice calls and reports event	95%	System running, turn on contraband cellular phone in coverage area, verify no service at cellular phone	Multiply by All: local technologies × Providers × Bands. Locations will be determined by applying a 10 wide × 10 long grid across coverage area and selecting test points within each grid sector
10	Interdictions	System Interdicts cellular phone Generated SMS Messages and reports event	95%	System running, send SMS from contraband phone, verify no SMS sent	Multiply by All: local technologies × Providers × Bands. Locations will be determined by applying a 10 wide × 10 long grid across coverage area and selecting test points within each grid sector
11	Interdictions	System provides graphic representation of localized cellular phone on representative map of coverage area	95%	System running, invoke contraband cellular phone, locate on site map	Multiply by All: local technologies × Providers × Bands. Locations will be determined by applying a 10 wide × 10 long grid across coverage area and selecting test points within each grid sector
12	Interdictions	System prevents incoming voice calls to contraband cellular phones in coverage area	95%	System running, call a contraband cellular phone number hosted in covered area, verify no call completed	Multiply by All: local technologies × Providers × Bands. Locations will be determined by applying a 10 wide × 10 long grid across coverage area and selecting test points within each grid sector

TABLE 1-continued

Example of High Level Tests and Verification					
Step	Capability	Key Performance Metrics	Success Criteria	Determination Methodology	Notes:
13	Interdictions	System prevents delivery of SMS messages to contraband cellular phones in coverage area	95% within 1 hr	System running, SMS message powered contraband cellular phone in covered area from outside cellular phone, verify no SMS delivered over 1 hour	Multiply by All: local technologies × Providers × Bands. Locations will be determined by applying a 10 wide × 10 long grid across coverage area and selecting test points within each grid sector
14	Access management	System Provides cellular phone initiated Voice Service to authorized users and reports event	95%	System running, turn on authorized cellular phone in coverage area, verify voice service at cellular phone	Multiply by All: local technologies × Providers × Bands. Locations will be determined by applying a 10 wide × 10 long grid across coverage area and selecting test points within each grid sector
15	Access management	System Provides 911 from any cellular phone in coverage area and forwards to specified cellular phone and reports event	95%	System running, dial 911 from cellular phone in coverage area, verify rings through to specified cellular phone	Multiply by All: local technologies × Providers × Bands. Locations will be determined by applying a 10 wide × 10 long grid across coverage area and selecting test points within each grid sector
16	Access management	System facilitates delivery incoming SMS Service to authorized cellular phones and reports event	95%	System running, SMS message powered authorized cellular phone in covered area, verify SMS delivered	Multiply by All: local technologies × Providers × Bands. Locations will be determined by applying a 10 wide × 10 long grid across coverage area and selecting test points within each grid sector



TABLE 1-continued

Example of High Level Tests and Verification					
Step	Capability	Key Performance Metrics	Success Criteria	Determination Methodology	Notes:
17	Access management	System facilitates delivery of SMS Service from authorized cellular phone and reports event	95%	System running, SMS message sent from powered authorized cellular phone in covered area, verify SMS delivered	Multiply by All: local technologies × Providers × Bands. Locations will be determined by applying a 10 wide × 10 long grid across coverage area and selecting test points within each grid sector
18	Access management	System does not interfere with commercial cellular service outside the property boundary of the facility	95%	System running, verify OEM service outside of property boundary	Multiply by All: local technologies × Providers × Bands. Locations will be determined by applying a 10 wide × 10 long grid across coverage area and selecting test points within each grid sector

Once the physical site survey is accomplished as explained above, engineers can determine site specific data such as power and cooling requirements for equipment, any cable routing access, any access and power requirements, and any antenna locations and similar details. Engineers may determine specifics relating to local or state building codes and issues relating to site (customer) specific permitting. Existing underground utilities may be identified and any other cables tested prior to being energized, including existing and new voltage, fiber optic or Ethernet cables.

As noted before, the managed access system **10** monitors and generates reports for system performance and threat assessments such as alert logs, audit trails, and long-term activity records. These reports can be standardized. Possible reports could include a blocked call detail record that identifies all blocked cellular wireless calls and includes information about the facility from which the call was placed, its date and time, the originator's phone number, the originator's cellular device hardware identifier (ID), and the destination phone number as the dialed digits.

A user ID report may reflect the activity of user ID accounts created and activated during a specific reporting period. This report may indicate the name and user ID of a user that created or activated the account with the date and time stamp and the user accounts that were created or activated and the date the profile was deactivated as well as the last successful or attempted log-in. Information regarding the creation, modification and deletion of a user account may be generated. An audit log report may provide the user ID, name, log-in date and time, activities with the files accessed for each session, and the records and reports for the user ID, name, time and date of failed attempts.

An authorized number alert report may be generated to notify an appropriate operator when a new mobile wireless device **42** has been added or mobile wireless devices deleted from the authorized device list. Authorized number reports may detail the telephone numbers that have been identified as authorized to make calls within the facility **44**. This report may include the unique identifier of a user that entered or modified the authorized number status and the dates of status changes to each number. Expiration reports may be provided for authorized cellular wireless device or groups of devices due to expire within 30 calendar days as a non-limiting example.

Software CSCI (Computer Software Configuration Items) are now described with reference to FIGS. **28-33**. For example, the managed access server **12** may operate with an operator interface **300** such as at the NOC **160** as shown in FIG. **28**. A web server **302** interacts between the operator **300** and a bridge **304**, including an Applications Programming Interface (API) library **306** and a managed access server main application **308**, which may be responsible for command/control of the system **10** and manage the access to a voice/data network and a state of health (SOH) for system hardware. It may authorize devices and access restrictions and generate reports of various activities and include database interactions.

The MAS main application CSCI **308** is shown in FIG. **29** and includes functional components of the message manager **310**, test manager **312**, SOH manager **314**, network manager **316** and surveyor manager **318** with interfaces to the database interface **320** and a geolocation interface **322**. An example function of the message manager **310** of FIG. **29** is shown in detail in FIG. **30** and operates with the bridge **304** and web server **302** with requests **324** to the main applica-



tion **308** from the operator **300** and responses **326** back and forward indications **320** to the operator. The message manager **310** handles buffering of incoming messages and dispatches the incoming requests **324**. Different supported message types include requests that are input from the graphical user interface **30** and a response **326** as a reply to a received request message. The indication is an unsolicited message sent by the main application.

The network manager **316** shown in FIG. **29** will maintain control and status for all hardware, including SNMP and the API from the manufacturer. It may include a database that maintains site-specific hardware configurations such as the IP address, hardware type, manufacturer and other details.

FIG. **31** illustrates the SOH manager **311** that interoperates with the network manager **316** and the server **12** with the various radio circuits **40**, firewalls **54** and UPS **64**. This manager **311** requests periodic statements of health (SOH) and identifies alarm conditions such as an unsolicited alarm received from hardware and may be based on limits defined in the database with the alarm severity configurable for a facility. For example, some minor problems may be detected but should not generate an alarm in an unsecured facility while a more secured facility such as a correctional facility may be configured to generate alarms more periodically for less critical events. The SOH manager also manages reporting and clearing of active alarms.

The surveyor manager **318** will initiate periodic surveys of surrounding cellular towers and the survey results are stored in the local coverage database **26** (FIG. **1**). Alarms are sent to the users when a new tower is detected, a new channel is detected, or a channel power has changed. A database may include system settings, hardware configuration, alarms, listing of authorized devices, detected RF events and authorized users as the system operator.

Referring now to FIG. **32**, the geolocation interface **322** interoperates with a guard server **340** and sends event messages when an RF signal is detected as with the external geolocation sensors **72** forming the external geolocation sensor array **70** and also operates with the internal geolocation sensors **82** forming the internal location sensor array **80** to obtain device location information. The internal sensor array **80** may have its own sensor database **342**. The test manager **312** in FIG. **29** may provide interactive menu-driven test capabilities for testing the system.

The web server **302** serves the web application and supports multiple simultaneous operators. As shown in FIG. **33**, the communications bridge **304** between the web server **302** and the MAS main application **308** will maintain a list of connected users and provides for Remote Procedure Calls (RPC) for the web server and may use the MAS Applications Programming Interface (API) libraries **306** as part of the managed access system **10** and be incorporated into the NOC interface **160** with network connections. Third party applications may include the My SQL database for storing events and settings and Quortus may provide core functionality for the cellular network and interface with radio hardware. A star solutions PDSN may provide data communications for CDMA radios and evaluate PDSM software options. GSOAP generates SOAP services for communicating with Quortus. Open source hardware may include node.js as a web server application and SNMP++ as the API for excessive hardware control and status information. Qt may be the framework used for a bridge application and Protobuf as a messaging library. Boost may provide general utilities and websocket PP may be the websocket API for interfacing with CRFS geolocation software as described above. Rapid JSON may be used as a parser for geolocation

data and asterisk may provide a path for voice communications to an SIP trunk. The network operations center can be a remote facility.

This application is related to copending patent applications entitled, "MANAGED ACCESS SYSTEM WITH MOBILE WIRELESS DEVICE GEOLOCATION CAPABILITY," assigned U.S. patent application Ser. No. 14/865,277 and "MANAGED ACCESS SYSTEM WITH MONITORING DEVICE TO DETERMINE AND CHANGE RADIO EQUIPMENT," assigned U.S. patent application Ser. No. 14/865,308 and "MANAGED ACCESS SYSTEM THAT DETERMINES AUTHORIZED AND UNAUTHORIZED MOBILE WIRELESS DEVICES," assigned U.S. patent application Ser. No. 14/865,400 and "MANAGED ACCESS SYSTEM HAVING FILTERED COMMUNICATIONS USING NETWORK INTERFACE DEVICE," assigned U.S. patent application Ser. No. 14/865,466, each which was filed on the same date and by the same Assignee, the disclosures which are hereby incorporated by reference.

Many modifications and other embodiments of the invention will come to the mind of one skilled in the art having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is understood that the invention is not to be limited to the specific embodiments disclosed, and that modifications and embodiments are intended to be included within the scope of the appended claims.

That which is claimed is:

**1.** A managed access system for mobile wireless devices (MWDs) in a facility, the facility being geographically within a wireless communications network, the managed access system comprising:

a plurality of antennas arranged at the facility;  
radio equipment coupled to said plurality of antennas;  
at least one MWD monitoring device for the wireless communications network; and

a management access controller cooperating with said radio equipment to communicate with a given MWD within the facility, block outside communications via the wireless communications network when the given MWD is an unauthorized MWD, and provide outside communications when the given MWD is an authorized MWD;

said management access controller cooperating with said at least one MWD monitoring device to determine whether the radio equipment and at least one MWD monitoring device both detect the given MWD and generate an indication that the given MWD is outside the facility when said at least one MWD monitoring device detects the given MWD but said radio equipment does not detect the given MWD.

**2.** The managed access system according to claim **1** wherein each of the plurality of antennas comprises a directional antenna.

**3.** The managed access system according to claim **1** wherein the plurality of antennas are arranged around a periphery of the facility.

**4.** The managed access system of claim **1** wherein the at least one MWD monitoring device is operable for both cellular and non-cellular communications.

**5.** The managed access system of claim **1** wherein the at least one MWD monitoring device comprises a plurality of external monitoring devices arranged around a periphery of the facility.



6. The managed access system of claim 5 wherein the plurality of external monitoring devices operates based on time-difference-of-arrival signals.

7. The managed access system of claim 1 wherein the at least one MWD monitoring device comprises a plurality of internal monitoring devices arranged within a periphery of the facility.

8. The managed access system of claim 7 wherein the facility comprises a building; and wherein at least some of the plurality of internal monitoring devices are located within the building.

9. The managed access system of claim 1 wherein said radio equipment comprises a plurality of picocell radios, each coupled to a respective antenna; and wherein said management access controller implements a corresponding change in said radio equipment in response to a change in the wireless communications network.

10. The managed access system of claim 9 wherein said management access controller implements the corresponding change in said radio equipment as at least one of change in a power level of at least one of said picocell radios, a change in a communications protocol of at least one of said picocell radios, and a change in a frequency range of at least one of said picocell radios.

11. The managed access system of claim 1 wherein said management access controller provides outside communications when the given MWD is an authorized MWD via another network other than the wireless communications network.

12. The managed access system of claim 1 wherein said management access controller provides outside communications when the given MWD is an authorized MWD via at least one of the Public Switched Telephone Network (PSTN), and an Internet Protocol (IP) network.

13. The managed access system of claim 1 wherein said radio equipment is operable according to at least one of an LTE, CDMA, UMTS and GSM protocol.

14. A management access controller for a managed access system for mobile wireless devices (MWDs) in a facility, the facility being geographically within a wireless communications network, the managed access system comprising a plurality of antennas arranged at the facility, radio equipment coupled to the plurality of antennas, and at least one MWD monitoring device for the wireless communications network, the management access controller comprising:

a processor and a memory coupled thereto to

cooperate with said radio equipment to communicate with a given MWD within the facility, block outside communications via the wireless communications network when the given MWD is an unauthorized MWD, and provide outside communications when the given MWD is an authorized MWD, and

cooperate with said at least one MWD monitoring device to determine whether the radio equipment and at least one MWD monitoring device both detect the given MWD and generate an indication that the given MWD is outside the facility when the at least one MWD monitoring device detects the given MWD but the radio equipment does not detect the given MWD.

15. The management access controller according to claim 14 wherein each of the plurality of antennas comprises a directional antenna.

16. The management access controller according to claim 14 wherein the plurality of antennas are arranged around a periphery of the facility.

17. The management access controller of claim 14 wherein said processor and memory cooperate with the at least one monitoring device to provide for both cellular and non-cellular communications.

18. The management access controller of claim 14 wherein the at least one MWD monitoring device comprises a plurality of external monitoring devices arranged around a periphery of the facility; and wherein said processor and memory cooperate with the external monitoring devices to determine whether the radio equipment and at least one MWD monitoring device both detect the given MWD.

19. The management access controller of claim 18 wherein said processor and memory cooperate with the plurality of external monitoring devices to operate based on time-difference-of-arrival signals.

20. The management access controller of claim 14 wherein the at least one MWD monitoring device comprises a plurality of internal monitoring devices arranged within a periphery of the facility.

21. The management access controller of claim 14 wherein the radio equipment comprises a plurality of picocell radios, each coupled to a respective antenna; and wherein said processor and memory implement a corresponding change in the radio equipment in response to a change in the wireless communications network as at least one of change in a power level of at least one of the picocell radios, a change in a communications protocol of at least one of the picocell radios, and a change in a frequency range of at least one of the picocell radios.

22. The management access controller of claim 14 wherein said processor and memory implement outside communications when the given MWD is an authorized MWD via another network other than the wireless communications network.

23. The management access controller of claim 14 wherein said processor and memory implement outside communications when the given MWD is an authorized MWD via at least one of the Public Switched Telephone Network (PSTN), and an Internet Protocol (IP) network.

24. The management access controller of claim 14 wherein the radio equipment is operable according to at least one of an LTE, CDMA, UMTS and GSM protocol.

25. A method for operating a managed access system for mobile wireless devices (MWDs) in a facility, the facility being geographically within a wireless communications network, the managed access system comprising a plurality of antennas arranged at the facility, radio equipment coupled to the plurality of antennas, and at least one MWD monitoring device for the wireless communications network, the method comprising:

operating a management access controller to

cooperate with the radio equipment to communicate with a given MWD within the facility, block outside communications via the wireless communications network when the given MWD is an unauthorized MWD, and provide outside communications when the given MWD is an authorized MWD,

cooperate with the at least one MWD monitoring device to determine whether the radio equipment and at least one MWD monitoring device both detect the given MWD, and

generate an indication that the given MWD is outside the facility when the at least one MWD monitoring device detects the given MWD but the radio equipment does not detect the given MWD.



37

26. The method of claim 25 wherein the plurality of antennas comprises a plurality of directional antennas arranged around a periphery of the facility.

27. The method of claim 25 wherein the management access controller comprises a processor and a memory 5 coupled thereto.

28. The method of claim 25 further comprising operating the management access controller to operate the at least one MWD monitoring device for both cellular and non-cellular 10 communications.

29. The method of claim 25 wherein the at least one MWD monitoring device comprises a plurality of external monitoring devices arranged around a periphery of the facility; and further comprising operating the management 15 access controller to cooperate with the plurality of external monitoring devices.

30. The method of claim 29 further comprising operating the plurality of external monitoring devices based on time-difference-of-arrival signals.

31. The method of claim 25 wherein the at least one 20 MWD monitoring device comprises a plurality of internal

38

monitoring devices arranged within a periphery of the facility; and further comprising operating the management access controller to cooperate with the plurality of internal monitoring devices to determine whether the radio equip- ment and at least one MWD device both detect the given MWD.

32. The method of claim 31 wherein the facility comprises a building; and wherein at least some of the plurality of internal monitoring devices are located within the building.

33. The method of claim 25 wherein the radio equipment comprises a plurality of picocell radios, each coupled to a respective antenna; and further comprising operating the management access controller to implement a corresponding change in the radio equipment in response to a change in the 15 wireless communications network.

34. The method of claim 25 further comprising operating the management access controller to provide outside com- munications when the given MWD is an authorized MWD via another network other than the monitoring wireless 20 communications network.

\* \* \* \* \*