



US009743937B2

(12) **United States Patent**
Blain et al.

(10) **Patent No.:** **US 9,743,937 B2**
(45) **Date of Patent:** **Aug. 29, 2017**

(54) **VERTEBRAL FACET JOINT DRILL AND METHOD OF USE**

(71) Applicant: **Spinal Elements, Inc.**, Carlsbad, CA (US)

(72) Inventors: **Jason Blain**, Encinitas, CA (US); **Eric J. Kovach**, Carlsbad, CA (US)

(73) Assignee: **Spinal Elements, Inc.**, Carlsbad, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 47 days.

(21) Appl. No.: **14/712,800**

(22) Filed: **May 14, 2015**

(65) **Prior Publication Data**

US 2015/0257773 A1 Sep. 17, 2015

Related U.S. Application Data

(60) Continuation of application No. 13/585,242, filed on Aug. 14, 2012, now Pat. No. 9,060,787, which is a division of application No. 12/035,366, filed on Feb. 21, 2008, now Pat. No. 8,652,137.

(60) Provisional application No. 60/891,159, filed on Feb. 22, 2007.

(51) **Int. Cl.**

A61B 17/16 (2006.01)
A61B 17/56 (2006.01)
A61B 17/70 (2006.01)

(52) **U.S. Cl.**

CPC **A61B 17/1671** (2013.01); **A61B 17/1608** (2013.01); **A61B 17/1615** (2013.01); **A61B 17/1642** (2013.01); **A61B 17/562** (2013.01); **A61B 17/7064** (2013.01); **A61B 2218/00** (2013.01)

(58) **Field of Classification Search**

CPC .. A61B 17/1608; A61B 17/30; A61B 17/1642

USPC 606/185

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

86,016 A 1/1869 Howell
1,630,239 A 5/1927 Binkley et al.
1,822,280 A 9/1931 Ervay
1,822,330 A 9/1931 Anslie
2,486,303 A 10/1949 Longfellow
2,706,023 A 4/1955 Merritt
3,111,945 A 11/1963 Von Solbrig

(Continued)

FOREIGN PATENT DOCUMENTS

CA 2 437 575 4/2009
DE 93 04 368 5/1993

(Continued)

OTHER PUBLICATIONS

Arthrotek, Curvtek Bone Tunneling System Users Manual; 2000.*

(Continued)


Primary Examiner — David Bates

(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson & Bear, LLP

(57) **ABSTRACT**

Devices and methods for creating holes in the articular process of the vertebra are provided. One embodiment of the invention comprises a drill head comprising a frame, punch arm with punch tip and opposing plate. Methods of using the resulting holes to anchor or stabilize facet joint prosthesis, and also altering the spacing and motion at the facet joints of the vertebral column, are provided.

18 Claims, 63 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

3,149,808 A	9/1964	Weckesser	5,425,773 A	6/1995	Boyd et al.
3,570,497 A	3/1971	Lemole	5,437,672 A	8/1995	Alleyne
3,867,728 A	2/1975	Stubstad	5,445,639 A	8/1995	Kuslich et al.
3,875,595 A	4/1975	Froning	5,458,642 A	10/1995	Beer et al.
3,879,767 A	4/1975	Stubstad	5,458,643 A	10/1995	Oka et al.
4,001,896 A	1/1977	Arkangel	5,462,542 A	10/1995	Alesi, Jr.
4,037,603 A	7/1977	Wendorff	5,487,756 A	1/1996	Kallesoe et al.
4,085,466 A	4/1978	Goodfellow et al.	5,491,882 A	2/1996	Walston et al.
4,119,091 A	10/1978	Partridge	5,496,318 A	3/1996	Howland et al.
4,156,296 A	5/1979	Johnson et al.	5,507,823 A	4/1996	Walston et al.
4,231,121 A	11/1980	Lewis	5,509,918 A *	4/1996	Romano A61B 17/1642 408/241 R
D261,935 S	11/1981	Halloran	5,514,180 A	5/1996	Heggeness et al.
4,312,337 A	1/1982	Donohue	5,527,312 A	6/1996	Ray
4,323,217 A	4/1982	Dochterman	5,527,314 A	6/1996	Brumfield et al.
4,349,921 A	9/1982	Kuntz	5,534,028 A	7/1996	Bao et al.
4,502,161 A	3/1985	Wall	5,534,030 A	7/1996	Navarro et al.
D279,502 S	7/1985	Halloran	5,540,706 A	7/1996	Aust et al.
D279,503 S	7/1985	Halloran	5,545,229 A	8/1996	Parsons et al.
4,535,764 A	8/1985	Ebert	5,549,619 A	8/1996	Peters et al.
4,573,458 A	3/1986	Lower	5,556,431 A	9/1996	Buttner-Janz
4,634,445 A	1/1987	Helal	5,562,738 A	10/1996	Boyd et al.
4,662,371 A	5/1987	Whipple et al.	5,571,105 A	11/1996	Gundolf
4,706,659 A	11/1987	Matthews et al.	5,571,131 A	11/1996	Ek et al.
4,714,469 A	12/1987	Kenna	5,571,189 A	11/1996	Kuslich
4,722,331 A	2/1988	Fox	5,571,191 A	11/1996	Fitz
4,730,615 A	3/1988	Sutherland et al.	5,577,995 A	11/1996	Walker et al.
4,759,766 A	7/1988	Buettner-Janz et al.	5,586,989 A	12/1996	Bray, Jr.
4,759,769 A	7/1988	Hedman et al.	5,591,165 A	1/1997	Jackson
4,772,287 A	9/1988	Ray et al.	5,603,713 A	2/1997	Aust et al.
4,773,402 A	9/1988	Asher et al.	5,638,700 A	6/1997	Shechter
4,834,757 A	5/1989	Brantigan	5,645,597 A	7/1997	Krapiva
4,863,477 A	9/1989	Monson	5,645,599 A	7/1997	Samani
4,904,260 A	2/1990	Ray et al.	5,649,947 A	7/1997	Auerbach et al.
4,907,577 A	3/1990	Wu	5,653,762 A	8/1997	Pisharodi
4,911,718 A	3/1990	Lee et al.	5,674,295 A	10/1997	Ray et al.
4,919,667 A	4/1990	Richmond	5,674,296 A	10/1997	Bryan et al.
4,923,471 A	5/1990	Morgan	5,676,701 A	10/1997	Yuan et al.
4,936,848 A	6/1990	Bagby	5,683,464 A	11/1997	Wagner et al.
4,941,466 A *	7/1990	Romano A61B 17/1642 408/127	5,683,466 A	11/1997	Vitale
4,959,065 A	9/1990	Arnett et al.	5,700,265 A	12/1997	Romano
4,969,909 A	11/1990	Barouk	5,702,450 A	12/1997	Bisserie
5,000,165 A	3/1991	Watanabe	5,707,373 A	1/1998	Sevrain et al.
5,002,546 A	3/1991	Romano	5,713,542 A	2/1998	Benoit
5,011,484 A	4/1991	Bréard	5,716,415 A	2/1998	Steffee
5,015,255 A	5/1991	Kuslich	5,725,582 A	3/1998	Bevan et al.
5,047,055 A	9/1991	Bao et al.	5,741,260 A	4/1998	Songer et al.
5,062,845 A	11/1991	Kuslich	5,741,261 A	4/1998	Moskovitz et al.
5,071,437 A	12/1991	Steffee	D395,138 S	6/1998	Ohata
5,092,866 A	3/1992	Breard et al.	5,766,251 A	6/1998	Koshino
5,112,013 A	5/1992	Tolbert et al.	5,766,253 A	6/1998	Brosnahan
5,112,346 A	5/1992	Hiltebrandt et al.	5,772,663 A	6/1998	Whiteside et al.
5,127,912 A	7/1992	Ray et al.	5,797,916 A	8/1998	McDowell
5,135,188 A	8/1992	Anderson et al.	5,824,093 A	10/1998	Ray et al.
5,147,404 A	9/1992	Downey	5,824,094 A	10/1998	Serhan et al.
5,171,280 A	12/1992	Baumgartner	5,836,948 A	11/1998	Zucherman et al.
5,192,326 A	3/1993	Bao et al.	5,851,208 A	12/1998	Trott
5,209,755 A *	5/1993	Abrahan A61B 17/322 606/1	5,860,977 A	1/1999	Zucherman et al.
5,258,031 A	11/1993	Salib et al.	5,865,846 A	2/1999	Bryan et al.
5,282,861 A	2/1994	Kaplan	5,868,745 A	2/1999	Alleyne
5,286,249 A	2/1994	Thibodaux	5,876,404 A	3/1999	Zucherman et al.
5,300,073 A	4/1994	Ray et al.	5,879,396 A	3/1999	Walston et al.
5,306,275 A	4/1994	Bryan	5,888,203 A	3/1999	Goldberg
5,306,308 A	4/1994	Gross et al.	5,893,889 A	4/1999	Harrington
5,306,309 A	4/1994	Wagner et al.	5,895,428 A	4/1999	Berry
5,330,479 A	7/1994	Whitmore	RE36,221 E	6/1999	Breard et al.
5,360,431 A	11/1994	Puno et al.	5,918,604 A	7/1999	Whelan
5,368,596 A	11/1994	Burkhart	5,951,555 A	9/1999	Rehak et al.
5,370,697 A	12/1994	Baumgartner	5,964,765 A	10/1999	Fenton et al.
5,372,598 A	12/1994	Luhr et al.	5,993,452 A	11/1999	Vandewalle
5,400,784 A	3/1995	Durand et al.	5,997,542 A	12/1999	Burke
5,401,269 A	3/1995	Buttner-Janz et al.	6,001,130 A	12/1999	Bryan et al.
5,413,576 A	5/1995	Rivard	6,014,588 A	1/2000	Fitz
5,415,661 A	5/1995	Holmes	6,019,763 A	2/2000	Nakamura et al.
			6,019,792 A	2/2000	Cauthen
			6,039,763 A	3/2000	Shelokov
			6,048,342 A	4/2000	Zucherman et al.
			6,050,998 A	4/2000	Fletcher
			6,063,121 A	5/2000	Xavier et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,066,325	A	5/2000	Wallace et al.	7,585,300	B2	9/2009	Cha
6,068,630	A	5/2000	Zucherman et al.	7,608,104	B2	10/2009	Yuan et al.
RE36,758	E	6/2000	Fitz	7,695,472	B2	4/2010	Young
6,080,157	A	6/2000	Cathro et al.	7,799,077	B2	9/2010	Lang et al.
6,099,531	A	8/2000	Bonutti	7,806,895	B2	10/2010	Weier et al.
6,102,347	A	8/2000	Benoit	7,846,183	B2	12/2010	Blain
6,106,558	A	8/2000	Picha	7,862,590	B2	1/2011	Lim et al.
6,113,637	A	9/2000	Gill et al.	7,935,136	B2	5/2011	Alamin et al.
6,132,464	A	10/2000	Martin	D643,121	S	8/2011	Milford et al.
6,132,465	A	10/2000	Ray et al.	7,993,370	B2	8/2011	Jahng
6,146,422	A	11/2000	Lawson	7,998,172	B2	8/2011	Blain
6,156,067	A	12/2000	Bryan et al.	8,052,728	B2	11/2011	Hestad
6,179,839	B1	1/2001	Weiss et al.	8,109,971	B2	2/2012	Hale
D439,340	S	3/2001	Michelson	8,133,225	B2	3/2012	Pieske
6,200,322	B1	3/2001	Branch et al.	8,163,016	B2	4/2012	Linares
6,293,949	B1	9/2001	Justis et al.	8,192,468	B2	6/2012	Biedermann et al.
D450,122	S	11/2001	Michelson	8,216,275	B2	7/2012	Fielding et al.
6,325,803	B1	12/2001	Schumacher et al.	8,246,655	B2	8/2012	Jackson et al.
D454,953	S	3/2002	Michelson	8,292,954	B2	10/2012	Robinson et al.
6,368,325	B1	4/2002	McKinley et al.	8,306,307	B2	11/2012	Koike et al.
6,368,350	B1	4/2002	Erickson et al.	8,394,125	B2	3/2013	Assell et al.
6,371,958	B1	4/2002	Overaker	8,460,346	B2	6/2013	Ralph et al.
6,375,573	B2	4/2002	Romano	8,486,078	B2	7/2013	Carl et al.
6,379,386	B1	4/2002	Resch et al.	8,496,691	B2	7/2013	Blain
D460,188	S	7/2002	Michelson	8,579,903	B2	11/2013	Carl
D460,189	S	7/2002	Michelson	8,652,137	B2	2/2014	Blain et al.
6,419,678	B1	7/2002	Asfora	8,740,942	B2	6/2014	Blain
6,419,703	B1	7/2002	Fallin et al.	8,740,949	B2	6/2014	Blain
6,436,099	B1	8/2002	Drewry et al.	8,784,423	B2	7/2014	Kowarsch et al.
6,436,101	B1	8/2002	Hamada et al.	8,858,597	B2	10/2014	Blain
6,436,146	B1	8/2002	Hassler et al.	8,882,804	B2	11/2014	Blain
D463,560	S	9/2002	Michelson	8,961,613	B2	2/2015	Assell et al.
6,470,207	B1	10/2002	Simon et al.	D724,733	S	3/2015	Blain et al.
6,565,605	B2	5/2003	Goble et al.	8,974,456	B2	3/2015	Allen et al.
6,572,617	B1	6/2003	Senegas	8,979,529	B2	3/2015	Marcus
6,579,318	B2	6/2003	Varga et al.	8,992,533	B2	3/2015	Blain et al.
6,579,319	B2	6/2003	Goble et al.	8,998,953	B2	4/2015	Blain
6,589,244	B1	7/2003	Sevrain et al.	9,017,389	B2	4/2015	Assell et al.
6,600,956	B2	7/2003	Maschino et al.	9,060,787	B2	6/2015	Blain et al.
6,607,530	B1	8/2003	Carl et al.	D739,935	S	9/2015	Blain et al.
6,610,091	B1	8/2003	Reiley	9,149,283	B2	10/2015	Assell et al.
D479,331	S	9/2003	Pike et al.	9,161,763	B2	10/2015	Assell et al.
6,626,944	B1	9/2003	Taylor	9,179,943	B2	11/2015	Blain
6,641,614	B1	11/2003	Wagner et al.	9,220,547	B2	12/2015	Blain et al.
6,656,195	B2	12/2003	Peters et al.	D748,262	S	1/2016	Blain
6,669,697	B1	12/2003	Pisharodi	9,233,006	B2	1/2016	Assell et al.
6,669,729	B2	12/2003	Chin	D748,793	S	2/2016	Blain
6,706,068	B2	3/2004	Ferree	9,265,546	B2	2/2016	Blain
6,743,232	B2	6/2004	Overaker et al.	9,271,765	B2	3/2016	Blain
6,761,720	B1	7/2004	Senegas	9,301,786	B2	4/2016	Blain
6,764,491	B2	7/2004	Frey et al.	9,314,277	B2	4/2016	Assell et al.
6,770,095	B2	8/2004	Grinberg et al.	9,345,488	B2	5/2016	Assell et al.
6,783,527	B2	8/2004	Drewry et al.	9,421,044	B2	8/2016	Blain et al.
6,790,210	B1	9/2004	Cragg et al.	D765,853	S	9/2016	Blain et al.
6,802,863	B2	10/2004	Lawson et al.	D765,854	S	9/2016	Blain et al.
6,811,567	B2	11/2004	Reiley	9,456,855	B2	10/2016	Blain et al.
6,902,566	B2	6/2005	Zucherman et al.	9,517,077	B2	12/2016	Blain et al.
6,908,484	B2	6/2005	Zubok et al.	2001/0018614	A1	8/2001	Bianchi
6,966,930	B2	11/2005	Arnin et al.	2002/0018799	A1	2/2002	Spector et al.
6,974,478	B2	12/2005	Reiley et al.	2002/0019637	A1	2/2002	Frey et al.
6,974,479	B2	12/2005	Trieu	2002/0029039	A1	3/2002	Zucherman et al.
D517,404	S	3/2006	Schluter	2002/0040227	A1	4/2002	Harari
7,008,429	B2	3/2006	Golobek	2002/0065557	A1	5/2002	Goble et al.
7,013,675	B2	3/2006	Marquez-Pickering	2002/0072800	A1	6/2002	Goble et al.
7,051,451	B2	5/2006	Augustino et al.	2002/0077700	A1	6/2002	Varga et al.
7,074,238	B2	7/2006	Stinson et al.	2002/0086047	A1	7/2002	Mueller et al.
7,101,375	B2	9/2006	Zucherman et al.	2002/0120335	A1	8/2002	Angelucci et al.
7,223,269	B2	5/2007	Chappuis	2002/0123806	A1	9/2002	Reiley
D565,180	S	3/2008	Liao	2002/0151895	A1	10/2002	Soboleski et al.
7,371,238	B2	5/2008	Soboleski et al.	2002/0173800	A1	11/2002	Dreyfuss et al.
7,458,981	B2	12/2008	Fielding et al.	2002/0173813	A1	11/2002	Peterson et al.
7,517,358	B2	4/2009	Petersen	2002/0198527	A1	12/2002	Muckter
7,537,611	B2	5/2009	Lee	2003/0004572	A1	1/2003	Goble et al.
7,559,940	B2	7/2009	McGuire et al.	2003/0028250	A1	2/2003	Reiley et al.
7,563,286	B2	7/2009	Gerber et al.	2003/0040797	A1	2/2003	Fallin et al.
				2003/0120343	A1	6/2003	Whelan
				2003/0176919	A1	9/2003	Schmieding
				2003/0176922	A1	9/2003	Lawson et al.
				2003/0187454	A1	10/2003	Gill et al.

(56)

References Cited

FOREIGN PATENT DOCUMENTS

GB	2 366 736	3/2002
JP	62-270147	11/1987
JP	10-179622	7/1998
JP	2000-210297	8/2000
JP	2004-508888	3/2004
JP	2004-181236	7/2004
JP	2007-503884	3/2007
JP	2007-517627	7/2007
JP	2007-190389	8/2007
JP	2007-521881	8/2007
JP	2008-510526	4/2008
JP	2009-533167	9/2009
JP	2013-534451	9/2013
MX	6012309	1/2007
WO	WO 93/14721	8/1993
WO	WO 94/04088	3/1994
WO	WO 97/47246	12/1997
WO	WO 98/48717	11/1998
WO	WO 99/23963	5/1999
WO	WO 00/38582	7/2000
WO	WO 00/53126	9/2000
WO	WO 01/30248	5/2001
WO	WO 02/45765	6/2002
WO	WO 02/065954	8/2002
WO	WO 02/096300	12/2002
WO	WO 03/101350	12/2003
WO	WO 2004/071358	8/2004
WO	WO 2005/020850	3/2005
WO	WO 2005/072661	8/2005
WO	WO 2006/023980	3/2006
WO	WO 2006/096803	9/2006
WO	WO 2010/060072	5/2010
WO	WO 2010/122472	10/2010
WO	WO 2011/011621	1/2011
WO	WO 2012/007941	1/2012
WO	WO 2012/116266	8/2012
WO	WO 2012/116267	8/2012
WO	WO 2013/022880	2/2013
WO	WO 2013/138655	9/2013
WO	WO 2014/078541	5/2014
WO	WO 2016/044432	3/2016

OTHER PUBLICATIONS

3rd Party Lab Notebook, "Facet Cartilage Repair," dated May 20, 2003 in 2 pages.

ArthroTek, "CurvTek® Bone Tunneling System," Surgical Technique, 2000, pp. 6.

E-mail from 3rd Party citing U.S. Appl. Nos. 60/721,909; 60/750,005 and 60/749,000, initial e-mail dated May 11, 2009, reply e-mail dated May 18, 2009.

King et al., "Mechanism of Spinal Injury Due to Caudocephalad Acceleration," Symposium on the Lumbar Spine, Orthopedic Clinic of North America, Jan. 1975, vol. 6, pp. 19-31.

PARTEQ Innovations, "Facet Joint Implants & Resurfacing Devices," Technology Opportunity Bulletin, Tech ID 1999-012, Queen's University, Ontario Canada.

Official Communication in Australian Application No. 2005213459, dated Dec. 11, 2009.

Official Communication in Australian Application No. 2005213459, dated Dec. 15, 2010.

Official Communication in Australian Application No. 2011226832, dated Sep. 4, 2012.

Official Communication in Australian Application No. 2011226832, dated Oct. 31, 2012.

Official Communication in Australian Application No. AU2013237744, dated Sep. 2, 2014.

Notice of Acceptance in Australian Application No. AU2013237744, dated Apr. 23, 2015.

Official Communication in Canadian Application No. 2,555,355, dated Sep. 2, 2011.

Official Communication in Canadian Application No. 2,803,783, dated Sep. 29, 2014.

Official Communication in European Application No. 05712981.9, dated Jul. 24, 2007.

Official Communication in European Application No. 05712981.9, dated Mar. 10, 2008.

Official Communication in European Application No. 05712981.9, dated Apr. 6, 2009.

Official Communication in European Application No. 05712981.9, dated Jun. 15, 2010.

Official Communication in European Application No. 10178979.0, dated Mar. 14, 2011.

Official Communication in European Application No. 10178979.0, dated Nov. 13, 2012.

Official Communication in European Application No. 10178979.0, dated Aug. 5, 2013.

Official Communication in European Application No. 14175088.5, dated Sep. 8, 2014.

Official Communication in Japanese Application No. 2006-552309, dated May 25, 2010.

Official Communication in Japanese Application No. 2006-552309, dated Feb. 15, 2011.

Official Communication in Japanese Application No. 2010-221380, dated Feb. 15, 2011.

Official Communication in Japanese Application No. 2012-272106, dated Dec. 3, 2013.

Official Communication in Japanese Application No. 2012-272106, dated May 26, 2014.

Official Communication in Japanese Application No. 2012-272106, dated Feb. 23, 2015.

International Search Report and Written Opinion in International Application No. PCT/US2005/003753, dated Dec. 5, 2006.

International Preliminary Report and Written Opinion in International App No. PCT/US2005/003753, dated Jan. 9, 2007.

Official Communication in European Application No. 14177951.2, dated Nov. 13, 2014.

International Search Report and Written Opinion in International Application No. PCT/US2008/054607, dated Jul. 10, 2008.

Official Communication in Australian Application No. 2011292297, dated Jul. 10, 2013.

Official Communication in European Application No. 11818586.7, dated Nov. 6, 2014.

Official Communication in Japanese Application No. 2013-524882, dated Mar. 2, 2015.

International Search Report and Written Opinion in International Application No. PCT/US2011/047432, dated Dec. 12, 2011.

International Preliminary Report on Patentability in International Application No. PCT/US2011/047432, dated Feb. 28, 2013.

International Search Report in International Application No. PCT/US2012/026470, dated May 30, 2012.

International Preliminary Report on Patentability and Written Opinion in International Application No. PCT/US2012/026470, dated Sep. 6, 2013.

International Search Report and Written Opinion in International Application No. PCT/US2012/026472, dated Jun. 20, 2012.

International Preliminary Report on Patentability and Written Opinion in International Application No. PCT/US2012/026472, dated Mar. 12, 2014.

International Search Report and Written Opinion in International Application No. PCT/US2014/019302, dated May 18, 2015.

International Search Report and Written Opinion in International Application No. PCT/US2014/019325, dated Jun. 17, 2014.

International Search Report and Written Opinion in International Application No. PCT/US2014/056598, dated Dec. 29, 2014.

Official Communication in Japanese Application No. 2009-074336, dated Feb. 15, 2011.

International Search Report in International Application No. PCT/CA2002/000193 filed Feb. 15, 2002, dated Jun. 18, 2002.

International Search Report and Written Opinion in International Application No. PCT/US2004/028094, dated May 16, 2005.

International Preliminary Report on Patentability in International Application No. PCT/US2004/028094, dated Feb. 25, 2013.

(56)

References Cited

OTHER PUBLICATIONS

International Search Report in International Application No. PCT/US2005/000987 filed Jan. 13, 2005, dated May 24, 2005.

International Preliminary Report on Patentability in International Application No. PCT/US2005/000987 filed Jan. 13, 2005, dated Jan. 17, 2006.

Ash, H.E., "Proximal Interphalangeal Joint Dimensions for the Design of a Surface Replacement Prosthesis", School of Engineering, University of Durham, Proceedings of the Institution of Mechanical Engineers Part H Journal of Engineering in Medicine Feb. 1996, vol. 210, No. 2, pp. 95-108.

Beaman, MD et al., "Substance P Innervation of Lumbar Spine Facet Joints", SPINE, 1993, vol. 18, No. 8, pp. 1044-1049.

Butterman, et al., "An Experimental Method for Measuring Force on the Spinal Facet Joint: Description and Application of the Method", Journal of Biomechanical Engineering, Nov. 1991, vol. 113, pp. 375-386.

Cruess et al., "The Response of Articular Cartilage to Weight-Bearing Against Metal", The Journal of Bone and Joint Surgery, Aug. 1984, vol. 66-B, No. 4, pp. 592-597.

Dalldorf et al., "Rate of Degeneration of Human Acetabular Cartilage after Hemiarthroplasty", The Journal of Bone and Joint Surgery, Jun. 1995, vol. 77, No. 6, pp. 877-882.

Frost, Harold M., "From Wolff's Law to the Utah Paradigm: Insights About Bone Physiology and Its Clinical Applications", The Anatomical Record, 2001, vol. 262, pp. 398-419.

Kurtz, PhD et al., "Isoelastic Polyaryletheretherketone Implants for Total Joint Replacement", PEEK Biomaterials Handbook, Ch. 14, 2012, pp. 221-226.

Meisel et al., "Minimally Invasive Facet Restoration Implant for Chronic Lumbar Zygapophysial Pain: 1-Year Outcomes", Annals of Surgical Innovation and Research (ASIR), 2014, vol. 8, No. 7, pp. 6.

Panjabi, PhD et al., "Articular Facets of the Human Spine: Quantitative Three-Dimensional Anatomy", Spine, 1993, vol. 18, No. 10, pp. 1298-1310.

Ravikumar et al., "Internal Fixation Versus Hemiarthroplasty Versus Total Hip Arthroplasty for Displaced Subcapital Fractures of Femur—13 year Results of a Prospective Randomised Study", International Journal of the Care of the Injured (INJURY), 2000, vol. 31, pp. 793-797.

Schendel et al., "Experimental Measurement of Ligament Force, Facet Force, and Segment Motion in the Human Lumbar Spine", Journal of Biomechanics, 1993, vol. 26, No. 4/5, pp. 427-438.

Tanno et al., "Which Portion in a Facet is Specifically Affected by Articular Cartilage Degeneration with Aging in the Human Lumbar Zygapophysial Joint?", Okajimas Folia Anatomica Japonica, May 2003, vol. 80, No. 1, pp. 29-34.

Official Communication in Australian Application No. AU2015205875, dated Apr. 2, 2016.

Official Communication in Australian Application No. AU2015205875, dated Jun. 15, 2016.

Official Communication in Canadian Application No. 2,803,783, dated Aug. 5, 2015.

Official Communication in Canadian Application No. 2,803,783, dated Jul. 7, 2016.

Official Communication in European Application No. 14175088.5, dated Nov. 18, 2015.

Official Communication in Japanese Application No. 2012-272106, dated Nov. 2, 2015.

Official Communication in Australian Application No. 2014277721, dated Sep. 8, 2016.

Official Communication in Japanese Application No. 2013-524882, dated Nov. 16, 2015.

Official Communication in Japanese Application No. 2015-242990, dated Dec. 12, 2016.

Official Communication in Australian Application No. AU2012222229, dated Aug. 21, 2015.

Official Communication in Australian Application No. AU2012222229, dated May 11, 2016.

Official Communication in Australian Application No. AU2012222230, dated Aug. 21, 2015.

Official Communication in Japanese Application No. JP 2013-555591, dated Jan. 4, 2016.

Official Communication in Japanese Application No. JP 2013-555592, dated Dec. 7, 2015.

Official Communication in Japanese Application No. JP 2013-555592, dated Aug. 8, 2016.

Official Communication in European Application No. 14774714.1, dated Oct. 21, 2016.

Official Communication in European Application No. 14776445.0, dated Nov. 7, 2016.

International Preliminary Report on Patentability and Written Opinion in International Application No. PCT/US2014/019325, dated Sep. 24, 2015.

Official Communication in European Application No. 14850082.0, dated Aug. 31, 2016.

International Preliminary Report on Patentability and Written Opinion in International Application No. PCT/US2014/056598, dated Apr. 7, 2016.

International Search Report and Written Opinion in International Application No. PCT/US2015/050441, dated Dec. 28, 2015.

International Search Report and Written Opinion in International Application No. PCT/US2016/013062, dated Mar. 16, 2016.

* cited by examiner




FIG. 1

FIG. 2A







FIG. 2B








FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B







FIG. 8






FIG. 12A




FIG. 12B




FIG. 13




FIG. 14A




FIG. 14B




FIG. 15A




FIG. 15B




FIG. 16A

FIG. 16B







FIG. 17






FIG. 20




FIG. 21A




FIG. 21B




FIG. 22A




FIG. 22B




FIG. 23A




FIG. 23B

88




FIG. 24A

88




FIG. 24B




FIG. 25A




FIG. 25B




FIG. 26




FIG. 27A




FIG. 27B




FIG. 28




FIG. 29

FIG. 30A




FIG. 30B




FIG. 31




FIG. 32





FIG. 33






FIG. 34A




FIG. 34B




FIG. 35A







FIG. 35B






FIG. 37A






FIG. 37B






FIG. 40A




FIG. 40B




FIG. 41A






FIG. 41B






FIG. 44




FIG. 45






FIG. 46A




FIG. 46B




FIG. 47A




FIG. 47B




FIG. 48




FIG. 49




FIG. 50




FIG. 51C




FIG. 51B




FIG. 51A

FIG. 51E





FIG. 51D









FIG. 52B










FIG. 52E





FIG. 52F







FIG. 53C






FIG. 53D




FIG. 53E




FIG. 53F





FIG. 54

FIG. 55






FIG. 56A




FIG. 56B




FIG. 56C




FIG. 57A




FIG. 57B




FIG. 57C




FIG. 57D




FIG. 57E




FIG. 58A




FIG. 58B






FIG. 58C








FIG. 58F





FIG. 58G






FIG. 59B




FIG. 59C




FIG. 59D




FIG. 60

VERTEBRAL FACET JOINT DRILL AND METHOD OF USE

CROSS-REFERENCE TO RELATED APPLICATIONS

This present application is a continuation of U.S. application Ser. No. 13/585,242, filed Aug. 14, 2012, which is a divisional of U.S. application Ser. No. 12/035,366, filed Feb. 21, 2008, which claims priority under 35 U.S.C. §119(e) to U.S. Provisional Patent Application No. 60/891,159, filed Feb. 22, 2007, the disclosure of each of these applications is incorporated by reference herein in their entirety.

FIELD OF THE INVENTION

The present invention relates to devices for creating holes in the articular processes of the vertebra and the surgical method of using the devices for creation of holes and the use of the holes with facet joint prosthesis retainers.

BACKGROUND OF THE INVENTION

Traumatic, inflammatory, and degenerative disorders of the spine can lead to severe pain and loss of mobility. According to some studies, back and spinal musculoskeletal impairments are the leading causes of lost work productivity in the United States. Pain as a result of some type of spinal impairment may have its source in a variety of pathologies or clinical conditions.

One source for back and spine pain is related to degeneration of the facets of the spine or facet arthritis. Bony contact or grinding of degenerated facet joint surfaces may play a role in some pain syndromes. While many technological advances have focused on the spinal disc and artificial replacement or repair of the disc, little advancement in facet repair has been made. Facet joint and disc degeneration frequently occur together. Thus, there is a need to address the clinical concerns raised by degenerative facet joints.

The current standard of care to address the degenerative problems with the facet joints is to fuse the two adjacent vertebrae together. By performing this surgical procedure, the relative motion between the two adjacent vertebrae is stopped, thus stopping motion of the facets and any potential pain generated as a result thereof. This surgical procedure has a high rate of morbidity and can potentially lead to further clinical complications such as adjacent segment disorders. This procedure is also not reversible. Therefore, if the patient has an unsatisfactory result, they may be subject to additional surgical fusion procedures.

SUMMARY OF THE INVENTION

The present invention aims at addressing the clinical condition of the patient while allowing the patient to maintain mobility not common with fusion procedures. The device and procedure allow the restoration of the relative spacing between the facets within the facet joint, alleviating the bone on bone contact that is common in degenerative facet joints and often the source of pain generation, while allowing relative motion between the facets to continue post-operatively.

While other implants have been proposed with the objective of addressing facet degeneration by restoring motion, the subject device offers the benefit of requiring little to no bony resection in order for it to be placed within the spine. This advantage provides the opportunity for the patient to

rely more on those anatomical structures unaffected by degeneration while providing for very little morbidity in the surgical procedure.

Devices and methods for creating holes in the articular process of the vertebra are provided. One embodiment of the invention comprises a punch head comprising a frame, punch arm with punch tip and opposing plate. Methods of using the resulting holes to anchor or stabilize facet joint prosthesis, and also altering the spacing and motion at the facet joints of the vertebral column, are provided.

In one embodiment, a device for forming a lumen in an articular process of a vertebral column is provided, comprising a shaft member comprising a proximal section and a distal section, at least one movable lumen-forming member rotatably connected to the shaft member about the distal section of the shaft member and comprising a curved arm having a diameter less than 5 mm and a lumen-forming tip configured to pierce through a vertebral articular process; and a movable handle located about the proximal section of the shaft member connected to the at least one movable lumen forming member; wherein the at least one movable lumen-forming member has an open configuration and a closed configuration. The device may further comprise two opposing movable lumen-forming members, or an opposing support plate. The opposing support plate may have a fixed configuration, or a movable configuration relative to the shaft member.

In another embodiment, a method for forming a lumen in the articular process of the vertebra is provided, comprising accessing an articular process of a spine; contacting a curved piercing member against a first articular process; rotating the curved piercing member about an axis of rotation through the articular process to form a through lumen; and inserting an anchoring member of a facet joint implant through the anchoring lumen. Rotating the curved piercing member may comprise rotating the curved piercing member in a movement plane that is transverse to the axis of rotation. The axis of rotation may be oriented along the longitudinal length of the curved piercing member.

In another embodiment, a method for forming a lumen in the articular process of the vertebra is provided, comprising piercing a first articular surface of a spine with a first piercing member of a lumen-forming device; piercing a second articular surface of the spine with a second piercing member of the lumen-forming device; and contacting the first piercing member and the second piercing member to form a lumen between the first articular surface and the second articular surface. The lumen may be non-linear or curved. The lumen may be curved toward a base of the first articular surface.

Another embodiment of the invention is a method of creating a hole in the articular process of the vertebra comprising accessing the articular process, placing a lumen-forming tip against one side of an articular process, placing a plate against the opposite side of the adjacent articular process, and forcing said drill tip toward the plate in a non-spinning fashion.

One embodiment of the invention comprises a device for treating spinal disorders while preserving movement at a facet joint. The device comprises a prosthesis having a first face and a second face, where the first face is adapted to be secured to the adjacent articular surface of a facet and the second surface is configured for sliding contact with an adjacent structure. In one embodiment, the device is dimensioned to substantially fit within a joint capsule of the facet joint and has a thickness generally equal to the normal anatomic spacing between the two facets of the facet joint.

3

In some embodiments, the device has a curve adapted to match the natural shape of a facet and a size adapted to fit substantially within a joint capsule of the facet joint. The device may comprise at least one material selected from the group consisting of polymers, polyetheretherketone (PEEK), polyetherketoneketone (PEKK), polyethylene, fluoropolymers, hydrogels, elastomers, ceramics, zirconia, alumina, silicon nitride; metal(s), titanium, titanium alloy, cobalt chromium, stainless steel, and combinations of these materials. In one embodiment, the second face of the device comprises a highly polished surface. In one embodiment, the first face may comprise a roughened surface or a porous surface. In some embodiments, at least one face of the device is sufficiently malleable to be capable of generally conforming to the shape of an adjacent surface or structure under normal anatomical loads.

In one embodiment of the invention, a device for treating spinal disorders while preserving movement at a facet joint is provided. The device may comprise a prosthesis having a first face and a second face, where the first face is adapted for sliding contact with a first articular process of a facet joint and the second surface is configured for sliding contact with a second articular process of the facet joint. In one embodiment, the device is dimensioned to substantially fit within a joint capsule of the facet joint and has a thickness generally equal to the normal anatomic spacing between the two facets of a facet joint. In one embodiment, the device has a curve adapted to match the natural shape of a facet and a size adapted to fit substantially within a joint capsule of the facet joint. The device has a thickness approximately equal to the normal anatomic spacing between the two facets of the facet joint. In one embodiment, the device has an average thickness within the range of about 0.5 mm to about 3 mm. In one embodiment, the device has an average thickness within the range of about 1 mm to about 2 mm. In another embodiment, the device has a diameter within the range of about 5 mm to about 25 mm. In another embodiment, the device has a size within the range of about 10 mm to about 20 mm in diameter. In one embodiment, at least one face of the device has a bone contacting surface area of about 25 mm² to about 700 mm². In another embodiment, at least one face of the device has a bone contacting surface area of about 20 mm² to about 400 mm². In still another embodiment of the device, at least one face of the device has a bone contacting surface area of about 20 mm² to about 100 mm². In one embodiment, the device has at least one face comprising a highly polished surface. In some embodiments, at least one face of the device is sufficiently malleable to be capable of generally conforming to the shape of at least a portion of an articular process under normal anatomical conditions.

The prosthesis may further comprise an anchoring assembly configured to generally maintain at least a portion of the prosthesis between the first articular process and the second articular process of the facet joint. The anchoring assembly may comprise an elongate member and at least one retaining member. In one embodiment, the elongate member comprises a wire or cable. In another embodiment, the elongate member comprises a solid wire or cable. In still another embodiment, the elongate member comprises a braided cable. The retaining member may comprise a set screw retaining ring. In one embodiment, at least one end of the device comprises a threaded interface. In one embodiment, the retaining member comprises a threaded retainer. In some embodiments, the retaining member is integrally formed with one end of the elongate member.

4

In another embodiment of the invention, the device for treating facet joint dysfunction is provided. The device comprises a body with a first face and a second face adapted to contact the bony or cartilaginous articular surfaces of the facets of adjacent vertebrae. The device has at least one retaining interface capable of accepting an elongate retainer through it. An elongate retainer is adapted for generally maintaining the location of the body with respect to the facet joint. The retainer has a first portion adapted to engage a first facet of the facet joint and a second portion adapted to engage a second facet of the facet joint. In some embodiments of the invention, the device has a generally circular cross-section and a diameter adapted to fit substantially within a joint capsule of the facet joint. The device has a thickness generally equal to the normal anatomic spacing between the two facets of the facet joint. In still other embodiments of the device, the device has a curve adapted to match the natural shape of the facet and a size adapted to substantially fit within a joint capsule of the facet. The device may comprise at least one material selected from the group consisting of polymers, polyetheretherketone, polyetherketoneketone, polyethylene, fluoropolymers, hydrogels, elastomers, ceramics, zirconia, alumina, silicon nitride; metal(s), titanium, titanium alloy, cobalt chromium, stainless steel, and combinations of these materials. The elongate retainer may comprise a braided polymer, a braided metal, or a solid structure. In some embodiments of the invention, the elongate retainer comprises a flexibility sufficient to tie a knot in the elongate retainer. In another embodiment, at least one end of the elongate retainer has a threaded metal section adapted to accept a threaded knot. A threaded knot is provided to retain the elongate retainer against an articular process. In one embodiment of the invention, the threaded section is pressed or crimped onto the elongate retainer. The threaded section and knot may comprise titanium, titanium alloy, cobalt chromium or stainless steel. In some embodiments of the invention, the device comprises at least one face of the highly polished surface. In some embodiments, the elongate member may comprise at least one element with an enlarged cross-sectional area. The elongate member may comprise at least one end of with a bulbous retainer, a flared retainer, a T-bar retainer or an integral ring retainer. In some embodiments, at least one face of the device is sufficiently malleable to be capable of generally conforming to the shape of at least a portion of an articular surface.

In one embodiment of the invention, a prosthesis for treating facet joint dysfunction is provided. The prosthesis comprises a body with a first face and a second face, where at least one face adapted for sliding contact with the bony or cartilaginous articular surfaces of the facets of adjacent vertebrae or the prosthesis has at least one retaining interface capable of accepting a retainer member. The retaining member is adapted for securing the location of the body with respect to at least of the articular surfaces. The retaining member may comprise a first portion adapted to engage the retaining interface of the body and a second portion adapted to engage a first facet of the facet joint. The retainer may further comprise a third portion adapted to engage a second facet of the facet joint. In one embodiment, the retainer comprises a threaded shaft and a retaining interface of the body comprises a threaded hole with an opening on one face of the body. The retaining member may also comprise a projection extending from the body. In still another embodiment, the retaining member comprises a longitudinal member adapted to engage the retaining interface of the body and at least one retainer being capable of engaging the longitu-

dinal member. The retaining ring may comprise a set screw retaining ring. The set screw of the retaining member may have a blunted tip, curved tip, or piercing tip. Alternatively, at least one of the retaining rings may be a friction fit retaining ring. The body of the prosthesis may be curved. The prosthesis may comprise at least one material selected from the group consisting of polymers, polyetheretherketone, polyetherketoneketone, polyethylene, fluoropolymers, hydrogels, elastomers, ceramics, zirconia, alumina, silicon nitride; metal(s), titanium, titanium alloy, cobalt chromium, stainless steel, and combinations of these materials. In some embodiments, at least one face of the prosthesis is sufficiently malleable to be capable of generally conforming to the shape of at least a portion of an articular surface.

In one embodiment, a prosthesis for treating facet joint dysfunction is provided. The prosthesis comprises a first body with a first face and a second face and a second body within a first face and a second face. The first face of each body is adapted to articulate with the first face of the other body and the second face of each body is adapted to engage a facet of a facet joint. The prosthesis may further comprise a retaining member adapted for securing a location of at least one body. In some embodiments, at least one face of the prosthesis is sufficiently malleable to be capable of generally conforming to the shape of at least a portion of an articular surface.

In another embodiment of the invention, a method for treating vertebral dysfunction is provided. This method comprises opening a facet joint capsule between two facets of adjacent vertebral bodies, distracting the adjacent vertebral bodies from a first spacing to a second spacing and placing the spacer between the two facets to maintain the second spacing. The method may further comprise the steps of securing the spacer to one facet of the facet joint. The method may also comprise securing the spacer in the facet joint capsule. The step of securing the spacer may comprise introducing a hole through each facet, threading a retainer through the hole of the first facet, threading the retainer through the hole in the spacer, threading the retainer through the hole of the second facet, and tying a knot in at least one end of the retainer. The method may further comprise the steps of introducing a hole through a first facet and a second facet, advancing the retainer through the hole of the first facet, advancing the retainer through the hole in the spacer, threading the retainer through the hole of the second facet and threadably engaging an anchor to at least one end of the retainer. The step of securing the spacer may further comprise providing a spacer with a retaining member and advancing the retaining member at least partially into a facet to engage the facet. The method may also further comprise the step of conforming the shape of at least a portion of the spacer to at least a portion of a facet of the facet joint. In a further embodiment, the conforming step is performed after the placing step. In another embodiment, the conforming step is performed while the spacer is generally located between the facets of the facet joint.

In another embodiment of the invention, a method of treating the facet joint is provided. The method comprises providing a prosthesis dimension to fit within a facet joint capsule, accessing a facet joint capsule between two articular prosthesis of two vertebrae, inserting a prosthesis generally within the joint capsule and maintaining the prosthesis generally between the two articular prosthesis without penetrating the surface of a vertebrae. Maintaining the prosthesis may comprise anchoring the prosthesis to the joint capsule tissue, or generally closing the joint capsule over the prosthesis. The prosthesis can also be maintained between

the articular prosthesis by suturing the prosthesis to the surrounding soft tissue. The method may also further comprise the step of conforming the shape of at least a portion of the prosthesis to at least a portion of a facet of the facet joint. In a further embodiment, the conforming step is performed after the inserting step. In another embodiment, the conforming step is performed while the prosthesis is generally located between the facets of the facet joint.

BRIEF DESCRIPTION OF THE DRAWINGS

The structure and operation of the invention will be better understood with the following detailed description of embodiments of the invention, along with the accompanying illustrations, in which:

FIG. 1 is a lateral elevational view of a portion of the vertebral column;

FIGS. 2A and 2B are schematic superior and side views of an isolated thoracic vertebra;

FIGS. 3A and 3B are schematic posterior and posterior-oblique elevational views of a portion of the vertebral column;

FIGS. 4A and 4B are schematic side and superior views of a facet joint in the cervical vertebrae;

FIGS. 5A and 5B are schematic side and superior views of a facet joint in the thoracic vertebrae;

FIGS. 6A and 6B are schematic side and superior views of a facet joint in the lumbar vertebrae;

FIGS. 7A and 7B are schematic views of one embodiment of a facet joint prosthesis comprising a circular disc;

FIG. 8 is a schematic view of the prosthesis from FIG. 7A implanted in a facet joint;

FIGS. 9A and 9B are schematic views of one embodiment of a facet joint prosthesis comprising an octagonal disc;

FIGS. 10A and 10B are schematic views of one embodiment of a facet joint prosthesis comprising a biconcave disc;

FIGS. 11A and 11B are schematic views of one embodiment of a facet joint prosthesis comprising a single-face variable thickness disc;

FIGS. 12A and 12B are schematic views of one embodiment of a facet joint prosthesis comprising a curved disc;

FIG. 13 is a schematic view of the prosthesis from FIG. 12A implanted in a facet joint;

FIGS. 14A and 14B are schematic views of one embodiment of a facet joint prosthesis comprising a disc with a roughened surface on one face;

FIGS. 15A and 15B are schematic views of one embodiment of a facet joint prosthesis comprising a disc with a porous surface on one face;

FIGS. 16A and 16B are schematic views of one embodiment of a facet joint prosthesis comprising a bent disc with a roughened surface on the greater face;

FIG. 17 is a schematic view of the prosthesis from FIG. 16A implanted in a facet joint;

FIGS. 18A and 18B are schematic views of one embodiment of a facet joint prosthesis comprising two discs, each with a roughened surface on one face;

FIG. 19 is a schematic view of the prosthesis from FIG. 18A implanted in a facet joint;

FIG. 20 is a schematic view of a retaining member comprising a braided cable;

FIGS. 21A and 21B are schematic views of one embodiment of a facet joint prosthesis with a retaining interface comprising a centrally located hole;

FIGS. 22A and 22B are schematic views of one embodiment of a facet joint prosthesis with a retaining interface comprising an eccentrically located hole;

FIGS. 23A and 23B are schematic views of one embodiment of a facet joint prosthesis with a retaining interface comprising an edge contiguous hole;

FIGS. 24A and 24B are schematic views of one embodiment of a facet joint prosthesis comprising two discs, each with an eccentrically located hole;

FIGS. 25A and 25B are schematic views of one embodiment of a facet joint prosthesis comprising a curved disc with a retaining interface;

FIG. 26 depicts one embodiment of the invention where the cable is engaged to the articular processes using knots in the cable;

FIGS. 27A and 27B depict another embodiment of the retaining member comprising a braided cable with threaded ends adapted to accept threaded nuts;

FIG. 28 depicts one embodiment of the invention where a cable is engaged to the articular processes using nuts threaded onto the cable;

FIG. 29 depicts a preferred embodiment of the invention comprising a curved prosthesis, cable and two set-screw retaining rings;

FIGS. 30A and 30B are elevational and cross-sectional views of one embodiment of the set-screw retaining rings, respectively;

FIGS. 31 through 33 are elevational views of various embodiments of the screw in the set-screw retaining rings;

FIGS. 34A to 35B are one embodiment of the invention comprising friction fit retaining rings. FIGS. 34A and 34B depict the retaining rings in their reduced state and FIGS. 35A and 35B depict the retaining rings in their expanded state;

FIGS. 36A to 36C illustrate embodiments of the invention comprising a prosthesis with a close-ended threaded retaining interface and a threaded retaining member; FIGS. 36B and 36C depict a threaded retaining member with a pivotable washer;

FIG. 37A is a cross sectional view of the prosthesis in FIG. 36A implanted in a facet joint; FIG. 37B is a cross sectional view of the prosthesis in FIG. 36B implanted in a facet joint;

FIG. 38 is a cross sectional view of a two-part prosthesis comprising flat discs implanted into a facet joint;

FIG. 39 is a cross sectional view of a two-part prosthesis comprising curved discs implanted into a facet joint;

FIGS. 40A and 40B are schematic views of one embodiment of a facet joint prosthesis with an integral retaining member comprising a centrally located barbed spike;

FIGS. 41A and 41B are schematic views of one embodiment of a facet joint prosthesis with an integral retaining member comprising an eccentrically located barbed spike;

FIG. 42 depicts the prosthesis of FIG. 38A implanted into a facet joint;

FIG. 43 illustrates a two-part prosthesis implanted into a facet joint;

FIG. 44 shows one embodiment of the invention comprising a prosthesis with multiple anchoring projections;

FIG. 45 shows the prosthesis of FIG. 44 implanted into a facet joint;

FIGS. 46A and 46B depict one embodiment of the invention comprising a prosthesis with a rigid soft tissue side anchor;

FIGS. 47A and 47B depict one embodiment of the invention comprising a prosthesis with an embedded flexible soft tissue side anchor;

FIG. 48 depicts one embodiment of the invention depicting a posterior surgical approach for implanting a prosthesis in the cervical vertebrae;

FIG. 49 depicts one embodiment of the invention depicting the cross-sectional surgical approach for implanting a prosthesis in the cervical vertebrae;

FIG. 50 depicts one embodiment of the invention depicting a posterior surgical approach for implanting a prosthesis in the thoracic vertebrae; and

FIGS. 51A to 51E depicts one embodiment of the invention depicting a posterior surgical approach for implanting a prosthesis in the lumbar vertebrae; FIGS. 51A to 51C are posterior views of the surgical procedure and FIGS. 51D and 51E are cross sectional views of the surgical procedure.

FIGS. 52A to 52E illustrate one embodiment of the tool with a single punch arm and plate. FIG. 52F is a wire frame model of the embodiment depicted in FIGS. 52A to 52E.

FIGS. 53A to 53F are one embodiment of the tool with punch drill arms.

FIG. 54 depicts the distal end of the tool of FIGS. 53A to 53F without a frame member.

FIG. 55 is a component view of the tool shown in FIGS. 53A to 53F.

FIGS. 56A to 56C are sequential schematic representations of the use of the tool shown in FIGS. 53A to 53F.

FIGS. 57A to 57E show an embodiment of the method of use of the tool in FIGS. 52A to 52F wherein it is used to create a hole in the articular process of the vertebra.

FIGS. 58A to 58G show an embodiment of the method of use of the tool in FIGS. 53A to 53E wherein it is used to create a hole in the articular process of the vertebra.

FIGS. 59A to 59D show one embodiment of the tool with dual punch arms and a spacer.

FIG. 60 shows an embodiment of the method of use of the tool in FIGS. 59A to 59D 53E wherein it is used to create a hole in the articular process of the vertebra.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

A. Anatomy of the Spine

As shown in FIG. 1, the vertebral column 2 comprises a series of alternating vertebrae 4 and fibrous discs 6 that provide axial support and movement to the upper portions of the body. The vertebral column 2 typically comprises thirty-three vertebrae 4, with seven cervical (C1-C7), twelve thoracic (T1-T12), five lumbar (L1-L5), five fused sacral (S1-S5) and four fused coccygeal vertebrae. FIGS. 2A and 2B depict a typical thoracic vertebra. Each vertebra includes an anterior body 8 with a posterior arch 10. The posterior arch 10 comprises two pedicles 12 and two laminae 14 that join posteriorly to form a spinous process 16. Projecting from each side of the posterior arch 10 is a transverse 18, superior 20 and inferior articular process 22. The facets 24, 26 of the superior 20 and inferior articular processes 22 form facet joints 28 with the articular processes of the adjacent vertebrae. See FIGS. 3A and 3B. The facet joints are true synovial joints with cartilaginous surfaces and a joint capsule.

The orientation of the facet joints vary, depending on the level of the vertebral column. In the C1 and C2 vertebrae, the facet joints are parallel to the transverse plane. FIGS. 4A to 6B depict the orientations of the facet joints at different levels of the vertebral column. In the C3 to C7 vertebrae shown in FIGS. 4A and 4B, the facets are oriented at a 45-degree angle to the transverse plane 30 and parallel to the frontal plane 32, respectively. This orientation allows the facet joints of the cervical vertebrae to flex, extend, lateral flex and rotate. At a 45-degree angle in the transverse plane 30, the facet joints of the cervical spine can guide, but do not

limit, the movement of the cervical vertebrae. FIGS. 5A and 5B depict the thoracic vertebrae, where the facets are oriented at a 60-degree angle to the transverse plane 30 and a 20-degree angle to the frontal plane 32, respectively. This orientation is capable of providing lateral flexion and rotation, but only limited flexion and extension. FIGS. 6A and 6B illustrate the lumbar region, where the facet joints are oriented at 90-degree angles to the transverse plane 30 and a 45-degree angle to the frontal plane 32, respectively. The lumbar vertebrae are capable of flexion, extension and lateral flexion, but little, if any, rotation because of the 90-degree orientation of the facet joints in the transverse plane. The actual range of motion along the vertebral column can vary considerably with each individual vertebra.

In addition to guiding movement of the vertebrae, the facet joints also contribute to the load-bearing ability of the vertebral column. One study by King et al. *Mechanism of Spinal Injury Due to Caudocephalad Acceleration*, *Orthop. Clin. North Am.*, 6:19 1975, found facet joint load-bearing as high as 30% in some positions of the vertebral column. The facet joints may also play a role in resisting shear stresses between the vertebrae. Over time, these forces acting on the facet joints can cause degeneration and arthritis.

B. Joint Prosthesis

In one embodiment of the invention, a device for restoring the spacing between two facets of a facet joint is provided. As shown in FIGS. 7A and 7B, the device comprises a prosthesis 34 with a least two faces, a first face 36 adapted to contact the articular surface of one facet of the facet joint and a second face 38 adapted to contact the articular surface of the other facet. In one embodiment, the prosthesis 34 has a generally circular profile and is sized to fit generally within the joint capsule of the facet joint 28. FIG. 8 illustrates the prosthesis 34 of FIGS. 7A and 7B positioned in a facet joint. In other embodiment of the invention, the prosthesis can have any of a variety of profiles, including but not limited to square, rectangle, oval, star, polygon or combination thereof. An octagonal prosthesis is shown in FIGS. 9A and 9B. In one embodiment of the invention, a prosthesis having the desired shape is selected from an array of prostheses after radiographic visualization of the articular processes and/or by radio-contrast injection into the facet joint to visualize the joint capsule. In one embodiment, the prosthesis has a diameter of about 4 mm to about 30 mm. In another embodiment, the prosthesis has a diameter of about 5 mm to about 25 mm. In still another embodiment, the prosthesis has a diameter of about 10 mm to about 20 mm. In one embodiment, the prosthesis has a cross-sectional area of about 10 mm² to about 700 mm². In another embodiment, the prosthesis has a cross-sectional area of about 25 mm² to about 500 mm². In still another embodiment, the prosthesis has a cross-sectional area of about 20 mm² to about 400 mm², and preferably about 25 mm² to about 100 mm².

The prosthesis has a thickness generally equal to about the anatomic spacing between two facets of a facet joint. The prosthesis generally has a thickness within the range of about 0.5 mm to about 3.0 mm. In certain embodiments, the prosthesis has a thickness of about 1 mm to about 2 mm. In one preferred embodiment, the prosthesis has a thickness of about 0.5 mm to about 1.5 mm. In one embodiment, the thickness of the prosthesis is nonuniform within the same prosthesis. For example, in FIGS. 10A and 10B, the thickness of the prosthesis 42 is increased around the entire outer edge 44, along at least one and, as illustrated, both faces 46, 48. In FIGS. 11A and 11B, only a portion of the edge 44 on one face 46 of the prosthesis 42 has a thickness that is greater than the thickness of a central region, and, optionally, also

thicker than the typical anatomic spacing between two facets of a facet joint. An increased edge thickness may resist lateral displacement of the prosthesis out of the facet joint.

In some embodiments of the invention, the prosthesis is configured to provide an improved fit with the articular process and/or joint capsule. For example, in FIGS. 12A and 12B, the prosthesis 49 has a bend, angle or curve 50 to generally match the natural shape of an articular facet. FIG. 13 depicts the prosthesis of FIGS. 12A and 12B positioned in a facet joint. The prosthesis may be rigid with a preformed bend. Alternatively, the prosthesis may be sufficiently malleable that it will conform post implantation to the unique configuration of the adjacent facet face. Certain embodiments of the invention, such as those depicted in FIG. 8 and FIG. 13, the prosthesis is configured to be implanted between the articular processes and/or within the joint capsule of the facet joint, without securing of the prosthesis to any bony structures. Such embodiments can thus be used without invasion or disruption of the vertebral bone and/or structure, thereby maintaining the integrity of the vertebral bone and/or structure.

In one embodiment, at least a portion of one surface of the prosthesis is highly polished. A highly polished portion of the prosthesis may reduce the surface friction and/or wear in that portion of the prosthesis as it contacts bone, cartilage or another surface of the prosthesis. A highly polished surface on the prosthesis may also decrease the risk of the prosthesis wedging between the articular surfaces of the facet joint, which can cause pain and locking of the facet joint.

In one embodiment, shown in FIGS. 14A and 14B, at least a portion of one surface of the prosthesis 50 has a roughened surface 52. A roughened surface may be advantageous when in contact with a bone or tissue surface because it may prevent slippage of the prosthesis 50 against the bone and aid in maintaining the prosthesis 50 in the joint. In one embodiment of the invention, shown in FIGS. 15A and 15B, at least a portion of one surface of the prosthesis 50 has a porous surface 54. A porous surface 54 can be created in any a variety of ways known in the art, such as by applying sintered beads or spraying plasma onto the prosthesis surface. A porous surface 54 can allow bone to grow into or attach to the surface of the prosthesis 50, thus securing the prosthesis 50 to the bone. In one embodiment, an adhesive or sealant, such as a cyanoacrylate, polymethylmethacrylate, or other adhesive known in the art, is used to bond one face of the prosthesis to an articular surface.

In one embodiment of the invention, one surface of the prosthesis is roughened or porous and a second surface that is highly polished. The first surface contacts or engages one facet of the facet joint and aids in maintaining the prosthesis between the articular surfaces. The second surface of the prosthesis is highly polished and contacts the other facet of the facet joint to provide movement at that facet joint. FIGS. 16A and 16B represent one embodiment of the prosthesis comprising a curved or bent disc 56 with a roughened surface 52 on the greater face 58 of the disc and a highly polished surface 60 on the lesser face 62. FIG. 17 depicts the prosthesis of FIGS. 16A and 16B positioned in a facet joint. The prosthesis generally maintains a fixed position relative to the facet contacting the roughened surface while the movement of the facet joint is preserved between the other facet and the highly polished lesser face of the prosthesis.

FIGS. 18A and 18B show one embodiment of the invention, where the prosthesis 64 comprises two separate discs 66, each disc comprising a first face 68 that articulates with the complementary first face 68 of the other disc, and a second face 70 adapted to secure the disc to the adjacent

bone or cartilage of one facet of the facet joint **28**. In one embodiment of the invention, the thickness of one disc will generally be about half of the anatomic spacing between two facets of the facet joint. In other embodiments of the invention, the prosthesis comprises three or more discs. In one embodiment the total thickness of all the discs is generally about 25% to about 300% of the anatomic spacing between the two facets. In another embodiment, the total thickness of the discs is generally about 50% to about 150% of the anatomic spacing. In still another embodiment, the total thickness of the discs is about 75% to about 125% of the anatomic spacing. Each disc of the two-part prosthesis can otherwise also have features similar to those of a single-disc prosthesis, including but not limited to curved or bent configurations, highly polished or roughened surfaces, and other feature mentioned below. The two discs need not have the same size, thickness, configuration or features. FIG. **19** depicts one embodiment of a two-part prosthesis **64** positioned within a facet joint **28**.

The prosthesis can be manufactured from any of a variety of materials known in the art, including but not limited to a polymer such as polyetheretherketone (PEEK), polyetherketoneketone (PEKK), polyethylene, fluoropolymer, hydrogel, or elastomer; a ceramic such as zirconia, alumina, or silicon nitride; a metal such as titanium, titanium alloy, cobalt chromium or stainless steel; or any combination of the above materials.

C. Prosthesis with a Retaining Configuration

In one embodiment of the invention, the prosthesis is maintained between the two facets of the facet joint by taking advantage of the joint capsule and/or other body tissue surrounding the facet joint to limit the migration of the prosthesis out of the facet joint. In some embodiments of the invention, the shape of the prosthesis itself is capable of resisting displacement of the prosthesis from its position generally between the facet joint surfaces. In one embodiment, a concave or biconcave configuration resists displacement of the prosthesis by providing an increased thickness at the periphery of the prosthesis that requires a larger force and/or greater distraction of facet joint surfaces in order to cause displacement. In other embodiments, surface treatments or texturing are used to maintain the prosthesis against a facet of the facet joint, as described previously. In some embodiments, a combination of disc configuration, surface texturing and existing body tissue or structures are used to maintain the position of the prosthesis.

Bone growth facilitators, electrical current, or other known techniques may be used to accelerate osteoincorporation of textured or microporous anchoring surfaces.

D. Prosthesis with a Retaining Member

The prosthesis may be configured with a retaining interface to engage a retaining member that facilitates retention of the prosthesis within the joint capsule of the facet joint. Use of a retaining member may be advantageous for preventing migration of the prosthesis over time use or with the extreme ranges of vertebral movement that may distract the articular surfaces sufficiently to allow the prosthesis to slip out.

1. Wire/Cable Retaining Member

In one embodiment of the invention, shown in FIGS. **20** to **21B**, the retaining member comprises a wire or cable **72** with a portion **74** that engages the prosthesis **76** at a retaining interface **78**, and at least one other portion **80** that engages or anchors to the bone or soft tissue surrounding the facet joint. The wire or cable may be solid, braided or multifilamented. The retaining member in this embodiment will be described primarily as a cable or wire, but it is to be

understood that any of a variety of elongate structures capable of extending through a central aperture will also work, including pins, screws, and single strand or multistrand polymeric strings or weaves, polymeric meshes and fabric and other structures that will be apparent to those of skill in the art in view of the disclosure herein.

The cross-sectional shape of the retaining member can be any of a variety of shapes, including but not limited to circles, ovals, squares, rectangles, other polygons or any other shape. The wire or cable generally has a diameter of about 0.5 mm to about 2 mm and a length of about 5 mm to about 60 mm. In another embodiment, wire or cable has a diameter of about 0.25 mm to about 1 mm, and preferably about 0.75 mm to about 1.25 mm. The diameter of the wire or cable may vary along the length of the wire or cable. In one embodiment, the wire or cable has a length of about 10 mm to about 40 mm. In another embodiment, the wire or cable has a length of about 20 mm to about 30 mm.

In one embodiment, shown in FIGS. **21A** and **21B**, the retaining interface **78** of the prosthesis **76** is a conduit between the two faces **82**, **84** of the prosthesis **76**, forming an aperture **78**. In one embodiment, the aperture **78** has a diameter larger than the diameter of the wire or cable **72**, to provide the prosthesis **76** with a range of motion as the facet joint moves. The aperture **78** inside diameter may be at least about 110%, often at least about 150% and in certain embodiments at least about 200% or 300% or greater of the outside diameter or corresponding dimension of the retaining member in the vicinity of the engagement portion **78**. The cross-sectional shape of the aperture **78** can match or not match the cross sectional shape of the wire or cable used.

In another embodiment, the retaining interface **78** extends only partially through the prosthesis **72**. The retaining interface **78** may be located generally in the center of the prosthesis, or it may be located eccentrically, as depicted in FIGS. **22A** and **22B**. In one embodiment, shown in FIGS. **23A** and **23B**, the retaining interface **78** is located at the edge **86** of the prosthesis **76** such that the interior surface of the hole **78** is contiguous with the outer edge of the prosthesis. This configuration of the retaining interface **78** does not require the cable **72** to be threaded through the retaining interface **78** and may facilitate engagement of the retaining member with the prosthesis. FIGS. **24A** and **24B** depict an embodiment of the invention comprising a two-part prosthesis **88**. Either a single cable or two separate cables may be used retain both discs within the facet joint. FIGS. **25A** and **25B** depict another embodiment of the invention comprising a curved prosthesis **90** with a retaining interface **78** adapted to accept a cable.

In FIG. **26**, the wire or cable **72** is secured to the articular processes **20**, **22** by tying one or more knots **92** in the cable **72** that can resist pulling of the wire or cable through the articular process. In another embodiment, one or both ends of the wire or cable are provided with an anchor to resist migration of the implants. As shown in FIGS. **27A** and **27B**, one or both ends of the wire or cable **72** may be threaded such that a nut **94** can be tightened on the wire or cable **72** to secure the wire or cable to the articular processes **20**, **22**. FIG. **28** depicts the attachment of a nut onto a threaded end of a cable. The threaded portion **96** of the wire or cable can be secured to the cable by pressing, crimping or twisting the threaded **96** portion onto the cable **72**. In one embodiment, the threaded portion **96** is made from titanium, titanium alloy, cobalt chromium, stainless steel, or any combination thereof. In one embodiment, the wire or cable has two threaded ends **96** for engaging the bony or cartilaginous tissue, one portion for each facet of the facet joint.

In another embodiment, shown in FIG. 29, the wire or cable is secured to the articular process with retaining rings 98. As depicted in FIGS. 30A and 30B, the retaining rings 98 comprise a ring 100 with a central lumen 102 and a locking element to facilitate locking the ring 100 to a retaining member. The central lumen 102 is adapted to accept insertion of a wire or cable through it. The illustrated locking element is in the form of a side lumen 104 which is threaded and configured to accept a rotatable screw 106 with a proximal end 108, a threaded body 110 and a distal end 112. The threaded body 110 is complementary to the threads of the side lumen 104 so that when the screw 106 is rotated at its distal end 112, the proximal end 108 of the screw 106 moves further into the central lumen 102 and is capable of applying increasing force to a wire or cable inserted through the central lumen 102. In one embodiment, the force on the wire or cable is capable of creating a friction fit or a mechanical interfit to resist movement between the wire or cable and the retaining ring 98, thereby securing the wire or cable to the articular process 20 or 22. As shown in FIGS. 31 to 33, the distal end 112 of the screw 106 can be configured to engage the wire or cable in any of a variety of designs, including but not limited to a blunt tip 114, curved tip 116 and piercing tip 118.

In another embodiment, depicted in FIGS. 34A and 34B, the wire or cable is securable to the articular process with a retaining ring 120 having radially inward biased projections 122 defining a central lumen 124. The central lumen has a cross-sectional shape smaller than that of the wire or cable but is capable of enlargement when the inward projections 122 are bent away, as shown in FIGS. 35A and 35B. The inward projections 122 apply increasing force to the wire or cable within the central lumen 124 as the projections 122 are bent, thereby creating a friction fit.

In one embodiment of the invention, one end of the wire or cable retaining member is preformed with a retainer for engaging the articular process. The retainer may be a preformed ring, bulb, flared end, T-bar end, or any of a variety of shapes having a greater cross sectional area than the other portions of the wire or cable retaining member. This configuration of the wire or cable retaining member is adapted to engage an articular process by passing the free end of a wire or cable retaining member through an articular process such that the end with the preformed retainer can engage the articular process.

In one embodiment, the wire or cable retaining member is secured to the articular processes with sufficient laxity or length between the secured ends or between the prosthesis and one secured end so that the two articular processes are not fixed in position relative to each other and remain capable of performing movements such as flexion, extension, lateral flexion and/or rotation. In one embodiment, the retaining member comprises a cable of braided polymer, including but not limited to a braided polymer such as PEEK or PEKK, or a braided metal, such as braided cobalt chromium or titanium. The cable can be selected with different degrees of flexibility to provide different degrees of movement at that facet joint. The cable has a first segment capable of engaging the prosthesis at its retaining interface to limit the movement

2. Screw/Bolt Retaining Member

In one embodiment of the invention, shown in FIG. 36A, the retaining member comprises a screw or bolt 126 with a proximal end 128, body 130 and distal end 132. The distal end 132 of the screw or bolt is capable of forming a mechanical interfit with a complementary retaining interface 134 on the prosthesis or spacer 136. The distal end 132

typically comprises threads, but one skilled in the art will understand that other configurations may be used to form a mechanical interfit. The complementary retaining interface 134 on the prosthesis 136 could be a threaded through hole or preferably, a close-ended hole. The proximal end 128 of the screw or bolt 126 has a hex or other type of interface known in the art, capable of engaging a rotating tool to manipulate the screw or bolt 126. The body of the screw or bolt 126 has a length sufficient to at least span the length of the hole or conduit created through the articular process for securing the prosthesis. In FIG. 36B, the retaining member further comprises a pivotable washer 127 with a pivot surface 129 that articulates with the proximal end 128 of the screw 126. In one embodiment, the pivotable washer 127 is capable of a range of positions relative to the screw 126 and provides the screw 126 with a better surface area contact with the bone.

FIG. 37 is a cross-sectional view of a facet joint 28 with a spacer 136 bolted to one articular process 20 of a facet joint 28. The spacer 136 position is fixed relative to one facet 24 of the joint 28, but provides for spacing and movement of the other facet 26 with respect to the spacer 136. In embodiments of the invention comprising a two-part prosthesis, shown in FIGS. 38 and 39, each disc may have its own screw or bolt retaining member. FIG. 38 depicts a flat two-part prosthesis 138 and FIG. 39 depicts a curved two-part prosthesis 140.

3. Projection Retaining Member

In some embodiments of the invention, shown in FIGS. 40A through 41B, the retaining member is integral with or attached to the prosthesis and comprises a projection 142 from the prosthesis 144 that is adapted to engage the adjacent articular process or surrounding tissue. In one embodiment, the projection comprises at least one spike 142 or hook projecting from one face of the prosthesis 144. In one embodiment, the spike 142 or hook can be ribbed, barbed or threaded to resist separation after insertion into bone or tissue. FIG. 42 depicts the prosthesis 144 of FIG. 40A engaged to a facet 24 of the facet joint 28. In one embodiment comprising a two-part prosthesis 146, shown in FIG. 43, each disc 148 may have its own projection-retaining member 142. In some embodiments of the invention, as depicted in FIG. 44, more than one projection 150 is provided on the prosthesis 152. FIG. 45 illustrates the prosthesis of FIG. 44 placed in a facet joint 28. The projections 150 may be angled with respect to the prosthesis 152 to resist dislodgement by the movement at the joint.

FIGS. 46A to 47B illustrate embodiments of the invention where the retaining member comprises a projection 154 extending laterally such as from the side of the prosthesis 156, and adapted to engage the soft tissue surrounding the facet joint, rather than a bony or cartilaginous articular process. In one example, the prosthesis of FIG. 46 could be inserted into a facet joint through an incision made in the joint capsule, but the integrity of the joint capsule opposite the incision site is maintained and used as an anchoring site for the prosthesis. The orientation of the projection can be fixed as in FIG. 44, or flexible. FIG. 47 depicts a flexible tether such as a wire 158 with its proximal end 160 embedded in or otherwise attached to the prosthesis and one or more barbs which may be attached to its distal end 162. A flexible projection may provide greater selection of soft tissue anchoring sites for the prosthesis.

In one embodiment of the invention, the joint capsule is closed after placement of the prosthesis. Closure may be performed using adhesives, suturing, stapling or any of a variety of closure mechanisms known in the art.

E. Accessing the Facet Joints

1. Surgical Approach to the Cervical Spine

In one embodiment of the invention, general anesthesia is achieved and the patient is positioned prone on a turning frame or three-point head rest attached to the table. Skeletal traction is performed using tongs. The patient is prepped and draped in the usual sterile fashion. Pre-operative radiographic films are reviewed and any vertebral anomalies or variations are noted. In one embodiment, the spinous processes are palpated to identify the location of the cervical vertebrae and a skin incision is made over the desired vertebrae, as shown in FIG. 48. In another embodiment, a paraspinous skin incision is made over the desired facet joint. The exposed skin edges and subcutaneous tissue are injected with epinephrine 1:500,000 solution to facilitate hemostasis. Dissection to the spinous processor facet joint is performed using an electrocautery knife. In one embodiment, shown in FIG. 49, dissection is performed along the nuchal ligament 164 to avoid cutting into vascular muscle tissue. Soft tissue retractors are used to maintain tissue tension and aid the dissection process. The ligamentous attachments to the spinous process 16 are detached and the facet joints are exposed. In another embodiment, dissection is performed through the muscle tissue to directly access the facet joint. The joint capsule of the facet joint is opened by incision or piercing. The facets of the facet joint are distracted as required to provide access to the joint space. In one embodiment, the affected facet joint is sized and a joint prosthesis is selected. In one embodiment, the articular process or processes are prepared for receiving the joint prosthesis, including but not limited to roughening the articular surface of the articular process and/or creating a hole for the prosthesis anchor or retaining member. The prosthesis is inserted into the facet joint space and the anchor or retaining member, if any is attached to the articular process. The steps are repeated until all the joint prostheses have been inserted. The surgical site is closed in layers with a suction tube or drainage tube in place. The surgical site is cleaned and dressed.

2. Surgical Approach to the Thoracic Spine

In one embodiment of the invention, general anesthesia is achieved and the patient is positioned prone on a padded spinal operating frame. The patient is prepped and draped in the usual sterile fashion. Pre-operative radiographic films are reviewed and any vertebral anomalies or variations are noted. In one embodiment, shown in FIG. 50, a midline skin incision is made over the desired vertebrae. In another embodiment, a paraspinous skin incision is made over the desired facet joint. The exposed skin edges, subcutaneous tissue and erector spinae muscles are injected with epinephrine 1:500,000 solution to facilitate hemostasis. Dissection is performed using an electrocautery knife or scalpel through the superficial and lumbodorsal fascia to the tips of the spinous processes. The erector spinae muscle is reflected laterally to the tips of the transverse processes, thereby exposing the posterior arch. After exposure of all the desired vertebrae is achieved, an intra-operative x-ray is obtained to confirm access to the desired vertebrae. The facets of the facet joint are distracted as required to provide access to the joint space. The joint capsule of the facet joint is opened by incision or piercing. In one embodiment, the affected facet joint is sized and a joint prosthesis is selected. In one embodiment, the articular process or processes are prepared for receiving the joint prosthesis, including but not limited to roughening the articular surface of the articular process and/or creating a hole for the prosthesis anchor or retaining member. The prosthesis is inserted into the facet joint space

and the anchor or retaining member, if any is attached to the articular process. The steps are repeated until all the joint prostheses have been inserted. The surgical site is closed in layers with a suction tube or drainage tube in place. The surgical site is cleaned and dressed.

3. Surgical Approach to the Lumbar Spine

In one embodiment of the invention, general anesthesia is achieved and the patient is positioned prone or kneeling on a padded spinal operating frame. In one embodiment, by allowing the abdomen to hang free, intravenous pressure is reduced and blood loss during the procedure is decreased. The patient is prepped and draped in the usual sterile fashion. Pre-operative radiographic films are reviewed and any vertebral anomalies or variations are noted. FIG. 51A illustrates a midline skin incision is made over the desired vertebrae. The exposed skin edges and subcutaneous tissue are injected with epinephrine 1:500,000 solution to facilitate hemostasis. In FIGS. 51B and 51C, dissection is continued to the lumbodorsal fascia and the surgical site is exposed by retracting the skin and subcutaneous tissue laterally. In FIGS. 51D and 51E, blunt finger dissection is used between the multifidus and longissimus muscles to access the facet joints. Self-retaining Gelpi retractors are inserted between the muscle groups. Electrocautery or elevators are used to separate the transverse fibers of the multifidus from their heavy fascial attachments. Exposure of the transverse processes and fascial planes is continued. Cautery may be used to provide hemostasis from the lumbar arteries and veins along the base of the transverse processes. The facets of the facet joint are distracted as required to provide access to the joint space. The joint capsule of the facet joint is opened by incision or piercing. In one embodiment, the affected facet joint is sized and a joint prosthesis is selected. In one embodiment, the articular process or processes are prepared for receiving the joint prosthesis, including but not limited to roughening the articular surface of the articular process and/or creating a hole for the prosthesis anchor or retaining member. The prosthesis is inserted into the facet joint and the anchor or retaining member, if any is attached to the articular process. The steps are repeated until all the joint prostheses have been inserted. The surgical site is closed in layers over a suction tube and the skin flaps are sutured down to the fascia to eliminate any dead space in the tissue. The surgical site is cleaned and dressed.

4. Minimally Invasive Approach to the Cervical Spine

In one embodiment of the invention, general or local anesthesia is achieved and the patient is positioned prone on a turning frame or three-point head rest attached to the table. Skeletal traction is performed using tongs. The patient is prepped and draped in the usual sterile fashion. Pre-operative radiographic films are reviewed and any vertebral anomalies or variations are noted. The spinous processes are palpated to identify the location of the cervical vertebrae and a small 1 cm skin incision is made over the desired insertion site. Hemostasis is achieved with infiltration of epinephrine 1:500,000 solution around the incision site. Under fluoroscopy, a trocar or needle is inserted through the incision site and joint capsule to the desired facet joint. The needle or trocar is replaced with an introducer. In one embodiment, insertion is performed along the nuchal ligament to avoid cutting into vascular muscle tissue. In another embodiment, insertion is performed directly through the skin and muscle overlying the facet joint. The facets of the facet joint are distracted as required to provide access to the joint space. In one embodiment, the affected facet joint is sized by injecting a radio-contrast agent into the facet joint and a joint prosthesis is selected. In one embodiment, the articular process

or processes are prepared for receiving the joint prosthesis, including but not limited to roughening the articular surface of the articular process and/or creating a hole using endoscopic instruments known in the art. The prosthesis is inserted into the facet joint space through the introducer and an anchor or retaining member, if any is attached to the articular process. The steps are repeated until all the joint prostheses have been inserted. The surgical site is closed, cleaned and dressed.

5. Minimally Invasive Approach to the Thoracic Spine

In one embodiment of the invention, general or local anesthesia is achieved and the patient is positioned prone on a padded spinal operating frame. The patient is prepped and draped in the usual sterile fashion. Pre-operative radiographic films are reviewed and any vertebral anomalies or variations are noted. A small 1 cm skin incision is made over the desired insertion site. Hemostasis is achieved by injecting epinephrine 1:500,000 solution around the incision site. Under fluoroscopy, a trocar or needle is inserted through the superficial and lumbodorsal fascia, the erector spinae muscle and joint capsule to access the facet joint. The trocar or needle is replaced with an introducer. The facets of the facet joint are distracted as required to provide access to the joint space. An intra-operative x-ray or fluoroscopy is obtained to confirm access to the desired facet joint. In one embodiment, the affected facet joint is sized and a joint prosthesis is selected. In one embodiment, the articular process or processes are prepared for receiving the joint prosthesis, including but not limited to roughening the articular surface of the articular process and/or creating a hole for the prosthesis anchor or retaining member, using endoscopic instruments known in the art. The prosthesis is inserted into the facet joint space and the anchor or retaining member, if any is attached to the articular process. The steps are repeated until all the joint prostheses have been inserted. The surgical site is closed, cleaned and dressed.

6. Minimally Invasive Approach to the Lumbar Spine

In one embodiment of the invention, general or local anesthesia is achieved and the patient is positioned prone or kneeling on a padded spinal operating frame. In one embodiment, by allowing the abdomen to hang free, intravenous pressure is reduced and blood loss during the procedure is decreased. The patient is prepped and draped in the usual sterile fashion. Pre-operative radiographic films are reviewed and any vertebral anomalies or variations are noted. A small 1 cm skin incision is made over the desired insertion site. Hemostasis is achieved by injecting epinephrine 1:500,000 solution around the incision site. Under fluoroscopy, a trocar or needle is inserted through the lumbodorsal fascia. The trocar or needle is replaced with an introducer. In one embodiment, radio-contrast agent is injected through the introducer to identify the junction between the lumbodorsal fascia and the multifidus and longissimus muscles. A blunt dissector is inserted through the introducer to dissect between the multifidus and longissimus muscles and pierce the joint capsule to access the facet joints. The facets of the facet joint are distracted as required to provide access to the joint space. In one embodiment, the affected facet joint is sized and a joint prosthesis is selected. In one embodiment, the articular process or processes are prepared for receiving the joint prosthesis, including but not limited to roughening the articular surface of the articular process and/or creating a hole for the prosthesis anchor or retaining member. The prosthesis is inserted into the facet joint space and the anchor or retaining member, if any is attached to the articular process. The steps are repeated until

all the joint prostheses have been inserted. The surgical site is closed, cleaned and dressed.

F. Facet Drill

Other embodiments of the invention comprise tools and methods for creating holes or lumens through one or more articular processes of the vertebra to facilitate implantation of a prosthesis stabilizer or retainer. Preferably, the holes or lumens have a curved or non-linear configuration. The curved or non-linear configuration allows relatively greater penetration through the thicker portions of the articular process(es) and therefore the articular process(es) may be less likely to fracture during formation of the hole or lumen. While various instruments have been proposed for drilling into and through bone, including for example, the curved drills described in U.S. Pat. Nos. 5,700,265, 6,419,678, and 6,607,530, herein incorporated by reference in their entirety, the subject tool offers the benefits of lumen formation through the articular processes within the limited surgical access available about the vertebra. The preferred devices utilize one or more curved punch members that rotate about an axis that is transverse to the movement plane of the curved punch member. Unlike traditional orthopedic procedures that require unimpeded access to the surgical site due to the longitudinally-oriented surgical tools, the curved punch members also permit access using a limited space or cavity around the articular processes. As used herein, the terms "lumen-forming" and "lumen formation" refer to the creation of a hole, passageway or indentation generally such as by, for example, piercing, punching, boring, puncturing, or drilling.

One embodiment of the tool **200**, shown in FIGS. **52A** and **52F**, comprises a shaft **202** with a proximal handle **204** and a movable distal lumen-forming member **206** and a distal opposing support member **208**. The lumen-forming member **206** may comprise a punch or lumen-forming arm **210** with a punch or lumen-forming tip **212**. The arm **210** of the lumen-forming member **206** may have a diameter in the range of about 1 mm to 5 mm, preferably about 2 mm to 4 mm, and most preferably about 3 mm. The lumen-forming tip **212** can be of any appropriate configuration and with any number of points. In some embodiments, the lumen-forming tip **212** may be round, flat, beveled or stepped. In some embodiments of the lumen-forming tool with more than one tip, the tips may have a similar or different configurations. The support member **208** permits stabilization of the articular processes as the lumen-forming member **206** passes or punctures through the bone. The support member **208** may comprise a plate **214** that is flat or curved. In some embodiments, the plate **214** may have a concave or convex configuration. The plate **214** may optionally comprise a recess **216**, depicted in FIG. **52E**, to seat the articular process and/or to allow the lumen-forming tip **212** of the lumen-forming member **206** to penetrate through the bone and into the recess **216**. The support member **208** may also comprise a textured surface to resist slippage, including but not limited to serrations, ridges or indentations, or comprise a slip-resistant material. In some embodiments of the lumen-forming tool **200**, as depicted in FIG. **52E**, the support member **206** comprises a movable opposing plate **214**. The movable opposing plate **214** may be connected by any of a variety of movable joints known in the art. For example, in the embodiment depicted in FIG. **52F**, the plate **214** is connected to rest of the support member **208** with a pivot pin **215**. In other embodiments, ball-and-socket joints may be used. The movable opposing plate allows increased conformance or seating of the tool against the articular process. In some embodiments, the movable opposing plate **214** pivots

passively as the tool **200** is applied to the bone. In other embodiments, the position or orientation of the movable opposing plate **214** may be controlled at the proximal end of the tool **200**. Manipulation of the plate may be performed using push/pull rods, gears pull wires or combinations thereof, as is known to those of skill in the art. The plate may be biased in a particular orientation using springs or other bias structures.

Referring to FIGS. **52C** to **52F**, the lumen-forming member **206** may be movably attached and secured to the distal frame **218** of the shaft **202** by a pivot pin **220**. The lumen-forming member **206** may be moved between a closed configuration, depicted in FIG. **52C**, to an open configuration, depicted in FIG. **52D**, by a proximal actuator **222** that moves a control rod **224** within the shaft **202** of the tool **200**. In the embodiment depicted in FIGS. **52C** to **52F**, manipulation of the actuator **222** causes a longitudinal movement of the control rod **224**, which in turn causes a translational/angular movement of a link member **226** joining the control rod **224** and lumen-forming member **206** using pivot pins **228**, **230**. The actuator **222** may be connected to the control rod **224** directly, in which case the actuator **222** is also manipulated by pushing and pulling. The control rod **224** may be straight or curved or a combination of these shapes. The control rod **224** may be stiff, bendable, or partially stiff and partially bendable. In a preferred embodiment, the actuator **222** is manipulated by rotation, through a threaded surface that rotatably interfaces with a threaded surface on the control rod **224**. A rotational coupling between the actuator **222** and the control rod **224** may provide increased mechanical advantage to the lumen-forming member **206** for piercing through bone. In still other embodiments, a power source may be provided for hydraulic, pneumatic or other power-assisted manipulation of the lumen-forming member **206**.

As mentioned previously, the plate **214** can be fixed, or movable with respect to the frame **218**. Various attachment means include, but are not limited to, welding, brazing, gluing, cementing, pin, hinge, and ball and socket. In one embodiment, the punch arm is curved. Different curved shapes of the punch arm are possible. In one embodiment the punch arm **210** is straight. In another embodiment the punch arm **210** has at least one straight segment and at least one curved segment. The segments may lie within the movement plane of the punch arm **210**, or alternatively, one or more segments may lie outside the movement plane. Likewise, the movement of both lumen-forming tips **212** typically occurs in the same plane, but in other embodiments, the movement of each tip **212** may occur in different planes that intersect at the intermediate position. In other embodiments of the lumen-forming tool **200**, only one arm moves or the two arms may move asymmetrically. In another embodiment of the lumen-forming tool, the lumen-forming arms move sequentially or in an alternating manner.

In one embodiment, the punch arm **210** is sized to be able to pass through the articular processes of the spine and the resulting hole is sized for a prosthesis retainer to be inserted. The size is appropriate for the retainer to slide or not slide in the hole, depending on the retainer design selected.

Referring to FIGS. **57A** to **57E**, the tool **200** may be used by positioning the lumen-forming tip **212** against one articular process **22** and positioning the plate **214** against the corresponding articular process **20**. When the tool **200** is actuated, the tip **212** is forced through both articular processes **20**, **22** while supported by the plate **214** support member **208**.

FIG. **57B** depicts one approach to the articular processes **20**, **22** that may be used with the tool **200**. In this particular embodiment, the support member **208** is applied to the articular process **20** of the inferior vertebra **238**, but in other embodiments, the support member **208** may be applied to the articular process **22** of the superior vertebra.

In another embodiment, illustrated in FIGS. **53A** to **53F**, the tool **232** comprises dual lumen-forming members **206** that are movable in a pincher-like fashion. The tool **232** comprises an shaft **202** with a proximal handle **204** and a distal frame member **218** with two lumen-forming members **206** connected to a frame **218**. Each lumen-forming member **206** comprises an arm **210** with a piercing tip **212** at one end and is rotatably connected to the frame **218** by a pivot pin **220**. Each lumen-forming member **206** is also joined to the control rod **224** by a link member **226** with pivot pins **228**, **230**, as depicted in FIGS. **54** and **55**. The control rod **224** runs through the outer shaft **202** and connects to the actuator **222** preferably with threads. The outer shaft **202** is connected at one end to the handle **204**. Although the embodiment depicted in FIGS. **53A** to **55** have lumen-forming members that pivot in equal amounts, one of skill in the art will understand that the configuration may be modified to move in differently. In one specific embodiment, only one lumen-forming member moves while the other member is fixed in position. One of skill in the art will also recognize that other movements of the control rod, link members and lumen-forming members are not limited to pivoting or angular movements. Alternate embodiments of the dual-arm tool **232** may include similar alternate structures as described for tool **200** above.

Referring to FIGS. **58A** to **58C**, one method of use for the tool **232** comprises placing one lumen-forming tip **212** against an exposed articular process **22** of a superior vertebra **236** and placing the other lumen-forming tip **212** against the corresponding articular process **20** of the inferior vertebra **238**. The handle **204** of the tool **232** is held while the actuator **222** is rotated. Rotation motion of the actuator **222** is transferred to the control rod **224** as a linear motion away from the actuator **222** via the threaded connection. This movement of the control rod **234** is transferred to the lumen-forming members **206** via the link members **226** and pivot pins **228**, **230** as a pinching motion where the piercing tips **212** approach each other through the bone of the articular processes **20**, **22**. Movement of the lumen-forming tips **212** continues until they meet at an intermediate position to form a curved or non-linear passageway **234** through the articular processes **20**, **22**. FIGS. **56A** to **56C** depict the tool **232** after the formation of the passageway **234**, as the tool **232** is moved from a closed configuration, as shown in FIG. **56A**, to an open configuration, as shown in FIG. **56C**. The resulting passageway **234** through the articular processes **20**, **22** may be straight or preferably curved, depending on the design of the lumen-forming member **206** and particularly the configuration of the lumen-forming arms **210**. For example, the lumen-forming arm **210** can be straight or preferably curved or non-linear. When two lumen-forming arms **210** are present, the two arms **210** need not have the same configuration. They can be of any appropriate cross-section area or shape, including but not limited to triangular, square, rectangular, hexagonal, pentagonal, octagonal, heptagonal, round, elliptical, or any combination of shapes. These shapes are applicable to single-arm and two-arm tools **200**, **232**. In embodiments of the tool **232** with two arms **210**, the arms **210** can have a similar configuration or different configurations. With two movable arms **210**, the two arms preferably move in the same movement plane and preferably

move by rotating around rotational axes that are generally perpendicular to the movement plane. In other embodiments, the arms may have cutting edges along its length and exhibit some rotation along its longitudinal axis, similar to a drill.

FIGS. 58D to 58G illustrate various approaches and relative orientations that may be taken with the tool 232 with respect to the articular processes 20, 22 and vertebrae 236, 238. The surgeon may select a particular rotational and/or angular approach to the surgical site, depending upon the particular vertebral morphology of the patient, the extent and location of damage or injury, prior surgery, and other factors known in the art.

In another embodiment, illustrated in FIGS. 59A to 59D, the tool 300 comprises dual lumen-forming members 206 that are movable in a pincher-like fashion in a manner similar to the tool 232 of FIGS. 53A to 53F described above. In this illustrated embodiment, the tool 300 comprises a shaft 202 with a proximal handle 204 and a distal frame member 218 with two lumen-forming members 206 connected to a frame 218. Each lumen-forming member 206 comprises an arm 210 with a piercing tip 212 at one end and is rotatably connected to the frame 218 by a pivot pin 220. Each lumen-forming member 206 is also joined to the control rod 224 by a link member 226 with pivot pins 228, 230. The control rod 224 runs through the outer shaft 202 and connects to the actuator 222 preferably with threads. The outer shaft 202 is connected at one end to the handle 204. In this illustrated embodiment, each lumen-forming member 206 comprises a bend that puts the lumen-forming arm 210 and the lumen-forming tip (i.e., piercing tip) 212 in the same plane as the longitudinal axis of a spacing member 310, to be described below. In this illustrated embodiment, the lumen-forming tip is out of the plane as the shaft 202.

The tool 300 further comprises a spacing member 310 that can be coupled to the shaft 202 through a detachable clipping member 306. In the illustrated arrangement, the spacing member 310 comprises a spacing member shaft 304 that is connected to the clipping member 306 at the proximal end and a spacer 302 at the distal end. The spacer 302, in turn, may comprise a disk-like member and two indentations 308 on each side of the disk-like member, and the indentations 308 are lined up or aligned with the lumen-forming member 206 to allow the lumen-forming tips 212 of the lumen-forming members 206 to penetrate through the bones and into the indentations 308. In some embodiments, the disk-like member of the spacer 302 may have an opening or a hole instead of the indentations 308, and the two lumen-forming tips 212 could make contact with each other through the opening or the hole after penetrating the bones. The spacer 302 may have a curved shape disk-like member to facilitate positioning between the articular processes 20 and 22. In some embodiments, the disk-like member of the spacer 302 may have different shape, size and thickness for used with different sized vertebra. The clipping member 306 allows the spacing member 310 to be detached from and attached to the facet drill tool with ease.

Although the tool 300 depicted in FIGS. 59A to 59D have a straight spacing member 310, a person skilled in the art would understand that the spacing member shaft 304 or the connection between the spacing member shaft 304 and the spacer 302 can be modified to have a bend, corner or curvature to position the spacer 302 for placing between the articular processes 20, 22 and for lining up with the lumen-forming members. For example, in an alternative embodiment, the spacing member 310 may be configured to have the spacer 302 bend toward the lumen-forming members

206, so the indentations 308 or the hole on the disk-like member of the spacer 302 are aligned with the lumen-forming tips. In some embodiments, the spacing member 310 may be used with either tool 200 or 232, wherein the lumen-forming member 206 is in the same plane as the shaft 202, as shown in FIGS. 52B and 53B. The spacing member 310 may have a bend near the distal end of the spacer member spacing member shaft 304 that allows the spacer 302 to bend into the plane of the longitudinal axis of the shaft 202, and the indentations 308 of the spacer 302 would be aligned with the lumen-forming tip 212.

In another alternative embodiment, the spacing member 310 may be used with tool 200. The spacing member 310 may be configured to have a bend to allow the spacer 302 to bend into the plane of the lumen-forming arm 210 and the piercing tip 212. In addition, the spacer 302 may also be movably connected to the spacing member shaft 304 through a pivot joint, wherein the disk-like member of the spacer 302 may be tilted out of the plane of the spacing member shaft 304 to allow for adjusting the distance between the plate 214 and the spacer 302 when positioning the tool 200 onto the articular processes 20, 22.

Referring to FIG. 60, one method of use for the tool 300 comprises placing one lumen-forming tip 212 against an exposed articular process 22 of a superior vertebra 236, placing the other lumen-forming tip 212 against the corresponding articular process 20 of the inferior vertebra 238, and positioning the spacer 302 between the articular processes 20 and 22. The handle 204 of the tool 232 is held while the actuator 222 is rotated. Rotation motion of the actuator 222 is transferred to the control rod 224 as a linear motion away from the actuator 222 via the threaded connection. This movement of the control rod 234 is transferred to the lumen-forming members 206 via the link members 226 and pivot pins 228, 230 as a pinching motion where the piercing tips 212 approach each other through the bone of the articular processes 20, 22. Movement of the lumen-forming tips 212 continues until they pierce through the articular processes 20 and 22 and make contact with the indentations 308 to form a curved or non-linear passageway 234. In embodiments where the spacer has a hole instead of indentations, the lumen-forming tips 212 moves until they meet at an intermediate position to form a curved or non-linear passageway 234 through the articular processes 20, 22.

Although the embodiment depicted in FIGS. 59A to 60 have lumen-forming members that pivot in equal amounts, one of skill in the art will understand that the configuration may be modified to move in differently. In one specific embodiment, only one lumen-forming member moves while the other member is fixed in position. One of skill in the art will also recognize that other movements of the control rod, link members and lumen-forming members are not limited to pivoting or angular movements. Alternate embodiments of the tool 300 may include similar alternate structures as described for tool 200 above and with reference to FIGS. 52A-58G.

In some embodiments of the either tool 200, 232 or 300, the movement of the lumen-forming members 206 and/or plate 214 can be effected by manual force applied by a person, such as by his or her hands, or alternatively it can be supplied or supplemented with a motor, pneumatics, hydraulics, springs, and/or magnetics. A movable grip may be used to manipulate and actuate the lumen-forming members of the tool. The grip may be designed for rotational, pivoting linear relative movement, or combination thereof, depending on the mechanical advantage that may be needed to

facilitate movement of the lumen-forming arm(s) and piercing through the articular processes. One embodiment of the tool may comprise a squeeze handle for actuating the tool. In other embodiments, the tool comprises an actuator with a switch or trip mechanism. Movement of the lumen-forming tips can be effected with coaxial shafts, non-coaxial shafts, wires, rods, springs, hydraulics, gas cylinder, piston, gears, motor, electrical signal, magnetics, or other suitable means for communicating a signal or transferring movement or providing the closing force. Other embodiments of the tool include closing mechanisms that include compound leverage, ratcheting, and/or multistep closing.

The size of the tool is appropriate for drilling the particular bone in the way that is desired. Smaller devices can be used for smaller vertebra and larger devices for larger vertebra. In addition, the device can be use on bones other than the vertebra and on bones for humans and non-humans. Other applications of the tool are for creating anchor points in bone for sutures and for bone immobilization such as with pins.

Other means of attaching the actuator to the inner shaft or other movement-transmitting member such that a movement of the actuator results in a desired corresponding movement of the inner shaft are possible and are considered within the scope of the invention.

The tool can be made of any appropriate material for the particular part. Exemplary materials include, but are not limited to, stainless steel, surgical steel, cutlery steel, tool steel, cobalt and its alloys, nickel and its alloys, chromium and its alloys, titanium and its alloys, zirconium and its alloys, aluminum and its alloys, magnesium and its alloys, polymers, elastomers, and ceramics. Ceramics may include, but are not limited to silicon carbide, silicon oxide(s), silicon nitride, aluminum oxide, alumina, zirconia, tungsten carbide, other carbides.

Other embodiments of the invention comprise a method of forming a passageway in the articular processes of the vertebra using a facet lumen-forming tool described herein. The method may comprise placing the lumen-forming tips of the facet lumen-forming against a pair of articular processes of the vertebra, and actuating the lumen-forming member(s). Another embodiment may comprise placing the lumen-forming tip and plate of the single-arm facet lumen-forming against the articular processes of the vertebra, and actuating the lumen-forming.

A further embodiment of the invention is a method of anchoring or restraining a prosthesis between the facet joints of the vertebra comprising forming a curved lumen through the articular processes with the facet lumen-forming tool described herein, positioning a facet joint implant into the facet joint associated with the articular processes and inserting an anchoring member through the curved lumen.

While embodiments of this invention have been particularly shown and described with references to embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the scope of the invention. For all of the embodiments described above, the steps of the methods need not be performed sequentially.

What is claimed is:

1. A device for forming a lumen in a bone, comprising: a shaft member comprising a proximal section and a distal section; a first lumen-forming member and a second lumen-forming member, the first lumen-forming member rotatably coupled to the distal section, the first lumen-

forming member comprising a first piercing tip and the second lumen-forming member comprising a second piercing tip;

a control rod extending at least partially through the shaft member, the control rod coupled to the first lumen-forming member;

wherein linear motion of the control rod is transferred to the first lumen-forming member as a pinching motion, and

wherein the first lumen-forming member moves until it meets the second lumen-forming member at an intermediate position to form a curved or non-linear passageway, wherein the first lumen-forming member is movable and the second lumen-forming member is fixed.

2. The device for forming a lumen as in claim 1, wherein the first lumen-forming member is joined to the control rod by a link member.

3. The device for forming a lumen as in claim 2, wherein the link member is coupled to the control rod with a first pivot pin and the link member is coupled to the first lumen-forming member with a second pivot pin.

4. The device for forming a lumen as in claim 1, further comprising an actuator.

5. The device for forming a lumen as in claim 4, wherein rotation of the actuator is transferred to the control rod as linear motion.

6. The device for forming a lumen as in claim 4, wherein the actuator is threaded.

7. A device for forming a lumen in a bone, comprising: a tubular shaft member comprising a proximal section, a distal section, and a central lumen;

a first lumen-forming member and a second lumen-forming member, the first lumen-forming member rotatable about a fixed point of the tubular shaft, the first lumen-forming member comprising a first piercing tip and the second lumen-forming member comprising a second piercing tip;

an actuator;

a control rod extending through the tubular shaft member at least partially within the central lumen, the control rod coupled to the actuator, the first lumen-forming member and the second lumen-forming member; and

wherein linear motion of the control rod is transferred to the first lumen-forming member and the second lumen-forming member as a pinching motion wherein the piercing tips contact each other, where the piercing tips contact each other through a hole in a spacer.

8. The device for forming a lumen as in claim 7, further comprising a link member, wherein the link member is coupled to the control rod with a first pivot pin and the link member is coupled to the first lumen-forming member with a second pivot pin.

9. The device for forming a lumen as in claim 8, further comprising a second link member, wherein the second link member is coupled to the control rod with a third pivot pin and the second link member is coupled to the second lumen-forming member with a fourth pivot pin.

10. The device for forming a lumen as in claim 7, wherein the first lumen-forming member and the second lumen-forming member pivot in equal amounts relative to the distal section.

11. The device for forming a lumen as in claim 7, wherein rotation of the actuator is transferred to the control rod as linear motion.

12. The device for forming a lumen as in claim 7, wherein the actuator is threaded.

25

13. A device for forming a lumen in a bone, comprising:
a shaft member comprising a proximal section and a distal
section;

a first lumen-forming member and a second lumen-
forming member, the first lumen-forming member and 5
the second lumen-forming member coupled to the
distal section at a fixed point, the first lumen-forming
member comprising a first piercing tip and the second
lumen-forming member comprising a second piercing
tip;

a control rod assembly extending at least partially through
the shaft member, the control rod assembly comprising
a control rod, a first link member, and second link
member; and

wherein the control rod is coupled to the first link member 15
and the second link member, wherein the first lumen-
forming member is coupled to the first link member,
and wherein the second lumen-forming member is
coupled to the second link member, and wherein linear
motion of the control rod is transferred to the first

26

lumen-forming member and the second lumen-forming
member as a pinching motion where the piercing tips
move until they meet at an intermediate position to
form a curved or non-linear passageway, where the
piercing tips move until they meet at the intermediate
position through a hole in a spacer.

14. The device for forming a lumen as in claim 13,
wherein the first and second lumen-forming members pivot
in equal amounts relative to the distal section.

10 15. The device for forming a lumen as in claim 13, further
comprising an actuator.

16. The device for forming a lumen as in claim 15,
wherein rotation of the actuator is transferred to the control
rod as linear motion.

15 17. The device for forming a lumen as in claim 15,
wherein the actuator is threaded.

18. The device for forming a lumen as in claim 13,
wherein the first link member and the second link member
are coupled to the control rod with pivot pins.

* * * * *