

(12) **United States Patent**  
**Bai**

(10) **Patent No.:** **US 9,750,377 B2**  
(45) **Date of Patent:** **Sep. 5, 2017**

(54) **FOAM GENERATOR**

(71) Applicant: **Peter Bai**, Placentia, CA (US)

(72) Inventor: **Peter Bai**, Placentia, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 61 days.

(21) Appl. No.: **14/973,534**

(22) Filed: **Dec. 17, 2015**

(65) **Prior Publication Data**

US 2017/0172357 A1 Jun. 22, 2017

(51) **Int. Cl.**  
**A47K 5/14** (2006.01)  
**A47K 5/12** (2006.01)  
**B05B 7/00** (2006.01)  
**B05B 11/00** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **A47K 5/14** (2013.01); **A47K 5/1211** (2013.01); **B05B 7/0037** (2013.01); **B05B 11/3001** (2013.01); **B05B 11/3047** (2013.01); **B05B 11/3087** (2013.01)

(58) **Field of Classification Search**  
CPC .... **A47K 5/14**; **A47K 5/1211**; **B05B 11/3047**; **B05B 11/3087**; **B05B 11/3001**; **B05B 7/0037**  
USPC ..... **222/190**  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,443,569 A 8/1995 Uehira  
5,445,288 A 8/1995 Banks  
6,082,586 A \* 7/2000 Banks ..... **A47K 5/14**  
222/105  
2005/0224519 A1 \* 10/2005 Law ..... **B05B 7/0025**  
222/190

\* cited by examiner


*Primary Examiner* — Donnell Long

(74) *Attorney, Agent, or Firm* — Clement Cheng

(57) **ABSTRACT**

A foam generator includes a container having a liquid. The container includes a container neck. A bubble generator is mounted to the container. The bubble generator has a liquid piston and an air piston that are mechanically connected together to simultaneously dispense the liquid and a flow of air. The liquid piston extends into the container as a bubble generator input stem. The liquid is received into the bubble generator input stem at a liquid piston intake of the bubble generator input stem. The air piston and the liquid piston feed both air and liquid to a mixing chamber that provides both air and liquid to a pair of mixing screens mounted on a bubble generator output stem. The bubble generator output stem is oriented below the bubble generator input stem. An inverted straw cover fits over the liquid piston intake of the input stem.

**16 Claims, 4 Drawing Sheets**






Fig. 1




Fig. 2




Fig. 3




Fig. 4





Fig. 5






Fig. 7



**1****FOAM GENERATOR****FIELD OF THE INVENTION**

The present invention is in the field of foam generators.

**DISCUSSION OF RELATED ART**

a variety of different foam generators have been used for generating large numbers of bubbles, such as U.S. Pat. No. 6,082,586 by inventor Stuart Banks issued Jul. 4, 2000, entitled liquid dispenser for dispensing foam, the disclosure of which is incorporated herein by reference.

The banks reference provides for a foam generator that has a flexible seal for an air pump chamber. The air seal is angled outwardly toward a first enclosure member and engaging a first enclosure member.

**SUMMARY OF THE INVENTION**

A foam generator includes a container having a liquid. The container includes a container neck. A bubble generator is mounted to the container. The bubble generator has a liquid piston and an air piston that are mechanically connected together to simultaneously dispense the liquid and a flow of air. The liquid piston extends into the container as a bubble generator input stem. The liquid is received into the bubble generator input stem at a liquid piston intake of the bubble generator input stem. The air piston and the liquid piston feed both air and liquid to a mixing chamber that provides both air and liquid to a pair of mixing screens mounted on a bubble generator output stem. The bubble generator output stem is oriented below the bubble generator input stem. An inverted straw cover fits over the liquid piston intake of the input stem. The inverted straw cover has an inverted straw cover fluid channel that draws liquid from the container upward beginning at an inverted straw liquid intake located below the liquid piston intake of the bubble generator input stem.

Preferably, the foam generator has a nozzle removably mounted over the output stem for directing a flow of generated foam downward. An air gap cavity can be formed at an upper end of the inverted straw cover. The inverted straw cover fluid channel is formed on a protruding ridge, and the protruding ridge is regularly oriented and extends from an inverted straw cover shoulder. The annular fluid collection trough is located around the bubble generator input stem below a level of the inverted straw liquid intake. The annular fluid collection trough is formed between a conical toroid inside trough wall and a conical toroid diagonal trough wall.

The foam generator has a conical toroid diagonal trough wall that is generally diagonally oriented and a conical toroid inside trough wall that is generally vertically oriented. A locking sleeve locks the bubble generator to the container. Latching rim slots formed on an upper edge of the bubble generator locking sleeve define fingers that hook to the foam generator. The locking sleeve latching rim is formed as a triangular plastic hook that hooks onto a bubble generator external sidewall upper edge.

**BRIEF DESCRIPTION OF THE DRAWINGS**

FIG. 1 is a perspective view of the foam generator present invention.

FIG. 2 is a bottom view of the present invention.

FIG. 3 is a front view of the present invention.

**2**

FIG. 4 is a top view of the present invention.

FIG. 5 is a side view of the present invention.

FIG. 6 is a front cross-section view of the present invention sectioned at a bisecting plane shown as section line x defined on FIG. 5.

FIG. 7 is an exploded view of the present invention.

The following callout list of elements can be a useful guide in referencing the elements of the drawings.

- 10 foam generator
- 11 container
- 12 container shoulder
- 13 container neck
- 14 bubble generator locking sleeve
- 15 bubble generator
- 16 nozzle cover
- 17 container side
- 18 container crumple fold area indent
- 19 nozzle
- 21 inverted straw cover
- 22 inverted straw cover tip
- 23 inverted straw cover flange
- 24 protruding ridge
- 25 air gap
- 26 inverted straw cover fluid channel
- 31 bubble generator output stem
- 32 bubble generator input stem
- 33 inlet ball valve
- 41 air piston
- 51 liquid piston
- 52 inverted straw liquid intake
- 53 liquid piston spring
- 54 liquid piston intake
- 55 liquid piston compressor
- 56 liquid piston exit valve
- 57 liquid piston exit opening
- 58 liquid piston valve shaft
- 61 locking sleeve latching rim
- 62 locking sleeve lower flange
- 63 nozzle flange
- 64 nozzle tip
- 65 bubble generator thread
- 66 locking sleeve interface
- 67 container thread
- 68 locking sleeve latching groove
- 69 latching rim slots
- 71 mixing screens
- 72 mixing chamber
- 73 air intake valve
- 74 air intake flapper
- 75 air intake opening
- 81 neck ring
- 82 bubble generator external sidewall upper edge
- 83 inverted straw cover shoulder
- 84 bubble generator external sidewall
- 85 bubble generator external sidewall lower edge
- 86 conical toroid inside trough wall
- 87 conical toroid diagonal trough wall
- 88 annular fluid collection trough
- 89 undissolved solids

**DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT**

The foam generator 10 has a container 11 with a generally hollow body that can be watertight and hold liquids such as foam liquid soap and bubble soap. The soap can have vitamin E and moisturizer in it as well as a variety of



different scented fragrances such as lavender and rosemary. The container has a container shoulder **12** defining a rectangular prism from which a container neck **13** extends. The container neck can be integrally formed with the main container body that is generally formed as a rectangular prism. The container can be made of plastic. A bubble generator locking sleeve **14** secures a bubble generator **15** to the threaded portion of the container neck. A nozzle cover **16** covers the nozzle of the bubble generator. The container has a container side **17**. A plurality of container sides can form various faces of the container body. Some of the container sides have a container crumple fold area indent **18** for allowing collapsibility of the container as the container is emptied.

An inverted straw cover **21** has an inverted straw cover tip **22**. The inverted straw also has an inverted straw cover flange **23**. The inverted straw cover tip points up and is at an opposite end of the inverted straw cover flange. The inverted straw cover flange extends away from the inverted straw cover at a lower edge of the inverted straw cover. The inverted straw cover optionally includes a protruding ridge **24**. The protruding ridge allows liquid to be received into the inverted straw cover. The air gap **25** is located above the protruding ridge and can receive any air that collects in the inverted straw cover. The protruding ridge houses an inverted straw cover fluid channel **26** which can be formed as a passage through the protruding ridge. Optionally, the inverted straw cover fluid channel **26** can be formed as a gap between the inverted straw cover and the bubble generator to which the inverted straw cover is attached. The inverted straw cover receives a flow of fluid that passes from the container to the inverted straw cover fluid channel, and then to the bubble generator. The inverted straw cover optionally is formed with an inverted straw cover shoulder **83** that has an inside surface that fits onto the bubble generator input stem **32**. The inverted straw cover **21** can be formed as a plastic cover that acts as a straw for drawing liquid starting from a bottom portion of the container **11**. The liquid is drawn upward through the straw to the liquid piston intake **54**. The liquid piston **51** can be coaxial to the straw such that the straw covers or encapsulates at least a portion of the liquid piston **51**.

The bubble generator has a bubble generator output stem **31** that is below a bubble generator input stem **32**. The inverted straw cover **21** fits over the bubble generator input stem **32** in an interference fit, or a partially threaded connection. The bubble generator input stem **32** preferably includes an inlet ball valve **33** that receives fluid into the input stem, but does not allow fluid to exit from the input stem. The inlet ball valve can be a plastic floating ball, or a metal ball. The inlet ball valve ball can be biased by a spring such as a helical spring.

An air piston **41** receives air from an air intake. The air piston is mechanically coordinated to move simultaneously with the liquid piston **51**. As the air piston moves with the liquid piston, both pistons draw air and liquid in a drawing phase and then expel air and liquid in an expulsion phase. In the drawing phase, liquid passes into the inverted straw liquid intake **52** formed as an opening on the inverted straw cover **21**. The inverted straw liquid intake **52** is above an excess reservoir that collects waste fluid. The liquid piston has a liquid piston spring **53** that biases the liquid piston from a retracted position to an extended position to provide a spring bias for mechanically inducing the drawing phase. The liquid piston spring draws air as well as liquid since the air piston and liquid piston are mechanically connected. A liquid piston intake **54** receives fluid into the liquid piston

and the liquid piston intake is directly above the inlet ball valve **33**. The liquid piston has a liquid piston compressor **55**. The liquid piston compressor pushes the liquid out of the liquid piston exit valve **56**. The liquid piston exit valve **56** is mounted over a liquid piston exit opening **57** and is a one-way valve just like the intake ball valve is a one-way valve. The liquid piston exit valve **56** can be connected to a liquid piston valve shaft **58** that abuts a portion of the liquid piston **51** after traveling a certain distance. Thus, changing a length of the liquid piston valve shaft **58** can provide a calibration of the amount of air and liquid being dispensed.

As described above, the bubble generator locking sleeve **14** fits over the entire bubble generator **15** to lock it to the container and provide a tamper-resistant seal. The bubble generator locking sleeve **14** preferably has a locking sleeve latching rim **61** that can have a triangular hook end biased over an external surface of the bubble generator such as over the bubble generator external sidewall **84**. The locking sleeve lower flange **62** extends outward as an annular ring that can allow the foam generator to be mounted to a dispenser such as a wall-mounted bathroom manual push dispenser for example. When mounted on a standard dispenser, the nozzle **19** is preferably fitted with a nozzle flange **63** near or immediately above the nozzle tip **64**. The nozzle flange **63** can be pressed against the locking sleeve lower flange **62**.

The nozzle tip **64** can be made removable to provide ease of cleaning the nozzle tip. The bubble generator external sidewall **84** is at an external surface of the bubble generator. The bubble generator external sidewall **84** has an internal bubble generator thread **65** that engages container thread **67** formed on the container **11**. The bubble generator locking sleeve **14** fits over the bubble generator external sidewall **84** so that rotation of the bubble generator locking sleeve **14** slides a smooth inside surface of the sleeve along a smooth bubble generator external sidewall **84** so that manual turning does not allow rotation of the bubble generator away from the container thread **67** after the bubble generator locking sleeve **14** is snap fitted over the bubble generator external sidewall **84**. The locking sleeve interface **66** is a smooth bubble generator locking sleeve **14** that can freely rotate around the bubble generator external sidewall **84** as a rotating bearing.

The locking sleeve engages on a locking sleeve latching groove **68**. The locking sleeve latching rim **61** has triangular cross section plastic hooks that have a pointed tip for biasing into the locking sleeve latching groove **68**. The latching rim has latching rim slots **69** that segment the locking sleeve latching rim **61** into a plurality of fingers that engage onto the locking sleeve latching groove **68**. The container **11** has a neck ring **81**. The neck ring **81** cooperates with the bubble generator external sidewall upper edge **82** to form a locking sleeve latching groove **68** between them.

A variety of different mixing screens **71** receives a flow of liquid and air simultaneously from the air piston **41** and the liquid piston **51**. The flow of liquid and air are received in the mixing chamber **72** and then pushed through the mixing screens to create a multitude of bubbles sufficient for forming foam. The air intake valve **73** can be formed near the mixing chamber **72** and can be mounted on an air intake opening covered by an air intake flapper **74** that acts as a one-way valve for receiving air into the mixing chamber **72**. The mixing chamber **72** has air that can pass into the air piston **41**. The air intake flapper **74** can be made as a thin plastic or rubber sheet that allows air to enter through an air intake opening **75**, but does not allow air to exit through the air intake opening **75**. In this way, the pump continuously



5

produces foam in a reciprocating manner when a user depresses the nozzle flange upward either manually or via a dispenser mechanism. A dispenser mechanism can be wall-mounted such as on a bathroom wall for convenience.

The bubble generator preferably has a bubble generator external sidewall **84** that has a bubble generator external sidewall lower edge **85** at a lower edge of the bubble generator external sidewall **84** and a bubble generator external sidewall upper edge **82** at an upper edge of the bubble generator external sidewall. The bubble generator lower edge **85** and bubble generator external sidewall upper edge **82** are both preferably covered by the bubble generator locking sleeve **14**.

Near the inverted straw liquid intake **52** at the beginning of the container neck **13**, a conical toroid inside trough wall **86** meets with a conical toroid diagonal trough wall **87** to form an annular fluid collection trough **88** that can collect undissolved solids **89**. The annular fluid collection trough **88** is ring-shaped around the inverted straw liquid intake **52** and is formed around the liquid piston **51**. The liquid piston **51** can be adapted for receiving liquid soap such as liquid foam soap. The annular fluid collection trough **88** has a downwardly pointing tip that is located below the inverted straw liquid intake **52**. A separation zone is created between the annular fluid collection trough and the inverted straw liquid intake.

As can be seen from the above description and drawings, the objects of the invention are at least twofold, namely first to provide an annular fluid collection trough **88** to collect any undissolved solids **89** that may form or be introduced in the liquid stored in the container **11** to prevent them from jamming the bubble mechanism. Also, secondly, the locking sleeve latching rim retains the bubble generator tightly to the neck of the container to provide a tamper-resistant seal.

The locking sleeve latching rim is preferably formed with a locking sleeve latching groove that is located immediately above the locking sleeve latching rim. The locking sleeve latching groove is preferably rectangular in configuration for receiving a connection to a dispenser body.

The invention claimed is:

**1.** A foam generator comprising:

a container having a liquid, wherein the container includes a container neck;

a bubble generator mounted to the container, wherein the bubble generator has a liquid piston and an air piston that are mechanically connected together to simultaneously dispense the liquid and a flow of air, wherein the liquid piston extends into the container as a bubble generator input stem, wherein the liquid is received into the bubble generator input stem at a liquid piston intake of the bubble generator input stem, wherein the air piston and the liquid piston feed both air and liquid to a mixing chamber that provides both air and liquid to a pair of mixing screens mounted on a bubble generator output stem, wherein the bubble generator output stem is oriented below the bubble generator input stem;

an inverted straw cover fitting over the liquid piston intake of the input stem, wherein the inverted straw cover has an inverted straw cover fluid channel that

6

draws liquid from the container upward beginning at an inverted straw liquid intake located below the liquid piston intake of the bubble generator input stem; and a locking sleeve locking the bubble generator to the container, wherein the locking sleeve comprises a locking sleeve latching rim that is formed as a triangular plastic hook that hooks onto a bubble generator external sidewall upper edge.

**2.** The foam generator of claim **1**, further including a nozzle removably mounted over the output stem, for directing a flow of generated foam downward.

**3.** The foam generator of claim **1**, further including an air gap cavity formed at an upper end of the inverted straw cover.

**4.** The foam generator of claim **1**, wherein the inverted straw cover fluid channel is formed on a protruding ridge, wherein the protruding ridge extends from an inverted straw cover shoulder.

**5.** The foam generator of claim **1**, further including an annular fluid collection trough located around the bubble generator input stem below a level of the inverted straw liquid intake.

**6.** The foam generator of claim **5**, wherein the annular fluid collection trough is formed between a conical toroid inside trough wall and a conical toroid diagonal trough wall.

**7.** The foam generator of claim **6**, wherein the conical toroid diagonal trough wall is generally diagonally oriented.

**8.** The foam generator of claim **6**, wherein the conical toroid inside trough wall is generally vertically oriented.

**9.** The foam generator of claim **6**, wherein the conical toroid diagonal trough wall is generally diagonally oriented and, wherein the conical toroid inside trough wall is generally vertically oriented.

**10.** The foam generator of claim **1**, further comprising: a plurality of latching rim slots formed on an upper edge of the bubble generator locking sleeve.

**11.** The foam generator of claim **1**, further including a nozzle removably mounted over the output stem, for directing a flow of generated foam downward.

**12.** The foam generator of claim **1**, further including an air gap cavity formed at an upper end of the inverted straw cover.

**13.** The foam generator of claim **1**, wherein the inverted straw cover fluid channel is formed on a protruding ridge, wherein the protruding ridge extends from an inverted straw cover shoulder.

**14.** The foam generator of claim **1**, further including an annular fluid collection trough located around the bubble generator input stem below a level of the inverted straw liquid intake.

**15.** The foam generator of claim **14**, wherein the annular fluid collection trough is formed between a conical toroid inside trough wall and a conical toroid trough wall.

**16.** The foam generator of claim **15**, wherein the conical toroid diagonal trough wall is generally diagonally oriented.

\* \* \* \* \*