

US009750607B2

(12) **United States Patent**
Ganesan et al.

(10) **Patent No.:** **US 9,750,607 B2**
(45) **Date of Patent:** **Sep. 5, 2017**

(54) **SYSTEMS AND METHODS FOR HEART VALVE THERAPY**

(71) Applicant: **Caisson Interventional, LLC**, Maple Grove, MN (US)

(72) Inventors: **Kavitha Ganesan**, Maple Grove, MN (US); **Ramji T. Venkatasubramanian**, Maple Grove, MN (US); **Andrew T. Forsberg**, Plymouth, MN (US); **Cyril J. Schweich, Jr.**, Maple Grove, MN (US); **Todd J. Mortier**, Mound, MN (US); **Erik O. Martz**, Bloomington, MN (US); **Douglas J. Krone**, Rogers, MN (US)

(73) Assignee: **Caisson Interventional, LLC**, Maple Grove, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 174 days.

(21) Appl. No.: **14/674,349**

(22) Filed: **Mar. 31, 2015**

(65) **Prior Publication Data**
US 2016/0113768 A1 Apr. 28, 2016

Related U.S. Application Data
(63) Continuation of application No. 14/673,055, filed on Mar. 30, 2015, which is a continuation of application No. 14/671,577, filed on Mar. 27, 2015.
(Continued)

(51) **Int. Cl.**
A61F 2/24 (2006.01)

(52) **U.S. Cl.**
CPC **A61F 2/2448** (2013.01); **A61F 2/2403** (2013.01); **A61F 2/2409** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC ... **A61F 2/2403**; **A61F 2/2409**; **A61F 2/2412**; **A61F 2/2418**; **A61F 2/2427**; **A61F 2/243**;
(Continued)

(56) **References Cited**
U.S. PATENT DOCUMENTS
4,680,031 A 7/1987 Alonso
5,423,887 A 6/1995 Love et al.
(Continued)


FOREIGN PATENT DOCUMENTS
EP 350302 1/1990
EP 0592410 4/1994
(Continued)

OTHER PUBLICATIONS
US 9,532,869, 01/2017, Quadri et al. (withdrawn)
(Continued)

Primary Examiner — Ryan J Severson
(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(57) **ABSTRACT**
Prosthetic mitral valves described herein can be deployed using a transcatheter mitral valve delivery system and technique to interface and anchor in cooperation with the anatomical structures of a native mitral valve. This document describes prosthetic heart valve designs that interface with native mitral valve structures to create a fluid seal, thereby minimizing mitral regurgitation and paravalvular leaks. This document also describes prosthetic heart valve designs and techniques to manage blood flow through the left ventricular outflow tract. In addition, this document describes prosthetic heart valve designs and techniques that reduce the risk of interference between the prosthetic valves and chordae tendineae.

16 Claims, 29 Drawing Sheets



Related U.S. Application Data					
		7,785,364	B2	8/2010	Styrc
		7,837,727	B2 *	11/2010	Goetz A61F 2/2418 623/1.15
(60)	Provisional application No. 62/067,907, filed on Oct. 23, 2014.	7,896,915	B2	3/2011	Guyenot et al.
		7,914,569	B2	3/2011	Nguyen et al.
		7,935,144	B2	5/2011	Robin et al.
(52)	U.S. Cl.	7,947,072	B2	5/2011	Yang et al.
	CPC <i>A61F 2/2436</i> (2013.01); <i>A61F 2/2439</i>	7,947,075	B2	5/2011	Goetz et al.
	(2013.01); <i>A61F 2/2418</i> (2013.01); <i>A61F</i>	7,959,672	B2	6/2011	Salahieh et al.
	<i>2230/0078</i> (2013.01); <i>A61F 2250/0063</i>	7,981,153	B2	7/2011	Fogarty et al.
	(2013.01)	7,988,725	B2	8/2011	Gross et al.
(58)	Field of Classification Search	8,016,882	B2	9/2011	Macoviak et al.
	CPC <i>A61F 2/2433</i> ; <i>A61F 2/2436</i> ; <i>A61F 2/2439</i> ;	8,025,695	B2	9/2011	Fogarty et al.
	<i>A61F 2/2448</i>	8,048,153	B2	11/2011	Salahieh et al.
	See application file for complete search history.	8,052,749	B2	11/2011	Salahieh et al.
		8,055,360	B2	11/2011	Park et al.
		8,057,540	B2	11/2011	Letac et al.
		8,062,355	B2	11/2011	Figulla et al.
(56)	References Cited	8,092,518	B2	1/2012	Schreck
	U.S. PATENT DOCUMENTS	8,092,521	B2	1/2012	Figulla et al.
		8,092,524	B2	1/2012	Nugent et al.
		8,123,801	B2	2/2012	Milo
		8,133,270	B2	3/2012	Kheradvar et al.
		8,142,492	B2	3/2012	Forster et al.
		8,157,852	B2	4/2012	Bloom et al.
		8,157,853	B2	4/2012	Laske et al.
		8,163,011	B2	4/2012	Rankin
		8,172,898	B2	5/2012	Alferness et al.
		8,182,528	B2	5/2012	Salahieh et al.
		8,182,530	B2	5/2012	Huber
		8,206,437	B2	6/2012	Bonhoeffer et al.
		8,231,670	B2	7/2012	Salahieh et al.
		8,236,049	B2	8/2012	Rowe et al.
		8,246,677	B2	8/2012	Ryan
		8,252,051	B2	8/2012	Chau et al.
		8,262,724	B2	9/2012	Seguin et al.
		8,273,120	B2	9/2012	Dolan
		8,277,502	B2	10/2012	Miller et al.
		8,282,051	B2	10/2012	Nutaro et al.
		8,287,591	B2	10/2012	Keidar et al.
		8,292,938	B2	10/2012	Case
		8,308,796	B2	11/2012	Lashinski et al.
		8,308,798	B2	11/2012	Pintor et al.
		8,317,858	B2	11/2012	Straubinger et al.
		8,323,332	B2	12/2012	Agnew
		8,323,335	B2	12/2012	Rowe et al.
		8,348,998	B2	1/2013	Pintor et al.
		8,403,983	B2	3/2013	Quadri et al.
		8,449,599	B2	5/2013	Chau et al.
		8,454,686	B2	6/2013	Alkhatib
		8,460,366	B2	6/2013	Rowe
		8,500,798	B2	8/2013	Rowe et al.
		8,512,398	B2	8/2013	Alkhatib
		8,512,399	B2 *	8/2013	Lafontaine A61F 2/2418 623/2.11
		7,217,287	B2	5/2007	Wilson et al.
		7,252,682	B2	8/2007	Seguin
		7,320,704	B2	1/2008	Lashinski et al.
		7,329,278	B2	2/2008	Seguin et al.
		7,381,218	B2	6/2008	Schreck
		7,381,220	B2	6/2008	Macoviak et al.
		7,393,360	B2	7/2008	Spenser et al.
		7,442,204	B2	10/2008	Schwammenthal et al.
		7,503,930	B2	3/2009	Sharkawy et al.
		7,510,575	B2	3/2009	Spenser et al.
		7,524,330	B2	4/2009	Berrekouw
		7,524,331	B2	4/2009	Birdsall
		7,578,843	B2	8/2009	Shu
		7,585,321	B2	9/2009	Cribier
		7,597,711	B2	10/2009	Drews et al.
		7,618,446	B2	11/2009	Andersen et al.
		7,625,403	B2	12/2009	Krivoruchko
		7,632,308	B2	12/2009	Loulmet
		7,708,775	B2	5/2010	Rowe et al.
		7,717,955	B2	5/2010	Lane et al.
		7,722,666	B2 *	5/2010	Lafontaine A61F 2/2418 623/2.11
		7,727,276	B2	6/2010	Machiraju
		7,748,389	B2	7/2010	Salahieh et al.
		7,776,083	B2	8/2010	Vesely
		7,780,725	B2	8/2010	Haug et al.
		8,852,272	B2	10/2014	Gross et al.
		8,858,620	B2	10/2014	Salahieh et al.
		8,840,662	B2	9/2014	Salahieh et al.
		8,840,663	B2	9/2014	Salahieh et al.
		8,845,720	B2 *	9/2014	Conklin A61F 2/2412 623/2.14

(56)

References Cited

U.S. PATENT DOCUMENTS

			2001/0021872	A1	9/2001	Bailey et al.	
			2002/0151970	A1	10/2002	Garrison et al.	
			2003/0130726	A1	7/2003	Thorpe et al.	
			2004/0210307	A1*	10/2004	Khairkhahan	A61F 2/2403 623/2.18
8,870,948	B1	10/2014	Erzberger et al.				
8,870,949	B2	10/2014	Rowe				
8,876,895	B2	11/2014	Tuval et al.				
8,894,702	B2	11/2014	Quadri et al.				
8,911,493	B2	12/2014	Rowe et al.				
8,926,690	B2	1/2015	Kovalsky				
8,926,691	B2	1/2015	Chau et al.				
8,932,358	B1	1/2015	Nehls				
8,961,595	B2	2/2015	Alkhatib				
8,968,395	B2	3/2015	Hauser et al.				
8,986,370	B2	3/2015	Annest				
8,986,373	B2	3/2015	Chau et al.				
9,005,277	B2	4/2015	Pintor et al.				
9,005,278	B2	4/2015	Pintor et al.				
9,017,399	B2	4/2015	Gross et al.				
9,023,100	B2	5/2015	Quadri et al.				
9,034,032	B2	5/2015	McLean et al.				
9,034,033	B2	5/2015	McLean et al.				
9,039,757	B2	5/2015	McLean et al.				
9,039,759	B2	5/2015	Alkhatib et al.				
9,050,188	B2	6/2015	Schweich et al.				
9,066,801	B2	6/2015	Kovalsky et al.				
9,072,604	B1	7/2015	Melnick et al.				
9,084,676	B2	7/2015	Chau et al.				
9,132,006	B2	9/2015	Spenser et al.				
9,155,617	B2	10/2015	Carpentier et al.				
9,168,130	B2*	10/2015	Straubinger	A61F 2/2418			
9,168,133	B2	10/2015	Spenser et al.				
9,173,738	B2	11/2015	Murray, III et al.				
9,192,466	B2	11/2015	Kovalsky et al.				
9,226,826	B2	1/2016	Rust				
9,241,792	B2	1/2016	Benichou et al.				
9,248,016	B2*	2/2016	Oba	A61F 2/2418			
9,259,315	B2	2/2016	Zhou et al.				
9,265,631	B2*	2/2016	Straubinger	A61F 2/2418			
9,289,293	B2	3/2016	Murad et al.				
9,295,547	B2	3/2016	Costello et al.				
9,295,548	B2	3/2016	Drews et al.				
9,295,550	B2	3/2016	Nguyen et al.				
9,301,843	B2	4/2016	Richardson et al.				
9,301,863	B2	4/2016	Punga et al.				
9,331,328	B2	5/2016	Eberhardt et al.				
9,339,377	B2	5/2016	Quadri et al.				
9,339,378	B2	5/2016	Quadri et al.				
9,339,379	B2	5/2016	Quadri et al.				
9,339,380	B2	5/2016	Quadri et al.				
9,339,382	B2	5/2016	Tabor et al.				
9,345,573	B2	5/2016	Nyuli et al.				
9,358,111	B2	6/2016	Spence et al.				
9,370,423	B2	6/2016	Ryan				
9,370,424	B2	6/2016	Call et al.				
9,375,311	B2	6/2016	Gloss et al.				
9,387,071	B2	7/2016	Tuval et al.				
9,402,719	B2	8/2016	Lane et al.				
9,402,721	B2	8/2016	Buchbinder et al.				
9,414,913	B2	8/2016	Beith et al.				
9,414,918	B2	8/2016	Chau et al.				
9,433,503	B2	9/2016	Tsukashima et al.				
9,439,757	B2	9/2016	Wallace et al.				
9,456,896	B2	10/2016	Quadri et al.				
9,468,525	B2	10/2016	Kovalsky				
9,480,556	B2	11/2016	Reuelta et al.				
9,480,559	B2	11/2016	Vidlund et al.				
9,486,306	B2	11/2016	Tegels et al.				
9,492,273	B2	11/2016	Wallace et al.				
9,510,946	B2	12/2016	Chau et al.				
9,522,062	B2	12/2016	Tuval				
9,532,870	B2	1/2017	Cooper et al.				
9,554,903	B2	1/2017	Rowe et al.				
9,561,100	B2	2/2017	Pintor et al.				
9,561,103	B2	2/2017	Granada et al.				
9,572,662	B2	2/2017	Morriss et al.				
9,579,194	B2	2/2017	Elizondo et al.				
9,579,196	B2	2/2017	Morriss et al.				
2001/0007956	A1	7/2001	Letac et al.				
			2005/0137689	A1	6/2005	Salahieh et al.	
			2005/0137690	A1	6/2005	Salahieh et al.	
			2005/0165479	A1	7/2005	Drews et al.	
			2006/0235509	A1*	10/2006	Lafontaine	A61F 2/2418 623/2.11
			2007/0027533	A1	2/2007	Douk	
			2007/0168024	A1*	7/2007	Khairkhahan	A61F 2/2403 623/2.18
			2008/0004697	A1	1/2008	Lichtenstein et al.	
			2008/0015671	A1	1/2008	Bonhoeffer	
			2008/0086164	A1	4/2008	Rowe	
			2008/0103586	A1	5/2008	Styrc et al.	
			2008/0140189	A1	6/2008	Nguyen et al.	
			2008/0183273	A1*	7/2008	Mesana	A61F 2/2418 623/1.11
			2008/0221672	A1	9/2008	Lamphere et al.	
			2009/0005863	A1	1/2009	Goetz et al.	
			2009/0216310	A1*	8/2009	Straubinger	A61F 2/2418 623/1.15
			2009/0216312	A1*	8/2009	Straubinger	A61F 2/2418 623/1.16
			2010/0049315	A1	2/2010	Kirson	
			2010/0100173	A1	4/2010	Lafontaine	
			2010/0161036	A1*	6/2010	Pintor	A61F 2/2418 623/1.26
			2010/0217382	A1	8/2010	Chau et al.	
			2010/0249894	A1*	9/2010	Oba	A61F 2/2418 623/1.11
			2010/0249908	A1*	9/2010	Chau	A61F 2/2418 623/1.26
			2010/0262232	A1	10/2010	Annest	
			2010/0280606	A1	11/2010	Naor	
			2010/0298931	A1	11/2010	Quadri et al.	
			2010/0312333	A1	12/2010	Navia et al.	
			2010/0331972	A1*	12/2010	Pintor	A61F 2/2409 623/2.11
			2011/0004296	A1	1/2011	Lutter et al.	
			2011/0022168	A1	1/2011	Cartledge	
			2011/0040374	A1*	2/2011	Goetz	A61F 2/2418 623/2.11
			2011/0137397	A1	6/2011	Chau et al.	
			2011/0137410	A1	6/2011	Hacohen	
			2011/0166636	A1	7/2011	Rowe	
			2011/0208293	A1	8/2011	Tabor	
			2011/0218619	A1	9/2011	Benichou et al.	
			2011/0224785	A1	9/2011	Hacohen	
			2011/0245911	A1	10/2011	Quill et al.	
			2011/0257721	A1	10/2011	Tabor	
			2011/0282438	A1	11/2011	Drews et al.	
			2011/0295363	A1	12/2011	Girard et al.	
			2011/0301702	A1	12/2011	Rust et al.	
			2011/0319988	A1	12/2011	Schankereli et al.	
			2011/0319989	A1	12/2011	Lane et al.	
			2012/0010697	A1	1/2012	Shin et al.	
			2012/0016464	A1	1/2012	Seguin	
			2012/0035722	A1	2/2012	Tuval	
			2012/0053675	A1	3/2012	Borock	
			2012/0059458	A1	3/2012	Buchbinder et al.	
			2012/0078357	A1*	3/2012	Conklin	A61F 2/2412 623/2.18
			2012/0101571	A1	4/2012	Thambar et al.	
			2012/0136430	A1	5/2012	Sochman et al.	
			2012/0310328	A1	12/2012	Olson et al.	
			2013/0053949	A1*	2/2013	Pintor	A61F 2/2418 623/2.18
			2013/0079869	A1*	3/2013	Straubinger	A61F 2/2418 623/1.26
			2013/0090725	A1*	4/2013	Pintor	A61F 2/2409 623/2.11
			2013/0116777	A1*	5/2013	Pintor	A61F 2/2409 623/2.11
			2013/0172992	A1	7/2013	Gross et al.	
			2013/0184811	A1	7/2013	Rowe et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

2013/0211508 A1 8/2013 Lane et al.
 2013/0282110 A1 10/2013 Schweich et al.
 2013/0282114 A1 10/2013 Schweich et al.
 2013/0304200 A1 11/2013 McLean et al.
 2013/0345799 A1* 12/2013 Lafontaine A61F 2/2418
 623/2.11
 2014/0005778 A1 1/2014 Buchbinder et al.
 2014/0012372 A1 1/2014 Chau et al.
 2014/0012373 A1 1/2014 Chau et al.
 2014/0039611 A1 2/2014 Lane et al.
 2014/0052237 A1 2/2014 Lane et al.
 2014/0200662 A1 7/2014 Eftel et al.
 2014/0214156 A1 7/2014 Navia et al.
 2014/0222136 A1 8/2014 Geist et al.
 2014/0228946 A1 8/2014 Chau et al.
 2014/0236291 A1 8/2014 Schweich et al.
 2014/0257467 A1 9/2014 Lane et al.
 2014/0316516 A1 10/2014 Vidlund
 2014/0343669 A1 11/2014 Lane et al.
 2014/0358223 A1 12/2014 Rafiee et al.
 2014/0364943 A1* 12/2014 Conklin A61F 2/2412
 623/2.11
 2015/0039083 A1 2/2015 Rafiee
 2015/0094802 A1 4/2015 Buchbinder et al.
 2015/0112433 A1 4/2015 Schweich et al.
 2015/0127096 A1 5/2015 Rowe et al.
 2015/0142103 A1 5/2015 Vidlund
 2015/0150678 A1 6/2015 Brecker
 2015/0157458 A1 6/2015 Thambar et al.
 2015/0173897 A1 6/2015 Raanani et al.
 2015/0196390 A1 7/2015 Ma et al.
 2015/0216656 A1* 8/2015 Pintor A61F 2/2418
 623/2.11
 2015/0216657 A1 8/2015 Braido
 2015/0216660 A1* 8/2015 Pintor A61F 2/2409
 623/2.11
 2015/0238312 A1 8/2015 Lashinski
 2015/0238313 A1 8/2015 Spence et al.
 2015/0265402 A1 9/2015 Centola et al.
 2015/0320553 A1 11/2015 Chau et al.
 2015/0327995 A1 11/2015 Morin et al.
 2015/0327996 A1 11/2015 Fahim et al.
 2015/0327999 A1 11/2015 Board et al.
 2015/0335421 A1 11/2015 Figulla et al.
 2015/0342733 A1 12/2015 Alkhatib et al.
 2015/0351906 A1 12/2015 Hammer et al.
 2015/0359629 A1 12/2015 Ganesan et al.
 2016/0000564 A1 1/2016 Buchbinder et al.
 2016/0008131 A1 1/2016 Christianson et al.
 2016/0022417 A1 1/2016 Karapetian et al.
 2016/0045307 A1 2/2016 Yohanan et al.
 2016/0045309 A1 2/2016 Valdez et al.
 2016/0051362 A1 2/2016 Cooper et al.
 2016/0074160 A1 3/2016 Christianson et al.
 2016/0106539 A1 4/2016 Buchbinder et al.
 2016/0120646 A1 5/2016 Dwork et al.
 2016/0158000 A1 6/2016 Granada et al.
 2016/0158001 A1 6/2016 Wallace et al.
 2016/0158003 A1 6/2016 Wallace et al.
 2016/0184095 A1 6/2016 Spence et al.
 2016/0193044 A1 7/2016 Achiluzzi
 2016/0199180 A1 7/2016 Zeng et al.
 2016/0220364 A1* 8/2016 Straubinger A61F 2/2418
 2016/0228251 A1 8/2016 Nyuli et al.
 2016/0235529 A1 8/2016 Ma et al.
 2016/0242906 A1 8/2016 Morriss et al.
 2016/0270917 A1 9/2016 Tuval et al.
 2016/0310268 A1 10/2016 Oba et al.
 2016/0317290 A1 11/2016 Chau et al.
 2016/0317304 A1 11/2016 Spence et al.
 2016/0324631 A1 11/2016 Lane et al.
 2016/0324633 A1 11/2016 Gross et al.
 2016/0331523 A1 11/2016 Chau et al.
 2016/0331531 A1 11/2016 Quadri et al.
 2016/0331534 A1 11/2016 Buchbinder et al.

2016/0338826 A1 11/2016 Chau et al.
 2016/0338829 A1 11/2016 Call et al.
 2016/0346080 A1 12/2016 Righini et al.
 2016/0354203 A1 12/2016 Tuval et al.
 2016/0354204 A1 12/2016 Braido et al.
 2016/0361162 A1 12/2016 Richter et al.
 2016/0361163 A1 12/2016 Yohanan et al.
 2016/0374801 A1 12/2016 Jiminez et al.
 2017/0007398 A1 1/2017 Drews et al.
 2017/0049564 A1 2/2017 Board et al.
 2017/0056162 A1 3/2017 Harewood
 2017/0056163 A1 3/2017 Tayeb et al.
 2017/0056166 A1 3/2017 Ratz et al.
 2017/0056176 A1 3/2017 Rowe et al.

FOREIGN PATENT DOCUMENTS

EP 592410 4/1994
 EP 705081 10/2001
 EP 1338255 8/2003
 EP 825841 10/2003
 EP 833595 10/2003
 EP 910313 11/2003
 EP 910314 11/2003
 EP 0910314 11/2003
 EP 1006949 10/2004
 EP 1233731 12/2004
 EP 1251803 6/2005
 EP 2674130 6/2005
 EP 1267753 10/2005
 EP 830112 11/2005
 EP 1171059 11/2005
 EP 1328215 11/2005
 EP 1318775 11/2006
 EP 1474077 2/2007
 EP 1143882 12/2007
 EP 1180987 8/2008
 EP 1237509 12/2008
 EP 1562522 12/2008
 EP 2000115 12/2008
 EP 1330213 3/2009
 EP 1610727 4/2009
 EP 1343438 7/2009
 EP 2078498 7/2009
 EP 1684667 8/2009
 EP 1408850 9/2009
 EP 1653888 9/2009
 EP 1049425 11/2009
 EP 1703865 2/2010
 EP 1682048 3/2010
 EP 1509171 6/2010
 EP 1968491 7/2010
 EP 1176913 10/2010
 EP 1465554 12/2010
 EP 1940321 12/2010
 EP 2258312 12/2010
 EP 1441672 9/2011
 EP 2160150 10/2011
 EP 1603493 12/2011
 EP 2399549 12/2011
 EP 2399550 12/2011
 EP 1788984 2/2012
 EP 2055266 2/2012
 EP 2420205 2/2012
 EP 1621162 5/2012
 EP 2138132 6/2012
 EP 2476394 7/2012
 EP 2124824 10/2012
 EP 2088965 11/2012
 EP 2526895 11/2012
 EP 2526898 11/2012
 EP 2526899 11/2012
 EP 2529696 12/2012
 EP 2529697 12/2012
 EP 2529698 12/2012
 EP 2529699 12/2012
 EP 2537487 12/2012
 EP 1919397 1/2013
 EP 2015709 1/2013

(56)

References Cited

FOREIGN PATENT DOCUMENTS

EP	1750622	2/2013
EP	2257242	2/2013
EP	2260796	2/2013
EP	1701668	3/2013
EP	2260797	3/2013
EP	2340075	3/2013
EP	2260798	6/2013
EP	2626040	8/2013
EP	1758523	9/2013
EP	2073756	10/2013
EP	2109417	11/2013
EP	2477555	12/2013
EP	1838241	2/2014
EP	1926455	4/2014
EP	2405966	4/2014
EP	2257243	5/2014
EP	2316381	5/2014
EP	2745805	6/2014
EP	2117469	7/2014
EP	2124826	7/2014
EP	2258316	7/2014
EP	2749254	7/2014
EP	1667604	8/2014
EP	2211779	8/2014
EP	2772228	9/2014
EP	2142143	11/2014
EP	2815723	12/2014
EP	2815724	12/2014
EP	2815725	12/2014
EP	2254515	1/2015
EP	1465555	5/2015
EP	2068767	7/2015
EP	1702247	8/2015
EP	1729688	8/2015
EP	2262447	8/2015
EP	2901966	8/2015
EP	1804686	9/2015
EP	2675396	9/2015
EP	1734903	10/2015
EP	2254513	10/2015
EP	2544626	10/2015
EP	2926766	10/2015

EP	2926767	10/2015
EP	1748745	12/2015
EP	1755459	12/2015
EP	1850796	12/2015
EP	1991168	1/2016
EP	2254512	1/2016
EP	2263609	1/2016
EP	2012712	2/2016
EP	1585463	3/2016
EP	2170416	3/2016
EP	2278944	3/2016
EP	1871300	4/2016
EP	2572676	4/2016
EP	2626041	4/2016
EP	2237746	5/2016
EP	2582326	5/2016
EP	2618784	5/2016
EP	1734902	6/2016
EP	1906884	6/2016
EP	2190379	6/2016
EP	2416739	6/2016
EP	2572675	6/2016
WO	WO 2005/062980	7/2005
WO	WO 2009/155561	12/2009
WO	WO 2011/109813	9/2011
WO	WO 2011/119101	9/2011
WO	WO 2012/103204	8/2012

OTHER PUBLICATIONS

European Search Report in European Application No. 15170546.4, dated Apr. 12, 2016, 7 pages.
 U.S. Appl. No. 61/266,774, filed Dec. 16, 2009, Chau et al.
 U.S. Appl. No. 61/287,099, filed Dec. 4, 2009, Chau et al.
 Supplementary European Search Report in European Application No. 13778768, dated Jan. 12, 2016, 7 pages.
 International Search Report and Written Opinion in International Application No. PCT/US2015/056935, dated Feb. 12, 2016, 14 pages.
 International Preliminary Report on Patentability in International Application No. PCT/US2015/035303, dated Dec. 15, 2016, 10 pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9






FIG. 10






FIG. 12B




FIG. 11B




FIG. 13




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 38

FIG. 37




FIG. 39






FIG. 40



SYSTEMS AND METHODS FOR HEART VALVE THERAPY

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 14/673,055 filed Mar. 30, 2015, which is a continuation of U.S. patent application Ser. No. 14/671,577 filed Mar. 27, 2015, which claims the benefit of U.S. Application Ser. No. 62/067,907, filed Oct. 23, 2014. The disclosure of the prior application is considered part of and is incorporated by reference in the disclosure of this application.

TECHNICAL FIELD

This document relates to prosthetic heart valves, such as prosthetic mitral valves that can be implanted using transcatheter techniques.

BACKGROUND

The long-term clinical effect of valve regurgitation is recognized as a significant contributor to cardiovascular related morbidity and mortality. Thus, for many therapies intended to treat the mitral valve, one primary goal is to significantly reduce or eliminate regurgitation. By eliminating the regurgitation at the mitral valve, the destructive volume overload effects on the left ventricle can be attenuated. The volume overload of mitral regurgitation (MR) relates to the excessive kinetic energy required during isotonic contraction to generate overall stroke volume in an attempt to maintain forward stroke volume and cardiac output. It also relates to the pressure potential energy dissipation of the leaking valve during the most energy-consuming portion of the cardiac cycle, isovolumetric contraction. Additionally, therapies for MR reduction can have the effect of reducing the elevated pressures in the left atrium and pulmonary vasculature reducing pulmonary edema (congestion) and shortness of breath symptomatology. Such therapies for MR reduction may also have a positive effect on the filling profile of the left ventricle (LV) and the restrictive LV physiology that can result with MR. These pathophysiologic issues indicate the potential benefits of MR therapy, but also indicate the complexity of the system and the need for a therapy to focus beyond the MR level or grade.

Some therapies for treating MR may worsen other (non-MR) existing pathologic conditions or create new pathologic conditions. One of the conditions to be managed is mitral stenosis or creation of an inflow gradient. That is, if a prosthetic valve system is used that does not allow for sufficient LV inflow without elevated filling pressures, then some benefits of MR reduction may be dissipated or lost. An additional condition to be managed is left ventricular outflow tract (LVOT) obstruction or creation of high LVOT pressure gradients. That is, if a prosthetic valve system is used that does significantly obstructs the LVOT, then some benefits of MR reduction may be dissipated or lost. Also, if the procedure results in damage to atrial tissue at surgery, it can increase the likelihood of the negative physiologic effect of atrial fibrillation. Further, some prosthetic valve systems may increase the risk of higher LV wall stress through an increase in LV size (LV geometry). Due to the integral relationship of the mitral valve with LV geometry through the papillary and chordal apparatus, LV wall stress levels can

be directly affected resulting in alterations of LV filling and contraction mechanics. Accordingly, in some circumstances, a prosthetic valve system that worsens the geometry of the LV can counter the benefits of MR reduction because of the alteration of contractile physiology.

SUMMARY

This document describes prosthetic heart valves, such as prosthetic mitral valves that can be implanted using transcatheter techniques. For example, some embodiments of a transcatheter mitral valve delivery system and method described herein can be deployed to interface and anchor in cooperation with the native anatomical structures of a mitral valve. In addition, this document describes prosthetic heart valve systems that interface with native mitral valve structures to create a fluid seal, thereby minimizing MR and paravalvular leaks after implantation. Further, this document describes prosthetic heart valve systems and techniques that, in particular embodiments, are configured to manage blood flow through the left ventricular outflow tract (LVOT) and to thereby reduce the risk of full or partial blockages of the LVOT. In addition, some embodiments of the prosthetic heart valve systems and techniques described herein may be configured to reduce the risk of interference between the prosthetic valves and chordae tendineae of the native mitral valve leaflets, which can advantageously facilitate or preserve the geometry of the LV.

Particular embodiments described herein include a mitral valve replacement system for a heart. The system may include an expandable anchor assembly configured to implant at a native mitral valve, and the expandable anchor assembly may include a first expandable frame that is adjustable from a delivery condition to an expanded condition. The system may also include a first delivery sheath device having a distal end insertable into a left atrium and being configured to express the anchor assembly out from the distal end such that the anchor assembly expands within the left atrium to the expanded condition. Optionally, the system may further include a pusher instrument releasably attachable to the expandable anchor frame and being configured to longitudinally advance the anchor assembly within the left atrium towards an annulus of the native mitral valve while the anchor assembly is in the expanded condition. Also, the system may include an artificial valve assembly comprising a second expandable frame that is adjustable from a compressed condition to a deployed condition to selectively engage with the anchor assembly while the anchor assembly is in the expanded condition.

Some embodiments described herein include a method for deploying a prosthetic mitral valve system within a native mitral valve of a patient. The method may include navigating a first delivery sheath within the patient such that a distal end of the first delivery sheath is positioned within a left atrium. The method may also include expressing an anchor assembly of the prosthetic heart valve system from the distal end of the first delivery sheath such that the anchor assembly at least partially expands while located within the left atrium. Further, the method may include, after expressing the anchor assembly within the left atrium, moving the anchor assembly towards an annulus of the native mitral valve.

Various embodiments described herein include a prosthetic mitral valve system. The system may include a valve assembly, which may include a frame member defining an outer profile and an interior frame member space, and an occluder disposed within the interior frame member space.

The occluder may have an open configuration and a closed configuration. The frame member comprises a proximal end frame portion and a distal end frame portion. Optionally, an outer periphery of the distal end frame portion may include a generally flat region and a generally round region, and at least some portions of the generally flat region may extend toward the interior frame member space.

Particular embodiments described herein include a method of using a prosthetic mitral valve system. The method may include advancing a valve assembly of the prosthetic mitral valve system toward an annulus of a native mitral valve. Optionally, the valve assembly may include a frame member defining an outer profile and an interior frame member space, and occluder disposed within the interior frame member space. The frame member may include a proximal end frame portion and a distal end frame portion. An outer periphery of the distal end frame portion may optionally include a generally flat region and a generally round region, and at least some portions of the generally flat region extend toward the interior frame member space. The method may also include anchoring the valve assembly at the native mitral valve such that the generally flat region is adjacent to an anterior native leaflet of the native mitral valve.

Some embodiments described herein include a prosthetic mitral valve system that is implantable at a native mitral valve. The prosthetic mitral valve system may include an anchor assembly defining an interior anchor assembly space and longitudinal axis. The anchor assembly may include an expandable anchor frame including a hub and a sub-annular support arm extending from the hub. The sub-annular support arm may extend to an anchor foot having a surface configured for engagement with a sub-annular gutter of the native mitral valve. The system may further include a valve assembly that includes an expandable valve frame defining an outer profile and an interior frame member space, and an occluder disposed within the interior frame member space. The valve assembly may be releasably engageable with the anchor assembly within the interior anchor assembly space. Optionally, a distance measured parallel to the longitudinal axis from a distal-most end of the anchor assembly to the surface is at least 14 millimeters.

Various embodiments described herein include a method of using a prosthetic mitral valve system. The method may include advancing an anchor assembly of the prosthetic mitral valve system toward an annulus of a native mitral valve. The anchor assembly may an interior anchor assembly space and longitudinal axis, and the anchor assembly may include an expandable anchor frame including a hub and one or more sub-annular support arms extending from the hub. Each of the one or more sub-annular support arm may extend to an anchor foot configured to engage with a sub-annular gutter of the native mitral valve. The method may further include engaging the anchor assembly of the prosthetic mitral valve system with tissue proximate the native mitral valve such that each anchor foot is engaged with the sub-annular gutter, and (optionally) such that the hub is positioned distal of the distal-most area of coaptation between anterior and post leaflets of the native mitral valve.

Particular embodiments described herein include a method of sealing between a prosthetic mitral valve system and native leaflets of a mitral valve. The method may include anchoring an anchor assembly of the prosthetic mitral valve system with tissue proximate to an annulus of a native mitral valve. Optionally, the anchor assembly defines an interior anchor assembly space and longitudinal axis, and the anchor assembly may include an expandable anchor frame includ-

ing a hub and one or more sub-annular support arms extending from the hub. Each of the one or more sub-annular support arm may extend to an anchor foot that engages with a sub-annular gutter of the native mitral valve. The method may further include delivering a valve assembly of the prosthetic mitral valve system to engage with the anchor assembly. Optionally, the valve assembly may include: an expandable valve frame defining an outer profile and an interior frame member space, a tissue layer disposed over at least a portion of the outer profile, and an occluder disposed within the interior frame member space. The tissue layer of the valve assembly can abut with native leaflets of the mitral valve while each anchor foot of the anchor assembly is engaged with the sub-annular gutter.

Some embodiments described herein include a prosthetic mitral valve system. The system may include an anchor assembly comprising an expandable anchor frame and a set of sub-annular anchor feet configured to engage with a sub-annular gutter of the native mitral valve. The system may further include a valve assembly that includes: an expandable valve frame defining an outer profile and an interior frame member space, a tissue layer disposed over at least a portion of the outer profile, and an occluder mounted within the interior frame member space. Optionally, an outwardly facing periphery of the tissue layer along the valve assembly is positioned to abut native leaflets of the mitral valve when the set of anchor feet of the anchor assembly is engaged with the sub-annular gutter.

Various embodiments described herein include a method for deploying a prosthetic mitral valve system within a native mitral valve of a patient. The method may comprise navigating a delivery sheath such that a distal end of the delivery sheath is positioned within a left atrium of the patient. Also, the method may include expressing, in the left atrium, an anchor assembly of the prosthetic mitral valve system. A distal pusher instrument may be releasably engaged with the anchor assembly. The method may further include engaging the anchor assembly with the native mitral valve while the distal pusher instrument remains engaged with the anchor assembly. The method may also include expressing, in the left atrium, a valve assembly of the prosthetic mitral valve system. Optionally, the valve assembly may slidably engaged with an exterior of the distal pusher instrument. The method may further include moving the valve assembly into an interior space defined by the anchor assembly. The moving may optionally include sliding the valve assembly along the exterior of the distal pusher catheter while the distal pusher catheter remains engaged with to the anchor assembly. The method may also include, after moving the valve assembly, mounting the valve assembly with the anchor assembly. Further, the method may include, after mounting the valve assembly, decoupling the distal pusher instrument from the anchor assembly.

Particular embodiments described herein include an implantable medical device delivery system. The system may include a first deflectable catheter defining a first lumen therethrough, and a distal end portion of the first deflectable catheter may be controllably laterally deflectable. The system may also include a first device delivery sheath slidably disposable within the first lumen, and the first device delivery sheath may define a second lumen therethrough. The system may further include a first device control sheath slidably disposable within the second lumen, and the first device control sheath may define a third lumen therethrough and one or more first device control wire lumens. The system may also include a second deflectable catheter slidably disposable within the third lumen, and the second deflect-

5

able catheter may define a fourth lumen therethrough. A distal end portion of the second deflectable catheter may be controllably laterally deflectable. The system may further include a device pusher catheter slidably disposable within the fourth lumen, and the device pusher catheter may define a fifth lumen therethrough. A distal end portion of the device pusher catheter may be configured to releasably couple with a first implantable medical device.

Some embodiments described herein include a method for deploying a prosthetic mitral valve system within a native mitral valve of a patient. The method may include expanding an anchor assembly of the prosthetic heart valve system within a left atrium, while the anchor assembly is releasably secured to a first delivery catheter, such that the anchor assembly at least partially expands while located within the left atrium. The method may optionally include, after expressing the anchor assembly within the left atrium, panning or rotating the anchor assembly within the left atrium by articulating a tip portion of the first delivery catheter.

Various embodiments described herein include a method for deploying a prosthetic mitral valve system within a native mitral valve of a patient. The method may include expressing a valve assembly of the prosthetic heart valve system within a left atrium, while the valve assembly is releasably secured to a valve delivery catheter, such that the valve assembly at least partially expands while located within the left atrium. The method may optionally include, after expressing the valve assembly within the left atrium, panning or rotating the valve assembly within the left atrium by articulating a tip portion of the valve delivery catheter.

Some or all of the embodiments described herein may provide one or more of the following advantages. First, some embodiments of the prosthetic mitral valve systems provided herein can be used in a completely percutaneous/transcatheter mitral replacement procedure that is safe, reliable, and repeatable by surgeons of a variety of different skill levels. For example, in some implementations the prosthetic mitral valve system can establish a reliable and consistent anchor/substrate to which the valve/occluder structure subsequently engages. Thus, the prosthetic mitral valve system can be specifically designed to make use of the geometry/mechanics of the native mitral valve to create sufficient holding capability. In one particular aspect, the anatomical gutter found below a native mitral valve annulus can be utilized as a site for anchoring the prosthetic mitral valve system, yet the anchoring structure can be deployed in a manner that maintains native leaflet function of the mitral valve, thereby providing the ability to completely separate and stage the implantation of the components of the prosthetic mitral valve system. Accordingly, some embodiments of the prosthetic mitral valve systems described herein are configured to be implanted in a reliable, repeatable, and simplified procedure that is broadly applicable to a variety of patients and physicians, while also employing a significantly less invasive method.

Second, some embodiments of the prosthetic mitral valve systems described herein facilitate effective long lasting MR reduction without creating negative physiologic consequences to the cardiopulmonary system (heart, lungs, peripheral vasculature) including stenosis, LV wall stress, and atrial fibrillation. Also, the system may provide a safe and durable anchoring effect at the native mitral valve to provide an effective mitral regurgitation therapy as well as providing structures that provide sealing benefits and avoid significant impairment of the chordal interface of the native mitral valve leaflets.

6

Third, in particular embodiments, the prosthetic mitral valve system can be delivered to the native mitral valve using a technique in which an expandable frame of the anchor component is at least partially expanded in the left atrium prior to reaching the mitral valve location. As such, in addition to facilitating the delivery of the anchor, the heart surgeon or other user can visualize the expanded component (and its orientation) within the heart before it is advanced to the annulus of the mitral valve (thereby permitting the user the opportunity to laterally pivot (rotate, pan, re-orient) the expanded component prior to reaching the annulus).

Fourth, some embodiments of the prosthetic mitral valve systems described herein can be configured to partially extend into the left ventricle after implantation, yet may include a profile shape that is configured to reduce the likelihood of obstructing blood flow through the LVOT. Accordingly, even though some portions of the prosthetic mitral valve systems extend into the left atrium above the mitral valve annulus (supra-annular) and other portions extend into the left ventricle below the mitral valve annulus (sub-annular), the prosthetic mitral valve system is designed to account for the natural LVOT and thereby reduce the risk of full or partial blockages of the LVOT.

Fifth, in particular embodiments, the prosthetic mitral valve system can include two different expandable components (e.g., an anchor assembly and a valve assembly) that are separately delivered to the implantation site, and both components can abut and engage with native heart tissue at the mitral valve. For example, the first component (e.g., the anchor assembly) can be configured to engage with the heart tissue that is at or proximate to the annulus of the native mitral valve, and the second component (e.g., the valve assembly) can be configured to provide a seal interface with native valve leaflets of the mitral valve.

The details of one or more embodiments of the invention are set forth in the accompanying drawings and the description below. Other features, objects, and advantages of the invention will be apparent from the description and drawings, and from the claims.

DESCRIPTION OF DRAWINGS

FIG. 1 is a perspective view of a portion of a prosthetic mitral valve deployment system in a cross-sectional view of a native human heart, in accordance with some embodiments.

FIG. 2 shows a perspective view of a prosthetic mitral valve anchor assembly in the left atrium of the heart after the anchor assembly has emerged from an anchor delivery sheath of the deployment system of FIG. 1.

FIG. 3 shows a perspective view of the anchor assembly of FIG. 2 after being rotated in the left atrium so as to orient the anchor assembly generally perpendicular to the native mitral valve.

FIG. 4 shows a perspective view of the anchor assembly of FIG. 3 after being partially advanced through the native mitral valve so as to position projections of the anchor assembly below a sub-annular gutter of the native mitral valve.

FIG. 5 shows a perspective view of the anchor assembly in a similar arrangement as shown in FIG. 4, but in a commissural cross-sectional view of the heart (from the left side of the heart).

FIG. 6 shows a perspective view of the anchor assembly of FIG. 5 after being retracted so as to position the projections of the anchor assembly in the sub-annular gutter of the native mitral valve.

FIG. 7 shows a perspective view of the anchor assembly of FIG. 6 after the retraction of some members of the deployment system.

FIG. 8 is a top view of a native mitral valve and depicts a gutter perimeter of the sub-annular gutter of FIG. 7 (without the anchor assembly).

FIG. 9 shows a perspective top view of an example anchor assembly of FIGS. 2-6 in accordance with some embodiments.

FIG. 10 shows a perspective view of the anchor assembly of FIG. 9 with a covering material disposed on portions of the anchor frame.

FIG. 11A shows a perspective top view of the anchor assembly of FIG. 9 implanted within a native mitral valve (with the native mitral valve leaflets in a closed state), and FIG. 11B shows a corresponding anatomical top view of the anchor assembly of FIG. 11A.

FIG. 12A shows a perspective top view of the anchor assembly of FIG. 9 implanted within the native mitral valve of FIG. 11A (with the native mitral valve leaflets in an open state), and FIG. 12B shows a corresponding anatomical top view of the anchor assembly of FIG. 12A.

FIG. 13 shows a perspective view of the anchor assembly of FIG. 7 implanted within the native mitral valve and a valve assembly delivery sheath extending into the left atrium.

FIG. 14 shows a perspective view of a valve assembly in the left atrium after partial emergence from the valve assembly delivery sheath of FIG. 13. The valve assembly is configured in a first (partially expanded) arrangement.

FIG. 15 shows a perspective view of the valve assembly of FIG. 14 with the valve deployment system being manipulated in preparation for the installation of the valve assembly into the anchor assembly.

FIG. 16 shows a perspective view of the valve assembly of FIG. 15 (while still in the first (partially expanded) arrangement) being positioned within the anchor assembly.

FIG. 17 shows a perspective view of the valve assembly of FIG. 16 the valve assembly expanded within the anchor assembly and detached from the deployment system.

FIG. 18 shows an anterior side view of a valve frame of a valve assembly of FIG. 17, in accordance with some embodiments.

FIG. 19 shows a bottom view of the valve frame of FIG. 18.

FIG. 20 is an exploded posterior side view of an anchor assembly and valve assembly of FIG. 17, in accordance with some embodiments.

FIG. 21 is a top view of an example prosthetic mitral valve system that includes a valve assembly engaged with an anchor assembly, in accordance with some embodiments.

FIG. 22 is a bottom view of the example prosthetic mitral valve system of FIG. 21.

FIG. 23 shows a top view of the prosthetic mitral valve system of FIG. 21 implanted within a native mitral valve. The occluder portion of prosthetic mitral valve system is shown in a closed state.

FIG. 24 shows a top view of the prosthetic mitral valve system of FIG. 21 implanted within a native mitral valve. The occluder portion of the prosthetic mitral valve system is shown in an open state.

FIG. 25 is a lateral cross-sectional top view of a heart showing the mitral, aortic, tricuspid and pulmonary valves.

FIG. 26 is a schematic diagram of a cross-section of a native mitral valve including the mitral valve annulus.

FIG. 27 is an anterior side view of a valve assembly, in accordance with some embodiments. A sealing region of the anterior side of the valve assembly is demarcated on the valve assembly.

FIG. 28 is a posterior side view of a valve assembly, in accordance with some embodiments. A sealing region of the posterior side of the valve assembly is demarcated on the valve assembly.

FIG. 29 is a lateral side view of a valve assembly, in accordance with some embodiments. A sealing region of the lateral side of the valve assembly is demarcated on the valve assembly.

FIG. 30 is a schematic depiction of an anterior portion of a valve assembly in relationship to the annulus of the native mitral valve.

FIG. 31 is a schematic depiction of a commissural region portion of a valve assembly in relationship to the annulus of the native mitral valve.

FIG. 32 is a schematic depiction of a posterior portion of a valve assembly in relationship to the annulus of the native mitral valve.

FIG. 33 is a cross-sectional view of the left side of a heart showing an example valve assembly in relationship to the annulus of the native mitral valve and the annulus of the aortic root.

FIG. 34 is a fluoroscopic image of a native mitral valve with an example prosthetic valve therein, an aortic valve, and a left ventricular outflow track of a heart. The image also shows blood flowing from the left ventricle to the aorta through the left ventricular outflow track.

FIG. 35 is another fluoroscopic image of a native mitral valve with an example prosthetic valve therein, an aortic valve, and a left ventricular outflow track of a heart. The image also shows blood flowing from the left ventricle to the aorta through the left ventricular outflow track.

FIG. 36 is a schematic depiction of the annulus of the native mitral valve and the annulus of the aortic root.

FIG. 37 is a commissural cross-sectional view of a heart showing an anchor assembly of a prosthetic mitral valve engaged in the sub-annular gutter of the native mitral valve. Chordae tendineae in the left ventricle are also depicted.

FIG. 38 is a lateral cross-section of a left ventricle of a heart showing an anchor assembly of a prosthetic mitral valve engaged in the sub-annular gutter of the native mitral valve. Chordae tendineae in the left ventricle are also depicted.

FIG. 39 is a perspective view of an anchor assembly showing control wires that are threaded through portions of the anchor assembly.

FIG. 40 is another perspective view of an anchor assembly showing control wires that are threaded through portions of the anchor assembly.

FIG. 41 is a side view of a valve assembly frame showing control wires that are threaded through portions of the valve assembly frame.

FIG. 42 is a schematic diagram of a threading pattern of a proximal control wire corresponding to the valve assembly frame embodiment of FIG. 41.

FIG. 43 is a schematic diagram of a threading pattern of a mid-body control wire corresponding to the valve assembly frame embodiment of FIG. 41.

Like reference symbols in the various drawings indicate like elements.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

This disclosure describes embodiments of a prosthetic heart valve system, such as prosthetic mitral valve systems,

and transcatheter systems and methods for implanting prosthetic heart valve systems. In some embodiments, the prosthetic mitral valve system can be deployed to interface and anchor in cooperation with the native anatomical structures of a mitral valve (and, optionally, in a manner that permits the continued natural function of the chordae tendineae of the native mitral valve leaflets even after the anchor component is deployed). As described herein, the prosthetic mitral valve system can be deployed in a manner that interfaces with native mitral valve structures to create a fluid seal, thereby minimizing MR and paravalvular leaks after implantation. As described in more detail below, FIGS. 1-17 and 39-43 describe a transcatheter mitral valve delivery system and method by which the prosthetic mitral valve system can be deployed to interface and anchor in cooperation with the anatomical structures of a native mitral valve. Also, in FIGS. 18-32, prosthetic mitral valve features are described by which the prosthetic valves interface with native mitral valve structures to create a fluid seal, thereby reducing the likelihood of MR and paravalvular leaks. In FIGS. 33-36, prosthetic mitral valve features and techniques are described for managing blood flow through the left ventricular outflow tract (LVOT). In FIGS. 37-38, prosthetic mitral valve features and techniques are described for reducing the risk of interference between the prosthetic valves and chordae tendineae.

Referring to FIG. 1, an example transcatheter mitral valve delivery system 100 can be navigated through a patient's vasculature to obtain access to the patient's heart 10. The transcatheter delivery system 100 facilitates implantation of a prosthetic mitral valve in a beating heart 10 using a percutaneous, vessel cutdown, or minimally invasive technique (without open-chest surgery). In some implementations, the transcatheter delivery system 100 is used in conjunction with one or more imaging modalities such as x-ray fluoroscopy, echocardiography, magnetic resonance imaging, computed tomography (CT), and the like.

The heart 10 (depicted in cross-section from a posterior perspective) includes a right atrium 12, a right ventricle 14, a left atrium 16, and a left ventricle 18. A tricuspid valve 13 separates the right atrium 12 from the right ventricle 14. A mitral valve 17 separates the left atrium 16 from the left ventricle 18. An atrial septum 15 separates the right atrium 12 from the left atrium 16. An inferior vena cava 11 is confluent with the right atrium 12. It should be understood that this depiction of the heart 10 is somewhat stylized. The same is true for FIGS. 2-4. FIGS. 1-4 provide general depictions of the approach to the mitral valve 17 that is used in some implementations. But, the commissural cross-sectional views of FIG. 5 and thereafter more accurately depict the orientation of the prosthetic mitral valves in relation to the heart 10.

In the depicted embodiment, the delivery system 100 includes a guidewire 110, a primary deflectable catheter 120, and an anchor delivery sheath 130. Additional components of the delivery system 100 will be described further below. The anchor delivery sheath 130 is slidably (and rotationally) disposed within a lumen of the primary deflectable catheter 120. The guidewire 110 is slidably disposed within a lumen of the anchor delivery sheath 130. In this depiction, the anchor delivery sheath 130 has been partially extended relative to the primary deflectable catheter 120, allowing a flared portion 132 to expand outward, as described further below.

In the depicted implementation, the guidewire 110 is installed into the heart 10 prior to the other components of the delivery system 100. In some embodiments, the guide-

wire 110 has a diameter of about 0.035 inches (about 0.89 mm). In some embodiments, the guidewire 110 has a diameter in a range of about 0.032 inches to about 0.038 inches (about 0.8 mm to about 0.97 mm). In some embodiments, the guidewire 110 has a diameter smaller than 0.032 inches (about 0.80 mm) or larger than 0.038 inches (about 0.97 mm). In some embodiments, the guidewire 110 is made of materials such as, but not limited to, nitinol, stainless steel, high-tensile-strength stainless steel, and the like, and combinations thereof. The guidewire 110 may include various tip designs (e.g., J-tip, straight tip, etc.), tapers, coatings, covers, radiopaque (RO) markers, and other features.

In some implementations, the guidewire 110 is percutaneously inserted into a femoral vein of the patient. The guidewire 110 is routed to the inferior vena cava 11 and into the right atrium 12. After creating an opening in the atrial septum 15 (e.g., a trans-septal puncture of the fossa ovalis), the guidewire 110 is routed into the left atrium 16. Lastly, the guidewire 110 is routed through the mitral valve 17 and into the left ventricle 18. In some implementations, the guidewire 110 can be installed into the heart 10 along other anatomical pathways. The guidewire 110 thereafter serves as a rail over which other components of the delivery system 100 are passed.

In the depicted implementation, the primary deflectable catheter 120 is installed by pushing it over the guidewire 110. In some implementations, a dilator tip is used in conjunction with the primary deflectable catheter 120 as the primary deflectable catheter 120 is advanced over the guidewire 110. Alternatively, a balloon catheter could be used as the initial dilation means. After the distal end of the primary deflectable catheter 120 reaches the left atrium 16, the dilator tip can be withdrawn. In some embodiments, the distal end portion of the primary deflectable catheter 120 is steerable. Using steering, the distal end portion of the primary deflectable catheter 120 can be oriented as desired in order to navigate the patient's anatomy. For example, the primary deflectable catheter 120 can be angled within the right atrium 12 to navigate the primary deflectable catheter 120 from the inferior vena cava 11 to the atrial septum 15.

In some embodiments, the primary deflectable catheter 120 has an outer diameter of about 28 Fr (about 9.3 mm). In some embodiments, the primary deflectable catheter 120 has an outer diameter in the range of about 26 Fr to about 34 Fr (about 8.7 mm to about 11.3 mm). In some embodiments, the primary deflectable catheter 120 has an outer diameter in the range of about 20 Fr to about 28 Fr (about 6.7 mm to about 9.3 mm).

The primary deflectable catheter 120 can comprise a tubular polymeric or metallic material. For example, in some embodiments the primary deflectable catheter 120 can be made from polymeric materials such as, but not limited to, polytetrafluoroethylene (PTFE), fluorinated ethylene propylene (FEP), HYTREL®, nylon, PICOFLEX®, PEBAX®, TECOFLEX®, and the like, and combinations thereof. In alternative embodiments, the primary deflectable catheter 120 can be made from metallic materials such as, but not limited to, nitinol, stainless steel, stainless steel alloys, titanium, titanium alloys, and the like, and combinations thereof. In some embodiments, the primary deflectable catheter 120 can be made from combinations of such polymeric and metallic materials (e.g., polymer layers with metal braid, coil reinforcement, stiffening members, and the like, and combinations thereof).

The example delivery system 100 also includes the anchor delivery sheath 130. In some implementations, after the primary deflectable catheter 120 is positioned with its distal

11

end in the left atrium **16**, the anchor delivery sheath **130** is installed into a lumen of the primary deflectable catheter **120** (over the guidewire **110**) and advanced through the primary deflectable catheter **120**. As described further below, in some embodiments the anchor delivery sheath **130** is preloaded with a prosthetic valve anchor assembly and other components of the delivery system **100**.

In some embodiments, the anchor delivery sheath **130** can be made from the materials described above in reference to the primary deflectable catheter **120**. In some embodiments, the anchor delivery sheath **130** has an outer diameter in the range of about 20 Fr to about 28 Fr (about 6.7 mm to about 9.3 mm). In some embodiments, the anchor delivery sheath **130** has an outer diameter in the range of about 14 Fr to about 24 Fr (about 4.7 mm to about 8.0 mm).

In the depicted embodiment, the anchor delivery sheath **130** includes a flared distal end portion **132**. In some embodiments, no such flared distal end portion **132** is included. The flared distal end portion **132** can collapse to a lower profile when constrained within the primary deflectable catheter **120**. When the flared distal end portion **132** is expressed from the primary deflectable catheter **120**, the flared distal end portion **132** can self-expand to the flared shape. In some embodiments, the material of the flared distal end portion **132** includes pleats or folds, may be a continuous flared end or may be separated into sections such as flower pedals, and may include one or more resilient elements that bias the flared distal end portion **132** to assume the flared configuration in the absence of restraining forces (such as from containment within the primary deflectable catheter **120**). The flared distal end portion **132** can be advantageous, for example, for recapturing the anchor assembly within the lumen of the anchor delivery sheath **130** after the anchor assembly has been expressed from the flared distal end portion **132**.

In some embodiments, the maximum outer diameter of the flared distal end portion **132** is in a range of about 30 Fr to about 34 Fr (about 10.0 mm to about 11.3 mm). In some embodiments, the maximum outer diameter of the flared distal end portion **132** is in a range of about 32 Fr to about 44 Fr (about 10.7 mm to about 14.7 mm). In some embodiments, the maximum outer diameter of the flared distal end portion **132** is in a range of about 24 Fr to about 30 Fr (about 8.0 mm to about 10.0 mm). In some embodiments, the maximum outer diameter of the flared distal end portion **132** is less than about 24 Fr (about 8.0 mm) or greater than about 44 Fr (about 14.7 mm).

Referring to FIG. 2, additional components of the example delivery system **100** can include a proximal control sheath **140**, a secondary deflectable catheter **150**, and a distal pusher catheter **160**. The proximal control sheath **140** is slidably disposed within a lumen of the anchor delivery sheath **130**. The secondary deflectable catheter **150** is slidably disposed within a lumen of the proximal control sheath **140**. The distal pusher catheter **160** is slidably disposed within a lumen of the secondary deflectable catheter **150**. These components of the delivery system **100** can be manipulated by a clinician operator to control the position and orientation of an anchor assembly **200**. The anchor assembly **200** is slidably disposed over the guidewire **110**.

In some implementations of delivery system **100**, one or more of the proximal control sheath **140**, the secondary deflectable catheter **150**, the distal pusher catheter **160**, and the anchor assembly **200** have been loaded into the anchor delivery sheath **130** prior to the advancement of the anchor delivery sheath **130** into the primary deflectable catheter **120** as shown in FIG. 1. That is, in some cases the proximal

12

control sheath **140**, the secondary deflectable catheter **150**, the distal pusher catheter **160**, and/or the anchor assembly **200** are already installed in the anchor delivery sheath **130** as the anchor delivery sheath **130** is distally advanced into the primary deflectable catheter **120** to attain the arrangement shown in FIG. 1. In other implementations, one or more of the proximal control sheath **140**, the secondary deflectable catheter **150**, the distal pusher catheter **160**, and the anchor assembly **200** are distally advanced into the anchor delivery sheath **130** after the anchor delivery sheath **130** has been advanced into the primary deflectable catheter **120** to attain the arrangement shown in FIG. 1.

The distal pusher catheter **160** is releasably coupled with a hub **210** of the anchor assembly **200**. A proximal end of the anchor assembly **200** is also releasably coupled to the proximal control sheath **140** by one or more control wires **142**. While the depicted embodiment includes one control wire **142**, in some embodiments two, three, four, five, or more than five control wires are included.

Referring to FIGS. 39 and 40, the control wire **142** is shown in an example engagement pattern with the anchor assembly **200**. In the depicted embodiment, the control wire **142** is threaded through a plurality of proximal portions of the anchor assembly **200**. In the depicted embodiment, the control wire **142** is configured in a lasso arrangement. Accordingly, a tensioning of the control wire **142** will cause at least the proximal end of the anchor assembly **200** to contract. Conversely, a removal of tension from the control wire **142** will allow the anchor assembly **200** to expand. In some embodiments, the control wire **142** is threaded through eyelets that are disposed on various positions on the anchor assembly **200**. In some embodiments, the control wire **142** is threaded through attachment features that are disposed on various positions on the covering or frame of the anchor assembly **200**. The control wire **142** can be tensioned or relaxed to arrive at a desired extent of expansion of the proximal end of the anchor assembly **200** (e.g., the atrial holding features **240a**, **240b**, **240c**, and **240d**, and/or the undulating supra-annular ring **250**). Multiple control wires **142** could also be used to achieve asymmetric, controlled expansion of the anchor assembly **300**.

Referring again to FIG. 2, the position of the anchor assembly **200** can be controlled by manipulating the positions of the distal pusher catheter **160** and/or the proximal control sheath **140**. For example, in the depicted embodiment the anchor assembly **200** can be expressed out from the anchor delivery sheath **130** (as shown in FIG. 2) by moving the distal pusher catheter **160** and/or the proximal control sheath **140** distally in relation to the anchor delivery sheath **130**. In some implementations, the expression of the anchor assembly **200** is caused by proximally pulling back the anchor delivery sheath **130** while generally maintaining the positions of the distal pusher catheter **160** and/or the proximal control sheath **140**. In some implementations, the expression of the anchor assembly **200** is caused by a combination of proximally pulling back the anchor delivery sheath **130** while distally extending the positions of the distal pusher catheter **160** and/or the proximal control sheath **140**.

As the anchor assembly **200** emerges from the confines of the anchor delivery sheath **130**, the anchor assembly **200** expands from a low-profile delivery configuration to a partially expanded configuration (as shown in FIG. 2). The extent of expansion of the anchor assembly **200** can be at least partially controlled by the relative positioning of the proximal control sheath **140** in relation to the distal pusher catheter **160**. For instance, as the proximal control sheath

140 is moved proximally in relation to the distal pusher catheter 160, the anchor assembly 200 is axially elongated and radially contracted. Conversely, as the proximal control sheath 140 is moved distally in relation to the distal pusher catheter 160, the anchor assembly 200 is axially shortened and radially expanded. In some implementations, this control of the radial size of the anchor assembly 200 is used by a clinician during the process of deploying the anchor assembly 200 within the native mitral valve 17, as described further below. As described further below, the control wire 142 can also be used to control some radial expansion of the anchor assembly 300 (without changing the relative distance of the proximal control sheath 140 in relation to the distal pusher catheter 160).

It should be understood that the prosthetic mitral valves provided herein are comprised of an anchor assembly 200 and a separable valve assembly (e.g., refer to FIGS. 14-20). The anchor assembly 200 is deployed to an arrangement interfacing within the native mitral valve 17 prior to deployment of the valve assembly. Said differently, after implanting the anchor assembly 200 within the native mitral valve 17, the valve assembly can then be deployed within the anchor assembly 200 and within the native mitral valve 17 (as described further below). Therefore, it can be said that the prosthetic mitral valves provided herein are deployed using a staged implantation method. That is, the anchor assembly 200 is deployed in one stage, and the valve assembly is deployed in a subsequent stage. In some implementations, the deployment of the valve assembly takes place right after the deployment of the anchor assembly 200 (e.g., during the same medical procedure). In some implementations, the deployment of the valve assembly takes place hours, days, weeks, or even months after the deployment of the anchor assembly 200 (e.g., during a subsequent medical procedure).

The staged implantation method of the prosthetic mitral valves provided herein is facilitated by the fact that when the anchor assembly 200 itself is implanted within the native mitral valve 17, the native mitral valve 17 continues to function essentially as before the implantation of the anchor assembly 200 without a significant impact on cardiovascular physiology. That is the case because, as described further below, the anchor assembly 200 interfaces and anchors within structural aspects of the native mitral valve 17 without substantially interfering with the leaflets or chordae tendineae of the native mitral valve 17.

Still referring to FIG. 2, in the depicted arrangement the distal end portion of the secondary deflectable catheter 150 is located at least partially internally within the anchor assembly 200. The secondary deflectable catheter 150 can be manipulated by a clinician operator to reversibly bend the distal end portion of the secondary deflectable catheter 150. As the secondary deflectable catheter 150 is bent by the clinician, other components of the delivery system 100 may bend along with the secondary deflectable catheter 150. For example, one or more of the distal pusher 160 and the proximal control sheath 140 may bend in response to the bending of the deflectable catheter 150. Because the anchor assembly 200 is coupled to the distal pusher 160 and the proximal control sheath 140, the anchor assembly 200 can, in turn, be rotated by bending the secondary deflectable catheter 150.

Referring to FIG. 3, as described above, the secondary deflectable catheter 150 can be articulated (also referred to as steered, deflected, bent, curved, etc.) to pivot laterally (pan, rotate, etc.) the anchor assembly 200 while the anchor assembly 200 is within the left atrium 16. Such rotation of

the anchor assembly 200 is advantageous, for example, to orient the anchor assembly 200 in a desired relationship to the native mitral valve 17 in preparation for implanting the anchor assembly 200 within the native mitral valve 17. In some implementations, it is desirable to orient the anchor assembly 200 so that its longitudinal axis is generally perpendicular to the native mitral valve 17. The lateral pivoting of the partially or fully expanded anchor assembly 200 within the atrium 16 may be advantageous versus having to pivot laterally the anchor assembly 200 while it is still constrained within a delivery sheath, as the latter assembly is a relatively large and stiff catheter assembly.

In preparation for engaging the anchor assembly 200 with the native mitral valve 17, the clinician operator may manipulate the radial size of the anchor frame 200 so that the anchor frame 200 can be passed through the native mitral valve 17 without damaging the native mitral valve 17. For example, the clinician can move the proximal control sheath 140 proximally in relation to the distal pusher catheter 160 to radially contract the anchor assembly 200. With the anchor assembly 200 radially contracted, the anchor frame 200 can be safely passed through the native mitral valve 17 without damaging the native mitral valve 17.

Referring to FIG. 4, while the secondary deflectable catheter 150 is retained in its bent configuration as described in reference to FIG. 3, the distal pusher catheter 160 and the proximal control sheath 140 can be simultaneously advanced. Because the distal pusher catheter 160 is releasably coupled to the hub 210 of the anchor assembly 200, and because the proximal control sheath 140 is releasably coupled to the proximal end of the anchor assembly 200 via the one or more wires 142a and 142b, simultaneous advancement of the distal pusher catheter 160 and the proximal control sheath 140 results in advancement of the anchor assembly 200. The anchor assembly 200 is advanced such that the distal end of anchor assembly 200 is within the left ventricle 18 while the proximal end of the anchor assembly 200 is within the left atrium 16. Hence, some portions of the anchor assembly 200 are on each side of the native mitral valve 17.

In the depicted embodiment, the anchor assembly 200 includes four anchor feet: a left anterior foot 220a, a left posterior foot 220b, a right posterior foot 220c, and a right anterior foot 220d. In some embodiments, fewer or more anchor feet may be included (e.g., two, three, five, six, or more than six). In some embodiments, the anchor feet 220a, 220b, 220c, and 220d are portions of the anchor assembly 200 that are configured for contact with a sub-annular gutter 19 of the native mitral valve 17, without penetrating tissue of the native mitral valve 17. Accordingly, the anchor feet 220a, 220b, 220c, and 220d have atraumatic surfaces that are generally comparable to feet. However, in some embodiments one or more of the anchor feet 220a, 220b, 220c, and 220d are configured to penetrate tissue and may have anchor features such as barbs, coils, hooks, and the like.

In the arrangement of FIG. 4, the anchor feet 220a, 220b, 220c, and 220d are positioned below the sub-annular gutter 19. In this arrangement, the radial size of the anchor assembly 200 can be increased to align the anchor feet 220a, 220b, 220c, and 220d with the sub-annular gutter 19. For example, the clinician can move the proximal control sheath 140 distally in relation to the distal pusher catheter 160 to radially expand the anchor assembly 200 to align the anchor feet 220a, 220b, 220c, and 220d with the sub-annular gutter 19. Such alignment can be performed in preparation for seating the anchor feet 220a, 220b, 220c, and 220d within the sub-annular gutter 19.

Referring to FIG. 5, a commissural cross-sectional view of the heart 10 provides another perspective of the anchor assembly 200 in the same arrangement in relation to the native mitral valve 17 as shown in FIG. 4. This commissural cross-sectional view of the heart 10 is a cross-sectional view taken through the mitral valve 17 along a plane through the left atrium 16 and left ventricle 18 that is parallel to the line that intersects the two commissures of the mitral valve 17 (as described further in reference to FIG. 8 below). In the following FIGS. 5-7 and 13-17, the commissural cross-sectional view of the heart 10 will be used to describe the delivery system 100 and methods for deploying the prosthetic mitral valves provided herein. The view in FIGS. 5-7 and 13-17 is slightly tilted so that better visualization of the anchor assembly 200 is provided.

The anchor feet 220a, 220b, 220c, and 220d are positioned below the sub-annular gutter 19. In this position, the anchor feet 220a, 220b, 220c, and 220d are positioned under the systolic and diastolic excursions of the leaflets of the native mitral valve 17. In this orientation, the anchor feet 220a, 220b, 220c, and 220d can be aligned with the sub-annular gutter 19 in preparation for seating the anchor feet 220a, 220b, 220c, and 220d within the sub-annular gutter 19.

Referring to FIG. 6, the distal pusher 160 and the proximal control sheath 140 can be simultaneously refracted in relation to the secondary deflectable catheter 150 and the primary deflectable catheter 120. As a result, the anchor feet 220a, 220b, 220c, and 220d become seated in the sub-annular gutter 19. In this position, the anchor feet 220a, 220b, 220c, and 220d are positioned under the systolic and diastolic excursions of the leaflets of the native mitral valve 17, and the other structures of the anchor assembly 200 do not inhibit the movements of the leaflets. Therefore, with the anchor assembly 200 coupled to the structures of the mitral valve 17 as described, the mitral valve 17 can continue to function as it did before the placement of the anchor assembly 200. In addition, the manner in which the anchor assembly 200 interfaces with the native mitral valve 17 does not result in deformation of the native mitral valve 17. Therefore, the native mitral valve 17 can continue to function as it did before the placement of the anchor assembly 200.

Referring to FIG. 7, with the anchor assembly 200 engaged within the native mitral valve 17, components of the delivery system 100 can be withdrawn from the anchor assembly 200. For example, the control wire 142 can be detached from the proximal end of the anchor assembly 200. Thereafter, the proximal control sheath 140 can be withdrawn. The secondary deflectable catheter 150 can also be withdrawn. In fact, if so desired, the proximal control sheath 140, the secondary deflectable catheter 150, and the anchor delivery sheath 130 can be completely withdrawn from the primary deflectable catheter 120. In contrast, in some implementations the distal pusher catheter 160 is advantageously left attached to the hub 210 of the anchor assembly 200. As will be described further below, in some implementations the distal pusher catheter 160 can be used as a rail on which a valve assembly is deployed into the interior of the anchor assembly 200. However, in some implementations the anchor assembly 200 is completely detached from the delivery system 100, and the delivery system 100 is removed from the patient. After a period of hours, days, weeks, or months, subsequent to the deployment of the anchor assembly 200, a valve assembly can be installed into the anchor assembly 200 to complete the installation of the prosthetic mitral valve.

Referring to FIGS. 8 and 9, the anatomy of the native mitral valve 17 includes some consistent and predictable structural features across patients that can be utilized for engaging the anchor assembly 200 therewith. For example, the native mitral valve 17 includes the aforementioned sub-annular gutter 19. In addition, the native mitral valve 17 includes a D-shaped annulus 28, an anterolateral commissure 30a, a posteromedial commissure 30b, a left fibrous trigone 134a, and a right fibrous trigone 134b. Further, the native mitral valve 17 includes an anterior leaflet 20 and a three-part posterior leaflet 22. The posterior leaflet 22 includes a lateral scallop 24a, a middle scallop 24b, and a medial scallop 24c. The free edges of the posterior leaflet 22 and the anterior leaflet 20 meet along a coaptation line 32.

The D-shaped annulus 28 defines the structure from which the anterior leaflet 20 and posterior leaflet 22 extend and articulate. The left and right fibrous trigones 134a and 134b are located near the left and right ends of the anterior leaflet 20 and generally adjacent the lateral and medial scallops 24a and 24c of the posterior leaflet 22. The sub-annular gutter 19 runs along the annulus 28 between the left and right fibrous trigones 134a and 134b along the posterior leaflet 22.

The regions at or near the high collagen annular trigones 134a and 134b can generally be relied upon to provide strong, stable anchoring locations. The muscle tissue in the regions at or near the trigones 134a and 134b also provides a good tissue ingrowth substrate for added stability and migration resistance of the anchor assembly 200. Therefore, the regions at or near the trigones 134a and 134b define a left anterior anchor zone 34a and a right anterior anchor zone 34b respectively. The left anterior anchor zone 34a and the right anterior anchor zone 34b provide advantageous target locations for placement of the left anterior foot 220a and the right anterior foot 220d respectively.

The depicted embodiment of the anchor assembly 200 also includes the left posterior foot 220b and the right posterior foot 220c. As previously described, the left posterior foot 220b and the right posterior foot 220c can also be advantageously positioned in the sub-annular gutter 19 in order to provide balanced and atraumatic coupling of the anchor assembly 200 to the native mitral valve 17. Therefore, a left posterior anchor zone 34b and a right anterior anchor zone 34c are defined in the sub-annular gutter 19. The left posterior anchor zone 34b and the right anterior anchor zone 34c can receive the left posterior foot 220b and the right posterior foot 220c respectively. In some implementations, the locations of the left posterior anchor zone 34b and the right anterior anchor zone 34c may vary from the depicted locations while still remaining within the sub-annular gutter 19. It should be understood that the depicted anchor assembly 200 is merely one non-limiting example of the anchor assemblies provided within the scope of this disclosure.

In some embodiments, the anchor assembly 200 includes supra-annular structures and sub-annular structures. For example, the sub-annular structures of the anchor assembly 200 include the aforementioned anchor feet 220a, 220b, 220c, and 220d, and the hub 210. In some embodiments, as described above, the hub 210 functions as a connection structure for the delivery system 100 (e.g., refer to FIG. 2). In addition, the hub 210 can function as a stabilizing structural component from which a left anterior sub-annular support arm 230a, a left posterior sub-annular support arm 230b, a right posterior sub-annular support arm 230c, and a right anterior sub-annular support arm 230d extend to the anchor feet 220a, 220b, 220c, and 220d respectively.

In some embodiments, such as the depicted embodiment, the supra-annular structures of the anchor assembly **200** include: a left anterior atrial holding feature **240a**, a left posterior atrial holding feature **240b**, a right posterior atrial holding feature **240c**, and a right anterior atrial holding feature **240d**; an anterior anchor arch **250a**, a left anchor arch **250b**, a posterior anchor arch **250c**, and a right anchor arch **250d**; and connection bridges **260**. The anterior anchor arch **250a**, left anchor arch **250b**, posterior anchor arch **250c**, and right anchor arch **250d** are joined with each other to form an undulating supra-annular ring **250** that acts as a supra-annular structural element for the anchor assembly **200**. As will be described further below, the supra-annular ring **250** also defines an opening to a space within the interior of the anchor assembly **200** that is configured to receive and engage with a valve assembly. The atrial holding features **240a**, **240b**, **240c**, and **240d** are configured to contact the shelf-like supra-annular tissue surface above the mitral valve annulus, and to thereby stabilize the anchor assembly **200** in supra-annular areas that are generally opposite of the anchor feet **220a**, **220b**, **220c**, and **220d** respectively.

In some embodiments, connection bridges **260** provide enhanced stability and fatigue resistance from vertically oriented forces on a companion artificial valve assembly when the valve (not shown) is closed and blocking pressurized blood during systole. The anchor assembly **200** can also include one or more holes **226** in frame portions adjacent the feet, which are additional control points for delivery and retrieval of the assembly, or could be used to secure a positional delivery frame.

In some embodiments, such as the depicted embodiment, the supra-annular structures and sub-annular structures of the anchor assembly **200** are interconnected by a lateral anterior inter-annular connection **270a**, a lateral posterior inter-annular connection **270b**, a medial posterior inter-annular connection **270c**, and a medial anterior inter-annular connection **270d**. For example, the lateral anterior inter-annular connection **270a** connects the lateral anterior anchor foot **220a** with the lateral anterior atrial holding feature **240a**. In addition, the lateral anterior inter-annular connection **270a** connects the lateral anterior anchor foot **220a** with the anterior anchor arch **250a** and the left anchor arch **250b**. In the depicted embodiment, each of the other inter-annular connections **270b**, **270c**, and **270d** interconnect portions of the supra-annular structures and sub-annular structures in manners analogous to that of the lateral anterior inter-annular connection **270a**. For example, the lateral anterior inter-annular connection **270b** connects the lateral anterior anchor foot **220b** with the left anchor arch **250b** and the posterior anchor arch **250c**; the lateral anterior inter-annular connection **270c** connects the lateral anterior anchor foot **220c** with the posterior anchor arch **250c** and the right anchor arch **250d**; and the lateral anterior inter-annular connection **270d** connects the lateral anterior anchor foot **220d** with the right anchor arch **250d** and the anterior anchor arch **250a**.

In some embodiments, the elongate members of the anchor assembly **200** are formed from a single piece of precursor material (e.g., sheet or tube) that is cut, expanded, and connected to the hub **210**. For example, some embodiments are fabricated from a tube that is laser-cut (or machined, chemically etched, water jet cut, etc.) and then expanded and heat-set into its final expanded size and shape. In some embodiments, the anchor assembly **200** is created compositely from multiple elongate members (e.g., wires or

cut members) that are joined together with the hub **210** and each other to form the anchor assembly **200**.

The elongate members of the anchor assembly **200** can be comprised of various materials and combinations of materials. In some embodiments, nitinol (NiTi) is used as the material of the elongate members of the anchor assembly **200**, but other materials such as stainless steel, L605 steel, polymers, MP35N steel, stainless steels, titanium, cobalt/chromium alloy, polymeric materials, Pyhnox, Elgiloy, or any other appropriate biocompatible material, and combinations thereof can be used. The super-elastic properties of NiTi make it a particularly good candidate material for the elongate members of the anchor assembly **200** because, for example, NiTi can be heat-set into a desired shape. That is, NiTi can be heat-set so that the anchor assembly **200** tends to self-expand into a desired shape when the anchor assembly **200** is unconstrained, such as when the anchor assembly **200** is deployed out from the anchor delivery sheath **130**. An anchor assembly **200** made of NiTi, for example, may have a spring nature that allows the anchor assembly **200** to be elastically collapsed or "crushed" to a low-profile delivery configuration and then to reconfigure to the expanded configuration as shown in FIG. 9. The anchor assembly **200** may be generally conformable, fatigue resistant, and elastic such that the anchor assembly **200** can conform to the topography of the surrounding tissue when the anchor assembly **200** is deployed in a native mitral valve of a patient.

In some embodiments, the diameter or width/thickness of one or more of the elongate members forming the anchor assembly **200** may be within a range of about 0.008" to about 0.015" (about 0.20 mm to about 0.40 mm), or about 0.009" to about 0.030" (about 0.23 mm to about 0.76 mm), or about 0.01" to about 0.06" (about 0.25 mm to about 1.52 mm), or about 0.02" to about 0.10" (about 0.51 mm to about 2.54 mm), or about 0.06" to about 0.20" (about 1.52 mm to about 5.08 mm). In some embodiments, the elongate members forming the anchor assembly **200** may have smaller or larger diameters or widths/thicknesses. In some embodiments, each of the elongate members forming the anchor assembly **200** has essentially the same diameter or width/thickness. In some embodiments, one or more of the elongate members forming the anchor assembly **200** has a different diameter or width/thickness than one or more of the other elongate members of the anchor assembly **200**. In some embodiments, one or more portions of one or more of the elongate members forming the anchor assembly **200** may be tapered, widened, narrowed, curved, radiused, wavy, spiraled, angled, and/or otherwise non-linear and/or not consistent along the entire length of the elongate members of the anchor assembly **200**. Such features and techniques can also be incorporated with the valve assemblies of the prosthetic mitral valves provided herein.

In some embodiments, the elongate members forming the anchor assembly **200** may vary in diameter, thickness and/or width so as to facilitate variations in the forces that are exerted by the anchor assembly **200** in specific regions thereof, to increase or decrease the flexibility of the anchor assembly **200** in certain regions, to enhance migration resistance, and/or to control the process of compression (crushability) in preparation for deployment and the process of expansion during deployment of the anchor assembly **200**.

In some embodiments, one or more of the elongate members of the elongate members forming the anchor assembly **200** may have a circular cross-section. In some embodiments, one or more of the elongate members forming the anchor assembly **200** may have a rectangular cross-

sectional shape, or another cross-sectional shape that is not rectangular. Examples of cross-sectional shapes that the elongate members forming the anchor assembly **200** may include circular, C-shaped, square, ovular, rectangular, elliptical, triangular, D-shaped, trapezoidal, including irregular cross-sectional shapes formed by a braided or stranded construct, and the like. In some embodiments, one or more of the elongate members forming the anchor assembly **200** may be essentially flat (i.e., such that the width to thickness ratio is about 2:1, about 3:1, about 4:1, about 5:1, or greater than about 5:1). In some examples, one or more of the elongate members forming the anchor assembly **200** may be formed using a center-less grind technique, such that the diameter of the elongate members varies along the length of the elongate members.

The anchor assembly **200** may include features that are directed to enhancing one or more desirable functional performance characteristics of the prosthetic mitral valve devices. For example, some features of the anchor assembly **200** may be directed to enhancing the conformability of the prosthetic mitral valve devices. Such features may facilitate improved performance of the prosthetic mitral valve devices by allowing the devices to conform to irregular tissue topographies and/or dynamically variable tissue topographies, for example. Such conformability characteristics can be advantageous for providing effective and durable performance of the prosthetic mitral valve devices. In some embodiments of the anchor assembly **200**, some portions of the anchor assembly **200** are designed to be more conformable than other portions of the same anchor assembly **200**. That is, the conformability of a single anchor assembly **200** can be designed to be different at various areas of the anchor assembly **200**.

In some embodiments, the anchor assembly **200** includes features for enhanced in vivo radiographic visibility. In some embodiments, portions of the anchor assembly **200**, such as one or more of the anchor feet **220a**, **220b**, **220c**, and **220d**, may have one or more radiopaque markers attached thereto. In some embodiments, some or all portions of the anchor assembly **200** are coated (e.g., sputter coated) with a radiopaque coating.

Still referring to FIGS. **8** and **9**, as described above the anchor feet **220a**, **220b**, **220c**, and **220d** are sized and shaped to engage the sub-annular gutter **19** of the mitral valve **17**. In some embodiments, the anterior feet **220a** and **220d** are spaced apart from each other by a distance in a range of about 30 mm to about 45 mm, or about 20 mm to about 35 mm, or about 40 mm to about 55 mm. In some embodiments, the posterior feet **220b** and **220c** are spaced apart from each other by a distance in a range of about 20 mm to about 30 mm, or about 10 mm to about 25 mm, or about 25 mm to about 40 mm.

In some embodiments, the anchor feet **220a**, **220b**, **220c**, and **220d** have a height ranging from about 8 mm to about 12 mm, or more than about 12 mm. In some embodiments, the anchor feet **220a**, **220b**, **220c**, and **220d** have a gutter engaging surface area (when fabric covered) ranging from about 6 mm² to about 24 mm². In some embodiments, the anchor feet **220a**, **220b**, **220c**, and **220d** each have essentially the same gutter engaging surface area. In particular embodiments, one or more of the anchor feet **220a**, **220b**, **220c**, and **220d** has a different gutter engaging surface area than one or more of the other anchor feet **220a**, **220b**, **220c**, and **220d**. The anchor feet **220a**, **220b**, **220c**, and **220d** can have widths ranging within about 1.5 mm to about 4.0 mm or more, and lengths ranging within about 3 mm to about 6 mm or more. The anchor feet **220a**, **220b**, **220c**, and **220d** are

sized and shaped so that the anchor assembly **200** does not significantly impair the natural function of mitral valve chordae tendineae, the native mitral valve leaflets, and papillary muscles even after the anchor assembly is anchored at the mitral valve site.

As described previously, the anchor assembly **200** is designed to avoid interference with the functioning of the native mitral valve **17**. Therefore, the anchor assembly **200** can be implanted within the native mitral valve **17** some time prior to the deployment therein of a replacement valve assembly, without degradation of valve **17** function during the period of time between the anchor implantation and the valve implantation (whether that time is on the order of minutes, or even several days or months). To avoid such interference between the anchor assembly **200** and the native mitral valve **17**, the inter-annular connections **270a**, **270b**, **270c**, and **270d** pass through the coaptation line **32** approximately. More particularly, the left anterior inter-annular connection **270a** passes through the coaptation line **32** adjacent to the anterolateral commissure **30a**. In like manner, the right anterior inter-annular connection **270d** passes through the coaptation line **32** adjacent to the posteromedial commissure **30b**. In some implementations, the left posterior inter-annular connection **270b** and right posterior inter-annular connection **270c** pass through the native mitral valve **17** in locations that are posteriorly biased from the natural coaptation line **32**. The posterior leaflet **22** will tend to compliantly wrap around the left posterior inter-annular connection **270b** and right posterior inter-annular connection **270c** to facilitate sealing of the mitral valve **17**, with the anchor assembly **200** coupled thereto.

In reference to FIG. **10**, in some embodiments the anchor assembly **200** includes a covering material **270** disposed on one or more portions of the anchor assembly **200**. The covering material **270** can provide various benefits. For example, in some implementations the covering material **270** can facilitate tissue ingrowth and/or endothelialization, thereby enhancing the migration resistance of the anchor assembly **200** and preventing thrombus formation on blood contact elements. In another example, as described further below, the covering material **270** can be used to facilitate coupling between the anchor assembly **200** and a valve assembly that is received therein. The cover material **270** also prevents or minimizes abrasion and/or fretting between the anchor assembly **200** and valve assembly **300**. The cover material **270** also prevents valve outer tissue abrasion related wear.

In the depicted embodiment, the covering material **270** is disposed essentially on the entire anchor assembly **200**. In some embodiments, the covering material **270** is disposed on one or more portions of the anchor assembly **200**, while one or more other portions of the anchor assembly **200** do not have the covering material **270** disposed thereon. While the depicted embodiment includes the covering material **270**, the covering material **270** is not required in all embodiments. In some embodiments, two or more portions of covering material **270**, which can be separated and/or distinct from each other, can be disposed on the anchor assembly **200**. That is, in some embodiments a particular type of covering material **270** is disposed on some areas of the anchor assembly **200** and a different type of covering material **270** is disposed on other areas of the anchor assembly **200**.

In some embodiments, the covering material **270**, or portions thereof, comprises a fluoropolymer, such as an expanded polytetrafluoroethylene (ePTFE) polymer. In some embodiments, the covering material **270**, or portions

thereof, comprises a polyester, a silicone, a urethane, ELAST-EON™ (a silicone and urethane polymer), another biocompatible polymer, DACRON®, polyethylene terephthalate (PET), copolymers, or combinations and sub-combinations thereof. In some embodiments, the covering material 270 is manufactured using techniques such as, but not limited to, extrusion, expansion, heat-treating, sintering, knitting, braiding, weaving, chemically treating, and the like. In some embodiments, the covering material 270, or portions thereof, comprises a biological tissue. For example, in some embodiments the covering material 270 can include natural tissues such as, but not limited to, bovine, porcine, ovine, or equine pericardium. In some such embodiments, the tissues are chemically treated using glutaraldehyde, formaldehyde, or triglycidylamine (TGA) solutions, or other suitable tissue crosslinking agents.

In the depicted embodiment, the covering material 270 is disposed on the interior and the exterior of the anchor assembly 200. In some embodiments, the covering material 270 is disposed on the just the exterior of the anchor assembly 200. In some embodiments, the covering material 270 is disposed on the just the interior of the anchor assembly 200. In some embodiments, some portions of the anchor assembly 200 are covered by the covering material 270 in a different manner than other portions of the anchor assembly 200.

In some embodiments, the covering material 270 is attached to at least some portions of the anchor assembly 200 using an adhesive. In some embodiments, FEP (fluorinated ethylene propylene) is used as an adhesive to attach the covering material 270 to the anchor assembly 200, or portions thereof. For example, an FEP coating can be applied to some or all portions of the anchor assembly 200, and the FEP can act as a bonding agent to adhere the covering material 270 to the anchor assembly 200. In some embodiments, wrapping, stitching, lashing, banding, and/or clips, and the like can be used to attach the covering material 270 to the anchor assembly 200. In some embodiments, a combination of techniques are used to attach the covering material 270 to the anchor assembly 200.

In some embodiments, the covering material 270, or portions thereof, has a microporous structure that provides a tissue ingrowth scaffold for durable sealing and/or supplemental anchoring strength of the anchor assembly 200. In some embodiments, the covering material 270 is made of a membranous material that inhibits or reduces the passage of blood through the covering material 270. In some embodiments, the covering material 270, or portions thereof, has a material composition and/or configuration that inhibits or prevents tissue ingrowth and/or endothelialization to the covering material 270.

In some embodiments, the covering material 270 can be modified by one or more chemical or physical processes that enhance certain physical properties of the covering material 270. For example, a hydrophilic coating may be applied to the covering material 270 to improve the wettability and echo translucency of the covering material 270. In some embodiments, the covering material 270 may be modified with chemical moieties that promote or inhibit one or more of endothelial cell attachment, endothelial cell migration, endothelial cell proliferation, and resistance to thrombosis. In some embodiments, the covering material 270 may be modified with covalently attached heparin or impregnated with one or more drug substances that are released in situ.

In some embodiments, covering material 270 is pre-perforated to modulate fluid flow through the covering material 270 and/or to affect the propensity for tissue

ingrowth to the covering material 270. In some embodiments, the covering material 270 is treated to make the covering material 270 stiffer or to add surface texture. For example, in some embodiments the covering material 270 is treated with FEP powder to provide a stiffened covering material 270 or roughened surface on the covering material 270. In some embodiments, selected portions of the covering material 270 are so treated, while other portions of the covering material 270 are not so treated. Other covering material 270 material treatment techniques can also be employed to provide beneficial mechanical properties and tissue response interactions. In some embodiments, portions of the covering material 270 have one or more radiopaque markers attached thereto to enhance in vivo radiographic visualization.

Referring now to FIGS. 11A and 12A, the anchor assembly 200 is shown implanted within a native mitral valve 17. FIGS. 11B and 12B are photographs that correspond to FIGS. 11A and 12A respectively. In FIG. 11A, the mitral valve 17 is shown in a closed state. In FIG. 12A, the mitral valve 17 is shown in an open state. These illustrations are from the perspective of the left atrium looking towards the mitral valve 17. For instance, in FIG. 12A chordae tendineae 40 are visible through the open leaflets of the mitral valve 17.

These figures illustrate the supra-annular structures and sub-annular structures of the anchor assembly 200 in their relationships with the native mitral valve 17. For example, the closed state of the native mitral valve 17 in FIG. 11A allows visibility of the supra-annular structures such as the left anterior atrial holding feature 240a, the left posterior atrial holding feature 240b, the right posterior atrial holding feature 240c, and the right anterior atrial holding feature 240d. In addition, the anterior anchor arch 250a, the left anchor arch 250b, the posterior anchor arch 250c, the right anchor arch 250d, and the connection bridges 260 are visible. However, the sub-annular structures are not visible in FIG. 11A because such structures are obstructed from view by the anterior leaflet 20 and the three-part posterior leaflet 24a, 24b, and 24c.

In contrast, in FIG. 12A certain sub-annular structures of the anchor assembly 200 are visible because the native mitral valve 17 is open. For example, sub-annular support arms 230a, 230b, 230c, and 230d and hub 210 are in view through the open mitral valve 17. Nevertheless, the anchor feet 220a, 220b, 220c, and 220d remain out of view because of their location within the sub-annular gutter of the mitral valve 17.

Referring to FIG. 13, after implantation of the anchor assembly 200 within the native mitral valve 17 (as performed, for example, in accordance with FIGS. 1-7 described above), a valve delivery sheath 170 of the delivery system 100 can be used to deploy a valve assembly within the anchor assembly 200. As described above in reference to FIG. 7, with the distal pusher catheter 160 coupled with the hub 210 of the anchor assembly 200, the distal pusher catheter 160 can be used to guide the valve assembly into the interior of the anchor assembly 200.

In some implementations, with the primary deflectable catheter 120 positioned with its distal end in the left atrium 16, the valve delivery sheath 170 is installed into a lumen of the primary deflectable catheter 120 (over the distal pusher catheter 160) and advanced through the primary deflectable catheter 120. As described further below, in some embodiments the valve delivery sheath 170 is preloaded with a prosthetic valve assembly and other components of the delivery system 100. The primary deflectable catheter 120

may be the same catheter that was used to deliver the anchor assembly **200**, or it may be a different catheter (but still referred to here as the primary deflectable catheter **120** for simplicity sake).

In some embodiments, the valve delivery sheath **170** can be made from the materials described above in reference to the primary deflectable catheter **120**. In some embodiments, the valve delivery sheath **170** has an outer diameter in the range of about 20 Fr to about 28 Fr (about 6.7 mm to about 9.3 mm). In some embodiments, the valve delivery sheath **170** has an outer diameter in the range of about 14 Fr to about 24 Fr (about 4.7 mm to about 8.0 mm).

In the depicted embodiment, the valve delivery sheath **170** includes a flared distal end portion **172**. In some embodiments, no such flared distal end portion **172** is included. The flared distal end portion **172** can collapse to a lower profile when constrained within the primary deflectable catheter **120**. When the flared distal end portion **172** is expressed from the primary deflectable catheter **120**, the flared distal end portion **172** can self-expand to the flared shape. In some embodiments, the material of the flared distal end portion **172** includes pleats or folds, may be a continuous flared end or may be separated into sections such as flower pedals, and may include one or more resilient elements that bias the flared distal end portion **172** to assume the flared configuration in the absence of restraining forces (such as from containment within the primary deflectable catheter **120**). The flared distal end portion **172** can be advantageous, for example, for recapturing the valve assembly within the lumen of the valve delivery sheath **170** after the valve assembly has been expressed from the flared distal end portion **172**.

In some embodiments, the maximum outer diameter of the flared distal end portion **172** is in a range of about 30 Fr to about 34 Fr (about 10.0 mm to about 11.3 mm). In some embodiments, the maximum outer diameter of the flared distal end portion **172** is in a range of about 32 Fr to about 44 Fr (about 10.7 mm to about 14.7 mm). In some embodiments, the maximum outer diameter of the flared distal end portion **172** is in a range of about 24 Fr to about 30 Fr (about 8.0 mm to about 10.0 mm). In some embodiments, the maximum outer diameter of the flared distal end portion **172** is less than about 24 Fr (about 8.0 mm) or greater than about 44 Fr (about 14.7 mm).

Referring to FIG. **14**, in some implementations the valve delivery sheath **170** can be withdrawn into the primary deflectable catheter **120** while a valve delivery catheter **180** is held substantially stationary to express a valve assembly **300** from a lumen of the valve delivery sheath **170**. The valve delivery sheath **170** and the valve delivery catheter **180** are additional components in some embodiments of the example delivery system **100**.

The valve assembly **300** can be releasably coupled to the valve delivery catheter **180** and retained in a low-profile configuration. In some embodiments, both the distal and proximal ends of the valve assembly **300** are releasably coupled to the valve delivery catheter **180**. In some embodiments, just one of the distal end or the proximal end of the valve assembly **300** is releasably coupled to the valve delivery catheter **180**. In particular embodiments, one or more control wires may be included to releasably couple one or more portions of the valve assembly **300** to the valve delivery catheter **180**.

Referring to FIGS. **41-43**, the valve assembly **300** is releasably coupled to the valve delivery catheter **180** via a proximal control wire **342a** and a mid-body control wire **342b**. The control wires **342a** and **342b** are threaded through

one or more lumens within the valve delivery catheter **180**. The control wires **342a** and **342b** exit the valve delivery catheter **180** and pass through eyelets on the proximal end and mid-body portions of the valve assembly **300** respectively. The control wires **342a** and **342b** are then threaded back into the valve delivery catheter **180**. By manipulating the control wires **342a** and **342b**, a clinician operator can control the valve assembly **300**. For example, the expansion and contraction of the valve assembly **300** can be controlled, and the detachment of the valve assembly **300** from the valve delivery catheter can be controlled, by manipulating the tension and position of the control wires **342a** and **342b** within the delivery catheter **180**.

Referring again to FIG. **14**, a lumen of the valve delivery catheter **180** can slidably surround the distal pusher catheter **160**. Therefore, advancement of the valve delivery catheter **180** results in advancement of the valve assembly **300** over the distal pusher catheter **160** towards the anchor assembly **200**.

Referring to FIGS. **15** and **16**, the delivery system **100** can be manipulated by a clinician operator to perform a lateral pivot (panning, rotation, etc.) of the valve assembly **300** within the left atrium **16**. The rotation of the valve assembly **300** changes the alignment of the valve assembly **300** from being generally axial with the distal end portion of the primary deflectable catheter **120** to being generally axial with the anchor assembly **200** (in preparation for installation of the valve assembly **300** into the interior of the anchor assembly **200**).

In some implementations, the aforementioned rotation of the valve assembly **300** can be performed as follows. As shown in FIG. **15**, because of the influence from the primary deflectable catheter **120** on the valve delivery catheter **180**, the axis of the valve assembly **300** is initially in general alignment with the axis of the distal end portion of the primary deflectable catheter **120**. From this arrangement, a simultaneous counter movement between the distal pusher catheter **160** and the valve delivery catheter **180** can be performed by the clinician to rotate the valve assembly **300**. That is, as the distal pusher catheter **160** is pulled proximally, the valve delivery catheter **180** is pushed distally. As a result of that counter movement, the valve assembly **300** rotates in a relatively tight radius, as required by the confines of the left atrium **16**. Thereafter, the valve delivery catheter **180** can be advanced further so that the valve assembly **300** is coaxially positioned within the interior of the anchor assembly **200** as shown in FIG. **16**.

Referring now also to FIG. **17**, in some embodiments the valve assembly **300** and the anchor assembly **200** become aligned with each other coaxially, linearly (along their axes), and rotationally prior to or during the expansion of the valve assembly **300**, resulting in engagement between the valve assembly **300** and the anchor assembly **200**. Thereafter, the delivery system **100** can be withdrawn from the heart **10** and the prosthetic mitral valve can perform its function.

Coaxial alignment between the valve assembly **300** and the anchor assembly **200**, as described above, is achieved by virtue of the valve delivery catheter **180** being slidably disposed over the distal pusher catheter **160**. Linear alignment between the valve assembly **300** and the anchor assembly **200** can be achieved by the interaction of a distal end feature **182** of the valve delivery catheter **180** and the hub **210** of the anchor assembly **200**. For example, in some embodiments an abutting of the distal end feature **182** and the hub **210** can result in proper linear alignment between the valve assembly **300** and the anchor assembly **200**.

Relative rotational alignment between the valve assembly 300 and the anchor assembly 200 (about their axes) can be achieved in various manners. For example, in some embodiments the valve delivery catheter 180 is mechanically keyed to the distal pusher catheter 160 to slidably fix a desired rotational alignment between the valve assembly 300 and the anchor assembly 200. In some embodiments, other types of mechanical features (e.g., pins/holes, protrusions/receptacles, etc.) can be included to facilitate a desired rotational/spin alignment between the valve assembly 300 and the anchor assembly 200. Alternatively, or additionally, radiopaque markers can be included on the valve assembly 300 and on the anchor assembly 200 in locations and/or patterns that are indicative of the relative rotational orientation (about their axes) of the valve assembly 300 and the anchor assembly 200. In some embodiments, (e.g., when the valve delivery catheter 180 "torqueable") the valve delivery catheter 180 can be rotated about its axis until the markers are in proper position relative to the anchor assembly 200, prior to final expansion of valve assembly 300. Fluoroscopy can be used to attain a desired relative orientation of the radiopaque markers, and of the valve assembly 300 and the anchor assembly 200 correspondingly.

Referring to FIGS. 18 and 19, an example valve assembly 300 is shown without any covering or valve/occluder leaflets. Hence, a valve assembly frame 301 of the valve assembly 300 is shown. FIG. 18 shows an anterior side view of the valve assembly frame 301, and FIG. 19 shows a bottom view of the valve assembly frame 301. The valve assembly 300 can be constructed using any of the various materials and manufacturing techniques described above in reference to the anchor frame 200 (e.g., refer to FIG. 9). It should be understood that the depicted valve assembly 300 is merely one non-limiting example of the valve assemblies provided within the scope of this disclosure.

The valve assembly 300 includes a proximal end portion 302 and a distal end portion 304. The valve assembly includes a flared external skirt portion 303 and defines an interior orifice portion 305. When the valve assembly 300 is implanted in a native mitral valve, the proximal end portion 302 is located supra-annular (in the left atrium) and the distal end portion 304 is located sub-annular (in the left ventricle). The proximal end portion 302 defines the generally circular entrance orifice of the valve assembly 300, as described further below.

In the depicted embodiment, the valve assembly 300 generally flares outward along a distal direction. Said differently, the distal end portion 304 is flared outward in comparison to the proximal end portion 302. Accordingly, the proximal end portion 302 defines a smaller outer profile in comparison to the distal end portion 304. However, some regions of the distal end portion 304 bow inwardly. In particular, for example, a posteromedial commissural corner 330a and anterolateral commissural corner 330b of the valve assembly 300 may bow inwardly. It should be understood that the outward flare of the distal end portion 304 in comparison to the proximal end portion 302 is merely one example configuration for a profile of the valve assembly 300. In some embodiments, for example, a shoulder (a portion of the valve assembly 300 having the largest outer periphery) is located proximal of the middle of the valve assembly 300.

The valve assembly 300 also includes an anterior side 306 between the posteromedial commissural corner 330a and anterolateral commissural corner 330b. When the valve assembly 300 is implanted in a native mitral valve, the anterior side 306 faces the anterior leaflet of the native mitral

valve. The anterior side 306 of the distal end portion 304 defines a generally flat surface, whereas the other sides of the distal end portion 304 are rounded. Hence, the periphery of the distal end portion 304 is generally D-shaped. The D-shaped periphery of the distal end portion 304 provides the valve assembly 300 with an advantageous outer profile for interfacing and sealing with the native mitral valve. As described further below, sealing is attained by coaptation between the D-shaped periphery of the distal end portion 304 and the leaflets of the native mitral valve, and, in some embodiments, between the D-shaped periphery in the region of the skirt 303 with the native valve annulus.

In the depicted embodiment, the proximal end portion 302 of the valve assembly 300 includes three atrial leaflet arches 310a, 310b, and 310c that together define an undulating ring at the proximal end portion 302. Each of the leaflet arches 310a, 310b, and 310c includes an apex having an attachment hole 312a, 312b, and 312c respectively. In some embodiments, the attachment holes 312a, 312b, and 312c are used for coupling the proximal end of the valve assembly 300 to a delivery catheter (e.g., valve delivery catheter 180 of FIGS. 14-16).

The valve assembly 300 also includes three commissural posts 320a, 320b, and 320c that each extend distally from the intersections of the three leaflet arches 310a, 310b, and 310c. The commissural posts 320a, 320b, and 320c are disposed at about 120° apart from each other. The commissural posts 320a, 320b, and 320c each have a series of holes that can be used for attachment of leaflets, such as by suturing. The three leaflet arches 310a, 310b, and 310c and the three commissural posts 320a, 320b, and 320c are areas on the valve assembly 300 to which three prosthetic valve leaflets become attached to comprise a tri-leaflet occluder (e.g., refer to FIGS. 22-25).

As best seen in FIG. 19, the three leaflet arches 310a, 310b, and 310c and the commissural posts 320a, 320b, and 320c define a generally cylindrical frame for the tri-leaflet occluder construct. As such, the valve assembly 300 provides a proven and advantageous frame configuration for the tri-leaflet occluder. The tri-leaflet occluder provides open flow during diastole and occlusion of flow during systole.

Referring to FIG. 20, an exploded depiction of an example prosthetic mitral valve 400 includes an anchor assembly 200 and a valve assembly 300. This figure provides a posterior side view of the anchor assembly 200 and the valve assembly 300.

The valve assembly 300 includes a covering 340. The covering 340 can be made of any of the materials and constructed using any of the techniques described above in reference to covering 270. Additionally, in some embodiments the covering 340 can comprise natural tissues such as, but not limited to, bovine, porcine, ovine, or equine pericardium. In some such embodiments, the tissues are chemically cross-linked using glutaraldehyde, formaldehyde, or triglycidyl amine solution, or other suitable crosslinking agents.

When the valve assembly 300 and the anchor assembly 200 are coupled together, the valve assembly 300 is geometrically interlocked within the interior of the anchor assembly 200 (e.g., in some embodiments by virtue of the tapered shape of the valve assembly 300 within the supra-annular ring and interior space of the anchor assembly 200). In particular, in some embodiments the valve assembly 300 is contained within the interior space between the supra-annular ring 250 and the sub-annular support arms 230a, 230b, 230c, and 230d. As described above, the interlocked arrangement between the valve assembly 300 and the anchor

assembly **200** is accomplished by positioning a valve assembly **300** in a low-profile configuration within the interior of the anchor assembly **200** and then allowing expansion of the valve assembly **300** within the interior of the anchor assembly **200** (e.g., refer to FIGS. **16** and **17**).

Referring to FIGS. **21** and **22**, a deployed configuration of the example prosthetic mitral valve **400** includes the valve assembly **300** engaged within the anchor assembly **200**. FIG. **21** shows a top (atrial) view of the prosthetic mitral valve **400**, and FIG. **22** shows a bottom (ventricle) view of the prosthetic mitral valve **400**.

In some embodiments, such as the depicted embodiment, valve assembly **300** includes three leaflets **350a**, **350b**, and **350c** that perform the occluding function of the prosthetic mitral valve **400**. The cusps of the three leaflets **350a**, **350b**, and **350c** are fixed to the three atrial leaflet arches **310a**, **310b**, and **310c**, and to the three commissural posts **320a**, **320b**, and **320c** (refer to FIGS. **18** and **19**). The free edges of the three leaflets **350a**, **350b**, and **350c** can seal by coaptation with each other during systole and open during diastole.

The three leaflets **350a**, **350b**, and **350c** can be comprised of natural or synthetic materials. For example, the three leaflets **350a**, **350b**, and **350c** can be comprised of any of the materials described above in reference to the covering **340**, including the natural tissues such as, but not limited to, bovine, porcine, ovine, or equine pericardium. In some such embodiments, the tissues are chemically cross-linked using glutaraldehyde, formaldehyde, or triglycidyl amine solution, or other suitable crosslinking agents. In some embodiments, the leaflets **350a**, **350b**, and **350c** have a thickness in a range of about 0.005" to about 0.020" (about 0.13 mm to about 0.51 mm), or about 0.008" to about 0.012" (about 0.20 mm to about 0.31 mm). In some embodiments, the leaflets **350a**, **350b**, and **350c** have a thickness that is less than about 0.005" (about 0.13 mm) or greater than about 0.020" (about 0.51 mm).

In some embodiments, the occluding function of the prosthetic mitral valve **400** can be performed using configurations other than a tri-leaflet occluder. For example, bi-leaflet, quad-leaflet, or mechanical valve constructs can be used in some embodiments.

Referring to FIGS. **23** and **24**, the prosthetic mitral valve **400** is shown implanted within a native mitral valve **17**. In FIG. **23**, the prosthetic mitral valve **400** is shown in a closed state (occluded). In FIG. **24**, the prosthetic mitral valve **400** is shown in an open state. These illustrations are from the perspective of the left atrium looking towards the mitral valve **17**. For instance, in FIG. **24** the hub **210** and the sub-annular support arms **230a**, **230b**, **230c**, and **230d** of the anchor assembly **200** is visible through the open leaflets **350a**, **350b**, and **350c** of the prosthetic mitral valve **400**, whereas in FIG. **23** the hub **210** and the sub-annular support arms **230a**, **230b**, **230c**, and **230d** are not visible because the closed leaflets **350a**, **350b**, and **350c** block the hub **210** from view.

FIGS. **25-33** describe additional aspects pertaining to sealing between native mitral valve structures and the implantable prosthetic mitral valves described herein. During systole, ventricle-to-atrium sealing is relevant in order to effectively treat MR via implantation of a prosthetic mitral valve. In addition, during diastole, atrium-to-ventricle sealing between native mitral valve structures and the prosthetic mitral valves described herein is relevant for preventing or reducing paravalvular leakage, and for good healing and chronic stability. The prosthetic mitral valves described

herein are designed to have various features that provide for effective sealing with the native mitral valve structures.

One feature that enhances the sealing of the prosthetic mitral valves provided herein pertains to the shape of the prosthetic valve framework in relation to the shape of the native mitral valve. As described above, the annulus of a native mitral valve is generally D-shaped (e.g., refer to FIG. **8**). In addition, as described above, the distal end portions of the prosthetic mitral valves described herein are D-shaped (e.g., refer to FIG. **19**). In other words, the portion of the prosthetic valve that is designed to interface with the native valve annulus has a D-shaped profile that is similar to the shape of the annulus. This similarity of shapes can provide particular sealing efficacy in the areas of the lateral scallop **24a** and the medial scallop **24c** of the posterior leaflets **22** (refer to FIG. **8**).

Another feature that enhances the sealing of the prosthetic mitral valves provided herein pertains to the size of the selected prosthetic valve in relation to the size of the native mitral valve, especially during systole. In some implementations, a selected prosthetic valve will intentionally have an outer profile (when unconstrained) that is equal to or slightly larger than the size of the annulus of the native mitral valve. That is, in the area on the valve surface that is intended to be adjacent to the native valve annulus, the size of the valve may result in a line-to-line fit or a slight interference fit with the native valve annulus. Hence, in some implementations the atrium-to-ventricle sealing during diastole is provided by the line-to-line fit or slight interference fit between the valve and the native valve annulus.

Another feature that enhances the sealing of the prosthetic mitral valves provided herein pertains to the relative geometric orientation of sealing surfaces on the prosthetic valve in relation to the annulus of the native mitral valve. While in some implementations, some sealing is provided by the mechanical fit between the outer profile of the valve and the receiving structure of the native mitral valve, in some implementations substantial sealing is provided by coaptation between the native leaflets and sealing surfaces on the perimeter of the prosthetic valve (to thereby create a contact seal during diastole and a left ventricle pressurized seal during systole). This type of sealing may be referred to herein as a leaflet to valve body seal. As described further below, the prosthetic mitral valves provided herein have sealing surfaces that are geometrically oriented in relation to the native valve annulus so that a leaflet to valve body seal is provided. While the leaflet to valve body seal is not entirely a mechanically compressive type of seal or an attachment onto the native tissue (active fixation) type of seal, in some embodiments such mechanical or attachment type of seals may alternatively or additionally be incorporated.

In some implementations, an effective leaflet to valve body seal (not based entirely on compression or attachment) may necessitate some native leaflet movement to the sealing surface of the valve body. Hence, a valve body shape that mimics the shape of the native mitral valve is advantageous. As described above, in some embodiments the outer periphery of the valve assemblies provided herein have a D-shaped periphery that generally correlates with the D-shaped annulus of native mitral valves. Accordingly, the movement distance of the native valve leaflets to the sealing surface of the valve body can be minimized (or essentially eliminated in some implementations), and sealing can thereby be enhanced.

In addition, an effective leaflet to valve body seal exhibits contiguous coaptation between the native leaflets and pros-

thetic valve body around the entire periphery of the prosthetic valve body. As described further below, the profiles of the prosthetic mitral valves provided herein are designed to interface with the native leaflets so as to provide contiguous coaptation around the entire periphery of the prosthetic valve. To accomplish this, in some embodiments the profile of some regions of the prosthetic mitral valves are different than the profile of other regions of the same valve (e.g., in correspondence with differing anatomical features in various portions of the native mitral valve).

Referring to FIG. 25, a lateral cross-sectional atrial view of a heart 10 shows the mitral valve 17, aortic valve 510, tricuspid valve, 520 and pulmonary valve 530. As described above in reference to FIG. 8, the mitral valve 17 includes the anterior leaflet 20, the posterior leaflet 22 (including the medial scallop 24a, the middle scallop 24b, and the lateral scallop 24c), the left fibrous trigone 134a, and the right fibrous trigone 134b.

In regard to sealing between a prosthetic mitral valve and a native mitral valve, the differing anatomical features of various portions of the native mitral valve 17 make it advantageous to consider the mitral valve 17 as having three distinct sealing regions that together comprise the entirety of the mitral valve 17. The three distinct sealing regions are: an anterior region 25a, a posterior region 25b, and two commissural regions 25c. The anterior region 25a extends generally linearly between the left and right trigones 134a and 134b. The posterior region 25b comprises the middle scallop 24b and posterior portions of the lateral scallop 24a and medial scallop 24c. The commissural regions 25c extend between the anterior region 25a and the posterior region 25b. The commissural regions 25c generally encompass the commissures 30a and 30b, and anterior portions of the lateral scallop 24a and medial scallop 24c. These three sealing regions 25a, 25b, and 25c will be referenced again in regard to FIGS. 28-33.

Referring to FIG. 26, a schematic diagram of a cross-section of a native mitral 17 valve indicates the location of the mitral valve annulus 28. Three geometric variables (S, W, and H) that can be used to quantify a relative geometric orientation of sealing surfaces on the prosthetic valve in relation to the annulus 28 of the native mitral valve 17 are also indicated. As used herein, the term "sealing surfaces" is defined as surface areas on the prosthetic valve that are intended to make sealing contact with structures of the native mitral valve 17 (especially the leaflets of the native mitral valve 17). Hence, the sealing surfaces are the areas on the prosthetic valve that are used to facilitate the leaflet to valve body seal.

The geometric variable S quantifies the radial distance from the annulus 28 to the adjacent prosthetic valve framework surface. A negative S-value indicates that the annulus 28 and the adjacent prosthetic valve surface are spaced apart from each other. For example, an S-value of negative 2 mm indicates that there is a 2 mm space between the annulus 28 and the adjacent prosthetic valve surface. When S equals zero, it indicates that the annulus 28 and the adjacent prosthetic valve surface are in contact with each other in a line-to-line fit relationship. When S is a positive number, it indicates that the annulus 28 and the adjacent prosthetic valve surface are in an interference fit relationship. In other words, when S is a positive number some compressive force is being applied to the annulus 28 by the adjacent prosthetic valve surface.

The geometric variable H quantifies the distance from the superior limit (upper edge) to the inferior limit (lower edge) of the sealing surface on the prosthetic valve. H-values are

measured downward (in reference to the illustration). For example, an H-value of 10 mm indicates that, for a particular sealing region, the sealing surface on the prosthetic valve ends 10 mm below the superior limit of the sealing surface.

In another example, when the superior limit is at the annulus 28, an H-value of 7 mm indicates that the inferior limit of the sealing surface is 7 mm below the annulus 28. In general, the superior limit of the sealing surface on the prosthetic valve is either at, slightly above, or slightly below the annulus 28 (e.g., about 2 mm above or about 2 mm below the annulus 28 in some embodiments).

The geometric variable W quantifies the radial distance from the superior limit of the sealing surface to the inferior limit of the sealing surface on the prosthetic valve. A negative W-value indicates that the inferior limit of the sealing surface is positioned radially inward in comparison to the superior limit of the sealing surface (e.g., at least a portion of the sealing surface is flared or bowed inward at the distal end). A positive W-value indicates that the inferior limit of the sealing surface is positioned radially outward in comparison to superior limit of the sealing surface (e.g., at least a portion of the sealing surface is flared or bowed outward at the distal end). A W-value of zero indicates that the inferior limit of the sealing surface is positioned at the same radial position as the superior limit of the sealing surface.

Referring to FIG. 27, an anterior side view of a valve assembly 300 includes an anterior sealing surface 360a in accordance with some embodiments. In the depicted embodiment, the anterior sealing surface 360a spans the lower portion of the anterior side of valve assembly 300. The anterior sealing surface 360a comprises the surface area on the anterior side of the prosthetic valve assembly 300 that is intended to make sealing contact with structures of the native mitral valve. The anterior sealing surface 360a consists of structural support from the valve frame 301 as well as a tissue surface 361a. The anterior tissue surface 361a provides sealing interface height (H) but its flexible nature reduces the amount of LVOT obstruction, as will be described later. For example, at least a portion of the anterior sealing surface 360a is intended to make sealing contact with the anterior leaflet of the native mitral valve.

Referring to FIG. 28, a posterior side view of a valve assembly 300 includes a posterior sealing surface 360b in accordance with some embodiments. In the depicted embodiment, the posterior sealing surface 360b spans the lower portion of the posterior side of valve assembly 300. The posterior sealing surface 360b comprises the surface area on the posterior side of the prosthetic valve assembly 300 that is intended to make sealing contact with structures of the native mitral valve. For example, at least a portion of the posterior sealing surface 360b is intended to make sealing contact with the posterior leaflet of the native mitral valve.

Referring to FIG. 29, a commissural (lateral) side view of a valve assembly 300 includes a commissural sealing surface 360c in accordance with some embodiments. This view is slightly biased to the anterior side of the valve assembly 300. In the depicted embodiment, the commissural sealing surface 360c spans the lower portion of the commissural side of valve assembly 300. The commissural sealing surface 360c comprises the surface area on the lateral side of the prosthetic valve assembly 300 that is intended to make sealing contact with structures of the native mitral valve. For example, at least a portion of the commissural sealing surface 360c is intended to make sealing contact with the medial scallop or the lateral scallop of the posterior leaflet of

the native mitral valve, and with the leaflet tissue in the commissural regions of the native mitral valve.

Referring to FIG. 30, the geometric relationship between a native mitral valve annulus and an anterior sealing surface of a prosthetic mitral valve in accordance with some embodiments can be represented by the S, H, and W values as described above in reference to FIG. 26. For example, in some embodiments the S-value of the anterior sealing surface of the prosthetic mitral valve is in a range from about zero millimeters to about positive 2 millimeters. In other words, the S-value of the anterior sealing surface in relation to the native mitral valve annulus is in a range from about line-to-line contact to about 2 millimeters interference. It should be understood that in this context an interference fit does not necessarily mean that the native valve annulus is stretched or deformed as a result of the interference. More likely, rather, the prosthetic valve assembly will be inhibited by the annulus from enlarging to its unconstrained fully expanded size. While in the depicted embodiment the S-value is in a range of about zero millimeters to about positive 2 millimeters, in some embodiments the S-value is in a range of about negative 2 millimeters to about positive 1 millimeter, or about negative 1 millimeter to about positive 3 millimeters, or about zero millimeters to about positive 4 millimeters. In some embodiments, the S-value can be more negative than about negative 2 millimeters or more positive than about positive 4 millimeters.

In some embodiments the H-value of the anterior sealing surface of the prosthetic mitral valve is about 14 millimeters. In other words, in some embodiments the distance from the superior edge of the anterior sealing surface to the inferior edge of the anterior sealing surface is about 14 millimeters. More specifically, the H-value of the anterior sealing surface can be divided into two portions: (1) a superior portion, H_{LVOT} and (2) an inferior portion, H_{TISSUE} . The H_{LVOT} -value generally corresponds to the distance from the superior edge of the anterior sealing surface to the inferior end of the valve frame 301 at various places along the anterior sealing surface 360a (refer to FIG. 27). The H_{TISSUE} -value corresponds to the distance from the inferior end of the valve frame 301 at various places along the anterior sealing surface 360a to the inferior end of the anterior tissue surface 361a at those places. While in the depicted embodiment, the H_{LVOT} -value and the H_{TISSUE} -value are equal to each other, in some embodiments the ratio between the H_{LVOT} -value and the H_{TISSUE} -value is about 3:1, about 2:1, about 1.5:1, about 1:1.5, about 1:2, or about 3:1.

While in the depicted embodiment the total H-value is about 14 millimeters, in some embodiments the H-value is in a range of about 8 millimeters to about 10 millimeters, or about 10 millimeters to about 12 millimeters, or about 12 millimeters to about 14 millimeters, or about 14 millimeters to about 16 millimeters, or about 13 millimeters to about 15 millimeters. In some embodiments, the H-value can be less than about 8 millimeters or more than about 16 millimeters.

In some embodiments the W-value of the anterior sealing surface of the prosthetic mitral valve is about negative 2 millimeters. In other words, in some embodiments the radial distance from the superior edge of the anterior sealing surface to the inferior edge of the anterior sealing surface on the prosthetic valve is about negative 2 millimeters. A W-value of negative 2 millimeters indicates that the lower edge of the anterior sealing surface is positioned radially inward in comparison to the superior edge of the anterior sealing surface by about 2 millimeters. This also indicates that the sub-annular anterior valve assembly is flared or bowed inward, such as indicated by valve body profile line

362a. While in the depicted embodiment the W-value is about negative 2 millimeters, in some embodiments the W-value is in a range of about negative 6 millimeters to about negative 4 millimeters, or about negative 4 millimeters to about negative 2 millimeters, or about negative 2 millimeters to about zero millimeters, or about zero millimeters to about positive 2 millimeters, or about negative 3 millimeters to about negative 1 millimeter. In some embodiments, the W-value can be more negative than about negative 6 millimeters or more positive than about positive 2 millimeters.

Referring to FIG. 31, the geometric relationship between a native mitral valve annulus and a commissural sealing surface of a prosthetic mitral valve in accordance with some embodiments can be represented by the S, H, and W values as described above in reference to FIG. 26. For example, in some embodiments the S-value of the commissural sealing surface of the prosthetic mitral valve is in a range from about zero millimeters to about positive 2 millimeters. In other words, the S-value of the commissural sealing surface in relation to the native mitral valve annulus is in a range from about line-to-line contact to about 2 millimeters interference. It should be understood that in this context an interference fit does not necessarily mean that the native valve annulus is stretched or deformed as a result of the interference. More likely, rather, the prosthetic valve assembly will be inhibited by the annulus from enlarging to its fully expanded size. While in the depicted embodiment the S-value is in a range of about zero millimeters to about positive 2 millimeters, in some embodiments the S-value is in a range of about negative 2 millimeters to about positive 1 millimeter, or about negative 1 millimeter to about positive 3 millimeters, or about zero millimeters to about positive 4 millimeters. In some embodiments, the S-value can be more negative than about negative 2 millimeters or more positive than about positive 4 millimeters.

In some embodiments, the H-value of the commissural sealing surface of the prosthetic mitral valve is in a range of about 8 millimeters to about 14 millimeters. In other words, in some embodiments the distance from the native valve annulus to the lower (inferior) edge of the commissural sealing surface is in a range of about 8 millimeters to about 14 millimeters. This range, from about 8 millimeters to about 14 millimeters, is at least partly a result of the shape of a commissural corner 364 (refer to FIG. 29) that comprises part of the commissural sealing surface. Accordingly, the lower edge of the commissural sealing surface varies across the lateral width of the commissural sealing surface just by the nature of the shape of the commissural sealing surface. While in the depicted embodiment the H-value is in a range of about 8 millimeters to about 14 millimeters, in some embodiments the H-value is in a range of about 4 millimeters to about 10 millimeters, or about 6 millimeters to about 12 millimeters, or about 8 millimeters to about 14 millimeters, or about 10 millimeters to about 16 millimeters, or about 7 millimeters to about 15 millimeters. In some embodiments, the H-value can be less than about 4 millimeters or more than about 15 millimeters.

In some embodiments the W-value of the commissural sealing surface of the prosthetic mitral valve is about negative 2 millimeters. In other words, in some embodiments the radial distance from the superior (upper) edge of the commissural sealing surface to the inferior (lower) edge of the commissural sealing surface on the prosthetic valve is about negative 2 millimeters. A W-value of negative 2 millimeters indicates that the lower edge of the commissural sealing surface is positioned radially inward in comparison to the

upper edge of the commissural sealing surface by about 2 millimeters. This also indicates that the sub-annular commissural valve assembly is flared or bowed inward, such as indicated by valve body profile line **362b**. While in the depicted embodiment the W-value is about negative 2 millimeters, in some embodiments the W-value is in a range of about negative 6 millimeters to about negative 4 millimeters, or about negative 4 millimeters to about negative 2 millimeters, or about negative 2 millimeters to about zero millimeters, or about zero millimeters to about positive 2 millimeters, or about negative 3 millimeters to about negative 1 millimeter. In some embodiments, the W-value can be more negative than about negative 6 millimeters or more positive than about positive 2 millimeters.

Referring to FIG. **32**, the geometric relationship between a native mitral valve annulus and a posterior sealing surface of a prosthetic mitral valve in accordance with some embodiments can be represented by the S, H, and W values as described above in reference to FIG. **26**. For example, in some embodiments the S-value of the posterior sealing surface of the prosthetic mitral valve is in a range from about zero millimeters to about positive 2 millimeters. In other words, the S-value of the posterior sealing surface in relation to the native mitral valve annulus is in a range from about line-to-line contact to about 2 millimeters interference. It should be understood that in this context an interference fit does not necessarily mean that the native valve annulus is stretched or deformed as a result of the interference. More likely, rather, the prosthetic valve assembly will be inhibited by the annulus from enlarging to its fully expanded size. While in the depicted embodiment the S-value is in a range of about zero millimeters to about positive 2 millimeters, in some embodiments the S-value is in a range of about negative 2 millimeters to about positive 1 millimeter, or about negative 1 millimeter to about positive 3 millimeters, or about zero millimeters to about positive 4 millimeters. In some embodiments, the S-value can be more negative than about negative 2 millimeters or more positive than about positive 4 millimeters.

In some embodiments, the H-value of the posterior sealing surface of the prosthetic mitral valve is about 8 millimeters. In other words, in some embodiments the distance from the native valve annulus to the lower (inferior) edge of the posterior sealing surface is about 8 millimeters. While in the depicted embodiment the H-value is about 8 millimeters, in some embodiments the H-value is in a range of about 4 millimeters to about 6 millimeters, or about 6 millimeters to about 8 millimeters, or about 8 millimeters to about 10 millimeters, or about 10 millimeters to about 12 millimeters, or about 7 millimeters to about 9 millimeters. In some embodiments, the H-value can be less than about 4 millimeters or more than about 12 millimeters.

In some embodiments, the W-value of the posterior sealing surface of the prosthetic mitral valve is about positive 2 millimeters. In other words, in some embodiments the radial distance from the upper (superior) edge of the posterior sealing surface to the lower (inferior) edge of the posterior sealing surface on the prosthetic valve is about positive 2 millimeters. A W-value of positive 2 millimeters indicates that the lower edge of the posterior sealing surface is positioned radially outward in comparison to the upper edge of the posterior sealing surface by about 2 millimeters. This also indicates that the sub-annular posterior valve assembly is flared or bowed outward, such as indicated by valve body profile line **362c**. While in the depicted embodiment the W-value is about positive 2 millimeters, in some embodiments the W-value is in a range of about negative 4

millimeters to about negative 2 millimeters, or about negative 2 millimeters to about zero millimeters, or about zero millimeters to about positive 2 millimeters, or about positive 2 millimeters to about positive 4 millimeters, or about positive 1 millimeter to about positive 3 millimeters. In some embodiments, the W-value can be more negative than about negative 2 millimeters or more positive than about positive 3 millimeters.

Referring to FIG. **33**, during systole the aortic valve **510** receives blood flowing out from the left ventricle **18**. The blood flows to the aortic valve **510** via a left ventricular outflow tract (LVOT) **512**. In some circumstances, a prosthetic mitral valve **600** (shown without an anchor assembly for simplicity) implanted in the native mitral valve **17** may obstruct the LVOT **512**, as represented by an obstruction **514**, resulting in reduced ejection of blood from the left ventricle **18**. As described herein, the prosthetic mitral valves provided by this disclosure may be configured to reduce or eliminate LVOT obstructions **514**.

Referring to FIGS. **34** and **35**, a first fluoroscopic image **700** and a second fluoroscopic image **730** were obtained after fluoroscopic dye was injected into the left ventricle to enhance visualization of blood flow and blood flow obstructions. The images show blood flowing from the left ventricle to the aorta through the left ventricular outflow track (LVOT).

The first fluoroscopic image **700** illustrates an area of reduced blood flow **710** caused by an LVOT obstruction from a prosthetic mitral valve **720**. The second fluoroscopic image **730** illustrates improved blood flow **740** through the LVOT. The improved blood flow **740** can be a result of less obstruction attributable to the prosthetic mitral valve **750**. For example, in some embodiments the prosthetic mitral valve **750** can be positioned or designed so that less structure of the valve **750** is below the native mitral valve annulus, resulting in less structure of the valve **750** within the LVOT. Additionally, the prosthetic mitral valve **750** can be positioned or designed so that less structure of the valve **750** is within the LVOT such as by tapering, bowing, or shaping the structure away from the LVOT.

Referring again to FIG. **33**, the portion of the prosthetic mitral valve **600** that faces the aortic valve **510** is the anterior sealing surface **625a**. Therefore, the geometric orientation of the anterior sealing surface **625a** in relation to the LVOT **512** is a factor relating to whether or not the prosthetic mitral valve **600** will cause obstructions **514**.

Referring also to FIG. **36**, the geometric relationships between the LVOT **512**, the native mitral valve annulus **28**, and the anterior sealing surface variables (S-value, H-value, and W-value, as described in reference to FIGS. **25**, **26**, and **30**) can be used to quantify LVOT obstructions **514**. The angle between the LVOT **512** and the native mitral valve annulus **28** is identified as θ . The R-value is a variable that accounts for prosthetic valve positioning variations from the anticipated/ideal location of the prosthetic valve relative to the native valve annulus.

Using geometry, the LVOT obstruction **514** distance (identified as "O" in the equation below) can be calculated using the following equation:

$$O = R \sin \theta + \sqrt{W^2 + H_{LVOT}^2} \sin \left\{ \theta - \tan^{-1} \left(\frac{W}{H} \right) \right\} - S \cos \theta \quad \text{Equation \#1}$$

where:

O is the calculated distance of an LVOT obstruction;

R is the distance from the native valve annulus to the top of the anterior sealing surface;

θ is the angle between the mitral valve annulus and the LVOT;

W is the radial distance from the upper edge of the sealing surface to the lower edge of the sealing surface on the prosthetic valve;

H_{LVOT} is the distance from the superior edge of the sealing surface to the lower structural (frame) edge of the sealing surface on the prosthetic valve: and

S is the radial distance from the mitral valve annulus to the adjacent prosthetic valve surface.

The following examples are provided to illustrate Equation #1 above.

Example	R (mm)	S (mm)	H _{LVOT} (mm)	W (mm)	θ°	O (mm)
1	0	2	8	-2	164	2.2
2	0	0	8	-2	119	6.0
3	0	2	8	-4	119	6.0
4	0	2	5	-4	119	3.4
5	0	0	14	-2	164	1.9

By comparing Examples #1 and #5, with Examples #2, #3, and #4 it can be ascertained that O (the LVOT obstruction) tends to be less when θ is greater. By comparing Example #3 and Example #4, it is seen that a greater H_{LVOT} tends to result in a higher O. By comparing Example #2 and Example #3, it can be determined that the effect of a greater S-value can be offset by a more negative W-value. In summary, one of ordinary skill in the art can use these teachings to select an R-value, S-value, H_{LVOT}-value, and W-value for a given θ (based on patient anatomy) in effort to attain an acceptable O (the LVOT obstruction).

Referring to FIGS. 37 and 38, an anchor assembly 200 can be engaged with a native mitral valve 17 such that the feet 220a, 220b, 220c, and 220d are seated in the sub-annular gutter 19 of the native mitral valve 17, while the leaflets 20 and 22 and chordae tendineae 40 are substantially unhindered by the anchor assembly 200. As described above, the anchor assembly 200 is designed to be implanted within a native mitral valve 17, without substantially interfering with the native valve 17, so that the native valve 17 can continue to function as it did prior to the placement of the anchor assembly 200. To accomplish that, the leaflets 20 and 22 and chordae tendineae 40, especially the chordae tendineae 40 that are attached to the anterior leaflet 20, need to be substantially unhindered by the anchor assembly 200.

In some implementations, the positioning of the hub 210 relative to the anatomical features of the mitral valve 17 is relevant to facilitating substantially unhindered leaflets 20 and 22 and chordae tendineae 40. For example, a depth 810 of the hub 210 in the left ventricle 18 is one relevant consideration. In order to substantially prevent hindrances to the leaflets 20 and 22 and chordae tendineae 40, the depth 810 should be at least slightly below the coaptation depth of the mitral valve 17. The coaptation depth is the greatest vertical distance from the annulus of the mitral valve 17 to an area of coaptation between the native leaflets 20 and 22. Hence, positioning the hub 210 below the coaptation depth will facilitate substantially unhindered leaflets 20 and 22 and chordae tendineae 40. In some implementations, the depth 810 is in a range of about 14 mm to about 20 mm, or about 10 mm to about 16 mm, or about 12 mm to about 18 mm,

or about 16 mm to about 22 mm. In some implementations, the depth 810 is less than about 10 mm or greater than about 22 mm.

The positioning of the hub 210 relative to the line of coaptation between the leaflets 20 and 22 (e.g., the line of coaptation 32 shown in FIG. 8) is also relevant to facilitating substantially unhindered leaflets 20 and 22 and chordae tendineae 40. For example, in some implementations positioning the hub 210 generally in vertical alignment with the line of coaptation will serve to substantially prevent hindrances to the leaflets 20 and 22 and the chordae tendineae 40.

In some implementations, the angular positioning of the left anterior sub-annular support arm 230a, the left posterior sub-annular support arm 230b, the right posterior sub-annular support arm 230c, and the right anterior sub-annular support arm 230d in relation to the native mitral valve 17 is relevant to facilitating substantially unhindered leaflets 20 and 22 and chordae tendineae 40. In some implementations, the sub-annular support arms 230a, 230b, 230c, and 230d are arranged symmetrically in relation to a left ventricular long axis (LAX) 840. That is, the LAX 840 bisects an anterior support arm angle 830 and a posterior support arm angle 820.

To minimize disturbances to the anterior leaflet 20 and chordae tendineae 40, the anterior support arms 220a and 220d are positioned essentially between the chordae tendineae 40. In some embodiments, the anterior support arm angle 830 is in a range of about 100° to about 135°, or about 80° to about 120°, or about 120° to about 160°. To minimize disturbances to the posterior leaflet 22 and chordae tendineae 40, in some implementations the posterior support arms 220b and 220c may extend essentially amongst the chordae tendineae 40. In some embodiments, the posterior support arm angle 820 is in a range of about 50° to about 120°, or about 40° to about 80°, or about 60° to about 100°, or about 80° to about 120°, or about 100° to about 140°.

A number of embodiments of the invention have been described. Nevertheless, it will be understood that various modifications may be made without departing from the scope of the invention. Accordingly, other embodiments are within the scope of the following claims.

What is claimed is:

1. A prosthetic mitral valve system comprising:

a valve assembly comprising:

a frame member defining an outer profile and an interior frame member space; and

an occluder disposed within the interior frame member space, the occluder having an open configuration and a closed configuration,

wherein the frame member comprises a proximal end frame portion and a distal end frame portion, wherein an outer periphery of the distal end frame portion comprises a generally flat region and a generally round region, and wherein at least some portions of the generally flat region extend distally toward the interior frame member space; and

an anchor assembly defining an interior anchor assembly space, wherein the valve assembly is selectively mateable with the interior anchor assembly space, wherein the anchor assembly comprises an expandable anchor frame including a hub and a sub-annular support arm extending from the hub, wherein the sub-annular support arm extends to an anchor foot having a surface configured for engagement with a sub-annular gutter of a native mitral valve.

37

2. The prosthetic mitral valve of claim 1, wherein a distance measured parallel to a longitudinal axis of the valve assembly from a distal-most end of the anchor assembly to the surface is at least 14 millimeters.

3. The prosthetic mitral valve of claim 1, wherein the distal end frame portion comprises a generally D-shaped outer periphery, and wherein the proximal end frame portion comprises a circular valve orifice located radially inward from the generally D-shaped outer peripheral region and carrying valve leaflets that define a circular perimeter at the circular valve orifice.

4. A method of using a prosthetic mitral valve system, comprising:

prior to implanting a valve assembly, engaging an anchor assembly of the prosthetic mitral valve system with tissue proximate to an annulus of the native mitral valve, the anchor assembly defining an interior anchor assembly space, and wherein said anchoring the valve assembly comprises interlocking the valve assembly within the interior anchor assembly space, wherein the anchor assembly comprises an expandable anchor frame including a hub and a sub-annular support arm extending from the hub, wherein the sub-annular support arm extends to an anchor foot having a surface configured for engagement with a sub-annular gutter of the native mitral valve;

advancing the valve assembly of the prosthetic mitral valve system toward the annulus of the native mitral valve, the valve assembly comprising:

a frame member defining an outer profile and an interior frame member space; and
an occluder disposed within the interior frame member space, the occluder having an open configuration and a closed configuration,

wherein the frame member comprises a proximal end frame portion and a distal end frame portion, wherein an outer periphery of the distal end frame portion comprises a generally flat region and a generally round region, and wherein at least some portions of the generally flat region extend toward the interior frame member space; and

anchoring the valve assembly at the native mitral valve such that the generally flat region is adjacent to an anterior native leaflet of the native mitral valve.

5. The method of claim 4, wherein a distance measured parallel to a longitudinal axis of the valve assembly from a distal-most end of the anchor assembly to the surface is at least 14 millimeters.

6. The method of claim 4, wherein the distal end frame portion comprises a generally D-shaped outer periphery, and wherein the proximal end frame portion comprises a circular valve orifice located radially inward from the generally D-shaped outer peripheral region and carrying valve leaflets that define a circular perimeter at the circular valve orifice.

7. A prosthetic mitral valve system that is implantable at a native mitral valve, the prosthetic mitral valve system comprising:

an anchor assembly defining an interior anchor assembly space and a longitudinal axis, the anchor assembly comprising an expandable anchor frame including a hub and a sub-annular support arm extending from the hub, wherein the sub-annular support arm extends to an anchor foot having a surface configured for engagement with a sub-annular gutter of the native mitral valve; and

a valve assembly comprising:

38

an expandable valve frame defining an outer profile and an interior frame member space; and
an occluder disposed within the interior frame member space, the occluder having an open configuration and a closed configuration,

wherein the valve assembly is releasably engageable with the anchor assembly within the interior anchor assembly space, and wherein a distance measured parallel to the longitudinal axis from a distal-most end of the anchor assembly to the surface is at least 14 millimeters.

8. The prosthetic mitral valve system of claim 7, wherein the valve assembly comprises a distal end frame portion having a generally D-shaped outer periphery, and wherein the valve assembly comprises a proximal end frame portion having a circular valve orifice located radially inward from the generally D-shaped outer peripheral region and carrying valve leaflets that define a circular perimeter at the circular valve orifice.

9. A method of using a prosthetic mitral valve system, the method comprising:

advancing an anchor assembly of the prosthetic mitral valve system toward an annulus of a native mitral valve, the anchor assembly defining an interior anchor assembly space and longitudinal axis, the anchor assembly comprising an expandable anchor frame including a hub and one or more sub-annular support arms extending from the hub, wherein each of the one or more sub-annular support arm extends to an anchor foot configured to engage with a sub-annular gutter of the native mitral valve; and

engaging the anchor assembly of the prosthetic mitral valve system with tissue proximate the native mitral valve such that a surface of each anchor foot is engaged with the sub-annular gutter, and such that the hub is positioned distal of the distal-most area of coaptation between anterior and post leaflets of the native mitral valve.

10. The method of claim 9, further comprising delivering a valve assembly of the prosthetic mitral valve system to the anchor assembly after engaging the anchor assembly with said tissue proximate the native mitral valve, a valve assembly comprising: an expandable valve frame defining an outer profile and an interior frame member space, and an occluder disposed within the interior frame member space, the occluder having an open configuration and a closed configuration.

11. The method of claim 10, wherein the valve assembly comprises a distal end frame portion having a generally D-shaped outer periphery, and wherein the valve assembly comprises a proximal end frame portion having a circular valve orifice located radially inward from the generally D-shaped outer peripheral region and carrying valve leaflets that define a circular perimeter at the circular valve orifice.

12. The method of claim 10, wherein a distance measured parallel to a longitudinal axis of the valve assembly from a distal-most end of the anchor assembly to the surface of at least one anchor foot is at least 14 millimeters.

13. A prosthetic mitral valve system comprising:

an anchor assembly comprising an expandable anchor frame and a set of sub-annular anchor feet configured to engage with a sub-annular gutter of a native mitral valve; and

a valve assembly comprising: an expandable valve frame defining an outer profile and an interior frame member space, a tissue layer disposed over at least a portion of

39

the outer profile, and an occluder mounted within the interior frame member space, wherein an outwardly facing periphery of the tissue layer along the valve assembly is positioned to abut native leaflets of the mitral valve when the set of anchor feet of the anchor assembly is engaged with the sub-annular gutter.

14. The prosthetic mitral valve system of claim **13**, wherein the valve assembly comprises a distal end frame portion having a generally D-shaped outer periphery, and wherein the valve assembly comprises a proximal end frame portion having a circular valve orifice located radially inward from the generally D-shaped outer peripheral region and carrying valve leaflets that define a circular perimeter at the circular valve orifice.

15. A method of sealing between a prosthetic mitral valve system and native leaflets of a mitral valve, the method comprising:

anchoring an anchor assembly of the prosthetic mitral valve system with tissue proximate to an annulus of a native mitral valve, the anchor assembly defining an interior anchor assembly space and longitudinal axis, the anchor assembly comprising an expandable anchor frame including a hub and one or more sub-annular support arms extending from the hub, wherein each of

40

the one or more sub-annular support arm extends to an anchor foot that engages with a sub-annular gutter of the native mitral valve; and

delivering a valve assembly of the prosthetic mitral valve system to engage with the anchor assembly, the valve assembly comprising: an expandable valve frame defining an outer profile and an interior frame member space; a tissue layer disposed over at least a portion of the outer profile; and an occluder disposed within the interior frame member space, the occluder having an open configuration and a closed configuration,

wherein the tissue layer of the valve assembly abuts with native leaflets of the mitral valve while each anchor foot of the anchor assembly is engaged with the sub-annular gutter.

16. The method of claim **15**, wherein the valve assembly comprises a distal end frame portion having a generally D-shaped outer periphery, and wherein the valve assembly comprises a proximal end frame portion having a circular valve orifice located radially inward from the generally D-shaped outer peripheral region and carrying valve leaflets that define a circular perimeter at the circular valve orifice.

* * * * *