

US009750988B1

(12) **United States Patent**  
**Auld et al.**

(10) **Patent No.:** **US 9,750,988 B1**  
(45) **Date of Patent:** **Sep. 5, 2017**

(54) **HOCKEY PUCK STORAGE AND DISPENSING UNIT**

(71) Applicants: **Winston J. Auld**, Niagara Falls (CA);  
**Elaine A. Auld**, Niagara Falls (CA)

(72) Inventors: **Winston J. Auld**, Niagara Falls (CA);  
**Elaine A. Auld**, Niagara Falls (CA)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

3,977,521 A \* 8/1976 Murphy ..... A47B 81/00  
206/315.1  
4,565,375 A \* 1/1986 Dresel ..... A63B 67/06  
273/401  
4,936,454 A \* 6/1990 Wang ..... B42F 7/06  
206/425  
5,147,061 A \* 9/1992 Karpisek ..... B65D 77/061  
220/1.5  
5,702,140 A 12/1997 Radja  
6,079,930 A \* 6/2000 Valdes-Rodriguez A63B 47/021  
294/19.2

(Continued)

(21) Appl. No.: **14/929,688**

(22) Filed: **Nov. 2, 2015**

**Related U.S. Application Data**

(60) Provisional application No. 62/076,108, filed on Nov. 6, 2014.

(51) **Int. Cl.**  
*A63B 69/00* (2006.01)  
*A63B 47/00* (2006.01)

(52) **U.S. Cl.**  
CPC ..... *A63B 47/002* (2013.01); *A63B 69/0026* (2013.01)

(58) **Field of Classification Search**  
CPC ... A63B 2102/24; A63B 47/02; A63B 63/004; A63B 69/0026  
USPC ..... 473/446, 180; 206/747-749; 220/817, 220/822, 826  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,700,243 A \* 10/1972 Kenney ..... A63B 57/357  
206/315.9  
3,817,535 A \* 6/1974 Doughty ..... A63F 7/305  
473/185

**OTHER PUBLICATIONS**

Puck Keeper Puck Bag. Product listing [online]. Sideline Sports, 2009. [Retrieved on Aug. 26, 2014]. Retrieved on the Internet: <http://www.hockeyshot.com/Puck-Keeper-Puck-Bag-p/coaching-033.htm>.

(Continued)


*Primary Examiner* — Mark Graham

(74) *Attorney, Agent, or Firm* — Robert C. Montgomery; Montgomery Patent & Design, LP.

(57) **ABSTRACT**

A device for storing and dispensing hockey pucks includes a box defining an interior capable of receiving a plurality of the hockey pucks, wherein the box comprises a first door opening and a second door opening disposed approximately perpendicular to the first door opening, a first door pivotably attached to the box within the first door opening, wherein, when closed, the first door encloses the interior when closed, and wherein, when open, the first door forms a ramp for receiving the hockey pucks through the first door opening and into the interior, and a second door pivotably attached to the box within the second door opening, wherein, when closed, the second door encloses the interior, and wherein, when open, the second door dispenses the hockey pucks from the interior through the second opening.

**18 Claims, 5 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

6,398,661 B1 \* 6/2002 Llewellyn ..... A63B 63/00  
473/180  
6,405,888 B1 \* 6/2002 Overholt ..... B65D 11/1833  
220/1.5  
6,513,845 B2 \* 2/2003 Campomane ..... A63B 47/02  
206/315.9  
6,629,607 B1 \* 10/2003 Gibson ..... A45C 11/20  
206/551  
7,066,847 B2 6/2006 Power  
8,590,893 B2 \* 11/2013 Monopoli ..... A63B 67/00  
273/108  
2006/0116224 A1 6/2006 Andersen  
2006/0252581 A1 11/2006 Wegryn  
2008/0015060 A1 \* 1/2008 Erickson ..... A63B 63/004  
473/446  
2009/0023523 A1 \* 1/2009 Poillucci ..... A63B 47/007  
473/478  
2009/0127877 A1 5/2009 Wright  
2011/0077108 A1 \* 3/2011 Gulka ..... A63B 47/002  
473/446  
2015/0174466 A1 \* 6/2015 Folland ..... A63B 71/0036  
206/315.1

OTHER PUBLICATIONS

Nice Rink Puck Bucket. Product listing [online]. Sears, 2014.  
[Retrieved on Aug. 26, 2014]. Retrieved on the Internet: <http://www.sears.com/nice-rink-pucket-puck-bucket-no-more/p-SPM1358926701>.

\* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5

1

## HOCKEY PUCK STORAGE AND DISPENSING UNIT

### RELATED APPLICATIONS

The present invention is a continuation-in-part of, was first described in, and claims the benefit of U.S. Provisional Application No. 62/076,108, filed Nov. 6, 2014, the entire disclosures of which are incorporated herein by reference.

### FIELD OF THE INVENTION

The present invention relates generally to structures for storing or dispensing objects and, more particularly, to a storage and dispensing device for storing and dispensing hockey pucks.

### BACKGROUND OF THE INVENTION

When playing or practicing the game of hockey, a lot of pucks are required in order to maintain a proper practice. This is to ensure everyone participating can practice shooting, passing, or basic puck keeping skills. When performing these practice skills on ice, it is imperative that the pucks can be gathered in a single place because of the tendency for the pucks to travel farther due to the relative lack of friction of practicing on ice.

Gathering pucks is time consuming because of the need to bend over and grab a myriad of pucks and place them in a container. There is therefore a need to provide a puck holding container.

### SUMMARY OF THE INVENTION

The inventor has recognized the aforementioned inherent problems and lack in the art and observed that there is a need for a puck holding container that allows users to "shoot" or otherwise direct pucks inside of the container while also being capable of easily dispensing the pucks housed inside. The development of the present invention, which will be described in greater detail herein, substantially departs from conventional solutions to fulfill this need.

In one (1) embodiment, the disclosed device for storing and dispensing hockey pucks includes a box defining an interior capable of receiving a plurality of the hockey pucks, wherein the box comprises a first door opening and a second door opening disposed approximately perpendicular to the first door opening, a first door pivotably attached to the box within the first door opening, wherein, when closed, the first door encloses the interior when closed, and wherein, when open, the first door forms a ramp for receiving the hockey pucks through the first door opening and into the interior, and a second door pivotably attached to the box within the second door opening, wherein, when closed, the second door encloses the interior, and wherein, when open, the second door dispenses the hockey pucks from the interior through the second opening.

In another embodiment, the disclosed device for storing and dispensing hockey pucks includes a box defining an interior capable of receiving a plurality of hockey pucks, wherein the box includes a first side, a first door opening disposed in the first side, a second side opposite the first side, a first end, a second end opposite the first end, a second door opening disposed in the second end, a top, and a bottom, wherein the bottom slopes downward from the first side to the second side. The device also includes a first door pivotably attached to the box within the first door opening,

2

wherein, when closed, the first door encloses the interior when closed, and wherein, when open, the first door forms a ramp for receiving the hockey pucks through the first door opening and into the interior, and a second door pivotably attached to the box within the second door opening, wherein, when closed, the second door encloses the interior, and wherein, when open, the second door dispenses the hockey pucks from the interior through the second opening.

In yet another embodiment, the disclosed device for storing and dispensing hockey pucks includes a box defining an interior capable of receiving a plurality of hockey pucks, wherein the box includes a first side, a first door opening disposed in the first side, a second side opposite the first side, a first end, a second end opposite the first end, a second door opening disposed in the second end, a top, a bottom, wherein the bottom slopes downward from the first side to the second side, a plurality of bottom apertures disposed through the bottom to drain water from within the interior, at least two (2) second side apertures disposed through the second side to enable tilting of the box about the first side to dispense the hockey pucks from within the interior through the first door opening, a first end aperture disposed through the first end to enable tilting the box about the second end to dispense the hockey pucks from within the interior through the second door opening, an opposed pair of first door slide apertures, a first door slide aperture disposed in each of the first end and the second end near the bottom, an opposed pair of first door latch apertures, a first door latch aperture disposed in each of the first end and the second end near the top, and an opposed pair of second door slide apertures, a second door slide aperture disposed in each of the first side and the second side near the bottom. The device also includes a first door pivotably attached to the first side within the first door opening, wherein when closed, the first door encloses the interior when closed, and when open, the first door forms a ramp for receiving the hockey pucks through the first door opening and into the interior. The first door includes an opposed pair of first door pivot pins near a first door bottom edge, an opposed pair of first door latch pins near a first door top edge, an opposed pair of ramp ridges extending from a first door bottom edge to a first door top edge on opposing sides of the ramp, and a ramp nose extending along the first door top edge, wherein the first door pivot pins are rotatably and slidably retained within the first door slide apertures to allow the first door to open and close, the first door latch pins are releasably retained within the first door latch apertures when the first door is closed. The device also includes a second door pivotably attached to the second end within the second door opening, wherein when closed, the second door encloses the interior, and when open, the second door dispenses the hockey pucks from the interior through the second opening. The second door includes an opposed pair of second door pivot pins near a second door top edge, and a second door tab protruding from a second door bottom edge, wherein the second door pivot pins are rotatably and slidably retained within the second door slide apertures to allow the second door to open and close, and the second door tab is releasably retained within the second door slot when the second door is closed.

Furthermore, the described features and advantages of the embodiments disclosed by this disclosure may be combined in various manners and implementations as one skilled in the relevant art will recognize. Various embodiments can be practiced without one or more of the features and advantages described in a particular embodiment disclosed by this disclosure.



Further advantages of the embodiments disclosed by the present disclosure will become apparent from a consideration of the drawings and ensuing description.

## BRIEF DESCRIPTION OF THE DRAWINGS

The advantages and features of the present disclosure will become better understood with reference to the following more detailed description and claims taken in conjunction with the accompanying drawings, in which like elements are identified with like symbols, and in which:

FIG. 1 is an isometric view of a puck container for pick-up, storage, and dispensing of hockey pucks, in accordance with one embodiment of the present invention;

FIG. 2 is an isometric view of the puck container, as viewed from a different angle from FIG. 1, in accordance with one embodiment of the present invention;

FIG. 3 is a section view of the puck container, taken along line A-A of FIG. 1, in accordance with one embodiment of the present invention;

FIG. 4 is an isometric view of the puck container shown with a first door open, in accordance with one embodiment of the present invention; and,

FIG. 5 is an isometric view of the puck container shown with a second door open, in accordance with the one embodiment of the present invention.

## DESCRIPTIVE KEY

10 puck container  
 20 box  
 25 first side  
 30 first stile  
 32 first door opening  
 35 second stile  
 40 first door slide aperture  
 45 first door latch aperture  
 50 second side  
 55 second side aperture  
 60 first end  
 65 first end aperture  
 70 indicia  
 75 second end  
 80 third stile  
 85a second door slide aperture  
 85b second door blind slide aperture  
 90 second door inset  
 93 second door slot  
 95 second door opening  
 100 bottom  
 105 bottom aperture  
 110 top  
 115 handle aperture  
 120 center strut  
 125 interior  
 130 first door  
 133 first door top edge  
 135 first door pivot pin  
 140 first door latch pin  
 145 first door exterior  
 150 first door actuator  
 155 ramp face  
 160 ramp ridge  
 165 ramp nose  
 170 second door  
 175 second door pivot pin  
 178 second door top edge

180 door tab  
 185 second door exterior  
 190 second door actuator  
 200 hockey puck

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

In accordance with the invention, the best mode is presented in terms of a one or more of the disclosed embodiments, herein depicted within FIGS. 1 through 5. However, the disclosure is not limited to a single described embodiment and a person skilled in the art will appreciate that many other embodiments are possible without deviating from the basic concept of the disclosure and that any such work around will also fall under its scope.

Further, those skilled in the art will recognize that other styles and configurations can be incorporated into the teachings of the present disclosure, and that the example configurations shown and described herein are for the purpose of clarity and disclosure and not by way of limitation.

As used herein, singular terms such as “a”, “an”, and “the” do not denote a limitation of quantity, but rather denote the presence of at least one (1), as well as a plurality of, the referenced items, unless the context clearly indicates otherwise.

As used herein, terms such as “first”, “second”, “third”, etc. are used as labels to describe various elements, features, and/or components, and are not intended to impose ordinal, positional, or hierarchical requirements on the referenced items, unless other indicated. For example, such terms may be used to distinguish one (1) element from another element.

As used herein, relative terms such as “front”, “rear”, “left”, “right”, “top”, “bottom”, “below”, “above”, “upper”, “lower”, “horizontal”, or “vertical” are used to describe a relationship of one element, feature and/or region to another element, feature and/or region as illustrated in the figures.

Referring generally to FIGS. 1-5, a puck container (herein described as the “device”) 10 is disclosed, where like reference numerals represent similar or like parts. Generally, the disclosed device 10 provides for the pick-up, storage, and dispensing of a plurality of hockey pucks 200 to collect and store the hockey pucks 200 easily and efficiently so as to have them available for an ensuing event. It is envisioned that in various embodiments, the device 10 may be presented in a different size so as to be capable of storing more, or fewer, hockey pucks 200 without limitation.

Referring to FIG. 1, an isometric view of the device 10, according one embodiment of the present invention, is disclosed. The device 10 includes a box 20 having a first side 25, a planar second side 50, a planar first end 60, a second end 75, a planar top 110 and a sloped bottom 100 joined along all horizontal and vertical abutting edges to form an interior 125 (FIG. 3).

As one example, the box 20 is made from a plurality of injection-molded thermoplastic pieces fitted together in a manufacturing process necessary to yield the finished product in the shape of a rectangular prism. As such, the box 20 may be presented in a wide variety of sizes, colors, and surface textures.

Referring to FIGS. 1 and 4, the first side 25 is more of a nominal position than a physical vertical barrier as the majority of the first side 25 is formed by a first door 130 enclosing a first door opening 32, on a longer side of the box 20 (FIG. 4). The first door 130 is a planar cover for the first door opening 32 having a pair of first door pivot pins 135 located on either side of the first door 130 in proximity to a

5

first door bottom edge. The first door **130** is also provided with a pair of first door latch pins **140**. The first door latch pins **140** are located on either side of the first door **130** adjacent to the first door top edge **133**.

The first side **25** has a first stile **30** configured to essentially be a corner in conjunction with the first end **60**. A second stile **35** is located at an opposite position along the first side **25** as a corner in conjunction with the second end **75**. The first stile **30** and the second stile **35** have identical corresponding first door pin apertures **40** and first door latch apertures **45** to accommodate the respective first door pivot pins **135** and first door latch pins **140** to mount the first door **130**.

The first door pivot pins **135** are configured to be assembled into the first door pin apertures **40** for the purpose of hingedly connecting the first door **130** to the box **20**. The first door pin apertures **40** are elongated slots with semicircular ends to accommodate lifting the first door **130** slightly to disengage the first door latch pins **140** from the first door latch apertures **45** so as to be able to pivot the first door **130** about the first door pivot pins **135** in order to open the first door **130**.

The first door **130** is provided with a first door actuator **150** located on the first door exterior **145**. The first door actuator **150** is a handle adapted to be manipulated by a user as a means to raise and rotate the first door **130**.

Referring to FIGS. **1** and **2**, the first end **60** is configured to be a planar vertical barrier on a narrow end of the box **20** being perpendicular to the first side **25**. A second door **170** is located in a second end **75** of the box **20** (FIG. **2**). However, the device **10** is not limited to the arrangement shown here as the first end **60** may be on either the right or left side without limiting the scope, or the intent of the device **10**.

For the purpose of this disclosure, the first end **60** is that end of the box **20** in which a first end aperture **65** is disposed. The first end aperture **65** is a horizontal slot, having semicircular ends, into which a user may place a portion of a hand; lift the first end **60** of the box **20** so as to position the box **20** at a declining angle; and, enable any hockey pucks **200** contained within the interior **125** to be dislodged and dispensed out of the second door **170** (see FIG. **5**).

It is envisioned that some surface portions of the box **20** may include various indicia **70**, which may provide script or logos based upon a user's preference and may include images such as, but not limited to, business names, team logos, personal names, symbols, lines, pictures, and the like, in various colors and patterns, to further customize and personalize the device **10**.

Referring to FIGS. **1-5**, disposed in the top **110** of the box **20** are two (2) handle apertures **115**. The handle apertures **115** are configured to be oval-shaped or similarly shaped slots arranged such that a center strut **120**, located between the handle apertures **115**, can serve as a handle by which the box **10** may be transported, with, or without, hockey pucks **200** in the interior **125**, from one location to another.

Referring to FIG. **2**, an isometric view of the device **10**, from a viewing angle different than FIG. **1**, according to one (1) embodiment of the present invention, is disclosed. The second side **50** is configured to be a planar vertical barrier on a longer side of the box **20** opposite from the first side **25**. Two (2) circular second side apertures **55** are disposed in the second side **50**, into which a user may place one (1) or more fingers and a thumb of a hand for the purpose of position the box **20** at a declining angle to dispense contained hockey pucks **200** through the first door **130**.

6

Referring to FIGS. **2** and **5**, the second end **75**, similar to the first side **25** includes a second door opening **95** (FIG. **5**). This second door opening **95** is an aperture in a second door inset **90** formed into the second end **75**. A second door slot **93** is a crease, or slot, in a lower face of the second door inset **90** in the second end **75** (FIG. **5**).

The second end **75**, as previously discussed, shares a second stile **35** with the first side **25**. A third stile **80** is located at an opposite position from the second stile **35** along the second end **75** as a corner in conjunction with the second side **50**. The third stile **80** is provided with a second door slide aperture **85a** into which a second door pivot pin **175** is inserted as a means to pivotally install the second door **170**. Disposed in the second stile **35** is a second door blind slide aperture **85b** having similar function to the second door slide pin aperture **85a**. However, due to the proximity of the latch aperture **45** of the first door **130** in that same second stile **35** the depth of the second door blind slide aperture **85b** must be truncated so as to not interfere with the first door latch aperture **45**. The second door slide apertures **85a**, **85b** are configured to be elongated slots with semicircular ends to accommodate lifting the second door **170** slightly to disengage the door tab **180** from the second door slot **93** so as to be able to pivot the second door **170** about the second door slide pins **175** in order to open the second door **170**.

The second door inset **90** is adapted to span a space between the second stile **35** and the third stile **80** (FIG. **5**). The second door **170** is a planar cover of the second door opening **95** having a pair of second door slide pins **175** located on either side of the second door **170** in proximity to a second door top edge **178**. The second door **170** is also provided with a door tab **180** (FIG. **5**), along an edge opposite from the second door top edge **178**. This door tab **180** is adapted to fit within the second door slot **93** to secure the closure of the second door **170**. The second door **170** is provided with a second door actuator **190** located on the second door exterior **185**. The second door actuator **190** is a handle, similar to the first door actuator **140** as pictured in FIG. **1**, adapted to be manipulated by a user as a means to raise and rotate the second door **170**.

Referring to FIG. **3**, a section view taken along line A-A, as shown in FIG. **1**, of the device **10**, according to one (1) embodiment of the present invention, is disclosed. The bottom **100** of the box **20** is configured to be sloped downwardly from the entry of a hockey puck **200** on the first side **25**, to the second side **50**. The intended purpose of this arrangement is to function positively in regard to retaining the hockey pucks **200** within the interior **125**. Additionally, some moisture may inadvertently be introduced into the interior **125**, either by transferring shaved ice on a hockey puck **200** or by condensed moisture resulting from the hockey pucks **200** being frozen prior to play in a conventional manner. The sloped bottom **100** provides a means to direct the collected water to a plurality of bottom apertures **105** disposed in the bottom **100** whereby the collected water may exit the interior **125**. The bottom apertures **105** may be lateral or longitudinal slots in proximity to the second side **50**. Other configurations may be utilized for the bottom apertures **105** without limiting the scope of the device **10**.

Referring to FIG. **4**, an isometric view of the device **10**, with the first door **130** in an open state so as to receive hockey pucks **200**, according to one (1) embodiment of the present invention, is disclosed. The aforementioned first door **130** is configured to pivot about the first door pivot pins **135** in the first door pin apertures **40**. This pivoting action reveals a ramp face **155** disposed on that side of the first door **130** directed toward the interior **125** of the box **20**. The first

door **130** will pivot without restriction to touch upon the ice surface thereby forming a ramp via which the hockey pucks **200** may be slid into the interior **125** of the box **20**.

The first door **130** is provided with a ramp nose **165** at the first door top edge **133**, which provides a tapered edge portion of the first door **130** to assist the hockey pucks **200** onto the ramp face **155** with a minimal amount of obstruction.

Vertically protruding extensions of parallel outer edges of the ramp face **155** constitute ramp ridges **160**. A ramp ridge **160** on either side of the ramp face **155** prevents the hockey pucks **200** from sliding off of the sides of the ramp face **155** prior to entering the interior **125**.

After all of the hockey pucks **200** are pushed into the box **20**, the first door **130** may be rotated into the first door opening **32** to close the first door **130**. The first door **130** may be raised slightly in the first door pin apertures **40** to allow the first door latch pins **140** to be engaged within the first door latch apertures **45**.

Referring to FIG. **5**, an isometric view of the device **10**, with the second door **170** partially opened to dispense hockey pucks **200**, according to one (1) embodiment of the present invention, is disclosed. The second door **170** can be selectively opened to permit the hockey pucks **200** to exit from the interior **125** of the box **20**. The slope of the bottom **100** relative to the second door inset **90** is clearly illustrated in FIG. **5**. The second door slot **93** at the lower edge of the second door inset **90** is also clearly illustrated.

Those skilled in the art will recognize that other styles and configurations of the disclosed device **10** can be easily incorporated into the teachings of the present disclosure, and that only particular configurations have been shown and described for purposes of clarity and disclosure and not by way of limitation of scope.

The example embodiments of the present invention can be utilized by the common user in a simple and effortless manner with little or no training. After initial purchase or acquisition of the device **10**, it would be arranged and utilized as indicated in FIGS. **1-5**.

The method of arranging and utilizing the device **10** may be achieved by performing the following steps: acquiring a model of the device **10** having a desired size and style to suit the taste of a user; placing the device **10** on the ice surface at some location in which an obstruction, such as the boards or the net, may obviate any displacement of the device **10**; orienting the first door **130** away from the stabilizing obstruction; raising the first door **130** slightly, by manipulating the first door actuator **150**, to disengage the first door latch pins **140** from the first door latch apertures **45**; rotating the first door **130** about the first door pivot pins **135** in the first door pin apertures **40** to lower the ramp nose **165** onto the ice surface, thereby exposing the ramp face **155**; utilizing a hockey stick, or other similar device, to push a desired number of hockey pucks **200** up the ramp face **155**, between the ramp ridges **160**, into the interior **125**; and, closing and latching the first door **130** by engaging the first door latch pins **140** and first door latch apertures **45**.

The device **10** may be transported to another location for retrieval of additional hockey pucks **200**, if desired, by placing one (1) or more digits into one (1) of the handle apertures **115** and the thumb of the same hand into the other handle aperture **115**, and carrying the device **10** by grasping and lifting the center strut **120**.

The hockey pucks **200** may be removed from the interior **125** of the box **29** by manipulating the second door actuator **190** to enable displacement of the door tab **180** from the second door slot **93**; rotating the second door **170** about the

second door slide pins **175** in the slide apertures **85a**, **85b**; opening the second door **170**; manipulating the device **10** using the handle apertures **115**, center strut **120**, and second side apertures **55** to eject a desired number of hockey pucks **200** at a desired location.

Accordingly, the disclosed device **10** beneficially provides an efficient and convenient means to collect and store a plurality of hockey pucks **200**.

The foregoing descriptions of specific embodiments have been presented for purposes of illustration and description. They are not intended to be exhaustive or to limit to the precise forms disclosed and many modifications and variations are possible in light of the above teachings. The embodiments were chosen and described in order to best explain principles and practical application to enable others skilled in the art to best utilize the various embodiments with various modifications as are suited to the particular use contemplated.

What is claimed is:

**1.** A device for storing and dispensing hockey pucks, said device comprising:

a box defining an interior capable of receiving a plurality of said hockey pucks, wherein said box comprises a first side, a first door opening disposed in said first side, a second side opposite said first side, a first end, a second end opposite said first end, a top, a bottom, and a second door opening disposed in said second end and approximately perpendicular to said first door opening; a first door pivotably attached to said box within said first door opening, wherein, when closed, said first door encloses said interior when closed, and wherein, when open, said first door forms a ramp for receiving said hockey pucks through said first door opening and into said interior; and,

a second door pivotably attached to said box within said second door opening, wherein, when closed, said second door encloses said interior, and wherein, when open, said second door dispenses said hockey pucks from said interior through said second opening; wherein said bottom slopes downward from said first side to said second side.

**2.** The device of claim **1**, wherein said box further comprises a plurality of bottom apertures disposed through said bottom to drain water from within said interior.

**3.** The device of claim **1**, wherein said box comprises at least two second side apertures disposed through said second side to enable tilting of said box about said first side to dispense said hockey pucks from within said interior through said first door opening, when said first door is open.

**4.** The device of claim **1**, wherein said box comprises a first end aperture disposed through said first end to enable tilting said box about said second end to dispense said hockey pucks from within said interior through said second door opening, when said second door is open.

**5.** The device of claim **1**, wherein:

said box further comprises:

an opposed pair of first door slide apertures, a first door slide aperture disposed in each of said first end and said second end near said bottom; and,

an opposed pair of first door latch apertures, a first door latch aperture disposed in each of said first end and said second end near said top;

said first door comprises:

an opposed pair of first door pivot pins near a first door bottom edge; and,

an opposed pair of first door latch pins near a first door top edge;

9

said first door pivot pins are rotatably retained within said first door slide apertures to allow said first door to open and close; and,

said first door latch pins are releasably retained within said first door latch apertures when said first door is closed.

6. The device of claim 5, wherein each of said first door slide apertures comprises an elongated slot having opposed semicircular ends; and wherein said first door pivot pins are slidably retained within said first door slide apertures and movable between said semicircular ends.

7. The device of claim 5, wherein each one of said first door latch apertures comprises a semicircular slot having an open top end; and wherein said first door latch pins sit inside said first door latch apertures when said first door is closed.

8. The device of claim 1, wherein:

said box further comprises an opposed pair of second door slide apertures, a second door slide aperture disposed in each of said first side and said second side near said top; said second door comprises an opposed pair of second door pivot pins near a second door top edge; and, said second door pivot pins are rotatably retained within said second door slide apertures to allow said second door to open and close.

9. The device of claim 8, wherein each of said second door slide apertures comprises an elongated slot having opposed semicircular ends; and wherein said second door pivot pins are slidably retained within said second door slide apertures and movable between said semicircular ends.

10. The device of claim 8, wherein:

said box further comprises a second door slot disposed within said second end along a lower edge of said second door opening; said second door comprises a second door tab protruding from a second door bottom edge; and, said second door tab is releasably retained within said second door slot when said second door is closed.

11. The device of claim 1, wherein said box further comprises a pair of handle apertures disposed through said top and separated by a center strut.

12. The device of claim 1, wherein said first door comprises an opposed pair of ramp ridges extending from a first door bottom edge to a first door top edge.

13. The device of claim 1, wherein said first door comprises a ramp nose extending along a first door top edge.

14. A device for storing and dispensing hockey pucks, said device comprising:

a box defining an interior capable of receiving a plurality of hockey pucks, wherein said box comprises:

a first side;

a first door opening disposed in said first side;

a second side opposite said first side;

a first end;

a second end opposite said first end;

a second door opening disposed in said second end;

a top; and,

a bottom, wherein said bottom slopes downward from said first side to said second side;

a first door pivotably attached to said box within said first door opening, wherein, when closed, said first door encloses said interior when closed, and wherein, when open, said first door forms a ramp for receiving said hockey pucks through said first door opening and into said interior; and,

a second door pivotably attached to said box within said second door opening, wherein, when closed, said second door encloses said interior, and wherein, when

10

open, said second door dispenses said hockey pucks from said interior through said second opening.

15. The device of claim 14, wherein said box further comprises:

a plurality of bottom apertures disposed through said bottom to drain water from within said interior;

at least two second side apertures disposed through said second side to enable tilting of said box about said first side to dispense said hockey pucks from within said interior through said first door opening, when said first door is open;

a first end aperture disposed through said first end to enable tilting said box about said second end to dispense said hockey pucks from within said interior through said second door opening, when said second door is open.

16. The device of claim 14, wherein:

said box further comprises:

an opposed pair of first door slide apertures, a first door slide aperture disposed in each of said first end and said second end near said bottom;

an opposed pair of first door latch apertures, a first door latch aperture disposed in each of said first end and said second end near said top;

an opposed pair of second door slide apertures, a second door slide aperture disposed in each of said first side and said second side near said top; and, comprises a second door slot disposed within said second end along a lower edge of said second door opening;

said first door comprises:

an opposed pair of first door pivot pins near a first door bottom edge; and,

an opposed pair of first door latch pins near a first door top edge;

said second door comprises:

an opposed pair of second door pivot pins near a second door top edge; and,

a second door tab protruding from a second door bottom edge;

said first door pivot pins are rotatably and slidably retained within said first door slide apertures to allow said first door to open and close;

said first door latch pins are releasably retained within said first door latch apertures when said first door is closed;

said second door pivot pins are rotatably and slidably retained within said second door slide apertures to allow said second door to open and close; and, said second door tab is releasably retained within said second door slot when said second door is closed.

17. The device of claim 14, wherein said first door comprises:

an opposed pair of ramp ridges extending from a first door bottom edge to a first door top edge; and,

a ramp nose extending along said first door top edge.

18. A device for storing and dispensing hockey pucks, said device comprising:

a box defining an interior capable of receiving a plurality of hockey pucks, wherein said box comprises:

a first side;

a first door opening disposed in said first side;

a second side opposite said first side;

a first end;

a second end opposite said first end;

a second door opening disposed in said second end;

a top;

11

a bottom, wherein said bottom slopes downward from said first side to said second side;  
 a plurality of bottom apertures disposed through said bottom to drain water from within said interior;  
 at least two second side apertures disposed through said 5  
 second side to enable tilting of said box about said first side to dispense said hockey pucks from within said interior through said first door opening;  
 a first end aperture disposed through said first end to enable tilting said box about said second end to 10  
 dispense said hockey pucks from within said interior through said second door opening;  
 an opposed pair of first door slide apertures, a first door slide aperture disposed in each of said first end and said second end near said bottom; 15  
 an opposed pair of first door latch apertures, a first door latch aperture disposed in each of said first end and said second end near said top; and,  
 an opposed pair of second door slide apertures, a second door slide aperture disposed in each of said 20  
 first side and said second side near said top;  
 a first door pivotably attached to said first side within said first door opening, wherein:  
 when closed, said first door encloses said interior when closed; 25  
 when open, said first door forms a ramp for receiving said hockey pucks through said first door opening and into said interior;  
 said first door comprises:  
 an opposed pair of first door pivot pins near a first 30  
 door bottom edge;

12

an opposed pair of first door latch pins near a first door top edge;  
 an opposed pair of ramp ridges extending from a first door bottom edge to a first door top edge on opposing sides of said ramp; and,  
 a ramp nose extending along said first door top edge;  
 said first door pivot pins are rotatably and slidably retained within said first door slide apertures to allow said first door to open and close; and,  
 said first door latch pins are releasably retained within said first door latch apertures when said first door is closed;  
 a second door pivotably attached to said second end within said second door opening, wherein:  
 when closed, said second door encloses said interior;  
 when open, said second door dispenses said hockey pucks from said interior through said second opening; and,  
 said second door comprises:  
 an opposed pair of second door pivot pins near a second door top edge; and,  
 a second door tab protruding from a second door bottom edge;  
 said second door pivot pins are rotatably and slidably retained within said second door slide apertures to allow said second door to open and close; and,  
 said second door tab is releasably retained within said second door slot when said second door is closed.

\* \* \* \* \*